

US010805994B2

(12) **United States Patent**
Hausman, Jr.

(10) **Patent No.: US 10,805,994 B2**
(45) **Date of Patent: *Oct. 13, 2020**

(54) **METHOD AND APPARATUS FOR DETERMINING A TARGET LIGHT INTENSITY FROM A PHASE-CONTROL SIGNAL**

(71) Applicant: **Lutron Technology Company LLC**,
Coopersburg, PA (US)

(72) Inventor: **Donald F. Hausman, Jr.**, New Tripoli,
PA (US)

(73) Assignee: **Lutron Technology Company LLC**,
Coopersburg, PA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **16/119,670**

(22) Filed: **Aug. 31, 2018**

(65) **Prior Publication Data**

US 2018/0376573 A1 Dec. 27, 2018

Related U.S. Application Data

(60) Continuation of application No. 15/783,604, filed on
Oct. 13, 2017, now Pat. No. 10,070,507, which is a
(Continued)

(51) **Int. Cl.**
H05B 41/392 (2006.01)
H05B 41/295 (2006.01)

(Continued)

(52) **U.S. Cl.**
CPC **H05B 41/3924** (2013.01); **H02M 1/08**
(2013.01); **H05B 41/2828** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC H05B 41/3924; H05B 41/295; H05B
41/2828; H05B 41/3925; H05B 33/0845;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,797,599 A 1/1989 Ference et al.
5,021,716 A * 6/1991 Lesea H05B 41/2821
315/209 R

(Continued)


Primary Examiner — Raymond R Chai

(74) *Attorney, Agent, or Firm* — Glen Farbanish; Philip
Smith; Amy Yanek

(57) **ABSTRACT**

A dimmable ballast circuit for a compact fluorescent lamp
controls the intensity of a lamp tube in response to a
phase-control voltage received from a dimmer switch. The
ballast circuit comprises a phase-control-to-DC converter
circuit that receives the phase-control voltage, which is
characterized by a duty cycle defining a target intensity of
the lamp tube, and generates a DC voltage representative of
the duty cycle of the phase-control voltage. Changes in the
duty cycle of the phase-control voltage that are below a
threshold amount are filtered out by the converter circuit,
while intentional changes in the duty cycle of the phase-
control voltage are reflected in changes in the target intensity
level and thereby the intensity level of the lamp tube.

14 Claims, 12 Drawing Sheets



Related U.S. Application Data

continuation of application No. 15/077,090, filed on Mar. 22, 2016, now Pat. No. 9,795,019, which is a continuation of application No. 14/323,495, filed on Jul. 3, 2014, now Pat. No. 9,326,356, which is a division of application No. 13/464,358, filed on May 4, 2012, now Pat. No. 8,803,432.

(60) Provisional application No. 61/484,481, filed on May 10, 2011.

- (51) **Int. Cl.**
H05B 41/282 (2006.01)
H05B 45/10 (2020.01)
H05B 45/37 (2020.01)
H05B 47/10 (2020.01)
H02M 1/08 (2006.01)

(52) **U.S. Cl.**
 CPC *H05B 41/295* (2013.01); *H05B 41/3925* (2013.01); *H05B 45/10* (2020.01); *H05B 45/37* (2020.01); *H05B 47/10* (2020.01); *Y02B 20/19* (2013.01)

(58) **Field of Classification Search**
 CPC H05B 33/0818; H05B 37/02; H02M 1/08; Y02B 20/19
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

- 5,245,253 A * 9/1993 Quazi H05B 41/2925 315/224
 5,245,523 A 9/1993 Juzswik

5,463,280	A *	10/1995	Johnson	F21V 3/00	
				315/187	
5,530,321	A *	6/1996	Sears	H05B 41/392	
				315/283	
5,872,429	A	2/1999	Xia et al.		
5,925,990	A *	7/1999	Crouse	H05B 41/2855	
				315/127	
6,111,368	A	8/2000	Luchaco		
6,359,393	B1 *	3/2002	Brown	H05B 41/3925	
				315/209 R	
6,452,344	B1	9/2002	MacAdam et al.		
6,642,669	B1	11/2003	MacAdam et al.		
6,982,528	B2	1/2006	Cottongim et al.		
7,061,191	B2	6/2006	Chitta		
7,321,202	B2	1/2008	Chitta		
7,436,131	B2	10/2008	Cottongim et al.		
7,675,250	B2	3/2010	Chitta et al.		
7,830,093	B2	11/2010	Chitta		
7,911,156	B2	3/2011	Cottongim et al.		
7,940,015	B2	5/2011	Chitta et al.		
8,008,866	B2	8/2011	Newman, Jr. et al.		
8,049,430	B2	11/2011	Newman, Jr. et al.		
8,324,822	B2 *	12/2012	Peng	H05B 45/37	
				315/209 R	
8,358,078	B2	1/2013	Natarelli		
8,436,548	B2 *	5/2013	Anissimov	H05B 45/37	
				315/291	
8,803,432	B2	8/2014	Hausman, Jr.		
9,795,019	B2 *	10/2017	Hausman, Jr.	H05B 41/2828	
10,070,507	B2 *	9/2018	Hausman, Jr.	H05B 33/0845	
2002/0158591	A1	10/2002	Ribarich et al.		
2004/0239263	A1	12/2004	Vakil et al.		
2008/0258637	A1	10/2008	Leung		
2008/0278080	A1 *	11/2008	Yu	H05B 41/295	
				315/94	
2010/0213859	A1	8/2010	Shteynberg et al.		
2011/0080110	A1	4/2011	Nuhfer et al.		
2013/0293139	A1 *	11/2013	Sadwick	H05B 47/10	
				315/224	

* cited by examiner




Fig. 1
PRIOR ART




Fig. 2
PRIOR ART




Fig. 3A

PRIOR ART




Fig. 3B

PRIOR ART




Fig. 4




Fig. 5




Fig. 6




Fig. 8




Fig. 9




Fig. 10A




Fig. 10B




Fig. 11




Fig. 12

1

**METHOD AND APPARATUS FOR
DETERMINING A TARGET LIGHT
INTENSITY FROM A PHASE-CONTROL
SIGNAL**

CROSS REFERENCES TO RELATED
APPLICATIONS

This application is a continuation of U.S. Ser. No. 15/783,604, filed Oct. 13, 2017 by Donald F. Hausman, Jr. entitled METHOD AND APPARATUS FOR DETERMINING A TARGET LIGHT INTENSITY FROM A PHASE-CONTROL SIGNAL, now U.S. Pat. No. 10,070,507, issued Sep. 4, 2018, which is a continuation of prior U.S. Ser. No. 15/077,090, filed Mar. 22, 2016 by Donald F. Hausman, Jr. entitled METHOD AND APPARATUS FOR DETERMINING A TARGET LIGHT INTENSITY FROM A PHASE-CONTROL SIGNAL, now U.S. Pat. No. 9,795,019, issued Oct. 17, 2017, which is a continuation of U.S. Ser. No. 14/323,495, filed Jul. 3, 2014, by Donald F. Hausman, Jr. entitled METHOD AND APPARATUS FOR DETERMINING A TARGET LIGHT INTENSITY FROM A PHASE-CONTROL SIGNAL, now U.S. Pat. No. 9,326,356, issued Apr. 26, 2016, which is a divisional application of Ser. No. 13/464,358, filed May 4, 2012, by Donald F. Hausman, Jr. entitled METHOD AND APPARATUS FOR DETERMINING A TARGET LIGHT INTENSITY FROM A PHASE-CONTROL SIGNAL, now U.S. Pat. No. 8,803,432, issued Aug. 12, 2014, which is a non-provisional application of commonly-assigned U.S. Provisional Patent Application No. 61/484,481, filed May 10, 2011, entitled DIMMABLE SCREW-IN COMPACT FLUORESCENT LAMP HAVING INTEGRAL ELECTRONIC BALLAST CIRCUIT, the entire disclosure of which is hereby incorporated by reference.

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to a load control device for controlling the amount of power delivered to an electrical load, such as a lighting load, and more particularly, a phase-control-to-DC converter circuit for determining a target intensity level for the lighting load from a phase-control signal.

Description of the Related Art

In order to save energy, high-efficiency lighting loads, such as, for example, compact fluorescent lamps (CFLs) and light-emitting diode (LED) light sources, are being used in place of or as replacements for conventional incandescent or halogen lamps. High-efficiency light sources typically consume less power and provide longer operational lives as compared to incandescent and halogen lamps. FIG. 1 is a simplified block diagram of a prior art lighting control system 10 having a screw-in compact fluorescent lamp 20. The screw-in compact fluorescent lamp 20 comprises a fluorescent lamp tube 22, which may be formed in a spiral (as shown in FIG. 1). The screw-in compact fluorescent lamp 20 also comprises an enclosure 24 for housing a load regulation circuit 40 (FIG. 2), e.g., an electronic ballast circuit, which is electrically coupled to the lamp tube 22 for illuminating the lamp tube. The screw-in compact fluorescent lamp 20 has a screw-in base 26 adapted to be coupled to a standard Edison socket. The lamp tube 22 of a typical

2

prior art screw-in compact fluorescent lamp 20 is filled with a fill gas of 100% argon at a pressure of approximately 4 Torr.

The lighting control system 10 also comprises a “two-wire” dimmer switch 30, which is coupled in series between an alternating-current (AC) power source 15 and the screw-in compact fluorescent lamp 20 for controlling the intensity of the lamp tube 22. The dimmer switch 30 may be adapted to be mounted to a standard electrical wallbox and comprises a hot terminal H coupled to the AC power source 15 for receiving an AC mains line voltage V_{AC} , and a dimmed-hot terminal DH coupled to the screw-in compact fluorescent lamp 20. The dimmer switch 30 does not require a direct connection to the neutral side N of the AC power source 15. Examples of prior art dimmer switches are described in greater detail in commonly-assigned U.S. Pat. No. 5,248,919, issued Sep. 29, 1993, entitled LIGHTING CONTROL DEVICE; U.S. Pat. No. 6,969,959, issued Nov. 29, 2005, entitled ELECTRONIC CONTROL SYSTEMS AND METHODS; and U.S. Pat. No. 7,687,940, issued Mar. 30, 2010, entitled DIMMER SWITCH FOR USE WITH LIGHTING CIRCUITS HAVING THREE-WAY SWITCHES, the entire disclosures of which are hereby incorporated by reference.

The dimmer switch 30 comprises a bidirectional semiconductor switch 32 coupled between the hot terminal H and the dimmed hot terminal DH for conducting a load current LOAD through the screw-in compact fluorescent lamp 20. The bidirectional semiconductor switch 32 may comprise a single device, such as a triac, or a combination of devices, such as, two field-effect transistors (FETs) or insulated-gate bipolar junction transistors (IGBTs) coupled in anti-series connection. To control the amount of power delivered to the lamp tube 22, the bidirectional semiconductor switch 32 is controlled to be conductive and non-conductive for portions of a half-cycle of the AC power source 15, such that the bidirectional semiconductor switch is rendered conductive for a conduction time T_{ON} each half-cycle. The dimmer switch 30 may comprise a toggle actuator for turning the high-efficiency lamp tube 22 on and off and an intensity adjustment actuator for adjusting the intensity of the lamp tube 22 between a low-end intensity and a high-end intensity.

The dimmer switch 30 further comprises a control circuit 34 coupled in parallel with the bidirectional semiconductor switch 32 for conducting a control current I_{CNTL} through the screw-in compact fluorescent lamp 20. The control circuit 34 is coupled to a control input of the bidirectional semiconductor switch 32 for rendering the bidirectional semiconductor switch conductive and non-conductive to generate a phase-control voltage V_{PC} using either the forward phase-control dimming technique or the reverse phase-control technique. Accordingly, the bidirectional semiconductor switch 32 is rendered conductive for the conduction time T_{CON} each half-cycle, thus setting a duty cycle DC_{PC} of the phase-control voltage V_{PC} . The control circuit 34 may be operable to provide, for example, a constant gate drive to the bidirectional semiconductor switch 32, such that the bidirectional semiconductor switch will remain conductive independent of the magnitude of the load current I_{LOAD} conducted through the bidirectional semiconductor switch and the screw-in compact fluorescent lamp 20. An example of a two-wire dimmer switch having a constant gate drive control circuit is described in greater detail in commonly-assigned, co-pending U.S. patent application Ser. No. 12/952,920, filed Nov. 23, 2010, entitled TWO-WIRE DIMMER

SWITCH FOR LOW-POWER LOADS, the entire disclosure of which is hereby incorporated by reference.

The screw-in base **26** of the compact fluorescent lamp **20** provides for only two electrical connections: a phase-control connection PC to the dimmer switch **30** for receiving the phase-control voltage V_{PC} and a neutral connection NC to the neutral side N of the AC power source **15**. The load regulation circuit **40** of the screw-in compact fluorescent lamp **20** is operable to adjust the intensity of the lamp tube **22** between the low-end intensity and the high-end intensity in response to the duty-cycle DC_{PC} of the phase-control signal V_{PC} (i.e., the conduction time of the bidirectional semiconductor switch **32** of the dimmer switch **30**).

With forward phase-control dimming, the bidirectional semiconductor switch **32** is rendered conductive at some point within each AC line voltage half-cycle and remains conductive until approximately the next voltage zero-crossing, such that the bidirectional semiconductor switch is conductive for the conduction time each half-cycle. A zero-crossing is defined as the time at which the AC line voltage transitions from positive to negative polarity, or from negative to positive polarity, at the beginning of each half-cycle. Forward phase-control dimming is often used to control energy delivered to a resistive or inductive load, which may include, for example, an incandescent lamp or a magnetic low-voltage transformer. The bidirectional semiconductor switch of a forward phase-control dimmer switch is typically implemented as a thyristor, such as a triac or two silicon-controlled rectifiers (SCRs) coupled in anti-parallel connection, since a thyristor becomes non-conductive when the magnitude of the current conducted through the thyristor decreases to approximately zero amps. Thyristors are typically characterized by a rated latching current and a rated holding current, and comprise two main terminals and a control terminal. The current conducted through the main terminals of the thyristor must exceed the latching current for the thyristor to become fully conductive. In addition, the magnitude of the load current LOAD conducted through the main terminals of the thyristor must remain above the holding current for the thyristor to remain in full conduction.

The control circuits of many forward phase-control dimmers comprise analog control circuits (such as timing circuits) for controlling when the thyristor is rendered conductive each half-cycle of the AC power source. The analog control circuit typically comprises a potentiometer, which may be adjusted in response to a user input provided from, for example, a linear slider control or a rotary knob in order to control the amount of power delivered to the lighting load. The analog control circuit is typically coupled in parallel with the thyristor and conducts a small timing current through the lighting load when the thyristor is non-conductive.

With reverse phase-control dimming, the bidirectional semiconductor switch **32** is rendered conductive at the zero-crossing of the AC line voltage and rendered non-conductive at some point within each half-cycle of the AC line voltage, such that the bidirectional semiconductor switch is conductive for a conduction time each half-cycle. The bidirectional semiconductor switch of reverse phase-control dimmers typically comprises two field-effect transistors (FETs) in anti-serial connection, or the like. Accordingly, prior art reverse phase-control dimmer switches have required advanced control circuits (such as microprocessors) for controlling the operation of the FETs, and power supplies for powering the microprocessors. In order to properly charge, the power supply of such a two-wire dimmer switch must develop an amount of voltage across the power supply

and must conduct a charging current from the AC power source through the electrical load, in many instances even when the lighting load is off.

FIG. **2** is a simplified block diagram of the load regulation circuit **40** of the prior art screw-in compact fluorescent lamp **20**. The load regulation circuit **40** comprises an electromagnetic interference (EMI) filter **50** for preventing noise generated by the load regulation circuit from being conducted on the AC mains wiring. A full-wave bridge rectifier **52** receives the phase-control voltage V_{PC} from the EMI filter **50** and generates a rectified voltage V_{RECT} . The rectified voltage V_{RECT} is coupled to a bus capacitor C_{BUS} through a diode **54** for generating a direct-current (DC) bus voltage V_{BUS} across the bus capacitor. The load regulation circuit **40** further comprises an inverter circuit **56** for generating a high-frequency square-wave voltage V_{SQ} from the rectified voltage V_{RECT} , and a resonant tank circuit **58** for receiving the square-wave voltage V_{SQ} and producing a substantially sinusoidal high-frequency AC voltage V_{LAMP} (i.e., an arc voltage or lamp voltage), which is provided to the lamp tube **22**. The inverter circuit **56** adjusts the operating frequency f_{OP} of the square-wave voltage V_{SQ} in order to adjust the intensity of the lamp tube **22**.

The load regulation circuit **40** further comprises a phase-to-DC converter circuit **60** for receiving the rectified voltage V_{RECT} and generating a DC voltage V_{DC} that has a magnitude that is representative of the duty-cycle DC_{PC} of the phase-control signal V_{PC} , and a lamp current sense circuit **62** that generates a lamp current control signal V_{ILAMP} representative of a magnitude of a lamp current I_{LAMP} conducted through the lamp tube **22**. A control circuit **64** is coupled to the inverter circuit **56** for adjusting an operating frequency f_{OP} of the square wave voltage V_{SQ} and thus the magnitude of the lamp current I_{LAMP} in response to the duty-cycle DC_{PC} of the phase-control signal V_{PC} and the magnitude of the lamp current I_{LAMP} . The load regulation circuit **40** also comprises a power supply **66** that receives the bus voltage V_{BUS} and generates a DC voltage V_{CC} for powering the control circuit **64**.

Since the dimmer switch **30** is a two-wire dimmer switch, the compact fluorescent lamp **20** receives both power for energizing the lamp tube **22** and information for determining the target intensity of the lamp tube from the phase-control signal V_{PC} . The phase-to-DC circuit **60** typically comprises a filter circuit for preventing voltage fluctuations in the AC mains line voltage V_{AC} of the AC power source **15** or noise on the AC mains line voltage V_{AC} from altering the magnitude of the DC voltage V_{DC} generated by the phase-to-DC converter circuit **60**. Therefore, there is typically a delay time period between a change in the duty-cycle DC_{PC} of the phase-control signal V_{PC} and a resulting change in the magnitude of the DC voltage V_{DC} generated by the phase-to-DC converter circuit **60**. If the intensity adjustment actuator of the dimmer switch **30** is controlled such that the target intensity is quickly reduced from the high-end intensity to the low-end intensity, the magnitude of the phase-control signal V_{PC} (and thus the amount of power available to the load regulation circuit **40**) will quickly decrease while the control circuit **64** is still controlling the intensity of the lamp tube **22** to the high-end intensity (due to the delay time period). Accordingly, the bus capacitor C_{BUS} will quickly discharge, such that the control circuit **64** becomes unpowered and the lamp tube **22** is extinguished, which, of course, is undesirable.

FIGS. **3A** and **3B** show example waveforms of the DC bus voltage V_{BUS} and the lamp current I_{LAMP} , respectively. As shown in FIG. **3A**, the bus voltage V_{BUS} is characterized by

some low-frequency voltage ripple having a frequency approximately equal to twice the frequency of the AC power source **15** (e.g., approximately 120 Hz). The control circuit **64** is typically characterized by a corner frequency of approximately 10-20 Hz, and thus controls the inverter circuit **56** to adjust the operating frequency f_{OP} of the square-wave voltage V_{SQ} at a relatively slow rate in response to the lamp current control signal V_{ILAMP} . Since the corner frequency (i.e., approximately 10-20 Hz) is less than the frequency of the voltage ripple of the bus voltage V_{BUS} (i.e., approximately 120 Hz), the operating frequency f_{OP} of the square-wave voltage V_{SQ} (and thus the lamp current I_{LAMP}) is maintained relatively constant over short time intervals (e.g., during a single half-cycle T_{HC} of the AC power source **15**, i.e., approximately 8.33 msec). As a result, the lamp current I_{LAMP} has an envelope I_{ENV} that is characterized by the frequency of the voltage ripple of the bus voltage V_{BUS} (as shown in FIG. 3B). This fluctuation (or ripple) in the envelope I_{ENV} of the lamp current I_{LAMP} can cause undesirable flicker in the lamp tube **22**.

Accordingly, there is a need for a dimmable screw-in compact fluorescent lamp having an integral electronic ballast circuit that avoids the disadvantages of the prior art circuits.

SUMMARY OF THE INVENTION

According to an embodiment of the present invention, a load control circuit controls a target intensity level of a lighting load in response to a duty cycle of a phase-control voltage by adjusting the target intensity level of the lighting load using a slow time constant in response to changes in the duty cycle of the phase-control voltage that are below a threshold amount, and adjusts the target intensity level of the lighting load using a fast time constant less than the first time constant in response to intentional changes in the duty cycle of the phase-control voltage. The load control circuit comprises a bus-voltage-generating circuit receiving the phase-control voltage and producing a DC bus voltage, a load regulation circuit receiving said DC bus voltage and adapted to be coupled to the lighting load for adjusting the intensity of the lighting load, and a control circuit operable to determine a target intensity level of the lighting load in response to the duty cycle of the phase-control voltage. The control circuit controls the load regulation circuit to adjust the intensity level of the lighting load in response to the duty cycle of the phase-control voltage and an actual-intensity signal related to the actual intensity level of the lighting load.

In addition, a phase-control-to-DC converter circuit for a load control device for controlling the amount of power delivered to an electrical load is also described herein. The phase-control-to-DC converter circuit receives a phase-control voltage characterized by a duty cycle for determining a target amount of power to be delivered to the electrical load and generates a DC voltage representative of the duty cycle of the phase-control voltage. The phase-control-to-DC converter circuit comprises a first filter circuit for generating a first filtered voltage in response to the duty cycle of the phase-control voltage, and a second filter circuit for receiving a first filtered voltage and generating a second filtered voltage (i.e., DC voltage representative of the duty cycle of the phase-control voltage) in response to the first filtered voltage. The first filter circuit is characterized by a first time constant, while the second filter circuit is characterized by a second time constant having a nominal value that is slower than a value of the first time constant of the first filter circuit.

When the difference between the magnitudes of the first and second filtered voltages exceeds a predetermined threshold, the second time constant has a fast value that is faster than the nominal value, such that the magnitude of the second filtered voltage quickly changes to be equal to the magnitude of the first filtered voltage.

According to another embodiment of the present invention, a control circuit for a load control circuit for a lighting load receives a phase-control voltage that is characterized by a duty cycle for determining a target intensity level of the lighting load, and operates to adjust said target intensity level of said lighting load using a slow time constant in response to changes in said duty cycle of said phase-control voltage that are below a threshold amount, and adjust said target intensity level of said lighting load using a fast time constant less than the first time constant in response to intentional changes in said duty cycle of said phase-control voltage. The control circuit comprises a phase-control-voltage converter circuit for converting the phase-control voltage into a target signal that is used to determine the target intensity level of the lighting load, and an error amplifier circuit for comparing the target signal and an actual-intensity signal related to the actual intensity level of the lighting load and generating a drive control signal for controlling said lighting load to said target intensity level.

According to yet another embodiment of the present invention, a lighting control system receiving power from an AC power source comprises a dimmable high-efficiency lighting load comprises a light source and a load regulation circuit for illuminating the light source, and a two-wire dimmer switch adapted to be coupled in series electrical connection between the AC power source and the dimmable compact fluorescent lamp for generating a phase-control voltage characterized by a duty cycle. The load regulation circuit receives the phase-control voltage and illuminates the light source in response to the phase-control voltage. The load regulation circuit comprises a control circuit operable to determine a target intensity level of said lamp in response to the duty cycle of the phase-control voltage. The control circuit converts the phase-control voltage into a DC target intensity signal, and controls the load regulation circuit in response to the DC target intensity signal to adjust the intensity of the light source to target intensity level. The control circuit adjusts said target intensity level of said lamp using a slow time constant in response to changes in said duty cycle of said phase-control voltage that are below a threshold amount, and adjusts said target intensity level of said lamp using a fast time constant less than the first time constant in response to intentional changes in said duty cycle of said phase-control voltage.

Further, a method of converting a duty cycle of a phase-control voltage to a DC voltage in a load control device for controlling the amount of power delivered to an electrical load, where the duty cycle of the phase-control voltage is used to determine a target amount of power to be delivered to the electrical load, is also described herein. The method comprises the steps of: (1) generating a first filtered signal in response to the duty cycle of the phase-control voltage using a first time constant; (2) generating a second filtered signal in response to the first filtered signal using a second nominal time constant that is slower than the first time constant when the difference between the magnitudes of the first and second filtered signals is below a predetermined threshold; and (3) generating the second filtered signal in response to the first filtered voltage using a third fast time constant that is faster than the nominal time constant when the difference between the magnitudes of the first and second filtered signals

exceeds a predetermined threshold, such that the magnitude of the second filtered signal quickly changes to be equal to the magnitude of the first filtered signal.

According to another embodiment of the present invention, a method of controlling a compact fluorescent lamp comprises: (1) receiving a phase-control voltage characterized by a duty cycle set by a dimmer switch that operates according to either a forward phase-control method or reverse phase-control method; (2) determine a target intensity level of said lamp in response to the duty cycle of the phase-control voltage; (3) providing a sinusoidal output voltage to said lamp for illuminating said lamp to said target intensity level; (4) adjusting said target intensity level of said lamp using a slow time constant in response to changes in said duty cycle of said phase-control voltage that are below a threshold amount; and (5) adjusting said target intensity level of said lamp using a fast time constant less than the first time constant in response to intentional changes in said duty cycle of said phase-control voltage.

Other features and advantages of the present invention will become apparent from the following description of the invention that refers to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will now be described in greater detail in the following detailed description with reference to the drawings in which:

FIG. 1 is a simplified block diagram of a prior art lighting control system including a “two-wire” dimmer switch for controlling the amount of power delivered to a screw-in compact fluorescent lamp;

FIG. 2 is a simplified block diagram of the screw-in compact fluorescent lamp of the lighting control system of FIG. 1;

FIG. 3A shows an example waveform of a bus voltage of the screw-in compact fluorescent lamp of FIG. 2;

FIG. 3B shows an example waveform of a lamp current of the screw-in compact fluorescent lamp of FIG. 2;

FIG. 4 is a side view of a dimmable screw-in compact fluorescent lamp according to a first embodiment of the present invention;

FIG. 5 is a simplified schematic diagram of the screw-in compact fluorescent lamp of FIG. 4;

FIG. 6 is a simplified schematic diagram of the electrical circuitry of the screw-in compact fluorescent lamp of FIG. 4 showing a load regulation circuit and two power supplies in greater detail;

FIG. 7 is a simplified schematic diagram of an inverter circuit of the load regulation circuit and an over-voltage protection circuit of the screw-in compact fluorescent lamp of FIG. 4;

FIG. 8 is a simplified schematic diagram of a control circuit of the screw-in compact fluorescent lamp of FIG. 4;

FIG. 9 is an example plot of the magnitude of a lamp voltage with respect to the magnitude of a lamp current of the screw-in compact fluorescent lamp of FIG. 4;

FIG. 10A shows an example waveform of a bus voltage of the screw-in compact fluorescent lamp of FIG. 4;

FIG. 10B shows an example waveform of a lamp current of the screw-in compact fluorescent lamp of FIG. 4 according to the first embodiment of the present invention;

FIG. 11 is a simplified schematic diagram of a control circuit of the dimmable screw-in compact fluorescent lamp according to a second embodiment of the present invention; and

FIG. 12 is a simplified flowchart of a control procedure executed periodically by a microprocessor of the control circuit of FIG. 11.

DETAILED DESCRIPTION OF THE INVENTION

The foregoing summary, as well as the following detailed description of the preferred embodiments, is better understood when read in conjunction with the appended drawings. For the purposes of illustrating the invention, there is shown in the drawings an embodiment that is presently preferred, in which like numerals represent similar parts throughout the several views of the drawings, it being understood, however, that the invention is not limited to the specific methods and instrumentalities disclosed.

FIG. 4 is a side view of a dimmable screw-in compact fluorescent lamp 120 according to a first embodiment of the present invention. The dimmable screw-in compact fluorescent lamp 120 comprises a light source, e.g., a fluorescent lamp tube 122, which may be formed in a spiral (as shown in FIG. 4), in two or more U-bends, or in any other suitable form. The lamp tube 122 may be filled with a fill-gas mixture having a fill-gas pressure of approximately 2 Torr and a fill-gas ratio of approximately 85:15 argon to neon. The dimmable screw-in compact fluorescent lamp 120 further comprises an enclosure 24 for housing a load regulation circuit 130 (FIG. 5), e.g., an electronic ballast circuit, which is electrically coupled to the lamp tube 122 for illuminating the lamp tube.

The screw-in compact fluorescent lamp 120 has a screw-in base 126 adapted to be coupled to a standard Edison socket, such that the lamp is adapted to be coupled to a two-wire dimmer switch (such as the dimmer switch 30) via the phase-control connection PC of the screw-in base 126 and to the neutral side N of an AC power source via the neutral connection NC (as in the prior art lighting control system 100 shown in FIG. 1). As defined herein, a “two-wire” dimmer switch or load control device does not require a direct connection to the neutral side N of the AC power source. In other words, all currents conducted by the two-wire dimmer switch must also be conducted through the load. A two-wire dimmer switch may have only two terminals (i.e., the hot terminal H and the dimmed hot terminal DH as shown in FIG. 1). Alternatively, a two-wire dimmer switch could comprise a three-way dimmer switch that may be used in a three-way lighting system and has at least three load terminals, but does not require a neutral connection. In addition, a two-wire dimmer switch may comprise an additional connection that provides for communication with a remote control device (for remotely controlling the dimmer switch), but does not require the dimmer switch to be directly connected to neutral.

FIG. 5 is a simplified schematic diagram of a dimmable screw-in compact fluorescent lamp 120 according to the first embodiment of the present invention. As previously mentioned, the screw-in base 126 provides for only two electrical connections: the phase-control connection PC to the dimmer switch for receiving the phase-control voltage V_{PC} and the neutral connection NC to the neutral side N of the AC power source. The load regulation circuit 130 of the screw-in compact fluorescent lamp 120 is operable to adjust the intensity of the lamp tube 122 to a target intensity L_{TRGT} (i.e., a desired intensity) in response to the duty-cycle DC_{PC} of the phase-control signal V_{PC} . The target intensity L_{TRGT}

may range between a low-end intensity L_{LE} (e.g., approximately 1%) and a high-end intensity L_{HE} (e.g., approximately 100%).

The screw-in compact fluorescent lamp **120** comprises a filter network **200** coupled to the phase-control connection PC and the neutral connection NC of the connector **126** for receiving the phase-control voltage V_{PC} from the dimmer switch **30**. The filter network **200** comprises an inductor **L201** (e.g., having an inductance of approximately 680 μ H) and two capacitors **C202**, **C203** (e.g., having capacitances of approximately 33 nF). The filter network **200** operates to prevent noise generated by the load regulation circuit **130** from being conducted on the AC mains wiring. The filter network **200** couples the phase-control voltage V_{PC} to a voltage doubler circuit **205** (i.e., a bus-voltage-generating circuit), which generates a direct-current (DC) bus voltage V_{BUS} across two series connected bus capacitors C_{B1} , C_{B2} . The first bus capacitor C_{B1} conducts the load current I_{LOAD} through a diode **D206** (and the dimmer switch **30**) to charge during the positive half-cycles, while the second bus capacitor C_{B2} conducts the load current I_{LOAD} through a diode **D208** to charge during the negative half-cycles. Accordingly, the peak magnitude of the bus voltage V_{BUS} is approximately twice the peak voltage of the AC mains line voltage V_{AC} . A half-bus voltage V_{HB} is generated across the first bus capacitor C_{B1} and has a magnitude equal to approximately half of the bus voltage V_{BUS} .

The load regulation circuit **130** (i.e., the electronic ballast circuit) includes a half-bridge inverter circuit **210** for converting the DC bus voltage V_{BUS} to a high-frequency square-wave voltage V_{SQ} having an operating frequency f_{OP} . The load regulation circuit **130** further comprises an output filter circuit, e.g., a resonant tank circuit **220**, for filtering the square-wave voltage V_{SQ} to produce a substantially sinusoidal high-frequency AC voltage, which is coupled to the electrodes of the lamp tube **122**. A control circuit **230** is coupled to the inverter circuit **210** for providing a drive control signal V_{DR} to the inverter circuit **210** for adjusting the operating frequency f_{OP} of the square wave voltage V_{SQ} and thus the magnitude of a lamp current I_{LAMP} conducted through the lamp tube **122** in order to turn the lamp tube on and off and adjust the intensity of the lamp tube. Alternatively, the screw-in compact fluorescent lamp **120** could comprise a different high-efficiency lighting load, such as, a dimmable screw-in LED light source having an LED light engine, and the load regulation circuit **130** could comprise an LED driver. An example of the LED driver **102** is described in greater detail in commonly-assigned, co-pending U.S. patent application Ser. No. 12/813,908, filed Jun. 11, 2009, and U.S. patent application Ser. No. 13/416,741, filed Mar. 9, 2012, both entitled LOAD CONTROL DEVICE FOR A LIGHT-EMITTING DIODE LIGHT SOURCE, the entire disclosures of which are hereby incorporated by reference.

The screw-in compact fluorescent lamp **120** further comprises two power supplies: an inverter power supply **240** and a control power supply **250**. The inverter power supply **240** receives the half-bus voltage V_{HB} across the first bus capacitor C_{B1} and generates a direct-current (DC) inverter supply voltage V_{INV} (e.g., approximately 15 volts) for powering the control circuitry of the inverter circuit **210**. The control power supply **250** draws current from the resonant tank circuit **220** and generates a DC control supply voltage V_{CC} (e.g., approximately 12 volts) for powering the control circuit **230** while the inverter circuit **210** is generating the high-frequency square-wave voltage V_{SQ} . When the screw-in compact fluorescent lamp **120** is first powered up, the

inverter power supply **240** is operable to generate the inverter supply voltage V_{INV} before the control power supply **250** begins to produce the control supply voltage V_{CC} . After the inverter power supply **240** is generating the inverter supply voltage V_{INV} , the inverter circuit **210** is able to begin generating the high-frequency square-wave voltage V_{SQ} , such that the control power supply **250** is able to draw current from the resonant tank circuit **220**. Accordingly, the control power supply **250** then produces the control supply voltage V_{CC} to power the control circuit **230**.

The screw-in compact fluorescent lamp **120** further comprises an over-voltage protection (OVP) circuit **260**, which provides an OVP control signal V_{OV} to the inverter circuit **210** for protecting the lamp tube **122** and the load regulation circuit **130** during over-voltage conditions. A lamp current sense circuit **270** is coupled in series with the lamp tube **122** to conduct the lamp current I_{LAMP} and to generate a lamp current control signal V_{ILAMP} representative of a magnitude of the lamp current I_{LAMP} . The screw-in compact fluorescent lamp **120** further comprises a rectifier circuit **280** (e.g., a full-wave rectifier diode bridge as shown in FIG. 5), which has AC terminals coupled to receive the phase-control voltage V_{PC} from the filter network **200** and DC terminals for providing a rectified voltage V_{RECT} .

The rectified voltage V_{RECT} is received by an artificial load circuit **290** for conducting an artificial load current I_{ART} through the dimmer switch **30** in addition to the load current I_{LOAD} conducted by the bus capacitors C_{B1} , C_{B2} when the bus capacitors are charging. If the dimmer switch **30** includes a triac for generating the phase-control voltage V_{PC} , the artificial load circuit **290** is able to conduct enough current to ensure that the magnitude of the total current conducted through the triac of the dimmer switch exceeds the rated latching and holding currents of the triac. In addition, the artificial load circuit **290** may conduct a timing current if the dimmer switch **30** comprises a timing circuit and may conduct a charging current if the dimmer switch comprises a power supply, such that these currents need not be conducted through the load regulation circuit **130** and do not affect the intensity of the lamp tube **122**.

The artificial load circuit **290** comprises a current-passing switch, e.g., a FET **Q282**, coupled in series with a resistor **R284** (e.g., having a resistance of approximately 12.4 Ω), where the series combination of the drain-source junction of the FET **Q282** and the resistor **R284** is coupled across the DC terminals of the rectifier circuit **280**. The gate of the FET **Q282** is coupled to the drain of the FET **Q282** through a resistor **R285** (e.g., having a resistance of approximately 1 M Ω), such that the FET **Q282** is rendered conductive and conducts the artificial load current I_{ART} when the magnitude of the rectified voltage V_{RECT} increases from approximately zero volts to exceed a turn-on threshold (e.g., approximately 4 volts). Accordingly, the FET **Q282** is rendered conductive, such that the artificial load circuit **290** conducts the artificial load current I_{ART} through the dimmer switch **30** after the triac is rendered conductive (if the dimmer switch is using the forward phase-control dimming technique), or shortly after the beginning of each half-cycle (if the dimmer switch is using the reverse phase-control dimming technique). The artificial load circuit **290** further comprises an NPN bipolar junction transistor **Q286** having a base-emitter junction coupled across the resistor **R284** and a collector coupled to the gate of the FET **Q282**. The transistor **Q286** controls the FET **Q282** in the linear region to provide over-current protection of the FET **Q282** when the voltage across the resistor **R284** exceeds the rated base-emitter voltage of the transistor **Q286** (e.g., approximately 0.7 volt).

The artificial load circuit **290** also comprises an NPN bipolar junction transistor **Q288** having a collector coupled to the gate of the FET **Q282**, and a zener diode **Z292**, having, for example, break-over voltage V_{BR} of approximately 13.2 volts. Three resistors **R294**, **R295**, **R296** are coupled in series between the DC terminals of the rectifier circuit **180** and have, for example, resistances of approximately 22 k Ω , 470 k Ω , and 150 k Ω , respectively. The zener diode **Z292** is coupled between the base of the transistor **Q288** and the junction of the resistors **R295**, **R296**. A capacitor **C298** is coupled across the resistor **R296** and has, for example, a capacitance of approximately 1000 pF. When the magnitude of the rectified voltage V_{RECT} exceeds a turn-off threshold (e.g., approximately 60 volts), the zener diode **Z292** conducts current into the base of the transistor **Q288**. Accordingly, the transistor **Q288** is rendered conductive and the FET **Q282** is rendered non-conductive, such that the artificial load circuit **290** stops conducting the artificial load current I_{ART} . If the dimmer switch **30** is using the forward phase-control dimming technique, the capacitor **C298** provides some delay, such that the artificial load circuit **290** conducts the artificial load current I_{ART} for a period of time after the triac is rendered conductive.

The artificial load circuit **290** also provides a phase-control input control signal V_{PC-IN} to the control circuit **230**. Specifically, the artificial load circuit **290** comprises a PNP bipolar junction transistor **Q299** having a collector coupled to the control circuit **230** for providing the phase-control input control signal V_{PC-IN} . The emitter-base junction of the transistor **Q299** is coupled across the resistor **R294**, such that the transistor **Q299** is rendered conductive shortly after the triac is rendered conductive (with forward phase-control dimming) or shortly after the beginning of each half-cycle (with reverse phase-control dimming). The control circuit **230** uses the phase-control input control signal V_{PC-IN} to determine the duty-cycle DC_{PC} of the phase-control voltage V_{PC} (i.e., the conduction time T_{CON} of the bidirectional semiconductor switch **32** of the dimmer switch **30**). The control circuit **230** determines the present magnitude of the lamp current I_{LAMP} from the lamp current control signal V_{ILAMP} received from the lamp current sense circuit **270**. The control circuit **230** then adjusts the operating frequency f_{OP} of the square wave voltage V_{SQ} to control the magnitude of the lamp current I_{LAMP} to a desired level that is dependent upon the duty-cycle DC_{PC} of the phase-control voltage V_{PC} to thus control the intensity of the lamp tube **122** to the target intensity L_{TRGT} .

FIG. 6 is a simplified schematic diagram of the electrical circuitry of the screw-in compact fluorescent lamp **120** showing the inverter circuit **210**, the resonant tank circuit **220**, the inverter power supply **240**, the control power supply **250**, and lamp current sense circuit **270** in greater detail. The inverter circuit **210** comprises first and second series-connected switching devices (e.g., FETs **Q212**, **Q214**) and an inverter control circuit **216**, which may comprise, for example, an inverter control integrated circuit (IC) **U300** (FIG. 5), such as part number FAN7532, manufactured by Fairchild Semiconductor Incorporated. The inverter control IC **U300** of the inverter control circuit **216** is powered by the inverter supply voltage V_{INV} and controls the FETs **Q212**, **Q214** in response to the drive control signal V_{DR} received from the control circuit **230** as will be described in greater detail below with reference to FIG. 7. The inverter control circuit **216** renders the FETs **Q212**, **Q214** conductive and non-conductive on a complementary basis (such that only one of the FETs is conducting at a time) using a constant duty cycle (e.g., approximately 50%). When the first FET

Q212 is conductive, the output of the inverter circuit **210** is pulled up towards the bus voltage V_{BUS} . When the second FET **Q214** is conductive, the output of the inverter circuit **210** is pulled down towards circuit common. The magnitude of the lamp current I_{LAMP} conducted through the lamp tube **122** is controlled by adjusting the operating frequency f_{OP} of the high-frequency square wave voltage V_{SQ} generated by the inverter circuit **210**.

The resonant tank circuit **220** comprises a resonant inductor **L222** adapted to be coupled in series between the inverter circuit **210** and the lamp tube **122**, and a resonant capacitor **C224** adapted to be coupled in parallel with the lamp tube. For example, the inductor **L222** may have an inductance of approximately 1.4 mH, while the resonant capacitor **C224** may have a capacitance of approximately 1.2 nF, such that resonant tank circuit is characterized by a resonant frequency of approximately 110 kHz. The resonant tank circuit **220** further comprises a DC-blocking capacitor **C226** that has a capacitance of, for example, approximately 2.7 nF and operates to minimize the DC component of the lamp current I_{LAMP} conducted through the lamp tube **122**.

When the lamp tube **122** is not illuminated and the control circuit **230** receives a command to turn the lamp tube on (from the phase-control voltage V_{PC}), the control circuit first preheats filaments **228A**, **228B** of the lamp tube **122** and then attempts to strike the lamp tube. The load regulation circuit **130** may comprise, for example, two filament windings **229A**, **229B** that are magnetically coupled to the resonant inductor **L222** and electrically coupled to the respective filaments **228A**, **228B** for generating filament voltages for heating the filaments of the lamp tube **122** prior to striking the lamp. To preheat the filaments **228A**, **228B**, the inverter circuit **210** controls the operating frequency f_{OP} of the square wave voltage V_{SQ} to a preheat frequency f_{PH} (e.g., approximately 150 kHz) for a preheat time period T_{PH} (e.g., approximately 700 msec). An example of a ballast having a circuit for heating the filaments of a fluorescent lamp is described in greater detail in U.S. Pat. No. 7,586,268, issued Sep. 8, 2009, titled APPARATUS AND METHOD FOR CONTROLLING THE FILAMENT VOLTAGE IN AN ELECTRONIC DIMMING BALLAST, the entire disclosure of which is hereby incorporated by reference.

The inverter power supply **240** receives the half-bus voltage V_{HB} developed across the first bus capacitor C_{B1} and generates the inverter supply voltage V_{INV} across a storage capacitor **C242** (e.g., having a capacitance of approximately 1 μ F). The inverter power supply **240** comprises a simple zener-regulated power supply having a zener diode **Z243**, which is coupled across the storage capacitor **C242** and may have, for example, a break-over voltage of approximately 13.2 volts. When the screw-in compact fluorescent lamp **120** is first powered up, the storage capacitor **C242** is able to charge by conducting a small trickle current from the AC power source **15** through a resistor **R244** (e.g., having a resistance of approximately 392 k Ω) until the inverter supply voltage V_{INV} is developed across the storage capacitor **C242**. After the magnitude of the inverter supply voltage V_{INV} exceeds the rated operating voltage of the inverter control IC **U300** of the inverter control circuit **216**, the inverter control IC begins to control the FETs **Q212**, **Q214** to be conductive and non-conductive to generate the square wave voltage V_{SQ} .

The inverter power supply **240** further comprises a snubber capacitor **C245** that has, for example, a capacitance of approximately 470 pF and provides a path for charging the storage capacitor **C242** after the inverter control circuit **216**

begins generating the square wave voltage V_{SQ} . The snubber capacitor **C245** is coupled between junction of the two FETs **Q212**, **Q214** and the storage capacitor **C242** through a diode **D246** and a resistor **R246** (e.g., having a resistance of approximately 5.6Ω). The storage capacitor **C242** is able to charge when the first FET **Q212** is conductive (i.e., when the square-wave voltage V_{SQ} is being pulled high towards the bus voltage V_{BUS}). When the second FET **Q214** is conductive and the square-wave voltage V_{SQ} is being pulled low towards circuit common, the snubber capacitor **C245** is able to discharge through the second FET **Q214** and a diode **D248**. Accordingly, after the inverter control circuit **216** begins generating the square wave voltage V_{SQ} , the inverter power supply **240** is operable to generate the inverter supply voltage V_{INV} by conducting current through the snubber capacitor **C245** rather than conducting current through the resistor **R244**, which would needlessly dissipate an excessive amount of power.

The control power supply **250** comprises a linear regulator, for example, an adjustable linear regulator **U252**, such as part number LM317L, manufactured by Fairchild Semiconductor Incorporated. The control power supply **250** comprises a winding **254** magnetically coupled to the resonant inductor **L222** of the resonant tank circuit **220** for generating an electromagnetically-coupled voltage, such that the linear regulator **U252** is able to draw current from the resonant tank circuit through a diode **D255** when the inverter control circuit **216** is generating the square-wave voltage V_{SQ} . A capacitor **C256** is coupled across the input of the linear regulator **U252** and has, for example, a capacitance of approximately $0.1\ \mu\text{F}$. A first resistor **R258** is coupled between the output of the adjustable linear regulator **U252** and the adjustment pin of the linear regulator, while a second resistor **R259** is coupled between the adjustment pin and circuit common. For example, the first and second resistors **R258**, **R259** may have resistances of approximately 475Ω and $5.23\ \text{k}\Omega$, respectively, such that the control supply voltage V_{CC} at the output of the linear regulator **U252** has a nominal magnitude of approximately 15 volts.

FIG. 7 is a simplified schematic diagram of the inverter circuit **210** and the OVP circuit **260**. As previously mentioned, the inverter control circuit **216** includes the inverter control IC **U300**, which is powered by the inverter supply voltage V_{INV} . The inverter control IC **U300** is directly coupled to the gates of the FETs **Q212**, **Q214** for controlling the FETs to be conductive and non-conductive (via pins 16 and 13). The inverter control circuit **216** comprises a pre-heat-frequency-set resistor R_{PH} , which is coupled to a pre-heat-frequency-set input (pin 7) of the inverter control IC **U300** for setting the preheat frequency f_{PH} . The pre-heat-frequency-set resistor R_{PH} may have a resistance of, for example, approximately $27\ \text{k}\Omega$, such that the preheat frequency f_{PH} is approximately 150 kHz. The inverter control circuit **216** also comprises a preheat-time-set capacitor C_{PH} , which is coupled to a preheat-time-set input (pin 5) of the inverter control IC **U300** for setting the length of the preheat time period T_{PH} . For example, the preheat-time-set capacitor C_{PH} may have a capacitance of approximately $0.33\ \mu\text{F}$, such that the preheat time period T_{PH} is approximately 700 msec.

During the preheat time period T_{PH} , a voltage V_{RPH} generated across the preheat-frequency-set resistor R_{PH} (i.e., at pin 7) is maintained constant, while a voltage V_{CPH} generated across the preheat-time-set capacitor C_{PH} (i.e., at pin 5) increases in magnitude with respect to time from approximately zero volts. When the voltage V_{CPH} across the preheat-time-set capacitor C_{PH} exceeds a preheat voltage

threshold V_{PH} at the end of the preheat time period T_{PH} , the inverter control IC **U300** then controls the operating frequency f_{OP} to attempt to strike the lamp tube **122**. The voltage V_{RPH} across the preheat-frequency-set resistor R_{PH} and the voltage V_{CPH} across the preheat-time-set capacitor C_{PH} are also provided to the control circuit **230**, such that the control circuit is operable to properly control the inverter control IC **U300** during the preheat time period T_{PH} as will be described in greater detail below.

The inverter control circuit **216** comprises an operating-frequency-set resistor R_T coupled to an frequency-set-resistor input (pin 8) of the inverter control IC **U300** and an operating-frequency-set capacitor C_T coupled to a frequency-set-capacitor input (pin 6) for setting the operating frequency f_{OP} of the square-wave voltage V_{SQ} when the lamp tube **122** is illuminated (i.e., after the lamp tube has been struck). For example, the operating-frequency-set resistor R_T may have a resistance of approximately $30\ \text{k}\Omega$ and the operating-frequency-set capacitor C_T may have a capacitance of approximately $330\ \text{pF}$, such that a default operating frequency of the square-wave voltage V_{SQ} is approximately 110 kHz.

The inverter control circuit **216** further comprises an NPN bipolar junction transistor **Q310** having a collector-emitter junction coupled between the frequency-set-resistor input of the inverter control IC **U300** and circuit common through a resistor **R312** (e.g., having a resistance of approximately $10\ \text{k}\Omega$). The base of the transistor **Q310** is coupled to receive the drive control signal V_{DR} from the control circuit **230**. The drive control signal V_{DR} has a DC magnitude that is representative of a target operating frequency f_{TRGT} to which the operating frequency f_{OP} should be controlled to control the intensity of the lamp tube **122** to the target intensity L_{TRGT} . The transistor **Q310** is controlled to operate in the linear region, such that the transistor **Q310** provides a controllable impedance between the frequency-set-resistor input of the inverter control IC **U300** and circuit common in response to the DC magnitude of the drive control signal V_{DR} . Accordingly, the control circuit **230** is operable to adjust the operating frequency f_{OP} of the square-wave voltage V_{SQ} by controlling the impedance provided by the transistor **Q310** and thus the current conducted through the frequency-set-resistor input of the inverter control IC **U300**.

The inverter control circuit **216** receives the OVP control signal V_{OVP} from the OVP circuit **260**. Specifically, the OVP control signal V_{OVP} is coupled to an open lamp protection (OLP) input (pin 10) of the inverter control IC **U300** through a resistor **R320** (e.g., having a resistance of approximately $10\ \text{k}\Omega$), and is coupled to circuit common through a capacitor **C322** (e.g., having a capacitance of approximately $0.1\ \mu\text{F}$). The OVP circuit **260** comprises a voltage divider having resistors **R261**, **R262** for scaling the magnitude of the lamp voltage V_{LAMP} down to a magnitude that is appropriate to be received by the inverter control IC **U300**. For example, the resistors **R261**, **R262** may have resistances of approximately $1\ \text{M}\Omega$ and $25.5\ \text{k}\Omega$, respectively. The junction of the resistors **R261**, **R262** is coupled to a capacitor **C264** (e.g., having a capacitance of approximately $0.1\ \mu\text{F}$) through a diode **D265**. The junction of the capacitor **C264** and the diode **D265** is coupled to the inverter control circuit **216** through a zener diode **Z266** for generating the OVP control signal V_{OVP} , which is coupled to circuit common through a resistor **R268** (e.g., having a resistance of approximately $100\ \text{k}\Omega$). For example, the zener diode **Z266** may have a break-over voltage of approximately 13.2 volts.

During normal operation, the voltage at the OLP input of the inverter control IC **U300** remains low (i.e., at approxi-

mately circuit common). However, in the event of an over-voltage condition across the lamp tube **122**, the zener diode **Z266** begins to conduct, such that the voltage at the OLP input of the inverter control IC **U300** increases in magnitude. When the magnitude of the voltage at the OLP input exceeds an OLP threshold voltage of the inverter control IC **U300** (e.g., approximately 2 volts), the inverter control IC disables the outputs (i.e., pins 13 and 16) such that the FETs **Q212**, **Q214** are rendered non-conductive and the lamp tube **122** is not illuminated until the control circuit **230** controls the inverter circuit **210** to attempt to restrike the lamp tube once again.

FIG. **8** is a simplified schematic diagram of the control circuit **230**. The control circuit **230** comprises a two-speed phase-to-DC converter circuit **400** for converting the phase-control input control signal V_{PC-IN} to a DC target voltage V_{TRGT} that is representative of the duty-cycle DC_{PC} of the phase-control voltage V_{PC} and thus the target intensity L_{TRGT} of the lamp tube **122**. The DC target voltage V_{TRGT} is amplified by a non-inverting amplifier circuit **420** to generate an amplified target voltage V_{A-TRGT} such that the magnitude of the amplified target voltage V_{A-TRGT} is within a correct range to be received by an error amplifier circuit **430**. For example, the DC target voltage V_{TRGT} may be in the range of approximately 1-4 volts, while the amplified target voltage V_{A-TRGT} is in the range of approximately 0.5-6.5 volts. A non-linear amplifier circuit **440** receives the lamp current control signal V_{ILAMP} from the lamp current sense circuit **270** and generates an amplified lamp current signal $V_{A-ILAMP}$. The error amplifier circuit **430** receives the amplified target voltage V_{A-TRGT} and the amplified lamp current signal $V_{A-ILAMP}$ and generates the drive control signal V_{DR} to adjust the operating frequency f_{OP} of the inverter circuit **210**, so as to minimize the error between the amplified target voltage V_{A-TRGT} and the amplified lamp current signal $V_{A-ILAMP}$.

The phase-to-DC converter circuit **400** comprises a voltage divider having two resistors **R401**, **R402** for scaling down the phase-control input control signal V_{PC-IN} . For example, the resistors **R401**, **R402** may have resistances of approximately 1 M Ω and 47 k Ω , respectively. Next, the phase-to-DC converter circuit **400** generates a switched voltage V_S that has a duty-cycle approximately equal to the duty cycle DC_{PC} of the phase-control input control signal V_{PC-IN} . Specifically, the junction of the resistors **R401**, **R402** is coupled to the base of a first NPN bipolar junction transistor **Q404** that has a collector-emitter junction coupled between the control supply voltage V_{CC} and circuit common through a resistor **R405** (e.g., having a resistance of approximately 220 k Ω). The junction of the collector of the transistor **Q404** and the resistor **R405** is coupled to the base of a second NPN bipolar junction transistor **Q406** that has a collector-emitter junction coupled between the control supply voltage V_{CC} and circuit common through two resistors **R408**, **R409** (e.g., having resistances of approximately 40 k Ω and 1 k Ω , respectively). Accordingly, the switched voltage V_S is generated at the collector of the second transistor **Q406**.

When the magnitude of the phase-control input control signal V_{PC-IN} is approximately zero volts (i.e., when the bidirectional semiconductor switch **32** of the dimmer switch **30** is non-conductive), the first transistor **Q404** is rendered non-conductive, such that the second transistor **Q406** is rendered conductive and the switched voltage V_S is pulled low towards circuit common. When the magnitude of the phase-control input control signal V_{PC-IN} is greater than a phase-control threshold, e.g., approximately 15 volts (i.e.,

when the bidirectional semiconductor switch **32** of the dimmer switch **30** is conductive), the first transistor **Q404** is rendered conductive, such that the second transistor **Q406** is rendered non-conductive and the switched voltage V_S is pulled high towards control supply voltage V_{CC} through the resistors **R408**, **R409**.

A ramp voltage V_R is generated across a capacitor **C410** (e.g., having a capacitance of approximately 0.22 μ F) in response to the square-wave voltage V_S . When the second transistor **Q406** is non-conductive, the capacitor **C410** is able to charge towards the control supply voltage V_{CC} through the resistor **R408**, such that the magnitude of the ramp voltage V_R increases with respect to time while the switched voltage V_S is high. When the second transistor **Q406** is conductive, the capacitor **C410** is able to discharge through the resistor **R409**, such that the magnitude of the ramp voltage V_R decreases at a second rate that is much faster than the first rate at which the ramp voltage increases in magnitude. Accordingly, the ramp voltage V_R is generated across the capacitor **C410** and has a duty cycle equal to approximately the duty cycle of the phase-control input control signal V_{PC-IN} . Next, the ramp voltage V_R is filtered by a first filter circuit, e.g., a resistor-capacitor (RC) circuit (including a resistor **R411** and a capacitor **C412**), to generate a filtered voltage V_F . For example, the resistor **R411** has a resistance of approximately 220 k Ω and the capacitor **C412** has a capacitance of approximately 0.22 μ F, such that the first RC circuit has a time constant τ_{RC1} of approximately 48.4 msec.

The filtered voltage V_F from the first RC circuit is then filtered by a second RC circuit (having a resistor **R413** and a capacitor **C414**) to generate the target voltage V_{TRGT} . Two diodes **D416**, **D418** are coupled in anti-parallel connection across the resistor **R413**. For example, the resistor **R413** has a resistance of approximately 2.2 M Ω and the capacitor **C414** has a capacitance of approximately 0.22 μ F, such that a time constant τ_{RC2} of the second RC circuit has a nominal value of approximately 484 msec (i.e., approximately 10 times slower than the first RC circuit). The magnitude of the target voltage V_{TRGT} is a function of the square of the conduction time T_{CON} of the bidirectional semiconductor switch **32** of the dimmer switch **30**, i.e., $V_{TRGT} = f(T_{CON}^2)$. Accordingly, the control circuit **230** is operable to adjust the intensity of the lamp tube **122** in response to the duty-cycle DC_{PC} of the phase-control voltage V_{PC} according to a "square-law" dimming curve. As a result, the control circuit **230** provides finer tuning of the intensity of the lamp tube **122** near the low-end intensity L_{LE} , such that larger variations in the conduction time T_{CON} of the bidirectional semiconductor switch **32** result in smaller changes in the intensity of the lamp tube **122** near the low-end intensity L_{LE} .

Voltage fluctuations in the AC mains line voltage V_{AC} of the AC power source **15** or noise on the AC mains line voltage V_{AC} can cause the duty-cycle DC_{PC} of the phase-control signal V_{PC} and the magnitude of the filtered voltage V_F to vary slightly. Therefore, the slow nominal value $\tau_{RC2-NOM}$ of the time constant τ_{RC2} of the second RC circuit provides enough filtering such that the target voltage V_{TRGT} is not responsive to changes in the filtered voltage V_F that are less than a predetermined threshold, e.g., approximately the forward voltage of the diodes **D416**, **D418**, i.e., a diode drop (e.g., approximately 0.7 volts).

However, changes in the target intensity L_{TRGT} at the dimmer switch **30** that result in the dimmer switch changing the duty cycle DC_{PC} of the phase-control signal V_{PC} cause the magnitude of the filtered voltage V_F to change by greater

amounts and at faster rates than the voltage fluctuations and noise of the AC mains line voltage V_{AC} . Therefore, when the magnitude of the filtered voltage V_F changes by more than the forward voltage of the diodes **D416**, **D418**, one of the diodes **D416**, **D418** will begin to conduct such that the magnitude of the target voltage V_{TRGT} across the capacitor **C414** changes quickly in response to changes in the target intensity L_{TRGT} . Specifically, the first diode **D416** is operable to conduct current into the capacitor **C414** when the target intensity L_{TRGT} increases, such that the time constant τ_{RC2} has a fast value $\tau_{RC2-FAST}$ that is less than the nominal value $\tau_{RC2-NOM}$. In addition, the capacitor **C414** is operable to discharge through the diode **D418** with the fast value $\tau_{RC2-FAST}$ when the target intensity L_{TRGT} decreases. Accordingly, the two-speed phase-to-DC converter circuit **400** is able to filter out changes in the duty cycle DC_{PC} of the phase-control voltage V_{PC} due to voltage fluctuations and noise of the AC mains line voltage V_{AC} while still providing a fast response as a result of changes in the target intensity L_{TRGT} .

Each of the diodes **D416**, **D418** stops conducting when the difference between the magnitudes of the target voltage V_{TRGT} and the filtered voltage V_F falls below approximately the forward voltage of the respective diode. After the diodes **D416**, **D418** stop conducting, the magnitude of the target intensity L_{TRGT} will slowly change to be equal to the magnitude of the filtered voltage V_F (according to the nominal time constant $\tau_{RC2-NOM}$) until the magnitudes of the voltages are equal. This results in a slow fading of the intensity of the lamp tube **122** at the end of a change in the target intensity L_{TRGT} , which provides a pleasant, soft effect on a human eye that is observing the change in the intensity of the lamp tube.

The non-inverting amplifier circuit **420** comprises an operational amplifier (“op amp”) **U421**, such as, for example, part number LM2902PWR, manufactured by National Semiconductor Corporation. The target voltage V_{TRGT} is coupled to the non-inverting input of the op amp **U421**, while an offset voltage V_{OFF} is coupled to the inverting input of the op amp through a resistor **R422** (e.g., having a resistance of approximately 160 k Ω). The offset voltage V_{OFF} is generated by a voltage divider that is coupled between the control supply voltage V_{CC} and circuit common, and includes two resistors **R424**, **R425**. For example, the resistors **R424**, **R425** may have resistances of approximately 33 k Ω and 5 k Ω , respectively, such that the offset voltage V_{OFF} has a magnitude of approximately 2 volts. The output of the op amp **U421** is coupled to the inverting input via the parallel combination of a resistor **R426** (e.g., having a resistance of approximately 150 k Ω) and a capacitor **C428** (e.g., having a capacitance of approximately 0.22 μ F). The magnitude of the amplified target voltage V_{A-TRGT} ranges from approximately 0.5 to 6.5 volts as the magnitude of the target voltage V_{TRGT} ranges from approximately 1 to 4 volts.

The non-linear amplifier circuit **440** receives the lamp current control signal V_{ILAMP} from the lamp current sense circuit **270**, which is shown in FIG. 6. The lamp current control signal V_{ILAMP} is generated across the parallel combination of a resistor **R272** (e.g., having a resistance of approximately 4 Ω) and a capacitor **C274** (e.g., having a capacitance of approximately 2.2 μ F). During the negative half-cycles of the lamp current I_{LAMP} , the lamp current is conducted through a diode **D276** and the parallel combination of the resistor **R272** and the capacitor **C274**. During the positive half-cycles of the lamp current I_{LAMP} , the lamp current is conducted through a diode **D278** and is not

conducted through the parallel combination of the resistor **R272** and the capacitor **C274**. Accordingly, the lamp current control signal V_{ILAMP} has a negative magnitude that is representative of the magnitude of the lamp current I_{LAMP} during the negative half-cycles of the lamp current. Since the resistor **R272** only conducts the lamp current I_{LAMP} every other half-cycle, the resistor **R272** dissipates half of the amount of power that would be dissipated if the resistor **R272** conducted the lamp current each half-cycle.

Referring back to FIG. 8, the non-linear amplifier circuit **440** comprises an op amp **U441** having a non-inverting input coupled to circuit common and an inverting input coupled to receive the lamp current control signal V_{ILAMP} through a resistor **R442** (e.g., having a resistance of approximately 1 k Ω). The output of the op amp **U441** is coupled to the inverting input through a resistor **R444** (e.g., having a resistance of approximately 68.1 k Ω). The non-linear amplifier circuit **440** further comprises a PNP bipolar junction transistor **Q445** and a resistor **R446** (e.g., having a resistance of approximately 27 k Ω). The series combination of the collector-emitter junction of the transistor **Q445** and the resistor **R446** is also coupled between the inverting input and the output of the op amp **U441**. A capacitor **C448** is coupled in parallel with the resistor **R446** and may have, for example, a capacitance of approximately 470 pF.

When the magnitude of the lamp current I_{LAMP} is less than a current threshold (e.g., approximately 100 mA), the magnitude of the amplified lamp current signal $V_{A-ILAMP}$ is less than approximately the rated emitter-base voltage of the transistor **Q445**. At this time, only the resistor **R444** is coupled between the inverting input and the output of the op amp **U441**, such that the non-linear amplifier circuit **440** is characterized by a first gain α_1 (e.g., approximately -68). However, when the magnitude of the lamp current I_{LAMP} is greater than the current threshold, the transistor **Q445** is rendered conductive, such that the resistor **R446** is coupled in parallel with the resistor **R444** between the inverting input and the output of the op amp **U441**. Accordingly, above the current threshold, the non-linear amplifier circuit **440** is characterized by a second gain α_2 that has a smaller magnitude than the first gain α_1 (e.g., approximately -25).

The error amplifier circuit **430** comprises an op amp **U431** having a non-inverting input coupled to receive the amplified lamp current signal $V_{A-ILAMP}$ and an inverting input coupled to receive the amplified target voltage V_{A-TRGT} through a resistor **R432** (e.g., having a resistance of approximately 30 k Ω). The error amplifier circuit **430** further comprises two capacitors **C434**, **C435** (e.g., each having a capacitance of approximately 4.7 nF) and a resistor **R436** (e.g., having a resistance of approximately 47 k Ω). The capacitor **C434** is coupled between the inverting input and the output of the op amp **U431**, while the series combination of the capacitor **C435** and the resistor **R436** is also coupled between the inverting input and the output of the op amp **U431**. The output of the op amp **U431** is coupled to circuit common through a resistor divider having two resistors **R438**, **R439** (e.g., having resistances of 18.7 k Ω and 6.8 k Ω , respectively), where the drive control signal V_{DR} is produced at the junction of the resistors **R438**, **R439**. The error amplifier circuit **430** operates to adjust the operating frequency f_{OP} of the inverter circuit **210** so as to minimize the error (i.e., the difference) between the amplified lamp current signal $V_{A-ILAMP}$ and the amplified target voltage V_{A-TRGT} . For example, the error amplifier circuit **430** may be characterized by a cutoff frequency of greater than or equal to approximately 10 kHz (i.e., the control circuit **230** has a bandwidth greater than or equal to approximately 10 kHz).

As previously mentioned, the lamp tube **122** of the screw-in compact fluorescent lamp **120** of the first embodiment of the present invention may be filled with the fill-gas mixture having a fill-gas pressure of approximately 2 Torr and a fill-gas ratio of approximately 85:15 argon to neon. FIG. **9** is an example V-I curve **500** (i.e., the plot of the magnitude of the lamp voltage V_{LAMP} across the lamp tube **122** with respect to the magnitude of the lamp current I_{LAMP} conducted through the lamp tube) according to the first embodiment of the present invention. FIG. **9** also shows an example V-I curve **550** of the prior art screw-in compact fluorescent lamp **20** that has a fill gas of 100% argon at a pressure of approximately 4 Torr.

By combining the lamp tube **122** having the fill-gas mixture having a fill-gas ratio of approximately 85:15 argon to neon at a pressure of approximately 2 Torr and the error amplifier **430** having a cutoff frequency of approximately 10 kHz, the V-I curve **500** of the screw-in compact fluorescent lamp **120** of the first embodiment of the present invention is much “flatter” than the V-I curve **550** of the prior art screw-in compact fluorescent lamp **20** as shown in FIG. **9**. In other words, the magnitude of the lamp voltage V_{LAMP} does not change as much with respect to the magnitude of the lamp current I_{LAMP} as in the prior art screw-in compact fluorescent lamp **20**. Therefore, the size of the components of the resonant tank circuit **220** may be smaller and the resonant tank circuit may operate more efficiently during normal operation. Since the filament windings **229A**, **229B** are magnetically coupled to the resonant inductor **L222**, the flatter V-I curve **500** of the screw-in compact fluorescent lamp **120** of the first embodiment of the present invention provides for more favorable magnitudes of the filament voltages across the dimming range of the lamp tube **122**, particularly, near the low-end intensity L_{LE} when the magnitude of the lamp voltage V_{LAMP} begins to decrease as the magnitude of the lamp current I_{LAMP} decreases.

FIGS. **10A** and **10B** show example waveforms of the DC bus voltage V_{BUS} and the lamp current I_{LAMP} , respectively, of the screw-in compact fluorescent lamp **120** of the first embodiment of the present invention. Since the cutoff frequency of the error amplifier circuit **430** (i.e., approximately 10 kHz) is much greater than the frequency of the voltage ripple of the bus voltage V_{BUS} (i.e., approximately 120 Hz), the control circuit **230** is able to adjust the operating frequency f_{OP} of the square-wave voltage V_{SQ} (and thus the lamp current I_{LAMP}) within a single half-cycle of the AC power source **15**. Therefore, the operating frequency f_{OP} changes in magnitude in response to the voltage ripple of the bus voltage V_{BUS} during each half-cycle and the lamp current I_{LAMP} has an envelope I_{ENV} that is relatively constant or flat (as shown in FIG. **10B**). It has been observed that this high speed operation of the error amplifier circuit **430** reduces flickering in the lamp tube **122**, particularly when the lamp tube is cold and/or has just been started up. In addition, since the operating frequency f_{OP} of the inverter circuit **210** changes during each half-cycle even when the screw-in compact fluorescent lamp **120** is maintaining the target intensity L_{TRGT} of the lamp tube **122** constant, the compact fluorescent lamp does not generate EMI noise at specific frequencies, but spreads the frequency of the EMI noise out over a range, such that the peak magnitude of the noise is decreased.

Referring back to FIG. **8**, the control circuit **230** further comprises a preheat adjustment circuit **450** that modifies the operation of the phase-to-DC converter circuit **400** while the load regulation circuit **130** is preheating the filaments **228A**, **228B** of the lamp tube **122** (i.e., during the preheat time

period T_{PH}). The preheat adjustment circuit **450** comprises an op amp **U452** having a non-inverting input coupled to receive the voltage V_{RPH} across the preheat-frequency-set resistor R_{PH} of the inverter control circuit **216**, and an inverting input coupled to receive the voltage V_{CPH} across the preheat-time-set capacitor C_{PH} . The output of the op amp **U452** is coupled to the capacitor **C410** of the phase-to-DC converter circuit **400** through a resistor **R454** (e.g., having a resistance of approximately 464 k Ω). As previously mentioned, while the inverter control IC **U300** is preheating the filaments **228A**, **228B** of the lamp tube **122**, the voltage V_{RPH} across the preheat-frequency-set resistor R_{PH} is maintained constant, while the voltage V_{CPH} across the preheat-time-set capacitor C_{PH} increases in magnitude with respect to time from approximately zero volts. During the preheat time period T_{PH} , the op amp **U452** injects current into the capacitor **C410** of the phase-to-DC converter circuit **400**, such that the magnitude of the target voltage V_{TRGT} increases. Therefore, if the lamp tube **122** is being turned on to an intensity near the low-end intensity L_{LE} , the magnitude of the lamp current I_{LAMP} will be large enough at the end of the preheat time period T_{PH} to ensure that the arc current is established in the lamp tube when the lamp tube is struck. After the arc current has been properly established in the lamp tube **122**, the op amp **U452** stops injecting current into the capacitor **C410** of the phase-to-DC converter circuit **400** and the intensity of the lamp tube is controlled in response to the target intensity L_{TRGT} determined from the duty-cycle DC_{PC} of the phase-control voltage V_{PC} .

FIG. **11** is a simplified schematic diagram of a control circuit **630** of the dimmable screw-in compact fluorescent lamp **120** according to a second embodiment of the present invention. The control circuit **630** comprises a microprocessor **U600** that implements the functions of the control circuit **330** of the first embodiment that were executed by the two-speed phase-to-DC converter circuit **400**, the non-inverting amplifier circuit **420**, and the error amplifier circuit **430**. The control circuit **630** comprises a resistive divider including two resistors **R601**, **R602** for scaling the phase-control input control signal V_{PC-IN} to generate a scaled phase-control input control signal V_{PC-S} . The microprocessor **U600** receives the scaled phase-control input control signal V_{PC-S} and the amplified target voltage V_{A-TRGT} from the non-linear amplifier circuit **440**. The microprocessor **U600** generates a drive control signal V_{DR} to control the intensity level of the lamp tube **122** to a target intensity level L_{TRGT} . Alternatively, the microprocessor **U600** may be implemented as a microcontroller, a programmable logic device (PLD), an application specific integrated circuit (ASIC), a field-programmable gate array (FPGA), or any suitable controller or processing device.

FIG. **12** is a simplified flowchart of a control procedure **700** executed periodically by the microprocessor **U600**, e.g., once every half-cycle of the AC power source **15**. The microprocessor **U600** first measures the duty cycle V_{PC} of the scaled phase-control input control signal V_{PC-S} at step **710**, and then determines a requested intensity level L_{PRES} from the duty cycle V_{PC} of the scaled phase-control input control signal V_{PC-S} at step **712**. The microprocessor **U600** then determines a phase-control input change value Δ_{PC} , i.e., the absolute value of the difference between the new requested intensity level L_{PRES} and the present target intensity level L_{TRGT} from the last sample, at step **714**.

The microprocessor **U600** uses a digital low-pass filter (LPF) to process the values of the requested intensity level L_{PRES} . If the phase-control input change value Δ_{PC} is less than a phase-control input change threshold Δ_{TH} at step **716**,

the microprocessor U600 adjusts the pole of the digital low-pass filter such that the passband frequency f_p of the filter is a first predetermined frequency (e.g., approximately 0.5 Hz) at step 718. If the phase-control input change value Δ_{PC} is not less than the phase-control input change threshold Δ_{TH} at step 716, the microprocessor U600 adjusts the pole of the digital low-pass filter so that the passband frequency f_p of the filter is a second predetermined frequency (e.g., approximately 5 Hz) at step 720. Accordingly, when the duty-cycle DC_{PC} of the phase-control signal V_{PC} is remaining relatively constant (i.e., when the phase-control input change value Δ_{PC} is less than the phase-control input change threshold Δ_{TH}), the requested intensity level L_{PRES} is more heavily filtered, and the target intensity level L_{TRGT} is adjusted with a slow time constant $\tau_{DLPF-SLOW}$. When the duty cycle DC_{PC} is changing rapidly, the requested intensity level L_{PRES} is filtered less, and the target intensity level L_{TRGT} is adjusted with a fast time constant $\tau_{DLPF-FAST}$. For example, the phase-control input change threshold Δ_{TH} may be equal to the target intensity level L_{TRGT} divided by ten, such that the microprocessor U600 adjusts the target intensity level L_{TRGT} using the fast time constant $\tau_{DLPF-FAST}$ when there is greater than or equal to a 10% change in the target intensity level L_{TRGT} .

After adjusting the passband frequency f_p of the digital low-pass filter at steps 718, 720, the microprocessor U600 processes the requested intensity level L_{PRES} through the digital low-pass filter at step 722 to determine the target intensity level L_{TRGT} to which the microprocessor will now control the intensity level of the lamp tube 122. The microprocessor U600 then samples the amplified lamp current signal $V_{A-ILAMP}$ at step 724, and determines an actual intensity level L_{ACTUAL} from the sampled values of the amplified lamp current signal $V_{A-ILAMP}$ at step 726. The microprocessor U600 then determines an error e_L between the target intensity level L_{TRGT} and the actual intensity level L_{ACTUAL} at step 728 and controls the drive control signal V_{DR} in response to the error e_L to adjust the lighting intensity of the lamp tube 122 towards the target intensity level L_{TRGT} at step 730 before the control procedure 700 exits.

While the present invention has been described with reference to the screw-in compact fluorescent lamp 120, the concepts of the present invention could be used in lighting control systems having a ballast circuit that is separate from the controlled fluorescent lamps, for example, mounted to a junction box next to a lighting fixture in which the lamps are installed. In addition, the circuits and methods of determining the target intensity level L_{TRGT} in response to the duty cycle DC_{PC} of the phase-control signal V_{PC} could be used in another type of load control device, such as, for example, a light-emitting diode (LED) driver for driving an LED light source (i.e., an LED light engine); a screw-in luminaire including a dimmer circuit and an incandescent or halogen lamp; a dimming circuit for controlling the intensity of an incandescent lamp, a halogen lamp, an electronic low-voltage lighting load, a magnetic low-voltage lighting load, or another type of lighting load; an electronic switch, controllable circuit breaker, or other switching device for turning electrical loads or appliances on and off; a plug-in load control device, controllable electrical receptacle, or controllable power strip for controlling one or more plug-in electrical loads; and a motor control unit for controlling a motor load, such as a ceiling fan or an exhaust fan.

Although the present invention has been described in relation to particular embodiments thereof, many other variations and modifications and other uses will become apparent to those skilled in the art. It is preferred, therefore,

that the present invention be limited not by the specific disclosure herein, but only by the appended claims.

What is claimed is:

1. A lamp configured to receive a phase-control voltage characterized by a duty cycle, the lamp comprising:
 - a lighting load;
 - a load regulation circuit configured to receive a drive control signal and to control an intensity level of the lighting load in response to the drive control signal;
 - a control circuit configured to receive a signal representative of the intensity level of the lighting load, and to generate the drive control signal to cause the load regulation circuit to adjust the intensity level of the lighting load towards a target level;
 - an enclosure for housing the load regulation circuit; and
 - a screw-in base adapted to be coupled to a standard Edison socket;
 wherein the control circuit is configured to determine the target level for the lighting load in response to the duty cycle of the phase-control voltage, the control circuit configured to adjust the target level for the lighting load using a first time constant in response to changes in the duty cycle of the phase-control voltage that are less than a threshold amount, and to adjust the target level for the lighting load using a second time constant in response to changes in the duty cycle of the phase-control voltage that are greater than the threshold amount, where the second time constant is less than the first time constant.
2. The lamp of claim 1, wherein the control circuit comprises a processing device configured to use a digital low-pass filter to determine the target level for the lighting load in response to the phase-control voltage.
3. The lamp of claim 2, wherein the processing device is configured to receive a scaled version of the phase-control voltage, and measure a duty cycle of the scaled version of the phase-control voltage, the processing device further configured to determine a requested level in response to the duty cycle of the scaled version of the phase-control voltage, and process the requested level using the digital low-pass filter to determine the target level.
4. The lamp of claim 3, wherein the processing device is configured to determine a change in the duty cycle of the scaled version of the phase-control voltage by calculating a difference between the requested level and the target level.
5. The lamp of claim 4, wherein the processing device is configured to adjust a pole of the digital low-pass filter to set a passband frequency of the digital low-pass filter to a first frequency when the change in the duty cycle of the scaled version of the phase-control voltage is less than a change threshold.
6. The lamp of claim 5, wherein the processing device is configured to adjust the pole of the digital low-pass filter to set a passband frequency of the digital low-pass filter to a second frequency when the change in the duty cycle of the scaled version of the phase-control voltage is greater than the change threshold.
7. The lamp of claim 6, wherein the change threshold is dependent upon the target level for the lighting load.
8. The lamp of claim 2, wherein the processing device is configured to sample the signal representative of the intensity level of the lighting load and determine an actual level of the lighting load from the sampled signal representative of the intensity level of the lighting load, the processing device configured to calculate an error between the actual level and the target level.

9. The lamp of claim 8, wherein the processing device is configured to control the drive control signal in response to the error to adjust the intensity level of the lighting load towards the target level.

10. The lamp of claim 2, wherein the processing device 5 comprises a microprocessor.

11. The lamp of claim 1, wherein the control circuit is configured to convert the phase-control voltage into a target signal that is representative of the target level of the lighting load, the control circuit configured to produce the drive 10 control signal by comparing a magnitude of the target signal and a magnitude of the signal representative of the intensity level of the lighting load.

12. The lamp of claim 11, wherein the control circuit comprises a first filter circuit configured to generate a 15 filtered voltage in response to the phase-control voltage, the control circuit configured to adjust the magnitude of the target signal in response to changes in the duty cycle of the phase-control voltage that cause a magnitude of the filtered voltage to change by an amount in excess of a threshold 20 voltage.

13. The lamp of claim 12, wherein the control circuit comprises a second filter circuit configured to filter the filtered voltage to generate the target signal, the second filter circuit configured to have the first time constant when the 25 filtered voltage increases or decreases by an amount less than the threshold voltage, and have the second time constant when the filtered voltage increases or decreases by an amount greater than the threshold voltage.

14. The lamp of claim 1, wherein the lighting load 30 comprises a LED light source and the load regulation circuit comprises an LED driver circuit.

* * * * *