



US010806570B2

(12) **United States Patent**
Tuval et al.

(10) **Patent No.:** **US 10,806,570 B2**
(45) **Date of Patent:** **Oct. 20, 2020**

(54) **PROSTHETIC HEART VALVE HAVING IDENTIFIERS FOR AIDING IN RADIOGRAPHIC POSITIONING**

2230/005 (2013.01); A61F 2230/008 (2013.01); A61F 2230/0054 (2013.01); A61F 2250/0098 (2013.01)

(71) Applicant: **Medtronic, Inc.**, Minneapolis, MN (US)

(58) **Field of Classification Search**
CPC A61F 2/2409; A61F 2/2418; A61F 2/2236; A61F 2250/0096-0098
See application file for complete search history.

(72) Inventors: **Yossi Tuval**, Netanya (IL); **Raphael Benary**, Tel Aviv (IL)

(56) **References Cited**

(73) Assignee: **Medtronic, Inc.**, Minneapolis, MN (US)

U.S. PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 183 days.

3,334,629 A 8/1967 Cohn
3,409,013 A 11/1968 Berry
3,540,431 A 11/1970 Mobin-Uddin
3,587,115 A 6/1971 Shiley
3,628,535 A 12/1971 Ostrowsky et al.
3,642,004 A 2/1972 Osthagen et al.
3,657,744 A 4/1972 Ersek
3,671,979 A 6/1972 Mouloupoulos

(21) Appl. No.: **15/939,497**

(22) Filed: **Mar. 29, 2018**

(Continued)

(65) **Prior Publication Data**

FOREIGN PATENT DOCUMENTS

US 2018/0214265 A1 Aug. 2, 2018

CN 2007-100074433 10/2007
DE 3640745 6/1987

Related U.S. Application Data

(Continued)

(63) Continuation of application No. 14/641,545, filed on Mar. 9, 2015, now Pat. No. 9,943,407, which is a continuation of application No. 12/559,945, filed on Sep. 15, 2009, now Pat. No. 8,998,981.

(60) Provisional application No. 61/192,201, filed on Sep. 15, 2008.

OTHER PUBLICATIONS

Andersen, H.R. et al, "Transluminal implantation of artificial heart valves. Description of a new expandable aortic valve and initial results with implantation by catheter technique in closed chest pigs." Euro. Heart J. (1992) 13:704-708.

(Continued)


(51) **Int. Cl.**
A61F 2/24 (2006.01)
A61B 34/20 (2016.01)
A61B 90/00 (2016.01)

Primary Examiner — William H Matthews
(74) *Attorney, Agent, or Firm* — Dicke, Billig & Czaja, PLLC

(52) **U.S. Cl.**
CPC *A61F 2/2418* (2013.01); *A61B 34/20* (2016.02); *A61F 2/2436* (2013.01); *A61B 2090/376* (2016.02); *A61F 2220/0016* (2013.01); *A61F 2220/0075* (2013.01); *A61F*

(57) **ABSTRACT**
A prosthetic heart valve having identifiers for aiding in radiographic positioning is described.

20 Claims, 8 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

3,714,671 A	2/1973	Edwards et al.	5,370,685 A	12/1994	Stevens
3,755,823 A	9/1973	Hancock	5,389,106 A	2/1995	Tower
3,795,246 A	3/1974	Sturgeon	5,397,351 A	3/1995	Pavcnik et al.
3,839,741 A	10/1974	Haller	5,411,552 A	5/1995	Andersen et al.
3,868,956 A	3/1975	Alfidi et al.	5,415,633 A	5/1995	Lazarus et al.
3,874,388 A	4/1975	King et al.	5,431,676 A	7/1995	Dubrul et al.
4,035,849 A	7/1977	Angell et al.	5,443,446 A	8/1995	Shturman
4,056,854 A	11/1977	Boretos et al.	5,449,384 A	9/1995	Johnson
4,106,129 A	8/1978	Carpentier et al.	5,480,424 A	1/1996	Cox
4,222,126 A	9/1980	Boretos et al.	5,489,294 A	2/1996	McVenes et al.
4,233,690 A	11/1980	Akins	5,489,297 A	2/1996	Duran
4,265,694 A	5/1981	Boretos	5,496,346 A	3/1996	Horzewski et al.
4,291,420 A	9/1981	Reul	5,500,014 A	3/1996	Quijano et al.
4,297,749 A	11/1981	Davis et al.	5,507,767 A	4/1996	Maeda et al.
4,339,831 A	7/1982	Johnson	5,545,209 A	8/1996	Roberts et al.
4,343,048 A	8/1982	Ross et al.	5,545,211 A	8/1996	An et al.
4,345,340 A	8/1982	Rosen	5,545,214 A	8/1996	Stevens
4,425,908 A	1/1984	Simon	5,554,185 A	9/1996	Block et al.
4,470,157 A	9/1984	Love	5,575,818 A	11/1996	Pinchuk
4,501,030 A	2/1985	Lane	5,580,922 A	12/1996	Park et al.
4,574,803 A	3/1986	Storz	5,591,195 A	1/1997	Taheri et al.
4,580,568 A	4/1986	Gianturco	5,609,626 A	3/1997	Quijano et al.
4,592,340 A	6/1986	Boyles	5,645,559 A	7/1997	Hachtman et al.
4,610,688 A	9/1986	Silvestrini et al.	5,665,115 A	9/1997	Cragg
4,612,011 A	9/1986	Kautzky	5,667,523 A	9/1997	Bynon et al.
4,647,283 A	3/1987	Carpentier et al.	5,674,277 A	10/1997	Freitag
4,648,881 A	3/1987	Carpentier et al.	5,695,498 A	12/1997	Tower
4,655,771 A	4/1987	Wallsten	5,702,368 A	12/1997	Stevens et al.
4,662,885 A	5/1987	DiPisa, Jr.	5,713,953 A	2/1998	Vallana et al.
4,665,906 A	5/1987	Jervis	5,716,417 A	2/1998	Girard et al.
4,681,908 A	7/1987	Broderick et al.	5,746,709 A	5/1998	Rom et al.
4,710,192 A	12/1987	Liotta et al.	5,749,890 A	5/1998	Shaknovich
4,733,665 A	3/1988	Palmaz	5,766,151 A	6/1998	Valley et al.
4,777,951 A	10/1988	Cribier et al.	5,782,809 A	7/1998	Umeno et al.
4,787,899 A	11/1988	Lazarus	5,800,456 A	9/1998	Maeda et al.
4,796,629 A	1/1989	Grayzel	5,800,508 A	9/1998	Goicoechea et al.
4,797,901 A	1/1989	Baykut	5,817,126 A	10/1998	Imran
4,819,751 A	4/1989	Shimada et al.	5,824,041 A	10/1998	Lenker
4,834,755 A	5/1989	Silvestrini et al.	5,824,043 A	10/1998	Cottone, Jr.
4,856,516 A	8/1989	Hillstead	5,824,053 A	10/1998	Khosravi et al.
4,872,874 A	10/1989	Taheri	5,824,056 A	10/1998	Rosenberg
4,878,495 A	11/1989	Grayzel	5,824,061 A	10/1998	Quijano et al.
4,878,906 A	11/1989	Lindemann et al.	5,824,064 A	10/1998	Taheri
4,883,458 A	11/1989	Shiber	5,840,081 A	11/1998	Andersen et al.
4,909,252 A	3/1990	Goldberger	5,843,158 A	12/1998	Lenker et al.
4,917,102 A	4/1990	Miller et al.	5,851,232 A	12/1998	Lois
4,922,905 A	5/1990	Strecker	5,855,597 A	1/1999	Jayaraman
4,954,126 A	9/1990	Wallsten	5,855,601 A	1/1999	Bessler et al.
4,966,604 A	10/1990	Reiss	5,860,996 A	1/1999	Tower
4,979,939 A	12/1990	Shiber	5,861,028 A	1/1999	Angell
4,986,830 A	1/1991	Owens et al.	5,868,783 A	2/1999	Tower
4,994,077 A	2/1991	Dobben	5,876,448 A	3/1999	Thompson et al.
5,002,559 A	3/1991	Tower	5,888,201 A	3/1999	Stinson et al.
5,007,896 A	4/1991	Shiber	5,891,191 A	4/1999	Stinson
5,026,366 A	6/1991	Leckrone	5,906,619 A	5/1999	Olson et al.
5,032,128 A	7/1991	Alonso	5,907,893 A	6/1999	Zadno-Azizi et al.
5,037,434 A	8/1991	Lane	5,908,451 A	6/1999	Yeo
5,047,041 A	9/1991	Samuels	5,913,842 A	6/1999	Boyd et al.
5,059,177 A	10/1991	Towne et al.	5,925,063 A	7/1999	Khosravi
5,061,273 A	10/1991	Yock	5,944,738 A	8/1999	Amplatz et al.
5,085,635 A	2/1992	Cragg	5,957,949 A	9/1999	Leonhardt et al.
5,089,015 A	2/1992	Ross	5,968,068 A	10/1999	Dehdashtian et al.
5,152,771 A	10/1992	Sabbaghian et al.	5,984,957 A	11/1999	Laptewicz, Jr. et al.
5,161,547 A	11/1992	Tower	5,997,573 A	12/1999	Quijano et al.
5,163,953 A	11/1992	Vince	6,022,370 A	2/2000	Tower
5,167,628 A	12/1992	Boyles	6,022,374 A	2/2000	Imran
5,217,483 A	7/1993	Tower	6,027,525 A	2/2000	Suh et al.
5,232,445 A	8/1993	Bonzel	6,029,671 A	2/2000	Stevens et al.
5,272,909 A	12/1993	Nguyen et al.	6,042,589 A	3/2000	Marianne
5,295,958 A	3/1994	Shturman	6,042,598 A	3/2000	Tsugita et al.
5,327,774 A	7/1994	Nguyen et al.	6,042,607 A	3/2000	Williamson, IV
5,332,402 A	7/1994	Teitelbaum et al.	6,051,104 A	4/2000	Jang
5,344,442 A	9/1994	Deac	6,059,809 A	5/2000	Amor et al.
5,350,398 A	9/1994	Pavcnik et al.	6,110,201 A	8/2000	Quijano et al.
5,354,330 A	10/1994	Hanson et al.	6,146,366 A	11/2000	Schachar
			6,159,239 A	12/2000	Greenhalgh
			6,162,208 A	12/2000	Hipps
			6,162,245 A	12/2000	Jayaraman
			6,168,614 B1	1/2001	Andersen et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,171,335 B1	1/2001	Wheatley et al.	6,733,525 B2	5/2004	Yang et al.
6,200,336 B1	3/2001	Pavcnik et al.	6,736,846 B2	5/2004	Cox
6,203,550 B1	3/2001	Olson	6,752,828 B2	6/2004	Thornton
6,210,408 B1	4/2001	Chandrasekaran et al.	6,758,855 B2	7/2004	Fulton, III et al.
6,218,662 B1	4/2001	Tchakarov et al.	6,769,434 B2	8/2004	Liddicoat et al.
6,221,006 B1	4/2001	Dubrul et al.	6,786,925 B1	9/2004	Schoon
6,221,091 B1	4/2001	Khosravi	6,790,229 B1	9/2004	Berrekouw
6,241,757 B1	6/2001	An et al.	6,792,979 B2	9/2004	Konya et al.
6,245,102 B1	6/2001	Jayaraman	6,797,002 B2	9/2004	Spence
6,248,116 B1	6/2001	Chevilon	6,821,297 B2	11/2004	Snyders
6,258,114 B1	7/2001	Konya et al.	6,830,575 B2	12/2004	Stenzel et al.
6,258,115 B1	7/2001	Dubrul	6,830,584 B1	12/2004	Seguin
6,258,120 B1	7/2001	McKenzie et al.	6,830,585 B1	12/2004	Artof
6,277,555 B1	8/2001	Duran et al.	6,846,325 B2	1/2005	Liddicoat
6,296,662 B1	10/2001	Caffey	6,866,650 B2	3/2005	Stevens
6,299,637 B1	10/2001	Shaolia et al.	6,872,223 B2	3/2005	Roberts
6,302,906 B1	10/2001	Goicoechea et al.	6,875,231 B2	4/2005	Anduiza et al.
6,309,382 B1	10/2001	Garrison et al.	6,883,522 B2	4/2005	Spence et al.
6,309,417 B1	10/2001	Spence et al.	6,887,266 B2	5/2005	Williams et al.
6,312,465 B1	11/2001	Griffin et al.	6,890,330 B2	5/2005	Streeter et al.
6,338,735 B1	1/2002	Stevens	6,893,460 B2	5/2005	Spenser et al.
6,348,063 B1	2/2002	Yassour et al.	6,896,690 B1	5/2005	Lambrecht et al.
6,350,277 B1	2/2002	Kocur	6,908,481 B2	6/2005	Cribier
6,352,708 B1	3/2002	Duran et al.	6,913,600 B2	7/2005	Valley et al.
6,361,557 B1	3/2002	Gittings et al.	6,929,653 B2	8/2005	Streeter
6,371,970 B1	4/2002	Khosravi et al.	6,936,066 B2	8/2005	Palmaz et al.
6,371,983 B1	4/2002	Lane	6,939,365 B1	9/2005	Fogarty et al.
6,379,383 B1	4/2002	Palmaz et al.	6,951,571 B1	10/2005	Srivastava
6,380,457 B1	4/2002	Yurek et al.	6,974,474 B2	12/2005	Pavcnik et al.
6,398,807 B1	6/2002	Chouinard et al.	6,974,476 B2	12/2005	McGuckin et al.
6,409,750 B1	6/2002	Hyodoh et al.	6,986,742 B2	1/2006	Hart et al.
6,425,916 B1	7/2002	Garrison et al.	6,989,027 B2	1/2006	Allen et al.
6,440,164 B1	8/2002	DiMatteo et al.	6,989,028 B2	1/2006	Lashinski et al.
6,454,799 B1	9/2002	Schreck	6,991,649 B2	1/2006	Sievers
6,458,153 B1	10/2002	Bailey et al.	7,018,401 B1	3/2006	Hyodoh et al.
6,461,382 B1	10/2002	Cao	7,018,406 B2	3/2006	Seguin et al.
6,468,303 B1	10/2002	Amplatz et al.	7,018,408 B2	3/2006	Bailey et al.
6,475,239 B1	11/2002	Campbell et al.	7,041,128 B2	5/2006	McGuckin, Jr. et al.
6,482,228 B1	11/2002	Norred	7,044,966 B2	5/2006	Svanidze et al.
6,488,704 B1	12/2002	Connelly et al.	7,048,014 B2	5/2006	Hyodoh et al.
6,494,909 B2	12/2002	Greenhalgh	7,097,659 B2	8/2006	Woolfson et al.
6,503,272 B2	1/2003	Duerig et al.	7,101,396 B2	9/2006	Artof et al.
6,508,833 B2	1/2003	Pavcnik et al.	7,105,016 B2	9/2006	Shui et al.
6,527,800 B1	3/2003	McGuckin, Jr. et al.	7,115,141 B2	10/2006	Menz et al.
6,530,949 B2	3/2003	Konya et al.	7,128,759 B2	10/2006	Osborne et al.
6,530,952 B2	3/2003	Vesely	7,137,184 B2	11/2006	Schreck
6,562,031 B2	5/2003	Chandrasekaran et al.	7,147,663 B1	12/2006	Berg et al.
6,562,058 B2	5/2003	Seguin et al.	7,153,324 B2	12/2006	Case et al.
6,569,196 B1	5/2003	Vesely	7,160,319 B2	1/2007	Chouinard et al.
6,585,758 B1	7/2003	Chouinard et al.	7,175,656 B2	2/2007	Khairkahan
6,592,546 B1	7/2003	Barbut et al.	7,186,265 B2	3/2007	Sharkawy et al.
6,605,112 B1	8/2003	Moll et al.	7,195,641 B2	3/2007	Palmaz et al.
6,613,077 B2	9/2003	Gilligan et al.	7,198,646 B2	4/2007	Figulla et al.
6,622,604 B1	9/2003	Chouinard et al.	7,201,761 B2	4/2007	Woolfson et al.
6,635,068 B1	10/2003	Dubrul et al.	7,201,772 B2	4/2007	Schwammenthal et al.
6,652,571 B1	11/2003	White et al.	7,252,682 B2	8/2007	Seguin
6,652,578 B2	11/2003	Bailey et al.	7,300,457 B2	11/2007	Palmaz
6,656,213 B2	12/2003	Solem	7,300,463 B2	11/2007	Liddicoat
6,663,663 B2	12/2003	Kim et al.	7,316,706 B2	1/2008	Bloom et al.
6,669,724 B2	12/2003	Park et al.	7,329,278 B2	2/2008	Seguin
6,673,089 B1	1/2004	Yassour et al.	7,335,218 B2	2/2008	Wilson et al.
6,673,109 B2	1/2004	Cox	7,338,520 B2	3/2008	Bailey et al.
6,676,698 B2	1/2004	McGuckin, Jr. et al.	7,374,571 B2	5/2008	Pease et al.
6,682,558 B2	1/2004	Tu et al.	7,377,938 B2	5/2008	Sarac et al.
6,682,559 B2	1/2004	Myers et al.	7,381,218 B2	6/2008	Shreck
6,685,739 B2	2/2004	DiMatteo et al.	7,384,411 B1	6/2008	Condado
6,689,144 B2	2/2004	Gerberding	7,429,269 B2	9/2008	Schwammenthal et al.
6,689,164 B1	2/2004	Seguin	7,442,204 B2	10/2008	Schwammenthal et al.
6,692,512 B2	2/2004	Jang	7,462,191 B2	12/2008	Spenser et al.
6,692,513 B2	2/2004	Streeter et al.	7,470,284 B2	12/2008	Lambrecht et al.
6,695,878 B2	2/2004	McGuckin, Jr. et al.	7,481,838 B2	1/2009	Carpentier et al.
6,702,851 B1	3/2004	Chinn et al.	7,544,206 B2	6/2009	Cohn et al.
6,719,789 B2	4/2004	Cox	7,547,322 B2	6/2009	Sarac et al.
6,730,118 B2	5/2004	Spenser et al.	7,556,646 B2	7/2009	Yang et al.
6,730,377 B2	5/2004	Wang	7,806,919 B2	10/2010	Bloom et al.
			8,052,750 B2	11/2011	Tuval et al.
			8,784,478 B2	7/2014	Tuval et al.
			8,998,981 B2	4/2015	Tuval et al.
			2001/0002445 A1	3/2001	Vesely

(56)

References Cited

U.S. PATENT DOCUMENTS

2001/0001314 A1	5/2001	Davison et al.	2004/0098112 A1	5/2004	DiMatteo et al.
2001/0007956 A1	7/2001	Letac et al.	2004/0106976 A1	6/2004	Bailey et al.
2001/0010017 A1	7/2001	Letac et al.	2004/0106990 A1	6/2004	Spence et al.
2001/0011189 A1	8/2001	Drasler et al.	2004/0111096 A1	6/2004	Tu et al.
2001/0021872 A1	9/2001	Bailey et al.	2004/0116951 A1	6/2004	Rosengart
2001/0025196 A1	9/2001	Chinn et al.	2004/0117004 A1	6/2004	Osborne et al.
2001/0032013 A1	10/2001	Marton	2004/0122468 A1	6/2004	Yodfat et al.
2001/0039450 A1	11/2001	Pavcnik et al.	2004/0122514 A1	6/2004	Fogarty et al.
2001/0041928 A1	11/2001	Pavcnik et al.	2004/0122516 A1	6/2004	Fogarty
2001/0044647 A1	11/2001	Pinchuk et al.	2004/0127979 A1	7/2004	Wilson
2002/0010508 A1	1/2002	Chobotov	2004/0138742 A1	7/2004	Myers et al.
2002/0029014 A1	3/2002	Jayaraman	2004/0138743 A1	7/2004	Myers et al.
2002/0032480 A1	3/2002	Spence et al.	2004/0153146 A1	8/2004	Lashinski et al.
2002/0032481 A1	3/2002	Gabbay	2004/0167573 A1	8/2004	Williamson
2002/0035396 A1	3/2002	Heath	2004/0167620 A1	8/2004	Ortiz
2002/0042650 A1	4/2002	Vardi et al.	2004/0186563 A1	9/2004	Iobbi
2002/0052651 A1	5/2002	Myers et al.	2004/0193261 A1	9/2004	Berrekouw
2002/0058995 A1	5/2002	Stevens	2004/0210240 A1	10/2004	Saint
2002/0072789 A1	6/2002	Hackett et al.	2004/0210304 A1	10/2004	Seguin et al.
2002/0095209 A1	7/2002	Zadno-Azizi et al.	2004/0210307 A1	10/2004	Khairkahan
2002/0099439 A1	7/2002	Schwartz et al.	2004/0215333 A1	10/2004	Duran
2002/0103533 A1	8/2002	Langberg et al.	2004/0215339 A1	10/2004	Drasler et al.
2002/0107565 A1	8/2002	Greenhalgh	2004/0225353 A1	11/2004	McGuckin, Jr.
2002/0111674 A1	8/2002	Chouinard et al.	2004/0225354 A1	11/2004	Allen
2002/0123802 A1	9/2002	Snyders	2004/0236411 A1	11/2004	Sarac et al.
2002/0133183 A1	9/2002	Lentz et al.	2004/0254636 A1	12/2004	Flagle et al.
2002/0138138 A1	9/2002	Yang	2004/0260389 A1	12/2004	Case et al.
2002/0151970 A1	10/2002	Garrison et al.	2004/0260394 A1	12/2004	Douk et al.
2002/0156521 A1	10/2002	Ryan et al.	2004/0267357 A1	12/2004	Allen et al.
2002/0161392 A1	10/2002	Dubrul	2005/0010246 A1	1/2005	Streeter
2002/0161394 A1	10/2002	Macoviak et al.	2005/0010285 A1	1/2005	Lambrecht et al.
2002/0193871 A1	12/2002	Beyersdorf et al.	2005/0010287 A1	1/2005	Macoviak
2003/0014104 A1	1/2003	Cribier	2005/0015112 A1	1/2005	Cohn et al.
2003/0023300 A1	1/2003	Bailey et al.	2005/0027348 A1	2/2005	Case et al.
2003/0023303 A1	1/2003	Palmaz et al.	2005/0033398 A1	2/2005	Seguin
2003/0028247 A1	2/2003	Cali	2005/0043790 A1	2/2005	Seguin
2003/0036791 A1	2/2003	Bonhoeffer et al.	2005/0049692 A1	3/2005	Numamoto
2003/0040771 A1	2/2003	Hyodoh et al.	2005/0049696 A1	3/2005	Siess
2003/0040772 A1	2/2003	Hyodoh et al.	2005/0055088 A1	3/2005	Liddicoat et al.
2003/0040792 A1	2/2003	Gabbay	2005/0060029 A1	3/2005	Le
2003/0050694 A1	3/2003	Yang et al.	2005/0060030 A1	3/2005	Lashinski et al.
2003/0055495 A1	3/2003	Pease et al.	2005/0075584 A1	4/2005	Cali
2003/0065386 A1	4/2003	Weadock	2005/0075712 A1	4/2005	Biancucci
2003/0069492 A1	4/2003	Abrams et al.	2005/0075717 A1	4/2005	Nguyen
2003/0109924 A1	6/2003	Cribier	2005/0075719 A1	4/2005	Bergheim
2003/0125795 A1	7/2003	Pavcnik et al.	2005/0075720 A1	4/2005	Nguyen et al.
2003/0130726 A1	7/2003	Thorpe et al.	2005/0075724 A1	4/2005	Svanidze
2003/0130729 A1	7/2003	Paniagua et al.	2005/0075727 A1	4/2005	Wheatley
2003/0139804 A1	7/2003	Hankh et al.	2005/0075730 A1	4/2005	Myers
2003/0149475 A1	8/2003	Hyodoh et al.	2005/0075731 A1	4/2005	Artof
2003/0149476 A1	8/2003	Damm et al.	2005/0085841 A1	4/2005	Eversull et al.
2003/0149478 A1	8/2003	Figulla et al.	2005/0085842 A1	4/2005	Eversull et al.
2003/0153974 A1	8/2003	Spenser et al.	2005/0085843 A1	4/2005	Opolski et al.
2003/0181850 A1	9/2003	Diamond et al.	2005/0085890 A1	4/2005	Rasmussen et al.
2003/0191519 A1	10/2003	Lombardi et al.	2005/0085900 A1	4/2005	Case et al.
2003/0199913 A1	10/2003	Dubrul et al.	2005/0096568 A1	5/2005	Kato
2003/0199963 A1	10/2003	Tower et al.	2005/0096692 A1	5/2005	Linder et al.
2003/0199971 A1	10/2003	Tower et al.	2005/0096724 A1	5/2005	Stenzel et al.
2003/0212410 A1	11/2003	Stenzel et al.	2005/0096734 A1	5/2005	Majercak et al.
2003/0212454 A1	11/2003	Scott et al.	2005/0096735 A1	5/2005	Hojeibane et al.
2003/0225445 A1	12/2003	Derus et al.	2005/0096736 A1	5/2005	Osse et al.
2004/0019374 A1	1/2004	Hojeibane et al.	2005/0096738 A1	5/2005	Cali et al.
2004/0034411 A1	2/2004	Quijano et al.	2005/0107871 A1	5/2005	Realyvasquez et al.
2004/0039436 A1	2/2004	Spenser et al.	2005/0113910 A1	5/2005	Paniagua
2004/0049224 A1	3/2004	Buehlmann et al.	2005/0119688 A1	6/2005	Berheim
2004/0049262 A1	3/2004	Obermiller et al.	2005/0131438 A1	6/2005	Cohn
2004/0049266 A1	3/2004	Anduiza et al.	2005/0137686 A1	6/2005	Salahieh
2004/0082904 A1	4/2004	Houde et al.	2005/0137688 A1	6/2005	Salahieh et al.
2004/0088045 A1	5/2004	Cox	2005/0137690 A1	6/2005	Salahieh et al.
2004/0092858 A1	5/2004	Wilson et al.	2005/0137691 A1	6/2005	Salahieh et al.
2004/0092989 A1	5/2004	Wilson et al.	2005/0137692 A1	6/2005	Haug
2004/0093005 A1	5/2004	Durcan	2005/0137695 A1	6/2005	Salahieh
2004/0093060 A1	5/2004	Sequin et al.	2005/0137701 A1	6/2005	Salahieh
2004/0093075 A1	5/2004	Kuehn	2005/0143807 A1	6/2005	Pavcnik et al.
2004/0097788 A1	5/2004	Mourles et al.	2005/0143809 A1	6/2005	Salahieh
			2005/0148997 A1	7/2005	Valley et al.
			2005/0149181 A1	7/2005	Eberhardt
			2005/0165477 A1	7/2005	Anduiza et al.
			2005/0182483 A1	8/2005	Osborne et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2005/0187616	A1	8/2005	Realyvasquez	2007/0239266	A1	10/2007	Birdsall
2005/0197695	A1	9/2005	Stacchino et al.	2007/0239269	A1	10/2007	Dolan et al.
2005/0203549	A1	9/2005	Realyvasquez	2007/0239273	A1	10/2007	Allen
2005/0203605	A1	9/2005	Dolan	2007/0244544	A1	10/2007	Birdsall et al.
2005/0203618	A1	9/2005	Sharkawy	2007/0244545	A1	10/2007	Birdsall et al.
2005/0222674	A1	10/2005	Paine	2007/0244546	A1	10/2007	Francis
2005/0228495	A1	10/2005	Macoviak	2007/0244553	A1	10/2007	Rafiee et al.
2005/0234546	A1	10/2005	Nugent	2007/0244554	A1	10/2007	Rafiee et al.
2005/0240200	A1	10/2005	Bergheim	2007/0244555	A1	10/2007	Rafiee et al.
2005/0240263	A1	10/2005	Fogarty et al.	2007/0244556	A1	10/2007	Rafiee et al.
2005/0261759	A1	11/2005	Lambrecht et al.	2007/0244557	A1	10/2007	Rafiee et al.
2005/0283962	A1	12/2005	Boudjemline	2007/0250160	A1	10/2007	Rafiee
2006/0004439	A1	1/2006	Spenser et al.	2007/0255394	A1	11/2007	Ryan
2006/0004469	A1	1/2006	Sokel	2007/0255396	A1	11/2007	Douk et al.
2006/0009841	A1	1/2006	McGuckin et al.	2007/0288000	A1	12/2007	Bonan
2006/0025855	A1	2/2006	Lashinski et al.	2008/0004696	A1	1/2008	Vesely
2006/0025857	A1	2/2006	Bergheim et al.	2008/0009940	A1	1/2008	Cribier
2006/0047338	A1	3/2006	Jenson et al.	2008/0015671	A1	1/2008	Bonhoeffer
2006/0052867	A1	3/2006	Revuelta et al.	2008/0021552	A1	1/2008	Gabbay
2006/0058775	A1	3/2006	Stevens et al.	2008/0048656	A1	2/2008	Tan
2006/0058872	A1	3/2006	Salahieh et al.	2008/0065001	A1	3/2008	Marchand et al.
2006/0074485	A1	4/2006	Realyvasques	2008/0065206	A1	3/2008	Liddicoat
2006/0089711	A1	4/2006	Dolan	2008/0071361	A1	3/2008	Tuval et al.
2006/0100685	A1	5/2006	Seguin et al.	2008/0071362	A1	3/2008	Tuval et al.
2006/0116757	A1	6/2006	Lashinski et al.	2008/0071363	A1	3/2008	Tuval et al.
2006/0135964	A1	6/2006	Vesely	2008/0071366	A1	3/2008	Tuval et al.
2006/0142848	A1	6/2006	Gabbay	2008/0071368	A1	3/2008	Tuval et al.
2006/0149360	A1	7/2006	Schwammenthal et al.	2008/0077234	A1	3/2008	Styrc
2006/0167474	A1	7/2006	Bloom et al.	2008/0082165	A1	4/2008	Wilson et al.
2006/0178740	A1	8/2006	Stacchino et al.	2008/0082166	A1	4/2008	Styrc et al.
2006/0195134	A1	8/2006	Crittenden	2008/0133003	A1	6/2008	Seguin et al.
2006/0206192	A1	9/2006	Tower et al.	2008/0140189	A1	6/2008	Nguyen et al.
2006/0206202	A1	9/2006	Bonhoefer et al.	2008/0147105	A1	6/2008	Wilson et al.
2006/0212111	A1	9/2006	Case et al.	2008/0147180	A1	6/2008	Ghione et al.
2006/0247763	A1	11/2006	Slater	2008/0147181	A1	6/2008	Ghione et al.
2006/0259134	A1	11/2006	Schwammenthal et al.	2008/0147182	A1	6/2008	Righini et al.
2006/0259136	A1	11/2006	Nguyen et al.	2008/0154355	A1	6/2008	Benichow et al.
2006/0259137	A1	11/2006	Artof et al.	2008/0154356	A1	6/2008	Obermiller et al.
2006/0265056	A1	11/2006	Nguyen et al.	2008/0161910	A1	7/2008	Revuelta et al.
2006/0271166	A1	11/2006	Thill et al.	2008/0161911	A1	7/2008	Revuelta et al.
2006/0271175	A1	11/2006	Woolfson et al.	2008/0183273	A1	7/2008	Mesana et al.
2006/0276874	A1	12/2006	Wilson et al.	2008/0188928	A1	8/2008	Salahieh et al.
2006/0276882	A1	12/2006	Case et al.	2008/0215143	A1	9/2008	Seguin et al.
2006/0282161	A1	12/2006	Huynh et al.	2008/0215144	A1	9/2008	Ryan et al.
2007/0005129	A1	1/2007	Damm et al.	2008/0228254	A1	9/2008	Ryan
2007/0005131	A1	1/2007	Taylor	2008/0228263	A1	9/2008	Ryan
2007/0010878	A1	1/2007	Rafiee et al.	2008/0234797	A1	9/2008	Stryc
2007/0016286	A1	1/2007	Case et al.	2008/0243246	A1	10/2008	Ryan et al.
2007/0027518	A1	2/2007	Herrmann et al.	2008/0255651	A1	10/2008	Dwork
2007/0027533	A1	2/2007	Douk	2008/0255660	A1	10/2008	Guyenot et al.
2007/0038295	A1	2/2007	Case et al.	2008/0255661	A1	10/2008	Straubinger et al.
2007/0043431	A1	2/2007	Melsheimer	2008/0262593	A1	10/2008	Ryan et al.
2007/0043435	A1	2/2007	Seguin et al.	2008/0269878	A1	10/2008	Iobbi
2007/0051377	A1	3/2007	Douk et al.	2009/0005863	A1	1/2009	Goetz et al.
2007/0073392	A1	3/2007	Heyninck-Janitz	2009/0012600	A1	1/2009	Styrc et al.
2007/0078509	A1	4/2007	Lotfy et al.	2009/0048656	A1	2/2009	Wen
2007/0078510	A1	4/2007	Ryan	2009/0054976	A1	2/2009	Tuval et al.
2007/0088431	A1	4/2007	Bourang et al.	2009/0069886	A1	3/2009	Suri et al.
2007/0093869	A1	4/2007	Bloom et al.	2009/0069887	A1	3/2009	Righini et al.
2007/0100439	A1	5/2007	Cangialosi	2009/0069889	A1	3/2009	Suri et al.
2007/0100440	A1	5/2007	Figulla	2009/0082858	A1	3/2009	Nugent et al.
2007/0100449	A1	5/2007	O'Neil et al.	2009/0085900	A1	4/2009	Weiner
2007/0112415	A1	5/2007	Bartlett	2009/0099653	A1	4/2009	Suri et al.
2007/0162102	A1	7/2007	Ryan et al.	2009/0138079	A1	5/2009	Tuval et al.
2007/0162113	A1	7/2007	Sharkawy et al.	2009/0164004	A1	6/2009	Cohn
2007/0185513	A1	8/2007	Woolfson et al.	2009/0171447	A1	7/2009	VonSegesser et al.
2007/0203391	A1	8/2007	Bloom et al.	2009/0192585	A1	7/2009	Bloom et al.
2007/0225681	A1	9/2007	House	2009/0192586	A1	7/2009	Tabor et al.
2007/0232898	A1	10/2007	Huynh et al.	2009/0192591	A1	7/2009	Ryan et al.
2007/0233228	A1	10/2007	Eberhardt et al.	2009/0198316	A1	8/2009	Laske et al.
2007/0233237	A1	10/2007	Krivoruchko	2009/0216310	A1	8/2009	Straubinger et al.
2007/0233238	A1	10/2007	Huynh et al.	2009/0216312	A1	8/2009	Straubinger et al.
2007/0238979	A1	10/2007	Huynh et al.	2009/0216313	A1	8/2009	Straubinger et al.
2007/0239254	A1	10/2007	Marchand et al.	2009/0222082	A1	9/2009	Lock et al.
2007/0239265	A1	10/2007	Birdsall	2009/0234443	A1	9/2009	Ottma et al.
				2009/0240264	A1	9/2009	Tuval et al.
				2009/0240320	A1	9/2009	Tuval
				2009/0287296	A1	11/2009	Manasse
				2010/0036479	A1	2/2010	Hill et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2010/0094411	A1	4/2010	Tuval et al.
2010/0100167	A1	4/2010	Bortlein et al.
2010/0131054	A1	5/2010	Tuval et al.
2010/0137979	A1	6/2010	Tuval et al.
2010/0161045	A1	6/2010	Righini
2010/0198346	A1	8/2010	Keogh et al.
2010/0234940	A1	9/2010	Dolan
2010/0256723	A1	10/2010	Murray

FOREIGN PATENT DOCUMENTS

DE	195 32 846	3/1997
DE	195 46 692 A1	6/1997
DE	195 46 692 C2	6/1997
DE	198 57 887 A1	7/2000
DE	199 07 646	8/2000
DE	100 49 812	4/2002
DE	100 49 813	4/2002
DE	100 49 815	4/2002
EP	1057460 A1	6/2000
EP	1255510	11/2002
EP	1469797	11/2005
FR	2788217	12/1999
FR	2815844	5/2000
GB	2056023	3/1981
GB	2433700	12/2007
SU	1271508	11/1986
WO	95/29640	11/1995
WO	00/47136	8/2000
WO	01/35870	5/2001
WO	01/47438	7/2001
WO	01/49213	7/2001
WO	01/54625	8/2001
WO	01/62189	8/2001
WO	01/64137	9/2001
WO	02/22054	3/2002
WO	02/36048	5/2002
WO	03/003943	1/2003
WO	03/003949	1/2003
WO	03/011195	2/2003
WO	04/019825	3/2004
WO	04/089250	10/2004
WO	05/004753	1/2005
WO	2005/002466	1/2005
WO	05/046528	5/2005
WO	06/026371	3/2006
WO	2006/070372	7/2006
WO	08/047354	4/2008
WO	08/138584	11/2008
WO	08/150529	12/2008
WO	09/002548	12/2008
WO	09/029199	3/2009
WO	09/042196	4/2009
WO	09/045338	4/2009
WO	09/061389	5/2009
WO	09/091509	7/2009
WO	09/111241	9/2009

OTHER PUBLICATIONS

Babaliaros, et al., "State of the Art Percutaneous Intervention for the Treatment of Valvular Heart Disease: A Review of the Current Technologies and Ongoing Research in the Field of Percutaneous Heart Valve Replacement and Repair," *Cardiology* 2007; 107:87-96.

Bailey, "Percutaneous Expandable Prosthetic Valves," In: Topol EJ, ed. *Textbook of Interventional Cardiology*. vol. II. Second edition. WB Saunders, Philadelphia, 1994:1268-1276.

Block, et al., "Percutaneous Approaches to Valvular Heart Disease," *Current Cardiology Reports*, vol. 7 (2005) pp. 108-113.

Bonhoeffer, et al., "Percutaneous Insertion of the Pulmonary Valve," *Journal of the American College of Cardiology* (United States), May 15, 2002, pp. 1664-1669.

Bonhoeffer, et al., "Percutaneous Replacement of Pulmonary Valve in a Right-Ventricle to Pulmonary-Artery Prosthetic Conduit with Valve Dysfunction," *Lancet* (England), Oct. 21, 2000, pp. 1403-1405.

Bonhoeffer, et al., "Transcatheter Implantation of a Bovine Valve in Pulmonary Position: A Lamb Study," *Circulation* (United States), Aug. 15, 2000, pp. 813-816.

Boudjemline, et al., "Images in Cardiovascular Medicine. Percutaneous Aortic Valve Replacement in Animals," *Circulation* (United States), Mar. 16, 2004, 109, p. e161.

Boudjemline, et al., "Is Percutaneous Implantation of a Bovine Venous Valve in the Inferior Vena Cava a Reliable Technique to Treat Chronic Venous Insufficiency Syndrome?" *Medical Science Monitor—International Medical Journal of Experimental and Clinical Research* (Poland), Mar. 2004, pp. BR61-BR66.

Boudjemline, et al., "Off-pump Replacement of the Pulmonary Valve in Large Right Ventricular Outflow Tracts: A Hybrid Approach," *Journal of Thoracic and Cardiovascular Surgery* (United States), Apr. 2005, pp. 831-837.

Boudjemline, et al., "Percutaneous Aortic Valve Replacement: Will We Get There?" *Heart* (British Cardiac Society) (England), Dec. 2001, pp. 705-706.

Boudjemline, et al., "Percutaneous Implantation of a Biological Valve in the Aorta to Treat Aortic Valve Insufficiency—A Sheep Study," *Medical Science Monitor—International Medical Journal of Experimental and Clinical Research* (Poland), Apr. 2002, pp. BR113-BR116.

Boudjemline, et al., "Percutaneous Implantation of a Biological Valve in Aortic Position: Preliminary Results in a Sheep Study," *European Heart Journal* 22, Sep. 2001, p. 630.

Boudjemline, et al., "Percutaneous Implantation of a Valve in the Descending Aorta in Lambs," *European Heart Journal* (England), Jul. 2002, pp. 1045-1049.

Boudjemline, et al., "Percutaneous Pulmonary Valve Replacement in a Large Right Ventricular Outflow Tract: An Experimental Study," *Journal of the American College of Cardiology* (United States), Mar. 17, 2004, pp. 1082-1087.

Boudjemline, et al., "Percutaneous Valve Insertion: A New Approach," *Journal of Thoracic and Cardiovascular Surgery* (United States), Mar. 2003, pp. 741-742.

Boudjemline, et al., "Stent Implantation Combined with a Valve Replacement to Treat Degenerated Right Ventricle to Pulmonary Artery Prosthetic Conduits," *European Heart Journal* Sep. 22, 2001, p. 355.

Boudjemline, et al., "Steps Toward Percutaneous Aortic Valve Replacement," *Circulation* (United States), Feb. 12, 2002, pp. 775-778.

Boudjemline, et al., "The Percutaneous Implantable Heart Valve," *Progress in Pediatric Cardiology* (Ireland), 2001, pp. 89-93.

Boudjemline, et al., "Transcatheter Reconstruction of the Right Heart," *Cardiology in the Young* (England), Jun. 2003, pp. 308-311.

Coats, et al., "The Potential Impact of Percutaneous Pulmonary Valve Stent Implantation on Right Ventricular Outflow Tract Re-Intervention," *European Journal of Cardio-Thoracic Surgery* (England), Apr. 2005, pp. 536-543.

Cribier, A. et al., "Percutaneous Transcatheter Implantation of an Aortic Valve Prosthesis for Calcific Aortic Stenosis: First Human Case Description," *Circulation* (2002) 3006-3008.

Davidson et al., "Percutaneous therapies for valvular heart disease," *Cardiovascular Pathology* 15 (2006) 123-129.

Hanzel, et al., "Complications of percutaneous aortic valve replacement: experience with the Cribier-Edwards™ percutaneous heart valve," *EuroIntervention Supplements* (2006), 1 (Supplement A) A3-A8.

Huber, et al., "Do Valved Stents Compromise Coronary Flow?" *Eur. J. Cardiothorac. Surg.* 2004;25:754-759.

Khambadkone, "Nonsurgical Pulmonary Valve Replacement: Why, When, and How?" *Catheterization and Cardiovascular Interventions—Official Journal of the Society for Cardiac Angiography & Interventions* (United States), Jul. 2004, pp. 401-408.

Khambadkone, et al., "Percutaneous Implantation of Pulmonary Valves," *Expert Review of Cardiovascular Therapy* (England), Nov. 2003, pp. 541-548.

(56)

References Cited

OTHER PUBLICATIONS

Khambadkone, et al, "Percutaneous Pulmonary Valve Implantation: Early and Medium Term Results," *Circulation* 108 (17 Supplement), Oct. 28, 2003, p. IV-375.

Khambadkone, et al, "Percutaneous Pulmonary Valve Implantation: Impact of Morphology on Case Selection," *Circulation* 108 (17 Supplement), Oct. 28, 2003, p. IV-642-IV-643.

Lutter, et al, "Percutaneous Aortic Valve Replacement: An Experimental Study. I. Studies on Implantation," *The Journal of Thoracic and Cardiovascular Surgery*, Apr. 2002, pp. 768-776.

Lutter, et al, "Percutaneous Valve Replacement: Current State and Future Prospects," *Annals of Thoracic Surgery (Netherlands)*, Dec. 2004, pp. 2199-2206.

Ma, Ling, et al., "Double-crowned valved stents for off-pump mitral valve replacement," *European Journal of Cardio Thoracic Surgery*, 28:194-198, 2005.

Medtech Insight, "New Frontiers in Heart Valve Disease," vol. 7, No. 8 (2005).

Palacios, "Percutaneous Valve Replacement and Repair, Fiction or Reality?" *Journal of American College of Cardiology*, vol. 44, No. 8 (2004) pp. 1662-1663.

Pelton et al., "Medical Uses of Nitinol," *Materials Science Forum* vols. 327-328, pp. 63-70 (2000).

Ruiz, "Transcatheter Aortic Valve Implantation and Mitral Valve Repair: State of the Art," *Pediatric Cardiology*, vol. 26, No. 3 (2005).

Saliba, et al, "Treatment of Obstructions of Prosthetic Conduits by Percutaneous Implantation of Stents," *Archives des Maladies du Coeur et des Vaisseaux (France)*, 1999, pp. 591-596.

Webb, et al., "Percutaneous Aortic Valve Implantation Retrograde from the Femoral Artery," *Circulation* (2006), 113:842-850.

Stassano et al., "Mid-term results of the valve-on-valve technique for bioprosthetic failure," *Eur. J. Cardiothorac. Surg.* 2000; 18:453-457.

Pavcnik et al., "Aortic and venous valve for percutaneous insertion," *Min. Invas. Ther. & Allied Technol.* 2000, vol. 9, pp. 287-292.




FIG. 2A





FIG. 2B







FIG. 4






FIG. 5

FIG. 6A





FIG. 6B






FIG. 7A




FIG. 7B




FIG. 7D





FIG. 7E






FIG. 9




FIG. 10A





FIG. 10B



**PROSTHETIC HEART VALVE HAVING
IDENTIFIERS FOR AIDING IN
RADIOGRAPHIC POSITIONING**

CROSS-REFERENCE TO RELATED
APPLICATIONS

This application is a Continuation of and claims priority to U.S. patent application Ser. No. 14/641,545, filed Mar. 9, 2015, now allowed, which is a Division of and claims priority to U.S. patent application Ser. No. 12/559,945, filed Sep. 15, 2009, now U.S. Pat. No. 8,998,981, which claims the benefit under 35 U.S.C. § 119(c) of U.S. Patent Application No. 61/192,201, filed Sep. 15, 2008, which are incorporated by references in their entirety.

FIELD OF THE INVENTION

The present invention relates generally to prosthetic heart valves, and specifically to techniques for accurately positioning such valves during implantation procedures.

BACKGROUND

Aortic valve replacement in patients with severe valve disease is a common surgical procedure. The replacement is conventionally performed by open heart surgery, in which the heart is usually arrested and the patient is placed on a heart bypass machine. In recent years, prosthetic heart valves have been developed which are implanted using minimally invasive procedures such as transapical or percutaneous approaches. These methods involve compressing the prosthesis radially to reduce its diameter, inserting the prosthesis into a delivery tool, such as a catheter, and advancing the delivery tool to the correct anatomical position in the heart. Once properly positioned, the prosthesis is deployed by radial expansion within the native valve annulus.

While these techniques are substantially less invasive than open heart surgery, the lack of line-of-sight visualization of the prosthesis and the native valve presents challenges, because the physician cannot see the actual orientation of the prosthesis during the implantation procedure. Correct positioning of the prostheses is achieved using radiographic imaging, which yields a two-dimensional image of the viewed area. The physician must interpret the image correctly in order to properly place the prostheses in the desired position. Failure to properly position the prostheses sometimes leads to device migration or to improper functioning. Proper device placement using radiographic imaging is thus critical to the success of the implantation.

PCT Publication WO 05/002466 to Schwammenthal et al., which is assigned to the assignee of the present application and is incorporated herein by reference, describes prosthetic devices for treating aortic stenosis.

PCT Publication WO 06/070372 to Schwammenthal et al., which is assigned to the assignee of the present application and is incorporated herein by reference, describes a prosthetic device having a single flow field therethrough, adapted for implantation in a subject, and shaped so as to define a fluid inlet and a diverging section, distal to the fluid inlet.

US Patent Application Publication 2006/0149360 to Schwammenthal et al., which is assigned to the assignee of the present application and is incorporated herein by reference, describes a prosthetic device including a valve-orifice attachment member attachable to a valve in a blood vessel

and including a fluid inlet, and a diverging member that extends from the fluid inlet, the diverging member including a proximal end near the fluid inlet and a distal end distanced from the proximal end. A distal portion of the diverging member has a larger cross-sectional area for fluid flow therethrough than a proximal portion thereof.

US Patent Application Publication 2005/0197695 to Stacchino et al., describes a cardiac-valve prosthesis adapted for percutaneous implantation. The prosthesis includes an armature adapted for deployment in a radially expanded implantation position, the armature including a support portion and an anchor portion, which are substantially axially coextensive with respect to one another. A set of leaflets is coupled to the support portion. The leaflets can be deployed with the armature in the implantation position. The leaflets define, in the implantation position, a flow duct that is selectably obstructable. The anchor portion can be deployed to enable anchorage of the cardiac-valve prosthesis at an implantation site.

The following patents and patent application publications, are set forth as background:

U.S. Pat. No. 6,312,465 to Griffin et al.

U.S. Pat. No. 5,908,451 to Yeo

U.S. Pat. No. 5,344,442 to Deac

U.S. Pat. No. 5,354,330 to Hanson

US Patent Application Publication 2004/0260389 to Case et al.

U.S. Pat. No. 6,730,118 to Spencer et al.

U.S. Pat. No. 7,018,406 to Seguin et al.

U.S. Pat. No. 7,018,408 to Bailey et al.

U.S. Pat. No. 6,458,153 and US Patent Application Publication 2003/0023300 to Bailey et al.

US Patent Application Publication 2004/0186563 to Lobbi

US Patent Application Publication 2003/0130729 to Paniagua et al.

US Patent Application Publication 2004/0236411 to Sarac et al.

US Patent Application Publication 2005/0075720 to Nguyen et al.

US Patent Application Publication 2006/0058872 to Salahieh et al.

US Patent Application Publication 2005/0137686 Salahieh et al.

US Patent Application Publication 2005/0137690 to Salahieh et al.

US Patent Application Publication 2005/0137691 to Salahieh et al.

US Patent Application. Publication 2005/0143809 to Salahieh et al.

US Patent Application Publication 2005/0182483 to Osborne et al.

US Patent Application Publication 2005/0137695 to Salahieh et al.

US Patent Application Publication 2005/0240200 to Bergheim

US Patent Application Publication 2006/0025857 to Bergheim et al.

US Patent Application Publication 2006/0025855 to Lashinski et al.

US Patent Application Publication 2006/0047338 to Jenson et al.

US Patent Application Publication 2006/0052867 to Revuelta et al.

US Patent Application Publication 2006/0074485 to Realyvasquez

US Patent Application Publication 2006/0259136 to Nguyen et al.

U.S. Pat. No. 7,137,184 to Schreck
U.S. Pat. No. 6,296,662 to Caffey

SUMMARY

In some embodiments of the present invention, a prosthetic heart valve prosthesis comprises three commissural posts to which are coupled a prosthetic valve. The commissural posts are shaped so as to define therethrough respective openings that serve as radiographic identifiers during an implantation procedure. During the procedure, the valve prosthesis, including the commissural posts, is initially collapsed within a delivery tube. Before expanding the valve prosthesis, a physician uses radiographic imaging, such as x-ray fluoroscopy, to provide visual feedback that aids the physician in rotationally aligning the commissural posts with respective native commissures of a native semilunar valve. The identifiers strongly contrast with the rest of the commissural posts and the valve prosthesis, which comprise a radiopaque material. Without such identifiers, it is generally difficult to three-dimensionally visually distinguish the commissural posts from one another and from the rest of the valve prosthesis, because the radiographic imaging produces a two-dimensional representation of the three-dimensional valve prosthesis. When the valve prosthesis is in a collapsed state, the elements thereof overlap in a two-dimensional image and are generally indistinguishable.

In some embodiments of the present invention, the physician selects one of the commissural posts having a radiographic identifier, and attempts to rotationally align the selected post with one of the native commissures, such as the commissure between the left and right coronary sinuses. Because the radiographic image is two-dimensional, all of the posts appear in the image as though they are in the same plane. The physician thus cannot distinguish between two possible rotational positions of the posts: (1) the desired rotational position, in which the selected post faces the desired native commissure, and (2) a rotational position 180 degrees from the desired rotational position, in which the selected post faces the side of the native valve opposite the desired native commissure. For example, if the desired native commissure is the commissure between the left and right coronary sinuses, in position (2) the post is rotationally aligned with the noncoronary sinus, although this undesired rotation is not apparent in the radiographic image.

To ascertain whether the posts are in rotational Position (1) or (2), the physician slightly rotates the valve prosthesis. If the radiographic identifier on the selected post appears to move in the radiographic image in the same direction as the rotation, the selected post is correctly rotationally aligned in the desired position (1). If, on the other hand, the radiographic identifier appears to move in the direction opposite the direction of rotation, the selected post is incorrectly rotationally aligned in position (2). To correct the alignment, the physician may rotate the valve prosthesis approximately 60 degrees in either direction, thereby ensuring that one of the two other posts is now rotationally aligned in position (1). (The valve prosthesis typically has three-fold rotational symmetry, such that rotation of 60 degrees is sufficient to properly align one of the posts with the selected native commissure, and the prosthesis need not be rotated a full 180 degrees.) In these embodiments, the openings through the posts that define the radiographic identifiers may assume any convenient shape, such as a slit.

In some embodiments of the present invention, the openings that define the radiographic identifiers are shaped to be reflection-asymmetric along respective post axes that are

generally parallel with a central longitudinal axis of the prosthesis when the posts assume their collapsed position. For example, the identifiers may be shaped as one or more reflection-asymmetric characters, such as numbers or letters of the alphabet, e.g., B, C, D, E, etc. The physician can thus readily identify the true orientation of the selected post that appears to be rotationally aligned with the selected native commissure. If the identifier on the selected post appears in the correct left-right orientation, the selected post is aligned in the desired position (1). If, on the other hand, the identifier appears as the mirror image of its correct left-right orientation, the selected post is incorrectly rotationally aligned in position (2). To correct the alignment, the physician may rotate the valve prosthesis approximately 60 degrees in either direction, thereby ensuring that one of the two other posts is now rotationally aligned in position (1).

There is therefore provided, in accordance with an embodiment of the present invention, apparatus including a valve prosthesis, which includes a prosthetic heart valve, and three or more commissural posts, to which the prosthetic heart valve is coupled. The posts are arranged circumferentially around a central longitudinal axis of the valve prosthesis, and are configured to assume a collapsed position prior to implantation of the prosthesis, and an expanded position upon the implantation of the prosthesis. One or more of the commissural posts are provided with respective radiographic identifiers that are shaped to be reflection-asymmetric about respective post axes that are generally parallel with the central longitudinal axis when the posts assume the collapsed position.

For some applications, the radiographic identifiers have the shape of one or more reflection-asymmetric characters.

In an embodiment, the one or more of the commissural posts are shaped to define respective openings therethrough which define the respective radiographic identifiers. Alternatively, the radiographic identifiers include a material having a first radiopacity that is different from a second radiopacity of the commissural posts, which material is coupled to the one or more of the commissural posts.

For some applications, the valve prosthesis includes exactly three commissural posts.

There is further provided, in accordance with an embodiment of the present invention, a method including:

providing a valve prosthesis that includes a prosthetic heart valve, and three or more commissural posts, to which the prosthetic heart valve is coupled, which posts are arranged circumferentially around a central longitudinal axis of the valve prosthesis, and are configured to assume a collapsed position prior to implantation of the prosthesis, and an expanded position upon the implantation of the prosthesis, and at least one of which commissural posts is provided with a radiographic identifier;

while the posts assume the collapsed position, placing, via a blood vessel of the subject, the valve prosthesis at least partially in a heart of a subject in a vicinity of a native heart valve having native commissures;

generating a fluoroscopic image of the native commissures and valve prosthesis; and

rotationally aligning the at least one of the commissural posts with one of the native commissures using the radiographic identifier visible in the image.

In an embodiment, rotationally aligning includes rotating the valve prosthesis; observing whether the at least one of the commissural posts appears to move in the image in the same direction that the valve prosthesis is rotated, or in an opposite direction; and, if the at least one of the commissural

posts appears to move in the image. in the opposite direction, rotating the valve prosthesis to correct. a rotational alignment of the valve prosthesis.

For some applications, the valve prosthesis includes exactly three commissural posts, and is configured to have three-fold rotational symmetry, and rotating the valve prosthesis to correct the rotational alignment includes rotating the valve prosthesis approximately 60 degrees.

In an embodiment, the radiographic identifier is shaped to be reflection-asymmetric about a post axis of the at least one of the commissural posts, which axis is generally parallel with the central longitudinal axis when the posts assume the collapsed position. For some applications, the radiographic identifier has the shape of a reflection-asymmetric character.

For some applications, rotationally aligning includes observing in the image whether the radiographic identifier appears in a correct left-right orientation, and, if the radiographic identifier does not appear in the correct left-right orientation, rotating the valve prosthesis to correct a rotational alignment of the valve prosthesis. For some applications, the valve prosthesis includes exactly three commissural posts, and is configured to have three-fold rotational symmetry, and rotating the valve prosthesis to correct the rotational alignment includes rotating the valve prosthesis approximately 60 degrees.

In an embodiment, the at least one of the commissural posts is shaped to define an opening therethrough which defines the radiographic identifier. Alternatively, the radiographic identifier includes a material having a first radiopacity that is different from a second radiopacity of the at least one of the commissural posts, which material is coupled to the at least one of the commissural posts.

For some applications, the one of the native commissures is a native commissure (C_{RL}) between a left coronary sinus and a right coronary sinus, and rotationally aligning includes rotationally aligned the one of the commissural posts with the C_{RL} .

There is still further provided, in accordance with an embodiment of the present invention, a method including:

providing a valve prosthesis that includes a prosthetic heart valve, and three or more commissural posts, to which the prosthetic heart valve is coupled, which posts are arranged circumferentially around a central longitudinal axis of the valve prosthesis, and are configured to assume a collapsed position prior to implantation of the prosthesis, and an expanded position upon the implantation of the prosthesis;

while the posts assume the collapsed position, placing, via a blood vessel of the subject, the valve prosthesis at least partially in a heart of a subject in a vicinity of a native heart valve having native commissures;

generating a fluoroscopic image of the native commissures and valve prosthesis; and

rotationally aligning the at least one of the commissural posts with one of the native commissures by:

rotating the valve prosthesis,

observing whether the at least one of the commissural posts appears to move in the image in the same direction that the valve prosthesis is rotated, or in an opposite direction, and

if the at least one of the commissural posts appears to move in the image in the opposite direction, rotating the valve prosthesis to correct a rotational alignment of the valve prosthesis.

For some applications, the valve prosthesis includes exactly three commissural posts, and is configured to have three-fold rotational symmetry, and rotating the valve pros-

thesis to correct the rotational alignment includes rotating the valve prosthesis approximately 60 degrees.

There is additionally provided, in accordance with an embodiment of the present invention, apparatus including a valve prosthesis, which includes:

a prosthetic heart valve;

a support structure, which includes a first material having a first radiopacity; and

one or more radiographic identifiers, which include a second material having a second radiopacity different from the first radiopacity, and which are coupled to the support structure at respective locations.

In an embodiment, the radiographic identifiers are shaped to be reflection-asymmetric about respective identifier axes that are generally parallel with a central longitudinal axis of the valve prosthesis.

For some applications, the identifiers are arranged circumferentially around a central longitudinal axis of the valve prosthesis.

For some applications, the support structure is shaped so as to define a bulging proximal skirt, and the identifiers are coupled to the skirt.

For some applications, the support structure includes three or more commissural posts, to which the prosthetic heart valve is coupled, which posts are arranged circumferentially around a central longitudinal axis of the valve prosthesis, the locations at which the identifiers are coupled to the support structure are not on the posts, and the locations are radially aligned with the posts.

For some applications, the support structure includes three or more commissural posts, to which the prosthetic heart valve is coupled, which posts are arranged circumferentially around a central longitudinal axis of the valve prosthesis, and the locations at which the identifiers are coupled to the support structure are on the posts.

The present invention will be more fully understood from the following detailed description of embodiments thereof, taken together with the drawings, in which:

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic illustration of a fully-assembled valve prosthesis, in accordance with an embodiment of the present invention;

FIGS. 2A and 2B are schematic illustrations of a collapsible outer support structure and a collapsible inner support structure, respectively, prior to assembly together into the valve prosthesis of FIG. 1, in accordance with an embodiment of the present invention;

FIG. 3 is a schematic illustration of a subject undergoing a transapical or percutaneous valve replacement procedure, in accordance with an embodiment of the present invention;

FIG. 4 shows an exemplary fluoroscopic view generated with a fluoroscopic system during a valve replacement procedure, in accordance with an embodiment of the present invention;

FIG. 5 shows an exemplary ultrasound view generated with an ultrasound probe during a valve replacement procedure, in accordance with an embodiment of the present invention;

FIGS. 6A and 6B are schematic and fluoroscopic views, respectively, of the valve prosthesis of FIG. 1 in a collapsed position in a catheter, in accordance with an embodiment of the present invention;

FIGS. 7A and 7B are schematic illustrations of the valve prosthesis of FIG. 1 in situ upon completion of transapical

and retrograde transaortic implantation procedures, respectively, in accordance with respective embodiments of the present invention;

FIGS. 7C-7E are schematic illustrations of an implantation procedure of an alternative configuration of the valve prosthesis of FIG. 1, in accordance with an embodiment of the present invention;

FIGS. 8A-B are schematic illustrations of the valve prosthesis of FIG. 1 positioned within the aortic root, in accordance with an embodiment of the present invention;

FIG. 9 is a flow chart that schematically illustrates a method for ascertaining whether the valve prosthesis of FIG. 1 or FIGS. 7C-E are properly rotationally aligned with the native commissures, in accordance with an embodiment of the present invention and

FIGS. 10A and 10B are schematic illustrations of reflection-asymmetric radiographic identifiers on commissural posts of the valve prosthesis of FIG. 1 or FIGS. 7C-E, in accordance with respective embodiments of the present invention.

DETAILED DESCRIPTION

FIG. 1 is a schematic illustration of a fully-assembled valve prosthesis 10, in accordance with an embodiment of the present invention. Typically, valve prosthesis 10 comprises exactly three commissural posts 11, arranged circumferentially around a central longitudinal axis 13 of valve prosthesis 10. Valve prosthesis 10 further comprises a prosthetic distal valve 104 coupled to couple to commissural posts 11. Valve 104 typically comprises a pliant material 105. Pliant material 105 of valve 104 is configured to collapse inwardly (i.e., towards central longitudinal axis 13) during diastole, in order to inhibit retrograde blood flow, and to open outwardly during systole, to allow blood flow through the prosthesis. For some applications, valve prosthesis 10 comprises a collapsible inner support structure 12 that serves as a proximal fixation member, and a collapsible outer support structure 14 that serves as a distal fixation member.

One or more (e.g., all) of commissural posts 11 are shaped so as to define therethrough respective openings 16 that serve as radiographic identifiers during an implantation procedure, as described herein below with reference to FIGS. 3-8B. The openings may assume any convenient, shape, for example, slits, as shown in FIGS. 1, 2A-B, and 6A-B. In some embodiments, the openings are shaped to be reflection-asymmetric along respective post axes generally parallel with central longitudinal axis 13 of prosthesis 10 when the posts assume their collapsed position, as described herein below with reference to FIGS. 10A-B. For some applications, in addition to serving as the radiographic identifiers, openings 16 are used for coupling valve 104 to support structures 12 and 14. Although pliant material 105 of valve 104 at least partially fills openings 16, the material is substantially more radiolucent than commissural posts 11, and thus does not reduce the radiographic visibility of the radiographic identifiers. Alternatively, one or more of posts 11 do not necessarily define openings 16, and the one or more posts instead comprise radiographic identifiers comprising a material having a radiopacity different from (greater or less than) the radiopacity of posts 11, such as gold or tantalum.

Valve prosthesis 10 is configured to be placed in a native diseased valve of a subject, such as a native stenotic aortic or pulmonary valve, using a minimally-invasive approach, such as a beating heart transapical procedure, such as

described herein below with reference to FIG. 7A, or a retrograde transaortic procedure, such as described herein below with reference to FIG. 7B. As used in the present application, including in the claims, a “native semilunar valve” is to be understood as including: (a) native semilunar valves that include their native leaflets, and (b) native semilunar valves, the native leaflets of which have been surgically excised or are otherwise absent.

Reference is made to FIG. 2A, which is a schematic illustration of collapsible outer support structure 14 prior to assembly with inner support structure 12, in accordance with an embodiment of the present invention. In this embodiment, outer support structure 14 is shaped so as to define a plurality of distal diverging strut supports 20, from which a plurality of proximal engagement arms 22 extend radially outward in a proximal direction. Engagement arms 22 are typically configured to be at least partially disposed within aortic sinuses of the subject, and, for some applications, to engage and/or rest against floors of the aortic sinuses, and to apply an axial force directed toward a left ventricle of the subject. Outer support structure 14 comprises a suitable material that allows mechanical deformations associated with crimping and expansion of valve prosthesis 10, such as, but not limited to, nitinol or a stainless steel alloy (e.g., AISI 316).

Reference is made to FIG. 23, which is a schematic illustration of collapsible inner support structure 12 prior to assembly with outer support structure 14, in accordance with an embodiment of the present invention. For some applications, inner support structure 12 is shaped so as to define a plurality of distal diverging inner struts 30, and a bulging proximal skirt 32 that extends from the struts. A proximal portion 34 of proximal skirt 32 is configured to engage a left ventricular outflow tract (LVOT) of the subject and/or periannular tissue at the top of the left ventricle. A relatively narrow throat section 36 of proximal skirt 32 is configured to be positioned at a valvular annulus of the subject, and to engage the native valve leaflets. Inner support structure 12 comprises, for example, nitinol, a stainless steel alloy, another metal, or another biocompatible material.

Reference is again made to FIG. 1. Inner and outer support structures 12 and 14 are assembled together by placing outer support structure 14 over inner support structure 12, such that outer strut supports 20 are aligned with, and typically support, respective inner struts 30, and engagement arms 22 are placed over a portion of proximal skirt 32. Inner struts 30 and outer strut supports 20 together define commissural posts 11.

Although exactly three commissural posts 11 are shown in the figures, for some applications valve prosthesis 10 comprises fewer or more posts 11, such as two posts 11, or four or more posts 11.

Typically, valve prosthesis 10 further comprises a graft covering 106 which is coupled to proximal skirt 32, such as by sewing the covering within the skirt (configuration shown in FIG. 1) or around the skirt (configuration not shown). Inner support structure 12 thus defines a central structured body for flow passage that proximally terminates in a flared inlet (proximal skirt 32) that is configured to be seated within an LVOT immediately below an aortic annulus/aortic valve. For some applications, graft covering 106 is coupled at one or more sites to pliant material 105.

In an embodiment of the present invention, a portion of valve prosthesis 10 other than commissural posts 11, e.g., proximal skirt 32, is shaped so as to define openings 16 that serve as radiographic identifiers. Alternatively or additionally, the commissural posts or this other portion of the

prosthesis comprise radiographic identifiers comprising a material having a radiopacity different from (greater or less than) the radiopacity of other portions of the prosthesis. For some applications, the radiographic identifiers are radially aligned with commissural posts 11.

FIG. 3 is a schematic illustration of a subject 200 undergoing a transapical or percutaneous valve replacement procedure, in accordance with an embodiment of the present invention. A fluoroscopy system 210 comprises a fluoroscopy source 213, a fluoroscopy detector 212, and a monitor 214. Fluoroscopy source 213 is positioned over subject 200 so as to obtain a left anterior oblique (LAO) projection of between 30 and 45, such as between 30 and 40, degrees with a 30-degree cranial tilt (for orthogonal projection of the annulus). Typically, imaging is enhanced using an ultrasound probe 216.

FIG. 4 shows an exemplary fluoroscopic view 220 generated with fluoroscopic system 210 during a valve replacement procedure, in accordance with an embodiment of the present invention. In the view, a right coronary sinus (RCS) 222 and a left coronary sinus (LCS) 224 are visible, as are the respective coronary arteries that originate from the sinuses. The view also shows a commissure 226 between the right and left sinuses (C_{RL}). RCS 222, LCS 224, and C_{RL} 226 serve as clear anatomical landmarks during the replacement procedure, enabling the physician to readily ascertain the layout of the aortic root.

FIG. 5 shows an exemplary ultrasound view 230 generated with ultrasound probe 216 during a valve replacement procedure, in accordance with an embodiment of the present invention. In the view, the RCS, LCS, and non-coronary sinus (N) are visible. The orientation of view 230 can be seen with respect to a sternum 232 and a spine 234, as well as with respect to fluoroscopy detector 212.

FIGS. 6A and 6B are schematic and fluoroscopic views, respectively, of valve prosthesis 10 in a collapsed position in a catheter 300, in accordance with an embodiment of the present invention. In this embodiment, openings 16 are shaped as slits. As can be seen in FIG. 613, these slits are clearly visible with fluoroscopy.

Reference is made to FIGS. 7A and 7B, which are schematic illustrations of valve prosthesis 10 in situ upon completion of transapical and retrograde transaortic implantation procedures, respectively, in accordance with respective embodiments of the present invention.

In the transapical procedure, as shown in FIG. 7A, an introducer overtube or trocar 150 is inserted into a left ventricular apex 156 using a Seldinger technique. Through this trocar, a delivery catheter (not shown in the figure) onto which collapsed valve prosthesis 10 is mounted, is advanced into a left ventricle 357 where its motion is terminated, or through left ventricle 357 until the distal end of a dilator (not shown) passes native aortic valve leaflets 358. For example, apex 356 may be punctured using a standard Seldinger technique, and a guidewire may be advanced into an ascending aorta 360. Optionally, a native aortic valve 340 is partially dilated to about 15-20 mm (e.g., about 16 mm), typically using a standard valvuloplasty balloon catheter. (In contrast, full dilation would be achieved utilizing dilation of 20 mm or more.) Overtube or trocar 350 is advanced into the ascending aorta. Overtube or trocar 350 is pushed beyond aortic valve 340 such that the distal end of overtube or trocar 350 is located above the highest point of native aortic valve 340. The dilator is removed while overtube or trocar 350 remains in place with its distal end located above aortic valve 340. Alternatively, the procedure may be modified so that overtube or trocar 350 is placed within left ventricle 350

and remains within the left ventricle throughout the entire implantation procedure. Valve prosthesis 10 is advanced through the distal end of overtube or trocar 350 into ascending aorta 360 distal to native leaflets 358.

Valve prosthesis 10, typically while still within the catheter, is rotated to align arms 22 with aortic sinuses 364, as described herein below with reference to FIGS. 8A-B or FIGS. 10A-B. After the prosthesis is properly rotationally aligned, withdrawal of the catheter causes engagement arms 22 to flare out laterally to an angle which is typically predetermined by design, and to open in an upstream direction. Gentle withdrawal of the delivery catheter, onto which prosthesis 10 with flared-out arms 22 is mounted, causes the arms to slide into aortic sinuses 364. Release of the device from the delivery catheter causes a lower inflow portion of prosthesis 10 to unfold and press against the upstream side of native leaflets 358, thereby engaging with the upstream fixation arms in the aortic sinuses. The upstream fixation arms serve as counterparts to the lower inflow portion of the prosthesis in a mechanism that locks the native leaflets and the surrounding periannular tissue for fixation.

For some applications, prosthesis 10 is implanted using techniques described with reference to FIGS. 5A-C in U.S. application Ser. No. 12/050,628, filed Mar. 18, 2008, entitled, "Valve suturing and implantation procedures," which is incorporated herein by reference.

In the retrograde transaortic procedure, as shown in FIG. 7B, valve prosthesis 10 is positioned in a retrograde delivery catheter 450. A retrograde delivery catheter tube 451 of catheter 450 holds engagement arms 22, and a delivery catheter cap 452 holds proximal skirt 32 (not shown). A guidewire 490 is transaortically inserted into left ventricle 357. Optionally, stenotic aortic valve 340 is partially dilated to about 15-20 mm (e.g., about 16 mm), typically using a standard valvuloplasty balloon catheter. Retrograde delivery catheter 450 is advanced over guidewire 490 into ascending aorta 360 towards native aortic valve 340. Retrograde delivery catheter 450 is advanced over guidewire 490 until delivery catheter cap 452 passes through native aortic valve 340 partially into left ventricle 357.

Valve prosthesis 10, typically while still within the catheter, is rotated to align arms 22 with aortic sinuses 364, as described herein below with reference to FIGS. 8A-B or FIGS. 1A-B. Retrograde delivery catheter tube 451 is pulled back (in the direction indicated schematically by an arrow 455), while a device stopper (not shown) prevents valve prosthesis 10 within tube 451 from being pulled back with tube 451, so that engagement arms 22 are released and flare out laterally into the sinuses. At this stage of the implantation procedure, proximal skirt 32 of prosthesis 10 remains in delivery catheter cap 452.

Delivery catheter cap 452 is pushed in the direction of the apex of the heart, using a retrograde delivery catheter cap shaft (not shown) that passes through tube 451 and prosthesis 10. This advancing of cap 452 frees proximal skirt 32 to snap or spring open, and engage the inner surface of the LVOT. Retrograde delivery catheter tube 451 is further pulled back until the rest of valve prosthesis 10 is released from the tube. Retrograde delivery catheter tube 451 is again advanced over the shaft toward the apex of the heart, until tube 451 rejoins cap 452. Retrograde delivery catheter 450 and guidewire 490 are withdrawn from left ventricle 357, and then from ascending aorta 360, leaving prosthesis 10 in place.

For some applications, prosthesis 10 is implanted using techniques described with reference to FIGS. 9A-G in above-mentioned U.S. application Ser. No. 12/050,628.

11

Reference is made to FIGS. 7C-7E, which are schematic illustrations of an implantation procedure of an alternative configuration of valve prosthesis 10, in accordance with an embodiment of the present invention. In this configuration, valve prosthesis 10 does not comprise proximal engagement arms 22. Even without these arms, which rest in the sinus floors and thus may aid in properly rotationally aligning the prosthesis, the techniques described herein achieve proper alignment of the prosthesis. For some applications, valve prosthesis 10 is configured as described in a US provisional patent application filed on even date herewith, entitled, "Prosthetic heart valve for transfemoral delivery," which is assigned to the assignee of the present application and is incorporated herein by reference.

FIG. 7C shows valve prosthesis 10 positioned in retrograde delivery catheter 450, which is advanced into left ventricle 357 over guidewire 490. Valve prosthesis 10, typically while still within the catheter, is rotated to align commissural posts 11 with the native commissures, as described herein below with reference to FIGS. 8A-B or FIGS. 10A-B. After the prosthesis is properly rotationally aligned, withdrawal of the catheter causes expansion of the frame of prosthesis, as shown in FIG. 7D. FIG. 7E shows this configuration of prosthesis 10 positioned within the aortic root (viewed from the aorta). The frame of the prosthesis is shaped so as to define distal support members 492, which extend in a downstream direction (i.e., they do not extend into the floors of the aortic sinuses). Distal support elements 492 are configured to rest against the downstream portion of the aortic sinuses upon implantation of valve prosthesis 10, so as to provide support against tilting of the prosthesis with respect to a central longitudinal axis of the prosthesis. As can be seen in FIG. 7E, commissural posts 11 of the valve prosthesis are rotationally aligned with native commissures 494.

Reference is made to FIGS. 8A-B, which are schematic illustrations of valve prosthesis 10 positioned within the aortic root (viewed from the aorta), in accordance with an embodiment of the present invention. As described above with reference to FIGS. 7A-B, during an implantation procedure, a delivery catheter is inserted into an overtube and advanced until the distal end of commissural posts 11 arrive near the end of the overtube.

For configurations of valve prosthesis 10 that include proximal engagement arms 22, the arms are still within the catheter. To properly rotationally align posts with the native commissures, the physician rotates valve prosthesis 10 under fluoroscopy until one 496 of commissural posts 11 is aligned with one of the native commissures, such as commissure 226 between the right and left sinuses (C_{RL}). In an attempt to achieve such a rotational position, the physician rotates the prosthesis until one of openings 16 that serve as radiographic identifiers is centered from the viewpoint of the fluoroscopic LAO projection such as shown in FIG. 6B (openings 16 are not visible from the view of FIGS. 8A-B). The other two commissural posts 11 flank the centered post.

At this stage of the procedure, because the radiographic image is two-dimensional and all of the posts appear in the image as though they are in the same plane, it is difficult for the physician to ascertain whether commissural post 496 selected for alignment is:

- (1) in the desired rotational position, closer to fluoroscopy detector 212 (FIG. 3) than are the other two commissures, and thus properly aligned with the C_{RL} 226, as shown in FIG. 8A; or
- (2) farther away from the fluoroscopy detector than are the other two posts, rotated 180 degrees from the

12

desired rotational position, as shown in FIG. 8B. In this rotational orientation, centered post 496 projects itself onto C_{RL} 226, but actually faces the noncoronary sinus (N) away from the fluoroscopy detector, such that valve prosthesis 10 is misaligned by 60 degrees (because the prosthesis typically has three-fold rotational symmetry).

Reference is made to FIG. 9, which is a flow chart that schematically illustrates a method 500 for ascertaining whether the posts are in the first or second possible rotational position, in accordance with an embodiment of the present invention. At an initial rotation step 502, the physician slightly rotates valve prosthesis 10. At an apparent rotation check step 504, the physician ascertains whether the radiographic identifier on the selected post appears to move in the radiographic image in the same direction as the rotation. If the identifier appears to move in the same direction as the rotation, the physician ascertains that the selected post is correctly rotationally aligned in the desired position (1) (after the physician slightly rotates the prosthesis in the opposite direction to return it to its initial position), at a proper alignment ascertainment step 506. If, on the other hand, the radiographic identifier appears to move in the direction opposite the direction of rotation, the physician ascertains that the selected post is incorrectly rotationally aligned in position (2), at an improper alignment ascertainment step 508. To correct the alignment, the physician rotates the valve prosthesis approximately 60 degrees in either direction, thereby ensuring that one of the two other posts is now rotationally aligned in position (1), at an alignment correction step 510. (The valve prosthesis typically has three-fold rotational symmetry, such that rotation of 60 degrees is sufficient to properly align one of the posts with the selected native commissure, and the prosthesis need not be rotated a full 180 degrees.) For example, assume that at initial rotation step 502 the physician rotates the prosthesis clockwise, as viewed from the aorta. If the valve prosthesis is properly aligned, the radiographic identifier on the selected post appears to move toward the LCS at apparent rotation check step 504. Once the valve prosthesis is properly aligned, commissural posts 11 are released from the catheter, as well as proximal engagement arms 22, for configurations of the prosthesis that include such arms, at a commissural post release step 512. In these embodiments, openings 16 through posts 11 that define the radiographic identifiers may assume any convenient shape, such as a slit.

In an embodiment of the present invention, this technique for rotationally aligning posts 11 with the native commissures is used for aligning a valve prosthesis that does not include radiographic identifiers. Instead of using such identifiers, the physician observes elements of the prosthesis that are discernible in the radiographic images, such as posts 11.

FIGS. 10A and 10B are schematic illustrations of reflection-asymmetric radiographic identifiers 600 on commissural posts 11, in accordance with respective embodiments of the present invention. Identifiers 600 may be used with both the configuration of valve prosthesis 10 described hereinabove with reference to FIG. 1, and that described hereinabove with reference to FIGS. 7C-E. Openings 16 that define radiographic identifiers 600 are shaped to be reflection-asymmetric along respective, post axes 604 that are generally parallel central longitudinal axis 13 of prosthesis 10 when the posts assume their collapsed position. For example, as shown in FIG. 10A, identifiers 600 may be shaped as one or more reflection-asymmetric letters of the alphabet, such as B, C, D, E, etc., or numbers. Alternatively, the identifier may be shaped as any reflection-symmetric

symbol, such as the inverted elongated L shown in FIG. 10B. The physician can thus readily identify the true orientation of the selected post that appears to be rotationally aligned with the selected native commissure. If the identifier on the selected post appears in the correct left-right orientation, the selected post is aligned in the desired position (1), as described hereinabove with reference to FIGS. 8A-B. If, on the other hand, the identifier appears as the mirror image of its correct left-right orientation, the selected post is incorrectly rotationally aligned in position (2) as described hereinabove with reference to FIGS. 8A-B. To correct the alignment, the physician rotates the valve prosthesis approximately 60 degrees in either direction, thereby ensuring that one of the two other posts is now rotationally aligned in position (1).

For some applications, such as shown in FIG. 10A, at least one of commissural posts **11** is shaped so as to define both reflection-asymmetric radiographic identifier **600** and another reflection-symmetric shape **610**, such as a slit. For example, such a slit may have a mechanical purpose, such as coupling valve **104** to support structures **12** and **14**, as described hereinabove with reference to FIG. 1. Alternatively, the physician may use reflection-symmetric shape **610** for rotational orientation as described hereinabove with reference to FIGS. 8A-B in the event that reflection-asymmetric radiographic identifiers **600** are not be clearly visible in the radiographic image during a particular implantation procedure.

For some applications, reflection-asymmetric radiographic identifiers **600** are not defined by openings **16**, but instead comprise a material having a radiopacity different from (greater or less than) the radiopacity of other portions of the posts. For some applications, a portion of valve prosthesis **10** other than commissural posts **11** comprises radiographic identifiers **600** (whether defined by openings, or comprising a material having a different radiopacity).

For some applications, techniques described herein are performed in combination with techniques described in a US provisional patent application filed on even date herewith, entitled, "Prosthetic heart valve for transfemoral delivery," which is assigned to the assignee of the present application and is incorporated herein by reference.

The scope of the present invention includes embodiments described in the following applications, which are assigned to the assignee of the present application and are incorporated herein by reference. In an embodiment, techniques and apparatus described in one or more of the following applications are combined with techniques and apparatus described herein:

U.S. patent application Ser. No. 11/024,908, filed Dec. 30, 2004, entitled, "Fluid flow prosthetic device," which issued as U.S. Pat. No. 7,201,772;

International Patent Application PCT/IL2005/001399, filed Dec. 29, 2005, entitled, "Fluid flow prosthetic device," which published as PCT Publication WO 06/070372;

International Patent Application PCT/IL2004/000601, filed Jul. 6, 2004, entitled, "Implantable prosthetic devices particularly for transarterial delivery in the treatment of aortic stenosis, and methods of implanting such devices," which published as PCT Publication WO 05/002466, and U.S. patent application Ser. No. 10/563,384, filed Apr. 20, 2006, in the national stage thereof, which published as US Patent Application Publication 2006/0259134;

U.S. Provisional Application 60/845,728, filed Sep. 19, 2006, entitled, "Fixation member for valve";

U.S. Provisional Application 60/852,435, filed Oct. 16, 2006, entitled, "Transapical delivery system with ventriculo-arterial overflow bypass";

U.S. application Ser. No. 11/728,253, filed Mar. 23, 2007, entitled, "Valve prosthesis fixation techniques using sandwiching";

International Patent Application PCT/IL2007/001237, filed Oct. 16, 2007, entitled, "Transapical delivery system with ventriculo-arterial overflow bypass," which published as POT Publication WO 2008/047354; and/or

U.S. application Ser. No. 12/050,628, filed Mar. 18, 2008, entitled, "Valve suturing and implantation procedures."

It will be appreciated by persons skilled in the art that the present invention is not limited to what has been particularly shown and described hereinabove. Rather, the scope of the present invention includes both combinations and subcombinations of the various features described hereinabove, as well as variations and modifications thereof that are not in the prior art, which would occur to persons skilled in the art upon reading the foregoing description.

What is claimed is:

1. A method comprising the steps of:

providing a valve prosthesis that includes a prosthetic heart valve, wherein the valve prosthesis has a collapsed configuration and an expanded configuration, and at least one radiographic identifier;

wherein the valve prosthesis is configured to have three-fold rotational symmetry;

while the valve prosthesis is in the collapsed configuration, placing, via a blood vessel of the subject, the valve prosthesis at least partially in a heart of a subject in a vicinity of a native heart valve having native commissures;

generating a fluoroscopic image of the native commissures and valve prosthesis; and

rotationally aligning the radiographic identifier visible in the image with at least one of the native commissures; wherein rotationally aligning comprises:

rotating the valve prosthesis;

observing whether the radiographic identifier appears to move in the image in the same direction that the valve prosthesis is rotated, or in an opposite direction; and

if the radiographic identifier appears to move in the image in the opposite direction, rotating the valve prosthesis approximately 60 degrees to correct a rotational alignment of the valve prosthesis.

2. The method of claim 1, wherein the valve prosthesis includes a plurality of commissural posts.

3. The method of claim 2, wherein the valve prosthesis includes exactly three commissural posts.

4. The method of claim 2, wherein the radiographic identifier is shaped to be reflection-asymmetric about a post axis of one of the plurality of commissure posts, which the post axis is generally parallel with a central longitudinal axis of the valve prosthesis when the plurality of commissure posts assume the collapsed configuration.

5. The method of claim 4, wherein the radiographic identifier has a shape of a reflection-asymmetric character.

6. The method of claim 2, wherein the radiographic identifier comprises a material having a first radiopacity that is different from a second radiopacity of the plurality of commissural posts, which material is coupled to each of the plurality of commissural posts.

7. The method of claim 2, wherein the native commissures of the native heart valve include a first native commissure between a left coronary sinus and a right coronary sinus of

15

the native heart valve and wherein rotationally aligning comprises rotationally aligning one of the plurality of commissural posts with the first native commissure.

8. The method of claim **2**, wherein at least one of the plurality of commissure posts includes an opening that serves as the at least one radiographic identifier.

9. The method of claim **2**, wherein the at least one radiographic identifier is positioned on at least one of the plurality of commissure posts.

10. The method of claim **9**, wherein at least one of the plurality of commissure posts includes an opening and the radiographic identifier is positioned adjacent the opening.

11. The method of claim **10**, wherein the opening is a reflection-symmetric shape.

12. The method of claim **2**, wherein at least one of the plurality of commissural posts is shaped so as to define both reflection asymmetrical radiographic identifier and a reflection-symmetric shape.

13. The method of claim **1**, wherein the radiographic identifier is shaped like a letter of the alphabet.

14. The method of claim **1**, wherein the radiographic identifier is shaped like a number.

16

15. The method of claim **1**, wherein the radiographic identifier is a slit.

16. The method of claim **1**, wherein the radiographic identifier is shaped to be reflection-asymmetric about a longitudinal axis which is generally parallel with a central longitudinal axis of the valve prosthesis when the valve prosthesis assumes the collapsed configuration.

17. The method of claim **1**, wherein the radiographic identifier has a shape of a reflection-asymmetric character.

18. The method of claim **1**, wherein the valve prosthesis includes a frame, wherein the radiographic identifier comprises a material having a first radiopacity that is different from a second radiopacity of the frame, which material is coupled to the frame.

19. The method of claim **1**, wherein the valve prosthesis includes a frame, wherein at least a portion of the frame is shaped so as to define both reflection asymmetrical radiographic identifier and a reflection-symmetric shape.

20. The method of claim **1**, wherein the valve prosthesis includes a frame, wherein at least a portion of the frame includes an opening that serves as the at least one radiographic identifier.

* * * * *