



US010821231B2

(12) **United States Patent**
Veasey et al.

(10) **Patent No.:** **US 10,821,231 B2**
(45) **Date of Patent:** ***Nov. 3, 2020**

(54) **PEN-TYPE INJECTOR**

(71) Applicant: **Sanofi-Aventis Deutschland GMBH**,
Frankfurt am Main (DE)

(72) Inventors: **Robert Frederick Veasey**,
Warwickshire (GB); **Robert Perkins**,
Oxfordshire (GB); **David Aubrey**
Plumtre, Worcestershire (GB)

(73) Assignee: **Sanofi-Aventis Deutschland GMBH**,
Frankfurt am Main (DE)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **16/385,682**

(22) Filed: **Apr. 16, 2019**

(65) **Prior Publication Data**

US 2019/0240412 A1 Aug. 8, 2019

Related U.S. Application Data

(60) Continuation of application No. 15/681,604, filed on
Aug. 21, 2017, which is a continuation of application
(Continued)

(30) **Foreign Application Priority Data**

Mar. 3, 2003 (GB) 0304822.0

(51) **Int. Cl.**

A61M 5/24 (2006.01)
A61M 5/315 (2006.01)
A61M 5/32 (2006.01)
A61M 5/31 (2006.01)

(52) **U.S. Cl.**

CPC *A61M 5/24* (2013.01); *A61M 5/3157*
(2013.01); *A61M 5/31528* (2013.01);
(Continued)

(58) **Field of Classification Search**

CPC .. *A61M 5/31551*; *A61M 5/20*; *A61M 5/2033*;
A61M 5/31553; *A61M 5/24*;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

533,575 A 2/1895 Wilkens
2,444,570 A 7/1948 Lawrence
(Continued)

FOREIGN PATENT DOCUMENTS

CA 2138528 12/1998
CA 2359375 7/2000
(Continued)

OTHER PUBLICATIONS

“Pen-injectors for medical use—Part 1: Pen-injectors—
Requirements and test methods,” International Standard, reference
No. ISO 11608-1:2000(E), first edition Dec. 15, 2000, 32 pages.
(Continued)



Primary Examiner — Manuel A Mendez

(74) *Attorney, Agent, or Firm* — Fish & Richardson P.C.

(57) **ABSTRACT**

The present invention relates to injectors, such as pen-type
injectors, that provide for administration of medicinal prod-
ucts from a multidose-cartridge and permit a user to set the
delivery dose. The injector may include a housing, a piston
rod adapted to operate through the housing, a dose dial
sleeve located between the housing and the piston rod, and
a drive sleeve located between the dose dial sleeve and the
piston rod. The dose dial sleeve may have a helical thread of
first lead and the drive sleeve may have a helical groove of
second lead. The first lead of the helical thread and the
second lead of the helical groove may be the same.

37 Claims, 7 Drawing Sheets



Related U.S. Application Data

No. 15/180,141, filed on Jun. 13, 2016, now Pat. No. 9,775,954, which is a continuation of application No. 14/946,203, filed on Nov. 19, 2015, now Pat. No. 9,408,979, which is a continuation of application No. 14/635,573, filed on Mar. 2, 2015, now Pat. No. 9,233,211, which is a continuation of application No. 13/919,251, filed on Jun. 17, 2013, now Pat. No. 9,011,391, which is a division of application No. 13/040,198, filed on Mar. 3, 2011, now Pat. No. 8,512,297, which is a continuation of application No. 11/483,546, filed on Jul. 11, 2006, now Pat. No. 7,918,833, which is a continuation of application No. 10/790,255, filed on Mar. 2, 2004, now abandoned.

(52) **U.S. Cl.**

CPC *A61M 5/31533* (2013.01); *A61M 5/31535* (2013.01); *A61M 5/31536* (2013.01); *A61M 5/31541* (2013.01); *A61M 5/31546* (2013.01); *A61M 5/31551* (2013.01); *A61M 5/31563* (2013.01); *A61M 5/31568* (2013.01); *A61M 5/31585* (2013.01); *A61M 5/31593* (2013.01); *A61M 5/32* (2013.01); *A61M 5/3156* (2013.01); *A61M 5/31565* (2013.01); *A61M 5/31575* (2013.01); *A61M 5/31578* (2013.01); *A61M 2005/2407* (2013.01); *A61M 2005/3126* (2013.01); *A61M 2205/581* (2013.01); *A61M 2205/582* (2013.01)

(58) **Field of Classification Search**

CPC *A61M 5/3158*; *A61M 5/31585*; *A61M 5/31541*; *A61M 5/31535*; *A61M 5/3155*; *A61M 5/31525*; *A61M 5/31568*; *A61M 5/31583*; *A61M 5/31543*; *A61M 5/31536*; *A61M 5/3202*; *A61M 5/2448*; *A61M 5/3157*; *A61M 5/31511*; *A61M 5/31501*; *A61M 5/31528*; *A61M 5/30*; *A61M 5/315*; *A61M 5/31586*; *A61M 5/31593*; *A61M 5/3156*

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,717,597 A 9/1955 Hein, Jr.
 2,722,931 A 11/1955 May
 3,815,785 A 6/1974 Gilmont
 4,083,288 A 4/1978 Williams
 4,470,317 A 9/1984 Sabloewski et al.
 4,498,904 A 2/1985 Turner et al.
 4,568,335 A 2/1986 Updike et al.
 4,585,439 A 4/1986 Michel
 4,592,745 A 6/1986 Rex et al.
 4,833,379 A 5/1989 Kaibel et al.
 4,863,072 A 9/1989 Perler
 4,865,591 A 9/1989 Sams
 4,883,472 A 11/1989 Michel
 4,919,596 A 4/1990 Slate et al.
 4,936,833 A 6/1990 Sams
 4,973,318 A 11/1990 Holm et al.
 4,994,033 A 2/1991 Shockey et al.
 5,000,650 A 3/1991 Brewer et al.
 5,019,190 A 5/1991 Simon et al.
 5,030,209 A 7/1991 Wanderer et al.
 5,092,842 A 3/1992 Bechtold et al.
 5,112,317 A 5/1992 Michel
 5,207,752 A 5/1993 Sorenson et al.
 5,226,895 A 7/1993 Harris
 5,226,896 A 7/1993 Harris

5,246,417 A 9/1993 Haak et al.
 5,257,987 A 11/1993 Athayde et al.
 5,271,527 A 12/1993 Haber et al.
 5,279,585 A 1/1994 Balkwill
 5,279,586 A 1/1994 Balkwill
 5,281,198 A 1/1994 Haber et al.
 5,284,480 A 2/1994 Porter et al.
 5,304,152 A 4/1994 Sams
 5,308,340 A 5/1994 Harris
 5,314,412 A 5/1994 Rex
 5,318,540 A 6/1994 Athayde et al.
 5,320,609 A 6/1994 Haber et al.
 5,328,486 A 7/1994 Noodroff
 5,331,954 A 7/1994 Rex et al.
 5,370,629 A 12/1994 Michel et al.
 5,378,233 A 1/1995 Haber et al.
 5,380,297 A 1/1995 Nadman et al.
 5,383,865 A 1/1995 Michel
 5,391,157 A 2/1995 Harris et al.
 5,440,976 A 8/1995 Giuliano et al.
 5,445,606 A 8/1995 Haak et al.
 5,447,150 A 9/1995 Bacon
 5,478,316 A 12/1995 Bitdinger et al.
 5,478,324 A 12/1995 Meyer
 5,480,387 A 1/1996 Gabriel et al.
 5,492,534 A 2/1996 Athayde et al.
 5,505,704 A 4/1996 Dawelka et al.
 5,545,147 A 8/1996 Harris
 5,546,932 A 8/1996 Salli
 5,547,131 A 8/1996 Brace
 5,549,574 A 8/1996 Townsend
 5,549,575 A 8/1996 Giambattista et al.
 5,582,598 A 12/1996 Chanoch
 5,584,815 A 12/1996 Pawelka et al.
 5,591,135 A 1/1997 Gabriel
 5,591,136 A 1/1997 Gabriel
 5,599,314 A 2/1997 Neill
 5,611,783 A 3/1997 Mikkelsen
 5,626,566 A 5/1997 Peterson et al.
 5,645,052 A 7/1997 Kersey
 5,674,204 A 10/1997 Chanoch
 5,679,111 A 10/1997 Hjertman et al.
 5,681,285 A 10/1997 Ford et al.
 5,685,864 A 11/1997 Shanley et al.
 5,688,251 A 11/1997 Chanoch
 5,693,027 A 12/1997 Hansen et al.
 5,709,662 A 1/1998 Olive et al.
 5,716,990 A 2/1998 Bagshawe et al.
 5,725,508 A 3/1998 Chanoch et al.
 5,728,074 A 3/1998 Castellano et al.
 5,728,075 A 3/1998 Evander
 5,743,889 A 4/1998 Sams
 5,755,692 A 5/1998 Maincom
 5,807,346 A 9/1998 Frezza
 5,820,602 A 10/1998 Kovelman et al.
 5,823,998 A 10/1998 Yamagata
 5,827,232 A 10/1998 Chanoch et al.
 5,843,036 A 12/1998 Olive et al.
 5,851,079 A 12/1998 Horstman et al.
 5,882,718 A 3/1999 Pommer et al.
 5,898,028 A 4/1999 Jensen et al.
 5,921,966 A 7/1999 Bendek et al.
 5,928,201 A 7/1999 Poulsen et al.
 5,938,642 A 8/1999 Burroughs et al.
 5,947,934 A 9/1999 Hansen et al.
 5,951,530 A 9/1999 Steengaard et al.
 5,954,689 A 9/1999 Poulsen
 5,957,896 A 9/1999 Bendek et al.
 5,961,495 A 10/1999 Nalters et al.
 5,961,496 A 10/1999 Nielsen et al.
 5,980,491 A 11/1999 Hansen
 5,984,900 A 11/1999 Mikkelsen
 6,001,089 A 12/1999 Burroughs et al.
 6,003,736 A 12/1999 Ljunggren
 6,004,297 A 12/1999 Steinfeldt-Jensen et al.
 6,010,485 A 1/2000 Buch-Rasmussen et al.
 6,033,376 A 3/2000 Reckley

(56)

References Cited

U.S. PATENT DOCUMENTS

6,033,377	A	3/2000	Rasmussen et al.	7,678,085	B2	3/2010	Graf	
6,048,336	A	4/2000	Gabriel	7,736,343	B2	6/2010	Marshall et al.	
6,059,755	A	5/2000	Michel	7,771,400	B2	8/2010	Neilsen	
6,074,372	A	6/2000	Hansen	RE41,956	E	11/2010	Klitgaard et al.	
6,083,197	A	7/2000	Umbaugh	7,850,662	B2	12/2010	Veasey et al.	
6,086,567	A	7/2000	Kirchhofer et al.	7,905,867	B2	3/2011	Veasey et al.	
6,096,010	A	8/2000	Nalters et al.	7,918,833	B2 *	4/2011	Veasey	A61M 5/24 604/209
6,110,149	A	8/2000	Klitgaard et al.	7,935,088	B2	5/2011	Veasey et al.	
6,129,080	A	10/2000	Pitcher et al.	8,021,345	B2	9/2011	Veasey et al.	
6,146,361	A	11/2000	DiBiasi et al.	8,187,233	B2	5/2012	Harms et al.	
6,193,698	B1	2/2001	Kirchhofer et al.	8,197,450	B2	6/2012	Glejbol et al.	
6,221,046	B1 *	4/2001	Burroughs A61M 5/31551 604/153	8,257,319	B2	9/2012	Plumptre	
6,221,053	B1	4/2001	Nalters et al.	RE43,834	E	11/2012	Steenfeldt-Jensen et al.	
6,231,540	B1	5/2001	Smedegaard	8,444,606	B2	5/2013	Radmer et al.	
6,235,004	B1 *	5/2001	Steenfeldt-Jensen A61M 5/31551 604/207	8,512,297	B2	8/2013	Veasey et al.	
6,248,090	B1	6/2001	Jensen et al.	8,556,864	B2	10/2013	Veasey et al.	
6,248,095	B1	6/2001	Giambattista et al.	8,603,044	B2	12/2013	Veasey et al.	
6,258,062	B1	7/2001	Thielen et al.	8,608,709	B2	12/2013	Veasey et al.	
6,269,340	B1	7/2001	Ford et al.	8,663,175	B2	3/2014	Veasey et al.	
6,277,097	B1	8/2001	Mikkelsen et al.	8,672,896	B2	3/2014	Plumptre	
6,277,098	B1	8/2001	Klitmose et al.	8,679,069	B2	3/2014	Veasey et al.	
6,277,099	B1	8/2001	Strowe et al.	8,876,782	B2	11/2014	Veasey et al.	
6,277,101	B1	8/2001	Kirchhofer et al.	8,992,486	B2	3/2015	Veasey et al.	
6,281,225	B1	8/2001	Hearst et al.	9,011,391	B2	4/2015	Veasey et al.	
6,283,941	B1	9/2001	Schoenfeld et al.	9,022,991	B2	5/2015	Moeller	
6,302,869	B1	10/2001	Klitgaard	9,028,454	B2	5/2015	Veasey et al.	
6,287,283	B1	11/2001	Ljunggreen et al.	9,205,197	B2	12/2015	Dette et al.	
6,312,413	B1	11/2001	Jensen et al.	9,233,211	B2	1/2016	Veasey et al.	
6,340,357	B1	1/2002	Poulsen et al.	9,408,979	B2	8/2016	Veasey et al.	
6,379,399	B1	4/2002	Klitgaard et al.	9,526,844	B2	12/2016	Veasey et al.	
6,383,167	B2	5/2002	Kirchhofer et al.	9,533,105	B2	1/2017	Veasey et al.	
6,514,230	B1	2/2003	Munk et al.	9,561,331	B2	2/2017	Veasey et al.	
6,547,763	B2	4/2003	Steenfeldt-Jensen et al.	9,604,008	B2	3/2017	Veasey et al.	
6,547,764	B2	4/2003	Larsen et al.	9,604,009	B2	4/2017	Veasey et al.	
6,562,006	B1	5/2003	Hjertman et al.	9,610,409	B2	4/2017	Veasey et al.	
6,562,011	B1	5/2003	Buch-Rasmussen et al.	9,623,189	B2	4/2017	Veasey et al.	
6,569,126	B1	5/2003	Poulsen et al.	9,623,190	B2	4/2017	Veasey et al.	
6,582,404	B1	6/2003	Klitgaard et al.	9,775,954	B2	10/2017	Veasey et al.	
6,605,067	B1	8/2003	Larsen	9,827,379	B2	11/2017	Veasey et al.	
6,613,019	B2	9/2003	Munk	2001/0034507	A1	10/2001	Kirchhofer et al.	
6,613,023	B2	9/2003	Kirchhofer et al.	2002/0007154	A1	1/2002	Hansen et al.	
6,663,602	B2	12/2003	Miller	2002/0052578	A1 *	5/2002	Moller A61M 5/24 604/208	
6,692,472	B2	2/2004	Hansen et al.	2002/0053578	A1	5/2002	Iwamoto et al.	
6,699,224	B2	3/2004	Kirchhofer et al.	2002/0077852	A1	6/2002	Ford et al.	
6,716,198	B2	4/2004	Larsen	2002/0120235	A1	8/2002	Enggaard	
6,726,661	B2	4/2004	Munk et al.	2002/0165499	A1	11/2002	Slate et al.	
6,770,288	B2	8/2004	Duirs	2003/0039679	A1	2/2003	Duirs	
6,796,970	B1	9/2004	Klitmose et al.	2003/0050609	A1	3/2003	Sams	
6,893,415	B2	5/2005	Madsen et al.	2003/0172924	A1	9/2003	Staniforth et al.	
6,899,698	B2	5/2005	Sams	2004/0026728	A1	2/2004	Yoshida et al.	
6,899,699	B2	5/2005	Enggaard	2004/0059299	A1	3/2004	Moller et al.	
6,921,995	B2	7/2005	Nishimura et al.	2004/0097883	A1	5/2004	Roe	
6,932,794	B2	8/2005	Giambattista et al.	2004/0127858	A1	7/2004	Bendek et al.	
6,936,032	B1	8/2005	Bush, Jr. et al.	2004/0186431	A1	9/2004	Graf et al.	
6,945,961	B2	9/2005	Miller et al.	2004/0210199	A1	10/2004	Atterbury et al.	
7,008,399	B2	3/2006	Larsen et al.	2004/0236282	A1	11/2004	Braithwaite	
7,090,662	B2	8/2006	Nimpenny et al.	2004/0249348	A1	12/2004	Nimpenny et al.	
7,094,221	B2	8/2006	Veasey et al.	2004/0260247	A1	12/2004	Veasey et al.	
7,104,972	B2	9/2006	Moller et al.	2004/0267207	A1	12/2004	Veasey et al.	
7,133,329	B2	11/2006	Skyggebjerg et al.	2004/0267208	A1	12/2004	Veasey et al.	
D533,575	S	12/2006	Reawsanguanwong et al.	2005/0004529	A1	1/2005	Veasey et al.	
7,169,132	B2	1/2007	Bendek et al.	2005/0019400	A1	1/2005	Deveney et al.	
7,175,055	B2	2/2007	Hansen et al.	2005/0033244	A1	2/2005	Veasey et al.	
7,195,616	B2	3/2007	Diller et al.	2005/0055011	A1	3/2005	Enggaard	
7,241,278	B2	7/2007	Moller	2005/0113765	A1	5/2005	Veasey et al.	
7,291,132	B2	11/2007	DeRuntz et al.	2005/0205083	A1	9/2005	Staniforth et al.	
7,316,670	B2	1/2008	Graf et al.	2005/0209570	A1	9/2005	Moller	
7,361,161	B2	4/2008	Bainton	2005/0268915	A1	12/2005	Nassenaar et al.	
7,553,299	B2	6/2009	Veasey et al.	2006/0153693	A1	7/2006	Fiechter et al.	
7,678,084	B2	3/2010	Judson et al.	2006/0206057	A1	9/2006	DeRuntz et al.	
				2006/0264839	A1	11/2006	Veasey et al.	
				2007/0016143	A1	1/2007	Miller et al.	
				2007/0093761	A1	4/2007	Veasey et al.	
				2007/0123829	A1	5/2007	Atterbury et al.	
				2009/0275916	A1	11/2009	Harms et al.	

(56)

References Cited

U.S. PATENT DOCUMENTS

2010/0042054	A1	2/2010	Elahi et al.
2012/0053528	A1	3/2012	Bollenbach et al.
2015/0224266	A1	8/2015	Plumptre et al.
2017/0340832	A1	11/2017	Veasey et al.
2018/0036483	A1	2/2018	Veasey et al.
2019/0240412	A1	8/2019	Veasey et al.

FOREIGN PATENT DOCUMENTS

DE	3609555		9/1987	
DE	10237258		3/2004	
EP	0583291		12/1986	
EP	0295075		12/1988	
EP	0327910		8/1989	
EP	0359070		3/1990	
EP	0450905		10/1991	
EP	0496141		7/1992	
EP	0498737		8/1992	
EP	0554996		8/1993	
EP	0594349		4/1994	
EP	0667469		8/1995	
EP	0702970		3/1996	
EP	0608343		12/1997	
EP	0673482		4/1998	
EP	0879610		11/1998	
EP	0897729		2/1999	
EP	0937471		8/1999	
EP	0937476		8/1999	
EP	0937477		8/1999	
EP	1250167		7/2005	
EP	1294418		7/2005	
EP	1570876		9/2005	
EP	1776975		4/2007	
EP	1855743		12/2008	
FR	2583291		12/1986	
FR	2583291	A1 *	12/1986 A61M 5/20
FR	2767479		2/1999	
GB	1232899		5/1971	
GB	2064012		6/1981	
GB	2141799		1/1985	
GB	0735433		8/1995	
GB	2384431		7/2003	
GB	2384431	A *	7/2003 A61M 5/30
JP	05-337179		12/1993	
JP	06-296691		10/1994	
RU	2111019		5/1998	
WO	WO 89/07463		8/1989	
WO	WO 1990/09202		8/1990	
WO	WO 1991/10460		7/1991	
WO	WO 1991/14467		10/1991	
WO	WO 93/07922		4/1993	
WO	WO 93/24160		12/1993	
WO	WO 94/19034		9/1994	
WO	WO 96/25965		8/1996	
WO	WO 1996/26754		9/1996	
WO	WO 96/38190		12/1996	
WO	WO 97/36626		10/1997	
WO	WO 98/10813		3/1998	
WO	WO 1998/57688		12/1998	
WO	WO 9856436		12/1998	
WO	WO 1999/16487		4/1999	
WO	WO 99/38554		8/1999	
WO	WO 1999/38554		8/1999	
WO	WO 2001/10484		7/2000	
WO	WO 01/19434		3/2001	
WO	WO 2011/051366		5/2001	
WO	WO 01/83008		11/2001	
WO	WO 02/30495		4/2002	
WO	WO 02/053214		7/2002	
WO	WO 02/092153		11/2002	
WO	WO 2002/092153		11/2002	
WO	WO 03/080160		10/2003	
WO	WO 2006/084876		8/2006	

OTHER PUBLICATIONS

English Translation of Abstract of European Patent Application No. 0359070 dated Dec. 15, 2016.

First Office Action on merits dated Mar. 14, 2006 in U.S. Appl. No. 101790,866 (11 pages).

Reissue U.S. Appl. No. 10/442,855, "Injection Syringe", filed May 21, 2003.

Reissue U.S. Appl. No. 10/960,900, "Injection Syringe", filed Oct. 7, 2004.

Reissue U.S. Appl. No. 11/121,331, "Injection Syringe", filed May 3, 2005.

Reissue U.S. Appl. No. 11/640,610, "Injection Syringe", filed Dec. 18, 2006.

"British Standard Specification for Spring Washers for General Engineering and Automobile Purposes—Metric Series," British Standards Institution, BS 4464, May 19, 1969, 14 pages.

Deposition of Andreas Bode, *Sanofi-Aventis U.S. LLC v. Mylan N. V.*, May 3, 2019 (excerpts concerning Novo FlexPen).

Deposition of David A. Plumptre, *Sanofi-Aventis U.S. LLC v. Mylan N. V.*, Apr. 26, 2019 (excerpts).

A. G. Erdman & G. N. Sandor, "Mechanical Advantage", §3.7 in 1 Mechanism Design: Analysis and Synthesis (1984).

Flexpen—Assembly study Presented by DCA Design International to Aventis as part of HM26 Stage 5 on Nov. 8, 2002, 5 pages.

Flexpen—Component details and proposed assembly sequence, 6 pages.

FlexPen—Novo Nordisk, 1 page.

Novo Nordisk A/S, Annual Financial Report 2003 obtained from https://www.marketscreener.com/NOVO-NORDISK-AS-1412980/pdf/9923/Novo%20Nordisk%20AS_Annual-Report.pdf.

Sclater et al., "Mechanisms & Mechanical Devices Sourcebook, Twenty Screw Devices" Third Edition, pp. 191-195, Jul. 2, 2001.

Mylan Pharmaceuticals Inc., v. Sanofi-Aventis Deutschland GmbH, "Preliminary Guidance Patent Owners Motion to Amend," Case No. IPR2018-01679, U.S. Pat. No. 8,992,486 B2, entered Oct. 16, 2019, 11 pages.

Mylan Pharmaceuticals Inc., v. Sanofi-Aventis Deutschland GmbH, "Preliminary Guidance Patent Owner's Motion to Amend," Case No. IPR2018-01680, U.S. Pat. No. 9,526,844 B2, entered Oct. 16, 2019, 11 pages.

Mylan Pharmaceuticals Inc., v. Sanofi-Aventis Deutschland GmbH, "Preliminary Guidance Patent Owner's Motion to Amend," Case No. IPR2018-01682, U.S. Pat. No. 9,526,844, entered Oct. 16, 2019, 11 pages.

Opinion dated Mar. 9, 2020, *Sanofi-Aventis U.S. LLC v. Mylan GmbH*, United States District Court, District of New Jersey, (SRC).

Mylan Pharmaceuticals Inc., v. Sanofi-Aventis Deutschland GmbH, "Final Written Decision Determining Sole Challenged Claim Unpatentable Denying Petitioner's Motion to Exclude," U.S. Pat. No. 8,679,069 B2, entered Apr. 2, 2020, 108 pages.

Mylan Pharmaceuticals Inc., v. Sanofi-Aventis Deutschland GmbH, "Final Written Decision Determining All Challenged Claims Unpatentable Denying Patent Owner's Motion To Amend Denying-in-Part, Dismissing-in-Part Petitioner's Motion to Exclude," Case No. IPR2018-01679, U.S. Pat. No. 8,992,486, entered May 29, 2020, 117 pages.

Mylan Pharmaceuticals Inc., v. Sanofi-Aventis Deutschland GmbH, "Final Written Decision Determining All Challenged Claims Unpatentable Denying Petitioner's Motion to Amend Denying Petitioner's Motion to Exclude," Case No. IPR2018-01680, U.S. Pat. No. 9,526,844 B2, entered May 29, 2020, 131 pages.

Mylan Pharmaceuticals Inc., v. Sanofi-Aventis Deutschland GmbH, "Final Written Decision Determining All Challenged Claims Unpatentable Denying Petitioner's Motion to Amend Denying Petitioner's Motion to Exclude," Case No. IPR2018-01682, U.S. Pat. No. 9,526,844 B2, entered May 29, 2020, 135 pages.

Mylan Pharmaceuticals Inc., v. Sanofi-Aventis Deutschland GmbH, "Final Written Decision Determining All Challenged Claims Unpatentable Denying Petitioner's Motion to Exclude," Case No. IPR2018-00122, U.S. Pat. No. 8,992,486 B2, entered May 29, 2020, 73 pages.

(56)

References Cited

OTHER PUBLICATIONS

Mylan Pharmaceuticals Inc., v. Sanofi-Aventis Deutschland GmbH, “Final Written Decision Determining All Challenged Claims Unpatentable Denying Petitioner’s Motion to Exclude,” Case No. IPR2018-01676, U.S. Pat. No. 8,603,044 B2, entered May 29, 2020, 59 pages.

Mylan Pharmaceuticals Inc., v. Sanofi-Aventis Deutschland GmbH, “Final Written Decision Determining Claims 1, 7, 8, and 17 are Unpatentable Denying Petitioner’s Motion To Exclude,” Case No. IPR2018-01684, U.S. Pat. No. 9,604,008 B2, entered May 29, 2020, 67 pages.

Mylan Pharmaceuticals Inc., v. Sanofi-Aventis Deutschland GmbH, “Final Written Decision Determining All Challenged Claims Unpatentable Denying Petitioner’s Motion to Exclude,” Case No. IPR2018-01675, U.S. Pat. No. 8,603,044 B2, entered May 29, 2020, 66 pages.

Pfizer Inc., v. Sanofi-Aventis Deutschland GmbH, “Final Written Decision Determining All Challenged Claims Unpatentable Denying Petitioner’s Motion to Exclude,” Case No. IPR2019-00979, U.S. Pat. No. 8,679,069, entered Aug. 11, 2020, 108 pages.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11






FIG. 14




FIG. 15




FIG. 16

PEN-TYPE INJECTOR**CROSS REFERENCE TO RELATED APPLICATIONS**

The present application is a continuation of U.S. patent application Ser. No. 15/681,604, filed Aug. 21, 2017, which is a continuation of U.S. patent application Ser. No. 15/180,141, filed Jun. 13, 2016, now U.S. Pat. No. 9,775,954, which is a continuation of U.S. patent application Ser. No. 14/946,203, filed Nov. 19, 2015, now U.S. Pat. No. 9,408,979, which is a continuation of U.S. patent application Ser. No. 14/635,573, filed Mar. 2, 2015, now U.S. Pat. No. 9,233,211, which is a continuation of U.S. patent application Ser. No. 13/919,251, filed Jun. 17, 2013, now U.S. Pat. No. 9,011,391, which is a divisional of U.S. patent application Ser. No. 13/040,198, filed Mar. 3, 2011, now U.S. Pat. No. 8,512,297, which is a continuation of U.S. patent application Ser. No. 11/483,546, filed Jul. 11, 2006, now U.S. Pat. No. 7,918,833, which is a continuation of U.S. patent application Ser. No. 10/790,225, filed Mar. 2, 2004, which claims priority to GB 0304822.0, filed Mar. 3, 2003, the entire contents of which are incorporated herein by reference.

BACKGROUND

The present invention relates to pen-type injectors, that is, to injectors of the kind that provide for administration by injection of medicinal products from a multidose cartridge. In particular, the present invention relates to such injectors where a user may set the dose.

Such injectors have application where regular injection by persons without formal medical training occurs. This is increasingly common amongst those having diabetes where self-treatment enables such persons to conduct effective management of their diabetes.

These circumstances set a number of requirements for pen-type injectors of this kind. The injector must be robust in construction, yet easy to use both in terms of the manipulation of the parts and understanding by a user of its operation. In the case of those with diabetes, many users will be physically infirm and may also have impaired vision. Where the injector is to be disposable rather than reusable, the injector should be cheap to manufacture and easy to dispose of (preferably being suitable for recycling).

SUMMARY

It is an advantage of the present invention that an improved pen-type injector is provided.

According to a first aspect of the present invention, a pen-type injector comprises

- a housing;
- a piston rod adapted to operate through housing;
- a dose dial sleeve located between the housing and the piston rod, the dose dial sleeve having a helical thread of first lead;

- a drive sleeve located between the dose dial sleeve and the piston rod, the drive sleeve having a helical groove of second lead;

- characterized in that the first lead of the helical thread and the second lead of the helical groove are the same.

Preferably, the piston rod has a first threaded portion at a first end and a second threaded portion at a second end;

- an insert or radially inwardly extending flange is located in the housing and through which the first threaded portion of the piston rod may rotate;

- the dose dial sleeve being rotatable with respect to the housing and the insert;

- the drive sleeve being releasably connected to the dose dial sleeve and connected to the piston rod for rotation with respect thereto along the second threaded portion of the piston rod;

- a button is located on the dose dial sleeve and rotatable with respect to the dose dial sleeve; and

- clutch means are provided which upon depression of the button permit rotation between the dose dial sleeve and the drive sleeve.

Preferably, the injector further comprises a nut which is rotatable with respect to the drive sleeve and axially displaceable but not rotatable with respect to the housing.

More preferably, the drive sleeve is provided at a first end with first and second flanges with an intermediate thread between the first and second flanges, the nut being disposed between the first and second flanges and keyed to the housing by spline means. Additionally, a first radial stop may be provided on a second face of the nut and a second radial stop may be provided on a first face of the second flange.

Preferably, the first thread of the piston rod is oppositely disposed to the second thread of the piston rod.

Preferably, a second end of the clutch is provided with a plurality of dog teeth adapted to engage with a second end of the dose dial sleeve.

Preferably, the pen-type injector further includes clicker means disposed between the clutch means and spline means provided on the housing.

More preferably, the clicker means comprises a sleeve provided at a first end with a helically extending arm, a free end of the arm having a toothed member, and at a second end with a plurality of circumferentially directed saw teeth adapted to engage a corresponding plurality of circumferentially directed saw teeth provided on the clutch means.

Alternatively, the clicker means comprises a sleeve provided at a first end with at least one helically extending arm and at least one spring member, a free end of the arm having a toothed member, and at a second end with a plurality of circumferentially directed saw teeth adapted to engage a corresponding plurality of circumferentially directed saw teeth provided on the clutch means.

Preferably, the main housing is provided with a plurality of maximum dose stops adapted to be abutted by a radial stop provided on the dose dial sleeve. More preferably, at least one of the maximum dose stops comprises a radial stop located between a helical rib and spline means provided at a second end of the housing. Alternatively, at least one of the maximum dose stops comprises a part of a raised window portion provided at a second end of the housing.

Preferably, the dose dial sleeve is provided with a plurality of radially extending members adapted to abut a corresponding plurality of radial stops provided at a second end of the housing.

BRIEF DESCRIPTION OF THE FIGURES

The invention will now be described with reference to the accompanying drawings in which:

FIG. 1 shows a sectional view of a pen-type injector in accordance with the present invention in a first, cartridge full, position;

FIG. 2 shows a sectional view of the pen-type injector of FIG. 1 in a second, maximum first dose dialed, position;

3

FIG. 3 shows a sectional view of the pen-type injector of FIG. 1 in a third, first maximum first dose dispensed, position;

FIG. 4 shows a sectional view of the pen-type injector of FIG. 1 in a fourth, final dose dialed, position;

FIG. 5 shows a sectional view of the pen-type injector of FIG. 1 in a fifth, final dose dispensed, position;

FIG. 6 shows a cut-away view of a first detail of the pen-type injector of FIG. 1;

FIG. 7 shows a partially cut-away view of a second detail of the pen-type injector of FIG. 1;

FIG. 8 shows a partially cut-away view of a third detail of the pen-type injector of FIG. 1;

FIG. 9 shows the relative movement of parts of the pen-type injector shown in FIG. 1 during dialing up of a dose;

FIG. 10 shows the relative movement of parts of the pen-type injector shown in FIG. 1 during dialing down of a dose;

FIG. 11 shows the relative movement of parts of the pen-type injector shown in FIG. 1 during dispensing of a dose;

FIG. 12 shows a partially cut-away view of the pen-type injector of FIG. 1 in the second, maximum first dose dialed, position;

FIG. 13 shows a partially cut-away view of the pen-type injector of FIG. 1 in the fourth, final dose dialed, position;

FIG. 14 shows a partially cut-away view of the pen-type injector of FIG. 1 in one of the first, third or fifth positions;

FIG. 15 shows a cut-away view of a first part of a main housing of the pen-type injector of FIG. 1; and

FIG. 16 shows a cut-away view of a second part of the main housing of the pen-type injector of FIG. 1.

DETAILED DESCRIPTION

Referring first to FIGS. 1 to 5, there may be seen a pen-type injector in accordance with the present invention in a number of positions.

The pen-type injector comprises a housing having a first cartridge retaining part 2, and second main housing part 4. A first end of the cartridge retaining means 2 and a second end of the main housing 4 are secured together by retaining features 6. In the illustrated embodiment, the cartridge retaining means 2 is secured within the second end of the main housing 4.

A cartridge 8 from which a number of doses of medicinal product may be dispensed is provided in the cartridge retaining part 2. A piston 10 is retained in a first end of the cartridge 8.

A removable cap 12 is releasably retained over a second end of the cartridge retaining part 2. In use the removable cap 12 can be replaced by a user with a suitable needle unit (not shown). A replaceable cap 14 is used to cover the cartridge retaining part 2 extending from the main housing 4. Preferably, the outer dimensions of the replaceable cap 14 are similar or identical to the outer dimensions of the main housing 4 to provide the impression of a unitary whole when the replaceable cap 14 is in position covering the cartridge retaining part 2.

In the illustrated embodiment, an insert 16 is provided at a first end of the main housing 4. The insert 16 is secured against rotational or longitudinal motion. The insert 16 is provided with a threaded circular opening 18 extending therethrough. Alternatively, the insert may be formed integrally with the main housing 4 the form of a radially inwardly directed flange having an internal thread.

4

A first thread 19 extends from a first end of a piston rod 20. The piston rod 20 is of generally circular section. The first end of the piston rod 20 extends through the threaded opening 18 in the insert 16. A pressure foot 22 is located at the first end of the piston rod 20. The pressure foot 22 is disposed to abut a second end of the cartridge piston 10. A second thread 24 extends from a second end of the piston rod 20. In the illustrated embodiment the second thread 24 comprises a series of part threads rather than a complete thread. The illustrated embodiment is easier to manufacture and helps reduce the overall force required for a user to cause medicinal product to be dispensed.

The first thread 19 and the second thread 24 are oppositely disposed. The second end of the piston rod 20 is provided with a receiving recess 26.

A drive sleeve 30 extends about the piston rod 20. The drive sleeve 30 is generally cylindrical. The drive sleeve 30 is provided at a first end with a first radially extending flange 32. A second radially extending flange 34 is provided spaced a distance along the drive sleeve 30 from the first flange 32. An intermediate thread 36 is provided on an outer part of the drive sleeve 30 extending between the first flange 32 and the second flange 34. A helical groove 38 extends along the internal surface of the drive sleeve 30. The second thread 24 of the piston rod 20 is adapted to work within the helical groove 38.

A first end of the first flange 32 is adapted to conform to a second side of the insert 16.

A nut 40 is located between the drive sleeve 30 and the main housing 2, disposed between the first flange 32 and the second flange 34. In the illustrated embodiment the nut 40 is a half-nut. This assists in the assembly of the injector. The nut 40 has an internal thread matching the intermediate thread 36. The outer surface of the nut 40 and an internal surface of the main housing 4 are keyed together by splines 42 (see FIGS. 10, 11, 15 and 16) to prevent relative rotation between the nut 40 and the main housing 4, while allowing relative longitudinal movement therebetween.

A shoulder 37 is formed between a second end of the drive sleeve 30 and an extension 38 provided at the second end of the drive sleeve 30. The extension 38 has reduced inner and outer diameters in comparison to the remainder of the drive sleeve 30. A second end of the extension 38 is provided with a radially outwardly directed flange 39.

A clicker 50 and a clutch 60 are disposed about the drive sleeve 30, between the drive sleeve 30 and a dose dial sleeve 70 (to be described below).

The clicker 50 is located adjacent the second flange 34 of the drive sleeve 30. The clicker 50 is generally cylindrical and is provided at a first end with a flexible helically extending arm 52 (shown most clearly in FIG. 6). A free end of the arm 52 is provided with a radially directed toothed member 54. A second end of the clicker 50 is provided with a series of circumferentially directed saw teeth 56 (of FIG. 7). Each saw tooth comprises a longitudinally directed surface and an inclined surface.

In an alternative embodiment (not shown) the clicker means further includes at least one spring member. The at least one spring member assists in the resetting of the clutch means 60 following dispense.

The clutch means 60 is located adjacent the second end of the drive sleeve 30. The clutch means 60 is generally cylindrical and is provided at a first end with a series of circumferentially directed saw teeth 66 (see FIG. 7). Each saw tooth comprises a longitudinally directed surface and an inclined surface. Towards the second end 64 of the clutch means 60 there is located a radially inwardly directed flange

5

62. The flange 62 of the clutch means 60 is disposed between the shoulder 37 of the drive sleeve 30 and the radially outwardly directed flange 39 of the extension 38. The second end of the clutch means 60 is provided with a plurality of dog teeth 65 (FIG. 8). The clutch 60 is keyed to the drive sleeve 30 by way of splines (not shown) to prevent relative rotation between the clutch 60 and the drive sleeve 30.

In the illustrated embodiment, the clicker 50 and the clutch 60 each extend approximately half the length of the drive sleeve 30. However, it will be understood that other arrangements regarding the relative lengths of these parts are possible.

The clicker 50 and the clutch means 60 are normally engaged, that is as shown in FIG. 7.

A dose dial sleeve 70 is provided outside of the clicker 50 and clutch means 60 and radially inward of the main housing 4. A helical groove 74 is provided about an outer surface of the dose dial sleeve 70.

The main housing 4 is provided with a window 44 through which a part of the outer surface of the dose dial sleeve may be seen. The main housing 4 is further provided with a helical rib 46, adapted to be seated in the helical groove 74 on the outer surface of the dose dial sleeve 70. The helical rib 46 extends for a single sweep of the inner surface of the main housing 4. A first stop 100 is provided between the splines 42 and the helical rib 46 (FIG. 15). A second stop 102, disposed at an angle of 180° to the first stop 100 is formed by a frame surrounding the window 44 in the main housing 4 (FIG. 16).

Conveniently, a visual indication of the dose that may be dialed, for example reference numerals (not shown) is provided on the outer surface of the dose dial sleeve 70. The Window 44 conveniently only allows to be viewed a visual indication of the dose currently dialed.

A second end of the dose dial sleeve 70 is provided with an inwardly directed flange in the form of number of radially extending members 75. A dose dial grip 76 is disposed about an outer surface of the second end of the dose dial sleeve 70. An outer diameter of the dose dial grip 76 preferably corresponds to the outer diameter of the main housing 4. The dose dial grip 76 is secured to the dose dial sleeve 70 to prevent relative movement therebetween. The dose dial grip 76 is provided with a central opening 78. An annular recess 80 located in the second end of the dose dial grip 76 extends around the opening 78.

A button 82 of generally 'T' section is provided at a second end of the pen-type injector. A stem 84 of the button 82 may extend through the opening 78 in the dose dial grip 76, through the inner diameter of the extension 38 of the drive sleeve 30 and into the receiving recess 26 of the piston rod 20. The stem 84 is retained for limited axial movement in the drive sleeve 30 and against rotation with respect thereto. A head 85 of the button 82 is generally circular. A skirt 86 depends from a periphery of the head 85. The skirt 86 is adapted to be seated in the annular recess 80 of the dose dial grip 76.

Operation of the pen-type injector in accordance with the present invention will now be described. In FIGS. 9, 10 and 11 arrows A, B, C, D, E, F and G represent the respective movements of the button 82, the dose dial grip 76, the dose dial sleeve 70, the drive sleeve 30, the clutch means 60, the clicker 50 and the nut 40.

To dial a dose (FIG. 9) a user rotates the dose dial grip 76 (arrow A). With the clicker 50 and clutch means 60 engaged, the drive sleeve 30, the clicker 50, the clutch means 60 and the dose dial sleeve 70 rotate with the dose dial grip 76.

6

Audible and tactile feedback of the dose being dialed is provided by the clicker 50 and the clutch means 60. Torque is transmitted through the saw teeth 56, 66 between the clicker 50 and the clutch means 60. The flexible arm 52 deforms and drags the toothed member 54 over the splines 42 to produce a click. Preferably, the splines 42 are disposed such that each click corresponds to a unit dose.

The helical groove 74 on the dose dial sleeve 70 and the helical groove 38 in the drive sleeve 30 have the same lead. This allows the dose dial sleeve 70 (arrow C) to extend from the main housing 4 and the drive sleeve 30 (arrow D) to climb the piston rod 20 at the same rate. At the limit of travel, a radial stop 104 on the dose dial sleeve 70 engages either the first stop 100 or the second stop 102 provided on the main housing 4 to prevent further movement. Rotation of the piston rod 20 is prevented due to the opposing directions of the overhauled and driven threads on the piston rod 20.

The nut 40, keyed to the main housing 4, is advanced along the intermediate thread 36 by the rotation of the drive sleeve 30 (arrow D). When the final dose dispensed position (FIGS. 4, 5 and 13) is reached, a radial stop 106 formed on a second surface of the nut 40 abuts a radial stop 108 on a first surface of the second flange 34 of the drive sleeve 30 preventing both the nut 40 and the drive sleeve 30 from rotating further.

In an alternative embodiment (not shown) a first surface of the nut 40 is provided with a radial stop for abutment with a radial stop provided on a second surface of the first flange 32. This aids location of the nut 40 at the cartridge full position during assembly of the pen-type injector.

Should a user inadvertently dial beyond the desired dosage, the pen-type injector allows the dosage to be dialed down without dispense of medicinal product from the cartridge (FIG. 10). The dose dial grip 76 is counter rotated. This causes the system to act in reverse. The flexible arm 52 now acts as a ratchet preventing the clicker from rotating. The torque transmitted through the clutch means 60 causes the saw teeth 56,66 to ride over one another to create the clicks corresponding to dialed dose reduction. Preferably the saw teeth 56,66 are so disposed that the circumferential extent of each saw tooth corresponds to a unit dose.

When the desired dose has been dialed, the user may then dispense this dose by depressing the button 82 (FIG. 11). This displaces the clutch means 60 axially with respect to the dose dial sleeve 70 causing the dog teeth 65 to disengage. However the clutch means 60 remains keyed in rotation to the drive sleeve 30. The dose dial sleeve 70 and associated dose dial grip 76 are now free to rotate (guided by the helical rib 46 located in helical groove 74).

The axial movement deforms the flexible arm 52 of the clicker 50 to ensure the saw teeth 56,66 cannot be overhauled during dispense. This prevents the drive sleeve 30 from rotating with respect to the main housing 4 though it is still free to move axially with respect thereto. This deformation is subsequently used to urge the clicker 50, and the clutch 60, back along the drive sleeve 30 to restore the connection between the clutch 60 and the dose dial sleeve 70 when pressure is removed from the button 82.

The longitudinal axial movement of the drive sleeve 30 causes the piston rod 20 to rotate through the opening 18 in the insert 16, thereby to advance the piston 10 in the cartridge 8. Once the dialed dose has been dispensed, the dose dial sleeve 70 is prevented from further rotation by contact of a plurality of members 110 (FIG. 14) extending from the dose dial grip 76 with a corresponding plurality of stops 112 formed in the main housing 4 (FIGS. 15 and 16). In the illustrated embodiment, the members 110 extend

7

axially from the dose dial grip 76 and have an inclined end surface. The zero dose position is determined by the abutment of one of the axially extending edges of the members 110 with a corresponding stop 112.

The invention claimed is:

1. A pen type injector comprising:
 - a housing;
 - a piston rod adapted to operate through the housing;
 - a clicker configured to generate audible feedback, the clicker comprising a first sleeve, the first sleeve comprising a flexible arm;
 - a second sleeve;
 - a dose dial grip; and
 - a nut configured to be advanced along a thread towards a radial stop when the dose dial grip is rotated to dial a dose, such that when a final dose position is reached, the nut abuts the radial stop,
 wherein an end of the clicker comprises a plurality of circumferential teeth adapted to be coupled to a corresponding plurality of circumferential teeth of the second sleeve and adapted to prevent relative rotation between the first and second sleeves in a first rotational direction when the circumferential teeth of the first sleeve and the circumferential teeth of the second sleeve are coupled, and the clicker and the second sleeve are configured to rotate with the dose dial grip in the first rotational direction when the circumferential teeth of the first sleeve and the circumferential teeth of the second sleeve are coupled.
2. The pen type injector according to claim 1, wherein the second sleeve is a clutch.
3. The pen type injector according to claim 1, wherein the clicker is generally cylindrical.
4. The pen type injector according to claim 1, wherein a free end of the arm has a toothed member.
5. The pen type injector according to claim 1, wherein the clicker is disposed between the second sleeve and a splined surface of the housing.
6. The pen type injector according to claim 1, wherein the flexible arm is configured to ride over splines of a splined surface of the pen type injector to generate audible feedback when the clicker and the splined surface are rotated relative to each other.
7. The pen type injector according to claim 1, wherein the nut is a half-nut.
8. The pen type injector according to claim 1, wherein the housing comprises a housing body and an insert secured against longitudinal or rotational motion relative to the housing body.
9. The pen type injector according to claim 8, wherein the insert is integral with the housing body.
10. The pen type injector according to claim 1, wherein the piston rod has a first end comprising a threaded portion.
11. The pen type injector according to claim 1, further comprising a cartridge disposed within the housing, the cartridge containing a medicament.
12. The pen type injector according to claim 1, wherein the circumferential teeth of the first and second sleeves are adapted to prevent relative rotation between the first and second sleeves in the first rotational direction and to permit relative rotation between the first and second sleeves in a second rotational direction when the circumferential teeth of the first sleeve and the circumferential teeth of the second sleeve are coupled.
13. The pen type injector according to claim 1, wherein the nut is configured to move axially relative to the housing

8

without rotating relative to the housing when the dose dial grip is rotated to dial the dose.

14. The pen type injector according to claim 1, wherein the radial stop is separate from the thread.
15. The pen type injector according to claim 1, wherein the nut is a partial nut that spans less than an entire circle and is the only partial nut within the housing.
16. The pen type injector according to claim 1, wherein the nut comprises an internal thread.
17. A pen type injector comprising:
 - a housing;
 - a piston rod disposed at least partially within the housing, the piston rod being moveable relative to the housing;
 - a first sleeve disposed at least partially within the housing, the first sleeve comprising a flexible arm, an end of the first sleeve comprising circumferentially spaced teeth;
 - a second sleeve disposed at least partially within the housing, the second sleeve comprising circumferentially spaced teeth configured to be coupled to the teeth of the first sleeve to prevent relative rotation between the first and second sleeves in a first rotational direction;
 - a splined surface comprising a plurality of splines, wherein the flexible arm of the first sleeve is configured to ride over the splines to generate audible feedback when the first sleeve and the splined surface are rotated relative to each other;
 - a dose dial grip; and
 - a nut configured to be advanced along a thread towards a radial stop when the dose dial grip is rotated to dial a dose, such that when a final dose position is reached, the nut abuts the radial stop.
18. The pen type injector according to claim 17, wherein the circumferentially spaced teeth of the first and second sleeves extend axially.
19. The pen type injector according to claim 17, wherein a free end of the flexible arm has a toothed member.
20. The pen type injector according to claim 17, wherein the second sleeve is a clutch.
21. The pen type injector according to claim 17, wherein the first and second sleeves are configured to rotate with the dose dial grip in the first rotational direction when the teeth of the first sleeve and the teeth of the second sleeve are coupled.
22. The pen type injector according to claim 17, wherein the circumferentially spaced teeth of the first and second sleeves are adapted to prevent relative rotation between the first and second sleeves in the first rotational direction and to permit relative rotation between the first and second sleeves in a second rotational direction when the circumferentially spaced teeth of the first sleeve and the circumferentially spaced teeth of the second sleeve are coupled.
23. The pen type injector according to claim 17, wherein the nut is configured to move axially relative to the housing without rotating relative to the housing when the dose dial grip is rotated to dial the dose.
24. The pen type injector according to claim 17, wherein the radial stop is separate from the thread.
25. The pen type injector according to claim 17, wherein the nut is a partial nut that spans less than an entire circle and is the only partial nut within the housing.
26. The pen type injector according to claim 17, wherein the nut comprises an internal thread.
27. A pen type injector comprising:
 - a housing;
 - a piston rod disposed at least partially within the housing, the piston rod being moveable relative to the housing;

9

a first sleeve disposed at least partially within the housing,
 the first sleeve comprising a flexible arm;
 a second sleeve configured to engage the first sleeve in a
 manner to prevent relative rotation between the first
 and second sleeves in a first rotational direction;
 a splined surface comprising a plurality of splines,
 wherein the flexible arm of the first sleeve is configured
 to ride over the splines to generate audible feedback
 when the first sleeve and the splined surface are rotated
 relative to each other;
 a dose dial grip; and
 a nut configured to be advanced along a thread towards a
 radial stop when the dose dial grip is rotated to dial a
 dose, such that when a final dose position is reached,
 the nut abuts the radial stop.

28. The pen type injector according to claim **27**, wherein
 the first sleeve comprises circumferentially spaced teeth
 configured to be coupled to circumferentially spaced teeth of
 the first sleeve to prevent relative rotation between the first
 and second sleeves in the first rotational direction.

29. The pen type injector according to claim **28**, wherein
 the circumferentially spaced teeth of the first and second
 sleeves extend axially.

30. The pen type injector according to claim **28**, wherein
 the circumferentially spaced teeth of the first and second
 sleeves are adapted to prevent relative rotation between the

10

first and second sleeves in the first rotational direction and
 to permit relative rotation between the first and second
 sleeves in a second rotational direction when the circumfer-
 entially spaced teeth of the first sleeve and the circumfer-
 entially spaced teeth of the second sleeve are coupled.

31. The pen type injector according to claim **27**, wherein
 a free end of the flexible arm has a toothed member.

32. The pen type injector according to claim **27**, wherein
 the second sleeve is a clutch.

33. The pen type injector according to claim **27**, wherein
 the first and second sleeves are configured to rotate with the
 dose dial grip when the first sleeve and the second sleeve are
 coupled.

34. The pen type injector according to claim **27**, wherein
 the nut is configured to move axially relative to the housing
 without rotating relative to the housing when the dose dial
 grip is rotated to dial the dose.

35. The pen type injector according to claim **27**, wherein
 the radial stop is separate from the thread.

36. The pen type injector according to claim **27**, wherein
 the nut is a partial nut that spans less than an entire circle and
 is the only partial nut within the housing.

37. The pen type injector according to claim **27**, wherein
 the nut comprises an internal thread.

* * * * *