



US010823439B2

(12) **United States Patent**
Shelnutt et al.

(10) **Patent No.:** **US 10,823,439 B2**
(45) **Date of Patent:** **Nov. 3, 2020**

(54) **SYSTEMS AND METHODS FOR RELIABILITY CONTROL OF INFORMATION HANDLING SYSTEM**

(71) Applicant: **Dell Products L.P.**, Round Rock, TX (US)

(72) Inventors: **Austin M. Shelnutt**, Leander, TX (US); **Edmond I. Bailey**, Cedar Park, TX (US); **John R. Stuewe**, Round Rock, TX (US); **Steven Embleton**, Austin, TX (US)

(73) Assignee: **Dell Products L.P.**, Round Rock, TX (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 257 days.

(21) Appl. No.: **15/378,999**

(22) Filed: **Dec. 14, 2016**

(65) **Prior Publication Data**

US 2018/0163985 A1 Jun. 14, 2018

(51) **Int. Cl.**

F24F 11/30 (2018.01)
H04L 12/26 (2006.01)
F24F 11/65 (2018.01)
F24F 11/64 (2018.01)
F24F 11/32 (2018.01)
F24F 110/20 (2018.01)
F24F 110/10 (2018.01)

(52) **U.S. Cl.**

CPC **F24F 11/30** (2018.01); **F24F 11/32** (2018.01); **F24F 11/64** (2018.01); **F24F 11/65** (2018.01); **H04L 43/0817** (2013.01); **F24F 2110/10** (2018.01); **F24F 2110/20** (2018.01)

(58) **Field of Classification Search**

CPC G06F 11/3058; H05K 7/207; F25D 21/04; B60H 1/00785; B60H 1/00642; G01N 25/56; G01N 25/66; G01N 25/68; G01N 17/00; G01N 21/3554; G01N 21/94; G05B 2219/23227; G05B 2219/23317
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,449,764 A * 5/1984 Hastings E05G 5/02 261/106
4,745,564 A * 5/1988 Tennes G01P 1/127 346/33 D
5,240,177 A * 8/1993 Muramatsu G05D 22/02 236/44 C
5,446,369 A * 8/1995 Byrne G01N 17/00 204/404

(Continued)


Primary Examiner — Darrin D Dunn

(74) *Attorney, Agent, or Firm* — Jackson Walker L.L.P.

(57) **ABSTRACT**

In accordance with embodiments of the present disclosure, a controller may include one or more environmental sensor inputs configured to receive data from one or more environmental sensors integral to an information handling system and a microcontroller unit communicatively coupled to the one or more environmental sensor inputs. The microcontroller unit may be configured to monitor the one or more environmental sensor inputs for one or more reliability-impacting events affecting or likely to affect operability of the information handling system and in response to an occurrence of a reliability-impacting event, apply an event-based policy affecting operation of one or more components of the information handling system.

14 Claims, 2 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

5,936,523	A *	8/1999	West	G08B 13/1481 340/545.2	2011/0129705	A1 *	6/2011	Lee	H02J 7/0031 429/90
6,253,834	B1 *	7/2001	Sterner	G06F 1/203 165/104.34	2011/0279978	A1 *	11/2011	Yoshikawa	H01L 23/427 361/700
6,453,266	B1 *	9/2002	Chainer	G06F 1/1613 340/506	2011/0292601	A1 *	12/2011	Campbell	F24F 3/14 361/691
6,490,874	B2 *	12/2002	Chu	H05K 5/0213 62/271	2012/0053861	A1 *	3/2012	Kremer	C10G 75/02 702/50
7,818,156	B2 *	10/2010	Vachhani	C10G 7/10 208/47	2012/0216992	A1 *	8/2012	So	H05K 5/0213 165/104.33
7,865,253	B2 *	1/2011	Harrington	G11B 19/042 700/21	2012/0289217	A1 *	11/2012	Riemer	H04M 1/72577 455/418
8,290,629	B1 *	10/2012	Mateski	H05K 7/20836 137/2	2012/0331119	A1 *	12/2012	Bose	H04L 61/2015 709/223
8,330,305	B2 *	12/2012	Hart	H04M 1/185 307/650	2013/0020397	A1 *	1/2013	Branham	F24F 11/0001 236/44 A
8,570,179	B2 *	10/2013	Holloway	F16P 3/14 340/539.22	2013/0048535	A1 *	2/2013	Wang	C10G 75/02 208/47
8,786,462	B2 *	7/2014	Bowman	H04Q 9/00 340/870.02	2013/0054180	A1 *	2/2013	Barfield	G01P 15/0891 702/138
9,097,772	B2 *	8/2015	Kromrey	G01R 31/362	2013/0063602	A1 *	3/2013	Scapier	H04N 7/185 348/160
9,109,989	B2 *	8/2015	Hamann	G01N 17/04	2013/0138715	A1 *	5/2013	Petersen	H04M 1/24 709/203
9,146,207	B2 *	9/2015	Harper	G06F 1/1656	2013/0138997	A1 *	5/2013	Wang	H04L 41/0663 714/4.11
9,152,178	B2 *	10/2015	Koch	G06F 1/206	2013/0182360	A1 *	7/2013	Stevens	H02H 5/00 361/71
9,164,519	B2 *	10/2015	Holloway	G05B 19/0428	2013/0220423	A1 *	8/2013	Campbell	F17D 3/00 137/1
9,689,887	B1 *	6/2017	Srinivas	G01B 21/18	2013/0226364	A1 *	8/2013	Artman	G06F 1/206 700/300
9,834,732	B2 *	12/2017	Wang	G05B 23/0221	2013/0257582	A1 *	10/2013	Rothkopf	G06F 1/1656 340/3.1
9,927,853	B2 *	3/2018	Vichare	G06F 1/206	2013/0265064	A1 *	10/2013	Hamann	G01N 17/04 324/700
9,983,621	B1 *	5/2018	Menon	G06F 1/1626	2013/0265153	A1 *	10/2013	Taylor	G08B 21/182 340/539.1
10,048,733	B2 *	8/2018	David	G06F 1/28	2013/0335716	A1 *	12/2013	Shields	B44F 1/10 353/99
10,211,753	B2 *	2/2019	Tsukano	F24F 1/24	2014/0049774	A1 *	2/2014	Horii	G01N 21/274 356/237.3
2003/0163287	A1 *	8/2003	Vock	A43B 3/0005 702/187	2014/0159634	A1 *	6/2014	Yokoyama	H05K 7/20836 318/471
2004/0050072	A1 *	3/2004	Palfy	A42B 3/24 62/3.4	2014/0180953	A1 *	6/2014	Westcott	A23B 7/148 705/332
2004/0050076	A1 *	3/2004	Palfy	A42B 3/24 62/155	2014/0237268	A1 *	8/2014	Mese	G06F 1/26 713/300
2006/0010967	A1 *	1/2006	Matsuo	G01N 25/56 73/73	2014/0253093	A1 *	9/2014	Bermudez Rodriguez	G06Q 10/083 324/76.11
2006/0213267	A1 *	9/2006	Tronconi	G01P 15/18 73/510	2014/0285333	A1 *	9/2014	Imamura	G01P 15/0891 340/436
2007/0043485	A1 *	2/2007	Meissner	B60R 21/01562 701/45	2014/0307356	A1 *	10/2014	Hong	H02H 5/083 361/78
2007/0218732	A1 *	9/2007	Honda	H04R 1/021 439/188	2014/0321879	A1 *	10/2014	Sato	G03G 21/203 399/97
2007/0253093	A1 *	11/2007	Cook	G11B 19/042 360/75	2015/0016001	A1 *	1/2015	Quirk	H02H 5/083 361/78
2008/0106366	A1 *	5/2008	Zhang	G06F 21/88 340/5.1	2015/0022357	A1 *	1/2015	Gettings	G08B 3/00 340/568.1
2008/0218366	A1 *	9/2008	Chen	G11B 19/043 340/669	2015/0068702	A1 *	3/2015	So	H05K 7/20272 165/11.1
2008/0232063	A1 *	9/2008	Koo	F25B 21/02 361/679.48	2015/0124390	A1 *	5/2015	Koch	G06F 1/1633 361/679.26
2008/0253015	A1 *	10/2008	Harrington	G11B 19/042 360/75	2015/0171491	A1 *	6/2015	Lim	H01M 10/625 429/50
2008/0304236	A1 *	12/2008	Murakami	H05K 7/207 361/699	2015/0234363	A1 *	8/2015	Yoon	H02J 7/0036 320/137
2010/0085197	A1 *	4/2010	Delia	G01W 1/00 340/601	2015/0241370	A1 *	8/2015	Mueller	G01K 1/20 345/173
2010/0097208	A1 *	4/2010	Rosing	G06Q 50/30 340/539.13	2015/0338315	A1 *	11/2015	Manahan	G01M 99/008 702/183
2010/0142104	A1 *	6/2010	Cooper	H02H 3/32 361/49	2015/0346127	A1 *	12/2015	Kalinichev	G01N 27/048 361/86
2010/0185401	A1 *	7/2010	Hernandez	F17D 5/00 702/25						
2010/0300284	A1 *	12/2010	Bash	G05D 22/02 95/10						
2011/0101118	A1 *	5/2011	Criss	F24F 13/22 236/44 C						
2011/0118896	A1 *	5/2011	Holloway	G05B 19/0428 700/300						

(56)

References Cited

U.S. PATENT DOCUMENTS

2016/0041085	A1 *	2/2016	England	G01N 17/043 436/6
2016/0063433	A1 *	3/2016	Glasgow	G06Q 10/0832 705/332
2016/0080553	A1 *	3/2016	Dempster	H04M 1/72569 455/550.1
2016/0154439	A1 *	6/2016	Rothkopf	G06F 1/1656 340/3.1
2016/0195566	A1 *	7/2016	Vock	G01G 23/00 73/514.01
2016/0286389	A1 *	9/2016	Cai	H04W 12/02
2016/0361973	A1 *	12/2016	Mayer	B60H 1/00764
2017/0013744	A1 *	1/2017	Shelnutt	F28F 27/02
2017/0030888	A1 *	2/2017	Vandersleen	G01N 33/5091
2017/0065210	A1 *	3/2017	Borkholder	A63B 71/10
2017/0074899	A1 *	3/2017	Oouchi	G01P 15/18
2017/0089607	A1 *	3/2017	Vichare	G06F 1/206
2017/0092405	A1 *	3/2017	Manahan	H01F 7/064
2017/0099746	A1 *	4/2017	Rubenstein	H05K 1/0203
2017/0160775	A1 *	6/2017	Sun	G06F 1/20
2017/0168531	A1 *	6/2017	Casparian	G06F 1/206
2017/0208707	A1 *	7/2017	Teeter	H05K 7/20727
2017/0295677	A1 *	10/2017	Shelnutt	H05K 7/20836
2017/0344175	A1 *	11/2017	Hung	G06F 3/0488
2017/0347473	A1 *	11/2017	Freer	H05K 5/0213
2017/0372585	A1 *	12/2017	Iv Evangelista	G01P 15/0891
2018/0007164	A1 *	1/2018	Ruxton	H04L 43/10
2018/0039313	A1 *	2/2018	David	G06F 1/28
2018/0059695	A1 *	3/2018	Carignan	G05D 27/02
2018/0149623	A1 *	5/2018	Notohardjono	G01P 15/0891
2018/0157211	A1 *	6/2018	Tomiyasu	G03G 21/0005
2018/0164728	A1 *	6/2018	Mandachi	B41J 29/377
2018/0292877	A1 *	10/2018	David	G06F 1/28
2018/0367059	A1 *	12/2018	Tsukano	F24F 1/24
2019/0220105	A1 *	7/2019	Noma	G06F 3/0383

* cited by examiner




FIG. 1




FIG. 2

1**SYSTEMS AND METHODS FOR
RELIABILITY CONTROL OF
INFORMATION HANDLING SYSTEM**

TECHNICAL FIELD

The present disclosure relates in general to information handling systems, and more particularly to reliability control of an information handling system.

BACKGROUND

As the value and use of information continues to increase, individuals and businesses seek additional ways to process and store information. One option available to users is information handling systems. An information handling system generally processes, compiles, stores, and/or communicates information or data for business, personal, or other purposes thereby allowing users to take advantage of the value of the information. Because technology and information handling needs and requirements vary between different users or applications, information handling systems may also vary regarding what information is handled, how the information is handled, how much information is processed, stored, or communicated, and how quickly and efficiently the information may be processed, stored, or communicated. The variations in information handling systems allow for information handling systems to be general or configured for a specific user or specific use such as financial transaction processing, airline reservations, enterprise data storage, or global communications. In addition, information handling systems may include a variety of hardware and software components that may be configured to process, store, and communicate information and may include one or more computer systems, data storage systems, and networking systems.

Manufacturers commonly deliver pre-integrated and validated racks of information handling systems, thus allowing consumers of such systems to receive fully-populated, cabled, and tested racks which they can simply transfer from their point of delivery to their data center environments without requiring the use of teams of technicians to assemble the racks on site. However, compared with shipping an individual server in an enclosed package that is drop tested and sealed with moisture-absorbing desiccant, shipping of a pre-integrated rack with servers may present unique challenges with respect to non-operational reliability concerns. In particular, the volume and mass of a pre-integrated rack may make it susceptible to condensation and shock events during shipment that may be difficult and expensive to completely eliminate from the shipping process.

SUMMARY

In accordance with the teachings of the present disclosure, one or more disadvantages and problems associated with ensuring operability of an information handling system may be reduced or eliminated.

In accordance with embodiments of the present disclosure, a controller may include one or more environmental sensor inputs configured to receive data from one or more environmental sensors integral to an information handling system and a microcontroller unit communicatively coupled to the one or more environmental sensor inputs. The microcontroller unit may be configured to monitor the one or more environmental sensor inputs for one or more reliability-

2

impacting events affecting or likely to affect operability of the information handling system and in response to an occurrence of a reliability-impacting event, apply an event-based policy affecting operation of one or more components of the information handling system.

In accordance with these and other embodiments of the present disclosure, a method may include receiving data from one or more environmental sensors integral to an information handling system, monitoring the one or more environmental sensor inputs for one or more reliability-impacting events affecting or likely to affect operability of the information handling system, and in response to an occurrence of a reliability-impacting event, applying an event-based policy affecting operation of one or more components of the information handling system.

In accordance with these and other embodiments of the present disclosure, an information handling system may include one or more environmental sensors a controller comprising one or more environmental sensor inputs configured to receive data from the one or more environmental sensors and a microcontroller unit communicatively coupled to the one or more environmental sensor inputs. The microcontroller unit may be configured to monitor the one or more environmental sensor inputs for one or more reliability-impacting events affecting or likely to affect operability of the information handling system and in response to an occurrence of a reliability-impacting event, apply an event-based policy affecting operation of one or more components of the information handling system.

Technical advantages of the present disclosure may be readily apparent to one skilled in the art from the figures, description and claims included herein. The objects and advantages of the embodiments will be realized and achieved at least by the elements, features, and combinations particularly pointed out in the claims.

It is to be understood that both the foregoing general description and the following detailed description are examples and explanatory and are not restrictive of the claims set forth in this disclosure.

BRIEF DESCRIPTION OF THE DRAWINGS

A more complete understanding of the present embodiments and advantages thereof may be acquired by referring to the following description taken in conjunction with the accompanying drawings, in which like reference numbers indicate like features, and wherein:

FIG. 1 illustrates a block diagram of an example information handling system, in accordance with certain embodiments of the present disclosure; and

FIG. 2 illustrates a flow chart of an example method for reliability control of an information handling system, in accordance with certain embodiments of the present disclosure.

DETAILED DESCRIPTION

Preferred embodiments and their advantages are best understood by reference to FIGS. 1 and 2, wherein like numbers are used to indicate like and corresponding parts.

For the purposes of this disclosure, an information handling system may include any instrumentality or aggregate of instrumentalities operable to compute, classify, process, transmit, receive, retrieve, originate, switch, store, display, manifest, detect, record, reproduce, handle, or utilize any form of information, intelligence, or data for business, scientific, control, entertainment, or other purposes. For

example, an information handling system may be a personal computer, a personal digital assistant (PDA), a consumer electronic device, a network storage device, or any other suitable device and may vary in size, shape, performance, functionality, and price. The information handling system may include memory, one or more processing resources such as a central processing unit (“CPU”) or hardware or software control logic. Additional components of the information handling system may include one or more storage devices, one or more communications ports for communicating with external devices as well as various input/output (“I/O”) devices, such as a keyboard, a mouse, and a video display. The information handling system may also include one or more buses operable to transmit communication between the various hardware components.

For the purposes of this disclosure, computer-readable media may include any instrumentality or aggregation of instrumentalities that may retain data and/or instructions for a period of time. Computer-readable media may include, without limitation, storage media such as a direct access storage device (e.g., a hard disk drive or floppy disk), a sequential access storage device (e.g., a tape disk drive), compact disk, CD-ROM, DVD, random access memory (RAM), read-only memory (ROM), electrically erasable programmable read-only memory (EEPROM), and/or flash memory; as well as communications media such as wires, optical fibers, microwaves, radio waves, and other electromagnetic and/or optical carriers; and/or any combination of the foregoing.

For the purposes of this disclosure, information handling resources may broadly refer to any component system, device or apparatus of an information handling system, including without limitation processors, service processors, basic input/output systems (BIOSs), buses, memories, I/O devices and/or interfaces, storage resources, network interfaces, motherboards, and/or any other components and/or elements of an information handling system.

For the purposes of this disclosure, the terms “wireless transmissions” and “wireless communication” may be used to refer to all types of electromagnetic communications which do not require a wire, cable, or other types of conduits. Examples of wireless transmissions which may be used include, but are not limited to, short-range wireless communication technologies (e.g., proximity card, Radio-Frequency Identification (RFID), Near Field Communication (NFC), Bluetooth, ISO 14443, ISO 15693, or other suitable standard), personal area networks (PAN) (e.g., Bluetooth), local area networks (LAN), wide area networks (WAN), narrowband personal communications services (PCS), mobile telephony technologies, broadband PCS, circuit-switched cellular, cellular digital packet data (CDPD), radio frequencies, such as the 800 MHz, 900 MHz, 1.9 GHz and 2.4 GHz bands, infra-red and laser.

FIG. 1 illustrates a block diagram of an example information handling system 102. In some embodiments, information handling system 102 may comprise a personal computer. In some embodiments, information handling system 102 may comprise or be an integral part of a server. In other embodiments, information handling system 102 may comprise a portable information handling system (e.g., a laptop, notebook, tablet, handheld, smart phone, personal digital assistant, etc.). As depicted in FIG. 1, information handling system 102 may include a processor 103, a memory 104 communicatively coupled to processor 103, a BIOS 105 communicatively coupled to processor 103, a network interface 108 communicatively coupled to processor 103, a management controller 112 communicatively coupled to

processor 103, a reliability controller 116 communicatively coupled to a processor 113, and one or more environmental sensors (e.g., temperature sensor 119, humidity sensor 120, moisture sensor 122, and accelerometer 124).

Processor 103 may include any system, device, or apparatus configured to interpret and/or execute program instructions and/or process data, and may include, without limitation, a microprocessor, microcontroller, digital signal processor (DSP), application specific integrated circuit (ASIC), or any other digital or analog circuitry configured to interpret and/or execute program instructions and/or process data. In some embodiments, processor 103 may interpret and/or execute program instructions and/or process data stored in memory 104 and/or another component of information handling system 102.

Memory 104 may be communicatively coupled to processor 103 and may include any system, device, or apparatus configured to retain program instructions and/or data for a period of time (e.g., computer-readable media). Memory 104 may include RAM, EEPROM, a PCMCIA card, flash memory, magnetic storage, opto-magnetic storage, or any suitable selection and/or array of volatile or non-volatile memory that retains data after power to information handling system 102 is turned off.

As shown in FIG. 1, memory 104 may have stored thereon an operating system 106. Operating system 106 may comprise any program of executable instructions, or aggregation of programs of executable instructions, configured to manage and/or control the allocation and usage of hardware resources such as memory, processor time, disk space, and input and output devices, and provide an interface between such hardware resources and application programs hosted by operating system 106. In addition, operating system 106 may include all or a portion of a network stack for network communication via a network interface (e.g., network interface 108 for communication over a data network). Active portions of operating system 106 may be transferred to memory 104 for execution by processor 103. Although operating system 106 is shown in FIG. 1 as stored in memory 104, in some embodiments operating system 106 may be stored in storage media accessible to processor 103, and active portions of operating system 106 may be transferred from such storage media to memory 104 for execution by processor 103.

A BIOS 105 may include any system, device, or apparatus configured to identify, test, and/or initialize information handling resources of information handling system 102, and/or initialize interoperation of information handling system 102 with other information handling systems. “BIOS” may broadly refer to any system, device, or apparatus configured to perform such functionality, including without limitation, a Unified Extensible Firmware Interface (UEFI). In some embodiments, BIOS 105 may be implemented as a program of instructions that may be read by and executed on processor 103 to carry out the functionality of BIOS 105. In these and other embodiments, BIOS 105 may comprise boot firmware configured to be the first code executed by processor 103 when information handling system 102 is booted and/or powered on. As part of its initialization functionality, code for BIOS 105 may be configured to set components of information handling system 102 into a known state, so that one or more applications (e.g., an operating system or other application programs) stored on compatible media (e.g., disk drives) may be executed by processor 103 and given control of information handling system 102.

Network interface 108 may comprise any suitable system, apparatus, or device operable to serve as an interface

5

between information handling system **102** and one or more other information handling systems via an in-band network. Network interface **108** may enable information handling system **102** to communicate using any suitable transmission protocol and/or standard. In these and other embodiments, network interface **108** may comprise a network interface card, or “NIC.” In these and other embodiments, network interface **108** may be enabled as a local area network (LAN)-on-motherboard (LOM) card.

In operation, processor **103**, memory **104**, BIOS **105**, and network interface **108** may comprise at least a portion of a host system **98** of information handling system **102**.

Management controller **112** may be configured to provide management facilities for management of information handling system **102**. Such management may be made by management controller **112** even if information handling system **102** is powered off or powered to a standby state. Management controller **112** may include a processor **113**, memory, and a management network interface **118** separate from and physically isolated from data network interface **108**. In certain embodiments, management controller **112** may include or may be an integral part of a baseboard management controller (BMC) or a remote access controller (e.g., a Dell Remote Access Controller or Integrated Dell Remote Access Controller). As shown in FIG. 1, management controller **112** may comprise a processor **113** and a network interface **118** communicatively coupled to processor **113**.

Processor **113** may include any system, device, or apparatus configured to interpret and/or execute program instructions and/or process data, and may include, without limitation, a microprocessor, microcontroller, digital signal processor (DSP), application specific integrated circuit (ASIC), or any other digital or analog circuitry configured to interpret and/or execute program instructions and/or process data. In some embodiments, processor **113** may interpret and/or execute program instructions and/or process data stored in a memory and/or another component of information handling system **102** or management controller **112**. As shown in FIG. 1, processor **113** may be communicatively coupled to processor **103**. Such coupling may be via a Universal Serial Bus (USB), System Management Bus (SMBus), and/or one or more other communications channels.

Network interface **118** may comprise any suitable system, apparatus, or device operable to serve as an interface between management controller **112** and one or more other information handling systems via an out-of-band management network. Network interface **118** may enable management controller **112** to communicate using any suitable transmission protocol and/or standard. In these and other embodiments, network interface **118** may comprise a network interface card, or “NIC.”

Reliability controller **116** may comprise any suitable system, device, or apparatus configured to receive one or more sensor inputs indicating environmental conditions within information handling system **102**, and based thereon, determine whether a reliability-impacting event has occurred within information handling system **102**. For example, in some embodiments, reliability controller **116** may primarily operate during shipment of information handling system **102** to a consumer of information handling system **102**, to determine if a reliability-impacting event occurs during shipment. In addition, a “reliability-impacting event” may broadly include any event associated with information handling system **102** and detectable by one or more environmental sensors wherein such event indicates a substantial probability that one or more components of

6

information handling system **102** may not operate properly in response to the reliability-impacting event. One non-limiting example of a reliability-impacting event includes condensation occurring within information handling system **102** that could lead to electrical shorting and damage if information handling system **102** is powered on with such condensation present. Another non-limiting example includes a mechanical shock event that could cause physical damage to one or more components, which could in turn cause additional damage if information handling system **102** is powered on with such physical damage unremedied.

As shown in FIG. 1, reliability controller **116** may include a microcontroller unit (MCU) **126**, a memory **128**, a battery **130**, and one or more inputs for receiving sensor data from one or more environmental sensors (e.g., temperature sensor **119**, humidity sensor **120**, moisture sensor **122**, and accelerometer **124**).

MCU **126** may comprise a microprocessor, DSP, ASIC, FPGA, EEPROM, or any combination thereof, or any other device, system, or apparatus for carrying out the functionality of reliability controller **116**. As such, MCU **126** may comprise firmware, logic, and/or data for controlling functionality of reliability controller **116**.

Memory **128** may be communicatively coupled to processor **103** and may include any system, device, or apparatus configured to retain program instructions and/or data for a period of time (e.g., computer-readable media). Memory **104** may include RAM, EEPROM, a PCMCIA card, flash memory, magnetic storage, opto-magnetic storage, or any suitable selection and/or array of volatile or non-volatile memory that retains data after power to information handling system **102** is turned off. In particular, memory **128** may include data and instructions that may be loaded and executed by MCU **126** in order to carry out the functionality of reliability controller **116**. For example, memory **128** may store definitions of reliability-impacting events and remedies in response to reliability-impacting events. For example, memory **128** may store definitions of “direct” events such as a parameter measured by an environmental sensor exceeding a threshold value for such sensor. As another example, memory **128** may store definitions of “indirect” events that are algorithmically defined, such as a time rate of change of a dew point exceeding a threshold may indicate likelihood of condensation which itself is not directly detectable, or such as a spectral density of power over a frequency range of interest (e.g., as determined from readings from accelerometer **124**) exceeding a particular threshold which may indicate a likelihood of mechanically-induced damage that may not be directly detectable.

In addition, in some embodiments, reliability controller **116** may interact with management controller **112** or other control circuitry/systems of information handling system to apply event-based policies to information handling system **102**. Such policies may be defined within memory **128**. For example, if reliability controller **116** detects the presence or likelihood of condensation, it may interact with management controller **112** such that management controller **112** prevents information handling system **102** from powering for a period of time following the condensation event. As another example, if reliability controller **116** detects the presence or likelihood of condensation, it may interact with management controller **112** such that management controller **112** powers on cooling fans of information handling system **102** while leaving the remainder of information handling system **102** powered down in order to assist in drying out affected or potentially-affected components. As a further example, if reliability controller **116** detects the presence or likelihood

of a physical shock event (e.g., one which could have dislodged an electrical bus bar), it may interact with management controller **112** to prevent powering on of information handling system **102** pending a manual inspection of information handling system **102**. As an additional example, reliability controller **116** may include a light or other visual indicator (not explicitly shown in FIG. 1) that provides a visual indication of a past and/or present reliability-impacting event in accordance with an event-based policy.

Battery **130** may comprise any system, device, or apparatus configured to store energy which may be used by reliability controller **116** to power components of reliability controller **116** to perform the functionality thereof. In some embodiments, battery **130** may comprise an electrochemical cell configured to convert stored chemical energy into electrical energy. In other embodiments, battery **130** may comprise a capacitor or “supercap” configured to store electrical energy and deliver such electrical energy to components of reliability controller **116**.

Temperature sensor **119** may be any system, device, or apparatus (e.g., a thermometer, thermistor, etc.) configured to communicate a signal to reliability controller **116** indicative of a temperature proximate to or within information handling system **102**.

Humidity sensor **120** may be any system, device, or apparatus (e.g., a hygrometer, etc.) configured to communicate a signal to reliability controller **116** indicative of a relative humidity proximate to or within information handling system **102**.

Moisture sensor **122** may be any system, device, or apparatus configured to communicate a signal to reliability controller **116** indicative of presence of liquid water or other water proximate to or within information handling system **102**.

Accelerometer **124** may include any system, device, or apparatus configured to measure acceleration (e.g., proper acceleration) experienced by information handling system **102**.

Although FIG. 1 and the discussion above enumerates specific types of environmental sensors, it is understood that other types of environmental sensors may be employed by information handling system **102**, and that any number of any types of environmental sensors may also be employed.

In these and other embodiments, environmental sensors may be strategically placed within information handling system **102** (e.g., within or proximate to hard disk drives or other data storage devices). In such cases, environmental sensors may be coupled to reliability controller **116** via wireless or wire-line transmissions.

In these and other embodiments, reliability controller **116** may include a wireless network interface (not shown in FIG. 1) that may be used to remotely query (e.g., via a handheld computing device, such as a tablet) reliability controller **116** in order to view reliability-impacting event information from such remote device.

In these and other embodiments, environmental sensors may be incorporated within modular information handling resources of information handling system **102**. For example, a hard disk drive may incorporate an accelerometer **124**, and if reliability controller **116** detects a reliability-impacting event, such event may be logged or otherwise reported by reliability controller **116**, to which a technician or other user may simply replace the particular hard disk drive experiencing the reliability-impacting event.

In addition to processor **103**, memory **104**, network interface **108**, management controller **112**, and reliability

controller **116**, and environmental sensors, information handling system **102** may include one or more other information handling resources.

Although FIG. 1 depicts information handling system **102** as only having a single host system **98** for the purposes of clarity and exposition, in some embodiments, information handling system **102** may comprise a server rack including a plurality of racks of host systems **98**.

FIG. 2 illustrates a flow chart of an example method **200** for reliability control of an information handling system, in accordance with certain embodiments of the present disclosure. According to some embodiments, method **200** may begin at step **202**. As noted above, teachings of the present disclosure may be implemented in a variety of configurations of information handling system **102**.

At step **202**, an information handling system **102** including reliability controller **116** and environmental sensors may be shipped from a manufacturer or other provider of information handling system **102**. At step **204**, during shipping, reliability controller **116** may monitor for reliability-impacting events, as may be defined by information stored in memory **128**. At step **206**, reliability controller **116** may determine if any reliability-impacting events occur within a particular period of time, wherein such particular period of time may be related to a period of time required to ship information handling system **102** to its intended destination. If a reliability-impacting event has occurred, method **200** may proceed to step **208**. If a reliability-impacting event does not occur, method **200** may end.

At step **208**, in response to occurrence of a reliability-impacting event, reliability controller **116** may, alone or in concert with management controller **112** or another component of information handling system **102**, apply an event-based policy to the operation of information handling system **102**, as described above. After application of the event-based policy, method **200** may end.

Although FIG. 2 discloses a particular number of steps to be taken with respect to method **200**, method **200** may be executed with greater or lesser steps than those depicted in FIG. 2. In addition, although FIG. 2 discloses a certain order of steps to be taken with respect to method **200**, the steps comprising method **200** may be completed in any suitable order.

Method **200** may be implemented using information handling system **102** or any other system operable to implement method **200**. In certain embodiments, method **200** may be implemented partially or fully in software and/or firmware embodied in computer-readable media.

This disclosure encompasses all changes, substitutions, variations, alterations, and modifications to the exemplary embodiments herein that a person having ordinary skill in the art would comprehend. Similarly, where appropriate, the appended claims encompass all changes, substitutions, variations, alterations, and modifications to the exemplary embodiments herein that a person having ordinary skill in the art would comprehend. Moreover, reference in the appended claims to an apparatus or system or a component of an apparatus or system being adapted to, arranged to, capable of, configured to, enabled to, operable to, or operative to perform a particular function encompasses that apparatus, system, or component, whether or not it or that particular function is activated, turned on, or unlocked, as long as that apparatus, system, or component is so adapted, arranged, capable, configured, enabled, operable, or operative.

All examples and conditional language recited herein are intended for pedagogical objects to aid the reader in under-

standing the invention and the concepts contributed by the inventor to furthering the art, and are construed as being without limitation to such specifically recited examples and conditions. Although embodiments of the present inventions have been described in detail, it should be understood that various changes, substitutions, and alterations could be made hereto without departing from the spirit and scope of the disclosure.

What is claimed is:

1. A reliability controller for an information handling system, wherein the reliability controller includes:

one or more environmental sensor inputs configured to receive data from one or more environmental sensors of an information handling system, wherein the information handling system includes a host system, comprising a central processing unit (CPU) communicatively coupled to a host memory, and a management controller, comprising a management controller processor communicatively coupled to the host processor, wherein the one or more environmental sensors include an accelerometer; and

a microcontroller unit, distinct from the CPU and the management controller processor, wherein the microcontroller unit is communicatively coupled to the one or more environmental sensor inputs and configured to perform reliability control operations, wherein the reliability control operations include:

monitoring, during shipping of the information handling system with the host system and the management controller in a powered-off state, the one or more environmental sensor inputs for sensor data indicative of one or more reliability impacting events occurring during said shipping, wherein the one or more reliability impacting events include:

a mechanical damage event, wherein the mechanical damage event is indicated by data from the accelerometer indicating an acceleration of the information handling system exceeding a threshold acceleration; in response to detecting a reliability impacting event during shipping of the information handling system, performing one or more reliability policy actions, wherein the one or more reliability policy actions include:

a mechanical damage action performed in response to detecting a mechanical damage event, wherein the mechanical damage action includes preventing powering on of the host system processor pending an inspection of the information handling system.

2. The reliability controller of claim 1, wherein the one or more environmental sensors include at least one of a temperature sensor and a humidity sensor.

3. The reliability controller of claim 1, wherein the one or more environmental sensors include at least one of a temperature sensor, a humidity sensor, and a moisture sensor, and wherein the one or more reliability impacting events include:

a condensation event indicative of condensation within the information handling system.

4. The reliability controller of claim 3, wherein condensation event is indicated by a time rate of change of a dew point associated with the information handling system exceeding a threshold rate.

5. The reliability controller of claim 4, wherein the one or more reliability policy actions includes a condensation action for powering on a cooling fan of the information handling system and preventing powering on of at least one other component of the information handling system for a

selected period of time responsive to detecting sensor data satisfying the condensation event.

6. A reliability control method for an information handling system, the reliability control method comprising:

monitoring, by a reliability controller of the information handling system, during shipping of the information handling system with a host system and a management controller of the information handling system in a powered-off state, one or more environmental sensor inputs for sensor data indicative of one or more reliability impacting events occurring during said shipping, wherein the one or more reliability impacting events include:

a mechanical damage event, wherein the mechanical damage event is indicated by data from the accelerometer indicating an acceleration of the information handling system exceeding a threshold acceleration; in response to detecting a reliability impacting event during shipping of the information handling system, performing one or more reliability policy actions, wherein the one or more reliability policy actions include:

a mechanical damage action performed in response to detecting a mechanical damage event, wherein the mechanical damage action includes preventing powering on of the host system processor pending an inspection of the information handling system.

7. The reliability control method of claim 6, wherein the one or more environmental sensors include at least one of a temperature sensor and a humidity sensor.

8. The reliability method of claim 6, wherein the one or more environmental sensors include at least one of a temperature sensor, a humidity sensor, and a moisture sensor, and wherein the one or more reliability impacting events include:

a condensation event indicative of condensation within the information handling system.

9. The method of claim 8, wherein the condensation event is indicated indirectly by a time rate of change of a dew point associated with the information handling system exceeding a threshold rate of change.

10. The method of claim 8, wherein the reliability policy includes a provision for powering on a cooling fan of the information handling system and preventing powering on of at least one other component of the information handling system for a selected period of time responsive to detecting the condensation event.

11. An information handling system comprising:

a host system including a host processor coupled to a host memory and to a host network interface configured to couple the host processor to a data network;

a management controller communicatively coupled to the host processor, wherein the management controller includes a management controller processor communicatively coupled to a management network interface configured to couple the management controller processor to a management network;

one or more environmental sensors wherein the one or more environmental sensors include an accelerometer; and

a reliability controller comprising:

one or more environmental sensor inputs configured to receive data from the one or more environmental sensors; and

a microcontroller unit communicatively coupled to the one or more environmental sensor inputs and config-

11

ured to perform reliability monitoring operations, wherein the reliability monitoring operations include: monitoring, during shipping of the information handling system with the host system and the management controller in a powered-off state, the one or more environmental sensor inputs for sensor data indicative of one or more reliability impacting events occurring during said shipping, wherein the one or more reliability impacting events include:

a mechanical damage event, wherein the mechanical damage event is indicated by data from the accelerometer indicating an acceleration of the information handling system exceeding a threshold acceleration;

in response to detecting a reliability impacting event during shipping of the information handling system, performing one or more reliability policy actions, wherein the one or more reliability policy actions include:

a mechanical damage action performed in response to detecting a mechanical damage event, wherein

12

the mechanical damage action includes preventing powering on of the host system processor pending an inspection of the information handling system.

12. The information handling system of claim **11**, wherein the one or more environmental sensors include at least one of a temperature sensor, a humidity sensor, and a moisture sensor, and wherein the one or more reliability impacting events include:

a condensation event indicative of condensation within the information handling system.

13. The information handling system of claim **12**, wherein the condensation event is indicated by a time rate of change of a dew point associated with the information handling system exceeding a threshold rate of change.

14. The information handling system of claim **12**, wherein the one or more reliability policy actions include a condensation action for powering on a cooling fan of the information handling system and preventing powering on of at the host system for a selected period of time responsive to detecting the condensation event.

* * * * *