



US010838350B2

(12) **United States Patent**  
**Okabe**

(10) **Patent No.:** **US 10,838,350 B2**  
(45) **Date of Patent:** **\*Nov. 17, 2020**

(54) **IMAGE FORMING APPARATUS, IMAGE FORMING CARTRIDGE SUPPORTER, AND IMAGE FORMING UNIT**

(71) Applicant: **Brother Kogyo Kabushiki Kaisha**, Nagoya (JP)

(72) Inventor: **Yasushi Okabe**, Nagoya (JP)

(73) Assignee: **Brother Kogyo Kabushiki Kaisha**, Nagoya (JP)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **16/683,566**

(22) Filed: **Nov. 14, 2019**

(65) **Prior Publication Data**

US 2020/0081393 A1 Mar. 12, 2020

**Related U.S. Application Data**

(63) Continuation of application No. 16/130,708, filed on Sep. 13, 2018, now Pat. No. 10,481,550, which is a (Continued)

(30) **Foreign Application Priority Data**

Sep. 28, 2005 (JP) ..... 2005-281139

(51) **Int. Cl.**  
**G03G 21/16** (2006.01)  
**G03G 21/18** (2006.01)  
**G03G 15/00** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **G03G 21/1647** (2013.01); **G03G 15/80** (2013.01); **G03G 21/1619** (2013.01); (Continued)

(58) **Field of Classification Search**  
CPC ..... G03G 21/1867; G03G 21/1647; G03G 21/1652; G03G 15/80; G03G 21/1619; G03G 2221/1684; G03G 2221/1869  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,912,563 A 3/1990 Narita  
4,952,989 A 8/1990 Kawano et al.

(Continued)

FOREIGN PATENT DOCUMENTS

CN 1503070 A 6/2004  
EP 1273980 A2 1/2003

(Continued)

OTHER PUBLICATIONS

EP Search Report dated Oct. 16, 2006, EP Appln. 06013842.

(Continued)


*Primary Examiner* — Sandra Brase

(74) *Attorney, Agent, or Firm* — Banner & Witcoff, Ltd.

(57) **ABSTRACT**

An image forming apparatus has a body frame and a slide frame. The slide frame is configured to be pulled out from the body frame along a sliding direction. A plurality of image forming cartridges is detachably mounted on the slide frame. A plurality of electrode members is mounted on the slide frame and aligned along the sliding direction so as to correspond to the image forming cartridges. A body-side contact portion of each of the electrode members is electrically connected to the body frame. A cartridge-side contact portion of the electrode member is electrically connected to the image forming cartridge. The image forming cartridge is connected to the body via the corresponding electrode member when the slide frame mounting the image forming cartridges is inserted to the body frame.

**14 Claims, 20 Drawing Sheets**



**Related U.S. Application Data**

continuation of application No. 15/643,939, filed on Jul. 7, 2017, now Pat. No. 10,082,763, which is a continuation of application No. 15/098,590, filed on Apr. 14, 2016, now Pat. No. 9,709,949, which is a continuation of application No. 14/318,039, filed on Jun. 27, 2014, now Pat. No. 9,317,000, which is a continuation of application No. 13/936,528, filed on Jul. 8, 2013, now Pat. No. 8,768,197, which is a continuation of application No. 13/567,404, filed on Aug. 6, 2012, now Pat. No. 8,483,588, which is a continuation of application No. 13/239,966, filed on Sep. 22, 2011, now Pat. No. 8,249,482, which is a continuation of application No. 12/756,486, filed on Apr. 8, 2010, now Pat. No. 8,041,248, which is a continuation of application No. 11/525,070, filed on Sep. 22, 2006, now Pat. No. 7,711,282.

7,155,151	B2	12/2006	Okamoto	
7,466,939	B2	12/2008	Nakashima et al.	
7,711,282	B2	5/2010	Okabe	
8,041,248	B2	10/2011	Okabe	
8,249,482	B2	8/2012	Okabe	
8,483,588	B2	7/2013	Okabe	
8,768,197	B2	7/2014	Okabe	
9,317,000	B2	4/2016	Okabe	
9,709,949	B2	7/2017	Okabe	
10,082,763	B2	9/2018	Okabe	
2002/0191981	A1*	12/2002	Miyabe .....	G03G 21/1867 399/90
2003/0053819	A1	3/2003	Nomura et al.	
2003/0185594	A1	10/2003	Okabe	
2003/0228173	A1	12/2003	Nittani et al.	
2005/0047823	A1	3/2005	Nakashima et al.	
2005/0063735	A1	3/2005	Okabe	
2005/0185980	A1	8/2005	Okamoto	
2006/0210304	A1	9/2006	Nakashima et al.	
2007/0009281	A1	1/2007	Sato et al.	
2007/0009282	A1	1/2007	Sato et al.	

(52) **U.S. Cl.**

CPC ..... **G03G 21/1652** (2013.01); **G03G 21/1676** (2013.01); **G03G 21/1867** (2013.01); **G03G 2221/166** (2013.01); **G03G 2221/1684** (2013.01); **G03G 2221/1815** (2013.01); **G03G 2221/1869** (2013.01)

**FOREIGN PATENT DOCUMENTS**

EP	1422577	A2	5/2004
JP	1-282574	A	11/1989
JP	04-337758	A	11/1992
JP	6-051629	A1	2/1994
JP	9-044061	A	2/1997
JP	10-020743	A	12/2002
JP	2003-295614	A	10/2003
JP	2004-258440	A	9/2004
JP	2005-077440	A	3/2005

(56)

**References Cited**

U.S. PATENT DOCUMENTS

5,521,693	A	5/1996	Kojima et al.
5,802,432	A	9/1998	Coffey et al.
5,815,782	A	9/1998	Yokomori et al.
5,870,655	A	2/1999	Nishiuwatoko et al.
6,101,349	A	8/2000	Ohashi et al.
6,246,841	B1	6/2001	Merrifield et al.
6,272,299	B1	8/2001	Numagami et al.
6,823,160	B2	11/2004	Okabe
6,944,415	B2	9/2005	Nomura
6,973,276	B2	12/2005	Mizoguchi
7,062,192	B2	6/2006	Oguma et al.
7,072,602	B2	7/2006	Hatori et al.
7,092,657	B2	8/2006	Nakashima et al.

**OTHER PUBLICATIONS**

International Search Report dated Oct. 24, 2006, PCT/JP2006/313804.  
 CN Office Action dated Jul. 4, 2008, CN App 2006100924768.  
 JP Office Action dated Apr. 7, 2009, JP App 2005-376522, partial English translation.  
 NZ Office Action dated Sep. 9, 2009, NZ App 565680.  
 JP Office Action dated Jan. 12, 2011, JP Appln. 2005-281139, English translation.

\* cited by examiner




FIG. 1




FIG. 2





FIG.3

100

FIG. 4






FIG. 5




FIG. 6







FIG. 7

FIG. 8



120





FIG. 9

FIG. 10






FIG.11




FIG.12




FIG.13





FIG.14A

FIG.14B



FIG. 15






FIG.16




FIG.17





FIG.18

FIG.19






FIG.20

**IMAGE FORMING APPARATUS, IMAGE  
FORMING CARTRIDGE SUPPORTER, AND  
IMAGE FORMING UNIT**

CROSS-REFERENCE TO RELATED  
APPLICATIONS

This application is a continuation of prior U.S. application Ser. No. 16/130,708, filed Sep. 13, 2018, which is a continuation of prior U.S. application Ser. No. 15/643,939, filed Jul. 7, 2017 (now U.S. Pat. No. 10,082,763B2, issued Sep. 25, 2018), which is a continuation of prior U.S. application Ser. No. 15/098,590, filed Apr. 14, 2016 (now U.S. Pat. No. 9,709,949B2, issued Jul. 18, 2017), which is a continuation of prior U.S. application Ser. No. 14/318,039, filed Jun. 27, 2014 (now U.S. Pat. No. 9,317,000B2, issued Apr. 19, 2016), which is a continuation of prior U.S. application Ser. No. 13/936,528, filed Jul. 8, 2013 (now U.S. Pat. No. 8,768,197B2, issued Jul. 1, 2014), which is a continuation of prior U.S. application Ser. No. 13/567,404, filed Aug. 6, 2012 (now U.S. Pat. No. 8,483,588B2, issued Jul. 9, 2013), which is a continuation of prior U.S. application Ser. No. 13/239,966, filed Sep. 22, 2011 (now U.S. Pat. No. 8,249,482B2, issued Aug. 21, 2012), which is a continuation of prior U.S. application Ser. No. 12/756,486, filed Apr. 8, 2010 (now U.S. Pat. No. 8,041,248B2, issued Oct. 18, 2011), which is a continuation of prior U.S. application Ser. No. 11/525,070, filed Sep. 22, 2006 (now U.S. Pat. No. 7,711,282B2, issued May 4, 2010), which claims priority under 35 U.S.C. § 119(a) on Patent Application No. 2005-281139, filed in Japan on Sep. 28, 2005, the entire contents of which are hereby incorporated by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to an image forming apparatus that is capable of forming a multicolor image, an image forming cartridge supporter that is capable of being pulled out from the body of the image forming apparatus and supporting a plurality of image forming cartridges, and an image forming unit included in the image forming apparatus.

2. Description of the Related Art

Image forming apparatuses are known that removably include an image forming unit which removably contains a plurality of image forming cartridges.

For example, Japanese Patent Application Laid-Open (kokai) No. 4-337758 describes an image forming apparatus including a main cartridge and a plurality of sub cartridges. The main cartridge is removably attached to the body of the image forming apparatus. The main cartridge includes an image carrier on which an electrostatic latent image is formed. The sub cartridges are removably attached to the main cartridge. The sub cartridges are parts of a developing unit. Each sub cartridge includes a developer carrying member (a development roller).

In this image forming apparatus, each of the sub cartridges is electrically connected to the body of the image forming apparatus via the main cartridge. More specifically, one end of the developer carrying member is in contact with a contact member secured to a contact plate disposed on the main cartridge. Additionally, the contact plate is in contact with a contact provided to the body of the image forming

apparatus. Thus, a high-voltage power supply unit provided to the body for applying a developing bias voltage is electrically connected to the developer carrying member so that the developing bias voltage is applied between the image carrier and the developer carrying member.

In the image forming apparatus having such a structure, in order to perform a reliable image forming operation, a reliable electrical connection is required between a power feeding portion (an electrical connection portion) and each of the image forming cartridges. That is, a reliable electrical connection is required between each of the image forming cartridges and the image forming cartridge supporter which is part of the frame of the image forming unit. In addition, a reliable electrical connection is required between the image forming cartridge supporter and the body of the image forming apparatus.

The amounts of consumption of the individual color developer materials are different in the image forming apparatus. Accordingly, every time the developer material of a specific color runs out, it is necessary to pull out the image forming unit from the body, take out the image forming cartridge with the developer material running out from the image forming unit, and do maintenance. To facilitate the maintenance of the image forming apparatus, the image forming cartridge and the image forming cartridge supporter need to be easily removed and mounted.

SUMMARY OF THE INVENTION

Accordingly, it is an object of the present invention to provide an image forming apparatus, an image forming cartridge supporter, and an image forming unit for, when the image forming unit including an image forming cartridge supporter with a plurality of image forming cartridges removably mounted thereon is removably mounted in a body of the image forming apparatus, providing reliable electrical connection in power supply feeding portions of the image forming cartridges and facilitating the maintenance thereof.

In the image forming apparatus according to the present invention, the plurality of image forming cartridges are removably mounted. The image forming apparatus may be configured to form a multicolor image.

The image forming cartridge supporter according to the present invention is configured so as to be capable of being pulled out from the body of the image forming apparatus. Additionally, the image forming cartridge supporter is configured to be capable of supporting the plurality of image forming cartridges.

The plurality of image forming cartridges is removably mounted in the image forming unit according to the present invention. Additionally, the image forming unit can be accommodated in the image forming apparatus capable of forming a multicolor image.

(1) According to the present invention, the image forming apparatus includes a body frame, a slide frame, and a plurality of electrode members. In addition, the image forming cartridge supporter includes the slide frame and the plurality of electrode members. Furthermore, the image forming unit includes the slide frame and the plurality of electrode members.

The body frame is a member configured to comprise the body of the image forming apparatus. The slide frame is supported by the body frame so as to be capable of being pulled out from the body frame in a first direction. The image forming cartridges are aligned along the first direction

and are mountable on and dismountable from the slide frame in a second direction that crosses the first direction.

The electrode members are mounted on the slide frame. The electrode members are aligned along the first direction so as to correspond to the image forming cartridges in a one-to-one fashion. Each of the electrode members includes a body-side contact portion and a cartridge-side contact portion.

The body-side contact portion is disposed so as to protrude towards the body frame. The body-side contact portion is in contact with a body frame contact provided on the body frame so as to be electrically connected to the body frame contact.

The cartridge-side contact portion is disposed so as to protrude towards the image forming cartridge. The cartridge-side contact portion is in contact with an image forming cartridge contact provided on the image forming cartridge so as to be electrically connected to the image forming cartridge contact.

In such a structure, when the slide frame is pulled out from the body frame in the first direction, the physical contact between the body-side contact portion on the slide frame and the body frame contact on the body frame is released. Thus, the electrical connection between the body-side contact portion and the body frame contact is released. In addition, when the image forming cartridge is pulled out from the slide frame in the dismounting direction, the physical contact between the cartridge-side contact portion on the slide frame and the image forming cartridge contact on the image forming cartridge is released. Thus, the electrical connection between the cartridge-side contact portion and the image forming cartridge contact is released.

In contrast, when the slide frame is inserted into the body frame along the first direction and is mounted on the body frame in a predetermined state, the body-side contact portion protruding towards the body frame is brought into contact with the body frame contact. Thus, the body-side contact portion is electrically connected to the body frame contact. Furthermore, the image forming cartridge is inserted into the slide frame in the mounting direction and is mounted on the slide frame, the cartridge-side contact portion is brought into contact with the image forming cartridge contact. Accordingly, the cartridge-side contact portion is electrically connected to the image forming cartridge contact. In this way, the body frame (the body frame contact) is electrically connected to the image forming cartridge (the image forming cartridge contact) via the electrode member including the body-side contact portion and the cartridge-side contact portion.

As noted above, in this structure, by simply mounting the slide frame on the body frame, electrical connection between the body and the image forming cartridge mounted on the slide frame is achieved. In addition, in this structure, by simply pulling out the slide frame from the body frame along the first direction, the electrical connection between the body and the image forming cartridge is released. Furthermore, in this structure, the first directions in which the slide frame is mounted on and dismounted from the body frame cross the second direction in which the image forming cartridge is mounted on and dismounted from the slide frame.

The advantages of this structure are as follows. According to this structure, the relative movement between the body of the image forming apparatus and the image forming cartridge supporter (the image forming unit) along the first direction is synchronized with the open and close of the electrical connection. Accordingly, the electrical connection

between the body and the image forming cartridge is easily achieved by means of a simple structure. Thus, according to this structure, the maintenance of the image forming apparatus is facilitated.

Furthermore, according to this structure, as noted above, since the first direction crosses the second direction, changes in a mounting state of the image forming cartridge with respect to the slide frame can be inhibited when the slide frame slides in the first direction. Accordingly, when the slide frame is inserted into the body frame in the first direction, a loose electrical connection between the cartridge-side contact portion of the electrode member and the image forming cartridge contact caused by a positional shift of the slide frame from the image forming cartridge can be inhibited. Consequently, a reliable electrical connection between the body of the image forming apparatus and the image forming cartridge can be achieved. (1') Here, for example, it is desirable that the first direction is substantially perpendicular to the second direction (at an angle of about 50° to about 130°).

Also, it is desirable that the cartridge-side contact portion is disposed inside the slide frame.

In such a structure, the cartridge-side contact portion is disposed so as to protrude from inside the slide frame towards the image forming cartridge. That is, the cartridge-side contact portion of the electrode member for electrical connection with the image forming cartridge that is disposed inside the slide frame is accommodated in a space inside the slide frame. Additionally, the protrusion of the electrode member that protrudes outwardly from the slide frame can be limited to the body-side contact portion for electrical connection with the body that is outside of the slide frame.

In such a structure, mechanical interference between the body frame contact provided on the body frame and the cartridge-side contact portion is inhibited. Thus, in this structure, reliable electrical connection between the body and the slide frame and reliable electrical connection between the slide frame and the image forming cartridge can be achieved. (1'') The slide frame may be configured so as to be removable from the body frame. That is, the image forming cartridge supporter (the image forming cartridge unit) may be completely detached from the body. In other words, the image forming cartridge supporter (the image forming cartridge unit) may be configured so as to be interchangeable.

According to this structure, the maintenance of the image forming apparatus can be facilitated. (2) The slide frame may include a guiding portion formed thereon guiding the image forming cartridge in the second direction, and the cartridge-side contact portion may be disposed so as to face the guiding portion.

In such a structure, when the image forming cartridge is mounted on the slide frame, the image forming cartridge is guided by the guiding portion in the second direction. After the image forming cartridge is mounted on the slide frame, the image forming cartridge contact provided on the image forming cartridge is in contact with the cartridge-side contact portion that is disposed so as to face the guiding portion. Accordingly, electrical connection between the image forming cartridge contact and the cartridge-side contact portion is achieved.

According to this structure, the advantages are as follows. In this structure, the image forming cartridge is guided by the guiding portion, and therefore, electrical connection between the image forming cartridge contact and the cartridge-side contact portion that is disposed so as to face the



## 5

guiding portion is achieved. Accordingly, the reliability of the electrical connection can be improved.

(3) The slide frame may include a pair of side panels disposed parallel to both the first direction and the second direction, and the guiding portion may include a guide groove formed on the side panel.

In such a structure, when the image forming cartridge is mounted on the slide frame, the image forming cartridge is inserted into a space surrounded by the pair of side panels. At that time, the image forming cartridge is guided by the guide groove along the second direction.

According to this structure, the advantages are as follows. In this structure, the image forming cartridge is guided by the guiding groove, and therefore, electrical connection between the image forming cartridge contact and the cartridge-side contact portion that is disposed so as to face the guiding groove is achieved. Accordingly, the reliability of the electrical connection can be improved by means of a simple structure.

(4) The electrode member may include a wire-shaped connecting portion that connects the body-side contact portion to the cartridge-side contact portion and may be disposed in the vicinity of the guide groove on the side panel.

According to this structure, the advantages are as follows. In this structure, the electrode member that electrically connects the body of the image forming apparatus to the image forming cartridge can be formed as a significantly simple structure. Additionally, since the electrode member is disposed in the vicinity of the guide groove, electrical connection between the image forming cartridge contact and the cartridge-side contact portion that is disposed so as to face the guiding groove is reliably achieved.

(5) The connecting portion and the cartridge-side contact portion may be integrated into a wire-like member having a shape of a torsion coil spring, and the cartridge-side contact portion may be formed from an arm portion extending outwardly from a coil portion in the shape of the torsion coil spring.

In such a structure, since the image forming cartridge contact presses the arm portion against the elastic force of the torsion coil spring, physical contact and electrical connection between the arm portion (the cartridge-side contact portion) and the image forming cartridge contact are achieved.

According to this structure, the advantages are as follows. In this structure, the electrode member that electrically connects the body of the image forming apparatus to the image forming cartridge can be formed as a significantly simple structure. Additionally, due to the elastic force of the torsion coil spring, physical contact and establishment of electrical connection between the cartridge-side contact portion and the image forming cartridge contact can be reliably achieved.

(6) The image forming cartridge contact may include a conductive protrusion that is formed so as to be accommodated in the guide groove, and the cartridge-side contact portion may be in contact with the protrusion so as to be electrically connected to the protrusion.

In such a structure, when the image forming cartridge is mounted on the slide frame, the protrusion is accommodated in the guide groove. Accordingly, the image forming cartridge is guided by the guide groove, and the protrusion is brought into contact with the cartridge-side contact portion. Thus, electrical connection between the protrusion and the cartridge-side contact portion is achieved.

According to this structure, the advantages are as follows. In this structure, the image forming cartridge can be

## 6

smoothly mounted on the slide frame by means of a significantly simple structure. Additionally, reliable electrical connection between the image forming cartridge and the cartridge-side contact portion can be achieved by means of a significantly simple structure.

(7) The image forming cartridge may include a development roller disposed so as to face an image carrier on which an electrostatic latent image is formed, and the protrusion may be formed from a conductive synthetic resin collar member that covers the metallic center shaft protruding from an end of the development roller in the length direction of the development roller.

In such a structure, when the image forming cartridge is mounted on the slide frame, the collar member is accommodated in the guide groove. Accordingly, the image forming cartridge is guided by the guide groove, and the collar member is brought into contact with the cartridge-side contact portion. Thus, electrical connections between the cartridge-side contact portion and the collar member and between the cartridge-side contact portion and the development roller are achieved.

According to this structure, reliable electrical connection between the development roller and the cartridge-side contact portion can be achieved by means of a significantly simple structure.

(8) The side panel may be separated into a plurality of sections, which correspond to the image forming cartridges and are aligned along the first direction, and a supporting plate is disposed outside the plurality of sections so as to support the plurality of sections. Also, the body-side contact portion may be disposed so as to pass through the supporting plate and so as to be exposed to outside the supporting plate.

According to this structure, the side plate and the guide groove can be produced by means of a significantly simple manufacturing process at low cost.

(9) A driving force may be transferred from the body frame to one end of the image forming cartridge in a third direction that is perpendicular to the first direction and the second direction, and the electrode member may be disposed so as to face the other end of the image forming cartridge.

In such a structure, the driving force is transferred from the body frame to one end of the image forming cartridge in the third direction. In contrast, electrical connection between the image forming cartridge and the body is achieved at the other end of the image forming cartridge in the third direction via the electrode member.

According to this structure, the advantages are as follows. In this structure, even when foreign materials, such as dust and grease, are generated on a portion to which the driving force is transferred, deposition of the foreign materials to electrical contacts between the electrode member and the image forming cartridge contact and between the electrode member and the body frame contact can be reliably inhibited. Accordingly, reliable electrical connection at the electrical contacts can be achieved.

(10) The electrode member may be configured as follows: the cartridge-side contact portion is pressed in a third direction crossing the second direction so as to be in contact with the image forming cartridge contact. Additionally, the body-side contact portion is pressed in a fourth direction crossing the first direction so as to be in contact with the body frame contact.

In such a structure, the cartridge-side contact portion is pressed in the third direction crossing the first direction. Accordingly, the body-side contact portion is brought into contact with the body frame contact. Additionally, the cartridge-side contact portion is pressed in the fourth direction

crossing the second direction. Accordingly, the cartridge-side contact portion is brought into contact with the image forming cartridge contact.

According to this structure, the advantages are as follows. In this structure, the first direction in which the slide frame is inserted into the body frame crosses the fourth direction in which the body frame contact is pressed by the body-side contact portion. Accordingly, reliable electrical connection between the body frame contact and the body-side contact portion can be achieved by means of a simple structure.

Furthermore, according to this structure, the second direction along which the image forming cartridge moves relative to the slide frame when the image forming cartridge is mounted and dismounted crosses the third direction in which the cartridge-side contact portion is pressed by the image forming cartridge contact. Accordingly, the mount and dismount operation of the image forming cartridge is not affected by the pressure between the cartridge-side contact portion and the image forming cartridge contact. Accordingly, the mount and dismount operation of the image forming cartridge can be smoothly carried out. In addition, reliable electrical connection between the cartridge-side contact portion and the image forming cartridge contact can be achieved by means of a simple structure.

(11) The electrode member may be configured so that the third direction crosses the fourth direction.

According to this structure, when the image forming cartridge is mounted on the slide frame along the second direction, the cartridge-side contact portion and the image forming cartridge contact press each other. Thus, electrical connection between the cartridge-side contact portion and the image forming cartridge contact is achieved. Thereafter, the slide frame is inserted into the body frame along the first direction and is mounted on the body frame. At that time, the body-side contact portion and the body frame contact press each other in the fourth direction crossing the third direction in which the cartridge-side contact portion and the image forming cartridge contact press each other. Thus, electrical connection between the body-side contact portion and the body frame contact is achieved. In this way, electrical connection between the body frame (the body frame contact) and the image forming cartridge (the image forming cartridge contact) can be achieved via the electrode member including the body-side contact portion and the cartridge-side contact portion.

According to this structure, the advantages are as follows. In this structure, the size of the apparatus can be reduced, compared with the case where the third direction in which the cartridge-side contact portion and the image forming cartridge contact press each other is parallel to the fourth direction in which the body-side contact portion and the body frame contact press each other.

Additionally, when the body-side contact portion and the cartridge-side contact portion for one image forming cartridge are integrated into one component, the direction of a pressing force exerted on the body-side contact portion crosses the direction of a pressing force exerted on the cartridge-side contact portion. Accordingly, interference between the pressing force exerted on the body-side contact portion and the pressing force exerted on the cartridge-side contact portion can be inhibited. Consequently, unreliable electrical connections at the body-side contact portion and the cartridge-side contact portion can be inhibited. As a result, reliable electrical connection between the cartridge-side contact portion and the image forming cartridge contact can be achieved by means of a simple structure.

(12) The image forming cartridge and the slide frame may have structures in which the image forming cartridge is pressed in a sixth direction along the third direction which the cartridge-side contact portion and the image forming cartridge contact press each other (hereinafter also referred to as a "pressing direction") so that the position of the image forming cartridge relative to the slide frame is determined.

According to this structure, when the image forming cartridge is pressed in the sixth direction, the position of the image forming cartridge relative to the slide frame is determined. At that time, the image forming cartridge contact provided on the image forming cartridge and the cartridge-side contact portion provided on the slide frame press each other along the sixth direction.

There are following two cases: the sixth direction is equal to the pressing direction; and the sixth direction is equal to the direction opposite the pressing direction.

According to this structure, the advantages are as follows. In the case where the sixth direction is equal to the pressing direction, since the sixth direction is equal to the pressing direction, the reliable positioning can be achieved. In the case where the sixth direction is equal to the direction opposite the pressing direction, when the position of the image forming cartridge relative to the slide frame is determined, the image forming cartridge contact and the cartridge-side contact portion press each other so that electrical connection between the image forming cartridge contact and the cartridge-side contact portion is achieved. Consequently, reliable electrical connection caused by the contact between the image forming cartridge contact and the cartridge-side contact portion can be achieved by means of a simple structure.

(13) The sixth direction may be along a seventh direction in which the image forming cartridge receives a force from the body frame when the image forming cartridge carries out an image forming operation.

In such a structure, when the image forming cartridge carries out an image forming operation, the image forming cartridge is pressed in the seventh direction which is along the sixth direction. Thus, the position of the image forming cartridge relative to the slide frame is determined. At that time, the image forming cartridge contact provided on the image forming cartridge and the cartridge-side contact portion provided on the slide frame press each other along the sixth direction.

According to this structure, the advantages are as follows. In this structure, when the image forming cartridge carries out an image forming operation, by using the force received by the image forming cartridge from the body frame, positioning between the image forming cartridge and the slide frame (and electrical connection between the image forming cartridge contact and the cartridge-side contact portion) can be reliably achieved in a simple structure.

(14) The number of the plurality of the electrode members may be equal to the number of the plurality of image forming cartridges.

In such a structure, the electrode members that electrically connect the body of the image forming apparatus to the plurality of image forming cartridges can be formed by means of a significantly simple structure.

(15) A plurality of image carriers may be disposed in the slide frame. In such a case, the image forming cartridge may be disposed so as to face one of the image carriers and develop an electrostatic latent image formed on a peripheral surface of the corresponding image carrier when the image forming cartridge is mounted in the slide frame. Here, the image carrier has a cylindrical shape and is disposed along

a third direction that is perpendicular to both the first direction and the second direction. Additionally, the image carriers are aligned along the first direction so as to correspond to the image forming cartridges in a one-to-one fashion. Each of the image carriers is rotatably supported by the slide frame.

In such a structure, the image forming cartridge is inserted into the slide frame along the second direction and is mounted on the slide frame. At that time, physical contact and electrical connection between the cartridge-side contact portion and the image forming cartridge contact is achieved. In addition, the image forming cartridge is disposed so as to face the image carrier. Thus, the image forming cartridge can develop the electrostatic latent image formed on the peripheral surface of the image carrier.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of the appearance of a color laser printer, which is an image forming apparatus according to an embodiment of the present invention;

FIG. 2 is a perspective view of the color image forming unit when the color image forming unit shown in FIG. 1 is pulled out towards the front side;

FIG. 3 is a perspective view of the color image forming unit when the color image forming unit shown in FIG. 1 is further pulled out towards the front side and is removed to outside a body of the color laser printer;

FIG. 4 is a side cross-sectional view of the color laser printer shown in FIG. 1;

FIG. 5 is a side cross-sectional view of the image forming cartridge and a drum unit shown in FIG. 4;

FIG. 6 is a side cross-sectional view of the image forming cartridge shown in FIG. 4;

FIG. 7 is a side elevational view of the image forming cartridge shown in FIG. 4;

FIG. 8 is a plan view of the image forming cartridge shown in FIG. 4;

FIG. 9 is a perspective view, viewed from above at an oblique angle (the same direction as that of FIG. 3), of the color image forming unit shown in FIGS. 1 to 3;

FIG. 10 is a side elevational view of the color image forming unit shown in FIG. 9;

FIG. 11 is a perspective view, viewed from above at an oblique angle, of a slide frame shown in FIG. 9 when all the image forming cartridges are removed;

FIG. 12 is a perspective view of a pair of the side plates and the drum unit removed from the structure shown in FIG. 11;

FIG. 13 is a perspective view of the pair of the side plates and the drum unit when the pair of the side plates and the drum unit shown in FIG. 12 are disassembled;

FIG. 14A is a perspective view of the side plate when viewed from inside the slide frame and FIG. 14B is a perspective view of the side plate when viewed from outside the slide frame;

FIG. 15 is an enlarged perspective view of an electrode member shown in FIG. 14B;

FIG. 16 is a partial exploded perspective view of the color image forming unit shown in FIG. 9;

FIG. 17 is a perspective view of a main portion of the outer surface of the side plate shown in FIG. 16;

FIG. 18 is a perspective view of the color image forming unit and the image forming cartridge shown in FIG. 9 when the image forming cartridge is mounted on or dismounted from the color image forming unit;

FIG. 19 is a partial exploded side elevational view of the color image forming unit shown in FIG. 10; and

FIG. 20 is a side cross-sectional view of the structure of a modification of the image forming cartridge shown in FIG. 6.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

Preferred embodiments of the present invention (what the inventor believes to be the best mode for practicing the present invention at the time this application was filed) are described with reference to the accompanying drawings.

##### Outline of Architecture of Color Laser Printer

FIG. 1 is a perspective view of a color laser printer 100, which is an image forming apparatus according to an embodiment of the present invention.

A body section 110, which defines a body of the color laser printer 100, includes a body casing 111 and a body frame 112 accommodated in the body casing 111.

The body casing 111 has a parallelepiped shape formed from synthetic resin plates. A catch tray 111b is formed to the top surface 111a of the body casing 111. The catch tray 111b includes a part of the top surface 111a that slopes downward from the front side (proximal side) to the back side (distal side) thereof. That is, a recess formed on the top surface 111a functions as the catch tray 111b. A paper ejection port 111c, which is an opening, is formed on the upper portion of the body casing 111 and above the lower end of the catch tray 111b. The catch tray 111b can hold a paper sheet ejected from the paper ejection port 111c.

A front opening 111d is formed on the front side of the body casing 111. In addition, a planar front cover 111e is attached to the front side of the body casing 111 so as to cover the front opening 111d. The front cover 111e is supported in a pivotal manner about the lower end thereof.

The body frame 112 supports a variety of parts accommodated in the body section 110 and needed for an image forming operation. The body frame 112 includes a driving source and a driving force transmission mechanism for rotatably driving the above-described parts.

In the interior of the body frame 112, a pair of upper guide rails 112a and a pair of lower guide rails 112b extend inwardly. The upper guide rails 112a have a length direction which is indicated by arrow S (a sliding direction). The sliding direction corresponding to the first direction in the present invention is substantially parallel to the fore-aft direction of the color laser printer 100. The upper guide rails 112a are aligned along a width direction of the color laser printer 100 (i.e., a direction perpendicular to the sliding direction and the vertical direction) so as to extend towards inside the color laser printer 100. The lower guide rails 112b are disposed so as to be substantially parallel to the upper guide rails 112a. An image-forming-unit removal guide groove 112c is formed between the upper guide rail 112a and the lower guide rail 112b on either side.

A color image forming unit 120 is accommodated in the body frame 112. The color image forming unit 120 includes a slide frame 130 and an image forming cartridge 140. The slide frame 130 serves as a member (an image forming cartridge supporter) for supporting the image forming cartridge 140. The image forming cartridge 140 is supported by the body frame 112 so as to be pulled out from the body frame 112 in the sliding direction (the direction indicated by arrow S). A front beam 131 of the slide frame 130 is

disposed so as to face the front opening **111d**. A front-side grip **131a** is formed on the proximal side of the front beam **131** (i.e., the front side).

In the color laser printer **100** according to the present embodiment, when the front cover **111e** is open towards the front side and the front-side grip **131a** is pulled out in the sliding direction (the direction indicated by arrow S), as shown in FIG. 1, the color image forming unit **120** is pulled out towards the front side, as shown in FIGS. 2 and 3.

FIG. 2 is a perspective view of the color image forming unit **120** when the color image forming unit **120** shown in FIG. 1 is pulled out towards the front side. FIG. 3 is a perspective view of the color image forming unit **120** when the color image forming unit **120** is further pulled out and is removed from the body section **110**.

As shown in FIG. 2, two supporting plates **132** and **133** are connected to either end of the front beam **131**. The supporting plates **132** and **133** are disposed so as to be perpendicular to a horizontal plane and so as to be parallel to the sliding direction. A flange **132a** is formed on the upper end of the supporting plate **132**. The flange **132a** extends outwardly so as to be accommodated in the image-forming-unit removal guide groove **112c** formed on the body frame **112**. Similarly, a flange **133a** is formed on the upper end of the supporting plate **133**.

Thus, according to the present embodiment, for the body frame **112** and the slide frame **130**, the flanges **132a** and **133a** are guided by the image-forming-unit removal guide groove **112c** so that the color image forming unit **120** can be pulled out in the sliding direction.

As shown in FIG. 3, the slide frame **130** is removable from the body frame **112**. That is, the slide frame **130** can be completely separated from the body section **110** so that the color image forming unit **120** is interchangeable.

The slide frame **130** includes the front beam **131**, the supporting plate **132**, the supporting plate **133**, a rear beam **134**, and side plates **135**, and side plates **136**.

The front end of either one of the supporting plates **132** and **133** is connected to the front beam **131**. The rear end of either one of the supporting plates **132** and **133** is connected to the rear beam **134**. These front beam **131**, the supporting plate **132**, the supporting plate **133**, and the rear beam **134** forms a rectangular frame in plan view, which serves as a main frame of the slide frame **130**. Inside the rectangular frame, the four image forming cartridges **140** are aligned along the sliding direction.

An inverted U-shaped back-side grip **134a** is formed on the upper end of the rear beam **134**. The front-side grip **131a** and the back-side grip **134a** are formed so that the color image forming unit **120** (the slide frame **130**) can be easily carried by holding the back-side grip **134a** and the front-side grip **131a**.

A pair of the side plates **135** and **136** supports the image forming cartridge **140** in the slide frame **130**. According to the present embodiment, four pairs of side plates **135** and **136** are provided so as to correspond to the four image forming cartridges **140**. Four pairs of the side plates **135** and **136** are aligned along the sliding direction. The four side plates **135** are supported by the supporting plate **132** disposed outside the side plates **135**. Similarly, the four side plates **136** are supported by the supporting plate **133** disposed outside the side plates **136**.

#### Outline of Internal Structure of Color Laser Printer

FIG. 4 is a side cross-sectional view of the color laser printer **100** shown in FIG. 1. As noted above, in the body section **110** of the color laser printer **100**, a plurality of the image forming cartridges **140** are arranged. A plurality of

drum units **150** are arranged so as to face the plurality of the image forming cartridges **140**, respectively. A scanner unit **160** is disposed above the image forming cartridges **140** and the drum units **150**. A transfer unit **170** is disposed under the image forming cartridges **140** and the drum units **150**. A feeder unit **180** is disposed under the transfer unit **170**.

#### Outline of Structure of Image Forming Cartridge

The image forming cartridges **140** contain black toner (developer material), cyan toner, magenta toner, and yellow toner, respectively. That is, a black image forming cartridge **140K** contains black toner. A cyan image forming cartridge **140C** contains cyan toner. A magenta image forming cartridge **140M** contains magenta toner. A yellow image forming cartridge **140Y** contains yellow toner. The black image forming cartridge **140K**, the cyan image forming cartridge **140C**, the magenta image forming cartridge **140M**, and the yellow image forming cartridge **140Y** have the same structure.

Each of the image forming cartridges **140** includes a cartridge case **141**, an agitator **142**, a supply roller **143**, a development roller **144**, and a blade **145**.

The cartridge case **141** can support the agitator **142**, the supply roller **143**, the development roller **144**, and the blade **145**, and can also contain toner, which serves as a developer material for developing an electrostatic latent image.

The agitator **142** agitates the toner particles contained in the cartridge case **141**. The agitator **142** is rotatably supported by the cartridge case **141**.

The supply roller **143** is formed from a sponge roller. The supply roller **143** is rotatably supported by the cartridge case **141**. The development roller **144** is formed from a rubber roller. The development roller **144** is also rotatably supported by the cartridge case **141**. The supply roller **143** and the development roller **144** are disposed in parallel so as to be in contact with each other.

The supply roller **143** is rotatably driven in a direction shown by an arrow of FIG. 4 so as to supply the periphery of the development roller **144** with charged toner particles. The blade **145** is in contact with the peripheral surface of the development roller **144**, which is rotatably driven in the direction shown by an arrow of FIG. 4, in the counter direction so as to control the amount of toner particles deposited on the peripheral surface.

The structure of the image forming cartridge **140** will be described in more detail later.

#### Outline of Structure of Drum Unit

Each of the drum units **150** includes a photoconductive drum **151** and a scorotron charger **152**.

The photoconductive drum **151** allows an electrostatic latent image to be formed on the peripheral surface thereof. The photoconductive drum **151** is disposed so as to face the development roller **144** of the image forming cartridge **140**. The scorotron charger **152** uniformly charges the peripheral surface of the photoconductive drum **151**. The structure of the drum unit **150** will be described in more detail later.

In the scanner unit **160**, a laser beam generated by a laser emitting unit (not shown) on the basis of image data scans the peripheral surface of the photoconductive drum **151** in the width direction (a direction that is perpendicular to the plane of FIG. 4).

#### Structure of Transfer Unit

The transfer unit **170** includes a belt driving roller **171**, a driven roller **172**, a transport belt **173**, a transfer roller **174**, and a belt cleaner **175**.

The belt driving roller **171** is disposed closer to the back side than the drum unit **150** that faces the black image forming cartridge **140K** located at the closest position to the

back side among the plurality of image forming cartridges **140**. The driven roller **172** is disposed closer to the front side than the drum unit **150** that faces the yellow image forming cartridge **140Y** located at the closest position to the front side among the plurality of image forming cartridges **140**. The belt driving roller **171** and the driven roller **172** are rotatably supported by the body section **110**.

The transport belt **173** is in the form of a continuous belt. The transport belt **173** is formed from a conductive resin film such as a conductive polycarbonate or polyimide film in which conductive particles (such as carbon particles) are dispersed. The transport belt **173** is entrained about the belt driving roller **171** and the driven roller **172**. When the belt driving roller **171** rotates in the direction shown by an arrow in FIG. 4, the transport belt **173** moves in the direction shown by an arrow in FIG. 4. That is, when the transport belt **173** moves in the direction shown by an arrow in FIG. 4, a paper sheet P held on the transport belt **173** can be transported in the direction in which the image forming cartridges **140** are aligned.

The transfer roller **174** is disposed beneath the photoconductive drum **151** so as to face the photoconductive drum **151** with the transport belt **173** therebetween. The transfer roller **174** is rotatably supported. The transfer roller **174** can rotate in synchronization with the movement of the transport belt **173** in a direction indicated by arrows of FIG. 4. A high-voltage power supply for outputting a transfer bias voltage is electrically connected to the transfer roller **174** so that the toner particles on the photoconductive drum **151** are transferred towards the transport belt **173** (onto the paper sheet P).

The belt cleaner **175** is disposed beneath the transport belt **173** that is entrained under the transfer rollers **174**. The belt cleaner **175** is configured to clean the surface areas of the transport belt **173** which have faced the image forming cartridges **140** and the drum units **150**.

#### Structure of Feeder Unit

A feeder case **181** defines a casing of the feeder unit **180**. The feeder case **181** can store a plurality of the stacked paper sheets P. A sheet pressure plate **182** is disposed in the feeder case **181**. A rear end **182a** of the sheet pressure plate **182**, which is located at the back side (the left-hand side in FIG. 4), is rotatably supported by the feeder case **181**. That is, the sheet pressure plate **182** is pivotably supported by the feeder case **181** so that a front end **182b** of the sheet pressure plate **182**, which is located at the front side (the right-hand side in FIG. 4), can substantially vertically move.

A feed roller **183** is disposed above the front end **182b** of the sheet pressure plate **182**. The feed roller **183** is formed from synthetic rubber. The feed roller **183** is supported by the body section **110** so as to be rotatably driven in the direction indicated by an arrow of FIG. 4. When the feed roller **183** is rotatably driven in the direction indicated by the arrow of FIG. 4, the feed roller **183** can feed the paper sheet P stored in the feeder case **181** towards the front side (the right-hand side in FIG. 4).

In the direction in which the paper sheet P is fed by the feed roller **183** (the front side, i.e., the right-hand side in FIG. 4), a separation roller **184** is disposed. The separation roller **184** is formed from synthetic rubber. The separation roller **184** is supported by the body section **110** so as to be rotatably driven in the direction indicated by an arrow of FIG. 4.

A separation pad **185** is disposed so as to face the separation roller **184**. The separation pad **185** has a separation surface **185a** that faces the separation roller **184**. The separation surface **185a** is formed from a material having a

high coefficient of friction (such as synthetic rubber or felt). A separation pad biasing spring **186** is disposed beneath the separation pad **185**. The separation pad biasing spring **186** presses the separation pad **185** against the separation roller **184** so that the separation roller **184** and the separation pad **185** press each other.

When the separation roller **184** is rotatably driven in the direction indicated by an arrow of FIG. 4, the separation roller **184**, the separation pad **185**, and the separation pad biasing spring **186** separate the paper sheets P one by one and deliver the paper sheet P into a nip formed by a paper-dust removal roller **187** and a pinch roller **188**.

The paper-dust removal roller **187** removes paper dusts deposited on the paper sheet P. The paper-dust removal roller **187** is disposed so as to face the pinch roller **188**. The paper-dust removal roller **187** is also disposed so as to be parallel to the pinch roller **188** along the direction in which the paper sheet P is fed by the separation roller **184**.

#### Structure of Sheet Transport and Fixing System

In the transfer unit **170**, at a position closer to the front side than the driven roller **172**, a sheet transport roller **191** and a sheet guide **192** are disposed. The sheet transport roller **191** and the sheet guide **192** are configured to transport the paper sheet P fed from the feeder unit **180** onto the transport belt **173** disposed on the peripheral surface of the driven roller **172**.

In the transfer unit **170**, a fixing unit **193** is disposed at a position that is closer to the back side than the belt driving roller **171** and that is the destination of the paper sheet P delivered by the belt driving roller **171** and the transport belt **173**.

The fixing unit **193** includes a heat roller **193a** and a pressure roller **193b**. The heat roller **193a** includes a metallic cylinder with the surface subjected to a mold release treatment. The metallic cylinder accommodates a halogen lamp. The heat roller **193a** is rotatably supported so as to be driven in a direction indicated by an arrow in FIG. 4 (in the clockwise direction). The pressure roller **193b** is formed from a silicon rubber. The pressure roller **193b** is disposed so as to press against the heat roller **193a** at a predetermined pressure. The pressure roller **193b** is rotatably supported so that the rotation of the pressure roller **193b** follows the rotation of the heat roller **193a**. Thus, the pressure roller **193b** rotates in the counterclockwise direction in FIG. 4. In the fixing unit **193**, when the heat roller **193a** is rotatably driven in a direction indicated by an arrow of FIG. 4, the toner particles deposited on the paper sheet P are fused (fixed) to the paper sheet P while the paper sheet P is transported towards the paper ejection port **111c**.

The paper sheet P is transported by the heat roller **193a** and the pressure roller **193b** to a fused sheet transport roller **194** and a pinch roller **195**. The fused sheet transport roller **194** is rotatably supported so as to be driven in a direction indicated by an arrow of FIG. 4. The pinch roller **195** is disposed so as to face the fused sheet transport roller **194**. The pinch roller **195** is rotatably supported so that the rotation of the pinch roller **195** follows the rotation of the fused sheet transport roller **194** indicated by an arrow of FIG. 4. Thus, when the fused sheet transport roller **194** and the pinch roller **195** rotate in the directions indicated by the arrow of FIG. 4 for the fused sheet transport roller **194**, the fused sheet transport roller **194** and the pinch roller **195** can transport the fused paper sheet P towards the paper ejection port **111c**.

The fused sheet transport roller **194** and the pinch roller **195** transport the fused paper sheet P to fused sheet guides **196a** and **196b**. The fused sheet guides **196a** and **196b** can

guide the fused paper sheet P transported by the fused sheet transport roller 194 and the pinch roller 195 to a contact point between a paper ejection roller 197 and a paper ejection driven roller 198.

The paper ejection roller 197 and the paper ejection driven roller 198 are disposed in the vicinity of the paper ejection port 111c so as to face the paper ejection port 111c. The paper ejection roller 197 is rotatably disposed so as to be driven in a direction indicated by an arrow of FIG. 4. The paper ejection driven roller 198 is disposed so as to face the paper ejection roller 197. The paper ejection driven roller 198 is rotatably supported so that the rotation of the paper ejection driven roller 198 follows the rotation of the paper ejection roller 197 indicated by an arrow of FIG. 4. Thus, when the paper ejection roller 197 and the paper ejection driven roller 198 rotate in the directions indicated by the arrow of FIG. 4 for the paper ejection roller 197, the paper ejection roller 197 and the paper ejection driven roller 198 can eject the fused paper sheet P to outside the body section 110.

#### Detailed Internal Structure of Image Forming Cartridge

FIG. 5 is a side cross-sectional view of the image forming cartridge 140 and the drum unit 150 shown in FIG. 4.

As shown in FIG. 5, the cartridge case 141 includes a toner container case 141a that forms a toner container 140a for storing toner particles and a roller supporter 141b for rotatably supporting a supply roller 143 and a development roller 144.

A cartridge grip 141a1 is formed on the top surface of the toner container case 141a. The cartridge grip 141a1 is used to mount or dismount the image forming cartridge 140. Partition walls 141c and 141d are formed in the interface between the toner container case 141a and the roller supporter 141b. A toner passage opening 141e for allowing the toner particles to pass therethrough is formed between the partition walls 141c and 141d.

The agitator 142 is rotatably disposed in the toner container 140a of the toner container case 141a. The agitator 142 includes a metallic agitator rotation center shaft 142a and an agitating member 142b secured to the agitator rotation center shaft 142a. When the agitator 142 is rotatably driven, the agitator 142 agitates the toner particles contained in the toner container 140a and delivers the toner particles to the toner passage opening 141e.

The supply roller 143 is rotatably supported in the roller supporter 141b and in the vicinity of the toner passage opening 141e. The supply roller 143 is disposed between the development roller 144 and the toner passage opening 141e. The supply roller 143 includes a metallic supply-roller rotation center shaft 143a and a sponge layer 143b formed around the supply-roller rotation center shaft 143a. When the supply roller 143 is rotatably driven in a direction indicated by an arrow of FIG. 5, the supply roller 143 can supply the toner particles delivered through the toner passage opening 141e to a contact point between the supply roller 143 and the development roller 144.

A development-roller exposure opening 141f is formed on an end of the cartridge case 141 adjacent to the roller supporter 141b. The development-roller exposure opening 141f is formed so that the peripheral surface of the development roller 144 can be exposed to outside the cartridge case 141 (to the peripheral surface of the photoconductive drum 151).

The development roller 144 includes a metallic development-roller rotation center shaft 144a and a semiconductive rubber layer 144b formed around the development-roller rotation center shaft 144a. The semiconductive rubber layer

144b is formed by mixing carbon black with synthetic rubber. That is, the development roller 144 is formed so that a developing bias voltage can be applied to the interface between the peripheral surface of the development roller 144 and the photoconductive drum 151.

The development roller 144 is disposed so as to press against the sponge layer 143b of the supply roller 143 at a predetermined pressure. Thus, the sponge layer 143b deforms when pressed by the development roller 144. Additionally, when the development roller 144 and the supply roller 143 are rotatably driven in the directions indicated by the arrows of FIG. 5, toner particles are tribocharged at the interface between the supply roller 143 and the development roller 144. The charged toner particles are supplied to the peripheral surface of the development roller 144.

The blade 145 includes a blade body 145a and a blade tip 145b. The blade body 145a is formed from a flexible metallic plate. The blade tip 145b is formed from synthetic rubber. The blade tip 145b is secured at the top end of the blade body 145a. The base end of the blade body 145a (an end remote from the end at which the blade tip 145b is secured) is pressed by a blade presser 145c formed from a metallic plate and is secured to the cartridge case 141 by means of, for example, a screw. At that time, the blade 145 is disposed so that, since the blade body 145a resiliently deforms, the blade tip 145b is pressed against the peripheral surface of the development roller 144 at a predetermined pressure. Since the blade tip 145b is pressed against the peripheral surface of the development roller 144 at a predetermined pressure, the blade 145 can control the amount of toner particles deposited on the peripheral surface of the development roller 144 and the amount of charge retained on the peripheral surface of the development roller 144.

#### Detailed Structure of Drum Unit

As shown in FIG. 5, the drum unit 150 includes the photoconductive drum 151, the scorotron charger 152, a drum cleaner 153, and a drum unit frame 154.

The photoconductive drum 151 includes a metallic photoconductive-drum rotation center shaft 151a and a sleeve-shaped drum body 151b formed around the metallic photoconductive-drum rotation center shaft 151a. The drum body 151b includes a metallic sleeve and a photoconductive layer (a photoconductive resin layer) formed on the outer surface of the sleeve. The photoconductive-drum rotation center shaft 151a is coupled with an end of the drum body 151b. Also, the photoconductive-drum rotation center shaft 151a is electrically connected to the drum body 151b.

The scorotron charger 152 is disposed upstream of a position at which the photoconductive drum 151 faces the development roller 144 (a position at which the photoconductive drum 151 is the closest to the development roller 144) in the rotational direction of the photoconductive drum 151 (the direction indicated by an arrow of FIG. 5). The scorotron charger 152 is located so as to face the peripheral surface of the photoconductive drum 151 with a predetermined spacing therebetween.

The scorotron charger 152 includes a discharge wire 152a and a grid 152b. The discharge wire 152a and the grid 152b are electrically connected to a high-voltage power supply for outputting a predetermined high voltage.

The drum cleaner 153 for cleaning the peripheral surface of the photoconductive drum 151 is disposed upstream of a position at which the photoconductive drum 151 faces the scorotron charger 152 (a position at which the photoconductive drum 151 is the closest to the scorotron charger 152) in the rotational direction of the photoconductive drum 151 (the direction indicated by the arrow of FIG. 5). The drum

cleaner **153** includes a brush formed from a conductive synthetic resin. By applying a predetermined cleaning bias voltage to the interface between the brush and the peripheral surface of the photoconductive drum **151**, the drum cleaner **153** can electrostatically attract dusts and toner particles remaining on the peripheral surface of the photoconductive drum **151**. The drum cleaner **153** is also connected to the high-voltage power supply for outputting a predetermined high voltage.

The photoconductive drum **151** is rotatably supported by the drum unit frame **154**. The drum unit frame **154** is formed from a synthetic resin. Additionally, the scorotron charger **152** and the drum cleaner **153** are supported by the drum unit frame **154** at predetermined positions.

Detailed External Structure of Image Forming Cartridge

FIG. **6** is a side cross-sectional view of the image forming cartridge **140** shown in FIG. **4**. That is, FIG. **6** is a side cross-sectional view of the image forming cartridge **140** when the drum unit **150** is removed from the view of FIG. **5**. FIG. **7** is a side elevational view illustrating the appearance of the image forming cartridge **140**. That is, FIG. **7** is a side elevational view corresponding to the center section of FIG. **6**. FIG. **8** is a plan view of the image forming cartridge **140**.

As shown in FIG. **7**, a leg **141a2** is formed so as to protrude from the bottom of the toner container case **141a** (on the right-hand side in FIG. **7**) of the cartridge case **141**. The leg **141a2** is designed so that, when the image forming cartridge **140** is placed on a workbench or a table, the leg **141a2** is in contact with the top surface of the workbench or the table.

As shown in FIGS. **7** and **8**, a gear train **146** is disposed on an end of the cartridge case **141** in the width direction of the cartridge case **141** (in a horizontal direction in FIG. **8**). The gear train **146** is configured to transfer a rotational driving force to components of a rotational driving system provided to the image forming cartridge **140** (i.e., the agitator **142**, the supply roller **143**, and the development roller **144** shown in FIG. **6**).

The structure of the gear train **146** is described in more detail next. A gear cover **146a** is provided so as to cover an end of the cartridge case **141** in the width direction. As shown in FIG. **7**, gears including a coupling gear **146b**, an agitator driving gear **146c**, a supply roller driving gear **146d**, and a development roller driving gear **146e** are disposed in the interior of the gear cover **146a**, that is, in the space between the side wall of the cartridge case **141** and the gear cover **146a**. Each of these gears is rotatably supported by the side wall of the cartridge case **141** and the gear cover **146a**.

As shown in FIG. **7**, a coupling recess **146b1** is formed on the coupling gear **146b**. The coupling recess **146b1** is exposed to outside the gear cover **146a** through an opening **146a1**, which is a through-hole formed in the gear cover **146a**. The coupling recess **146b1** has a shape so as to engage with a coupling input shaft (not shown) (a coupling input shaft **112d** shown in FIG. **9**) provided outside the image forming cartridge **140** (the body frame **112** shown in FIG. **1**). That is, since the coupling input shaft having a rotational driving force from the driving source provided outside (the body frame **112** shown in FIG. **11**) engages with the coupling recess **146b1**, the rotational driving force from the driving source can be transferred to the coupling gear **146b** via the coupling input shaft.

The agitator driving gear **146c** is mounted on an end of the agitator rotation center shaft **142a**. The agitator driving gear **146c** is engaged with the coupling gear **146b** via an intermediate gear (not shown).

The supply roller driving gear **146d** is coupled with an end of the supply-roller rotation center shaft **143a**. The supply roller driving gear **146d** is directly engaged with the coupling gear **146b**.

The development roller driving gear **146e** is coupled with an end of the development-roller rotation center shaft **144a**. The development roller driving gear **146e** is directly engaged with the coupling gear **146b**.

A collar member **147** is provided so as to cover an end of the development-roller rotation center shaft **144a**. The collar member **147** is formed from a conductive synthetic resin (e.g., a synthetic resin mixed with carbon black). The collar member **147** is in contact with the development-roller rotation center shaft **144a**, and therefore, the collar member **147** is electrically connected to the development-roller rotation center shaft **144a** (the development roller **144**). As shown in FIG. **8**, the collar member **147** is provided so as to correspond to either end of the development roller **144** (the development-roller rotation center shaft **144a** shown in FIGS. **6** and **7**).

Detailed Structure of Sliding Frame

FIG. **9** is a perspective view, viewed from above at an oblique angle (the same direction as that of FIG. **3**), of the color image forming unit **120** shown in FIGS. **1** to **3**. FIG. **10** is a side elevational view of the color image forming unit **120** shown in FIG. **9**. FIG. **11** is a perspective view, viewed from above at an oblique angle, of the slide frame **130** shown in FIG. **9** when all the image forming cartridges **140** are removed.

As shown in FIG. **9**, the front beam **131**, the supporting plate **132**, the supporting plates **132** and **133**, and the rear beam **134** of the slide frame **130** form a space. In this space, the image forming cartridges **140** are aligned along the sliding direction (the direction indicated by arrow **S** of FIG. **9**). The slide frame **130** is configured so that the image forming cartridge **140** can be removed in a predetermined direction of insertion of the cartridge that crosses the sliding direction. That is, the image forming cartridge **140** is inserted into the slide frame **130** along the direction of insertion of the cartridge (the direction indicated by arrow **A** of FIG. **9**: the second direction in the present invention) so as to be mounted on the slide frame **130** via the side plates **135** and **136**.

As noted above, a plurality of the side plates **135** and **136** are aligned along the sliding direction (the direction indicated by arrow **S** of FIG. **9**). These side plates **135** and **136** are arranged in parallel to the sliding direction and the direction of insertion of the cartridge (the direction indicated by arrow **A** of FIG. **9**). These side plates **135** and **136** are configured so as to guide the image forming cartridges **140** along the direction of insertion of the cartridge when the image forming cartridges **140** are mounted in or dismounted from the slide frame **130**.

The structure of each component of the slide frame **130** is described in detail below with reference to the accompanying drawings.

Structure of Supporting Plate on One Side

As shown in FIGS. **9** and **10**, the supporting plate **132** is attached to the side plates **135** by means of screws in order to support the side plates **135**. The supporting plate **132** is disposed in parallel to the side plates **135**.

A plurality of coupling through-holes **132b** is formed in the supporting plate **132**. The coupling gear **146b** is exposed through a corresponding one of the coupling through-holes **132b** so as to be engaged with the coupling input shaft **112d**. The coupling through-holes **132b** are aligned along the

sliding direction (the direction indicated by arrow S of FIG. 9) so as to correspond to the arrangement of the image forming cartridges 140.

A conductive-drum shaft supporting hole 132c is formed diagonally below each of the coupling through-holes 132b. The photoconductive-drum rotation center shaft 151a is inserted into the conductive-drum shaft supporting hole 132c.

#### Structure of Side Plate

As shown in FIGS. 9 and 11, a guide groove 135a is formed in each of the side plates 135 and a guide groove 136a is formed on each of the side plates 136 so as to guide the image forming cartridge 140 in the direction of insertion of the cartridge (the direction indicated by arrow A of FIGS. 9 and 11).

As shown in FIG. 11, the drum unit 150 (see FIG. 5) is supported between the side plates 135 and 136. FIG. 12 is a perspective view of a pair of the side plates 135 and 136 and the drum unit 150 removed from the structure shown in FIG. 11. FIG. 13 is a perspective view of the pair of the side plates 135 and 136 and the drum unit 150 when the pair of the side plates 135 and 136 and the drum unit 150 shown in FIG. 12 are disassembled.

As shown in FIG. 11, a coupling exposure section 135b corresponding to the coupling through-hole 132b of the supporting plate 132 is formed on the side plate 135. As shown in FIGS. 12 and 13, the coupling exposure section 135b is a short tube that extends outwardly from the side wall of the side plate 135. As shown in FIG. 11, the coupling exposure section 135b is inserted into the corresponding coupling through-hole 132b of the supporting plate 132.

As shown in FIGS. 12 and 13, a drum center shaft insertion hole 135c is formed in the lower section of the side plate 135. As shown in FIG. 12, the photoconductive-drum rotation center shaft 151a is disposed in the drum center shaft insertion hole 135c.

The guide groove 136a formed on the side plate 136 includes a lead-in portion 136a1, a guide portion 136a2, and a supporting portion 136a3. It is noted that the guide groove 135a of the side plate 135 has a similar structure.

The lead-in portion 136a1 is formed so as to be open in, substantially, a “V-shape” in side view. The lead-in portion 136a1 facilitates the easy insertion of the collar member 147 into the guide groove 136a when the image forming cartridge 140 is mounted in the slide frame 130, as shown in FIG. 9.

Referring back to FIGS. 12 and 13, the guide portion 136a2 extends obliquely downward from the lower end of the lead-in portion 136a1. The guide portion 136a2 is formed so as to be parallel to the direction of insertion of the cartridge (the direction indicated by arrow A of FIGS. 12 and 13). The supporting portion 136a3 extends obliquely downward and backward (in a direction indicated by arrow A' of FIG. 13) from the lower end of the guide portion 136a2. As shown in FIG. 9, the supporting portion 136a3 is formed so as to support the collar member 147 when the image forming cartridge 140 is mounted in the slide frame 130. The supporting portion 136a3 is a relatively short groove having a length slightly larger than the outer diameter of the collar member 147.

That is, as shown in FIGS. 9 and 13, the side plate 136 can guide the collar member 147 (see FIG. 9) using the guide portion 136a2 in the direction indicated by arrow A. Subsequently, the side plate 136 can guide the collar member 147 using the supporting portion 136a3 in the direction indicated by arrow A'.

#### Detailed Configuration of Electric Connecting Part Between Image Forming Cartridge and Slide Frame

FIGS. 14A and 14B are perspective views of the side plate 136 shown in FIG. 13. FIG. 14A is a perspective view of the side plate 136 when viewed from inside (the side of the drum unit 150 shown in FIG. 13 or inside of the slide frame 130 shown in FIG. 11). FIG. 14B is a perspective view of the side plate 136 when viewed from outside (outside the slide frame 130 shown in FIG. 11).

As shown in FIG. 14A, an electrode exposure opening 136a4 is formed in the bottom of the supporting portion 136a3 that faces the lower end of the guide portion 136a2. The electrode exposure opening 136a4 serves as a through-hole for communicating with outside the side plate 136 (the side shown in FIG. 14B). As shown in FIG. 14B, an electrode member 121 is mounted outside the outer surface of the side plate 136 at a position near the supporting portion 136a3. The electrode exposure opening 136a4 allows part of the electrode member to protrude into the interior of the supporting portion 136a3.

Positioning end surfaces 136a5 and 136a6 are formed on the supporting portion 136a3. The positioning end surface 136a5 includes a wall surface of the supporting portion 136a3 that faces the electrode exposure opening 136a4. The positioning end surface 136a6 includes a wall surface of the end of the guide groove 136a. When the peripheral surface of the collar member 147 (see FIG. 9) is in contact with the positioning end surfaces 136a5 and 136a6, the position of the image forming cartridge 140 (see FIG. 9) with respect to the slide frame 130 (see FIG. 9) can be determined.

#### Detailed Structure of Electrode Member

FIG. 15 is an enlarged perspective view of the electrode member 121 shown in FIG. 14B. The electrode member 121 electrically connects the image forming cartridge 140 shown in FIG. 1 to the body frame 112. The electrode member 121 is mounted on the slide frame 130.

As shown in FIGS. 14B and 15, the electrode member 121 is formed as a torsion coil spring. The electrode member 121 is formed from a steel wire into one component. The electrode member 121 includes a base end portion 121a, a body-side contact portion 121b, a connection coil spring portion 121c, and a cartridge-side contact portion 121d.

The base end portion 121a and the body-side contact portion 121b function as one arm portion of the torsion coil spring. This arm portion extends outwardly from the connection coil spring portion 121c. The body-side contact portion 121b is provided between the base end portion 121a and the connection coil spring portion 121c. The body-side contact portion 121b has substantially a “U-shape”. The body-side contact portion 121b extends perpendicularly from a plane that is parallel to the base end portion 121a and the connection coil spring portion 121c.

The cartridge-side contact portion 121d functions as the other arm portion of the torsion coil spring. This arm portion extends outwardly from the connection coil spring portion 121c.

The connection coil spring portion 121c connects the body-side contact portion 121b to the cartridge-side contact portion 121d. When the cartridge-side contact portion 121d is pressed in a direction indicated by arrow r of FIG. 15 and rotates to a position indicated by a chain double-dashed line, the connection coil spring portion 121c can press against the cartridge-side contact portion 121d in a direction indicated by arrow r' of FIG. 15.

#### Supporting Structure of Electrode Member

As shown in FIG. 14B, a body-side contact supporting portion 136b, a coil supporting portion 136c, a leg guide



portion **136d**, and a base-end supporting portion **136e** are formed on the outer surface of the side plate **136**.

The body-side contact supporting portion **136b** can support the body-side contact portion **121b** while allowing a substantially middle portion of the body-side contact portion **121b** (a portion parallel to the base end portion **121a** and the connection coil spring portion **121c**) to protrude outwardly. The coil supporting portion **136c** allows the connection coil spring portion **121c** to pass therethrough so as to support the connection coil spring portion **121c**. The leg guide portion **136d** is formed from a plate extending outwardly. The leg guide portion **136d** can guide the swing movement of an arm end **121d1**, which is an end of the cartridge-side contact portion **121d**, about a center axis of the connection coil spring portion **121c**. The base-end supporting portion **136e** locks the base end portion **121a** so as to support the base end portion **121a**.

Detailed Configuration of Electrical Connection of Electrode Member

FIG. **16** is a partial exploded perspective view of the color image forming unit **120** shown in FIG. **9**. FIG. **17** is a perspective view of a main portion of the outer surface of the side plate **136** shown in FIG. **16**.

As shown in FIG. **16**, when the image forming cartridge **140** is mounted on the slide frame **130**, the cartridge-side contact portion **121d** of the electrode member **121** presses against the collar member **147** of the image forming cartridge **140** at a predetermined pressure. Additionally, when the cartridge-side contact portion **121d** is in contact with the collar member **147**, electrical connection between the cartridge-side contact portion **121d** of the electrode member **121** and the development-roller rotation center shaft **144a** is achieved.

More specifically, as shown in FIG. **16**, the cartridge-side contact portion **121d** is disposed so as to protrude towards the image forming cartridge **140**. As shown in FIG. **17**, the electrode member **121** is configured so that the cartridge-side contact portion **121d** presses against the collar member **147** in a direction indicated by arrow **F** of FIG. **17**. The direction indicated by arrow **F** crosses the direction of insertion of the cartridge (the direction indicated by arrow **A** of FIG. **17**). In addition, the direction indicated by arrow **F** is substantially perpendicular to the swing direction of the collar member **147** (a swing direction of the cartridge indicated by arrow **A'** of FIG. **17**). This swing direction of the cartridge is the same as the direction indicated by arrow **A'** shown in FIGS. **13** and **14**.

Referring back to FIG. **16**, a plurality of the electrode members **121** corresponding to a plurality of the image forming cartridges **140** are aligned along the sliding direction (a direction indicated by arrow **S**), which is a direction in which the image forming cartridges **140** are aligned.

FIG. **18** is a perspective view of the color image forming unit **120** and the image forming cartridge **140** shown in FIG. **9** when the image forming cartridge **140** is mounted on or dismantled from the color image forming unit **120**. That is, FIG. **16** is a view obtained when the supporting plate **133** is removed from the view shown in FIG. **18**.

As shown in FIG. **18**, electrode through-holes **133b** are formed in the supporting plate **133**. Each of the electrode through-holes **133b** allows the body-side contact portion **121b** and the body-side contact supporting portion **136b** to protrude towards a body frame contact **112e** provided on the body frame **112** (see FIG. **1**).

The body frame contact **112e** is disposed so as to protrude towards the slide frame **130** (the color image forming unit **120**). When the body frame contact **112e** presses against the

body-side contact portion **121b** in a direction indicated by arrow **C** of FIG. **18**, the body frame contact **112e** is in contact with the body-side contact portion **121b**, and therefore, the body frame contact **112e** is electrically connected to the body-side contact portion **121b**. The direction indicated by arrow **C** in which the body frame contact **112e** presses against the body-side contact portion **121b** is perpendicular to the sliding direction (a direction indicated by arrow **S**) and the direction of insertion of the cartridge (a direction indicated by arrow **A**). That is, the direction indicated by arrow **C** is the above-described width direction. As shown in FIGS. **17** and **18**, the direction indicated by arrow **C** of FIG. **18** is perpendicular to the direction indicated by arrow **F** of FIG. **17**.

#### Operation of Structure According to Present Embodiment

The operation of the structure according to the present embodiment is described below with reference to the accompanying drawings.

##### Image Forming Operation

First, the image forming operation performed by the color laser printer **100** according to this embodiment is described with reference to FIG. **4**.

##### Paper Feed Operation

When the feed roller **183** is rotatably driven in a direction indicated by an arrow of FIG. **4**, the paper sheet **P** placed in the feeder case **181** is fed to the separation roller **184**. Thereafter, the leading edge of the paper sheet **P** reaches the nip formed by the separation roller **184** and the separation pad **185**. By rotating the separation roller **184** in a direction indicated by an arrow of FIG. **4**, only the top paper sheet **P** is delivered to the paper-dust removal roller **187**. After the paper-dust removal roller **187** removes paper dusts on the paper sheet **P**, the paper sheet **P** passes through the sheet transport roller **191** and the sheet guide **192** and reaches the transfer unit **170**.

##### Development Operation

When the agitator **142** is rotatably driven, toner particles in the cartridge case **141** are agitated and are delivered to the supply roller **143**. The toner particles delivered to the supply roller **143** are further delivered to the development roller **144** by the supply roller **143** rotating in a direction indicated by an arrow. Subsequently, the toner particles are tribocharged at a position where the supply roller **143** is in contact with the development roller **144**. Thus, the toner particles adhere to the peripheral surface of the development roller **144**. The density and the charge amount of the toner particles on the peripheral surface of the development roller **144** are adjusted to predetermined values by the blade **145**. Thereafter, since the development roller **144** rotates in a direction indicated by an arrow of FIG. **4**, the toner particles are delivered to a position at which the development roller **144** faces the photoconductive drum **151**.

After uniformly charged by the scorotron charger **152**, the peripheral surface of the photoconductive drum **151** is irradiated with a laser beam in accordance with image information. Thus, an electrostatic latent image is formed on the peripheral surface of the photoconductive drum **151** in accordance with the image information. When the peripheral surface of the photoconductive drum **151** having the electrostatic latent image formed thereon faces the peripheral surface of the development roller **144** having the toner particles with a predetermined density and charge amount deposited thereon, the electrostatic latent image on the peripheral surface of the photoconductive drum **151** is

developed with the toner particles. Consequently, a toner image appears on the peripheral surface of the photoconductive drum 151.

#### Transfer Operation

The paper sheet P delivered to the transfer unit 170 is held on the transport belt 173. Thus, the paper sheet P is transported from the front side to the back side (from right to left in FIG. 4). When the paper sheet P is delivered to the nip formed by the photoconductive drum 151 and the transfer roller 174, the toner particles on the peripheral surface of the photoconductive drum 151 are transferred to the paper sheet P by means of a transfer bias voltage between the photoconductive drum 151 and the transfer roller 174.

#### Fixing and Paper Ejection Operations

After the toner particles are deposited on the surface of the paper sheet P in the transfer unit 170, the paper sheet P is delivered to the fixing unit 193. Thereafter, the paper sheet P is pinched by the heat roller 193a and the pressure roller 193b and is heated. Thus, the toner particles deposited on the paper sheet P are fused onto the surface of the paper sheet P. Subsequently, the paper sheet P is ejected to the catch tray 111b outside the body section 110 by the paper ejection roller 197.

#### Mount/Dismount Operation of Unit

The mount and dismount operations of the color image forming unit 120 in the color laser printer 100 are described next.

As shown in FIG. 1, when the front cover 111e is open toward the front side (the proximal side), the color image forming unit 120 is exposed to outside through the front opening 111d. Subsequently, when the front-side grip 131a of the slide frame 130 is pulled out towards the proximal side along the sliding direction (the direction indicated by arrow S of FIG. 1), the color image forming unit 120 is pulled out to the proximal side, as shown in FIG. 2. Thus, the image forming cartridge 140 exposed to outside can be removed.

When the color image forming unit 120 is further pulled out towards the proximal side, the color image forming unit 120 can be completely removed to outside the body section 110, as shown in FIG. 3. Thus, the color image forming unit 120 is interchangeable.

#### Mount/Dismount Operation of Cartridge

The mount and dismount operations of the image forming cartridge 140 to and from the color image forming unit 120 in the color laser printer 100 are described next.

FIG. 19 is a side elevational view of the color image forming unit 120 shown in FIG. 10 when the color image forming unit 120 is partially disassembled and the image forming cartridge 140 is mounted in or dismounted from the slide frame 130. First, the mount operation of the image forming cartridge 140 in the slide frame 130 is described with reference to FIGS. 17 to 19.

As shown in FIGS. 18 and 19, the collar member 147 extending outwardly from either side of the image forming cartridge 140 is inserted into the upper end of the guide grooves 135a and 136a (i.e., the lead-in portion 136a1). Subsequently, when the image forming cartridge 140 is moved downward, the collar member 147 is guided obliquely downward along the direction of insertion of the cartridge indicated by arrow A of FIGS. 18 and 19 by the guide portion 136a2. Thus, the image forming cartridge 140 is inserted into a space between the side plates 135 and 136 along the direction of insertion of the cartridge indicated by arrow A of FIGS. 18 and 19.

When the collar member 147 passes through the lower end of the guide portion 136a2 and reaches the supporting portion 136a3, the collar member 147 is guided obliquely downward along the swing direction of the cartridge indicated by arrow A' of FIG. 19 by the supporting portion 136a3. Thus, the image forming cartridge 140 is mounted on the slide frame 130.

As shown in FIG. 17, when the image forming cartridge 140 is mounted on the slide frame 130, the cartridge-side contact portion 121d is in contact with the collar member 147. Thus, the electrode member 121 is electrically connected to the collar member 147 (the image forming cartridge 140 shown in FIGS. 18 and 19). Additionally, as shown in FIGS. 17 and 18, the body-side contact portion 121b of the electrode member 121 is in contact with the body frame contact 112e. Thus, the electrode member 121 is electrically connected to the body frame contact 112e (the body section 110 shown in FIG. 1). In this way, electrical connection between the body frame contact 112e (the body section 110 shown in FIG. 1) and the collar member 147 (the image forming cartridge 140 shown in FIGS. 1, 18, and 19) is achieved via the electrode member 121 attached on the slide frame 130.

#### Positioning of Image Forming Cartridge

As shown in FIG. 17, in the supporting portion 136a3, the collar member 147 is pressed by the cartridge-side contact portion 121d of the electrode member 121 in the direction indicated by arrow F of FIG. 17. The pressing force and the weight of the image forming cartridge 140 cause the outer periphery of the collar member 147 to be brought into contact with the positioning end surfaces 136a5 and 136a6 at a predetermined pressure. Thus, the position of the image forming cartridge 140 relative to the slide frame 130 is determined. That is, a positional relationship between the photoconductive drum 151 and the development roller 144 is set to predetermined conditions.

As shown in FIG. 19, when a rotational driving force is provided to the coupling gear 146b in a direction indicated by arrow D of FIG. 19, a couple of forces act on the image forming cartridge 140 in the direction indicated by arrow D. Accordingly, the collar member 147 is urged in a direction indicated by arrow R of FIG. 19 (the seventh direction in the present invention). Thus, the collar member 147 is urged against the positioning end surface 136a6. The direction indicated by arrow R is substantially the same as the direction indicated by arrow F of FIG. 17.

That is, when the rotational driving force is provided to the coupling gear 146b in the direction indicated by arrow D of FIG. 19, a force acts on the image forming cartridge 140 in a direction so that the positioning of the image forming cartridge 140 with respect to the slide frame 130 (i.e., the positioning between the photoconductive drum 151 and the development roller 144) is ensured.

#### Advantages of Structure According to Present Embodiment

The advantages of the structure according to the present embodiment are described next.

As shown in FIG. 18, according to the structure of the present embodiment, the body-side contact portion 121b of the electrode member 121 is disposed so as to protrude towards the body frame 112. Additionally, the electrode member 121 is attached to the side plate 136 (the slide frame 130). A plurality of the electrode members 121, each cor-

responding to one of the image forming cartridges 140, are aligned along the sliding direction (the direction indicated by arrow S).

In such a structure, by simply mounting the slide frame 130 on the body frame 112, electrical connection between the body section 110 and the image forming cartridge 140 mounted on the slide frame 130 is achieved. In addition, according to this structure, by simply pulling out the slide frame 130 from the body frame 112 in the sliding direction (the direction indicated by arrow S), the body section 110 is electrically disconnected from the image forming cartridge 140. As noted above, according to this structure, the electrical connection and disconnection between the body section 110 and the image forming cartridge 140 are provided in conjunction with the relative movement between the body section 110 and the slide frame 130 (the color image forming unit 120). Accordingly, the electrical connection between the body section 110 and the image forming cartridge 140 can be easily achieved using a simple structure. Consequently, this structure can facilitate the maintenance of the color laser printer 100.

As shown in FIG. 19, according to the structure of the present embodiment, when the slide frame 130 is mounted on or dismounted from the body frame 112, the sliding direction (the direction indicated by arrow S) is substantially perpendicular to the directions in which the image forming cartridge 140 is mounted on and dismounted from the slide frame 130 (i.e., the directions indicated by arrows A and A').

In such a structure, when the slide frame 130 slides in the sliding direction (the direction indicated by arrow S), the mounting state of the image forming cartridge 140 on the slide frame 130 tends to remain unchanged. Thus, when the slide frame 130 is inserted into the body frame 112 along the sliding direction (the direction indicated by arrow S), a loose electrical connection between the cartridge-side contact portion 121d and the collar member 147 caused by a positional shift of the slide frame 130 from the image forming cartridge 140 can be inhibited. Accordingly, reliable electrical contact between the body section 110 and the image forming cartridge 140 can be achieved.

As shown in FIGS. 16 and 18, according to the structure of the present embodiment, the cartridge-side contact portion 121d is disposed on the inner surface of the slide frame 130. Additionally, the cartridge-side contact portion 121d protrudes from the inner surface of the slide frame 130 towards the image forming cartridge 140. In contrast, the body-side contact portion 121b is disposed so as to protrude towards the body frame contact 112e outside the supporting plate 133 (the slide frame 130) through the electrode through-hole 133b.

In such a structure, part of the electrode member 121 that extends to outside the slide frame 130 is limited to the body-side contact portion 121b. Accordingly, mechanical interference between the body frame contact 112e provided on the body frame 112 and the cartridge-side contact portion 121d is inhibited. Thus, in this structure, reliable electrical connection between the body section 110 and the slide frame 130 and reliable electrical connection between the slide frame 130 and the image forming cartridge 140 can be achieved.

As shown in FIG. 3, according to the structure of the present embodiment, the slide frame 130 is removably mounted on the body frame 112. That is, the color image forming unit 120 is completely detached from the body section 110. Thus, the color image forming unit 120 is interchangeable.

Consequently, this structure can facilitate the maintenance of the color laser printer 100.

As shown in FIG. 18, according to the structure of the present embodiment, since the body-side contact portion 121b is urged in a direction indicated by arrow C that is substantially perpendicular to the sliding direction (the direction indicated by arrow S), the body-side contact portion 121b is in contact with the body frame contact 112e.

According to such a structure, reliable electrical connection between the body frame contact 112e and the body-side contact portion 121b can be achieved using the simple structure.

As shown in FIGS. 16 and 17, according to the structure of the present embodiment, when the image forming cartridge 140 is mounted and dismounted, the direction in which the cartridge swings (the direction indicated by arrow A' of FIG. 17) is substantially perpendicular to the direction in which the collar member 147 is urged by the cartridge-side contact portion 121d (the direction indicated by arrow F of FIG. 17).

According to such a structure, the mount and dismount operation of the image forming cartridge 140 and positioning of the image forming cartridge 140 relative to the slide frame 130 are not affected by the pressure between the cartridge-side contact portion 121d and the collar member 147. Accordingly, the mount and dismount operation of the image forming cartridge 140 can be smoothly carried out. In addition, reliable electrical connection between the cartridge-side contact portion 121d and the collar member 147 can be achieved using the simple structure.

As shown in FIGS. 17 and 18, according to the structure of the present embodiment, the electrode member 121 is configured so that the direction in which the cartridge-side contact portion 121d and the collar member 147 press each other is substantially perpendicular to the direction in which the body-side contact portion 121b and the body frame contact 112e press each other.

According to such a structure, compared with the case where the direction in which the cartridge-side contact portion 121d and the collar member 147 press each other is parallel to the direction in which the body-side contact portion 121b and the body frame contact 112e press each other, the size of the slide frame 130 (the color image forming unit 120) in the width direction can be further reduced.

Additionally, since the direction of an urging force acting on the body-side contact portion 121b is substantially perpendicular to the direction of an urging force acting on the cartridge-side contact portion 121d, the interference between the urging force acting on the body-side contact portion 121b and the urging force acting on the cartridge-side contact portion 121d is inhibited. Accordingly, unreliable electrical connections at the body-side contact portion 121b and the cartridge-side contact portion 121d can be inhibited. Accordingly, reliable electrical connection caused by the physical contact between the cartridge-side contact portion 121d and the collar member 147 can be achieved using the simple structure.

As shown in FIGS. 17 and 19, according to the structure of the present embodiment, the collar member 147 is urged towards the positioning end surfaces 136a5 and 136a6 in the directions (the directions indicated by arrows A' and R (hereinafter referred to as "predetermined positioning directions": these directions correspond to a sixth direction in the present invention)) so that the position of the image forming cartridge 140 is determined. Such predetermined positioning directions are substantially the same as directions in which

the image forming cartridge **140** (the collar member **147**) receive a force when the rotational driving force is input to the coupling gear **146b**. In addition, in FIG. **17**, the direction **F** in which the collar member **147** is urged by the cartridge-side contact portion **121d** is substantially the same as the direction **R** in which the collar member **147** receives the force when the rotational driving force is input to the coupling gear **146b**.

According to such a structure, the positioning between the image forming cartridge **140** and the slide frame **130** can be reliably carried out.

As shown in FIG. **14**, according to the structure of the present embodiment, the cartridge-side contact portion **121d** is disposed so as to face the guide groove **136a**.

According to such a structure, the collar member **147** of the image forming cartridge **140** is guided by the guide groove **136a** and, subsequently, the cartridge-side contact portion **121d** that is disposed so as to face the guide groove **136a** is electrically connected to the collar member **147**. Accordingly, the reliability of the electrical connection can be improved using the simple structure.

As shown in FIGS. **14** and **15**, according to the structure of the present embodiment, the electrode member **121** includes the wire-shaped connection coil spring portion **121c** that connects the body-side contact portion **121b** to the cartridge-side contact portion **121d**. The electrode member **121** is disposed in the vicinity of the guide groove **136a** of the side plate **136**.

This structure provides the following advantage. According to such a structure, the electrode member **121** can have a significantly simple structure. Additionally, since the electrode member **121** is disposed in the vicinity of the guide groove **136a** of the side plate **136**, reliable electrical connection between the cartridge-side contact portion **121d** that faces the guide groove **136a** and the collar member **147** can be achieved.

As shown in FIGS. **14** and **15**, according to the structure of the present embodiment, the connection coil spring portion **121c** and the cartridge-side contact portion **121d** are integrated into the wire member having a torsion coil spring structure. The cartridge-side contact portion **121d** functions as the arm portion extending outwardly from the coil portion of the torsion coil spring.

According to such a structure, when the collar member **147** presses against the cartridge-side contact portion **121d** while resisting the elastic force of the torsion coil spring, the cartridge-side contact portion **121d** is in contact with the collar member **147** and is electrically connected to the collar member **147**. Thus, reliable contact and reliable electrical connection between the cartridge-side contact portion **121d** and the collar member **147** are achieved.

As shown in FIGS. **16** and **17**, according to the structure of the present embodiment, since the collar member **147** which is a conductive protrusion that can be accommodated in the guide groove **136a** is in contact with the cartridge-side contact portion **121d**, electrical connection between the collar member **147** and the cartridge-side contact portion **121d** is achieved.

According to such a structure, the image forming cartridge **140** can be smoothly mounted on the slide frame **130** using the significantly simple structure. In addition, this significantly simple structure can provide reliable electrical connection between the development roller **144** and the cartridge-side contact portion **121d**.

As shown in FIG. **9**, according to the structure of the present embodiment, a plurality of the separate side plates **136** are provided so as to correspond to a plurality of the

image forming cartridges **140**. The separate side plates **136** are aligned along the sliding direction (the direction indicated by arrow **S**). Additionally, in the slide frame **130**, outside the side plates **136**, the supporting plate **133** is disposed so as to support the side plates **136**. The body-side contact portion **121b** is disposed so as to pass through the electrode through-hole **133b** formed in the supporting plate **133** and be exposed outside the supporting plate **133**.

According to such a structure, the side plate **136** and the guide groove **136a** can be produced through significantly simple manufacturing steps at low cost.

As shown in FIGS. **9** and **18**, according to the structure of the present embodiment, the image forming cartridge **140** is configured so that a driving force is transferred from the side of the body frame **112** via the coupling gear **146b** disposed at one end in the width direction that is perpendicular to the sliding direction (the direction indicated by arrow **S**) and the directions in which the image forming cartridge **140** is mounted and dismounted (the directions indicated by arrow **A** and **A'**). In addition, the electrode member **121** is disposed so as to face the other end of the image forming cartridge **140**.

According to such a structure, even when foreign materials, such as dust and grease, are generated on a portion to which the driving force is transferred in the vicinity of the coupling gear **146b**, deposition of the foreign materials to electrical contact points between the electrode member **121** and the collar member **147** and between the electrode member **121** and the body frame contact **112e** can be reliably inhibited. Accordingly, reliable electrical connection at the electrical contact points can be achieved.

As shown in FIG. **16**, according to the structure of the present embodiment, the number of the separate electrode members **121** is equal to the number of the image forming cartridges **140**.

According to such a structure, the electrode member **121** can be formed using a significantly simple structure.

#### Modifications

As noted above, the embodiments above provide illustrations of some of the preferred embodiments that the inventor believes to be the best mode for practicing the present invention at the time this application was filed. Therefore, these should not be construed as limiting the scope of the invention. It should be understood that many modifications are possible which remain within the concept, scope, and spirit of the invention.

Several modifications are described herewith. However, it should be understood that the modifications are not limited thereto. The above-described embodiments and the following modification should not be construed as limiting the scope of the invention because this would unfairly disadvantage the present inventor who filed the application and this would unfairly benefit an imitator of the invention.

(1) According to the present invention, an image forming apparatus is not limited to a color laser printer. For example, the present invention is applicable to a color copier.

(2) In FIGS. **17** and **19**, the direction in which the collar member **147** is urged by the cartridge-side contact portion **121d** (the direction indicated by arrow **F** of FIG. **17**) may be a direction opposite to the positioning direction (the direction indicated by arrow **R** of FIG. **19**). In this case, a force received by the image forming cartridge **140** (the collar member **147**) for positioning urges the collar member **147** against the cartridge-side contact portion **121d**. Thus, electrical connection between the collar member **147** and the cartridge-side contact portion **121d** can be reliably achieved.

29

(3) FIG. 20 is a side cross-sectional view of the structure of a modification of the image forming cartridge shown in FIG. 6. As shown in FIG. 20, in place of the leg 141a2 shown in FIG. 6, a roller 141a3 may be used.

(4) According to the present invention, operational and functional elements included in means for solving the problems include any structures that can realize the above-described embodiments and modifications as well as the specific structures described in the foregoing embodiments and modifications.

The invention claimed is:

1. An image forming apparatus comprising:  
a main body including a first electrode;  
a frame being mountable to and dismountable from the main body, the frame including a photoconductive drum and a second electrode contacting the first electrode in a state where the frame is mounted to the main body; and  
a cartridge being mountable to and dismountable from the frame, the cartridge includes a cartridge case configured to contain a toner and a third electrode contacting the second electrode in a state where the cartridge is mounted to the frame,  
wherein the frame includes a guide groove configured to guide a portion of the cartridge, and  
wherein a portion of the second electrode is in the guide groove.
2. The image forming apparatus according to claim 1, wherein the second electrode includes a cartridge-side contact portion contacting the third electrode in a state where the cartridge is mounted to the frame, and wherein the cartridge-side contact portion is in the guide groove.
3. The image forming apparatus according to claim 1, wherein the second electrode includes a wire.

30

4. The image forming apparatus according to claim 1, wherein the second electrode is formed from steel.

5. The image forming apparatus according to claim 1, wherein the second electrode has a U shape.

6. The image forming apparatus according to claim 1, wherein the second electrode includes a spring.

7. The image forming apparatus according to claim 6, wherein the spring is a coil spring.

8. The image forming apparatus according to claim 1, wherein the cartridge includes a development roller.

9. The image forming apparatus according to claim 1, wherein the photoconductive drum is rotatable about an axis extending in a first direction, and wherein the frame is mountable to and dismountable from the main body in a second direction crossing the first direction, and

wherein the cartridge is mountable to and dismountable from the frame in a third direction crossing the first direction and the second direction.

10. The image forming apparatus according to claim 1, wherein the frame is mounted to the main body in a state where the cartridge is mounted to the frame.

11. The image forming apparatus according to claim 1, wherein the frame includes a charger configured to contact a peripheral surface of the photoconductive drum.

12. The image forming apparatus according to claim 11, wherein the charger is a scorotron charger.

13. The image forming apparatus according to claim 1, wherein the frame includes a drum cleaner that contacts a peripheral surface of the photoconductive drum.

14. The image forming apparatus according to claim 13, wherein the drum cleaner includes a brush.

\* \* \* \* \*