



US010844762B2

(12) **United States Patent**
Dadam et al.

(10) **Patent No.:** **US 10,844,762 B2**
(45) **Date of Patent:** **Nov. 24, 2020**

(54) **METHOD FOR VARIABLE POSITION EXHAUST TUNING VALVE DIAGNOSTICS**

(71) Applicant: **Ford Global Technologies, LLC**,
Dearborn, MI (US)

(72) Inventors: **Sumanth Dadam**, Novi, MI (US);
Sanyam Sharma, Dearborn, MI (US);
Robert Roy Jentz, Westland, MI (US)

(73) Assignee: **Ford Global Technologies, LLC**,
Dearborn, MI (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 525 days.

(21) Appl. No.: **15/792,666**

(22) Filed: **Oct. 24, 2017**

(65) **Prior Publication Data**

US 2019/0120101 A1 Apr. 25, 2019

(51) **Int. Cl.**

F01N 1/16 (2006.01)
F01N 9/00 (2006.01)
F01N 13/04 (2010.01)
F01N 11/00 (2006.01)

(52) **U.S. Cl.**

CPC **F01N 1/163** (2013.01); **F01N 1/166** (2013.01); **F01N 1/168** (2013.01); **F01N 9/00** (2013.01); **F01N 11/00** (2013.01); **F01N 13/04** (2013.01); **F01N 2240/36** (2013.01); **F01N 2550/00** (2013.01); **F01N 2900/06** (2013.01)

(58) **Field of Classification Search**

CPC F01N 1/163; F01N 1/166; F01N 1/168; F01N 13/04; F01N 9/00; F01N 2550/00; F01N 2240/36; F01N 2900/06; F02D 41/042; F02D 41/221; Y02T 10/47
USPC 60/277
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,662,554 B2 12/2003 Sheidler et al.
7,983,834 B2* 7/2011 Blumendeller F02D 41/0055 701/114
9,441,568 B2 9/2016 Ossareh et al.
9,835,094 B2* 12/2017 Lahti F02D 41/0002
2017/0051684 A1* 2/2017 Lahti F02D 41/0007

* cited by examiner

Primary Examiner — Thai Ba Trieu



Assistant Examiner — Dapinder Singh

(74) Attorney, Agent, or Firm — Geoffrey Brumbaugh; McCoy Russell LLP

(57) **ABSTRACT**

Methods and systems are provided for adjusting and troubleshooting an adjustable exhaust valve of a variable exhaust tuning system. In one example, a method may include comparing engine startup conditions to engine conditions of a last engine off event, adjusting a position of the adjustable exhaust valve, and providing a diagnostic summary to a vehicle operator based upon the results of the comparison and adjustment.

20 Claims, 6 Drawing Sheets






FIG. 2A




FIG. 2B

FIG. 3





FIG. 4







FIG. 6



1

METHOD FOR VARIABLE POSITION EXHAUST TUNING VALVE DIAGNOSTICS

FIELD

The present description relates generally to methods and systems for robust diagnostics of a variable exhaust tuning system configured to improve vehicle operator experience.

BACKGROUND/SUMMARY

In high-powered internal combustion engines, variable exhaust pipe tuning systems are desired to control the noise output levels of motor vehicles equipped. Additionally, a vehicle operator's ability to adjust the sound levels, or noise, vibration and harshness (NVH) from a control unit within the vehicle, may lead to an improved driving experience wherein the driver may select their preferred sound levels. As an example, a variable exhaust tuning system may comprise a resonator and one or more mufflers fluidically connected to the resonator. A muffler may include one or more adjustable exhaust valves and the angle of the valve may be adjusted automatically with a motor responsive to settings by the vehicle operator. In some examples, further opening the adjustable exhaust valve may decrease back pressure in the muffler and/or resonator and increase the noise level, while in other examples, further closing the valve may increase back pressure in the muffler and/or resonator and decrease the noise level.

An issue that may arise with the abovementioned variable exhaust tuning systems is that one or more adjustable exhaust valves may become stuck open or closed or in a fixed position, causing performance issues related to engine performance or NVH. If one or more adjustable exhaust valves becomes stuck, the quality of the driving experience may significantly decrease and the variable exhaust tuning system may incur degradation due to undesirable buildup of exhaust gases or backpressure. Thus, as recognized by the inventors herein, providing robust diagnostics for the variable exhaust tuning system may help the operator of the vehicle determine if the problem can be solved via the variable exhaust tuning system's self-healing and/or retry procedures or if the vehicle requires maintenance.

Other attempts to address issues related to variable exhaust tuning systems is shown by Sheidler et al. in U.S. Pat. No. 6,662,554 B2. Therein, the Sheidler et al. patent provides teachings related to a damper for an exhaust system providing volume attenuation. Sheidler et al. provides systems and methods to electronically or manually adjust the volume attenuation of exhaust gases from a combustion engine.

However, the inventors herein have also recognized potential issues with such systems. As one example, variable exhaust tuning systems may experience elevated temperatures during normal operation of a motor vehicle and the systems may heat up significantly. However, when the engine is turned off, and if temperatures are low enough, condensation and ice may form within the variable exhaust tuning system. In an example, condensation and ice may lead to adjustable exhaust valves becoming stuck when ambient air temperatures are below freezing.

In one example, the issues described above may be addressed by a method for an adjustable engine-exhaust valve, comprising: monitoring engine off time and checking for one or more entry conditions at engine startup, operating with the valve being stuck, and responsive to the valve being stuck: during selected engine start-up conditions and after

2

sufficient engine-off time, setting an error code associated with the one or more entry conditions upon an exhaust temperature reaching an exhaust temperature threshold, commanding the adjustable exhaust valve to a first commanded valve position, and based upon a current valve position of the adjustable exhaust valve being within a tolerance band of a first commanded valve position, clearing the error code.

In this way, improved diagnostic and troubleshooting methods for exhaust valves may provide improved valve self-healing, prevent false errors from being latched, eliminate unnecessary effort from vehicle owners of driving error-latched vehicle to a service station, and reduce unnecessary vehicle technicians' effort for resetting and clearing false latched, or permanent, errors which may not be reset or cleared without a manufacturer-approved technician.

It should be understood that the summary above is provided to introduce in simplified form a selection of concepts that are further described in the detailed description. It is not meant to identify key features of the claimed subject matter, the scope of which is defined uniquely by the claims that follow the detailed description. Furthermore, the claimed subject matter is not limited to implementations that solve any disadvantages noted above or in any part of this disclosure.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows an example internal combustion engine with variable exhaust tuning system.

FIG. 2A shows an alternative, enlarged view of an example variable exhaust tuning system.

FIG. 2B shows an upstream-looking point of view from the downstream end of either a first or second muffler inner exhaust port.

FIG. 3 shows a flow chart depicting a method of diagnosing a stuck valve.

FIG. 4 shows a flow chart depicting an alternative method of diagnosing a stuck valve.

FIG. 5 shows a graph representing sample conditions for a stuck valve diagnosis.

FIG. 6 shows a graph representing alternative sample conditions for a stuck valve diagnosis.

DETAILED DESCRIPTION

The following description relates to systems and methods for diagnosing a stuck adjustable exhaust valve and delaying and preventing setting an alarm based upon at least one of an ambient and exhaust temperature. Methods include launching self-healing routines, cycling adjustable exhaust valve positioning, and checking sensor and actuator feedback.

FIGS. 1, 2A, and 2B may be discussed collectively to provide a clear description. FIG. 1 depicts an example embodiment of a combustion chamber or cylinder of internal combustion engine 10. Engine 10 may receive control parameters from a control system including controller 12 and input from a vehicle operator 130 via an input device 132. In this example, input device 132 includes an accelerator pedal and a pedal position sensor 134 for generating a proportional pedal position signal PP. Cylinder (herein also "combustion chamber") 14 of engine 10 may include combustion chamber walls 136 with piston 138 positioned therein. Piston 138 may be coupled to crankshaft 140 so that reciprocating motion of the piston is translated into rotational motion of the crankshaft. Crankshaft 140 may be

coupled to at least one drive wheel of the passenger vehicle via a transmission system. Further, a starter motor may be coupled to crankshaft **140** via a flywheel to enable a starting operation of engine **10**. Cylinder **14** can receive intake air via a series of intake air passages **142**, **144**, and **146**. Intake air passage **146** may communicate with other cylinders of engine **10** in addition to cylinder **14**. In some embodiments, one or more of the intake passages may include a boosting device such as a turbocharger or a supercharger. For example, FIG. **1** shows engine **10** configured with a turbocharger including a compressor **174** arranged between intake passages **142** and **144**, and an exhaust turbine **176** arranged along exhaust passage **148**. Compressor **174** may be at least partially powered by exhaust turbine **176** via a shaft **180** where the boosting device is configured as a turbocharger. However, in other examples, such as where engine **10** is provided with a supercharger, exhaust turbine **176** may be optionally omitted, where compressor **174** may be powered by mechanical input from a motor or the engine. A throttle **162** including a throttle plate **164** may be provided along an intake passage of the engine for varying the flow rate and/or pressure of intake air provided to the engine cylinders. For example, throttle **162** may be disposed downstream of compressor **174** as shown in FIG. **1**, or alternatively may be provided upstream of compressor **174**.

Exhaust passage **148** may receive exhaust gases from other cylinders of engine **10** in addition to cylinder **14**. Exhaust gas sensor **128** is shown coupled to exhaust temperature sensor **129** and exhaust constituent sensor **127** off exhaust passage **148** upstream of emission control device **178**. In an alternate embodiment, these sensors may not be located adjacent to one another and may be dispersed through exhaust passage **148**. Exhaust gas sensor **128** may be selected from among various suitable sensors for providing an indication of exhaust gas air/fuel ratio such as a linear oxygen sensor or UEGO (universal or wide-range exhaust gas oxygen), a two-state oxygen sensor or EGO (as depicted), a HEGO (heated EGO), a NO_x, HC, or CO sensor, for example. Emission control device **178** may be a three way catalyst (TWC), NO_x trap, various other emission control devices, or combinations thereof. Exhaust gas sensor **128**, exhaust temperature sensor **129** and exhaust constituent sensor **127** provide input to controller **12** via input/output ports **108**.

Exhaust tuning resonator **191** may receive exhaust gases from emission control device **178** via post-treatment passage **193** having post-treatment walls **189**. Resonator **191** may be fluidically coupled to emission control device **178** via post-treatment passage **193**. In an example, resonator **191** may also be fluidically coupled via a first post-resonator passage **193a** to a first muffler **197a** and resonator **191** may also be fluidically coupled via second post-resonator passage **193b** to a second muffler **197b**. In an example, the first muffler **197a** may include a first temperature sensor and/or delta pressure sensor **194a** and the second muffler **197b** may include a second temperature sensor and/or delta pressure sensor **194b**. In an example the first and second temperature sensor and/or delta pressure sensors **194a**, **194b** may track receive temperature and pressure input of the exhaust gases of the variable exhaust tuning system which may change over time and as a position of one or more adjustable exhaust valves **196a**, **196b** changes. In another example, the first muffler **197a** may be fluidically connected to a first muffler inner exhaust port **198a** and a first muffler outer exhaust port **199a**. In another example, the second muffler **197b** may be fluidically connected to a second muffler inner exhaust port **198b** and a second muffler outer exhaust port **199b**. In an

example, a microphone **195** may be located between the first and second mufflers **197a**, **197b** and may be attached to first and second mufflers **197a** and **197b** via supports. In another example, the microphone may be attached to a bottom surface of the vehicle. In an example, the bottom surface of the vehicle may face the road on which the vehicle is travelling and the bottom surface of the vehicle may face away from the cabin of the vehicle.

In a further example, the first muffler inner exhaust port **198a** and the second muffler inner exhaust port **198b** may, respectively, include a first adjustable exhaust valve **196a** and a second adjustable exhaust valve **196b**. In an example, the first and second adjustable exhaust valves **196a**, **196b** may be communicatively coupled to the controller **12** via input/output ports **108**. In an example, the first and second adjustable exhaust valves **196a**, **196b** may be damper valves, butterfly valves, globe valves, ball valves, poppet valves, quarter turn valve, compression valve or other valve controlled by an actuator (the actuator to be discussed in more detail with respect to FIGS. **2A** and **2B**). In an example, the first temperature sensor and/or delta pressure sensor **194a** and the second temperature sensor and/or delta pressure sensor **194b** may each be communicatively coupled to controller **12** via input/output ports **108**. In an example, the first and second adjustable exhaust valves **196a** and **196b** may be controlled by an operator of the motor vehicle to adjust a sound experience of the vehicle. In an example, adjusting the first and second adjustable exhaust valves **196a** and **196b** may adjust the sound level and/or back pressure of the exhaust system of the vehicle.

In an example, the resonator **191**, post-resonator passages **193a** and **193b**, mufflers **197a** and **197b**, outer exhaust ports **199a** and **199b**, and inner exhaust ports **198a** and **198b** may be configured and/or shaped to provide adjustable exhaust tuning, or increased and decreased exhaust sound levels, via adjustment of adjustable exhaust valves **196a**, **196b**.

In an example, the first and second adjustable exhaust valves **196a** and **196b** may be adjustable by the vehicle operator **130** via exhaust control **109**. Exhaust control **109** may be controllable by the vehicle operator **130** to adjust an angular positioning of the first and second adjustable exhaust valves **196a** and **196b**. The exhaust control **109** may include one or more exhaust valve settings which may be selectable by the vehicle operator **130**. As an example, a vehicle operator **130** selection of an exhaust valve setting may command the first and second adjustable exhaust valves **196a** and **196b** to the angular positioning associated with the exhaust valve setting of the exhaust control **109**. As an example, exhaust control **109** may be communicatively coupled to the controller **12** via input/output ports **108**. As an example, exhaust control **109** may command, via vehicle operator **130** selection of the exhaust valve setting, the first and second adjustable exhaust valves **196a** and **196b** to between and including angular positioning wherein the first and second adjustable exhaust valves **196a** and **196b** may be either completely open or completely closed.

In another example, resonator **191** may be configured to receive exhaust gases directly from exhaust passage **148** downstream of exhaust turbine **176** and the first and second mufflers **197a**, **197b** may each include emission control device **178** within the first and second mufflers **197a**, **197b**. In such an example post-treatment passage **193** may fluidically couple exhaust turbine **176** to resonator **191**.

Exhaust temperature may be measured by one or more temperature sensors such as exhaust temperature sensor **129** located in exhaust passage **148** and temperature sensors contained within the variable exhaust tuning system com-

prising at least post-treatment passage **193**, resonator **191**, post-resonator passages **193a** and **193b**, mufflers **197a** and **197b**, outer exhaust ports **199a** and **199b**, and inner exhaust ports **198a** and **198b**. Alternatively, exhaust temperature may be inferred based on engine operating conditions such as speed, load, air-fuel ratio (AFR), spark retard, etc. Further, exhaust temperature may be computed by one or more exhaust gas sensors **128**. It may be appreciated that the exhaust gas temperature may alternatively be estimated by any combination of temperature estimation methods listed herein.

Each cylinder of engine **10** may include one or more intake valves and one or more exhaust valves. For example, cylinder **14** is shown including at least one intake poppet valve **150** and at least one exhaust poppet valve **156** located at an upper region of cylinder **14**. In some embodiments, each cylinder of engine **10**, including cylinder **14**, may include at least two intake poppet valves and at least two exhaust poppet valves located at an upper region of the cylinder.

Intake valve **150** may be controlled by controller **12** by cam actuation via cam actuation system **151**. Similarly, exhaust valve **156** may be controlled by controller **12** via cam actuation system **153**. Cam actuation systems **151** and **153** may each include one or more cams and may utilize some form of variable valve timing (VVT) such as one or more of cam profile switching (CPS), variable cam timing (VCT), such as twin independent variable cam timing (tiVCT), and/or variable valve lift (VVL) systems that may be operated by controller **12** to vary valve operation. The operation of intake valve **150** and exhaust valve **156** may be determined by valve position sensors (not shown) and/or camshaft position sensors **155** and **157**, respectively. In alternative embodiments, the intake and/or exhaust valve may be controlled by electric valve actuation. For example, cylinder **14** may alternatively include an intake valve controlled via electric valve actuation and an exhaust valve controlled via cam actuation including CPS and/or VCT systems.

In some embodiments, each cylinder of engine **10** may include a spark plug **192** for initiating combustion. Ignition system **190** can provide an ignition spark to combustion chamber **14** via spark plug **192** in response to spark advance signal SA from controller **12**, under select operating modes. However, in some embodiments, spark plug **192** may be omitted, such as where engine **10** may initiate combustion by auto-ignition or by injection of fuel as may be the case with some diesel engines.

In some embodiments, each cylinder of engine **10** may be configured with one or more injectors for providing fuel. As a non-limiting example, cylinder **14** is shown including one fuel injector **166**. Fuel injector **166** is shown coupled directly to cylinder **14** for injecting fuel directly therein in proportion to the pulse width of signal FPW received from controller **12** via electronic driver **168**. In this manner, fuel injector **166** provides what is known as direct injection (hereafter also referred to as "DI") of fuel into combustion cylinder **14**. While FIG. **1** shows injector **166** as a side injector, it may also be located overhead of the piston, such as near the position of spark plug **192**. Fuel may be delivered to fuel injector **166** from a high pressure fuel system **8** including fuel tanks, fuel pumps, and a fuel rail. Alternatively, fuel may be delivered by a single stage fuel pump at lower pressure, in which case the timing of the direct fuel injection may be more limited during the compression stroke than if a high pressure fuel system is used. Further, while not shown, the fuel tanks may have a pressure transducer

providing a signal to controller **12**. It will be appreciated that, in an alternate embodiment, injector **166** may be a port injector **170**, indicated as a variation in dotted line, providing fuel into the intake port upstream of cylinder **14**.

Fuel may be delivered by the injector to the cylinder during a single cycle of the cylinder. Furthermore, for a single combustion event, multiple injections of the delivered fuel may be performed per cycle. The multiple injections may be performed during the compression stroke, intake stroke, or any appropriate combination thereof.

As described above, FIG. **1** shows one cylinder of a multi-cylinder engine. As such each cylinder may similarly include its own set of intake/exhaust valves, fuel injector(s), spark plug, etc.

Controller **12** is shown in FIG. **1** as a microcomputer, including microprocessor unit **106**, input/output ports **108**, an electronic storage medium for executable programs and calibration values shown as read only memory **110** in this particular example, random access memory **112**, keep alive memory **114**, and a data bus. Controller **12** may receive various signals from sensors coupled to engine **10**, in addition to those signals previously discussed, including measurement of inducted mass air flow (MAF) from mass air flow sensor **122**; engine coolant temperature (ECT) from temperature sensor **116** coupled to cooling sleeve **118**; a profile ignition pickup signal (PIP) from Hall effect sensor **120** (or other type) coupled to crankshaft **140**; throttle position (TP) from a throttle position sensor; manifold absolute pressure signal (MAP) from sensor **124**; and knock signal (KS) from knock sensor **181**. Knock sensor **181** may alternatively be located on the cylinder head or may be a sensor to detect vibrations from knock in crankshaft **140**. Engine speed signal, RPM, may be generated by controller **12** from signal PIP. Manifold pressure signal MAP from a manifold pressure sensor may be used to provide an indication of vacuum, or pressure, in the intake manifold. Still other sensors may include fuel level sensors and fuel composition sensors coupled to the fuel tank(s) of the fuel system.

Storage medium read-only memory **110** can be programmed with computer readable data representing instructions executable by microprocessor unit **106** for performing the methods described below as well as other variants that are anticipated but not specifically listed. Engine **10** may be controlled at least partially by a control system **15** including controller **12**. Controller **12** may receive various signals from sensors **16** coupled to engine **10**, and send control signals to various actuators **81** coupled to the engine and/or vehicle. The various sensors may include, for example, various temperature, pressure, and air-fuel ratio sensors. The various actuators may include, for example, valves, throttles, and fuel injectors.

As mentioned above, sensors **16** may include any temperature, pressure, positioning, humidity or contacting sensors or any other sensors described herein. In an example, sensors **16** may include one or more microphones. Actuators **81** may include actuators used to control the first and second adjustable exhaust valves **196a**, **196b**. Controller **12** may be a microcomputer, including a microprocessor unit, input/output ports, an electronic storage medium for executable programs and calibration values. Controller **12** may be programmed with computer readable data representing instructions executable to perform the methods described below as well as other variants that are anticipated but not specifically listed.

For example, adjusting the first and second adjustable exhaust valves **196a**, **196b** may include adjusting actuators

81 coupled to adjustable exhaust valves **196a**, **196b**. In an example, to adjust an angle of an adjustable exhaust valve **196a**, **196b**, or herein described valve **220**, actuators **224a**, **224b**, **222** may open or close the valve by providing torque via a rotational rod connected to valve **220** along the valve rotational axis **214**, further described below with respect to FIG. 2B.

FIG. 2A shows an example alternative view of the variable exhaust tuning system. In an example, the variable exhaust tuning system may include sensors **16** such as post-catalyst sensor **202**, pre-flap sensors **204a** and **204b**, pivot sensors **206a** and **206b**, post-flap sensors **208a** and **208b**, and first valve positioning sensor **210a** and second valve positioning sensor **210b**, all located within the variable exhaust tuning system. In an example, valve positioning sensors **210a** and **210b** may be located on the external housing of valve **220** and in an example, the second valve positioning sensor **210b** may be located on the valve **220**. In another example, the valve positioning sensors **210a** and **210b** may be included within the actuator **222**. Sensors **202**, **204a**, **204b**, **206a** and **206b**, and **208a** and **208b** may, in an example, all be temperature and/or pressure sensors and the exhaust temperature and exhaust back pressure may be measured by one or more sensors. In an example, sensors **202**, **204a**, **204b**, **206a** and **206b**, and **208a** and **208b** may be communicatively coupled to controller **12** via input/output ports **108** and the controller may determine a temperature and/or back pressure model for the variable exhaust tuning system based upon the input provided from the plurality of sensors. In an example, the sensors mentioned herein with respect to FIG. 2A may be installed within the post-treatment walls **189**, wherein post-treatment walls **189** may form the structure of the different bodies of the variable exhaust tuning system. In an example the post-treatment walls **189** may be formed from any desirable metal such as aluminum or steel or any desirable alloy. In an example, any of the sensors **202**, **204a**, **204b**, **206a** and **206b**, and **208a** and **208b** may be included within sensors **16** of the control system. In a further example, post-treatment walls **189** may further comprise an inner post-treatment layer **289a**, a post-treatment wall material **289b** having a post-treatment wall thickness **289c**, and an outer post-treatment wall layer **289d**.

In an example, the variable exhaust tuning system may comprise a plurality of actuators **81**. In an example, adjustable exhaust valves **196a** and **196b** may be respectively adjusted by a first valve actuator **224a** and a second valve actuator **224b**. First and second valve actuators **224a**, **224b** may be communicatively coupled to controller **12**. In an example, control system may include controller **12** which may receive signals from the sensors **16** and employ actuators **81** to adjust engine operation and/or variable exhaust tuning system operation based on the received signals and instructions stored on a memory of the controller further described herein.

FIG. 2B shows an upstream-looking point of view from the downstream end of either a first or second muffler inner exhaust port **198a** or **198b** (in FIG. 2B, as an example, shown as **198a**), and in such an example, either adjustable exhaust valves **196a** or **196b** may comprise a butterfly, damper, quarter turn, or compression valve represented by valve **220**. In some cases, the positioning of adjustable exhaust valves **196a**, **196b** may be adjusted by adjustable exhaust valve actuators **224a**, **224b** which may be represented in FIG. 2B by actuator **222**. Actuator **222** may, in an example, adjust the position or rotation angle of valve **220** along a valve rotational axis **214**, wherein the rotational axis includes a rotational rod in order to provide turning of the

valve **220** via actuator **222**. In an example, the rotational rod of valve rotational axis **214** may be attached to and passing through valve **220** or it may be built into valve **220** as a single body. Actuator **222** may optionally or additionally include a valve stuck sensor **226**.

In another example, FIG. 2B includes one or more valve positioning sensors **212** which may be positioned along the valve rotational axis **214** of the valve and they may also be attached to the rotational rod running along valve rotational axis **214**. In an example, valve positioning sensors **212** may provide continuous indication of valve **220** position. In addition, valve positioning sensors **212** may be communicatively coupled to controller **12** via input/output ports **108**. In an example, valve **220** may only include a single valve positioning sensor **212**.

Instructions for carrying out methods **300**, **400**, and the rest of the methods included herein may be executed by the controller **12** based on instructions stored on a memory of the controller and in conjunction with signals received from sensors of the engine system, such as the sensors described above with reference to FIGS. 1, 2A and 2B. The controller may employ engine actuators of the engine system to adjust engine operation and variable exhaust tuning system operation according to the methods described below.

FIG. 3 shows a high-level flow chart detailing method **300** for providing stuck adjustable exhaust valve diagnostics with a valve position sensor. In an example, the method **300** may begin at **302** wherein at an engine-off event, the controller **12** may determine an engine-off time and/or engine-off conditions at the engine-off event. In an example, engine-off conditions may include any of exhaust temperature, ambient temperature, adjustable exhaust valve positioning, or any other condition measured by sensors **16** at engine-off conditions. Following the engine-off event, controller **12** may determine an engine-on time and engine-on conditions via sensors **16** when the engine is next started up.

Next, at **303** the controller **12** may execute a stuck valve check via input/output ports **108** with an actuator **222** of valve **220** if the actuator **222** reports a stuck status. In an example, the stuck valve check may comprise the controller **12** commanding the actuator **222** to move the valve **220** to a check valve position or to adjust the valve **220** position by a programmable check valve adjustment. If the valve **220** is stuck or unable to move to the check valve position or by the programmable check valve adjustment, the actuator **222** may send a stuck valve status to the controller **12** via input/output ports **108**. In an example, the valve **220** may be rotated to the check valve position or rotated by the programmable check valve adjustment via actuator **222** rotating the rotational rod. In another example, one or more of the valve positioning sensors **210a** and **210b** may be used to determine that the stuck valve check has revealed valve **220** to be stuck. In an example the valve positioning sensors **210a** and/or **210b** may be used to determine that the valve **220** was unable to move the check valve positioning or have the actuator **222** adjust the valve **220** position by the programmable check valve adjustment. In an example, if at **303**, the actuator **222** does not send the stuck valve status and upon executing the stuck valve check (wherein the valve is moved to the check valve position or adjusted by the programmable check valve adjustment) then the method **300** may end.

In an example, method **300** may proceed next to **304** where the controller may determine if one or more entry conditions are met at engine start, or engine-on. In a non-limiting example, entry conditions may comprise any of the following: an actuator of an adjustable exhaust valve **196a**

or **196b** reporting the stuck valve status; a humidity sensor of the variable exhaust tuning system reading a water concentration higher than a threshold water concentration at the most recent engine-off time; a vehicle soak time being greater than a calculated amount of time for ice formation while engine is off, wherein the calculated amount of time for ice formation is based upon ambient temperature and the water concentration sensed by the humidity sensor of the variable exhaust tuning system; a current ambient temperature being either greater than (a hot day) or less than (a cold day) a threshold temperature; and an exhaust volume level failing to fall between a first volume threshold and a second volume threshold associated with each commanded position of a valve **220**. In an example, the controller may determine that no entry conditions are met and method **300** may end. In another example, the controller **12** may determine that one or more entry conditions are met via data obtained via input/output ports **108** by sensors **16** and the method **300** may proceed to **306**.

At **306**, the controller **12** may determine if an exhaust temperature is equivalent to or above an exhaust temperature threshold. In an example, controller **12** may determine the exhaust temperature from data received via input/output ports **108** from any of the temperature sensors of the variable exhaust tuning system described above with respect to FIG. **2A**. In an example, the controller **12** may determine that the exhaust temperature has not yet reached the threshold exhaust temperature and the method **300** may proceed to **308** wherein the controller **12** may suspend setting a stuck valve code until the exhaust temperature has reached the exhaust temperature threshold. In an example, suspending setting the stuck valve code may allow for adjustable exhaust valve diagnostics to self-heal a potentially stuck valve or eliminate a “false-positive” stuck valve code in which an adjustable exhaust valve **196a**, **196b** may be reported as stuck but is not actually so. In an example, if the controller **12** has determined that the exhaust temperature has not yet reached the threshold exhaust temperature, the method **300** may return to **306** to check again if the exhaust temperature is equivalent to or is greater than the exhaust temperature threshold. In such an example, as the engine has been turned on by the vehicle operator **130**, the exhaust temperature may increase over time. In an example, the method **300** may cycle between **306** and **308** as many times as necessary in order for the exhaust temperature to reach the threshold exhaust temperature. In an example, the method **300** may only cycle between **306** and **308** an allowed number of times before latching an exhaust error or temperature exhaust error, wherein one or more temperature sensors may be defective or inoperable, and the method **300** may then end or proceed to **310**.

Method **300** may proceed to **310** when the controller **12** receives data via input/output ports **108** indicating that the exhaust temperature is equivalent to or greater than the threshold exhaust temperature. At **310**, the controller **12** may measure a first measured valve position of a valve **220** and then command an adjustable exhaust valve **196a**, **196b** via adjustable exhaust valve actuators **224a**, **224b** to a commanded valve position either 50% less or 50% greater than the first measured valve position. In an example, the first measured valve position and commanded valve position and any other valve positions may be measured by valve positioning sensors **210a** and **210b** and the positions may be normalized valve positions wherein a range of normalized valve positions may range from 0% (completely closed) to 100% (completely open). After commanding the adjustable exhaust valve **196a**, **196b** to the commanded valve position,

the controller may execute a retry logic wherein the valve may be commanded to an updated commanded position comprising alternate end-stop positions (0% and 100%) or any intermediate positions for a calibratable number of times.

Next, the method **300** may proceed to **312** wherein the controller **12** may run a threshold band check which may compare an updated measured position of the valve **220** with the updated commanded position of the valve **220**. In an example, the controller **12** may run the threshold band check every 90 seconds during the execution of the retry logic. In an example, if the updated measured position of the valve **220** is within a tolerance band, or tolerance limit, of the updated commanded position then the method may **300** may end. In an example, if the updated measured position of the valve **220** is not within the tolerance band, or threshold, the controller **12** may proceed to **314**. In an example, at **314** of the method **300**, the controller **12** may add a command counter and execute a command counter check to see if the method **300** has reached a command counter threshold. In an example, the command counter threshold may be reset to zero at each vehicle start up. In an example, the command counter threshold may be programmed to a desired number of valve positioning commands.

If the controller **12** determines that the command counter threshold has been reached, method **300** may proceed to **316** wherein the controller **12** may latch a valve trouble code indicating to the vehicle operator **130** that there is an issue with one or more adjustable exhaust valves **196a**, **196b**. In a further example, if the controller **12** determines that the command counter threshold has not been reached, method **300** may revert to **310** and again command the valve **220** to the commanded valve position and this process may loop until either the updated measured position of the valve **220** is within the tolerance band of the updated commanded position or if the command counter check returns that the command counter threshold has been reached. After latching the valve trouble code, method **300** may end.

In an example, the calculated amount of time for ice formation may be obtained by assuming that the ice may be formed due to a certain quantity of water during a soak time, or the time between a most recent engine-off and an engine start wherein the temperature was below freezing. By using the known specific heat of water, estimating a mass of water can be accomplished following the formula: $Q=mc\Delta T$ and differentiating to solve for time for ice formation, the following formula may be used:

$$\text{time for ice formation} = (\text{mass of water estimation}) * (\text{specific heat transfer for water}) * (\text{last engine off temperature} - \text{engine on temperature}) / (\text{power in J/s})$$

In an example, sensors **16** of the variable exhaust tuning system may provide humidity and temperature measurements at an engine off event and may provide the mass of water estimation. In another example, the mass of water estimation may be provided as a calibratable and/or programmable number based upon the volume of the variable exhaust tuning system.

In a further example, the controller **12** may additionally use the microphone **195** to obtain sound and/or volume levels of the variable exhaust tuning system via input/output ports **108**. In an example, vehicle operator **130** may be able to adjust a position of a valve between a number of positions in order to adjust the backpressure, and therefore volume level, of the variable exhaust tuning system. In an example, the vehicle operator **130** may be able to select between 4 different positions of valve **220** achieved by commanding

11

actuator **222**. In an example, the vehicle operator **130** may choose 4 different calibratable positions of valve **220**, namely, “quiet”, “normal”, “sport”, and “track”, being in respective decreasing order of backpressure and increasing order of volume. In an example, each position of valve **220** associated with different calibratable positions may have an associated volume level as well as an upper volume threshold and lower volume threshold. In an example, if a live volume level from microphone **195** does not fall between the upper volume threshold and lower volume threshold of an associated volume level of a calibratable position of valve **220** then the controller **12** may set a volume error code. In a further example, the controller **12** may command the valve **220** to an updated volume positioning in order to adjust the live volume level so that it may fall between the upper and lower volume thresholds mentioned above. In an example, the controller **12** may further update the calibratable positions of valve **220** to updated calibratable positions based upon the adjustment made with respect to volume level, as mentioned above.

In a further example, as shown in FIG. 1, a first adjustable exhaust valve **196a** may be located on a passenger’s side of the vehicle and a second adjustable exhaust valve **196b** may be located on a driver’s side of the vehicle wherein the outer exhaust ports **199a** and **199b**, and inner exhaust ports **198a** and **198b** direct exhaust gases towards the rear of the vehicle and the resonator is located upstream of the exhaust ports and toward the front of the vehicle. In an example, a microphone **195** may be attached to a bottom of the vehicle and/or between the first and second exhaust ports. In an example, the microphone **195** may be capable of receiving stereo volume (i.e. left and right channels). In an example, volume diagnostics may include one or more of: commanding the first and second adjustable exhaust valves **196a**, **196b** to close wherein low volume should be detected; commanding the first adjustable exhaust valve **196a** closed wherein the microphone **195** may detect an increase in volume from the passenger’s side of the vehicle; and commanding the second adjustable exhaust valve **196b** closed wherein the microphone **195** may detect an increase in volume from the driver’s side of the vehicle. By running one or more of the above volume diagnostics, the controller **12** may be able to provide improved diagnostics and the controller **12** may declare a fault when the above conditions are not observed. Additionally delta pressure and/or temperature sensors **194a**, **194b** included within mufflers **197a**, **197b** may detect a difference in pressure and/or temperature when an adjustable exhaust valve **196a**, **196b** is commanded to a new position. In an example, when sensors **194a**, **194b** do not detect the difference in pressure and/or temperature when **196a**, **196b** are commanded to the new position, the controller **12** may also declare a fault.

FIG. 4 shows a high-level flow chart detailing method **400** for providing stuck adjustable exhaust valve diagnostics without a valve position sensor. In an example, method **400** may begin at **402** wherein at an engine-off event, the controller **12** may determine an engine-off time and/or engine-off conditions at the engine-off event. In an example, engine-off conditions may include any of exhaust temperature, ambient temperature, adjustable exhaust valve positioning, or any other condition measured by sensors **16** at engine-off conditions. Following the engine-off event, controller **12** may determine an engine-on time and engine-on conditions via sensors **16** when the engine is next started up.

Next, at **403** the controller **12** may execute a stuck valve check via input/output ports **108** with an actuator **222** of valve **220** if the actuator **222** reports a stuck status. In an

12

example, the stuck valve check may comprise the controller **12** commanding the actuator **222** to move the valve **220** to a check valve position or to adjust the valve **220** position by a programmable check valve adjustment. If the valve **220** is stuck or unable to move to the check valve position or by the programmable check valve adjustment, the actuator **222** may send a stuck valve status to the controller **12** via input/output ports **108**. In an example, valve stuck sensor **226** may determine that the stuck valve check has revealed the valve **220** to be stuck and may communicate to the controller **12** that valve is stuck. In an example, the valve **220** may be rotated to the check valve position or rotated by the programmable check valve adjustment via actuator **222** rotating the rotational rod. In an example, if at **403**, the actuator **222** does not send the stuck valve status and upon executing the stuck valve check (wherein the valve is moved to the check valve position or adjusted by the programmable check valve adjustment) then the method **300** may end.

In an example, method **400** may proceed next to **404** where the controller may determine if one or more entry conditions are met at engine start, or engine-on. In a non-limiting example, entry conditions may comprise any of the following: an actuator of an adjustable exhaust valve **196a** or **196b** reporting a stuck status; a valve stuck sensor **226** reporting a stuck valve status; a humidity sensor of the variable exhaust tuning system reading a water concentration higher than a threshold water concentration at the most recent engine-off time; a vehicle soak time being greater than a calculated amount of time for ice formation while engine is off, wherein the calculated amount of time for ice formation is based upon ambient temperature and the water concentration sensed by the humidity sensor of the variable exhaust tuning system; a current ambient temperature being either greater than (a hot day) or less than (a cold day) a threshold; and an exhaust volume level failing to fall between a first volume threshold and a second volume threshold associated with each commanded position of a valve **220**. In an example, the vehicle soak time may be a duration of time during which a vehicle having a variable exhaust tuning system rests with the engine off having ambient temperature below freezing. In an example, the controller may determine that no entry conditions are met and method **400** may end. In another example, the controller **12** may determine that one or more entry conditions are met via data obtained via input/output ports **108** by sensors **16** and the method **400** may proceed to **406**.

At **406**, the controller **12** may determine if an exhaust temperature is equivalent to or above an exhaust temperature threshold. In an example, controller **12** may determine the exhaust temperature from data received via input/output ports **108** from any of the temperature sensors of the variable exhaust tuning system described above with respect to FIG. 2A. In an example, the controller **12** may determine that the exhaust temperature has not yet reached the threshold exhaust temperature and the method **400** may proceed to **408** wherein the controller **12** may suspend setting a stuck valve code until the exhaust temperature has reached the exhaust temperature threshold. In an example, suspending setting the stuck valve code may allow for adjustable exhaust valve diagnostics to self-heal a potentially stuck valve or eliminate a “false-positive” stuck valve code in which an adjustable exhaust valve **196a**, **196b** may be reported as stuck but is not actually so. In an example, if the controller **12** has determined that the exhaust temperature has not yet reached the threshold exhaust temperature, the method **400** may return to **406** to check again if the exhaust temperature is equivalent to or is greater than the exhaust temperature threshold.

In such an example, as the engine has been turned on by the vehicle operator 130, the exhaust temperature may increase over time. In an example, the method 400 may cycle between 406 and 408 as many times as necessary in order for the exhaust temperature to reach the threshold exhaust temperature. In an example, the method 400 may only cycle between 406 and 408 an allowed number of times before latching an exhaust error or temperature exhaust error, wherein one or more temperature sensors may be defective or inoperable, and the method 400 may then end or proceed to 410.

At 410, the controller 12 may execute a valve self-healing routine via input/output ports 108 to command the actuator 222 of valve 220 to toggle the valve a programmable number of times to return the valve to a normal state of operation. In an example, the valve may be toggled 11 times. In an example, a valve toggle may comprise the controller 12 commanding the actuator 222 of the valve 220 to completely open and completely close. In an example, the valve 220 is not reported as a stuck valve via the valve stuck sensor 226 or the actuator 222 when the valve successfully completes the programmable number of valve toggles. In an example, the valve 220 may be reported as stuck to the controller 12 via input/output ports 108 when the actuator 222 of the valve 220 reports that it cannot move, and issues a stuck valve code, or the stuck valve sensor 226 reports that the valve 220 is not moved when commanded to. In another example, an adjustable exhaust valve either 196a or 196b may be reported as stuck when the valve 220, having the stuck valve sensor 226 incorporated within the actuator 222, cannot move along the valve rotational axis 214. In an example, the stuck valve sensor 226 may be positioned on or within the actuator 222, or the stuck valve sensor may be positioned on or within the valve 220 on either an edge or an inner portion of the valve 220 nearest the valve housing of the inner exhaust ports 198a and 198b.

Next, method 400 may move to 412 where the controller 12 via input/output ports 108 may see if there is still a stuck valve code from either the actuator 222 or valve stuck sensor 226. If the controller 12 fails to receive the stuck valve code then the method 400 may end. If there is a stuck valve code then the method 400 may proceed to 413 where the controller 12 may count a first self-healing counter. In an example, at 413, if the controller has not reached a threshold number of self-healing counters, then the routine may return to 410 and running the self-healing routine once again. If, at 413, however, the controller 12 has reached the threshold number of self-healing counters, which may be programmable, the method may proceed to 414. In another example, instead of counting self-healing counters each time the method 400 reaches 413 and returns to 410, the method 400 may instead run a self-healing timer during which the self-healing routine is executed and the self-healing routine may be executed by controller 12 until the stuck valve code may be removed or until the self-healing timer reaches a self-healing timer threshold.

In an example, at 414 the controller 12 may latch a valve trouble code. In an example, the valve trouble code may provide a visual and/or volume notification to the vehicle operator 130 and may only be reset, or unlatched, via an automotive technician or by re-running method 400 either by the vehicle operator 130 command or by manually restarting the vehicle and providing an engine-on event. In an example, the vehicle operator 130 may re-run the method 400 via a command user interface provided in the vehicle.

Next, FIG. 5 shows a graph 500 displaying sample conditions over time during a stuck valve diagnosis for a

variable exhaust tuning system. In an example, FIG. 5 illustrates various engine and ambient conditions during the execution of method 300 illustrated in FIG. 3.

In FIG. 5 time is depicted along the x (horizontal) axis while values of each respective parameter are depicted along the y (vertical) axis. At T1 along the time axis, there is an engine-on event and the controller 12 may monitor engine off time and engine start up conditions, as explained above with respect to 302 of method 300. Turning to graph 500, at T1 within the Ambient Temperature sub-graph, 502 shows an ambient temperature threshold with a temperature reading 504 shown to be below the temperature threshold. At T1, within the Exhaust Temperature sub-graph, 506 illustrates rising exhaust temperature as the engine runs while exhaust temperature threshold indicator 508 shows a binary readout representing if the exhaust temperature has reached an exhaust temperature threshold or is below an exhaust temperature threshold. At T1, 506 indicates that the exhaust temperature threshold has not been reached. Continuing at T1 within the Valve Angular Positioning sub-graph, 510 shows a measured valve position, 512 shows an upper threshold for valve position, 514 shows a desired valve position, and 516 shows a lower threshold for valve position. At T1, 510 is currently above the upper threshold for valve position 512 and, as such, at least one entry condition, described above with respect to 304 of method 300, is met. Continuing at T1, fault declaration 518 may be a binary readout shown in Fault Declaration sub-graph which indicates whether there is a fault or no fault.

Turning now to T2 of graph 500, referring to sub-graph Exhaust Temperature it is shown that exhaust temperature 506 has reached the exhaust temperature threshold indicated by 508. In an example, the exhaust temperature threshold may be programmable. Continuing at T2, within the Fault Declaration sub-graph, an error may be declared at 520 due to the measured valve position 510 being outside the upper threshold for valve position 512 and lower threshold for valve position 516. Referring back to FIG. 3, at 306-308 once the exhaust temperature reaches the exhaust threshold then the method no longer suspends setting an error code or declaring a fault within the variable exhaust tuning system.

With reference to 310 of FIG. 3, the method 300 may command valve to commanded valve position at T2 in FIG. 5 within the Valve Angular Positioning sub-graph. In an example, the controller 12 may command the valve 220 via input/output ports 108 to updated desired valve position 524. In an example, based upon 514 changing to 524 upper and lower thresholds for valve position 512 and 516 also change, respectively to updated upper threshold for valve position 522 and updated lower threshold for valve position 526. According to the Valve Angular Positioning sub-graph shown in graph 500 of FIG. 5, the desired and updated valve positions 514 and 524 as well as thresholds 512, 516, 522, 526 may alternate back and forth over time in order to loosen or unstuck a stuck valve i.e. valve 220. In an example, the desired valve position 514 may toggle back and forth between 2 angular valve positions, or in other examples, toggle back and forth between a programmable number of angular valve positions. With reference to 312 of method 300 of FIG. 3, as the measured valve position 510 is not yet within the thresholds 512, 516 and 522, 526, the method may, in an example, proceed to 314 and return to 310 to keep adjusting a commanded, or desired, valve position. In an example, the commanded, or desired, valve position need not be the same valve angular position each and every time the method 300 cycles from 310 to 312 to 314 and back to 310.

Turning now to T3 of FIG. 5, at 528 of the sub-graph Valve Angular Positioning, the measured valve position 510 drops to within the upper and lower thresholds 512, 516, 522, 526. As such, and with reference to FIG. 3, the method discontinues commanding the valve to new positions and the method ends. In an example, FIG. 5 shows 510 at T3 and after T3 as within thresholds 512 and 516 but not exactly matching with desired valve position 514. In some examples, the valve angular positioning may be normalized from 0% to 100%. In an example, the upper threshold for valve position 512 may be 8% or 0.08 greater than the desired valve position 514 and the lower threshold for valve position 516 may be 8% or 0.08 less than the desired valve position 514. In an example, now that 510 falls between 512 and 516, at 530 in the Fault Declaration sub-graph of FIG. 5 the fault declaration is eliminated and the vehicle operator 130 is not alerted to any fault and no error code is latched. In another example, the commanding to different positions of measured valve position 510 between times T2 and T3 may also occur any number of additional instances, and if the valve command counter reaches the command counter threshold, then the method 300 may proceed to 316 and latch an error if the measured valve position 510 fails to fall within the thresholds 512, 516. In an example where the valve command counter reaches the command counter threshold and the error is latched, the vehicle operator 130 may be alerted to the latched error code via volume and/or visual alert within the cabin of the vehicle.

Next, FIG. 6 shows a graph 600 displaying sample conditions over time during a stuck valve diagnosis for a variable exhaust tuning system not having a valve angular positioning sensor. In an example, FIG. 6 illustrates various engine and ambient conditions during the execution of method 400 illustrated in FIG. 4. In FIG. 6 time is depicted along the x (horizontal) axis while values of each respective parameter are depicted along the y (vertical) axis. At T1 along the time axis, there is an engine-on event and the controller 12 may monitor engine off time and engine start up conditions, as explained above with respect to 402 of method 400. In an example, one or more entry conditions may be met at engine start up, according to 404 of method 400, such as an actuator 222 operating valve 220 not being able to move. Turning to graph 600, at T1 within the Ambient Temperature sub-graph, 602 shows an ambient temperature threshold with a temperature reading 604 shown to be below the temperature threshold. At T1, within the Exhaust Temperature sub-graph, 606 illustrates rising exhaust temperature as the engine runs while exhaust temperature threshold indicator 608 shows a binary readout representing if the exhaust temperature has reached an exhaust temperature threshold or is below an exhaust temperature threshold. At T1, an exhaust temperature indicator 608 indicates that the exhaust temperature threshold has not been reached. Continuing at T1, fault declaration 610 may be a binary readout shown in Fault Declaration sub-graph which indicates whether there is a fault or no fault.

Turning now to T2 of graph 600, at 612 the exhaust temperature indicator 608 shows that an exhaust temperature threshold has been reached. Referring to 406 and 408 of method 400, once the exhaust temperature has been reached, the method 400 may advance to 410 wherein the controller 12 may execute a self-healing routine via input/output ports 108. As shown by 614, the controller 12 may track self-healing time elapsed as the self-healing routine is executed. Turning next to T3 of graph 600 in the Fault Declaration sub-graph, at 616 the method may declare a fault and/or issue a stuck valve code indicated by the fault declaration

610 showing a fault. Referring to method 400 of FIG. 4, the method may declare, or latch, a fault at 412 if the valve is stuck. In an example, as explained above, the controller 12 may recognize the valve as stuck and latch a fault if the valve 220 is unable to move via actuator 222. In an example, when the valve 220 cannot move via actuator 222, the controller 12 may recognize that the valve is in a non-normal state of operation. Continuing at T3, 614 may continue to increase as the self-healing routine may continue, or, in an example when the self-healing routine has already run once, the self-healing routine may be executed via controller 12 an additional programmable number of times.

Turning next to T4, at 618 the fault declaration shown at 616 may be removed due to continued self-healing routine after T3. In an example, the fault declaration may be removed or canceled at 618 once the valve 220 may become movable via actuator 222. In an example, when the fault declaration is removed at 618 the self-healing procedure may also end as shown at 620 due to the valve 220 functionality being restored.

As another example, the controller 12 may make a logical determination (e.g., regarding a position of one or more adjustable exhaust valve actuators 224a, 224b, 222) based on logic rules that are a function of parameters illustrated in FIGS. 5 and 6. The controller may then generate a control signal that is sent to, for example, actuators 224a, 224b, 222. In another example, microphone 195 may provide volume input to controller 12 via input/output ports 108. In an example, controller 12 may include volume parameters associated with commanded positions of valve 220.

FIGS. 1, 2A, and 2B show example configurations with relative positioning of the various components. If shown directly contacting each other, or directly coupled, then such elements may be referred to as directly contacting or directly coupled, respectively, at least in one example. Similarly, elements shown contiguous or adjacent to one another may be contiguous or adjacent to each other, respectively, at least in one example. As an example, components laying in face-sharing contact with each other may be referred to as in face-sharing contact. As another example, elements positioned apart from each other with only a space therebetween and no other components may be referred to as such, in at least one example. As yet another example, elements shown above/below one another, at opposite sides to one another, or to the left/right of one another may be referred to as such, relative to one another. Further, as shown in the figures, a topmost element or point of element may be referred to as a "top" of the component and a bottommost element or point of the element may be referred to as a "bottom" of the component, in at least one example. As used herein, top/bottom, upper/lower, above/below, may be relative to a vertical axis of the figures and used to describe positioning of elements of the figures relative to one another. As such, elements shown above other elements are positioned vertically above the other elements, in one example. As yet another example, shapes of the elements depicted within the figures may be referred to as having those shapes (e.g., such as being circular, straight, planar, curved, rounded, chamfered, angled, or the like). Further, elements shown intersecting one another may be referred to as intersecting elements or intersecting one another, in at least one example. Further still, an element shown within another element or shown outside of another element may be referred to as such, in one example.

In this way methods and devices are provided to adjust and diagnose a variable exhaust tuning system having one or more stuck valves, in some cases stuck valves may be

caused due to ice formation and may cause a false stuck valve error. The methods and devices enable additional advantages by providing both direct (valve positioning, stuck valve, etc.) and indirect valve (volume input, temperature input, pressure input) diagnostics. The technical effect of executing the herein described valve diagnostics is that fewer false errors are issued and the noise, vibration and harshness (NVH) experience for the vehicle operator **130** is improved.

In one example, a method for an adjustable engine-exhaust valve is provided, comprising: monitoring engine off time and checking for one or more entry conditions at engine startup, operating with the valve being stuck, and responsive to the valve being stuck: during selected engine start-up conditions and after sufficient engine-off time, setting an error code associated with the one or more entry conditions upon an exhaust temperature reaching an exhaust temperature threshold, commanding the adjustable exhaust valve to a first commanded valve position, and based upon a current valve position of the adjustable exhaust valve being within a tolerance band of a first commanded valve position, clearing the error code. In any or all of the preceding example, the method may optionally or additionally include the one or more entry conditions further comprising any of an actuator of the adjustable exhaust valve reporting a stuck status; a humidity sensor reading a water concentration higher than a threshold water concentration at the most recent engine-off time; a vehicle soak time being greater than a calculated amount of time for ice formation while engine is off; a current ambient temperature being either greater than or less than a threshold temperature; and an exhaust volume level failing to fall between a first volume threshold and a second volume threshold. In any or all of the preceding examples, the method may further comprise calculating the calculated amount of time for ice formation based upon a difference in temperature of exhaust at an engine-off event and at the next engine-on event. In any or all of the preceding examples, the method may further comprise measuring the exhaust volume level via a microphone attached to a bottom surface of the vehicle. In any or all of the preceding example, the method may optionally or additionally include the exhaust temperature is measured by temperature sensors within the walls of the adjustable exhaust valve. In any or all of the preceding examples the method may optionally or additionally include wherein the current valve position of the adjustable exhaust valve is not within the tolerance band of the first commanded valve position then adding a valve command counter. In any or all of the preceding examples, the method may further comprise after adding the valve command counter then again commanding the adjustable exhaust valve to the first commanded valve position. In any or all of the preceding examples, the method may further comprise upon reaching a command counter threshold latching a valve error code. In any or all of the preceding examples, the method may further comprise alerting a vehicle operator within the cabin of the vehicle to the valve error code via a volume and/or visual alert.

In another example, a method for troubleshooting an adjustable exhaust valve of an engine is provided, comprising: monitoring engine off time and checking for one or more entry conditions at engine startup, executing a stuck valve check, operating with exhaust temperature rising up to and above an exhaust temperature threshold; setting a stuck valve error code associated with the one or more entry conditions upon the exhaust temperature reaching the exhaust temperature threshold, running a valve self-healing

routine, checking a first time for a stuck valve code of the adjustable exhaust valve, and based upon failing to receive the stuck valve code, clearing the error code. In any or all of the preceding examples, the method may optionally or additionally include the valve self-healing routine comprises toggling the adjustable exhaust valve between open and closed states a programmable number of times. In any or all of the preceding examples, the method may further comprise issuing the stuck valve code at an actuator of the adjustable exhaust valve when the actuator cannot move. In any or all of the preceding examples, the method may further comprise based upon receiving the stuck valve code, counting a first self-healing counter. In any or all of the preceding examples, the method may further comprise running the self-healing routine again and checking an additional time for the stuck valve code.

In any another example, a device for adjusting and diagnosing a valve position of a post-catalyst variable exhaust tuning system to control an exhaust backpressure is provided, comprising: a resonator fluidically connected to a muffler having a first and a second muffler exhaust port, an adjustable exhaust valve included within the first muffler exhaust port adjusted via a valve actuator communicatively coupled to a controller, and a positioning sensor included within the adjustable exhaust valve. In any or all of the preceding examples, the device may optionally or additionally include that the adjustable exhaust valve is a butterfly valve. In any or all of the preceding examples, the device may further comprise a humidity sensor to estimate an engine off estimation of a mass of water remaining in the device. In any or all of the preceding examples, the device may further comprise a rotational rod connected to both the adjustable exhaust valve and the valve actuator for rotating the adjustable exhaust valve. In any or all of the preceding examples, the device may further comprise a microphone attached to a bottom surface of the vehicle for obtaining volume input of the variable exhaust tuning system. In any or all of the preceding examples, the device may further comprise a pressure and temperature sensor included within the muffler for tracking both temperature and pressure of exhaust gases of the variable exhaust tuning system.

Note that the example control and estimation routines included herein can be used with various engine and/or vehicle system configurations. The control methods and routines disclosed herein may be stored as executable instructions in non-transitory memory and may be carried out by the control system including the controller in combination with the various sensors, actuators, and other engine hardware. The specific routines described herein may represent one or more of any number of processing strategies such as event-driven, interrupt-driven, multi-tasking, multi-threading, and the like. As such, various actions, operations, and/or functions illustrated may be performed in the sequence illustrated, in parallel, or in some cases omitted. Likewise, the order of processing is not necessarily required to achieve the features and advantages of the example embodiments described herein, but is provided for ease of illustration and description. One or more of the illustrated actions, operations and/or functions may be repeatedly performed depending on the particular strategy being used. Further, the described actions, operations and/or functions may graphically represent code to be programmed into non-transitory memory of the computer readable storage medium in the engine control system, where the described actions are carried out by executing the instructions in a system including the various engine hardware components in combination with the electronic controller.

It will be appreciated that the configurations and routines disclosed herein are exemplary in nature, and that these specific embodiments are not to be considered in a limiting sense, because numerous variations are possible. For example, the above technology can be applied to V-6, I-4, I-6, V-12, opposed 4, and other engine types. The subject matter of the present disclosure includes all novel and non-obvious combinations and sub-combinations of the various systems and configurations, and other features, functions, and/or properties disclosed herein.

The following claims particularly point out certain combinations and sub-combinations regarded as novel and non-obvious. These claims may refer to "an" element or "a first" element or the equivalent thereof. Such claims should be understood to include incorporation of one or more such elements, neither requiring nor excluding two or more such elements. Other combinations and sub-combinations of the disclosed features, functions, elements, and/or properties may be claimed through amendment of the present claims or through presentation of new claims in this or a related application. Such claims, whether broader, narrower, equal, or different in scope to the original claims, also are regarded as included within the subject matter of the present disclosure.

The invention claimed is:

1. A method for an adjustable engine-exhaust valve, comprising:

via a controller including executable instructions stored in non-transitory memory, monitoring engine off time and checking for one or more entry conditions at engine startup, operating with the adjustable engine-exhaust valve being stuck, and responsive to the adjustable engine-exhaust valve being stuck: during selected engine start-up conditions and after sufficient engine-off time, setting an error code associated with the one or more entry conditions upon an exhaust temperature sensed via a temperature sensor reaching an exhaust temperature threshold, commanding the adjustable engine-exhaust valve to a first commanded valve position, and based upon a current valve position of the adjustable engine-exhaust valve being within a tolerance band of a first commanded valve position, clearing the error code.

2. The method of claim 1, wherein the one or more entry conditions comprises any of

an actuator of the adjustable exhaust valve reporting a stuck status;
a humidity sensor reading a water concentration higher than a threshold water concentration at the most recent engine-off time;
a vehicle soak time being greater than a calculated amount of time for ice formation while engine is off;
a current ambient temperature being either greater than or less than a threshold temperature;
and an exhaust volume level failing to fall between a first volume threshold and a second volume threshold.

3. The method of claim 2, further comprising calculating the calculated amount of time for ice formation based upon a difference in temperature of exhaust at an engine-off event and at the next engine-on event.

4. The method of claim 2, further comprising measuring the exhaust volume level via a microphone attached to a bottom surface of the vehicle.

5. The method of claim 1, wherein the exhaust temperature is measured by temperature sensors within the walls of the adjustable exhaust valve.

6. The method of claim 1, wherein the current valve position of the adjustable exhaust valve is not within the tolerance band of the first commanded valve position then adding a valve command counter.

7. The method of claim 6, further comprising after adding the valve command counter then again commanding the adjustable exhaust valve to the first commanded valve position.

8. The method of claim 6, further comprising upon reaching a command counter threshold latching a valve error code.

9. The method of claim 6, further comprising alerting a vehicle operator within the cabin of the vehicle to the valve error code via a volume and/or visual alert.

10. A method for troubleshooting an adjustable exhaust valve of an engine, comprising:

via a controller including executable instructions stored in non-transitory memory, monitoring engine off time and checking for one or more entry conditions at engine startup, executing a stuck valve check, operating with exhaust temperature rising up to and above an exhaust temperature threshold; setting a stuck valve error code associated with the one or more entry conditions upon the exhaust temperature sensed via a temperature sensor reaching the exhaust temperature threshold, running a valve self-healing routine, checking a first time for a stuck valve code of the adjustable exhaust valve, and based upon failing to receive the stuck valve code, clearing the error code.

11. The method of claim 10, wherein the valve self-healing routine comprises toggling the adjustable exhaust valve between open and closed states a programmable number of times.

12. The method of claim 10, further comprising issuing the stuck valve code at an actuator of the adjustable exhaust valve when the actuator cannot move.

13. The method of claim 10, further comprising based upon receiving the stuck valve code, counting a first self-healing counter.

14. The method of claim 13, further comprising running the self-healing routine again and checking an additional time for the stuck valve code.

15. A device for adjusting and diagnosing a valve position of a post-catalyst variable exhaust tuning system to control an exhaust backpressure, comprising:

a resonator fluidically connected to a muffler having a first and a second muffler exhaust port, an adjustable exhaust valve included within the first muffler exhaust port adjusted via a valve actuator communicatively coupled to a controller, a positioning sensor included within the adjustable exhaust valve, the controller including executable instructions stored in non-transitory memory that cause the controller to: check for one or more entry conditions at engine startup, operate an engine with the adjustable exhaust valve being stuck, and responsive to the adjustable exhaust valve being stuck:

during selected engine start-up conditions and after sufficient engine-off time, set an error code associated with the one or more entry conditions upon an exhaust temperature reaching an exhaust temperature threshold,

command the adjustable exhaust valve to a first commanded valve position, and

based upon a current valve position of the adjustable exhaust valve being within a tolerance band of a first commanded valve position, clear the error code. 5

16. The device of claim 15, wherein the adjustable exhaust valve is a butterfly valve.

17. The device of claim 15, further comprising a humidity sensor to estimate an engine off estimation of a mass of water remaining in the device. 10

18. The device of claim 15, further comprising a rotational rod connected to both the adjustable exhaust valve and the valve actuator for rotating the adjustable exhaust valve.

19. The device of claim 15, further comprising a microphone attached to a bottom surface of the vehicle for obtaining volume input of the variable exhaust tuning system. 15

20. The device of claim 15, further comprising a pressure and temperature sensor included within the muffler for tracking both temperature and pressure of exhaust gases of the variable exhaust tuning system. 20

* * * * *