



US010846465B2

(12) **United States Patent**  
**Peacock et al.**

(10) **Patent No.: US 10,846,465 B2**  
(45) **Date of Patent: Nov. 24, 2020**

(54)	<b>INTEGRATING AN APPLICATION FOR SURFACING DATA ON AN EMAIL MESSAGE PANE</b>	9,009,152 B2	4/2015	Lai et al.
		9,043,403 B2	5/2015	Schnitman et al.
		9,070,117 B2	6/2015	Rideout et al.
		9,104,294 B2	8/2015	Forstall et al.
(71)	Applicant: <b>Microsoft Technology Licensing, LLC</b> , Redmond, WA (US)	2008/0083003 A1	4/2008	Biniak et al.
		2008/0162439 A1	7/2008	Bosarge et al.
		2008/0189622 A1*	8/2008	Sanchez ..... G06Q 10/06 715/752
(72)	Inventors: <b>Andrew James Peacock</b> , Seattle, WA (US); <b>Shahil Soni</b> , Seattle, WA (US)	2009/0024944 A1	1/2009	Louch et al.
		2010/0153219 A1	6/2010	Mei et al.
		2011/0191316 A1*	8/2011	Lai ..... G06F 7/10 707/706
(73)	Assignee: <b>Microsoft Technology Licensing, LLC</b> , Redmond, WA (US)	2011/0252103 A1*	10/2011	Beyer ..... G06Q 10/107 709/206
(*)	Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 278 days.	2012/0010995 A1*	1/2012	Skirpa ..... G06F 3/0481 705/14.49

(Continued)

(21) Appl. No.: **15/198,362**

(22) Filed: **Jun. 30, 2016**

(65) **Prior Publication Data**

US 2018/0004373 A1 Jan. 4, 2018

(51) **Int. Cl.**

**G06F 3/00** (2006.01)

**G06F 40/166** (2020.01)

**H04L 12/58** (2006.01)

**G06F 40/30** (2020.01)

(52) **U.S. Cl.**

CPC ..... **G06F 40/166** (2020.01); **G06F 40/30**  
(2020.01); **H04L 51/22** (2013.01)

(58) **Field of Classification Search**

CPC .... G06F 3/0484; G06F 3/0481; G06F 3/0482;  
G06F 17/24; H04L 51/22

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

8,321,801 B2 11/2012 Chaudhri et al.  
8,875,029 B1\* 10/2014 Naidu ..... G06Q 10/10  
715/752

**OTHER PUBLICATIONS**

Justin, "Interactive Shopping Widget for Email", Published on: Feb. 11, 2015, Available at: <http://freshinbox.com/blog/shopping-in-email-add-to-cart/>.

(Continued)


*Primary Examiner* — Anil N Kumar

(74) *Attorney, Agent, or Firm* — Christopher J. Volkman; Kelly, Holt & Christenson, PLLC

(57) **ABSTRACT**

An electronic mail (email) system generates an email user interface display for composing an email message. A context-sensitive widget display is surfaced, on the user interface display, in-line with other message content. A widget that generates the widget display interacts with a remote data service to surface data from the remote data service, on the widget display.

**20 Claims, 13 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS

2012/0185781 A1\* 7/2012 Guzman ..... G06Q 10/107  
715/752  
2013/0097526 A1\* 4/2013 Stovicek ..... G06Q 10/107  
715/752  
2014/0245175 A1\* 8/2014 Rydenhag ..... H04L 51/08  
715/752  
2015/0019665 A1 1/2015 Linner et al.  
2015/0100648 A1 4/2015 Shmarovez et al.  
2015/0244655 A1\* 8/2015 Vohra ..... H04L 51/18  
715/752  
2016/0026439 A1 1/2016 Zaydman et al.

OTHER PUBLICATIONS

Robbins, Mark, "Punched card coding: the secret of interactive email", Published on: Oct. 19, 2015, Available at: <http://www.webdesignerdepot.com/2015/10/punched-card-coding-the-secret-of-interactive-email/>.

Justin, "Burberry's Interactive Scarf Personalizer Email", Published on: Dec. 10, 2015, Available at: <http://freshinbox.com/blog/burberrys-interactive-scarf-personalizer/>.

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B










FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9

1

## INTEGRATING AN APPLICATION FOR SURFACING DATA ON AN EMAIL MESSAGE PANE

### BACKGROUND

Computing systems are currently in wide use. Some such computing systems include electronic mail systems. Others include systems that interact with remote data services, or data sources, to continuously or repeatedly return data.

Computing systems often run different types of applications. One such application is a relatively small application that can be installed into a web page or a service page. This type of application often interacts with a remote service or data source in order to obtain and display data from the remote source. For example, a weather application may repeatedly surface and update weather forecast data on a web page or service page. This type of application is often referred to as a widget. It automatically obtains the data from the remote source and surfaces it in a display. The widget may have relatively limited functionality compared to other applications, and can be installed and executed within a webpage by an end user. A widget is often a transient or auxiliary application, meaning that it only occupies part of a web page and generates a display based on information fetched from other web sites or data sources, and displays that data in place, on the portion of the web page that is occupied by the widget display.

Users of such systems often communicate using electronic mail systems and attempt to incorporate data that is returned using the widget that interacts with the remote data service. This often requires a user who is composing an electronic mail (email) message to navigate away from the email user interface display to a user interface for the widget. The user then interacts with the widget to obtain data from the remote service, and then attempts to incorporate that data into the message content in the email message being composed.

By way of example, assume that a first user is generating an email message to a second user, and attempting to set up a travel itinerary. It may be that the first user uses an application (or widget) that accesses data from a weather service in order to obtain weather forecast data for a desired location. The first user may then review the weather forecast data and attempt to incorporate it, by typing a representation of it, into a message body in the email message and sending the message to the second user. Later, if the weather forecast data changes, it is not uncommon for the first user to generate yet another email message to the second user, including information about the updated weather forecast.

This is just one example of how a user may use an email system and an application that accesses a remote data service or data source. There are a wide variety of other scenarios and examples where users use such systems and applications.

The discussion above is merely provided for general background information and is not intended to be used as an aid in determining the scope of the claimed subject matter.

### SUMMARY

An electronic mail (email) system generates an email user interface display for composing an email message. A context-sensitive widget display is surfaced, on the user interface display, in-line with other message content. A widget

2

that generates the widget display interacts with a remote data service to surface data from the remote data service, on the widget display.

This Summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used as an aid in determining the scope of the claimed subject matter. The claimed subject matter is not limited to implementations that solve any or all disadvantages noted in the background.

### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of one example of a computing system architecture.

FIG. 2 is a block diagram of one example of a widget integration system, in more detail.

FIGS. 3A and 3B (collectively referred to herein as FIG. 3) show a flow diagram illustrating one example of the operation of the architecture shown in FIG. 1, and the widget integration system shown in FIG. 2, in integrating a widget into an email message.

FIGS. 4A-4D show examples of user interface displays.

FIG. 5 is a block diagram showing one example of the architecture illustrated in FIG. 1, deployed in a cloud computing architecture.

FIGS. 6-8 show examples of mobile devices that can be used in the architectures shown in the previous Figures.

FIG. 9 is a block diagram of one example of a computing environment that can be used in the architecture, shown in the previous Figures.

### DETAILED DESCRIPTION

FIG. 1 is a block diagram of one example of a computing system architecture 100. Architecture 100 is shown with computing systems 102 and 104 in communication with one another over network 106. Architecture 100 also shows that, in one example, computing systems 102 and 104 can communicate with a plurality of different remote data services or data sources 108-110. It will be noted that, while FIG. 1 only shows two computing systems 102 and 104 and two remote data services or data sources 108-110 in communication with one another, there can be additional computing systems and data services or sources as well. Those shown in FIG. 1 are shown for the sake of example only.

Computing system 102 illustratively generates user interfaces 112 with user input mechanisms 114 for interaction by user 116. User 116 illustratively interacts with user input mechanisms 114 in order to control and manipulate computing system 102. Similarly, computing system 104 is shown generating user interfaces 118 with user input mechanisms 120 for interaction by user 122. User 122 illustratively interacts with user input mechanisms 120 in order to control and manipulate computing 104.

Network 106 can be any of a wide variety of different kinds of networks. It can be a wide area network, a local area network, a cellular network, a near field communication network, or another network or a combination of networks.

Computing systems 102 and 104 illustratively run applications. Some applications may communicate over network 106 with data services or sources 108-110 in order to repeatedly obtain data from them, and update displayed data. The data may be live data or streaming data that is constantly



received by, and presented to, an end user while the data is being delivered by the remote data service or data source **108-110**.

Computing system **102** illustratively includes one or more processors or servers **124**, electronic mail (email) system **126**, widget servicing system **128**, user interface logic **130**, data store **132**, and it can include other items **134**. Electronic mail system **126**, itself, illustratively includes widget integration system **136** and it can include a wide variety of other email functionality **138**. Widget servicing system **128**, itself, illustratively includes service interaction logic **140** and it can include other items **142**. It will also be noted that computing systems **102** and **104** can be similar systems. However, they can be different as well. For purposes of the present description, it will be assumed that they are similar systems, and the description will proceed under that assumption. That is made for the sake of example only and the two systems can be different as well.

Before describing the overall operation of architecture **100** in more detail, a brief overview of some of the items in architecture **100**, and their operation, will first be provided. User interface logic **130** in computing system **102** illustratively receives inputs from other items in computing system **102** and generates user interfaces **112** and also detects user inputs through mechanisms **114**. Email system **126** illustratively allows user **116** to compose, send and receive electronic mail messages and attachments and perform other email functions, such as arrange folders, add and delete contacts or recipients, etc. Widget servicing system **128** is illustratively used by widgets that may be running in electronic mail system **126**, to repeatedly obtain data from data services or sources **108-110**, for display within email interfaces in email system **126**. Thus, widget integration system **136** in email system **126** may integrate a widget (by installing it into an email message display), and run it, in the display in electronic mail system **126**. The widget display is illustratively auxiliary to the email display that it is installed into and thus only displays its data on the portion of the email message display that it occupies, which may be relatively small and is less than the entire email message display. When that widget needs data, it may use service interaction logic **140** in widget servicing system **128** in order to automatically call or otherwise access one or more of the remote data services or sources **108-110** to obtain that data. By automatically it is meant that it does this without user input, except perhaps to authorize or initiate running the widget.

FIG. **2** is one example of a more detailed block diagram of widget integration system **136**. In the example shown in FIG. **2**, widget integration system **136** illustratively includes functionality activation detector logic **150**, widget identification logic **152**, application installation logic **154**, widget component **156**, widget sizing/formatting logic **158**, widget interaction processing logic **160**, returned data representation generator logic **162**, recipient processing system **163**, and it can include other items **164**. Functionality activation detector logic **150**, itself, can include user actuation detector **166** and content analysis detector **168**. Again, before describing the operation of architecture **100** (shown in FIG. **1**) and the widget integration system **136** (shown in FIG. **2**) in more detail, a brief overview of some of the items in system **136**, and their operation, will first be provided.

Functionality activation detector logic **150** illustratively detects when the functionality of widget integration system **136** is activated. User actuation detector **166** detects user actuation of an actuator that explicitly activates the functionality of system **136**, and which may be displayed on an

email user interface display. Content analysis detector **168** illustratively detects activation of system **136** based on the context or content of a message being displayed or composed in email system **126**. For instance, detector **168** may include natural language understanding or natural language processing components (or have access to them) to detect when the content of an email message, or a conversation, indicates that the functionality of widget integration system **136** should be activated. These are examples only.

Widget identification logic **152** then identifies a particular widget that may be integrated into the email message, based upon the content of the email message being composed, or the conversation displayed, or other content or context information. Application installation logic **154** then installs the widget (which is an application) into a message display in the email system **126** so that it generates a widget display that surfaces data it retrieves, in-line with the message content of the email message being displayed. Widget component **156** illustratively runs the widget so that it continuously or repeatedly obtains data from the remote data source or data service **108-110** that it is configured to interact with. Returned data representation generator logic **162** illustratively generates a visual representation of that data and uses sizing/formatting logic **158** to size and format the representation, and to locate it on the email user interface display, in-line with other message content.

Some widgets also surface one or more user input mechanisms with which a user can interact. In those scenarios, widget interaction processing logic **160** illustratively detects user interaction with those mechanisms on the widget and either controls email system **126** to perform an action based on the detected interaction, or passes the detected interaction along to other items in computing system **102** so that they can take appropriate actions.

Recipient processing system **163** illustratively identifies when user **116** receives an email message with an integrated widget. It illustratively generates a user interface with user input mechanisms that allow the recipient to view the widget display generated by the widget. Once displayed, system **136** can process the widget as described above.

FIGS. **3A** and **3B** (collectively referred to herein as FIG. **3**) show a flow diagram illustrating one example of the operation of architecture **100** and widget integration system **136** in allowing user **116** to integrate a widget into an email message, in-line with other message content in the message. It is first assumed that user **116** has email system **126** open and running on computing system **102**. This is indicated by block **180** in the flow diagram of FIG. **3**. In one example, user **116** also has the compose pane open on the email user interface, so that the user can author or otherwise compose an email message by entering message content onto the compose pane. This can be done using a keyboard, a keypad, a virtual keyboard, etc. Having the compose pane open on the email user interface display is indicated by block **182** in FIG. **3**. The email system can be open and generating a display in other ways as well, and this is indicated by block **184**.

Functionality activation detector logic **150** then detects that the functionality of widget integration system **136** should be activated. This is indicated by block **186**. In one example, the user interface display has a widget insertion actuator that can be actuated by user **116** in order to activate system **136**. Detecting user actuation of the widget insertion actuator is indicated by block **188**. In another example, content analysis detector **168** illustratively analyzes the context or content of the message being composed or being displayed and determines that widget integration system **136**

## 5

should be activated based upon that context or content. For instance, detector **168** may identify other applications that user **116** has open in computer system **102**. It may identify the history of inputs or operations performed by user **116** on computing system **102** (such as searching for a destination, looking at a weather site, etc.), or it may identify other context information and determine that the user may wish to insert a widget into the email message. In another example, detector **168** illustratively has natural language understanding or natural language processing components (or has access to them) and generates a linguistic or semantic understanding of the content in the email message, or conversation, being displayed. The content may indicate that the user wishes to have a widget inserted into the email message.

For instance, if the displayed message includes a text string such as "We should find a day when the weather is nice to go to the beach." This may be detected by content analysis detector **168** as a text string that indicates that user **116** may wish to insert a weather service widget that interacts with a weather service to show weather forecast data for one or more different locations, and/or a mapping widget that interacts with a map service to show directions and other location information, into the email message being displayed in email system **126**. Thus, this may serve to actuate the functionality of widget integration system **136**.

Automatic detection and activation of the functionality of system **136** is indicated by block **190** in FIG. **3**. The functionality may be activated in other ways as well, and this is indicated by block **192**.

Once the functionality is activated, widget identification logic **152** illustratively identifies a particular widget that is to be inserted in the email message. Again, this can be done based on the subject matter content of the email message being composed or the conversation being displayed, or in other ways. If widget identification logic **152** is unable to identify a particular widget, or if identification is ambiguous relative to a number of different widgets, it may surface a user interface display that allows the user to select or otherwise identify a particular widget (or set of widgets) for insertion. Identifying a widget for installation in electronic mail system **126** is indicated by block **194** in the flow diagram of FIG. **3**.

Application installation logic **154** then installs the identified widget in the email system **126** onto the open pane. This is indicated by block **196**. For instance, if user **116** has the compose pane in email system **126** open, so that the user can compose an email (or reply to an email), then the identified widget is installed by logic **154** on that particular message display that represents the message being composed.

Once installed, widget component **156** runs or activates the widget, as indicated by block **198**. Thus, the widget can interact with the remote service itself, or it can use service interaction logic **140** (shown in FIG. **1**) to make a call to a remote data service or data source **108-110** to obtain data. This is indicated by block **200**. Component **156** can run or activate the widget in other ways as well, and this indicated by block **202**.

Once the data is retrieved, returned data representation generator logic **162** illustratively generates a widget display representing the returned data. In cases where the widget also has user interactive functionality, logic **162** may also generate a display of user input mechanisms that the user can interact with, on the widget display. Generating a widget display representing the returned data and possibly any interaction mechanisms is indicated by block **204**.

## 6

Sizing/formatting logic **158** then sizes and formats the widget display and locates it on the pane with the email message and displays it at that location. This is indicated by block **206**. Sizing/formatting logic **158** illustratively displays the widget display in-line with other message content. This is indicated by block **208**. As mentioned above, it can format it as desired, and as indicated by block **210**. It can size it and locate it at a desired place as indicated by blocks **212** and **214**. For instance, it may locate the widget at the top of the message being authored, at the bottom of the message being authored, at a position of the user's cursor, or elsewhere. In one example, the widget is a transient or auxiliary application so it only shows up and displays its data where it is located, and it may be smaller than the display into which it is inserted. It can display the widget display on the open pane in other ways as well, and this is indicated by block **216**.

Widget interaction processing logic **160** then detects any user interactions with the widget display and controls the email system to perform actions based on any detected user interactions. This is indicated by blocks **218** and **220** in FIG. **3**. For instance, where the widget is a weather service widget that displays weather forecast data, the user may interact with user input mechanisms on the widget display that allow the user to change the location for the weather forecast data, the date or time for the weather forecast data, etc. Where the widget is an airline data widget that shows flight status information, the user input mechanisms may allow the user to change the flight number of the desired information, to book a ticket or reservation on a particular airline, etc. All of these and a wide variety of other widgets and interactions are contemplated herein.

Widget component **156**, in running the widget, illustratively determines whether it is time to update the data displayed in the widget display. This will be determined by the application code for the widget and is indicated by block **222** in the flow diagram of FIG. **3**. If so, processing returns to block **198** where the widget can call the remote service, itself, or use service interaction logic **140** to call the appropriate remote data service or data source to obtain the new data.

In one example, the widget display can also be dismissed by user **116**. For instance, it may include an actuator that can be actuated by the user to close or otherwise dismiss the widget from the email user interface display. In another example, when the user closes the email message that the widget is installed in, then this also dismisses or closes the widget. The widget can be dismissed or closed in a wide variety of other ways as well. This is indicated by block **224**. If it is not closed or dismissed, processing reverts to block **218** where the system detects any user interactions with the widget, controls the email system to perform appropriate actions, and then determines whether it is time to again update the data displayed in the widget display.

FIGS. **4A-4D** are examples of a number of different user interface displays. They will be discussed in conjunction with FIGS. **1-3**.

FIG. **4A** shows one example of a user interface display **258** that can be generated using email system **126**. It can be seen that user interface display **258** includes a mailboxes pane **260** that displays the various mailboxes in the user's email system. It includes a message list pane **262** that includes a list of messages, and it also includes a compose pane **264** in which user **116** can compose message content **270** in an email message. Compose actuators (such as a keyboard, dictation components, a keypad, etc.) can be used to input content **270** into the email message.

User interface display **258** also illustratively includes a widget insertion actuator **272**. When user **116** actuates the widget insertion actuator **272**, then user actuation detector **166** (in FIG. 2) activates the functionality of widget integration system **136**. In one example, actuator **272** is always displayed when the compose pane **264** (or when another message viewing pane) is displayed in email system **126**. In another example, actuator **272** is only displayed in certain contexts, when message content **270** contains certain content items, or in other circumstances.

It will also be noted that the functionality of widget integration system **136** can be activated in other ways as well. For instance, when content analysis detector **168** (shown in FIG. 2) detects certain items in message content **270**, this may activate system **136** as well.

Once the functionality of widget integration system **136** is activated, widget identification logic **152** either automatically, or with the assistance of a user selection or guidance input, identifies the particular widget (or widgets) that the user wishes to insert into compose pane **264**. In doing so, it may search a widget store that stores a list of indexed widget identifiers that identify various widgets. The index may index the widgets based on subject matter or other indexing criteria. The identifier may identify the widget and where it can be obtained or downloaded. The widget store (not shown) may be local to computing system **102** or remote, but accessible. The widget can be identified in other ways as well. Application installation logic **154** then obtains and installs the widget, and widget component **156** runs it. The running widget obtains data from the remote data service or data source **108-110** and returned data representation generator logic **162** illustratively generates a widget display displaying the returned data. Sizing/formatting logic **158** sizes it, formats it, and locates it on the compose pane, in-line with the other message content **270**. FIG. 4B shows one example of this.

It can be seen in FIG. 4B that the compose pane **264** now includes widget display **274**. Display **274** is at the top of message content **270**, but displayed in-line with that message content. This is only one example. Display **274** may be located at the position of the user's cursor in message content **270**, at the bottom of the compose pane **264**, or at another location.

In the example shown in FIG. 4B, widget display **274** includes a live data display portion **276** that displays the data retrieved from the remote data service or data source **108-110**. It can also include interaction mechanisms **278** that user **116** can interact with to perform functionality using the installed widget. It can include a dismiss actuator **280** that can be actuated by user **116** to dismiss the widget display **274**. It can also include other actuators **282** that can be actuated to perform other actions.

FIG. 4C shows another user interface display which is similar to that shown in FIG. 4B, and similar items are similarly numbered. However, FIG. 4C now shows that the user has used widget integration system **136** to include a second widget display **284** in message content **270**. The two widget displays **274** and **284** can be displayed at different positions in-line with message content **270**, or they can be displayed together. In the example shown in FIG. 4C, they are displayed at different locations, but both are still in-line with the message content **270** in compose pane **264**.

FIG. 4D shows one example of a user interface display **286**. Display **286** is similar, in some ways, to display **258** shown in FIG. 4C, and similar items are similarly numbered. However, in the example shown in FIG. 4D, user **116** is the recipient of an email message with two integrated widgets,

and display **286** shows a reading pane **288** in which the user is reading the email message with the integrated widgets. In the example shown in FIG. 4D, widgets **274** and **284** were inserted or integrated into an email message by another user (e.g., user **122**). The message was then sent to email system **126** of user **116**, and user **116** selected that message from the message list pane **262**, for display in reading pane **288**. In the example shown in FIG. 4D, the two widget displays **274** and **284** are displayed at the top of the email message, but still in-line with message content **270**. It will be noted, however, that they may be displayed in other ways as well, such as separated within message content **270**, at the bottom of message content **270**, or in other locations.

Also, where a widget is inserted in a message display, but it is off the display screen, it can be automatically repositioned so it can be seen. For instance, assume that a message has an inserted widget and a recipient replies to the message. When that happens, the widget in the original message may get pushed downwardly off the display screen. Therefore, in one example, logic **162** may automatically reposition the widget from its location in the original message to the top of the reply message, so that it is visible when viewing the reply message as well. In another example, all widgets from all messages in a conversation thread can be repositioned so they are visible regardless of which message in the thread is being viewed. This can be done by logic **162** opening a display area at the top of the message, but in-line with the message content, and having the widget installed by logic **154** in that display area and run there by component **156**. All of these examples are contemplated herein.

It can thus be seen that the present discussion greatly enhances the functionality of email system **126**, and thus computing system **102**. It reduces the processing and memory overhead needed for rendering, because the user need not navigate to a separate application in order to obtain data that the user will then type into, or copy and paste into, the email message. Thus, all of the user interface displays associated with searching for an application, obtaining data from a remote data service or data source, and then retrieving that data into the email message, are unneeded. Instead, the system automatically detects when a widget is to be inserted, and installs it in the display that is displaying the email message. This greatly enhances the user experience as well, as the user need not navigate to different sites to obtain desired data and attempt to incorporate that into the email message being composed.

It will be noted that the above discussion has described a variety of different systems, components and/or logic. It will be appreciated that such systems, components and/or logic can be comprised of hardware items (such as processors and associated memory, or other processing components, some of which are described below) that perform the functions associated with those systems, components and/or logic. In addition, the systems, components and/or logic can be comprised of software that is loaded into a memory and is subsequently executed by a processor or server, or other computing component, as described below. The systems, components and/or logic can also be comprised of different combinations of hardware, software, firmware, etc., some examples of which are described below. These are only some examples of different structures that can be used to form the systems, components and/or logic described above. Other structures can be used as well.

The present discussion has mentioned processors and servers. In one embodiment, the processors and servers include computer processors with associated memory and timing circuitry, not separately shown. They are functional

parts of the systems or devices to which they belong and are activated by, and facilitate the functionality of the other components or items in those systems.

Also, a number of user interface displays have been discussed. They can take a wide variety of different forms and can have a wide variety of different user actuable input mechanisms disposed thereon. For instance, the user actuable input mechanisms can be text boxes, check boxes, icons, links, drop-down menus, search boxes, etc. They can also be actuated in a wide variety of different ways. For instance, they can be actuated using a point and click device (such as a track ball or mouse). They can be actuated using hardware buttons, switches, a joystick or keyboard, thumb switches or thumb pads, etc. They can also be actuated using a virtual keyboard or other virtual actuators. In addition, where the screen on which they are displayed is a touch sensitive screen, they can be actuated using touch gestures. Also, where the device that displays them has speech recognition components, they can be actuated using speech commands.

A number of data stores have also been discussed. It will be noted they can each be broken into multiple data stores. All can be local to the systems accessing them, all can be remote, or some can be local while others are remote. All of these configurations are contemplated herein.

Also, the figures show a number of blocks with functionality ascribed to each block. It will be noted that fewer blocks can be used so the functionality is performed by fewer components. Also, more blocks can be used with the functionality distributed among more components.

FIG. 5 is a block diagram of architecture 100, shown in FIG. 1, except that its elements are disposed in a cloud computing architecture 500. Cloud computing provides computation, software, data access, and storage services that do not require end-user knowledge of the physical location or configuration of the system that delivers the services. In various embodiments, cloud computing delivers the services over a wide area network, such as the internet, using appropriate protocols. For instance, cloud computing providers deliver applications over a wide area network and they can be accessed through a web browser or any other computing component. Software or components of architecture 100 as well as the corresponding data, can be stored on servers at a remote location. The computing resources in a cloud computing environment can be consolidated at a remote data center location or they can be dispersed. Cloud computing infrastructures can deliver services through shared data centers, even though they appear as a single point of access for the user. Thus, the components and functions described herein can be provided from a service provider at a remote location using a cloud computing architecture. Alternatively, they can be provided from a conventional server, or they can be installed on client devices directly, or in other ways.

The description is intended to include both public cloud computing and private cloud computing. Cloud computing (both public and private) provides substantially seamless pooling of resources, as well as a reduced need to manage and configure underlying hardware infrastructure.

A public cloud is managed by a vendor and typically supports multiple consumers using the same infrastructure. Also, a public cloud, as opposed to a private cloud, can free up the end users from managing the hardware. A private cloud may be managed by the organization itself and the infrastructure is typically not shared with other organizations. The organization still maintains the hardware to some extent, such as installations and repairs, etc.

In the example shown in FIG. 5, some items are similar to those shown in FIG. 1 and they are similarly numbered. FIG. 5 specifically shows that some items in architecture 500 can be located in cloud 502 (which can be public, private, or a combination where portions are public while others are private). For instance, one or more of computing systems 102 and 104 can be in cloud 502 or outside cloud 502. They are shown in both places in FIG. 5 to indicate this. Therefore, users 116-122 use user devices 504-506 to access those systems either directly or through cloud 502.

FIG. 5 also depicts another example of a cloud architecture. FIG. 5 shows that it is also contemplated that some elements of architecture 100 can be disposed in cloud 502 while others are not. By way of example, data store 132 can be disposed outside of cloud 502, and accessed through cloud 502. In another example, data sources/services 108-110 can be outside of cloud 502. Different portions of computing system 102 and 104 can be distributed inside or outside of cloud 502. Regardless of where they are located, they can be accessed directly by devices 504 and 506, through a network (either a wide area network or a local area network), they can be hosted at a remote site by a service, or they can be provided as a service through a cloud or accessed by a connection service that resides in the cloud. All of these architectures are contemplated herein.

It will also be noted that architecture 100, or portions of it, can be disposed on a wide variety of different devices. Some of those devices include servers, desktop computers, laptop computers, tablet computers, or other mobile devices, such as palm top computers, cell phones, smart phones, multimedia players, personal digital assistants, etc.

FIG. 6 is a simplified block diagram of one illustrative example of a handheld or mobile computing device that can be used as a user's or client's hand held device 16, in which the present architecture (or parts of it) can be deployed or which can interact with the present architecture. FIGS. 7-8 are examples of handheld or mobile devices.

FIG. 6 provides a general block diagram of the components of a client device 16 that can run components of architecture 100 or that interacts with architecture 100, or both. In the device 16, a communications link 13 is provided that allows the handheld device to communicate with other computing devices and under some embodiments provides a channel for receiving information automatically, such as by scanning. Examples of communications link 13 include an infrared port, a serial/USB port, a cable network port such as an Ethernet port, and a wireless network port allowing communication through one or more communication protocols including General Packet Radio Service (GPRS), LTE, HSPA, HSPA+ and other 3G and 4G radio protocols, 1xrtt, and Short Message Service, which are wireless services used to provide cellular access to a network, as well as Wi-Fi protocols, and Bluetooth protocol, which provide local wireless connections to networks.

In other examples, applications or systems are received on a removable Secure Digital (SD) card that is connected to a SD card interface 15. SD card interface 15 and communication links 13 communicate with a processor 17 (which can also embody processors or servers 124 from FIG. 1) along a bus 19 that is also connected to memory 21 and input/output (I/O) components 23, as well as clock 25 and location system 27.

I/O components 23, in one embodiment, are provided to facilitate input and output operations. I/O components 23 for various embodiments of the device 16 can include input components such as buttons, touch sensors, multi-touch sensors, optical or video sensors, voice sensors, touch

## 11

screens, proximity sensors, microphones, tilt sensors, and gravity switches and output components such as a display device, a speaker, and or a printer port. Other I/O components **23** can be used as well.

Clock **25** illustratively comprises a real time clock component that outputs a time and date. It can also, illustratively, provide timing functions for processor **17**.

Location system **27** illustratively includes a component that outputs a current geographical location of device **16**. This can include, for instance, a global positioning system (GPS) receiver, a LORAN system, a dead reckoning system, a cellular triangulation system, or other positioning system. It can also include, for example, mapping software or navigation software that generates desired maps, navigation routes and other geographic functions.

Memory **21** stores operating system **29**, network settings **31**, applications **33**, application configuration settings **35**, data store **37**, communication drivers **39**, and communication configuration settings **41**. Memory **21** can include all types of tangible volatile and non-volatile computer-readable memory devices. It can also include computer storage media (described below). Memory **21** stores computer readable instructions that, when executed by processor **17**, cause the processor to perform computer-implemented steps or functions according to the instructions. Similarly, device **16** can have a client system **24** which can run various business applications or embody parts or all of architecture **100**. Processor **17** can be activated by other components to facilitate their functionality as well.

Examples of the network settings **31** include things such as proxy information, Internet connection information, and mappings. Application configuration settings **35** include settings that tailor the application for a specific enterprise or user. Communication configuration settings **41** provide parameters for communicating with other computers and include items such as GPRS parameters, SMS parameters, connection user names and passwords.

Applications **33** can be applications that have previously been stored on the device **16** or applications that are installed during use, although these can be part of operating system **29**, or hosted external to device **16**, as well.

FIG. **7** shows one example in which device **16** is a tablet computer **600**. In FIG. **7**, computer **600** is shown with user interface display screen **602**. Screen **602** can be a touch screen (so touch gestures from a user's finger can be used to interact with the application) or a pen-enabled interface that receives inputs from a pen or stylus. It can also use an on-screen virtual keyboard. Of course, it might also be attached to a keyboard or other user input device through a suitable attachment mechanism, such as a wireless link or USB port, for instance. Computer **600** can also illustratively receive voice inputs as well.

FIG. **8** shows that the device can be a smart phone **71**. Smart phone **71** has a touch sensitive display **73** that displays icons or tiles or other user input mechanisms **75**. Mechanisms **75** can be used by a user to run applications, make calls, perform data transfer operations, etc. In general, smart phone **71** is built on a mobile operating system and offers more advanced computing capability and connectivity than a feature phone.

Note that other forms of the devices **16** are possible.

FIG. **9** is one example of a computing environment in which architecture **100**, or parts of it, (for example) can be deployed. With reference to FIG. **9**, an example system for implementing some embodiments includes a general-purpose computing device in the form of a computer **810**. Components of computer **810** may include, but are not

## 12

limited to, a processing unit **820** (which can comprise processors or servers **124**), a system memory **830**, and a system bus **821** that couples various system components including the system memory to the processing unit **820**.

The system bus **821** may be any of several types of bus structures including a memory bus or memory controller, a peripheral bus, and a local bus using any of a variety of bus architectures. By way of example, and not limitation, such architectures include Industry Standard Architecture (ISA) bus, Micro Channel Architecture (MCA) bus, Enhanced ISA (EISA) bus, Video Electronics Standards Association (VESA) local bus, and Peripheral Component Interconnect (PCI) bus also known as Mezzanine bus. Memory and programs described with respect to FIGS. **1** and **2** can be deployed in corresponding portions of FIG. **9**.

Computer **810** typically includes a variety of computer readable media. Computer readable media can be any available media that can be accessed by computer **810** and includes both volatile and nonvolatile media, removable and non-removable media. By way of example, and not limitation, computer readable media may comprise computer storage media and communication media. Computer storage media is different from, and does not include, a modulated data signal or carrier wave. It includes hardware storage media including both volatile and nonvolatile, removable and non-removable media implemented in any method or technology for storage of information such as computer readable instructions, data structures, program modules or other data. Computer storage media includes, but is not limited to, RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, digital versatile disks (DVD) or other optical disk storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to store the desired information and which can be accessed by computer **810**. Communication media typically embodies computer readable instructions, data structures, program modules or other data in a transport mechanism and includes any information delivery media. The term "modulated data signal" means a signal that has one or more of its characteristics set or changed in such a manner as to encode information in the signal. By way of example, and not limitation, communication media includes wired media such as a wired network or direct-wired connection, and wireless media such as acoustic, RF, infrared and other wireless media. Combinations of any of the above should also be included within the scope of computer readable media.

The system memory **830** includes computer storage media in the form of volatile and/or nonvolatile memory such as read only memory (ROM) **831** and random access memory (RAM) **832**. A basic input/output system **833** (BIOS), containing the basic routines that help to transfer information between elements within computer **810**, such as during start-up, is typically stored in ROM **831**. RAM **832** typically contains data and/or program modules that are immediately accessible to and/or presently being operated on by processing unit **820**. By way of example, and not limitation, FIG. **9** illustrates operating system **834**, application programs **835**, other program modules **836**, and program data **837**.

The computer **810** may also include other removable/non-removable volatile/nonvolatile computer storage media. By way of example only, FIG. **9** illustrates a hard disk drive **841** that reads from or writes to non-removable, nonvolatile magnetic media and an optical disk drive **855** that reads from or writes to a removable, nonvolatile optical disk **856** such as a CD ROM or other optical media. Other removable/non-removable, volatile/nonvolatile computer storage media that

can be used in the exemplary operating environment include, but are not limited to, magnetic tape cassettes, flash memory cards, digital versatile disks, digital video tape, solid state RAM, solid state ROM, and the like. The hard disk drive **841** is typically connected to the system bus **821** through a non-removable memory interface such as interface **840**, and optical disk drive **855** are typically connected to the system bus **821** by a removable memory interface, such as interface **850**.

Alternatively, or in addition, the functionality described herein can be performed, at least in part, by one or more hardware logic components. For example, and without limitation, illustrative types of hardware logic components that can be used include Field-programmable Gate Arrays (FPGAs), Program-specific Integrated Circuits (ASICs), Program-specific Standard Products (ASSPs), System-on-a-chip systems (SOCs), Complex Programmable Logic Devices (CPLDs), etc.

The drives and their associated computer storage media discussed above and illustrated in FIG. 9, provide storage of computer readable instructions, data structures, program modules and other data for the computer **810**. In FIG. 9, for example, hard disk drive **841** is illustrated as storing operating system **844**, application programs **845**, other program modules **846**, and program data **847**. Note that these components can either be the same as or different from operating system **834**, application programs **835**, other program modules **836**, and program data **837**. Operating system **844**, application programs **845**, other program modules **846**, and program data **847** are given different numbers here to illustrate that, at a minimum, they are different copies.

A user may enter commands and information into the computer **810** through input devices such as a keyboard **862**, a microphone **863**, and a pointing device **861**, such as a mouse, trackball or touch pad. Other input devices (not shown) may include a joystick, game pad, satellite dish, scanner, or the like. These and other input devices are often connected to the processing unit **820** through a user input interface **860** that is coupled to the system bus, but may be connected by other interface and bus structures, such as a parallel port, game port or a universal serial bus (USB). A visual display **891** or other type of display device is also connected to the system bus **821** via an interface, such as a video interface **890**. In addition to the monitor, computers may also include other peripheral output devices such as speakers **897** and printer **896**, which may be connected through an output peripheral interface **895**.

The computer **810** is operated in a networked environment using logical connections to one or more remote computers, such as a remote computer **880**. The remote computer **880** may be a personal computer, a hand-held device, a server, a router, a network PC, a peer device or other common network node, and typically includes many or all of the elements described above relative to the computer **810**. The logical connections depicted in FIG. 9 include a local area network (LAN) **871** and a wide area network (WAN) **873**, but may also include other networks. Such networking environments are commonplace in offices, enterprise-wide computer networks, intranets and the Internet.

When used in a LAN networking environment, the computer **810** is connected to the LAN **871** through a network interface or adapter **870**. When used in a WAN networking environment, the computer **810** typically includes a modem **872** or other means for establishing communications over the WAN **873**, such as the Internet. The modem **872**, which may be internal or external, may be connected to the system bus **821** via the user input interface **860**, or other appropriate

mechanism. In a networked environment, program modules depicted relative to the computer **810**, or portions thereof, may be stored in the remote memory storage device. By way of example, and not limitation, FIG. 9 illustrates remote application programs **885** as residing on remote computer **880**. It will be appreciated that the network connections shown are exemplary and other means of establishing a communications link between the computers may be used.

It should also be noted that the different embodiments described herein can be combined in different ways. That is, parts of one or more embodiments can be combined with parts of one or more other embodiments. All of this is contemplated herein.

Example 1 is a computing system, comprising:

- an electronic mail (email) system that displays an email user interface display with a display pane displaying message content of an email message;

- a widget component that runs a widget to repeatedly obtain data from a remote data service; and

- returned data representation generator logic that generates a representation of the obtained data in a widget display and displays the widget display in line with the message content in the display pane.

Example 2 is the computing system of any or all previous examples wherein the widget display includes a user interaction mechanism, and further comprising:

- widget interaction processing logic configured to detect actuation of the user interaction mechanism and control the computing system to perform an action based on the detected actuation.

FIG. 3 is the computing system of any or all previous examples and further comprising:

- a content analysis detector that identifies a subject matter content of the message content.

Example 4 is the computing system of any or all previous examples and further comprising:

- widget identification logic that identifies the widget based on the identified subject matter content.

Example 5 is the computing system of any or all previous examples and further comprising:

- application installation logic that installs the identified widget in the email message in the email system.

Example 6 is the computing system of any or all previous examples wherein the email message is part of a conversation comprising a plurality of email messages and wherein the content analysis detector is configured to identify a subject matter content of the conversation.

Example 7 is the computing system of any or all previous examples and further comprising:

- a recipient processing system that receives a received email message with a different widget integrated into the received email message, the widget component running the different widget when the received email message is displayed by the email system.

Example 8 is the computing system of any or all previous examples and further comprising:

- widget integration detector logic that detects a widget insertion input to insert the widget into the email message.

Example 9 is the computing system of any or all previous examples wherein the email system is configured to display on the display pane a widget insertion actuator and wherein the widget integration detector comprises:

- a user actuation detector configured to detect actuation of the widget insertion actuator.

Example 10 is a computer implemented method, comprising:

## 15

displaying an email user interface display, in an email system, with a display pane displaying message content of an email message;

running an application to repeatedly obtain data from a remote data service;

generating a representation of the obtained data in a first display; and

displaying the first display in line with the message content on the display pane.

Example 11 is the computer implemented method of any or all previous examples wherein displaying the first display includes displaying a user interaction mechanism, and further comprising:

detecting actuation of the user interaction mechanism; and

controlling a computing system to perform an action based on the detected actuation.

Example 12 is the computer implemented method of any or all previous examples and further comprising:

identifying a subject matter content of at least a portion of the message content; and

identifying the application based on the identified subject matter content.

Example 13 is the computer implemented method of any or all previous examples and further comprising:

installing the identified application to run to display the obtained information in the email message in the email system.

Example 14 is the computer implemented method of any or all previous examples wherein the email message is part of a conversation comprising a plurality of email messages and wherein identifying a subject matter content comprises:

identifying a subject matter content of the conversation.

Example 15 is the computer implemented method of any or all previous examples and further comprising:

before running the application, detecting an application insertion input to insert the application into the email message.

Example 16 is the computer implemented method of any or all previous examples wherein displaying the email system user interface display comprises displaying on the display pane an application insertion actuator and wherein detecting an application input comprises:

detecting actuation of the application insertion actuator.

Example 17 is the computer implemented method of any or all previous examples and further comprising:

receiving a received email message with a different application integrated into the received email message; and

running the different application when the received email message is displayed by the email system.

Example 18 is a computing system, comprising:

an electronic mail (email) system that displays an email user interface display with a display pane displaying message content of an email message;

an application component that runs an application to repeatedly obtain data from a remote data service;

returned data representation generator logic that generates a representation of the obtained data in a first display and displays the first display in line with the message content in the display pane; and

application interaction processing logic configured to detect actuation of a user interaction mechanism on the first display and control the computing system to perform an action based on the detected actuation.

Example 19 is the computing system of any or all previous examples and further comprising:

a content analysis detector that identifies a subject matter content of the message content; and

## 16

application identification logic that identifies the application based on the identified subject matter content.

Example 20 is the computing system of any or all previous examples and further comprising:

application installation logic that installs the identified application in the email message in the email system.

Although the subject matter has been described in language specific to structural features and/or methodological acts, it is to be understood that the subject matter defined in the appended claims is not necessarily limited to the specific features or acts described above. Rather, the specific features and acts described above are disclosed as example forms of implementing the claims.

What is claimed is:

1. A computing system, comprising:

at least one processor; and

memory storing instructions executable by the at least one processor, wherein the instructions, when executed, cause the computing system to:

display an email user interface display with a compose

pane content that includes a user input mechanism;

based on user input detected through the user input mechanism, compose message content in the compose

pane;

identify a subject matter content of the message content in the compose pane;

identify a widget based on the identified subject matter content;

display, on the email user interface display with the compose pane, a widget insertion actuator; and

based on a detected user actuation of the widget insertion actuator, insert the widget into the email message;

run the widget to repeatedly obtain data from a remote data service;

display a widget display, that represents the widget inserted into the email message, in line with the message content in the compose pane;

dynamically update the widget display, displayed in line with the message content in the compose pane, to represent the repeatedly obtained data; and

send the email message including, the message content and the inserted widget.

2. The computing system of claim 1 wherein the widget display includes a user interaction mechanism, and wherein the instructions, when executed, cause the computing system to:

detect actuation of the user interaction mechanism; and perform an action based on the detected actuation.

3. The computing system of claim 1 wherein the instructions, when executed, cause the computing system to:

display the widget insertion actuator in response to determining that the subject matter content of the message content activates widget insertion functionality.

4. The computing system of claim 1 wherein the instructions, when executed, cause the computing system to:

select the widget, from a plurality of widgets, based on the identified subject matter content.

5. The computing system of claim 1, wherein the instructions when executed, cause the computing system to:

install the identified widget in the email message.

6. The computing system of claim 1, wherein the instructions cause the computing system to:

position the wide display within the message content based on a display area of the compose pane.

7. The computing system of claim 1 wherein the widget comprises a first widget, and the instructions, when executed cause the computing system to:

17

receive a second email message with a second widget, that is different than the first widget, integrated into the second email message;

run the second widget when the second email message is displayed by the computing system;

generate a reply email message that is in reply to the second email message and includes the second widget; and

automatically reposition the second widget in the reply email message from a first position to a second position that is closer to a beginning of the reply email message than the first position.

**8.** A computer implemented method, comprising:

displaying an email user interface display, in an email system, with a compose pane displaying message content of an email message and including a user input mechanism configured to receive user input to compose the message content;

identifying a subject matter content of the message content displayed in the compose pane;

selecting a widget based on the identified subject matter content;

inserting the widget into the email message;

running the widget to repeatedly obtain data from a remote data service;

displaying a widget display, that represents the widget inserted into the email message, in line with the message content on the compose pane

dynamically updating the widget display, displayed in line with the message content in the compose pane, to represent the repeatedly obtained data; and

sending the email message including the message content and the inserted widget.

**9.** The computer implemented method of claim **8**, and further comprising:

displaying, on the email user interface display, an indication of the selected widget along with a widget insertion actuator; and

based on a detected user actuation of the widget insertion actuator, inserting the selected widget into the email message.

**10.** The computer implemented method of claim **9**, wherein the widget insertion actuator is displayed on the compose pane.

**11.** The computer implemented method of claim **8** and further comprising:

installing the widget in the email message in the email system.

**12.** The computer implemented method of claim **11** wherein the email message is part of a conversation comprising a plurality of email messages and wherein identifying a subject matter content comprises:

identifying a subject matter content of the conversation.

**13.** The computer implemented method of claim **8** and further comprising:

before running the widget, detecting a widget insertion input to insert the widget into the email message.

18

**14.** The computer implemented method of claim **13** and further comprising displaying, on the compose pane, a widget insertion actuator and wherein detecting the widget insertion input comprises:

detecting actuation of the widget insertion actuator.

**15.** The computer implemented method of claim **8**, wherein displaying the first display includes displaying a user interaction mechanism, and further comprising:

detecting actuation of the user interaction mechanism; and

controlling a computing system to perform an action based on the detected actuation.

**16.** A computing system, comprising:

at least one processor; and

memory storing instructions executable by the at least one processor, wherein the instructions, when executed, cause the computing system to:

receive an email message including a widget;

display an email user interface display with a display pane displaying message content of the received email message;

run the widget to repeatedly obtain data from a remote data service;

display a widget display, that represents the widget in the email message, line with the message content in the display pane,

dynamically update the widget display, displayed in line the message content in the display pane, to represent the repeatedly obtained data;

generate a reply email message that is in reply to the received email message and includes the widget;

automatically reposition the widget in the reply email message from a first position to a second position, and

send the reply email message that includes:

the message content, and

a set of data represented in the repositioned widget display.

**17.** The computing system of claim **16** wherein the instructions cause the computing system to:

identify a subject matter content of the message content; and

select the widget based on the identified subject matter content.

**18.** The computing system of claim **16**, wherein the second position is closer to a beginning of the reply email message compared to the first position.

**19.** The computing system of claim **16**, wherein the received email message includes a plurality of widgets, and the instructions cause the computing system to:

automatically reposition the plurality of widgets in the reply email message.

**20.** The computer implemented method of claim **8**, and further comprising positioning the widget display within the message content based on a display area of the compose pane.

\* \* \* \* \*