



US010854389B2

(12) **United States Patent**
Cho et al.

(10) **Patent No.:** **US 10,854,389 B2**
(45) **Date of Patent:** ***Dec. 1, 2020**

(54) **ELECTRONIC COMPONENT**

(71) Applicant: **SAMSUNG**
ELECTRO-MECHANICS CO., LTD.,
Suwon-si (KR)

(72) Inventors: **Beom Joon Cho**, Suwon-si (KR); **Woo Chul Shin**, Suwon-si (KR); **Ki Young Kim**, Suwon-si (KR); **Sang Soo Park**, Suwon-si (KR)

(73) Assignee: **SAMSUNG**
ELECTRO-MECHANICS CO., LTD.,
Suwon-si (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **16/821,042**

(22) Filed: **Mar. 17, 2020**

(65) **Prior Publication Data**

US 2020/0219654 A1 Jul. 9, 2020

Related U.S. Application Data

(63) Continuation of application No. 16/279,101, filed on Feb. 19, 2019, now Pat. No. 10,636,571, which is a
(Continued)

(30) **Foreign Application Priority Data**

Aug. 29, 2018 (KR) 10-2018-0101969

(51) **Int. Cl.**
H01G 4/232 (2006.01)
H01G 4/38 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **H01G 4/232** (2013.01); **H01G 2/06** (2013.01); **H01G 4/38** (2013.01); **H01G 4/12** (2013.01); **H01G 4/30** (2013.01)

(58) **Field of Classification Search**
CPC H01G 2/06; H01G 4/38; H01G 4/232; H01G 4/242
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,191,933 B1 * 2/2001 Ishigaki H01G 4/232
361/309
6,512,632 B2 1/2003 Yamamoto
(Continued)

FOREIGN PATENT DOCUMENTS

JP H07-249541 A 9/1995
JP 2004-273935 A 9/2004

OTHER PUBLICATIONS

U.S. Notice of Allowance dated Feb. 19, 2019 issued in U.S. Appl. No. 16/279,101.

(Continued)

Primary Examiner — Eric W Thomas


(74) *Attorney, Agent, or Firm* — Morgan, Lewis & Bockius LLP

(57) **ABSTRACT**

An electronic component includes a capacitor array including a plurality of multilayer capacitors; and first and second metal frames disposed on a side surface and another side surface of the capacitor array and electrically connected to first and second external electrodes, respectively, wherein the first metal frame includes a first support portion; a first mounting portion; and a first connection portion, the second metal frame includes a second support portion; a second mounting portion; and a second connection portion, and lengths of the first and second mounting portions in the first

(Continued)

100



direction are smaller than a length of the capacitor array in the first direction.

11 Claims, 11 Drawing Sheets

Related U.S. Application Data

continuation of application No. 16/170,645, filed on Oct. 25, 2018, now Pat. No. 10,636,570.

- (51) **Int. Cl.**
H01G 2/06 (2006.01)
H01G 4/30 (2006.01)
H01G 4/12 (2006.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

9,911,535 B2 3/2018 Mori et al.
2002/0048142 A1 4/2002 Moriwaki et al.
2005/0041367 A1 2/2005 Yoshii et al.
2015/0131202 A1 5/2015 Masuda et al.

OTHER PUBLICATIONS

U.S. Final Office Action dated Sep. 30, 2019 issued in U.S. Appl. No. 16/279,101.

U.S. Non-Final Office Action dated Apr. 15, 2019 issued in U.S. Appl. No. 16/279,101.

* cited by examiner




FIG. 1




FIG. 2A




FIG. 2B




FIG. 3




FIG. 4




FIG. 5




FIG. 6






FIG. 7



PRIOR ART
FIG. 8A



PRIOR ART
FIG. 8B




FIG. 9A




FIG. 9B




FIG. 10A




FIG. 10B




FIG. 11




FIG. 12

1

ELECTRONIC COMPONENT**CROSS-REFERENCE TO RELATED APPLICATION(S)**

This application is a continuation of U.S. patent application Ser. No. 16/279,101, filed on Feb. 19, 2019, which is a continuation of U.S. patent application Ser. No. 16/170,645, filed on Oct. 25, 2018, which claims the benefit of priority to Korean Patent Application No. 10-2018-0101969 filed on Aug. 29, 2018 in the Korean Intellectual Property Office, the disclosures of which are incorporated herein by reference in their entireties.

TECHNICAL FIELD

The present disclosure relates to an electronic component.

BACKGROUND

Multilayer capacitors are commonly used in a variety of electronic devices due to being able to be implemented with a small size and high capacity.

In recent years, due to the rapid rise in popularity of environmentally-friendly automobiles and electric vehicles, power driving systems in automobiles have increased, and accordingly, demand for the multilayer capacitors required for automobiles has also increased.

Since a high level of thermal reliability, electrical reliability, and mechanical reliability are required in use as an automotive part, the level of performance required for the multilayer capacitor is also being advanced.

In particular, there is an increasing demand for a modular electronic device having high resistance to vibrations and deformation, while allowing high capacity to be implemented by stacking a plurality of multilayer capacitors in a limited space.

Meanwhile, modular electronic components are being manufactured to be elongated. Therefore, when a modular electronic component is mounted on a substrate, a position of a metal frame is distorted and the metal frame may contact land patterns having different polarities, which may result in a short circuit defect.

SUMMARY

An aspect of the present disclosure may provide an electronic component capable of implementing high capacity, improving durability and reliability against vibration and deformation, and preventing a short circuit when being mounted on a substrate even though it is manufactured in a modular type.

According to an aspect of the present disclosure, an electronic component may include a capacitor array including a plurality of multilayer capacitors which are sequentially arranged in a first direction; a first metal frame disposed on one side surface of the capacitor array and electrically connected to first external electrodes of the plurality of multilayer capacitors; and a second metal frame disposed on another side surface of the capacitor array and electrically connected to second external electrodes of the plurality of multilayer capacitors, wherein the first metal frame includes a first support portion bonded to first head portions of the first external electrodes; a first mounting portion extending in a second direction perpendicular to the first direction from a lower end of the first support portion; and a first connection portion extending in the second

2

direction from an upper end of the first support portion and bonded to first band portions of the first external electrodes, the second metal frame includes a second support portion bonded to second head portions of the second external electrodes; a second mounting portion extending in the second direction from a lower end of the second support portion; and a second connection portion extending in the second direction from an upper end of the second support portion and bonded to second band portions of the second external electrodes, and lengths of the first and second mounting portions in the first direction are smaller than a length of the capacitor array in the first direction.

Lengths of the first and second support portions in the first direction may be smaller than the length of the capacitor array in the first direction.

A first cutout portion may be provided at one corner of the first mounting portion and the first support portion in the first direction, and a second cutout portion may be provided at a corner of the second mounting portion and the second support portion in the first direction facing the first cutout portion in a diagonal direction.

First cutout portions may be provided at opposite corners of the first mounting portion and the first support portion in the first direction, respectively, and second cutout portions may be provided at opposite corners of the second mounting portion and the second support portion in the first direction, respectively.

At least one third cutout portion may be disposed at a middle region of a corner edge between the first mounting portion and the first support portion in the first direction, such that the first mounting portion and the first support portion are divided into multiple pieces having a predetermined gap therebetween. At least one fourth cutout portion may be disposed at a middle region of a corner edge between the second mounting portion and the second support portion in the first direction, such that the second mounting portion and the second support portion are divided into multiple pieces having a predetermined gap therebetween.

$0.4 \leq b/a < 1.0$ may be satisfied in which the length of the capacitor array in the first direction is a and the length of the first or second mounting portion in the first direction is b .

A conductive adhesive portion may be each disposed between the first external electrodes, and the first support portion and the first connection portion, and the conductive adhesive portion may be each disposed between the second external electrodes, and the second support portion and the second connection portion.

The multilayer capacitor may include a body, and the first and second external electrodes formed on opposite end surfaces of the body in a second direction, and the body may include a dielectric layer, and first and second internal electrodes alternately disposed while having the dielectric layer interposed therebetween.

The first and second external electrodes may include the first and second head portions formed on the opposite end surfaces of the body in the second direction; and first and second band portions extending from the first and second head portions to portions of upper and lower surfaces of the body and to portions of opposing side surfaces of the body.

BRIEF DESCRIPTION OF DRAWINGS

The above and other aspects, features and other advantages of the present disclosure will be more clearly understood from the following detailed description taken in conjunction with the accompanying drawings, in which:

3

FIG. 1 is a perspective view schematically illustrating a multilayer capacitor applied to an exemplary embodiment in the present disclosure;

FIGS. 2A and 2B are plan views illustrating first and second internal electrodes applied to the multilayer capacitor of FIG. 1;

FIG. 3 is a cross-sectional view taken along a line I-I' of FIG. 1;

FIG. 4 is a perspective view illustrating a schematic structure of an electronic component according to an exemplary embodiment in the present disclosure;

FIG. 5 is an exploded perspective view of the electronic component of FIG. 4;

FIG. 6 is a perspective view illustrating a schematic structure of an electronic component according to another exemplary embodiment in the present disclosure;

FIG. 7 is an exploded perspective view of the electronic component of FIG. 6;

FIGS. 8A and 8B are plan views illustrating a state in which a mounting portion is bonded to a land pattern of a substrate without being distorted and a state in which the mounting portion is bonded to the land pattern of the substrate while being distorted at a predetermined angle in the conventional electronic component, respectively;

FIGS. 9A and 9B are plan views illustrating a state in which a mounting portion is bonded to a land pattern of a substrate without being distorted and a state in which the mounting portion is bonded to the land pattern of the substrate while being distorted at a predetermined angle in an electronic component including the mounting portion of FIG. 4, respectively;

FIGS. 10A and 10B are plan views illustrating a state in which a mounting portion is bonded to a land pattern of a substrate without being distorted and a state in which the mounting portion is bonded to the land pattern of the substrate while being distorted at a predetermined angle in an electronic component including the mounting portion of FIG. 6, respectively; and

FIG. 11 is a graph illustrating a result of a shear test according to a ratio of a length of the mounting portion to a length of a capacity array.

FIG. 12 is a perspective view illustrating a schematic structure of an electronic component according to still another exemplary embodiment in the present disclosure.

DETAILED DESCRIPTION

Hereinafter, exemplary embodiments of the present disclosure will now be described in detail with reference to the accompanying drawings.

Directions will be defined in order to clearly describe exemplary embodiments in the present disclosure. X, Y and Z in the drawings refer to a length direction, a width direction, and a thickness direction of a multilayer capacitor, respectively.

In addition, X, Y, and Z refer to a width direction, length direction, and a thickness direction of a capacitor array, respectively.

Here, the Y direction refers to a stacked direction in which dielectric layers are stacked in the present exemplary embodiment.

FIG. 1 is a perspective view schematically illustrating a multilayer capacitor applied to an exemplary embodiment in the present disclosure, FIGS. 2A and 2B are plan views illustrating first and second internal electrodes applied to the multilayer capacitor of FIG. 1, and FIG. 3 is a cross-sectional view taken along a line I-I' of FIG. 1.

4

First, a structure of a multilayer capacitor applied to an electronic component according to the present exemplary embodiment will be described with reference to FIGS. 1 through 3.

Referring to FIGS. 1 through 3, a multilayer capacitor 100 according to the present exemplary embodiment may include a body 110, and first and second external electrodes 131 and 132 formed on opposite end surfaces of the body 110, respectively, in an X direction of the body 110.

The body 110 may be formed by stacking a plurality of dielectric layers 111 in a Y direction of the body 110 and then sintering the plurality of dielectric layers 111. The dielectric layers 111 adjacent to each other of the body 110 of the capacitor may be integrated with each other so that boundaries therebetween are not readily apparent without using a scanning electron microscope (SEM).

In addition, the body 110 may include the plurality of dielectric layers 111, and first and second internal electrodes 121 and 122 alternately disposed in a Y direction of the body 110 while having the dielectric layers 111 interposed therebetween and having different polarities.

In addition, the body 110 may include an active region, which is a portion contributing to formation of capacitance of the capacitor, and cover regions provided on left and right portions of the active region in the Y direction of the body 110 and upper and lower portions of the active region in a Z direction of the body 110 as margin portions.

A shape of the body 110 is not particularly limited, but may be a hexahedron shape. The body 110 may have first and second surfaces 1 and 2 opposing each other in the Z direction of the body 110, third and fourth surfaces 3 and 4 connected to the first and second surfaces 1 and 2 and opposing each other in the X direction of the body 110, and fifth and sixth surfaces 5 and 6 connected to the first and second surfaces 1 and 2, connected to the third and fourth surfaces 3 and 4, and opposing each other in the Y direction of the body 110.

The dielectric layer 111 may include a ceramic powder, for example, a BaTiO₃ based ceramic powder or the like.

An example of the barium titanate (BaTiO₃) based ceramic powder may include (Ba_{1-x}Ca_x)TiO₃, Ba(Ti_{1-y}Ca_y)O₃, (Ba_{1-x}Ca_x)(Ti_{1-y}Zr_y)O₃, Ba(Ti_{1-y}Zr_y)O₃, and the like, in which Ca, Zr, or the like, is partially dissolved in BaTiO₃, but is not limited thereto.

In addition, the dielectric layer 111 may further include a ceramic additive, an organic solvent, a plasticizer, a binder, a dispersant, and the like, in addition to the ceramic powder.

The ceramic additive may include, for example, a transition metal oxide or carbide, a rare earth element, magnesium (Mg), aluminum (Al), or the like.

The first and second internal electrodes 121 and 122, which are electrodes to which different polarities are applied, may be formed on the dielectric layer 111 to be stacked in the Y direction of the body 110, and may be alternately disposed in the body 110 so as to opposite to each other along the Y direction of the body 110 while having one dielectric layer 111 interposed therebetween.

At this time, the first and second internal electrodes 121 and 122 may be electrically insulated from each other by the dielectric layer 111 disposed therebetween.

Meanwhile, the present disclosure illustrates and describes a structure in which the internal electrodes are stacked in the Y direction of the body 110, but the present disclosure is not limited thereto and may also be applied to a structure in which the internal electrodes are stacked in the Z direction of the body, if necessary.

One end portion of each of the first and second internal electrodes **121** and **122** may be exposed through the third and fourth surfaces **3** and **4** of the body **110**, respectively.

The end portions of the first and second internal electrodes **121** and **122** alternately exposed through the third and fourth surfaces **3** and **4** of the body **110** may be electrically connected to the first and second external electrodes **131** and **132** disposed on the opposite end surfaces of the body **110** in the X direction of the body **110**, respectively, to be described below.

According to the configuration as described above, when a predetermined voltage is applied to the first and second external electrodes **131** and **132**, electric charges may be accumulated between the first and second internal electrodes **121** and **122**.

At this time, a capacitance of the multilayer capacitor **100** may be in proportional to an overlapping area of the first and second internal electrodes **121** and **122** overlapping with each other along the Y direction of the body **110** in the active region.

In addition, a material forming the first and second internal electrodes **121** and **122** is not particularly limited, but may be a conductive paste formed of one or more of, for example, a noble metal material such as platinum (Pt), palladium (Pd), a palladium-silver (Pd—Ag) alloy, or the like, nickel (Ni), and copper (Cu).

At this time, a method of printing the conductive paste may be a screen printing method, a gravure printing method, or the like, but is not limited thereto.

Voltages having different polarities may be provided to the first and second external electrodes **131** and **132**, and the first and second external electrodes **131** and **132** may be disposed on the opposite end surfaces of the body **110** in the X direction of the body **110**, and may be electrically connected to the exposed portions of the first and second internal electrodes **121** and **122**, respectively.

The first external electrode **131** may include a first head portion **131a** and a first band portion **131b**.

The first head portion **131a** may be disposed on the third surface **3** of the body **110**, and may be in contact with the end portion of the first internal electrode **121** exposed to the outside through the third surface **3** of the body **110** to serve to electrically connect the first internal electrode **121** and the first external electrode **131** to each other.

The first band portion **131b** may be a portion extending from the first head portion **131a** to portions of the first, second, fifth, and sixth surfaces **1**, **2**, **5**, and **6** of the body **110** to improve fixing strength.

The second external electrode **132** may include a second head portion **132a** and a second band portion **132b**.

The second head portion **132a** may be disposed on the fourth surface **4** of the body **110**, and may be in contact with the end portion of the second internal electrode **122** exposed to the outside through the fourth surface **4** of the body **110** to serve to electrically connect the second internal electrode **122** and the second external electrode **132** to each other.

The second band portion **132b** may be a portion extending from the second head portion **132a** to portions of the first, second, fifth, and sixth surfaces **1**, **2**, **5**, and **6** of the body **110** to improve fixing strength.

Meanwhile, the first and second external electrodes **131** and **132** may further include a plating layer.

The plating layer may include first and second nickel (Ni) plating layers, and first and second tin (Sn) plating layers covering the first and second Ni plating layers, respectively.

FIG. **4** is a perspective view illustrating a schematic structure of an electronic component according to an exem-

plary embodiment in the present disclosure and FIG. **5** is an exploded perspective view of the electronic component of FIG. **4**.

Referring to FIGS. **4** and **5**, an electronic component **200** according to the present exemplary embodiment may include a capacitor array **101** including a plurality of multilayer capacitors **100** which are sequentially arranged in the Y direction, which is the first direction, a first metal frame **140** disposed on one side surface of the capacitor array **101** in an X direction thereof and connected to the first external electrode **131** of each of the plurality of multilayer capacitors **100**, and a second metal frame **150** disposed on the other side surface of the capacitor array **101** in the X direction thereof and connected to the second external electrode **132** of each of the plurality of multilayer capacitors **100**.

The first metal frame **140** may be bonded to the respective first external electrodes **131** of the plurality of multilayer capacitors **100** to serve as a common electrode connecting the first external electrodes **131** adjacent to each other to each other.

Such a first metal frame **140** may include a first support portion, a first mounting portion **142**, and a first connection portion **143**.

The first support portion **141** may be a portion which is perpendicular to a mounting surface, is elongated in the Y direction, and is bonded to the respective first head portions **131a** of the plurality of first external electrodes **131**, and may electrically and physically connect the first head portions **131a** of the plurality of first external electrodes **131** to each other.

At this time, a length of the first support portion **141** in the Y direction may be smaller than a length of the capacitor array **101** in the Y direction. To this end, a first cutout portion **144** may be provided at one corner of the first support portion **141** in the Y direction.

At this time, a conductive adhesive portion **160** may be disposed between the first external electrodes **131** and the first support portion **141**.

According to the present exemplary embodiment, the conductive adhesive portion **160** may be disposed in the respective first head portions **131a** of the first external electrodes **131**.

Such a conductive adhesive portion **160** may be formed of a high temperature solder, a conductive adhesive material, or the like, but is not limited thereto.

The first mounting portion **142** may be a portion extending in the X direction, which is the second direction, perpendicular to the Y direction, which is the first direction, from a lower end of the first support portion **141** and formed to be horizontal with respect to the mounting surface, and may serve as a connection terminal at the time of mounting the substrate.

In addition, the first mounting portion **142** may be disposed to be spaced apart from a lower surface of the multilayer capacitor **100** by a predetermined distance in the Z direction.

At this time, a length of the first mounting portion **142** in the Y direction may be smaller than the length of the capacitor array **101** in the Y direction.

To this end, the first cutout portion **144** may be provided at one corner of the first mounting portion **142** in the Y direction.

That is, the first cutout portion **144** may be provided at a portion connecting the first support portion **141** and one corner of the first mounting portion **142** to each other.

The first connection portion **143** may extend in the X direction from an upper end of the first support portion **141**

and be formed horizontally with respect to the mounting surface, maybe bonded to the respective first band portions **131b** of the plurality of first external electrodes **131**, and may electrically and physically connect the first band portions **131b** of the plurality of first external electrodes **131** to each other.

At this time, a conductive adhesive portion **161** may be further disposed between the first external electrodes **131** and the first connection portion **143**.

According to the present exemplary embodiment, the conductive adhesive portion **161** may be disposed in upper sides of the respective first band portions **131b** of the first external electrodes **131**.

Such a conductive adhesive portion **161** may be formed of a high temperature solder, a conductive adhesive material, or the like, but is not limited thereto.

The second metal frame **150** may be bonded to the respective second external electrodes **132** of the plurality of multilayer capacitors **100** to serve as a common electrode connecting the second external electrodes **132** adjacent to each other to each other.

Such a second metal frame **150** may include a second support portion **151**, a second mounting portion **152**, and a second connection portion **153**.

The second support portion **151** may be a portion which is perpendicular to a mounting surface, is elongated in the Y direction, and is bonded to the respective second head portions **132a** of the plurality of second external electrodes **132**, and may electrically and physically connect the second head portions **132a** of the plurality of second external electrodes **132** to each other.

At this time, a length of the second support portion **151** in the Y direction may be smaller than the length of the capacitor array **101** in the Y direction.

To this end, a second cutout portion **154** may be provided at one corner of the second support portion **151** in the Y direction.

The second cutout portion **154** may be provided at a corner of the second support portion **151** facing the first cutout portion **144** in a diagonal direction.

At this time, a conductive adhesive portion **160** may be disposed between the second external electrodes **132** and the second support portion **151**.

According to the present exemplary embodiment, the conductive adhesive portion **160** may be disposed in the second head portions **132a** of the second external electrodes **132**.

Such a conductive adhesive portion **160** may be formed of a high temperature solder, a conductive adhesive material, or the like, but is not limited thereto.

The second mounting portion **152** may be a portion extending in the X direction, which is the second direction, perpendicular to the Y direction, which is the first direction, from a lower end of the second support portion **151** and formed to be horizontal with respect to the mounting surface, and may serve as a connection terminal at the time of mounting the substrate.

In addition, the second mounting portion **152** may be disposed to be spaced apart from a lower surface of the multilayer capacitor **100** by a predetermined distance in the Z direction.

At this time, a length of the second mounting portion **152** in the Y direction may be smaller than the length of the capacitor array **101** in the Y direction.

To this end, the second cutout portion **154** may be provided at one corner of the second mounting portion **152** in the Y direction.

The second cutout portion **154** may be provided at a corner of the second mounting portion **152** facing the first cutout portion **144** in a diagonal direction.

That is, the second cutout portion **154** may be provided at a portion connecting the second support portion **151** and one corner of the second mounting portion **152** to each other.

The second connection portion **153** may extend in the X direction from an upper end of the second support portion **151** and be formed horizontally with respect to the mounting surface, maybe bonded to the respective first band portions **132b** of the plurality of second external electrodes **132**, and may electrically and physically connect the first band portions **131b** of the plurality of first external electrodes **131** to each other.

The second connection portion **153** may extend in the X direction from an upper end of the second support portion **151** and be formed horizontally with respect to the mounting surface, may be bonded to the respective second band portions **132b** of the plurality of second external electrodes **132**, and may electrically and physically connect the second band portions **132b** of the plurality of second external electrodes **132** to each other.

At this time, a conductive adhesive portion **162** may be further disposed between the second external electrodes **132** and the second connection portion **153**.

According to the present exemplary embodiment, the conductive adhesive portion **162** may be disposed in upper sides of the respective first band portions **132b** of the second external electrodes **132**.

Such a conductive adhesive portion **162** may be formed of a high temperature solder, a conductive adhesive material, or the like, but is not limited thereto.

A multilayer capacitor according to the related art has a structure in which a capacitor body and a substrate are in direct contact with each other by a solder when being mounted on the substrate. Here, since heat or mechanical deformation generated in the substrate is directly transferred to the multilayer capacitor, it is difficult to secure a high level of reliability.

In the electronic component **200** according to the present exemplary embodiment, since the plurality of multilayer capacitors **100** are formed of an integrated capacitor array **101**, a high capacitance maybe implemented, and thermal reliability and mechanical reliability of the electronic component **200** may be improved by preventing stress from the substrate from being directly transferred to the respective multilayer capacitors **100** when the electronic component **200** is mounted on the substrate by bonding the first and second metal frames **140** and **150** to the opposing side surfaces of the capacitor array **101** to secure an interval between the capacitor array **101** and the substrate.

Meanwhile, in the case of a modular electronic component including the capacitor array, when a position and a direction of the modular electronic component at the time of mounting the modular electronic component on the substrate are deviated from regular position and direction on the design, an end portion of the metal frame is in contact with land patterns having different polarities due to an extended length of the metal frame, which tends to result in a short circuit defect.

In the electronic component **200** according to the present exemplary embodiment, the first and second mounting portions **142** and **152** of the first and second metal frames **140** and **150** maybe shorter than the capacitor array. Therefore, even though the first and second metal frames **140** and **150** are distorted at a predetermined angle when the electronic component **200** is mounted on the substrate, a short circuit

defect caused at the time of mounting the electronic component **200** on the substrate may be prevented by preventing the first or second mounting portion **142** or **152** from not being in contact with the land patterns having different polarities.

Meanwhile, in a case in which the lengths of the first and second mounting portions **142** and **152** are excessively short, since bonded areas between the first and second mounting portions **142** and **152** and the land patterns of the substrate are relatively reduced, fixing strength may be lowered.

Therefore, according to the present exemplary embodiment, the lengths of the first and second cutout portions **144** and **154** are limited so that a predetermined level of fixing strength may be secured.

FIG. **11** is a graph illustrating a result of a shear test according to a ratio of a length of the mounting portion to a length of a capacity array.

Here, "a" denotes a length of the capacity array **101** in the Y direction, and "b" denotes a length of the first mounting portion **142** or the first support portion **141**.

In the shear test, ten electronic component with b/a of 0.2 to 0.7 were mounted on the PCB, and a force of 20 N was then applied at a speed of 1 mm/min for 10 seconds to evaluate whether or not the components were detached.

Referring to FIG. **11**, in a case in which b/a is 0.35 or less, the area of the mounting portion is too small, so that the fixing strength by the solder may not be sufficiently secured, and it may be seen that defective results are obtained as a result of the shear test.

Therefore, the range of b/a in which the fixing strength may be sufficiently secured may be $0.4 \leq b/a < 1.0$.

FIG. **6** is a perspective view illustrating a schematic structure of an electronic component according to another exemplary embodiment in the present disclosure and FIG. **7** is an exploded perspective view of the electronic component of FIG. **6**.

Here, since the structure of the multilayer capacitor is similar to that of the above-described exemplary embodiment, a detailed description thereof will be omitted in order to avoid duplication, and the first and second metal frames having a structure different from the above-described exemplary embodiment will be described in detail.

Referring to FIGS. **6** and **7**, a first metal frame **140'** of an electronic component **200'** according to the present exemplary embodiment may have first cutout portions **144'** provided at opposite corners of a first mounting portion **142'** and a first support portion **141'** in the Y direction, respectively.

In addition, a second metal frame **150'** may have second cutout portions **154'** provided at opposite corners of a second mounting portion **152'** and a second support portion **151'** in the Y direction.

Therefore, according to the present exemplary embodiment, since the total area of the mounting portion and the support portion is smaller than that of the above-described exemplary embodiment, the fixing strength of the metal frames is weakened. However, an effect of preventing the short circuit defect may be further improved in a case in which the electronic component is distorted when being mounted on the substrate.

FIGS. **8A** and **8B** are plan views illustrating a state in which a mounting portion is bonded to a land pattern of a substrate without being distorted and a state in which the mounting portion is bonded to the land pattern of the substrate while being distorted at a predetermined angle in

an electronic component including the conventional mounting portion of a rectangular shape without having the cutout portion, respectively.

Referring to FIG. **8A**, in a case in which first and second mounting portions **42** and **52** are mounted and bonded onto first and second land patterns **211** and **212** without being distorted, the short circuit problem does not occur. However, as illustrated in FIG. **8B**, in a case in which the first and second mounting portions **42** and **52** are unintentionally bonded to the first and second land patterns **211** and **212** while being distorted at a predetermined angle when the electronic component is mounted on the substrate, an end of the first mounting portion **42** is in contact with a portion of the second land pattern **212** and an end of the second mounting portion **52** is in contact with a portion of the first land pattern **211**. As a result, the short circuit defect D may occur.

FIGS. **9A** and **9B** are plan views illustrating a state in which a mounting portion is bonded to a land pattern of a substrate without being distorted and a state in which the mounting portion is bonded to the land pattern of the substrate while being distorted at a predetermined angle in an electronic component including the mounting portion of FIG. **4**, respectively.

Referring to FIG. **9A**, in a case in which the first and second mounting portions **142** and **152** are mounted and bonded onto the first and second land patterns **211** and **212** without being distorted, the short circuit problem does not occur. As illustrated in FIG. **9B**, even though the first and second mounting portions **142** and **152** are bonded to the first and second land patterns **211** and **212** while being distorted at a predetermined angle, the length of the first mounting portion **142** is reduced by the first cutout portion **144**, such that an end of the first mounting portion **142** may not be in contact with the second land pattern **212**, and the length of the second mounting portion **152** is reduced by the second cutout portion **154**, such that an end of the second mounting portion **152** may not be in contact with the first land pattern **211**. As a result, the short circuit defect may be avoided.

FIGS. **10A** and **10B** are plan views illustrating a state in which a mounting portion is bonded to a land pattern of a substrate without being distorted and a state in which the mounting portion is bonded to the land pattern of the substrate while being distorted at a predetermined angle in an electronic component including the mounting portion of FIG. **6**, respectively.

Referring to FIG. **10A**, in a case in which the first and second mounting portions **142'** and **152'** are mounted and bonded onto the first and second land patterns **211** and **212** without being distorted, the short circuit problem does not occur. As illustrated in FIG. **10B**, even though the first and second mounting portions **142'** and **152'** are bonded to the first and second land patterns **211** and **212** while being distorted at a predetermined angle, the length of the first mounting portion **142'** is reduced by the first cutout portion **144'**, such that an end of the first mounting portion **142'** may not be in contact with the second land pattern **212**, and the length of the second mounting portion **152'** is reduced by the second cutout portion **154'**, such that an end of the second mounting portion **152'** may not be in contact with the first land pattern **211**. As a result, the short circuit defect may be avoided.

FIG. **12** is a perspective view illustrating a schematic structure of an electronic component **200''** according to still another exemplary embodiment in the present disclosure.

11

Here, since the structure of the multilayer capacitor **200**" is similar to that of the above-described exemplary embodiment **200** or **200'**, a detailed description thereof will be omitted in order to avoid duplication, and the first and second metal frames having a structure different from the above-described exemplary embodiment will be described in detail.

Referring to FIG. 12, in addition to first cutout portions **144'**, a first metal frame **140**" of the electronic component **200**" may have at least one third cutout portion **145** disposed at a middle region of a corner edge between the first mounting portion **142**" and the first support portion **141**" in the Y direction, such that the first mounting portion **142**" and the first support portion **141**" are divided into multiple pieces having a predetermined gap therebetween.

Likewise, a second metal frame **150**" of the electronic component **200**" may have at least one fourth cutout portion **155** disposed at a middle region of a corner edge between the second mounting portion **152**" and the second support portion **151**" in the Y direction, such that the second mounting portion **152**" and the second support portion **151**" are divided into multiple pieces having a predetermined gap therebetween.

As set forth above, according to the exemplary embodiment in the present disclosure, the high capacity electronic component which is manufactured in the modular type, may be provided, the durability and reliability against vibration and deformation of the electronic component may be improved, and even though the position of the metal frame is distorted when the electronic component is mounted on the substrate, the short circuit may be prevented.

While exemplary embodiments have been shown and described above, it will be apparent to those skilled in the art that modifications and variations could be made without departing from the scope of the present invention as defined by the appended claims.

What is claimed is:

1. An electronic component comprising:

a capacitor array including a plurality of multilayer capacitors which are sequentially arranged in a first direction;

a first metal frame disposed on one side surface of the capacitor array and electrically connected to first external electrodes of the plurality of multilayer capacitors; and

a second metal frame disposed on another side surface of the capacitor array and electrically connected to second external electrodes of the plurality of multilayer capacitors,

wherein the first metal frame includes a first support portion bonded to first head portions of the first external electrodes; a first mounting portion extending in a second direction perpendicular to the first direction from a lower end of the first support portion; and a first connection portion extending in the second direction from an upper end of the first support portion and bonded to first band portions of the first external electrodes,

the second metal frame includes a second support portion bonded to second head portions of the second external electrodes; a second mounting portion extending in the second direction from a lower end of the second support portion; and a second connection portion extending in the second direction from an upper end of the second support portion and bonded to second band portions of the second external electrodes,

12

each multilayer capacitor of the plurality of multilayer capacitors includes a body and the first and second external electrodes disposed on opposite end surfaces of the body in the second direction, and the body includes a dielectric layer, and first and second internal electrodes alternately disposed while having the dielectric layer interposed therebetween, and

lengths of the first and second support portions in the first direction are smaller than a length of the capacitor array in the first direction.

2. The electronic component of claim 1, wherein lengths of the first and second mounting portions in the first direction are smaller than the length of the capacitor array in the first direction.

3. The electronic component of claim 1, wherein a first cutout portion is provided at one corner of the first mounting portion and the first support portion in the first direction, and a second cutout portion is provided at a corner of the second mounting portion and the second support portion in the first direction facing the first cutout portion in a diagonal direction.

4. The electronic component of claim 1, wherein first cutout portions are provided at opposite corners of the first mounting portion and the first support portion in the first direction, respectively, and

second cutout portions are provided at opposite corners of the second mounting portion and the second support portion in the first direction, respectively.

5. The electronic component of claim 4, wherein at least one third cutout portion is disposed at a middle region of a corner edge between the first mounting portion and the first support portion in the first direction, such that the first mounting portion and the first support portion are divided into multiple pieces having a predetermined gap therebetween, and

at least one fourth cutout portion is disposed at a middle region of a corner edge between the second mounting portion and the second support portion in the first direction, such that the second mounting portion and the second support portion are divided into multiple pieces having a predetermined gap therebetween.

6. The electronic component of claim 1, wherein $0.4 \leq b/a < 1.0$ in which dimension "a" is the length of the capacitor array in the first direction and dimension b is a length of the first or second mounting portion in the first direction.

7. The electronic component of claim 1, wherein a conductive adhesive portion is disposed between the first external electrodes and the first support portion, and between the first external electrodes and the first connection portion, and the conductive adhesive portion is disposed between the second external electrodes and the second support portion, and between the second external electrodes and the second connection portion.

8. The electronic component of claim 1, wherein the first and second external electrodes respectively include the first and second head portions disposed on the opposite end surfaces of the body in the second direction; and the first and second band portions extending from the first and second head portions to portions of upper and lower surfaces of the body and to portions of opposing side surfaces of the body.

9. The electronic component of claim 1, wherein each of the first and second mounting portions is spaced apart from a lower surface of the capacitor array by a predetermined distance in a mounting direction of the electronic component which is orthogonal to the first and second directions.

13

10. An electronic component comprising:
 a capacitor array including a plurality of multilayer capacitors which are sequentially arranged in a first direction;
 a first metal frame disposed on one side surface of the capacitor array and electrically connected to first external electrodes of the plurality of multilayer capacitors;
 and
 a second metal frame disposed on another side surface of the capacitor array and electrically connected to second external electrodes of the plurality of multilayer capacitors,
 wherein the first metal frame includes a first support portion bonded to first head portions of the first external electrodes; a first mounting portion extending in a second direction perpendicular to the first direction from a lower end of the first support portion; and a first connection portion extending in the second direction from an upper end of the first support portion and bonded to first band portions of the first external electrodes,
 the second metal frame includes a second support portion bonded to second head portions of the second external electrodes; a second mounting portion extending in the second direction from a lower end of the second support portion; and a second connection portion extending in the second direction from an upper end of the second support portion and bonded to second band portions of the second external electrodes,
 each multilayer capacitor of the plurality of multilayer capacitors includes a body and the first and second external electrodes disposed on opposite end surfaces of the body in the second direction, and the body includes a dielectric layer, and first and second internal electrodes alternately disposed while having the dielectric layer interposed therebetween, and
 $0.4 \leq b/a < 1.0$ in which dimension "a" is the length of the capacitor array in the first direction and dimension b is a length of the first or second mounting portion in the first direction.
11. An electronic component comprising:
 a capacitor array including a plurality of multilayer capacitors which are sequentially arranged in a first direction;

14

- a first metal frame disposed on one side surface of the capacitor array and electrically connected to first external electrodes of the plurality of multilayer capacitors;
 and
 a second metal frame disposed on another side surface of the capacitor array and electrically connected to second external electrodes of the plurality of multilayer capacitors,
 wherein the first metal frame includes a first support portion bonded to first head portions of the first external electrodes; a first mounting portion extending in a second direction perpendicular to the first direction from a lower end of the first support portion; and a first connection portion extending in the second direction from an upper end of the first support portion and bonded to first band portions of the first external electrodes,
 the second metal frame includes a second support portion bonded to second head portions of the second external electrodes; a second mounting portion extending in the second direction from a lower end of the second support portion; and a second connection portion extending in the second direction from an upper end of the second support portion and bonded to second band portions of the second external electrodes,
 each multilayer capacitor of the plurality of multilayer capacitors includes a body and the first and second external electrodes disposed on opposite end surfaces of the body in the second direction, and the body includes a dielectric layer, and first and second internal electrodes alternately disposed while having the dielectric layer interposed therebetween,
 a conductive adhesive portion is disposed between the first external electrodes and the first support portion, and between the first external electrodes and the first connection portion, and
 the conductive adhesive portion is disposed between the second external electrodes and the second support portion, and between the second external electrodes and the second connection portion.

* * * * *