



US010858564B2

(12) **United States Patent**
Rached

(10) **Patent No.:** **US 10,858,564 B2**
(45) **Date of Patent:** ***Dec. 8, 2020**

(54) **HEAT-TRANSFER FLUIDS AND USE THEREOF IN COUNTERCURRENT HEAT EXCHANGERS**

(71) Applicant: **Arkema France**, Colombes (FR)

(72) Inventor: **Wissam Rached**, Chaponost (FR)

(73) Assignee: **ARKEMA FRANCE**, Colombes (FR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **16/382,640**

(22) Filed: **Apr. 12, 2019**

(65) **Prior Publication Data**

US 2019/0233700 A1 Aug. 1, 2019

Related U.S. Application Data

(63) Continuation of application No. 13/697,027, filed as application No. PCT/FR2011/050884 on Apr. 18, 2011, now Pat. No. 10,308,854.

(30) **Foreign Application Priority Data**

May 11, 2010 (FR) 10 53675

(51) **Int. Cl.**
C09K 5/04 (2006.01)

(52) **U.S. Cl.**
CPC **C09K 5/045** (2013.01); **C09K 2205/126** (2013.01); **C09K 2205/22** (2013.01)

(58) **Field of Classification Search**
CPC **C09K 5/045**; **C09K 2205/126**; **C09K 2205/22**; **C09K 2205/32**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,076,064	A	12/1991	Kopko
5,363,674	A	11/1994	Powell
6,248,255	B1	6/2001	Pearson
6,991,743	B2	1/2006	Poole et al.
7,524,805	B2	4/2009	Singh et al.
8,070,977	B2	12/2011	Rached
8,075,798	B2	12/2011	Rached
8,951,432	B2	2/2015	Boutier et al.
9,005,468	B2	4/2015	Rached
9,315,706	B2	4/2016	Boussand
9,512,343	B2	12/2016	Rached et al.
9,574,124	B2*	2/2017	Rached F25B 1/053
9,683,154	B2	6/2017	Rached
10,029,963	B2	7/2018	Bonnet et al.
10,119,056	B2	11/2018	Rached et al.
10,266,465	B2	4/2019	Bonnet et al.
10,308,854	B2*	6/2019	Rached C09K 5/045
10,450,489	B2	10/2019	Rached
10,759,983	B2	9/2020	Rached et al.
2004/0089839	A1	5/2004	Thomas et al.

2005/0245421	A1	11/2005	Singh et al.
2006/0243944	A1	11/2006	Minor et al.
2007/0069175	A1	3/2007	Thomas et al.
2007/0108403	A1	5/2007	Sievert et al.
2008/0111099	A1	5/2008	Singh et al.
2008/0166305	A1	7/2008	Singh et al.
2008/0184731	A1	8/2008	Sienel et al.
2008/0230738	A1	9/2008	Minor
2008/0314073	A1	12/2008	Minor
2009/0120619	A1	5/2009	Sievert et al.
2009/0158771	A1	6/2009	Low et al.
2009/0241562	A1	10/2009	Thomas et al.
2009/0272931	A1	11/2009	Minor
2009/0314015	A1	12/2009	Minor
2010/0038583	A1	2/2010	Shimomura
2010/0044619	A1	2/2010	Hulse et al.
2010/0108936	A1	5/2010	Kaneko
2010/0119460	A1	5/2010	Pham et al.
2010/0133463	A1	6/2010	Kaneko
2010/0186432	A1	7/2010	Perti et al.
2010/0319377	A1	12/2010	Moriwaki et al.
2010/0326129	A1	12/2010	Moriwaki et al.
2011/0011124	A1	1/2011	Matsuura et al.
2011/0191268	A1*	8/2011	Low C09K 5/044 705/500

2011/0258147	A1	10/2011	Low
2012/0068104	A1	3/2012	Rached et al.
2012/0068105	A1	3/2012	Rached et al.
2012/0097885	A9	4/2012	Hulse et al.
2012/0126187	A1	5/2012	Low
2012/0292556	A1	11/2012	Van Horn
2013/0055733	A1	3/2013	Rached
2013/0055739	A1	3/2013	Rached
2013/0061613	A1	3/2013	Rached
2013/0299733	A1	11/2013	Boussand
2014/0110623	A1	4/2014	Boutier et al.
2015/0184051	A1	7/2015	Rached
2016/0031773	A1	2/2016	Bonnet et al.
2016/0032165	A1	2/2016	Boussand

(Continued)

FOREIGN PATENT DOCUMENTS

EP	2 149 592	A2	2/2010
JP	H04-110388		4/1992

(Continued)

OTHER PUBLICATIONS

U.S. Appl. No. 16/545,239, Rached.

(Continued)

Primary Examiner — John R Hardee
(74) *Attorney, Agent, or Firm* — Buchanan Ingersoll & Rooney P.C.

(57) **ABSTRACT**

A ternary composition including difluoromethane, 1,3,3,3-tetrafluoropropene and a hydrocarbon-derived compound containing at least two fluorine atoms and having a boiling point of between -30 and -20° C., which is selected from 1,1-difluoroethane, 1,1,1,2-tetrafluoroethane and 2,3,3,3-tetrafluoropropene. This composition is particularly suitable for use as a heat-transfer fluid in the presence of counter-current heat exchangers.

10 Claims, No Drawings

(56)

References Cited

U.S. PATENT DOCUMENTS

2017/0037291 A1 2/2017 Rached et al.
 2018/0079943 A1 3/2018 Rached
 2018/0312453 A1 11/2018 Bonnet et al.
 2019/0023956 A1 1/2019 Rached et al.
 2019/0375971 A1 12/2019 Rached

FOREIGN PATENT DOCUMENTS

JP 2007-538115 A1 12/2007
 JP 2008-531836 A 8/2008
 JP 2008-544072 A1 12/2008
 JP 2009-222362 A1 10/2009
 JP 2010-047754 A 3/2010
 JP 2012-524137 A1 10/2012
 WO WO 97/17414 A1 5/1997
 WO WO 2010/119265 A1 2/2001
 WO WO 2004/037913 A2 5/2004
 WO WO 2005/108522 A1 11/2005
 WO WO 2006/094303 A2 9/2006
 WO WO 2006/094303 A3 9/2006
 WO WO 2007/002625 A2 1/2007
 WO WO 2007/002625 A3 1/2007
 WO WO 2007/053697 A2 5/2007
 WO WO 2007/053697 A3 5/2007
 WO WO 2007/126414 A2 11/2007
 WO WO 2007/126414 A3 11/2007
 WO WO 2008/053951 A1 5/2008
 WO WO 2008/130026 A1 10/2008
 WO WO 2009/018117 A1 2/2009
 WO WO 2009/047535 A2 4/2009
 WO WO 2009/047535 A3 4/2009
 WO WO 2009/047542 A1 4/2009
 WO WO 2009/107364 A1 9/2009
 WO WO 2009/110228 A1 9/2009
 WO WO 2009/114398 A1 9/2009
 WO WO 2009/116282 A1 9/2009
 WO WO 2009/150763 A1 12/2009
 WO WO 2009/151669 A1 12/2009
 WO WO 2010/000993 A2 1/2010
 WO WO 2010/000993 A3 1/2010
 WO WO 2010/000994 A2 1/2010
 WO WO 2010/000994 A3 1/2010
 WO WO 2010/002020 A1 1/2010
 WO WO 2010/022018 A2 2/2010
 WO WO 2010/056695 A2 5/2010
 WO WO 2010/056695 A3 5/2010
 WO WO 2010/059677 A2 5/2010
 WO WO 2010/059677 A3 5/2010
 WO WO 2010/064005 A1 6/2010
 WO WO 2011/023923 A1 3/2011
 WO WO 2011/082003 A1 7/2011

WO WO 2011/101608 A1 8/2011
 WO WO 2011/101621 A2 8/2011
 WO WO 2011/101621 A3 8/2011

OTHER PUBLICATIONS

International Search Report (English translation) issued in International Patent Application No. PCT/FR2011/050884, dated Dec. 27, 2011, 3 pages, European Patent Office, Rijswijk, NL.

Kontomaris, Kostas, et al., "Low GWP Refrigerants for Centrifugal Chillers," Ashrae Annual Conference, Jun. 20-24, 2009, 23 pages, Louisville, KY, DuPont Fluoroproducts, XP002604604.

Rudnick, Leslie R. and Shubkin, Ronald L., Editors, Synthetic Lubricants and High-Performance Functional Fluids, 2nd Ed, "25, Refrigeration Lubes", 1999, 46 pages including prefaces and introduction, Marcel Dekker, Inc., NY, NY.

Taira, Shigeharu, et al., "Examination regarding Air conditioning and Heat Pump WaterSystem using Post New alternative Refrigerant," International Symposium on Next-Generation Air Conditioning and Refrigeration Technology, Feb. 17, 2010, 8 pages, Tokyo, JP, XP002604605.

Brasz, J.J., "Variable-speed centrifugal compressor behavior with low GWP refrigerants," International Conference on Compressors and Their Systems, Sep. 7, 2009, pp. 247-256, London, UK, XP008127860.

Official Action issued by the European Patent Office in EP Appln. No. 11 731 422.9, dated Sep. 4, 2013, 4 pages, European Patent Office.

Excerpt from "Thermophysical Properties Handbook," Mar. 25, 2008, 4 pages including Front Matter pages, pp. 645-646, ISBN978-4-8425-0426-1 C3053, Yokendo Co. Ltd., Tokyo, Japan, Textbook pages in Japanese with partial English-language translation.

Higashi, Yukihiro, Thermophysical Properties of HFO-1234yf and HFO-1234ze(E), 2010 International Symposium on Next-generation Air Conditioning and Refrigeration Technology, Feb. 17-19, 2010, Tokyo, JP, 9 pages.

Yamada, Yasufu, et al., "Environmentally friendly non-flammable refrigerants," 2010 International Symposium on Next-generation Air Conditioning and Refrigeration Technology, Feb. 17-19, 2010, Tokyo, JP, 8 pages.

Aoi, Tatsufumi, et al., "Verification of Reliability for Variable Speed Motor Drive System of Compressor," *Mitsubishi Heavy Industries, Ltd., Technical Review*, pp. 150-153, vol. 41, No. 3 (May 2004), 8 pages (including English-language translation).

Rached, Wissam, U.S. Appl. No. 16/545,239 entitled "Heat-Transfer Fluid for a Centrifugal Compressor," filed in the U.S. Patent and Trademark Office Aug. 20, 2019.

U.S. Appl. No. 16/927,242, Rached et al.

Rached, Wissam, et al., U.S. Appl. No. 16/927,242 entitled "Composition Based on 1,3,3,3-Tetrafluoropropene," filed in the U.S. Patent and Trademark Office Jul. 13, 2020.

* cited by examiner

HEAT-TRANSFER FLUIDS AND USE THEREOF IN COUNTERCURRENT HEAT EXCHANGERS

CROSS REFERENCE TO RELATED APPLICATIONS

The present application is a continuation of U.S. application Ser. No. 13/697,027, filed on Nov. 9, 2012, now U.S. Pat. No. 10,308,854, which is a U.S. national stage of International Application No. PCT/FR2011/050884, filed on Apr. 18, 2011, which claims the benefit of French Application No. 1053675, filed on May 11, 2010. The entire contents of each of U.S. application Ser. No. 13/697,027, International Application No. PCT/FR2011/050884, and French Application No. 1053675 are hereby incorporated herein by reference in their entirety.

TECHNICAL FIELD

The present invention relates to heat-transfer fluids suitable for use in countercurrent heat exchangers.

TECHNICAL BACKGROUND

Fluids based on fluorocarbon compounds are widely used in vapor-compression heat-transfer systems, in particular air conditioning, heat pump, refrigeration and freezing devices. These devices have in common the fact that they are based on a thermodynamic cycle comprising the vaporization of the fluid at low pressure (in which the fluid absorbs heat); the compression of the vaporized fluid up to a high pressure; the condensation of the vaporized fluid to liquid at high pressure (in which the fluid releases heat); and the expansion of the fluid in order to complete the cycle.

Vapor compression heat-transfer systems comprise at least two heat exchangers, one in which the fluid vaporizes, and the other in which it condenses. Heat exchangers may be of co-current type or of countercurrent type.

The choice of a heat-transfer fluid (which may be a pure compound or a mixture of compounds) is dictated, on the one hand, by the thermodynamic properties of the fluid, and on the other hand, by additional constraints. Thus, one particularly important criterion is that of the impact of the fluid considered on the environment. In particular, chlorinated compounds (chlorofluorocarbons and hydrochlorofluorocarbons) have the disadvantage of damaging the ozone layer. Henceforth, generally non-chlorinated compounds such as hydrofluorocarbons, fluoroethers and fluoroolefins are therefore preferred to them.

Heat-transfer fluids currently used are HFC-134a, R404a (ternary mixture of 52% of HFC-143a, 44% of HFC-125 and 4% HFC-134a), R407c (ternary mixture of 52% of HFC-134a, 25% of HFC-125 and 23% of HFC-32) and R410a (binary mixture of 50% of HFC-32 and 50% of HFC-125).

It is, however, necessary to develop other heat-transfer fluids that have a global warming potential (GWP) lower than that of the fluids above, and that have equivalent or improved performance levels.

Document WO 2007/002625 describes compositions based on fluoroolefins, and in particular on HFO-1234yf or on HFO-1234ze, in various uses, and in particular as heat-transfer fluids. The document does not specify the type of heat exchanger used.

Document WO 2007/126414 describes generally a large variety of fluoroolefin-based compositions and a large vari-

ety of uses of these compositions. The document does not specify the type of heat exchanger used.

Documents WO 2009/107364, WO 2009/110228 and WO 2009/116282 describe refrigeration apparatuses in which the refrigerants used are mixtures based on HFO-1234yf and on HFC-32, optionally supplemented or replaced with other compounds, such as HFC-125. The type of heat exchanger used is not specified.

Document US 2009/0158771 describes the use of a ternary mixture comprising HFC-32, HFC-134a and HFO-1243zf, in a heat transfer application. The coefficients of performance that are obtained are lower than those of the fluid taken as reference, namely HFC-134a. The type of heat exchanger used is not specified.

Document WO 2009/150763 describes an air-conditioning apparatus with a countercurrent heat exchanger, in which the heat-transfer fluid is a mixture of an HFO-1234 and of HFC-32 or of HFC-41.

Document WO 2010/000993 describes the use of a ternary mixture comprising HFO-1234yf, HFC-32 and HFC-134a, as a heat-transfer fluid. The document does not specify the type of heat exchanger used.

Document WO 2010/000994 describes the use of a ternary mixture comprising HFO-1234yf, HFC-32 and HFC-152a, as a heat-transfer fluid. The document does not specify the type of heat exchanger used.

However, there is still a need to develop other heat-transfer fluids that have a relatively low GWP and that have good energy performance levels, in particular in applications using countercurrent heat exchangers.

SUMMARY

The invention relates firstly to a ternary composition comprising difluoromethane, 1,3,3,3-tetrafluoropropene and a hydrocarbon-derived compound containing at least two fluorine atoms and having a boiling point of between -30 and -20° C., which is selected from 1,1-difluoroethane, 1,1,1,2-tetrafluoroethane and 2,3,3,3-tetrafluoropropene.

According to one embodiment, the composition comprises difluoromethane, 1,1-difluoroethane and 1,3,3,3-tetrafluoropropene, preferably from 2 to 96% of difluoromethane, from 2 to 96% of 1,1-difluoroethane and from 2 to 96% of 1,3,3,3-tetrafluoropropene, and particularly preferably:

from 25 to 50% of difluoromethane, from 2 to 35% of 1,1-difluoroethane and from 15 to 73% of 1,3,3,3-tetrafluoropropene, ideally from 35 to 50% of difluoromethane, from 2 to 10% of 1,1-difluoroethane and from 40 to 63% of 1,3,3,3-tetrafluoropropene; or

from 65 to 96% of difluoromethane, from 2 to 20% of 1,1-difluoroethane and from 2 to 25% of 1,3,3,3-tetrafluoropropene, ideally from 65 to 93% of difluoromethane, from 2 to 10% of 1,1-difluoroethane and from 5 to 25% of 1,3,3,3-tetrafluoropropene; or

from 2 to 20% of difluoromethane, from 2 to 85% of 1,1-difluoroethane and from 10 to 96% of 1,3,3,3-tetrafluoropropene, ideally from 5 to 15% of difluoromethane, from 2 to 35% of 1,1-difluoroethane and from 50 to 93% of 1,3,3,3-tetrafluoropropene; or

from 20 to 50% of difluoromethane, from 2 to 65% of 1,1-difluoroethane and from 5 to 78% of 1,3,3,3-tetrafluoropropene, ideally from 25 to 50% of difluoromethane, from 2 to 15% of 1,1-difluoroethane and from 35 to 73% of 1,3,3,3-tetrafluoropropene; or

from 65 to 93% of difluoromethane, from 2 to 30% of 1,1-difluoroethane and from 5 to 33% of 1,3,3,3-tetrafluoropropene, ideally from 65 to 93% of difluo-

3

romethane, from 2 to 10% of 1,1-difluoroethane and from 5 to 33% of 1,3,3,3-tetrafluoropropene.

According to another embodiment, the composition comprises difluoromethane, 2,3,3,3-tetrafluoropropene and 1,3,3,3-tetrafluoropropene, preferably from 2 to 96% of difluoromethane, from 2 to 96% of 2,3,3,3-tetrafluoropropene and from 2 to 96% of 1,3,3,3-tetrafluoropropene, and particularly preferably:

from 5 to 70% of 2,3,3,3-tetrafluoropropene, from 20 to 60% of difluoromethane and from 5 to 75% of 1,3,3,3-tetrafluoropropene, ideally from 5 to 70% of 2,3,3,3-tetrafluoropropene, from 25 to 50% of difluoromethane and from 5 to 55% of 1,3,3,3-tetrafluoropropene; or from 2 to 50% of 2,3,3,3-tetrafluoropropene, from 50 to 96% of difluoromethane and from 2 to 40% of 1,3,3,3-tetrafluoropropene, ideally from 5 to 30% of 2,3,3,3-tetrafluoropropene, from 65 to 90% of difluoromethane and from 5 to 25% of 1,3,3,3-tetrafluoropropene; or from 5 to 75% of 2,3,3,3-tetrafluoropropene, from 2 to 20% of difluoromethane and from 10 to 83% of 1,3,3,3-tetrafluoropropene, ideally from 10 to 75% of 2,3,3,3-tetrafluoropropene, from 5 to 15% of difluoromethane and from 10 to 75% of 1,3,3,3-tetrafluoropropene; or

from 5 to 75% of 2,3,3,3-tetrafluoropropene, from 15 to 70% of difluoromethane and from 5 to 80% of 1,3,3,3-tetrafluoropropene, ideally from 5 to 65% of 2,3,3,3-tetrafluoropropene, from 25 to 50% of difluoromethane and from 10 to 70% of 1,3,3,3-tetrafluoropropene; or

from 5 to 45% of 2,3,3,3-tetrafluoropropene, from 50 to 90% of difluoromethane and from 5 to 45% of 1,3,3,3-tetrafluoropropene, ideally from 5 to 30% of 2,3,3,3-tetrafluoropropene, from 65 to 90% of difluoromethane and from 5 to 30% of 1,3,3,3-tetrafluoropropene.

According to another embodiment, the composition comprises difluoromethane, 1,1,1,2-tetrafluoroethane and 1,3,3,3-tetrafluoropropene, preferably from 2 to 96% of difluoromethane, from 2 to 96% of 1,1,1,2-tetrafluoroethane and from 2 to 96% of 1,3,3,3-tetrafluoropropene, and particularly preferably:

from 20 to 60% of difluoromethane, from 2 to 60% of 1,1,1,2-tetrafluoroethane and from 5 to 78% of 1,3,3,3-tetrafluoropropene, ideally from 25 to 50% of difluoromethane, from 5 to 60% of 1,1,1,2-tetrafluoroethane and from 10 to 70% of 1,3,3,3-tetrafluoropropene; or from 50 to 93% of difluoromethane, from 2 to 45% of 1,1,1,2-tetrafluoroethane and from 5 to 48% of 1,3,3,3-tetrafluoropropene, ideally from 65 to 93% of difluoromethane, from 2 to 30% of 1,1,1,2-tetrafluoroethane and from 5 to 33% of 1,3,3,3-tetrafluoropropene; or from 2 to 25% of difluoromethane, from 5 to 88% of 1,1,1,2-tetrafluoroethane and from 10 to 93% of 1,3,3,3-tetrafluoropropene, ideally from 5 to 15% of difluoromethane, from 5 to 60% of 1,1,1,2-tetrafluoroethane and from 25 to 90% of 1,3,3,3-tetrafluoropropene; or from 15 to 50% of difluoromethane, from 5 to 65% of 1,1,1,2-tetrafluoroethane and from 10 to 80% of 1,3,3,3-tetrafluoropropene, ideally from 15 to 35% of difluoromethane, from 5 to 55% of 1,1,1,2-tetrafluoroethane and from 10 to 80% of 1,3,3,3-tetrafluoropropene; or from 50 to 93% of difluoromethane, from 2 to 45% of 1,1,1,2-tetrafluoroethane and from 5 to 48% of 1,3,3,3-tetrafluoropropene, ideally from 65 to 93% of difluoromethane, from 2 to 25% of 1,1,1,2-tetrafluoroethane and from 5 to 33% of 1,3,3,3-tetrafluoropropene.

4

According to another embodiment, the composition comprises from 70 to 98% of difluoromethane, from 1 to 28% of 2,3,3,3-tetrafluoropropene and from 1 to 15% of 1,3,3,3-tetrafluoropropene.

According to one embodiment, the composition comprises from 80 to 98% of difluoromethane, from 1 to 18% of 1,1,1,2-tetrafluoroethane and from 1 to 12% of 1,3,3,3-tetrafluoropropene.

The invention also relates to the use of the abovementioned composition, as a heat-transfer fluid in a vapor compression circuit.

According to one embodiment, the vapor compression circuit comprises a countercurrent heat exchanger.

The invention also relates to a heat-transfer composition comprising the abovementioned composition as heat-transfer fluid, and one or more additives selected from lubricants, stabilizers, surfactants, tracers, fluorescent agents, odorous agents, solubilizing agents and mixtures thereof.

The invention also relates to heat-transfer equipment comprising a vapor compression circuit containing the abovementioned composition as heat-transfer fluid or containing the abovementioned heat-transfer composition.

According to one embodiment, the equipment comprises a countercurrent heat exchanger.

According to one embodiment, the equipment is selected from mobile or stationary equipment for heating via a heat pump, for air conditioning, for refrigeration and for freezing.

The invention also relates to a process for heating or cooling a fluid or a body by means of a vapor compression circuit containing a heat-transfer fluid, said process successively comprising the evaporation of the heat-transfer fluid, the compression of the heat-transfer fluid, the condensation of the heat fluid and the expansion of the heat-transfer fluid, in which the heat-transfer fluid is the composition according to the invention.

According to one embodiment, the abovementioned process is a process for cooling a fluid or a body, in which the temperature of the fluid or of the body cooled is from -40° C. to -10° C., and preferably from -35° C. to -25° C., more particularly preferably from -30° C. to -20° C., and in which the heat-transfer fluid comprises:

from 25 to 50% of difluoromethane, from 2 to 35% of 1,1-difluoroethane and from 15 to 73% of 1,3,3,3-tetrafluoropropene, ideally from 35 to 50% of difluoromethane, from 2 to 10% of 1,1-difluoroethane and from 40 to 63% of 1,3,3,3-tetrafluoropropene; or from 5 to 70% of 2,3,3,3-tetrafluoropropene, from 20 to 60% of difluoromethane and from 5 to 75% of 1,3,3,3-tetrafluoropropene, ideally from 5 to 70% of 2,3,3,3-tetrafluoropropene, from 25 to 50% of difluoromethane and from 5 to 55% of 1,3,3,3-tetrafluoropropene; or from 20 to 60% of difluoromethane, from 2 to 60% of 1,1,1,2-tetrafluoroethane and from 5 to 78% of 1,3,3,3-tetrafluoropropene, ideally from 25 to 50% of difluoromethane, from 5 to 60% of 1,1,1,2-tetrafluoroethane and from 10 to 70% of 1,3,3,3-tetrafluoropropene; or from 65 to 96% of difluoromethane, from 2 to 20% of 1,1-difluoroethane and from 2 to 25% of 1,3,3,3-tetrafluoropropene, ideally from 65 to 93% of difluoromethane, from 2 to 10% of 1,1-difluoroethane and from 5 to 25% of 1,3,3,3-tetrafluoropropene; or from 2 to 50% of 2,3,3,3-tetrafluoropropene, from 50 to 96% of difluoromethane and from 2 to 40% of 1,3,3,3-tetrafluoropropene, ideally from 5 to 30% of 2,3,3,3-tetrafluoropropene, from 65 to 90% of difluoromethane and from 5 to 25% of 1,3,3,3-tetrafluoropropene; or

3-tetrafluoropropene, ideally from 5 to 70% of 2,3,3,3-tetrafluoropropene, from 25 to 50% of difluoromethane and from 5 to 55% of 1,3,3,3-tetrafluoropropene; or from 20 to 60% of difluoromethane, from 2 to 60% of 1,1,1,2-tetrafluoroethane and from 5 to 78% of 1,3,3,3-tetrafluoropropene, ideally from 25 to 50% of difluoromethane, from 5 to 60% of 1,1,1,2-tetrafluoroethane and from 10 to 70% of 1,3,3,3-tetrafluoropropene; or from 20 to 50% of difluoromethane, from 2 to 65% of 1,1-difluoroethane and from 5 to 78% of 1,3,3,3-tetrafluoropropene, ideally from 25 to 50% of difluoromethane, from 2 to 15% of 1,1-difluoroethane and from 35 to 73% of 1,3,3,3-tetrafluoropropene; or from 5 to 75% of 2,3,3,3-tetrafluoropropene, from 15 to 70% of difluoromethane and from 5 to 80% of 1,3,3,3-tetrafluoropropene, ideally from 5 to 65% of 2,3,3,3-tetrafluoropropene, from 25 to 50% of difluoromethane and from 10 to 70% of 1,3,3,3-tetrafluoropropene; or

from 15 to 50% of difluoromethane, from 5 to 65% of 1,1,1,2-tetrafluoroethane and from 10 to 80% of 1,3,3,3-tetrafluoropropene, ideally from 15 to 35% of difluoromethane, from 5 to 55% of 1,1,1,2-tetrafluoroethane and from 10 to 80% of 1,3,3,3-tetrafluoropropene.

According to another embodiment of said process for reducing environmental impact, the initial heat-transfer fluid is a binary mixture of 50% of difluoromethane and 50% of pentafluoroethane, and in which the final heat-transfer fluid comprises:

from 65 to 96% of difluoromethane, from 2 to 20% of 1,1-difluoroethane and from 2 to 25% of 1,3,3,3-tetrafluoropropene, ideally from 65 to 93% of difluoromethane, from 2 to 10% of 1,1-difluoroethane and from 5 to 25% of 1,3,3,3-tetrafluoropropene; or from 2 to 50% of 2,3,3,3-tetrafluoropropene, from 50 to 96% of difluoromethane and from 2 to 40% of 1,3,3,3-tetrafluoropropene, ideally from 5 to 30% of 2,3,3,3-tetrafluoropropene, from 65 to 90% of difluoromethane and from 5 to 25% of 1,3,3,3-tetrafluoropropene; or from 50 to 93% of difluoromethane, from 2 to 45% of 1,1,1,2-tetrafluoropropene and from 5 to 48% of 1,3,3,3-tetrafluoroethane, ideally from 65 to 93% of difluoromethane, from 2 to 30% of 1,1,1,2-tetrafluoroethane and from 5 to 33% of 1,3,3,3-tetrafluoropropene; or from 65 to 93% of difluoromethane, from 2 to 30% of 1,1-difluoroethane and from 5 to 33% of 1,3,3,3-tetrafluoropropene, ideally from 65 to 93% of difluoromethane, from 2 to 10% of 1,1-difluoroethane and from 5 to 33% of 1,3,3,3-tetrafluoropropene; or from 5 to 45% of 2,3,3,3-tetrafluoropropene, from 50 to 90% of difluoromethane and from 5 to 45% of 1,3,3,3-tetrafluoropropene, ideally from 5 to 30% of 2,3,3,3-tetrafluoropropene, from 65 to 90% of difluoromethane and from 5 to 30% of 1,3,3,3-tetrafluoropropene; or from 50 to 93% of difluoromethane, from 2 to 45% of 1,1,1,2-tetrafluoroethane and from 5 to 48% of 1,3,3,3-tetrafluoropropene, ideally from 65 to 93% of difluoromethane, from 2 to 25% of 1,1,1,2-tetrafluoroethane and from 5 to 33% of 1,3,3,3-tetrafluoropropene.

According to another embodiment of said process for reducing environmental impact, the initial heat-transfer fluid is 1,1,1,2-tetrafluoroethane, and in which the final heat-transfer fluid comprises:

from 2 to 20% of difluoromethane, from 2 to 85% of 1,1-difluoroethane and from 10 to 96% of 1,3,3,3-tetrafluoropropene, ideally from 5 to 15% of difluo-

romethane, from 2 to 35% of 1,1-difluoroethane and from 50 to 93% of 1,3,3,3-tetrafluoropropene; or from 5 to 75% of 2,3,3,3-tetrafluoropropene, from 2 to 20% of difluoromethane and from 10 to 83% of 1,3,3,3-tetrafluoropropene, ideally from 10 to 75% of 2,3,3,3-tetrafluoropropene, from 5 to 15% of difluoromethane and from 10 to 75% of 1,3,3,3-tetrafluoropropene; or

from 2 to 25% of difluoromethane, from 5 to 88% of 1,1,1,2-tetrafluoroethane and from 10 to 93% of 1,3,3,3-tetrafluoropropene, ideally from 5 to 15% of difluoromethane, from 5 to 60% of 1,1,1,2-tetrafluoroethane and from 25 to 90% of 1,3,3,3-tetrafluoropropene.

The present invention makes it possible to overcome the drawbacks of the prior art. It provides more particularly heat-transfer fluids that have a relatively low GWP and that have good energy performance levels, in particular in applications using countercurrent heat exchangers.

This is accomplished by virtue of ternary mixtures comprising HFO-1234ze and HFC-32, the rest making up the mixtures being selected from HFO-152a, HFO-1234yf and HFC-134a. These three compounds are hydrocarbon-based molecules which have at least two fluorine substituents and a boiling point of between -30°C . and -18°C . HFC-152a has a boiling point of -24°C ., HFO-1234yf has a boiling point of -29°C . and HFC-134a has a boiling point of -26°C .

The ternary mixtures above have the particularity of exhibiting good energy performance levels, in particular with countercurrent heat exchangers.

According to some particular embodiments, the invention also has one or preferably more of the advantageous characteristics listed below.

The heat-transfer fluids of the invention have a coefficient of performance which is higher than the reference refrigerants R404a, R407c, HFC-134a and R410a in applications involving a countercurrent heat exchanger. In certain cases, the capacity of the heat-transfer fluids is greater than or equal to that of the reference refrigerants, in these same applications. Correspondingly, the invention makes it possible to reduce the GWP of existing systems comprising one of the above reference refrigerants, without being detrimental to the performance levels of these systems, and, on the contrary, while improving them to a large extent, by replacing the reference refrigerants with the heat-transfer fluids of the invention.

The heat-transfer fluids of the invention have a coefficient of performance which is higher than that of the HFO-1243zf/HFC-134a/HFC-32 mixture such as is used in document US 2009/0158771.

The heat-transfer fluids of the invention are less inflammable and/or more effective than those used in document WO 2009/150763.

According to the invention, the global warming potential (GWP) is defined relative to carbon dioxide and with respect to a period of 100 years, according to the method indicated in *"The scientific assessment of ozone depletion, 2002, a report of the World Meteorological Association's Global Ozone Research and Monitoring Project"*.

DETAILED DESCRIPTION OF EMBODIMENTS

The invention is now described in greater detail and in a non-limiting manner in the description which follows.

The term "heat-transfer compound", respectively "heat-transfer fluid" (or refrigerant fluid) is intended to mean a

compound, respectively a fluid, capable of absorbing heat by evaporating at low temperature and low pressure and of releasing heat by condensing at high temperature and high pressure, in a vapor compression circuit. Generally, a heat-transfer fluid may comprise just one, or two, three or more than three heat-transfer compounds.

The term "heat-transfer composition" is intended to mean a composition comprising a heat-transfer fluid and, optionally, one or more additives which are not heat-transfer compounds for the envisioned application.

The heat transfer process according to the invention is based on the use of equipment comprising a vapor compression circuit which contains a heat-transfer fluid. The heat-transfer process may be a process for heating or cooling a fluid or body.

The vapor compression circuit containing a heat-transfer fluid comprises at least one evaporator, a compressor, a condenser and an expansion valve, and also is for transporting heat-transfer fluid between these components. The evaporator and the condenser comprise a heat exchanger making it possible to exchange heat between the heat-transfer fluid and another fluid or body.

By way of compressor, use may in particular be made of a centrifugal compressor having one or more stages or a centrifugal mini-compressor. Rotary compressors, reciprocating compressors or screw compressors can also be used. The compressor may be driven by an electric motor or by a gas turbine (for example fed with the exhaust gases of a vehicle, for mobile applications), or by gearing.

The equipment may comprise a turbine for generating electricity (Rankine cycle).

The equipment may also optionally comprise at least one coolant circuit used for transmitting heat (with or without a change of state) between the heat-transfer fluid circuit and the fluid or body to be heated or cooled.

The equipment may also optionally comprise two (or more) vapor compression circuits containing identical or distinct heat-transfer fluids. For example, the vapor compression circuits may be coupled together.

The vapor compression circuit operates according to a conventional vapor compression cycle. The cycle comprises the change of state of the heat-transfer fluid from a liquid phase (or liquid/vapor two phase state) to a vapor phase at a relatively low pressure, then the compression of the fluid in the vapor phase up to a relatively high pressure, the change of state (condensation) of the heat-transfer fluid from the vapor phase to the liquid phase at a relatively high pressure, and the reduction of the pressure in order to recommence the cycle.

In the case of a cooling process, heat from the fluid or from the body that is being cooled (directly or indirectly, via a coolant) is absorbed by the heat-transfer fluid, during the evaporation of the latter, at a relatively low temperature compared with the surroundings.

The cooling processes include air-conditioning processes (with mobile equipment, for example in vehicles, or stationary equipment), refrigeration processes and freezing processes or cryogenic processes.

In the case of a heating process, heat is imparted (directly or indirectly, via a coolant) from the heat-transfer fluid, during the condensation thereof, to the fluid or the body that is being heated, at a relatively high temperature compared to the surroundings. The equipment that makes it possible to implement the heat transfer is called, in this case, a "heat pump".

It is possible to use any type of heat exchanger for using the heat-transfer fluids according to the invention, and in particular cocurrent heat exchangers.

However, according to a preferred embodiment, the invention provides for the cooling and heating processes, and the corresponding equipment, to comprise a counter-current heat exchanger, said heat exchanger being counter-current with respect either to the condenser or to the evaporator. Indeed, the heat-transfer fluids according to the invention are particularly effective with countercurrent heat exchangers. Preferably, both the evaporator and the condenser comprise a countercurrent heat exchanger.

According to the invention, the term "countercurrent heat exchanger" is intended to mean a heat exchanger in which the heat is exchanged between a first fluid and a second fluid, the first fluid at the inlet of the exchanger exchanging heat with the second fluid at the outlet of the exchanger, and the first fluid at the outlet of the exchanger exchanging heat with the second fluid at the inlet of the exchanger.

For example, the countercurrent heat exchangers include devices in which the flow of the first fluid and the flow of the second fluid are in opposite directions or virtually opposite directions. Exchangers which operate in cross-current mode with countercurrent tendency are also included among the countercurrent heat exchangers within the meaning of the present application.

The meaning of the various abbreviations used to denote the various chemical compounds mentioned in the application is the following:

HFC-134a: 1,1,1,2-tetrafluoroethane;
 HFC-143a: 1,1,1-trifluoroethane;
 HFC-125: pentafluoroethane;
 HFC-32: difluoromethane;
 HFC-152a: 1,1-difluoroethane;
 HFC-41: fluoromethane;
 HFO-1234ze: 1,3,3,3-tetrafluoropropene;
 HFO-1234yf: 2,3,3,3-tetrafluoropropene;
 HFO-1243zf: 3,3,3-trifluoropropene.

The heat-transfer fluids used in the invention are the following ternary mixtures:

- 1) HFC-32, HFC-152a and HFO-1234ze;
- 2) HFO-1234yf, HFC-32 and HFO-1234ze; and
- 3) HFC-32, HFC-134a and HFO-1234ze.

Compositions 2) and 3) have the advantage of being less inflammable than those described in document WO 2009/150763.

The term "ternary mixture" is intended to mean a composition consisting essentially of the three compounds mentioned, i.e. in which the three compounds mentioned represent at least 99% (preferably at least 99.5% or even at least 99.9%) of the composition.

Unless otherwise mentioned, throughout the application, the proportions of compounds indicated are given as percentages by weight.

The HFO-1234ze may be in cis or trans form or be a mixture of these two forms.

In each of the three compositions above, each compound can be present preferably in an amount of from 1 to 99%, and in particular from 1 to 96%.

For use in low-temperature refrigeration processes, i.e. those in which the temperature of the fluid or of the body cooled is from -40°C. to -10°C. , and preferably from -35°C. to -25°C. , more particularly preferably from -30°C. to -20°C. (ideally approximately -25°C.), it has been found that the compounds which are most effective as a replacement for R404a or R407c are the following:

11

for composition 1): from 25 to 50% of HFC-32, from 2 to 35% of HFC-152a and from 15 to 73% of HFO-1234ze, and preferably from 35 to 50% of HFC-32, from 2 to 10% of HFC-152a and from 40 to 63% of HFO-1234ze;

for composition 2): from 5 to 70% of HFO-1234yf, from 20 to 60% of HFC-32 and from 5 to 75% of HFO-1234ze, and preferably from 5 to 70% of HFO-1234yf, from 25 to 50% of HFC-32 and from 5 to 55% of HFO-1234ze; and

for composition 3): from 20 to 60% of HFC-32, from 2 to 60% of HFC-134a and from 5 to 78% of HFO-1234ze, and preferably from 25 to 50% of HFC-32, from 5 to 60% of HFC-134a and from 10 to 70% of HFO-1234ze.

For use in low-temperature refrigeration processes, i.e. those in which the temperature of the fluid or of the body cooled is from -40°C . to -10°C ., and preferably from -35°C . to -25°C ., more particularly preferably from -30°C . to -20°C . (ideally approximately -25°C .), it has been found that the compositions which are most effective as a replacement for R410a are the following:

for composition 1): from 65 to 96% of HFC-32, from 2 to 20% of HFC-152a and from 2 to 25% of HFO-1234ze, and preferably from 65 to 93% of HFC-32, from 2 to 10% of HFC-152a and from 5 to 25% of HFO-1234ze;

for composition 2): from 2 to 50% of HFO-1234yf, from 50 to 96% of HFC-32 and from 2 to 40% of HFO-1234ze, and preferably from 5 to 30% of HFO-1234yf, from 65 to 90% of HFC-32 and from 5 to 25% of HFO-1234ze; and

for composition 3): from 50 to 93% of HFC-32, from 2 to 45% of HFC-134a and from 5 to 48% of HFO-1234ze, and preferably from 65 to 93% of HFC-32, from 2 to 30% of HFC-134a and from 5 to 33% of HFO-1234ze.

For use in:

moderate-temperature cooling processes, i.e. those in which the temperature of the fluid or the body cooled is from -15°C . to 15°C ., preferably from -10°C . to 10°C ., more particularly preferably from -5°C . to 5°C . (ideally approximately 0°C .), and also

moderate-temperature heating processes, i.e. those in which the temperature of the fluid or of the body heated is from 30°C . to 80°C ., and preferably from 35°C . to 55°C ., more particularly preferably from 40°C . to 50°C . (ideally approximately 45°C .),

it has been found that the compositions which are most effective as a replacement for HFC-134a are the following:

for composition 1): from 2 to 20% of HFC-32, from 2 to 85% of HFC-152a and from 10 to 96% of HFO-1234ze, and preferably from 5 to 15% of HFC-32, from 2 to 35% of HFC-152a and from 50 to 93% of HFO-1234ze;

for composition 2): from 5 to 75% of HFO-1234yf, from 2 to 20% of HFC-32 and from 10 to 83% of HFO-1234ze, and preferably from 10 to 75% of HFO-1234yf, from 5 to 15% of HFC-32 and from 10 to 75% of HFO-1234ze; and

for composition 3): from 2 to 25% of HFC-32, from 5 to 88% of HFC-134a and from 10 to 93% of HFO-1234ze, and preferably from 5 to 15% of HFC-32, from 5 to 60% of HFC-134a and from 25 to 90% of HFO-1234ze.

For use in:

moderate-temperature cooling processes, i.e. those in which the temperature of the fluid or of the body cooled is from -15°C . to 15°C ., preferably from -10°C . to 10°C ., more particularly preferably from -5°C . to 5°C . (ideally approximately 0°C .), and also

12

moderate-temperature heating processes, i.e. those in which the temperature of the fluid or of the body heated is from 30°C . to 80°C ., and preferably from 35°C . to 55°C ., more particularly preferably from 40°C . to 50°C . (ideally approximately 45°C .),

it has been found that the compositions which are most effective as a replacement for R404a or for R407c are the following:

for composition 1): from 20 to 50% of HFC-32, from 2 to 65% of HFC-152a and from 5 to 78% of HFO-1234ze, and ideally from 25 to 50% of HFC-32, from 2 to 15% of HFC-152a and from 35 to 73% of HFO-1234ze;

for composition 2): from 5 to 75% of HFO-1234yf, from 15 to 70% of HFC-32 and from 5 to 80% of HFO-1234ze, and ideally from 5 to 65% of HFO-1234yf, from 25 to 50% of HFC-32 and from 10 to 70% of HFO-1234ze; and

for composition 3): from 15 to 50% of HFC-32, from 5 to 65% of HFC-134a and from 10 to 80% of HFO-1234ze, and ideally from 15 to 35% of HFC-32, from 5 to 55% of HFC-134a and from 10 to 80% of HFO-1234ze.

For use in:

moderate-temperature cooling processes, i.e. those in which the temperature of the fluid or of the body cooled is from -15°C . to 15°C ., preferably from -10°C . to 10°C ., more particularly preferably from -5°C . to 5°C . (ideally about 0°C .), and also

moderate-temperature heating processes, i.e. those in which the temperature of the fluid or of the body heated is from 30°C . to 80°C ., and preferably from 35°C . to 55°C ., more particularly preferably from 40°C . to 50°C . (ideally approximately 45°C .),

it has been found that the compositions which are most effective as a replacement for R410a are the following:

for composition 1): from 65 to 93% of HFC-32, from 2 to 30% of HFC-152a and from 5 to 33% of HFO-1234ze, and ideally from 65 to 93% of HFC-32, from 2 to 10% of HFC-152a and from 5 to 33% of HFO-1234ze;

for composition 2): from 5 to 45% of HFO-1234yf, from 50 to 90% of HFC-32 and from 5 to 45% of HFO-1234ze, and ideally from 5 to 30% of HFO-1234yf, from 65 to 90% of HFC-32 and from 5 to 30% of HFO-1234ze; and

for composition 3): from 50 to 93% of HFC-32, from 2 to 45% of HFC-134a and from 5 to 48% of HFO-1234ze, and ideally from 65 to 93% of HFC-32, from 2 to 25% of HFC-134a and from 5 to 33% of HFO-1234ze.

In the "low-temperature refrigeration" processes mentioned above, the inlet temperature of the heat-transfer fluid at the evaporator is preferably from -45°C . to -15°C ., in particular from -40°C . to -20°C ., more particularly preferably from -35°C . to -25°C . and, for example, approximately -30°C .; and the temperature at the beginning of the condensation of the heat-transfer fluid at the condenser is preferably from 25°C . to 80°C ., in particular from 30°C . to 60°C ., more particularly preferably from 35°C . to 55°C . and, for example, approximately 40°C .

In the "moderate-temperature refrigeration" processes mentioned above, the inlet temperature of the heat-transfer fluid at the evaporator is preferably from -20°C . to 10°C ., in particular from -15°C . to 5°C ., more particularly preferably from -10°C . to 0°C . and, for example, approximately -5°C .; and the temperature at the beginning of the condensation of the heat-transfer fluid at the condenser is preferably from 25°C . to 80°C ., in particular from 30°C . to 60°C ., more particularly preferably from 35°C . to 55°C .

and, for example, approximately 50° C. These processes may be refrigeration or air-conditioning processes.

In the “moderate-temperature heating” processes mentioned above, the inlet temperature of the heat-transfer fluid at the evaporator is preferably from -20° C. to 10° C., in particular from -15° C. to 5° C., more particularly preferably from -10° C. to 0° C. and, for example, approximately -5° C.; and the temperature at the beginning of the condensation of the heat-transfer fluid at the condenser is preferably from 25° C. to 80° C., in particular from 30° C. to 60° C., more particularly preferably from 35° C. to 55° C. and, for example, approximately 50° C.

In addition, the mixtures having the following formulations are quasi-azeotropic mixtures:

- from 1 to 28% of HFO-1234yf, from 70 to 98% of HFC-32 and from 1 to 15% of HFO-1234ze;
- from 80 to 98% of HFC-32, from 1 to 18% of HFC-134a and from 1 to 12% of HFO-1234ze.

For these heat-transfer fluids, at constant temperature, the liquid saturation pressure and the vapor saturation pressure are virtually identical (the maximum pressure difference being 10%). These heat-transfer fluids have an advantage in terms of ease of use. In the absence of significant temperature glide, there is no significant change in the composition circulating, and no significant change either in the composition in the event of a leak. These heat-transfer fluids are particularly suitable for replacing R410a, for example.

The heat-transfer fluids which are not quasi-azeotropic, for their part, are however very effective when they are correctly coupled with a countercurrent heat exchanger (with a temperature difference with the second fluid which is approximately constant in the exchanger).

Each heat-transfer fluid above can be mixed with one or more additives so as to provide the heat transfer composition actually circulating in the vapor compression circuit. The additives can in particular be selected from lubricants, stabilizers, surfactants, tracers, fluorescent agents, odorous agents, solubilizing agents and mixtures thereof.

When it (they) is (are) present, the stabilizer(s) preferably represent(s) at most 5% by weight in the heat-transfer composition. Among the stabilizers, mention may in particular be made of nitromethane, ascorbic acid, terephthalic acid, azoles such as tolytriazole or benzotriazole, phenolic compounds such as tocopherol, hydroquinone, t-butyl hydroquinone, 2,6-di-tert-butyl-4-methylphenol, epoxides (alkyl, optionally fluorinated or perfluorinated, or alkenyl or aromatic) such as n-butyl glycidyl ether, hexanediol diglycidyl ether, allyl diglycidyl ether, butylphenyl glycidyl ether, phosphites, phosphonates, thiols and lactones.

By way of lubricants, use may in particular be made of oils of mineral origin, silicone oils, paraffins, naphthenes, synthetic paraffins, alkylbenzenes, poly- α -olefins, polyalkene glycols, polyol esters and/or polyvinyl ethers.

By way of tracers (capable of being detected), mention may be made of hydrofluorocarbons, deuterated hydrofluorocarbons, deuterated hydrocarbons, perfluorocarbons, fluoroethers, brominated compounds, iodinated compounds, alcohols, aldehydes, ketones, nitrous oxide and combinations thereof. The tracer is different than the heat-transfer compound(s) making up the heat-transfer fluid.

By way of solubilizing agents, mention may be made of hydrocarbons, dimethyl ether, polyoxyalkylene ethers, amides, ketones, nitriles, chlorocarbons, esters, lactones, aryl ethers, fluoroethers and 1,1,1-trifluoroalkanes. The solubilizing agent is different than the heat-transfer compound(s) making up the heat-transfer fluid.

By way of fluorescent agents, mention may be made of naphthalimides, perylenes, coumarins, anthracenes, phenanthracenes, xanthenes, thioxanthenes, naphthoxanthenes, fluoresceins and derivatives and combinations thereof.

By way of odorous agents, mention may be made of alkyl acrylates, allyl acrylates, acrylic acids, acryl esters, alkyl ethers, alkyl esters, alkynes, aldehydes, thiols, thioethers, disulfides, allyl isothiocyanates, alkanolic acids, amines, norbornenes, norbornene derivatives, cyclohexene, aromatic heterocyclic compounds, ascaridole, o-methoxy(methyl) phenol and combinations thereof.

The compositions according to the invention can also be used as an expansion agent, an aerosol or a solvent.

EXAMPLES

The following examples illustrate the invention without limiting it.

Example 1—Method for Calculating the Properties of the Heat-Transfer Fluids in the Various Configurations Envisioned

The RK-Soave equation is used for the calculation of the densities, enthalpies, entropies and liquid/vapor equilibrium data of the mixtures. The use of this equation requires knowledge of the properties of the pure substances used in the mixtures in question and also the interaction coefficients for each binary mixture.

The data necessary for each pure substance are the boiling point, the critical temperature and the critical pressure, the pressure curve as a function of the temperature from the boiling point up to the critical point, and the saturated liquid and saturated vapor densities as a function of the temperature.

The data with regard to HFCs are published in the ASHRAE Handbook 2005, chapter 20, and are also available under Refprop (software developed by NIST for the calculation of the properties of refrigerant fluids).

The HFO temperature-pressure curve data are measured by the static method. The critical temperature and the critical pressure are measured using a C80 calorimeter sold by Setaram. The densities, at saturation as a function of the temperature, are measured by means of the vibrating-tube densimeter technology developed by the laboratories of the école de Mines de Paris [French Engineering School].

The RK-Soave equation uses coefficients of binary interaction to represent the behavior of products in mixtures. The coefficients are calculated according to the experimental liquid/vapor equilibrium data.

The technique used for the liquid/vapor equilibrium measurements is the static analytical cell method. The equilibrium cell comprises a sapphire tube and is equipped with two Rolsitm electromagnetic samplers. It is immersed in a cryothermostat bath (Huber HS40). Magnetic stirring driven by a magnetic field rotating at a variable speed is used to accelerate the reaching of the equilibria. The sample analysis is carried out by gas chromatography (HP5890 series II) using a katharometer (TCD).

The liquid/vapor equilibrium measurements on the binary mixture HFC-32/HFO-1234ze are carried out for the following isotherm: 15° C.

The liquid/vapor equilibrium measurements on the binary mixture HFC-134a/HFO-1234ze are carried out for the following isotherm: 20° C.

The liquid/vapor equilibrium measurements on the binary mixture HFC-134a/HFO-1234ze are carried out for the following isotherm: 15° C.

The liquid/vapor equilibrium measurements on the binary mixture HFC-32/HFO-1234yf are carried out for the following isotherms: 70° C., 30° C., -10° C.

The liquid/vapor equilibrium measurements on the binary mixture HFO-1234ze/HFO-1234yf are carried out for the following isotherm: 18° C.

The liquid/vapor equilibrium data for the binary mixture HFC-152a/HFC-32 are available under Refprop. Two isotherms (-20° C. and 20° C.) and two isobars (1 bar and 25 bar) are used for the calculation of the interaction coefficients for this binary mixture.

The liquid/vapor equilibrium data for the binary mixture HFC-134a/HFC-32 are available under Refprop. Two isotherms (-20° C. and 20° C.) and two isobars (1 bar and 30 bar) are used for the calculation of the interaction coefficients for this binary mixture.

A compression system equipped with a countercurrent evaporator and condenser, with a screw compressor and with an expansion valve is considered.

The system operates with 15° C. of overheat and 5° C. of undercooling. The minimum temperature difference between the secondary fluid and the refrigerant fluid is considered to be about 5° C.

The isentropic efficiency of the compressors depends on the compression ratio. This efficiency is calculated according to the following equation:

$$\eta_{isen} = a - b(\tau - c)^2 - \frac{d}{\tau - e} \quad (1)$$

For a screw compressor, the constants a, b, c, d and e of the isentropic efficiency equation (1) are calculated according to the standard data published in the "Handbook of air conditioning and refrigeration", page 11.52.

The coefficient of performance (COP) is defined as being the useful power supplied by the system over the power provided or consumed by the system.

The Lorenz coefficient of performance (COPLorenz) is a reference coefficient of performance. It depends on temperatures and is used to compare the COPs of the various fluids.

The Lorenz coefficient of performance is defined as follows (the temperatures T are in K):

$$T_{average}^{condenser} = T_{inlet}^{condenser} - T_{outlet}^{condenser} \quad (2)$$

$$T_{average}^{evaporator} = T_{outlet}^{evaporator} - T_{inlet}^{evaporator} \quad (3)$$

The Lorenz COP in the case of conditioned air and of refrigeration is:

$$COP_{Lorenz} = \frac{T_{average}^{evaporator}}{T_{condenser}^{average} - T_{average}^{evaporator}} \quad (4)$$

The Lorenz COP in the case of heating is:

$$COP_{Lorenz} = \frac{T_{condenser}^{average}}{T_{condenser}^{average} - T_{average}^{evaporator}} \quad (5)$$

For each composition, the coefficient of performance of the Lorenz cycle is calculated as a function of the corresponding temperatures.

In low-temperature refrigeration mode, the compression system operates between an inlet temperature of the refrigerant fluid at the evaporator of -30° C. and an inlet temperature of the refrigerant fluid at the condenser of 40° C. The system provides refrigeration at -25° C.

In moderate-temperature heating mode, the compression system operates between an inlet temperature of the refrigerant fluid at the evaporator of -5° C. and a temperature at the beginning of the condensation of the refrigerant fluid at the condenser of 50° C. The system supplies heat at 45° C.

In moderate-temperature cooling mode, the compression system operates between an inlet temperature of the refrigerant fluid at the evaporator of -5° C. and a temperature at the beginning of the condensation of the refrigerant fluid at the condenser of 50° C. The system provides refrigeration at 0° C.

In the tables that follow, "Temp. evap outlet" denotes the temperature of the fluid at the outlet of the evaporator, "Temp. comp outlet" denotes the temperature of the fluid at the outlet of the compressor, "T cond outlet" denotes the temperature of the fluid at the outlet of the condenser, "evap P" denotes the pressure of the fluid in the evaporator, "cond P" denotes the pressure of the fluid in the condenser, "Ratio (w/w)" denotes the compression ratio, "Glide" denotes the temperature glide, "comp efficiency" denotes the efficiency of the compressor, "% CAP" denotes the volumetric capacity of the fluid relative to the reference fluid indicated on the first line, "% COP/COPLorenz" denotes the ratio of the COP of the system relative to the COP of the corresponding Lorenz cycle, "Psat liquid" denotes the liquid saturation pressure, "Psat vapor" denotes the vapor saturation pressure, and "% diff in pressure" denotes the difference between these two pressures, expressed as a percentage.

Example 2—Results for a Low-Temperature Refrigeration, Comparison with R404a and R407c

HFC-32/HFC-134a/HFO-1234ze Mixture:

Composition (%)	Temp sortie évap (° C.)	Temp sortie comp (° C.)	T sortie cond (° C.)	evap P (bar)	cond P (bar)	Taux (p/p)	Glide	rendement comp	% CAP	% COP/COPLorenz		
R404A	-30	101	40	2.1	18.1	8.8	0.46	53.8	100	32		
R407C	-26	131	35	1.7	15.3	9.0	4.48	51.9	108	35		
HFC-32	HFC-134a	HFO-1234ze										
25	40	35	-24	133	33	1.4	12.8	9.1	5.64	51.1	94	36
35	60	5	-25	144	34	1.7	14.9	8.9	4.97	52.6	111	37
35	50	15	-25	140	34	1.7	14.7	8.8	5.38	53.6	111	37
35	40	25	-24	136	33	1.7	14.4	8.7	5.90	54.5	110	38
35	30	35	-24	132	33	1.6	14.2	8.6	6.44	55.5	110	39
35	20	45	-23	128	32	1.6	13.9	8.5	6.99	56.3	110	40
35	10	55	-22	126	32	1.6	13.6	8.4	7.53	57.0	109	40

-continued

50	45	5	-25	153	35	2.0	17.1	8.6	4.83	55.0	130	38
50	35	15	-25	148	34	2.0	16.9	8.5	5.30	56.0	130	39
50	25	25	-24	143	34	2.0	16.6	8.4	5.89	57.1	130	40
50	15	35	-23	139	33	2.0	16.3	8.2	6.52	58.1	131	41
50	5	45	-23	136	32	2.0	16.0	8.1	7.14	59.1	131	41

HFO-1234yf/HFC-32/HFO-1234ze Mixture:

Composition (%)	Temp sortie évap (° C.)	Temp sortie comp (° C.)	T sortie cond (° C.)	evap P (bar)	cond P (bar)	Taux (p/p)	Glide	rendement comp	% CAP	% COP/ COPLorenz
R404A	-30	101	40	2.1	18.1	8.8	0.46	53.8	100	32
R407C	-26	131	35	1.7	15.3	9.0	4.48	51.9	108	35

HFO-1234yf HFC-32 HFO-1234ze

70	25	5	-25	103	32	1.8	14.7	8.1	5.27	58.9	107	40
60	25	15	-24	105	32	1.7	14.3	8.2	5.65	58.5	105	39
50	25	25	-24	106	32	1.7	13.8	8.2	6.14	58.4	103	40
40	25	35	-23	107	31	1.6	13.3	8.2	6.62	58.3	102	40
30	25	45	-23	108	31	1.6	12.8	8.3	7.04	58.0	99	40
60	35	5	-25	113	34	2.1	16.6	8.1	5.06	59.5	122	40
50	35	15	-24	114	33	2.0	16.1	8.1	5.63	59.4	120	40
40	35	25	-24	114	32	1.9	15.4	8.0	6.29	59.8	119	41
30	35	35	-23	114	31	1.8	14.8	8.0	6.93	60.0	117	41
20	35	45	-23	116	31	1.8	14.2	8.0	7.46	59.8	115	42
10	35	55	-22	118	31	1.7	13.7	8.1	7.85	59.1	112	42
45	50	5	-26	132	36	2.3	19.3	8.3	3.72	57.9	138	38
35	50	15	-25	132	35	2.3	18.5	8.2	4.66	58.5	137	39
25	50	25	-24	131	34	2.2	17.6	8.1	5.63	59.3	136	40
15	50	35	-24	131	33	2.1	16.8	8.0	6.49	59.8	135	41
5	50	45	-23	133	32	2.0	16.2	8.0	7.17	59.8	132	42

HFC-32/HFC-152a/HFO-1234ze Mixture:

Composition (%)	Temp sortie évap (° C.)	Temp sortie comp (° C.)	T sortie cond (° C.)	evap P (bar)	cond P (bar)	Taux (p/p)	Glide	rendement comp	% CAP	% COP/ COPLorenz
R404A	-30	101	40	2.1	18.1	8.8	0.46	53.8	100	32
R407C	-26	131	35	1.7	15.3	9.0	4.48	51.9	108	35

HFC-32 HFC-152a HFO-1234ze

35	30	35	-24	152	31	1.5	13.2	9.1	6.21	51.3	105	37
35	20	45	-23	140	31	1.5	13.1	8.8	6.96	54.0	106	39
35	10	55	-22	130	31	1.5	13.1	8.5	7.65	56.3	108	40
50	35	15	-24	176	33	1.7	15.7	9.2	5.96	50.4	122	36
50	25	25	-24	162	33	1.8	15.7	8.8	6.39	53.4	125	38
50	15	35	-23	148	32	1.8	15.6	8.4	7.14	56.6	128	40
50	5	45	-22	137	32	1.9	15.7	8.1	7.64	59.0	130	42

Example 3—Results for a Low-Temperature Refrigeration, Comparison with R410a

50

HFC-32/HFC-134a/HFO-1234ze Mixture:

Composition (%)	Temp sortie évap (° C.)	Temp sortie comp (° C.)	T sortie cond (° C.)	evap P (bar)	cond P (bar)	Taux (p/p)	Glide	rendement comp	% CAP	% COP/ COPLorenz
R410A	-30	153	40	2.7	24.2	8.9	0.06	52.5	100	33

HFC-32 HFC-134a HFO-1234ze

65	30	5	-26	167	36	2.2	19.4	8.6	3.91	55.2	96	38
65	20	15	-26	162	36	2.3	19.1	8.5	4.40	56.1	96	39
65	10	25	-25	157	35	2.3	18.9	8.4	5.07	57.3	97	39
80	15	5	-28	185	38	2.5	21.7	8.7	2.49	54.1	105	37
80	5	15	-27	180	37	2.5	21.5	8.6	3.01	54.9	105	37
90	5	5	-29	199	39	2.6	23.3	8.9	1.34	53.0	110	35

HFO-1234yf/HFC-32/HFO-1234ze Mixture:

Composition (%)			Temp sortie évap (° C.)	Temp sortie comp (° C.)	T sortie cond (° C.)	evap P (bar)	cond P (bar)	Taux (p/p)	Glide	rendement comp	% CAP	% COP/ COPLorenz
R410A			-30	153	40	2.7	24.2	8.9	0.06	52.5	100	33
HFO-1234yf	HFC-32	HFO-1234ze										
30	65	5	-28	155	38	2.5	21.4	8.5	2.22	55.8	99	37
20	65	15	-26	154	37	2.4	20.5	8.4	3.55	56.7	99	38
10	65	25	-25	153	35	2.3	19.4	8.3	4.76	57.8	98	39
15	80	5	-29	180	39	2.6	23.0	8.8	1.19	53.9	106	36
5	80	15	-27	179	38	2.5	21.9	8.7	2.69	54.9	106	37
5	90	5	-29	198	39	2.7	23.8	8.9	0.82	52.8	110	35

15

HFC-32/HFC-152a/HFO-1234ze Mixture:

Composition (%)			Temp sortie évap (° C.)	Temp sortie comp (° C.)	T sortie cond (° C.)	evap P (bar)	cond P (bar)	Taux (p/p)	Glide	rendement comp	% CAP	% COP/ COPLorenz
R410A			-30	153	40	2.7	24.2	8.9	0.06	52.5	100	33
HFC-32	HFC-152a	HFO-1234ze										
65	20	15	-24	180	35	2.1	18.4	8.9	5.51	52.6	93	36
65	10	25	-24	164	34	2.2	18.4	8.5	5.92	56.0	95	39
80	15	5	-26	201	37	2.3	21.2	9.1	4.14	51.2	102	34
80	5	15	-26	185	37	2.4	21.3	8.8	3.70	54.1	104	36
90	5	5	-28	205	39	2.6	23.1	9.0	2.20	52.0	109	35

30

Example 4—Results for a Moderate-Temperature Cooling, Comparison with HFC-134a

HFC-32/HFC-134a/HFO-1234ze Mixture:

Composition (%)			Temp sortie évap (° C.)	Temp sortie comp (° C.)	T sortie cond (° C.)	evap P (bar)	cond P (bar)	Taux (p/p)	Glide	rendement comp	% CAP	% COP/ COPLorenz
R134a			-5	81	50	2.4	13.2	5.4	0.00	75.9	100	54
HFC-32	HFC-134a	HFO-1234ze										
5	25	70	-3	77	46	2.3	12.0	5.1	2.38	77.3	99	55
5	35	60	-3	78	47	2.4	12.3	5.1	2.22	77.2	101	55
5	45	50	-3	79	47	2.5	12.7	5.1	2.05	77.2	103	55
5	55	40	-3	80	47	2.5	13.0	5.1	1.88	77.2	105	55
5	65	30	-3	80	48	2.6	13.3	5.1	1.70	77.2	107	55
5	75	20	-3	81	48	2.6	13.6	5.1	1.53	77.2	109	55
5	85	10	-4	82	48	2.7	13.8	5.1	1.37	77.2	112	55
15	5	80	1	79	42	3.0	13.3	4.5	6.02	79.6	128	58
15	15	70	1	80	43	3.0	13.7	4.5	5.52	79.5	129	58
15	25	60	0	81	44	3.1	14.0	4.5	5.10	79.4	130	58
15	35	50	0	82	44	3.1	14.3	4.6	4.72	79.3	132	57
15	45	40	-1	83	44	3.2	14.6	4.6	4.36	79.2	133	57
15	55	30	-1	84	45	3.2	15.0	4.6	4.03	79.1	135	57
15	65	20	-1	85	45	3.3	15.2	4.7	3.71	79.0	136	57
15	75	10	-2	86	46	3.3	15.5	4.7	3.44	78.9	138	57

55

HFO-1234yf/HFC-32/HFO-1234ze Mixture:

Composition (%)			Temp sortie évap (° C.)	Temp sortie comp (° C.)	T sortie cond (° C.)	evap P (bar)	cond P (bar)	Taux (p/p)	Glide	rendement comp	% CAP	% COP/ COPLorenz
R134a			-5	81	50	2.4	13.2	5.4	0.00	75.9	100	54
HFO-1234yf	HFC-32	HFO-1234ze										
25	5	70	-2	73	46	2.4	11.9	4.9	2.89	78.1	98	55
35	5	60	-2	72	46	2.5	12.3	4.8	2.85	78.3	101	55
45	5	50	-2	72	46	2.6	12.7	4.8	2.75	78.5	103	55

-continued

55	5	40	-2	71	46	2.7	13.0	4.7	2.60	78.7	106	55
5	15	80	1.2	78	42	3.0	13.3	4.4	6.23	79.8	129	58
15	15	70	1.1	78	42	3.2	13.6	4.3	6.13	80.1	131	58
25	15	60	1.0	77	42	3.3	14.0	4.3	6.03	80.2	134	58
35	15	50	0.9	76	42	3.4	14.5	4.2	5.90	80.3	138	58
45	15	40	0.7	76	43	3.6	14.9	4.2	5.71	80.4	142	58
55	15	30	0.5	76	43	3.7	15.4	4.2	5.47	80.4	145	58
65	15	20	0.2	75	43	3.8	15.9	4.2	5.19	80.5	148	57
75	15	10	-0.1	75	43	3.9	16.2	4.2	4.93	80.5	149	57

HFC-32/HFC-152a/HFO-1234ze Mixture:

Composition (%)			Temp sortie évap (° C.)	Temp sortie comp (° C.)	T sortie cond (° C.)	evap P (bar)	cond P (bar)	Taux (p/p)	Glide	rendement comp	% CAP	% COP/COPLorenz
HFC-134a			-5	81	50	2.4	13.2	5.4	0.00	75.9	100	54
HFC-32	HFC-152a	HFO-1234ze										
5	5	90	-3	76	45	2.2	11.2	5.1	2.32	77.1	93	56
5	15	80	-3	79	46	2.2	11.4	5.2	1.92	76.9	95	56
5	25	70	-3	81	47	2.3	11.7	5.2	1.75	76.9	98	56
5	35	60	-3	84	47	2.3	11.9	5.2	1.65	76.9	100	57
5	45	50	-3	86	47	2.3	12.0	5.2	1.55	77.0	103	57
5	55	40	-4	89	47	2.4	12.2	5.2	1.43	77.0	105	57
5	65	30	-4	91	47	2.4	12.3	5.2	1.29	77.0	106	58
5	75	20	-4	93	47	2.4	12.3	5.2	1.14	76.9	108	58
5	85	10	-4	95	47	2.4	12.3	5.2	0.97	76.8	108	58
15	5	80	1	80	42	2.9	13.1	4.5	5.61	79.4	126	59
15	15	70	0	83	43	2.9	13.2	4.6	4.89	79.1	126	59
15	25	60	0	85	43	2.9	13.3	4.7	4.54	79.0	128	59
15	35	50	-1	88	43	2.9	13.5	4.7	4.28	78.9	130	59
15	45	40	-1	90	43	2.9	13.7	4.7	4.00	78.7	131	59
15	55	30	-1	93	43	2.9	13.7	4.8	3.70	78.6	132	59
15	65	20	-2	95	44	2.9	13.8	4.8	3.37	78.4	132	59
15	75	10	-2	98	44	2.8	13.7	4.9	3.04	78.1	132	59

Example 5—Results for a Moderate-Temperature Heating, Comparison with HFC-134a

HFC-32/HFC-134a/HFO-1234ze Mixture:

Composition (%)			Temp sortie évap (° C.)	Temp sortie comp (° C.)	T sortie cond (° C.)	evap P (bar)	cond P (bar)	Taux (p/p)	Glide	rendement comp	% CAPc	% COPc/COPLorenz
R134a			-5	81	50	2.4	13.2	5.4	0.00	75.9	100	63
HFC-32	HFC-134a	HFO-1234ze										
5	35	60	-3	78	47	2.4	12.3	5.1	2.22	77.2	99	64
5	45	50	-3	79	47	2.5	12.7	5.1	2.05	77.2	102	64
5	55	40	-3	80	47	2.5	13.0	5.1	1.88	77.2	104	64
5	65	30	-3	80	48	2.6	13.3	5.1	1.70	77.2	106	64
5	75	20	-3	81	48	2.6	13.6	5.1	1.53	77.2	108	64
5	85	10	-4	82	48	2.7	13.8	5.1	1.37	77.2	110	64
15	5	80	1	79	42	3.0	13.3	4.5	6.02	79.6	121	66
15	15	70	1	80	43	3.0	13.7	4.5	5.52	79.5	123	66
15	25	60	0	81	44	3.1	14.0	4.5	5.10	79.4	124	65
15	35	50	0	82	44	3.1	14.3	4.6	4.72	79.3	125	65
15	45	40	-1	83	44	3.2	14.6	4.6	4.36	79.2	127	65
15	55	30	-1	84	45	3.2	15.0	4.6	4.03	79.1	128	65
15	65	20	-1	85	45	3.3	15.2	4.7	3.71	79.0	130	65
15	75	10	-2	86	46	3.3	15.5	4.7	3.44	78.9	132	65

HFO-1234yf/HFC-32/HFO-1234ze Mixture:

Composition (%)			Temp sortie évap (° C.)	Temp sortie comp (° C.)	T sortie cond (° C.)	evap P (bar)	cond P (bar)	Taux (p/p)	Glide	rendement comp	% CAP	% COP/COPLorenz
R134a			-5	81	50	2.4	13.2	5.4	0.00	75.9	100	63
HFO-1234yf	HFC-32	HFO-1234ze										
35	5	60	-2	72	46	2.5	12.3	4.8	2.85	78.3	100	64
45	5	50	-2	72	46	2.6	12.7	4.8	2.75	78.5	102	64
55	5	40	-2	71	46	2.7	13.0	4.7	2.60	78.7	105	64
65	5	30	-3	71	46	2.8	13.4	4.7	2.41	78.8	107	64
5	15	80	1.2	78	42	3.0	13.3	4.4	6.23	79.8	122	66
15	15	70	1.1	78	42	3.2	13.6	4.3	6.13	80.1	125	66
25	15	60	1.0	77	42	3.3	14.0	4.3	6.03	80.2	129	66
35	15	50	0.9	76	42	3.4	14.5	4.2	5.90	80.3	132	66
45	15	40	0.7	76	43	3.6	14.9	4.2	5.71	80.4	136	66
55	15	30	0.5	76	43	3.7	15.4	4.2	5.47	80.4	139	66
65	15	20	0.2	75	43	3.8	15.9	4.2	5.19	80.5	142	66
75	15	10	-0.1	75	43	3.9	16.2	4.2	4.93	80.5	143	65

20

HFC-32/HFC-152a/HFO-1234ze Mixture:

Composition (%)			Temp sortie évap (° C.)	Temp sortie comp (° C.)	T sortie cond (° C.)	evap P (bar)	cond P (bar)	Taux (p/p)	Glide	rendement comp	% CAP	% COP/COPLorenz
HFC-134a			-5	81	50	2.4	13.2	5.4	0.00	75.9	100	63
HFC-32	HFC-152a	HFO-1234ze										
5	5	90	-3	76	45	2.2	11.2	5.1	2.32	77.1	91	64
5	15	80	-3	79	46	2.2	11.4	5.2	1.92	76.9	93	64
5	25	70	-3	81	47	2.3	11.7	5.2	1.75	76.9	95	65
5	35	60	-3	84	47	2.3	11.9	5.2	1.65	76.9	98	65
5	45	50	-3	86	47	2.3	12.0	5.2	1.55	77.0	100	65
5	55	40	-4	89	47	2.4	12.2	5.2	1.43	77.0	102	66
5	65	30	-4	91	47	2.4	12.3	5.2	1.29	77.0	103	66
5	75	20	-4	93	47	2.4	12.3	5.2	1.14	76.9	104	66
5	85	10	-4	95	47	2.4	12.3	5.2	0.97	76.8	104	66
15	5	80	1	80	42	2.9	13.1	4.5	5.61	79.4	120	66
15	15	70	0	83	43	2.9	13.2	4.6	4.89	79.1	119	66
15	25	60	0	85	43	2.9	13.3	4.7	4.54	79.0	121	67
15	35	50	-1	88	43	2.9	13.5	4.7	4.28	78.9	123	67
15	45	40	-1	90	43	2.9	13.7	4.7	4.00	78.7	124	67
15	55	30	-1	93	43	2.9	13.7	4.8	3.70	78.6	125	67
15	65	20	-2	95	44	2.9	13.8	4.8	3.37	78.4	125	67
15	75	10	-2	98	44	2.8	13.7	4.9	3.04	78.1	125	67

45

Example 6—Results for a Moderate-Temperature Cooling, Comparison with R404a and R407c

HFC-32/HFC-134a/HFO-1234ze Mixture:

Composition (%)			Temp sortie évap (° C.)	Temp sortie comp (° C.)	T sortie cond (° C.)	evap P (bar)	cond P (bar)	Taux (p/p)	Glide	rendement comp	% CAP	% COP/COPLorenz
R404A			-5	77	50	5.2	23.0	4.5	0.37	79.7	100	48
R407C			-1	89	45	4.5	19.8	4.4	4.46	79.9	114	56
HFC-32	HFC-134a	HFO-1234ze										
25	5	70	2	84	42	3.7	15.4	4.2	7.24	80.4	100	59
25	15	60	2	85	42	3.7	15.7	4.2	6.76	80.3	100	59
25	25	50	1	86	43	3.8	16.0	4.3	6.30	80.3	101	59
25	35	40	1	87	43	3.8	16.3	4.3	5.87	80.2	101	58
25	45	30	0	88	44	3.8	16.6	4.3	5.43	80.0	102	58
25	55	20	0	89	44	3.9	17.0	4.4	5.01	79.9	103	58
25	65	10	0	90	45	3.9	17.3	4.4	4.64	79.7	104	58
35	5	60	2	89	42	4.3	17.5	4.1	7.49	80.8	115	59
35	15	50	2	90	42	4.3	17.7	4.1	7.03	80.7	116	59
35	25	40	2	91	43	4.4	18.0	4.1	6.55	80.6	116	59

-continued

Composition (%)			Temp sortie evap (° C.)	Temp sortie comp (° C.)	T sortie cond (° C.)	evap P (bar)	cond P (bar)	Taux (p/p)	Glide	rendement comp	% CAP	% COP/ COPLorenz
35	35	30	1	92	43	4.4	18.4	4.2	6.05	80.5	116	59
35	45	20	1	93	44	4.4	18.7	4.2	5.56	80.3	117	58
35	55	10	0	95	44	4.4	19.0	4.3	5.12	80.2	117	58

HFO-1234yf/HFC-32/HFO-1234ze Mixture:

Composition (%)			Temp sortie evap (° C.)	Temp sortie comp (° C.)	T sortie cond (° C.)	evap P (bar)	cond P (bar)	Taux (p/p)	Glide	rendement comp	% CAP	% COP/ COPLorenz
R404A			-5	77	50	5.2	23.0	4.5	0.37	79.7	100	48
R407C			-1	89	45	4.5	19.8	4.4	4.46	79.9	114	56
HFO- 1234yf	HFC-32	HFO- 1234ze										
5	25	70	2.4	83	42	3.7	15.4	4.1	7.44	80.6	100	59
15	25	60	2.3	82	41	3.9	15.8	4.1	7.32	80.8	102	59
25	25	50	2.2	82	41	4.1	16.3	4.0	7.15	80.9	105	58
35	25	40	1.9	81	42	4.2	16.9	4.0	6.92	80.9	108	59
45	25	30	1.6	81	42	4.4	17.5	4.0	6.59	80.9	111	58
55	25	20	1.2	81	42	4.5	18.1	4.0	6.20	80.9	113	58
65	25	10	0.8	81	43	4.6	18.7	4.0	5.83	80.9	113	57
5	35	60	2.6	88	42	4.4	17.5	4.0	7.63	80.9	116	59
15	35	50	2.4	87	41	4.5	18.0	4.0	7.40	81.0	119	59
25	35	40	2.1	87	42	4.7	18.7	3.9	7.05	81.1	122	59
35	35	30	1.6	87	42	4.9	19.4	4.0	6.58	81.0	124	58
45	35	20	1.0	87	43	5.1	20.3	4.0	6.01	80.9	125	57
5	50	45	1.9	97	43	5.2	20.8	4.0	6.88	80.9	136	58
15	50	35	1.2	96	43	5.4	21.6	4.0	6.25	80.9	138	58
25	50	25	0.4	96	44	5.6	22.6	4.1	5.43	80.8	139	57

HFC-32/HFC-152a/HFO-1234ze Mixture:

Composition (%)			Temp sortie evap (° C.)	Temp sortie comp (° C.)	T sortie cond (° C.)	evap P (bar)	cond P (bar)	Taux (p/p)	Glide	rendement comp	% CAP	% COP/ COPLorenz
R404A			-5	77	50	5.2	23.0	4.5	0.37	79.7	100	48
R407C			-1	89	45	4.5	19.8	4.4	4.46	79.9	114	56
HFC-32	HFC-152a	HFO- 1234ze										
25	5	70	2	85	41	3.6	15.1	4.2	7.26	80.4	99	60
25	15	60	2	87	41	3.5	15.0	4.3	6.82	80.2	100	60
25	25	50	1	90	41	3.5	15.2	4.3	6.42	80.1	100	60
25	35	40	1	92	42	3.5	15.3	4.4	5.98	79.8	101	60
25	45	30	1	95	42	3.4	15.4	4.5	5.54	79.6	101	60
25	55	20	0	98	42	3.4	15.4	4.5	5.15	79.4	100	60
25	65	10	0	100	42	3.3	15.3	4.6	4.84	79.1	100	60
35	5	60	3	90	41	4.2	17.1	4.1	7.89	80.8	116	60
35	15	50	3	92	41	4.1	17.0	4.1	7.68	80.7	116	60
35	25	40	2	95	41	4.1	17.1	4.2	7.18	80.4	116	60
35	35	30	2	98	42	4.0	17.3	4.3	6.61	80.2	115	60
35	45	20	1	101	42	3.9	17.3	4.4	6.17	79.9	115	60
35	55	10	1	103	42	3.8	17.2	4.5	5.96	79.6	114	60
50	5	45	2	98	42	5.0	20.3	4.0	7.48	80.9	135	59
50	15	35	2	101	42	4.9	20.3	4.1	7.22	80.7	135	59
50	25	25	2	105	43	4.8	20.4	4.2	6.59	80.3	133	58
50	35	15	1	108	43	4.7	20.4	4.4	6.20	80.0	132	58
50	45	5	1	111	43	4.6	20.2	4.4	6.34	79.8	131	58

Example 7—Results for a Moderate-Temperature Heating, Comparison with R404a and R407c

HFC-32/HFC-134a/HFO-1234ze Mixture:

Composition (%)	Temp sortie evap (° C.)	Temp sortie comp (° C.)	T sortie cond (° C.)	evap P (bar)	cond P (bar)	Taux (p/p)	Glide	rendement comp	% CAPc	% COPc/COPLorenz		
R404A	-5	77	50	5.2	23.0	4.5	0.37	79.7	100	58		
R407C	-1	89	45	4.5	19.8	4.4	4.46	79.9	107	64		
HFC-32	HFC-134a	HFO-1234ze										
35	5	60	2	89	42	4.3	17.5	4.1	7.49	80.8	104	66
35	15	50	2	90	42	4.3	17.7	4.1	7.03	80.7	105	66
35	25	40	2	91	43	4.4	18.0	4.1	6.55	80.6	105	66
35	35	30	1	92	43	4.4	18.4	4.2	6.05	80.5	106	65
35	45	20	1	93	44	4.4	18.7	4.2	5.56	80.3	106	65
35	55	10	0	95	44	4.4	19.0	4.3	5.12	80.2	107	65
50	5	45	2	98	43	5.1	20.6	4.0	6.86	80.9	122	65
50	15	35	1	98	43	5.1	20.9	4.1	6.30	80.8	122	65
50	25	25	1	100	44	5.1	21.2	4.1	5.70	80.6	122	65

HFO-1234yf/HFC-32/HFO-1234ze Mixture:

Composition (%)	Temp sortie evap (° C.)	Temp sortie comp (° C.)	T sortie cond (° C.)	evap P (bar)	cond P (bar)	Taux (p/p)	Glide	rendement comp	% CAPc	% COPc/COPLorenz		
R404A	-5	77	50	5.2	23.0	4.5	0.37	79.7	100	58		
R407C	-1	89	45	4.5	19.8	4.4	4.46	79.9	107	64		
HFO-1234yf	HFC-32	HFO-1234ze										
35	25	40	1.9	81	42	4.2	16.9	4.0	6.92	80.9	100	67
45	25	30	1.6	81	42	4.4	17.5	4.0	6.59	80.9	102	66
55	25	20	1.2	81	42	4.5	18.1	4.0	6.20	80.9	104	66
65	25	10	0.8	81	43	4.6	18.7	4.0	5.83	80.9	105	65
5	35	60	2.6	88	42	4.4	17.5	4.0	7.63	80.9	105	66
15	35	50	2.4	87	41	4.5	18.0	4.0	7.40	81.0	108	66
25	35	40	2.1	87	42	4.7	18.7	3.9	7.05	81.1	111	66
35	35	30	1.6	87	42	4.9	19.4	4.0	6.58	81.0	114	66
45	35	20	1.0	87	43	5.1	20.3	4.0	6.01	80.9	115	65
5	50	45	1.9	97	43	5.2	20.8	4.0	6.88	80.9	124	65
15	50	35	1.2	96	43	5.4	21.6	4.0	6.25	80.9	126	65

HFC-32/HFC-152a/HFO-1234ze Mixture:

Composition (%)	Temp evap outlet (° C.)	Temp comp outlet (° C.)	T cond outlet (° C.)	evap P (bar)	cond P (bar)	Ratio w/w	Glide	comp efficiency	% CAP	% COPc/COPLorenz		
R404A	-5	77	50	5.2	23.0	4.5	0.37	79.7	100	58		
R407C	-1	89	45	4.5	19.8	4.4	4.46	79.9	107	64		
HFC-32	HFO-152a	HFO-1234ze										
35	5	60	3	90	41	4.2	17.1	4.1	7.89	80.8	104	67
35	15	50	3	92	41	4.1	17.0	4.1	7.68	80.7	104	67
35	25	40	2	95	41	4.1	17.1	4.2	7.18	80.4	104	67
35	35	30	2	98	42	4.0	17.3	4.3	6.61	80.2	104	67
35	45	20	1	101	42	3.9	17.3	4.4	6.17	79.9	103	66
35	55	10	1	103	42	3.8	17.2	4.5	5.96	79.6	103	67
50	5	45	2	98	42	5.0	20.3	4.0	7.48	80.9	122	66
50	15	35	2	101	42	4.9	20.3	4.1	7.22	80.7	122	66
50	25	25	2	105	43	4.8	20.4	4.2	6.59	80.3	121	65
50	35	15	1	108	43	4.7	20.4	4.4	6.20	80.0	120	65
50	45	5	1	111	43	4.6	20.2	4.4	6.34	79.8	119	65

Example 8—Results for a Moderate-Temperature
Cooling, Comparison with R410a

HFC-32/HFC-134a/HFO-1234ze Mixture:

Composition (%)	Temp evap outlet (° C.)	Temp comp outlet (° C.)	T cond outlet (° C.)	evap P (bar)	cond P (bar)	Ratio w/w	Glide	comp efficiency	% CAP	% COP/ COPLorenz		
R410A	-5	103	50	6.8	30.7	4.5	0.07	79.5	100	50		
HFC-32	HFC-134a	HFO-1234ze										
65	5	30	0	107	45	5.8	24.0	4.1	5.22	80.6	100	57
65	15	20	0	108	45	5.8	24.3	4.2	4.52	80.4	99	57
65	25	10	-1	110	46	5.8	24.6	4.3	3.93	80.3	99	56
80	5	15	-2	118	47	6.3	27.5	4.3	2.83	80.0	107	55
80	15	5	-3	119	48	6.3	27.6	4.4	2.33	79.9	106	55
90	5	5	-4	126	49	6.6	29.6	4.5	1.23	79.6	111	54

HFO-1234yf/HFC-32/HFO-1234ze Mixture:

Composition (%)	Temp evap outlet (° C.)	Temp comp outlet (° C.)	T cond outlet (° C.)	evap P (bar)	cond P (bar)	Ratio w/w	Glide	comp efficiency	% CAP	% COP/ COPLorenz		
R404A	-5	77	50	5.2	23.0	4.5	0.37	79.7	100	58		
R407C	-1	89	45	4.5	19.8	4.4	4.46	79.9	107	64		
HFC-32	HFO-152a	HFO-1234ze										
35	5	60	3	90	41	4.2	17.1	4.1	7.89	80.8	104	67
35	15	50	3	92	41	4.1	17.0	4.1	7.68	80.7	104	67
35	25	40	2	95	41	4.1	17.1	4.2	7.18	80.4	104	67
35	35	30	2	98	42	4.0	17.3	4.3	6.61	80.2	104	67
35	45	20	1	101	42	3.9	17.3	4.4	6.17	79.9	103	66
35	55	10	1	103	42	3.8	17.2	4.5	5.96	79.6	103	67
50	5	45	2	98	42	5.0	20.3	4.0	7.48	80.9	122	66
50	15	35	2	101	42	4.9	20.3	4.1	7.22	80.7	122	66
50	25	25	2	105	43	4.8	20.4	4.2	6.59	80.3	121	65
50	35	15	1	108	43	4.7	20.4	4.4	6.20	80.0	120	65
50	45	5	1	111	43	4.6	20.2	4.4	6.34	79.8	119	65

HFC-32/HFC-152a/HFO-1234ze Mixture:

Composition (%)	Temp evap outlet (° C.)	Temp comp outlet (° C.)	T cond outlet (° C.)	evap P (bar)	cond P (bar)	Ratio w/w	Glide	comp efficiency	% CAP	% COP/ COPLorenz		
R410A	-5	103	50	6.8	30.7	4.5	0.07	79.5	100	50		
HFC-32	HFC-152a	HFO-1234ze										
65	5	30	1	108	45	5.7	23.7	4.2	5.78	80.5	100	57
65	15	20	0	112	45	5.5	23.8	4.3	5.37	80.1	99	56
65	25	10	0	116	46	5.4	23.8	4.4	5.12	79.7	97	56
80	5	15	-2	120	47	6.2	27.3	4.4	3.27	79.9	106	55
80	15	5	-2	124	48	6.0	27.2	4.5	3.36	79.5	105	54
90	5	5	-3	127	49	6.5	29.5	4.5	1.69	79.5	110	54

Example 9—Results for a Moderate-Temperature
Heating, Comparison with R410a

HFC-32/HFC-134a/HFO-1234ze Mixture:

Composition (%)	Temp evap outlet (° C.)	Temp comp outlet (° C.)	T cond outlet (° C.)	evap P (bar)	cond P (bar)	Ratio w/w	Glide	comp efficiency	% CAP	% COP/ COPLorenz
R410A	-5	103	50	6.8	30.7	4.5	0.07	79.5	100	59

-continued

Composition (%)			Temp evap outlet (° C.)	Temp comp outlet (° C.)	T cond outlet (° C.)	evap P (bar)	cond P (bar)	Ratio w/w	Glide	comp efficiency	% CAPc	% COPc/COPLorenz
HFC-32	HFC-134a	HFO-1234ze										
80	5	15	-2	118	47	6.3	27.5	4.3	2.83	80.0	103	62
80	15	5	-3	119	48	6.3	27.6	4.4	2.33	79.9	103	63
90	5	5	-4	126	49	6.6	29.6	4.5	1.23	79.6	108	62

HFO-1234yf/HFC-32/HFO-1234ze Mixture:

Composition (%)			Temp evap outlet (° C.)	Temp comp outlet (° C.)	T cond outlet (° C.)	evap P (bar)	cond P (bar)	Ratio w/w	Glide	comp efficiency	% CAP	% COP/COPLorenz
HFO-1234yf	HFC-32	HFO-1234ze										
R410A			-5	103	50	6.8	30.7	4.5	0.07	79.5	100	59
5	80	15	-2	118	48	6.4	28.0	4.4	2.50	80.0	104	62
15	80	5	-4	117	49	6.6	29.2	4.4	1.10	79.7	104	61
5	90	5	-4	125	49	6.7	30.2	4.5	0.74	79.6	108	61

25

HFC-32/HFC-152a/HFO-1234ze Mixture:

Composition (%)			Temp evap outlet (° C.)	Temp comp outlet (° C.)	T cond outlet (° C.)	evap P (bar)	cond P (bar)	Ratio w/w	Glide	comp efficiency	% CAP	% COPc/COPLorenz
HFC-32	HFC-152a	HFO-1234ze										
R410A			-5	103	50	6.8	30.7	4.5	0.07	79.5	100	59
80	5	15	-2	120	47	6.2	27.3	4.4	3.27	79.9	103	62
80	15	5	-2	124	48	6.0	27.2	4.5	3.36	79.5	101	62
90	5	5	-3	127	49	6.5	29.5	4.5	1.69	79.5	107	61

Example 10—Data Regarding the Quasi-Azeotropic Mixtures

HFC-32/HFO-1234yf/HFO-1234ze Mixture:

HFO-1234yf	HFC-32	HFO-1234ze	Temperature (° C.)	Psat liquid (bar)	Psat vapor (bar)	% diff in pressure
20	70	10	-5	6.4	5.9	9
28	70	2	-5	6.5	6.2	5
15	75	10	-5	6.5	6.0	8
23	75	2	-5	6.6	6.3	4
5	80	15	-5	6.5	5.9	9
10	80	10	-5	6.6	6.1	7
18	80	2	-5	6.7	6.5	3
2	86	12	-5	6.6	6.2	7
5	86	9	-5	6.7	6.3	5
12	86	2	-5	6.7	6.6	2
2	90	8	-5	6.7	6.4	4
5	90	5	-5	6.8	6.6	3
8	90	2	-5	6.8	6.7	1

40 HFC-32/HFC-134a/HFO-1234ze Mixture:

	HFC-32	HFC-134a	HFO-1234ze	Temperature (° C.)	Psat liquid (bar)	Psat vapor (bar)	% diff in pressure
45	80	18	2	-5	6.4	5.8	9
	86	2	12	-5	6.6	6.1	8
	86	5	9	-5	6.6	6.1	7
	86	12	2	-5	6.6	6.1	6
	90	2	8	-5	6.7	6.3	5
50	90	5	5	-5	6.7	6.4	5
	90	8	2	-5	6.7	6.4	5

The invention claimed is:

- 55 1. A ternary composition comprising: from 20 to 60% difluoromethane, from 5 to 78% 1,3,3,3-tetrafluoropropene, and from 2 to 60% 1,1,1,2-tetrafluoroethane.
- 60 2. The composition as claimed in claim 1, comprising: from 20 to 60% of difluoromethane, from 2 to 60% of 1,1,1,2-tetrafluoroethane, and from 10 to 70% of 1,3,3,3-tetrafluoropropene.
- 65 3. The composition as claimed in claim 1, comprising: from 25 to 50% of difluoromethane, from 5 to 60% of 1,1,1,2-tetrafluoroethane, and from 10 to 70% of 1,3,3,3-tetrafluoropropene.
4. A process for heating or cooling a fluid or a body by means of a vapor compression circuit containing a heat-

33

transfer fluid, said process successively comprising the evaporation of the heat-transfer fluid, the compression of the heat-transfer fluid, the condensation of the heat fluid and the expansion of the heat-transfer fluid, in which the heat-transfer fluid is a composition as claimed in claim 1.

5 **5.** A ternary composition comprising: from 80 to 98% of difluoromethane, from 1 to 18% of 1,1,1,2-tetrafluoroethane, and from 1 to 12% of 1,3,3,3-tetrafluoropropene.

6. The composition as claimed in claim 5, comprising: from 80 to 90% of difluoromethane, from 5 to 18% of 1,1,1,2-tetrafluoroethane, and from 5 to 12% of 1,3,3,3-tetrafluoropropene.

7. A process for heating or cooling a fluid or a body by means of a vapor compression circuit containing a heat-transfer fluid, said process successively comprising the evaporation of the heat-transfer fluid, the compression of the heat-transfer fluid, the condensation of the heat fluid and the

34

expansion of the heat-transfer fluid, in which the heat-transfer fluid is a composition as claimed in claim 5.

8. A ternary composition comprising: from 50 to 93% of difluoromethane, from 2 to 45% of 1,1,1,2-tetrafluoroethane, and from 5 to 48% of 1,3,3,3-tetrafluoropropene.

9. The composition as claimed in claim 8, comprising: from 65 to 93% of difluoromethane, from 2 to 30% of 1,1,1,2-tetrafluoroethane, and from 5 to 33% of 1,3,3,3-tetrafluoropropene.

10 **10.** A process for heating or cooling a fluid or a body by means of a vapor compression circuit containing a heat-transfer fluid, said process successively comprising the evaporation of the heat-transfer fluid, the compression of the heat-transfer fluid, the condensation of the heat fluid and the expansion of the heat-transfer fluid, in which the heat-transfer fluid is a composition as claimed in claim 8.

* * * * *