



US010883834B2

(12) **United States Patent**
Denaro

(10) **Patent No.:** US 10,883,834 B2
(45) **Date of Patent:** Jan. 5, 2021

(54) **DATA MINING IN A DIGITAL MAP DATABASE TO IDENTIFY INSUFFICIENT SUPERELEVATION ALONG ROADS AND ENABLING PRECAUTIONARY ACTIONS IN A VEHICLE**

(71) Applicant: **HERE Global B.V.**, Eindhoven (NL)

(72) Inventor: **Robert Denaro**, Long Grove, IL (US)

(73) Assignee: **HERE Global B.V.**, Eindhoven (NL)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 157 days.

(21) Appl. No.: **15/878,555**

(22) Filed: **Jan. 24, 2018**

(65) **Prior Publication Data**

US 2018/0156619 A1 Jun. 7, 2018

Related U.S. Application Data

(63) Continuation of application No. 14/808,015, filed on Jul. 24, 2015, now Pat. No. 9,909,881, which is a
(Continued)

(51) **Int. Cl.**
G01C 21/26 (2006.01)
G06F 16/29 (2019.01)
(Continued)

(52) **U.S. Cl.**
CPC **G01C 21/26** (2013.01); **B60W 30/18009**
(2013.01); **G06F 16/29** (2019.01);
(Continued)

(58) **Field of Classification Search**

None

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,270,708 A 12/1993 Kamishima
5,315,295 A 5/1994 Fujii

(Continued)

FOREIGN PATENT DOCUMENTS

EP 1069547 1/2001
EP 1104881 A1 6/2001

OTHER PUBLICATIONS

European Search Report for related European Application No. 09251231.8 dated Apr. 5, 2016.

(Continued)

Primary Examiner — Thomas G Black


Assistant Examiner — Ana D Thomas

(74) *Attorney, Agent, or Firm* — Lempia Summerfield Katz LLC

(57) **ABSTRACT**

Disclosed is a feature for a vehicle that enables taking precautionary actions in response to conditions on the road network around or ahead of the vehicle, in particular, a curved portion of a road with insufficient superelevation. A database that represents the road network is used to determine locations where curved sections of roads have insufficient superelevation (banking), i.e., where the superelevation is below a threshold. Then, precautionary action data is added to the database to indicate a location at which a precautionary action is to be taken about the location of insufficient superelevation. A precautionary action system installed in a vehicle uses this database, or a database derived therefrom, in combination with a positioning system to determine when the vehicle is at a location that corresponds to the location of a precautionary action. When the vehicle is at such a location, a precautionary action is taken by a vehicle system as the vehicle is approaching a location of insufficient superelevation.

37 Claims, 5 Drawing Sheets



Related U.S. Application Data

continuation of application No. 12/156,326, filed on May 30, 2008, now Pat. No. 9,121,716.

- (51) **Int. Cl.**
B60W 30/18 (2012.01)
B60W 10/06 (2006.01)
B60W 10/184 (2012.01)
- (52) **U.S. Cl.**
 CPC *B60W 10/06* (2013.01); *B60W 10/184* (2013.01); *B60W 2552/00* (2020.02); *B60W 2556/50* (2020.02)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,904,728	A	5/1999	Tamai	
5,983,389	A *	11/1999	Shimizu	H03M 13/151 714/781
6,092,014	A *	7/2000	Okada	G01P 15/00 340/438
6,141,619	A	10/2000	Sekine	
6,223,125	B1	4/2001	Hall	
6,226,389	B1	5/2001	Lemelson	
6,343,253	B1	1/2002	Matsuura et al.	
6,405,128	B1	6/2002	Bechtolsheim et al.	
6,411,896	B1 *	6/2002	Shuman	G01C 21/32 340/425.5
6,466,867	B1	10/2002	Sakashita	
6,470,265	B1	10/2002	Tanaka	
6,674,434	B1	1/2004	Chojnacki	
6,696,976	B1	2/2004	Hansen	
6,853,919	B2	2/2005	Kellum	
6,895,332	B2	5/2005	King	
7,043,357	B1	5/2006	Stankoulov et al.	
7,171,306	B2	1/2007	Hirose	
7,184,073	B2	2/2007	Varadarajan et al.	
7,194,347	B2	3/2007	Harumoto	
7,751,973	B2	7/2010	Ibrahim	
8,204,680	B1	6/2012	Dorum	
8,571,811	B1	10/2013	Mueller	
8,775,073	B2	7/2014	Denaro	
9,121,716	B2	9/2015	Denaro	
9,182,241	B2	11/2015	Denaro	
9,752,884	B2	9/2017	Denaro	
2001/0020902	A1	9/2001	Tamura	
2002/0188400	A1	12/2002	Sato et al.	
2002/0194016	A1	12/2002	Moribe et al.	
2003/0005765	A1	1/2003	Brudis et al.	
2003/0043059	A1	3/2003	Miller, Jr.	
2003/0090392	A1	5/2003	Schuessler	
2004/0030670	A1	2/2004	Barton	
2004/0107047	A1	6/2004	Joshi	
2004/0143390	A1	7/2004	King et al.	

2004/0143391	A1 *	7/2004	King	G01C 21/26 701/468
2004/0193347	A1	9/2004	Harumoto et al.	
2004/0201495	A1 *	10/2004	Lim	G08G 1/096758 340/905
2004/0201672	A1	10/2004	Varadarajan et al.	
2005/0149251	A1	7/2005	Donath et al.	
2005/0192746	A1 *	9/2005	King	G08G 1/0965 701/468
2005/0240334	A1	10/2005	Matsumoto et al.	
2005/0251335	A1	11/2005	Ibrahim	
2005/0264404	A1	12/2005	Franczyk et al.	
2006/0041372	A1	2/2006	Kubota et al.	
2006/0109095	A1	5/2006	Takata et al.	
2006/0287817	A1	12/2006	Nagel	
2007/0021910	A1	1/2007	Iwami et al.	
2007/0027583	A1	2/2007	Tamir et al.	
2007/0040705	A1	2/2007	Yoshioka et al.	
2007/0050127	A1	3/2007	Kellum et al.	
2007/0162019	A1	7/2007	Burns et al.	
2007/0192020	A1	8/2007	Brulle-Drews et al.	
2007/0222662	A1	9/2007	Toennesen et al.	
2007/0288158	A1	12/2007	Dorum	
2008/0004806	A1	1/2008	Kimura et al.	
2008/0033621	A1	2/2008	Nakamura et al.	
2008/0042815	A1	2/2008	Breed et al.	
2008/0046274	A1	2/2008	Geelen et al.	
2008/0169914	A1	7/2008	Albertson	
2008/0215238	A1	9/2008	Geelen et al.	
2008/0243380	A1	10/2008	Han	
2009/0144030	A1	6/2009	Witmer	
2009/0295598	A1	12/2009	Denaro	
2009/0295604	A1	12/2009	Denaro	
2009/0299615	A1	12/2009	Denaro	
2009/0299616	A1	12/2009	Denaro	
2009/0299617	A1	12/2009	Denaro	
2009/0299622	A1	12/2009	Denaro	
2009/0299624	A1	12/2009	Denaro	
2009/0299625	A1	12/2009	Denaro	
2009/0299626	A1	12/2009	Denaro	
2009/0299630	A1	12/2009	Denaro	
2009/0300035	A1	12/2009	Denaro	
2009/0300053	A1	12/2009	Denaro	
2009/0300067	A1	12/2009	Denaro	
2010/0001133	A1	1/2010	Kempa et al.	
2010/0121886	A1	5/2010	Koshiba et al.	
2016/0018227	A1	1/2016	Denaro	

OTHER PUBLICATIONS

European Office Action dated Mar. 8, 2018, European Office Action cited in the corresponding European Application No. 09 251 231.8; dated Mar. 8, 2018; 6 pages.
 European Office Action for European Patent Application No. 09 251 231.8-1001 dated Oct. 23, 2020.

* cited by examiner




FIG. 1B




FIG. 1A




FIG. 2

FIG. 3




FIG. 4





FIG. 5



**DATA MINING IN A DIGITAL MAP
DATABASE TO IDENTIFY INSUFFICIENT
SUPERELEVATION ALONG ROADS AND
ENABLING PRECAUTIONARY ACTIONS IN
A VEHICLE**

REFERENCE TO RELATED APPLICATIONS

This application is a continuation under 37 C.F.R. § 1.53(b) of U.S. patent application Ser. No. 14/808,015 filed Jul. 24, 2015 U.S. Pat. No. 9,909,881, which is a continuation under 37 C.F.R. § 1.53(b) of U.S. patent application Ser. No. 12/156,326 filed May 30, 2008 U.S. Pat. No. 9,121,716 the entire disclosure of which is hereby incorporated by reference. The present patent application is related to patent application Ser. No. 12/156,264, filed on May 30, 2008, now U.S. Pat. No. 9,134,133, entitled "DATA MINING TO IDENTIFY LOCATIONS OF POTENTIALLY HAZARDOUS CONDITIONS FOR VEHICLE OPERATION AND USE THEREOF," the entire disclosure of which is incorporated by reference herein.

BACKGROUND

The present invention relates to a method and system that enables taking a precautionary action in a vehicle, such as providing a warning to a vehicle driver about a potentially difficult or hazardous driving condition on the road network.

Advanced driver assistance systems ("ADAS"), including active safety and fuel economy systems, have been developed to improve the comfort, efficiency, safety, and overall satisfaction of driving. Examples of these advanced driver assistance systems include adaptive headlight aiming, adaptive cruise control, lane departure warning and control, curve warning, speed limit notification, hazard warning, predictive cruise control, and adaptive shift control, as well as others. Some of these advanced driver assistance systems use a variety of sensor mechanisms in the vehicle to determine the current state of the vehicle and the current state of the roadway in front of the vehicle. These sensor mechanisms may include radar, infrared, ultrasonic and vision-oriented sensors, such as digital video cameras and lidar. Some advanced driver assistance systems also use digital map data. Digital map data can be used in advanced driver assistance systems to provide information about the road network, road geometry, road conditions and other items associated with the road and terrain around the vehicle. Digital map data is not affected by environmental conditions, such as fog, rain or snow. In addition, digital map data can provide useful information that cannot reliably be provided by cameras or radar, such as curvature, grade, bank, speed limits that are not indicated by signage, traffic and lane restrictions, etc. Further, digital map data can provide a predictive capability well beyond the range of other sensors or even beyond the driver's vision to determine the road ahead of the vehicle, around corners, over hills or beyond obstructions. Accordingly, digital map data can be a useful addition for some advanced driver assistance systems.

Although these kinds of systems provide useful features, there exists room for further improvements. For example, it would be useful to identify locations on the road network where a relatively high number of traffic accidents have occurred. However, statistics pertaining to accidents are maintained by various different administrative entities that use different formats, standards, reporting methods, reporting periods, etc. Accordingly, it is difficult to obtain consistent information about traffic accidents on roads in a large

geographic region, such as the entire United States or Europe. Moreover, data indicating locations where a statistically large number of traffic accidents occur may not indicate the causes of the accidents or how accidents can be avoided.

Accordingly, it is an objective to provide a system that facilitates taking a precautionary action in a vehicle, such as providing a warning to a vehicle operator, when approaching a location where accidents may occur.

SUMMARY

To address these and other objectives, the present invention comprises a feature that enables taking a precautionary action in a vehicle as the vehicle approaches the location of a curve that is banked outward instead of inward toward the center of the curve radius. The precautionary action may be a warning message provided to the vehicle driver to alert the vehicle driver about the curve that is banked outward so that the vehicle driver can pay extra attention. Alternatively, the precautionary action may be an actual modification of the operation or control of the vehicle, such as braking, accelerating, or maneuvering the vehicle, or activating a sensor. Alternatively, the precautionary action may be providing an input to an algorithm that also processes inputs from other sensors for taking such actions. In another alternative, the precautionary action may include a combination of any of these aforementioned actions.

According to another aspect, a database that represents the road network is used to determine locations where curves are banked outward instead of inward. Then, precautionary action data is added to the database to indicate a location at which a precautionary action is to be provided about the curve with that is banked outward.

According to further aspects, a precautionary action system installed in a vehicle uses this database, or a database derived therefrom, in combination with a positioning system, to determine when the vehicle is at a location that corresponds to the location where a precautionary action should be taken. When the vehicle is at such a location, the precautionary action is taken, such as providing a warning to the vehicle operator, as the vehicle is approaching a curve that is banked outward. Alternatively, the precautionary action may consist of an actual modification of the operation or control of the vehicle, such as braking, accelerating, or maneuvering the vehicle, or activating a sensor. Alternatively, the precautionary action may include providing an input to an algorithm that also processes inputs from other sensors for taking such actions. Alternatively, the precautionary action may be an adjustment of sensitivities of other ADAS applications such as increasing the control authority and sensitivity of a lane departure warning or control system to lane edge approach and violation. In another alternative, the precautionary action may include a combination of any of these aforementioned actions.

BRIEF DESCRIPTION OF THE DRAWINGS

FIGS. 1A and 1B illustrate a portion of a road network with a curve in which the superelevation (banking) is sloping outward.

FIG. 2 is a flowchart of a process that uses a database that represents a road network to identify conditions such as the one shown in FIG. 1.

FIG. 3 is a diagram of a data record formed by the process of FIG. 2.

FIG. 4 is a diagram of a vehicle system that uses data produced by the process of FIG. 2.

FIG. 5 is a flowchart of a process performed by the system of FIG. 4.

DETAILED DESCRIPTION OF THE DRAWINGS AND PRESENTLY PREFERRED EMBODIMENTS

FIG. 1A depicts a road segment **10**. The road segment **10** is located along a hill **12**. The road segment **10** is curved along a portion **14** thereof.

Superelevation refers to a property of the road. Specifically, the superelevation of a road refers to the transverse inclination of the road surface in a curved portion of the road. Superelevation is also referred to as banking. A positive superelevation refers to a transverse inclination in which the outside edge of the road (i.e., the side farthest from the center of the curve radius) is at a higher elevation than the inside edge. A negative superelevation refers to a transverse inclination in which the outside edge of the road is at a lower elevation than the inside edge. A neutral superelevation refers to a road surface in a curve in which the outside and inside edges are at the same elevation. Roads are often constructed with a positive superelevation in curves to counter centrifugal forces that might cause slippage. A road with neutral or negative superelevation in a curve typically cannot be driven as fast as a road with positive superelevation.

Referring to FIG. 1A, the road **10** is shown to have a negative superelevation in the curved portion **14**. The transverse inclination of the road **10** in the portion **14** is shown to slope away from the curve by an angle α .

FIG. 1B is an illustration of how the road **10** in FIG. 1A is represented by data contained in a map database (such as the database **110** in FIG. 2). The road segment **10** is represented by a data record that defines a line **16** that extends between two endpoints, or nodes, **18** and **20**. The location of the road segment **10** is defined by the data indicating the locations (e.g., geographic coordinates, including altitude) of the nodes. The data record that represents the road segment **10** includes data that indicates the shape of the road segment **10**. One way to represent the shape of the road segment is to define shape points along the road segment. Shape points indicate the geographic coordinates at points along the road segment between the nodes. In the case of a straight road segment, no shape points are required. However, in the case of a curved road segment, one or more shape points are used to define locations along the road segment. FIG. 1B shows several shape points, **22**, **24**, **26** . . . **34**, defined along the road segment between the endpoints, i.e., nodes **18** and **20**. Thus, the curved road segment **10** in FIG. 1A is represented by an approximation comprised of a series of short, straight lines **36**, as shown in FIG. 1B. (Alternatively, a database may represent a curved road segment by a curved line, such as a spline, clothoid, etc. In this alternative, data that defines the curved line is included in the database.)

The database representation of the curved road segment also includes data that indicates the superelevation along the road segment. One way to do this is to associate superelevation values with shape points defined for the curved road segment. In the case of a curved road represented by curved line, other methods may be used, such as indicating the superelevation at a point along the line.

FIG. 2 is a flowchart of a process **100**. The process **100** is performed by a software program or routine that is run on a

suitable computing platform, such as a database server, PC or plurality of PCs coupled together for parallel computing applications.

The process **100** uses a database **110** that contains data that represents the road network in a region. The region may be a country, such as the United States, Germany, France or Korea. Alternatively, the region may include several countries or an entire continent. According to another alternative, the region may include only a portion of a country, such as a state or several states or metropolitan areas.

The process **100** is performed by a map developer, such as NAVTEQ Corporation. Alternatively, the process **100** may be performed by another entity that has access to an editable version of a map database **110**. For example, the process may be performed by a customer or licensee of NAVTEQ, such as a manufacturer of navigation systems or active safety systems, or by a traffic information services company or by a government office at any level.

The database **110** is in a format that can be edited. That is, new or updated information can be added to the database **110**. Alternatively, the database **110** is in a format such that new information can be combined with the original data to form a new database that includes both the original data and new data. In one embodiment, the database is in an Oracle spatial format. Alternatively, the database may be in delivery format, such as GDF (Geographic Data File), SIF (Standard Interchange Format), or other formats, including proprietary formats.

As stated above, the database **110** contains data that represents the road network in the region. The database **110** contains information such as the locations (geographic coordinates, including altitude) of roads and intersections, road names, the three-dimensional shape of the roads including curvature, slope and bank, speed limits along roads, turn restrictions at intersections, addresses or address ranges along roads, the number of lanes each road has, lane width, lane markings, functional classes of roads, the locations of medians, and so on. The database may also contain information about other geographic features, such as bodies of water, parks, administrative areas (including municipal, state and country boundaries), and locations of points of interest, such as businesses, hospitals, police stations, and so on.

In FIG. 2, the process **100** examines each data record that represents a road segment (also referred to herein as a "link") to determine whether it represents one similar to the road segment **10** in FIG. 1A. (The process **100** may use a procedure that examines in turn each data record that represents each road segment represented in the entire database.) In one step, a data record that represents a link or road segment is read from the database **110** (Step **130**). This road segment record may include data (e.g., shape points) that indicate whether the road segment is curved. This data is evaluated (Step **134**). If the represented road segment is not curved, the process **100** proceeds to a step in which it is determined whether all the road segment records in the database have been examined (Step **138**). If there are more segment records to examine, the process **100** proceeds to get the next segment record (Step **130**) and continues.

Referring back to Step **136**, if the represented road segment is curved, the process **100** proceeds to obtain the data that indicates the superelevation along the road segment's curved portion (Step **142**). This superelevation data is evaluated (Step **144**). From an evaluation of the degree of curvature, as well as the superelevation information associated with the segment's curved portion, it is determined whether there exists insufficient superelevation (such as the

negative superelevation in the curved portion **14** shown in FIG. 1A). If examination of the segment's curvature and superelevation information indicates that there is sufficiently positive superelevation in a curved portion of the road, the process **100** proceeds to the step in which it is determined whether all the road segment records in the database have been examined (Step **138**) and if there are more segment records to examine, the process **100** proceeds to get the next segment record (Step **130**).

Referring back to Step **150**, if examination of the segment's curvature and superelevation information indicates that there is insufficient superelevation (i.e., negative, neutral or not sufficiently positive for the degree of curvature) along a curved portion of the road segment, the process **100** adds precautionary action data **160** to the database **110** (Step **156**). The precautionary action data **160** indicates the presence of a feature in the road network where a precautionary action may be taken.

In determining whether to add precautionary action data to the database **110**, a threshold may be used. For example, a threshold value of zero may be used. With a threshold value of zero, precautionary action data would be added for any curved section that has a negative superelevation. Alternatively, a threshold value may be set at other values, such as $-2.\text{degree}$. or $+2.\text{degree}$.

After the precautionary action data **160** is added to the database **110**, the process **100** proceeds to the step in which it is determined whether all the road segment records in the database have been examined (Step **138**) and if there are more segment records to examine, the process **100** proceeds to get the next segment record (Step **130**).

The process **100** ends when it is determined whether all the road segment records have been examined (Step **138**).

It is noted that the process **100**, above, performs a data mining function. The existence of the potentially difficult location, i.e., a curve with insufficient positive superelevation, is derived from data already collected and present in the database. It is noted that the process **100**, above, evaluates multiple data items in the original database, to determine whether the condition exists, in this case, insufficient positive superelevation. By evaluating these multiple data items, a determination is made whether these multiple data items describe the condition of interest. If these data items do describe the condition, a new data item, i.e., the precautionary action data, is added to the database.

The above process for determining whether a sufficiently positive superelevation exists can take into account other factors, such as speed limits, road surface, the presence and type of shoulders, and so on. According to this alternative, the threshold may take into account the speed limit along the road segment (which is also stored as data in the database **110**.) For example, a road segment with a 55 mph speed limit would have a threshold of $+10.\text{degree}$. defined as sufficiently positive. In the case, precautionary action data would be added if the superelevation were only $+8.\text{degree}$. On the other hand, a road segment with a 20 mph speed limit might have a threshold of $+1.\text{degree}$. defined as sufficiently positive so that superelevation of $+8.\text{degree}$. would not require including precautionary action data.

FIG. 3 is a diagram that shows a data record **200** in the database **110**. The data record **200** represents a road segment located in a geographic region. As explained above, the geographic region may include an entire country or continent. Accordingly, the database **110** includes many data records like the one shown in FIG. 3.

The data record **200** shown in FIG. 3 is exemplary and shows only one way to represent a road segment. Databases

may represent road segments in various different ways and may include different kinds of information. The present invention is not limited to any particular way of representing roads.

Referring to FIG. 3, various data are associated with the data record **200** that represents a road segment. This various data indicates features or attributes of the represented road segment. For example, associated with the data record is data that indicates the permitted direction(s) of travel. Also associated with the road segment record **200** are data that indicate a speed limit, a classification of the road segment (i.e., the type of road, such as controlled access, etc.), a rank (e.g., 1-4), the endpoints of the road segment, shape points (i.e., locations along the road segment between its endpoints). Also associated with the road segment records is data that indicate the successors at each endpoint. Successors are those road segments that connect to the represented road segment at each of its endpoints. The segment record **200** may identify these successors by reference to the data records that represent the successors.

In FIG. 3, the database **110** also includes precautionary action data **160**. The precautionary action data **160** is the data added to the database **110** by the process **100** in FIG. 2. In FIG. 3, the precautionary action data **160** is shown as added to the road segment record **200**. It should be understood that the process **100** adds precautionary action data **160** with respect to only certain records, i.e., records that represent those roads segments that meet the conditions identified by the process. Accordingly, the database **110** will contain data records that represent road segments that contain the precautionary action data **160** and other data records that represent road segments that do not contain the precautionary action data **160**.

In the embodiment shown in FIG. 3, the precautionary action data **160** is associated with the road segment identified as having insufficient superelevation along a curve. In this embodiment, the precautionary action data **160** includes several components. One component **160(1)** indicates a condition type. This condition type **160(1)** indicates the type of condition about which a precautionary action is to be taken, which in this case is an insufficient superelevation along a curve. This condition type **160(1)** component is used when different conditions are identified in the database **110** about which precautionary action may be taken.

Another component of the precautionary action data **160** is the precautionary action location **160(2)**. The precautionary action location **160(2)** indicates where along the represented road segment a precautionary action may be taken. The precautionary action location **160(2)** data may include multiple entries. For example, the precautionary action location **160(2)** may indicate where a warning may be provided to a vehicle driver to advise the driver about the upcoming condition, i.e., the insufficient superelevation along a curve. In the case of insufficient superelevation along a curve, the warning location **160(2)** may indicate a distance (e.g., x meters) from the curve. The location **160(2)** is determined based on an analysis of factors, such as the superelevation, curvature, the speed limit along the represented road segment, the road classification, and possibly other factors. These factors may be determined from other data contained in the database **110**. According to one example, the location **160(2)** may indicate that a warning should be provided at a location 400 meters along the road segment from the curve.

The precautionary action location **160(2)** may also indicate where a vehicle control action should be taken, such as tightening the seatbelts, pre-loading or engaging the brakes,

tightening sensitivities of lane departure warning systems or stability control systems, etc. This may be a different location from where the precautionary warning is provided and would be based on a different analysis of factors.

Another component of the precautionary action data **160** is direction data **160(3)**. The direction data **160(3)** indicates the direction along the represented road segment where the precautionary action should be taken. In this case, the direction data **160(3)** may indicate both directions. (Note that the database **110** may indicate a direction along a road segment as positive or negative based on the relative latitude and longitude of the road segment endpoints.)

Another component of the precautionary action data **160** is a reference **160(4)**. In this case, the reference **160(4)** indicates the location of the insufficient superelevation along a curve. The reference **160(4)** may refer to shape points that represent the curved portion of the road.

The precautionary action data **160** described in FIG. **3** is one way that this data may be included in a database that represents a geographic region. There are alternative ways to include the precautionary action data. For example, the precautionary action data may be included as separate data records in the database **110**. If included as separate data records, the precautionary action data may be associated with the road segments to which they apply by pointers or other suitable data references. Alternatively, the precautionary action data may be associated with node data records, instead of the road segments leading to the intersections. Various other ways exist and the present invention is not intended to be restricted to any specific implementation.

FIG. **4** is a diagram depicting components of a vehicle **300**. The vehicle **300** is operated on a road network, such as the road network represented by the database **110** in FIG. **2**. The vehicle **300** may be an automobile, truck, bicycle, motorcycle, etc.

The vehicle **300** includes systems **310**. In this embodiment, the vehicle systems **310** include a positioning system **320**. The positioning system **320** determines the position of the vehicle **300** on the road network. The positioning system **320** includes appropriate hardware and software to determine the position of the vehicle **300**. For example, the positioning system may include hardware **322** that includes a GPS unit, an accelerometer, wheel speed sensors, etc. The positioning system **320** also includes a positioning application **324**. The positioning application **324** is a software application that uses outputs from the positioning system hardware **322** and information from a map database **330**. The positioning application **324** determines the position of the vehicle **300** with respect to the road network, including the location of the vehicle **300** along a road segment and a direction of travel of the vehicle along the road segment.

In one embodiment, the map database **330** is located in the vehicle. In an alternative embodiment, the map database **330** may be located remotely and accessed by the vehicle systems **310** using a wireless communication system. In yet another embodiment, part of the map database **330** may be located locally in the vehicle and part of the map database **330** may be located remotely.

The map database **330** is stored on a computer readable medium **334**. The computer-readable medium may be implemented using any suitable technology. For example, the computer readable medium may be a DVD disk, a CD-ROM disk, a hard disk, flash memory, or any other medium, or a plurality of media.

The map database **330** includes data that represents the geographic region in which the vehicle **300** is being operated. The map database **330** may represent the same geo-

graphic region as the database **110** in FIG. **2**, or alternatively, the map database **330** may represent only a portion of the region represented by the database **110**.

The map database **330** used by the vehicle systems **310** may be in a different format from the database **110** in FIG. **2**. The map database **330** is formed or derived from the database **110** by a compilation process that organizes and presents the data in a form and format that specifically facilitates its use for performing specific functions. For example, the map database **330** may be separated into different collections of data that are used for specific functions, such as vehicle positioning, route calculation, map display, route guidance, destination selection, and so on. The map database **330** may also be organized into groupings spatially. One kind of compiled database format is disclosed in U.S. Pat. No. 5,968,109, the entire disclosure of which is incorporated by reference herein. Various other compiled database formats exist, including proprietary formats, and the disclosed embodiment(s) are not limited to any particular format.

Included among the vehicle systems **310** in FIG. **4** is a navigation system **340**. The navigation system **340** uses outputs from the positioning system **320** and data from the map database **330** to provide navigation-related features to a vehicle user, e.g., the vehicle operator or passenger. The navigation system **340** includes applications for route calculation **344**, map display **346**, as well as possibly other applications. The navigation system **340** provides the navigation-related features to the vehicle user via a user interface **354**. (The navigation system **340** is optional and may be omitted.)

Also included among the vehicle systems **310** is a precautionary action application **350**. The precautionary action application **350** uses outputs from the positioning system **320** and data from the map database **330** to take precautionary actions, such as provide warnings to the vehicle operator. The precautionary action application **350** provides the warning to the vehicle operator via the user interface **354**.

FIG. **4** also shows that precautionary action application **350** provides an output to vehicle control systems and actuator **356**. The vehicle control systems and actuator are operatively connected to various vehicle mechanical systems, such as the vehicle's brakes **356(1)**, engine **356(2)**, seatbelts (including tensioners) **356(3)**, airbags **356(4)**, stability control algorithms, as well as other system systems **356(5)**.

FIG. **5** is a flowchart **400** showing operation of the precautionary action application **350** (in FIG. **4**). As the vehicle **300** (in FIG. **4**) is being operated on a road, the precautionary action application **350** obtains the current vehicle position from the positioning system **320** (Step **410**). (During vehicle operation, the positioning system **320** continuously determines the current geographic position of the vehicle **300** as the vehicle is being operated using data from the map database **330**.) The positioning system **320** provides the precautionary action application with data that indicates the current vehicle position with respect to the road network as represented by the map database **330**. Specifically, the location of the vehicle along a road segment and the direction of travel of the vehicle along the road segment are determined and provided to the precautionary action application **350**.

Next, the process **400** obtains data from the map database **330** that represents the geographic features (i.e., roads, intersections, etc.) at the current location of the vehicle and in the direction in which the vehicle is heading (Step **420**). In one embodiment, an electronic horizon is used (Step **430**).

Building an electronic horizon and using it to provide warnings are disclosed in U.S. Pat. Nos. 6,405,128 and 6,735,515 and U.S. patent application Ser. No. 11/400,151, the entire disclosures of which are incorporated by reference herein. Using an electronic horizon and/or the inventions disclosed in these patents and pending patent application is optional and the disclosed process **400** is not limited to using the electronic horizon technology.

After obtaining data from the map database **300** that represents the geographic features at the current location of the vehicle and in the direction in which the vehicle is heading, the process **400** includes the step of examining the data to determine whether any precautionary action data (**160** in FIG. **3**) is associated with the represented geographic features (Step **440**). If there is no precautionary action data associated with the represented geographic features, the process **400** loops back to get a new current vehicle position (Step **410**). On the other hand, if there is precautionary action data associated with the represented geographic features, the process **400** takes a precautionary action (Step **450**). The precautionary action may be a warning provided to the vehicle operator when the vehicle is at the location (i.e., **160(2)** in FIG. **3**) indicated by the precautionary action data. The warning may be provided via the user interface **354**. The warning may be an audible warning message or a visual warning.

The precautionary action is not limited to warnings, but may also include other actions. For example, in the case of a curve with insufficient superelevation, vehicle systems **356**, such as the brakes, engine or transmission, can be readied for a deceleration. In addition, the seatbelts may be tightened or the airbags set to deploy. As explained above, to facilitate these kinds of actions, additional information may be added to the warning data **160** (in FIG. **3**) to indicate the type of action as well as the location where the action should be taken.

Referring still to FIG. **5**, after taking the precautionary action, the process **400** loops back to get a new current vehicle position (Step **410**).

Alternative with Dynamic Data

The process (**400** in FIG. **5**) was described as a way to use the precautionary action data that had been stored in the map database to take an appropriate action in a vehicle when the vehicle is at or is approaching a location identified as having a potentially hazardous condition. This process uses a positioning system and map database in the vehicle to determine when the vehicle is at or is approaching such a location. The process may also take into account dynamic information. Dynamic information may include current traffic and weather conditions, ambient light conditions, road conditions (e.g., ice), and so on. The vehicle may include systems to obtain such information. For example, the vehicle may have a traffic data receiver that obtains real-time traffic information, e.g., RDS-TMC messages. The process **400** may use the dynamic information in combination with the precautionary action data. For example, the process may modify the location at which a warning is provided. As an example, if weather conditions indicate that it is raining, the location at which a warning is provided to the vehicle driver about an upcoming curve with insufficient superelevation may be modified, i.e., adjusted to a point farther in advance of the location of the hazardous condition, in order to give the vehicle operator additional time or distance. The process may even take certain actions only under certain conditions. For example, a warning about insufficient superelevation may be provided only during nighttime hours or during inclement weather conditions.

Verification

The process (**100** in FIG. **2**) was described as a way to automatically examine records in a database that represents roads to identify locations or conditions along the road network where a precautionary action might be taken. According to the described process, data is then added to indicate the location where the precautionary action should be taken. Alternatively, instead of automatically adding the precautionary action data to the database, the locations where such conditions are identified could be marked on a temporary basis. Then, a geographic analyst (or other human operator) could review some or all such temporarily marked locations. The analyst may conduct this review by physically traveling to the locations or by reviewing satellite or aerial photographs of the locations, or video taken while driving by the locations (previously or subsequently acquired either by the analyst or others including members of the public). Based on the review, the analyst then determines whether precautionary action data should be added to the database.

It is intended that the foregoing detailed description be regarded as illustrative rather than limiting and that it is understood that the following claims including all equivalents are intended to define the scope of the invention.

I claim:

1. A vehicle comprising:

- one or more vehicle mechanical systems;
 - a positioning system that determines a current location of the vehicle along a road of a road network relative to data representing a geographic region;
 - a database that contains data representing the geographic region in which the vehicle is being operated, wherein the data includes data that represents roads of the road network located in the geographic region and precautionary action data associated with a plurality of locations along the roads of the road network where one or more different hazardous conditions which may impair control of the vehicle exists, wherein each of the plurality of locations where the hazardous condition exists comprises a location along a road of the road network at which it has been determined, prior to approach of the location by the vehicle, based on the data in the database that represents roads of a road network, that a condition comprising a combination of a curved section of road and insufficient superelevation thereof for operation of a vehicle at a given speed exists at the location;
 - a precautionary action application, responsive to the positioning system and the database, that determines whether, based on the current location of the vehicle, the vehicle is approaching a location along a road of the road network associated with precautionary action data; and
 - a vehicle control system coupled with the one or more vehicle mechanical systems and responsive to the precautionary action application to actuate at least a subset of the one or more vehicle mechanical systems to take a precautionary action when the precautionary action application determines that the vehicle is approaching a location along a road of the road network associated with precautionary action data.
2. The vehicle of claim **1** wherein the condition further comprises the insufficiency of the superelevation exceeding a threshold based on a speed limit, road surface type, presence of shoulders, or a combination thereof.
3. The vehicle of claim **1** wherein the one or more vehicle mechanical systems comprise brakes, engine, seatbelts, airbags, or stability control.

11

4. The vehicle of claim 1 wherein the positioning system is further operative determine a direction of travel of the vehicle and wherein the precautionary action data further includes data that indicates a direction along a road segment at which a precautionary action is to be taken, wherein the precautionary action application is further operative to determine whether the vehicle is approaching the location along a road of the road network associated with precautionary action data in the direction along the road segment at which the precautionary action is to be taken, the vehicle control system being further responsive thereto.

5. The vehicle of claim 1 wherein the precautionary action data further includes data that indicates a location along a road segment at which the precautionary action is to be taken by the vehicle preceding the location along the road of the road network associated with the precautionary action data, wherein the precautionary action application is further operative to determine whether the vehicle is at the location at which the precautionary action is to be taken, the vehicle control system being further responsive thereto.

6. The vehicle of claim 1 wherein the precautionary action data further includes data that refers to the location of the actual hazardous condition.

7. The vehicle of claim 1 wherein the vehicle control system is further responsive to the precautionary action application to not actuate at least a subset of the one or more vehicle mechanical systems to take a precautionary action when the precautionary action application determines that the vehicle is approaching a location along a road of the road network not associated with precautionary action data.

8. The vehicle of claim 1 further comprising one or more sensors operative to sense conditions ahead of the vehicle.

9. The vehicle of claim 8 wherein the one or more sensors comprise camera or radar.

10. The vehicle of claim 8 wherein the condition is not capable of being sensed by the sensors.

11. The vehicle of claim 8 wherein the precautionary action application determines whether the vehicle is approaching a location along a road of the road network associated with precautionary action data before any of the one or more sensors can sense the hazardous condition indicated thereby.

12. The vehicle of claim 1 wherein the precautionary action application determines whether the vehicle is approaching a location along a road of the road network associated with precautionary action data when the vehicle is operating in inclement weather.

13. The vehicle of claim 1 wherein the precautionary action includes maneuvering the vehicle, tightening seatbelts, pre-loading or engaging brakes, tightening sensitivities of lane departure warning systems or stability control systems, or readying the brakes, engine or transmission for quick deceleration or stop.

14. The vehicle of claim 1 wherein the precautionary action application is further operative to factor in dynamic information when determining whether the vehicle is approaching a location along a road of the road network associated with precautionary action data.

15. The vehicle of claim 14 wherein the dynamic information includes current traffic conditions, current weather conditions, current ambient light conditions, current road conditions, or combinations thereof.

16. The vehicle of claim 14 wherein the precautionary action application is further operative to alter a location at which a precautionary action is to be taken based on the dynamic information.

12

17. The vehicle of claim 1 wherein the data that represents roads of the road network located in the geographic region further includes data representing nodes (intersections), boundaries, cartographic features, pedestrian walkways, bike paths, or points-of-interest.

18. The vehicle of claim 1 wherein the database further includes precautionary action data in association with one or more locations defined as hazardous based on sufficient comments occurring about the particular location received via community input from citizens or organizations.

19. A method of operating a vehicle, the method comprising:

determining, using a positioning system, a current location of the vehicle along a road of a road network relative to data representing a geographic region;

accessing a database that contains data representing the geographic region in which the vehicle is being operated, wherein the data includes data that represents roads of the road network located in the geographic region and precautionary action data associated with a plurality of locations along the roads of the road network where one or more different hazardous conditions which may impair control of the vehicle exists, wherein each of the plurality of locations where the hazardous condition exists comprises a location along a road of the road network at which it has been determined, prior to approach of the location by the vehicle, based on the data in the database that represents roads of a road network, that a condition comprising a combination of a curved section of road and insufficient superelevation thereof for operation of a vehicle at a given speed exists at the location;

determining, by a precautionary action application, responsive to the determination of the current position of the vehicle and the access to the database, whether, based on the current location of the vehicle, the vehicle is approaching a location along a road of the road network associated with precautionary action data; and actuating, by a vehicle control system coupled with one or more vehicle mechanical systems and responsive to the precautionary action application, at least a subset of the one or more vehicle mechanical systems to take a precautionary action when the precautionary action application determines that the vehicle is approaching a location along a road of the road network associated with precautionary action data.

20. The method of claim 19 wherein the condition further comprises the insufficiency of the superelevation exceeding a threshold based on a speed limit, road surface type, presence of shoulders, or a combination thereof.

21. The method of claim 19 wherein the one or more vehicle mechanical systems comprise brakes, engine, seatbelts, airbags, or stability control.

22. The method of claim 19 wherein the determining of the current location further comprises determining a direction of travel of the vehicle and wherein the precautionary action data further includes data that indicates a direction along a road segment at which a precautionary action is to be taken, wherein the determining of whether the vehicle is approaching the location along a road of the road network associated with precautionary action data further comprises determining whether the vehicle is approaching in the direction along the road segment at which the precautionary action is to be taken, the actuating being further responsive thereto.

23. The method of claim 19 wherein the precautionary action data further includes data that indicates a location

13

along a road segment at which the precautionary action is to be taken by the vehicle preceding the location along the road of the road network associated with the precautionary action data, wherein the determining whether the vehicle is approaching a location along a road of the road network associated with precautionary action data further comprises determining whether the vehicle is at the location at which the precautionary action is to be taken, the actuating being further responsive thereto.

24. The method of claim 19 wherein the precautionary action data further includes data that refers to the location of the actual hazardous condition.

25. The method of claim 19 further comprising not actuating, by the vehicle control system, at least a subset of the one or more vehicle mechanical systems to take a precautionary action when the precautionary action application determines that the vehicle is approaching a location along a road of the road network not associated with precautionary action data.

26. The method of claim 19 further comprising one or more sensors operative to sense conditions ahead of the vehicle.

27. The method of claim 26 wherein the one or more sensors comprise camera or radar.

28. The method of claim 26 wherein the one or more different hazardous conditions comprises conditions not capable of being sensed by the sensors.

29. The method of claim 26 wherein the determining whether the vehicle is approaching a location along a road of the road network associated with precautionary action data further comprises determining whether the vehicle is approaching a location along a road of the road network associated with precautionary action data before any of the one or more sensors can sense the hazardous condition indicated thereby.

30. The method of claim 19 wherein the determining whether the vehicle is approaching a location along a road of the road network associated with precautionary action data further comprises determining whether the vehicle is approaching a location along a road of the road network associated with precautionary action data when the vehicle is operating in inclement weather.

31. The method of claim 19 wherein the actuating includes maneuvering the vehicle, tightening seatbelts, preloading or engaging brakes, tightening sensitivities of lane departure warning systems or stability control systems, or readying the brakes, engine or transmission for quick deceleration or stop.

32. The method of claim 19 wherein the determining whether the vehicle is approaching a location along a road of the road network associated with precautionary action data further comprises determining further comprises factoring in dynamic information when determining whether the vehicle is approaching a location along a road of the road network associated with precautionary action data.

33. The method of claim 32 wherein the dynamic information includes current traffic conditions, current weather conditions, current ambient light conditions, current road conditions, or combinations thereof.

14

34. The method of claim 32 further comprising altering a location at which a precautionary action is to be taken based on the dynamic information.

35. The method of claim 19 wherein the data that represents roads of the road network located in the geographic region further includes data representing nodes (intersections), boundaries, cartographic features, pedestrian walkways, bike paths, or points-of-interest.

36. The method of claim 19 wherein the database further includes precautionary action data in association with one or more locations defined as hazardous based on sufficient comments occurring about the particular location received via community input from citizens or organizations.

37. A method of operating a vehicle, the method comprising:

determining, using a positioning system, a current location of the vehicle along a road of a road network relative to data representing a geographic region;

accessing a database that contains data representing the geographic region in which the vehicle is being operated, wherein the data includes data that represents roads of the road network located in the geographic region and precautionary action data associated with a plurality of locations along the roads of the road network where one or more different hazardous conditions which may impair control of the vehicle exists, wherein each of the plurality of locations where the hazardous condition exists comprises a location along a road of the road network at which it has been determined, prior to approach of the location by the vehicle, based on the data in the database that represents roads of a road network, that a condition comprising a combination of a curved section of road and insufficient superelevation thereof for operation of a vehicle at a given speed exists at the location;

determining, by a precautionary action application before an operator or sensors of the vehicle can sense the hazardous condition, responsive to the determination of the current position of the vehicle and the access to the database, whether, based on the current location of the vehicle, the vehicle is approaching a location along a road of the road network associated with precautionary action data;

actuating, by a vehicle control system coupled with one or more vehicle mechanical systems and responsive to the precautionary action application, at least a subset of the one or more vehicle mechanical systems to take a precautionary action when the precautionary action application determines that the vehicle is approaching a location along a road of the road network associated with precautionary action data; and

not actuating, by the vehicle control system, at least a subset of the one or more vehicle mechanical systems to take a precautionary action when the precautionary action application determines that the vehicle is approaching a location along a road of the road network not associated with precautionary action data.

* * * * *