



US010893521B2

(12) **United States Patent**  
**Kuchibhotla et al.**

(10) **Patent No.:** **US 10,893,521 B2**  
(45) **Date of Patent:** **Jan. 12, 2021**

(54) **RADIO RESOURCE ASSIGNMENT IN CONTROL CHANNEL IN WIRELESS COMMUNICATION SYSTEMS**

(58) **Field of Classification Search**  
CPC ..... H04W 72/0446; H04W 28/06; H04W 72/042; H04W 72/1273

See application file for complete search history.

(71) Applicant: **Google Technology Holdings LLC**,  
Mountain View, CA (US)

(56) **References Cited**

(72) Inventors: **Ravi Kuchibhotla**, Gurnee, IL (US);  
**Raja S. Bachu**, Des Plaines, IL (US);  
**Brian K. Classon**, Palatine, IL (US);  
**Robert T. Love**, Barrington, IL (US);  
**Ravikiran Nory**, Grayslake, IL (US);  
**Kenneth A. Stewart**, Grayslake, IL (US);  
**Yakun Sun**, Evanston, IL (US)

U.S. PATENT DOCUMENTS

4,491,947 A 1/1985 Frank  
4,939,746 A 7/1990 Childress

(Continued)

FOREIGN PATENT DOCUMENTS

CN 1284798 A 2/2001  
CN 1526225 A 9/2004

(Continued)

(73) Assignee: **GOOGLE TECHNOLOGY HOLDINGS LLC**, Mountain View, CA (US)

OTHER PUBLICATIONS

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 100 days.

United States Patent and Trademark Office; Non-Final Office Action; U.S. Appl. No. 11/538,758; dated Jul. 23, 2009.

(Continued)

(21) Appl. No.: **15/897,773**

(22) Filed: **Feb. 15, 2018**

(65) **Prior Publication Data**

US 2018/0176916 A1 Jun. 21, 2018

*Primary Examiner* — Andrew Lai

*Assistant Examiner* — Sumitra Ganguly

(74) *Attorney, Agent, or Firm* — Marshall, Gerstein & Borun LLP

**Related U.S. Application Data**

(63) Continuation of application No. 14/960,078, filed on Dec. 4, 2015, now Pat. No. 9,918,312, which is a (Continued)


(57) **ABSTRACT**

(51) **Int. Cl.**  
**H04W 72/04** (2009.01)  
**H04W 72/12** (2009.01)  
**H04W 28/06** (2009.01)

A method in a wireless communication device including receiving (410) a composite control channel including at least two control channel elements, each control channel element only contains radio resource assignment information, for example, a codeword, exclusively addressed to a single wireless communication entity. The device combines (420) at least two of the control channel elements, and decodes (430) the combined control channel elements.

(52) **U.S. Cl.**  
CPC ..... **H04W 72/0446** (2013.01); **H04W 72/042** (2013.01); **H04W 72/1273** (2013.01); **H04W 28/06** (2013.01)

**4 Claims, 4 Drawing Sheets**



**Related U.S. Application Data**

continuation of application No. 11/538,758, filed on Oct. 4, 2006, now abandoned.

**FOREIGN PATENT DOCUMENTS**

(56)

**References Cited**

**U.S. PATENT DOCUMENTS**

5,099,511	A	3/1992	Matsumoto
6,031,826	A	2/2000	Hassan
6,064,662	A	5/2000	Gitlin et al.
6,097,772	A	8/2000	Johnson et al.
6,243,580	B1	6/2001	Garner
6,252,910	B1	6/2001	West et al.
6,347,391	B1	2/2002	Uesugi et al.
6,549,772	B1	4/2003	Chavez et al.
6,567,416	B1	5/2003	Chuah
6,574,211	B2	6/2003	Padovani et al.
6,633,762	B1	10/2003	Rauscher
6,697,422	B1	2/2004	Mathai
6,751,187	B2	6/2004	Walton et al.
6,885,630	B2	4/2005	Kostic et al.
6,934,275	B1	8/2005	Love et al.
6,856,812	B1	12/2005	Budka et al.
7,016,319	B2	3/2006	Baum et al.
7,200,405	B2	4/2007	Rudolf et al.
7,664,091	B2	2/2010	Batariere et al.
7,778,307	B2	8/2010	Kuchibhotla et al.
9,918,312	B2	3/2018	Kuchibhotla et al.
2001/0034209	A1	10/2001	Tong
2001/0053142	A1	12/2001	Abe et al.
2002/0029229	A1	3/2002	Jakopac et al.
2002/0032030	A1	3/2002	Berglund et al.
2002/0114401	A1	8/2002	Kim et al.
2002/0118666	A1	8/2002	Stanwood et al.
2002/0183066	A1	12/2002	Pankaj
2003/0032030	A1	2/2003	Prolla et al.
2003/0112778	A1	6/2003	Lundby
2003/0157953	A1	8/2003	Das et al.
2003/0189918	A1	10/2003	Das et al.
2004/0082333	A1	4/2004	Ito et al.
2004/0095907	A1	5/2004	Agee et al.
2004/0116143	A1	6/2004	Love et al.
2005/0025101	A1	2/2005	Paneth et al.
2005/0047387	A1	3/2005	Frederiksen et al.
2005/0111397	A1	5/2005	Attar et al.
2005/0147078	A1	7/2005	Arima et al.
2005/0169275	A1	8/2005	Jiang et al.
2005/0232181	A1	10/2005	Park et al.
2005/0254442	A1	11/2005	Proctor, Jr. et al.
2006/0009228	A1	1/2006	Kang et al.
2006/0050742	A1	3/2006	Grandhi et al.
2006/0072520	A1	4/2006	Chitrapu et al.
2006/0094432	A1	5/2006	Chang et al.
2006/0120486	A1	6/2006	Visalli et al.
2006/0146756	A1	7/2006	Wang et al.
2006/0245384	A1	11/2006	Talukdar et al.
2006/0291403	A1	12/2006	Kahtava et al.
2007/0025345	A1	2/2007	Bachl et al.
2007/0025468	A1	2/2007	Li
2007/0047474	A1	3/2007	Anderson
2007/0058595	A1	3/2007	Classon et al.
2007/0110104	A1	5/2007	Sartori et al.
2007/0115796	A1*	5/2007	Jeong ..... H04L 1/0026 370/203
2007/0165731	A1	7/2007	Xiao et al.
2007/0211657	A1	9/2007	McBeath et al.
2007/0214400	A1	9/2007	Smith et al.
2008/0040105	A1	2/2008	Wang et al.
2008/0049690	A1	2/2008	Kuchibhotla et al.
2008/0062912	A1	3/2008	Tiedemann, Jr. et al.
2008/0084853	A1	4/2008	Kuchibhotla et al.
2008/0085718	A1	4/2008	Kuchibhotla et al.
2008/0232291	A1	9/2008	Hus et al.
2009/0268695	A1	10/2009	Zhao
2010/0309891	A1	12/2010	Kuchibhotla et al.

CN	1592482	A	3/2005
CN	1770917	A	5/2006
EP	1 610 497	A1	12/2005
EP	1635592	A1	3/2006
EP	1638271	A	3/2006
EP	1 670 274	A2	6/2006
JP	11355195	A	12/1999
JP	2003-521151	A	7/2003
JP	2005-525720	A	8/2005
JP	2006-005946		1/2006
JP	2006505219	A	2/2006
KR	2003-0089517	A	11/2003
WO	92/11716	A1	7/1992
WO	0241520	A2	5/2002
WO	WO-02/41520	A2	5/2002
WO	0249305	A2	6/2002
WO	2004098072	A2	11/2004
WO	2004100569	A2	11/2004
WO	2004/105294	A2	12/2004
WO	2005050852	A	6/2005
WO	WO-2005050852	A2 *	6/2005
WO	2005109705	A1	11/2005
WO	2005117464	A2	12/2005
WO	2006034401	A2	3/2006
WO	2006039812	A1	4/2006
WO	2006065069	A1	6/2006
WO	2006102746	A1	10/2006
WO	2006105004	A2	10/2006
WO	2006105005	A2	10/2006
WO	WO-2008/042513	A2	4/2008

**OTHER PUBLICATIONS**

United States Patent and Trademark Office; Final Office Action; U.S. Appl. No. 11/538,758; dated Feb. 5, 2010.

United States Patent and Trademark Office; Non-Final Office Action; U.S. Appl. No. 11/538,758; dated Aug. 18, 2010.

United States Patent and Trademark Office; Final Office Action; U.S. Appl. No. 11/538,758; dated Feb. 9, 2011.

United States Patent and Trademark Office; Non-Final Office Action; U.S. Appl. No. 11/538,758; dated Dec. 30, 2011.

United States Patent and Trademark Office; Final Office Action; U.S. Appl. No. 11/538,758; dated Jun. 14, 2012.

United States Patent and Trademark Office; Examiners Answer to Appeal Brief; U.S. Appl. No. 11/538,758; dated Apr. 10, 2013.

United States Patent and Trademark Office; Patent Board Decision—Examiner Affirmed; Application No. 11/538,758; dated Oct. 26, 2015.

The Intellectual Property Office of the People’s Republic of China; Notice of the First Office Action; Application No. 200780040923.8; dated Oct. 10, 2011.

European Patent Office; Extended European Search Report; International Application No. 11170222.1; dated Aug. 11, 2011.

European Patent Office; Extended European Search Report; International Application No. 11157378.8; dated Jul. 22, 2011.

Korean Intellectual Property Office; Non-Final Rejection; Application No. 10-2009-7009127; dated Aug. 9, 2011.

European Patent Office; Extended European Search Report; International Application No. 11157380.4; dated May 18, 2011.

United States Patent and Trademark Office; Non-Final Office Action; U.S. Appl. No. 11/934,172; dated Apr. 20, 2011.

United States Patent and Trademark Office; Notice of Allowance; U.S. Appl. No. 11/858,155; dated Oct. 29, 2010.

Scalable OFDMA Physical Layer in IEEE 802.16 Wirelessman; Intel Technology Journal; Aug. 20, 2004.

R1-060378; E-UTRA Downlink Control Channel Structure and TP; 3GPP TSG RAN1 #44; Denver USA; Motorola; Feb. 13-17, 2006.

R1-050590; Physical Channels and Multiplexing in Evolved Utra Downlink; 3GPP TSG RAN WG1 Ad Hoc on LTE; Sophia Antipolis, France; Jun. 20-21, 2005.

United States Patent and Trademark Office; Non-Final Office Action; U.S. Appl. No. 11/538,771; dated Oct. 28, 2009.

(56)

**References Cited**

## OTHER PUBLICATIONS

European Patent Office; European Search Report; Application No. 09007847.8; dated Aug. 4, 2009.

European Patent Office; International Search Report and Written Opinion; International Appl. No. PCT/US2007/076468; dated Jun. 11, 2008.

European Patent Office; International Search Report and Written Opinion; International Appl. No. PCT/US2007/076477; dated Feb. 1, 2008.

Holma, Harri et al.; WCDMA for UMTS; 2000; Wiley and Sons; XP002537677; pp. 95-97.

Lee et al.; Extended rtPS for VoIP services; IEEE 802.16 Broadband Wireless Access Working Group; Nov. 4, 2004.

3GPP TS 36.211 v.8.7.0; 3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Evolved Universal Terrestrial Radio Access (E-UTRA); Physical Channels and Modulation (Release 8); May 2009.

3GPP TSG RAN2 #55; RS-062970; Downlink Resource Allocation; Motorola; Oct. 9-13, 2006.

3GPP TSG RAN1 #45; RI-061173; EUTRA Downlink Distributed Multiplexing and Mapping Rules TP; May 8-12, 2006.

Intel Technology Journal; IEEE 802.16 Medium Access Control and Service Provisioning; vol. 08; issue 03; Aug. 20, 2004.

Gesbert, David et al.; How Much Feedback is Multi-User Diversity Really Worth?; IEEE; 2004.

3rd Generation Partnership Project 2 "3GPP2", 3GP2 X.S002-A; Version 0.0; Date: TBD; Broadcast and Multicast Service in CDMA2000 Wireless IP Network; Revision A; 138 pages.

United States Patent and Trademark Office; Non-Final Office Action; U.S. Appl. No. 14/960,078; dated May 19, 2017.

3GPP TSG RAN1 #44, R 1-060018, Performance Evaluation of EUTRA Downlink CQI Feedback Schemes (2006).

European Office Action for Application No. 07814333.6, dated Aug. 19, 2009.

European Office Action for Application No. 09007846.0, dated Oct. 15, 2010.

European Office Action for Application No. 11157378.8, dated Apr. 12, 2019.

European Office Action for Application No. 11157378.8, dated Nov. 6, 2017.

European Office Action for Application No. 11157380.4, dated Jun. 14, 2017.

European Office Action for Application No. 11170222.1, dated Dec. 14, 2017.

European Patent Office; Extended European Search Report; Application No. 09007846.0; dated Aug. 5, 2009.

European Patent Office; Extended European Search Report; Application No. 09007847.8; dated Aug. 4, 2009.

European Patent Office; Extended European Search Report; Application No. 11157379.6; dated Apr. 19, 2011.

Final Notice of Reasons for Refusal for Japanese Application No. 2012-024019, dated Sep. 17, 2013.

First Office Action for Chinese Application No. 200780037314.7, dated Aug. 23, 2011.

First Office Action for Chinese Application No. 201110443544.1, dated Mar. 3, 2014.

First Office Action for Chinese Application No. 201110443567.2, dated Nov. 5, 2013.

First Office Action for Chinese Application No. 201110443579.5, dated Feb. 24, 2014.

First Office Action for Chinese Application No. 201110443595.4, dated Dec. 16, 2013.

First Office Action for Chinese Application No. 20111044378.1, dated Dec. 27, 2013.

Fourth Office Action for Chinese Application No. 201110443579.5, dated Dec. 11, 2015.

Fourth Office Action for Chinese Application No. 20111044378.1, dated Dec. 24, 2015.

Notice of Final Rejection for Korean Application No. 10-2009-7006930, dated Jun. 14, 2011.

Notice of Final Rejection for Korean Application No. 10-2011-7009136, dated Apr. 24, 2012.

Notice of Reasons for Refusal for Japanese Application No. 2009-530499, dated Nov. 8, 2011.

Notice of Reasons for Refusal for Japanese Application No. 2012-024019, dated Dec. 25, 2012.

Notice of Reasons for Refusal for Japanese Application No. 2013-059304, dated Sep. 17, 2013.

Notice of Reasons for Refusal for Japanese Application No. 2013-202948, dated Jul. 29, 2014.

Second Office Action for Chinese Application No. 200780037314.7, dated Apr. 12, 2012.

Second Office Action for Chinese Application No. 201110443579.5, dated Nov. 14, 2014.

Second Office Action for Chinese Application No. 201110443595.4, dated Aug. 29, 2014.

Second Office Action for Chinese Application No. 20111044378.1, dated Nov. 17, 2014.

Third Office Action for Chinese Application No. 200780037314.7, dated Dec. 25, 2012.

Third Office Action for Chinese Application No. 201110443579.5, dated May 25, 2015.

Third Office Action for Chinese Application No. 20111044378.1, dated May 26, 2015.

Office Action for Brazilian Application No. 0717508-6, dated Jul. 11, 2019.

\* cited by examiner




FIG. 1




FIG. 2






FIG. 3

*FIG. 4**FIG. 5*

# RADIO RESOURCE ASSIGNMENT IN CONTROL CHANNEL IN WIRELESS COMMUNICATION SYSTEMS

## CROSS-REFERENCE TO RELATED APPLICATIONS

The present application is a continuation of U.S. application Ser. No. 14/960,078 filed on Dec. 4, 2015, which is a continuation of U.S. application Ser. No. 11/538,758 filed on 4 Oct. 2006 (now abandoned), the contents of which are incorporated by reference herein and from which benefits are claimed under 35 USC 120.

## FIELD OF THE DISCLOSURE

The present disclosure relates generally to wireless communications, and more particularly to controlling channel signaling for shared channels in wireless communication systems, for example cellular communication networks, corresponding entities and methods.

## BACKGROUND

Time division multiplexing (TDM) and frequency division multiplexing (FDM) methods, including hybrids thereof, have been proposed in addition to separate and joint coding of control channel signaling for scheduling downlink data transmission in the Long Term Evolution (LTE) of UMTS Terrestrial Radio Access (UTRA) and UTRA Network (UTRAN) specifications. In TDM and FDM transmissions of control channel signaling, the control information for downlink and uplink assignments may be transmitted over the first few symbols of the downlink frame or it may be spread out over the length of the frame. The frame duration is approximately 0.5 ms, though other durations are also possible.

The various aspects, features and advantages of the disclosure will become more fully apparent to those having ordinary skill in the art upon careful consideration of the following Detailed Description and the accompanying drawings described below. The drawings may have been simplified for clarity and are not necessarily drawn to scale.

## BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a wireless communication system.

FIG. 2 illustrates a radio frame comprising a composite control channel having a plurality of control channel elements.

FIG. 3 illustrates a composite control channel having different of control channel element types.

FIG. 4 illustrates a process flow diagram.

FIG. 5 illustrates another process flow diagram.

## DETAILED DESCRIPTION

FIG. 1 illustrates a wireless communication system **100** comprising multiple cell serving base units forming a network distributed over a geographical region. A base unit may also be referred to as an access point, access terminal, Node-B, or similar terminologies known in the art. The one or more base units **101** and **102** serve a number of remote units **103** and **110** within a serving area or cell or within a sector thereof. The remote units may also be referred to as subscriber units, mobile units, users, terminals, subscriber stations, user equipment (UE), user terminals or by other

terminology known in the art. The network base units communicate with remote units to perform functions such as scheduling the terminals to receive or transmit data using available radio resources. The wireless network also comprises management functionality including data routing, admission control, subscriber billing, terminal authentication etc., which may be controlled by other network entities, as is known generally by those having ordinary skill in the art.

Base units **101** and **102** transmit downlink communication signals **104** and **105** to serving remote units on at least a portion of the same resources (time and/or frequency). Remote units **103** and **110** communicate with one or more base units **101** and **102** via uplink communication signals **106** and **113**. The one or more base units may comprise one or more transmitters and one or more receivers that serve the remote units. The number of transmitters at the base unit may be related, for example, to the number of transmit antennas **109** at the base unit. When multiple antennas are used to serve each sector to provide various advanced communication modes, for example, adaptive beam-forming, transmit diversity, transmit SDMA, and multiple stream transmission, etc., multiple base units can be deployed. These base units within a sector may be highly integrated and may share various hardware and software components. For example, all base units co-located together to serve a cell can constitute what is traditionally known as a base station. The remote units may also comprise one or more transmitters and one or more receivers. The number of transmitters may be related, for example, to the number of transmit antennas at the remote unit.

In one embodiment, the communication system utilizes OFDMA or a next generation single-carrier based FDMA architecture for uplink transmissions, such as interleaved FDMA (IFDMA), Localized FDMA (LFDMA), DFT-spread OFDM (DFT-SOFDM) with IFDMA or LFDMA. In other embodiments, the architecture may also include the use of spreading techniques such as direct-sequence CDMA (DS-CDMA), multi-carrier CDMA (MC-CDMA), multi-carrier direct sequence CDMA (MC-DS-CDMA), Orthogonal Frequency and Code Division Multiplexing (OFCDM) with one or two dimensional spreading, or simpler time and frequency division multiplexing/multiple access techniques.

Generally, a wireless communication network infrastructure scheduling entity located, for example, at each base unit **101** and **102** in FIG. 1, allocates or assigns radio resources to remote units in the network. The base units each include a scheduler for scheduling and allocating resources to remote units in corresponding serving areas or cells or sectors. In multiple access schemes such as those based on OFDM methods and the long term evolution of UTRA/UTRAN Study Item in 3GPP (also known as evolved UTRA/UTRAN (EUTRA/EUTRAN)), scheduling may be performed in the time and frequency dimensions using a Frequency Selective (FS) scheduler. In some embodiments, each remote unit may provide a frequency band channel quality indicator (CQI) or other metric to the scheduler to enable scheduling.

In OFDM systems or OFDM like systems such as DFT-SOFDM and IFDMA, a resource allocation is a frequency and time allocation that maps information for a particular base unit to sub-carrier resources from a set of available sub-carriers as determined by the scheduler. This allocation may depend, for example, on the frequency-selective channel-quality indication (CQI) or some other metric reported by the UE to the scheduler. The channel-coding rate and the modulation scheme, which may be different for different



portions of the sub-carrier resources, are also determined by the scheduler and may also depend on the reported CQI or other metric. In code division multiplexed networks, the resource allocation is code allocation that maps information for a particular base unit to sub-carrier resources from a set of available sub-carriers as determined by the scheduler.

FIG. 2 illustrates a frame **200** that constitutes a portion of a radio frame. The radio frame generally comprises a plurality of frames, which may form a concatenated continuum of frames. In FIG. 2, each frame includes a composite control channel portion **210** comprising at least two control channel elements. FIG. 2 illustrates the composite control channel include a plurality of control channel elements **212**, **214**, **216** and **218**. The control channel elements each comprise a codeword that provides a physical mapping of a logical control channel to a sequence of symbols, for example, QAM symbols. The control channel elements are generally not the same type. In FIG. 2, for example, control channel elements **212** and **218** have different sizes. Control channel elements may also be for uplink or downlink assignments, and have different associated information payload. Control channel elements may also be associated with different releases of the specification. In some embodiments, the composite control channel includes reference symbols, for example, pilot symbols, that are distinct from the control channel elements. The reference symbols are typically read by all remote units.

Each frame corresponds to a transmission time interval (TTI). An exemplary TTI is 1 ms. In one embodiment, a single TTI has a length 1 ms or 2 ms wherein the TTI is segmented into two sub-frames each having a 0.5 ms length. Such a construction however implies the need to address multiple resource blocks, i.e., more than the number of resource blocks in a single 0.5 ms sub-frame, unless the resource block (RB) definition is expanded to automatically define the RB as extending over the entire length of the TTI, without regard for the TTI duration. This can lead to inefficiency, however, in the form of excessive per-RB capacity. In case the RB is defined to extend over a fraction of the length of the TTI, it would be possible to independently address each of the resource blocks in the multiple sub-frames making up the TTI. Accordingly mechanisms are required to signal resource assignments in the case of a frame or TTI composed of concatenated sub-frames. Furthermore, mechanisms are required to be able to assign resources based on the needs of individual UE wherein fewer resources being assigned for a UE served smaller packets while more resources assigned to UE served with larger packets. In the case of UMTS (Universal Mobile Telecommunications System), a TTI is defined as the length of time over which a transmission or transport block is transmitted. A transmission block or transport block is composed of a block of jointly coded data protected by a single CRC. In the present instance, an alternate definition of TTI could be the length of transmission controlled by a single instance of control channel signaling.

In one embodiment, each control channel element contains only radio resource assignment information, for example, a codeword, exclusively addressed to a single wireless communication entity, for example, one of the remote units **102**, **103** in FIG. 1. The radio resource assignment information includes, among other remote unit specific information and a time-frequency radio resource assignment. In other embodiments, the radio resource assignment information may additionally comprise modulation, code rate, information block size, antenna mode indicator, and other information.

In one embodiment, the wireless communication network infrastructure entity, for example, the scheduler, may address more than one control channel element to the same wireless communication entity, for example, one of the remote units **101** or **103** in FIG. 1. More particularly, the control channel may include a first version of a codeword including a resource assignment on a first control channel element of the composite control channel and a second version of the codeword including a resource assignment on a second control channel element of the composite control channel, wherein both of the first and second versions of the codeword are addressed to the same mobile unit. In one embodiment, the first and second versions of the codeword are the same, and in another embodiment the first and second versions of the codeword are different. Whether codes words addressed to the same entity are different or the same affects how the addressed entity combines the control channel elements as discussed further below. Thus the wireless communication network infrastructure entity transmits the composite control channel including at least two control channel elements, wherein each elements includes corresponding first and second codeword versions addressed to the same entity. In some instances, the wireless network infrastructure entity may, typically based on the channel conditions of the entity, transmit the composite control channel including a single control channel element addressed to the entity.

In embodiments where the composite control channel includes a composite control channel including at least two different types of radio resource assignment control channel elements, the remote unit generally determines the number of types of control channel elements constituting the composite control channel upon receiving the composite control channel. In one embodiment, the composite control channel includes type indicator information for each type of control channel element constituting the composite control channel. The remote unit may thus determine the number of types of control channel elements based on the type indicator information. In FIG. 3, a radio frame **300** includes a composite control channel **310** comprising a first control channel element type **312** and a second control channel element types **316**. The first control channel element type is identified by a first indicator, for example, a sequence of bits, **314** appended to a last control channel element of the first type. The second control channel element type is identified by a second indicator **318** appended to a last control channel element of the second type. In another embodiment, the indicators **316** and **318** are not present, and the control channel element type is determined after successful decoding of the control element. For example, a type bit may indicate an uplink or downlink control element in the decoded payload. The control element may be addressed to a single UE by a color coded CRC or by other means. According to another aspect of the disclosure, the remote unit determines a number of control channel elements constituting at least one or at least two control channel elements of the composite control channel. FIG. 3 is only one illustrative embodiment of the physical layout of the control channel elements on the radio-sub frame. In an alternate embodiment, the layout may be viewed as a logical layout, where the control channel elements comprise a number of sub-carriers distributed across the frame.

In one embodiment, the determining the number of types of control channel elements constituting the composite control channel includes determining a number of uplink control channel elements and determining a number of downlink control channel elements. The number of uplink control

5

channel elements may be determined based on a first sequence of bits and the number of downlink control channel elements based on a second sequence of bits embedded within the frame. In one embodiment, the numbers of uplink and down link control channel elements are determined based on where the first and second bit sequences are embedded within the frame. Alternatively, the use of different bit sequences may be used to indicate the different numbers of control channel elements. For example, a first bit sequence may indicate a first number of uplink elements and a second bit sequence may indicate a second number of uplink elements.

In some embodiments, the composite control channel includes a first composite control channel portion in a first receive bandwidth on first center frequency and a second composite control channel in a second receive bandwidth on a second center frequency. Such a control channel structure may be implemented to accommodate remote users having limited receive bandwidth. More generally, the composite control channel may be divided into multiple composite control channel portions on corresponding center frequencies. For example, terminals may have their receiver bandwidths limited to 10 MHz, while the carrier bandwidth is 20 MHz. In order accommodate such terminals of limited minimum bandwidth capability, it might be necessary to map the composite control channel to both the lower 10 MHz and the upper 10 MHz sub-bands of the 20 MHz carrier. Terminals with 10 MHz capability camp on either one of the upper or lower sib-bands and receive the respective composite control channel.

In the process 400 of FIG. 4, at 410 a wireless communication entity, for example, the remote unit, the terminals receives a composite control channel including at least two control channel elements. In one embodiment, each the control channel element only contains radio resource assignment information exclusively addressed to a single wireless communication entity.

In FIG. 4, at 420, two or more control channel elements are combined before decoding at 430. Generally, however, the remote unit may attempt to decode a single control channel element without first combining elements or it may attempt to decode a single control channel element after decoding or attempting to decode combined elements. Whether or not any combining is necessary depends generally on whether the remote unit is successful decoding single control channel elements. Combining may be required, for example, in instances where a cyclic redundancy check (CRC) or other information verification check fails after decoding a single control channel element, or where decoding is not successful. Information verification typically involves remote unit specific information, which may be included in the decoded control channel element, or masked with the encoded control channel element, or masked or fed into a CRC for CRC color coding.

In some implementations, each of the plurality of control channel elements has an associated root index, which may be used as a basis for combining the control channel elements. For example, if the composite control channel comprises 12 control channel elements, 4 of those elements may have the same associated root index and may be used as the basis for decoding and combining and decoding the control channel elements. In embodiments where the control channel is divided into portions on corresponding center frequencies, as discussed above, the remote unit only combines control channel elements from the same control channel portion. In other words, control channel elements from different control channel portions are not combined.

6

In some embodiments, the remote unit combines at least two control channel elements of the composite control channel, wherein each control channel element is of the type that contains only radio resource assignment information exclusively addressed to a single wireless communication entity. Combining may be required, for example, in instances where a cyclic redundancy check (CRC) or other information verification check fails after decoding a single control channel element, or instances where decoding is not successful. Generally, however, the remote unit may attempt to decode a control channel element without first combining.

In one embodiment, at least two of the control channel elements are combined by summing soft information derived from first and second codeword information, wherein the first codeword information is within a first control channel element and the second codeword information is within a second control channel element. In such a combination, the combine control channel elements are temporally aligned and superimposed (known as Chase combining). The superposition may involve max-ratio combining, or adding together log-likelihood-ratios (LLRs), or the like. The assumption here is that the first and second codeword information is addressed to the same remote unit. If not, either the decoding or the information verification check after decoding will be unsuccessful. In the case of failure, the remote unit may form a different combination of control channel elements, for example, by combining a different set of control channel elements or by combining an additional element.

In another embodiment, at least two of the control channel elements are combined by rearranging and summing soft information derived from different first and second codeword information, wherein the first codeword information is within a first control channel element and the second codeword information is within a second control channel element. For example, the first codeword and second codeword may comprise subsets of an information set and parity bits generated from a lower rate channel encoder. The subsets may be non-overlapping or partially overlapping. Soft information corresponding to overlapping codeword bit positions is typically summed in the remote unit, while non-overlapping bit positions are typically rearranged to an appropriate position for decoding.

In one embodiment, the remote unite combines the at least two control channel elements according to predefined combinations of control channel elements. For example, at least one of the pre-defined combinations includes a combination of at least two logically contiguous control channel elements. The logically contiguous control channel elements may or may not be physically contiguous. For example, if a set of sub-carriers distributed across frequency (a comb) is used for one control channel element, another control channel element may or may not physically occupy the sub-carriers adjacent to the first control channel element. Or, if the logical and physical orderings of sub-carriers are identical, that is, there is a one-to-one mapping of logical and physical sub-carriers, then logical adjacency implies physical adjacency and vice versa. In other embodiments, at least two non-adjacent control channel elements are combined, wherein the non-adjacent control elements may be physical or logical.

In some implementations, the order in which the remote unit attempts to combine the control channel elements according to the pre-defined combinations is based on one or more hypotheses or assumptions. For example, the control channel elements may be combined based on a determination of the number of control channel elements constituting

the composite control channel. Such a determination also includes determining the number of control channel elements constituting a particular type of control channel element in embodiments where the composite control channel includes more than one elements type as discussed above. The number of control channel elements may be determined, for example, based on the existence of control channel element number information included in the composite control channel. For example, the number of control channel elements may be determined based on a sequence of bits appended to the composite control channel. In one implementation, different bit sequences are indicative of different numbers of control channel elements. In another implementation, the location of the sequence of bits within the frame is indicative of the number of the control channel elements. In this latter implementation, the same bit sequence may be used to indicate different numbers of control channel elements depending on where the bit sequence is located within the frame. The number of control channel elements may also be determined based on data or messaging shared between a wireless communication device and a network infrastructure entity. This may occur in a message sent to all remote units via a broadcast channel sent occasionally or a broadcast message sent in each TTI. The number of control channel elements or subset of control channel elements that the remote unit should decode may also be sent via a message dedicated for that remote unit.

In one embodiment, control channels may be one or two control channel elements, with the size of the control element indicating the type of control element. Convolutional encoding may be used for the control elements. And the decoder may decode the first control element, check the CRC, and then stop decoding if the control element is designated for the user. If not, the decoding may commence from the point just prior to tail bit insertion on the first control element, through the end of the trellis comprised of both control elements. The CRC is again checked. In this way, control channel decoding may be achieved with less effort than if combined control elements were decoded from the beginning of the trellis. Note that the code rate for the single and two control elements must be the same in this embodiment.

In some embodiments, a portion of the composite control channel is allocated for assigning radio resources in each frame. In these embodiments, the unallocated portion of the control channel may be used for data transfer. Thus a wireless communication network infrastructure entity, for example, a scheduler, may allocate a portion of the control channel for assigning radio resources in each frame by embedding a bit sequence within the corresponding frame. In one embodiment, the location of the sequence of bits within the frame is indicative of the size of the control channel, for example, how many control channel elements are allocated for assigning radio resources to one or more remote units. In this implementation, the control channel elements may be addressed exclusively to a single remote unit or to more than one remote unit. More generally, the network infrastructure entity may dynamically change the portion of the control channel for assigning radio resources in each frame by changing the bit sequence or the location of the bit sequence embedded in each frame before transmitting the frames. As suggested above, moreover, the network infrastructure entity may also dynamically allocated different types of control channel elements and the number thereof within a frame.

In another embodiment, the bit sequence embedded within the sub-frame is used to identify that the control

channel element is for a remote unit. In this case, the bit sequence embedded within the sub-frame may be a data dependent bit sequence, such as a CRC processed with wireless communication device identification information, the codeword masked with wireless communication device identification information or the like. In this embodiment, a first sub-frame, which may be the last sub-frame of a TTI, contains control information including modulation type, resources, or antenna mode indicator. Each control channel may be one or more control channel elements, and the size of the control channel may be different in the first and second sub-frames. The second sub-frame may occur on the same or different portions of the control channel as the control information from the first sub-frame. If a different portion of the sub-frame is used, blind decoding complexity may be reduced by having the control channel elements in the second sub-frame known from the location of the remote units control channel elements from the first sub-frame.

In the process diagram **500** of FIG. **5**, at **510**, the wireless communication network infrastructure entity allocates a portion of the control channel for assigning radio resources in each frame by embedding a bit sequence within the corresponding frame. Allocating a portion of the control channel includes allocating all available portions of the control channel or less than all available portions thereof, wherein the unallocated portion may be used for other purposes, for example, data transfer. At **520**, the wireless communication network infrastructure entity dynamically changes the portion of the control channel for assigning radio resources in each frame, wherein multiple frames constitutes a radio frame. According to this aspect of the disclosure, potentially, a different portion of each control channel in each frame, constituting the radio frame, may be allocated to assigning radio resources. The portion of the control channel for assigning radio resources in each frame may be changed dynamically by changing the location of the bit sequence embedded in each frame or by using different bit sequences, as discussed above. At **530**, the wireless communication network infrastructure entity transmits at least two frames, for example, constitute a radio frame, wherein each frame includes a control channel having a portion thereof allocated for radio resource assignment.

In FIG. **2**, for example, a portion of the control channel used for radio resource assignment is indicated based on where a bit sequence **220**, referred to as a terminating marker or signature, is embedded within the corresponding frame. Depending on where the bit sequence is located, the portion of the control channel, e.g., the number of elements, used for radio resource assignment may be less than the entire control channel of the frame. Generally, different frames constituting a radio frame may allocate different portions of the corresponding control channels for radio resource assignment. In one implementation, a wireless communication device, comprises a receiver capable of receiving a frame corresponding to a transmission time interval, wherein the frame includes a control channel and a bit sequence embedded within the frame. A controller communicably coupled to the receiver is configured for determining a portion of the control channel used for radio resource assignment based on where the corresponding bit sequence is embedded within the received frame, wherein the portion of the control channel used for radio resource assignment may be less than the entire control channel.

In the wireless communication device, for example, one of the remote units **101** or **103** in FIG. **1**, the device receives a plurality of at least two frames, wherein each frame includes a control channel having at least two control

channel elements and each frame includes a bit sequence embedded within the frame. In one embodiment, the wireless communication device determines a portion of the control channel used for radio resource assignment in each frame based on where the corresponding bit sequence is embedded within the frame. Generally, the portion of the control channel used for radio resource assignment may be less than the entire control channel and each frame may use different portions of the control channel for radio resource assignment based upon where the corresponding bit sequences is embedded within the frame.

In some instances, all control channel elements of the composite control channel communicate control channel information. In this particular embodiment, the absence of control channel element number information, e.g., a bit sequence embedded within the frame, is indicative of the use of the full composite control channel for radio resource assignment. For example, in the absence of control channel element number information, the remote unit may assume a default number of control channel elements are used for assigning radio resources.

While the present disclosure and the best modes thereof have been described in a manner establishing possession and enabling those of ordinary skill to make and use the same, it will be understood and appreciated that there are equivalents to the exemplary embodiments disclosed herein and that modifications and variations may be made thereto without departing from the scope and spirit of the inventions, which are to be limited not by the exemplary embodiments but by the appended claims.

What is claimed is:

1. A method in a wireless infrastructure entity, the method comprising:

determining a channel condition of a wireless communication entity connected to the wireless infrastructure entity; and

transmitting a composite control channel from the wireless infrastructure entity, the composite control channel including (i) a single control channel element based on the channel condition of the wireless communication entity and (ii) a first portion allocated for assigning radio resources and a second portion allocated for data transfer.

2. The method of claim 1, wherein the first portion includes additional control channel elements that are allocated for assigning the radio resources, further comprising providing radio resource assignment information on the additional control channel elements of the composite control channel before transmitting the composite control channel.

3. A method in a wireless infrastructure entity, the method comprising:

determining a channel condition of a wireless communication entity connected to the wireless infrastructure entity; and

transmitting a composite control channel from the wireless infrastructure entity, the composite control channel including (i) at least two control channel elements based on the channel condition of the wireless communication entity and (ii) a first portion allocated for assigning radio resources and a second portion allocated for data transfer.

4. The method of claim 3, wherein the first portion includes additional control channel elements that are allocated for assigning the radio resources, further comprising providing radio resource assignment information on the additional control channel elements of the composite control channel before transmitting the composite control channel.

\* \* \* \* \*