

US010897913B1

(12) **United States Patent**
Blessing

(10) **Patent No.:** **US 10,897,913 B1**
(45) **Date of Patent:** **Jan. 26, 2021**

(54) **AUTOMATIC WAFFLE CONE SHAPER**

(71) Applicant: **Dan Blessing**, Lahaina, HI (US)

(72) Inventor: **Dan Blessing**, Lahaina, HI (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 285 days.

(21) Appl. No.: **16/159,501**

(22) Filed: **Oct. 12, 2018**

1,720,304	A *	7/1929	Taylor	A21C 15/025
					425/214
2,108,298	A *	2/1938	Scharf	A47J 37/0611
					99/325
3,269,335	A *	8/1966	Heyman	A21C 15/025
					425/391
4,624,855	A *	11/1986	Haas, Sr.	A21B 5/026
					426/501
4,927,656	A *	5/1990	Ito	A21B 5/023
					426/138
5,336,511	A *	8/1994	Der Beek	A21B 5/026
					425/414
5,518,748	A *	5/1996	Ito	A21B 5/026
					426/138

(Continued)

Related U.S. Application Data

(60) Provisional application No. 62/588,845, filed on Nov. 20, 2017.

(51) **Int. Cl.**
A21C 15/02 (2006.01)

(52) **U.S. Cl.**
CPC *A21C 15/025* (2013.01)

(58) **Field of Classification Search**
CPC A47J 37/0611; A21B 3/132; A21B 5/026;
A21C 11/00; A21C 15/025; A21C 3/06;
A21C 3/065; A21D 8/00; A21D 13/33;
A23P 20/20; A23P 30/10
USPC 99/372, 374, 376, 377, 380-383, 384,
99/426, 427, 428, 430, 431, 432, 433,
99/439, 442

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,310,990	A *	7/1919	Hauge	A21B 5/026
					99/373
1,440,851	A *	1/1923	Tatosian	A21C 15/025
					425/334
1,540,041	A *	6/1925	Tatosian	A21B 5/023
					99/373

FOREIGN PATENT DOCUMENTS

CN 102165132 B * 5/2015 E06B 9/68

OTHER PUBLICATIONS

English translation of CN-102165132-B (Year: 2015).*

Primary Examiner — Christopher M Koehler


Assistant Examiner — Chris Q Liu

(74) *Attorney, Agent, or Firm* — Plager Schack LLP

(57) **ABSTRACT**

An automated waffle cone shaper for shaping waffle cones may include a mounting plate; a slide rail mounted to a top surface of the mounting plate, the slide rail including a slide carriage slidably mounted thereon; a tray attached to the slide carriage, such that when the slide carriage slides along a length of the slide rail, the tray moves along a length of the mounting plate, wherein the tray comprises a waffle feed portion and a cone shaper mold extending from the waffle feed portion; a motor and gearbox operatively attached to an end of the mounting plate distal from the slide rail; and a cone shaping spindle operatively attached to the motor, such that when the motor is activated, the cone shaping spindle rotates.

9 Claims, 5 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

6,227,103	B1 *	5/2001	Haas	A21C 15/025
					99/354
2015/0201625	A1 *	7/2015	Goldstein	A21C 15/025
					426/500
2016/0165900	A1 *	6/2016	Haas	A21C 15/025
					425/185

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10

1**AUTOMATIC WAFFLE CONE SHAPER**

RELATED APPLICATION

This application claims priority to provisional patent application U.S. Ser. No. 62/588,845 filed on Nov. 20, 2017, the entire contents of which is herein incorporated by reference.

BACKGROUND

The embodiments herein relate generally to food manufacturing, and more particularly, to an automated waffle cone shaper.

In small ice cream shops or similar type shops, homemade waffle cones are shaped by manually rolling and shaping. Specifically, the waffle is baked and then immediately transferred to a cone shaper with a shaper spindle that must be manually rotated by a user. For each cone, a user may have to rotate the spindle about 10 times. Not only does this manual requirement prevent the user from completing other tasks, such as starting to bake the next waffle, but it also can lead to injuries due to the repetitive rotating motion.

Existing automated systems are designed for industrial operations that make thousands of cones per day and are too large and too expensive for local and small retail shops.

Therefore, what is needed is an automated waffle cone shaper that is smaller in size and less expensive than industrial-sized systems.

SUMMARY

Some embodiments of the present disclosure include an automated waffle cone shaper for shaping waffle cones. The automated waffle cone shaper may include a mounting plate; a slide rail mounted to a top surface of the mounting plate, the slide rail including a slide carriage slidably mounted thereon; a tray attached to the slide carriage, such that when the slide carriage slides along a length of the slide rail, the tray moves along a length of the mounting plate, wherein the tray comprises a waffle feed portion and a cone shaper mold extending from the waffle feed portion; a motor and gearbox operatively attached to an end of the mounting plate distal from the slide rail; and a cone shaping spindle operatively attached to the motor, such that when the motor is activated, the cone shaping spindle rotates.

BRIEF DESCRIPTION OF THE FIGURES

The detailed description of some embodiments of the invention is made below with reference to the accompanying figures, wherein like numerals represent corresponding parts of the figures.

FIG. 1 is a front perspective view of one embodiment of the present disclosure.

FIG. 2 is a rear perspective view of one embodiment of the present disclosure.

FIG. 3 is a partial exploded view of one embodiment of the present disclosure.

FIG. 4 is a section view of one embodiment of the present disclosure, taken along line 4-4 in FIG. 2.

FIG. 5 is a section view of one embodiment of the present disclosure.

FIG. 6 is a front view of one embodiment of the present disclosure.

FIG. 7 is a front view of one embodiment of the present disclosure.

2

FIG. 8 is a perspective view of one embodiment of the present disclosure.

FIG. 9 is a flow chart describing the use of one embodiment of the present disclosure.

FIG. 10 is a wiring diagram of one embodiment of the present disclosure.

DETAILED DESCRIPTION OF CERTAIN EMBODIMENTS

In the following detailed description of the invention, numerous details, examples, and embodiments of the invention are described. However, it will be clear and apparent to one skilled in the art that the invention is not limited to the embodiments set forth and that the invention can be adapted for any of several applications.

The device of the present disclosure may be used to shape waffle cones and may comprise the following elements. This list of possible constituent elements is intended to be exemplary only, and it is not intended that this list be used to limit the device of the present application to just these elements. Persons having ordinary skill in the art relevant to the present disclosure may understand there to be equivalent elements that may be substituted within the present disclosure without changing the essential function or operation of the device.

a.	Mounting Plate
b.	Self-Aligning Feet
c.	Slide Carriage and Rail
d.	Return Spring
e.	Control Box
f.	Photoelectric Sensor
g.	Motor and Gearbox
h.	Shaft Coupler
i.	Tray with Cone Shaper Mold
j.	Cone shaping spindle

The various elements of the device of the present disclosure may be related in the following exemplary fashion. It is not intended to limit the scope or nature of the relationships between the various elements and the following examples are presented as illustrative examples only.

By way of example, and referring to FIGS. 1-10, some embodiments of the present disclosure include an automated waffle cone shaper designed to sense the presence of a user, automatically turn on, take the cone from the user and pull it into a former that shapes and cools the cones. Instead of having capabilities to sense the user, some embodiments of the automated waffle cone shaper may include an on-off switch or other known and similar activation mechanism.

The automated waffle cone shaper may comprise a mounting plate 10, feet, such as adjustable self-aligning feet 12, mounted to a bottom surface of the mounting plate 10, a slide rail 14 mounted to a top surface of the mounting plate 10, the slide rail 14 including a slide carriage 48 slidably mounted thereon, a tray 44 attached to the slide carriage 48, such that when the slide carriage 48 slides along a length of the slide rail 14, the tray 44 moves along a length of the mounting plate 10, wherein the tray 44 comprises a flat waffle feed portion and a cone shaper mold 46 extending from the flat waffle feed portion, a motor and gearbox 32 operatively attached to an end of the mounting plate 10 distal from the slide rail 14, a motor shaft 36 extending outward from the motor and gearbox 32, a shaft coupler 38 engaged with the motor shaft 36, the shaft coupler 38 designed to rotate when the motor 34 within the motor and gearbox 32

3

is activated, and a cone shaping spindle **40** attached to a spindle shaft **42** extending from an end of the shaft coupler **38** distal from the motor and gearbox **32**, such that when the shaft coupler **38** rotates, the cone shaping spindle **40** also rotates and wherein the cone shaping spindle **40** has a size slightly smaller than the cone shaper mold **46** such that the cone shaping spindle **40** fits within the cone shaper mold **46**. As shown in the Figures, the motor and gearbox **32** may be operatively attached to a power source via a power cord **56**, such that when the power cord **56** provides power to the motor and gearbox **32**, the motor shaft **36** and thus the shaft coupler **38** and cone shaping spindle **40** begin spinning. A waffle **60** may be placed on the tray **44** and slid into the cone shaper mold **46**, wherein the rotation of the cone shaping spindle **40** may pull the waffle **60** into the cone shaper mold **46** and continue spinning to form and set the waffle **60** into the traditional cone-shape. After a sufficient period of time, the cone shaping spindle **40** may stop rotating. At such time, the user **58** may slide the tray **44** down the slide rail **14** away from the cone shaping spindle **40** to remove the waffle cone from the cone shaper mold **46**.

In embodiments, the automated waffle cone shaper may further comprise a control box **18**, optionally with a power light **22**, run light **24**, and switches **20** or buttons, operatively attached to the motor and gearbox **32**. The power light **22** may illuminate when the motor and gearbox **32** and control box **18** receive power, while the run light **24** may illuminate when the motor **34** receives power and causes the motor shaft **36** to spin. The switch **20** may be designed to allow a user to completely turn off the automated waffle cone shaper without having to unplug it from a power source. A photoelectric sensor **26** with a timer relay may also be operatively attached to the motor and gearbox **32** using, for example, sensor wiring **30**, such that when a sensor region **28** of the photoelectric sensor **26** senses a user, power is sent to the motor and gearbox **32**, causing the motor and thus the motor shaft **36**, shaft coupler **38**, and cone shaping spindle **40** to rotate. An exemplary wiring diagram showing an example of the connections of the motor and gearbox **32**, the control box **18**, and the photoelectric sensor **26** is illustrated in FIG. **10**. The electric components may be operatively attached to one another by appropriate wires and cables. In some embodiments, a separator may separate the motor and electrical plastic.

In embodiments, the automated waffle cone shaper may further comprise a return spring **16** attaching the tray **44** to a portion of the mounting plate **10** distal from the slide rail **14**. The return spring **16** may prevent the tray **44** from moving away from the cone shaping spindle **40** unless purposely slide along the slide rail **14** by a user. In yet a further embodiment, the tray **44** may include a slide knob (not shown) that a user may grasp to slide the tray **44** away from the cone shaping spindle **40**.

Embodiments of the automated waffle cone shaper may also comprise a cooling fan **50** mounted to the mounting plate **10**. Specifically, the cooling fan **50** may comprise a fan mounting frame **52** surrounding the cooling fan **50**, wherein the fan mounting frame **52** is attached to the mounting plate **10**. In some embodiments, and as shown in FIG. **4**, the fan mounting frame **52** may be attached to the mounting plate **10** at an angle, such that it leans outwards away from a central area of the mounting plate **10**. The cooling fan **50** may be positioned such that the cooling fan **50** blows air toward the cone shaping spindle **40** and cone shaper mold **46** during use. Fan wiring **54** may attach the cooling fan **50** to the motor and gearbox **32**, the control box **18**, or other desired

4

electrical component. In embodiments, when the motor is powered on, the cooling fan **52** is also powered on.

Each of the components of the automated waffle cone shaper may be mounted to the mounting plate **10** via mounting blocks. For example, the control box **18** may be mounted to the mounting plate **10** via a control box mounting block and the photoelectric sensor **28** may be mounted to the control box **18** or the mounting plate **10** via a photoelectric mounting block or plate. Of course, any other conventional fasteners, such as nuts and bolts, may be used to mount the components to the mounting plate **10**.

Enhanced versions of the automated waffle cone shaper may include additional optional features, such as an edge trim attached to an outer edge of the mounting plate **10** and a strain relief structure attached to the power cord **11**. The enhanced versions may also include the power light **22** and run light **24** on the control box **18**, while other more basic versions may not.

Persons of ordinary skill in the art may appreciate that numerous design configurations may be possible to enjoy the functional benefits of the inventive systems. Thus, given the wide variety of configurations and arrangements of embodiments of the present invention the scope of the invention is reflected by the breadth of the claims below rather than narrowed by the embodiments described above.

What is claimed is:

1. An automated waffle cone shaper for shaping waffle cones, the automated waffle cone shaper comprising:

- a mounting plate;
- a slide rail mounted to a top surface of the mounting plate, the slide rail including a slide carriage slidably mounted thereon;
- a tray attached to the slide carriage, such that when the slide carriage slides along a length of the slide rail, the tray moves along a length of the mounting plate, wherein the tray comprises a flat waffle feed portion and a cone shaper mold extending from the flat waffle feed portion, and the tray is configured to contain a waffle on the flat waffle feed portion;
- a motor and a gearbox operatively attached to an end of the mounting plate distal from the slide rail;
- a cone shaping spindle operatively attached to the motor, such that when the motor is activated, the cone shaping spindle rotates, wherein the cone shaping spindle is configured to pull the waffle into the cone shape mold from the flat waffle feed portion; and
- a return spring attaching the tray to a portion of the mounting plate distal from the slide rail,

wherein:

- a first end of the return spring is attached to the tray via the slide carriage such that the first end of the spring moves along a length of the mounting plate with movement of the tray and the slide carriage; and
- a second end of the return spring is attached to a stationary point on the mounting plate proximate to the motor and the gearbox.

2. The automated waffle cone shaper of claim **1**, further comprising:

- a motor shaft extending outward from the motor and the gearbox, the motor shaft designed to rotate when the motor is activated;
- a spindle shaft extending from an end of the cone shaping spindle proximate to the motor and the gearbox; and
- a shaft coupler attaching the motor shaft to the spindle shaft.

3. The automated waffle cone shaper of claim 1, wherein the cone shaping spindle has a size smaller than the cone shaper mold such that the cone shaping spindle fits within the cone shaper mold.

4. The automated waffle cone shaper of claim 1, further comprising a plurality of self-aligning feet attached to a bottom surface of the mounting plate. 5

5. The automated waffle cone shaper of claim 1, further comprising a control box operatively attached to the motor and gearbox. 10

6. The automated waffle cone shaper of claim 1, further comprising a photoelectric sensor operatively attached to the motor and gearbox.

7. The automated waffle cone shaper of claim 1, further comprising a cooling fan mounted to the mounting plate. 15

8. The automated waffle cone shaper of claim 7, wherein: a fan mounting frame surrounds the cooling fan; and the fan mounting frame is attached to the mounting plate.

9. The automated waffle cone shaper of claim 7, wherein the cooling fan is positioned such that the cooling fan blows air toward the cone shaping spindle and cone shaper mold during use. 20

* * * * *