

US010907859B2

(12) **United States Patent**
Jeong et al.

(10) **Patent No.:** **US 10,907,859 B2**
(45) **Date of Patent:** **Feb. 2, 2021**

(54) **HEAT EXCHANGER**

(71) Applicant: **KYUNG DONG NAVIEN CO., LTD.**,
Pyeongtaek-si (KR)

(72) Inventors: **Inchul Jeong**, Seoul (KR); **Tae Hyun Hwnag**, Seoul (KR)

(73) Assignee: **KYUNG DONG NAVIEN CO., LTD.**,
Pyeongtaek-si (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 265 days.

(21) Appl. No.: **16/072,409**

(22) PCT Filed: **Feb. 3, 2017**

(86) PCT No.: **PCT/KR2017/001183**
§ 371 (c)(1),
(2) Date: **Jul. 24, 2018**

(87) PCT Pub. No.: **WO2017/135727**
PCT Pub. Date: **Aug. 10, 2017**

(65) **Prior Publication Data**
US 2018/0363946 A1 Dec. 20, 2018

(30) **Foreign Application Priority Data**
Feb. 5, 2016 (KR) 10-2016-0015085

(51) **Int. Cl.**
B23K 1/00 (2006.01)
B23K 101/14 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **F24H 1/34** (2013.01); **B23K 1/0012**
(2013.01); **F24H 1/40** (2013.01); **F24H**
9/0026 (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC B23K 1/0012; B23K 2101/14; F24H 1/32;
F24H 1/34; F24H 1/40; F24H 9/0026;
(Continued)

(56) **References Cited**
U.S. PATENT DOCUMENTS
9,702,589 B2 * 7/2017 Kim F24H 1/145
2017/0059201 A1 * 3/2017 Kim F24H 1/38


FOREIGN PATENT DOCUMENTS
EP 1 211 473 A2 6/2002
JP 2006-214628 A 8/2006
(Continued)

OTHER PUBLICATIONS
Family Handyman, How to Solder Copper Pipe, Jul. 14, 2013, Home Service Publications, Inc., <https://www.familyhandyman.com/plumbing/how-to-solder-copper-pipe/> (Year: 2013).*
(Continued)

Primary Examiner — Filip Zec
Assistant Examiner — Chang H Park
(74) *Attorney, Agent, or Firm* — Stein IP, LLC

(57) **ABSTRACT**
The present subject matter includes: a heat exchange part having heating medium channels, through which heating medium flows, and combustion gas channels, through which combustion gas burned in a burner flows, adjacently disposed in alternation in the spaces between the plurality of plates; a first welding part in which the outer edges of a pair of plates forming the heating medium channel are welded together; a second welding part in which the plates forming the combustion gas channel, between the plates forming the heating medium channel, are welded to the outer edges of the plates forming the heating medium channel to form; and a guide part for guiding the welding material molten solution of the first welding part into moving to the second welding part.

9 Claims, 16 Drawing Sheets



- (51) **Int. Cl.**
F24H 1/32 (2006.01)
F24H 1/34 (2006.01)
F24H 1/40 (2006.01)
F24H 9/00 (2006.01)
F28D 20/02 (2006.01)
F28D 9/00 (2006.01)
F28F 3/02 (2006.01)
F28F 3/04 (2006.01)
F28F 9/02 (2006.01)
- (52) **U.S. Cl.**
 CPC *F28D 9/0093* (2013.01); *F28D 20/026*
 (2013.01); *B23K 2101/14* (2018.08); *F24H*
1/32 (2013.01); *F28D 9/005* (2013.01); *F28F*
3/025 (2013.01); *F28F 3/046* (2013.01); *F28F*
9/028 (2013.01); *F28F 2250/104* (2013.01);
Y02E 60/14 (2013.01)
- (58) **Field of Classification Search**
 CPC *F28D 20/026*; *F28D 9/005*; *F28D 9/0093*;
F28F 2250/104; *F28F 3/025*; *F28F 3/046*;
F28F 9/028; *Y02E 60/145*
 See application file for complete search history.

- (56) **References Cited**
- FOREIGN PATENT DOCUMENTS
- | | | | | |
|----|-----------------|----|-----------|-------------------|
| KR | 1996-0024209 | A | 7/1996 | |
| KR | 10-2006-0116732 | A | 11/2006 | |
| KR | 10-0813807 | B1 | 3/2008 | |
| KR | 100813807 | B1 | 3/2008 | |
| KR | 20130006062 | A | * 1/2013 | |
| KR | 10-2015-0108450 | A | 9/2015 | |
| KR | 10-2015-0108959 | A | 10/2015 | |
| KR | 20150108959 | A | * 10/2015 | F28D 9/0093 |
| KR | 10-2016-0002438 | A | 1/2016 | |

- OTHER PUBLICATIONS
- Dover, SWEP: What is a Brazed Plate Heat Exchanger (BPHE),
 Nov. 7, 2014, 0:31, 0:40, 0:44, <https://www.youtube.com/watch?v=5WgnJ8e49pg> (Year: 2014).*
- International Search Report dated Apr. 27, 2017, issued to Interna-
 tional Application No. PCT/KR2017/001183.

* cited by examiner

[FIG. 1]







FIG. 2






[FIG. 3]


FIG. 4




[FIG. 5]



[FIG. 6]




[FIG. 7]




[FIG. 8]


1



[FIG. 9]



[FIG. 10]



[FIG. 11]





FIG. 12



[FIG. 13]

1







FIG. 14




[FIG. 15]




[FIG. 16]



[FIG. 17]



[FIG. 18]



1

HEAT EXCHANGER

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a national stage of International Application No. PCT/KR2017/001183, filed Feb. 3, 2017, which claims the benefit of Korean Application No. 10-2016-0015085, filed Feb. 5, 2016 in the Korean Intellectual Property Office, the disclosures of which are incorporated herein by reference.

TECHNICAL FIELD

The present invention relates to a heat exchanger, and more particularly, to a heat exchanger capable of ensuring welding quality while reducing a material cost and a process cost by reducing a portion to which a welding material is applied during production of a plate-type heat exchanger having a plurality of plates stacked and welded together.

BACKGROUND ART

A boiler used for providing heating or hot water is a device configured to heat a desired site or supply hot water by heating tap water or heating water (hereinafter referred to as a "heating medium") by a heat source, wherein the boiler includes a burner configured to burn a mixture of a gas and air, and a heat exchanger configured to transfer combustion heat of a combustion gas to a heating medium.

As an example of a prior art relating to a conventional heat exchanger, Korean Registered Patent No. 10-0813807 discloses a heat exchanger including a burner disposed at a central portion of the heat exchanger, and a heat exchange tube wound around a circumference of the burner in the form of a coil.

The heat exchanger disclosed in the above-described Patent Document has problems in that, since the heat exchange tube is formed in a flat shape, the heat exchange tube is deformed into a rounded shape when a pressure is applied to a heat transfer medium portion, and, since the heat exchange tube is formed to be rolled up, a thickness of the heat transfer medium portion becomes thicker.

Further, since the conventional heat exchanger has a structure in which the heat exchange tube is wound around a combustion chamber in the form of a coil, heat exchange between the combustion gas and a heating medium is performed only in a local space around the heat exchanger formed in the form of a coil, such that there is a disadvantage in that a heat transfer area cannot be widely secured.

In order to resolve such a problem, a plate-shaped heat exchanger has recently been developed in which a plurality of plates are stacked and thus a heating medium channel and a combustion gas channel are formed in the plurality of stacked plates, such that heat exchange between a heating medium and a combustion gas is performed.

A related art relating to the above-described plate-shaped heat exchanger is disclosed in Japanese Patent Application Publication No. 2006-214628. A conventional plate heat exchanger including the plate-type heat exchanger disclosed in the above-described Patent Document is configured such that a plurality of plates are stacked and welded so as to prevent leakage of fluid between the plurality of plates.

However, the conventional plate-type heat exchanger has a structure in which a welding material is applied between adjacently stacked plates and heated and melted at a predetermined temperature for welding so that there are problems

2

in that a material cost of the welding material increases and the number of welding processes are increased.

DISCLOSURE

Technical Problem

The present invention is directed to providing a heat exchanger capable of ensuring welding quality while reducing a material cost and a process cost by reducing a portion to which a welding material is applied during production of a plate-type heat exchanger having a plurality of plates stacked and welded together.

Technical Solution

One aspect of the present invention provides a heat exchanger including a heat exchange part in which a heating medium channel (P1), through which a heating medium flows, and a combustion gas channel (P2), through which a combustion gas combusted in a burner flows, are alternately formed adjacent to each other in a space between a plurality of plates, wherein edges of a pair of plates forming the heating medium channel (P1) are weld-coupled to form a first welding part (W1), a plate forming the combustion gas channel (P2) is welded to the edge of the plate forming the heating medium channel (P1) between the pair of plates forming the heating medium channel (P1) to form a second welding part (W2), and a guide part is formed to guide a molten solution of a welding material of the first welding part (W1) to be movable to the second welding part (W2).

Advantageous Effects

In accordance with a heat exchanger of the present invention, a guide part for guiding a molten solution of a welding material of a first welding portion to be movable to a second welding portion is formed so that welding quality can be ensured while reducing a material cost and a process cost by reducing a portion to which a welding material is applied during production of a plate-type heat exchanger having a plurality of plates stacked and welded together.

Further, a flow direction of the heating medium circulating along a circumference of a combustion chamber is formed in one direction, and thus circulation of the heating medium is smoothly performed so that a pressure drop of the heating medium is minimized and local overheating is prevented such that the heat exchange efficiency can be improved.

Furthermore, a stepped level is formed on a surface of each of a protruding portion and a recessed portion, and protrusions are configured to be brought into contact with each other at corresponding positions in a heating medium channel and a combustion gas channel so that generation of turbulent flows of the heating medium and the combustion gas is induced such that the heat exchange efficiency can be improved and, at the same time, deformation of the plurality of plates due to a pressure of fluid can be prevented and pressure resistance performance can be improved.

DESCRIPTION OF DRAWINGS

FIG. 1 is a perspective view of a heat exchanger according to one embodiment of the present invention.

FIG. 2 is a front view of the heat exchanger according to one embodiment of the present invention.

3

FIG. 3 is an exploded perspective view of the heat exchanger according to one embodiment of the present invention.

FIG. 4 is an enlarged perspective view of some unit plates shown in FIG. 3.

FIG. 5 is a perspective view illustrating a flow path of a heating medium.

FIG. 6 is a cross-sectional view taken along the line A-A of FIG. 2.

FIG. 7 is a partially exploded perspective view illustrating a state in which a combustion gas pass-through portion is formed at a lower portion of the heat exchanger.

FIG. 8 is a perspective view illustrating a state in which a welding material is stacked between unit plates of the heat exchanger according to the present invention.

FIG. 9 is a partially exploded perspective view of FIG. 8.

FIG. 10 is a cutaway perspective view illustrating a state in which a welding material is interposed between a plurality of plates.

FIG. 11 is a diagram for describing an action of a molten solution of a welding material flowing between ends of a flange of a plate by a guide part.

FIG. 12 is a side view illustrating a state in which welding is completed.

FIG. 13 is a perspective view illustrating a state in which welding is completed.

FIG. 14 is a cross-sectional perspective view taken along the line B-B in FIG. 2.

FIG. 15 is a partial perspective view for describing an action of a heating medium dispersion portion.

FIG. 16 is a cross-sectional view taken along the line C-C of FIG. 2 for describing an action of a heating medium distribution portion.

FIG. 17 is a cross-sectional perspective view taken along the line D-D in FIG. 2.

FIG. 18 is a cross-sectional perspective view taken along the line E-E in FIG. 2.

** Description of Reference Numerals **

1: heat exchanger	100: heat exchange part
100-1 to 100-12: unit plates	100a-1 to 100a-12: first plates
100B-1 to 100b-12: second plates	100c: welding material
100-A: first heat exchange part	100-B: second heat exchange part
100-C: third heat exchange part	101: heating medium inlet
102: heating medium outlet	110: first flat surface
120: protruding portion	120a: first protruding piece
120b: second protruding piece	121: first protrusion
122: second protrusion	
123: first heating medium dispersion portion	
123': opened portion	123'': blocking portion
124: first heating medium distribution portion	
130: first flange	131: first incised portion
132: convex portion	140: second flat surface
150: recessed portion	150a: first recessed piece
150b: second recessed piece	151: third protrusion
152: fourth protrusion	
153: second heating medium dispersion portion	
153': opened portion	153'': blocked portion
154: second heating medium distribution portion	
160: second flange	161: second incised portion
162: concave portion	A1: first opening
A2: second opening	H1 to H4: through-holes
H1' and H3': first blocked portions	
H2' and H4': second blocked portions	
P1: heating medium channel	
P2: combustion gas channel	
W1: first welding part	W2: second welding part

4

MODES OF THE INVENTION

Hereinafter, configurations and operations for preferred embodiments of the present invention will be described in detail with reference to the accompanying drawings.

Referring to FIGS. 1 to 7, a heat exchanger 1 according to one embodiment of the present invention includes a heat exchange part 100 configured with a plurality of plates stacked at a circumference of a combustion chamber C in which combustion heat and a combustion gas are generated by combustion of a burner (not shown).

The heat exchange part 100 may have a structure in which a plurality of plates are to be upright along a longitudinal direction and are stacked from a front side to a rear side, and a plurality of heat exchange parts 100-A, 100-B, and 100-C are stacked. Therefore, the burner may be assembled by being horizontally inserted into the combustion chamber C from the front side, and thus convenience in attachment or detachment of the burner and in maintenance of the heat exchanger 1 may be improved.

For example, the plurality of plates may be configured with first to twelfth unit plates 100-1, 100-2, 100-3, 100-4, 100-5, 100-6, 100-7, 100-8, 100-9, 100-10, 100-11, and 100-12, and the first to twelfth unit plates 100-1, 100-2, 100-3, 100-4, 100-5, 100-6, 100-7, 100-8, 100-9, 100-10, 100-11, and 100-12 are configured with first plates 100a-1, 100a-2, 100a-3, 100a-4, 100a-5, 100a-6, 100a-7, 100a-8, 100a-9, 100a-10, 100a-11, and 100a-12, respectively, which are disposed at front positions of the first to twelfth unit plates 100-1, 100-2, 100-3, 100-4, 100-5, 100-6, 100-7, 100-8, 100-9, 100-10, 100-11, and 100-12, and second plates 100b-1, 100b-2, 100b-3, 100b-4, 100b-5, 100b-6, 100b-7, 100b-8, 100b-9, 100b-10, 100b-11, and 100b-12, which are stacked in rear of the first plates 100a-1, 100a-2, 100a-3, 100a-4, 100a-5, 100a-6, 100a-7, 100a-8, 100a-9, 100a-10, 100a-11, and 100a-12, respectively.

A heating medium channel P1, through which a heating medium flows, is formed between a first plate and a second plate constituting each unit plate, and a combustion gas channel P2, through which a combustion gas flows, is formed between a second plate constituting one unit plate, which is disposed at one side, among adjacently stacked unit plates and a first plate constituting another unit plate, which is disposed at the other side, thereamong. The heating medium channel P1 and the combustion gas channel P2 are alternately formed adjacent to each other between the plurality of plates to allow heat exchange between the heating medium and the combustion gas.

Referring to FIGS. 3 to 5, the first plate includes a first flat surface 110 having a first opening A1 formed at a central portion thereof, a protruding portion 120 formed to protrude from the first flat surface 110 to the front side and having sections being communicated in a circumferential direction, and a first flange 130 extending from an edge of the first flat surface 110 to the rear side.

The second plate includes a second flat surface 140 having a second opening A2 formed at a central portion thereof to correspond to the first opening A1 in a front-rear direction and configured to be brought into contact with the first flat surface 110, a recessed portion 150 formed to protrude from the second flat surface 140 to the rear side, having sections being communicated in a circumferential direction, and configured to form the heating medium channel P1 between the protruding portion 120 and the recessed portion 150, and a second flange 160 extending from an edge

5

of the second flat surface **140** to the rear side and configured to be coupled to a first flange **130** of a unit plate disposed next to the second plate.

In FIGS. **3** and **5**, arrows indicate flow directions of the heating medium.

Referring to FIG. **5**, the heat exchange part **100** is configured in a structure in which a plurality of heat exchange parts are stacked, and, for example, the heat exchange part **100** may be configured with first heat exchange part **100-A**, a second heat exchange part **100-B**, and a third heat exchange part **100-C**. The heating medium channel **P1** in the plurality of heat exchange parts **100-A**, **100-B**, and **100-C** is configured such that a flow direction of the heating medium is formed in only one direction. That is, a flow direction of a heating medium in each of the plurality of heat exchange parts **100-A**, **100-B**, and **100-C** is directed in one direction, but flow directions of heating media in adjacent heat exchange parts among the plurality of heat exchange units **100-A**, **100-B**, and **100-C** are formed in series and directed in opposite directions (a clockwise direction and a counterclockwise direction). Further, the heating medium channels **P1** are formed in parallel at a plurality of unit plates constituting each of the heat exchange parts **100-A**, **100-B**, and **100-C**.

A configuration for a unidirectional flow of the heating medium will be described below.

Referring to FIGS. **3** and **4**, the first through-hole **H1** and the second through-hole **H2** are formed adjacent to each other at one side of an upper portion of the first plate, and the third through-hole **H3** corresponding to the first through-hole **H1** and the fourth through-hole **H4** corresponding to the second through-hole **H2** are formed at one side of an upper portion of the second plate.

At one side of an upper portion of the first plate **100a-1** disposed at a foremost position, a first blocked portion **H1'** is formed at a position corresponding to the first through-hole **H1**, and the heating medium outlet **102** is formed at a position corresponding to the second through-hole **H2**.

At one side of an upper portion of the second plate **100b-12** disposed at a rearmost position, the heating medium inlet **101** is formed at a position corresponding to the third through-hole **H3**, and a fourth blocked portion **H4'** is formed at a position corresponding to the fourth through-hole **H4**.

Further, the fourth blocked portion **H4'** is formed at a position corresponding to the fourth through-hole **H4** on the second plate **100b-4** of the fourth unit plate **100-4**, a second blocked portion **H2'** is formed at a position corresponding to the second through-hole **H2** on the first plate **100a-5** of the fifth unit plate **100-5**, a third blocked portion **H3'** is formed at a position corresponding to the third through-hole **H3** on the second plate **100b-8** of the eighth unit plate **100-8**, and the first blocked portion **H1'** is formed at a position corresponding to the first through-hole **H1**, on the first plate **100a-9** of the ninth unit plate **100-9**.

Therefore, a heating medium flowing into the heating medium channel **P1** of the twelfth unit plate **100-12** through the heating medium inlet **101** formed in the second plate **100b-12** of the twelfth unit plate **100-12** disposed at the rearmost position flows to the front side through the first to fourth through-holes **H1**, **H2**, **H3**, and **H4** formed in the twelfth to ninth unit plates **100-12**, **100-11**, **100-10**, and **100-9**, and at the same time, since the first blocked portion **H1'** is formed at the first plate **100a-9** of the ninth unit plate **100-9**, the heating medium flows in a clockwise direction in the heating medium channels **P1** inside the twelfth to ninth unit plates **100-12**, **100-11**, **100-10**, and **100-9**.

6

Further, the heating medium flowing into the heating medium channel **P1** of the eighth unit plate **100-8** through the second through-hole **H2** formed in the first plate **100a-9** of the ninth unit plate **100-9** and the fourth through-hole **H4** formed in the second plate **100b-8** of the eighth unit plate **100-8** flows to the front side through the first to fourth through-holes **H1**, **H2**, **H3**, and **H4** formed in the eighth to fifth unit plates **100-8**, **100-7**, **100-6**, and **100-5**, and at the same time, since the second blocked portion **H2'** is formed at the first plate **100a-5** of the fifth unit plate **100-5**, the heating medium flows in a counterclockwise direction in the heating medium channels **P1** inside the eighth to fifth unit plates **100-8**, **100-7**, **100-6**, and **100-5**.

Furthermore, the heating medium flowing into the heating medium channel **P1** of the fourth unit plate **100-4** through the first through-hole **H1** formed in the first plate **100a-5** of the fifth unit plate **100-5** and the third through-hole **H3** formed in the second plate **100b-5** of the fourth unit plate **100-4** flows to the front side through the first to fourth through-holes **H1**, **H2**, **H3**, and **H4** formed into the fourth to first unit plates **100-4**, **100-3**, **100-2**, and **100-1**, and at the same time, since the first blocked portion **H1'** is formed at the first plate **100a-1** of the first unit plate **100-1**, the heating medium flows in the clockwise direction in the heating medium channels **P1** inside the fourth to first unit plates **100-4**, **100-3**, **100-2**, and **100-1**.

As described above, in the structure in which the heat exchange part **100** is formed to be upright along a longitudinal direction, heating medium connection channels configured with the heating medium channels **P1** and the first to fourth through-holes **H1**, **H2**, **H3**, and **H4** are formed to allow the heating medium to flow in one direction so that the heating medium flowing along the circumference of the combustion chamber **C** circulates smoothly such that a pressure drop of the heating medium is minimized and local overheating thereof is prevented, thus improving thermal efficiency.

Further, a capacity of the heat exchanger may be increased without a pressure drop by adjusting the number of parallel channels in each of the heat exchange parts **100-A**, **100-B**, and **100-C** when the capacity of the heat exchanger is increased.

Referring to FIGS. **6** and **7**, the combustion gas generated by combustion of the burner in the combustion chamber **C** is discharged downward through the lower portion of the heat exchange part **100**.

As a configuration for allowing the combustion gas to be smoothly discharged by passing through the combustion gas channels **P2**, a configuration in which the first and second plates are stacked, the first flange **130** of the first plate and the second flange **160** of the second plate are partially overlapped with each other, and the combustion gas pass-through portion **D** through which the combustion gas, which is flowing by passing through the combustion gas channels **P2**, is discharged is formed at some region of the edges of the first plate and the second plate.

A plurality of first incised portions **131** are formed at a combustion gas discharge side of the first flange **130**, a plurality of second incised portions **161** are formed at a combustion gas discharge side of the second flange **160**, and when the first plate and the second plate are stacked, the combustion gas pass-through portion **D** is formed at some regions of the first incised portion **131** and the second incised portion **161**.

A plurality of combustion gas pass-through portions **D** are formed to be spaced apart from each other in lateral and longitudinal directions at the lower portion of the heat

exchange part **100**, and thus the combustion gas passing through the heat exchange part **100** may be distributed and discharged at a uniform flow rate across an entire region of the lower portion of the heat exchange part **100** such that flow resistance of the discharged combustion gas is reduced and noise and vibration are prevented.

Hereinafter, a configuration and an action in which a plurality of plates are stacked and welded will be described with reference to FIGS. **8** to **13**.

The plurality of plates are configured in a structure capable of being welded using a welding material **100c** which is commonly used by a first welding part **W1** in which an end of the first flange **130** of the first plate and an end of the second flange **160** of the second plate are welded, wherein the first plate and the second plate form the heating medium channel **P1**, and a second welding portion **W2** in which an end of the second flange **160** formed at a second plate of a unit plate disposed at one side of adjacent unit plates and an end of the first flange **130** formed at a first plate of a unit plate disposed at the other side of the adjacent unit plates are welded.

As a configuration for the foregoing, guide parts **132** and **162** are included to guide a molten solution of a welding material of the first welding part **W1** to be movable to the second welding part **W2**.

The guide parts **132** and **162** include a convex portion **132** convexly protruding outward from an edge of a first plate, which is disposed at one side and forms the heating medium channel **P1**, and a concave portion **162** incised inward from an edge of a second plate, which is disposed at the other side and forms the heating medium channel **P1**, and partially overlapping with the convex portion **132** to form a gap to allow a molten solution of the welding material **100c** to be movable.

The convex portion **132** and the concave portion **162** are respectively formed along the edges of the first plate and the second plate at predetermined intervals.

Therefore, as indicated by an arrow in FIG. **11**, the molten solution of the welding material **100c** applied between the first plate **100a-1** and the second plate **100b-1** flows along the gap formed at the overlapping region between the convex portion **132** and the concave portion **162** to form the first welding part **W1** at a boundary between the first plate **100a-1** and the second plate **100b-1**, and, at the same time, the molten solution further flows to a boundary between the second plate **100b-1** and the first plate **100a-2** adjacent thereto to form the second welding part **W2**.

As shown in FIG. **9**, even though the welding material **100c** is alternately applied between the plurality of plates, the first plate, the second plate, and the first plate adjacent thereto may be simultaneously welded. To compare with a conventional structure in which a welding material is applied between every plate, in the present invention, it is possible to ensure welding quality while reducing a material cost and a production cost by reducing a region to which the welding material is applied during production of the plate-type heat exchanger.

Meanwhile, in a section where the flow direction of the heating medium is switched in the heat exchange parts **100-A**, **100-B**, and **100-C**, that is, a section connected from the third heat exchange part **100-C** to the second heat exchange part **100-B**, or a section connected from the second heat exchange part **100-B** to the first heat exchange part **100-A**, a flow rate of the heating medium flowing to the heating medium channel **P1** formed in each of the heat exchange parts **100-A**, **100-B**, and **100-C** may tend to be unevenly distributed by inertia and pressure.

As described above, when a flow rate is unevenly distributed to the heating medium channels **P1**, there are problems in that performance of heat exchange is degraded, and noise and foreign materials are generated due to boiling of the heating medium caused by local overheating in a region where the flow rate is low.

As a part for resolving the problem of non-uniform distribution in flow rate of the heating medium, as shown in FIGS. **14** and **15**, heating medium dispersion portions **123** and **153**, at which opened portions **123'** and **153'** and blocked portions **123''** and **153''** are formed, are provided at inlet parts, through which the heating medium flows into the heating medium channel **P1**, or outlet parts, through which the heating medium flows out from the heating medium channel **P1**.

A plurality of heating medium dispersion portions **123** and **153** are provided to be spaced apart in the flow direction of the heating medium, and the opened portions **123'** and **153'** and the blocked portions **123''** and **153''** are provided to intersect with each other along the flow direction of the heating medium between adjacently disposed heating medium dispersion portions **123** and **153**.

The opened portions **123'** and **153'** and the blocked portions **123''** and **153''** are alternately formed in the heating medium dispersion portions **123** and **153** in a circumferential direction thereof.

Thus, as indicated by arrows in FIG. **15**, the heating medium having passed through a first opened portion **123'** formed at the first heating medium dispersion portion **123** is dispersed by colliding with a second blocked portion **153''** of the second heating medium dispersion portion **153** located behind the first opened portion **123'**, and the heating medium having passed through a second opened portion **153'** formed at the second heating medium dispersion portion **153** is dispersed by colliding with the first blocked portion **123''** of the first heating medium dispersion portion **123** located behind the second opened portion **153'**, and inertia of the heating medium is alleviated by such a dispersion action so that a flow rate of the heating medium flowing to the heating medium channel **P1** of each layer may be evenly adjusted.

As another part for resolving the problem of non-uniform distribution in flow rate of the heating medium, as shown in FIGS. **14** and **16**, heating medium distribution portions **124** and **154** are provided at portions of the heating medium channel **P1** where the flow direction of the heating medium is switched, thereby narrowing the heating medium channel **P1**.

The heating medium distribution portions **124** and **154** may be formed in embossed shapes protruding toward the heating medium channel **P1** in portions where the heating medium flows into and out from the heating medium channel **P1**.

Therefore, a cross-sectional area of a channel formed between a first heating medium distribution portion **124** formed at the first plate and a second heating medium distribution portion **154** formed at the second plate is formed to be smaller than a cross-sectional area of the heating medium channel **P1** formed between the first plate and the second plate, and thus a phenomenon in which the heating medium is intensively flowed into some of the heating medium channels **P1** of layers may be prevented so that a flow rate of the heating medium flowing through the heating medium channel **P1** of each layer may be evenly adjusted.

Meanwhile, referring to FIG. **4**, the protruding portion **120** formed at the first plate is configured such that a first protruding piece **120a** and a second protruding piece **120b** having different heights in a front-rear direction are alter-

nately disposed along a circumferential direction, and the recessed portion **150** formed at the second plate is configured such that a first recessed piece **150a** and a second recessed piece **150b** having different heights in the front-rear direction are alternately disposed along the circumferential direction. As described above, a stepped level is formed at each of the protruding portion **120** and the recessed portion **150** so that heat exchange efficiency may be improved by inducing a turbulent flow to be actively generated in the flows of the heating medium and the combustion gas.

Referring to FIG. 17, a plurality of first protrusions **121** protruding toward the heating medium channel **P1** are formed in the protruding portion **120**, and a plurality of third protrusions **151** protruding toward the heating medium channel **P1** and being brought into contact with the plurality of first protrusions **121** are formed at the recessed portion **150**.

Further, referring to FIG. 18, a plurality of second protrusions **122** protruding toward the combustion gas channel **P2** are formed in the protruding portion **120**, and a plurality of fourth protrusions **152** protruding toward the combustion gas channel **P2** and being brought into contact with the plurality of second protrusions **122** are formed in the recessed portion **150**. Thus, the first protrusion **121** and the third protrusion **151** protrude inward toward the heating medium channel **P1** and are brought into contact with each other, and the second protrusion **122** and the fourth protrusion **152** protrude inward toward the combustion gas channel **P2** and are brought into contact with each other so that heat exchange efficiency can be improved by inducing a turbulent flow to be generated in the flows of the heating medium and the combustion gas, and at the same time, deformation of the plates due to a pressure of fluid can be prevented and pressure resistance performance can be improved.

The invention claimed is:

1. A heat exchanger comprising:

a plurality of plates; and

a heat exchange part in which a heating medium channel (**P1**), through which a heating medium flows, and a combustion gas channel (**P2**), through which a combustion gas combusted in a burner flows, are alternately formed adjacent to each other in a space between the plurality of plates,

wherein edges of a pair of plates forming the heating medium channel (**P1**) among the plurality of plates are weld-coupled to form a first welding part (**W1**),

edges of a pair of plates forming the combustion gas channel (**P2**) among the plurality of plates are weld-coupled to form a second welding part (**W2**), the pair of plates forming the combustion gas channel (**P2**) being a first plate and a second plate, and

a guide part is formed to guide a molten solution of a welding material of the first welding part (**W1**) to be movable to the second welding part (**W2**),

wherein the guide part includes:

a convex portion (**132**) convexly protruding outward from an edge of the first plate, which is disposed at one side and forms the heating medium channel (**P1**); and

a concave portion (**162**) recessed inward from an edge of the second plate, which is disposed at the other side and forms the heating medium channel (**P1**), partially overlapping with the convex portion (**132**), and forming a gap to allow the molten solution of the welding material to be movable,

wherein a plurality of convex portions (**132**) are formed along the edge of the first plate at predetermined

intervals, and a plurality of concave portions (**162**) are formed along the edge of the second plate at predetermined intervals.

2. The heat exchanger of claim 1, wherein:

the plurality of plates are formed by stacking a plurality of unit plates, wherein a first plate and a second plate are stacked in each of the plurality of unit plates,

the heating medium channel (**P1**) is formed between the first plate and the second plate,

the combustion gas channel (**P2**) is formed between a second plate of a unit plate disposed at one side of adjacently disposed unit plates, and a first plate of a unit plate disposed at the other side of the adjacently disposed unit plates, and

the welding material is interposed between the first plate and the second plate which form the heating medium channel (**P1**).

3. The heat exchanger of claim 1, wherein:

the plurality of plates are formed by stacking a plurality of unit plates, wherein a first plate and a second plate are stacked in each of the plurality of unit plates,

a first flat surface (**110**) having a first opening (**A1**) formed at a central portion thereof, a protruding portion (**120**) formed to protrude from the first flat surface (**110**) to a front side and having sections being communicated in a circumferential direction, and a first flange (**130**) extending from an edge of the first flat surface (**110**) to a rear side are formed on the first plate,

a second flat surface (**140**) having a second opening (**A2**) formed at a central portion thereof to correspond to the first opening (**A1**) in a front-rear direction and configured to be brought into contact with the first flat surface (**110**), a recessed portion (**150**) formed to protrude from the second flat surface (**140**) to a rear side, having sections being communicated in a circumferential direction, and configured to form the heating medium channel (**P1**) between the protruding portion (**120**) and the recessed portion (**150**), and a second flange (**160**) extending from an edge of the second flat surface (**140**) to the rear side and configured to be coupled to the first flange (**130**) of a unit plate, which is disposed next to the second plate, are formed on the second plate, and the guide part is formed at an edge of each of the first flange (**130**) and the second flange (**160**).

4. The heat exchanger of claim 3, wherein:

the protruding portion (**120**) is configured with a first protruding piece (**120a**) and a second protruding piece (**120b**), which are alternately disposed along a circumferential direction and have different heights in the front-rear direction, and

the recessed portion (**150**) is configured with a first recessed piece (**150a**) and a second recessed piece (**150b**), which are alternately disposed along the circumferential direction and have different heights in the front-rear direction.

5. The heat exchanger of claim 3, wherein:

a plurality of protrusions (**121**) protruding toward the heating medium channel (**P1**) are formed at the protruding portion (**120**), and

a plurality of protrusions (**151**) protruding toward the heating medium channel (**P1**) and being brought into contact with the plurality of protrusions (**121**) are formed at the recessed portion (**150**).

6. The heat exchanger of claim 3, wherein:

a plurality of protrusions (**122**) protruding toward the combustion gas channel (**P2**) are formed at the protruding portion (**120**), and

11

a plurality of protrusions (152) protruding toward the combustion gas channel (P2) and being brought into contact with the plurality of protrusions (122) are formed at the recessed portion (150).

7. The heat exchanger of claim 1, wherein:

the heat exchange part is configured to surround a combustion chamber (C) provided at a central portion of the heat exchange part, and a plurality of the heat exchange part is provided in a stacked structure, and

each of the heating medium channels (P1) of the plurality of heat exchange parts is formed to direct a flow of the heating medium in one direction, and the heating medium channels (P1) of adjacently disposed heat exchange parts among the plurality of heat exchange parts are formed in series to direct flows of the heating media in opposite directions.

8. The heat exchanger of claim 7, wherein the heating medium channels (P1) are formed in parallel inside each of the plurality of heat exchange parts.

12

9. The heat exchanger of claim 7, wherein:

through-holes (H1 and H3) at one side and through-holes (H2 and H4) at the other side for providing a heating medium connection channel to allow the heating medium to flow in one direction between adjacently stacked heat exchange parts,

first blocked portions (H1' and H3') for inducing the heating medium flowing into the heating medium channel (P1) through the through-holes (H1 and H3) at the one side to flow to the through-holes (H2 and H4) at the other side via a circumference of the combustion chamber (C) in one direction, and

second blocked portions (H2' and H4') for inducing the heating medium flowing into the heating medium channel (P1) through the through-holes (H2 and H4) at the other side to flow to the through-holes (H1 and H3) at the one side via the circumference of the combustion chamber (C) in an opposite direction are formed at one side of a portion of the heat exchange part.

* * * * *