



US010912975B1

(12) **United States Patent**
Ward

(10) **Patent No.:** **US 10,912,975 B1**
(45) **Date of Patent:** **Feb. 9, 2021**

(54) **EXTENDED SKATING RINK AND METHOD OF PLAY THEREON**

(71) Applicant: **Lycurgus Barnhill Ward**, Marco Island, FL (US)

(72) Inventor: **Lycurgus Barnhill Ward**, Marco Island, FL (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/828,711**

(22) Filed: **Mar. 24, 2020**

Related U.S. Application Data

(60) Provisional application No. 62/842,913, filed on May 3, 2019.

(51) **Int. Cl.**
A63B 67/00 (2006.01)
A63C 19/10 (2006.01)
A63B 63/00 (2006.01)
A63B 69/40 (2006.01)
E01C 13/00 (2006.01)

(52) **U.S. Cl.**
CPC *A63B 67/002* (2013.01); *A63B 63/00* (2013.01); *A63B 69/40* (2013.01); *A63C 19/10* (2013.01); *E01C 13/003* (2013.01)

(58) **Field of Classification Search**
CPC *A63C 19/10*; *A63B 67/002*; *E01C 13/003*
USPC 473/476
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

823,049 A * 6/1906 Kelly A63F 7/0005
273/352
836,561 A * 11/1906 Bush A63F 7/0005
273/352

867,330 A 10/1907 Young
905,941 A 12/1908 Simpson
961,595 A * 6/1910 Fitch A63F 7/025
273/124 R

1,648,196 A 11/1927 Rohmer
2,466,613 A 4/1949 Richardson
3,277,878 A 10/1966 Pankratz

(Continued)

FOREIGN PATENT DOCUMENTS

BE 1010123 A3 1/1998
BE 1011751 A6 12/1999

(Continued)

OTHER PUBLICATIONS



Rollersport, Inc. Vintage Track Plans, (c) 1989, www.skategforum.com/pdf/track-plans.pdf (Year: 1989).*

Primary Examiner — Laura Davison
(74) *Attorney, Agent, or Firm* — Quickpatents, LLC; Kevin Prince

(57) **ABSTRACT**

A roller skating rink for players to play a skating game utilizes one or more game implements. A skating track includes a peripheral edge and a center area. The roller skating rink includes a concave peripheral wall that encloses the skating track and has a lower end and an upper end that are substantially vertically aligned. The concave peripheral wall may include one or more doorways through which the players and the game implements may traverse. One or more propelling devices are each adapted to propel one of the game implements into the roller skating rink. One or more scoring receptacles are situated for receiving one or more of the game implements therein proximate the upper end of the concave peripheral wall. A method of game play is further disclosed.

4 Claims, 6 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

3,467,073 A 9/1969 Rhodes
 3,480,257 A 11/1969 Bourn
 3,508,405 A 4/1970 Koch
 3,615,110 A 10/1971 Fugate
 3,633,862 A 1/1972 Breen
 3,838,676 A 10/1974 Kahelin
 3,923,301 A 12/1975 Myers
 3,923,304 A 12/1975 Warren
 3,941,381 A * 3/1976 Trbovich A63F 7/06
 273/317.1
 3,946,529 A 3/1976 Chevaux
 D244,306 S 5/1977 Bisch
 4,045,026 A 8/1977 Gillespie
 4,098,508 A 7/1978 Gandy
 4,172,593 A 10/1979 Palakanis
 4,194,733 A 3/1980 Whitehouse, Jr.
 4,198,043 A 4/1980 Timbes
 D256,827 S 9/1980 Allen, 3rd
 4,258,911 A 3/1981 Alexander
 4,273,339 A 6/1981 Fortunato
 4,278,247 A 7/1981 Joppe
 4,286,806 A 9/1981 Bergstein
 4,379,551 A 4/1983 Ahrens
 4,492,380 A 1/1985 Saytar
 4,502,690 A 3/1985 Ruperto
 4,595,205 A 6/1986 Ruperto
 4,765,622 A 8/1988 Rienzo
 4,778,430 A 10/1988 Goldfarb
 4,805,897 A 2/1989 Dubeta
 4,909,517 A * 3/1990 Furlong A63F 7/0005
 273/352
 5,033,734 A 7/1991 Jalbert
 5,137,497 A 8/1992 Dubeta
 5,213,333 A 5/1993 Petrovich
 5,312,109 A 5/1994 Cagle
 5,320,350 A * 6/1994 Savage A63F 7/0684
 273/108.53
 5,382,028 A 1/1995 Sciandra
 5,427,574 A 6/1995 Donnelly-Weide

5,507,271 A 4/1996 Actor
 5,524,310 A 6/1996 Farnen
 5,540,622 A 7/1996 Gold
 5,599,025 A 2/1997 Pobee-Mensah
 5,624,122 A 4/1997 Winkelhorn
 5,718,412 A 2/1998 Levanas
 5,897,438 A 4/1999 Kunz
 5,906,545 A 5/1999 Eden
 5,993,335 A 11/1999 Eden
 6,062,983 A 5/2000 Butsook
 6,149,259 A * 11/2000 Otsuka B41J 2/04525
 347/12
 6,186,902 B1 2/2001 Briggs
 6,450,891 B1 9/2002 Dubeta
 6,527,646 B1 3/2003 Briggs
 7,007,978 B1 3/2006 Purdom
 7,958,876 B2 6/2011 Lay
 8,435,142 B2 5/2013 Gibson
 9,656,136 B2 5/2017 Van Alen
 9,844,203 B1 12/2017 Mori
 D838,800 S 1/2019 Ozsoz
 10,493,343 B2 * 12/2019 Horner A63B 39/00
 10,569,160 B1 * 2/2020 Peel A63F 11/0051
 2004/0029654 A1 * 2/2004 Bates A63B 71/06
 473/415
 2007/0021241 A1 1/2007 Geller
 2009/0286609 A1 11/2009 Dyrdek

FOREIGN PATENT DOCUMENTS

CA 2087554 A1 * 7/1994 A63C 19/10
 CN 107401322 A 11/2017
 CN 207583079 U 7/2018
 EP 2196244 A2 6/2010
 EP 2628509 A1 8/2013
 FI 96486 B 3/1996
 FI 99262 C 2/1998
 FR 2669834 A1 6/1992
 RU 133429 U1 10/2013
 WO 20023400341 A1 10/2001
 WO 2011004381 A1 1/2011

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12

EXTENDED SKATING RINK AND METHOD OF PLAY THEREON

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of U.S. Provisional Patent Application 62/842,913, filed on May 3, 2019, and incorporated herein by reference.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH AND DEVELOPMENT

Not Applicable.

FIELD OF THE INVENTION

This invention relates to skating, and more particularly to an extended skating rink and a method of playing a game thereon.

BACKGROUND

Team sport on roller skates was developed as early as the 1930's and 1940's, and continues in alternative forms today as a speed and body blocking sport without playing devices, device control apparatuses, device expelling apparatuses, or a concave enclosure along the perimeter of the skating area that may be utilized as an indirect path to scoring receptacles. The lack of devices, and the tools that support the use and implementation of device play is a major shortcoming for the field and accordingly, there is a need for a sport that involves a playing surface which extends beyond the surface available to participants in the sport, and which allows for the simultaneous attempts at control of one or more playing devices (balls) which have been introduced into play by one or more device expelling apparatuses, for placement in a unique manner into one or more scoring receptacles, in a predetermined manner where the playing surface must be utilized in order to direct the playing device into one of the receptacles, and where control of the playing device is done utilizing a device handling tool, shortcomings which the present invention solves.

SUMMARY OF THE INVENTION

The present invention is a roller skating rink for players to play a skating game that utilizes one or more game implements. A skating track includes a peripheral edge and a center area. The skating track is adapted for supporting the players and the game implements thereon. In preferred embodiments the skating track is oval or oblong with curved ends. The roller skating rink includes a concave peripheral wall that encloses the skating track and has a lower end and an upper end. The lower end and the upper end are substantially vertically aligned.

In some relatively mobile embodiments, the skating track is comprised of a plurality of abutting track panels each including a portion of the peripheral edge of the skating track. Preferably each track panel includes one wall segment that is selectively attachable to the portion of the peripheral edge of the track panel.

In a more permanent installation, the track can be formed of concrete, plaster, or the like and shaped as desired. The concave peripheral wall can likewise be formed of concrete

or plaster, or may be formed with attachable wall segments made of fiberglass or the like.

In some embodiments the skating track is substantially level with a ground surface. In other embodiments wherein the skating track is oval or oblong, just the rounded or curved ends are sloped. In still other embodiments, the peripheral edge is raised with respect to the center area. In such embodiments, track panels are each raised at their portion of the peripheral edge, sloped towards the center area, preferably held-up with a sturdy stand proximate the peripheral edge and under the track panel.

The concave peripheral wall includes one or more doorways through which the players and the game implements may traverse. Preferably each doorway includes an openable door to allow the players movement between the skating track and a doorway platform when in an open position. Each door when in a closed position is flush with the concave peripheral wall and separates the doorway platform from the skating track.

Preferably the roller skating rink includes one or more propelling devices, each adapted to propel one of the game implements into the roller skating rink, such as through an open one of the doorways for example.

One or more scoring receptacles are preferably situated for receiving one or more of the game implements therein proximate the upper end of the concave peripheral wall. Each scoring receptacle is preferably oriented outwardly from the center area of the skating track, such that the game implement in order to be captured by the scoring receptacle must be moving inwardly towards the center area of the skating track. In a preferred implementation, each scoring receptacle has an opening facing the concave peripheral wall at the upper end of the concave peripheral wall, whereby a game implement rolling up the concave peripheral wall may enter the opening when the game implement reaches the upper end of the concave peripheral wall.

Each scoring receptacle allows for visual inspection of the appearance and scoring sequence of any of the game implements deposited therein. As such, preferably at least a portion of each scoring receptacle is transparent, includes netting, or the like.

An inner gutter is preferably included and takes the form of a raised curb surrounding the center area of the skating track, the inner gutter inhibiting the game implements and players from inadvertently leaving the skating track and entering the center area, which is considered out-of-bounds during play. In such an embodiment, the concave peripheral wall is also referred to as the outer gutter.

In use, a skating game is played with two or more teams each having one or more of the players attempting to direct one of the game implements into one of the scoring receptacles to score. The team that achieves a predetermined score first wins the game.

Scoring for a first team preferably takes the form of surrounding an opponent's game implement between two of the first team's game implements, each game implement being preferably one of two contrasting colors. For example, if the scoring receptacle is able to hold up to three of the game implements, a team scoring first one of their game implements into the scoring receptacle, and then one of the opponent's game implements, and then another of their game implements would score a point, referred to as a Nim. Once three of the game implements are captured by the scoring receptacle the scoring receptacle is emptied, with the game implements being returned to one of the propelling devices or "stores" to be reintroduced to the skating track in future play.

Preferably proximate each end of the skating track three of the scoring receptacles are positioned side-by-side to form a 3×3 grid of the game implements when each of the scoring receptacles has captured three of the game implements. In this way points can be obtained by surrounding one of the opponent's game implements with two of the first team's game implements either vertically, horizontally, or diagonally.

During the game, preferably when one of the game implements is captured by one of the scoring receptacles, one of the propelling device propels a corresponding game implement into the skating rink, such that there are almost always a predetermined number of the game implements in play. If there are two colors of the game implements then preferably there are always the same predetermined number of each color of the game implements in play.

The present invention is a sport rink and game that involves a playing surface which extends beyond the surface available to participants in the sport, and which allows for the simultaneous attempts at control of a plurality of game implements (balls) which have been introduced into play by one or a plurality of propelling devices, for placement in a unique manner into a plurality of scoring receptacles, in a predetermined manner where the skating track must be utilized in order to direct a ball into one of the scoring receptacles, and where control of the playing device is done utilizing a device handling tool or stick. Other features and advantages of the present invention will become apparent from the following more detailed description, taken in conjunction with the accompanying drawings, which illustrate, by way of example, the principles of the invention.

DESCRIPTION OF THE DRAWINGS

FIG. 1 is a top plan view of a one embodiment of the invention, illustrated with doors of the invention in an open position;

FIG. 2 is a top plan view of an alternate embodiment of the invention, illustrated with the doors in the open position;

FIG. 3 is a top plan view of the embodiment of FIG. 2 but with the doors each in a closed position;

FIG. 4 is a side elevational view of one embodiment of the invention;

FIG. 5 is a side elevational view of an alternate embodiment of the invention;

FIG. 6 is a side elevational view of another alternate embodiment of the invention;

FIG. 7 is a partial perspective view of a track panel and a concave peripheral wall of the invention;

FIG. 8 is a perspective view of a portion of the invention, illustrating a doorway platform with one of the doors in the open position;

FIG. 9 is a side elevational view of a portion of the invention, illustrating one of the track panels and the concave peripheral wall and further including a scoring receptacle of the invention;

FIG. 10 is a perspective view of one embodiment of the scoring receptacle;

FIG. 11 is a cross-sectional view across a longitudinal axis of the scoring receptacle, further illustrating a holder of the scoring receptacle filled with three game implements; and

FIG. 12 is a front elevational view of one embodiment of three adjacent scoring receptacles.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Illustrative embodiments of the invention are described below. The following explanation provides specific details

for a thorough understanding of and enabling description for these embodiments. One skilled in the art will understand that the invention may be practiced without such details. In other instances, well-known structures and functions have not been shown or described in detail to avoid unnecessarily obscuring the description of the embodiments.

Unless the context clearly requires otherwise, throughout the description and the claims, the words "comprise," "comprising," and the like are to be construed in an inclusive sense as opposed to an exclusive or exhaustive sense; that is to say, in the sense of "including, but not limited to." Words using the singular or plural number also include the plural or singular number respectively. Additionally, the words "herein," "above," "below" and words of similar import, when used in this application, shall refer to this application as a whole and not to any particular portions of this application. When the claims use the word "or" in reference to a list of two or more items, that word covers all of the following interpretations of the word: any of the items in the list, all of the items in the list and any combination of the items in the list. When the word "each" is used to refer to an element that was previously introduced as being at least one in number, the word "each" does not necessarily imply a plurality of the elements, but can also mean a singular element.

FIGS. 1-3 illustrate a roller skating rink 10 for players 20 (FIG. 9) to play a skating game that utilizes one or more game implements 30. A skating track 50 includes a peripheral edge 55 and a center area 54. The skating track 50 is adapted for supporting the players 20 and the game implements 30 thereon. In preferred embodiments the skating track 50 is oval or oblong with curved ends 58. In other embodiments the skating track 50 is circular, or can take other forms as desired.

The roller skating rink 10 includes a concave peripheral wall 60 that encloses the skating track 50 and has a lower end 62 and an upper end 68. The lower end 62 and the upper end 68 are substantially vertically aligned.

In some relatively mobile embodiments, the skating track 50 is comprised of a plurality of abutting track panels 40 each including a portion of the peripheral edge 55 of the skating track 50. Preferably each track panel 40 includes one wall segment 61 that is selectively attachable to the portion of the peripheral edge 55 of the track panel 40. The upper ends 68 of each wall segment 61 in such embodiments are held together with a peripheral cable or metal rod 69, latching hardware (not shown), interlocking tongue-in-groove structures (not shown), or the like.

In a more permanent installation, the skating track 50 can be formed of concrete, plaster, or the like and shaped as desired. The concave peripheral wall 60 can likewise be formed of concrete or plaster, or may be formed with attachable wall segments 61 made of fiberglass or the like. In some embodiments, ice (not shown) may cover the skating track 50 for use with ice skates.

In some embodiments the skating track 50 is substantially level with a ground surface 15 (FIG. 4). In other embodiments wherein the skating track 50 is oval or oblong, just the curved ends 58 are sloped (FIG. 5). In still other embodiments, the peripheral edge 55 is raised with respect to the center area 54 (FIG. 6). In such embodiments, track panels 40 are each raised at their portion of the peripheral edge 55, sloped towards the center area 54, preferably held-up with a sturdy stand 110 (FIG. 7) proximate the peripheral edge 55 and under the track panel 40.

The concave peripheral wall 60 includes one or more doorways 70 through which the players 20 and the game

5

implements 30 may traverse. Preferably each doorway 70 includes an openable door 75 to allow the players 20 movement between the skating track 50 and a doorway platform 80 (FIG. 8) when in an open position 135. Each openable door 75 when in a closed position 130 is flush with the concave peripheral wall 60 and separates the doorway platform 80 from the skating track 50. Each openable door 75 may take the form of one of the wall segments 61 that is pivotally attached to an adjacent wall segment 61, or that is pivotally attached or slidably attached to the doorway platform 80. The doorway platform 80 preferably has a set of steps 85 at a rear end 88 thereof.

Preferably the roller skating rink 10 includes one or more propelling devices 90, each adapted to propel one of the game implements 30 into the roller skating rink 10, such as through an open one of the doorways 70 for example. Alternately, each propelling device 90 may be cooperative with an aperture 93 (FIG. 7) in the concave peripheral wall 60 such that the propelling device 90 propels one of the game implements 30 into the roller skating rink 10 through such aperture 93. Alternately, the propelling device 90 may be positioned to propel the game implement 30 over the concave peripheral wall 60 and onto the skating track 50, or through an offset (not shown) in adjacent wall segments 61 the concave peripheral wall 60.

One or more scoring receptacles 100 (FIGS. 9-12) are preferably situated for receiving one or more of the game implements 30 therein proximate the upper end 68 of the concave peripheral wall 60. Each scoring receptacle 100 is preferably oriented outwardly from the center area 54 of the skating track 50, such that the game implement 30 in order to be captured by the scoring receptacle 100 must be moving inwardly towards the center area 54 of the skating track 50. In a preferred implementation, each scoring receptacle 100 has an opening 102 facing the concave peripheral wall 60 at the upper end 68 of the concave peripheral wall 60, whereby a game implement 30 rolling up the concave peripheral wall 60 may enter the opening 102 when the game implement 30 reaches the upper end 68 of the concave peripheral wall 60, presuming that the trajectory of the game implement 30 coincides with the opening 102.

Each scoring receptacle 100 allows for visual inspection of the appearance and scoring sequence of any of the game implements 30 deposited therein. As such, preferably at least a portion 105 (FIG. 10) of each scoring receptacle 100 is transparent, includes netting (not shown), or the like.

An inner gutter 51 is preferably included and takes the form of a raised curb surrounding the center area 54 of the skating track 50, the inner gutter 51 inhibiting the game implements 30 and players 20 from inadvertently leaving the skating track 50 and entering the center area 54, which is considered out-of-bounds during play. In such an embodiment, the concave peripheral wall 60 is also referred to as the outer gutter 60.

In use, a skating game is played with two or more teams each having one or more of the players 20 attempting to direct the game implements 30 into one of the scoring receptacles 100 to score. The team that achieves a predetermined score first wins the game.

Scoring for a first team preferably takes the form of surrounding an opponent's game implement 30 between two of the first team's game implements 30, each game implement 30 being preferably one of two contrasting colors. For example, if the scoring receptacle 100 is able to hold up to three of the game implements 30, a team scoring first one of their game implements 30 into the scoring receptacle 100, and then one of the opponent's game implements 30, and

6

then another of their game implements 30 would score a point, referred to as a "Nim" 109. Once three of the game implements 30 are captured by the scoring receptacle 100 the scoring receptacle 100 is emptied, with the game implements 30 being returned to one of the propelling devices 90 to be reintroduced to the skating track 50 in future play.

In one embodiment proximate each curved end 58 of the skating track 50 three of the scoring receptacles 100 are positioned side-by-side to form a 3x3 grid of the game implements 30 (FIG. 12) when each of the scoring receptacles has captured three of the game implements 30. In this way points can be obtained by surrounding one of the opponent's game implements 30 with two of the first team's game implements 30 either vertically, horizontally, or diagonally.

During the game, preferably when one of the game implements 30 is captured by one of the scoring receptacles 100, one of the propelling device 90 propels a corresponding game implement 30 into the roller skating rink 10, such that there are almost always a predetermined number of the game implements 30 in play. If there are two colors of the game implements 30 then preferably there are always the same predetermined number of each color of the game implements 30 in play.

In one preferred specific method of play, there are eight teams each of at least two of the players 20, where subsequent teams enter the match to replace the losing team of each round.

The game is played on the oval embodiment of the skating track 50, what is referred to as the "Cancha" 50, which is composed of flat track straightaways 57 and banked end zones 58, or curved ends 58, with both an inner gutter 51 and an outer gutter 60, or curved concave peripheral wall 60, acting as track boundaries.

The doorway 70 for players 20, and one of the propelling devices 90, or "Canon" 90 for the game implements 30, also referred to as a "Pelota" 30 (or a ball 30), is placed at the beginning of one of the curved ends 58 when moving in a counter-clockwise direction (FIG. 1). Access to the center area 54 is considered "out-of-bounds" and restricted to reserve players 20, coach players 20, referees (not shown), the chief umpire (not shown), and inactive players 20, for example.

The scoring receptacles 100, called "Mancalas" 100, may be placed in groups of three at the end of each flat track straightaway 57, and before the curved end 58. Each scoring receptacles 100 can hold, for example, up to three balls 30. The Mancalas 100 may be positioned at the upper end 68 of the outer gutter 60 and oriented to hang below the upper end 68 so that an accurately projected ball 30 must curve up into the outer gutter 60 and bank into the Mancala 100.

The skating track 50 may be marked with two of the Starting Lines 140, for example one at a point one-thirds of the flat track straightaway distance before the doorway 70 position where the Canon 90 injects Pelotas 30 into the Cancha 50. The skating track 50 may also be marked with two Pass Lines 142 along each flat track straightaway 57, for a total of four Pass Lines 142, with one placed at the intersection of the curved end 58 meets the beginning of the flat track straightway 57 (FIG. 1), and the second halfway between the first pass line 142 and the starting line 140. The skating track 50 may further be marked with two Shot Lines 144, one before each set of scoring receptacles 100 or Mancalas 100 at the end of each flat track straightaway 57.

In one embodiment of the game there are two sets of the game implements 30, or balls 30 or "Pelotas 30." A first set of the balls 30 is colored, for example, red, and a second set

of the balls **30** is colored white, with nine of the balls **30** in each set. Balls **30** may be the size and weight of regulation Cricket Balls, for example.

Each player **20** has a playing implement **35** for handling balls **30**, also referred to as a ball handling “Cesta” **35** (FIG. **9**) similar in style to a hockey stick or a shinty stick, which the players **20** use to catch and throw the balls **30** during play. The Cesta **35** preferably has the basic shape of a regulation hockey stick, but a head **36** of the Cesta **35** may be shaped to form a basket or net, similar to a Lacrosse stick head, allowing the player **20** to achieve better control of the balls **30** during play. The length of a Cesta handle **37** or stick **35** preferably extends no higher than the player’s midriff (navel).

Players **20** must wear approved safety equipment (not shown), consisting at a minimum of gloves, a helmet, with face guard, a mouth guard, shoulder, elbow and knee pads, plus other approved apparel. Players **20** are preferably using “quad” roller skates as opposed to “in-line” roller skates for safety.

Preferably all players **20** wear uniforms (not shown) consisting of jerseys, shorts and knee socks, visually distinctive from the uniforms of players **20** on other teams. A team’s uniform may have any color combination, but may not match another team in their league. Each team preferably has an alternate jersey with a reversed color combination for inter-team play and practice. A player’s socks should be mutually uniform and pulled up to knee guards.

All jerseys are preferably numbered uniquely for each player **20** in clearly visible Arabic figures in colors that contrast with the color of the jersey, displayed on both a back and on a front of the jersey.

A team shall have five of the players **20**, with a maximum of three of the players **20** on the Cancha **50** at any time. Two team players **20** in play on the Cancha **50** are preferably designated as offensive players **20**, and the third player **20** is designated as a defensive player **20**. A fourth player **20** on each team is a reserve or substitute player **20**, and may only enter play when tagged to relieve an active player **20**. The fifth player **20** shall be designated as a Coach player **20** and may only enter play on the Cancha **50** in the case of injury to an active player **20** or ejection of an active player **20** from the game.

Reserve or substitute players **20** sit in the center area **54** during regulation play. Coaches whose teams are not in the current, or the upcoming two games or rounds, may act as umpires for the current round with the exception that the coach of the third upcoming round is designated as the Chief Referee for the current round or game.

During play, a team may play as either a “Red” or a “White” team, for example, designated by a color of their helmet covers, and the color of the Pelotas **30** they are assigned. Clearly other colors could be used instead, such as green, blue, gold, black, yellow, orange, brown, or the like.

The game is played in a “Round Robin” format where the first team to win a predetermined number of points is declared the match winner. The first round a team shall play shall be determined by lot, with subsequent rounds being determined by position in the sequence of lost rounds.

Play continues until three top winners are decided, with first place going to the winner of the match, second place to the team with the second highest number of rounds won or points scored, and third place to the team with the third highest number of rounds won or points scored.

The game is played in rounds, with a match being composed of a minimum of six teams and a maximum of eight teams participating in a match. There is no time limit

on a round, which continues until one team has created a Nim **109**. In case of injury or for safety, the game may be stopped or a timeout called by an Umpire or the Chief Referee, however, neither team players **20** nor coaches may call for a timeout during a round.

A team wins a round by being the first team to create a “Nim” **109**, defined as a combination of three balls **30**, where two balls **30** are of one color and one ball **30** is of the opposing color. The team whose ball **30** “tops off” or completes the Nim **109** in a Mancala **100** with their team color Pelota **30** receives the win and score for that round. Nims **109** may be arranged in any direction in a single mancala **100** or a combination of the three Mancalas **100**. The allowable scoring lines are, in this way, reminiscent of the game of “tic-tac-toe.”

At the end of a round, the winning team of that round will remain on the skating track **50** to continue play with another team, which will enter for a new round. The new team will take on the colors of the team that is leaving the skating track **50**. The team leaving the skating track **50** will return to the “infield” or center area **54** and wait at the end of rotation to play another round.

The Chief Referee for the current round begins play by causing Pelotas **30** to be simultaneously injected (or fired) into the Cancha **50** from the canons **90** placed at each doorway **70**. Red Pelotas **30** are injected (or fired) from the canon **90** located nearest the starting line **140** of the “red” team, and white Pelotas **30** are injected (or fired) from the Canon **90** located nearest the Starting Lines **140** of the “white” team.

At the start of each round, offensive players **20** are positioned at each starting line **140**, corresponding with the Pelota **30** they have been assigned, and a defensive player **20** from each team is positioned between the opposing offensive players **20**.

Players **20** preferably may only skate the Cancha **50** in a counter-clockwise direction. Players **20** may skate facing any direction, forward or backward, but body motion remains in a counter-clockwise direction relative to the Cancha **50**.

Players **20** may pass the Pelota **30** in either a clockwise or counter-clockwise direction. Shooting a Pelota **30** into the Mancala **100** may only be done in a counter-clockwise direction. Players **20** may not “cradle” the ball **30** with their Cesta **35** more than nine seconds, at which time they may either pass, attempt a goal shot towards the scoring receptacles **100**, pass the Pelota **30** across two of the lines **140,142,144**, or yield control of the Pelota **30**.

Players **20** may compete or play using a Pelota **30** from either their own, or the other teams available Pelota **30**, however they may only score when a Pelota **30** bearing the color assigned to their team “tops off” or completes a Nim **109**, meaning that color Pelota **30** is the same for the first and third Pelotas **30** to create the Nim **109**, regardless of which team shot the Pelotas **30** into their team’s Mancala **100**.

A team may score by using any Mancala **100**, and all Mancalas **100** are in play. All Pelotas **30** are in play, however, preferably in this game there may not be more than two Pelotas **30** on the skating track **50** at any one time. A Pelota **30** may not be directed or “shot” into the Mancala **100** from any position between the “Shot Line” **144** and the next set of Mancalas **100**.

The area between the Shot Line **144** and the Starting Line **140**, also referred to as the “End Zone” **58**, shall be the banked or raised curved ends **58** of the Cancha **50**. Pelotas **30** that deposit into or top off a Mancala **100** after being shot from within the “End Zone” **58** shall be removed by an

Umpire at the direction of the Chief Referee and returned to its team inventory of Pelotas 30. The team responsible for any extra Pelotas 30 on the skating track 50 has the corresponding number of Pelotas 30 removed from play.

Players 20 may tag a relief player 20 at any time during play, but the relief player 20 may not enter the Cancha 50 until the retiring player 20 has left the Cancha 50. A player 20 may not be tagged back into the same round, nor start a subsequent round until they have been tagged back in.

Penalties shall be assessed for player actions that endanger other players 20 by causing injury, or have the potential to cause injury. A penalty shall be assessed against a player 20 for contact with an opposing team member 20 with a Cesta 35 at a level above the opposing team member's shoulders. When an opponent has the Pelota 30 or is within five yards of a Pelota 30, a player 20 can body check or block them. A body check is contact from the front between the waist and the shoulders. A player 20 may also stick check the player 20 on the stick 35 or gloves to try and knock the Pelota 30 away or to keep a player 20 from getting a free Pelota 30.

There is an area between the Mancala 100 and the Shot Line 144 called a crease 148 (FIG. 1). An opponent is not allowed to make contact in the crease 148, but they can reach in with their stick or Cesta 35 to block a shot or take control of the Pelota 30.

When a player 20 with the Pelota 30, or the Pelota 30 itself, goes out of the field of play, the opposing team gets the Pelota 30 unless the Pelota 30 goes out of bounds after a shot. In that case, the team with the player 20 closest to the Pelota 30 when it went out of bounds gets the Pelota 30.

Plays that are not allowed are called fouls. If a player 20 commits a foul, their team will have one Pelota 30 removed from active play for that round. At five personal fouls the player 20 is removed from the game. Personal fouls include tripping, unnecessary roughness, cross checking (making contact with another player 20 with the stick 35 or Cesta 35 between one's hands), slashing (a stick check not on the opponents gloves or stick 35), or illegal body checking (such as blind side and full body blocks). Some technical fouls include holding, offsides (not the right number of players 20 on the Cancha 50), stalling, and pushing. Players 20 will not at any time physically abuse any official, opponent, spectator or other person within the precincts of the match site. For purposes of this rule, physical abuse is the unauthorized touching of an official, opponent, and spectator or other person.

While a particular form of the invention has been illustrated and described, it will be apparent that various modifications can be made without departing from the spirit and scope of the invention. For example, the shape of the skating track 50 may be a figure-8, square with rounded corners, or other shape. Accordingly, it is not intended that the invention be limited, except as by the appended claims.

Particular terminology used when describing certain features or aspects of the invention should not be taken to imply that the terminology is being redefined herein to be restricted to any specific characteristics, features, or aspects of the invention with which that terminology is associated. In general, the terms used in the following claims should not be construed to limit the invention to the specific embodiments disclosed in the specification, unless the above Detailed Description section explicitly defines such terms. Accordingly, the actual scope of the invention encompasses not only the disclosed embodiments, but also all equivalent ways of practicing or implementing the invention.

The above detailed description of the embodiments of the invention is not intended to be exhaustive or to limit the invention to the precise form disclosed above or to the particular field of usage mentioned in this disclosure. While specific embodiments of, and examples for, the invention are described above for illustrative purposes, various equivalent modifications are possible within the scope of the invention, as those skilled in the relevant art will recognize. Also, the teachings of the invention provided herein can be applied to other systems, not necessarily the system described above. The elements and acts of the various embodiments described above can be combined to provide further embodiments.

All of the above patents and applications and other references, including any that may be listed in accompanying filing papers, are incorporated herein by reference. Aspects of the invention can be modified, if necessary, to employ the systems, functions, and concepts of the various references described above to provide yet further embodiments of the invention.

Changes can be made to the invention in light of the above "Detailed Description." While the above description details certain embodiments of the invention and describes the best mode contemplated, no matter how detailed the above appears in text, the invention can be practiced in many ways. Therefore, implementation details may vary considerably while still being encompassed by the invention disclosed herein. As noted above, particular terminology used when describing certain features or aspects of the invention should not be taken to imply that the terminology is being redefined herein to be restricted to any specific characteristics, features, or aspects of the invention with which that terminology is associated.

While certain aspects of the invention are presented below in certain claim forms, the inventor contemplates the various aspects of the invention in any number of claim forms. Accordingly, the inventor reserves the right to add additional claims after filing the application to pursue such additional claim forms for other aspects of the invention.

What is claimed is:

1. A method of playing a skating game with players utilizing one or more game implements, the method comprising the steps:

providing a roller skating rink comprising: a skating track having a peripheral edge and adapted for supporting the players and the game implements thereon; a concave peripheral wall enclosing the skating track and having a lower end and an upper end, the lower end extending from the peripheral edge of the skating track, the lower end and the upper end being substantially vertically aligned; the concave peripheral wall including one or more doorways to allow the players movement between the skating track and a doorway platform; the concave peripheral wall including one or more scoring receptacles situated for receiving a plurality of the game implements therein proximate the upper end thereof, the skating track formed in a loop that circumscribes a center area, the center area being out of bounds during game play;

players skating on the skating track attempting to direct one of the game implements into one of the scoring receptacles to score;

the players achieving a predetermined score first winning the game.

2. The method of claim 1 further including the step: providing one or more propelling devices each periodically propelling one of the game implements into the skating rink.

3. The method of claim 1 further including the steps:
providing for at least two visually contrasting game
implements; and

players achieving a predetermined pattern of game imple-
ments in the scoring receptacle scoring. 5

4. The method of claim 1 further including the step:
the players segregated into two or more competing teams.

* * * * *