



US010914925B2

(12) **United States Patent**  
**Tang et al.**

(10) **Patent No.:** **US 10,914,925 B2**  
(45) **Date of Patent:** **Feb. 9, 2021**

(54) **IMAGE CAPTURING OPTICAL LENS SYSTEM**

(58) **Field of Classification Search**  
CPC ..... G02B 9/62; G02B 13/04; G02B 13/0045  
(Continued)

(71) Applicant: **LARGAN PRECISION CO., LTD.**,  
Taichung (TW)

(56) **References Cited**

(72) Inventors: **Hsiang-Chi Tang**, Taichung (TW);  
**Tsung-Han Tsai**, Taichung (TW);  
**Hsin-Hsuan Huang**, Taichung (TW)

U.S. PATENT DOCUMENTS

(73) Assignee: **LARGAN PRECISION CO., LTD.**,  
Taichung (TW)

3,415,592 A 12/1968 Price  
4,787,721 A 11/1988 Fukushima et al.  
(Continued)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 5 days.

FOREIGN PATENT DOCUMENTS

CN 201302618 Y 9/2009  
CN 202256844 U 5/2012  
(Continued)

(21) Appl. No.: **16/529,756**

*Primary Examiner* — William Choi

(22) Filed: **Aug. 1, 2019**

(74) *Attorney, Agent, or Firm* — CKC & Partners Co., LLC

(65) **Prior Publication Data**

US 2019/0353879 A1 Nov. 21, 2019

**Related U.S. Application Data**

(63) Continuation of application No. 16/008,004, filed on Jun. 13, 2018, now Pat. No. 10,416,417, which is a (Continued)

(30) **Foreign Application Priority Data**

Oct. 22, 2012 (TW) ..... 101138920 A

(51) **Int. Cl.**

**G02B 13/18** (2006.01)

**G02B 9/62** (2006.01)

(Continued)


(52) **U.S. Cl.**

CPC ..... **G02B 13/0045** (2013.01); **G02B 9/62** (2013.01); **G02B 13/18** (2013.01); **G02B 27/0025** (2013.01)

(57) **ABSTRACT**

An image capturing optical lens system includes, in order from an object side to an image side, a first lens element, a second lens element, a third lens element, a fourth lens element, a fifth lens element, and a sixth lens element. The first lens element with positive refractive power has a convex object-side surface. The second lens element has refractive power. The third lens element with refractive power has a concave image-side surface. The fourth lens element has refractive power, and at least one surface thereof is aspheric. The fifth lens element with negative refractive power has a concave object-side surface and a convex image-side surface, and the surfaces thereof are aspheric. The sixth lens element with refractive power has a convex object-side surface, and an image-side surface changing from concave at a paraxial region thereof to convex at a peripheral region thereof, and the surfaces are aspheric.

**26 Claims, 23 Drawing Sheets**



**Related U.S. Application Data**

continuation of application No. 15/196,052, filed on Jun. 29, 2016, now Pat. No. 10,018,809, which is a continuation of application No. 14/556,249, filed on Dec. 1, 2014, now Pat. No. 9,405,100, which is a continuation of application No. 13/709,073, filed on Dec. 10, 2012, now Pat. No. 8,934,178.

(51) **Int. Cl.**

**G02B 13/00** (2006.01)  
**G02B 27/00** (2006.01)

(58) **Field of Classification Search**

USPC ..... 359/713, 752, 756, 757, 758  
 See application file for complete search history.

(56)

**References Cited**

U.S. PATENT DOCUMENTS

6,867,933 B2 3/2005 Matsusaka  
 7,869,142 B2 1/2011 Chen et al.  
 8,000,031 B1 8/2011 Tsai  
 8,310,767 B2 11/2012 Huang et al.  
 8,335,043 B2 12/2012 Huang  
 8,385,006 B2 2/2013 Tsai et al.  
 8,780,464 B2 7/2014 Huang  
 8,891,177 B2 11/2014 Huang  
 2004/0257677 A1 12/2004 Matsusaka

2012/0229917 A1 9/2012 Huang  
 2012/0243108 A1 9/2012 Tsai et al.  
 2012/0320463 A1 12/2012 Shabtay et al.  
 2013/0003193 A1 1/2013 Huang  
 2013/0010181 A1 1/2013 Baba  
 2013/0050846 A1 2/2013 Huang  
 2013/0215520 A1 8/2013 Lai et al.  
 2014/0071543 A1 3/2014 Shinohara  
 2014/0078603 A1 3/2014 You  
 2014/0185150 A1 7/2014 Shinohara  
 2014/0285906 A1\* 9/2014 Huang ..... G02B 13/0045  
 359/713  
 2015/0109685 A1 4/2015 Shinohara  
 2015/0124333 A1 5/2015 Noda et al.

FOREIGN PATENT DOCUMENTS

CN 202256850 U 5/2012  
 CN 202330843 U 7/2012  
 JP 58-033211 2/1983  
 JP 61-138225 6/1986  
 JP 62-183419 8/1987  
 JP 02-272512 11/1990  
 JP 2004354572 A 12/2004  
 JP 2011-085733 A 4/2011  
 KR 10-2010-0040357 A 4/2010  
 TW 201239447 A 10/2012  
 WO 2013-150755 A1 10/2013  
 WO 2014-006822 A1 1/2014

\* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6






Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14






Fig. 15




Fig. 16




Fig. 17




Fig. 18




Fig. 19




Fig. 20




Fig. 21




Fig. 22






Fig. 23

## IMAGE CAPTURING OPTICAL LENS SYSTEM

### RELATED APPLICATIONS

The present application is a continuation of the application Ser. No. 16/008,004, filed Jun. 13, 2018, which is a continuation of the application Ser. No. 15/196,052, filed Jun. 29, 2016, U.S. Pat. No. 10,018,809 issued on Jul. 10, 2018, which is a continuation of the application Ser. No. 14/556,249, filed Dec. 1, 2014, U.S. Pat. No. 9,405,100 issued on Aug. 2, 2016, which is a continuation of the application Ser. No. 13/709,073, filed Dec. 10, 2012, U.S. Pat. No. 8,934,178 issued on Jan. 13, 2015, and claims priority to Taiwan application Serial Number 101138920, filed Oct. 22, 2012, which are herein incorporated by references.

### BACKGROUND

#### Technical Field

The present invention relates to an image capturing optical lens system. More particularly, the present invention relates to a compact image capturing optical lens system applicable to electronic products.

#### Description of Related Art

In recent years, with the popularity of mobile products with camera functionalities, the demand of optical lens systems is increasing. The sensor of a conventional optical lens system is typically a CCD (Charge-Coupled Device) or a CMOS (Complementary Metal-Oxide-Semiconductor) sensor. As the advanced semiconductor manufacturing technologies have allowed the pixel size of sensors to be reduced and compact optical lens systems have gradually evolved toward the field of higher megapixels, there is an increasing demand for compact optical lens systems featuring better image quality.

A conventional compact optical lens system employed in a portable electronic product mainly adopts a four-element lens structure or a five-element lens structure such as the one disclosed in U.S. Pat. No. 7,869,142 and the one disclosed in U.S. Pat. No. 8,000,031. Due to the popularity of mobile products with high-end specifications, such as smart phones and PDAs (Personal Digital Assistants), the pixel and image-quality requirements of the compact optical lens system have increased rapidly. However, the conventional four-element lens structure or five-element lens structure cannot satisfy the requirements of the compact optical lens system.

Although there are optical lens systems with six-element lens structure, such as the one disclosed in U.S. Publication No. 2012/0229917. However, the fifth lens element of this optical lens system is not a meniscus with stronger curvature and the peripheral field of view can not be focused on the image plane; therefore, it is not favorable for resolving power and image quality.

### SUMMARY

According to one aspect of the present disclosure, an image capturing optical lens system includes, in order from an object side to an image side, a first lens element, a second lens element, a third lens element, a fourth lens element, a fifth lens element, and a sixth lens element. The first lens

element with positive refractive power has an object-side surface being convex at a paraxial region thereof. The second lens element has negative refractive power. The third lens element has refractive power. The fourth lens element has refractive power, wherein at least one of an object-side surface and an image-side surface of the fourth lens element is aspheric. The fifth lens element with negative refractive power has an object-side surface being concave and an image-side surface being convex at a paraxial region thereof, wherein the object-side surface and the image-side surface of the fifth lens element are aspheric. The sixth lens element with refractive power has an image-side surface, wherein the image-side surface of the sixth lens element changes from concave at a paraxial region thereof to convex at a peripheral region thereof, and an object-side surface and the image-side surface of the sixth lens element are aspheric. When a curvature radius of the object-side surface of the first lens element is R1, and a curvature radius of an image-side surface of the first lens element is R2, the following relationship is satisfied:

$$-3.0 < (R1+R2)/(R1-R2) < 0.$$

According to another aspect of the present disclosure, an image capturing optical lens system includes, in order from an object side to an image side, a first lens element, a second lens element, a third lens element, a fourth lens element, a fifth lens element, and a sixth lens element. The first lens element with positive refractive power has an object-side surface being convex at a paraxial region thereof. The second lens element with refractive power has an image-side surface being concave at a paraxial region thereof. The third lens element has refractive power. The fourth lens element with refractive power has an image-side surface being convex at a paraxial region thereof, wherein at least one of an object-side surface and the image-side surface of the fourth lens element is aspheric. The fifth lens element with negative refractive power has an object-side surface being concave and an image-side surface being convex at a paraxial region thereof, wherein the object-side surface and the image-side surface of the fifth lens element are aspheric. The sixth lens element with refractive power has an image-side surface, wherein the image-side surface of the sixth lens element changes from concave at a paraxial region thereof to convex at a peripheral region thereof, and an object-side surface and the image-side surface of the sixth lens element are aspheric. When an Abbe number of the fifth lens element is V5, and an Abbe number of the sixth lens element is V6, the following relationship is satisfied:

$$0.20 < V5/V6 < 0.70.$$

According to still another aspect of the present disclosure, an image capturing optical lens system includes, in order from an object side to an image side, a first lens element, a second lens element, a third lens element, a fourth lens element, a fifth lens element, and a sixth lens element. The first lens element with positive refractive power has an object-side surface being convex at a paraxial region thereof. The second lens element with negative refractive power has a concave image-side surface. The third lens element has refractive power. The fourth lens element has refractive power, wherein at least one of an object-side surface and an image-side surface of the fourth lens element is aspheric. The fifth lens element with negative refractive power has an object-side surface being concave and an image-side surface being convex at a paraxial region thereof, wherein the object-side surface and the image-side surface of the fifth lens element are aspheric. The sixth lens element with refractive power has an image-side surface, wherein the

image-side surface of the sixth lens element changes from concave at a paraxial region thereof to convex at a peripheral region thereof, and an object-side surface and the image-side surface of the sixth lens element are aspheric. When a focal length of the image capturing optical lens system is  $f$ , a focal length of the second lens element is  $f_2$ , a focal length of the fifth lens element is  $f_5$ , and a curvature radius of the image-side surface of the sixth lens element is  $R_{12}$ , the following relationships are satisfied:

$$-1.50 < f/f_5 < -0.20; \text{ and}$$

$$-1.0 < R_{12}/f_2 < 0.$$

### BRIEF DESCRIPTION OF THE DRAWINGS

The disclosure can be more fully understood by reading the following detailed description of the embodiments, with reference made to the accompanying drawings as follows:

FIG. 1 is a schematic view of an image capturing optical lens system according to the 1st embodiment of the present disclosure;

FIG. 2 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing optical lens system according to the 1st embodiment;

FIG. 3 is a schematic view of an image capturing optical lens system according to the 2nd embodiment of the present disclosure;

FIG. 4 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing optical lens system according to the 2nd embodiment;

FIG. 5 is a schematic view of an image capturing optical lens system according to the 3rd embodiment of the present disclosure;

FIG. 6 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing optical lens system according to the 3rd embodiment;

FIG. 7 is a schematic view of an image capturing optical lens system according to the 4th embodiment of the present disclosure;

FIG. 8 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing optical lens system according to the 4th embodiment;

FIG. 9 is a schematic view of an image capturing optical lens system according to the 5th embodiment of the present disclosure;

FIG. 10 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing optical lens system according to the 5th embodiment;

FIG. 11 is a schematic view of an image capturing optical lens system according to the 6th embodiment of the present disclosure;

FIG. 12 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing optical lens system according to the 6th embodiment;

FIG. 13 is a schematic view of an image capturing optical lens system according to the 7th embodiment of the present disclosure;

FIG. 14 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing optical lens system according to the 7th embodiment;

FIG. 15 is a schematic view of an image capturing optical lens system according to the 8th embodiment of the present disclosure;

FIG. 16 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing optical lens system according to the 8th embodiment;

FIG. 17 is a schematic view of an image capturing optical lens system according to the 9th embodiment of the present disclosure;

FIG. 18 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing optical lens system according to the 9th embodiment;

FIG. 19 is a schematic view of an image capturing optical lens system according to the 10th embodiment of the present disclosure;

FIG. 20 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing optical lens system according to the 10th embodiment;

FIG. 21 is a schematic view of an image capturing optical lens system according to the 11th embodiment of the present disclosure;

FIG. 22 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing optical lens system according to the 11th embodiment; and

FIG. 23 shows  $\alpha$  of the sixth lens element of the image capturing lens system as illustrated in FIG. 1.

### DETAILED DESCRIPTION

An image capturing optical lens system includes, in order from an object side to an image side, a first lens element, a second lens element, a third lens element, a fourth lens element, a fifth lens element, and a sixth lens element. The image capturing optical lens system can further include an image sensor located on an image plane.

The first lens element with positive refractive power has an object-side surface being convex at a paraxial region thereof, and can have an image-side surface being concave at a paraxial region thereof, so that the total track length of the image capturing optical lens system can be reduced by adjusting the positive refractive power of the first lens element.

The second lens element has negative refractive power, so that the aberration generated from the first lens element can be corrected. The second lens element can have an object-side surface being convex at a paraxial region thereof, and can have an image-side surface being concave at a paraxial region thereof, so that the astigmatism of the image capturing optical lens system can be corrected.

The fourth lens element can have positive refractive power, and can have an image-side surface being convex at a paraxial region thereof. Therefore, it is favorable for reducing the system sensitivity to increase the manufacturing yield rate.

The fifth lens element with negative refractive power has an object-side surface being concave at a paraxial region thereof, and has an image-side surface being convex at a paraxial region thereof. Therefore, the Petzval sum of the image capturing optical lens system can be corrected effectively, so that the peripheral field of view can be better focused on the image plane with higher resolving power.

The sixth lens element can have an object-side surface being convex at a paraxial region thereof and has an image-side surface being concave at a paraxial region thereof. Therefore, the principal point of the image capturing optical lens system can be positioned away from the image plane, and the back focal length thereof can be reduced so as to keep the image capturing optical lens system compact. Furthermore, the image-side surface of the sixth lens element changes from concave at the paraxial region thereof to convex at a peripheral region thereof, so that the angle at which the incident light projects onto the image sensor from the off-axis field can be effectively reduced to increase the

image-sensing efficiency of the image sensor, and the aberration of the off-axis field can be further corrected.

When a curvature radius of the object-side surface of the first lens element is R1, and a curvature radius of the image-side surface of the first lens element is R2, the following relationship is satisfied:  $-3.0 < (R1+R2)/(R1-R2) < 0$ . Therefore, the curvatures of the surfaces of the first lens element are proper for correcting the spherical aberration and the astigmatism of the image capturing optical lens system thereof. The total track length of the image capturing optical lens system can be reduced by adjusting the positive refractive power of the first lens element.

When a curvature radius of the object-side surface of the fifth lens element is R9, and a curvature radius of the image-side surface of the fifth lens element is R10, the following relationship is satisfied:  $-0.50 < (R9-R10)/(R9+R10) < 0$ . Therefore, the Petzval sum of the image capturing optical lens system can be effectively corrected by adjusting the curvatures of the surfaces of the fifth lens element, and the peripheral field of view can thereby be better focused on the image plane with higher resolving power. Preferably, the following relationship is satisfied:  $-0.35 < (R9-R10)/(R9+R10) < 0$ .

When an Abbe number of the fifth lens element is V5, and an Abbe number of the sixth lens element is V6, the following relationship is satisfied:  $0.20 < V5/V6 < 0.70$ . Therefore, the chromatic aberration of the image capturing optical lens system can be corrected.

When a focal length of the image capturing optical lens system is f, and a focal length of the fifth lens element is f5, the following relationship is satisfied:  $-1.50 < f/f5 < -0.20$ . Therefore, the Petzval sum of the image capturing optical lens system can be effectively corrected by adjusting the refractive power together with the curvatures of the surfaces of the fifth lens element, and the peripheral field of view can thereby be better focused on the image plane with higher resolving power. Preferably, the following relationship is satisfied:  $-1.20 < f/f5 < -0.20$ .

When a central thickness of the fifth lens element is CT5, and a central thickness of the sixth lens element is CT6, the following relationship is satisfied:  $0.10 < CT5/CT6 < 0.50$ . Therefore, the thicknesses of the lens elements are thereby favorable for manufacturing processes and yield rate; otherwise, the lens elements with an excessively thin thickness or an excessively thick thickness will be easily crackled or deformed during the manufacturing processes.

When the focal length of the image capturing optical lens system is f, and a focal length of the fourth lens element is f4, the following relationship is satisfied:  $0.6 < f/f4 < 1.8$ . Therefore, the distribution of the positive refractive power of the image capturing optical lens system can be balanced to correct the aberration by properly adjusting the refractive power of the fourth lens element.

When an axial distance between the image-side surface of the sixth lens element and the image plane is BFL, and an axial distance between the object-side surface of the first lens element and the image-side surface of the sixth lens element is Td, the following relationship is satisfied:  $0.15 < BFL/Td < 0.4$ . Therefore, it is favorable for keeping the image capturing optical lens system compact by adjusting the BFL of the image capturing optical lens system.

When an Abbe number of the first lens element is V1, an Abbe number of the second lens element is V2, and the Abbe number of the fifth lens element is V5, the following relationship is satisfied:  $0.6 < (V2+V5)/V1 < 1.0$ . Therefore, it is favorable for correcting the chromatic aberration of the image capturing optical lens system.

When a central thickness of the second lens element is CT2, and an angle between a tangent of an inflection point on the image-side surface of the sixth lens element and an optical axis is  $\alpha$ , the following relationship is satisfied:  $0 \text{ mm} < CT2/\tan(\alpha) < 0.30 \text{ mm}$ . Therefore, it is favorable for effectively reducing the angle at which the incident light projects onto the image sensor from the off-axis field to improve the image-sensing efficiency of the image sensor. Moreover, it is also favorable for correcting the aberration of the off-axis field to better assemble and manufacture the lens elements by properly adjusting the surface shape of the image-side surface of the sixth lens element and the central thickness of the second lens element. Preferably, the following relationship is satisfied:  $0 \text{ mm} < CT2/\tan(\alpha) < 0.15 \text{ mm}$ .

When a maximum image height of the image capturing optical lens system is ImgH (half of a diagonal length of an effective photosensitive area of the image sensor), and the focal length of the image capturing optical lens system is f, the following relationship is satisfied:  $0.72 < \text{ImgH}/f < 1.0$ . Therefore, it is favorable for keeping the image capturing optical lens system compact in order to be applied to the compact and portable electronic products.

When the focal length of the image capturing optical lens system is f, the focal length of the fourth lens element is f4, the focal length of the fifth lens element is f5, and a focal length of the sixth lens element is f6, the following relationship is satisfied:  $0.3 < (|f/f5| + |f/f6|)/(f/f4) < 1.5$ . Therefore, it is favorable for reducing the sensitivity to increase the manufacturing yield rate by adjusting the refractive power of the fourth lens element, the fifth lens element and the sixth lens element.

When the maximum image height of the image capturing optical lens system is ImgH, and an axial distance between the object-side surface of the first lens element and the image plane is TTL, the following relationship is satisfied:  $TTL/\text{ImgH} < 1.8$ . Therefore, it is favorable for keeping the image capturing optical lens system compact in order to be applied to the compact and portable electronic products.

When a focal length of the second lens element is f2, and a curvature radius of the image-side surface of the sixth lens element is R12, the following relationship is satisfied:  $-1.0 < R12/f2 < 0$ . Therefore, it is favorable for correcting the aberration, and the principal point of the image capturing optical lens system can be positioned away from the image plane for reducing the back focal length, so that the compact size of the image capturing optical lens system can be maintained.

According to the image capturing optical lens system of the present disclosure, the lens elements thereof can be made of plastic or glass material. When the lens elements are made of glass material, the distribution of the refractive power of the image capturing optical lens system may be more flexible to design. When the lens elements are made of plastic material, the manufacturing costs can be effectively reduced. Furthermore, the surfaces of each lens element can be aspheric, so that it is easier to make the surfaces into non-spherical shapes. As a result, more controllable variables are obtained, and the aberration is reduced, as well as the number of required lens elements can be reduced while constructing an optical system. Therefore, the total track length of the image capturing optical lens system can also be reduced.

According to the image capturing optical lens system of the present disclosure, each of the object-side surface and the image-side surface of every lens element has a paraxial region and a peripheral region. The paraxial region refers to the region of the surface where light rays travel close to an

optical axis and the peripheral region refers to the region of the surface where light rays travel away from the optical axis.

According to the image capturing optical lens system of the present disclosure, the image capturing optical lens system can include at least one stop, such as an aperture stop, a glare stop, or a field stop, etc. Said glare stop or said field stop is allocated for reducing stray light while retaining high image quality. Furthermore, an aperture stop can be configured as a front stop or a middle stop. A front stop disposed between an object and the first lens element provides a longer distance from an exit pupil of the system to the image plane and thereby the generated telecentric effect improves the image-sensing efficiency of the image sensor. A middle stop disposed between the first lens element and the image plane is favorable for enlarging the field of view of the image capturing optical lens system and thereby provides a wider field of view for the same.

According to the image capturing optical lens system of the present disclosure, the image capturing optical lens system is featured with good correcting ability and high image quality, and can be applied to 3D (three-dimensional) image capturing applications, in products such as digital cameras, mobile devices and tablets.

According to the above description of the present disclosure, the following 1st-11th specific embodiments are provided for further explanation.

#### 1st Embodiment

FIG. 1 is a schematic view of an image capturing optical lens system according to the 1st embodiment of the present disclosure. FIG. 2 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing optical lens system according to the 1st embodiment. In FIG. 1, the image capturing optical lens system includes, in order from an object side to an image side, an aperture stop **100**, a first lens element **110**, a second lens element **120**, a third lens element **130**, a fourth lens element **140**, a fifth lens element **150**, a sixth lens element **160**, an IR-cut filter **180**, an image plane **170**, and an image sensor **190**.

The first lens element **110** with positive refractive power has an object-side surface **111** being convex at a paraxial region thereof and an image-side surface **112** being concave at a paraxial region thereof. The first lens element **110** is made of plastic material and has the object-side surface **111** and the image-side surface **112** being both aspheric.

The second lens element **120** with negative refractive power has an object-side surface **121** being convex at a paraxial region thereof and an image-side surface **122** being concave at a paraxial region thereof. The second lens element **120** is made of plastic material and has the object-side surface **121** and the image-side surface **122** being both aspheric.

The third lens element **130** with negative refractive power has an object-side surface **131** being convex at a paraxial region thereof and an image-side surface **132** being concave at a paraxial region thereof. The third lens element **130** is made of plastic material and has the object-side surface **131** and the image-side surface **132** being both aspheric.

The fourth lens element **140** with positive refractive power has an object-side surface **141** being concave at a paraxial region thereof and an image-side surface **142** being convex at a paraxial region thereof. The fourth lens element

**140** is made of plastic material and has the object-side surface **141** and the image-side surface **142** being both aspheric.

The fifth lens element **150** with negative refractive power has an object-side surface **151** being concave at a paraxial region thereof and an image-side surface **152** being convex at a paraxial region thereof. The fifth lens element **150** is made of plastic material and has the object-side surface **151** and the image-side surface **152** being both aspheric.

The sixth lens element **160** with positive refractive power has an object-side surface **161** being convex at a paraxial region thereof and an image-side surface **162** changing from concave at a paraxial region thereof to convex at a peripheral region thereof. The sixth lens element **160** is made of plastic material and has the object-side surface **161** and the image-side surface **162** being both aspheric.

The IR-cut filter **180** made of glass material is located between the sixth lens element **160** and the image plane **170**, and will not affect a focal length of the image capturing optical lens system.

The equation of the aspheric surface profiles of the aforementioned lens elements of the 1st embodiment is expressed as follows:

$$X(Y) = (Y^2/R)/(1 + \text{sqrt}(1 - (1+k) \times (Y/R)^2)) + \sum_i (Ai) \times (Y^i),$$

wherein,

X is the relative distance between a point on the aspheric surface spaced at a distance Y from the optical axis and the tangential plane at the aspheric surface vertex on the optical axis;

Y is the distance from the point on the curve of the aspheric surface to the optical axis;

R is the curvature radius;

k is the conic coefficient; and

Ai is the i-th aspheric coefficient.

In the image capturing optical lens system according to the 1st embodiment, when a focal length of the image capturing optical lens system is f, an f-number of the image capturing optical lens system is Fno, and half of a maximal field of view of the image capturing optical lens system is HFOV, these parameters have the following values:

f=4.14 mm;

Fno=2.20; and

HFOV=35.4 degrees.

In the image capturing optical lens system according to the 1st embodiment, when an Abbe number of the first lens element **110** is V1, an Abbe number of the second lens element **120** is V2, an Abbe number of the fifth lens element **150** is V5, and an Abbe number of the sixth lens element **160** is V6, the following relationships are satisfied:

$$(V2+V5)/V1=0.83; \text{ and}$$

$$V5/V6=0.417.$$

In the image capturing optical lens system according to the 1st embodiment, when a central thickness of the fifth lens element **150** is CT5, and a central thickness of the sixth lens element **160** is CT6, the following relationship is satisfied:

$$CT5/CT6=0.24.$$

In the image capturing optical lens system according to the 1st embodiment, when a curvature radius of the object-side surface **111** of the first lens element **110** is R1, and a

curvature radius of the image-side surface **112** of the first lens element **110** is R2, the following relationship is satisfied:

$$(R1+R2)/(R1-R2)=-1.07.$$

In the image capturing optical lens system according to the 1st embodiment, when a curvature radius of the object-side surface **151** of the fifth lens element **150** is R9, and a curvature radius of the image-side surface **152** of the fifth lens element **150** is R10, the following relationship is satisfied:

$$(R9-R10)/(R9+R10)=-0.17.$$

In the image capturing optical lens system according to the 1st embodiment, when a focal length of the second lens element **120** is f2, and a curvature radius of the image-side surface **162** of the sixth lens element **160** is R12, the following relationship is satisfied:

$$R12/f2=-0.31.$$

In the image capturing optical lens system according to the 1st embodiment, when the focal length of the image capturing optical lens system is f, a focal length of the fourth lens element **140** is f4, a focal length of the fifth lens element **150** is f5, and a focal length of the sixth lens element **160** is f6, the following relationships are satisfied:

$$f/f4=0.89;$$

$$f/f5=-0.61; \text{ and}$$

$$(|f/f5+|f/f6|)/(f/f4)=0.73.$$

FIG. **23** shows a of the sixth lens element **160** of the image capturing lens system as illustrated in FIG. **1**. In FIG. **23**, when an angle between a tangent of an inflection point on an image-side surface **162** of a sixth lens element **160** and an optical axis is  $\alpha$ , and a central thickness of the second lens element **120** is CT2, the following relationship is satisfied:

$$CT2/\tan(\alpha)=0.05 \text{ mm.}$$

In the image capturing optical lens system according to the 1st embodiment, when an axial distance between the image-side surface **162** of the sixth lens element **160** and the image plane **170** is BFL, and an axial distance between the object-side surface **111** of the first lens element **110** and the image-side surface **162** of the sixth lens element **160** is Td, the following relationship is satisfied:

$$BFL/Td=0.29.$$

In the image capturing optical lens system according to the 1st embodiment, when a maximum image height of the image capturing optical lens system is ImgH which here is a half of the diagonal length of the photosensitive area of the image sensor **190** on the image plane **170**, the focal length of the image capturing optical lens system is f, and an axial distance between the object-side surface **111** of the first lens element **110** and the image plane **170** is TTL, the following relationships are satisfied:

$$\text{ImgH}/f=0.724; \text{ and } \text{TTL}/\text{ImgH}=1.70.$$

The detailed optical data of the 1st embodiment are shown in Table 1, and the aspheric surface data are shown in Table 2 below.

TABLE 1

1st Embodiment								
f = 4.14 mm, Fno = 2.20, HFOV = 35.4 deg.								
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal length	
0	Object	Plano	Infinity					
1	Ape. Stop	Plano	-0.283					
2	Lens 1	1.688 (ASP)	0.523	Plastic	1.544	55.9	3.20	
3		47.745 (ASP)	0.036					
4	Lens 2	3.044 (ASP)	0.240	Plastic	1.640	23.3	-6.34	
5		1.685 (ASP)	0.380					
6	Lens 3	7.907 (ASP)	0.274	Plastic	1.544	55.9	-25.07	
7		4.945 (ASP)	0.186					
8	Lens 4	-205.400 (ASP)	0.360	Plastic	1.544	55.9	4.64	
9		-2.494 (ASP)	0.347					
10	Lens 5	-0.818 (ASP)	0.300	Plastic	1.640	23.3	-6.84	
11		-1.150 (ASP)	0.072					
12	Lens 6	2.293 (ASP)	1.229	Plastic	1.544	55.9	95.61	
13		1.946 (ASP)	0.500					
14	IR-cut filter	Plano	0.300	Glass	1.517	64.2	—	
15		Plano	0.449					
16	Image	Plano	—					

Note:

Reference wavelength (d-line) is 587.6 nm.

TABLE 2

Aspheric Coefficients						
Surface #						
	2	3	4	5	6	7
k=	1.8655E-01	5.0000E+00	-2.0784E+01	-5.0621E+00	0.0000E+00	0.0000E+00
A4=	-6.1899E-04	-4.5527E-02	-7.1197E-02	2.5381E-03	-7.0538E-02	-7.8575E-02
A6=	2.8358E-02	1.2620E-01	1.2670E-01	4.2100E-02	-4.2775E-02	-1.0851E-02

TABLE 2-continued

Aspheric Coefficients						
A8=	-5.0099E-02	-1.0849E-01	-3.6051E-02	9.4901E-02	6.0982E-02	-2.6489E-02
A10=	-3.4127E-03	-1.1151E-02	-1.2216E-01	-2.2870E-01	-4.2446E-02	1.4271E-03
A12=	9.9599E-02	4.2875E-02	4.4865E-02	1.5329E-01	-4.0004E-11	-2.6097E-10
A14=	-7.7512E-02	-3.6527E-02	1.5158E-02	-2.4257E-02	—	—
Surface #						
	8	9	10	11	12	13
k=	-4.0000E+01	1.6416E+00	-3.7855E+00	-8.1718E-01	-3.1624E+01	-9.1133E+00
A4=	-9.7160E-02	-4.3991E-02	-4.9566E-02	1.3509E-01	-1.2831E-01	-5.1858E-02
A6=	-5.6079E-03	-1.7664E-02	-1.4184E-02	-3.7856E-02	7.0118E-02	2.0398E-02
A8=	6.6760E-03	2.7241E-02	1.2088E-01	1.7679E-02	-4.1873E-02	-8.2739E-03
A10=	-3.6560E-02	3.6468E-02	-5.2829E-02	8.4334E-03	2.0999E-02	2.2506E-03
A12=	-8.1389E-03	-3.5812E-03	-1.0632E-02	-3.2045E-03	-5.8979E-03	-3.8544E-04
A14=	9.1601E-02	-6.5876E-03	4.8246E-03	-2.5396E-03	8.2208E-04	3.6567E-05
A16=	-4.8470E-02	—	4.0110E-04	8.1636E-04	-4.4862E-05	-1.4339E-06

In Table 1, the curvature radius, the thickness and the focal length are shown in millimeters (mm). Surface numbers 0-16 represent the surfaces sequentially arranged from the object-side to the image-side along the optical axis. In Table 2, k represents the conic coefficient of the equation of the aspheric surface profiles. A1-A16 represent the aspheric coefficients ranging from the 1st order to the 16th order. This information related to Table 1 and Table 2 applies also to the Tables for the remaining embodiments, and so an explanation in this regard will not be provided again.

### 2nd Embodiment

FIG. 3 is a schematic view of an image capturing optical lens system according to the 2nd embodiment of the present disclosure. FIG. 4 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing optical lens system according to the 2nd embodiment. In FIG. 3, the image capturing optical lens system includes, in order from an object side to an image side, a first lens element 210, an aperture stop 200, a second lens element 220, a third lens element 230, a fourth lens element 240, a fifth lens element 250, a sixth lens element 260, an IR-cut filter 280, an image plane 270, and an image sensor 290.

The first lens element 210 with positive refractive power has an object-side surface 211 being convex at a paraxial region thereof and an image-side surface 212 being concave at a paraxial region thereof. The first lens element 210 is made of plastic material and has the object-side surface 211 and the image-side surface 212 being both aspheric.

The second lens element 220 with negative refractive power has an object-side surface 221 being convex at a paraxial region thereof and an image-side surface 222 being concave at a paraxial region thereof. The second lens

element 220 is made of plastic material and has the object-side surface 221 and the image-side surface 222 being both aspheric.

The third lens element 230 with negative refractive power has an object-side surface 231 being convex at a paraxial region thereof and an image-side surface 232 being concave at a paraxial region thereof. The third lens element 230 is made of plastic material and has the object-side surface 231 and the image-side surface 232 being both aspheric.

The fourth lens element 240 with positive refractive power has an object-side surface 241 being convex at a paraxial region thereof and an image-side surface 242 being convex at a paraxial region thereof. The fourth lens element 240 is made of plastic material and has the object-side surface 241 and the image-side surface 242 being both aspheric.

The fifth lens element 250 with negative refractive power has an object-side surface 251 being concave at a paraxial region thereof and an image-side surface 252 being convex at a paraxial region thereof. The fifth lens element 250 is made of plastic material and has the object-side surface 251 and the image-side surface 252 being both aspheric.

The sixth lens element 260 with positive refractive power has an object-side surface 261 being convex at a paraxial region thereof and an image-side surface 262 changing from concave at a paraxial region thereof to convex at a peripheral region thereof. The sixth lens element 260 is made of plastic material and has the object-side surface 261 and the image-side surface 262 being both aspheric.

The IR-cut filter 280 made of glass material is located between the sixth lens element 260 and the image plane 270, and will not affect a focal length of the image capturing optical lens system.

The detailed optical data of the 2nd embodiment are shown in Table 3, and the aspheric surface data are shown in Table 4 below.

TABLE 3

2nd Embodiment							
f = 3.64 mm, Fno = 2.00, HFOV = 39.0 deg.							
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal length
0	Object	Plano	Infinity				
1	Lens 1	2.153 (ASP)	0.458	Plastic	1.572	58.7	3.79
2		335.570 (ASP)	0.012				
3	Ape. Stop	Plano	0.016				

TABLE 3-continued

2nd Embodiment								
f = 3.64 mm, Fno = 2.00, HFOV = 39.0 deg.								
Surface #		Curvature Radius		Thickness	Material	Index	Abbe #	Focal length
4	Lens 2	2.155	(ASP)	0.240	Plastic	1.634	23.8	-7.49
5		1.418	(ASP)	0.337				
6	Lens 3	5.467	(ASP)	0.329	Plastic	1.544	55.9	-19.12
7		3.508	(ASP)	0.105				
8	Lens 4	10.749	(ASP)	0.491	Plastic	1.544	55.9	3.07
9		-1.949	(ASP)	0.300				
10	Lens 5	-0.760	(ASP)	0.285	Plastic	1.634	23.8	-4.25
11		-1.214	(ASP)	0.084				
12	Lens 6	1.725	(ASP)	1.268	Plastic	1.535	56.3	12.39
13		1.736	(ASP)	0.500				
14	IR-cut filter	Plano		0.200	Glass	1.517	64.2	—
15		Plano		0.395				
16	Image	Plano		—				

Note:

Reference wavelength (d-line) is 587.6 nm.

TABLE 4

Aspheric Coefficients						
	Surface #					
	1	2	4	5	6	7
k=	2.4457E-01	-2.0000E+01	-1.3449E+01	-4.3098E+00	-1.4316E+01	-1.0637E+01
A4=	-3.5922E-03	-3.0418E-02	-2.7734E-02	-2.1105E-02	-7.5590E-02	-7.4219E-02
A6=	3.8748E-02	1.2918E-01	6.5777E-02	3.8720E-02	-4.3505E-02	4.1101E-02
A8=	-7.2214E-02	-1.6441E-01	-1.2333E-02	7.6934E-02	3.6620E-02	-8.3615E-02
A10=	4.6314E-03	2.8122E-02	-1.4011E-01	-2.2788E-01	1.3003E-02	1.1203E-02
A12=	9.9599E-02	4.2875E-02	4.4865E-02	1.5329E-01	-5.9070E-11	1.5762E-03
A14=	-7.7512E-02	-3.6527E-02	1.5158E-02	-2.4257E-02	—	—
	Surface #					
	8	9	10	11	12	13
k=	-2.0000E+01	1.0656E+00	-3.7586E+00	-8.4885E-01	-2.0000E+01	-6.7333E+00
A4=	-8.1612E-02	-2.9725E-02	-4.8386E-02	1.3364E-01	-1.2827E-01	-4.9930E-02
A6=	3.7678E-02	-1.3289E-03	-2.1777E-02	-2.9464E-02	7.0279E-02	2.0733E-02
A8=	2.9213E-02	2.3233E-02	1.2848E-01	1.5336E-02	-4.1651E-02	-8.2814E-03
A10=	-7.4599E-02	3.7969E-02	-5.0342E-02	7.8336E-03	2.0986E-02	2.2581E-03
A12=	-4.2027E-02	1.7118E-03	-1.2548E-02	-3.0509E-03	-5.9073E-03	-3.8625E-04
A14=	1.1763E-01	-6.0820E-03	4.0294E-03	-2.4660E-03	8.2073E-04	3.6257E-05
A16=	-4.8470E-02	—	1.3739E-03	7.9323E-04	-4.4360E-05	-1.3893E-06

In the image capturing optical lens system according to the 2nd embodiment, the definitions of these parameters shown in the following table are the same as those stated in the 1st embodiment with corresponding values for the 2nd embodiment. Moreover, these parameters can be calculated from Table 3 and Table 4 as the following values and satisfy the following relationships:

f (mm)	3.64	R12/f2	-0.23
Fno	2.00	f/f4	1.18
HFOV (deg.)	39.0	f/f5	-0.86
(V2 + V5)/V1	0.81	( f/f5  +  f/f6 )/(f/f4)	0.97
V5/V6	0.423	CT2/tan( $\alpha$ ) (mm)	0.06
CT5/CT6	0.22	BFL/Td	0.26
(R1 + R2)/(R1 - R2)	-1.01	ImgH/f	0.824
(R9 - R10)/(R9 + R10)	-0.23	TTL/ImgH	1.65

## 3rd Embodiment

FIG. 5 is a schematic view of an image capturing optical lens system according to the 3rd embodiment of the present disclosure. FIG. 6 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing optical lens system according to the 3rd embodiment. In FIG. 5, the image capturing optical lens system includes, in order from an object side to an image side, an aperture stop 300, a first lens element 310, a second lens element 320, a third lens element 330, a fourth lens element 340, a fifth lens element 350, a sixth lens element 360, an IR-cut filter 380, an image plane 370, and an image sensor 390.

The first lens element 310 with positive refractive power has an object-side surface 311 being convex at a paraxial region thereof and an image-side surface 312 being convex at a paraxial region thereof. The first lens element 310 is made of plastic material and has the object-side surface 311 and the image-side surface 312 being both aspheric.



## 15

The second lens element **320** with negative refractive power has an object-side surface **321** being convex at a paraxial region thereof and an image-side surface **322** being concave at a paraxial region thereof. The second lens element **320** is made of plastic material and has the object-side surface **321** and the image-side surface **322** being both aspheric.

The third lens element **330** with negative refractive power has an object-side surface **331** being convex at a paraxial region thereof and an image-side surface **332** being concave at a paraxial region thereof. The third lens element **330** is made of plastic material and has the object-side surface **331** and the image-side surface **332** being both aspheric.

The fourth lens element **340** with positive refractive power has an object-side surface **341** being convex at a paraxial region thereof and an image-side surface **342** being convex at a paraxial region thereof. The fourth lens element **340** is made of plastic material and has the object-side surface **341** and the image-side surface **342** being both aspheric.

## 16

The fifth lens element **350** with negative refractive power has an object-side surface **351** being concave at a paraxial region thereof and an image-side surface **352** being convex at a paraxial region thereof. The fifth lens element **350** is made of plastic material and has the object-side surface **351** and the image-side surface **352** being both aspheric.

The sixth lens element **360** with positive refractive power has an object-side surface **361** being convex at a paraxial region thereof and an image-side surface **362** changing from concave at a paraxial region thereof to convex at a peripheral region thereof. The sixth lens element **360** is made of plastic material and has the object-side surface **361** and the image-side surface **362** being both aspheric.

The IR-cut filter **380** made of glass material is located between the sixth lens element **360** and the image plane **370**, and will not affect a focal length of the image capturing optical lens system.

The detailed optical data of the 3rd embodiment are shown in Table 5, and the aspheric surface data are shown in Table 6 below.

TABLE 5

3rd Embodiment								
f = 4.20 mm, Fno = 2.07, HFOV = 37.6 deg.								
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal length	
0	Object	Plano	Infinity					
1	Ape. Stop	Plano	-0.217					
2	Lens 1	2.370 (ASP)	0.483	Plastic	1.543	56.5	3.96	
3		-21.803 (ASP)	0.050					
4	Lens 2	2.747 (ASP)	0.240	Plastic	1.650	21.4	-7.65	
5		1.708 (ASP)	0.338					
6	Lens 3	8.160 (ASP)	0.461	Plastic	1.543	56.5	-39.26	
7		5.785 (ASP)	0.197					
8	Lens 4	305.985 (ASP)	0.456	Plastic	1.543	56.5	4.22	
9		-2.310 (ASP)	0.386					
10	Lens 5	-0.914 (ASP)	0.285	Plastic	1.640	23.3	-7.70	
11		-1.258 (ASP)	0.192					
12	Lens 6	1.715 (ASP)	0.900	Plastic	1.543	56.5	135.54	
13		1.431 (ASP)	0.800					
14	IR-cut filter	Plano	0.300	Glass	1.517	64.2	—	
15		Plano	0.400					
16	Image	Plano	—					

Note:

Reference wavelength (d-line) is 587.6 nm.

TABLE 6

Aspheric Coefficients						
	Surface #					
	2	3	4	5	6	7
k=	2.5381E-01	-2.0000E+01	-1.9708E+01	-5.5454E+00	2.8590E+00	-1.2693E+01
A4=	-4.3261E-04	-3.7924E-04	-1.8028E-02	-3.3774E-02	-5.5935E-02	-6.6442E-02
A6=	1.0703E-02	6.4702E-02	2.8578E-02	1.8018E-02	-1.9881E-02	1.9509E-02
A8=	-1.6978E-02	-8.8112E-02	-1.8991E-02	3.8009E-02	1.5339E-02	-4.5863E-02
A10=	7.9623E-05	3.3050E-02	-3.9010E-02	-9.9688E-02	5.6330E-03	6.6107E-03
A12=	2.8188E-02	6.1037E-03	1.7352E-02	5.4569E-02	-6.2692E-04	4.0076E-03
A14=	-2.1606E-02	-1.5862E-02	-8.7443E-03	-8.0099E-03	—	—
	Surface #					
	8	9	10	11	12	13
k=	-2.0000E+01	1.1076E+00	-3.7451E+00	-7.8937E-01	-1.2153E+01	-5.8456E+00
A4=	-7.6005E-02	-3.0540E-02	-3.9649E-02	1.0498E-01	-1.1171E-01	-5.3577E-02
A6=	-3.8014E-03	-5.8796E-03	-1.5555E-02	-1.9811E-02	4.2713E-02	1.5409E-02
A8=	1.2471E-02	8.1726E-03	6.4762E-02	8.4971E-03	-2.1124E-02	-4.5079E-03

TABLE 6-continued

Aspheric Coefficients						
A10=	-2.7696E-02	1.4417E-02	-2.1115E-02	3.4516E-03	8.9390E-03	9.5885E-04
A12=	-1.1912E-02	7.0797E-04	-4.0215E-03	-1.0628E-03	-2.0697E-03	-1.3318E-04
A14=	3.4966E-02	-9.5575E-04	1.2756E-03	-7.0899E-04	2.3709E-04	1.0479E-05
A16=	-1.2080E-02	—	2.4717E-04	1.8710E-04	-1.0734E-05	-3.5225E-07

In the image capturing optical lens system according to the 3rd embodiment, the definitions of these parameters shown in the following table are the same as those stated in the 1st embodiment with corresponding values for the 3rd embodiment. Moreover, these parameters can be calculated from Table 5 and Table 6 as the following values and satisfy the following relationships:

f (mm)	4.20	R12/f2	-0.19
Fno	2.07	f/f4	1.00
HFOV (deg.)	37.6	f/f5	-0.55
(V2 + V5)/V1	0.79	( f/f5  +  f/f6 )/(f/f4)	0.58
V5/V6	0.412	CT2/tan( $\alpha$ ) (mm)	0.07
CT5/CT6	0.32	BFL/Td	0.35
(R1 + R2)/(R1 - R2)	-0.80	ImgH/f	0.785
(R9 - R10)/(R9 + R10)	-0.16	TTL/ImgH	1.63

#### 4th Embodiment

FIG. 7 is a schematic view of an image capturing optical lens system according to the 4th embodiment of the present disclosure. FIG. 8 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing optical lens system according to the 4th embodiment. In FIG. 7, the image capturing optical lens system includes, in order from an object side to an image side, an aperture stop 400, a first lens element 410, a second lens element 420, a third lens element 430, a fourth lens element 440, a fifth lens element 450, a sixth lens element 460, an IR-cut filter 480, an image plane 470, and an image sensor 490.

The first lens element 410 with positive refractive power has an object-side surface 411 being convex at a paraxial region thereof and an image-side surface 412 being concave at a paraxial region thereof. The first lens element 410 is made of plastic material and has the object-side surface 411 and the image-side surface 412 being both aspheric.

The second lens element 420 with negative refractive power has an object-side surface 421 being convex at a

paraxial region thereof and an image-side surface 422 being concave at a paraxial region thereof. The second lens element 420 is made of plastic material and has the object-side surface 421 and the image-side surface 422 being both aspheric.

The third lens element 430 with positive refractive power has an object-side surface 431 being convex at a paraxial region thereof and an image-side surface 432 being concave at a paraxial region thereof. The third lens element 430 is made of plastic material and has the object-side surface 431 and the image-side surface 432 being both aspheric.

The fourth lens element 440 with positive refractive power has an object-side surface 441 being concave at a paraxial region thereof and an image-side surface 442 being convex at a paraxial region thereof. The fourth lens element 440 is made of plastic material and has the object-side surface 441 and the image-side surface 442 being both aspheric.

The fifth lens element 450 with negative refractive power has an object-side surface 451 being concave at a paraxial region thereof and an image-side surface 452 being convex at a paraxial region thereof. The fifth lens element 450 is made of plastic material and has the object-side surface 451 and the image-side surface 452 being both aspheric.

The sixth lens element 460 with negative refractive power has an object-side surface 461 being convex at a paraxial region thereof and an image-side surface 462 changing from concave at a paraxial region thereof to convex at a peripheral region thereof. The sixth lens element 460 is made of plastic material and has the object-side surface 461 and the image-side surface 462 being both aspheric.

The IR-cut filter 480 made of glass material is located between the sixth lens element 460 and the image plane 470, and will not affect a focal length of the image capturing optical lens system.

The detailed optical data of the 4th embodiment are shown in Table 7, and the aspheric surface data are shown in Table 8 below.

TABLE 7

4th Embodiment								
f = 3.52 mm, Fno = 2.15, HFOV = 39.0 deg.								
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal length	
0	Object	Plano	Infinity					
1	Ape. Stop	Plano	-0.240					
2	Lens 1	1.526 (ASP)	0.434	Plastic	1.544	55.9	3.78	
3		5.319 (ASP)	0.031					
4	Lens 2	3.101 (ASP)	0.220	Plastic	1.640	23.3	-6.73	
5		1.753 (ASP)	0.267					
6	Lens 3	3.404 (ASP)	0.428	Plastic	1.535	56.3	17.00	
7		5.205 (ASP)	0.230					
8	Lens 4	-27.849 (ASP)	0.466	Plastic	1.535	56.3	3.47	
9		-1.749 (ASP)	0.251					
10	Lens 5	-0.973 (ASP)	0.260	Plastic	1.640	23.3	-12.30	
11		-1.226 (ASP)	0.328					

TABLE 7-continued

4th Embodiment								
f = 3.52 mm, Fno = 2.15, HFOV = 39.0 deg.								
Surface #		Curvature Radius		Thickness	Material	Index	Abbe #	Focal length
12	Lens 6	1.860	(ASP)	0.628	Plastic	1.544	55.9	-5.21
13		0.990	(ASP)	0.500				
14	IR-cut filter	Plano		0.150	Glass	1.517	64.2	—
15		Plano		0.303				
16	Image	Plano		—				

Note:

Reference wavelength (d-line) is 587.6 nm.

TABLE 8

Aspheric Coefficients						
	Surface #					
	2	3	4	5	6	7
k=	2.7915E-01	-2.4936E+01	-2.7594E+01	-5.8473E+00	-9.8578E+00	-2.1118E+00
A4=	2.4313E-04	-3.9606E-02	-5.3828E-02	1.8334E-02	-7.0035E-02	-9.1836E-02
A6=	3.1291E-02	1.5890E-01	1.6355E-01	1.1594E-01	2.1129E-02	-3.2061E-04
A8=	-5.6249E-02	-1.7755E-01	-1.2411E-01	4.0035E-02	-2.9000E-02	-8.2744E-02
A10=	-7.1236E-03	-4.4157E-02	-1.8261E-01	-2.8123E-01	1.9761E-02	2.5430E-02
A12=	1.7068E-01	7.5059E-02	7.6292E-02	2.6344E-01	-2.5108E-05	5.1347E-06
A14=	-1.4769E-01	-6.9236E-02	2.7542E-02	-4.5915E-02	—	—

	Surface #					
	8	9	10	11	12	13
k=	-1.0000E+00	5.1039E-01	-4.1329E+00	-7.0200E-01	-2.6121E+01	-6.4224E+00
A4=	-1.0058E-01	-2.9673E-02	-9.2923E-02	1.4126E-01	-1.8872E-01	-7.1095E-02
A6=	-1.9692E-02	-2.4332E-02	-3.4662E-02	-5.1905E-02	9.2722E-02	2.9091E-02
A8=	1.7002E-02	2.1407E-02	1.7437E-01	1.9044E-02	-5.8075E-02	-1.1727E-02
A10=	-9.5874E-02	5.2055E-02	-7.6455E-02	1.3553E-02	3.2738E-02	3.4867E-03
A12=	-3.2940E-02	-4.6551E-03	-1.4777E-02	-4.4324E-03	-1.0149E-02	-6.6684E-04
A14=	2.0100E-01	-1.0881E-02	9.5556E-03	-4.5447E-03	1.5541E-03	6.9187E-05
A16=	-1.0135E-01	—	-1.7410E-03	1.5160E-03	-9.3289E-05	-2.8417E-06

In the image capturing optical lens system according to the 4th embodiment, the definitions of these parameters shown in the following table are the same as those stated in the 1st embodiment with corresponding values for the 4th embodiment. Moreover, these parameters can be calculated from Table 7 and Table 8 as the following values and satisfy the following relationships:

f (mm)	3.52	R12/f2	-0.15
Fno	2.15	f/f4	1.02
HFOV (deg.)	39.0	f/f5	-0.29
(V2 + V5)/V1	0.83	( f/f5  +  f/f6 )/(f/f4)	0.95
V5/V6	0.417	CT2/tan(α) (mm)	0.07
CT5/CT6	0.41	BFL/Td	0.25
(R1 + R2)/(R1 - R2)	-1.80	ImgH/f	0.810
(R9 - R10)/(R9 + R10)	-0.12	TTL/ImgH	1.56

## 5th Embodiment

FIG. 9 is a schematic view of an image capturing optical lens system according to the 5th embodiment of the present disclosure. FIG. 10 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing optical lens system according to the 5th embodiment. In FIG. 9, the image capturing optical lens system

includes, in order from an object side to an image side, an aperture stop 500, a first lens element 510, a second lens element 520, a third lens element 530, a fourth lens element 540, a fifth lens element 550, a sixth lens element 560, an IR-cut filter 580, an image plane 570, and an image sensor 590.

The first lens element 510 with positive refractive power has an object-side surface 511 being convex at a paraxial region thereof and an image-side surface 512 being convex at a paraxial region thereof. The first lens element 510 is made of plastic material and has the object-side surface 511 and the image-side surface 512 being both aspheric.

The second lens element 520 with negative refractive power has an object-side surface 521 being convex at a paraxial region thereof and an image-side surface 522 being concave at a paraxial region thereof. The second lens element 520 is made of plastic material and has the object-side surface 521 and the image-side surface 522 being both aspheric.

The third lens element 530 with negative refractive power has an object-side surface 531 being convex at a paraxial region thereof and an image-side surface 532 being concave at a paraxial region thereof. The third lens element 530 is made of plastic material and has the object-side surface 531 and the image-side surface 532 being both aspheric.

## 21

The fourth lens element **540** with positive refractive power has an object-side surface **541** being convex at a paraxial region thereof and an image-side surface **542** being convex at a paraxial region thereof. The fourth lens element **540** is made of plastic material and has the object-side surface **541** and the image-side surface **542** being both aspheric.

The fifth lens element **550** with negative refractive power has an object-side surface **551** being concave at a paraxial region thereof and an image-side surface **552** being convex at a paraxial region thereof. The fifth lens element **550** is made of plastic material and has the object-side surface **551** and the image-side surface **552** being both aspheric.

## 22

The sixth lens element **560** with negative refractive power has an object-side surface **561** being convex at a paraxial region thereof and an image-side surface **562** changing from concave at a paraxial region thereof to convex at a peripheral region thereof. The sixth lens element **560** is made of plastic material and has the object-side surface **561** and the image-side surface **562** being both aspheric.

The IR-cut filter **580** made of glass material is located between the sixth lens element **560** and the image plane **570**, and will not affect a focal length of the image capturing optical lens system.

The detailed optical data of the 5th embodiment are shown in Table 9, and the aspheric surface data are shown in Table 10 below.

TABLE 9

5th Embodiment								
f = 3.53 mm, Fno = 2.28, HFOV = 38.5 deg.								
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal length	
0	Object	Plano	Infinity					
1	Ape. Stop	Plano	-0.125					
2	Lens 1	2.098 (ASP)	0.412	Plastic	1.570	57.5	3.07	
3		-9.769 (ASP)	0.040					
4	Lens 2	3.157 (ASP)	0.230	Plastic	1.640	23.3	-5.46	
5		1.611 (ASP)	0.236					
6	Lens 3	7.409 (ASP)	0.439	Plastic	1.544	55.9	-147.68	
7		6.642 (ASP)	0.167					
8	Lens 4	72.487 (ASP)	0.354	Plastic	1.544	55.9	3.62	
9		-2.019 (ASP)	0.292					
10	Lens 5	-0.951 (ASP)	0.280	Plastic	1.633	23.4	-6.64	
11		-1.369 (ASP)	0.199					
12	Lens 6	1.577 (ASP)	0.803	Plastic	1.544	55.9	-20.65	
13		1.134 (ASP)	0.600					
14	IR-cut filter	Plano	0.200	Glass	1.517	64.2	—	
15		Plano	0.300					
16	Image	Plano	—					

Note:

Reference wavelength (d-line) is 587.6 nm.

TABLE 10

Aspheric Coefficients						
	Surface #					
	2	3	4	5	6	7
k=	-2.9182E-02	-4.0000E+01	-3.9740E+01	-8.7375E+00	-2.4782E-01	-1.0194E+01
A4=	-6.1716E-03	3.7462E-03	-3.0152E-02	-2.1965E-02	-1.0134E-01	-1.0225E-01
A6=	-1.9011E-02	9.0896E-02	1.3569E-01	2.8108E-02	-3.5725E-02	-7.1141E-03
A8=	2.5131E-02	-2.1060E-01	-1.8667E-01	7.4668E-02	1.1420E-01	-7.4579E-02
A10=	-1.0473E-01	2.9488E-02	-1.0551E-01	-3.2137E-01	1.2721E-02	2.1331E-02
A12=	1.7110E-01	7.3654E-02	7.7073E-02	2.6333E-01	-1.9191E-02	1.2521E-02
A14=	-1.4692E-01	-6.9236E-02	2.8732E-02	-4.5979E-02	—	—
	Surface #					
	8	9	10	11	12	13
k=	0.0000E+00	9.0561E-01	-5.5036E+00	-7.1634E-01	-1.5362E+01	-6.1704E+00
A4=	-1.1202E-01	-3.1565E-02	-6.6246E-02	1.4768E-01	-1.7629E-01	-7.4355E-02
A6=	-1.0862E-02	-2.2451E-02	-3.0597E-02	-5.5223E-02	9.2042E-02	3.0461E-02
A8=	-2.6754E-03	3.7699E-02	1.5841E-01	2.0759E-02	-5.7974E-02	-1.2184E-02
A10=	-8.2421E-02	5.9365E-02	-8.0997E-02	1.3723E-02	3.2714E-02	3.5168E-03
A12=	-1.8457E-02	-4.3189E-03	-1.0397E-02	-4.6091E-03	-1.0165E-02	-6.6148E-04
A14=	1.8390E-01	-7.3347E-03	1.2640E-02	-4.5883E-03	1.5483E-03	6.9342E-05
A16=	-1.0137E-01	—	-2.8705E-03	1.5255E-03	-9.1738E-05	-2.9676E-06

## 23

In the image capturing optical lens system according to the 5th embodiment, the definitions of these parameters shown in the following table are the same as those stated in the 1st embodiment with corresponding values for the 5th embodiment. Moreover, these parameters can be calculated from

Table 9 and Table 10 as the following values and satisfy the following relationships:

f (mm)	3.53	R12/f2	-0.21
Fno	2.28	f/f4	0.98
HFOV (deg.)	38.5	f/f5	-0.53
(V2 + V5)/V1	0.81	( f/f5  +  f/f6 )/(f/f4)	0.72
V5/V6	0.419	CT2/tan( $\alpha$ ) (mm)	0.07
CT5/CT6	0.35	BFL/Td	0.30
(R1 + R2)/(R1 - R2)	-0.65	ImgH/f	0.809
(R9 - R10)/(R9 + R10)	-0.18	TTL/ImgH	1.57

## 6th Embodiment

FIG. 11 is a schematic view of an image capturing optical lens system according to the 6th embodiment of the present disclosure. FIG. 12 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing optical lens system according to the 6th embodiment. In FIG. 11, the image capturing optical lens system includes, in order from an object side to an image side, an aperture stop 600, a first lens element 610, a second lens element 620, a third lens element 630, a fourth lens element 640, a fifth lens element 650, a sixth lens element 660, an IR-cut filter 680, an image plane 670, and an image sensor 690.

The first lens element 610 with positive refractive power has an object-side surface 611 being convex at a paraxial region thereof and an image-side surface 612 being concave at a paraxial region thereof. The first lens element 610 is made of plastic material and has the object-side surface 611 and the image-side surface 612 being both aspheric.

## 24

The second lens element 620 with negative refractive power has an object-side surface 621 being convex at a paraxial region thereof and an image-side surface 622 being concave at a paraxial region thereof. The second lens element 620 is made of plastic material and has the object-side surface 621 and the image-side surface 622 being both aspheric.

The third lens element 630 with positive refractive power has an object-side surface 631 being convex at a paraxial region thereof and an image-side surface 632 being concave at a paraxial region thereof. The third lens element 630 is made of plastic material and has the object-side surface 631 and the image-side surface 632 being both aspheric.

The fourth lens element 640 with positive refractive power has an object-side surface 641 being concave at a paraxial region thereof and an image-side surface 642 being convex at a paraxial region thereof. The fourth lens element 640 is made of plastic material and has the object-side surface 641 and the image-side surface 642 being both aspheric.

The fifth lens element 650 with negative refractive power has an object-side surface 651 being concave at a paraxial region thereof and an image-side surface 652 being convex at a paraxial region thereof. The fifth lens element 650 is made of plastic material and has the object-side surface 651 and the image-side surface 652 being both aspheric.

The sixth lens element 660 with positive refractive power has an object-side surface 661 being convex at a paraxial region thereof and an image-side surface 662 changing from concave at a paraxial region thereof to convex at a peripheral region thereof. The sixth lens element 660 is made of plastic material and has the object-side surface 661 and the image-side surface 662 being both aspheric.

The IR-cut filter 680 made of glass material is located between the sixth lens element 660 and the image plane 670, and will not affect a focal length of the image capturing optical lens system.

The detailed optical data of the 6th embodiment are shown in Table 11, and the aspheric surface data are shown in Table 12 below.

TABLE 11

6th Embodiment							
f = 3.62 mm, Fno = 2.35, HFOV = 37.8 deg.							
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal length
0	Object	Plano	Infinity				
1	Ape. Stop	Plano	-0.148				
2	Lens 1	1.962 (ASP)	0.418	Plastic	1.544	55.9	4.11
3		14.881 (ASP)	0.050				
4	Lens 2	2.961 (ASP)	0.240	Plastic	1.640	23.3	-6.66
5		1.692 (ASP)	0.185				
6	Lens 3	3.007 (ASP)	0.362	Plastic	1.544	55.9	14.05
7		4.745 (ASP)	0.321				
8	Lens 4	-12.116 (ASP)	0.435	Plastic	1.544	55.9	4.08
9		-1.900 (ASP)	0.300				
10	Lens 5	-0.916 (ASP)	0.250	Plastic	1.640	23.3	-5.53
11		-1.367 (ASP)	0.128				
12	Lens 6	1.310 (ASP)	0.787	Plastic	1.530	55.8	70.78
13		1.075 (ASP)	0.600				
14	IR-cut filter	Plano	0.200	Glass	1.517	64.2	—
15		Plano	0.426				
16	Image	Plano	—				

Note:

Reference wavelength (d-line) is 587.6 nm.

TABLE 12

Aspheric Coefficients						
	Surface #					
	2	3	4	5	6	7
k=	4.6664E-01	-4.0000E+01	-3.0098E+01	-7.5608E+00	-4.8799E+00	1.9273E+00
A4=	-2.1799E-04	-5.3426E-02	-6.9007E-02	-3.8393E-02	-9.5062E-02	-9.2795E-02
A6=	1.3945E-02	1.7055E-01	6.3894E-02	9.3340E-03	-3.7983E-02	-3.5163E-02
A8=	5.2083E-04	-2.5636E-01	-6.9036E-02	7.0595E-02	7.2969E-02	-6.9952E-02
A10=	-7.4073E-02	-3.8467E-02	-3.1084E-01	-3.5385E-01	-1.9872E-02	5.1614E-02
A12=	1.7110E-01	7.3654E-02	7.7073E-02	2.6333E-01	1.8507E-02	3.6115E-02
A14=	-1.4692E-01	-6.9236E-02	2.8732E-02	-4.5979E-02	—	—

	Surface #					
	8	9	10	11	12	13
k=	-1.0000E+00	1.0135E+00	-6.1714E+00	-6.3844E-01	-1.2851E+01	-5.3345E+00
A4=	-8.7034E-02	-4.5830E-02	-1.0529E-01	1.3602E-01	-1.7692E-01	-8.0147E-02
A6=	-2.2875E-02	-4.7613E-03	-2.1382E-02	-6.0425E-02	9.2596E-02	3.3015E-02
A8=	2.4491E-02	3.7893E-02	1.6663E-01	2.3794E-02	-5.8046E-02	-1.2613E-02
A10=	-7.1043E-02	5.4155E-02	-7.8022E-02	1.4800E-02	3.2694E-02	3.5304E-03
A12=	-2.0087E-02	-6.8905E-03	-1.2281E-02	-4.3372E-03	-1.0164E-02	-6.5395E-04
A14=	1.8513E-01	-1.0180E-02	1.1470E-02	-4.6163E-03	1.5482E-03	6.9323E-05
A16=	-1.0137E-01	—	-1.7129E-03	1.4470E-03	-9.1665E-05	-3.0797E-06

In the image capturing optical lens system according to the 6th embodiment, the definitions of these parameters shown in the following table are the same as those stated in the 1st embodiment with corresponding values for the 6th embodiment. Moreover, these parameters can be calculated from Table 11 and Table 12 as the following values and satisfy the following relationships:

f (mm)	3.62	R12/f2	-0.16
Fno	2.35	f/f4	0.89
HFOV (deg.)	37.8	f/f5	-0.65
(V2 + V5)/V1	0.83	( f/f5  +  f/f6 )/(f/f4)	0.80
V5/V6	0.418	CT2/tan( $\alpha$ ) (mm)	0.07
CT5/CT6	0.32	BFL/Td	0.33
(R1 + R2)/(R1 - R2)	-1.30	ImgH/f	0.789
(R9 - R10)/(R9 + R10)	-0.20	TTL/ImgH	1.62

#### 7th Embodiment

FIG. 13 is a schematic view of an image capturing optical lens system according to the 7th embodiment of the present disclosure. FIG. 14 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing optical lens system according to the 7th embodiment. In FIG. 13, the image capturing optical lens system includes, in order from an object side to an image side, an aperture stop 700, a first lens element 710, a stop 701, a second lens element 720, a third lens element 730, a fourth lens element 740, a fifth lens element 750, a sixth lens element 760, an IR-cut filter 780, an image plane 770, and an image sensor 790.

The first lens element 710 with positive refractive power has an object-side surface 711 being convex at a paraxial region thereof and an image-side surface 712 being concave at a paraxial region thereof. The first lens element 710 is made of plastic material and has the object-side surface 711 and the image-side surface 712 being both aspheric.

The second lens element 720 with negative refractive power has an object-side surface 721 being concave at a paraxial region thereof and an image-side surface 722 being

concave at a paraxial region thereof. The second lens element 720 is made of plastic material and has the object-side surface 721 and the image-side surface 722 being both aspheric.

The third lens element 730 with positive refractive power has an object-side surface 731 being convex at a paraxial region thereof and an image-side surface 732 being convex at a paraxial region thereof. The third lens element 730 is made of plastic material and has the object-side surface 731 and the image-side surface 732 being both aspheric.

The fourth lens element 740 with positive refractive power has an object-side surface 741 being concave at a paraxial region thereof and an image-side surface 742 being convex at a paraxial region thereof. The fourth lens element 740 is made of plastic material and has the object-side surface 741 and the image-side surface 742 being both aspheric.

The fifth lens element 750 with negative refractive power has an object-side surface 751 being concave at a paraxial region thereof and an image-side surface 752 being convex at a paraxial region thereof. The fifth lens element 750 is made of plastic material and has the object-side surface 751 and the image-side surface 752 being both aspheric.

The sixth lens element 760 with negative refractive power has an object-side surface 761 being convex at a paraxial region thereof and an image-side surface 762 changing from concave at a paraxial region thereof to convex at a peripheral region thereof. The sixth lens element 760 is made of plastic material and has the object-side surface 761 and the image-side surface 762 being both aspheric.

The IR-cut filter 780 made of glass material is located between the sixth lens element 760 and the image plane 770, and will not affect a focal length of the image capturing optical lens system.

The detailed optical data of the 7th embodiment are shown in Table 13, and the aspheric surface data are shown in Table 14 below.

TABLE 13

7th Embodiment							
f = 3.75 mm, Fno = 2.25, HFOV = 37.6 deg.							
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal length
0	Object	Plano	Infinity				
1	Ape. Stop	Plano	-0.230				
2	Lens 1	1.551 (ASP)	0.432	Plastic	1.544	55.9	3.47
3		7.794 (ASP)	0.078				
4	Stop	Plano	0.154				
5	Lens 2	-5.031 (ASP)	0.250	Plastic	1.640	23.3	-4.99
6		8.923 (ASP)	0.178				
7	Lens 3	3.714 (ASP)	0.514	Plastic	1.544	55.9	5.81
8		-20.315 (ASP)	0.522				
9	Lens 4	-1.856 (ASP)	0.572	Plastic	1.544	55.9	2.76
10		-0.920 (ASP)	0.039				
11	Lens 5	-4.324 (ASP)	0.318	Plastic	1.640	23.3	-17.02
12		-7.378 (ASP)	0.086				
13	Lens 6	4.222 (ASP)	0.472	Plastic	1.535	56.3	-2.57
14		0.996 (ASP)	0.700				
15	IR-cut filter	Plano	0.210	Glass	1.517	64.2	—
16		Plano	0.263				
17	Image	Plano	—				

Note:

Reference wavelength (d-line) is 587.6 nm.

Half of the diameter of the stop at Surface 4 is 0.82 mm.

TABLE 14

Aspheric Coefficients						
	Surface #					
	2	3	5	6	7	8
k=	-4.4079E-02	5.0000E+01	-1.0643E+00	-8.4921E+01	-1.3118E+00	1.0000E+00
A4=	1.7490E-02	9.4783E-04	2.2373E-02	-4.9248E-02	-2.3211E-01	-1.1809E-01
A6=	4.9271E-03	5.8422E-02	2.4605E-01	4.5161E-01	2.6588E-01	-1.7947E-02
A8=	1.2641E-01	-2.9751E-01	-9.9335E-01	-1.0749E+00	-4.8494E-01	1.8494E-02
A10=	-5.1819E-01	6.3338E-01	2.0612E+00	1.7513E+00	6.2343E-01	-2.3733E-03
A12=	9.3670E-01	-8.8581E-01	-2.6879E+00	-1.7291E+00	-4.7955E-01	3.4599E-03
A14=	-6.4751E-01	2.6447E-01	1.2659E+00	7.3759E-01	1.5910E-01	—
	Surface #					
	9	10	11	12	13	14
k=	-5.7148E-01	-1.0341E+00	-1.2747E+00	-8.2998E+00	-8.4741E+01	-5.1944E+00
A4=	-4.0590E-02	1.2497E-01	-9.6189E-03	-2.0558E-02	-1.5776E-01	-1.3667E-01
A6=	-1.2965E-01	-2.0774E-01	-6.6101E-03	-3.2392E-03	-9.1813E-03	7.4540E-02
A8=	-6.9615E-03	1.0877E-01	-1.9492E-03	-8.0848E-04	9.8789E-02	-2.8848E-02
A10=	2.6027E-01	2.0113E-02	-8.6543E-04	-3.8551E-05	-7.7556E-02	7.2957E-03
A12=	-1.7903E-01	-1.9185E-02	-5.6726E-05	8.0891E-05	2.7755E-02	-1.2091E-03
A14=	3.5718E-02	2.3228E-03	—	—	-4.7500E-03	1.1933E-04
A16=	—	—	—	—	3.1387E-04	-5.2507E-06

In the image capturing optical lens system according to the 7th embodiment, the definitions of these parameters shown in the following table are the same as those stated in the 1st embodiment with corresponding values for the 7th embodiment. Moreover, these parameters can be calculated from

Table 13 and Table 14 as the following values and satisfy the following relationships:

f (mm)	3.75	R12/f2	-0.20
Fno	2.25	f/f4	1.36
HFOV (deg.)	37.6	f/f5	-0.22
(V2 + V5)/V1	0.83	( f/f5  +  f/f6 )/(f/f4)	1.23
V5/V6	0.414	CT2/tan( $\alpha$ ) (mm)	0.07

-continued

CT5/CT6	0.67	BFL/Td	0.31
(R1 + R2)/(R1 - R2)	-1.50	ImgH/f	0.782
(R9 - R10)/(R9 + R10)	-0.26	TTL/ImgH	1.61

60

8th Embodiment

FIG. 15 is a schematic view of an image capturing optical lens system according to the 8th embodiment of the present disclosure. FIG. 16 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing optical lens system according to the 8th embodiment. In FIG. 15, the image capturing optical lens system

65

includes, in order from an object side to an image side, an aperture stop **800**, a first lens element **810**, a second lens element **820**, a third lens element **830**, a fourth lens element **840**, a fifth lens element **850**, a sixth lens element **860**, an IR-cut filter **880**, an image plane **870**, and an image sensor **890**.

The first lens element **810** with positive refractive power has an object-side surface **811** being convex at a paraxial region thereof and an image-side surface **812** being concave at a paraxial region thereof. The first lens element **810** is made of plastic material and has the object-side surface **811** and the image-side surface **812** being both aspheric.

The second lens element **820** with negative refractive power has an object-side surface **821** being convex at a paraxial region thereof and an image-side surface **822** being concave at a paraxial region thereof. The second lens element **820** is made of plastic material and has the object-side surface **821** and the image-side surface **822** being both aspheric.

The third lens element **830** with positive refractive power has an object-side surface **831** being convex at a paraxial region thereof and an image-side surface **832** being convex at a paraxial region thereof. The third lens element **830** is made of plastic material and has the object-side surface **831** and the image-side surface **832** being both aspheric.

The fourth lens element **840** with positive refractive power has an object-side surface **841** being convex at a paraxial region thereof and an image-side surface **842** being convex at a paraxial region thereof. The fourth lens element **840** is made of plastic material and has the object-side surface **841** and the image-side surface **842** being both aspheric.

The fifth lens element **850** with negative refractive power has an object-side surface **851** being concave at a paraxial region thereof and an image-side surface **852** being convex at a paraxial region thereof. The fifth lens element **850** is made of plastic material and has the object-side surface **851** and the image-side surface **852** being both aspheric.

The sixth lens element **860** with positive refractive power has an object-side surface **861** being convex at a paraxial region thereof and an image-side surface **862** changing from concave at a paraxial region thereof to convex at a peripheral region thereof. The sixth lens element **860** is made of plastic material and has the object-side surface **861** and the image-side surface **862** being both aspheric.

The IR-cut filter **880** made of glass material is located between the sixth lens element **860** and the image plane **870**, and will not affect a focal length of the image capturing optical lens system.

The detailed optical data of the 8th embodiment are shown in Table 15, and the aspheric surface data are shown in Table 16 below.

TABLE 15

8th Embodiment								
f = 3.75 mm, Fno = 2.22, HFOV = 37.6 deg.								
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal length	
0	Object	Plano	Infinity					
1	Ape. Stop	Plano	-0.230					
2	Lens 1	1.634 (ASP)	0.422	Plastic	1.544	55.9	3.69	
3		7.993 (ASP)	0.133					
4	Lens 2	2.740 (ASP)	0.240	Plastic	1.640	23.3	-7.05	
5		1.646 (ASP)	0.230					
6	Lens 3	14.616 (ASP)	0.250	Plastic	1.544	55.9	23.00	
7		-86.443 (ASP)	0.156					
8	Lens 4	100.000 (ASP)	0.312	Plastic	1.544	55.9	6.09	
9		-3.424 (ASP)	0.391					
10	Lens 5	-0.788 (ASP)	0.280	Plastic	1.640	23.3	-9.25	
11		-1.036 (ASP)	0.123					
12	Lens 6	2.018 (ASP)	1.116	Plastic	1.544	55.9	503.03	
13		1.636 (ASP)	0.700					
14	IR-cut filter	Plano	0.210	Glass	1.517	64.2	—	
15		Plano	0.226					
16	Image	Plano	—					

Note:

Reference wavelength (d-line) is 587.6 nm.

TABLE 16

Aspheric Coefficients						
	Surface #					
	2	3	4	5	6	7
k=	-2.7168E-02	-6.8822E+01	-3.2439E+01	-8.8020E+00	-8.9828E+01	1.0000E+00
A4=	4.4163E-03	-8.0677E-02	-1.2812E-01	-1.9572E-02	-2.3676E-02	-4.1131E-02
A6=	2.3039E-02	1.4665E-01	8.7887E-02	9.9597E-03	-2.1991E-02	-2.0921E-02
A8=	-1.7095E-02	-1.1445E-01	1.9406E-02	1.1952E-01	2.7782E-02	-2.2773E-03
A10=	-2.9339E-02	-7.0578E-03	-1.3469E-01	-2.5090E-01	1.7926E-03	4.3882E-02
A12=	9.9529E-02	4.2875E-02	4.4865E-02	1.5331E-01	-5.6449E-05	-1.1873E-05
A14=	-7.7512E-02	-3.6527E-02	1.5158E-02	-2.4257E-02	—	—



TABLE 16-continued

Aspheric Coefficients						
	Surface #					
	8	9	10	11	12	13
k=	-3.2429E+00	3.3303E+00	-3.3077E+00	-8.0426E-01	-1.9814E+01	-7.3813E+00
A4=	-1.0146E-01	-4.5648E-02	-8.1619E-02	1.1978E-01	-1.2012E-01	-5.1343E-02
A6=	-3.9893E-02	-4.2874E-02	-2.0633E-02	-2.6545E-02	6.7400E-02	1.9885E-02
A8=	2.2123E-02	1.9586E-02	1.2212E-01	2.4245E-02	-4.1778E-02	-7.8640E-03
A10=	-1.8964E-02	3.3795E-02	-4.4025E-02	8.1061E-03	2.1037E-02	2.1725E-03
A12=	2.0746E-02	-2.3182E-03	-7.9093E-03	-3.4715E-03	-5.8863E-03	-3.8311E-04
A14=	6.1208E-02	1.1093E-03	2.5948E-03	-2.7535E-03	8.2483E-04	3.8278E-05
A16=	-4.8470E-02	—	4.5007E-04	7.1272E-04	-4.5893E-05	-1.6059E-06

15

In the image capturing optical lens system according to the 8th embodiment, the definitions of these parameters shown in the following table are the same as those stated in the 1st embodiment with corresponding values for the 8th embodiment. Moreover, these parameters can be calculated from Table 15 and Table 16 as the following values and satisfy the following relationships:

f (mm)	3.75	R12/f2	-0.23
Fno	2.22	f/f4	0.62
HFOV (deg.)	37.6	f/f5	-0.40
(V2 + V5)/V1	0.83	( f/f5  +  f/f6 )/(f/f4)	0.67
V5/V6	0.417	CT2/tan( $\alpha$ ) (mm)	0.06
CT5/CT6	0.25	BFL/Td	0.29
(R1 + R2)/(R1 - R2)	-1.51	ImgH/f	0.783
(R9 - R10)/(R9 + R10)	-0.14	TTL/ImgH	1.61

## 9th Embodiment

FIG. 17 is a schematic view of an image capturing optical lens system according to the 9th embodiment of the present disclosure. FIG. 18 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing optical lens system according to the 9th embodiment. In FIG. 17, the image capturing optical lens system includes, in order from an object side to an image side, an aperture stop 900, a first lens element 910, a second lens element 920, a third lens element 930, a fourth lens element 940, a fifth lens element 950, a sixth lens element 960, an IR-cut filter 980, an image plane 970, and an image sensor 990.

The first lens element 910 with positive refractive power has an object-side surface 911 being convex at a paraxial region thereof and an image-side surface 912 being concave at a paraxial region thereof. The first lens element 910 is made of plastic material and has the object-side surface 911 and the image-side surface 912 being both aspheric.

The second lens element 920 with negative refractive power has an object-side surface 921 being concave at a

paraxial region thereof and an image-side surface 922 being concave at a paraxial region thereof. The second lens element 920 is made of plastic material and has the object-side surface 921 and the image-side surface 922 being both aspheric.

The third lens element 930 with positive refractive power has an object-side surface 931 being convex at a paraxial region thereof and an image-side surface 932 being concave at a paraxial region thereof. The third lens element 930 is made of plastic material and has the object-side surface 931 and the image-side surface 932 being both aspheric.

The fourth lens element 940 with positive refractive power has an object-side surface 941 being concave at a paraxial region thereof and an image-side surface 942 being convex at a paraxial region thereof. The fourth lens element 940 is made of plastic material and has the object-side surface 941 and the image-side surface 942 being both aspheric.

The fifth lens element 950 with negative refractive power has an object-side surface 951 being concave at a paraxial region thereof and an image-side surface 952 being convex at a paraxial region thereof. The fifth lens element 950 is made of plastic material and has the object-side surface 951 and the image-side surface 952 being both aspheric.

The sixth lens element 960 with negative refractive power has an object-side surface 961 being concave at a paraxial region thereof and an image-side surface 962 changing from concave at a paraxial region thereof to convex at a peripheral region thereof. The sixth lens element 960 is made of plastic material and has the object-side surface 961 and the image-side surface 962 being both aspheric.

The IR-cut filter 980 made of glass material is located between the sixth lens element 960 and the image plane 970, and will not affect a focal length of the image capturing optical lens system.

The detailed optical data of the 9th embodiment are shown in Table 17, and the aspheric surface data are shown in Table 18 below.

TABLE 17

9th Embodiment							
f = 3.75 mm, Fno = 2.25, HFOV = 37.3 deg.							
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal length
0	Object	Plano	Infinity				
1	Ape. Stop	Plano	-0.253				
2	Lens 1	1.472 (ASP)	0.467	Plastic	1.544	55.9	3.00
3		13.066 (ASP)	0.198				

TABLE 17-continued

9th Embodiment								
f = 3.75 mm, Fno = 2.25, HFOV = 37.3 deg.								
Surface #		Curvature Radius		Thickness	Material	Index	Abbe #	Focal length
4	Lens 2	-5.659	(ASP)	0.250	Plastic	1.650	21.4	-5.41
5		9.448	(ASP)	0.209				
6	Lens 3	5.478	(ASP)	0.478	Plastic	1.544	55.9	11.19
7		53.006	(ASP)	0.364				
8	Lens 4	-2.418	(ASP)	0.453	Plastic	1.544	55.9	3.22
9		-1.083	(ASP)	0.070				
10	Lens 5	-3.228	(ASP)	0.394	Plastic	1.583	30.2	-75.24
11		-3.641	(ASP)	0.247				
12	Lens 6	-4.543	(ASP)	0.579	Plastic	1.530	55.8	-2.39
13		1.829	(ASP)	0.400				
14	IR-cut filter	Plano		0.210	Glass	1.517	64.2	—
15		Plano		0.305				
16	Image	Plano		—				

Note:

Reference wavelength (d-line) is 587.6 nm.

TABLE 18

Aspheric Coefficients						
	Surface #					
	2	3	4	5	6	7
k=	-1.1941E-01	2.6303E+00	-1.0000E+00	-1.4392E+01	-7.3165E+00	-2.0000E+01
A4=	6.6018E-03	3.8742E-03	6.5278E-03	-4.8042E-02	-2.3979E-01	-1.3984E-01
A6=	4.2878E-02	5.6943E-02	2.7610E-01	4.5649E-01	2.5499E-01	-2.3033E-02
A8=	5.1710E-02	-3.0745E-01	-1.0040E+00	-1.0431E+00	-4.7326E-01	3.4853E-02
A10=	-4.7087E-01	6.9641E-01	2.1186E+00	1.7683E+00	6.5137E-01	-1.8006E-03
A12=	9.3977E-01	-8.8727E-01	-2.6876E+00	-1.7285E+00	-4.7999E-01	-1.6335E-03
A14=	-6.4751E-01	2.6447E-01	1.2659E+00	7.3759E-01	1.5835E-01	—
	Surface #					
	8	9	10	11	12	13
k=	-5.6564E-01	-1.0158E+00	-2.4737E+01	-1.5837E+01	-5.0000E+01	-3.4499E+00
A4=	-5.3796E-02	9.5124E-02	-3.6509E-02	-2.2990E-02	-1.4338E-01	-1.5150E-01
A6=	-1.0996E-01	-1.9462E-01	-6.7899E-03	8.0124E-04	-1.0711E-02	7.9095E-02
A8=	-8.8751E-03	1.2004E-01	1.0570E-03	-5.6126E-04	9.8961E-02	-2.9464E-02
A10=	2.5706E-01	2.3369E-02	-1.8894E-03	3.4463E-04	-7.7641E-02	7.2539E-03
A12=	-1.8086E-01	-1.9355E-02	2.5699E-05	-1.9140E-04	2.7727E-02	-1.2081E-03
A14=	3.5756E-02	1.0974E-03	—	—	-4.7428E-03	1.2009E-04
A16=	—	—	—	—	3.1657E-04	-5.1210E-06

In the image capturing optical lens system according to the 9th embodiment, the definitions of these parameters shown in the following table are the same as those stated in the 1st embodiment with corresponding values for the 9th embodiment. Moreover, these parameters can be calculated from

Table 17 and Table 18 as the following values and satisfy the following relationships:

f (mm)	3.75	R12/f2	-0.34
Fno	2.25	f/f4	1.16
HFOV (deg.)	37.3	f/f5	-0.05
(V2 + V5)/V1	0.92	( f/f5  +  f/f6 )/(f/f4)	1.39
V5/V6	0.541	CT2/tan( $\alpha$ ) (mm)	0.05
CT5/CT6	0.68	BFL/Td	0.23
(R1 + R2)/(R1 - R2)	-1.25	ImgH/f	0.782
(R9 - R10)/(R9 + R10)	-0.06	TTL/ImgH	1.55

## 10th Embodiment

FIG. 19 is a schematic view of an image capturing optical lens system according to the 10th embodiment of the present disclosure. FIG. 20 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing optical lens system according to the 10th embodiment. In FIG. 19, the image capturing optical lens system includes, in order from an object side to an image side, an aperture stop 1000, a first lens element 1010, a second lens element 1020, a third lens element 1030, a fourth lens element 1040, a fifth lens element 1050, a sixth lens element 1060, an IR-cut filter 1080, an image plane 1070, and an image sensor 1090.

The first lens element 1010 with positive refractive power has an object-side surface 1011 being convex at a paraxial region thereof and an image-side surface 1012 being concave at a paraxial region thereof. The first lens element 1010 is made of plastic material and has the object-side surface 1011 and the image-side surface 1012 being both aspheric.

## 35

The second lens element **1020** with negative refractive power has an object-side surface **1021** being concave at a paraxial region thereof and an image-side surface **1022** being concave at a paraxial region thereof. The second lens element **1020** is made of plastic material and has the object-side surface **1021** and the image-side surface **1022** being both aspheric.

The third lens element **1030** with positive refractive power has an object-side surface **1031** being convex at a paraxial region thereof and an image-side surface **1032** being concave at a paraxial region thereof. The third lens element **1030** is made of plastic material and has the object-side surface **1031** and the image-side surface **1032** being both aspheric.

The fourth lens element **1040** with positive refractive power has an object-side surface **1041** being concave at a paraxial region thereof and an image-side surface **1042** being convex at a paraxial region thereof. The fourth lens element **1040** is made of plastic material and has the object-side surface **1041** and the image-side surface **1042** being both aspheric.

## 36

The fifth lens element **1050** with negative refractive power has an object-side surface **1051** being concave at a paraxial region thereof and an image-side surface **1052** being convex at a paraxial region thereof. The fifth lens element **1050** is made of plastic material and has the object-side surface **1051** and the image-side surface **1052** being both aspheric.

The sixth lens element **1060** with negative refractive power has an object-side surface **1061** being convex at a paraxial region thereof and an image-side surface **1062** changing from concave at a paraxial region thereof to convex at a peripheral region thereof. The sixth lens element **1060** is made of plastic material and has the object-side surface **1061** and the image-side surface **1062** being both aspheric.

The IR-cut filter **1080** made of glass material is located between the sixth lens element **1060** and the image plane **1070**, and will not affect a focal length of the image capturing optical lens system.

The detailed optical data of the 10th embodiment are shown in Table 19, and the aspheric surface data are shown in Table 20 below.

TABLE 19

10th Embodiment								
f = 3.59 mm, Fno = 2.25, HFOV = 38.5 deg.								
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal length	
0	Object	Plano	Infinity					
1	Ape. Stop	Plano	-0.217					
2	Lens 1	1.555 (ASP)	0.434	Plastic	1.544	55.9	3.03	
3		25.036 (ASP)	0.159					
4	Lens 2	-8.152 (ASP)	0.250	Plastic	1.650	21.4	-6.15	
5		7.921 (ASP)	0.252					
6	Lens 3	6.513 (ASP)	0.408	Plastic	1.544	55.9	43.50	
7		8.787 (ASP)	0.259					
8	Lens 4	-3.391 (ASP)	0.510	Plastic	1.544	55.9	2.87	
9		-1.125 (ASP)	0.159					
10	Lens 5	-2.520 (ASP)	0.601	Plastic	1.544	55.9	-7.62	
11		-6.969 (ASP)	0.150					
12	Lens 6	2.819 (ASP)	0.552	Plastic	1.614	25.6	-3.65	
13		1.156 (ASP)	0.450					
14	IR-cut filter	Plano	0.210	Glass	1.517	64.2	—	
15		Plano	0.250					
16	Image	Plano	—					

Note:

Reference wavelength (d-line) is 587.6 nm.

TABLE 20

Aspheric Coefficients						
	Surface #					
	2	3	4	5	6	7
k=	-1.1562E-01	4.4393E+01	-9.9274E-01	-1.6521E+01	-1.7908E+01	9.0788E-01
A4=	6.1168E-03	3.6207E-03	-5.2100E-03	-5.0513E-02	-2.4346E-01	-1.4692E-01
A6=	4.8562E-02	8.4346E-02	2.8445E-01	4.3775E-01	2.4538E-01	-2.8027E-02
A8=	5.7173E-02	-3.2403E-01	-1.0170E+00	-1.0549E+00	-4.7435E-01	3.4510E-02
A10=	-4.8003E-01	6.8018E-01	2.1072E+00	1.7532E+00	6.4246E-01	-2.2892E-03
A12=	9.3889E-01	-8.8725E-01	-2.6876E+00	-1.7284E+00	-4.8003E-01	1.9669E-03
A14=	-6.4751E-01	2.6447E-01	1.2659E+00	7.3759E-01	1.5835E-01	—
	Surface #					
	8	9	10	11	12	13
k=	-2.4468E+00	-1.0234E+00	-3.2379E+01	-8.2036E+01	-3.7322E+01	-4.8110E+00
A4=	-4.3481E-02	9.7231E-02	-2.1372E-02	-1.2083E-02	-1.5853E-01	-1.4110E-01

TABLE 20-continued

Aspheric Coefficients						
A6=	-1.0331E-01	-1.8397E-01	-1.7901E-04	-3.0074E-03	-1.1837E-02	7.7668E-02
A8=	-8.7354E-03	1.2484E-01	3.6449E-03	-1.3178E-03	9.9016E-02	-2.9445E-02
A10=	2.5647E-01	2.3661E-02	-2.7268E-03	5.0464E-04	-7.7656E-02	7.2684E-03
A12=	-1.8137E-01	-2.0200E-02	-5.4706E-04	-9.1291E-05	2.7743E-02	-1.2048E-03
A14=	3.5075E-02	9.3894E-05	—	—	-4.7398E-03	1.2011E-04
A16=	—	—	—	—	3.1460E-04	-5.1835E-06

In the image capturing optical lens system according to the 10th embodiment, the definitions of these parameters shown in the following table are the same as those stated in the 1st embodiment with corresponding values for the 10th embodiment. Moreover, these parameters can be calculated from Table 19 and Table 20 as the following values and satisfy the following relationships:

f (mm)	3.59	R12/f2	-0.19
Fno	2.25	f/f4	1.25
HFOV (deg.)	38.5	f/f5	-0.47
(V2 + V5)/V1	1.38	( f/f5  +  f/f6 )/(f/f4)	1.16
V5/V6	2.184	CT2/tan( $\alpha$ ) (mm)	0.07
CT5/CT6	1.09	BFL/Td	0.23
(R1 + R2)/(R1 - R2)	-1.13	ImgH/f	0.816
(R9 - R10)/(R9 + R10)	-0.47	TTL/ImgH	1.56

### 11th Embodiment

FIG. 21 is a schematic view of an image capturing optical lens system according to the 11th embodiment of the present disclosure. FIG. 22 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing optical lens system according to the 11th embodiment. In FIG. 21, the image capturing optical lens system includes, in order from an object side to an image side, a first lens element 1110, an aperture stop 1100, a second lens element 1120, a third lens element 1130, a fourth lens element 1140, a fifth lens element 1150, a sixth lens element 1160, an IR-cut filter 1180, an image plane 1170, and an image sensor 1190.

The first lens element 1110 with positive refractive power has an object-side surface 1111 being convex at a paraxial region thereof and an image-side surface 1112 being concave at a paraxial region thereof. The first lens element 1110 is made of plastic material and has the object-side surface 1111 and the image-side surface 1112 being both aspheric.

The second lens element 1120 with negative refractive power has an object-side surface 1121 being convex at a paraxial region thereof and an image-side surface 1122

being concave at a paraxial region thereof. The second lens element 1120 is made of plastic material and has the object-side surface 1121 and the image-side surface 1122 being both aspheric.

The third lens element 1130 with positive refractive power has an object-side surface 1131 being convex at a paraxial region thereof and an image-side surface 1132 being concave at a paraxial region thereof. The third lens element 1130 is made of plastic material and has the object-side surface 1131 and the image-side surface 1132 being both aspheric.

The fourth lens element 1140 with positive refractive power has an object-side surface 1141 being concave at a paraxial region thereof and an image-side surface 1142 being convex at a paraxial region thereof. The fourth lens element 1140 is made of plastic material and has the object-side surface 1141 and the image-side surface 1142 being both aspheric.

The fifth lens element 1150 with negative refractive power has an object-side surface 1151 being concave at a paraxial region thereof and an image-side surface 1152 being convex at a paraxial region thereof. The fifth lens element 1150 is made of plastic material and has the object-side surface 1151 and the image-side surface 1152 being both aspheric.

The sixth lens element 1160 with negative refractive power has an object-side surface 1161 being convex at a paraxial region thereof and an image-side surface 1162 changing from concave at a paraxial region thereof to convex at a peripheral region thereof. The sixth lens element 1160 is made of plastic material and has the object-side surface 1161 and the image-side surface 1162 being both aspheric.

The IR-cut filter 1180 made of glass material is located between the sixth lens element 1160 and the image plane 1170, and will not affect a focal length of the image capturing optical lens system.

The detailed optical data of the 11th embodiment are shown in Table 21, and the aspheric surface data are shown in Table 22 below.

TABLE 21

11th Embodiment								
f = 3.58 mm, Fno = 2.60, HFOV = 38.6 deg.								
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal length	
0	Object	Plano	Infinity					
1	Lens 1	1.784 (ASP)	0.388	Plastic	1.535	56.3	4.02	
2		9.697 (ASP)	0.050					
3	Ape. Stop	Plano	0.235					
4	Lens 2	34.444 (ASP)	0.250	Plastic	1.650	21.4	-6.75	
5		3.880 (ASP)	0.191					
6	Lens 3	3.110 (ASP)	0.430	Plastic	1.535	56.3	13.56	
7		5.185 (ASP)	0.295					
8	Lens 4	-3.224 (ASP)	0.470	Plastic	1.544	55.9	3.21	

TABLE 21-continued

11th Embodiment							
f = 3.58 mm, Fno = 2.60, HFOV = 38.6 deg.							
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal length
9		-1.191 (ASP)	0.131				
10	Lens 5	-3.690 (ASP)	0.694	Plastic	1.614	25.6	-67.37
11		-4.341 (ASP)	0.283				
12	Lens 6	2.689 (ASP)	0.517	Plastic	1.614	25.6	-3.02
13		1.018 (ASP)	0.450				
14	IR-cut filter	Plano	0.210	Glass	1.517	64.2	—
15		Plano	0.257				
16	Image	Plano	—				

Note:

Reference wavelength (d-line) is 587.6 nm.

TABLE 22

Aspheric Coefficients						
	Surface #					
	1	2	4	5	6	7
k=	-7.6470E-02	3.1937E+01	-5.0000E+01	-2.5519E+01	-1.2297E+01	-1.9347E+01
A4=	7.1731E-03	1.2153E-02	-2.3455E-02	-5.4475E-02	-2.3603E-01	-1.5498E-01
A6=	4.4148E-02	6.8468E-02	2.4633E-01	4.1900E-01	2.5919E-01	-4.0139E-02
A8=	5.9718E-02	-3.9910E-01	-1.0863E+00	-1.0778E+00	-4.6874E-01	2.2970E-02
A10=	-5.2513E-01	7.2459E-01	2.1056E+00	1.7171E+00	6.1983E-01	-9.1050E-03
A12=	9.3889E-01	-8.8725E-01	-2.6876E+00	-1.7284E+00	-4.8001E-01	-2.9391E-04
A14=	-6.4751E-01	2.6447E-01	1.2659E+00	7.3759E-01	1.5835E-01	—
A16=	—	—	—	—	—	—

	Surface #					
	8	9	10	11	12	13
k=	-1.4331E+00	-1.0000E+00	-8.3901E+01	-2.6945E+01	-3.4415E+01	-4.3565E+00
A4=	-4.5095E-02	8.0598E-02	-1.6846E-03	6.7393E-03	-1.6535E-01	-1.4409E-01
A6=	-9.9740E-02	-1.8572E-01	-3.6514E-03	-6.8024E-03	-1.3688E-02	7.9199E-02
A8=	-1.0534E-02	1.2581E-01	5.1537E-04	-1.7253E-03	9.9446E-02	-2.9673E-02
A10=	2.5445E-01	2.4461E-02	-4.5088E-03	8.2334E-04	-7.7462E-02	7.2665E-03
A12=	-1.8191E-01	-1.9951E-02	5.8669E-04	-5.6815E-05	2.7782E-02	-1.2029E-03
A14=	3.6895E-02	-6.4052E-05	—	—	-4.7393E-03	1.2052E-04
A16=	—	—	—	—	3.1108E-04	-5.2565E-06

In the image capturing optical lens system according to the 11th embodiment, the definitions of these parameters shown in the following table are the same as those stated in the 1st embodiment with corresponding values for the 11th embodiment. Moreover, these parameters can be calculated from Table 21 and Table 22 as the following values and satisfy the following relationships:

f (mm)	3.58	R12/f2	-0.15
Fno	2.60	f/f4	1.11
HFOV (deg.)	38.6	f/f5	-0.05
(V2 + V5)/V1	0.83	( f/f5  +  f/f6 )/(f/f4)	1.11
V5/V6	1.000	CT2/tan( $\alpha$ ) (mm)	0.08
CT5/CT6	1.34	BFL/Td	0.22
(R1 + R2)/(R1 - R2)	-1.45	ImgH/f	0.820
(R9 - R10)/(R9 + R10)	-0.08	TTL/ImgH	1.63

It will be apparent to those skilled in the art that various modifications and variations can be made to the structure of the present disclosure without departing from the scope or spirit of the disclosure. In view of the foregoing, it is intended that the present disclosure cover modifications and

variations of this disclosure provided they fall within the scope of the following claims.

What is claimed is:

1. An image capturing optical lens system comprising six lens elements, the six lens elements being, in order from an object side to an image side:

a first lens element, a second lens element, a third lens element, a fourth lens element, a fifth lens element and a sixth lens element;

wherein each of the six lens elements has an object-side surface facing towards the object side and an image-side surface facing towards the image side;

wherein the first lens element has the image-side surface being concave in a paraxial region thereof; the third lens element has negative refractive power;

the sixth lens element has the image-side surface being concave in a paraxial region thereof and comprising at least one convex shape in an off-axis region thereof;

wherein an Abbe number of the fifth lens element is V5, an Abbe number of the sixth lens element is V6, a focal length of the image capturing optical lens system is f,

## 41

a focal length of the fourth lens element is  $f_4$ , and the following relationships are satisfied:

$$0.20 < V_5/V_6 < 0.70; \text{ and}$$

$$0.6 < f/f_4 < 1.8.$$

2. The image capturing optical lens system of claim 1, wherein the second lens element has the object-side surface being convex in a paraxial region thereof; the third lens element has the image-side surface being concave in a paraxial region thereof.

3. The image capturing optical lens system of claim 1, wherein the fourth lens element has the image-side surface being convex in a paraxial region thereof; the sixth lens element has the object-side surface being convex in a paraxial region thereof.

4. The image capturing optical lens system of claim 1, wherein the fifth lens element has negative refractive power.

5. The image capturing optical lens system of claim 1, wherein the sixth lens element has positive refractive power.

6. The image capturing optical lens system of claim 1, wherein an axial distance between the image-side surface of the sixth lens element and an image plane is BFL, an axial distance between the object-side surface of the first lens element and the image-side surface of the sixth lens element is  $T_d$ , and the following relationship is satisfied:

$$0.15 < BFL/T_d < 0.40.$$

7. The image capturing optical lens system of claim 1, wherein a maximum image height of the image capturing optical lens system is  $ImgH$ , an axial distance between the object-side surface of the first lens element and an image plane is TTL, and the following relationship is satisfied:

$$TTL/ImgH < 1.8.$$

8. The image capturing optical lens system of claim 1, wherein an axial distance between the third lens element and the fourth lens element is smaller than an axial distance between the fourth lens element and the fifth lens element.

9. An image capturing optical lens system comprising six lens elements, the six lens elements being, in order from an object side to an image side:

a first lens element, a second lens element, a third lens element, a fourth lens element, a fifth lens element and a sixth lens element;

wherein each of the six lens elements has an object-side surface facing towards the object side and an image-side surface facing towards the image side;

wherein the third lens element with negative refractive power has the object-side surface being convex in a paraxial region thereof and the image-side surface being concave in a paraxial region thereof; the sixth lens element has the image-side surface being concave in a paraxial region thereof and comprising at least one convex shape in an off-axis region thereof;

wherein an Abbe number of the fifth lens element is  $V_5$ , an Abbe number of the sixth lens element is  $V_6$ , a focal length of the image capturing optical lens system is  $f$ , a focal length of the fourth lens element is  $f_4$ , and the following relationships are satisfied:

$$0.20 < V_5/V_6 < 0.70; \text{ and}$$

$$0.6 < f/f_4 < 1.8.$$

10. The image capturing optical lens system of claim 9, wherein the fourth lens element has the object-side surface being convex in a paraxial region thereof.

## 42

11. The image capturing optical lens system of claim 9, wherein the sixth lens element has the object-side surface being convex in a paraxial region thereof.

12. The image capturing optical lens system of claim 9, wherein the focal length of the image capturing optical lens system is  $f$ , a focal length of the fifth lens element is  $f_5$ , and the following relationship is satisfied:

$$-0.61 \leq f/f_5 < -0.20.$$

13. The image capturing optical lens system of claim 9, wherein the focal length of the image capturing optical lens system is  $f$ , the focal length of the fourth lens element is  $f_4$ , and the following relationship is satisfied:

$$0.98 \leq f/f_4 < 1.8.$$

14. An image capturing optical lens system comprising six lens elements, the six lens elements being, in order from an object side to an image side:

a first lens element, a second lens element, a third lens element, a fourth lens element, a fifth lens element and a sixth lens element;

wherein each of the six lens elements has an object-side surface facing towards the object side and an image-side surface facing towards the image side;

wherein the third lens element with negative refractive power has the object-side surface being convex in a paraxial region thereof and the image-side surface being concave in a paraxial region thereof; the sixth lens element has the image-side surface being concave in a paraxial region thereof and comprising at least one convex shape in an off-axis region thereof;

wherein an Abbe number of the fifth lens element is  $V_5$ , an Abbe number of the sixth lens element is  $V_6$ , a maximum image height of the image capturing optical lens system is  $ImgH$ , an axial distance between the object-side surface of the first lens element and an image plane is TTL, and the following relationships are satisfied:

$$0.20 < V_5/V_6 < 0.70; \text{ and}$$

$$TTL/ImgH < 1.8.$$

15. The image capturing optical lens system of claim 14, wherein the fourth lens element with positive refractive power has the image-side surface being convex in a paraxial region thereof.

16. The image capturing optical lens system of claim 14, wherein a focal length of the image capturing optical lens system is  $f$ , a focal length of the fourth lens element is  $f_4$ , a focal length of the fifth lens element is  $f_5$ , a focal length of the sixth lens element is  $f_6$ , and the following relationship is satisfied:

$$0.3 < (|f/f_5| + |f/f_6|)/(f/f_4) < 1.5.$$

17. The image capturing optical lens system of claim 14, wherein an axial distance between the image-side surface of the sixth lens element and the image plane is BFL, an axial distance between the object-side surface of the first lens element and the image-side surface of the sixth lens element is  $T_d$ , and the following relationship is satisfied:

$$0.26 \leq BFL/T_d \leq 0.35.$$

## 43

18. The image capturing optical lens system of claim 14, wherein a curvature radius of the object-side surface of the first lens element is R1, a curvature radius of the image-side surface of the first lens element is R2, and the following relationship is satisfied:

$$-3.0 < (R1+R2)/(R1-R2) < 0.$$

19. The image capturing optical lens system of claim 14, wherein an absolute value of a focal length of the fifth lens element is larger than an absolute value of a focal length of the fourth lens element.

20. The image capturing optical lens system of claim 14, wherein an absolute value of a focal length of the fifth lens element is larger than an absolute value of a focal length of the first lens element.

21. An image capturing optical lens system comprising six lens elements, the six lens elements being, in order from an object side to an image side:

a first lens element, a second lens element, a third lens element, a fourth lens element, a fifth lens element and a sixth lens element;

wherein each of the six lens elements has an object-side surface facing towards the object side and an image-side surface facing towards the image side;

wherein the third lens element has negative refractive power; the sixth lens element has the object-side surface being convex in a paraxial region thereof, and the image-side surface being concave in a paraxial region thereof and comprising at least one convex shape in an off-axis region thereof;

wherein an absolute value of a focal length of the fifth lens element is larger than an absolute value of a focal length of the first lens element; an absolute value of a curvature radius of the object-side surface of the third lens element is larger than an absolute value of a curvature radius of the image-side surface of the third lens element;

## 44

wherein an Abbe number of the fifth lens element is V5, an Abbe number of the sixth lens element is V6, and the following relationship is satisfied:

$$0.20 < V5/V6 < 0.70.$$

22. The image capturing optical lens system of claim 21, wherein the sixth lens element has negative refractive power.

23. The image capturing optical lens system of claim 21, wherein the fifth lens element has negative refractive power; an axial distance between the image-side surface of the sixth lens element and an image plane is BFL, an axial distance between the object-side surface of the first lens element and the image-side surface of the sixth lens element is Td, and the following relationship is satisfied:

$$0.15 < BFL/Td < 0.40.$$

24. The image capturing optical lens system of claim 21, wherein the fourth lens element has the object-side surface being convex in a paraxial region thereof.

25. The image capturing optical lens system of claim 21, wherein a focal length of the image capturing optical lens system is f, a focal length of the fourth lens element is f4, a focal length of the fifth lens element is f5, a focal length of the sixth lens element is f6, and the following relationship is satisfied:

$$0.3 < (|f/f5| + |f/f6|)/(f/f4) \leq 0.73.$$

26. The image capturing optical lens system of claim 21, wherein an axial distance between the image-side surface of the sixth lens element and an image plane is BFL, an axial distance between the object-side surface of the first lens element and the image-side surface of the sixth lens element is Td, and the following relationship is satisfied:

$$0.26 \leq BFL/Td \leq 0.35.$$

\* \* \* \* \*