



US010939952B2

(12) **United States Patent**  
**Williams et al.**

(10) **Patent No.:** **US 10,939,952 B2**  
(45) **Date of Patent:** **Mar. 9, 2021**

(54) **ADAPTER, EXTENSION, AND CONNECTOR ASSEMBLIES FOR SURGICAL DEVICES**

2017/0046; A61B 18/14; A61B 17/1155;  
A61B 2017/00473; A61B 2017/0477;  
A61B 2017/00734; A61B 2018/0091

(71) Applicant: **Covidien LP**, Mansfield, MA (US)

See application file for complete search history.

(72) Inventors: **Justin Williams**, Southbury, CT (US);  
**Jon Wink**, Haddam, CT (US)

(56) **References Cited**

(73) Assignee: **Covidien LP**, Mansfield, MA (US)

U.S. PATENT DOCUMENTS

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 837 days.

2,777,340 A 1/1957 Hettwer et al.  
2,957,353 A 10/1960 Babacz  
(Continued)

(21) Appl. No.: **15/292,761**

FOREIGN PATENT DOCUMENTS

(22) Filed: **Oct. 13, 2016**

CA 2451558 A1 1/2003  
CN 1547454 A 11/2004  
(Continued)

(65) **Prior Publication Data**

US 2017/0128123 A1 May 11, 2017

OTHER PUBLICATIONS

**Related U.S. Application Data**

Extended European Search Report corresponding to counterpart International Application No. EP 14 18 4882.0 dated May 12, 2015.  
(Continued)

(60) Provisional application No. 62/251,930, filed on Nov. 6, 2015.

(51) **Int. Cl.**

**A61B 18/14** (2006.01)  
**A61B 17/115** (2006.01)

(Continued)

*Primary Examiner* — Eun Hwa Kim

*Assistant Examiner* — Adam Z Minchella

(74) *Attorney, Agent, or Firm* — Carter, DeLuca & Farrell, LLP

(52) **U.S. Cl.**

CPC ..... **A61B 18/14** (2013.01); **A61B 17/1155** (2013.01); **A61B 2017/0046** (2013.01); **A61B 2017/00398** (2013.01); **A61B 2017/00473** (2013.01); **A61B 2017/00477** (2013.01); **A61B 2017/00734** (2013.01); **A61B 2018/0091** (2013.01); **A61B 2018/00172** (2013.01)


(57) **ABSTRACT**

An assembly including an adapter assembly and an extension assembly for connecting an end effector to an electro-surgical instrument is provided. The adapter assembly includes a first pusher assembly configured for converting rotational motion into linear motion. The first pusher assembly includes a pusher member and first and second pawl assemblies for operable engagement with a flexible band assembly of the extension assembly.

(58) **Field of Classification Search**

CPC ..... A61B 2017/00376; A61B 2017/00398; A61B 2018/00172; A61B 30/34; A61B

**18 Claims, 29 Drawing Sheets**



(51) **Int. Cl.**  
*A61B 17/00* (2006.01)  
*A61B 18/00* (2006.01)

(56) **References Cited**  
 U.S. PATENT DOCUMENTS

3,111,328 A	11/1963	Di Rito et al.	6,032,849 A	3/2000	Mastri et al.
3,695,058 A	10/1972	Keith, Jr.	6,045,560 A	4/2000	McKean et al.
3,734,515 A	5/1973	Dudek	6,090,123 A	7/2000	Culp et al.
3,759,336 A	9/1973	Marcovitz et al.	6,126,651 A	10/2000	Mayer
4,162,399 A	7/1979	Hudson	6,129,547 A	10/2000	Cise et al.
4,606,343 A	8/1986	Conta et al.	6,165,169 A	12/2000	Panescu et al.
4,705,038 A	11/1987	Sjostrom et al.	6,239,732 B1	5/2001	Cusey
4,722,685 A	2/1988	de Estrada et al.	6,241,139 B1	6/2001	Milliman et al.
4,823,807 A	4/1989	Russell et al.	6,264,086 B1	7/2001	McGuckin, Jr.
4,874,181 A	10/1989	Hsu	6,264,087 B1	7/2001	Whitman
5,129,118 A	7/1992	Walmesley	6,302,311 B1	10/2001	Adams et al.
5,129,570 A	7/1992	Schulze et al.	6,315,184 B1	11/2001	Whitman
5,152,744 A	10/1992	Krause et al.	6,321,855 B1	11/2001	Barnes
5,301,061 A	4/1994	Nakada et al.	6,329,778 B1	12/2001	Culp et al.
5,312,023 A	5/1994	Green et al.	6,343,731 B1	2/2002	Adams et al.
5,326,013 A	7/1994	Green et al.	6,348,061 B1	2/2002	Whitman
5,350,355 A	9/1994	Sklar	6,368,324 B1	4/2002	Dinger et al.
5,383,874 A	1/1995	Jackson et al.	6,371,909 B1	4/2002	Hoeg et al.
5,383,880 A	1/1995	Hooven	6,434,507 B1	8/2002	Clayton et al.
5,389,098 A	2/1995	Tsuruta et al.	6,443,973 B1	9/2002	Whitman
5,395,033 A	3/1995	Byrne et al.	6,461,372 B1	10/2002	Jensen et al.
5,400,267 A	3/1995	Denen et al.	6,488,197 B1	12/2002	Whitman
5,411,508 A	5/1995	Bessler et al.	6,491,201 B1	12/2002	Whitman
5,413,267 A	5/1995	Solyntjes et al.	6,533,157 B1	3/2003	Whitman
5,427,087 A	6/1995	Ito et al.	6,537,280 B2	3/2003	Dinger et al.
5,433,721 A	7/1995	Hooven et al.	6,610,066 B2	8/2003	Dinger et al.
5,454,378 A *	10/1995	Palmer ..... A61B 17/00234 600/564	6,611,793 B1	8/2003	Burnside et al.
5,467,911 A	11/1995	Tsuruta et al.	6,645,218 B1	11/2003	Cassidy et al.
5,476,379 A	12/1995	Disel	6,654,999 B2	12/2003	Stoddard et al.
5,487,499 A	1/1996	Sorrentino et al.	6,698,643 B2	3/2004	Whitman
5,518,163 A	5/1996	Hooven	6,699,177 B1	3/2004	Wang et al.
5,518,164 A	5/1996	Hooven	6,716,233 B1	4/2004	Whitman
5,526,822 A	6/1996	Burbank et al.	6,743,240 B2	6/2004	Smith et al.
5,529,235 A	6/1996	Boiarski et al.	6,783,533 B2	8/2004	Green et al.
5,535,934 A	7/1996	Boiarski et al.	6,792,390 B1	9/2004	Burnside et al.
5,535,937 A	7/1996	Boiarski et al.	6,793,652 B1	9/2004	Whitman et al.
5,540,375 A	7/1996	Bolanos et al.	6,817,508 B1	11/2004	Racenet et al.
5,540,706 A	7/1996	Aust et al.	6,830,174 B2	12/2004	Hillstead et al.
5,542,594 A	8/1996	McKean et al.	6,846,308 B2	1/2005	Whitman et al.
5,549,637 A	8/1996	Crainich	6,846,309 B2	1/2005	Whitman et al.
5,553,675 A	9/1996	Pitzen et al.	6,849,071 B2	2/2005	Whitman et al.
5,562,239 A	10/1996	Boiarski et al.	6,860,892 B1	3/2005	Tanaka et al.
5,564,615 A	10/1996	Bishop et al.	6,899,538 B2	5/2005	Matoba
5,609,560 A	3/1997	Ichikawa et al.	6,905,057 B2	6/2005	Swayze et al.
5,626,587 A	5/1997	Bishop et al.	6,959,852 B2	11/2005	Shelton, IV et al.
5,632,432 A	5/1997	Schulze et al.	6,964,363 B2	11/2005	Wales et al.
5,645,209 A	7/1997	Green et al.	6,981,628 B2	1/2006	Wales
5,647,526 A	7/1997	Green et al.	6,981,941 B2	1/2006	Whitman et al.
5,653,374 A	8/1997	Young et al.	6,986,451 B1	1/2006	Mastri et al.
5,658,300 A	8/1997	Bito et al.	6,988,649 B2	1/2006	Shelton, IV et al.
5,662,662 A	9/1997	Bishop et al.	7,032,798 B2	4/2006	Whitman et al.
5,667,517 A	9/1997	Hooven	RE39,152 E	6/2006	Aust et al.
5,693,042 A	12/1997	Boiarski et al.	7,055,731 B2	6/2006	Shelton, IV et al.
5,704,534 A	1/1998	Huitema et al.	7,059,508 B2	6/2006	Shelton, IV et al.
5,713,505 A	2/1998	Huitema	7,077,856 B2	7/2006	Whitman
5,762,603 A	6/1998	Thompson	7,111,769 B2	9/2006	Wales et al.
5,779,130 A	7/1998	Alesi et al.	7,122,029 B2	10/2006	Koop et al.
5,782,396 A	7/1998	Mastri et al.	7,140,528 B2	11/2006	Shelton, IV
5,782,397 A	7/1998	Koukline	7,141,049 B2	11/2006	Stern et al.
5,792,573 A	8/1998	Pitzen et al.	7,143,923 B2	12/2006	Shelton, IV et al.
5,797,536 A	8/1998	Smith et al.	7,143,925 B2	12/2006	Shelton, IV et al.
5,820,009 A	10/1998	Melling et al.	7,143,926 B2	12/2006	Shelton, IV et al.
5,863,159 A	1/1999	Lasko	7,147,138 B2	12/2006	Shelton, IV
5,908,427 A	6/1999	McKean et al.	7,172,104 B2	2/2007	Scirica et al.
5,954,259 A	9/1999	Viola et al.	7,225,964 B2	6/2007	Mastri et al.
5,964,774 A	10/1999	McKean et al.	7,238,021 B1	7/2007	Johnson
5,993,454 A	11/1999	Longo	7,246,734 B2	7/2007	Shelton, IV
6,010,054 A	1/2000	Johnson et al.	7,252,660 B2	8/2007	Kunz
6,017,354 A	1/2000	Culp et al.	7,328,828 B2	2/2008	Ortiz et al.
			7,364,061 B2	4/2008	Swayze
			7,380,695 B2	6/2008	Doll et al.
			7,380,696 B2	6/2008	Shelton, IV et al.
			7,404,508 B2	7/2008	Smith et al.
			7,407,078 B2	8/2008	Shelton, IV et al.
			7,416,101 B2	8/2008	Shelton, IV et al.
			7,419,080 B2	9/2008	Smith et al.
			7,422,139 B2	9/2008	Shelton, IV et al.
			7,431,189 B2	10/2008	Shelton, IV et al.
			7,441,684 B2	10/2008	Shelton, IV et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

7,448,525 B2	11/2008	Shelton, IV et al.	8,357,144 B2	1/2013	Whitman et al.
7,464,846 B2	12/2008	Shelton, IV et al.	8,365,633 B2	2/2013	Simaan et al.
7,464,847 B2	12/2008	Viola et al.	8,365,972 B2	2/2013	Aranyi et al.
7,464,849 B2	12/2008	Shelton, IV et al.	8,371,492 B2	2/2013	Aranyi et al.
7,481,347 B2	1/2009	Roy	8,372,057 B2	2/2013	Cude et al.
7,481,824 B2	1/2009	Boudreaux et al.	8,391,957 B2	3/2013	Carlson et al.
7,487,899 B2	2/2009	Shelton, IV et al.	8,403,926 B2	3/2013	Nobis et al.
7,549,564 B2	6/2009	Boudreaux et al.	8,418,904 B2	4/2013	Wenchell et al.
7,565,993 B2	7/2009	Milliman et al.	8,424,739 B2	4/2013	Racenet et al.
7,568,603 B2	8/2009	Shelton, IV et al.	8,454,585 B2	6/2013	Whitman
7,575,144 B2	8/2009	Ortiz et al.	8,505,802 B2	8/2013	Viola et al.
7,588,175 B2	9/2009	Timm et al.	8,517,241 B2	8/2013	Nicholas et al.
7,588,176 B2	9/2009	Timm et al.	8,523,043 B2	9/2013	Ullrich et al.
7,637,409 B2	12/2009	Marczyk	8,551,076 B2	10/2013	Duval et al.
7,641,093 B2	1/2010	Doll et al.	8,561,871 B2	10/2013	Rajappa et al.
7,644,848 B2	1/2010	Swayze et al.	8,561,874 B2	10/2013	Scirica
7,670,334 B2	3/2010	Hueil et al.	8,602,287 B2	12/2013	Yates et al.
7,673,780 B2	3/2010	Shelton, IV et al.	8,623,000 B2	1/2014	Humayun et al.
7,699,835 B2	4/2010	Lee et al.	8,627,995 B2	1/2014	Smith et al.
7,721,931 B2	5/2010	Shelton, IV et al.	8,632,463 B2	1/2014	Drinan et al.
7,738,971 B2	6/2010	Swayze et al.	8,636,766 B2	1/2014	Milliman et al.
7,740,159 B2	6/2010	Shelton, IV et al.	8,647,258 B2	2/2014	Aranyi et al.
7,743,960 B2	6/2010	Whitman et al.	8,652,121 B2	2/2014	Quick et al.
7,758,613 B2	7/2010	Whitman	8,657,174 B2	2/2014	Yates et al.
7,766,210 B2	8/2010	Shelton, IV et al.	8,657,177 B2	2/2014	Scirica et al.
7,770,773 B2	8/2010	Whitman et al.	8,672,206 B2	3/2014	Aranyi et al.
7,770,775 B2	8/2010	Shelton, IV et al.	8,696,552 B2	4/2014	Whitman
7,793,812 B2	9/2010	Moore et al.	8,708,213 B2	4/2014	Shelton, IV et al.
7,799,039 B2	9/2010	Shelton, IV et al.	8,715,306 B2	5/2014	Faller et al.
7,802,712 B2	9/2010	Milliman et al.	8,758,391 B2	6/2014	Swayze et al.
7,803,151 B2	9/2010	Whitman	8,806,973 B2	8/2014	Ross et al.
7,822,458 B2	10/2010	Webster, III et al.	8,808,311 B2	8/2014	Heinrich et al.
7,845,534 B2	12/2010	Viola et al.	8,820,605 B2	9/2014	Shelton, IV
7,845,537 B2	12/2010	Shelton, IV et al.	8,844,789 B2 *	9/2014	Shelton, IV ..... A61B 34/30 227/176.1
7,857,185 B2	12/2010	Swayze et al.	8,851,355 B2	10/2014	Aranyi et al.
7,870,989 B2	1/2011	Viola et al.	8,858,571 B2	10/2014	Shelton, IV et al.
7,900,805 B2	3/2011	Shelton, IV et al.	8,875,972 B2	11/2014	Weisenburgh, II et al.
7,905,897 B2	3/2011	Whitman et al.	8,888,762 B2	11/2014	Whitman
7,918,230 B2	4/2011	Whitman et al.	8,893,946 B2	11/2014	Boudreaux et al.
7,922,061 B2	4/2011	Shelton, IV et al.	8,899,462 B2	12/2014	Kostrzewski et al.
7,922,719 B2	4/2011	Ralph et al.	8,905,289 B2	12/2014	Patel et al.
7,947,034 B2	5/2011	Whitman	8,919,630 B2	12/2014	Milliman
7,951,071 B2	5/2011	Whitman et al.	8,931,680 B2	1/2015	Milliman
7,954,682 B2	6/2011	Giordano et al.	8,939,344 B2	1/2015	Olson et al.
7,959,051 B2	6/2011	Smith et al.	8,950,646 B2	2/2015	Viola
7,963,433 B2	6/2011	Whitman et al.	8,960,519 B2	2/2015	Whitman et al.
7,967,178 B2	6/2011	Scirica et al.	8,961,396 B2	2/2015	Azarbarzin et al.
7,967,179 B2	6/2011	Olson et al.	8,967,443 B2	3/2015	McCuen
7,992,758 B2	8/2011	Whitman et al.	8,968,276 B2	3/2015	Zemlok et al.
8,011,550 B2	9/2011	Aranyi et al.	8,968,337 B2	3/2015	Whitfield et al.
8,016,178 B2	9/2011	Olson et al.	8,991,677 B2 *	3/2015	Moore ..... A61B 17/072 227/175.2
8,016,855 B2	9/2011	Whitman et al.	8,992,422 B2	3/2015	Spivey et al.
8,020,743 B2	9/2011	Shelton, IV	9,016,545 B2	4/2015	Aranyi et al.
8,025,199 B2	9/2011	Whitman et al.	9,023,014 B2	5/2015	Chowaniec et al.
8,035,487 B2	10/2011	Malackowski	9,033,868 B2	5/2015	Whitman et al.
8,052,024 B2	11/2011	Viola et al.	9,055,943 B2	6/2015	Zemlok et al.
8,114,118 B2	2/2012	Knodel et al.	9,064,653 B2	6/2015	Prest et al.
8,127,975 B2	3/2012	Olson et al.	9,072,515 B2	7/2015	Hall et al.
8,132,705 B2	3/2012	Viola et al.	9,113,847 B2	8/2015	Whitman et al.
8,152,516 B2	4/2012	Harvey et al.	9,113,875 B2	8/2015	Viola et al.
8,157,150 B2	4/2012	Viola et al.	9,113,876 B2	8/2015	Zemlok et al.
8,157,151 B2	4/2012	Ingmanson et al.	9,113,899 B2	8/2015	Garrison et al.
8,182,494 B1	5/2012	Yencho et al.	9,216,013 B2	12/2015	Scirica et al.
8,186,555 B2	5/2012	Shelton, IV et al.	9,241,712 B2	1/2016	Zemlok et al.
8,186,587 B2	5/2012	Zmood et al.	9,282,961 B2	3/2016	Whitman et al.
8,220,367 B2	7/2012	Hsu	9,282,963 B2	3/2016	Bryant
8,235,273 B2	8/2012	Olson et al.	9,295,522 B2	3/2016	Kostrzewski
8,241,322 B2	8/2012	Whitman et al.	9,307,986 B2	4/2016	Hall et al.
8,272,554 B2	9/2012	Whitman et al.	10,045,791 B2 *	8/2018	Sakaguchi ..... A61B 18/1445
8,292,150 B2	10/2012	Bryant	2001/0031975 A1	10/2001	Whitman et al.
8,292,888 B2	10/2012	Whitman	2002/0049454 A1	4/2002	Whitman et al.
8,342,379 B2	1/2013	Whitman et al.	2002/0165541 A1	11/2002	Whitman
8,348,130 B2	1/2013	Shah et al.	2003/0038938 A1	2/2003	Jung
8,348,855 B2	1/2013	Hillely et al.	2003/0165794 A1	9/2003	Matoba
8,353,440 B2	1/2013	Whitman et al.	2004/0034369 A1	2/2004	Sauer et al.
			2004/0111012 A1	6/2004	Whitman
			2004/0133189 A1	7/2004	Sakurai

(56)

References Cited

U.S. PATENT DOCUMENTS

2004/0153124	A1	8/2004	Whitman	2011/0204119	A1	8/2011	McCuen
2004/0176751	A1	9/2004	Weitzner et al.	2011/0218522	A1	9/2011	Whitman
2004/0193146	A1	9/2004	Lee et al.	2011/0276057	A1	11/2011	Conlon et al.
2005/0125027	A1	6/2005	Knodel et al.	2011/0290854	A1	12/2011	Timm et al.
2005/0131442	A1	6/2005	Yachia et al.	2011/0295242	A1	12/2011	Spivey et al.
2006/0142656	A1	6/2006	Malackowski et al.	2011/0295269	A1	12/2011	Swensgard et al.
2006/0142740	A1	6/2006	Sherman et al.	2012/0000962	A1	1/2012	Racenet et al.
2006/0142744	A1	6/2006	Boutoussov	2012/0074199	A1	3/2012	Olson et al.
2006/0259073	A1	11/2006	Miyamoto et al.	2012/0089131	A1	4/2012	Zemlok et al.
2006/0278680	A1	12/2006	Viola et al.	2012/0104071	A1	5/2012	Bryant
2006/0284730	A1	12/2006	Schmid et al.	2012/0116368	A1	5/2012	Viola
2007/0023476	A1	2/2007	Whitman et al.	2012/0143002	A1	6/2012	Aranyi et al.
2007/0023477	A1	2/2007	Whitman et al.	2012/0172924	A1	7/2012	Allen, IV
2007/0027469	A1	2/2007	Smith et al.	2012/0211542	A1	8/2012	Racenet
2007/0029363	A1	2/2007	Popov	2012/0223121	A1	9/2012	Viola et al.
2007/0084897	A1	4/2007	Shelton et al.	2012/0245428	A1	9/2012	Smith et al.
2007/0102472	A1	5/2007	Shelton	2012/0253329	A1	10/2012	Zemlok et al.
2007/0152014	A1	7/2007	Gillum et al.	2012/0310220	A1	12/2012	Malkowski et al.
2007/0175947	A1	8/2007	Ortiz et al.	2012/0323226	A1	12/2012	Chowaniec et al.
2007/0175949	A1	8/2007	Shelton et al.	2012/0330285	A1	12/2012	Hartoumbekis et al.
2007/0175950	A1	8/2007	Shelton et al.	2013/0012957	A1*	1/2013	Shelton, IV ..... B23P 6/00 606/130
2007/0175951	A1	8/2007	Shelton et al.	2013/0093149	A1	4/2013	Saur et al.
2007/0175955	A1	8/2007	Shelton et al.	2013/0181035	A1	7/2013	Milliman
2007/0175961	A1	8/2007	Shelton et al.	2013/0184704	A1	7/2013	Beardsley et al.
2007/0270784	A1	11/2007	Smith et al.	2013/0214025	A1	8/2013	Zemlok et al.
2008/0029570	A1	2/2008	Shelton et al.	2013/0274722	A1	10/2013	Kostrzewski et al.
2008/0029573	A1	2/2008	Shelton et al.	2013/0282052	A1	10/2013	Aranyi et al.
2008/0029574	A1	2/2008	Shelton et al.	2013/0292451	A1	11/2013	Viola et al.
2008/0029575	A1	2/2008	Shelton et al.	2013/0313304	A1	11/2013	Shelton, IV et al.
2008/0058801	A1	3/2008	Taylor et al.	2013/0317486	A1	11/2013	Nicholas et al.
2008/0109012	A1	5/2008	Falco et al.	2013/0319706	A1	12/2013	Nicholas et al.
2008/0110958	A1	5/2008	McKenna et al.	2013/0324978	A1	12/2013	Nicholas et al.
2008/0147089	A1	6/2008	Loh et al.	2013/0324979	A1	12/2013	Nicholas et al.
2008/0167736	A1	7/2008	Swayze et al.	2013/0334281	A1	12/2013	Williams
2008/0185419	A1	8/2008	Smith et al.	2014/0005661	A1*	1/2014	Shelton, IV ..... A61B 34/30 606/41
2008/0188841	A1	8/2008	Tomasello et al.	2014/0005680	A1*	1/2014	Shelton, IV ..... A61B 18/1445 606/130
2008/0197167	A1	8/2008	Viola et al.	2014/0012236	A1	1/2014	Williams et al.
2008/0208195	A1	8/2008	Shores et al.	2014/0012237	A1	1/2014	Pribanic et al.
2008/0237296	A1	10/2008	Boudreaux et al.	2014/0012289	A1	1/2014	Snow et al.
2008/0251561	A1	10/2008	Eades et al.	2014/0025046	A1	1/2014	Williams et al.
2008/0255413	A1	10/2008	Zemlok et al.	2014/0110455	A1	4/2014	Ingmanson et al.
2008/0255607	A1	10/2008	Zemlok	2014/0207125	A1	7/2014	Applegate et al.
2008/0262654	A1	10/2008	Omori et al.	2014/0207182	A1	7/2014	Zergiebel et al.
2008/0308603	A1	12/2008	Shelton et al.	2014/0207185	A1	7/2014	Goble et al.
2009/0012533	A1	1/2009	Barbagli et al.	2014/0236174	A1	8/2014	Williams et al.
2009/0090763	A1	4/2009	Zemlok et al.	2014/0276932	A1	9/2014	Williams et al.
2009/0099876	A1	4/2009	Whitman	2014/0299647	A1	10/2014	Scirica et al.
2009/0138006	A1	5/2009	Bales et al.	2014/0303668	A1	10/2014	Nicholas et al.
2009/0171147	A1	7/2009	Lee et al.	2014/0305994	A1*	10/2014	Parihar ..... A61B 17/115 227/180.1
2009/0179063	A1*	7/2009	Milliman ..... A61B 17/115 227/175.1	2014/0352463	A1*	12/2014	Parihar ..... F16H 19/02 74/25
2009/0182193	A1	7/2009	Whitman et al.	2014/0358129	A1	12/2014	Zergiebel et al.
2009/0209946	A1	8/2009	Swayze et al.	2014/0361068	A1	12/2014	Aranyi et al.
2009/0209990	A1	8/2009	Yates et al.	2014/0365235	A1	12/2014	DeBoer et al.
2009/0254094	A1	10/2009	Knapp et al.	2014/0373652	A1	12/2014	Zergiebel et al.
2009/0299141	A1	12/2009	Downey et al.	2015/0014392	A1	1/2015	Williams et al.
2010/0023022	A1	1/2010	Zeiner et al.	2015/0048144	A1	2/2015	Whitman
2010/0069942	A1	3/2010	Shelton, IV	2015/0076205	A1	3/2015	Zergiebel
2010/0160823	A1*	6/2010	Parihar ..... A61B 10/0275 600/567	2015/0080912	A1	3/2015	Sapre
2010/0193568	A1	8/2010	Scheib et al.	2015/0112381	A1	4/2015	Richard
2010/0211053	A1	8/2010	Ross et al.	2015/0122870	A1	5/2015	Zemlok et al.
2010/0225073	A1	9/2010	Porter et al.	2015/0133224	A1	5/2015	Whitman et al.
2011/0071508	A1	3/2011	Duval et al.	2015/0150547	A1	6/2015	Ingmanson et al.
2011/0077673	A1	3/2011	Grubac et al.	2015/0150574	A1	6/2015	Richard et al.
2011/0121049	A1	5/2011	Malinouskas et al.	2015/0157320	A1	6/2015	Zergiebel et al.
2011/0125138	A1	5/2011	Malinouskas et al.	2015/0157321	A1	6/2015	Zergiebel et al.
2011/0139851	A1	6/2011	McCuen	2015/0164502	A1	6/2015	Richard et al.
2011/0155783	A1	6/2011	Rajappa et al.	2015/0201931	A1	7/2015	Zergiebel et al.
2011/0155786	A1	6/2011	Shelton, IV	2015/0272577	A1	10/2015	Zemlok et al.
2011/0172648	A1	7/2011	Jeong	2015/0297199	A1	10/2015	Nicholas et al.
2011/0174009	A1	7/2011	Iizuka et al.	2015/0303996	A1	10/2015	Calderoni
2011/0174099	A1*	7/2011	Ross ..... A61B 17/072 74/89.32	2015/0320420	A1	11/2015	Penna et al.
2011/0184245	A1	7/2011	Xia et al.	2015/0327850	A1	11/2015	Kostrzewski
				2015/0342601	A1	12/2015	Williams et al.
				2015/0342603	A1	12/2015	Zergiebel et al.

(56)

**References Cited**

## U.S. PATENT DOCUMENTS

2015/0374366 A1 12/2015 Zergiebel et al.  
 2015/0374370 A1 12/2015 Zergiebel et al.  
 2015/0374371 A1 12/2015 Richard et al.  
 2015/0374372 A1 12/2015 Zergiebel et al.  
 2015/0374449 A1 12/2015 Chowanec et al.  
 2015/0380187 A1 12/2015 Zergiebel et al.  
 2016/0095585 A1 4/2016 Zergiebel et al.  
 2016/0095596 A1 4/2016 Scirica et al.  
 2016/0106406 A1 4/2016 Cabrera et al.  
 2016/0113648 A1 4/2016 Zergiebel et al.  
 2016/0113649 A1 4/2016 Zergiebel et al.

## FOREIGN PATENT DOCUMENTS

CN	1957854	A	5/2007
CN	101495046	A	7/2009
CN	102247182	A	11/2011
DE	102008053842	A1	5/2010
EP	1563793	A1	8/2005
EP	1769754	A1	4/2007
EP	2316345	A1	5/2011
EP	2668910	A2	12/2013
ES	2333509	A1	2/2010
JP	2005-125075	A	5/2005
KR	20120022521	A	3/2012
WO	0705571	A1	4/1996
WO	2011/108840	A2	9/2011
WO	2012/040984	A1	4/2012

## OTHER PUBLICATIONS

Canadian Office Action corresponding to counterpart International Application No. CA 2640399 dated May 7, 2015.  
 Japanese Office Action corresponding to counterpart International Application No. JP 2011-197365 dated Mar. 23, 2015.  
 Japanese Office Action corresponding to counterpart International Application No. JP 2011-084092 dated May 20, 2015.  
 Japanese Office Action corresponding to counterpart International Application No. JP 2014-148482 dated Jun. 2, 2015.  
 Extended European Search Report corresponding to counterpart International Application No. EP 14 18 9358.6 dated Jul. 8, 2015.  
 Extended European Search Report corresponding to counterpart International Application No. EP 14 19 6148.2 dated Apr. 23, 2015.  
 Partial European Search Report corresponding to counterpart International Application No. EP 14 19 6704.2 dated May 11, 2015.  
 Australian Office Action corresponding to counterpart International Application No. AU 2010241367 dated Aug. 20, 2015.  
 Partial European Search Report corresponding to counterpart International Application No. EP 14 19 9783.3 dated Sep. 3, 2015.  
 Extended European Search Report corresponding to counterpart International Application No. EP 15 16 9962.6 dated Sep. 14, 2015.  
 Extended European Search Report corresponding to International Application No. EP 15 15 1076.5 dated Apr. 22, 2015.  
 Japanese Office Action corresponding to International Application No. JP 2011-084092 dated Jan. 14, 2016.

Extended European Search Report corresponding to International Application No. EP 12 19 7970.2 dated Jan. 28, 2016.  
 Chinese Office Action corresponding to International Application No. CN 201210560638.1 dated Oct. 21, 2015.  
 European Office Action corresponding to International Application No. EP 14 15 9056.2 dated Oct. 26, 2015.  
 Australian Examination Report No. 1 corresponding to International Application No. AU 2015200153 dated Dec. 11, 2015.  
 Australian Examination Report No. 1 corresponding to International Application No. AU 2014204542 dated Jan. 7, 2016.  
 Chinese Office Action corresponding to International Application No. CN 201310125449.6 dated Feb. 3, 2016.  
 Extended European Search Report corresponding to International Application No. EP 15 19 0245.9 dated Jan. 28, 2016.  
 Extended European Search Report corresponding to International Application No. EP 15 16 7793.7 dated Apr. 5, 2016.  
 European Office Action corresponding to International Application No. EP 14 18 4882.0 dated Apr. 25, 2016.  
 Extended European Search Report corresponding to International Application No. EP 14 19 6704.2 dated Sep. 24, 2015.  
 International Search Report and Written Opinion corresponding to Int'l Appln. No. PCT/US2015/051837, dated Dec. 21, 2015.  
 Extended European Search Report corresponding to International Application No. EP 14 19 7563.1 dated Aug. 5, 2015.  
 Partial European Search Report corresponding to International Application No. EP 15 19 0643.5 dated Feb. 26, 2016.  
 Extended European Search Report corresponding to International Application No. EP 15 16 6899.3 dated Feb. 3, 2016.  
 Extended European Search Report corresponding to International Application No. EP 14 19 9783.3 dated Dec. 22, 2015.  
 Extended European Search Report corresponding to International Application No. EP 15 17 38071 dated Nov. 24, 2015.  
 Extended European Search Report corresponding to International Application No. EP 15 19 0760.7 dated Apr. 1, 2016.  
 Extended European Search Report corresponding to International Application No. EP 15 17 3803.6 dated Nov. 24, 2015.  
 Extended European Search Report corresponding to International Application No. EP 15 17 3804.4 dated Nov. 24, 2015.  
 Extended European Search Report corresponding to International Application No. EP 15 18 8539.9 dated Feb. 17, 2016.  
 Extended European Search Report corresponding to International Application No. EP 15 17 3910.9 dated Nov. 13, 2015.  
 European Office Action corresponding to International Application No. EP 14 15 2236.7 dated Aug. 11, 2015.  
 Extended European Search Report corresponding to International Application No. EP 15 18 4915.5 dated Jan. 5, 2016.  
 Chinese Office Action corresponding to counterpart Int'l Appln. No. CN 201310369318.2 dated Jun. 28, 2016.  
 Chinese Office Action (with English translation), dated Jul. 4, 2016, corresponding to Chinese Patent Application No. 2015101559718; 23 total pages.  
 European Search Report EP 15 156 035.6 dated Aug. 10, 2016.  
 Australian Examination Report No. 1 corresponding to International Application No. AU 2013205872 dated Oct. 19, 2016.  
 Australian Examination Report from Appl. No. AU 2013205840 dated Nov. 3, 2016.

\* cited by examiner







FIG. 1




**FIG. 2**



**FIG. 3**



**FIG. 4**



**FIG. 5**






FIG. 6




FIG. 7




FIG. 8





FIG. 9



**FIG. 10**




FIG. 11





FIG. 12



**FIG. 13**




FIG. 14




FIG. 15




FIG. 16

FIG. 17




FIG. 18







FIG. 19








**FIG. 21**




**FIG. 22**




**FIG. 23**


**FIG. 24**




**FIG. 25**




**FIG. 26**





**FIG. 27**



**FIG. 28**



**FIG. 29**






FIG. 30






FIG. 31







**FIG. 32**




**FIG. 33**




**FIG. 34**




**FIG. 35A**




**FIG. 35B**




**FIG. 36**




**FIG. 37**




**FIG. 38**



**FIG. 39**




**FIG. 40**




**FIG. 41**







**FIG. 42**



**FIG. 43**



## ADAPTER, EXTENSION, AND CONNECTOR ASSEMBLIES FOR SURGICAL DEVICES

### CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of and priority to U.S. Provisional Patent Application No. 62/251,930, filed Nov. 6, 2015, the entire disclosure of which is incorporated by reference herein.

### BACKGROUND

#### 1. Technical Field

The present disclosure relates generally to powered surgical devices. More specifically, the present disclosure relates to an adapter assembly for selectively connecting an extension assembly including an end effector to the actuation units of the powered surgical devices.

#### 2. Background of Related Art

Powered devices for use in surgical procedures are known. To permit reuse of the handle assemblies of these powered surgical devices and so that the handle assembly may be used with a variety of end effectors, adapter assemblies and extension assemblies have been developed for selective attachment to the handle assemblies and to a variety of end effectors. Following use, the adapter and/or extension assemblies may be disposed of along with the end effector. In some instances, the adapter assemblies and extension assemblies may be sterilized for reuse.

### SUMMARY

A surgical assembly for operably connecting an end effector to an electrosurgical instrument is provided. The surgical assembly includes an adapter assembly including a connector assembly, a drive transfer assembly operably received through the connector assembly and including a first rotatable shaft, and a first pusher assembly operably connected to the first rotatable shaft for converting rotational motion from the first rotatable shaft to longitudinal movement to perform a first function, the first pusher assembly including a first pusher member and first and second pawl assemblies. The surgical assembly further includes an extension assembly operably connected to a distal end of the adapter assembly. The extension assembly includes a flexible band assembly operably connectable to the first and second pawl assemblies of the first pusher assembly.

In embodiments, the surgical assembly further includes a second pusher assembly, and a second rotatable shaft operably connected to the second pusher assembly for converting rotational motion from the second rotatable shaft to longitudinal movement to perform a second function. The surgical assembly may further include a drive member, and a third rotatable shaft operably connected to the drive assembly for transferring rotational motion from the third rotatable shaft to perform a third function. The first pawl assembly may include a first plurality of pawl members, and the second pawl assembly includes a second plurality of pawl members. The flexible band assembly may include first and second connector members. Each of the first and second connector members may define an opening configured for selective receipt of a respective one of the first and second pawl assemblies.

In some embodiments, the first plurality of pawl members includes a protrusion selectively receivable within the opening of the first connector member, and the second plurality

of pawl members includes a protrusion selectively receivable within the opening of the second connector member. Each of the protrusions may include a flat proximal facing surface and a slanted distal facing surface. The first and second plurality of pawl members may be pivotally secured to the pusher member.

The pusher member may include a first retainer for supporting the first plurality of pawl members, and a second retainer for supporting the second plurality of pawl members. The first and second retainers may each define a longitudinal slot for receiving the respective first and second plurality of pawl members. The first plurality of pawl members may be pivotally received within the longitudinal slot of the first retainer, and the second plurality of pawl members may be pivotally received within the longitudinal slot of the second retainer. Each of the first and second plurality of pawl members may be configured to flex radially inward. The first and second plurality of pawl members may each include a curved profile. The first and second plurality of pawl members may each be formed of a resilient material.

### BRIEF DESCRIPTION OF THE DRAWINGS

Embodiments of the present disclosure are described herein with reference to the accompanying drawings, wherein:

FIG. 1 is a perspective separated view of an adapter assembly, in accordance with an embodiment of the present disclosure, an extension assembly, in accordance with an embodiment of the present disclosure, and an exemplary electromechanical surgical device;

FIG. 2 is a perspective side view of the exemplary electromechanical surgical device of FIG. 1;

FIG. 3 is a perspective side view of the adapter assembly of FIG. 1;

FIG. 4 is a perspective side view of the adapter assembly of FIG. 3 with the outer sleeve removed;

FIG. 5 is a perspective side view of the adapter assembly of FIGS. 3 and 4 with proximal and distal housings of first and second pusher assemblies removed;

FIG. 6 is a cross-sectional side view of the adapter assembly of FIGS. 2-4 taken along line 6-6 in FIG. 3;

FIG. 7 is a cross-sectional side view of the adapter assembly of FIGS. 2-5 taken along line 7-7 in FIG. 5;

FIG. 8 is an enlarged, perspective view of a coupling assembly and a transfer assembly of the adapter assembly of FIGS. 2-7;

FIG. 9 is a perspective side view of adapter assembly of FIGS. 2-7 with the housing assemblies removed;

FIG. 10 is an enlarged view of the indicated area of detail of FIG. 9;

FIG. 11 is an enlarged view of the indicated area of detail of FIG. 6;

FIG. 12 is an enlarged view of the indicated area of detail of FIG. 7;

FIG. 13 is a perspective end view of the transfer assembly of FIG. 8;

FIG. 14 is an enlarged view of the indicated area of detail of FIG. 6;

FIG. 15 is an enlarged view of the indicated area of detail of FIG. 7;

FIG. 16 is an enlarged view of the indicated area of detail of FIG. 9;

FIG. 17 is a perspective side view of the extension assembly of FIG. 1;

FIG. 18 is a perspective side view of an inner flexible band assembly of the extension assembly of FIG. 17;

FIG. 19 is a perspective side view of an outer flexible band assembly of the extension assembly of FIG. 17;

FIG. 20 is a perspective side view of the inner and outer flexible band assemblies of FIGS. 18 and 19 and an exploded view of a frame assembly of the extension assembly of FIG. 17;

FIG. 21 is a perspective side view of the inner and outer flexible band assemblies and frame assembly of FIG. 20;

FIG. 22 is an enlarged view of the indicated area of detail of FIG. 21;

FIG. 23 is a front, perspective view of the inner and outer flexible band assemblies and frame assembly of FIG. 20;

FIG. 24 is an enlarged view of the indicated area of detail of FIG. 23;

FIG. 25 is a cross-sectional end view taken along line 25-25 of FIG. 17;

FIG. 26 is a cross-sectional end view taken along line 26-26 of FIG. 17;

FIG. 27 is an enlarged perspective side view of a distal end of the inner and outer flexible band assemblies and frame assembly of FIG. 20 including a proximal seal member and first and second distal seal members;

FIG. 28 is an exploded perspective view of the proximal seal member and first and second distal seal members of FIG. 27;

FIG. 29 is an exploded view of a trocar assembly of the extension assembly of FIG. 17;

FIG. 29A is a perspective side view of a connector assembly of the extension assembly of FIG. 17;

FIG. 29B is a cross-section side view of the connector assembly of FIG. 29A;

FIG. 30 is a perspective side view of the trocar assembly of FIG. 29;

FIG. 31 is a cross-sectional side view taken along line 31-31 of FIG. 30;

FIG. 32 is a cross-sectional top view taken along line 32-32 of FIG. 17;

FIG. 33 is an enlarged cross-sectional view of the distal end of the extension assembly of FIG. 17;

FIG. 34 is a perspective side view of the adapter assembly of FIG. 3 connected to the extension assembly of FIG. 17 and an end effector and an anvil assembly connected to the extension assembly;

FIG. 35A is an enlarged cross-sectional top view of the indicated area of detail of FIG. 34;

FIG. 35B is an enlarged cross-sectional side view of the indicated area of detail in FIG. 34;

FIG. 36 is a perspective side view of an adapter assembly according to another embodiment of the present disclosure;

FIG. 37 is a cross-sectional side view taken along line 37-37 of FIG. 36;

FIG. 38 is an enlarged cross-sectional side view of the indicated area of detail of FIG. 37;

FIG. 39 is an exploded perspective view of a pusher assembly of the adapter assembly of FIG. 36;

FIG. 40 is a perspective side view of the pusher assembly of FIG. 39;

FIG. 41 is a cross-sectional side view taken along line 41-41 of FIG. 40;

FIG. 42 is a cross-sectional top view of the adapter assembly of FIG. 36 secured to the extension assembly of FIG. 17;

FIG. 43 is an enlarged cross-sectional top view of the indicated area of detail of FIG. 42, prior to full securement of the extension assembly to the adapter assembly;

FIG. 44 is an enlarged cross-sectional top view of the indicated area of detail of FIG. 42, with the extension assembly secured to the adapter assembly; and

FIG. 45 is a perspective side view of the adapter assembly and extension assembly of FIG. 42, with outer sleeves removed.

#### DETAILED DESCRIPTION OF EMBODIMENTS

Embodiments of the presently disclosed adapter assemblies and extension assemblies for surgical devices and/or handle assemblies are described in detail with reference to the drawings, in which like reference numerals designate identical or corresponding elements in each of the several views. As used herein the term “distal” refers to that portion of the adapter assembly or surgical device, or component thereof, farther from the user, while the term “proximal” refers to that portion of the adapter assembly or surgical device, or component thereof, closer to the user.

With reference to FIG. 1, an adapter assembly in accordance with an embodiment of the present disclosure, shown generally as adapter assembly 100, is configured for selective connection to a powered handheld electromechanical instrument shown, generally as surgical device 10. As illustrated in FIG. 1, the surgical device 10 is configured for selective connection with the adapter assembly 100, and, in turn, the adapter assembly 100 is configured for selective connection with an extension assembly 200. The extension assembly 200 is configured for selective connection with a tool assembly or end effector, e.g. tool assembly 30 (FIG. 34), including a loading unit, e.g. loading unit 40 (FIG. 34), and an anvil assembly, e.g., anvil assembly 50 (FIG. 34), for applying a circular array of staples (not shown) to tissue (not shown).

As illustrated in FIGS. 1 and 2, the surgical device 10 includes a handle housing 12 having a lower housing portion 14, an intermediate housing portion 16 extending from and/or supported on the lower housing portion 14, and an upper housing portion 18 extending from and/or supported on the intermediate housing portion 16. A distal half-section of the upper housing portion 18 defines a nose or connecting portion 18a configured to accept a corresponding drive coupling assembly 110 (FIG. 10) of the adapter assembly 100. For a detailed description of the structure and function of an exemplary electromechanical instrument, please refer to commonly owned U.S. Pat. Appl. Publ. No. 2012/0253329 (“the ’329 application”), the contents of which is incorporated by reference herein in its entirety.

The adapter assembly 100 will now be described with reference to FIGS. 3-20. Referring initially to FIG. 3, the adapter assembly 100 includes a proximal end 102 configured for operable connection to the connecting portion 18a (FIG. 1) of the surgical device 10 (FIG. 1) and a distal end 104 configured for operable connection to the extension assembly 200 (FIG. 1).

Turning to FIGS. 3-5, from the proximal end 102 to the distal end 104 of the adapter assembly 100, the adapter assembly 100 includes a drive coupling assembly 110, a drive transfer assembly 130 operably connected to the drive coupling assembly 110, a first pusher assembly 160 operably connected to the drive transfer assembly 130, and a second pusher assembly 180 operably connected to the drive transfer assembly 130. Each of the drive transfer assembly 130 and the first and second pusher assemblies 160, 180 are operably maintained within an outer sleeve 106 (FIG. 3). As will be described in further detail below, a shaft 108 (FIG.

3) extends longitudinally through the adapter assembly 100 and is operably connected to the drive transfer assembly 130.

With reference to FIGS. 5-9, the drive coupling assembly 110 has a cylindrical profile and is configured to selectively secure the adapter assembly 100 to the surgical device 10 (FIG. 1). The drive coupling assembly 110 includes a connector housing 112 and a connector extension 114 fixedly connected to the connector housing 112 by a mounting plate 113. The connector housing 112 and the connector extension 114 operate to rotatably support a first rotatable proximal drive shaft 116, a second rotatable proximal drive shaft 118, and a third rotatable proximal drive shaft 120. The connector housing 112 and the connector extension 114 of the drive coupling assembly 110 also rotatably support the first, second, and third connector sleeves 116, 118, and 120, respectively. Each of the connector sleeves 122, 124, 126 is configured to mate with the respective first, second, and third drive connectors (not shown) of surgical device 10 (FIG. 1). Each of the connector sleeves 122, 124, 126 is further configured to mate with a proximal end 116a, 118a, 120a of the respective first, second and third proximal drive shafts 116, 118, 120.

The drive coupling assembly 110 also includes first, second and third biasing members 122a, 124a and 126a disposed distally of the respective first, second and third connector sleeves 122, 124, 126. Each of the biasing members 122a, 124a and 126a is disposed about the respective first, second, and third rotatable proximal drive shafts 116, 118 and 120 to help maintain the connector sleeves 122, 124, and 126 engaged with the distal end of the respective rotatable drive connectors (not shown) of the surgical device 10 when the adapter assembly 100 is connected to the surgical device 10. In particular, the first, second, and third biasing members 122a, 124a, and 126a function to bias the respective connector sleeves 122, 124, and 126 in a proximal direction.

For a detailed description of an exemplary drive coupling assembly, please refer to the '329 application, the contents of which were previously incorporated by reference herein.

With reference to FIGS. 9-13, the drive transfer assembly 130 has a cylindrical profile and operably connects the distal ends of the first, second, and third rotatable proximal drive shafts 116, 118, and 120 to the shaft 108, the first pusher assembly 160, and the second pusher assembly 180, respectively. The drive transfer assembly 130 includes a support plate 132 (FIGS. 11 and 12) secured to a proximal end of the connector housing 112 and a drive transfer housing 134 positioned adjacent the support plate 132. The support plate 132 and the housing 134 operate to rotatably support a first rotatable distal drive shaft 136, a second rotatable distal drive shaft 138 and a drive member 140.

The first and second rotatable distal drive shafts 136 and 138 are each operably connected to the respective first and second rotatable proximal drive shafts 116 and 118 of the drive coupling assembly 110 by a pair of gears. In particular, the distal ends of each of the first and second rotatable proximal drive shaft 116 and 118 include a geared portion 142a and 144a, respectively, which engages a proximal drive gear 142b and 144b on a proximal end of the respective first and second distal drive shafts 136 and 138. As shown, each of the respective paired geared portions and proximal drive gears 142a, 142b and 144a, 144b are the same size to provide a 1:1 gear ratio between the respective first and second rotatable proximal and distal drive shafts 116, 136 and 118, 138. In this manner, the respective first and second rotatable proximal and distal drive shafts 116,

136 and 118, 138 rotate at the same speed. However, it is envisioned that either or both of the paired geared portions and proximal drive gears may be of different sizes to alter the gear ratio between the first and second rotatable proximal and distal drive shafts 116, 136 and 118, 138.

A distal end of the third proximal drive shaft 120 of the drive coupling assembly 110 includes a geared portion 146a that engages a geared portion 146b formed on a proximal end of the drive member 140 of the drive transfer assembly 130. The size of the geared portion 146a on the third proximal drive shaft 120 and the geared portion 146b on the drive member 140 are the same size to provide a 1:1 gear ratio between the third proximal drive shaft 120 and the drive member 140. In this manner, the third proximal drive shaft 120 and the drive member 140 rotate at the same speed. However, it is envisioned that either or both of the geared portions 146a, 146b may be of different sizes to alter the gear ratio between the third proximal drive shaft 120 and the drive member 140. A distal end of the drive member 140 defines a socket 145 that receives a proximal end 108a of the shaft 108. Alternatively, the socket 145 may be configured to operably engage a proximal end 208a of a drive shaft (FIG. 17) of an extension assembly 200 (FIG. 17).

The drive transfer assembly 130 also includes a drive connector 148 (FIG. 11) operably connecting the first rotatable distal drive shaft 136 to the first pusher assembly 160 and a tubular connector 150 operably connecting the second rotatable distal drive shaft 138 to the second pusher assembly 180. In particular, a distal end of the first rotatable distal drive shaft 136 includes a geared portion 152a that engages a geared portion 152b of the drive connector 148. A distal end of the second rotatable distal drive shaft 138 includes a geared portion 154a that engages a drive gear 154b secured to a distal end of the tubular connector 150.

As shown, the geared portion 152a of the first rotatable distal drive shaft 136 is smaller than the geared portion 152b of the drive connector 148 to provide a gear ratio of greater than 1:1 between the first rotatable distal drive shaft 136 and the drive connector 148. In this manner, the drive connector 148 rotates at a slower speed than the first rotatable distal drive shaft 136. Similarly, the geared portion 154a of the second rotatable distal drive shaft 138 is smaller than the drive gear 154b on the tubular connector 150 to provide a gear ratio of greater than 1:1 between the second rotatable distal drive shaft 138 and the drive connector 148. In this manner, the tubular connector 150 rotates at a slower speed than the second rotatable distal drive shaft 138. However, it is envisioned that each of the paired geared portions 152a, 152b, and the geared portion 154a and the drive gear 154b may be the same size to provide a gear ratio of 1:1 between the respective first rotatable distal drive shaft 136 and the drive connector 148 and between the second rotatable distal drive shaft 138 and the tubular connector 150.

With particular reference to FIGS. 9-13, the first pusher assembly 160 includes proximal and distal housing sections 162, 164 (FIG. 11), a planetary gear assembly 166 operably mounted within the proximal housing section 162, a screw member 168 (FIG. 11) operably connected to the planetary gear assembly 166 and rotatably supported within the distal housing section 164, and a pusher member 170 (FIG. 11) operably connected to the screw member 168 and slidably disposed within the distal housing section 164. The proximal housing section 162 includes a pair of longitudinal flanges 162a (FIG. 4; only one shown) and the distal housing section 164 includes a pair of longitudinally flattened portions 164a. Each of the flanges 162a and the flattened portions 164a of the respective proximal and distal housing sections 162, 164

engage an inner surface of the sleeve **106** to prevent rotation of the respective proximal housing section **162** and the distal housing section **164** relative to the sleeve **106** during operation of the surgical device **10**.

The planetary gear assembly **166** includes first and second planetary gear systems **166a**, **166b** (FIG. 10). The first planetary gear system **166a** of the first pusher assembly **160** includes a central drive gear **172a** mounted on a distal end of the drive connector **148** of the drive transfer assembly **130** and a plurality of planetary gears **174a** rotatably mounted to a rotatable support ring **176**.

Each of the planetary gears **174a** engages the central drive gear **172a** and a toothed inner surface **165** of the proximal housing section **162**. As central drive gear **172a** rotates in a first direction, i.e., clockwise, each of the planetary gears **174a** rotates in a second direction, i.e., counter-clockwise. As each of the planetary gears **174a** rotates in the second direction, engagement of the planetary gears **174a** with the toothed inner surface **165** of the distal housing section **162** causes the rotatable support ring **176** to rotate in the first direction. Conversely, rotation of the central drive gear **172a** in the second direction causes rotation of each of the planetary gears **174a** in the first direction thereby causing rotation of the rotatable support ring **176** in the second direction. The configuration of the first planetary gear system **166a** provides a reduction in the gear ratio. In this manner, the speed of rotation of the rotatable support ring **174** is less than the speed of rotation of the central drive gear **172a**.

The second planetary gear system **166b** of the first pusher assembly **160** includes a central drive gear **172b** securely affixed to the rotatable support ring **176** and a plurality of planetary gears **174b** rotatably mounted to a proximal end surface **168a** of the screw member **168**. Each of the planetary gears **174b** engages the central drive gear **172b** and the toothed inner surface **165** of the proximal housing section **162**. As the rotatable support ring **176** of the first planetary gear system **166a** rotates in the first direction thereby causing the central drive gear **172b** to also rotate in the first direction, each of the planetary gears **174b** rotates in the second direction. As each of the planetary gears **174b** rotates in the second direction, engagement of the planetary gears **174b** with the toothed inner surface **165** of the proximal housing section **162** causes the screw member **168** to rotate in the first direction. Conversely, rotation of the central drive gear **172b** in the second direction causes rotation of each of the planetary gears **174b** in the first direction, thereby causing the screw member **168** to rotate in the second direction. The configuration of the second planetary gear system **166b** provides a reduction in the gear ratio. In this manner, the speed of rotation of the screw member **168** is less than the speed of rotation of the central drive gear **172b**.

The first and second planetary gear systems **166a**, **166b** operate in unison to provide a reduction in the gear ratio between the first rotatable proximal drive shaft **116** and the screw member **168**. In this manner, the reduction in the speed of rotation of the screw member **168** relative to the drive connector **148** is a product of the reduction provided by the first and second planetary gear systems **166a**, **166b**.

The screw member **168** is rotatably supported within the proximal housing portion **162** and includes a threaded distal end **168b** that operably engages a threaded inner surface **170a** of the pusher member **170**. As the screw member **168** is rotated in the first direction, engagement of the threaded distal end **168b** of the screw member **168** with the threaded inner surface **170a** of the pusher member **170** causes longitudinal advancement of the pusher member **170**, as indi-

cated by arrows "A" in FIG. 12. Conversely, rotation of the screw member **168** in the second direction causes retraction of the pusher member **170**.

The pusher member **170** includes a pair of tabs **178** formed on a distal end thereof for engaging the connector extensions **240**, **242** (FIG. 19) of the outer flexible band assembly **230** (FIG. 19) of the extension assembly **200** (FIG. 17). Although shown as tabs **178**, it is envisioned that the pusher member **170** may include any structure suitable for selectively engaging the connector extensions **240**, **242** of the outer flexible band **230** of the extension assembly **200**.

With particular reference now to FIGS. 14-16, the second pusher assembly **180** is substantially similar to the first pusher assembly **160**, and includes proximal and distal housing sections **182**, **184**, a planetary gear assembly **186** operably mounted within the proximal housing section **182**, a screw member **188** operably connected to the planetary gear assembly **186** and rotatably supported within the distal housing section **184**, and a pusher member **190** operably connected to the screw member **188** and slidably disposed within the distal housing section **184**. Each of the proximal housing section **182** and the distal housing section **184** includes a pair of longitudinal flanges **182a**, **184a** (FIG. 4; only one shown), respectively, engaging an inner surface of the sleeve **106** of the adapter assembly **100** to prevent rotation of the respective proximal housing section **182** and the distal housing section **184** relative to the sleeve **106** during operation of the surgical device **10**.

The planetary gear assembly **186** includes first and second planetary gear systems **186a**, **186b** (FIG. 16). The first planetary gear system **186a** of the second pusher assembly **180** includes a central drive gear **192a** mounted on a distal end of the tubular connector **150** of the drive transfer assembly **130** and a plurality of planetary gears **194a** rotatably mounted to a rotatable support ring **196**.

Each of the planetary gears **194a** engages the central drive gear **192a** and a toothed inner surface **185** of the proximal housing section **182**. As central drive gear **192a** rotates in a first direction, i.e., clockwise, each of the planetary gears **194a** rotates in a second direction, i.e., counter-clockwise. As each of the planetary gears **194a** rotates in the second direction, engagement of the planetary gears **194a** with toothed inner surface **185** of the distal housing section **182** causes the rotatable support ring **196** to rotate in the first direction. Conversely, rotation of the central drive gear **192a** in the second direction causes rotation of each of the planetary gears **194a** in the first direction thereby causing rotation of the rotatable support ring **196** in the second direction. The configuration of the first planetary gear system **186a** provides a reduction in the gear ratio. In this manner, the speed of rotation of the rotatable support ring **194** is less than the speed of rotation of the central drive gear **190a**.

The second planetary gear system **186b** of the second pusher assembly **180** includes a central drive gear **192b** securely affixed to the rotatable support ring **196** and a plurality of planetary gears **194b** rotatably mounted to a proximal end surface **188a** of the screw member **188**. Each of the planetary gears **194b** engages the central drive gear **192b** and the toothed inner surface **185** of the proximal housing section **182**. As the rotatable support ring **196** of the first planetary gear system **186a** rotates in the first direction thereby causing the central drive gear **192b** to also rotate in the first direction, each of the planetary gears **194b** rotates in the second direction. As each of the planetary gears **194b** rotates in the second direction, engagement of the planetary gears **194b** with the toothed inner surface **185** of the proxi-

mal housing section **182** causes the screw member **188** to rotate in the first direction. Conversely, rotation of the central drive gear **192b** in the second direction causes rotation of each of the planetary gears **194b** in the first direction, thereby causing the screw member **198** to rotate in the second direction. The configuration of the second planetary gear system **186b** provides a reduction in the gear ratio. In this manner, the speed of rotation of the screw member **188** is less than the speed of rotation of the central drive gear **182b**. The first and second planetary gear systems **186a**, **186b** operate in unison to provide a reduction in the gear ratio between the second rotatable proximal drive shaft **118** and the screw member **188**. In this manner, the reduction in the speed of rotation of the screw member **188** relative to the tubular connector **150** is a product of the reduction provided by the first and second planetary gear systems **186a**, **186b**.

The screw member **188** is rotatably supported within the proximal housing portion **182** and includes a threaded distal end **188b** that operably engages a threaded inner surface **190a** of the pusher member **190**. As the screw member **188** is rotated in the first direction, engagement of the threaded distal end **188b** of the screw member **188** with the threaded inner surface **190a** of the pusher member **190** causes longitudinal advancement of the pusher member **190**. Conversely, rotation of the screw member **188** in the second direction causes retraction of the pusher member **190**. The pusher member **190** includes a pair of longitudinal flanges **191** (FIG. 5; only one shown) that engage the distal housing section **184** of the second pusher assembly **180** for preventing rotation of the pusher member **190** relative to the distal housing section **184**.

The pusher member **190** includes a pair of tabs **198** formed on a distal end thereof for engaging the connector extensions **220**, **224** (FIG. 18) of the inner flexible band assembly **220** (FIG. 18) of the extension assembly **200** (FIG. 17). Although shown as tabs **198**, it is envisioned that the pusher member **190** may include any structure suitable for selectively engaging the connector extensions **240**, **242** of the outer flexible band **230** of the extension assembly **200**.

The extension assembly **200** for operably connecting the adapter assembly **100** (FIG. 3) with a circular loading unit, e.g. the loading unit **40** (FIG. 34) and an anvil assembly, e.g., the anvil assembly **50** (FIG. 34) will be described with reference now to FIGS. 17-34. In particular, a proximal end **202** of the extension assembly **200** operably connects with the distal end **104** (FIG. 3) of the adapter assembly **100** (FIG. 3) and a distal end **204** of the extension assembly **200** operably connects with the loading unit **40** and the anvil assembly **50**. As shown, the extension assembly **200** provides a slight curvature between the proximal and distal ends **202**, **204**. In an alternative embodiment, the extension assembly **200** may be straight or may include a greater curvature. Although the extension assembly **200** will be shown and described as being used to connect the loading unit **40** and the anvil assembly **50** to the adapter assembly **100** (FIG. 3), it is envisioned that the aspects of the present disclosure may be modified for use with various loading units, anvil assemblies, and adapter assemblies. Exemplary loading units and anvil assemblies are described in commonly owned U.S. Pat. No. 8,590,763 and U.S. patent application Ser. Nos. 14/056,301 and 14/149,355, the contents of each being incorporated herein by reference in their entirety.

The extension assembly **200** includes an inner flexible band assembly **210** (FIG. 18), an outer flexible band assembly **230** (FIG. 19) slidably disposed about the inner flexible band assembly **210**, a frame assembly **250** (FIG. 20) for

supporting the inner and outer flexible band assemblies **210**, **230**, a trocar assembly **270** (FIG. 28) operably received through the inner and outer flexible band assemblies **210**, **230**, and a connector assembly **290** for securing the loading unit **40** (FIG. 34) to the extension assembly **200**. An outer sleeve **206** (FIG. 17) is received about the frame assembly **250** and the trocar assembly **270** and the inner and outer flexible band assemblies **210**, **230** are slidably received through the outer sleeve **206**. As will be described in further detail below, the extension assembly **200** may include a drive shaft **208** operably connected to the trocar assembly **270** and extending through the proximal end **202** of the extension assembly **200**.

With reference to FIG. 18, the inner flexible band assembly **210** includes first and second inner flexible bands **212**, **214**, a support ring **216**, a support base **218**, and first and second connection extensions **220**, **222**. The proximal ends **212a**, **214a** of the respective first and second inner flexible bands **212**, **214** are laterally spaced apart and securely attached to the support ring **216**. The distal ends **212b**, **214b** of the first and second inner flexible bands **212**, **214** are laterally spaced apart and securely attached to a proximal end **218a** of the support base **218**. Each of the first and second inner flexible bands **212**, **214** may be attached to the support ring **216** and/or the support base **218** in any suitable manner, including, for example, by press-fitting, welding, adhesives, and/or with mechanical fasteners. As will be described in further detail below, the inner flexible band assembly **210** is configured to be slidably received about the trocar assembly **270** (FIG. 28) and within the outer flexible band assembly **230** (FIG. 19) and the outer sleeve **206** (FIG. 17).

The first and second connection extensions **220**, **222** of the inner flexible band assembly **210** extend proximally from the support ring **216** and operably connect the inner flexible band assembly **210** with the pusher member **190** (FIG. 15) of the second pusher assembly **180** (FIG. 15) of the adapter assembly **100** (FIG. 3). In particular, each of the first and second connection extensions **220**, **222** define openings **221**, **223** configured to receive tabs **198** (FIG. 15) of the pusher member **190** (FIG. 15) of the second pusher assembly **180**. Receipt of the tabs **198** of the pusher member **190** within the openings **221**, **223** of the respective first and second extensions **220**, **222** secure the inner flexible band assembly **210** of the extension assembly **200** with the second pusher assembly **180** of the adapter assembly **100**. The first and second connection extensions **220**, **222** may be integrally formed with the support ring **216**, or attached thereto in any suitable manner.

The support base **218** extends distally from the inner flexible bands **212**, **214** and is configured to selectively connect the extension assembly **200** with the loading unit **40** (FIG. 34). Specifically, a distal end **218a** of the support base **218** includes a flange **224** for operable engagement with an axially movable assembly (not shown) of the loading unit **40** (FIG. 34). In one embodiment, the flange **224** is configured for connection with a knife assembly (not shown) of the loading unit **40** (FIG. 34).

With reference now to FIG. 19, the outer flexible band assembly **230** is substantially similar to the inner flexible band assembly **210** and includes first and second flexible bands **232**, **234** laterally spaced and connected on proximal ends **232a**, **234a** to a support ring **236** and on distal ends **234b**, **234b** to a proximal end **238a** of a support base **238**. Each of the first and second outer flexible bands **232**, **234** may be attached to the support ring **236** and the support base **238** in any suitable manner, including, for example, by

press-fitting, welding, adhesives, and/or with mechanical fasteners. As will be described in further detail below, the outer flexible band assembly 230 is configured to receive the trocar assembly 270 (FIG. 28) therethrough.

The first and second connection extensions 240, 242 of the outer flexible band assembly 230 extend proximally from the support ring 236 and operably connect the outer flexible band assembly 230 with the pusher member 170 (FIG. 12) of the first pusher assembly 160 (FIG. 12) of the adapter assembly 100 (FIG. 1). In particular, each of the first and second connection extensions 240, 242 define openings 241, 243 configured to receive the tabs 178 (FIG. 12) of the pusher member 170 of the first pusher assembly 180. Receipt of the tabs 178 of the pusher member 170 within the openings 241, 243 of the respective first and second extensions 240, 242 secures the outer flexible band assembly 230 of the extension assembly 200 with the first pusher assembly 180 of the adapter assembly 100. The first and second connection extensions 240, 242 may be integrally formed with the support ring 236, or attached thereto in any suitable manner.

The support base 238 extends distally from the outer flexible bands 232, 234 and is configured to selectively connect the extension assembly 200 with the loading unit 40 (FIG. 34). Specifically, a distal end 238b of the support base 238 includes a flange 244 for operable engagement with an axially movable assembly (not shown) of a loading unit (not shown). In one embodiment, the flange 244 is configured for connection with a staple pusher assembly (not shown) of the loading unit 40 (FIG. 34).

With reference now to FIGS. 20-26, the frame assembly 250 includes first and second proximal spacer members 252, 254, and first and second distal spacer members 256, 258. When secured together, the first and second proximal spacer members 252, 254 define a pair of inner longitudinal slots 253a for slidably receiving the first and second flexible bands 212, 214 (FIG. 18) of the inner flexible band assembly 210 (FIG. 18) and a pair of outer longitudinal slots 253b for slidably receiving the first and second flexible bands 232, 234 (FIG. 19) of the outer flexible band assembly 230 (FIG. 19). The first and second proximal spacer members 252, 254 further define a longitudinal passage 255 for receipt of the trocar assembly 270.

In one embodiment, and as shown, the first and second proximal spacer members 252, 254 are formed of plastic and are secured together with a snap-fit arrangement. Alternatively, the first and second proximal spacer members 252, 254 may be formed of metal or other suitable material and may be secured together in any suitable manner, including by welding, adhesives, and/or using mechanical fasteners.

The first and second distal spacer members 256, 258 define a pair of inner slots 257a for slidably receiving the first and second flexible bands 212, 214 (FIG. 18) of the inner flexible band assembly 210 (FIG. 18) and a pair of outer slots 257b for slidably receiving the first and second flexible bands 232, 234 (FIG. 19) of the outer flexible band assembly 230 (FIG. 19). The first and second distal spacer members 256, 258 further define a longitudinal passage 259 for receipt of the trocar assembly 270.

In one embodiment, and as shown, each of the first and second distal spacer members 256, 258 are secured about the inner and outer flexible band assemblies 210, 230 and to the outer sleeve 206 (FIG. 17) by a pair of screws 260a, 260b (FIG. 26). Alternatively, the first and second distal spacer members 256, 258 may be secured together in any suitable manner, including by welding, adhesives, and/or using

mechanical fasteners. The first and second distal spacer members 256, 258 may be formed of metal or any other suitable material.

With reference now to FIGS. 27 and 28, the frame assembly 250 further includes a proximal seal member 262 and first and second distal seal members 264, 266. Each of the proximal seal member 262 and the first and second distal seal members 264, 266 include seals halves 262a, 262b, 264a, 264b, 266a, 266b, respectively. The proximal seal member 262 is received between the first and second proximal spacer members 252, 254 and the first and second distal spacer members 256, 258. The first half 264a of the first distal seal member 264 is secured to the first half 266a of the second distal seal member 266 and the second half 264b of the first distal seal member 264 is secured to the second half 266b of the second distal seal member 266. The proximal seal member 262 and the first and second distal seal members 264, 266 engage the outer sleeve 206 (FIG. 17), the inner and outer flexible bands 212, 214, 232, 234 of the respective inner and outer flexible band assemblies 210, 230 and the trocar assembly 270 (FIG. 28) in a sealing manner. In this manner, the proximal seal member 262 and the first and second distal seal members 264, 266 operate to provide a fluid tight seal between the distal end 204 and the proximal end 202 of the extension assembly 200.

With reference to FIGS. 29-32, the trocar assembly 270 of the extension assembly 200 includes an outer housing 272, a trocar member 274 slidably disposed within the tubular outer housing 272, and a drive screw 276 operably received within the trocar member 274 for axially moving the trocar member 274 relative to the tubular housing 272. In particular, the trocar member 274 includes a proximal end 274a having an inner threaded portion 275 which engages a threaded distal portion 276b of the drive screw 276. As the drive screw 276 is rotated within the trocar member 274, engagement of the inner threaded portion 275 of the trocar member 274 with the threaded distal portion 276b of the drive screw 276 causes longitudinal movement of the trocar member 274 within the outer housing 272 of the trocar assembly 270. Rotation of the drive screw 276 in a first direction causes longitudinal advancement of the trocar member 274 and rotation of the drive screw 276 in a second direction causes longitudinal retraction of the trocar member 274. A distal end 274b of the trocar member 274 is configured to selectively engage the anvil assembly 50 (FIG. 34).

A bearing assembly 278 is mounted to a proximal end 272a of the outer housing 272 of the trocar assembly 270 for rotatably supporting a proximal end 276a of the drive screw 276 relative to the outer housing 272 and the trocar member 274. The bearing assembly 278 includes a housing 278a, proximal and distal spacers 278b, proximal and distal retention clips 278c, proximal and distal bearings 278d, and a washer 278e. As shown, the proximal end 276a of the drive screw 276 includes a flange 276c for connection with a link assembly 280.

The link assembly 280 operably connects the transfer assembly 130 (FIG. 6) of the adapter assembly 100 with the trocar assembly 270 (FIG. 30) of the extension assembly 200. More particularly, the link assembly 280 transfers rotational energy from the drive member 140 (FIG. 6) of the transfer assembly 130 of the adapter assembly 100 through the curved outer tube 206 (FIG. 17) of the extension assembly 200 to the flange 276c (FIG. 29) on the proximal end 276a of the drive screw 276 of the trocar assembly 270 of the extension assembly 200.

With reference to FIGS. 29A and 29B, the link assembly 280 includes a coupling member 282, a first drive shaft 284,



and a second drive shaft **286**. A proximal end **282a** of the coupling member **282** defines a recess **283a** for receiving a distal end **284b** of the first drive shaft **284**. A distal end **282b** of the coupling member **282** defines a recess **283a** for operably receiving the flange **276c** on the proximal end **276a** of the drive screw **276**. The coupling member **282** includes an annular flange **282c** for rotatably receiving the coupling member **282** between the first and second proximal spacer members **252**, **254** (FIG. 32). The proximal and distal ends **284a**, **284b** of the first drive shaft **284** define oversized openings **285a**, **285b**, respectively, for receiving pins **288a**, **288b**, respectively. A distal end **286b** of the second drive shaft **286** defines a recess **287** for operably receiving the proximal end **284a** of the drive shaft **284**. A proximal end **286a** of the drive shaft **286** includes a flange **286c** for operable receipt within the socket **145** of the drive member **140** of the drive transfer assembly **130** of the adapter assembly **100** (FIG. 12).

With particular reference to FIG. 29B, the proximal end **284a** of the first drive shaft **284** is operably received within the recess **285** in the distal end **286** of the second drive shaft **286**. The distal end **284b** of the first drive shaft **284** is pivotally secured within the recess **283a** of the coupling member **282** by the pin **288a** received through the oversized opening **285b** in the distal end **284b** of the first drive shaft **284**. The proximal end **284a** of the first drive shaft **284** is pivotally secured within the recess **287** in the distal end **286b** of the second drive shaft **286** by the pin **288b** received through the oversized opening **285a** in the proximal end **284a** of the first drive shaft **284**. The recesses **283a** and **287** of the coupling member **282** and the second drive shaft **286**, respectively, and the oversized openings **285a**, **285b** of the first drive shaft **284** are configured to permit pivoting of the second drive shaft **286** relative to the first drive shaft **284** and pivoting of the first drive shaft **284** relative to the coupling member **282** as each of the first and second drive shafts **284**, **286**, and the coupling member **282** are rotated about their respective longitudinal axes to transfer rotational force from the transfer assembly **130** (FIG. 6) of the adapter assembly **100** to the trocar assembly **270** (FIG. 30) of the extension assembly **200**.

With reference now to FIGS. 32 and 33, the connector assembly **290** of the extension assembly **200** includes a tubular connector **292** attached to a distal end **206a** of the outer sleeve **206** and about distal ends of the inner and outer flexible assemblies **210**, **230** (FIG. 26) and the trocar assembly **270**. In particular, a proximal end **292a** of the tubular connector **292** is received within and securely attached to the distal end **206b** of the outer sleeve **206** by a retaining clip **294**. An O-ring **296** forms a fluid tight seal between the tubular connector **292** of the connector assembly **290** and the outer sleeve **206**. A distal end **292b** of the tubular connector **292** is configured to selectively engage a proximal end of the loading unit **40** (FIG. 34). The distal end **292b** of the tubular connector **292** engages the circular loading unit **40** with a snap-fit arrangement, bayonet coupling, or in another suitable manner.

With reference now to FIGS. 34 and 35, the extension assembly **200** is connected to the adapter assembly **100** by receiving the proximal end **202** (FIG. 17) of the extension assembly **200** within the distal end **104** of the adapter assembly **100**. In particular, the first and second connection extensions **220**, **222**, **240**, **242** of respective inner and outer flexible band assemblies **210**, **230** are received within the sleeve **106** of the adapter assembly **100** such that tabs **178** of the pusher member **170** of the first pusher assembly **160** of the adapter assembly **100** are received within the openings

**241**, **243** of the respective first and second connection extensions **240**, **242** of the outer flexible band assembly **230**. In this manner, the outer flexible band assembly **230** is secured with the first pusher assembly **160**. Additionally, the tabs **198** of the pusher member **190** of the second pusher assembly **180** of the adapter assembly **100** are received within the openings **221**, **223** of the first and second connection extensions **221**, **223** of the inner flexible band assembly **210** to secure the inner flexible band assembly **210** with the second pusher assembly **180**.

As noted above, adapter assembly **100** may include a drive shaft **108** (FIG. 3) that extends from the distal end **104** of the adapter assembly **100**. Prior to receipt of the proximal portion **202** of the extension assembly **200** within the distal end **104** of the extension assembly **100**, the drive shaft **108** is removed from the adapter assembly **100**. As the proximal portion **202** of the extension assembly **200** is received within the distal end **102** of the adapter assembly **100**, the proximal end **286a** (FIG. 17) of the second drive shaft **286** (FIG. 17) is received within the socket **145** of the drive member **140** of the drive transfer assembly **130** of the extension assembly **100** (FIG. 12).

After the extension assembly **200** is operably engaged with the adapter assembly **100**, and the adapter assembly **100** is operably engaged with the surgical device **10** (FIG. 1), the loading unit **40** (FIG. 34) of the end effector **30** (FIG. 34) may be attached to the connector assembly **290** of the extension assembly **200** and an anvil assembly **50** (FIG. 34) may be attached to the distal end **274b** of the trocar **274** of the extension assembly **200** in a conventional manner. During actuation of the loading unit **40** and the anvil assembly **50**, longitudinal advancement of the pusher member **190** of the second pusher assembly **180** of the adapter assembly **100**, as described above, and as indicated by arrows "C" in FIG. 35, causes longitudinal advancement of the outer flexible band assembly **230** of the extension assembly **200** and longitudinal advancement of the pusher member **170** of the first pusher assembly **160**, as described above, and as indicated by arrows "D" in FIG. 35, causes longitudinal advancement of the inner flexible band assembly **210**. Rotation of the drive shaft **108** in a first direction, as described above, and as indicated by arrow "E", causes advancement of the trocar **274** of the extension assembly **200**. Conversely, longitudinal retraction of the pusher member **190** causes longitudinal retraction of the outer flexible band assembly **230**, longitudinal retraction of the pusher member **170** causes longitudinal retraction of the inner flexible band assembly **210**, and rotation of the drive shaft **108** in a second direction causes retraction of the trocar **274** of the extension assembly **200**.

In embodiments, the inner flexible band assembly **210** operably connects the second pusher assembly **180** of the adapter assembly **100** with a knife assembly (not show) of the loading unit **40** (FIG. 34) of the end effector **30** (FIG. 34) attached to the connection assembly **290** of the extension assembly **200**. The outer flexible band assembly **230** operably connects the first pusher assembly **160** of the adapter assembly **100** with a staple driver assembly (not shown) of the loading unit **40**. The trocar assembly **270** operably connects the drive transfer assembly **130** of the adapter assembly **100** to the anvil assembly **50** (FIG. 34) of the end effector **30** (FIG. 34). In this manner, operation of the second pusher assembly **160** causes longitudinal movement of the inner flexible band assembly **210** which causes longitudinal movement of the knife assembly, operation of the first pusher assembly **180** causes longitudinal movement of the outer flexible band assembly **230** which causes longitudinal

movement of the staple driver assembly, and operation of the drive transfer assembly **130** causes longitudinal movement of the trocar **274** which causes longitudinal movement of the anvil assembly **50** relative to the loading unit **40**.

By stacking the first and second pusher assemblies **160**, **180** of the adapter assembly **100**, as described, and positioning the drive shaft **108** of the transfer assembly **130** through the first and second pusher assemblies **160**, **180**, the adapter assembly **100** can perform three functions through an access port or other opening (not shown) having a small diameter, e.g., 21 mm. Similarly, by configuring the inner flexible band assembly **210** within the outer flexible band assembly **230** and receiving the trocar assembly **270** through the inner and outer flexible band assemblies **210**, **230**, the extension assembly **200** can perform three functions through an access port or other opening (not shown) having a small diameter, e.g., 21 mm.

With reference now to FIGS. **36-45**, an adapter assembly according to another embodiment of the present disclosure is shown as adapter assembly **300**. Adapter assembly **300** is substantially similar to adapter assembly **100** described hereinabove and will only be described as relates to the differences therebetween.

As will become apparent from the following description, the configuration of adapter assembly **300** permits rotation of a distal portion **304** of adapter assembly **300** about a longitudinal axis “x” (FIG. **37**), relative to a proximal portion **302** of adapter assembly **300**. In this manner, an end effector, e.g. the end effector **30** (FIG. **34**) secured to the distal portion **304** of the adapter assembly **300** or an end effector secured to an extension assembly, e.g., the extension assembly **200** (FIG. **17**) which is secured to the distal portion **304** of the adapter assembly **300** is rotatable about the longitudinal axis “x” independent of movement of the surgical device (not shown) to which the adapter assembly **300** is attached.

With particular reference to FIG. **37**, the adapter assembly **300** includes a base **306** and a support structure **308** rotatable relative to the base **306** along the longitudinal axis “x” of the adapter assembly **300**. A rotation handle **310** is rotatably secured to the base **306** and is fixedly secured to a proximal end of support structure **308**. The rotation handle **310** permits longitudinal rotation of the distal portion **304** of the adapter assembly **300** relative to the proximal end **302** of the adapter assembly **300**. A latch **312** (FIG. **36**) is mounted to the rotation handle **310** and selectively secures the rotation handle **310** in a fixed longitudinal position.

With reference still to FIG. **37**, the proximal portion **302** of the adapter assembly **300** includes a drive coupling assembly **320** and a drive transfer assembly **330** operably connected to the drive coupling assembly **320**. The distal portion **304** of the adapter assembly **300** includes a first pusher assembly **340** operably connected to the drive transfer assembly **330**, and a second pusher assembly **380** operably connected to the drive transfer assembly **330**. The drive coupling assembly **320** and the drive transfer assembly **330** are mounted within the base **306** and remain rotationally fixed relative to the surgical device (not shown) to which the adapter assembly **300** is attached. The first pusher assembly **340** and the second pusher assembly **380** are mounted within the support structure **308** and are rotatable relative to the surgical device (not shown) to which the adapter assembly **300** is attached.

The drive coupling assembly **320** is configured to selectively secure adapter assembly **300** to a surgical device (not shown). For a detailed description of an exemplary surgical device and drive coupling assembly, please refer to com-

monly owned U.S. patent application Ser. No. 14/550,183, filed Nov. 21, 2014, the content of which is incorporated by reference herein in its entirety.

With continued reference to FIGS. **36** and **37**, the rotation handle **310** of the adapter assembly **300** is rotatably secured to the base **306**. The latch **312** is configured to lock the rotation handle **310** relative to the base **306**. Proximal movement of the latch **312**, as indicated by arrow “F” in FIG. **36**, disengages the latch **312** from the base **306** to permit rotation of the rotation handle **310** relative to the base **306**. For a detailed description of an exemplary rotation handle and latch mechanism, please refer to commonly owned U.S. Provisional Patent Application Ser. No. 62/066,518, the content of which is incorporated by reference herein in its entirety.

The support structure **308** is fixedly received about the first and second drive pusher assemblies **340**, **380** and is rotatable relative to the base **306**. As noted above, the rotation handle **310** is fixedly secured to the proximal end of the support structure **308** to facilitate rotation of the support structure **308** relative to the base **306**. The support structure **308** is retained within the outer sleeve **305** of the adapter assembly **300** and is configured to maintain axial alignment of the first and second drive pusher assemblies **340**, **380**. For a detailed description of an exemplary support structure, please refer to commonly owned U.S. Provisional Patent Application Ser. No. 62/066,518, the content of which was previously incorporated by reference herein.

The drive transfer assembly **330**, the first pusher assembly **340**, and the second drive pusher assembly **380** of the adapter assembly **300** are substantially identical to the respective drive transfer assembly **130**, first pusher assembly **160**, and second drive pusher assembly **180** of the adapter assembly **100** described hereinabove, and therefore, will only be described as relates to the differences therebetween.

Briefly, the first pusher assembly **340** includes a planetary gear assembly **346** operably supported within a proximal housing section **342** and a screw member **348** operably connected to the planetary gear assembly **346** and rotatably supported within a distal housing section **344**. The first pusher assembly **340** further includes a pusher member **350** operably connected to the screw member **348** and slidably disposed within the distal housing section **344**.

With particular reference to FIGS. **38-41**, the pusher member **350** includes a substantially cylindrical body **352** having a threaded proximal inner surface **352a** and opposed planar outer surfaces **354**, **356**. Retainers **358**, **360** extend from the respective planar outer surfaces **354**, **356**. Each of the retainers **358**, **360** includes a pair of elongate flanges **358a**, **358b**, **360a**, **360b**, respectively, and a connector **358c**, **360c**, respectively, connecting a proximal end of the elongate flanges **358a**, **358b**, **360a**, **360b**, respectively. Each of the retainers **358**, **360** defines a longitudinal slot **359**, **361**, respectively, between respective elongate flanges **358a**, **358b**, **360a**, **360b**.

A pawl assembly **362**, **364** is received within each of the longitudinal slots **359**, **361**, respectively. The pawl assemblies **362**, **364** each include a plurality of pawl members **362a-e**, **364a-e**, respectively (collectively, pawls **366**, **368**, respectively), and pivot pins **363**, **365**. The pawls **366**, **368** are secured within the respective longitudinal slots **359**, **361** by the pivot pins **363**, **365**, respectively, received through openings **367**, **369**, respectively, formed in the respective distal ends **366b**, **368b** of the pawls **366**, **368**, respectively. The pawls **366**, **368** each include a curved profile and are formed of a resilient material. Protrusions **370**, **372** are formed on an outer curved surface of the respective pawls

366, 368 proximal to the distal ends 366b, 368b, respectively. The protrusions 370, 372 each include a flat proximal facing surface 370a, 372a, respectively, and a slanted or inclined distal facing surface 370b, 372b. As will be described in further detail below, the protrusions 370, 372 are configured to be received within openings 241, 243 (FIG. 43) of respective connector extensions 240, 242 (FIG. 43) of outer flexible band 230 (FIG. 42) of the extension assembly 200 (FIG. 42) to secure the outer flexible band 230 to the pusher member 350 of the first pusher assembly 340 when the extension assembly 200 is secured to the adapter assembly 300.

With particular reference to FIGS. 40 and 41, the pawls 366, 368 of the pawl assemblies 362, 364, respectively, are received within respective longitudinal slots 359, 361 of retainers 358, 360, respectively, with the respective distal ends 366b, 368b secured to retainers 358, 360, respectively, by pivot pins 363, 365, respectively. The proximal ends 366a, 368a of the pawls 366, 368, respectively, are received under the respective connectors 358c, 360c of the retainers 358, 360, respectively, and engage the planar surfaces 354, 356, respectively, of the cylindrical body 352 of the pusher member 350. The pawls 366, 368 are configured such that the protrusions 370, 372, respectively, extend above the elongate flanges 358a, 358b, 360a, 360b, respectively, of the retainers 358, 360, respectively, when the respective pawls 366, 368 are in a first or initial position (FIG. 40).

With reference now to FIGS. 42 and 43, the curved profile of pawls 366, 368 is such that an inward force applied to the protrusions 370, 372, respectively, when the respective inclined distal surfaces 370b, 372b are engaged by connector extensions 240, 242, respectively, of outer flexible band 230 (FIG. 42) of the extension assembly 200 (FIG. 42) cause the pawls 366, 368 to flex inwardly. As the pawls 366, 368 flex inwardly the protrusions 370, 372, respectively, are positioned below the respective retainers 358, 360, thereby allowing connector extensions 240, 242 of outer flexible band 230 to pass over the respective retainers 358, 360. Once the openings 241, 243 of respective connector extensions 240, 242 align with the protrusions 370, 372, respectively, of the respective pawls 366, 368, the pawls 366, 368, respectively spring back to the initial position (FIG. 45), causing the protrusions 370, 372, respectively, to be received within the respective openings 241, 243 of the connector extensions 240, 242, respectively, such that the outer flexible band 230 (FIG. 42) of the extension assembly 200 (FIG. 42) is secured to the first pusher member 340.

Once the connector extensions 240, 242 of the outer flexible band 230 of the extension assembly 200 are received over the pawls 366, 368, respectively, and once the protrusions 370, 372 are received within respective openings 241, 243 of the respective connector extensions 240, 242, engagement of the connector extensions 240, 242 by the flat proximal surface 370a, 372a of the protrusions 370, 372, respectively, prevents the connector extensions 240, 242 from being disengaging from the first pusher assembly 340 during operation of the adapter assembly 300 and the extension assembly 200.

The adapter assembly 300 operates in a substantially similar manner to adapter assembly 100 described hereinabove. In addition, adapter assembly 300 is configured to permit rotation of an end effector, e.g., end effector 30 (FIG. 34) attached to adapter assembly 300 or attached to an extension assembly that is attached to adapter assembly 300 to be selectively rotated about longitudinal axis "x" (FIG. 36) during use.

Any of the components described herein may be fabricated from either metals, plastics, resins, composites or the like taking into consideration strength, durability, wearabil-

ity, weight, resistance to corrosion, ease of manufacturing, cost of manufacturing, and the like.

Persons skilled in the art will understand that the devices and methods specifically described herein and illustrated in the accompanying drawings are non-limiting exemplary embodiments. It is envisioned that the elements and features illustrated or described in connection with one exemplary embodiment may be combined with the elements and features of another without departing from the scope of the present disclosure. As well, one skilled in the art will appreciate further features and advantages of the disclosure based on the above-described embodiments. Accordingly, the disclosure is not to be limited by what has been particularly shown and described, except as indicated by the appended claims.

What is claimed is:

1. A surgical assembly for operably connecting an end effector to an electrosurgical instrument, the surgical assembly comprising:

an adapter assembly including,

a connector assembly;

a drive transfer assembly operably received through the connector assembly and including a first rotatable shaft; and

a first pusher assembly operably connected to the first rotatable shaft for converting rotational motion from the first rotatable shaft to longitudinal movement to perform a first function, the first pusher assembly including a first pusher member, and first and second pawl assemblies; and

an extension assembly operably connected to a distal end of the adapter assembly, the extension assembly including a flexible band assembly having first and second connector members, the first connector member being releasably connectable to the first pawl assembly of the first pusher assembly and the second connector member being releasably connectable to the second pawl assembly, wherein the first connector member is laterally spaced from the second connector member.

2. The surgical assembly of claim 1, further including a second pusher assembly, and a second rotatable shaft operably connected to the second pusher assembly for converting rotational motion from the second rotatable shaft to longitudinal movement to perform a second function.

3. The surgical assembly of claim 2, further including a drive member, and a third rotatable shaft operably connected to the drive member for transferring rotational motion from the third rotatable shaft to perform a third function.

4. The surgical assembly of claim 1, wherein the first pawl assembly includes a first plurality of pawl members, and the second pawl assembly includes a second plurality of pawl members.

5. The surgical assembly of claim 4, wherein each of the first and second connector members define an opening configured for selective receipt of a respective one of the first and second pawl assemblies.

6. The surgical assembly of claim 5, wherein the first plurality of pawl members includes a first protrusion selectively receivable within the opening of the first connector member, and the second plurality of pawl members includes a second protrusion selectively receivable within the opening of the second connector member.

## 19

7. The surgical assembly of claim 6, wherein each of the first and second protrusions includes a flat proximal facing surface and a slanted distal facing surface.

8. The surgical assembly of claim 4, wherein the first and second plurality of pawl members are pivotally secured to the first pusher member.

9. The surgical assembly of claim 4, wherein the first pusher member includes a first retainer for supporting the first plurality of pawl members, and a second retainer for supporting the second plurality of pawl members.

10. The surgical assembly of claim 9, wherein the first and second retainers each define a longitudinal slot for receiving the respective first and second plurality of pawl members.

11. The surgical assembly of claim 10, wherein the first plurality of pawl members are pivotally received within the longitudinal slot of the first retainer, and the second plurality of pawl members are pivotally received within the longitudinal slot of the second retainer.

12. The surgical assembly of claim 11, wherein each of the first and second plurality of pawl members are configured to flex radially inward.

13. The surgical assembly of claim 4, wherein the first and second plurality of pawl members each include a curved profile.

14. The surgical assembly of claim 4, wherein the first and second plurality of pawl members are each formed of a flexible material.

15. A surgical assembly for operably connecting an end effector to an electrosurgical instrument, the surgical assembly comprising:

## 20

an adapter assembly including,

a connector assembly;

a drive transfer assembly operably received through the connector assembly and including a first rotatable shaft; and

a first pusher assembly operably connected to the first rotatable shaft for converting rotational motion from the first rotatable shaft to longitudinal movement to perform a first function, the first pusher assembly including a first pusher member, and first and second pawl assemblies; and

an extension assembly operably connected to a distal end of the adapter assembly, the extension assembly including a flexible band assembly releasably connectable to the first and second pawl assemblies of the first pusher assembly.

16. The surgical assembly of claim 15, wherein the first pawl assembly includes a first plurality of pawl members, and the second pawl assembly includes a second plurality of pawl members.

17. The surgical assembly of claim 16, wherein the flexible band assembly includes first and second connector members, each of the first and second connector members defining an opening configured for selective receipt of a respective one of the first and second pawl assemblies.

18. The surgical assembly of claim 17, wherein the first plurality of pawl members includes a first protrusion selectively receivable within the opening of the first connector member, and the second plurality of pawl members includes a second protrusion selectively receivable within the opening of the second connector member.

\* \* \* \* \*