



US010952505B2

(12) **United States Patent**
Hammerslag et al.

(10) **Patent No.:** **US 10,952,505 B2**
(45) **Date of Patent:** **Mar. 23, 2021**

(54) **REEL BASED CLOSURE SYSTEM**

(71) Applicant: **Boa Technology Inc.**, Denver, CO (US)

(72) Inventors: **Gary Hammerslag**, Steamboat Springs, CO (US); **Michael Mayberry**, Denver, CO (US); **Mark Soderberg**, Conifer, CO (US)

(73) Assignee: **Boa Technology Inc.**, Denver, CO (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/517,271**

(22) Filed: **Jul. 19, 2019**

(65) **Prior Publication Data**

US 2020/0008533 A1 Jan. 9, 2020

Related U.S. Application Data

(63) Continuation of application No. 15/687,299, filed on Aug. 25, 2017, now Pat. No. 10,362,836, which is a (Continued)

(51) **Int. Cl.**

A43C 11/00 (2006.01)

A43C 11/16 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **A43C 11/165** (2013.01); **A43B 5/16** (2013.01); **A43B 5/1666** (2013.01); **A43C 1/00** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC **A43C 11/165**; **A43C 1/04**; **A43C 11/00**; **A43C 11/004**; **A43C 11/008**; **A43C 1/00**;

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

59,332 A 10/1866 White et al.

80,834 A 8/1868 Prussia

(Continued)

FOREIGN PATENT DOCUMENTS

CA 2112789 8/1994

CH 199766 11/1938

(Continued)

OTHER PUBLICATIONS

U.S. Appl. No. 09/956,601, filed Sep. 18, 2001, Hammerslag.

(Continued)


Primary Examiner — Robert Sandy

(74) *Attorney, Agent, or Firm* — Kilpatrick Townsend & Stockton, LLP

(57) **ABSTRACT**

Disclosed is a closure system used in combination in any of a variety of applications including clothing, for example as a footwear lacing system comprising a lace attached to a tightening mechanism. The lace extends through a series of guide members positioned along two opposing footwear closure portions. The lace and guides preferably have low friction surfaces to facilitate sliding of the lace along the guide members so that the lace evenly distributes tension across the footwear member. The tightening mechanism allows incremental adjustment of the tension of the lace. The closure system allows a user to quickly loosen the lace and inhibits unintentional and/or accidental loosening of the lace.

19 Claims, 52 Drawing Sheets



Related U.S. Application Data

continuation of application No. 14/228,075, filed on Mar. 27, 2014, now Pat. No. 9,743,714, which is a continuation of application No. 13/343,658, filed on Jan. 4, 2012, now abandoned, which is a continuation of application No. 11/842,009, filed on Aug. 20, 2007, now Pat. No. 8,091,182, which is a continuation of application No. 11/263,253, filed on Oct. 31, 2005, now abandoned.

(60) Provisional application No. 60/704,831, filed on Aug. 2, 2005, provisional application No. 60/623,341, filed on Oct. 29, 2004.

(51) **Int. Cl.**
A43C 1/04 (2006.01)
A43B 5/16 (2006.01)
A43C 1/00 (2006.01)

(52) **U.S. Cl.**
 CPC *A43C 1/003* (2013.01); *A43C 1/04* (2013.01); *A43C 11/00* (2013.01); *A43C 11/004* (2013.01); *A43C 11/008* (2013.01); *A43C 11/16* (2013.01); *Y10T 24/2183* (2015.01); *Y10T 24/375* (2015.01); *Y10T 24/3768* (2015.01)

(58) **Field of Classification Search**
 CPC *A43C 1/003*; *A43C 11/16*; *A43B 5/16*; *A43B 5/1666*; *Y10T 24/375*; *Y10T 24/3768*; *Y10T 24/2183*
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

117,530 A	8/1871	Foote
228,946 A	6/1880	Schulz
230,759 A	8/1880	Drummond
746,563 A	12/1903	McMahon
908,704 A	1/1909	Sprinkle
1,060,422 A	4/1913	Bowdish
1,062,511 A	5/1913	Short
1,090,438 A	3/1914	Worth et al.
1,170,472 A	2/1916	Barber
1,288,859 A	12/1918	Feller et al.
1,393,188 A	10/1921	Whiteman
1,469,661 A	2/1922	Migita
1,412,486 A	4/1922	Paine
1,416,203 A	5/1922	Hobson
1,429,657 A	9/1922	Trawinski
1,481,903 A	4/1923	Hart
1,466,673 A	9/1923	Solomon et al.
1,530,713 A	2/1924	Clark
1,995,243 A	6/1934	Clarke
2,088,851 A	8/1937	Gantenbein
2,109,751 A	3/1938	Matthias et al.
2,124,310 A	9/1938	Murr, Jr.
2,316,102 A	4/1943	Preston
2,539,026 A	1/1951	Mangold
2,611,940 A	9/1952	Cairns
2,673,381 A	3/1954	Dueker
2,907,086 A	10/1959	Ord
2,991,523 A	7/1961	Del Conte
3,035,319 A	5/1962	Wolff
3,112,545 A	12/1963	Williams
3,163,900 A	1/1965	Martin
3,169,325 A	2/1965	Fesl
3,197,155 A	7/1965	Chow
3,221,384 A	12/1965	Aufenacker
3,276,090 A	10/1966	Nigon
3,401,437 A	9/1968	Christpohersen
3,430,303 A	3/1969	Perrin et al.

3,491,465 A	1/1970	Martin
3,545,106 A	12/1970	Martin
3,618,232 A	11/1971	Shnuriwsky
3,668,791 A	6/1972	Salzman et al.
3,678,539 A	7/1972	Graup
3,703,775 A	11/1972	Gatti
3,729,779 A	5/1973	Porth
3,738,027 A	6/1973	Schoch
3,793,749 A	2/1974	Gertsch et al.
3,808,644 A	5/1974	Schoch
3,834,048 A	9/1974	Maurer
3,934,346 A	1/1976	Sasaki et al.
3,975,838 A	8/1976	Martin
4,130,949 A	12/1978	Seidel
4,142,307 A	3/1979	Martin
4,227,322 A	10/1980	Annovi
4,261,081 A	4/1981	Lott
4,267,622 A	5/1981	Burnett-Johnston
4,408,403 A	10/1983	Martin
4,433,456 A	2/1984	Baggio
4,463,761 A	8/1984	Pols et al.
4,480,395 A	11/1984	Schoch
4,551,932 A	11/1985	Schoch
4,555,830 A	12/1985	Petrini et al.
4,574,500 A	3/1986	Aldinio et al.
4,616,524 A	10/1986	Biodia
4,619,057 A	10/1986	Sartor et al.
4,620,378 A	11/1986	Sartor
4,631,839 A	12/1986	Bonetti et al.
4,631,840 A	12/1986	Gamm
4,633,599 A	1/1987	Morell et al.
4,654,985 A	4/1987	Chalmers
4,660,300 A	4/1987	Morell et al.
4,660,302 A	4/1987	Arieh et al.
4,680,878 A	7/1987	Pozzobon et al.
4,719,670 A	1/1988	Kurt
4,719,709 A	1/1988	Vaccari
4,719,710 A	1/1988	Pozzobon
4,722,477 A	2/1988	Floyd
4,741,115 A	5/1988	Pozzobon
4,748,726 A	6/1988	Schoch
4,760,653 A	8/1988	Baggio
4,780,969 A	11/1988	White, Jr.
4,787,124 A	11/1988	Pozzobon et al.
4,790,081 A	12/1988	Benoit et al.
4,796,829 A	1/1989	Pozzobon et al.
4,799,297 A	1/1989	Baggio et al.
4,802,291 A	2/1989	Sartor
4,811,503 A	3/1989	Iwama
4,826,098 A	5/1989	Pozzobon et al.
4,841,649 A	6/1989	Baggio et al.
4,856,207 A	8/1989	Datson
4,870,723 A	10/1989	Pozzobon et al.
4,870,761 A	10/1989	Tracy
4,884,760 A	12/1989	Baggio et al.
4,937,953 A	7/1990	Walkhoff
4,961,544 A	10/1990	Biodia
5,001,817 A	3/1991	De Bortoli et al.
5,016,327 A	5/1991	Klausner
5,042,177 A	8/1991	Schoch
5,062,225 A	11/1991	Gorza
5,065,480 A	11/1991	DeBortoli
5,065,481 A	11/1991	Walkhoff
5,117,567 A	6/1992	Berger
5,152,038 A	10/1992	Schoch
5,157,813 A	10/1992	Carroll
5,158,428 A	10/1992	Gessner et al.
5,177,882 A	1/1993	Berger
5,181,331 A	1/1993	Berger
5,184,378 A	2/1993	Batra
D333,552 S	3/1993	Berger et al.
5,249,377 A	10/1993	Walkhoff
5,259,094 A	11/1993	Zepeda
5,315,741 A	5/1994	Debberke
5,319,868 A	6/1994	Hallenbeck
5,325,613 A	7/1994	Sussmann
5,327,662 A	7/1994	Hallenbeck
5,335,401 A	8/1994	Hanson
5,341,583 A	8/1994	Hallenbeck

(56)

References Cited

U.S. PATENT DOCUMENTS

5,345,697 A 9/1994 Quellais
 5,355,596 A 10/1994 Sussmann
 5,357,654 A 10/1994 Hsing-Chi
 5,381,609 A 1/1995 Hieblinger
 5,425,161 A 6/1995 Schoch
 5,425,185 A 6/1995 Gansler
 5,430,960 A 7/1995 Richardson
 5,433,648 A 7/1995 Frydman
 5,463,822 A 11/1995 Miller
 5,477,593 A 12/1995 Leick
 5,502,902 A 4/1996 Sussmann
 5,511,325 A 4/1996 Hieblinger
 5,535,531 A 7/1996 Karabed et al.
 5,537,763 A 7/1996 Donnadiou et al.
 5,557,864 A 9/1996 Marks
 5,566,474 A 10/1996 Leick et al.
 5,596,820 A 1/1997 Edauw et al.
 5,599,000 A 2/1997 Bennett
 5,599,288 A 2/1997 Shirley et al.
 5,600,874 A 2/1997 Jungkind
 5,606,778 A 3/1997 Jungkind
 5,638,588 A 6/1997 Jungkind
 5,640,785 A 6/1997 Egelja
 5,647,104 A 7/1997 James
 5,651,198 A 7/1997 Sussmann
 5,669,116 A 9/1997 Jungkind
 5,718,021 A 2/1998 Tatum
 5,718,065 A 2/1998 Locker
 5,732,483 A 3/1998 Cagliari
 5,736,696 A 4/1998 Del Rosso
 5,737,854 A 4/1998 Sussmann
 5,755,044 A 5/1998 Veylupek
 5,761,777 A 6/1998 Leick
 5,784,809 A 7/1998 McDonald
 5,791,021 A 8/1998 James
 5,819,378 A 10/1998 Doyle
 5,833,640 A 11/1998 Vazquez, Jr. et al.
 5,934,599 A 8/1999 Hammerslag
 5,956,823 A 9/1999 Borel
 6,029,323 A 2/2000 Dickie et al.
 6,038,791 A 3/2000 Cornelius et al.
 6,052,921 A 4/2000 Oreck
 6,070,886 A 6/2000 Cornelius et al.
 6,070,887 A 6/2000 Cornelius et al.
 6,073,370 A 6/2000 Okajima
 6,102,412 A 8/2000 Staffaroni
 6,119,318 A 9/2000 Maurer
 6,128,836 A 10/2000 Barret
 6,148,489 A 11/2000 Dickie et al.
 6,202,953 B1 3/2001 Hammerslag
 6,256,798 B1 7/2001 Egolf et al.
 6,267,390 B1 7/2001 Maravetz et al.
 6,289,558 B1 9/2001 Hammerslag
 6,416,074 B1 7/2002 Maravetz et al.
 6,467,195 B2 10/2002 Pierre et al.
 6,477,793 B1 11/2002 Pruitt et al.
 6,543,159 B1 4/2003 Carpenter et al.
 6,568,103 B2 5/2003 Durocher
 6,694,643 B1 2/2004 Hsu
 6,708,376 B1 3/2004 Landry
 6,711,787 B2 3/2004 Jungkind et al.
 6,757,991 B2 7/2004 Sussmann
 6,775,928 B2 8/2004 Grande et al.
 6,802,439 B2 10/2004 Azam et al.
 6,877,256 B2 4/2005 Martin et al.
 6,922,917 B2 8/2005 Kems et al.
 6,938,913 B2 9/2005 Elkington
 6,941,683 B2 9/2005 Freed
 6,945,543 B2 9/2005 De Bortoli et al.
 6,976,972 B2 12/2005 Bradshaw
 6,993,859 B2 2/2006 Martin et al.
 7,076,843 B2 7/2006 Sakabayashi
 7,082,701 B2 8/2006 Dalgaard et al.
 7,134,224 B2 11/2006 Elkington et al.
 7,281,341 B2 10/2007 Reagan et al.

7,293,373 B2 11/2007 Reagan et al.
 7,331,126 B2 2/2008 Johnson
 7,367,522 B2 5/2008 Chen
 7,386,947 B2 6/2008 Martin et al.
 7,490,458 B2 2/2009 Ford
 7,584,528 B2 9/2009 Hu
 7,591,050 B2 9/2009 Hammerslag
 7,597,675 B2 10/2009 Ingimundarson et al.
 7,600,660 B2 10/2009 Kasper et al.
 7,617,573 B2 11/2009 Chen
 7,694,354 B2 4/2010 Philpott et al.
 7,908,769 B2 3/2011 Pellegrini
 7,950,112 B2 5/2011 Hammerslag et al.
 7,954,204 B2 6/2011 Hammerslag et al.
 7,992,261 B2 8/2011 Hammerslag et al.
 8,056,150 B2 11/2011 Stokes et al.
 8,091,182 B2 1/2012 Hammerslag et al.
 8,245,371 B2 8/2012 Chen
 8,277,401 B2 10/2012 Hammerslag et al.
 8,308,098 B2 11/2012 Chen
 8,713,820 B2 5/2014 Kerns et al.
 8,984,719 B2 3/2015 Soderberg et al.
 9,101,181 B2 8/2015 Soderberg et al.
 9,179,729 B2 11/2015 Cotterman et al.
 9,743,714 B2 8/2017 Hammerslag et al.
 10,362,836 B2 7/2019 Hammerslag et al.
 2002/0095750 A1 7/2002 Hammerslag
 2002/0178548 A1 12/2002 Freed
 2003/0177662 A1 9/2003 Elkington et al.
 2003/0204938 A1 11/2003 Hammerslag
 2005/0054962 A1 3/2005 Bradshaw
 2005/0081403 A1 4/2005 Mathieu
 2005/0087115 A1 4/2005 Martin
 2005/0097780 A1 5/2005 Pellegrini
 2005/0098673 A1 5/2005 Huang
 2005/0102861 A1 5/2005 Martin
 2005/0126043 A1 6/2005 Reagan et al.
 2005/0198866 A1 9/2005 Wiper et al.
 2006/0156517 A1 7/2006 Hammerslag et al.
 2006/0185193 A1 8/2006 Pellegrini
 2007/0169378 A1 7/2007 Soderberg et al.
 2008/0060167 A1 3/2008 Hammerslag et al.
 2008/0060168 A1 3/2008 Hammerslag et al.
 2008/0066272 A1 3/2008 Hammerslag et al.
 2008/0066345 A1 3/2008 Hammerslag et al.
 2008/0066346 A1 3/2008 Hammerslag et al.
 2008/0083135 A1 4/2008 Hammerslag et al.
 2009/0172928 A1 7/2009 Messmer et al.
 2009/0184189 A1 7/2009 Soderberg et al.
 2010/0101061 A1 4/2010 Ha
 2010/0139057 A1 6/2010 Soderberg et al.
 2010/0299959 A1 12/2010 Hammerslag et al.
 2011/0167543 A1 7/2011 Kovacevich et al.
 2011/0225843 A1 9/2011 Kerns et al.
 2011/0266384 A1 11/2011 Goodman et al.
 2012/0000091 A1 1/2012 Cotterman et al.
 2012/0004587 A1 1/2012 Nickel et al.
 2012/0246974 A1 10/2012 Hammerslag et al.
 2013/0012856 A1 10/2013 Hammerslag et al.
 2013/0269219 A1 10/2013 Burns et al.
 2013/0277485 A1 10/2013 Soderberg et al.
 2016/0206047 A1 7/2016 Hammerslag et al.

FOREIGN PATENT DOCUMENTS

CH 204 834 A 8/1939
 DE 641976 2/1937
 DE 23 41 658 3/1974
 DE 29 00 077 A1 7/1980
 DE 31 01 952 A1 9/1982
 DE 3635 168 5/1987
 DE 38 13 470 11/1989
 DE 3822113 1/1990
 DE 2114387 1/1994
 DE 42 30 652 3/1994
 DE 42 30 653 3/1994
 DE 43 02 401 A1 8/1994
 DE 43 05 671 A1 9/1994
 DE 9315776 2/1995

(56)

References Cited

FOREIGN PATENT DOCUMENTS

DE	29503552.8	4/1995
DE	196 24 553	1/1998
DE	19945045 A1	9/1999
EP	0 123 050	2/1984
EP	0 201 051	11/1986
EP	0 099 504	1/1987
EP	0 255 869	7/1987
EP	0 155 596	1/1988
EP	0 393 380	3/1990
EP	474 708	3/1992
EP	0 651 954 A1	4/1993
EP	0 589 232 A1	3/1994
EP	0 679 346	11/1995
EP	0 693 260 B1	1/1996
EP	0 734 662 A1	2/1996
EP	0 858 821	8/1998
EP	0 923 965	6/1999
EP	0 937 467	8/1999
EP	0 848 917 81	4/2000
EP	1 219 195	2/2001
EP	1 236 412 A	2/2002
FR	1 404 799	7/1964
FR	2 019 991 A	10/1969
FR	2399811	9/1979
FR	2565795	6/1984
FR	2 598 292 A1	11/1987
FR	2 726 440 A1	5/1996
FR	2 770 379 A4	5/1997
FR	2 814 919 A1	4/2002
GB	189911673	7/1899
GB	216400	8/1923
JP	51-121375	10/1976
JP	53-124987	3/1977
JP	54-108125	2/1978
JP	6-284906	11/1994
JP	3031760	9/1996
JP	3030988	11/1996
JP	10-199366	7/1998
JP	2004-016732	1/2004
JP	2004-041666	2/2004
WO	95/11602	5/1995
WO	1995/03720	9/1995

WO	98/37782	9/1998
WO	99/09850	3/1999
WO	99/15043	4/1999
WO	00/53045	9/2000
WO	00/76603	12/2000
WO	2000/76337 A1	12/2000
WO	01/08525	2/2001
WO	01/15559	3/2001
WO	02/051511	7/2002
WO	2004/093569	11/2004
WO	2007/016983	2/2007

OTHER PUBLICATIONS

ASOLO® Boot Brochure Catalog upon information and belief date is as early as Aug. 22, 1997, 12 pages.
 International Search Report and Written Opinion in PCT/US2004/019032, dated Dec. 23, 2004, all pages.
 International Preliminary Report on Patentability for PCT/US2004/019032 dated Dec. 13, 2005, all pages.
 International Search Report and Written Opinion in PCT/US2005/039273, dated Nov. 20, 2007, all pages.
 International Preliminary Report on Patentability for PCT/US2005/039273 dated Dec. 17, 2007, all pages.
 International Search Report in PCT/US1998/16314 dated Oct. 13, 1998, all pages.
 International Preliminary Examination Report for PCT/US2000/19440 dated Oct. 15, 2001, all pages.
 Supplementary Partial European Search Report for EP 05819488, dated Feb. 18, 2011, 1 page.
 International Search Report and Written Opinion for PCT/US2007/000317 dated Jun. 13, 2007, all pages.
 Written Opinion for PCT/US00/19440 dated Jun. 25, 2001, 5 pages.
 U.S. Appl. No. 60/623,341, filed Oct. 29, 2004, Inventor: Hammerslag, expired.
 U.S. Appl. No. 60/704,831, filed Aug. 2, 2005, Inventor: Hammerslag, expired.
 U.S. Appl. No. 61/022,045, filed Jan. 18, 2008, Inventors: Soderberg et al., expired.
 U.S. Appl. No. 15/687,299, filed Aug. 25, 2017.
 U.S. Appl. No. 14/228,075, filed Mar. 27, 2014.
 U.S. Appl. No. 13/343,658, filed Jan. 4, 2012.
 U.S. Appl. No. 11/842,009, filed Aug. 20, 2007.
 U.S. Appl. No. 11/263,253, filed Oct. 31, 2005.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29A




FIG. 29C

FIG. 29B







FIG. 29D






FIG. 31





FIG. 32






FIG. 34




FIG. 36

FIG. 35




FIG. 37C

FIG. 37B

FIG. 37A




FIG. 38B




FIG. 38A




FIG. 39




FIG. 40A




FIG. 40B

FIG. 40C




FIG. 41






FIG. 42A






FIG. 43A




FIG. 43B




FIG. 44A




FIG. 44B




FIG. 45A

FIG. 45B




FIG. 46




FIG. 47A




FIG. 47B




FIG. 47C




FIG. 48B




FIG. 48A




FIG. 49A




FIG. 49B




FIG. 50A




FIG. 50B




FIG. 51




FIG. 52B




FIG. 52A

1400

1400




FIG. 53

FIG. 54A





FIG. 54B

FIG. 54E




FIG. 54C




FIG. 54D




FIG. 54F




FIG. 54G




FIG. 54J

FIG. 54H





FIG. 54I




FIG. 54K

FIG. 55A





FIG. 55E




FIG. 55B




FIG. 55C




FIG. 55F




FIG. 55D

FIG. 56A




FIG. 56E





FIG. 56B




FIG. 56C




FIG. 56F




FIG. 56D




FIG. 57B





FIG. 57A





FIG. 57C

FIG. 57F





FIG. 57D




FIG. 58




FIG. 59A

FIG. 59B

REEL BASED CLOSURE SYSTEM**CROSS-REFERENCE TO RELATED APPLICATIONS**

This application is a continuation of U.S. patent application Ser. No. 15/687,299, filed Aug. 25, 2017, which is a continuation of U.S. patent application Ser. No. 14/228,075, filed Mar. 27, 2014, now U.S. Pat. No. 9,743,714, which is a continuation of U.S. patent application Ser. No. 13/343,658, filed Jan. 4, 2012, which is a continuation of U.S. patent application Ser. No. 11/842,009, filed Aug. 20, 2007, now U.S. Pat. No. 8,091,182, which is a continuation of U.S. patent application Ser. No. 11/263,253, filed Oct. 31, 2005, which claims the benefit of U.S. Provisional Patent Application No. 60/623,341, filed Oct. 29, 2004, and U.S. Provisional Patent Application No. 60/704,831, filed Aug. 2, 2005.

INCORPORATE BY REFERENCE

This application hereby incorporates by reference U.S. patent application Ser. No. 13/343,658, filed Jan. 4, 2012; U.S. Pat. No. 8,091,182, issued Jan. 10, 2012; U.S. patent application Ser. No. 11/263,253, filed Oct. 31, 2005; U.S. Pat. No. 7,591,050, issued Sep. 22, 2009; U.S. patent application Ser. No. 09/993,296 filed Nov. 14, 2001; U.S. patent application Ser. No. 09/956,601 filed on Sep. 18, 2001; U.S. Pat. No. 6,289,558, issued Sep. 18, 2001; U.S. Pat. No. 6,202,953, issued Mar. 20, 2001; U.S. Pat. No. 5,934,599, issued Aug. 10, 1999; U.S. Provisional Patent Application No. 60/623,341, filed Oct. 29, 2004; and U.S. Provisional Patent Application No. 60/704,831, filed Aug. 2, 2005, in their entireties.

BACKGROUND OF THE INVENTION**Field of the Invention**

The present invention relates to closure systems used in combination in any of a variety of applications including clothing, for example in a low-friction lacing system for footwear that provides equilibrated tightening pressure across a wearer's foot.

Description of the Related Art

There currently exist a number of mechanisms and methods for tightening a shoe or boot around a wearer's foot. A traditional method comprises threading a lace in a zig-zag pattern through eyelets that run in two parallel rows attached to opposite sides of the shoe. The shoe is tightened by first tensioning opposite ends of the threaded lace to pull the two rows of eyelets towards the midline of the foot and then tying the ends in a knot to maintain the tension. A number of drawbacks are associated with this type of lacing system. First, laces do not adequately distribute the tightening force along the length of the threaded zone, due to friction between the lace and the eyelets, so that portions of the lace are slack and other portions are in tension. Consequently, the higher tensioned portions of the shoe are tighter around certain sections of the foot, particularly the ankle portions which are closer to the lace ends. This is uncomfortable and can adversely affect performance in some sports.

Another drawback associated with conventional laces is that it is often difficult to untighten or redistribute tension on the lace, as the wearer must loosen the lace from each of the

many eyelets through which the laces are threaded. The lace is not easily released by simply untightening the knot. The friction between the lace and the eyelets often maintains the toe portions and sometimes much of the foot in tension even when the knot is released. Consequently, the user must often loosen the lace individually from each of the eyelets. This is especially tedious if the number of eyelets is high, such as in ice-skating boots or other specialized high performance footwear.

Another tightening mechanism comprises buckles which clamp together to tighten the shoe around the wearer's foot. Typically, three to four or more buckles are positioned over the upper portion of the shoe. The buckles may be quickly clamped together and drawn apart to tighten and loosen the shoe around the wearer's foot. Although buckles may be easily and quickly tightened and untightened, they also have certain drawbacks. Specifically, buckles isolate the closure pressure across three or four points along the wearer's foot corresponding to the locations of the buckles. This is undesirable in many circumstances, such as for the use of sport boots where the wearer desires a force line that is evenly distributed along the length of the foot. Another drawback of buckles is that they are typically only useful for hard plastic or other rigid material boots. Buckles are not as practical for use with softer boots, such as ice skates or snowboard boots.

There is therefore a need for a tightening system for footwear that does not suffer from the aforementioned drawbacks. Such a system should automatically distribute lateral tightening forces along the length of the wearer's ankle and foot. The tightness of the shoe should desirably be easy to loosen and incrementally adjust. The tightening system should close tightly and should not loosen up with continued use.

SUMMARY OF THE INVENTION

There is provided in accordance with one aspect of the present invention, a footwear lacing system. The system comprises a footwear member including first and second opposing sides configured to fit around a foot. A plurality of lace guide members are positioned on the opposing sides. A lace is guided by the guide members, the lace being rotationally connected to a spool that is rotatable in a winding direction and an unwinding direction. A tightening mechanism is attached to the footwear member, and coupled to the spool, the tightening mechanism including a control for winding the lace around the spool to place tension on the lace thereby pulling the opposing sides towards each other. A safety device is moveable between a secure position in which the spool is unable to rotate in an unwinding direction, and a releasing position in which the spool is free to rotate in an unwinding direction.

In one embodiment, the lace is slideably positioned around the guide members to provide a dynamic fit in response to movement of the foot within the footwear. The guide members may have a substantially C-shaped cross section.

Additionally, the tightening mechanism is a rotatable reel that is configured to receive the lace. In accordance with one embodiment, a knob rotates the spool and thereby winds the lace about the spool. In some embodiments, rotating the knob in an unwinding direction releases the spool and allows the lace to unwind. A safety device can be attached, such as a lever, that selectively allows the knob to rotate in an unwinding direction to release the spool. Alternatively, the safety device can be a rotatable release that is rotated separately from the knob to release the spool.

In certain embodiments, the footwear lacing system is attached to footwear having a first opposing side configured to extend from one side of the shoe, across the upper midline of the shoe, and to the opposing side of the shoe. As such, the reel can be mounted to the first opposing side.

In one embodiment, the lace is formed of a polymeric fiber.

According to another aspect of the footwear lacing system, a closure system for footwear having an upper with a lateral side and a medial side, the closure system comprising at least a first lace guide attached to the lateral side of the upper, at least a second lace guide attached to the medial side of the upper, and each of the first and second lace guides comprising a lace pathway, a lace slideably extending along the lace pathway of each of the first and second lace guides. Additionally, a tightening reel of the footwear for retracting the lace and thereby advancing the first lace guide towards the second lace guide to tighten the footwear is positioned on the footwear, and a lock is moveable between a coupled position and an uncoupled position wherein the lock allows the reel to be only rotatable in a forward direction when the lock is engaged, and allows the reel to be rotatable in a reverse direction when the lock is disengaged.

An embodiment also includes a closed loop lace wherein the lace is permanently mounted in the reel. Accordingly, each of the at least first and second lace guides comprise an open channel to receive the closed loop lace.

According to another embodiment of the footwear lacing system, a spool and lace unit is provided for use in conjunction with a footwear lacing system comprises a spool having ratchet teeth disposed on its periphery configured to interact with a pawl for inhibiting relative rotation of the spool in at least one direction, and a lace securely attached to the spool. Optionally, the lace can be formed of a lubricious polymer having a relatively low elasticity and high tensile strength. Alternatively, the lace can be formed of a multi-strand polymeric cable. Alternatively, the lace can be formed of a multi-strand metallic cable, preferably with a lubricious polymer casing.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a side view of a sport boot including a lacing system configured in accordance with the present invention;

FIG. 2 is a front view of the sport boot of FIG. 1;

FIG. 3 is a perspective schematic view of the lacing system of the sport boot of FIG. 1;

FIG. 4 is a top plan view of the multi-piece guide member;

FIG. 5 is a side view of the sport boot including an ankle support strap;

FIG. 6 is a front view of the sport boot including a central lace guide member disposed adjacent the tongue of the boot;

FIG. 7 is a schematic front view of the instep portion of the boot with a plurality of lace locking members disposed along the lace pathway;

FIG. 8 is a front view of the instep portion of the boot;

FIG. 9 is an enlarged view of the region within line 9 of FIG. 8;

FIG. 10 is a top plan view of an alternative embodiment of a lace guide;

FIG. 11 is a side view of the lace guide of FIG. 10;

FIG. 12 is a top view of the lace guide of FIG. 10 mounted in a boot flap;

FIG. 13 is a cross-sectional view of the lace guide and boot flap along line 13-13 of FIG. 12;

FIG. 14 is a side view of a second embodiment of the tightening mechanism.

FIG. 15 is a top plan view showing one embodiment of the footwear lacing system of the present invention attached to a shoe that is shown in phantom.

FIG. 16 is a side elevational view of a shoe having another embodiment of the footwear lacing system of the present invention attached thereto.

FIG. 17 is a side elevational view of a shoe having yet another embodiment of the footwear lacing system of the present invention attached thereto.

FIG. 18 is a perspective view of an embodiment of a lacing system having a protective element.

FIG. 19 is a side elevational view of the lacing system of FIG. 18 showing the protective element.

FIG. 20 illustrates a perspective view of an embodiment of a lacing system having an alternative protective element.

FIG. 21 is an exploded perspective view of an embodiment of a self-winding tightening mechanism.

FIG. 22 is a top plan view of the mechanism of FIG. 21.

FIG. 23 is a section view of the mechanism of FIG. 22, taken through line A-A.

FIG. 24 is a top plan view of one embodiment of a portion of a self-winding tightening mechanism.

FIG. 25 is a section view of the mechanism of FIG. 24, taken through line B-B.

FIG. 26 is a perspective view of one embodiment of a portion of a self-winding tightening mechanism.

FIG. 27 is a perspective view of an embodiment of a spring assembly for use in some embodiments of a self-winding tightening mechanism.

FIG. 28 is a schematic plan view illustration of one embodiment of a multi-zone lacing system.

FIG. 29A-D are perspective, end elevation, top plan and side elevation views of one embodiment of a double-deck lace guide for use in embodiments of a multi-zone lacing system.

FIG. 30A-D are perspective, end elevation, top plan and side elevation views of one embodiment of a double-deck pass-through lace guide for use in embodiments of a multi-zone lacing system.

FIG. 31 is an exploded bottom perspective view of one embodiment of a vamp structure.

FIG. 32 is an exploded top perspective view of one embodiment of a vamp structure.

FIG. 33 is a detail view of an embodiment of a tightening mechanism for use in a vamp structure.

FIG. 34 is a side elevation view of one embodiment of an assembled vamp.

FIG. 35 is a perspective view of a lace guide comprising a slot for use in some embodiments of a lacing system.

FIG. 36 is a perspective view of a lace guide comprising a hook for use in some embodiments of a lacing system.

FIGS. 37A-C are schematic illustrations of embodiments of a lacing system configured to double-up laces in desired sections.

FIGS. 38A and 38B are side elevation views of one embodiment of a component of a lacing system.

FIG. 39 is an exploded top perspective view of one embodiment of a tightening mechanism.

FIGS. 40A through 40C are various views of one component of a tightening mechanism.

FIG. 41 is a top perspective view of one component of a tightening mechanism.

FIGS. 42A through 42E are various views of one component of a tightening mechanism.

FIGS. 43A and 43B are various views of one component of a tightening mechanism.

FIGS. 44A and 44B are top views of one embodiment of a tightening mechanism, shown engaged in FIG. 44A and disengaged in FIG. 44B.

FIGS. 45A and 45B are cross sectional side views of one embodiment of a tightening mechanism.

FIG. 46 is a cross sectional top perspective view of one embodiment of a tightening mechanism.

FIGS. 47A through 47C are various views of one embodiment of a lacing system mounted to an article of footwear.

FIGS. 48A and 48B are side elevation views of one embodiment of a tightening mechanism.

FIGS. 49A and 49B are front and back perspective views of one component of a tightening mechanism.

FIGS. 50A and 50B are various views of one embodiment of a lacing system mounted to an article of footwear.

FIG. 51 is a top perspective view of a component of a lacing system.

FIGS. 52A and 52B are front and perspective views, respectively, of one embodiment of a tightening mechanism.

FIG. 53 is an exploded top perspective view of one embodiment of a tightening mechanism.

FIGS. 54A through 54K are various views of one element that may be included in an embodiment of a tightening mechanism.

FIGS. 55A through 55F are various views of an assembled component of an embodiment of a tightening mechanism.

FIGS. 56A through 56F are various views of an assembled component of an embodiment of a tightening mechanism.

FIGS. 57A and 57F are various views of one component of an embodiment of a tightening mechanism.

FIG. 58 is a bottom perspective exploded view of one component of an embodiment of a tightening mechanism.

FIGS. 59A and 59B are cross sectional side views of a component of an embodiment of a tightening mechanism.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

Referring to FIG. 1, there is disclosed one embodiment of a sport boot 20 prepared in accordance with the present invention. The sport boot 20 generally comprises an ice skating or other action sport boot which is tightened around a wearer's foot using a lacing system 22. The lacing system 22 includes a lace 23 (FIG. 2) that is threaded through the boot 20 and attached at opposite ends to a tightening mechanism 25, as described in detail below. As used herein, the terms lace and cable have the same meaning unless specified otherwise. The lace 23 is a low friction lace that slides easily through the boot 20 and automatically equilibrates tightening of the boot 20 over the length of the lacing zone, which generally extends along the ankle and foot. Although the present invention will be described with reference to an ice skating boot, it is to be understood that the principles discussed herein are readily applicable to any of a wide variety of footwear, and are particularly applicable to sports shoes or boots suitable for snow boarding, roller skating, skiing and the like.

The boot 20 includes an upper 24 comprising a toe portion 26, a heel portion 28, and an ankle portion 29 that surrounds the wearer's ankle. An instep portion 30 of the upper 24 is interposed between the toe portion 26 and the ankle portion 29. The instep portion 30 is configured to fit around the upper part of the arch of the medial side of the wearer's foot between the ankle and the toes. A blade 31 (shown in phantom lines) extends downward from the bottom of the boot 20 in an ice-skating embodiment.

FIG. 2 is a front elevational view of the boot 20. As shown, the top of the boot 20 generally comprises two opposed closure edges or flaps 32 and 34 that partially cover a tongue 36. Generally, the lace 23 may be tensioned to draw the flaps 32 and 34 toward each other and tighten the boot 20 around the foot, as described in detail below. Although the inner edges of the flaps 32 and 34 are shown separated by a distance, it is understood that the flaps 32 and 34 could also be sized to overlap each other when the boot 20 is tightened, such as is known with ski footwear. Thus, references herein to drawing opposing sides of footwear towards each other refers to the portion of the footwear on the sides of the foot. This reference is thus generic to footwear in which opposing edges remain spaced apart even when tight (e.g. tennis shoes) and footwear in which opposing edges may overlap when tight (e.g. certain snow skiing boots). In both, tightening is accomplished by drawing opposing sides of the footwear towards each other.

Referring to FIG. 2, the tongue 36 extends rearwardly from the toe portion 26 toward the ankle portion 29 of the boot 20. Preferably, the tongue 36 is provided with a low friction top surface 37 to facilitate sliding of the flaps 32 and 34 and lace 23 over the surface of the tongue 32 when the lace 23 is tightened. The low friction surface 37 may be formed integrally with the tongue 32 or applied thereto such as by adhesives, heat bonding, stitching or the like. In one embodiment, the surface 37 is formed by adhering a flexible layer of nylon or polytetrafluoroethylene to the top surface of the tongue 36. The tongue 36 is preferably manufactured of a soft material, such as leather.

The upper 24 may be manufactured from any from a wide variety of materials known to those skilled in the art. In the case of a snow board boot, the upper 24 is preferably manufactured from a soft leather material that conforms to the shape of the wearer's foot. For other types of boots or shoes, the upper 24 may be manufactured of a hard or soft plastic. It is also contemplated that the upper 24 could be manufactured from any of a variety of other known materials.

As shown in FIG. 2, the lace 23 is threaded in a crossing pattern along the midline of the foot between two generally parallel rows of side retaining members 40 located on the flaps 32 and 34. In the illustrated embodiment, the side retaining members 40 each consist of a strip of material looped around the top and bottom edges of the flaps 32 and 34 so as to define a space in which guides 50 are positioned. The lace 23 slides through the guides 50 during tightening and untightening of the lace 23, as described more fully below. In the illustrated embodiment, there are three side retaining members 40 on each flap 32, 34 although the number of retaining members 40 may vary. In some embodiments, four, five or six or more retaining members 40 may be desirable on each side of the boot.

In certain boot designs, it may be possible during the tightening process for an opposing pair of lace guides to "bottom out" and come in contact with each other before that portion of the boot is suitably tightened. Further tightening of the system will not produce further tightening at that point. Rather, other portions of the boot which may already be sized appropriately would continue to tighten. In the embodiment illustrated in FIG. 2, the side retaining members 40 each consist of a strip of material looped around the guides 50. Additional adjustability may be achieved by providing a releasable attachment between the side retaining members 40 and the corresponding flap 32 or 34 of the shoe. In this manner, the side retaining member 40 may be moved

laterally away from the midline of the foot to increase the distance between opposing lace guides.

One embodiment of the adjustable side retaining member **40** may be readily constructed, that will appear similar to the structure disclosed in FIG. 2. In the adjustable embodiment, a first end of the strip of material is attached to the corresponding flap **32** or **34** using conventional means such as rivets, stitching, adhesives, or others known in the art. The strip of material loops around the guide **50**, and is folded back over the outside of the corresponding flap **32** or **34** as illustrated. Rather than stitching the top end of the strip of material to the flap, the corresponding surfaces between the strip of material and the flap may be provided with a releasable engagement structure such as hook and loop structures (e.g., Velcro®), or other releasable engagement locks or clamps which permits lateral-medial adjustability of the position of the guide **50** with respect to the edge of the corresponding flap **32** or **34**.

The guides **50** may be attached to the flaps **32** and **34** or to other spaced apart portions of the shoe through any of a variety of manners, as will be appreciated by those of skill in the art in view of the disclosure herein. For example, the retaining members **40** can be deleted and the guide **50** sewn directly onto the surface of the flap **32** or **34** or opposing sides of the upper. Stitching the guide **50** directly to the flap **32** or **34** may advantageously permit optimal control over the force distribution along the length of the guide **50**. For example, when the lace **23** is under relatively high levels of tension, the guide **50** may tend to want to bend and to possibly even kink near the curved transition in between longitudinal portion **51** and transverse portion **53** as will be discussed. Bending of the guide member under tension may increase friction between the guide member and the lace **23**, and, severe bending or kinking of the guide member **50** may undesirably interfere with the intended operation of the lacing system. Thus, the attachment mechanism for attaching the guide member **50** to the shoe preferably provides sufficient support of the guide member to resist bending and/or kinking. Sufficient support is particularly desirable on the inside radius of any curved portions particularly near the ends of the guide member **50**.

As shown in FIGS. 1 and 2, the lace **23** also extends around the ankle portion **29** through a pair of upper retaining members **44a** and **44b** located on the ankle portion **29**. The upper retaining members **44a** and **44b** each comprise a strip of material having a partially raised central portion that defines a space between the retaining members **44** and the upper **24**. An upper guide member **52** extends through each of the spaces for guiding the lace **23** around either side of the ankle portion **29** to the tightening mechanism **25**.

FIG. 3 is a schematic perspective view of the lacing system **22** of the boot **20**. As shown, each of the side and top guide members **50** and **52**, has a tube-like configuration having a central lumen **54**. Each lumen **54** has an inside diameter that is larger than the outside diameter of the lace **23** to facilitate sliding of the lace **23** through the side and top guide members **50**, **52** and prevent binding of the lace **23** during tightening and untightening. In one embodiment, the inside diameter of the lumen is approximately 0.040 inches, to cooperate with a lace having an outside diameter of about 0.027". However, it will be appreciated that the diameter of the lumen **54** can be varied to fit specific desired lace dimensions and other design considerations. The wall thickness and composition of the guides **50**, **52** may be varied to take into account the physical requirements imposed by particular shoe designs.

Thus, although the guides **50** are illustrated as relatively thin walled tubular structures, any of a variety of guide structures may be utilized as will be apparent to those of skill in the art in view of the disclosure herein. For example, either permanent (stitched, glued, etc.) or user removable (Velcro, etc.) flaps **40** may be utilized to hold down any of a variety of guide structures. In one embodiment, the guide **50** is a molded block having a lumen extending there-through. Modifications of the forgoing may also be accomplished, such as by extending the length of the lace pathway in a structure such as that illustrated in FIG. 4, such that the overall part has a shallow "U" shaped configuration which allows it to be conveniently retained by the retention structure **40**. Providing a guide member **50** having increased structural integrity over that which would be achieved by the thin tube illustrated in FIG. 2 may be advantageous in embodiments of the invention where the opposing guides **50** may be tightened sufficiently to "bottom out" against the opposing corresponding guide, as will be apparent to those of skill in the art in view of the disclosure herein. Solid and relatively harder lace guides as described above may be utilized throughout the boot, but may be particularly useful in the lower (e.g. toe) portion of the boot.

In general, each of the guide members **50** and **52** defines a pair of openings **49** that communicate with opposite ends of the lumen **54**. The openings **49** function as inlets/outlets for the lace **23**. The openings desirably are at least as wide as the cross-section of the lumen **54**.

As may be best seen in FIG. 3, each top guide **52** has an end **55** which is spaced apart from a corresponding side guide **50** on the opposing side of the footwear, with the lace **23** extending therebetween. As the system is tightened, the spacing distance will be reduced. For some products, the wearer may prefer to tighten the toe or foot portion more than the ankle. This can be conveniently accomplished by limiting the ability of the side guide **50** and top guide **52** to move towards each other beyond a preselected minimum distance during the tightening process. For this purpose, a selection of spacers having an assortment of lengths may be provided with each system. The spacers may be snapped over the section of lace **23** between a corresponding end **55** of top guide **52** and side guide **50**. When the ankle portion of the boot is sufficiently tight, yet the wearer would like to additionally tighten the toe or foot portion of the boot, a spacer having the appropriate length may be positioned on the lace **23** in-between the top guide **52** and side guide **50**. Further tightening of the system will thus not be able to draw the top guide **52** and corresponding side guide **50** any closer together.

The stop may be constructed in any of a variety of ways, such that it may be removably positioned between the top guide **52** and side guide **50** to limit relative tightening movement. In one embodiment, the stop comprises a tubular sleeve having an axial slot extending through the wall, along the length thereof. The tubular sleeve may be positioned on the boot by advancing the slot over the lace **23**, as will be apparent to those of skill in the art. A selection of lengths may be provided, such as 1/2 inch, 1 inch, 1 1/2 inch, and every half inch increment, on up to 3 or 4 inches or more, depending upon the position of the reel on the boot and other design features of a particular embodiment of the boot. Increments of 1/4 inch may also be utilized, if desired.

FIGS. 30-33 illustrate an embodiment of a dynamic spacer configured to allow a user to selectively determine an amount of spacing between portions of a footwear item. The structure of FIGS. 30-33 comprises a pair of stops **920** carried by first and second compression bands **902**, **904**

sandwiched between a bottom cover **906** and a top cover **908**. A drive mechanism **910** comprising a knob **940** can be provided to move the stops **920** laterally.

In use, a dynamic spacer such as that shown in FIGS. **30-33**, can be positioned on a tongue between the flaps (or vamps) of a footwear item. In some embodiments, the dynamic spacer is positioned between a pair of lace guides. As described above, when the laces **23** are tightened, the flaps will be drawn towards one another. However, in the region of the dynamic spacer, the flap edges (or the lace guides) will abut the stops **920**, thereby preventing further tightening of that region of the footwear item. The dynamic spacer **900** is generally configured to allow a user to adjust a spacing between the stops, and thereby to adjust an amount of tightening in the region of the dynamic spacer. As above, in some embodiments, a wearer may wish to provide more spacing (i.e. a looser fit) at a toe portion of a footwear item. Alternatively, in other embodiments, a user may wish to provide more spacing in an upper section of a footwear item.

The stops **920** are generally carried by the first and second compression bands **902, 904**. With reference to FIGS. **30** and **31** each of the first **902** and second **904** compression bands comprises an elongate slot **922** adjacent a distal end **912, 914** of the compression bands **902, 904**. Each slot **922** includes a plurality of teeth **924** on one edge, the other edge remaining substantially smooth and free of teeth. The bands **902, 904** are positioned as shown in FIGS. **30** and **31** such that the slots **922** overlap, thereby positioning the teeth **924** of each compression band **902, 904** on opposite sides of a centerline of the dynamic spacer **900**.

Adjacent to their proximal ends **932, 934**, the compression bands **902, 904** can also include attachment holes **936** configured to be secured to the stops **920**. In the embodiments illustrated in FIG. **30** and, the stops **920** can be secured to the compression straps **902, 904** by fasteners **926** which can extend through the stops **920**, through slots in the top cover **908**, through the fastener holes **936** in the compression bands **902, 904** and through slots in the bottom cover **906**. In some embodiments, the fasteners **926** can also comprise a retaining member positioned below the bottom cover **906** to retain the fastener in the spacer. The fasteners can be rivets, screws, bolts, pins, or any other suitable devices. Similarly, the retaining members can be crimped rivet ends, washers, nuts, or any other suitable device.

FIGS. **30-62** illustrate embodiments of a drive mechanism **910** for use with a dynamic spacer **900**. The drive mechanism **910** generally comprises a knob **940** configured to rotate in a direction corresponding to a laterally outward movement of the stops **920** (i.e. a counter-clockwise direction in the illustrated embodiment). In some embodiments, the knob **940** is also configured to be locked or otherwise prevented from rotating in a direction corresponding to a laterally inward movement of the stops **920** (i.e. a clockwise direction in the illustrated embodiment). In the illustrated embodiment, the knob **940** comprises a plurality of face ratchet teeth **942** on an underside thereof. The top cover **908** can also be provided with a plurality of mating face ratchet teeth **944** configured to engage the teeth **942** of the knob **940**. In the illustrated embodiments, the mating ratchet teeth **942, 944** are generally configured to resist a clockwise rotation of the knob **940**, thereby preventing the stops **920** from being pushed laterally inwards by the footwear flap edges. In alternative embodiments, other one-way rotational structures and/or other locking structures can also be used. For example, pins, latches, levers, or other devices can be used to prevent rotation of the knob and/or lateral movement of the stops **920**. In some embodiments, the knob **940** is also

configured to be releasable in order to allow the stops **920** to move laterally inwards in order to allow for increased tightening in the area of the dynamic spacer **900**.

In the illustrated embodiment, the knob **940** also includes a shaft **950** extending from its underside and including a drive gear **952** configured to engage the teeth **924** of each of the first **902** and second **904** compression bands. The gear **952** can be any suitable type as desired. The number and/or a spacing of teeth provided on the gear can be varied depending on a degree of mechanical advantage desired. In alternative embodiments, additional gears can also be provided in order to provide additional mechanical advantage to the drive mechanism. For example, in some embodiments, a substantial mechanical advantage may be desirable in order to allow a wearer to more easily loosen a section of a footwear item by turning the knob **940** and driving the stops **920** further apart.

In some embodiments, the shaft **950** is of sufficient length that the distal end **954** of the shaft **950** extends through a central aperture **960** in the bottom cover **906** when the dynamic spacer **900** is assembled. A spring washer **962** can be secured to the distal end **954** of the shaft **950** after the shaft **950** has been inserted through the central aperture **960** in the bottom cover **906**. The spring washer **962** is generally configured to bias the knob **940** downward along the axis of the shaft **950**, thereby maintaining the ratchet teeth **942, 944** in engagement with one another. In some embodiments, the spring washer **962** can also be configured to allow a degree of upward motion of the knob **940** in order to allow the face ratchet teeth **942** to disengage, thereby allowing the stops **920** to move laterally inward.

In some embodiments, the top cover **908** and bottom cover **906** include rails **964** configured to retain and guide the first and second compression bands **902, 904** along a desired path. A material of the compression bands **902, 904** and a space between the top and bottom covers **906, 908** are generally selected to prevent the compression bands from buckling under the compressive force that will be applied by the footwear flap edges engaging the stops **920**.

The dynamic spacer **900** can be secured to a footwear item by attaching the bottom and/or top covers **906, 908** to a portion of a footwear item by any suitable means, such as rivets, adhesives, stitches, hook-and-loop fasteners, etc. Additionally, in some embodiments, the dynamic spacer **900** can be configured to releasably attach to portions of a footwear item. For example, in some embodiments, a tongue of a boot may comprise a plurality of attachment locations for a dynamic spacer, such as at an upper section, an instep section, a toe section, etc. A dynamic spacer can then be removed from any of the attachment locations and moved to another of the attachment locations for a different fit. In still further embodiments, a dynamic spacer need not be attached to any portion of a footwear item. For example, a dynamic spacer can simply be held in place by friction created by a compressive force between the flaps of the footwear.

In alternative embodiments, other drive mechanisms can also be provided. For example, a rack-and-pinion type drive gear and teeth can be oriented such that a rotational axis of the drive gear is positioned perpendicular to the orientation of the illustrated embodiments. In still further embodiments, other mechanical transmission elements, such as worm screws, cable/pulley arrangements, or lockable sliding elements, can alternatively be used to provide an adjustable position between the stops **920**.

In FIG. **3**, the top guide **52** is illustrated for simplicity as unattached to the corresponding side flap **32**. However, in an actual product, the top guide **52** is preferably secured to the

side flap 32. For example, upper retaining member 44a, discussed above, is illustrated in FIG. 2. Alternatively, the top guide 52 may extend within the material of or between the layers of the side flap 32. As a further alternative, or in addition to the foregoing, the end 55 of top guide 52 may be anchored to the side flap 32 using any of a variety of tie down or clamping structures. The lace 23 may be slideably positioned within a tubular sleeve extending between the reel and the tie down at the end 55 of the sleeve.

Any of a variety of flexible tubular sleeves may be utilized, such as a spring coil with or without a polymeric jacket similar to that used currently on bicycle brake and shift cables. The use of a flexible but axially noncompressible sleeve for surrounding the lace 23 between the reel and the tie down at the end 55 isolates the tightening system from movement of portions of the boot, which may include hinges or flexibility points as is understood in the art. The tie down may comprise any of a variety of structures including grommets, rivets, staples, stitched or adhesively bonded eyelets, as will be apparent to those of skill in the art in view of the disclosure herein.

In the illustrated embodiment, the side guide members 50 each have a generally U-shape that opens towards the midline of the shoe. Preferably, each of the side guide members 50 comprise a longitudinal portion 51 and two inclined or transverse portions 53 extending therefrom. The length of the longitudinal portion 51 may be varied to adjust the distribution of the closing pressure that the lace 23 applies to the upper 24 when the lace 23 is under tension. In addition, the length of the longitudinal portion 51 need not be the same for all guide members 50 on a particular shoe. For example, the longitudinal portion 51 may be shortened near the ankle portion 29 to increase the closing pressure that the lace 23 applies to the ankles of the wearer. In general, the length of the longitudinal portion 51 will fall within the range of from about 2" to about 3", and, in some embodiments, within the range of from about 3" to about 4". In one snowboard application, the longitudinal portion 51 had a length of about 2". The length of the transverse portion 53 is generally within the range of from about χ " to about 1". In one snowboard embodiment, the length of transverse portion 53 was about 2". Different specific length combinations can be readily optimized for a particular boot design through routine experimentation by one of ordinary skill in the art in view of the disclosure herein.

In between the longitudinal portion 51 and transverse portion 53 is a curved transition. Preferably, the transition has a substantially uniform radius throughout, or smooth progressive curve without any abrupt edges or sharp changes in radius. This construction provides a smooth surface over which the lace 23 can slide, as it rounds the corner. The transverse section 53 can in some embodiments be deleted, as long as a rounded cornering surface is provided to facilitate sliding of the lace 23. In an embodiment which has a transverse section 53 and a radiused transition, with a guide member 50 having an outside diameter of 0.090" and a lace 23 having an outside diameter of 0.027", the radius of the transition is preferably greater than about 0.1", and generally within the range of from about 0.125" to about 0.4".

Referring to FIG. 3, the upper guide members 52 extend substantially around opposite sides of the ankle portion 29. Each upper guide member 52 has a proximal end 56 and a distal end 55. The distal ends 55 are positioned near the top of the tongue 36 for receipt of the lace 23 from the uppermost side guide members 50. The proximal ends 56 are coupled to the tightening mechanism 25. In the illustrated

embodiment, the proximal ends 56 include rectangular coupling mounts 57 that engage with the tightening mechanism 25 for feeding the ends of the lace 23 therein, as described more fully below. The guide members 50 and/or 52 are preferably manufactured of a low friction material, such as a lubricous polymer or metal, that facilitates the slideability of the lace 23 therethrough. Alternatively, the guides 50, 52 can be made from any convenient substantially rigid material, and then be provided with a lubricous coating on at least the inside surface of lumen 54 to enhance slideability. The guide members 50 and 52 are preferably substantially rigid to prevent bending and kinking of the guide members 50, 52 and/or the lace 23 within any of the guide members 50 and 52 as the lace 23 is tightened. The guide members 50, 52 may be manufactured from straight tube of material that is cold bent or heated and bent to a desired shape.

As an alternative to the previously described tubular guide members, the guide members 50 and/or 52 comprise an open channel having, for example, a semicircular or "U" shaped cross section. The guide channel is preferably mounted on the boot such that the channel opening faces away from the midline of the boot, so that a lace under tension will be retained therein. One or more retention strips, stitches or flaps may be provided for "closing" the open side of the channel, to prevent the lace from escaping when tension on the lace is released. The axial length of the channel can be preformed in a generally U configuration like the illustrated tubular embodiment, and may be continuous or segmented as described in connection with the tubular embodiment.

Several guide channels may be molded as a single piece, such as several guide channels molded to a common backing support strip which can be adhered or stitched to the shoe. Thus, a right lace retainer strip and a left lace retainer strip can be secured to opposing portions of the top or sides of the shoe to provide a right set of guide channels and a left set of guide channels.

With reference to FIG. 4, the gap 206 is elongated so that it defines a lace pathway that functions as the lumen 54 for the lace 23. The lumen 54 preferably includes an elongate region 209 that extends generally lengthwise along the edges of the flaps 32 or 34 when the guide member 199 is mounted on the boot. The elongate region 209 may be straight or may be defined by a smooth curve along the length thereof, such as a continuous portion of a circle or ellipse. As an example, the elongate region 209 may be defined by a portion of an ellipse having a major axis of about 0.5 inches to about 2 inches and a minor axis of about 0.25 inches to about 1.5 inches. In one embodiment, the major axis is approximately 1.4 inches and the minor axis is about 0.5 inches. The lumen 54 further includes a transverse region 210 on opposite ends of the elongate region 209. The transverse region 210 extends at an incline to the edges of the flaps 32 and 34. Alternatively, the elongate region 209 and the transverse region 210 may be merged into one region having a continuous circular or elliptical profile to spread load evenly along the length of the lumen 54 and thereby reduce total friction in the system.

Referring to FIG. 4, each of the guide members 199 has a predetermined distance between the first opening 207a and second opening 207b to the lace pathway therein. The effective linear distance between the first and second openings to the lace pathway may affect the fit of the boot.

The lace 23 may be formed from any of a wide variety of polymeric or metal materials or combinations thereof, which exhibit sufficient axial strength and bendability for the present application. For example, any of a wide variety of solid core wires, solid core polymers, or multi-filament

wires or polymers, which may be woven, braided, twisted or otherwise oriented can be used. A solid or multi-filament metal core can be provided with a polymeric coating, such as PTFE or others known in the art, to reduce friction. In one embodiment, the lace **23** comprises a stranded cable, such as a 7 strand by 7 strand cable manufactured of stainless steel. In order to reduce friction between the lace **23** and the guide members **50**, **52** through which the lace **23** slides, the outer surface of the lace **23** is preferably coated with a lubricous material, such as nylon or Teflon. In a preferred embodiment, the diameter of the lace **23** ranges from 0.024 inches to 0.060 inches and is preferably 0.027 inches. The lace **23** is desirably strong enough to withstand loads of at least 40 pounds and preferably at least about 90 pounds. In certain embodiments the lace is rated at least about 100 pounds up to as high as 200 pounds or more. A lace **23** of at least five feet in length is suitable for most footwear sizes, although smaller or larger lengths could be used depending upon the lacing system design.

The lace **23** may be formed by cutting a piece of cable to the desired length. If the lace **23** comprises a braided or stranded cable, there may be a tendency for the individual strands to separate at the ends or tips of the lace **23**, thereby making it difficult to thread the lace **23** through the openings in the guide members **50**, **52**. As the lace **23** is fed through the guide members, the strands of the lace **23** easily catch on the curved surfaces within the lace guide members. The use of a metallic lace, in which the ends of the strands are typically extremely sharp, also increases the likelihood of the cable catching on the guide members during threading. As the tips of the strands catch on the guide members and/or the tightening mechanism, the strands separate, making it difficult or impossible for the user to continue to thread the lace **23** through the tiny holes in the guide members and/or the tightening mechanism. Unfortunately, unstranding of the cable is a problem unique to the present replaceable-lace system, where the user may be required to periodically thread the lace through the lace guide members and into the corresponding tightening mechanism.

One solution to this problem is to provide the tips or ends **59** of the lace **23** with a sealed or bonded region **61** wherein the individual strands are retained together to prevent separation of the strands from one another. For clarity of illustration, the bonded region **61** is shown having an elongate length. However, the bonded region **61** may also be a bead located at just the extreme tip of the lace **23** and, in one embodiment, could be a bonded tip surface as short as 0.002 inch or less.

After the 7×7 multistrand stainless steel cable described above has been tightened and untightened a number of times, the cable tends to kink or take a set. Kink resistance of the cable may be improved by making the cable out of a nickel titanium alloy such as nitinol. Other materials may provide desirable kink resistance, as will be appreciated by those of skill in the art in view of the disclosure herein. In one particular embodiment, a 1×7 multi-strand cable may be constructed having seven nitinol strands, each with a diameter within the range of from about 0.005 inches to about 0.015 inches woven together. In one embodiment, the strand has a diameter of about 0.010 inches, and a 1×7 cable made with that strand has an outside diameter (“OD”) of about 0.030 inches. The diameter of the nitinol strands may be larger than a corresponding stainless steel embodiment due to the increased flexibility of nitinol, and a 1×7 construction and in certain embodiments a 1×3 construction may be utilized.

In a 1×3 construction, three strands of nitinol, each having a diameter within the range of from about 0.007 inches to about 0.025 inches, preferably about 0.015 inches are drawn and then swaged to smooth the outside. A drawn multistrand cable will have a nonround cross-section, and swaging and/or drawing makes the cross-section approximately round. Swaging and/or drawing also closes the interior space between the strands, and improves the crush resistance of the cable. Any of a variety of additives or coatings may also be utilized, such as additives to fill the interstitial space between the strands and also to add lubricity to the cable. Additives such as adhesives may help hold the strands together as well as improve the crush resistance of the cable. Suitable coatings include, among others, PTFE, as will be understood in the art.

In an alternate construction, the lace or cable comprises a single strand element. In one application, a single strand of a nickel titanium alloy wire such as nitinol is utilized. Advantages of the single strand nitinol wire include both the physical properties of nitinol, as well as a smooth outside diameter which reduces friction through the system. In addition, durability of the single strand wire may exceed that of a multi strand since the single strand wire does not crush and good tensile strength or load bearing capacity can be achieved using a small OD single strand wire compared to a multi strand braided cable. Compared to other metals and alloys, nitinol alloys are extremely flexible. This is useful since the nitinol laces are able to navigate fairly tight radii curves in the lace guides and also in the small reel. Stainless steel or other materials tend to kink or take a set if a single strand was used, so those materials are generally most useful in the form of a stranded cable. However, stranded cables have the disadvantage that they can crush in the spool when the lace is wound on top of itself. In addition, the stranded cables are not as strong for a given diameter as a monofilament wire because of the spaces in between the strands. Strand packing patterns in multistrand wire and the resulting interstitial spaces are well understood in the art. For a given amount of tensile strength, the multistrand cables therefore present a larger bulk than a single filament wire. Since the reel is preferably minimized in size the strongest lace for a given diameter is preferred. In addition, the stranded texture of multistrand wires create more friction in the lace guides and in the spool. The smooth exterior surface of a single strand creates a lower friction environment, better facilitating tightening, loosening and load distribution in the dynamic fit of the present invention.

Single strand nitinol wires having diameters within the range of from about 0.020 inches to about 0.040 inches may be utilized, depending upon the boot design and intended performance. In general, diameters which are too small may lack sufficient load capacity and diameters which are too large may lack sufficient flexibility to be conveniently threaded through the system. The optimal diameter can be determined for a given lacing system design through routine experimentation by those of skill in the art in view of the disclosure herein. In many boot embodiments, single strand nitinol wire having a diameter within the range of from about 0.025 inches to about 0.035 inches may be desirable. In one embodiment, single strand wire having a diameter of about 0.030 inches is utilized.

The lace may be made from wire stock, shear cut or otherwise severed to the appropriate length. In the case of shear cutting, a sharpened end may result. This sharpened end is preferably removed such as by deburring, grinding, and/or adding a solder ball or other technique for producing a blunt tip. In one embodiment, the wire is ground or coined

15

into a tapered configuration over a length of from about ½ inch to about 4 inches and, in one embodiment, no more than about 2 inches. The terminal ball or anchor is preferably also provided as discussed below. Tapering the end of the nitinol wire facilitates feeding the wire through the lace guides and into the spool due to the increased lateral flexibility of the reduced cross section.

Provision of an enlarged cross sectional area structure at the end of the wire, such as by welding, swaging, coining operations or the use of a melt or solder ball, may be desirable in helping to retain the lace end within the reel as well as facilitating feeding the lace end through the lace guides and into the reel. In one embodiment of the reel, discussed elsewhere herein, the lace end is retained within the reel under compression by a set screw. While set screws may provide sufficient retention in the case of a multi strand wire, set screw compression on a single stand cable may not produce sufficient retention force because of the relative crush resistance of the single strand. The use of a solder ball or other enlarged cross sectional area structure at the end of the lace can provide an interference fit behind the set screw, to assist retention within the reel.

In one example, a 0.030 inch diameter single strand lace is provided with a terminal ball having a diameter within the range of from about 0.035 inches to about 0.040 inches. In addition to or as an alternative to the terminal ball or anchor, a slight angle or curve may be provided in the tip of the lace. This angle may be within the range of from about 5° to about 25°, and, in one embodiment about 15°. The angle includes approximately the distal ¼ inch of the lace. This construction allows the lace to follow tight curves better, and may be combined with a rounded or blunted distal end which may assist navigation and locking within the reel. In one example, a single strand wire having a diameter of about 0.030 inches is provided with a terminal anchor having a diameter of at least about 0.035 inches. Just proximal to the anchor, the lace is ground to a diameter of about 0.020 inches, which tapers over a distance of about an inch in the proximal direction up to the full 0.030 inches. Although the term "diameter" is utilized to describe the terminal anchor, Applicant contemplates nonround anchors such that a true diameter is not present. In a noncircular cross-section embodiment, the closest approximation of the diameter is utilized for the present purposes.

As an alternative terminal anchor on the lace, a molded piece of plastic or other material may be provided on the end of each single strand. In a further variation, each cable end is provided with a detachable threading guide. The threading guide may be made from any of a variety of relatively stiff plastics like nylon, and be tapered to be easily travel around the corners of the lace guides. After the lace is threaded through the lace guides, the threading guide may be removed from the lace and discarded, and the lace may be then installed into the reel.

The terminal anchor on the lace may also be configured to interfit with any of a variety of connectors on the reel. Although set screws are a convenient mode of connection, the reel may be provided with a releasable mechanism to releasably receive the larger shaped end of the lace which snaps into place and is not removable from the reel unless it is released by an affirmative effort such as the release of a lock or a lateral movement of the lace within a channel. Any of a variety of releasable interference fits may be utilized between the lace and the reel, as will be apparent to those of skill in the art in view of the disclosure herein.

As shown in FIG. 3, the tightening mechanism 25 is mounted to the rear of the upper 24 by fasteners 64.

16

Although the tightening mechanism 25 is shown mounted to the rear of the boot 20, it is understood that the tightening mechanism 25 could be located at any of a wide variety of locations on the boot 20. In the case of an ice skating boot, the tightening mechanism is preferably positioned over a top portion of the tongue 36. The tightening mechanism 25 may alternatively be located on the bottom of the heel of the boot, on the medial or the lateral sides of the upper or sole, as well as anywhere along the midline of the shoe facing forward or upward. Location of the tightening mechanism 25 may be optimized in view of a variety of considerations, such as overall boot design as well as the intended use of the boot. The shape and overall volume of the tightening mechanism 25 can be varied widely, depending upon the gear train design, and the desired end use and location on the boot. A relatively low profile tightening mechanism 25 is generally preferred. The mounted profile of the tightening mechanism 25 can be further reduced by recessing the tightening mechanism 25 into the wall or tongue of the boot. Boots for many applications have a relatively thick wall, such as due to structural support and/or thermal insulation and comfort requirements. The tightening mechanism may be recessed into the wall of the boot by as much as ½" or more in some locations and for some boots, or on the order of about ¼" or 2" for other locations and/or other boots, without adversely impacting the comfort and functionality of the boot.

Any of a variety of spool or reel designs can be utilized in the context of the present invention, as will be apparent to those of skill in the art in view of the disclosure herein.

Depending upon the gearing ratio and desired performance, one end of the lace can be fixed to a guide or other portion of the boot and the other end is wound around the spool. Alternatively, both ends of the lace can be fixed to the boot, such as near the toe region and a middle section of the lace is attached to the spool.

Any of a variety of attachment structures for attaching the ends of the lace to the spool can be used. In addition to the illustrated embodiment, the lace may conveniently be attached to the spool by threading the lace through an aperture and providing a transversely oriented set screw so that the set screw can be tightened against the lace and to attach the lace to the spool. The use of set screws or other releasable clamping structures facilitates disassembly and reassembly of the device, and replacement of the lace as will be apparent to those of skill in the art.

In any of the embodiments disclosed herein, the lace may be rotationally coupled to the spool either at the lace ends, or at a point on the lace that is spaced apart from the ends. In addition, the attachment may either be such that the user can remove the lace with or without special tools, or such that the user is not intended to be able to remove the lace from the spool. Although the device is disclosed primarily in the context of a design in which the lace ends are attached to the spool, the lace ends may alternatively be attached elsewhere on the footwear. In this design, an intermediate point on the lace is connected to the spool such as by adhesives, welding, interference fit or other attachment technique. In one design the lace extends through an aperture which extends through a portion of the spool, such that upon rotation of the spool, the lace is wound around the spool. The lace ends may also be attached to each other, to form a continuous lace loop.

It is contemplated that a limit on the expansion of portions of the boot due to the sliding of the lace 23 could be accomplished such as through one or more straps that extend transversely across the boot 20 at locations where an expansion limit or increased tightness or support are desired. For

instance, a strap could extend across the instep portion **30** from one side of the boot **20** to another side of the boot. A second or lone strap could also extend around the ankle portion **29**.

With reference to FIG. 5, an expansion limiting strap **220** is located on the ankle portion of the boot **20** to supplement the closure provided by the lace **23** and provide a customizable limit on expansion due to the dynamic fit achieved by the lacing system of the present invention. The limit strap **220** may also prevent or inhibit the wearer's foot from unintentionally exiting the boot **20** if the lace **20** is unlocked or severed or the reel fails. In the illustrated embodiment, the strap **220** extends around the ankle of the wearer. The location of the limit strap **220** can be varied depending upon boot design and the types of forces encountered by the boot in a particular athletic activity.

For example, in the illustrated embodiment, the limit strap **220** defines an expansion limiting plane which extends generally horizontally and transverse to the wearer's ankle or lower leg. The inside diameter or cross section of the footwear thus cannot exceed a certain value in the expansion limiting plane, despite forces imparted by the wearer and the otherwise dynamic fit. The illustrated location tends to limit the dynamic opening of the top of the boot as the wearer bends forward at the ankle. The function of the limit strap **220** may be accomplished by one or more straps, wires, laces or other structures which encircle the ankle, or which are coupled to other boot components such that the limit strap in combination with the adjacent boot components provide an expansion limiting plane. In one embodiment the expansion limiting strap surrounds the ankle as illustrated in FIG. 5. The anterior aspect of the strap is provided with an aperture for receiving the reel assembly therethrough. This allows the use of the expansion limiting strap in an embodiment having a front mounted reel.

In an alternative design, the expansion limiting plane is positioned in a generally vertical orientation, such as by positioning the limit strap **220** across the top of the foot anterior of the ankle, to achieve a different limit on dynamic fit. In this location, the expansion limiting strap **220** may encircle the foot inside or outside of the adjacent shoe components, or may connect to the sole or other component of the shoe to provide the same net force effect as though the strap encircled the foot.

The limit strap **220** may also create a force limiting plane which resides at an angle in between the vertical and horizontal embodiments discussed above, such as in an embodiment where the force limiting plane inclines upwardly from the posterior to the anterior within the range of from about 25° to about 75° from the plane on which the sole of the boot resides. Positioning the limit strap **220** along an inclined force limiting plane which extends approximately through the ankle can conveniently provide both a limit on upward movement of the foot within the boot, as well as provide a controllable limit on the anterior flexing of the leg at the ankle with respect to the boot.

The strap **220** preferably includes a fastener **222** that could be used to adjust and maintain the tightness of the strap **220**. Preferably, the fastener **222** is capable of quick attachment and release, so that the wearer can adjust the limit strap **220** without complication. Any of a variety of fasteners such as corresponding hook and loop (e.g., Velcro) surfaces, snaps, clamps, cam locks, laces with knots and the like may be utilized, as will be apparent to those of skill in the art in view of the disclosure herein.

The strap **220** is particularly useful in the present low-friction system. Because the lace **23** slides easily through the

guide members, the tension in the lace may suddenly release if the lace is severed or the reel fails. This would cause the boot to suddenly and completely open which could cause injury to the wearer of the boot, especially if they were involved in an active sport at the time of failure. This problem is not present in traditional lacing systems, where the relatively high friction in the lace, combined with the tendency of the lace to wedge with the traditional eyelets on the shoe, eliminates the possibility of the lace suddenly and completely loosening.

The low-friction characteristics of the present system also provides the shoe with a dynamic fit around the wearer's foot. The wearer's foot tends to constantly move and change orientation during use, especially during active sports. This shifting causes the tongue and flaps of the shoe to shift in response to the movement of the foot. This is facilitated by the low-friction lacing system, which easily equilibrates the tension in the lace in response to shifting of the wearer's foot. The strap **220** allows the user to regulate the amount of dynamic fit provided by the boot by establishing an outer limit on the expansion which would otherwise have occurred due to the tension balancing automatically accomplished by the readjustment of the lace throughout the lace guide system.

For example, if the wearer of the boot in FIG. 5 did not have the ankle strap **220**, when he flexed his ankle forward during skating, the increased forward force at the top of the boot would cause the tongue to move out slightly while the laces lower in the boot would tighten. As the wearer straightened his ankle out again, closure force would equalize and the tongue would stay tight against his ankle. If the strap **220** were wrapped around his ankle however, it would prevent or reduce this forward movement of the ankle and tongue reducing the dynamic fit characteristics of the boot in the plane of the strap **220** and providing a very different fit and feel of the boot. Thus, the strap provides an effective means for regulating the amount of dynamic fit inherent in the low friction closure system. Since traditional lacing systems have so much friction in them, they do not provide this dynamic fit and consequently would not benefit from the strap in the same way.

Similar straps are commonly used in conjunction with traditional lacing systems but for entirely different reasons. They are used to provide additional closure force and leverage to supplement shoelaces but are not needed for safety and are not used to regulate dynamic fit.

The footwear lacing system **22** described herein advantageously allows a user to incrementally tighten the boot **20** around the user's foot. The low friction lace **23** combined with the low friction guide members **50**, **52** produce easy sliding of lace **23** within the guide members **50** and **52**. The low friction tongue **36** facilitates opening and closure of the flaps **32** and **34** as the lace is tightened. The lace **23** equilibrates tension along its length so that the lacing system **23** provides an even distribution of tightening pressure across the foot. The tightening pressure may be incrementally adjusted by turning the knob on the tightening mechanism **25**. A user may quickly untighten the boot **20** by simply turning or lifting or pressing the knob or operating any alternative release mechanism to automatically release the lace **23** from the tightening mechanism **25**.

As illustrated in FIG. 6, at least one anti-abrasion member **224** is disposed adjacent the tongue **36** and between the flaps **32**, **34**. The anti-abrasion member **224** comprises a flat disc-like structure having a pair of internal channels or lumen **127a,b** arranged in a crossing pattern so as to define a crossing point **230**. The lumen **127a,b** are sized to receive

the lace **23** therethrough. The lumen **127a,b** are arranged to prevent contact between adjacent sections of the lace **23** at the crossing point **230**. The anti-abrasion member **224** thereby prevents chafing of the lace **23** at the crossing point **230**. The anti-abrasion member **224** also shields the lace **23** from the tongue **36** to inhibit the lace **23** from chafing or abrading the tongue **36**.

The anti-abrasion member **224** may alternatively take the form of a knife edge or apex for minimizing the contact area between the lace **23** and the anti-abrasion member **224**. For example, at a crossing point where lace **23** crosses tongue **36**, an axially extending (e.g. along the midline of the foot or ankle) ridge or edge may be provided in-between the boot tongue **36** and the lace **23**. This anti-abrasion member **224** is preferably molded or otherwise formed from a lubricious plastic such as PTFE, or other material as can be determined through routine experimentation. The lace **23** crosses the apex so that crossing friction would be limited to a small contact area and over a lubricious surface rather than along the softer tongue material or through the length of a channel or lumen as in previous embodiments. Tapered sides of the anti-abrasion member **224** would ensure that the anti-abrasion member **224** stayed reasonably flexible as well as help distribute the downward load evenly laterally across the foot. The length along the midline of the foot would vary depending upon the boot design. It may be as short as one inch long or less and placed on the tongue just where the one or more lace crossings are, or it may extend along the entire length of the tongue with the raised ridge or crossing edge more prominent in the areas where the lace crosses and less prominent where more flexibility is desired. The anti-abrasion member **224** may be formed integrally with or attached to the tongue or could float on top of the tongue as in previously described disks.

In one embodiment, the anti-abrasion member **224** is fixedly mounted on the tongue **36** using any of a wide variety of well known fasteners, such as rivets, screws, snaps, stitching, glue, etc. In another embodiment, the anti-abrasion member **224** is not attached to the tongue **36**, but rather freely floats atop the tongue **36** and is held in place through its engagement with the lace **23**. Alternatively, the anti-abrasion member **224** is integrally formed with the tongue **36**, such as by threading a first portion of the lace **23** through the tongue, and the second, crossing portion of lace **23** over the outside surface of the tongue.

Alternatively, one or more of the sections of lace **23** which extend between the flaps **32** and **34** may slideably extend through a tubular protective sleeve. Referring to FIG. **6**, three crossover points are illustrated, each crossover point including a first and a second crossing segments of the lace **23**. A tubular protective sleeve may be provided on each of the first segments or on both the first and second segments at each of the crossover points. Alternatively, the short tubular protective sheaths may be provided on one or both of the segments of lace **23** at the central crossover point which, in FIG. **6**, is illustrated as carrying the anti-abrasion member **24**. Optimizing the precise number and location of the protective tubular segments may be routinely accomplished, by those of skill in the art observing wear patterns of the lacing system in a particular shoe design.

The tubular protective element may comprise any of a variety of tubular structures. Lengths of polymeric or metal tubing may be utilized. However, such tubular supports generally have a fixed axial length. Since the distance between the opposing flaps **32** and **34** will vary depending upon the size of the wearer's foot, the protective tubular sleeves should not be of such a great length that will inhibit

tightening of the lacing system. The tubular protective sheaths may also have a variable axial length, to accommodate tightening and loosening of the lacing system. This may be accomplished, for example, by providing a tubular protective sheath which includes a slightly stretched spring coil wall. During tightening of the system, when each of the opposing flaps **32** and **34** are brought towards each other, the axial length of the spring guide may be compressed to accommodate various sizes. A further alternative comprises a tubular bellows-like structure having alternating smaller-diameter and larger-diameter sections, that may also be axially compressed or stretched to accommodate varying foot sizes. A variety of specific accordion structures, having pleats or other folds, will be apparent to those of skill in the art in view of the disclosure herein. As a further alternative, a telescoping tubular sleeve may be utilized. In this embodiment, at least a first tubular sleeve having a first diameter is carried by the lace **23**. At least a second tubular sleeve having a second, greater diameter is also carried by the lace **23**. The first tubular sleeve is axially slideably advanceable within the second tubular sleeve. Two or three or four or more telescoping tubes may be provided, for allowing the axial adjustability described above.

FIG. **7** schematically illustrates a top view of the insole region of the boot **20**. Locking members **232** may be disposed at any of a wide variety of locations along the lace pathway, such as locations "b", and "c" to create various lace locking zones. By alternately locking and unlocking the locking members **232** and varying the tension in the lace **23**, a user may provide zones of varied tightness along the lace pathway.

FIG. **8** is a front view of the instep portion of the boot **20**. In the embodiment shown in FIG. **8**, the tubular guide members **50** and **52** are mounted directly within the flaps **32**, **34**, such as within or between single or multiple layers of material. Preferably, the tips **150** of each of the guide member **50**, **52** protrude outwardly from an inner edge **152** of each of the flaps **32**, **34**. As best shown in FIG. **9**, a set of stitches **154** surrounds each guide member **50** and **52**. The stitches **154** are preferably positioned immediately adjacent the guide members **50**, **52** to create a gap **156** therebetween. For ease of illustration, the gap **156** is shown having a relatively large size with respect to the diameter of the guide members **50**, **52**. However, the distance between each guide member **50**, **52** and the respective stitches **154** is preferably small.

Preferably, each set of stitches **154** forms a pattern that closely matches the shape of the respective guide members so that the guide members **50**, **52** fit snug within the flaps **32**, **34**. The stitches **154** thereby inhibit deformation of the guide members **50**, **52**, particularly the internal radius thereof, when the lace is tightened. Advantageously, the stitches **154** also function as anchors that inhibit the guide members **50**, **52** from moving or shifting relative to the flaps **32**, **34** during tightening of the lace.

The gap **156** may be partially or entirely filled with a material, such as glue, that is configured to stabilize the position of the guide members **50**, **52** relative to the flaps **32**, **34**. The material is selected to further inhibit the guide members **50**, **52** from moving within the gap **156**. The guide members may also be equipped with anchoring members, such as tabs of various shape, that are disposed at various locations thereon and that are configured to further inhibit the guide members **50**, **52** from moving or deforming relative to the flap **32**. The anchoring members may also comprise notches or grooves on the guide members **50**, **52** that generate friction when the guide members **50**, **52** begin

to move and thereby inhibit further movement. The grooves may be formed using various methods, such as sanding, sandblasting, etching, etc. Axial movement of the guide tubes **50** or **52** may also be limited through the use of any of a variety of guide tube stops (not shown). The guide tube stop includes a tubular body having an opening which provides access to a central lumen extending therethrough. The stop may also be provided with one or more fastening tabs for sewing or gluing to the shoe, as has been discussed. Tabs, once stitched or otherwise secured into place, resist axial movement of the device along its longitudinal pathway.

With reference to FIGS. **10** and **11**, an alternative guide member **250** comprises a thin, single-piece structure having an internal lumen **252** for passage of the lace **23** therethrough. The guide member **250** includes a main portion **254** that defines a substantially straight inner edge **256** of the guide member. A flange portion **260** extends peripherally around one side of the main portion **254**. The flange portion **260** comprises a region of reduced thickness with respect to the main portion **254**. An elongate slot **265** comprised of a second region of reduced thickness is located on the upper surface **266a** of the guide member **250**.

A pair of lace exit holes **262** extend through a side surface of the lace guide member **250** and communicate with the lumen **252**. The lace exit holes **262** may have an oblong shape to allow the lace **23** to exit therefrom at a variety of exit angles.

With reference to FIGS. **10** and **11**, a series of upper and lower channels **264a**, **264b**, respectively, extend through upper and lower surfaces **266a**, **266b**, respectively, of the lace guide member **250**. The channels **264** are arranged to extend along the pathway of the lumen **252** and communicate therewith. The location of each of the upper channels **264a** preferably successively alternates with the location of each of the lower channels **264b** along the lumen pathway so that the upper channels **264a** are offset with respect to the lower channels **264b**.

With respect to FIGS. **12** and **13**, the lace guide member **250** is mounted to the flaps **32**, **34** by inserting the flange region **260** directly within the flaps **32**, **34**, such as within or between single or multiple layers **255** (FIG. **13**) of material. The layers **255** may be filled with a filler material **257** to maintain a constant thickness in the flaps **32**, **34**.

The lace guide member **250** may be secured to the flaps **32**, **34**, for example, by stitching a thread through the flap **32**, **34** and through the lace guide member **250** to form a stitch pattern **251**. The thread is preferably stitched through the reduced thickness regions of the flange portion **260** and the elongate slot **265**. Preferably, the flaps **32**, **34** are cut so that the main portion **254** of the guide member **250** is exposed on the flap **32**, **34** when the lace guide member **250** is mounted thereon.

With respect to FIG. **13**, the upper surface **266a** of the main portion of the guide member **250** is preferably maintained flush with the upper surface of the flaps **32**, **34** to maintain a smooth and continuous appearance and to eliminate discontinuities on the flaps **32**, **34**. Advantageously, because the flange region **260** has a reduced thickness, the lace guide member **250** is configured to provide very little increase in the thickness of the flaps **32**, **34**, and preferably no increase in the thickness of the flaps. The lace guide member **250** therefore does not create any lumps in the flaps **32**, **34** when the guide member **250** is mounted therein.

As mentioned, a series of upper and lower offset channels **264a,b** extend through the lace guide member **250** and communicate with the lumen **252**. The offset arrangement of the channels advantageously facilitates manufacturing of the

guide members **250** as a single structure, such as by using shut-offs in an injection mold process.

The shape of the lumen may be approximately defined by an ellipse. In one embodiment, the ellipse has a major axis of about 0.970 inches and a minor axis of about 0.351 inches.

FIG. **14** is a side view of an alternative tightening mechanism **270**. The tightening mechanism **270** includes an outer housing **272** having a control mechanism, such as a rotatable knob **274**, mechanically coupled thereto. The rotatable knob **274** is slideably movable along an axis **A** between two positions with respect to the outer housing **272**. In a first, or engaged, position, the knob **274** is mechanically engaged with an internal gear mechanism located within the outer housing **272**. In a second, or disengaged, position (shown in phantom) the knob is disposed upwardly with respect to the first position and is mechanically disengaged from the gear mechanism. The tightening mechanism **270** may be removably mounted to the front, back, top or sides of the boot.

The closure system includes a rotatable spool for receiving a lace. The spool is rotatable in a first direction to take up lace and a second direction to release lace. A knob is connected to the spool such that the spool can be rotated in the first direction to take up lace only in response to rotation of the knob. A releasable lock is provided for preventing rotation of the spool in the second direction. One convenient lock mechanism is released by pulling the knob axially away from the boot, thereby enabling the spool to rotate in the second direction to unwind lace. However, the spool rotates in the second direction only in response to traction on the lace. The spool is not rotatable in the second direction in response to rotation of the knob. This prevents tangling of the lace in or around the spool, which could occur if reverse rotation on the knob could cause the lace to loosen in the absence of a commensurate traction on the lace.

In the foregoing embodiments, the wearer must pull a sufficient length of cable from the spool to enable the wearer's foot to enter or exit the footwear. The resulting slack cable requires a number of turns of the reel to wind in before the boot begins to tighten. An optional feature in accordance with the present invention is the provision of a spring drive or bias within the spool that automatically winds in the slack cable, similar to the mechanism in a self biased automatically winding tape measure. The spring bias in the spool is generally not sufficiently strong to tighten the boot but is sufficient to wind in the slack. The wearer would then engage the knob and manually tighten the system to the desired tension.

The self winding spring may also be utilized to limit the amount of cable which can be accepted by the spool. This may be accomplished by calibrating the length of the spring so that following engagement of the knob and tightening of the boot, the knob can only be rotated a preset additional number of turns before the spring bottoms out and the knob is no longer able to be turned. This limits how much lace cable could be wound onto the spool. Without a limit such as this, if a cable is used which is too long, the wearer may accidentally wind in the lace cable until it jams tightly against the reel housing and cannot be pulled back out.

FIGS. **21-27** illustrate one embodiment of a lace winder **600** including a spring configured to automatically eliminate loose slack in the laces **23** by maintaining the laces **23** under tension. In the illustrated embodiments, the winder **600** generally comprises a spool **610** rotatably positioned within a housing member **620** and rotationally biased in a winding direction. The spool **610** is also generally coupled to a knob **622** for manually tightening the laces **23**. Many features of

the winder 600 of FIGS. 21-27 are substantially similar to the tightening mechanism 270 discussed above with reference to FIG. 14. However, in alternative embodiments, features of the spring-biased winder 600 can be applied to many other tightening mechanisms as desired.

FIG. 21 illustrates an exploded view of one embodiment of a lace winder 600. The embodiment of FIG. 21 illustrates a spring assembly 630, a spool assembly 632 and a knob assembly 634. The spool assembly 632 and the spring assembly 630 are generally configured to be assembled to one another and placed within a housing 640. The knob assembly 634 can then be assembled with the housing 640 to provide a self-winding lacing device 600.

The knob assembly 634 generally comprises a knob 622 and a drive gear 642 configured to rotationally couple the knob 622 to a drive shaft 644 which extends through substantially the entire winder 600. In alternative embodiments, the knob assembly 634 can include any of the other devices described above, or any other suitable one-way rotating device.

With reference to FIGS. 23-26, in some embodiments, the housing 640 generally comprises an upper section with a plurality of ratchet teeth 646 configured to engage pawls 648 in to the knob 622 (see FIG. 22). The housing 640 also includes a spool cavity 650 sized and configured to receive the spool assembly 632 and spring assembly 630 therein. A lower portion of the spool cavity 650 generally comprises a plurality of teeth forming a ring gear 652 configured to engage planetary gears 654 of the spool assembly 632.

A transverse surface 656 generally separates the upper portion of the housing 640 from the spool cavity 650. A central aperture 658 in the transverse surface allows the drive shaft 644 to extend from the knob 622, through the housing 640 and through the spool assembly 632. In some embodiments, set-screw apertures 660 and/or a winding pin aperture 662 can also extend through the housing 640 as will be further described below. The housing 640 also typically includes a pair of lace entry holes 664 through which laces can extend.

As discussed above, a gear train can be provided between the knob 622 and the spool 610 in order to allow a user to apply an torsional force to a spool 610 that is greater than the force applied to the knob. In the embodiment of FIGS. 21-25, such a gear train is provided in the form of an epicyclic gear set including a sun gear 670 and a plurality of planetary gears 654 attached to the spool 610, and a ring gear 650 on an internal surface of the housing 640. The illustrated epicyclic gear train will cause a clockwise rotation of the drive shaft 644 relative to the housing 640 to result in a clockwise rotation of the spool 610 relative to the housing 640, but at a much slower rate, and with a much increased torque. This provides a user with a substantial mechanical advantage in tightening footwear laces using the illustrated device. In the illustrated embodiment, the epicyclic gear train provides a gear ratio of 1:4. In alternative embodiments, other ratios can also be used as desired. For example, gear ratios of anywhere from 1:1 to 1:5 or more could be used in connection with a footwear lace tightening mechanism.

With reference to FIGS. 21, 23 and 25, embodiments of a spool assembly 632 will now be described. The spool assembly 632 generally comprises a spool body 610, a drive shaft 644, a sun gear 670, a plurality of planetary gears 654, a pair of set screws 672 and a bushing 674. The spool body 610 generally comprises a central aperture 676, a pair of set screw holes 678, a winding section 680 and a transmission section 682. The winding section 680 comprises a pair of

lace receiving holes 684 for receiving lace ends which can be secured to the spool using set screws 672 or other means as described in previous embodiments. The lace receiving holes 684 are generally configured to be alignable with the lace entry holes 664 of the housing 640. In some embodiments, the spool body 610 also comprises a winding pin hole 690 configured to receive a winding pin for use in assembling the winder 600 as will be further described below. In some embodiments, the spool 610 can also include sight holes 692 to allow a user to visually verify that a lace 23 has been inserted a sufficient distance into the spool 610 without the need for markings on the lace 23.

The bushing 674 comprises an outer diameter that is slightly smaller than the inner diameter of the spool central aperture 676. The bushing 674 also comprises an inner aperture 694 configured to engage the drive shaft 644 such that the bushing 674 remains rotationally stationary relative to the drive shaft throughout operation of the device. In the illustrated embodiment, the drive shaft 644 comprises an hexagonal shape, and the bushing 674 comprises a corresponding hexagonal shape. In the illustrated embodiment, the sun gear 670 also comprises an hexagonal aperture 702 configured to rotationally couple the sun gear 670 to the drive shaft 644. Alternatively or in addition, the sun gear 670 and/or the bushing 674 can be secured to the drive shaft 644 by a press fit, keys, set screws, adhesives, or other suitable means. In other embodiments, the drive shaft 644, bushing 674 and/or sun gear 670 can comprise other cross-sectional shapes for rotationally coupling the elements.

In an assembled condition, the bushing 674 is positioned within the spool aperture 676, the drive shaft 644 extends through the central aperture 694 of the bushing 674 and through the sun gear 670. In some embodiments, the planetary gears 654 can be secured to axles 704 rigidly mounted to the transmission section 682 of the spool 610. The planetary gears 654, when assembled on the spool 610, generally extend radially outwards from the perimeter of the spool 610 such that they may engage the ring gear 652 in the housing 640. In some embodiments, the spool transmission section 682 comprises walls 706 with apertures located to allow the planetary gears 654 to extend therethrough. If desired, a plate 710 can be positioned between the planetary gears 654 and the spring assembly 630 in order to prevent interference between the moving parts.

The spring assembly 630 generally comprises a coil spring 712, a spring boss 714, and a backing plate 716. In some embodiments, a washer/plate 718 can also be provided within the spring assembly 630 between the coil spring 718 and the spring boss 714 in order to prevent the spring 712 from undesirably hanging up on any protrusions of the spring boss 714.

With particular reference to FIG. 27, in some embodiments, the spring boss 714 is rigidly joined to the backplate 716 and the torsional spring 712 is configured to engage the spring boss 714 in at least one rotational direction. The coil spring 712 generally comprises an outer end 720 located at a periphery of the spring 712, and an inner end 722 at a central portion of the spring 712. The outer end 720 is generally configured to engage a portion of the spool 610. In the illustrated embodiment, the outer end 720 comprises a necked-down portion to engage an aperture in a portion of the spool 610. In alternative embodiments, the outer end 720 of the spring 712 can be secured to the spool by welds, mechanical fasteners, adhesives or any other desired method. The inner end 722 of the spring 712 comprises a hooked portion configured to engage the spring boss 714.

The spring boss 714 comprises a pair of posts 730 extending upwards from the backplate 716. The posts 730 are generally crescent shaped and configured to engage the hooked interior end 722 of the spring 712 in only one rotational direction. Each post 730 comprises a curved end 736 configured to receive the hooked spring end 722 as the spring rotates counter-clockwise relative to the backplate 716. Each post 730 also comprises a flat end 738 configured to deflect the hooked spring end 722 as the spring 712 rotates clockwise relative to the backplate 716. In the illustrated embodiment, the posts 714 and spring 712 are oriented such that a clockwise rotation of the spring 712 relative to the spring boss 714 and backplate 716 will allow the spring to "skip" from one post 714 to the other without resisting such rotation. On the other hand, a counter-clockwise rotation of the spring 712 will cause the hooked end 722 to engage one of the posts 714, thereby holding the interior end 722 of the spring stationary relative to the outer portions of the spring 712. Continued rotation of the outer portions of the spring will deflect the spring, thereby biasing it in the clockwise winding direction.

The space 732 between the posts 730 of the spring boss 714 is generally sized and configured to receive the distal end of the drive shaft, which in some embodiments as shown in FIG. 21, can comprise a circular end 734 configured to freely rotate in the spring boss space 732. In the embodiment illustrated in FIG. 21, the spring boss 714 and the backplate 716 are shown as separately manufactured elements which are later assembled. In alternative embodiments, the backplate 716 and spring boss 714 can be integrally formed as a unitary structure and/or as portions of another structure.

Embodiments of methods for assembling a self-coiling lace winder 600 will now be described with reference to FIGS. 21-26. In one embodiment, the sun and planetary gears 670, 654 are assembled onto the transmission portion 682 of the spool 610, and the bushing 674 and drive shaft 644 are inserted through the aperture 676 in the spool. The spring assembly 630 is assembled by attaching the spring boss 714 to the back plate 716 by any suitable method and placing the spring 712 on the spring boss 714. The spool assembly 632 can then be joined to the spring assembly 630 by attaching the outer end 720 of the spring 712 to the spool 610. In some embodiments, the spring 712 may need to be pre-wound tightly in order to fit within the spool walls 706. The spool assembly 632 and the spring assembly 630 can then be placed within the housing member 640. In some embodiments, the backplate 716 is secured to the housing member 640 by screws 740 or other suitable fasteners such as rivets, welds, adhesives, etc. In some embodiments, the backplate 716 can include notches 742 configured to cooperate with extensions or recesses in the housing member 640 in order to prevent the entirety of the torsional spring load from bearing against the screws 740.

In some embodiments, once the spool assembly 632 and the spring assembly 630 are assembled and placed in the housing 640, the spring 712 can be tensioned prior to attaching the laces. In one embodiment, with reference to FIG. 26, the spring 712 is tensioned by holding the housing 640 stationary and rotating the drive shaft 644 in an unwinding direction 740, thereby increasing the deflection in the spring 712 and correspondingly increasing a biasing force of the spring. Once a desired degree of deflection/spring bias is reached, a winding pin 742 can be inserted through the winding pin aperture 662 in the housing 640 and the winding pin hole 690 in the spool 610.

In one embodiment, the winding pin hole 690 in the spool is aligned relative to the winding pin aperture 662 in the

housing such that the set screw holes 678 and the lacing sight holes 692 in the spool 610 will be aligned with corresponding apertures 660 in the housing 640 when the winding pin 742 is inserted (also see FIG. 25). The spool 610 and housing 640 are also preferably configured such that the lace receiving holes 684 of the spool 610 are aligned with the lace entry holes 664 of the housing 640 when the winding pin hole 690 and aperture 662 are aligned. In alternative embodiments, the winding pin hole 690 and aperture 662 can be omitted, and the spool can be held in place relative to the housing by some other means, such as by placing a winding pin 742 can be inserted through a set screw hole and aperture or a sight hole/aperture.

Once the spring 712 has been tensioned and a winding pin 742 has been inserted, the laces 23 can be installed in the spool using any suitable means provided. In the embodiment illustrated in the embodiments of FIGS. 21-26, the spool 610 is configured to secure the laces 23 therein with set screws 672. The laces can be inserted through the lace entry holes 664 in the housing 640 and through the lace receiving holes 684 in the spool 610 until a user sees the end of the lace in the appropriate sight hole 692. Once the user visually verifies that the lace is inserted a sufficient distance, the set screws 672 can be tightened, thereby securing the laces in the spool.

Once the laces 23 are secured, the winding pin 742 can be removed, thereby allowing the spring to wind up any slack in the laces. The knob 622 can then be attached to the housing 640, such as by securing a screw 750 to the drive shaft 644. A user can then tighten the laces 23 using the knob 622 as desired.

In alternative embodiments, it may be desirable to pre-tension the spring 712 after installing the laces 23 in the spool 610. For example, if an end user desires to change the laces in his/her footwear, the old laces 23 can be removed by removing the knob 622, loosening the set screws 672 and pulling out the laces 23. New laces can then be inserted through the lace entry holes 684 and secured to the spool with the set screws 672, and re-install the knob 622 as described above. In order to tension the spring 712, a user can then simply wind the lace by rotating the knob 622 in the winding direction until the laces are fully tightened (typically without a foot in the footwear). The spring will not resist such forward winding, since the spring boss 714 will allow the spring 712 to freely rotate in the forward direction as described above. In one preferred embodiment, the user tightens the laces as much as possible without a foot in the footwear. Once the laces are fully tightened, the knob can be released, such as by pulling outwards on the knob as described above, and the laces can be pulled out. As the spool rotates in an unwinding direction, the hooked inner end 722 of the spring 712 engages the spring boss 714, and the spring deflects, thereby again biasing the spool 610 in a winding direction.

In an alternative embodiment, a lace winder can be particularly useful for lightweight running shoes which do not require the laces to be very tight. Some existing lightweight running shoes employ elastic laces, however such systems are difficult, if not impossible, to lock once a desired lace tension is achieved. Thus, an embodiment of a lightweight spring-biased automatically winding lacing device can be provided by eliminating the knob assembly 634, gears 654, 670 and other components associated with the manual tightening mechanism. In such an embodiment, the spool 610 can be greatly simplified by eliminating the transmission section 682, the housing 640 can be substantially reduced in size and complexity by eliminating the ring

gear section **652** and the ratchet teeth **646**. A simplified spool can then be directly connected to a spring assembly **630**, and a simple locking mechanism can be provided to prevent unwinding of the laces during walking or running.

Therefore, a right reel and a left reel can be configured for opposite directional rotation to allow a user to more naturally grip and manipulate the reel. It is currently believed that an overhand motion, e.g. a clockwise rotation with a person's right hand, is a more natural motion and can provide a greater torque to tighten the reel. Therefore, by configuring a right and left reel for opposite rotation, each reel is configured to be tightened with an overhand motion by tightening the right reel with the right hand, and tightening the left reel with the left hand.

Alternatively, the guide members **490** may comprise a lace guide defining an open channel having, for example, a semicircular, "C" shaped, or "U" shaped cross section. The guide member **490** is preferably mounted on the boot or shoe such that the channel opening faces away from the midline of the boot, so that a lace under tension will be retained therein. One or more retention strips, stitches or flaps may be provided for "closing" the channel opening to prevent the lace from escaping when tension on the lace is released. The axial length of the channel can be preformed in a generally U configuration. Moreover, practically any axial configuration of the guide member **490** is possible, and is mainly dictated by fashion, and only partly by function.

Several guide members **490** may be molded as a single piece, such as several lace guides **491** molded to a common backing support strip which can be adhered or stitched to the shoe. Thus, a right lace guide member and a left lace guide member can be secured to opposing portions of the top or sides of the shoe to provide a right set of guide channels **492** and a left set of guide channels **492**. When referring to "right" and "left" guide members, this should not be construed as suggesting a mounting location of the retainer strips. For example, the guide members **490** can be located on a single side of the shoe, such as in a shoe having a vamp that extends generally from one side of the shoe, across the midline of the foot, and is secured by laces on the opposing side of the shoe. In this type of shoe, the guide members **490** are actually disposed vertically with respect to one another, and hence, a left and right guide member merely refers to the fact that the guide members **490** have openings that face one another, as illustrated in FIG. **16**.

FIGS. **15** and **16** illustrate exemplary embodiments and mounting configurations of the present footwear-lacing system. For example, a plurality of guide members **490** can be located in lieu of traditional shoe eyelet strips, as described above. Typically, the guide members **490** are installed as opposing pairs, with the guide members formed integrally with the reel **498** typically comprising one of the guide members. The term "reel" will be used hereinafter to refer to the various embodiments including the complete structure of the outer housing and its internal components, unless otherwise specified. Thus, in some embodiments, there are 2, 4, 6, or 8 or more cooperating guide members **490** installed to define a lace path. Moreover, a non-paired guide member **490** can be installed, such as toward the toe of the shoe and positioned transverse to the midline and having its lace openings directed toward the heel of the shoe. This configuration, in addition to applying tightening forces between the lateral and medial sides of the shoe, would also apply a lace tension force along the midline of the shoe. Of course, other numbers and arrangements of guide members can be pro-

vided and this application and its claims should not be limited to only configurations utilizing opposing or even paired guide members.

FIG. **15** shows an embodiment in which the reel **498** is located on the lateral quarter panel of the shoe. Of course, the reel **498** can be located practically anywhere on the shoe and only some of the preferred locations are described herein. Moreover, the illustrated reel can be any reel embodiment suitable for practicing the present invention, and should not be limited to one particular embodiment. The illustrated embodiment provides three guide members **490** spaced along the gap between the medial quarter panel **500** and lateral quarter panels **502** of the shoe and thus creates a lace path that zigzags across the tongue **504**. While the reel **498** is illustrated as being disposed on the lateral quarter **502** panel near the ankle, it may also be disposed on the medial quarter panel **500** of the shoe. In some embodiments, the reel **498** is disposed on the same quarter panel of each shoe, for example, the reel can be mounted on the lateral quarter panel **502** of each shoe, or in alternative embodiments, the reel can be disposed on the lateral quarter panel **502** of one shoe, and on the medial quarter panel **500** of the other shoe.

Notably, this particular embodiment has a lace path that forms an acute angle α as it enters the outer housing. As discussed above, a lace guide member can be integrally formed into the outer housing to direct the lace to approach and interact with the reel from substantially diametrical directions. Thus, the summation of tension forces applied to the reel are substantially cancelled.

FIG. **17** shows an alternative embodiment of a shoe incorporating a vamp closure structure. In this particular embodiment, the reel **498** can be disposed on the vamp **506**, as illustrated, or can be disposed on the lateral quarter panel, or even in the heel, as disclosed above. Similar to FIG. **15**, the reel illustrated in this FIG. **16** should not be limited to one specific embodiment, but should be understood to be any suitable embodiment of a reel for use with the disclosed invention. In the illustrated embodiment, three lace guides **490** are affixed to the shoe; two on the lateral quarter panel **502**, and one on the vamp **506** cooperating with the guide members integrally formed with the reel **498** to define a lace path between the lateral quarter panel **502** and the vamp **506**. Those of ordinary skill will appreciate that the guide members can be spaced appropriately to result in various tightening strategies.

For example, the opposing guide members **490** can be spaced a greater distance apart to allow a greater range of tightening. More specifically, by further separating the opposing guide members **490**, there is a greater distance that can be used to effectuate tightening before the guide members **490** bottom out. This embodiment offers the additional advantage of extending the lace **23** over a substantially planar portion of the shoe, rather than across a portion of the shoe having a convex curvature thereto.

FIG. **17** illustrates an alternative arrangement of a shoe incorporating a vamp closing structure and having a reel and a non-looping lace. In this particular embodiment, an open ended lace can be attached directly to a portion of the shoe. As illustrated, a reel **498** is mounted on the lateral quarter panel **502** of the shoe. The shoe has one or more lace guides **490** strategically positioned thereon. As illustrated, one lace guide **490** is mounted on the vamp **506** while a second lace guide **498** is mounted on the lateral quarter panel **502**. A lace has one end connected to a spool within the reel **498** and extends from the reel **498**, through the lace guides **490** and is attached directly to the shoe by any suitable connection **512**. One suitable location for attaching the lace is on the

vamp toward the toe for those embodiments in which the reel **498** is mounted on the lateral quarter panel **502**.

The connection **512** may be a permanent connection or may be releasable to allow the lace to be removed and replaced as necessary. The connection is preferably a suitable releasable mechanical connection, such as a clip, clamp, or screw, for example. Other types of mechanical connections, adhesive bonding, or chemical bonding may also be used to attach a lace end to the shoe.

While the illustrated embodiment shows the reel **498** attached to the lateral quarter panel **502**, it should be apparent that the reel **498** could readily be attached to the vamp **506** and still provide the beneficial features disclosed herein. Additionally, the lace could optionally be attached to the shoe on the lateral quarter panel **502** rather than the vamp **506**. The reel **498** and lace could be attached to a common portion of the shoe, or may be attached to different portions of the shoe, as illustrated. In any case, as the lace is tightened around the spool, the lace tension draws the guide members toward each other and tightens the footwear around a wearer's foot.

A shoe is typically curved across the midline to accommodate the dorsal anatomy of a human foot. Therefore, in an embodiment in which the laces zigzag across the midline of the shoe, the further the lace guides **490** are spaced, the closer the laces **23** are to the sole **510** of the shoe. Consequently, as the laces **23** tighten, a straight line between the lace guides **490** is obstructed by the midline of the shoe, which can result in a substantial pressure to the tongue of the shoe and further result in discomfort to the wearer and increased chaffing and wearing of the tongue. Therefore, by locating the laces **23** across a substantially flat surface on either the lateral or medial portion of the shoe, as illustrated, the laces **23** can be increasingly tightened without imparting pressure to other portions of the shoe.

It is contemplated that some embodiments of the lacing system **22** discussed herein will be incorporated into athletic footwear and other sports gear that is prone to impact. Such examples include bicycle shoes, ski or snowboard boots, and protective athletic equipment, among others. Accordingly, it is preferable to protect the reel from inadvertent releasing of the spool and lace by impact with external objects.

FIGS. **18** and **19** illustrate a lacing system **22** further having a protective element to protect the reel from impact from external objects. In one embodiment, the protective element is a shield **514** comprised of one or more raised ridges **516** or ramps configured to extend away from the mounting flange **406** a distance sufficiently high to protect the otherwise exposed reel. In the illustrated embodiment, the shield **514** is configured to slope toward the reel thus presenting an oblique surface to any objects it may contact to deflect the objects away from the reel. The shield **514** is positioned around the reel circumferentially and slopes radially toward the reel and may encircle the reel, or may be positioned around half the reel, a quarter of the reel, or any suitable portion or portions of the reel.

The shield **514** may be integrally formed with the mounting flange **406**, such as during molding, or may be formed as a separate piece and subsequently attached to the lacing system **22** such as by adhesives or other suitable bonding techniques. It is preferable that the shield **514** is formed of a material exhibiting a sufficient hardness to withstand repeated impacts without plastically deforming or showing undue signs of wear.

Another embodiment of a protective element is shown in FIG. **20**. In this embodiment, a shield **514** is in the form of a raised lip **517** that encircles a portion of the circumference

of the knob (not shown). The lip **517** can be of sufficient height to exceed the top of the knob, or can extend to just below the height of the knob to allow a user to still grasp the knob above the lip **517**, or the lip **517** can be formed with varying heights. The lip **517** is preferably designed to withstand impact from various objects to thereby protect the knob from being inadvertently rotated and/or displaced axially.

The lip **517** can be integrally molded with the mounting flange, or can be a separate piece. In addition, the lip **517** can take on various shapes and dimensions to satisfy aesthetic tastes while still providing the protective function it has been designed for. For example, it can be formed with various draft angles, heights, bottom fillets, of varying materials and the like. In the illustrated embodiment, the lip **517** extends substantially around the entire circumference of the knob **498**, except at holds **521** where the lip **517** recedes sufficiently to allow a user to grasp a large portion of the knob's height to be able to displace the knob axially by lifting it away from the housing. The illustrated embodiment additionally shows that the lip **517** extends outward to protect a substantial portion of the knob's height. While the lip **517** is illustrated as extending around a particular portion of the knob's circumference, it can of course extend around more or less of the knob's circumference. Certain preferred embodiments integrate a continuous shield **514** extending around between a quarter and a half of the knob circumference, while other embodiments incorporate a shield **514** comprising one or more discrete portions that combine to cover any appropriate range about the circumference of the knob. Of course, other protective elements or shields **514** could be incorporated to protect the reel, such as a protective covering or cap to cover the reel, a cage structure that fits over the reel, and the like.

FIGS. **28-30D** illustrate an embodiment of an alternative lacing arrangement which is generally configured to provide a plurality of lace tightening zones for an item of footwear. Such a multi-zone lacing system can provide substantial benefits by allowing a user to independently tighten various different sections of a footwear item to various different tensions. For example, in many cases, it may be desirable to tighten a toe portion more than an upper portion. In other cases, a user may desire the opposite, a tight upper and a looser toe section. However, in either case, users typically want a strong heel-hold-down force at an ankle portion of the footwear. Thus, in addition to providing multiple independent lacing zones, the systems illustrated in FIGS. **28-30** are also advantageously arranged to hold the ankle section of a footwear item under the tension of the tighter of the two laces.

FIG. **28** is a schematic illustration of one embodiment of multi-zone lacing system **800**. The system of FIG. **28** includes first **802** and second **804** lace tightening mechanisms arranged to tighten first **23a** and second **23b** laces. In some embodiments, the first tightening mechanism **802** may be located on a tongue, while the second **804** may be located on a side of a boot. Alternatively, both of the tightening mechanisms **802**, **804** can be provided on a tongue or on a side of the footwear. In alternative embodiments, the mechanisms can be otherwise located on a footwear item. In further alternative embodiments, a multi-zone lacing system can be provided with a single lace tightening device comprising a plurality of individually operable spools. Such individually operable spools can be operated by a single knob and a selector mechanism, or each spool can include its own knob.

One embodiment of multi-zone lacing system **800** is preferably a dual loop tightening system in which a first tightening loop has a first lace **23a** having a first length and a second tightening loop has a second lace **23b** having a second length. In some embodiments, first lace **23a** and second lace **23b** have equal lengths. In other embodiments, the length of second lace **23b** is preferably in the range of from about 100% to about 150% of the length of first lace **23a**. In some embodiments, the length of second lace **23b** is preferably at least 110% of the length of first lace **23a**. In still other embodiments, the length of second lace **23b** is preferably at least 125% of the length of first lace **23a**. In alternative embodiments, the lengths of first **23a** and second **23b** laces are reversed. First loop preferably has a lock **802** such as a reel located on a tongue of the footwear and second loop has a lock **804** such as a reel on the side or rear of the footwear. Alternatively, locks **802**, **804** may be located elsewhere on the footwear, including both located on a tongue or both on the sides or rear of the footwear.

The multi-zone lacing system **800** schematically shown in FIG. **28** is a triple-zone lacing system. Each zone is generally defined by a pair of lateral lace guides which will be drawn towards one another generally along a line between their centers. Thus, the first lacing zone **810** is defined by the first lace **23a** extending between first **812** and second **814** lace guides. A second lacing zone **820** is defined by the second lace **23b** extending between third **822** and fourth **824** lace guides, and a third lacing zone **830** is defined by the region between the fifth **832** and sixth **834** lace guides, through which both the first and second laces **23a**, **23b** extend. In alternative embodiments, multi-zone lacing systems can be provided with only two zones, or with four or more zones, and each zone can comprise any number of overlapping laces as desired.

In the embodiment of FIG. **28**, the third lacing zone **830** in which the laces overlap provides the unique advantage of automatically tightening the third zone **830** according to the tighter of the two laces **23a**, **23b**. In one embodiment, the third lacing zone **830** coincides with an ankle portion of a footwear item. In this embodiment, the third lacing zone advantageously lies along an ankle plane which can extend through a pivot axis of a wearer's ankle at an angle of anywhere from zero to 90 degrees relative to a horizontal plane. In some embodiments, the third zone lies in a plane at between about 30 and about 75 degrees relative to a horizontal plane. In one embodiment, the ankle plane lies at an angle of about 45° above a horizontal plane. In alternative embodiments, the third lacing zone **830** lies along a plane passing through a rear-most point of a wearer's heel and the ankle pivot axis. By locating the third lacing zone along the ankle plane, a wearer's heel can be held tightly in the footwear regardless of which lace is tighter.

As shown in FIG. **28**, the multizone lacing system **800** employs a plurality of lace guides of various types. For example, an upper section of the first lace **23a** and a lower section of the second lace **23b** are shown extending through first **812**, and second **814**, third **822** and fourth curved lace guides **824** respectively. Each of the curved lace guides **812**, **814**, **822**, **824** comprises a guide section **842** for substantially frictionless engagement with the laces **23** and an attachment section **844** for securing the lace guide to respective flaps of a footwear item. In some embodiments, the curved lace guides **812**, **814**, **822**, **824** can be similar to the guides **250** described above with reference to FIGS. **10-13**.

Central abrasion preventing guides **846**, **848** can also be provided between lateral pairs of lace guides to prevent the laces from abrading one another and to keep the laces from

tangling with one another. In alternative embodiments, any of the lace guides in the multi-zone lacing system of FIG. **28** can be replaced by any other suitable lace guides as described elsewhere herein. The lace guides can be injection molded or otherwise formed from any suitable material, such as nylon, PVC or PET. As discussed elsewhere herein, lace guides are generally configured to draw opposite flaps of a footwear item towards one another in order to tighten the footwear. This is generally accomplished by providing a guide with a minimum of friction or abrasion-causing surfaces.

In the illustrated embodiment, the third lacing zone advantageously employs a pair of "double-decker" lace guides **832**, **834** configured to guide both the first lace and the second lace along an overlapping path while holding the laces **23a**, **23b** apart in order to prevent their abrading one another. The lower section of the first lace **23a**, and a portion of the second lace **23b** are shown extending through a double-decker lace guide **834** and a double-decker pass-through lace guide **832**. FIGS. **29A-29D** illustrate an embodiment of a double-decker lace guide for use in embodiments of a multi-zone lacing system. The double-decker lace guide **834** generally comprises an upper lace guiding section **850** for guiding the first lace **23a**, a lower lace guiding section **852** for guiding the second lace **23b**, and an attachment section **844** for securing the guide to the footwear. In the illustrated embodiment, each of the upper and lower guide sections **850**, **852** comprise arcuate surfaces configured to guide the laces **23** in a substantially frictionless manner. Each of the arcuate sections can be similar to the guides described above with reference to FIGS. **10-13**.

FIGS. **30A-30D** illustrate one embodiment of a double-decker pass-through lace guide **832**. The pass-through guide **832** comprises an upper arcuate section **860** configured to guide the first lace **23a**, and a lower pass-through section **862**. The upper guide section **860** is preferably separated from the lower pass-through section in order to prevent the first **23a** and second **23b** laces from abrading one another. The lower pass-through section **862** is generally configured to receive a section of axially-incompressible tubing **864** which abuts a transverse surface **866** of the guide **832**. The transverse surface **866** also includes holes **868** sized to allow the lace **23b** to pass therethrough, while retaining the tubing on one side of the surface **866**. The tubing **864** can be any suitable type, such as a bicycle cable sheath or other material as described elsewhere herein. The incompressible tubing sections **864** are provided over the sections of the second lace **23b** between the lower section **862** of the double-decker pass-through guide **832** and the lace tightening mechanism **804**. This prevents the guide **832** from being drawn towards the tightening mechanism **804** as the lace is tightened, and insures that the tightening force is only applied to drawing the flaps of the footwear towards one another. In an alternative embodiment, the tubing sections **864** can be eliminated by incorporating the tightening mechanism into a lace guide in the position of the pass-through guide **832**.

In some embodiments, the attachment sections **844** of each of the double-decker lace guide **834**, and the double-decker pass-through lace guide **832** can be secured to a strap (not shown) which can extend to a position adjacent the heel of a footwear item, thereby providing additional heel hold-down ability.

The abrasion preventing guides **846** in the illustrated multi-zone lacing system generally include three conduits for supporting the laces **23a**, **23b**. As shown, each abrasion preventing guide **846** comprises two crossing diagonal conduits **870** and one linear conduit **872** to support the first and

second laces **23a**, **23b** in a substantially frictionless and non-interfering manner. In alternative embodiments, the functions of the abrasion preventing guides **846** can be divided among a plurality of separate guides as desired. In further alternative embodiments, any or all of the conduits can be replaced by loops of fabric or other material or straps attached to the footwear or other lace guides. In some embodiments, the double-decker lace guide **834** and the double-decker pass-through lace guide **832** can be attached to one another by a flexible strap with passages through portions of the strap for receiving the first and second laces. Such a strap can be configured to distribute a compressive force throughout the ankle region of the footwear. In some embodiments, such a strap can be made of neoprene or other durable elastic material.

Each of the lace guides is generally configured to be secured to an item of footwear by any suitable means. For example, the lace guides may be secured to a footwear item by stitches, adhesives, rivets, threaded or other mechanical fasteners, or the lace guides can be integrally formed with portions of a footwear item.

FIGS. **35-37C**, illustrate still another embodiment of a differential lacing system for tightening a first region of a footwear item differently than a second region. The system of FIGS. **37A-C** is generally a lace doubling system in which a lace can be passed through a pair of lace guides a second time by pulling the lace through a slot in a first guide and hooking the lace over a hook extending from a portion of a second guide. A third lace guide **1008** of any suitable type can also be provided opposite the tightening mechanism **1000**.

FIG. **37A** illustrates a lacing system comprising a lace tightening device **1000** and a lace **23** extending through a plurality of lace guides including a pair of doubling lace guides **1010**. In some embodiments, doubling lace guides **1010** can be provided in order to double a number of times a lace **23** passes through a single lace guide. As shown in FIG. **37C**, a lace **23** can be passed through a given pair of lace guides **1010** twice, thereby providing an additional tightening force between those two guides. In some embodiments, each pair of doubling lace guides **1010** comprises a hook lace guide **1012** and a slotted lace guide **1014**.

FIG. **35** illustrates one embodiment of a lace guide **1014** comprising a curved slot **1020**. The slot **1020** is generally sized and configured to allow a user to grasp a portion of the lace **23** which extends across the slot **1020**. At either side of the slot **1020**, the lace guide **1014** comprises shoulders **1022** configured to substantially frictionlessly support the lace **23** in the guide **1014**. As with other embodiments of lace guides described herein, the lace guide **1014** can also comprise a cover **1024** configured to enclose a conduit **1026** through which the lace **23** passes.

FIG. **36** illustrates one embodiment of a lace guide **1012** comprising a hook **1030**. The hook **1030** generally extends from an inner portion of the lace guide **1012** and is open so as to allow a lace to be looped over the hook **1030**. In some embodiments, the hook **1030** has a width that is approximately equal to the slot **1020** of the slotted lace guide **1014**. In some embodiments, the hook **1030** can be molded integrally with the lace guide **1012**, while in alternative embodiments, the hook **1030** can be separately formed and subsequently attached to the guide **1012**. In some embodiments, the hook **1030** is configured to allow the lace to slide thereon with minimal friction and minimal abrasion on the laces.

As with the other lace guides described herein, the slotted **1014** and hooked **1012** lace guides can be made of any suitable material, and can be attached to a footwear item in

any desired manner. Similarly, many embodiments of lace tightening mechanisms are described herein which can be used with the doubling lace guide system of FIGS. **35-37C**. A doubling lace guide system can also be used in connection with any other lacing system described herein or elsewhere.

In some embodiments, a plurality of pairs of doubling lace guides can be provided on a footwear item so as to provide a user with the option of doubling up laces in a number of sections of the footwear. In other embodiments, the tightening mechanism **1000** can include a hook extending from a portion thereof in order to provide further versatility.

FIGS. **37A-37C** illustrate one embodiment of a sequence for doubling up a lace with a pair of doubling lace guides **1010**. In a first position, as shown in FIG. **37A**, the lace **23** lies across the curved slot **1020**. A user can grasp the lace **23** with a finger or small tool, such as a key. A loop **1032** of the lace **23** can then be pulled through the slot towards the hooked lace guide **1012** as shown in FIG. **37B**. The loop **1032** can then be placed over the hook **1030** as shown in FIG. **37C**, so as to double the number of times the lace passes through the lace guides **1010**.

As discussed above, the lace **23** is preferably a highly lubricious cable or fiber having a low modulus of elasticity and a high tensile strength. While any suitable lace may be used, certain preferred embodiments utilize a lace formed from extended chain, high modulus polyethylene fibers. One example of a suitable lace material is sold under the trade name SPECTRA™, manufactured by Honeywell of Morris Township, N.J. The extended chain, high modulus polyethylene fibers advantageously have a high strength to weight ratio, are cut resistant, and have very low elasticity. One preferred lace made of this material is tightly woven. The tight weave provides added stiffness to the completed lace. The additional stiffness provided by the weave offers enhanced pushability, such that the lace is easily threaded through the lace guides, and into the reel and spool.

The lace made of high modulus polyethylene fibers is additionally preferred for its strength to diameter ratio. A small lace diameter allows for a small reel. In some embodiments, the lace has a diameter within the range of from about 0.010" to about 0.050", or preferably from about 0.020" to about 0.030", and in one embodiment, has a diameter of 0.025". Of course, other types of laces, including those formed of textile, polymeric, or metallic materials, may be suitable for use with the present footwear lacing system as will be appreciated by those of skill in the art in light of the disclosure herein.

Another preferred lace is formed of a high modulus polyethylene fiber, nylon or other synthetic material and has a rectangular cross-section. This cross-sectional shape can be formed by weaving the lace material as a flat ribbon, a tube, or other suitable configuration. In any case the lace will substantially flatten and present a larger surface area than a cable or other similar lace and will thereby reduce wear and abrasion against the lace guides and other footwear hardware. In addition, there is a sufficient amount of cross-sectional material to provide an adequate tension strength, while still allowing the lace to maintain a sufficiently thin profile to be efficiently wound around a spool. The thin profile of the lace advantageously allows the spool to remain small while still providing the capacity to receive a sufficient length of lace. Of course, the laces disclosed herein are only exemplary of any of a wide number of different types and configurations of laces that are suitable to be used with the lacing system described herein.

With reference to FIGS. **38A** through **51**, additional embodiments of a lacing system **22** are shown. FIGS. **38A**

and 38B are side views of an alternative tightening mechanism 1200. The tightening mechanism 1200 includes a base member 1202 including an outer housing 1203 and a mounting flange 1204 disposed near the bottom of outer housing 1203. In alternative embodiments, the flange 1204 is disposed a distance from the bottom of outer housing 1203. Mounting flange 1204 may be mounted to the outside structure of an article of footwear, or may be mounted underneath some or all of the outer structure of the footwear, to which the tightening mechanism 1200 is attached. Base member 1202 is preferably molded out of any suitable material, as discussed above, but in one embodiment, is formed of nylon. As in other embodiments, any suitable manufacturing process that produces mating parts fitting within the design tolerances is suitable for the manufacture of base 1202 and the other components disclosed herein. Tightening mechanism 1200 further includes a control mechanism, such as a rotatable knob assembly 1300, mechanically coupled thereto. Rotatable knob assembly 1300 is slideably movable along an axis A between two positions with respect to the outer housing 1203.

In a first, also referred to herein as a coupled or an engaged position (shown in FIG. 38A), knob 1300 is mechanically engaged with an internal gear mechanism located within outer housing 1203, as described more fully below. In a second, also referred to herein as an uncoupled or a disengaged position (shown in FIG. 38B), knob 1300 is disposed upwardly with respect to the first position and is mechanically disengaged from the gear mechanism. Disengagement of knob 1300 from the internal gear mechanism is preferably accomplished by pulling the control mechanism outward, away from mounting flange 1204, along axis A. Alternatively, the components may be disengaged using a button or release, or a combination of a button and rotation of knob 1300, or variations thereof, as will be appreciated by those of skill in the art and as herein described above.

FIG. 39 illustrates a top perspective exploded view of one embodiment of a tightening mechanism 1200. The embodiment of FIG. 39 illustrates a base unit 1202, a spool 1240, and a knob assembly 1300. Spool 1240 is generally configured to be placed within a housing 1203. Knob assembly 1300 can then be assembled with housing 1203 and spool 1240 to provide tightening mechanism 1200. Tightening mechanism 1200 may also be referred to herein as a lacing device, a lace lock, or more simply as a lock.

FIGS. 40A through 40C illustrate one embodiment of base member 1202. Base 1202 includes an outer housing 1203 and a mounting flange 1204. Preferably, flange 1204 extends circumferentially around housing 1203. In alternative embodiments, flange 1204 extends only partially around the circumference of housing 1203 and may comprise one or more distinct portions. Though flange 1204 is shown with a circular or ovular shape, it may also be rectangular, square, or any of a number of other regular or irregular shapes. Flange 1204 preferably includes a trough 1208 extending substantially the length of the outer circumference of flange 1204. The central portion of trough 1208 is preferably thinner than the rest of flange 1204, thereby facilitating attachment of base 1202 to the footwear by stitching. Though stitching is preferred, as discussed above, base 1202 may be securely attached by any suitable method, such as for example, by adhesives, rivets, threaded fasteners, and the like, or any combinations thereof. For example, adhesive may be applied to a lower surface 1232 of base member 1202. Alternatively, mounting flange 1204 may be removably attached to the footwear, such as by a releasable mechanical bonding structure in the form of cooperating

hook and loop structures. Flange 1204 is preferably contoured to curve with the portion of the footwear to which it is attached. One such contour is illustrated in FIGS. 38A and 38B and in FIGS. 45A and 45B. In some embodiments, the contour is flat. Flange 1204 is also preferably resilient enough to at least partially flex in response to forces which cause the structure of the footwear to which it is mounted to flex.

Outer housing 1203 of base member 1202 is generally a hollow cylinder having a substantially vertical wall 1210. Housing wall 1210 may include a minimal taper outward toward flange 1204 from the upper most surface 1332 of housing 1203 the base of housing 1203. Housing 1203 preferably includes sloped teeth 1224 formed onto its upper most surface 1332 such as those found on a ratchet, as has been described herein above. These base member teeth 1224 may be formed during the molding process, or may be cut into the housing after the molding process, and each defines a sloped portion 1226 and a substantially vertical portion 1228. In one embodiment, vertical portion 1228 may include a back cut vertical portion 1228 in which it is less than vertical, as described below.

In one embodiment, the sloped portion 1226 of each tooth 1224 allows relative clockwise rotation of a cooperating control member, e.g. knob assembly 1300, while inhibiting relative counterclockwise rotation of the control member. Of course, the teeth direction could be reversed as desired. The number and spacing of teeth 1224 controls the fineness of adjustment possible, and the specific number and spacing can be designed to suit the intended purpose by one of skill in the art in light of this disclosure. However, in many applications, it is desirable to have a fine adjustment of the lace tension, and the inventors have found that approximately 20 to 40 teeth are sufficient to provide an adequately fine adjustment of the lace tension.

Base member 1202 additionally contains a pair of lace entry holes 1214 for allowing each end of a lace to enter therein and pass through internal lace openings 1230. Lace entry holes 1214 and internal lace openings 1230 preferably define elongated lace pathways that correspond to the annular groove of spool 1240. Preferably, lace entry holes 1214 are disposed on vertical wall 1210 of housing 1203 directly opposed from each other. As discussed above, base member 1202 lace entry holes 1214 may be made more robust by the addition of higher durometer materials either as inserts or coatings to reduce the wear caused by the laces abrading against the base member 1202 entry holes 1214. Additionally, the site of the entry hole can be rounded or chamfered to provide a larger area of contact with the lace to further reduce the pressure abrasion effects of the lace rubbing on the base unit. In the illustrated embodiment, base member 1202 includes lace opening extensions 1212 including rounded entry hole edges 1216 to provide additional strength to the housing 1203 in the area of the lace entry holes 1214. FIG. 41 shows a modified entry hole edge 1216. As discussed above, a lace guide may be formed integrally with the base member 1202 and can be configured depending upon the specific application of the lacing system 22. An embodiment with an integrated lace guide is shown attached to footwear in FIG. 47B.

It is preferable that the inner bottom surface 1220 of the base member 1202 is highly lubricious to allow mating components an efficient sliding engagement therewith. Accordingly, in one embodiment, a washer or bushing (not shown) is disposed within the cylindrical housing portion 1203 of the base member 1202, and may be formed of any suitable lubricious polymer, such as PTFE, for example, or

may be formed of a lubricious metal. Alternatively, the inner bottom surface 1220 of the base member 1202 may be coated with any of a number of coatings (not shown) designed to reduce its coefficient of friction and thereby allow any components sharing surface contact therewith to easily slide. One advantage of the illustrated embodiment is the reduction in separate movable components required to manufacture tightening mechanism 1200. Fewer parts reduces the cost of manufacture and preferably results in lighter weight mechanisms. Overall, tightening mechanism 1200 is small and compact with few moving parts. Light weight and fewer moving parts also reduce the frictional forces generated on the components within lacing device 1200 during use.

An inner surface 1218 of housing 1203 is preferably substantially smooth to facilitate winding of the lace about the spool residing within housing 1203 during operation. When spool 1240 is inserted into housing 1203, inner surface 1218 cooperates with annular groove 1256 to hold the wound lace. Preferably, the material selected for inner surface 1218 is adapted to reduce the friction imparted upon the lace if the lace rubs against the surface when the lace is wound into or released from housing 1203. FIG. 40B shows a top view of base member 1202. Base 1202 preferably includes a central axial opening 1222. In a preferred embodiment, opening 1222 is adapted to receive a threaded insert 1223. Insert 1223 is preferably metallic or some other material offering suitable strength to securely retain axial pin 1360 (e.g., FIG. 39).

FIG. 40C illustrates grooves 1286 which are preferably included in base member 1202. Grooves 1286 further reduce the material utilized in the illustrated embodiment, thereby reducing the weight of the completed tightening mechanism 1200 and providing for improved molding by providing substantially similar wall thicknesses throughout base member 1202. Also shown is part indicia 1236. Indicia 1236 may be used to indicate the "handedness" of a particular part. In some applications, namely on a pair of footwear having a unit adapted for use with a right foot and another unit adapted for use with a left foot, it may be desirable to have lacing devices 1200 attached to the shoes operate in different directions. Indicia 1236 help coordinate the proper components for each lacing device 1200. Indicia 1236 may be used on some or all of the components described herein. Indicia 1236 may be formed during the molding process or may be painted onto the component parts.

With additional reference to FIG. 39, as well as to FIGS. 42A through 42E, a spool 1240 is provided and configured to reside within housing 1203 of base member 1202. Spool 1240 is preferably molded out of any suitable material, as discussed above, but in one preferred embodiment, is formed of nylon and may include a metal insert, preferably along the central axis. In alternative embodiments, spool 1240 is cast or molded from any suitable polymer or formed of metal such as aluminum. Spool 1240 preferably includes an upper flange 1253, a lower flange 1242, and a substantially cylindrical wall 1252 therebetween. A central axial opening 1286 extends through spool 1240 and includes inner side walls 1288. A bottom surface 1254 of upper flange 1253 cooperates with the outer surface of cylindrical wall 1252 and an upper surface 1244 of lower flange 1242 to form annular groove 1256. Annular groove 1256 is advantageously adapted to receive the spooled lace as it is wound around spool 1240.

In one preferred embodiment, bottom surface 1254 of upper flange 1253 and upper surface 1244 of lower flange 1242 are both angled relative to the horizontal axis of spool

1240. As shown in FIG. 42B, the distance between the surfaces adjacent cylindrical wall 1252 is smaller than the distance between the surfaces when measured from the outer diameter of the flanges. As lace 23 is wound around spool 1240, the effective diameter of the combined lace and spool increases. Advantageously, as tension is placed on lace 23, the coiled lace 23 will fan out, minimizing the effective diameter of the spool plus wound lace. The smaller the effective diameter, the greater the torque placed on lace 23 when knob 1300 is rotated. In alternative embodiments, spool 1240 includes one or more additional flanges to define additional annular grooves.

Preferably, the periphery of an upper surface 1260 of upper flange 1253 is configured to include sloped teeth 1262. Sloped teeth 1262 may be formed during the molding process, if spool 1240 is molded, or may be subsequently cut therein, and each defines a sloped portion 1264 and a substantially vertical portion 1266 as measured from upper surface 1260. Vertical portion 1266 is preferably back cut such that it is slightly less than vertical, preferably in the range of zero (0) and twenty (20) degrees less than ninety (90) degrees. More preferably, it is angled between one (1) and five (5) degrees less than vertical. Most preferably, it is angled about three (3) degrees less than vertical. In one embodiment, vertical portion 1266 of each tooth 1262 cooperates with teeth formed on a control member, e.g. knob teeth 1308, causing relative counter-clockwise rotation of spool 1240 upon counter-clockwise rotation of the cooperating control member, thereby winding the lace about the cylindrical wall 1252 of spool 1240. Of course, the teeth direction could be reversed as desired. The slight angle less than vertical, or back cut, is preferable as it increases the strength of the mating relationship between spool teeth 1262 and the control member. As lace tension increases, spool 1240 and knob 1300 may tend to disengage. Back cutting the vertical portion of the teeth helps prevent unintended disengagement.

Advantageously, spool 1240 is dimensioned to reduce the overall size of tightening mechanism 1200. Adjustments may be made with the ratio of the diameter of cylindrical wall 1252 of spool 1240 and the diameter of control knob 1300 to affect the torque that may be generated within tightening mechanism 1200 during winding. As lace 23 is wound about spool 1240, its effective diameter will increase and the torque generated by rotating knob 1300 will decrease. Preferably, torque will be maximized while maintaining the compact size of the lace lock 1200. For purposes of non-circular cross-sections, the diameter as used herein refers to the diameter of the best fit circle which encloses the cross-section in a plane transverse to the axis of rotation.

In many embodiments of the present invention, the knob 1300 will have an outside diameter of at least about 0.5 inches, often at least about 0.75 inches, and, in one embodiment, at least about 1.0 inches. The outside diameter of the knob 1300 will generally be less than about 2 inches, and preferably less than about 1.5 inches.

The cylindrical wall 1252 defines the base of the spool, and has a diameter of generally less than about 0.75 inches, often no more than about 0.5 inches, and, in one embodiment, the diameter of the cylindrical wall 1252 is approximately 0.25 inches.

The depth of the annular groove 1256 is generally less than a 1/2 inch, often less than 3/8 of an inch, and, in certain embodiments, is no more than about a 1/4 inch. In one embodiment, the depth is approximately 3/16 of an inch. The width of the annular groove 1256 at about the opening

thereof is generally no greater than about 0.25 inches, and, in one embodiment, is no more than about 0.13 inches.

The knob **1300** generally has a diameter of at least about 300%, and preferably at least about 400% of the diameter of the cylindrical wall **1252**.

The lace for cooperating with the forging cylindrical wall **1252** is generally small enough in diameter that the annular groove **1256** can hold at least about 14 inches, preferably at least about 18 inches, in certain embodiments at least about 22 inches, and, in one embodiment, approximately 24 inches or more of length, excluding attachment ends of the lace. At the fully wound end of the winding cycle, the outside diameter of the cylindrical stack of wound lace is less than 100% of the diameter of the knob **1300**, and, preferably, is less than about 75% of the diameter of the knob **1300**. In one embodiment, the outer diameter of the fully wound up lace is less than about 65% of the diameter of the knob **1300**.

By maintaining the maximum effective spool diameter less than about 75% of the diameter of the knob **1300** even when the spool is at its fully wound maximum, maintains sufficient leverage so that gearing or other leverage enhancing structures are not necessary. As used herein, the term effective spool diameter refers to the outside diameter of the windings of lace around the cylindrical wall **1252**, which, as will be understood by those of skill in the art, increases as additional lace is wound around the cylindrical wall **1252**.

In one embodiment, approximately 24 inches of lace will be received by 15 revolutions about the cylindrical wall **1252**. Generally, at least about 10 revolutions, often at least about 12 revolutions, and, preferably, at least about 15 revolutions of the lace around the cylindrical wall **1252** will still result in an effective spool diameter of no greater than about 65% or about 75% of the diameter of the knob **1301**.

In general, laces having an outside diameter of less than about 0.060 inches, and often less than about 0.045 inches will be used. In certain preferred embodiments, lace diameters of less than about 0.035 will be used.

Side edge **1258** of upper flange **1253** and side edge **1248** of lower flange **1242** are adapted to slidingly engage the inner wall surface **1218** of the housing **1203** of the base member **1202**. Sliding engagement with the inner wall surface **1218** helps stabilize spool **1240** inside housing **1203**. Similarly, inner side walls **1288** of axial opening **1286** of spool **1240** slidingly engage the axial body **1370** of axial pin **1360** to stabilize spool **1240** during use of lacing device **1200**. Lower surface **1246** of lower flange **1242** may be configured for efficient sliding engagement with inner bottom surface **1220** of base member **1202**. In FIG. **42C**, lower surface **1246** is shown substantially flat. In alternative embodiments, lower surface **1246** may be provided with a lip (not shown) that offers a small surface area that contacts bottom surface **1220** of base member **1202**.

As illustrated in FIGS. **42A** through **42B**, lower flange **1242** of spool **1240** preferably includes lace gaps **1250**. Lace gaps **1250** facilitate attachment of the lace to the spool as described below. Lace gaps **1250** also facilitate insertion of spool **1240** within housing **1203** after lace **23** has been attached to spool **1240**. Preferably, the edges of lace gaps **1250** are rounded. Rounded edges reduce the potential for the lace to catch on the gaps which could potentially adversely kink the lace. Advantageously, the edges of all the components that directly contact the lace are preferably rounded. This is especially advantageous where the lace slides against these edges.

As described in detail above, spool **1240** may include one or more annular grooves **1256** that are configured to receive

lace **23**. Preferably, the ends of lace **23** are connected to spool **1240**, either fixedly or removeably, in any one of a number of suitable attachment methods, including using set screws, crimps, or adhesives. In a preferred embodiment shown in FIG. **42E**, lace **23** is removeably secured to spool **1240**. Upper flange **1253** of spool **1240** preferably includes two sets of three retaining holes (see FIG. **42A**) adapted to receive lace **23**. An inner side wall **1268** of upper flange **1253** cooperates with side walls **1274** of a central divider **1272** to define knot cavities **1278**. In a preferred embodiment, side walls **1268** and **1274** include one or more lace indents **1276** to facilitate insertion of lace **23** into the retaining holes. In alternative embodiments, lace indents **1276** are not included.

Lace **23** is preferably secured to spool **1240** by threading lace **23** through one of the lace holes **1214** in base member **1202**. Lace **23** exits internal lace opening **1230** of housing **1203** and is directed toward spool **1240**. Lace **23** is then passed through lace gap **1250** and upwards through entrance hole **1280** in upper flange **1253**. Next, lace **23** is passed downward through loop hole **1282a** and back upwards through loop hole **1282b**. A portion of lace **23** therefore forms a loop disposed above upper flange **1253** and between entrance hole **1280** and loop hole **1282a**. The end of lace **23** is passed through the loop and tension is placed on the portion of lace **23** extending downwards from entrance hole **1280** to tighten the resulting knot **1292**. Preferably, knot **1292** is positioned such that it rests within knot cavity **1278** by passing the end of lace **23** through the loop from outside inwards, as shown in FIG. **42E**. A second knot **1292** is similarly formed. Advantageously, wall **1252** of spool **1240** may also include lace groove **1284**. Lace groove **1284** captures the portion of lace **23** that extends into annular groove **1256** after lace **23** is tied to spool **1240**. By accommodating this portion of lace **23** within wall **1252**, the winding of lace **23** around spool **1240** is cleaner and less compression and pressure is placed upon the portion of lace **23** extending into annular groove **1256**. Lace groove **1284** further minimizes the diameter of spool **1240** to maximize the torque that may be placed on lace **23** as discussed above. In alternative embodiments, lace groove **1284** is not included.

Although the above method of securing lace **23** to spool **1240** is preferred, other means for attaching the lace are also envisioned by the inventors. The method for attaching lace **23** to spool **1240** as described above is advantageous as it allows for a simple, secure connection to spool **1240** without requiring additional connection components. This saves weight and decreases the assembly time required to manufacture footwear incorporating a tightening mechanism **1200** as described herein. Further, this type of connection allows for simplified and easy replacement of lace **23** when it has become worn.

Referring now to FIGS. **39**, **43A**, and **43B**, tightening mechanism **1200** is further provided with a control knob assembly **1300** which is configured to be incrementally rotated in a forward rotational direction, i.e., in a rotational direction that causes lace **23** to wind around spool **1240**. Toward this end, control knob **1300** preferably includes a series of integrally-mounted pawls **1302** that engage the corresponding series of teeth **1224** on outer housing **1203** of base **1202**. Pawls **1302** are preferably engaged with base teeth **1224** only when the control knob **1300** is in the coupled or engaged position, as shown in FIG. **38A**. The tooth/pawl engagement inhibits knob **1300**, and mechanically connected spool **1240**, from being rotated in a backwards direction (i.e., in a rotational direction opposite the rota-

tional direction that winds lace **23** around spool **1240**) when knob **1300** is in the engaged position. This configuration prevents the user from inadvertently winding control knob **1300** backwards, which could cause lace **23** to kink or tangle in spool **1240**. In alternative embodiments, pawls **1302** may be configured, for instance by modifying the sloped surface **1304** of pawls **1302**, to allow incremental rotation of knob **1300** in the reverse direction. Such an embodiment is advantageous as it could allow for incremental decrease of the tension placed on the lace.

Knob assembly **1300** preferably includes a knob **1301**, a spring member **1340**, and a cap member **1350**. As shown in FIG. **43A**, the under side of knob **1301** further includes teeth **1308** for engagement with spool teeth **1262** of spool **1240**. Knob teeth **1308** include sloping portions **1310** and vertical portions **1312**. One or more cap engagement openings **1314** extend through knob **1301** to facilitate attachment of cap **1350** to knob **1301**. Preferably, cap **1350** includes one or more downwardly extending engagement arms **1352** of (FIG. **39**) which may cooperate with one or more engagement openings **1324**. In a preferred embodiment, arms **1352** are heat staked in place. As will be appreciated by those of skill in the art, cap **1350** may be permanently or removably coupled to knob **1301** in any one of a number of ways. For example, in alternative embodiments, engagement arms **1352** may include prongs or protrusions at the ends thereof for removably securing cap **1350** to knob **1301**. As shown in FIG. **39**, an upper surface **1354** of cap **1350** may advantageously include advertising indicia **1356**, which may be in the form of raised letters or symbols or, alternatively, be visually differentiated from the rest of upper surface **1354** with colors. As such, tightening mechanism may be used as an advertising tool. In other embodiments, upper surface **1354** does not include indicia **1356**.

An outer engagement surface **1319** of knob **1301** is preferably formed with knurls **1318** or some other friction enhancing feature. In preferred embodiments, the outer engagement surface **1317** is made of a softer material than the rest of knob **1301** to increase the tactile feel of knob **1301** and to ease the manipulation of the lacing device **1200** to apply tension to lace **23**.

As shown in FIGS. **39** and **43B**, an upper side of knob **1301** is configured to retain spring member **1340**. Preferably, spring member **1340** is of a unitary construction and includes engagement arms **1342**. In a preferred embodiment, engagement tabs **1322** of knob **1301** cooperate with outer side walls **1326** of central engagement projection **1324** to retain spring **1340**. As shown in FIGS. **45A** and **45B**, engagement arms **1342** are preferably retained within knob **1300**, but are secured such that they can move outwards in cavity **1334** when tightening mechanism **1200** is engaged or disengaged. FIG. **46** shows a top perspective cross sectional view of tightening mechanism **1200** in the disengaged position.

In a preferred embodiment, axial pin **1360** secures knob assembly **1300**, spool **1240**, and base member **1202**. Axial pin **1360** is preferably made of a metallic or other material of sufficient strength to withstand the forces imparted on tightening mechanism **1200**. Axial pin **1360** also preferably includes a multitude of regions with varying diameters, including a cap **1364** having an upper surface **1363**, an upper side engagement surface **1364**, a lower side engagement surface **1366**, and a lower surface **1367**. Upper side engagement surface **1364** preferably tapers outward from upper surface **1363** toward lower side engagement surface **1366**. Lower side engagement surface **1366** preferably tapers inward from upper side engagement surface **1364** toward

lower surface **1367**. Preferably, the diameter of axial pin **1360** is largest along the circumference of the intersection of upper and lower side engagement surfaces **1364** and **1366**. The diameter of upper surface **1363** is preferably greater than the diameter of lower surface **1367**.

Upper surface **1363** of cap **1350** also preferably includes one or more engagement holes **1374** for rotating pin **1360** into threaded engagement with base member **1202**. In other embodiments, a single, centrally located engagement hole is used with a non-circular opening as will be understood by those of skill in the art. Upper surface **1363** may also include indicia **1376**. In alternative embodiments, indicia **1376** is not included.

Disposed adjacent and just below cap **1362** is upper sleeve **1368**. The diameter of upper sleeve **1368** is preferably smaller than the diameter of lower surface **1367**. Pin body **1370** is preferably disposed adjacent and just below upper sleeve **1368**. The diameter of pin body **1370** is preferably smaller than the diameter of upper sleeve **1368**. Finally, threaded extension **1372** preferably extends downward from the lower surface of pin body **1370**. Though extension **1372** is preferably threaded, other mating or engagement means may be used to couple pin **1360** to base **1202**.

Axial pin **1360** includes multiple diameters to correspond to the varying internal diameters of the axial openings in knob **1300**, spool **1240**, and base member **1202**, respectively. Corresponding diameters of these components helps stabilize the tightening mechanism **1200**. Pin body **1370** is adapted to slidingly engage with inner side wall **1288** of seal opening **1286** of spool **1240**. Upper sleeve **1368** is adapted to slidingly engage with inner wall **1330** of axial opening **1316** of knob **1301**. Threaded extension **1372** couples with insert **1223** of base member **1202** to secure axial pin **1360** to base member **1202**. As will be appreciated by those of skill in the art, axial pin **1360** may be permanently or removably attached to base member **1202**. For example, an adhesive may be used, either alone or in combination with threads.

FIGS. **44A** and **44B** are top views tightening mechanism **1200** in engaged and disengaged positions, respectively. Referring now to FIGS. **45A** and **45B**, knob **1300** is illustrated to show its moveability between the two positions, coupled or engaged (FIG. **45A**) and uncoupled or disengaged (FIG. **45B**). In the uncoupled position, lace **23** may be manually removed from spool **1240**, by, for example, putting tension on lace **23** in a direction away from tightening mechanism **1200**.

Advantageously, the diameter of upper sleeve **1368** of axial pin **1360** is larger than the inner diameter of axial opening **1286** of spool **1240**. As such, upper sleeve **1368** of axial pin **1360** serves as an upper restraint for movement of spool **1240** along axis **A**, as can be seen in FIG. **45A**. Movement along axis **A** is limited such that when knob **1300** is in the disengaged position, as shown in FIG. **45B**, knob teeth **1308** disengage from spool teeth **1262**, allowing free rotation of spool **1240** in the disengaged position. In this disengaged state, lace **23** is manually removed from spool **1240**. In preferred embodiments, only a single control, e.g. knob **1300**, is needed to actuate the tightening mechanism **1200**. Push it in to tighten the lacing system **22** and pull it out to loosen the lacing system **22**.

In a preferred embodiment, spring engagement arms **1342** engage upper side engagement surfaces **1364** of cap **1362** in the uncoupled position and engage lower side engagement surface **1366** in the coupled position. In the coupled position, arms **1342** engage lower side engagement surface **1366** to bias knob **1300** in the coupled position. In the uncoupled position, arms **1342** engage upper side engagement surface

1364 to bias knob 1300 in the uncoupled position. Although spring 1340 biases knob 1300 in the coupled and the uncoupled positions in this embodiment, other options are available as will be understood by one of skill in the art. For example, knob 1300 could be biased only in the engaged position, such that it can be pulled out to disengage spool 1240, however, as soon as it is released it slides back into the engaged position.

In a preferred embodiment, knob 1300 will be biased in each of the coupled and the uncoupled positions such that the user is required to either push the knob in or pull the knob out against the bias to engage or disengage, respectively, the tightening mechanism 1200. Advantageously, engaging and disengaging tightening mechanism 1200 is accompanied by a “click” or other sound to indicate that it has changed positions. Tightening mechanism 1200 may also include visual indicia that the mechanism is disengaged, such as a colored block that is exposed from under the knob when in the disengaged position. Audible and visual indications that the mechanism is engaged or disengaged contribute to the user friendliness of the lacing systems described herein.

Tightening mechanism 1200 may be removably or securely mounted to a variety of locations on footwear, including the front, back, top, or sides. Base member 1202 illustrated in FIGS. 38A through 41 is preferably adapted to be attached to the side portion of a boot or shoe. FIGS. 47A through 47C show tightening mechanism 1200 securely stitched to the upper of a shoe near the eyestay of the shoe. Lace guides may be incorporated onto the base 1202 of the mechanism 1200, as shown in FIG. 47B, or they may be separate. In some embodiments, substantially all of tightening mechanism 1200 is secured within the footwear structure, leaving only knob 1300 and a small portion of housing 1203 exposed. In some such embodiments, lace holes 1214 are positions substantially along the axis of the eyestay to which the mechanism 1200 is attached (see FIG. 47B). When mechanism 1200 is attached in such a manner, it is preferable that flange 1204 extend in the direction opposite lace holes 1214, allowing mechanism 1200 to be positioned at or near the edge of the upper adjacent the tongue. Mechanism 1200 may also be positioned in other areas of the footwear including near the sole or toe portions. Lacing system 22 also includes tongue guides 1380 and lace guides 1392, as will be discussed in greater detail below.

FIGS. 48B and 49B show an alternate preferred embodiment of tightening mechanism 1200 including a modified base member 1202. Base member 1202 is configured with a lower outer housing 1208 and an upper outer housing 1203. Lower outer housing 1208 slopes outward from upper outer housing 1203 toward flange 1204. The upper most portion of lower outer housing 1208 preferably includes a protective lip 1290. In a preferred embodiment, protective lip 1290 extends partway up the outer engagement surface 1319 of knob assembly 1300 and only partway around the circumference of knob 1300. In alternative embodiments, the lip extends fully around the circumference of the knob. In still other embodiments, the lip extends only partway around the circumference of the knob, but extends upwards over substantially the entire width of the outer engagement surface 1319 of knob 1300.

In the embodiment illustrated in FIGS. 48A and 48B, lower outer housing 1208 preferably includes lace pathways 1238 leading from rear surface 1232 of base member 1202 and ending at lace holes 1214. As shown in FIG. 48A, lace holes 1214 preferably extend through the upper surface 1332 of upper outer housing 1203. Flange 1204 and lower outer

housing 1208 are shaped in a substantially curved manner to accommodate attachment surfaces with large inherent curvature, such as, for example on the rear portion of a boot or shoe.

Base member 1202 illustrated in FIGS. 48A through 49B is preferably adapted to be attached to the rear portion of a boot or shoe. FIGS. 50A and 50B show tightening mechanism 1200 securely stitched to the rear portion of a shoe. Advantageously, after passing through the upper most tongue guide 1380, lace 23 enters lace guide 1392 and is directed around the ankle portion of the shoe toward tightening mechanism 1200. Lace guide 1392 is preferably made of a low sliding resistance polymer, such as Teflon or nylon, and preferably includes rounded edges. The upper most lace guides 1392 preferably have only one entrance point on each side of the shoe, the exit point being directly coupled to the lace pathway 1338 of rear mounted tightening mechanism 1200.

Lacing system 22 preferably includes tongue guides 1380, shown in greater detail in FIG. 51. Tongue guide 1308 preferably includes mounting flange 1382, sliding surfaces 1384a and 1384b and central cap 1388. Central cap 1388 is preferably disposed in a raised manner above sliding surface 1384 by one or more support legs 1390. Sliding surfaces 1384a and 1384b are preferably disposed in different planes such that a generally vertical ledge 1386 is formed therebetween. The different planes of sliding surface 1384 helps reduce friction by limiting lace 23 from sliding against itself. Mounting flange 1382 may be sewn under one or more of the outer layers of shoe tongue or to the outer surface of the tongue. In alternative embodiments, tongue guide 1380 is attached to the tongue by adhesive, rivets, etc., or combinations thereof, as will be understood by those of skill in the art. Support legs 1390 are preferably angled to accommodate the different ingress and egress directions of lace 23 as it enters the central cap portion 1388.

As with the other components of lacing systems described herein, the tightening mechanism 1200, the tongue guides, and the other lace guides described above in connection with tightening mechanism 1200 can be made of any suitable material, and can be attached to footwear in any suitable manner. The various component parts of the lacing system may be used in part or in whole with other components or systems described herein. As discussed above, lace 23 may be formed from any of a wide variety of polymeric or metal materials or combinations thereof, which exhibit sufficient axial strength and suppleness for the present application. In one preferred embodiment, lace 23 comprises a stranded cable, such as a 7 strand by 7 strand cable manufactured of stainless steel. In order to reduce friction between lace 23 and the guide members through which lace 23 slides, the outer surface of the lace 23 is preferably coated with a lubricous material, such as nylon or Teflon. The coating also binds the threads of the stranded cable to ease insertion of the lace into the lace guides of the system and attachment of the lace to the gear mechanism within lacing device 1200. In a preferred embodiment, the diameter of lace 23 is in the range of from about 0.024 inches to about 0.060 inches inclusive of the coating of lubricous material. More preferably, the diameter of lace 23 is in the range of from about 0.028 to about 0.035. In one embodiment, lace 23 is preferably approximately 0.032 inches in diameter. A lace 23 of at least five feet in length is suitable for most footwear sizes, although smaller or larger lengths could be used depending upon the lacing system design. For example, lacing systems for use with running shoes may preferably use lace 23 in the range from about 15 inches to about 30 inches.

With reference to FIGS. 52A through 59B, additional embodiments of a lacing system 22 are shown. FIGS. 52A and 52B are top and perspective views, respectively, of an alternative tightening mechanism 1400. Tightening mechanism 1400 may also be referred to herein as a lacing device, a lace lock, or more simply as a lock. As with other embodiments presented herein, tightening mechanism 1400 may be configured for placement in any of a variety of positions on the footwear including in the ankle region (for example on snow board boots or hiking boots with ankle support), on the tongue (if the footwear includes a tongue), on the instep area of the footwear, or on the rear of the footwear. It is preferably molded out of any suitable material, as discussed above, but in one embodiment, comprises nylon, metal, and rubber. As in other embodiments, any suitable manufacturing process that produces mating parts fitting within the design tolerances is suitable for the manufacture of tightening mechanism 1400 and its components.

FIG. 53 illustrates a top perspective exploded view of one embodiment of a tightening mechanism 1400. The embodiment of FIG. 53 includes a base member (or bayonet) 1402, a housing assembly 1450 including a spool assembly 1480, and a control mechanism, such as a rotatable knob assembly 1550. Housing assembly 1450 is configured to mount within inner cavity 1406 of bayonet 1402 while spool assembly 1480 is generally configured to be placed within an inner cavity 1462 of housing 1460. Knob assembly 1550 can be mechanically coupled to housing 1460 to provide tightening mechanism 1400. In some embodiments, tightening mechanism 1400 further includes a coiler assembly 1600. Rotatable knob assembly 1550 is preferably slideably movable along an axis A between two positions with respect to housing 1560.

In many embodiments, the spool assembly 1480 is off axis from the knob assembly 1550. This allows for a mechanically geared tightening mechanism 1400 which maintains a low profile relative to the surrounding mounting surface.

Bayonet 1402 may include a mounting flange 1404 useful for mounting tightening mechanism 1400 to the outside structure of an article of footwear. Preferably, flange 1404 extends circumferentially around inner and outer sections 1412 and 1414. In alternative embodiments, flange 1404 extends only partially around the circumference of sections 1412 and 1414 and may comprise one or more distinct portions. Though flange 1404 is shown with an ovular shape, it may also be rectangular, circular, square, or any of a number of other regular or irregular shapes. Flange 1404 may be similar to flange 1204 disclosed herein above.

Mechanism 1400 may be mounted on the outer surface of the footwear or underneath some or all of the outer structure of the footwear by means of stitching, hook and loop fasteners, rivets, or the like. Though tightening mechanism 1400 need not be manufactured in various components, it may be advantageous to do so. For example, portions of tightening mechanism 1400 may be manufactured at various locations and later brought together to form the completed mechanism. In one instance, bayonet 1402 may be fixed to the footwear independent from the rest of tightening mechanism 1400. The footwear with bayonet 1402 may then be transported to one or more locations where the rest of tightening mechanism 1400 is installed. In addition, modularity allows a user of an article incorporating mechanism 1400 to replace individual components when needed.

As with other embodiments disclosed herein, tightening mechanism 1400 may be mounted in a number of different positions on the footwear, including, but not limited to, on the tongue, on the ankle portion in the case of a high top such

as a hiking boot or a snow board boot, on the instep of the footwear, or on the rear of the footwear. If the footwear includes an inner boot, tightening mechanism may be mounted thereon rather than on the surface of the footwear. If the footwear includes a canopy or other covering across the instep area, the mechanism 1400 may be mounted thereon or adjacent thereto. Embodiments of tightening mechanism 1400 may be used with some or all of the various lacing components disclosed herein above. For example, tightening mechanism could be used with the multi-zone lacing system 800 shown in FIG. 28. Embodiments of mechanism 1400 could be used in place of either first 802 or second 804 lace tightening mechanisms which are shown arranged to tighten first 23a and second 23b laces.

Referring now to FIGS. 54A through 54F, there are shown a number of different views of the bayonet 1402. Side views, such as 54E and 54I, are representative of both sides of the illustrated embodiment. Generally, tightening mechanism 1400 is symmetrical along its central axis (except for indicia located in various places on the mechanism). This embodiment of bayonet 1402 is configured for use at a location remote from the tongue, or midline of the lacing system, for instance on the side of the footwear or on the rear of the footwear. Inner section 1412, disposed on the side facing the footwear, preferably extends further from flange 1404 than does section 1412 to accommodate lace exit holes 1410. FIG. 54A is a rear view of bayonet 1402. FIG. 54B is a perspective rear view of bayonet 1402 showing lace entry holes 1410. FIG. 54C is a top view of bayonet 1402 showing lace exit holes 1408. Lace 23 may enter through lace entry holes 1410 and exit lace exit holes 1408 to join with housing 1450 (see FIG. 55 for housing 1450). FIG. 54D is a perspective front view of bayonet 1402. FIG. 54E is a side view of bayonet 1402 that shows lace entry hole 1410 disposed on inner section 1412 of bayonet 1402. FIG. 54F is an end view of bayonet 1402 showing entry holes 1410. FIG. 54F also shows the general arrangement of inner section 1412 and outer section 1414 for a particular embodiment.

In a preferred embodiment, lace holes mounted on the rear or inside of bayonet 1402 facilitate lace guides disposed inside the structure of the footwear. For cosmetic or structural reasons, it may be valuable to have the lace 23 completely hidden from the surface of the footwear. As will be understood, lace entry holes 1410 could easily be located at various other positions on inner section 1412 with similar effects.

FIGS. 54I through 54K illustrate various views of an alternative bayonet 1402. This embodiment may preferably be used for a tongue mounted, front mounted, or midline centered tightening mechanism or in another location in which it might be advantageous for the lace 23 to rest on the outer surface of the structure to which tightening mechanism 1400 is mounted. Side lace entry ports 1410 are located on outer section 1414 of bayonet 1402. Accordingly, outer section 1414 is deeper than inner section 1412. Lace exit holes 1408 again allow lace 23 to pass through bayonet 1402 to couple with housing 1450. It is also possible to form bayonet 1402 with equally deep inner 1412 and outer 1414 sections.

FIGS. 55A through 55D illustrate one embodiment of housing 1450 coupled to knob assembly 1550. FIG. 55A is a rear view showing backing plate 1468 secured to housing 1462. In the illustrated embodiment, backing plate 1468 is removeably secured with screws. However, in alternative embodiments, one may use any of a number of other securing means, both removable or permanent, including

rivets, snaps, or pins as will be understood by one of skill in the art. Backing plate **1468** provides a backing to cavity **1464** in housing **1462**. As shown in FIG. **53**, spool **1482** is configured to mount within cavity **1464** and, in this embodiment, rest against backing plate **1468**. Similarly, plate **1454** is secured to the rear side of housing **1462** to provide a seat for shaft **1456** (shown in FIG. **53**). The upper surface of housing **1464** is enclosed by cover **1490** which includes access hole **1496** and housing teeth **1492**. In a preferred embodiment, cover **1490** is removeably secured to housing **1462** by a combination of screws **1492** and a lipped flange **1491**. Other securing means may be used as disclosed herein above with respect to this and other embodiments. Preferably, cover **1490** is removeably secured to allow access to the inner components of tightening mechanism **1400**, e.g. spool assembly **1480**. Such a cover facilitates replacement of the various components and may ease replacement of the lace **23** in the housing **1460** and the spool **1480**.

FIGS. **56A** through **56D** illustrate another embodiment of housing **1450** coupled to knob assembly **1550** and differ from FIGS. **55A** through **55D** only in that this illustrated embodiment includes a coiler assembly **1600**. As illustrated in FIG. **53**, coiler assembly consists of a spring boss **1608** positioned in the center of power spring **1606**. Boss **1608** and spring **1606** are positioned within coiler backing **1604** which is, in turn, secured to housing **1462** by coiler screws **1602**. Coiler assembly **1600** works in a similar fashion to the coiling systems described herein above. Central boss post **1610** engages centered engagement section **1500** of spool **1482**. As such, as spool **1482** is rotated through interaction with pinion gear **1552** of knob assembly **1550**, so too is the spring boss **1608**. As discussed above, spring boss **1608** is coupled to power spring **1606** such that pulling lace **23** from spool **1482** biases the spring **1606**. When the lace **23** is released, spring **1606** rotates spool **1482** to take up excess lace length.

In a first, also referred to herein as a coupled or an engaged position (shown in FIGS. **55F** and **56F**), knob **1550** is mechanically engaged with an internal gear mechanism located within housing assembly **1460**, as described more fully below. In a second, also referred to herein as an uncoupled or a disengaged position (shown in FIGS. **55E** and **56E**), knob **1550** is disposed upwardly or outwardly with respect to the first position and is mechanically disengaged from the gear mechanism. Disengagement of knob **1550** from the internal gear mechanism is preferably accomplished by pulling the control mechanism outward, away from mounting flange **1404**, along axis A. Alternatively, the components may be disengaged using a button or release, or a combination of a button and rotation of knob **1550**, or variations thereof, as will be appreciated by those of skill in the art and as herein described above.

Referring now to FIGS. **57A** through **57F**, elements of the spool assembly **1480** are shown in greater detail. Spool **1482** includes annular groove **1483**. The base of spool **1482** is defined by cylindrical wall **1481**. In many embodiments, spool **1482** includes at least one lace entry hole **1488**, often it includes three or more holes **1488**, and most preferably, it includes two holes **1488**. Lace **23** may be removeably secured to spool **1482** with, for example, spool screws **1484** which pass through spool screw holes **1498** (FIG. **57C**). Though it is preferable for each screw **1484** to secure an individual lace end, it is also possible for a single screw to secure multiple lace ends. Other means for releasably securing the lace to the spool are also envisioned as disclosed above. For example, lace **23** may be tied to spool **1482** as discussed with above in reference to spool **1240** of tighten-

ing mechanism **1200**. It is also possible for lace **23** to be permanently affixed to the spool by welding or the like as will be appreciated by those of skill in the art. Releasable laces advantageously allow for replacement of individual components of tightening mechanism **1400** rather than replacement of the entire structure to which it is attached.

The cylindrical wall **1481** has a diameter of generally less than about 0.75 inches, often no more than about 0.5 inches, and, in one embodiment, the diameter of the cylindrical wall **1481** is approximately 0.4 inches.

The depth of the annular groove **1483** is generally less than a $\frac{1}{2}$ inch, often less than $\frac{3}{8}$ of an inch, and, in certain embodiments, is no more than about a $\frac{1}{4}$ inch. In one embodiment, the depth is approximately $\frac{3}{16}$ of an inch. The width of the annular groove **1483** at about the opening thereof is generally no greater than about 0.25 inches, and, in one embodiment, is no more than about 0.13 inches.

Spool assembly **1480** preferably includes spool **1482** and main gear **1486**. Main gear **1486** and spool **1482** are shown manufactured separately and later mechanically attached. Inner attachment teeth **1490** are configured to matingly engage with spool teeth **1491** to secure main gear **1486** to spool **1482**. In alternative embodiments, main gear **1486** and spool **1482** are manufactured from the same piece. Spool assembly **1480** may comprise a metal. Alternatively, it may comprise a nylon or other rigid polymeric material, a ceramic, or any combination thereof.

Spool screw holes **1498** are located in spool cavity **1495**. Access to holes **1498** is facilitated by access hole **1496** and cover **1490**. As such, lace **23** can be released from spool **1482** without fully disassembling housing **1450**. Rather, removal of knob assembly **1550** permits access to access hole **1496**. In some embodiments, knob **1560** is sized to allow access to access hole **1496** without removal of knob assembly **1550**.

Knob assembly **1550** (FIG. **58**), preferably includes a cap **1572**, a knob screw **1570**, a knob **1560**, and a pinion gear **1552**. When engaged with knob **1560**, cap **1572** loosely secures knob screw **1570** such that screw **1570** remains with knob assembly **1550** when the assembly is removed from the housing assembly **1450**. Cap **1572** may include indicia **1574** or may present a smooth surface. Advantageously, cap **1572** includes knob screw access hole **1576** such that knob screw **1570** may be engaged by an appropriate tool without removal of cap **1572** from knob **1560**. Pinion gear **1552** is configured to mount within cavity **1564** of knob **1560**.

As shown in FIG. **58**, knob **1560** preferably includes pawls **1562** for engagement with housing teeth **1494**. Pawls **1562** and housing teeth **1494** are preferably configured to limit the direction of rotation of knob **1560**. Tightening mechanism **1400** may be manufactured for right or left handed operation as discussed above with reference to other embodiments. The illustrated embodiment is configured for right handed operation. Indicia are used on the components to ensure that right handed components are used with other right handed components. Knob **1560** may also include protrusions **1568** which prevent mounting a right handed knob assembly on a left handed housing. Gripping surface **1569** of knob **1560** may be manufactured separately or together with knob **1560**. Preferably, an over mold of rubber, or some other friction enhancing material, is used to provide for increased traction on the knob **1560**.

Main gear **1486** includes gear teeth **1496** for engagement with pinion gear teeth **1556**. The ratio of the main gear to the pinion gear is a factor in determining the amount of mechanical advantage achieved by tightening mechanism **1400**. In some embodiments, this gear ratio will be greater

than about 1 to 1, often at least about 2 to 1, in one embodiment at least about 3 to 1, and can be up to between about 4 to 1 or about 6 to 1. In many embodiments of the present invention, main gear **1486** will have an outside diameter of at least about 0.5 inches, often at least about 0.75 inches, and, in one embodiment, at least about 1.0 inches. The outside diameter of main gear **1486** will generally be less than about 2 inches, and preferably less than about 1.5 inches. In many embodiments, the pinion gear **1552** will have an outside diameter of at least about ¼ inches, often at least about 0.5 inches, and, in one embodiment, at least about ¾ inches. The outside diameter of pinion gear **1552** will generally be less than about 1.0 inches, and preferably less than about 0.4 inches.

In many embodiments of the present invention, the knob **1560** will have an outside diameter of at least about 0.75 inches, often at least about 1.0 inches, and, in one embodiment, at least about 1.5 inches. The outside diameter of the knob **1560** will generally be less than about 2.25 inches, and preferably less than about 1.75 inches.

The lace for cooperating with the forgoing cylindrical wall **1481** is generally small enough in diameter that the annular groove **1483** can hold at least about 14 inches, preferably at least about 18 inches, in certain embodiments at least about 22 inches, and, in one embodiment, approximately 24 inches or more of length, excluding attachment ends of the lace. At the fully wound end of the winding cycle, the outside diameter of the cylindrical stack of wound lace is less than about 100% of the diameter of the knob **1560**, and, preferably, is less than about 75% of the diameter of the knob **1560**. In one embodiment, the outer diameter of the fully wound up lace is less than about 65% of the diameter of the knob **1560**.

Mechanical advantage is achieved by a combination of gear ratio and the effective spool diameter to knob ratio. This combination of ratios results in larger mechanical advantage than either alone while maintaining a compact package. In some embodiments of the present invention, the combined ratios will be greater than 1.5 to 1, in one embodiment at least about 2 to 1, in another about 3 to 1, and in another about 4 to 1. The ratios are generally less than about 7 to 1 and are often less than about 4.5 to 1.

The maximum effective spool diameter less than about 75% of the diameter of the knob **1300** even when the spool is at its fully wound maximum, maintains sufficient leverage so that gearing or other leverage enhancing structures are not necessary. As used herein, the term effective spool diameter refers to the outside diameter of the windings of lace around the cylindrical wall **1252**, which, as will be understood by those of skill in the art, increases as additional lace is wound around the cylindrical wall **1252**.

In one embodiment, approximately 24 inches of lace will be received by 15 revolutions about the cylindrical wall **1252**. Generally, at least about 10 revolutions, often at least about 12 revolutions, and, preferably, at least about 15 revolutions of the lace around the cylindrical wall **1252** will still result in an effective spool diameter of no greater than about 65% or about 75% of the diameter of the knob **1301**.

In general, laces having an outside diameter of less than about 0.060 inches, and often less than about 0.045 inches will be used. In certain preferred embodiments, lace diameters of less than about 0.035 will be used.

FIGS. **60A** and **60B** illustrate engaged and non-engaged states of the housing assembly **1450** and knob assembly **1550**. Knob assembly **1550** is mechanically coupled to housing assembly via shaft **1456** and knob screw **1570**. Spring **1458** engages housing **1462** on one end and shaft cap

1457 on the other. When knob assembly **1550** is coupled to shaft **1456**, spring **1458** biases knob assembly **1550** in the engaged position such that pawls **1562** of knob **1560** engage housing teeth **1494** of housing cover **1490** and pinion gear teeth **1556** of pinion gear **1552** engage main gear teeth **1496** of main gear **1486**.

In the non-engaged or disengaged position, shaft cap **1457** engages flange **1466** to secure knob assembly **1550** in the disengaged position. Pushing knob **1560** back towards housing assembly **1450** disengages flange **1466** and knob assembly **1550** re-engages with housing assembly **1450**. In some embodiments, pawls **1562** remain engaged with housing teeth **1494** to prevent rotation of the knob **1560** in the reverse direction even in the disengaged position. However, pinion gear **1552** becomes disengaged from the main gear **1486** in the disengaged position, allowing free rotation of spool assembly **1480**.

Though discussed in terms of footwear, which includes, but is not limited to, ski boots, snow boots, ice skates, horseback riding boots, hiking shoes, running shoes, athletic shoes, specialty shoes, and training shoes, the closure systems disclosed herein may also provide efficient and effective closure options in a number of various different applications. Such applications may include use in closure or attachment systems on back packs and other articles for transport or carrying, belts, waistlines and/or cuffs of pants and jackets, neck straps and headbands for helmets, gloves, bindings for watersports, snow sports, and other extreme sports, or in any situation where a system for drawing two objects together is advantageous.

Although this invention has been disclosed in the context of certain preferred embodiments and examples, it will be understood by those skilled in the art that the present invention extends beyond the specifically disclosed embodiments to other alternative embodiments and/or uses of the invention and obvious modifications and equivalents thereof. In addition, while a number of variations of the invention have been shown and described in detail, other modifications, which are within the scope of this invention, will be readily apparent to those of skill in the art based upon this disclosure. It is also contemplated that various combinations or subcombinations of the specific features and aspects of the embodiments may be made and still fall within the scope of the invention. Accordingly, it should be understood that various features and aspects of the disclosed embodiments can be combined with or substituted for one another in order to form varying modes of the disclosed invention. Thus, it is intended that the scope of the present invention herein disclosed should not be limited by the particular disclosed embodiments described above, but should be determined only by a fair reading of the claims that follow.

What is claimed is:

1. A reel based closure device comprising:

a housing having:

an interior region;

an inward projecting member that divides the interior region into an upper region and a lower region; and an open bottom end;

a spool insertable within the open bottom end of the housing and rotatably positioned within the lower region of the housing, the spool being configured for gathering a tension member there around; and

a knob coupled with the housing and operably coupled with the spool so that a rotation of the knob relative to the housing causes the spool to rotate within the housing's interior region in a first direction to gather

51

the tension member around the spool, the knob being further operable to allow the spool to rotate within the housing's interior region in a second direction to release the tension member from about the spool;

wherein the inward projecting member is configured so that when the reel based closure device is assembled, the spool is confined to the lower region of the housing.

2. The reel based closure device of claim 1, wherein the inward projecting member is configured to prevent the spool from being moved axially upward into the upper region of the housing.

3. The reel based closure device of claim 1, wherein the knob is axially moveable relative to the housing to allow the spool to rotate within in the second direction within the housing's interior region.

4. The reel based closure device of claim 1, further comprising radially extending pawls that are configured to engage with housing teeth to prevent the spool from being rotated in the second direction within the housing's interior region.

5. The reel based closure device of claim 4, wherein the knob is axially moveable relative to the housing to decouple the housing teeth from the radially extending pawls and thereby allow the spool to rotate in the second direction within the housing' interior region.

6. The reel based closure device of claim 5, wherein the radially extending pawls are coupled with the knob.

7. The reel based closure device of claim 1, further comprising a bottom member or plate that is attachable to the open bottom end of the housing to enclose the spool within the lower region of the housing.

8. The reel based closure device of claim 1, further comprising an auto winding component that is configured to automatically rotate the spool in the first direction to gather the tension member around the spool.

9. The reel based closure device of claim 1, further comprising one or more gears that are operably coupled with the spool to facilitate in gathering the tension member around the spool.

10. A reel based closure device comprising:

a housing having an inward projecting member that divides an interior region into an upper region and a lower region;

a spool positioned within the lower region of the housing, the spool being configured for gathering a tension member there around;

a knob coupled with the housing and operably coupled with the spool so that a rotation of the knob relative to the housing causes the spool to rotate in a first direction to gather the tension member around the spool; and

52

teeth that are configured to engage with housing teeth to prevent the spool from being rotated in a second direction within the housing's interior region; wherein the inward projecting member confines the spool to the lower region of the housing.

11. The reel based closure device of claim 10, wherein the knob is operable to allow the spool to rotate within the housing's lower region in a second direction to release the tension member from about the spool.

12. The reel based closure device of claim 11, wherein the knob is axially moveable relative to the housing to allow the spool to rotate within in the second direction within the housing's interior region.

13. The reel based closure device of claim 10, wherein the inward projecting member is configured to prevent the spool from being moved axially upward into the upper region of the housing.

14. The reel based closure device of claim 10, further comprising a bottom member or plate that is attachable to a bottom end of the housing to enclose the spool within the lower region of the housing.

15. A method of assembling a reel based closure device comprising:

coupling a knob with a top end of a housing, wherein the housing includes a partition that divides an interior region of the housing into an upper region and a lower region; and

inserting a spool within a bottom end of the housing so that the spool is operably coupled with the knob such that rotation of the knob causes the spool to rotate in a first direction within the interior region of the housing while rotation of the spool in a second direction is prevented;

wherein the housing's partition is configured to confine the spool to the lower region of the housing so that the spool is prevented from being axially moved to the upper region of the housing.

16. The method of claim 15, further comprising coupling a bottom member or plate with a bottom end of the housing to enclose the spool within the lower region of the housing.

17. The method of claim 15, wherein the knob is operable to allow the spool to rotate within the housing's lower region in the second direction.

18. The method of claim 17, wherein the knob is axially moveable relative to the housing to allow the spool to rotate within in the second direction within the housing's interior region.

19. The method of claim 15, wherein the knob includes radially extending teeth that are configured to engage with housing teeth to prevent the spool from being rotated in the second direction within the housing's interior region.

* * * * *