



US010957203B1

(12) **United States Patent**  
**Chan et al.**

(10) **Patent No.:** **US 10,957,203 B1**  
(45) **Date of Patent:** **Mar. 23, 2021**

(54) **OCCUPANT FACING VEHICLE DISPLAY**

(71) Applicant: **Waymo LLC**, Mountain View, CA (US)

(72) Inventors: **Min Li Chan**, San Francisco, CA (US); **Philip Nemeč**, San Jose, CA (US); **Brian Douglas Cullinane**, Palo Alto, CA (US); **Julien Mercay**, Redwood City, CA (US); **Peter Crandall**, San Jose, CA (US)

(73) Assignee: **Waymo LLC**, Mountain View, CA (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/776,073**

(22) Filed: **Jan. 29, 2020**

**Related U.S. Application Data**

(63) Continuation of application No. 16/165,283, filed on Feb. 8, 2019, which is a continuation of application No. 15/089,736, filed on Apr. 4, 2016, now Pat. No. 10,140,870.

(60) Provisional application No. 62/234,814, filed on Sep. 30, 2015.

(51) **Int. Cl.**  
**G08G 1/16** (2006.01)  
**G08G 1/015** (2006.01)  
**G08G 1/04** (2006.01)  
**G08G 1/017** (2006.01)  
**G08G 1/0962** (2006.01)  
**G06K 9/00** (2006.01)  
**G01C 21/36** (2006.01)  
**B60K 35/00** (2006.01)

(52) **U.S. Cl.**

CPC ..... **G08G 1/166** (2013.01); **B60K 35/00** (2013.01); **G01C 21/36** (2013.01); **G01C 21/3697** (2013.01); **G06K 9/00805** (2013.01); **G08G 1/015** (2013.01); **G08G 1/017** (2013.01); **G08G 1/04** (2013.01); **G08G 1/0962** (2013.01); **B60K 2370/152** (2019.05); **B60K 2370/16** (2019.05); **B60K 2370/179** (2019.05); **B60K 2370/193** (2019.05); **B60K 2370/52** (2019.05)

(58) **Field of Classification Search**

CPC ..... G08G 1/166; G08G 1/015; G08G 1/017; G08G 1/04; G08G 1/0962; B60K 35/00; G01C 21/36; G01C 21/3697; G06K 9/00805

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

7,265,661 B2 9/2007 Satou  
7,710,248 B2 5/2010 Greene et al.  
7,845,677 B2 12/2010 Franke  
8,139,109 B2 3/2012 Schmiedel et al.  
8,164,543 B2 4/2012 Seder et al.  
8,195,394 B1 6/2012 Zhu  
8,260,482 B1 9/2012 Szybalski et al.  
8,346,426 B1 1/2013 Szybalski et al.  
8,427,395 B2 4/2013 Seder et al.  
8,676,431 B1 3/2014 Mariet et al.  
8,912,978 B2 12/2014 Szczerba et al.

(Continued)


*Primary Examiner* — Michael D Lang

(74) *Attorney, Agent, or Firm* — Botos Churchill IP Law

(57) **ABSTRACT**

Aspects of the present disclosure relate to a vehicle for maneuvering an occupant of the vehicle to a destination autonomously as well as providing information about the vehicle and the vehicle's environment for display to the occupant.

**21 Claims, 19 Drawing Sheets**  
**(5 of 19 Drawing Sheet(s) Filed in Color)**



(56)


References Cited

U.S. PATENT DOCUMENTS

8,924,150	B2	12/2014	Tsimhoni et al.	2014/0139676	A1	5/2014	Wierich	
8,947,219	B2	2/2015	Popovic	2014/0226015	A1	8/2014	Takatsudo et al.	
8,989,944	B1	3/2015	Agarwal et al.	2014/0270378	A1	9/2014	Aimura et al.	
9,073,484	B2	7/2015	Aimura et al.	2014/0285667	A1	9/2014	Aimura	
9,092,987	B2	7/2015	Bone et al.	2014/0330479	A1	11/2014	Dolgov et al.	
9,146,898	B2	9/2015	Ihlenburg et al.	2015/0084755	A1*	3/2015	Chen .....	G08G 1/16 340/435
9,248,834	B1	2/2016	Ferguson et al.	2015/0158430	A1	6/2015	Dollinger et al.	
9,588,340	B2	3/2017	Ng-Thow-Hing et al.	2015/0202770	A1	7/2015	Patron	
9,669,827	B1	6/2017	Ferguson et al.	2015/0210274	A1*	7/2015	Clarke .....	B62D 6/00 382/104
9,914,452	B1	3/2018	Ferguson et al.	2015/0251599	A1	9/2015	Koravadi	
2004/0051659	A1	3/2004	Garrison	2015/0296135	A1	10/2015	Wacquand et al.	
2005/0024492	A1	2/2005	Schaefer et al.	2016/0003636	A1	1/2016	Ng-Thow-Hing et al.	
2006/0020662	A1	1/2006	Robinson	2016/0005229	A1	1/2016	Lee et al.	
2006/0151223	A1	7/2006	Knoll	2016/0019807	A1	1/2016	Uchida et al.	
2006/0213714	A1	9/2006	Igawa	2016/0054452	A1*	2/2016	Cosatto .....	G01S 19/48 701/412
2008/0309468	A1	12/2008	Greene et al.	2016/0221500	A1	8/2016	Sakai et al.	
2009/0138415	A1	5/2009	Lancaster	2016/0260326	A1	9/2016	Ng-Thow-Hing et al.	
2010/0253493	A1	10/2010	Szczerba et al.	2016/0282468	A1	9/2016	Gruver et al.	
2010/0253542	A1	10/2010	Seder et al.	2016/0321628	A1	11/2016	Xu	
2012/0106869	A1	5/2012	Machitani et al.	2016/0339959	A1	11/2016	Lee	
2012/0314074	A1	12/2012	Aimura et al.	2016/0362050	A1	12/2016	Lee et al.	
2013/0044218	A1	2/2013	Matsuda et al.	2016/0365068	A1	12/2016	Sakaguchi	
2013/0181823	A1	7/2013	Staehlin et al.	2017/0057514	A1	3/2017	Toyoda et al.	
2013/0321401	A1	12/2013	Piemonte et al.	2017/0074652	A1	3/2017	Send et al.	
2013/0321628	A1	12/2013	Eng et al.	2017/0277194	A1	9/2017	Frazzoli et al.	
2014/0019005	A1	1/2014	Lee et al.	2018/0045519	A1	2/2018	Ghadiok et al.	
2014/0044310	A1	2/2014	Schamp et al.	2018/0172454	A1	6/2018	Ghadiok et al.	
2014/0132407	A1	5/2014	Kumai et al.	2018/0198955	A1*	7/2018	Watanabe .....	B60K 35/00
2014/0133700	A1	5/2014	Seki					
2014/0136414	A1	5/2014	Abhyanker					

\* cited by examiner





100

FIGURE 1




FIGURE 2




FIGURE 3A






FIGURE 3C

FIGURE 3B




FIGURE 3D






FIGURE 4







FIGURE 5



600  
FIGURE 6








FIGURE 7



800  
FIGURE 8







900

FIGURE 9






1030




1020



1010


FIGURE 10





1100  
FIGURE 11






1200

FIGURE 12






1320



1310

1300


FIGURE 13




1400

FIGURE 14






**1500**  
**FIGURE 15**



1600

FIGURE 16





1700

FIGURE 17



**OCCUPANT FACING VEHICLE DISPLAY****CROSS-REFERENCE TO RELATED APPLICATIONS**

The present application is a continuation of U.S. patent application Ser. No. 16/165,283, filed on Feb. 8, 2019, which is a continuation of U.S. patent application Ser. No. 15/089,736, filed on Apr. 4, 2016, now issued as U.S. Pat. No. 10,140,870 on Nov. 27, 2018, which claims the benefit of the filing date of U.S. Provisional Patent Application No. 62/234,814 filed Sep. 30, 2015, the entire disclosures of which are incorporated by reference herein. The present application is related to co-pending application Ser. Nos. 15/089,708, 15/089,716, and 15/089,776, entitled Occupant Facing Vehicle Display, each of which is filed concurrently herewith, and the entire disclosures of which are incorporated by reference herein.

**BACKGROUND**

Autonomous vehicles, such as vehicles that do not require a human driver, can be used to aid in the transport of passengers or items from one location to another. Such vehicles may operate in a fully autonomous mode where passengers may provide some initial input, such as a destination, and the vehicle maneuvers itself to that destination.

A key component of an autonomous vehicle is the perception system, which allows the vehicle to perceive and interpret its surroundings during a trip. When the autonomous system is engaged, the system will make various decisions during the trip, for example, speed up, slow down, stop, etc. The operator may be unaware of the calculations or “reasoning” behind why the autonomous vehicle is taking some particular action. In order to feel safe and confident, the operator may want to know what the vehicle is planning to do in the immediate future.

**BRIEF SUMMARY**

One aspect of the disclosure provides a method. The method includes receiving, by one or more processors, sensor data from one or more sensor systems configured to detect objects in an external environment of a vehicle; identifying, by the one or more processors, an object in the vehicle’s environment using the sensor data; determining, by the one or more processors, that the vehicle must yield to the identified object in order to safely maneuver the vehicle to a destination; generating, by the one or more processors, a representation of the object for a scene display depicting the external environment of the vehicle, the representation of the object including a feature having a first color; generating, by the one or more processors, an intent indicator that indicates the determination that the vehicle must yield to the identified object for an intent display depicting the intent of the vehicle with respect to the external environment of the vehicle, the intent indicator including a feature having the first color; and providing, by the one or more processors, the representation of the object and intent indicator for display to an occupant of the vehicle in order to indicate to the occupant a relationship between the representation of the object and the intent indicator through the first color.

In one example, the representation of the object is provided for display in a first area of an electronic display corresponding to the scene display, the intent indicator is provided for display in a second area of an electronic display distinct from the scene display. In another example, the

representation of the object is provided for display in a first area of an electronic display corresponding to the scene display and the intent indicator is provided for display as an overlay on the first area of the electronic display over the scene display. In another example, an area within the intent indicator which overlays a portion the scene display includes a blur effect for the portion in order to distinguish the intent indicator from the scene display. In another example, the method also includes generating a three-dimensional background scene using detailed map information corresponding to the external environment of the vehicle, and the background scene is provided as a background for the representation of the object and the intent indicator is provided as a two-dimensional image configured to be overlaid onto the three-dimensional background scene. In another example, the feature of the representation of the object is a first ring, and the feature of the intent indicator is a second ring. In another example, the feature of the representation of the object is a first ring drawn around a depiction of sensor data corresponding to the object and the feature of the intent indicator is a second ring drawn around a depiction of intent of one or more computing devices of the vehicle. In another example, the feature of the representation of the object is an abstract depiction of the object and the feature of the intent indicator is a ring drawn around a depiction of intent of one or more computing devices of the vehicle.

A further aspect of the disclosure provides a method. The method includes receiving, by one or more processors, sensor data from a sensor configured to detect objects in an external environment of a vehicle; identifying, by the one or more processors, a first object and a second object in the vehicle’s environment from the sensor data; determining, by the one or more processors, that the first object is relevant to safely maneuvering the vehicle to a destination; determining, by the one or more processors, that the second object is not currently relevant to safely maneuvering the vehicle to the destination; generating, by the one or more processors, a representation of the first object for a scene display depicting the external environment of the vehicle, the representation of the first object including a feature having a first color scheme; generating, by the one or more processors, a representation of the second object for the scene display, the representation of the second object having a second color scheme, wherein the first color scheme is configured to stand out from the second color scheme; generating, by the one or more processors, a three-dimensional background scene in the second color scheme using detailed map information corresponding to the external environment of the vehicle; and providing, by the one or more processors, the representation of the first object, the representation of the second object, and the background scene for display to an occupant of the vehicle in order to indicate to the occupant that first object is relevant to safely maneuvering the vehicle to a destination and that the second object is not currently relevant to safely maneuvering the vehicle to the destination.

In one example, the background scene includes lane lines in the second color scheme, and the representation of the first object and the representation of the second object both represent vehicles. In another example, the background scene includes static objects detected the vehicle’s external environment and included with the detailed map information. In another example, the sensor data indicates that both the first object and the second object are of a same type. In another example, the method also includes, after providing the first representation for display, determining that the first object should no longer be shown as relevant to safely



3

maneuvering the vehicle to the destination; generating, based on the determination that the first object should no longer be shown as relevant, a new representation of the first object in the second color scheme; and providing the new representation as a replacement for the representation of the first object in order to indicate to the occupant that the first object is no longer relevant to safely maneuvering the vehicle to the destination. In another example, the new representation is provided such that the representation of the first object will appear to fade into the background scene by being replaced with the new representation. In another example, after providing the second representation for display, determining that the second object is relevant to safely maneuvering the vehicle to the destination; generating a new representation of the second object in the second color scheme; and providing the new representation as a replacement for the representation of the second object in order to indicate to the occupant that the first second is relevant to safely maneuvering the vehicle to the destination. In another example, the new representation is provided such that the new representation of the first object will appear to fade in from the background scene when replacing the representation of the first object. In another example, determining that the first object is relevant to safely maneuvering the vehicle to the destination is based on a determination that the vehicle must take a specific action in order to avoid the first object for a predetermined period of time into the future. In this example, determining that the second object is not currently relevant to safely maneuvering the vehicle to the destination is based on a determination that the vehicle need not take any specific action in order to avoid the second object for a predetermined period of time into the future. In another example, the method also includes determining a route to a destination; generating a path for display in the scene display representing the route; providing the route for display in a third color scheme different from the second color scheme in order to distinguish the path from the background scene; and after providing the route for display, when the vehicle has stopped to avoid an object, providing the route for display in the second color scheme in order to indicate to the occupant that the vehicle is temporarily stopped but will shortly resume the route.

Another aspect of the disclosure provides a method. The method includes receiving, by one or more processors, sensor data from a sensor configured to detect objects in an external environment of a vehicle; identifying, by the one or more processors, a first object of a first type and a second object of a second type in the vehicle's environment from the sensor data, the first type and the second type being different; generating, by the one or more processors, a representation of the first object for a scene display depicting the external environment of the vehicle based on the first type, wherein the representation of the first object includes a display of at least a portion of the sensor data corresponding to the object and indicates an intent of one or more of the vehicle's computers with regard to the first object; generating, by the one or more processors, a representation of the second object for the scene display based on the second type, wherein the representation of the second object is an abstract representation of an object and indicates an intent of the one or more of the vehicle's computers with regard to the second object; and providing, by the one or more processors, the representation of the first object and the representation of the second object for display on an electronic display to an occupant of the vehicle in order to indicate to the occupant that the first object and the second objects are of different

4

types and that the first object is more vulnerable to an impact with the vehicle than the second object.

In one example, the representation of the first object includes a laser point cloud that provides the occupant with an indication of the particular shape of the first object. In this example, the representation of the second object is a stylized cuboid that does not provide the occupant with an indication of the particular shape of the first object. In another example, the first object is a pedestrian and the second object is a vehicle. In another example, the first type is bicyclist and the second type is vehicle. In another example, the method also includes generating a three-dimensional background scene using detailed map information corresponding to the external environment of the vehicle; and providing the three-dimensional background scene for display with the representation of the first object and the representation of the second object. In another example, the method also includes identifying a third object of a third type in the vehicle's environment from the sensor data; generating a representation of the third object that is a same representation as the representation of the second object; and providing the representation of the third object for display with the representation of the first object and the representation of the second object. In this example, the third type is a same type as the second type. In addition, the second object and the first object are vehicles. Alternatively, the third type is a different type from the second type. In addition, the second object is a car and the third object is a tractor trailer.

Yet another aspect of the disclosure provides a method. The method includes receiving, by one or more processors, sensor data from a sensor configured to detect objects in an external environment of a vehicle; generating, by the one or more processors, a background scene for display corresponding to an area of the external environment of the vehicle; identifying, by the one or more processors, a set of objects in the area from the sensor data, the objects of the set of objects corresponding to one or more of a vehicle, a pedestrian, and a bicyclist; filtering, by the one or more processors, the set of objects based on a set of heuristics; generating, by the one or more processors, a representation of each object of the filtered second set of objects; and providing, by the one or more processors, any generated representations and the background scene for display to an occupant of the vehicle on an internal electronic display of the vehicle, wherein the filtering reduces clutter on the internal electronic display.

In one example, the heuristics include a vulnerability of the object. In this example, the vulnerability of a pedestrian gives an object corresponding to a pedestrian a higher priority to be included in the filtered set of objects than an object corresponding to a vehicle. In addition or alternatively, the vulnerability of a bicyclist gives an object corresponding to a bicyclist a higher priority to be included in the filtered set of objects than an object corresponding to a vehicle. In addition or alternatively, the vulnerability of a pedestrian gives an object corresponding to a pedestrian a higher priority to be included in the filtered set of objects than an object corresponding to a bicyclist. In another example, the filtering is based on a category of action of each object of the set of objects. In another example, the filtering is based on whether an object of the set of objects is in a same lane as the vehicle. In another example, the filtering is based on whether an object of the set of objects is merging into a same lane as the vehicle. In another example, the filtering is based on whether an object of the set of objects is turning into in a same lane as the vehicle. In another



example, the filtering is based on whether the vehicle needs to take an action to avoid an object of the set of objects.

The disclosure also provides for non-transitory, tangible computer readable medium on which instructions are stored, the instructions when executed by one or more processors cause the one or more processors to perform any of the methods discussed above and herein. In addition, the disclosure also provides for systems including one or more computing devices having one or more processors configured to perform any of the methods discussed above and herein.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The patent or application file contains at least one drawing executed in color. Copies of this patent or patent application publication with color drawing(s) will be provided by the Office upon request and payment of the necessary fee.

FIG. 1 is a functional diagram of an example vehicle in accordance with aspects of the disclosure.

FIG. 2 is an example representation of detailed map information in accordance with aspects of the disclosure.

FIGS. 3A-3D are example external views of a vehicle in accordance with aspects of the disclosure.

FIG. 4 is an example internal view of a vehicle in accordance with aspects of the disclosure.

FIG. 5 is an example of a console of a vehicle in accordance with aspects of the disclosure.

FIG. 6 is a functional diagram of an example system in accordance with aspects of the disclosure.

FIG. 7 is a pictorial diagram of the system of FIG. 6 in accordance with aspects of the disclosure.

FIG. 8 is an example of an intersection in accordance with aspects of the disclosure.

FIG. 9 is an example of a display in accordance with aspects of the disclosure.

FIG. 10 is example representations of objects in accordance with aspects of the disclosure.

FIG. 11 is further example representations of objects in accordance with aspects of the disclosure.

FIG. 12 is additional example representations of objects in accordance with aspects of the disclosure.

FIG. 13 is example representations of objects in accordance with aspects of the disclosure.

FIG. 14 is an example flow diagram in accordance with aspects of the disclosure.

FIG. 15 is an example flow diagram in accordance with aspects of the disclosure.

FIG. 16 is an example flow diagram in accordance with aspects of the disclosure.

FIG. 17 is an example flow diagram in accordance with aspects of the disclosure.

#### DETAILED DESCRIPTION

The technology relates to a vehicle for maneuvering a passenger to a destination, for example taking a trip, autonomously. In order to provide a safe, enjoyable and relaxing experience for passengers, it is important to be able to relate to providing information to an occupant of a vehicle about the vehicle's surrounding environment as well as about how the vehicle's computers are reacting to those surroundings. As an example, one or more in-vehicle displays may provide information about objects in a vehicle's surroundings. How and which objects are depicted can be used in order to quickly and easily indicate information about the objects to an occupant of the vehicle. For instance, different types or

categories of objects, such as pedestrians, vehicles, bicycles, static objects, moving objects, etc., can be displayed with different image treatments and colors to indicate different types of information to an occupant.

When the vehicle operates in a semiautonomous or fully autonomous mode, the vehicle's computers may not only detect these objects, but also respond or react to them. Thus, the in-vehicle display can display information about how the vehicle's computers plan to react to those objects, or rather, the vehicle's intent. In this regard, the in-vehicle display can include a scene display for displaying a one or more representative objects and a scene corresponding to an area around the vehicle and an intent display for displaying intent of the vehicle with respect to one or more of these objects.

The scene and intent displays can be arranged in various ways. For instance, the scene display and intent display may be displayed on the same or different electronic displays of the vehicle. The intent display may therefore actually include a sub-area of the scene display such as a side or corner area of the scene display such that the intent display appears to overlap or is overlaid or superimposed on the scene display. Similarly, the intent display and the scene display may be depicted as discrete areas of an electronic display such that there is no overlap or overlay.

In addition, the scene display and intent display may be distinguished based on how the features in these displays are depicted. As an example, the scene of the scene display may be a three-dimensional (3D) image having a depth while the features of the intent display may appear to be flat or two-dimensional (2D). Alternatively, both the scene and intent displays may appear to be in 2D or 3D.

The relationship between a representative object and the vehicle's intent relative to an object may be presented using colors. As an example, a pedestrian representation shown in the scene display may have a yellow ring or other indicator, while corresponding intent to yield (or simply an acknowledgement that an object has been identified as a pedestrian) may be displayed with a corresponding yellow ring in the intent display. Similarly, a representation of a vehicle shown in the scene display with a purple ring or indicator and a corresponding intent to yield to the vehicle may be displayed in the intent display with a corresponding purple ring or indicator. Also, different types of objects can be shown with the same color in the scene display when the same intent is shown in the intent display (i.e. yielding to a bicyclist and a vehicle).

In many examples, the vehicle's perception system will detect significantly more objects in the vehicle's external environment than are useful or helpful to display to a passenger. Objects that are identified must therefore be filtered. Filtering may be achieved, for example, using various heuristics related to the vulnerability of an object (pedestrians and bicyclists having higher priority than other objects unless those other objects are doing something else interesting), the category of action for the object (moving in the same lane, merging, turning into the lane, etc.), whether the vehicle needs to take an action to avoid the object (change lanes, slow down, turn the wheels, etc.), distance from the vehicle, speed of the object, etc. In addition, certain road features, such as construction zones or traffic signal lights, may be omitted from the scene display, but the intent for those features (cautious or slower than usual driving and/or stopping) may still be indicated in the intent display. By doing so, this will reduce the amount of "clutter" in the object display.

In some instances, representations of different types or categories of objects can be shown in the scene display using



different image treatments in order to quickly and easily indicate information about the objects to a passenger in the vehicle. For example, static objects or background features, such as lane lines, crosswalks, or other road features, may be displayed in one color scheme (i.e. all blues or grays), while objects that more important, such as vehicles, pedestrians, or bicyclists may be shown in different colors in order to distinguish them from the background features. For instance, moving objects to which the vehicle is actually reacting (i.e. changing its behavior to slow down, yield, etc.) may be distinguished from the background features using different colors. At the same time, moving objects which do not affect the vehicle's behavior may also be shown in the background color scheme.

In this regard, as objects become more or less important, their prominence can be represented through changes in the color of the representations of those objects as shown in the scene display. As an example, another vehicle in front of the vehicle may change from a brighter color to a duller color when the other vehicle has turned onto a different roadway. Thus, the other vehicle will appear to "fade" into the background of the scene display. In another example, another vehicle which moves into the vehicle's lane in front of the vehicle may change from a color of the background scheme to a brighter color as it becomes more relevant to the vehicle. Similarly, the scene display may show a representation of a path of the vehicle which also fades to the background color scheme when the vehicle has come to a stop or is temporarily yielding to an object.

In addition, specific types of the moving objects may be represented in the scene display in different ways. As an example, more vulnerable types of objects may be shown using laser point clouds. Point clouds allow a passenger to potentially pick up on details of a pedestrian or bicyclist such as what direction they are facing or moving. Other less vulnerable objects, such as vehicles, may be represented using a more abstract representation such as a box, tray, or stylized cuboid. These more generic representations in combination with the point cloud representations given a passenger a good sense that the vehicle has identified different objects and can also distinguish between vulnerable and less vulnerable objects.

As shown in FIG. 1, a vehicle **100** in accordance with one aspect of the disclosure includes various components. While certain aspects of the disclosure are particularly useful in connection with specific types of vehicles, the vehicle may be any type of vehicle including, but not limited to, cars, trucks, motorcycles, busses, recreational vehicles, etc. The vehicle may have one or more computing devices, such as computing device **110** containing one or more processors **120**, memory **130** and other components typically present in general purpose computing devices.

The memory **130** stores information accessible by the one or more processors **120**, including instructions **132** and data **134** that may be executed or otherwise used by the processor **120**. The memory **130** may be of any type capable of storing information accessible by the processor, including a computing device-readable medium, or other medium that stores data that may be read with the aid of an electronic device, such as a hard-drive, memory card, ROM, RAM, DVD or other optical disks, as well as other write-capable and read-only memories. Systems and methods may include different combinations of the foregoing, whereby different portions of the instructions and data are stored on different types of media.

The instructions **132** may be any set of instructions to be executed directly (such as machine code) or indirectly (such

as scripts) by the processor. For example, the instructions may be stored as computing device code on the computing device-readable medium. In that regard, the terms "instructions" and "programs" may be used interchangeably herein.

The instructions may be stored in object code format for direct processing by the processor, or in any other computing device language including scripts or collections of independent source code modules that are interpreted on demand or compiled in advance. Functions, methods and routines of the instructions are explained in more detail below.

The data **134** may be retrieved, stored or modified by processor **120** in accordance with the instructions **132**. For instance, although the claimed subject matter is not limited by any particular data structure, the data may be stored in computing device registers, in a relational database as a table having a plurality of different fields and records, XML documents or flat files. The data may also be formatted in any computing device-readable format.

The one or more processor **120** may be any conventional processors, such as commercially available CPUs. Alternatively, the one or more processors may be a dedicated device such as an ASIC or other hardware-based processor. Although FIG. 1 functionally illustrates the processor, memory, and other elements of computing device **110** as being within the same block, it will be understood by those of ordinary skill in the art that the processor, computing device, or memory may actually include multiple processors, computing devices, or memories that may or may not be stored within the same physical housing. As an example, internal electronic display **152** may be controlled by a dedicated computing device having its own processor or central processing unit (CPU), memory, etc. which may interface with the computing device **110** via a high-bandwidth or other network connection. In some examples, this computing device may be a user interface computing device which can communicate with a user's client device. Similarly, the memory may be a hard drive or other storage media located in a housing different from that of computing device **110**. Accordingly, references to a processor or computing device will be understood to include references to a collection of processors or computing devices or memories that may or may not operate in parallel.

Computing device **110** may all of the components normally used in connection with a computing device such as the processor and memory described above as well as a user input **150** (e.g., a mouse, keyboard, touch screen and/or microphone) and various electronic displays (e.g., a monitor having a screen or any other electrical device that is operable to display information). In this example, the vehicle includes an internal electronic display **152** as well as one or more speakers **154** to provide information or audio visual experiences. In this regard, internal electronic display **152** may be located within a cabin of vehicle **100** and may be used by computing device **110** to provide information to passengers within the vehicle **100**.

In one example, computing device **110** may be an autonomous driving computing system incorporated into vehicle **100**. The autonomous driving computing system may be capable of communicating with various components of the vehicle. For example, returning to FIG. 1, computing device **110** may be in communication with various systems of vehicle **100**, such as deceleration system **160** (for controlling braking of the vehicle), acceleration system **162** (for controlling acceleration of the vehicle), steering system **164** (for controlling the orientation of the wheels and direction of the vehicle), signaling system **166** (for controlling turn signals), navigation system **168** (for navigating the vehicle to a



location or around objects), positioning system **170** (for determining the position of the vehicle), perception system **172** (for detecting objects in the vehicle's environment), and power system **174** (for example, a battery and/or gas or diesel powered engine) in order to control the movement, speed, etc. of vehicle **100** in accordance with the instructions **134** of memory **130** in an autonomous driving mode which does not require or need continuous or periodic input from a passenger of the vehicle. Again, although these systems are shown as external to computing device **110**, in actuality, these systems may also be incorporated into computing device **110**, again as an autonomous driving computing system for controlling vehicle **100**.

The computing device **110** may control the direction and speed of the vehicle by controlling various components. By way of example, computing device **110** may navigate the vehicle to a destination location completely autonomously using data from the detailed map information and navigation system **168**. Computer **110** may use the positioning system **170** to determine the vehicle's location and perception system **172** to detect and respond to objects when needed to reach the location safely. In order to do so, computer **110** may cause the vehicle to accelerate (e.g., by increasing fuel or other energy provided to the engine by acceleration system **162**), decelerate (e.g., by decreasing the fuel supplied to the engine, changing gears, and/or by applying brakes by deceleration system **160**), change direction (e.g., by turning the front or rear wheels of vehicle **100** by steering system **164**), and signal such changes (e.g., by lighting turn signals of signaling system **166**). Thus, the acceleration system **162** and deceleration system **162** may be a part of a drivetrain that includes various components between an engine of the vehicle and the wheels of the vehicle. Again, by controlling these systems, computer **110** may also control the drivetrain of the vehicle in order to maneuver the vehicle autonomously.

As an example, computing device **110** may interact with deceleration system **160** and acceleration system **162** in order to control the speed of the vehicle. Similarly, steering system **164** may be used by computing device **110** in order to control the direction of vehicle **100**. For example, if vehicle **100** configured for use on a road, such as a car or truck, the steering system may include components to control the angle of wheels to turn the vehicle. Signaling system **166** may be used by computing device **110** in order to signal the vehicle's intent to other drivers or vehicles, for example, by lighting turn signals or brake lights when needed.

Navigation system **168** may be used by computing device **110** in order to determine and follow a route to a location. In this regard, the navigation system **168** and/or data **132** may store map information, e.g., highly detailed maps identifying the shape and elevation of roadways, lane markers, intersections, crosswalks, speed limits, traffic signal lights, buildings, signs, real time traffic information, vegetation, or other such objects and information. The lane markers may include features such as solid or broken double or single lane lines, solid or broken lane lines, reflectors, etc. A given lane may be associated with left and right lane lines or other lane markers that define the boundary of the lane. Thus, most lanes may be bounded by a left edge of one lane line and a right edge of another lane line.

FIG. **2** is an example of detailed map information **200** for a section of roadway including an intersection **202**. In this example, the detailed map information **200** includes information identifying the shape, location, and other characteristics of lane lines **210**, **212**, **214**, traffic signal lights **220**, **222**, **224**, **226**, crosswalks **230**, **232**, and sidewalks **240**.

Each lane may be associated with a rail **250**, **252**, **254**, **256** which indicates the direction in which a vehicle should generally travel in the respective lane. For example, a vehicle may follow rail **252** when driving in the lane between lane lines **210** and **212**.

Although the detailed map information is depicted herein as an image-based map, the map information need not be entirely image based (for example, raster). For example, the detailed map information may include one or more roadgraphs or graph networks of information such as roads, lanes, intersections, and the connections between these features. Each feature may be stored as graph data and may be associated with information such as a geographic location and whether or not it is linked to other related features, for example, a stop sign may be linked to a road and an intersection, etc. In some examples, the associated data may include grid-based indices of a roadgraph to allow for efficient lookup of certain roadgraph features.

FIGS. **3A-3D** are examples of external views of vehicle **100**. As can be seen, vehicle **100** includes many features of a typical vehicle such as headlights **302**, windshield **303**, taillights/turn signal lights **304**, rear windshield **305**, doors **306**, side view mirrors **308**, tires and wheels **310**, and turn signal/parking lights **312**. Headlights **302**, taillights/turn signal lights **304**, and turn signal/parking lights **312** may be associated the signaling system **166**. Light bar **307** may also be associated with the signaling system **166**.

FIG. **4** is an example internal view of vehicle **100** through the opening of door **306**. In this example, there are two seats **402** for passengers with a console **404** between them. Directly in ahead of the seats **402** is a dashboard configuration **406** having a storage bin area **408** and the internal electronic display **152**. As can be readily seen, vehicle **100** does not include a steering wheel, gas (acceleration) pedal, or brake (deceleration) pedal which would allow for a semiautonomous or manual driving mode where a passenger would directly control the steering, acceleration and/or deceleration of the vehicle via the drivetrain. Rather, as described in further detail below, user input is limited to a microphone of the user input **150** (not shown), features of the console **404**, and, if available, wireless network connections. In this regard, internal electronic display **152** may merely provide information to the passenger and need not include a touch screen or other interface for user input. In other embodiments, the internal electronic display **152** may include a touch screen or other user input device for entering information by a passenger such as a destination, etc. Similarly, the vehicle may include a steering, acceleration and braking input that a passenger can use to control the vehicle in a manual or semi-autonomous driving mode.

FIG. **5** is a top down view of the console **404**. Console **404** includes various buttons for controlling features of vehicle **100**. For example, console **404** includes buttons that may be found in a typical vehicle such as buttons **502** for locking and unlocking the doors **306**, buttons **504** for raising or lowering the windows of doors **306**, buttons **506** for turning on internal lights of the vehicle, buttons **508** for controlling a heating function of seats **402**, as well as buttons **510** for controlling the volume of speakers **154**.

In addition, console **404** also includes buttons **511** for initiating communication with a remote concierge via a wireless network connection if available. Buttons **512** and **514** may also be a part of user input **150** and in this regard, allow a passenger to communicate with computer **110**, for example, to initiate or end a trip in the vehicle. In this regard, button **512** may act as an emergency stopping button that, when pushed, causes vehicle **100** to stop in a short amount



of time. Because the passenger does not have direct control of the acceleration or deceleration of vehicle **100** by way of a gas or brake pedal, button **512** may be an emergency stop button that is critical to allowing a passenger to feel safe and act quickly in case of an immediate emergency.

Button **514** may be a multi-function button. For example, button **514** may have three different states. In the first state, button **514** may be inactive, that is, if pressed, the vehicle's computer **110** would not respond by taking any particular action with regard to controlling the movement of the vehicle. In the second state, when the vehicle is ready to begin a trip, the button **514** may change to a "GO" button which a passenger uses to initiate a trip to a destination or drop off location. Once vehicle **100** is moving, button **514** may change to a third state, where the button **514** is a "PULL OVER" button which a passenger uses to initiate a non-emergency stop. In this regard, computer **110** may respond by determining a reasonable place to pull the vehicle over, rather than coming to a more sudden stop as with the emergency stop button **512**.

Thus, passenger communication with computer **110** for navigation purposes may be limited to button **514**, emergency stopping button **512**, a short range wireless communication system (such as Bluetooth LE) with the passenger's client computing device, and by sending information from the passenger's client computing device to a remote server which then relays that information to the vehicle's computer. In some examples, a passenger may provide information to the vehicle's computer **110** via voice commands through the microphone as discussed above. In addition, however, the passenger may communicate with the concierge via a phone call, an application on the passenger's client computing device, a microphone, and/or the concierge button **511** and in turn, the concierge may provide instructions control certain aspects of a vehicle via a concierge work station.

The one or more computing devices **110** of vehicle **100** may also receive or transfer information to and from other computing devices. FIGS. **6** and **7** are pictorial and functional diagrams, respectively, of an example system **600** that includes a plurality of computing devices **610**, **620**, **630**, **640** and a storage system **650** connected via a network **660**. System **600** also includes vehicle **100**, and vehicle **100A** which may be configured similarly to vehicle **100**. Although only a few vehicles and computing devices are depicted for simplicity, a typical system may include significantly more.

As shown in FIG. **6**, each of computing devices **610**, **620**, **630**, **640** may include one or more processors, memory, data and instructions. Such processors, memories, data and instructions may be configured similarly to one or more processors **120**, memory **130**, data **132**, and instructions **134** of computing device **110**.

The network **660**, and intervening nodes, may include various configurations and protocols including short range communication protocols such as Bluetooth, Bluetooth LE, the Internet, World Wide Web, intranets, virtual private networks, wide area networks, local networks, private networks using communication protocols proprietary to one or more companies, Ethernet, WiFi and HTTP, and various combinations of the foregoing. Such communication may be facilitated by any device capable of transmitting data to and from other computing devices, such as modems and wireless interfaces.

In one example, one or more computing devices **110** may include a server having a plurality of computing devices, e.g., a load balanced server farm, that exchange information with different nodes of a network for the purpose of receiving, processing and transmitting the data to and from other

computing devices. For instance, one or more computing devices **210** may include one or more server computing devices that are capable of communicating with one or more computing devices **110** of vehicle **100** or a similar computing device of vehicle **100A** as well as client computing devices **620**, **630**, **640** via the network **660**. For example, vehicles **100** and **100A** may be a part of a fleet of vehicles that can be dispatched by server computing devices to various locations. In this regard, the vehicles of the fleet may periodically send the server computing devices location information provided by the vehicle's respective positioning systems and the one or more server computing devices may track the locations of the vehicles.

In addition, server computing devices **610** may use network **660** to transmit and present information to a user, such as user **622**, **632**, **642** on a display, such as displays **624**, **634**, **644** of computing devices **620**, **630**, **640**. In this regard, computing devices **620**, **630**, **640** may be considered client computing devices.

As shown in FIG. **7**, each client computing device **620**, **630**, **640** may be a personal computing device intended for use by a user **622**, **632**, **642**, and have all of the components normally used in connection with a personal computing device including a one or more processors (e.g., a central processing unit (CPU)), memory (e.g., RAM and internal hard drives) storing data and instructions, a display such as displays **624**, **634**, **644** (e.g., a monitor having a screen, a touch-screen, a projector, a television, or other device that is operable to display information), and user input devices **626**, **636**, **646** (e.g., a mouse, keyboard, touch-screen or microphone). The client computing devices may also include a camera for recording video streams, speakers, a network interface device, and all of the components used for connecting these elements to one another.

Although the client computing devices **620**, **630**, and **640** may each comprise a full-sized personal computing device, they may alternatively comprise mobile computing devices capable of wirelessly exchanging data with a server over a network such as the Internet. By way of example only, client computing device **620** may be a mobile phone or a device such as a wireless-enabled PDA, a tablet PC, a wearable computing device or system, or a netbook that is capable of obtaining information via the Internet or other networks. In another example, client computing device **630** may be a wearable computing system, shown as a head-mounted computing system in FIG. **7**. As an example the user may input information using a small keyboard, a keypad, microphone, using visual signals with a camera, or a touch screen.

In some examples, client computing device **640** may be concierge work station used by an administrator to provide concierge services to users such as users **622** and **632**. For example, a concierge **642** may use the concierge work station **640** to communicate via a telephone call or audio connection with users through their respective client computing devices or vehicles **100** or **100A** in order to ensure the safe operation of vehicles **100** and **100A** and the safety of the users as described in further detail below. Although only a single concierge work station **640** is shown in FIGS. **6** and **7**, any number of such work stations may be included in a typical system.

Storage system **650** may store various types of information as described in more detail below. This information may be retrieved or otherwise accessed by a server computing device, such as one or more server computing devices **610**, in order to perform some or all of the features described herein. For example, the information may include user account information such as credentials (e.g., a user name



and password as in the case of a traditional single-factor authentication as well as other types of credentials typically used in multi-factor authentications such as random identifiers, biometrics, etc.) that can be used to identify a user to the one or more server computing devices. The user account information may also include personal information such as the user's name, contact information, identifying information of the user's client computing device (or devices if multiple devices are used with the same user account), as well as one or more unique signals for the user.

The storage system **650** may also store routing data for generating and evaluating routes between locations. For example, the routing information may be used to estimate how long it would take a vehicle at a first location to reach a second location. In this regard, the routing information may include map information, not necessarily as particular as the detailed map information described above, but including roads, as well as information about those road such as direction (one way, two way, etc.), orientation (North, South, etc.), speed limits, as well as traffic information identifying expected traffic conditions, etc.

As with memory **130**, storage system **250** can be of any type of computerized storage capable of storing information accessible by the server computing devices **610**, such as a hard-drive, memory card, ROM, RAM, DVD, CD-ROM, write-capable, and read-only memories. In addition, storage system **650** may include a distributed storage system where data is stored on a plurality of different storage devices which may be physically located at the same or different geographic locations. Storage system **650** may be connected to the computing devices via the network **660** as shown in FIG. **6** and/or may be directly connected to or incorporated into any of the computing devices **110**, **610**, **620**, **630**, **640**, etc.

In addition to the operations described above and illustrated in the figures, various operations will now be described. It should be understood that the following operations do not have to be performed in the precise order described below. Rather, various steps can be handled in a different order or simultaneously, and steps may also be added or omitted.

In one aspect, a user may download an application for requesting a vehicle to a client computing device. For example, users **622** and **632** may download the application via a link in an email, directly from a website, or an application store to client computing devices **620** and **630**. For example, client computing device may transmit a request for the application over the network, for example, to one or more server computing devices **610**, and in response, receive the application. The application may be installed locally at the client computing device.

The user may then use his or her client computing device to access the application and request a vehicle. As an example, a user such as user **632** may use client computing device **630** to send a request to one or more server computing devices **610** for a vehicle. The request may include information identifying a pickup location or area and/or a destination location or area. As an example, such location may be identified by street addresses, location coordinates, points of interest, etc. In response the one or more server computing devices **610** may identify and dispatch, for example based on availability and location, a vehicle to the pickup location. This dispatching may involve sending information to the vehicle identifying the user (and/or the user's client device) in order to assign the vehicle to the user (and/or the user's client computing device), the pickup location, and the destination location or area.

Once the vehicle **100** receives the information dispatching the vehicle, the vehicle's one or more computing devices **110** may maneuver the vehicle to the pickup location using the various features described above. As the vehicle approaches the user's client device, the vehicle's computer may authenticate the user's client device and also the user. When the user is authenticated, the vehicle's computing devices may automatically unlock the vehicle's doors and allow the user to enter the vehicle. The vehicle's one or more computing devices **110** may also display a welcome screen on the internal electronic display **152**. This welcome screen may provide instructions to the user (now a passenger) on how to use the vehicle. For example, the instructions may include requesting that the passenger shut the doors **306** if needed and buckle his or her seatbelt. Sensors associated with the seats, doors, and seatbelts may be used to determine if the passenger has complied. Once the passenger has complied with the instructions, he or she may press or otherwise activate button **514**. In response, the computer **110** may initiate the necessary systems to control the vehicle autonomously along a route to the destination location.

As noted above, a vehicle's one or more computing devices may maneuver the vehicle using the various systems described above. For example, FIG. **8** depicts a section of roadway **800** including an intersection **802**. Vehicle **100** is approaching intersection **802** and may be controlled, for example by one or more one or more computing devices **110** in an autonomous driving mode as described above. In this example, intersection **802** corresponds to the intersection **202** of the detailed map information **200**, and vehicle is generally following rail **250** in order to follow a route towards the destination (both not shown in FIG. **8**). In this example, lane lines **810**, **812**, and **814** correspond to the shape, location, and other characteristics of lane lines **210**, **212**, and **214**, respectively. Similarly crosswalks **830** and **832** correspond to the shape, location, and other characteristics of crosswalks **230** and **232**, respectively, sidewalks **840** correspond to sidewalks **240**, and traffic signal lights **822**, **824**, and **826** correspond to the shape, location, and other characteristics of traffic signal lights **222**, **224** and **226**.

As the vehicle is maneuvered to the destination, the vehicle's perception system **172** may detect and identify objects in the vehicle's environment. For instance, the vehicle's computing devices **110** may detect and identify lane lines **810**, **812**, and **814**, crosswalks **830** and **832**, sidewalks **840**, and traffic signal lights **822**, **824**, and **826**. In addition to these "static" features, the vehicle's perception system may also detect, track, and identify various other objects such as vehicles **850-858** and pedestrians **860**, **862**. In other words, the perception system **172** may determine the general shape and orientation as well as speed of these objects by observing these objects over a brief period of time.

When the vehicle operates in a semiautonomous or fully autonomous mode, the vehicle's computers may not only detect these objects, but also respond or react to them. For instance, this can include yielding to an object, stopping, maneuvering around an object, etc. Returning to the example of FIG. **8**, vehicle **100** may need to yield to group of pedestrians **860** in crosswalk **830** as well as vehicle **852** which is passing through intersection **802** in the direction of pedestrians **860** in order to continue its route along rail **250** safely. In addition, the vehicle may have to respond to a red light at traffic signal light **826**, but at the same time, may be permitted (according to the traffic laws which govern the intersection defined in the detailed map information **200**) to make a right hand turn during the red light after properly



stopping and yielding to other traffic. While the vehicle's computing devices **110** may detect and identify vehicles **850** and **854-858** as well as pedestrian **862**, the vehicle's computing devices **110** may determine that no change to the vehicle's current actions is likely to be needed in the immediate future (such as the next few seconds or more or less). In other words, it is unlikely given the location, orientation, and speeds of vehicles **850** and **854-858** and pedestrian **862** and the route that vehicle **100** is following along rail **250**, that vehicle **100** would need to take any action in order to avoid these objects in the immediate future.

An in-vehicle display can display information about how the vehicle's computers plan to react to those objects, or rather, the vehicle's intent. In this regard, the in-vehicle display can include a scene display for displaying a one or more representative objects and a scene corresponding to an area around the vehicle and an intent display for displaying intent of the vehicle with respect to one or more of these objects.

FIG. **9** is an example display **900** which may be presented to an occupant of the vehicle on internal electronic display **152** while the vehicle is being maneuvered to the destination. In this example, display **900** includes a scene display **910** which displays a scene corresponding to section of roadway **800** of FIG. **8**. This scene includes a background image displayed in a background color scheme, here in blues and silvers. The background images corresponds to features of the detailed map information **200** such as lane lines **910**, **912**, and **914** and crosswalks **930** and **932**, which correspond to lane lines **210**, **212**, and **214** and crosswalks **230** and **232**, respectively. In addition, the display **910** includes representations of various objects **920-928** which correspond to vehicles **850**, **852**, **856**, and **858** as well as group of pedestrians **860**, respectively. The display **910** also includes a representation **902** of vehicle **100** and a representation **960** of a path corresponding to rail **250** that the vehicle is currently following to reach the destination.

In addition to scene display **910**, display **900** also includes an intent display **940** for display the vehicle's intent with regard to various of the representations in the scene display **910**. For instance, intent display **940** includes a plurality of two-dimensional intent icons **950**, **952**, and **954**. Although the term "icon" is used throughout to refer to a representations of the vehicle's intent, this term as used herein may include other types of representations, such as photographs, jpegs, pdfs, or other types of images.

In the example of intent display **940**, intent icon **950** indicates that the vehicle's computing devices **110** recognize that traffic signal light **826** is currently displaying a red (stop) light such that vehicle **100** must stop before intersection **802** and yield to other objects crossing intersection **802** in order to make a lawful right turn as discussed above. Intent icons **952** and **954** indicate that the vehicle's computing devices intend to yield to group of pedestrians **860** represented by representations **928** and to vehicle **852** represented by representation **922**.

The scene and intent displays can be arranged in various ways. For instance, the scene display and intent display may be displayed on the same or different electronic displays of the vehicle. The intent display may therefore actually include a sub-area of the scene display such as a side or corner area of the scene display such that the intent display appears to overlap or is overlaid or superimposed on the scene display. Similarly, the intent display and the scene

display may be depicted as discrete areas of an electronic display such that there is no overlap or overlay as shown in FIG. **9**.

FIG. **10** is an example of three different intent displays **1010**, **1020**, and **1030**, providing the different information from intent display **950** of FIG. **9**, but a similar arrangement of two intent icons and one traffic signal light icon. In the example of intent display **1010**, the icons are shown on a black field as if the intent display **1010** were separately arranged from intent display **910**, such as on another internal electronic display of vehicle **100** or as a discrete portion of display **900**. Intent displays **1020** and **1030** are displayed as if superimposed over scene display **910** allowing for features of the background scene to be displayed "behind" the icons of the intent display. Display **1030** shows the background features behind the icons with a blur to further distinguish the icons from the background features.

In addition, the scene display and intent display may be distinguished based on how the features in these displays are depicted. As an example, the scene of the scene display **910** may be a three-dimensional (3D) image having a depth while the features of the intent display **940** may appear to be flat or two-dimensional (2D). Alternatively, both the scene and intent displays may appear to be in 2D or 3D.

The relationship between a representative object and the vehicle's intent relative to an object may be presented using colors. As an example, pedestrian representation **928** shown in the scene display **910** may have a yellow ring or other indicator such as a pointer or marker located nearby the representation. At the same time, the corresponding intent icon **954**, indicating the vehicle's computing devices **110**'s intent to yield (or simply an acknowledgement that an object has been identified as a pedestrian), may be displayed in the same or a similar color (here yellow) or with a ring in a same or a similar color (here yellow) in the intent display **940**. This may indicate the vehicle's computing devices **110**'s intent to yield to the group of pedestrians **862** in a way in which an occupant of vehicle **100** may quickly and easily recognize. Although not shown in the example of FIG. **9**, the intent display **940** may also be used to identify corresponding intent icons for other types of objects such as bicyclists, constructions zone objects like cones or barriers, etc.

In other examples, objects need not include rings or other markers to identify corresponding intent icons, but may be shown in a corresponding color as the intent icon or a ring of the intent icon. For instance, representation **922** of vehicle **952** is shown in the scene display **910** in purple to correspond with the purple ring of intent icon **952** in the intent display **940**. This may indicate the vehicle's computing devices **110**'s intent to yield to the vehicle **852** in a way in which an occupant of vehicle **100** may quickly and easily recognize. Similarly, turning to FIG. **13**, representation **1310** of pedestrians is shown in silver to blend with the background color scheme as these pedestrians do not correspond to an intent icon, while representation **1320** of pedestrians is shown highlighted in yellow to correspond to the yellow ring and color of an intent icon, such as intent icon **954**. The corresponding color of the representation may be instead of or in addition to a colored ring or marker (as in the example of scene display **910**).

Also, representations of different types of objects can be shown in the same color and/or with the same color ring or marker in the scene display when the same intent is indicated for those representations in the intent display. As an example, if the vehicle **100** is yielding to both a bicyclist and a vehicle, both representations of these objects may be shown in purple and/or with a purple ring. However, in some



cases, such as in the example of display **900**, it may be clearer and more reassuring to the occupant if different intent icons are used for different objects to enable the occupant to understand that the vehicle's computing devices **110** have recognized the differences in how the vehicle should respond to a group of pedestrians (shown by representation **928**) and a vehicle (shown by representation **922**). Of course, the colors, shapes, markers, and icons used may be changed according to the number of objects and intent or aesthetics of the display.

In addition, to distinguish between intents for different objects of a similar type, the rings and/or colors for the different intent icons and representations may be displayed in different colors. As an example, a ring around one pedestrian may correspond in color to a ring for an intent to yield icon while a ring around another pedestrian may correspond in color to a ring for an intent to stop icon (not shown).

Of course, the colors and shapes may be changed according to the number of objects and intent or aesthetics of the display. For instance, in addition or alternatively to the examples of yellows and purples discussed above, reds, greens, oranges, and other such colors may also be used. In addition, although the example of FIG. **9** depicts the same shades of yellow and purple between the scene and intent displays, similar hues of the same color (a lighter shade of red and a corresponding darker shade of red, etc.) may also be used to identify correspondences between the intent icons in the intent display and representations in the scene display. Similarly, in addition or alternatively to the rings and shapes discussed above, other shapes, such as polygons, etc. may also be used.

In many examples, the vehicle's perception system **172** will detect significantly more objects in the vehicle's external environment than are useful or helpful to display to a passenger or occupant of the vehicle. Objects that are identified must therefore be filtered before representations of those objects are included in the display **900**. By doing so, this will reduce the amount of "clutter" in the object display.

Filtering may be achieved, for example, using various heuristics related to the vulnerability of an object (pedestrians and bicyclists having higher priority than other objects unless those other objects are doing something else interesting), the category of action for the object (moving in the same lane, merging, turning into the lane, etc.), whether the vehicle needs to take an action to avoid the object (change lanes, slow down, turn the wheels, etc.), distance from the vehicle, speed of the object, etc. For example, representations of pedestrian **860** and vehicle **854** are not included in the scene display **910**. In this example, even though pedestrian **860** is detected by vehicle **100**, it may be out of a field of view presented in the scene display **910**. Alternatively, if pedestrian **860** is within the field of view presented in the scene display, a representation of pedestrian **860** may not be displayed in the scene display because the pedestrian is not currently relevant to the vehicle, or rather, the location of pedestrian relative to the vehicle **100** is unlikely to affect vehicle **100**'s route to the destination or require some action by the one or more computing devices **110** in order to safely navigate vehicle **100** along the route. In other words, it is unlikely that the vehicle **100** would need to respond to this pedestrian. In yet another alternative, even where pedestrian is within the field of view but not currently relevant (as discussed above), a representation of the pedestrian may be included because of the vulnerable nature of pedestrians. In doing so, this may allow an occupant of the vehicle to feel

more comfortable in that the vehicle is able to recognize pedestrians in the vehicle's environment.

Returning to the example of FIG. **9**, a representation of vehicle **854** may not be included in the scene display because the location, orientation, and speed of vehicle **854** relative to vehicle **100** is unlikely to affect vehicle **100** as it continues along the route, in other words, vehicle **100** is not likely to need to respond to vehicle **854**. At the same time, representations of vehicle **856** and **858** are included in the scene display **910** because in this example, even though vehicles **856** and **858** are moving towards intersection **802** and in a different direction from vehicle **100** such that vehicle **100** is unlikely to need to respond to vehicles **856** and **858**, vehicle **100** is actually approaching vehicles **856** and **858**. In other words, vehicle **100** will be getting closer to these vehicles in the near future, while vehicle **854** will likely continue to move away from vehicle **100**. Thus, in this situation, representations **924** and **926** may be included in the scene display in order to indicate that the vehicle has detected these vehicles. Of course, once vehicles **856** and **858** move into intersection **802** and vehicle **100** continues further down rail **250**, vehicles **856** and **858** will become less relevant to vehicle **100**. At this time, representations **924** and **924** may fade or disappear from the scene display **910** indicating that vehicles **856** and **858** have become less relevant to the vehicle **100**.

In addition, certain road features identified the detailed map information, such as construction zones or traffic signal lights, may be omitted from the scene display, but the intent for those features (cautious or slower than usual driving and/or stopping) may still be indicated in the intent display. For example, representations of traffic signal lights **822**, **824**, and **826** are not included in the scene display **910** in order to reduce the amount of clutter and unnecessary items shown in the display **900**. However, at the same time, relevant information regarding traffic signal lights which are of importance or relevance to the vehicle **100** given its current position, may be included in the intent display **940**, as can be seen from intent icon **950**.

In some instances, representations of different types or categories of objects can be shown in the scene display using different image treatments in order to quickly and easily indicate information about the objects to a passenger in the vehicle. For example, representations of static objects or background features from the detailed map information **200**, such as lane lines **910**, **912**, and **914**, crosswalks **930** and **932**, or other road features, may be displayed in one color scheme (i.e. all blues or grays), while representations of objects not in the detailed map information that are relevant to vehicle **100**, such as representation **922** of vehicle **852**, representation **928** of group of pedestrians **862**, or bicyclists (not shown) may be shown in different colors in order to distinguish them from the background scene and color scheme.

For instance, representations of moving objects, such as representations **922** and **928** to which the vehicle is actually reacting (i.e. changing its behavior to slow down, yield, etc.) may be distinguished from the background features using different colors. This may indicate to the occupant that these objects are of relevant for controlling the vehicle **100** safely as discussed above. At the same time, moving objects which do not affect the vehicle's behavior may also be shown in the background color scheme such as representations **920**, **924**, and **926** to indicate that they are not currently relevant to controlling the vehicle **100** safely.

FIG. **11** is an example view **1100** of a representation **1110** of a vehicle (similar to representation **922**) to which vehicle



100 is reacting and a representation 1110 similar to representation 920) of a vehicle to which vehicle is not reacting. In this example, representation 1120 is displayed in a first color, here purple which stands out from the background color scheme of display 900, and representation 1130 is shown in a different second color, here blue, which blends or corresponds with the background color scheme of display 900.

FIG. 12 is an example view 1200 of rings 1210 and 1210 which would surround a representation of a pedestrian, bicyclist or other object (similar to representation 928) to which vehicle 100 is reacting and rings 1220 and 1222 of a pedestrian, bicyclist or other object to which vehicle is not reacting. In this example, rings 1210 and 1212 are displayed in a first color, here yellow which stands out from the background color scheme of display 900, and rings 1220 and 1222 are shown in a different second color, here silver, which blends or corresponds with the background color scheme of display 900.

In this regard, as objects become more or less important, their prominence or relevance to controlling the vehicle 100 can be represented through changes in the color of the representations of those objects as shown in the scene display. As an example, another vehicle in front of the vehicle may change from a brighter color to a duller color when the other vehicle has turned onto a different roadway. This may be because the other vehicle has become less or no longer relevant to controlling vehicle 100 and/or the vehicle's computer has determined that the other vehicle no longer should be displayed as relevant. Thus, the other vehicle will appear to "fade" into the background of the scene display for example by changing from the representation 1110 to the representation 1120 of FIG. 11. In another example, another vehicle which moves into the vehicle's lane in front of the vehicle may change from a color of the background scheme to a brighter color as it becomes more relevant to the vehicle, for example, by changing from the representation 1120 to the representation 1110. In this example, the other vehicle goes from being not relevant to currently relevant to controlling the vehicle 100.

In another example, turning to FIG. 12, pedestrian rings 1210 and 1212 are used to highlight representations of pedestrians to which the vehicle 100 is responding whereas rings 1220 and 1222 are silver and allow the representations to blend into the background color scheme. By switching between these different colored rings, the vehicle's computing devices 110 can easily convey the relevant or importance of these objects to the actions of the vehicle 100. Alternatively, rather than changing colors to blend into or stand out from the background color scheme, the rings may simply disappear or appear.

Similarly, the scene display 910 may show a representation 960 of a path of the vehicle which also fades to the background color scheme when the vehicle has come to a stop or is temporarily yielding to an object. The path may correspond to rail 250 or a portion of a route to the destination. In this regard, the changing of the color of the path from one color that stands out from the background scene to another that blends with the background scene may easily indicate to the occupant that the stop or yield maneuver is a temporary one and that the vehicle will resume the route shortly.

In addition, specific types of the moving objects may be represented in the scene display in different ways. As an example, more vulnerable types of objects, such as pedestrians and bicyclists, may be shown using laser point clouds, as in the example of representation 920 of FIG. 9. Point

clouds allow an occupant to potentially pick up on details of a pedestrian or bicyclist such as what direction they are facing or moving. Other less vulnerable objects, such as vehicles, may be represented using a more abstract representation such as a box, tray or stylized cuboid as in the examples of representations 920-926. In this regard, different types of vehicles, such as passenger car 856 and tractor trailer 858, are depicted in the scene display with the same types of generic representations 924 and 926. In other words, the representations 924 and 926 are the same shape and size relative to their three-dimensional distance from the representation 902 of vehicle 100 in the scene display 910 (i.e. representations of objects located further from representation 902 of vehicle 100 will appear smaller than representations of objects located closer to representation 902 of vehicle 100). In this regard, by viewing the scene display, the occupant would recognize that the representations 924 and 926 in the scene display 910 correspond to vehicles but not the specific types of those vehicles. These more generic representations in combination with the point cloud representations given an occupant a good sense that the vehicle has identified different objects and can also distinguish between vulnerable and less vulnerable objects.

In order to further indicate the relationship between an object in the scene display with an intent icon in the intent display and the direction of the object relative to the vehicle, additional color cues may be used. For instance, as shown in FIG. 9, a series of rings or circles may be displayed in the scene display 910 in order to indicate different distances from the representation 902. Sections of these circles may be highlighted in order to indicate the direction of an object. The highlighting may be in a coordinating color as a feature of the object that is colored to coordinate with an intent icon. For example, section 970 is highlighted in yellow to indicate the direction of group of pedestrians 860 represented by representations 928 relative to the representation 902 of vehicle 101. This yellow color further indicates the relationship of the representation 920 with intent icon 954, also shown in yellow. Similarly, section 972 is highlighted in purple to indicate the direction vehicle 852 represented by representation 922 relative to the representation 902 of vehicle 101. Again, this purple color further indicates the relationship of the representation 922 with intent icon 952, also shown in purple. In addition, the tips or narrow ends of these sections are oriented towards the representation 902 and the wide ends are oriented towards representations 922 and 928.

FIG. 14 is an example flow diagram 1400 that may be performed by one or more of the computing devices 110. In this example, sensor data is received from a sensor configured to detect objects in an external environment of a vehicle at block 1410. An object in the vehicle's environment is identified at block 1420. It is determined that the vehicle must yield to the identified object in order to safely maneuver the vehicle to a destination at block 1430. A representation of the object is generated for a scene display depicting the external environment of the vehicle at block 1440. The representation of the object includes a feature having a first color. An intent indicator that indicates the determination that the vehicle must yield to the identified object is generated for an intent display depicting the intent of the vehicle with respect to the external environment of the vehicle at block 1450. The intent indicator includes a feature having the first color. The representation of the object and intent indicator are provided for display to an occupant of the vehicle in order to indicate to the occupant a relationship



between the representation of the object and the intent indicator through the first color at block 1460.

FIG. 15 is an example flow diagram 1500 that may be performed by one or more of the computing devices 110. In this example, sensor data is received from a sensor configured to detect objects in an external environment of a vehicle at block 1510. A first object and a second object are identified in the vehicle's environment from the sensor data at block 1520. It is determined that the first object is relevant to safely maneuvering the vehicle to a destination and that the second object is not currently relevant to safely maneuvering the vehicle to the destination at block 1530. A representation of the first object is generated for a scene display depicting the external environment of the vehicle at block 1540. The representation of the first object includes a feature having a first color scheme. A representation of the second object is generated for the scene display at block 1550. The representation of the second object has a second color scheme. The first color scheme is configured to stand out from the second color scheme. A three-dimensional background scene is generated in the second color scheme using detailed map information corresponding to the external environment of the vehicle at block 1560. The representation of the first object, the representation of the second object, and the background scene are provided for display to an occupant of the vehicle in order to indicate to the occupant that first object is relevant to safely maneuvering the vehicle to a destination and that the second object is not currently relevant to safely maneuvering the vehicle to the destination.

FIG. 16 is an example flow diagram 1600 that may be performed by one or more of the computing devices 110. In this example, sensor data is received from a sensor configured to detect objects in an external environment of a vehicle at block 1610. A first object of a first type and a second object of a second type are identified in the vehicle's environment from the sensor data at block 1620. The first type and the second type are different. A representation of the first object is generated for a scene display depicting the external environment of the vehicle based on the first type at block 1630. The representation of the first object includes a display of at least a portion of the sensor data corresponding to the object and indicates an intent of one or more of the vehicle's computers with regard to the first object. A representation of the second object for the scene display based on the second type is generated at block 1640. The representation of the second object is an abstract representation of an object and indicates an intent of the one or more of the vehicle's computers with regard to the second object. The representation of the first object and the representation of the second object are provided for display on an electronic display to an occupant of the vehicle in order to indicate to the occupant that the first object and the second objects are of different types and that the first object is more vulnerable to an impact with the vehicle than the second object at block 1650.

FIG. 17 is an example flow diagram 1700 that may be performed by one or more of the computing devices 110. In this example, sensor data is received from a sensor configured to detect objects in an external environment of a vehicle at block 1710. A background scene is generated for display corresponding to an area of the external environment of the vehicle at block 1720. A set of objects in the area is identified from the sensor data at block 1730. The objects of the set of objects correspond to one or more of a vehicle, a pedestrian, and a bicyclist. The set of objects is filtered based on a set of heuristics at block 1740. A representation of each object

of the filtered second set of objects is generated at block 1750. Any generated representations and the background scene are provided for display to an occupant of the vehicle on an internal electronic display of the vehicle at block 1760. The filtering reduces clutter on the internal electronic display.

Although the examples above relate to a particular configuration for the images depicted on the internal electronic display 152, various other arrangements and features may be used to increase safety and comfort of occupants of the vehicle.

Unless otherwise stated, the foregoing alternative examples are not mutually exclusive, but may be implemented in various combinations to achieve unique advantages. As these and other variations and combinations of the features discussed above can be utilized without departing from the subject matter defined by the claims, the foregoing description of the embodiments should be taken by way of illustration rather than by way of limitation of the subject matter defined by the claims. In addition, the provision of the examples described herein, as well as clauses phrased as "such as," "including" and the like, should not be interpreted as limiting the subject matter of the claims to the specific examples; rather, the examples are intended to illustrate only one of many possible embodiments. Further, the same reference numbers in different drawings can identify the same or similar elements.

The invention claimed is:

1. A method comprising:

- receiving, by one or more processors, sensor data from a sensor of a first vehicle, the sensor being configured to detect objects in an external environment of the first vehicle;
- identifying from the sensor data, by the one or more processors, a plurality of moving objects in the external environment;
- identifying from the sensor data, by the one or more processors, a second vehicle in the external environment;
- generating, by the one or more processors, a representation of a scene depicting the external environment including:
  - a representation of each of the plurality of moving objects;
  - a representation of the first vehicle; and
  - a representation of the second vehicle, wherein the representation of the scene distinguishes one or more of the plurality of moving objects, to which the first vehicle reacts, from one or more of the plurality of moving objects to which the first vehicle does not react, and wherein the representation of the second vehicle changes based on its relevance to the first vehicle; and
- providing, by the one or more processors, the representation of the scene for display to an occupant of the first vehicle.

2. The method of claim 1, wherein brightness of a color of the representation of the second vehicle increases when the relevance increases.

3. The method of claim 2, wherein brightness of a color of the representation of the second vehicle decreases when the relevance decrease.

4. The method of claim 1, wherein the representation of the one or more moving objects includes a representation of a pedestrian with a ring arranged at a bottom of the representation of the pedestrian.



## 23

5. The method of claim 4, wherein the ring is a yellow color scheme.

6. The method of claim 1, wherein the representation of the second vehicle is one of a box, tray or stylized cuboid.

7. The method of claim 1, wherein the representation of the scene includes a blue and gray color background scheme.

8. The method of claim 1, wherein the representation of the scene further includes representations of lane lines.

9. The method of claim 1, wherein the representation of the scene includes a representation of a crosswalk.

10. The method of claim 1, wherein the representation of the scene further includes a representation of the first vehicle having an autonomous driving mode, and wherein the representation of the scene is from a perspective behind the first vehicle.

11. The method of claim 10, wherein the representation of the scene further includes a representation of a path which the first vehicle is currently following.

12. The method of claim 1, wherein the representation of the scene further includes an icon indicating that the first vehicle recognizes a traffic signal light.

13. The method of claim 12, wherein the icon further indicates that the first vehicle recognizes a state of the traffic signal light.

14. The method of claim 13, wherein the icon further indicates that the first vehicle recognizes the state of the traffic signal light as red.

15. The method of claim 12, wherein the representation of the scene appears as a three-dimensional (3D) image having a depth while the icon appears as two-dimensional (2D).

16. The method of claim 12, wherein the representation of the scene is arranged such that the icon is overlaid onto a background scene.

17. The method of claim 12, wherein the representation of the scene further includes a representation of a traffic signal light.

## 24

18. The method of claim 17, wherein the representation of the traffic signal light indicates that the vehicle must stop before an intersection.

19. The method of claim 1, wherein the representation of each of the plurality of moving objects includes an object having a color scheme which blends into a color background scene.

20. The method claim 1, wherein the representation of the second vehicle depicts a length, width and height of the second vehicle.

21. A system comprising:  
a display; and

one or more processors configured to:

receive sensor data from a sensor configured to detect

objects in an external environment of a first vehicle;

identify from the sensor data a plurality of moving

objects in the external environment;

identify from the sensor data a second vehicle in the external environment;

generate a representation of a scene depicting the external environment including:

a representation of each of the plurality of moving objects;

a representation of the first vehicle; and

a representation of the second vehicle,

wherein the representation of the scene distinguishes

one or more of the plurality of moving objects, to

which the first vehicle reacts, from one or more of

the plurality of moving objects to which the first

vehicle does not react, and

wherein the representation of the second vehicle changes based on its relevance to the first vehicle;

and

provide the representation of the scene for display on the display to an occupant of the first vehicle.

\* \* \* \* \*