

US010962048B2

(12) **United States Patent**  
**Takata et al.**

(10) **Patent No.:** **US 10,962,048 B2**  
(45) **Date of Patent:** **Mar. 30, 2021**

(54) **HALF BEARING**

(71) Applicant: **TAIHO KOGYO CO., LTD.**, Toyota (JP)  
(72) Inventors: **Hiroki Takata**, Toyota (JP); **Yuichiro Kajiki**, Toyota (JP)  
(73) Assignee: **TAIHO KOGYO CO., LTD.**  
(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/344,314**  
(22) PCT Filed: **Oct. 31, 2017**  
(86) PCT No.: **PCT/JP2017/039357**  
§ 371 (c)(1),  
(2) Date: **Apr. 23, 2019**  
(87) PCT Pub. No.: **WO2018/079839**  
PCT Pub. Date: **May 3, 2018**

(65) **Prior Publication Data**  
US 2019/0271355 A1 Sep. 5, 2019

(30) **Foreign Application Priority Data**  
Oct. 31, 2016 (JP) ..... JP2016-213389

(51) **Int. Cl.**  
**F16C 33/10** (2006.01)  
**F16C 9/02** (2006.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... **F16C 9/02** (2013.01); **F16C 9/04** (2013.01); **F16C 17/02** (2013.01); **F16C 33/10** (2013.01); **F16C 33/1065** (2013.01)

(58) **Field of Classification Search**  
CPC ..... F16C 33/10; F16C 33/1065; F16C 9/02; F16C 9/04; F16C 17/02  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,234,870 B2 6/2007 Kitahara et al.  
9,879,725 B2\* 1/2018 Ashihara ..... F16C 17/02  
(Continued)

FOREIGN PATENT DOCUMENTS

JP S55-135223 A 10/1980  
JP 2005249024 A 9/2005  
(Continued)

OTHER PUBLICATIONS


Japanese Office Action for Application No. 2016-213389 dated Dec. 10, 2019 with English translation (8 pages).  
(Continued)

*Primary Examiner* — Alan B Waits  
(74) *Attorney, Agent, or Firm* — Harness, Dickey & Pierce, P.L.C.

(57) **ABSTRACT**

A half bearing includes circumferentially extending first and second grooves on the inner circumferential surface. The circumferential end of the first groove, on the rotational upstream side of the shaft, has an inclination angle  $\theta_1$  of  $135^\circ$  formed by: a first imaginary line connecting the inner circumferential surface end of a mating surface and the origin of an outer circumferential surface; and a second imaginary line connecting the end of the first groove and the origin of the outer circumferential surface. The circumferential end of the second groove, on the rotational upstream side of the shaft, has an inclination angle  $\theta_2$  of  $135^\circ$  formed by: a first imaginary line connecting the inner circumferential surface end of the mating surface and the origin of the inner circumferential surface; and a third imaginary line connecting the end of the second groove and the origin of the outer circumferential surface.

**8 Claims, 3 Drawing Sheets**



- (51) **Int. Cl.**  
*F16C 17/02* (2006.01)  
*F16C 9/04* (2006.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

9,933,007 B2 \* 4/2018 Ashihara ..... F16C 33/1065  
9,958,007 B2 \* 5/2018 Ashihara ..... F16C 17/022  
9,964,140 B2 5/2018 Ashihara et al.  
10,054,153 B2 \* 8/2018 Seki ..... F16C 17/02  
2004/0062458 A1 \* 4/2004 Mian ..... F16C 9/02  
384/294  
2005/0196084 A1 \* 9/2005 Kitahara ..... F16C 9/02  
384/288  
2016/0195127 A1 \* 7/2016 Ashihara ..... F16C 9/02  
384/288  
2016/0273577 A1 9/2016 Ashihara et al.  
2018/0031030 A1 2/2018 Sekil et al.

FOREIGN PATENT DOCUMENTS

JP 2007-285456 A 11/2007  
JP 2015094428 A 5/2015  
JP 2016033414 A 3/2016  
WO WO-2012158749 A1 11/2012  
WO WO-2016136997 A1 9/2016

OTHER PUBLICATIONS

Office Action for Japanese Patent Application No. 2016-213389  
dated Jul. 7, 2020 (9 pages).

\* cited by examiner




FIG. 1




FIG. 2






FIG. 3




FIG. 4




FIG. 5




FIG. 6



**1****HALF BEARING**CROSS-REFERENCE TO RELATED  
APPLICATIONS

This application is a U.S. National Stage Application of International Application No. PCT/JP2017/039357, filed on Oct. 31, 2017, which claims priority to Japanese Application No. 2016-213389, filed on Oct. 31, 2016. The entire disclosures of the above applications are incorporated herein by reference.

## TECHNICAL FIELD

The present invention relates to technology for reducing the amount of lubricating oil that leaks from a half bearing.

## RELATED ART

In an internal-combustion engine, sliding bearings, which are a pair of semi-cylindrical bearings (called “half bearings”) abutting against each other, are used to support a crankshaft (main shaft) or a connecting rod shaft so as to be rotatable. In such bearings, lubricating oil is supplied to a gap between a shaft and the bearings, an oil film is formed and the shaft moves away from the bearings as a result of the shaft rotating, and the shaft is supported by the oil film so as to rotate.

Lubricating oil leaks from the bearings, and various inventions have been made to prevent lubricating oil from leaking. For example, JP 2015-94428A 1 discloses a lower half bearing that has a groove extending along a circumferential direction of the inner circumferential surface, formed on the downstream side in the rotational direction of the shaft, in an end portion in the axial direction.

JP 2015-94428A discloses a half bearing having a groove on the inner circumferential surface, on the downstream side in the rotational direction of the shaft, with respect to a central position in the circumferential direction. However, there is room for improvement regarding positioning the ends of the groove, in order to prevent lubricating oil from leaking.

The present invention aims to reduce the amount of leaked lubricating oil, using a half bearing that has a groove on the inner circumferential surface.

## SUMMARY

The present invention provides a half bearing that has a semi-cylindrical shape with an inner circumferential surface along which a shaft slides, the half bearing including: a groove that is provided on the inner circumferential surface and extends along a circumferential direction of the inner circumferential surface. An angle formed by: a line that connects an end on the inner circumferential surface of a mating surface that is located on a downstream side in a rotational direction of the shaft, and a central axis of the outer circumferential surface; and a line that connects an end of the groove in the circumferential direction, on an upstream side in the rotational direction of the shaft, and the central axis of the outer circumferential surface, is within the range of 135° to 173°.

The present invention may have a configuration in which the groove is provided as a pair of grooves.

Also, the present invention may have a configuration that further includes a crush relief formed on the inner circumferential surface, and in which the groove is formed at a

**2**

position that is away from the crush relief and that is on an edge side relative to a central position of the inner circumferential surface in an axial direction, and a recessed portion that is more shallow than the groove is formed adjacent to an edge side of the groove in the axial direction.

Also, the present invention may have a configuration in which the recessed portion is open in an end surface of the half bearing located in the axial direction.

Also, the present invention may have a configuration in which an overlay layer is formed on the inner circumferential surface.

Also, the present invention may have a configuration in which the groove is located further in an edge side relative to an intermediate position between a central position in an axial direction and an edge of the inner circumferential surface.

Also, the present invention may have a configuration in which the width of the groove in an axial direction of the inner circumferential surface is no greater than twice a width from the groove to an edge that is close to the groove in the axial direction.

## Advantageous Effects of Invention

According to the present invention, it is possible to reduce the amount of leaked lubricating oil, using a half bearing that has a groove on the inner circumferential surface.

## BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a plan view of half bearing **10** according to an embodiment of the present invention.

FIG. 2 is a cross-sectional view taken along line A-A in FIG. 1.

FIG. 3 is a cross-sectional view taken along line B-B in FIG. 1.

FIG. 4 is a cross-sectional view taken along line C-C in FIG. 2.

FIG. 5 shows an example of the results of analysis of the amount of leaked lubricating oil.

FIG. 6 shows half bearing **20** seen from the half bearing **10** side.

## DETAILED DESCRIPTION

The following describes half bearing **10** according to an embodiment of the present invention with reference to the drawings. FIG. 1 is a plan view of half bearing **10** according to an embodiment of the present invention, and FIG. 2 is a cross-sectional view taken along line A-A in FIG. 1. FIG. 3 is a cross-sectional view taken along line B-B in FIG. 1. In the drawings, half bearing **10** is illustrated using a polar coordinate system in which the center (the central axis) of the outer circumferential surface of half bearing **10** is defined as the origin, and a line that connects an end of the mating surface of half bearing **10** on the inner circumferential surface with the origin is defined as a starting line, and the central axis of a shaft that is supported by the sliding bearing (the axis of the inner circumferential surface) is defined as the z axis. In the coordinate system, a direction in which the z component increases, which is the direction from the front side to the back side of the sheet of FIG. 2, is defined as a +z direction, and the opposite direction in which the z component decreases is defined as a -z direction.

Half bearing **10** has a semi-cylindrical shape, and is to be positioned so as to face upper half bearing **20** described



below, which is the pair of half bearing **10**. Thus, a cylindrical sliding bearing is formed, which supports a shaft so as to be rotatable. That is, half bearing **10** is the lower half bearing of the sliding bearing. Half bearing **10** is an example of a half bearing according to the present invention. Note that the shaft is supported by half bearing **10** so as to extend in the z axis direction, and rotates clockwise in FIG. **2**. In the present embodiment, diameter  $\varphi$  of the supported shaft is in the range of 30 mm to 150 mm, for example, and the sliding bearing has an inner diameter that matches the diameter of the shaft that is to be supported.

Half bearing **10** has outer circumferential surface **11** that is an outer surface of the semi-cylindrical shape, and inner circumferential surface **12** that supports the shaft. Half bearing **10** has a three-layer structure with a back plate, a lining layer, and an overlay layer stacked in a direction from outer circumferential surface **11** to inner circumferential surface **12**. The back plate is a layer for reinforcing the mechanical strength of the lining layer. The back plate is formed of steel, for example.

The lining layer is a layer for providing bearing properties such as a frictional property, seizing resistance, wear resistance, conformability, a foreign matter embedding property (robustness against foreign matter), and corrosion resistance. The lining layer is formed of a bearing alloy. In order to prevent the lining layer from adhering to the shaft, a material type that is the same as that of the shaft is avoided, and a material type different from that of the shaft is used. For example, if half bearing **10** is used as a bearing for a shaft formed of steel, an aluminum alloy is used as the bearing alloy. Note that other than an aluminum alloy, an alloy that uses a metal other than aluminum as a base, such as a copper alloy, may be used.

The overlay layer is a layer that constitutes the inner circumferential surface of the shaft, and is a layer for improving the properties of the lining layer, such as a coefficient of friction, conformability, corrosion resistance, and a foreign matter embedding property (robustness against foreign matter). The overlay layer includes at least a binder resin, for example. A heat-curable resin is used as the binder resin, for example. Specifically, the binder resin includes at least one of a polyamide imide (PAI) resin, a polyimide (PI) resin, a polyamide resin, a phenol resin, a polyacetal resin, a polyether ether ketone resin, and a polyphenylene sulfide resin. The overlay layer may further include a solid lubricating material. The solid lubricating material is added in order to improve the friction property. For example, the solid lubricating material includes at least one of  $\text{MoS}_2$ ,  $\text{WS}_2$ , polytetrafluoroethylene (PTFE), graphite, h-BN, and  $\text{SB}_2\text{O}_3$ . For example,  $\text{MoS}_2$  provides a preferable lubricity. Also, since PTFE has a low intra-molecular cohesive force, it has an effect of reducing the frictional coefficient. Furthermore, graphite improves the wettability and improves the initial conformability. Initial conformability is a property by which the sliding surface wears, becomes smooth, and causes the sliding property to improve when coming into sliding contact with a counterpart member after the start of sliding. If the sliding property improves due to the expression of the initial conformability, the overall amount of wear of the sliding layer will decrease. In the present embodiment, half bearing **10** includes an overlay layer. However, half bearing **10** may not include the overlay layer, and may have a two-layer structure with the back plate and the lining layer.

Half bearing **10** has crush relief **13**, crush relief **14**, mating surface **15**, mating surface **16**, groove **111**, groove **112**, recessed portion **113**, and recessed portion **114**. Mating surface **15** is a surface that is to abut against the upper half

bearing, and is a mating surface on the upstream side in the rotational direction of the shaft. Mating surface **16** defines a first end of the half bearing **10**. Mating surface **16** is a surface that is to abut against the upper half bearing, and is a mating surface on the downstream side in the rotational direction of the shaft. Mating surface **16** defines a second end of the half bearing **10**. The crush reliefs are wide reliefs that are provided on the inner surface side of half bearing **10** so as to be in contact with the mating surfaces, over the entire width of half bearing **10** in the z axis direction. The crush reliefs are used to attach the bearing to the housing, and if portions of inner circumferential surface **12** near the mating surfaces are pushed toward the shaft, the crush reliefs prevent contact with the shaft. Also, the crush reliefs have an effect of cooling the bearing by allowing the lubricating oil that has fulfilled the lubricating effect to be discharged near the mating surfaces, and an effect of discharging foreign matter that has entered the inner circumferential surface **12** side. Crush relief **13** is a crush relief that is in contact with mating surface **15** and is located on the upstream side in the rotational direction of the shaft. Crush relief **14** is a crush relief that is in contact with mating surface **16** and is located on the downstream side in the rotational direction of the shaft.

Groove **111** and groove **112** are grooves provided in inner circumferential surface **12**. In the present embodiment, only two grooves, namely groove **111** and groove **112**, are provided on the inner circumferential surface. Groove **111** and groove **112** are grooves that extend along the circumferential direction of inner circumferential surface **12**, and have the function of returning the lubricating oil flowing in the rotational direction of the shaft as a result of the shaft rotating, in the direction opposite the rotational direction of the shaft. Groove **111** is formed in the z direction of a central portion of half bearing **10** in the z axis direction, and groove **112** is formed in the +z direction of the central portion of half bearing **10** in the z axis direction. Specifically, in the z axis direction, groove **111** is located further in the -z axis direction of an intermediate position between the central position in the z axis direction and the first edge located in the -z axis direction, and groove **112** is located further in the +z axis direction of the intermediate position between the central position in the z axis direction and the second edge located in the +z axis direction.

Recessed portion **113** and recessed portion **114** are recessed portions in inner circumferential surface **12**. The edge of groove **111** in the -z direction has a reduced thickness in a radial direction as a result of a cutting process, and thus recessed portion **113** that is recessed in inner circumferential surface **12** is formed. The edge of groove **112** in the +z direction has a reduced thickness in a radial direction as a result of a cutting process, and thus recessed portion **114** that is recessed in inner circumferential surface **12** is formed.

Groove **111** and recessed portion **113** are formed by applying a cutting process to inner circumferential surface **12** using a step-shaped cutter, and groove **112** and recessed portion **114** are similarly formed by applying a cutting process to inner circumferential surface **12** using a step-shaped cutter. The depth of a flat portion at the bottom of groove **111** is uniform in the circumferential direction, and the depth of a flat portion at the bottom of groove **112** is also uniform in the circumferential direction. The depth of a flat portion of recessed portion **113** is uniform in the circumferential direction, and the depth of a flat portion at the bottom of recessed portion **114** is also uniform in the circumferential direction. The inner surface side of half bearing **10** is



subjected to a cutting process, and thus groove **111**, groove **112**, recessed portion **113**, and recessed portion **114** are formed. Thereafter, the overlay layer is formed on inner circumferential surface **12** through pad printing. Thus, the overlay layer is not present on groove **111**, groove **112**, recessed portion **113**, and recessed portion **114**, and the lining layer is exposed therefrom. In the present embodiment, the depth of the grooves and the recessed portions is uniform in the circumferential direction, but may be non-uniform.

Next, regarding the position of groove **111** seen in the circumferential direction of inner circumferential surface **12**, as shown in FIG. 2, the end of groove **111** on the downstream side in the rotational direction of the shaft (the end on the crush relief **14** side), of the ends of groove **111** in the circumferential direction, is located at a distance from crush relief **14** so as not to reach crush relief **14**. Specifically, the distance from crush relief **14** to the end of groove **111** on the crush relief **14** side is shorter than the length of groove **111** in the circumferential direction. Also, when imaginary line **L1** that connects the inner surface side end of mating surface **15** with origin **A1** of outer circumferential surface **11** is defined as the starting line of the polar coordinate system, the end of groove **111** on the upstream side in the rotational direction of the shaft (the end on the crush relief **13** side), of the ends of groove **111** in the circumferential direction, is located at the position (the position of point **P2**) where line **L2** drawn from origin **A1** at inclination angle  $\theta_1$  intersects inner circumferential surface **12**. In the present embodiment, inclination angle  $\theta_1$  is  $135^\circ$ .

Next, regarding the position of groove **112** seen in the circumferential direction of inner circumferential surface **12**, as shown in FIG. 3, the end of groove **112** on the downstream side in the rotational direction of the shaft (the end on the crush relief **14** side), of the ends of groove **112** in the circumferential direction, is located at a distance from crush relief **14** so as not to reach crush relief **14**. Specifically, the distance from crush relief **14** to the end of groove **112** on the crush relief **14** side is shorter than the length of groove **112** in the circumferential direction. Also, when imaginary line **L1** that connects the inner surface side end of mating surface **15** with origin **A1** of outer circumferential surface **11** is defined as the starting line of the polar coordinate system, the end of groove **112** on the upstream side in the rotational direction of the shaft (the end on the crush relief **13** side), of the ends of groove **112** in the circumferential direction, is located at the position (the position of point **P3**) where line **L3** drawn from origin **A1** at inclination angle  $\theta_2$  intersects inner circumferential surface **12**. In the present embodiment, inclination angle  $\theta_2$  is  $135^\circ$ .

In half bearing **10**, a position at which an oil film has its minimum thickness may be located within the range where inclination angle  $\theta_1$  and an inclination angle  $\theta_2$  are greater than  $135^\circ$ , depending on the type of lubricating oil. Therefore, in the present embodiment, inclination angle  $\theta_1$  and inclination angle  $\theta_2$  are set to  $135^\circ$  so that the position at which an oil film has its minimum thickness is not present on groove **111** or groove **112**.

FIG. 4 is a cross-sectional view taken along line C-C in FIG. 2. In FIG. 4, in order to prevent the drawing from becoming complex, the back plate, the lining layer, and the overlay layer are not distinguished from each other. In the present embodiment, the wall thickness of half bearing **10** is not uniform, and the wall thickness increases in a direction toward a central portion in the left-right direction in FIG. 1, and decreases in directions from the central portion to the end portions (the mating surfaces). This is because a finished

inner diameter circle (a circle drawn by inner circumferential surface **12**) is decentered (shifted) outward from the center of an outer diameter circle (circle drawn by outer circumferential surface **11**). A so-called oil relief is formed due to this decentering. An oil relief refers to a gap between the finished inner diameter circle and a reference inner diameter circle that has a shorter radius than the outer diameter circle and has the same origin as the outer diameter circle. The depth (amount) of the oil relief is measured using a certain height (e.g., 6 to 13 mm) from the mating surface as a reference, and is 0.005 to 0.025 mm for example. The oil relief expands the oil clearance near the mating surfaces and assists in the formation of wedge film pressure. Moreover, the oil relief assists in the formation of an oil film, increases the amount of oil, and cools the bearing.

As shown in FIG. 4, height **h1** from the bottom of groove **111** to the bottom of recessed portion **113** on the edge side in the  $-z$  direction relative to groove **111** is smaller than height **h2** from the bottom of groove **111** to inner circumferential surface **12** on the central side relative to groove **111**. Also, as shown in the drawing, height **h3** from the bottom of groove **112** to the bottom of recessed portion **114** on the edge side in the  $+z$  direction relative to groove **112** is smaller than height **h2** from the bottom of groove **112** to inner circumferential surface **12** on the central side relative to groove **112**. In the present embodiment, height **h1**=height **h3** is satisfied.

In the present embodiment, recessed portion **113** and recessed portion **114** are open in the side surface of the half bearing in the axial direction. Thus, it is possible to improve the effect of sucking back the lubricating oil that leaks from, or is about to leak from, the inner circumferential surface of the half bearing, and returning it to the half bearing.

Also, in the present embodiment, width **w1** of groove **111** in the  $z$  axis direction is the same as width **w3** of recessed portion **113** in the  $z$  axis direction, the width of groove **112** in the  $z$  axis direction is the same as width **w3** of recessed portion **114** in the  $z$  axis direction, and width **w1**=width **w2** is satisfied. Note that width **w1** is preferably no greater than twice width **w3**, and width **w2** is preferably no greater than twice width **w4**.

In the present embodiment, width **w1** and width **w2** are 1 mm. Also, in the present embodiment, height **h1** and height **h3** are 1 mm, and height **h2** is 1.5 mm. Note that width **w1**, width **w2**, and heights **h1** to **h3** are not limited to the aforementioned dimensions, and other dimensions may be employed. For example, width **w1** and width **w2** may be smaller than 1 mm or greater than 1 mm. Also, height **h1** and height **h3** may be smaller than 1 mm or greater than 1 mm. Also, height **h2** may be smaller than 1.5 mm or greater than 1.5 mm.

FIG. 5 is a graph showing the results of analysis regarding the amount of leaked lubricating oil (side leak) when a sliding bearing in which groove **111** and groove **112** do not reach crush relief **14**, is used as a bearing that supports a crankshaft of an engine, and the engine is rotated by igniting the fuel supplied to the engine. As shown in FIG. 5, when inclination angle  $\theta$  is  $135^\circ$  as in the embodiment, the amount of leaked lubricating oil is smaller than when inclination angle  $\theta$  is  $90^\circ$ . Thus, the amount of leaked lubricating oil is reduced.

Also, if groove **111** and groove **112** reach crush relief **14**, the minimum thickness of the oil film is small. In contrast, according to the present embodiment, groove **111** and groove **112** do not reach crush relief **14**. Therefore, the minimum thickness of the oil film is large, and the load capacity is prevented from decreasing.



FIG. 6 is a diagram showing upper half bearing **20**, which is the pair of half bearing **10**, seen from the half bearing **10** side. The wall thickness of half bearing **20** is also not uniform as with half bearing **10**. The wall thickness increases in a direction toward a central portion, and decreases in directions from the central portion to the end portions (mating surfaces), and an oil relief is formed.

Half bearing **20** has crush relief **23**, crush relief **24**, mating surface **25**, mating surface **26**, hole **27**, and groove **211**. Hole **27** is a through hole penetrating from the outer circumferential surface to the inner circumferential surface of half bearing **20**. Lubricating oil that is supplied to the outer circumferential surface of half bearing **20** is supplied to the inner circumferential surface **22** side via hole **27**. Mating surface **15** is a surface that is to abut against mating surface **15**, and mating surface **26** is a surface that is to abut against mating surface **16**. Crush relief **13** is a crush relief that is in contact with mating surface **25**, and crush relief **24** is crush relief that is in contact with mating surface **16**.

Groove **211** is formed over the entire length of half bearing **20** in the circumferential direction, from mating surface **25** to mating surface **26**. The width of groove **211** (the length of the groove in the axial direction when viewing half bearing **20** from a direction orthogonal to the mating surfaces; hereinafter referred to as "groove width") is not uniform, but the groove **211** is relatively thin (narrow) in the crush reliefs and relatively thick (wide) at portions other than the crush reliefs. Hereinafter, a relatively thick portion of groove **211** will be referred to as thick groove **2111**, and a relatively thin portion of groove **211** will be referred to as thin groove **2112**. Thick groove **2111** and thin groove **2112** are both configured to be thicker (wider) than groove **111**, and thicker (wider) than groove **112**. The groove width does not continuously (i.e. gradually) change from thick groove **2111** to thin groove **2112**, but decreases rapidly. Note that the groove width of groove **2111** is uniform except for the vicinity of the border with thin groove **2112**, and the groove width of thin groove **2112** is uniform. Note that the groove width being uniform means that variation in the groove width is within a certain range, and for example, is  $\frac{1}{10}$  or less of the groove width, and preferably  $\frac{1}{100}$  or less of the groove width.

Also, the depth of groove **211** is not uniform, but is relatively small in the crush relief and relatively large at portions other than the crush relief. In other words, thick groove **2111** is relatively deep, and thin groove **2112** is relatively shallow. The groove width does not continuously (i.e. gradually) change from thick groove **2111** to thin groove **2112**, but decreases rapidly. Note that the depth of thick groove **2111** is uniform and the depth of thin groove **2112** is uniform. Note that the depth being uniform means that variation in the depth is within a certain range, and for example, is  $\frac{1}{10}$  or less of the depth of the groove, and preferably  $\frac{1}{100}$  or less of the depth of the groove. However, strictly speaking, there are cases where half bearing **20** is manufactured such that the thickness thereof from the bottom of the groove to the outer circumferential surface is uniform, and in such a case, the thickness of the groove fluctuates by an amount corresponding to the oil relief and the crush relief.

For example, the groove width of thick groove **2111** is 2 mm to 5 mm, and the depth of thick groove **2111** is smaller than the groove width, and is 0.5 mm to 1.5 mm, for example. The groove width of thin groove **2112** is more narrow than the groove width of the thick groove, and the depth of narrow groove **2112** is more shallow than the depth of the thick groove.

Thus, due to groove **211** being relatively thick and deep at the portion other than the crush reliefs, it is possible to sufficiently ensure the volume of groove **211**, or in other words, to sufficiently ensure the amount of lubricating oil to be supplied to the sliding surface. Moreover, due to the groove being relatively thin and shallow at the portions in the crush reliefs, it is possible to reduce the amount of oil that leaks from mating surface **25** and mating surface **26** in comparison to the case where the width and depth of the groove are uniform.

#### Modification

Although an embodiment of the present invention has been described above, the present invention is not limited to the above-described embodiment, and may be carried out in other various modes. For example, the above-described embodiment may be modified as follows and the present invention may be carried out as such. Note that the above-described embodiment and the following modifications may be combined with each other.

Regarding groove **111** and groove **112**, the positions of the crush relief **14** side ends (the positions of the ends on the downstream side in the rotational direction of the shaft) are not limited to those shown in the drawings, and may be other positions, provided that the grooves do not overlap the crush relief **14**. For example, the ends of groove **111** and groove **112** on the crush relief **14** side may be located on the right side of the central portion in the left-right direction in FIG. 1. Also, in a configuration in which half bearing **10** is not provided with a crush relief, it is preferable that the ends of groove **111** and groove **112** on the downstream side in the rotational direction of the shaft do not overlap mating surface **16**.

Although inclination angles  $\theta 1$  and  $\theta 2$  are  $135^\circ$  in the above-described embodiment, inclination angles  $\theta 1$  and  $\theta 2$  are not limited to  $135^\circ$ , and may be other angles. As shown in FIG. 5, the amount of leaked lubricating oil is smaller when inclination angle  $\theta$  is in the range of  $135^\circ$  to  $173^\circ$  than when inclination angle  $\theta$  is  $90^\circ$ . Therefore, it is preferable that the position where the thickness of the oil film is at its minimum is avoided, and inclination angles  $\theta 1$  and  $\theta 2$  are within the range of  $135^\circ$  to  $173^\circ$ .

Although half bearing **10** has a configuration in which both groove **111** and groove **112** are provided in the above-described embodiment, half bearing **10** may have a configuration in which one of groove **111** and groove **112** is not provided.

Although half bearing **10** is provided with recessed portion **113** and recessed portion **114** in the above-described embodiment, half bearing **10** may have a configuration in which recessed portion **113** and recessed portion **114** are not provided.

The present invention may have a configuration in which the above-described overlay layer is also provided on groove **111**, groove **112**, recessed portion **113**, and recessed portion **114**. Alternatively, it is possible to employ a configuration in which the above-described overlay layer is provided on recessed portion **113** and recessed portion **114**, but is not provided on the bottom of groove **111** or groove **112**.

In the above-described embodiment, in the z axis direction, groove **111** is located further in the  $-z$  axis direction of an intermediate position between the central position in the z axis direction and the edge located in the  $-z$  axis direction, and, in the z axis direction, groove **112** is located further in the  $+z$  axis direction of the intermediate position between the central position in the z axis direction and the edge located



in the +z axis direction. However, the positions of groove **111** and groove **112** in the z axis direction are not limited to those in the embodiment, and may be other positions. For example, it is possible to employ a configuration in which, in the z axis direction, groove **111** is located in the +z direction of an intermediate position between the central position in the z axis direction and the edge located in the -z axis direction, and, in the z axis direction, groove **112** is located in the -z direction of the intermediate position between the central position in the z axis direction and the edge located in the +z axis direction.

Although the depth from inner circumferential surface **12** to the bottom of groove **111** and the depth from inner circumferential surface **12** to the bottom of groove **112** are the same in the above-described embodiment, they may be different from each other.

Although the bottoms of groove **111** and groove **112** are flat as shown in FIG. 4 in the above-described embodiment, the bottoms of groove **111** and groove **112** are not limited to being flat. For example, the bottoms of groove **111** and groove **112** may be semi-circular. Also, central portions and edges of the bottoms of groove **111** and groove **112** in the z axis direction may be rounded.

The invention claimed is:

**1.** A half bearing comprising:

a semi-cylindrical bearing body that has an inner circumferential surface along which a shaft slides, the inner circumferential surface being bordered by:

a first edge and a second edge that extend in a circumferential direction of the inner circumferential surface; and

a first end and a second end that extend in an axial direction of the inner circumferential surface, the first end being located on an upstream side of a rotational direction of the shaft, the second end being located on a downstream side of the rotational direction of the shaft;

a first groove that is provided in the inner circumferential surface, the first groove extending along the circumferential direction of the inner circumferential surface,

a second groove that is provided in the inner circumferential surface, the second groove extending along the circumferential direction of the inner circumferential surface,

wherein the first groove is formed nearer to the first edge in an axial direction than a central position of the inner circumferential surface,

the second groove is formed nearer to the second edge in an axial direction than the central position of the inner circumferential surface,

the first groove has an inner circumferential end distal from the second end, the inner circumferential end of the first groove is located in a first area of the inner circumferential surface, the first area being defined by (i) the first edge, (ii) a first intermediate position of the inner circumferential surface, (iii) a 135° line, and (iv) a 173° line, the intermediate position being between the first edge and the central position of the inner circumferential surface in the axial direction, the 135° line being a line that connects the inner circumferential end of the first groove and a central axis of the outer

circumferential surface at a 135° angle from a reference line that connects the second end and the central axis, the 173° line being a line that connects the inner circumferential end of the first groove and the central axis at a 173° angle from the reference line;

the second groove has an inner circumferential end distal from the second end,

the inner circumferential end of the second groove is located in a second area of the inner circumferential surface, the second area being defined by (i) the second edge, (ii) a second intermediate position of the inner circumferential surface, (iii) the 135° line, and (iv) the 173° line, the second intermediate position being between the second edge and the central position of the inner circumferential surface in the axial direction.

**2.** The half bearing according to claim **1**, further comprising:

a crush relief formed in the inner circumferential surface; a first recessed portion formed adjacent to the first edge and the first groove in the axial direction, the first recessed portion being more shallow than the first groove; and

a second recessed portion formed adjacent to the second edge and the second groove in the axial direction, the second recessed portion being more shallow than the second groove,

wherein the first groove is circumferentially spaced apart from the crush relief, and

the second groove is circumferentially spaced apart from the crush relief.

**3.** The half bearing according to claim **2**, wherein an overlay layer is formed on the inner circumferential surface.

**4.** The half bearing according to claim **2**, wherein the first recessed portion is open along the first edge of the inner circumferential surface in the axial direction, and

the second recessed portion is open along the second edge of the inner circumferential surface in the axial direction.

**5.** The half bearing according to claim **4**, wherein an overlay layer is formed on the inner circumferential surface.

**6.** The half bearing according to claim **1**, wherein an overlay layer is formed on the inner circumferential surface.

**7.** The half bearing according to claim **1**, wherein the first groove is located closer to the first edge than to the first intermediate position, and the second groove is located closer to the second edge than to the second intermediate position.

**8.** The half bearing according to claim **1**, wherein a widest width of the first groove in the axial direction of the inner circumferential surface is no greater than twice a width from the first groove to the first edge in the axial direction, and

wherein a widest width of the second groove in the axial direction of the inner circumferential surface is no greater than twice a width from the second groove to the second edge in the axial direction.

\* \* \* \* \*