

US010962733B2

(12) **United States Patent**
Kim et al.

(10) **Patent No.:** **US 10,962,733 B2**
(45) **Date of Patent:** **Mar. 30, 2021**

(54) **CAMERA MODULE AND OPTICAL APPARATUS COMPRISING SAME**

(71) Applicant: **LG INNOTEK CO., LTD.**, Seoul (KR)

(72) Inventors: **Dong Hyun Kim**, Seoul (KR); **Chul Ro Lee**, Seoul (KR)

(73) Assignee: **LG INNOTEK CO., LTD.**, Seoul (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 86 days.

(21) Appl. No.: **16/089,549**

(22) PCT Filed: **Mar. 29, 2017**

(86) PCT No.: **PCT/KR2017/003396**

§ 371 (c)(1),
(2) Date: **Sep. 28, 2018**

(87) PCT Pub. No.: **WO2017/171388**

PCT Pub. Date: **Oct. 5, 2017**

(65) **Prior Publication Data**

US 2019/0137724 A1 May 9, 2019

(30) **Foreign Application Priority Data**

Mar. 30, 2016 (KR) 10-2016-0038624
Mar. 30, 2016 (KR) 10-2016-0038631

(Continued)

(51) **Int. Cl.**
G02B 27/12 (2006.01)
G02B 15/14 (2006.01)

(Continued)

(52) **U.S. Cl.**
CPC **G02B 7/021** (2013.01); **G02B 3/00**
(2013.01); **G02B 5/23** (2013.01); **G02B 7/02**
(2013.01);

(Continued)

(58) **Field of Classification Search**
CPC G02B 27/126; G02B 3/00; G02B 7/10;
G02B 25/002; G02B 7/021; G02B 7/02;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2005/0046740 A1 3/2005 Davis
2011/0037893 A1 2/2011 Okada
(Continued)

FOREIGN PATENT DOCUMENTS

CN 102972018 A 3/2013
CN 104880802 A 9/2015
(Continued)

OTHER PUBLICATIONS

GSMarena Team, LG G5(LG AT MWC 2016), In GSM Arena Website [Online], Feb. 20, 2016, Retrieved from the Internet: <URL: http://www.gsmarena.com/lg_mwc_2016-review-1382.php>, 16 pages.

(Continued)


Primary Examiner — Dawayne Pinkney

(74) *Attorney, Agent, or Firm* — Birch, Stewart, Kolasch & Birch, LLP

(57) **ABSTRACT**

An embodiment comprises: a lower surface; a first lens barrel comprising a first protrusion protruding from the lower surface; a first lens array comprising a plurality of first lenses disposed in the first lens barrel; a first holder comprising a first hole into which the first protrusion is inserted; a first adhesive member disposed between a lower surface of the first lens barrel around the first protrusion and an upper surface of the first holder around the first hole; and a first image sensor disposed under the first hole, wherein the first adhesive member comprises one end and the other end, which are disposed to encompass the first hole, and the one

(Continued)



end and the other end of the first adhesive member are spaced apart from each other.

20 Claims, 19 Drawing Sheets

USPC 359/640, 642, 704, 808, 811-830;
353/100-101; 396/529-531;
348/373-374

See application file for complete search history.

(30) **Foreign Application Priority Data**

Mar. 30, 2016 (KR) 10-2016-0038649
Mar. 30, 2016 (KR) 10-2016-0038653

(51) **Int. Cl.**

G02B 7/02 (2006.01)
G03B 21/14 (2006.01)
G03B 17/00 (2006.01)
G03B 3/10 (2021.01)
G02B 13/00 (2006.01)
G02B 5/23 (2006.01)
G02B 3/00 (2006.01)
G02B 7/36 (2021.01)
H04N 5/225 (2006.01)
G02B 9/60 (2006.01)
G02B 5/20 (2006.01)

(52) **U.S. Cl.**

CPC **G02B 7/36** (2013.01); **G02B 9/60**
(2013.01); **G02B 13/00** (2013.01); **G02B**
13/001 (2013.01); **G03B 3/10** (2013.01);
H04N 5/2253 (2013.01); **H04N 5/2254**
(2013.01); **G02B 5/208** (2013.01); **H04N**
5/2258 (2013.01)

(58) **Field of Classification Search**

CPC G02B 7/14; G02B 7/04; G11B 7/0932;
H04N 5/2251; H04N 5/2253; G03B
17/14; G03B 21/53; G03B 21/14

(56) **References Cited**

U.S. PATENT DOCUMENTS

2014/0184902 A1 7/2014 Chen
2015/0174715 A1 6/2015 Kang
2015/0301303 A1 10/2015 Kim et al.
2015/0326763 A1 11/2015 Campbell et al.
2015/0326766 A1* 11/2015 Czepowicz G03B 17/12
348/360

FOREIGN PATENT DOCUMENTS

JP 2010-050771 A 3/2010
JP 2012-129976 A 7/2012
KR 10-2009-0110978 A 10/2009
KR 10-1474221 B1 12/2014
KR 10-2015-0120735 A 10/2015
KR 10-2016-0017448 A 2/2016
WO WO 2005/032123 A1 4/2005
WO WO 2009/131017 A1 10/2009

OTHER PUBLICATIONS

Kim, Tae Jin, Closure of MWC 2016 which presented VR platform, In ZDNet Korea Website [Online], Feb. 25, 2016, Retrieved from the Internet: <URL: http://www.zdnet.co.kr/news/news_view.asp?artice_id=20160225034706>, 5 pages.

* cited by examiner

FIG.1




FIG.2




FIG.3A




FIG.3B




FIG.3C




FIG.3D




FIG.4A




FIG.4B




FIG.4C




FIG.5




FIG.6




FIG.7




FIG.8




FIG.9




FIG.10




FIG.11




FIG.12




FIG.13




FIG.14




FIG.15A




FIG.15B




FIG.16




FIG.17




FIG.18A




FIG.18B




FIG.19




FIG.20




FIG.21A




FIG.21B




FIG.22




FIG.23




FIG.24





FIG.25



1

CAMERA MODULE AND OPTICAL APPARATUS COMPRISING SAME**CROSS REFERENCE TO RELATED APPLICATIONS**

This application is the National Phase of PCT International Application No. PCT/KR2017/003396, filed on Mar. 29, 2017, which claims priority under 35 U.S.C. 119(a) to Patent Application No. 10-2016-0038624, filed in the Republic of Korea on Mar. 30, 2016, Patent Application No. 10-2016-0038631, filed in the Republic of Korea on Mar. 30, 2016, Patent Application No. 10-2016-0038649, filed in the Republic of Korea on Mar. 30, 2016, and to Patent Application No. 10-2016-0038653, filed in the Republic of Korea on Mar. 30, 2016, all of which are hereby expressly incorporated by reference into the present application.

TECHNICAL FIELD

Embodiments relate to a camera module and an optical apparatus including the same.

BACKGROUND ART

A mobile communication terminal, a computer, a laptop computer, a vehicle, or the like is equipped with a camera which is capable of displaying video information of the surroundings or performing photographing or the like. As the thickness of a mobile communication terminal is reduced and a computer or a laptop computer is miniaturized, a compact, lightweight, and high quality camera has come to be required.

In particular, a camera used for an automobile or a surveillance camera (CCTV) requires a wide-angle optical system for obtaining surrounding image information in a wide range, and it is required to design a bright optical system that may easily distinguish an object to be photographed even in a dark environment.

TECHNICAL OBJECT

Embodiments provide a camera module, which enables active alignment of a lens array unit and is capable of preventing the lens array unit from being out of focus due to the curing of a first adhesive member, and an optical apparatus including the camera module.

In addition, embodiments provide a camera module, which is capable of preventing separation of a lens array unit and preventing the lens array unit from being out of focus, and an optical apparatus including the camera module.

In addition, embodiments provide a camera module, which is capable of increasing the adhesive force between a circuit board and a holder and preventing breakage or warping of the holder due to impact, and an optical apparatus including the camera module.

In addition, embodiments provide a camera module, which is capable of suppressing distortion of an optical axis between a first imaging unit and a second imaging unit and improving the efficiency of dissipation of heat generated from an image sensor, and an optical apparatus including the camera module.

TECHNICAL SOLUTION

A camera module according to an embodiment includes: a first lens barrel including a lower surface and a first

2

protrusion protruding from the lower surface; a first lens array including a plurality of first lenses disposed in the first lens barrel; a first holder including a first hole into which the first protrusion is inserted; a first adhesive member disposed
5 between a lower surface of the first lens barrel around the first protrusion and an upper surface of the first holder around the first hole; and a first image sensor disposed under the first hole, wherein the first adhesive member includes one end and a remaining end, which are disposed so as to surround the first hole, and the one end and the remaining end of the first adhesive member are spaced apart from each other.

An outer circumferential surface of the first protrusion inserted into the first hole and an inner circumferential surface of the first hole may be spaced apart from each other.

The first holder may include: a body portion accommodating the first image sensor therein; and a support portion protruding from an upper surface of the body portion, and the first hole may penetrate the body portion and the support
15 portion, and the first adhesive member may be disposed on an upper surface of the support portion.

The first adhesive member may have a ring shape having an opening in a transverse direction between the one end and the remaining end thereof, which are spaced apart from each other.
20

The upper surface of the support portion may be disposed with a first groove, which is filled with a portion of the first adhesive member.

The camera module may further include a second adhesive member disposed in the opening in the first adhesive member between the first lens barrel and an upper surface of the support portion of the first holder.
25

The second adhesive member may be in contact with outer surfaces of the one end and the remaining end of the first adhesive member, and may be spaced apart from inner surfaces of the one end and the remaining end of the first adhesive member.
30

The camera module may include a retainer coupled to an upper end of the first lens barrel and configured to fix the first lens array.
35

The camera module may further include a reinforcement support portion disposed on the upper surface of the body portion so as to be in contact with the support portion, and the reinforcement support portion may protrude from the upper surface of the body portion, one end of the reinforcement support portion may come into contact with a side surface of the support portion, and the reinforcement support portion may protrude in a horizontal direction from the side surface of the support portion.
40

The camera module may further include: a first circuit board on which the first image sensor is disposed, the first circuit board being coupled to the first holder; an imaging unit including a second lens barrel having a second protrusion, a second lens array disposed in the second lens barrel, a second holder including a second hole into which the second protrusion is inserted, a third adhesive member disposed between a lower surface of the second lens barrel around the second protrusion and an upper surface of the second holder around the second hole, and a second image sensor disposed under the second hole; and a bracket configured to couple a lower surface of the first circuit board and a lower surface of a second circuit board to each other, wherein the bracket includes: a body including an upper surface coupled to the lower surface of the first circuit board, a lower surface coupled to the lower surface of the second circuit board, and a side surface located between the upper surface and the lower surface; and a guide portion having
45
50
55
60
65

one end protruding upwards from the upper surface of the body and a remaining end protruding downwards from the lower surface of the body in order to guide the first circuit board, the first holder, the second circuit board, and the second holder.

The first groove may take the form of a ring disposed on the upper surface of the support portion around the hole.

A length of the second adhesive member in a direction perpendicular to a longitudinal direction thereof may be less than a length of the first adhesive member in a direction perpendicular to a longitudinal direction thereof.

A second groove may be disposed in the upper surface of the support portion of the first holder corresponding to the opening in the first adhesive member, and the second adhesive member may be disposed in the second groove and the opening in the first adhesive member between the first lens barrel and the upper surface of the support portion of the first holder.

One end of the second groove may be open to the first hole, and a remaining end of the second groove may be open to an outside of the side surface of the support portion.

The second adhesive member may be disposed closer to the remaining end than the one end of the second groove.

A part of the plurality of first lenses may be disposed inside the first protrusion.

The first adhesive member may be a UV-curable and thermosetting adhesive member.

The second adhesive member may be a UV-curable adhesive member.

A distance between the one end and the remaining end of the first adhesive member may gradually increase in a direction from an inner circumferential surface to an outer circumferential surface of the first adhesive member.

A camera module according to another embodiment includes: a lens barrel including a plurality of seating portions defining hollow regions having different diameters; a lens array including a plurality of lenses disposed on the plurality of seating portions; a holder including a body portion, a support portion protruding from the body portion, and a hole penetrating the body portion and the support portion, a lowermost seating portion among the plurality of seating portions being inserted into the hole; a first adhesive member disposed between a lower surface of the lens barrel around the lowermost seating portion and an upper surface of the holder; and an image sensor disposed under the hole, wherein one end and a remaining end of the first adhesive member, disposed on an upper surface of the support portion around the hole, are spaced apart from each other, and an outer circumferential surface of the lowermost seating portion inserted into the hole and an inner circumferential surface of the hole are spaced apart from each other.

The lens barrel may include a first seating portion defining a first hollow region having a first diameter; a second seating portion protruding from a lower surface of the first seating portion and defining a second hollow region having a second diameter; and a third seating portion protruding from a lower surface of the second seating portion and having a third diameter. The third seating portion may be inserted into the hole, and the first adhesive member may be disposed between the lower surface of the second seating portion and the upper surface of the support portion of the holder.

The first adhesive member may have an opening in a transverse direction.

A groove may be formed in the upper surface of the support portion of the holder corresponding to the opening in the first adhesive member, one end of the groove may be

open to the hole, and a remaining end of the groove may be open to an outside of a side surface of the support portion.

The camera module may further include a second adhesive member disposed in the groove and the opening in the first adhesive member between the lower surface of the second seating portion and the upper surface of the support portion of the holder.

A camera module according to another embodiment includes: a lens barrel including a protrusion protruding from a center portion of a lower surface; a plurality of lenses disposed in the lens barrel; a holder including a hole into which the protrusion is inserted; a first adhesive member disposed between the lower surface of the lens barrel around the protrusion and an upper surface of the holder around the hole; and an image sensor disposed under the holder, wherein the first adhesive member takes the form of a ring having one end and a remaining end which are spaced apart from each other, an opening is disposed between the one end and the remaining end of the first adhesive member, one end of the opening is open to an inner circumferential surface of the first adhesive member, and a remaining end of the opening is open to an outer circumferential surface of the first adhesive member.

An optical apparatus according to an embodiment includes a display module including a plurality of pixels, the color of which changes in response to an electric signal; the camera module according to the above embodiments which convert an image input through a lens into an electric signal; and a controller configured to control the operation of the display module and the camera module.

A method of manufacturing a camera module according to an embodiment includes: coupling a lower surface of a holder and an upper surface of a circuit board, on which an image sensor is mounted, to each other; applying a first adhesive member to an upper surface of the holder; UV-curing the first adhesive member; seating a lens barrel so that a lower surface of the lens barrel comes into contact with the UV-cured first adhesive member; and thermally curing the first adhesive member in a state in which the lens barrel is seated, wherein one end and a remaining end of the first adhesive member are spaced apart from each other, and an opening is disposed between the one end and the remaining end of the first adhesive member so that a gas generated during UV curing or thermal curing of the adhesive member is discharged through the opening.

A camera module according to another embodiment includes a lens barrel including a plurality of seating portions defining hollow regions having different diameters and including a protrusion on a lower surface thereof; a lens array including a plurality of lenses disposed on the plurality of seating portions; a holder including a hole into which the protrusion is inserted; a first adhesive member disposed between the lower surface of the lens barrel around the protrusion and an upper surface of the holder around the hole; an image sensor disposed under the hole; and a retainer which is coupled to an upper end of the lens barrel and fixes the lens array, wherein an outer circumferential surface of the protrusion inserted into the hole and an inner circumferential surface of the hole are spaced apart from each other.

The retainer may be in contact with a first lens disposed on an uppermost seating portion.

The retainer may include: an engaging portion, which engages with an outer circumferential surface of the uppermost seating portion of the lens barrel; and a bent portion, which is bent from the engaging portion to support an edge of the first lens.

5

A screw thread for fastening may be formed in each of the uppermost seating portion of the lens barrel and the engaging portion.

The first lens may have the largest diameter among the plurality of lenses, and may have an upwardly convex exit surface.

An upper end of the bent portion may be located higher than an upper end of the lens barrel.

The exit surface of the first lens may protrude out of the bent portion.

The camera module may further include a reinforcement adhesive member disposed between the outer circumferential surface of the uppermost seating portion and the engaging portion.

A groove may be formed in an outer circumferential surface of the retainer, and the camera module may further include an O-ring disposed in the groove.

A camera module according to another embodiment includes: a lens barrel including a protrusion on a lower surface; a lens array including a plurality of lenses disposed in the lens barrel; a holder including a body portion, a support portion disposed on an upper surface of the body portion, and a hole penetrating the body portion and the support portion, into which the protrusion is inserted; a first adhesive member disposed between the lower surface of the lens barrel around the protrusion and an upper surface of the support portion around the hole; an image sensor disposed under the hole; and a reinforcement support portion disposed on the upper surface of the body portion so as to be in contact with the support portion, wherein an outer circumferential surface of the protrusion inserted into the hole and an inner circumferential surface of the hole are spaced apart from each other.

The reinforcement support portion may protrude from the upper surface of the body portion, and one end of the reinforcement support portion may be in contact with a side surface of the support portion.

The reinforcement support portion may include a plurality of reinforcement support portions spaced apart from each other, and the plurality of reinforcement support portions may be disposed so as to face each other in a direction parallel to a long side of the body portion.

A vertical distance from the upper surface of the body portion to an upper surface of the reinforcement support portion may be less than a vertical distance from the upper surface of the body portion to the upper surface of the support portion.

The reinforcement support portion may protrude in a horizontal direction from the side surface of the support portion.

The reinforcement support portion may be a single ring-shaped structure configured to surround the side surface of the support portion.

The camera module may further include a circuit board on which the image sensor is mounted, the circuit board being coupled to the body portion of the holder.

In addition, the camera module may further include a second adhesive member disposed on an edge of a lower surface of the body portion to bond the circuit board and the body portion to each other.

The camera module may further include a first reinforcement adhesive member having one end connected to a first area of the second adhesive member and a remaining end disposed on the lower surface of the body portion so as to extend in a direction parallel to a long side of the lower surface of the body portion.

6

A width of the first reinforcement adhesive member may be wider than a width of the second adhesive member.

The camera module may further include a second reinforcement adhesive member having one end connected to a second area of the second adhesive member and a remaining end extending in a direction parallel to a short side of the lower surface of the body portion so as to be connected to a third area of the second adhesive member.

The camera module may further include: a flexible substrate connected to the circuit board; and a third adhesive member configured to bond one end of the flexible substrate and a side surface of the body portion to each other.

The camera module may further include a filter located on the image sensor and disposed in a central area of the lower surface of the body portion, and the first reinforcement member and the second reinforcement adhesive member may be spaced apart from the filter.

A camera module according to a further embodiment includes: a first imaging unit; a second imaging unit; and a bracket configured to couple the first imaging unit and the second imaging unit to each other, wherein each of the first and second imaging units includes: a lens barrel having a protrusion on a lower surface; a lens array including a plurality of lenses disposed in the lens barrel; a holder including a hole into which the protrusion is inserted; a first adhesive member disposed between the lower surface of the lens barrel around the protrusion and an upper surface of the holder around the hole; and a circuit board on which the image sensor disposed under the hole is mounted, the circuit board being coupled to the holder, wherein an outer circumferential surface of the protrusion inserted into the hole is spaced apart from an inner circumferential surface of the hole, and wherein an upper surface of the bracket is coupled to a lower surface of the circuit board of the first imaging unit and a lower surface of the bracket is coupled to a lower surface of the circuit board of the second imaging unit.

The bracket may include: a body coupled to each of the first and second imaging units; and a guide portion connected to the body and configured to guide the circuit board and the holder of each of the first and second imaging units.

The guide portion may be in contact with a side surface of the body, one end of the guide portion may protrude upwards from an upper surface of the body, and a remaining end of the guide portion may protrude downwards from a lower surface of the body.

The guide portion includes a plurality of guide portions spaced apart from each other, and each of the plurality of guide portions may be positioned so as to come into contact with a corresponding one of corners of the body.

Each of the plurality of guide portions may include a bent portion, which surrounds a corresponding one of the corners of the body.

A side surface of the circuit board and a side surface of the holder of each of the first and second imaging units may be in contact with an inner surface of each of the plurality of guide portions.

A lower surface of the holder of each of the first and second imaging units may be disposed with a coupling boss, the body may include a hole including a first opening, which is open to the upper surface of the body, and a second opening, which is open to the lower surface of the body, the coupling boss of the holder of the first imaging unit may pass through the circuit board of the first imaging unit to thereby be inserted into a first opening in the bracket, and the coupling boss of the holder of the second imaging unit may pass through the circuit board of the second imaging unit to thereby be inserted into a second opening in the bracket.

The circuit board may be a printed circuit board formed of an insulating plate and a copper foil, the circuit board may include a first area formed with a circuit pattern electrically connected to the image sensor and a second area, which is not electrically connected to the image sensor, the copper foil of the second area may be exposed to a lower surface of the insulating plate, the copper foil of the second area exposed to the lower surface of the insulating plate of the first imaging unit may be in contact with the upper surface of the bracket, and the copper foil of the second area exposed to the lower surface of the insulating plate of the second imaging unit may be in contact with the lower surface of the bracket.

The camera module may further includes a thermally conductive tape disposed between the upper surface of the bracket or the lower surface of the bracket and the copper foil of the second area exposed to the lower surface of the insulating plate of each of the first and second imaging units.

ADVANTAGEOUS EFFECTS

Embodiments enable active alignment of a lens array unit and may prevent the lens array unit from being out of focus due to the curing of a first adhesive member.

In addition, embodiments may prevent separation of the lens array unit and may prevent the lens array unit from being out of focus.

In addition, embodiments may increase the adhesive force between a circuit board and a holder and may prevent breakage or warping of the holder due to impact.

In addition, embodiments may suppress distortion of an optical axis between a first imaging unit and a second imaging unit and may improve the efficiency of dissipation of heat generated from an image sensor.

DESCRIPTION OF DRAWINGS

FIG. 1 illustrates a perspective view of a camera module according to an embodiment.

FIG. 2 illustrates a cross-sectional view of the camera module taken in the direction I-I' of FIG. 1.

FIG. 3a illustrates an assembly perspective view of a lens array, a lens barrel, and a retainer of FIG. 1.

FIG. 3b illustrates a cross-sectional view taken in the direction II-II' of FIG. 3a.

FIG. 3c illustrates a cross-sectional view of the lens barrel of FIG. 3a.

FIG. 3d illustrates a bottom perspective view of FIG. 3a.

FIG. 4a illustrates a perspective view of a holder illustrated in FIG. 1.

FIG. 4b illustrates a cross-sectional view of the holder illustrated in FIG. 4a taken in the direction AB.

FIG. 4c illustrates a filter disposed in an accommodating groove in the holder illustrated in FIG. 4b.

FIG. 5 illustrates a first adhesive member disposed on a holder.

FIGS. 6 and 7 illustrate a process of attaching or fixing the lens barrel to a support portion of the holder.

FIG. 8 illustrates a first adhesive member according to another embodiment.

FIG. 9 illustrates first and second adhesive members according to another embodiment.

FIG. 10 illustrates a holder according to another embodiment.

FIG. 11 illustrates first and second adhesive members according to another embodiment.

FIG. 12 illustrates a first perspective view of a circuit board, an image sensor, a filter, a third adhesive member, and a connector illustrated in FIG. 1.

FIG. 13 illustrates a second perspective view of the circuit board, the image sensor, the filter, the third adhesive member, and the connector illustrated in FIG. 1.

FIG. 14 illustrates a perspective view of a holder according to another embodiment.

FIG. 15a illustrates a cross-sectional view of the holder illustrated in FIG. 14 taken in the direction AB.

FIG. 15b illustrates a cross-sectional view of the holder illustrated in FIG. 14 taken in the direction CD.

FIG. 16 illustrates a perspective view of a holder including a reinforcement support portion according to another embodiment.

FIG. 17 illustrates a fourth adhesive member disposed on the lower surface of a body portion of the holder.

FIG. 18a illustrates an embodiment of a first reinforcement adhesive member disposed on the lower surface of the holder.

FIG. 18b illustrates an embodiment of the first reinforcement adhesive member and a second reinforcement adhesive member disposed on the lower surface of the holder.

FIG. 19 illustrates a cross-sectional view of a camera module according to another embodiment.

FIG. 20 illustrates a perspective view of a camera module according to another embodiment.

FIG. 21a illustrates a first perspective view of a bracket illustrated in FIG. 20.

FIG. 21b illustrates a second perspective view of the bracket illustrated in FIG. 20.

FIG. 22 illustrates a bottom view of another embodiment of a circuit board illustrated in FIG. 20.

FIG. 23 illustrates a thermally conductive tape according to an embodiment.

FIG. 24 illustrates a perspective view of a portable terminal according to an embodiment.

FIG. 25 illustrates a view of the configuration of the portable terminal illustrated in FIG. 24.

MODE FOR INVENTION

Hereinafter, the embodiments will become apparent through the accompanying drawings and a description related to the embodiments. In the description of the embodiments, it will be understood that, when an element such as a layer (film), region, pattern or structure is referred to as being formed "on" or "under" another element, such as a substrate, layer (film), region, pad or pattern, it can be directly "on" or "under" the other element or be indirectly formed with intervening elements therebetween. It will also be understood that "on" or "under" the element may be described relative to the drawings. In addition, the same reference numerals will be used throughout the drawings to refer to the same or like parts.

Hereinafter, a camera module and an optical apparatus including the same according to the embodiments will be described with reference to the accompanying drawings. For convenience of description, the camera module according to the embodiments will be described using the Cartesian coordinate system (x, y, z), but may be described using any other coordinate system, and the embodiments are not limited thereto. In each drawing, the x-axis and the y-axis are orthogonal to the z-axis which is an optical-axis direction. The z-axis direction which is the optical axis (OA) direction may be referred to as a "first direction", the x-axis

direction may be referred to as a “second direction”, and the y-axis direction may be referred to as a “third direction”.

FIG. 1 illustrates a perspective view of a camera module 100 according to an embodiment, FIG. 2 illustrates a cross-sectional view of the camera module 100 taken in the direction I-I' of FIG. 1, FIG. 3a illustrates an assembly perspective view of a lens array 110, a lens barrel 120, and a retainer 125 of FIG. 1, FIG. 3b illustrates a cross-sectional view taken in the direction II-II' of FIG. 3a, FIG. 3c illustrates a cross-sectional view of the lens barrel 110 of FIG. 3a, and FIG. 3d illustrates a bottom perspective view of FIG. 3a.

Referring to FIGS. 1 and 3a to 3d, the camera module 100 includes the lens barrel 110, the lens array 120, the retainer 125, a holder 130, a first adhesive member 140, a circuit board 150, an image sensor 160, a filter 170, and a connector 180.

The lens array 120 is disposed or mounted in the lens barrel 110, and serves to concentrate external light on the image sensor 160.

The lens array 120 may include a plurality of lenses 120-1 to 120-5, and the plurality of lenses 120-1 to 120-5 may be arranged in a line within the lens barrel 120.

Referring to FIG. 3c, the lens barrel 110 may include a first opening 301 into which light is introduced, a through-bore 302 through which the light introduced into the first opening 301 passes, and a second opening 302 from which the light that has passed through the through-bore 302 is discharged to the image sensor 160. For example, each of the first opening 301 and the second opening 302 may have a circular shape, but is not limited thereto, and in another embodiment, may have an elliptical shape or a polygonal shape.

The through-bore 302 in the lens barrel 110 may include lens seating portions P1 to P3, which define hollow regions having different diameters, arranged in a direction from the first opening 301 to the second opening 302.

For example, the diameters of the lens seating portions P1 to P3 may decrease in the direction from the first opening 301 to the second opening 302.

For example, the lens barrel 110 may include a first lens seating portion P1, which is disposed in one end thereof with the first opening 301 and defines the hollow region having a first diameter, a second lens seating portion P2, which is connected at one end thereof to the first lens seating portion P1 and defines the hollow region having a second diameter, and a third lens seating portion P3, which is connected at one end thereof to the other end of the second lens seating portion P2 and is disposed at the other end thereof with the second opening 302.

Referring to FIG. 3b, the plurality of lenses 120-1 to 120-5 may be disposed on the first to third lens seating portions P1 to P3 of the lens barrel 110. The first to third lens seating portions P1 to P3 may be disposed with lens support portions 111 to 114, which support first to fifth lenses.

The second seating portion P2 of the lens barrel 110 may be configured so as to protrude from the lower surface 322 of the first seating portion P1, and the third seating portion P3 may be configured so as to protrude from the lower surface 324 of the second seating portion P2. The third seating portion P3 of the lens barrel 110 may be a protrusion that is located at the lower end of the lens barrel 110 protruding from the lower surface 324 of the second seating portion P2 of the lens barrel 110.

The lens barrel 110 may be formed of a plastic material, for example, a thermoplastic resin such as polycarbonate, without limitation thereto.

The camera module 100 may further include at least one O-ring 310 between the seating portions P1 to P3 of the lens barrel 110 and the lenses 120-1 to 120-5.

For example, the O-ring 310 may be inserted between the first seating portion P1 and the first lens 120-1. The O-ring 310 may serve to secure the air-tightness of the lens barrel 110 which faces the outside, and may prevent invasion of moisture, for example, by blocking a gap between the two.

The lens array 110 may be designed to realize a predetermined wide angle.

The plurality of lenses 120-1 to 120-5 may be designed in consideration of, for example, the curvature of the lenses and the distance between the lenses, so as to realize a wide angle.

For example, both the entrance surface and the exit surface of the first lens 120-1 may be convex in the upward direction, the second lens 120-2 may have an entrance surface which is convex in the upward direction and an exit surface which is concave in the upward direction, both the entrance surface and the exit surface of the third lens 120-3 may be convex in the upward direction, the fourth lens 120-4 may have an entrance surface which is concave in the upward direction and an exit surface which is convex in the upward direction, and the fifth lens 120-5 may have an entrance surface which is convex in the upward direction and an exit surface which is concave in the upward direction. However, the embodiment is not limited thereto, and a wide angle may be realized by any of various shapes. For example, the upward direction may be the direction from the lower end to the upper end of the lens barrel 110.

In order to realize a wide-angle lens which has a focal length shorter than the focal length of a standard lens (e.g., 40 mm to 60 mm) and which provides an angle of view (e.g., 180 degrees or more) wider than the angle of view of the standard lens, the first lens 120-1, which is disposed the farthest distance from the image sensor 160, may be a lens that has a diameter larger than those of the other lenses (e.g., 120-2 to 120-5) and includes the exit surface which is convex in the upward direction. For this reason, the weight of the lens array 120, which is a wide-angle lens, may be heavier than that of the standard lens, and may protrude from the first seating portion P1 of the lens barrel 120.

The retainer 125 may be coupled to the upper end of the lens barrel 110, may fix the lens array 120 so as to prevent the lens array 120 disposed in the lens barrel 110 from being separated from the lens barrel 110, and may protect the lens array from external impact.

For example, the retainer 125 may be in contact with the first lens 120-1 disposed on the uppermost first seating portion P1, thereby preventing the first lens 120-1 from being separated outwards from the lens barrel 110 and serving to protect the first lens 120-1 from external impact.

The retainer 125 may be formed of a high-strength metal material, but is not limited thereto, and may be formed of a plastic material having high strength.

For example, the retainer 125 may have a shape that corresponds to the shape of the lens barrel 110, for example, a hollow circular shape, without limitation thereto.

For example, the retainer 125 may include an engaging portion 125a, which engages with the outer circumferential surface of the first seating portion P1, which is located at the upper end of the lens barrel 110, and a bent portion 125b, which is bent from the engaging portion 125a so as to support the edge of the lens (e.g., 120-1) of the lens array 120.

For example, a screw thread 321 may be disposed on the outer circumferential surface of the first seating portion P1

11

of the lens barrel 110, and the engaging portion 125a of the retainer 125 may be disposed on the inner circumferential surface thereof with a screw thread, which engages with the screw thread 321 of the first seating portion P1 of the lens barrel 110.

For example, the upper end of the bent portion 125b may be positioned higher than the upper end of the lens barrel 110, for example, the upper end of the first seating portion P1, and the exit surface of the first lens 120 may bulge outwards from the bent portion 125b.

A ring-shaped groove 212, into which an O-ring 210 is coupled, may be disposed in the outer circumferential surface of the retainer 125.

The embodiment may further include a reinforcement member 129 disposed at a coupling portion between the retainer 125 and the lens barrel 110.

Referring to FIGS. 3b and 3d, the reinforcement member 129 may be disposed on the lower surface 322 of the first seating portion P1 of the lens barrel 110 so as to be in contact with the lower end of the screw thread 321 of the first seating portion P1 of the lens barrel 110 and the lower end of the screw thread of the engaging portion 125a of the retainer 125, which engage with each other.

The reinforcement member 129 may be formed by air-vent-sealing a bonding material, such as epoxy, to the screw-thread engaging portion after the retainer 125 and the lens barrel 110 are screwed to each other.

The reinforcement member 129 may prevent separation or distortion of the retainer 125 and the lens barrel 110, which are coupled to each other.

The bent portion 125b of the retainer 125 may be bent inwards from one end of the engaging portion 125a, and one end of the bent portion 125b may support the edge area of the first lens 120-1.

The first lens 120-1 of the lens array 120 may be exposed from the first seating portion P1 and the retainer 125. The exposed first lens 120-1 may protrude outwards from one end of the first seating portion P1 and the support portion 125b of the retainer 125. Thus, the embodiment may realize a wide angle of 180 degrees or more.

FIG. 4a illustrates a perspective view of the holder 130 illustrated in FIG. 1, and FIG. 4b illustrates a cross-sectional view of the holder 130 illustrated in FIG. 4a taken in the direction AB.

Referring to FIGS. 4a and 4b, the holder 130 supports and fixes the lens barrel 110, and accommodates therein the circuit board 150, the image sensor 160, and the filter 170.

The holder 130 has a hole 131, into which the protrusion (e.g., P3) at the lower end of the lens barrel 110 having a stepped structure is inserted, and an area of the upper surface of the holder 130 around the hole 131 supports an area of the lower surface of the protrusion around the holder 130.

For example, the holder 130 may include a body portion 130a, a support portion 130b positioned on the body portion 130a, and the hole 131 formed in the body portion 130a and the support portion 130b.

The body portion 130a accommodates therein the circuit board 50, the image sensor 160, and the filter 170.

The support portion 130b is disposed on the upper surface of the body portion 130a, and supports the lens barrel 110. The support portion 130b may protrude from the upper surface of the body portion 130a, and may have a cylindrical shape, an elliptical shape, or a polyhedral shape.

The third seating portion P3, which is the protrusion at the lower end of the lens barrel 110 or the lowermost seating portion among the seating portions P1 to P3 of the lens barrel 110, is inserted into the hole 131 in the holder 130.

12

The hole 131 may include a first opening 131a, into which the third seating portion P3 of the lens barrel 110 is inserted, and a second opening 131b, which is adjacent to the filter 170 and exposes the filter 170. The hole 131 may have the same shape as the shape of the outer circumferential surface of the third seating portion P3 of the lens barrel 110. For example, the hole 131 may have a cylindrical shape, an elliptical shape, or a polygonal shape, without limitation thereto.

The diameter d2 of the hole 131 is greater than the diameter d1 of the outer circumferential surface of the third seating portion P3 of the lens barrel 110 ($d2 > d1$). This serves to prevent the outer circumferential surface of the third seating portion P3 inserted into the hole 131 from coming into contact with the inner surface of the hole 131, in order to realize active alignment of the focal point of the lens array 120, which will be described below.

In addition, the depth H2 of the hole 131 corresponding to the support portion 130b may be greater than the length H1 of the third seating portion P3 of the lens barrel 110 in the vertical direction. This serves to prevent the third seating portion P3 of the lens barrel 110 inserted into the hole 131 from coming into contact with the filter 170. The protrusion of the lens barrel 110 inserted into the hole 131, for example, the lower surface of the third seating portion P3 may be spaced apart from the filter 170.

The body portion 130a and the support portion 130b of the holder 130 may be integrally formed, without limitation thereto.

An accommodating groove 132 may be disposed in the lower surface of the body portion 130a of the holder 130 to accommodate the filter 170 therein. The accommodating groove 132 may be located in contact with the second opening of the hole 131 in the support portion 130b.

FIG. 4c illustrates the filter 170 disposed in the accommodating groove 132 of the holder 130 illustrated in FIG. 4b. Referring to FIG. 4c, the filter 170 may be disposed in the accommodating groove 132 and may be fixed in the accommodating groove 132 using an adhesive member or the like.

One or more coupling bosses 135a and 135b may be disposed on the lower surface of the body portion 130a so as to be coupled to the circuit board 150. FIG. 4c illustrates two coupling bosses 135a and 135b, but the number of coupling bosses is not limited thereto and may be at least one.

The first adhesive member 140 couples and fixes the lens barrel 110 and the holder 130 to each other.

The first adhesive member 140 may be disposed between the lower surface 324 around the protrusion 131 of the lens barrel 110 inserted into the hole 131 and the upper surface of the holder, for example, the upper surface of the support portion 130b.

FIG. 5 illustrates the first adhesive member 140 disposed on the holder 130.

Referring to FIGS. 4a, 4b, and 5, the first adhesive member 140 is disposed on an upper surface 410 of the support portion 130b of the holder 130. For example, the first adhesive member 140 may be disposed on the upper surface 410 of the support portion 130b around the hole 131.

For example, the first adhesive member 140 may be disposed in a ring shape on the upper surface 410 of the support portion 130b so as to surround the hole 131.

The upper surface 410 of the support portion 130b of the holder 130 may be disposed with a first groove 410a, which is filled with a portion of the first adhesive member 140. The first groove 410a may be formed in the upper surface of the

13

support portion **130b** around the hole **131**, and may be formed in a ring shape so as to surround the hole **131**.

When the first groove **410a** is filled with a portion of the first adhesive member **140**, the contact area between the first adhesive member **140**, a portion of which fills the first groove **410a**, and the holder **130** may increase, whereby adhesive force may be increased.

In addition, the first adhesive member **140** may be a curable adhesive member, for example, a dual curable adhesive member that is completely cured by UV light or heat.

For example, the first adhesive member **140** may be UV-curable and thermosetting epoxy, but is not limited thereto. In another embodiment, the first adhesive member **140** may be either a UV-curable adhesive member or a thermosetting adhesive member.

The first adhesive member **140** may be fluid before being cured.

For example, when an adhesive material is primarily cured by UV light, the material may be pre-cured into a state of having fluidity, and when the adhesive material is secondarily cured by thermal curing after completion of active alignment, which will be described later, the adhesive material is completely cured into a state having no fluidity, so that the first adhesive member **140** may be formed.

The first groove **410a** disposed in the upper surface of the support portion **130b** of the holder **130** may prevent the first adhesive member **140**, which is fluid before being cured, from flowing out of the support portion **130b**.

In addition, the first groove **410a** in the support portion **130b** of the holder **130** may be shaped so as to correspond to the lower surface of the second seating portion P2 of the lens barrel **110**. As such, the first adhesive member **140** may be easily cured into a shape that corresponds to the lower surface **324** (see FIG. **3d**) of the second seating portion P2, which may enhance the adhesive force between the holder **130** and the lens barrel **110**.

In addition, the lower surface **324** of the second seating portion P2 of the lens barrel **110** may also be disposed with a groove **324a** (see FIG. **3d**), which is filled with a portion of the first adhesive member **140**. The groove **324a** in the lens barrel **110** may be located so as to correspond to the first groove **410a** in the support portion **130b** and may have a shape that corresponds to that of the first groove.

An embodiment of a method of manufacturing the camera module including a process of attaching or fixing the lens barrel **110** to the support portion **130b** of the holder **130** may be as follows.

First, the lower surface of the holder **130** and the upper surface of the circuit board, on which the image sensor is mounted, are coupled to each other. Subsequently, the first adhesive member **140** is applied to the upper surface of the holder **130**, for example, the upper surface of the support portion **130b** of the holder.

Subsequently, the first adhesive member **140** is subjected to UV curing.

Subsequently, the lens barrel **110** is seated so that the lower surface of the lens barrel **110** comes into contact with the UV-cured first adhesive member **140**.

Subsequently, active alignment is performed in the state in which the lens barrel **110** is seated.

Subsequently, after the active alignment is completed, the first adhesive member **140** is thermally cured in the state in which the lens barrel **110** is seated.

For example, the first adhesive member **140** may correspond to the embodiment of FIG. **5**.

14

In addition, the first adhesive member may correspond to the embodiment **140-1** illustrated in FIG. **8**, or may correspond to the embodiment **140-1a** illustrated in FIG. **11**.

In the case in which the first adhesive member corresponds to the embodiment of FIG. **8** or FIG. **11**, in the first adhesive member application step, one end and the other end of the first adhesive member **140-1** or **140-1a** may be spaced apart from each other, and an opening may be disposed between one end and the other end of the first adhesive member **140-1** or **140-1a** so that a gas generated during the UV curing or thermal curing of the first adhesive members **140-1** or **140-1a** is discharged through the opening.

Subsequently, after the curing of the first adhesive member **140-1** or **140-1a** is completed, a second adhesive member **145** or **145a** is applied to or formed in an opening **501** located between the upper surface of the holder **130**, for example, the upper surface **410** of the support portion **130b** and the lower surface of the lens barrel **110**, for example, the lower surface **324** of the second seating portion P2.

Subsequently, the second adhesive member **145** or **145a** is subjected to UV curing.

The following description of the first adhesive member **140-1** or **140-1a** and the second adhesive member **145** or **145a** may be applied to all embodiments of the method of manufacturing the camera module described above.

FIGS. **6** and **7** illustrate a process of attaching or fixing the lens barrel **110** to the support portion **130b** of the holder **130**.

Referring to FIG. **6**, an adhesive material **140'**, for example, thermosetting epoxy or UV-curable epoxy is applied to the upper surface **410** of the support portion **130b** of the holder **130**. For example, the adhesive material **140'** may be applied to the upper surface **410** of the support portion **130b** of the holder **130** so that the first groove **410a** is filled with the adhesive material **140'**.

The circuit board **150**, on which the filter **170** and the image sensor **160** are mounted, may be coupled to the holder **130** before the adhesive material **140'** is applied to the upper surface **410** of the support portion **130b** of the holder **130**.

Subsequently, the third seating portion P3 of the lens barrel **110** is inserted into the hole **131** in the support portion **130b** of the holder **130**, and the lens barrel **110** is seated on the upper surface of the support portion **130b** of the holder **130** so that the lower surface **324** of the second seating portion P2 of the lens barrel **110** comes into contact with the adhesive material **140'**.

Since the adhesive material **140'** is fluid before being cured, the lens barrel **110**, which is seated on the adhesive material before being cured, may tilt in the state in which the third seating portion P3 of the lens barrel **110** is inserted into the hole **131**.

For example, in the state in which the lens barrel **110** is in contact with the adhesive material **140'**, the lens barrel **110** may be moved in order to adjust the focal point of the lens array **120** mounted in the lens barrel **110** relative to the image sensor **160**.

For example, the lens barrel **110** may be moved forwards and rearwards and rightwards and leftwards so as to adjust the focal point of the lens array **120** mounted in the lens barrel **110** from a first focal point f1 to a second focal point f2, which is a desired target focal point. This adjustment of the focal point of the lens array **120** by directly moving the lens barrel **110** is referred to as "active alignment".

In order to perform active alignment, the protrusion of the lens barrel **110** inserted into the hole **131**, for example, the outer circumferential surface **139** of the third seating portion P3 is spaced apart from the inner circumferential surface **119** of the hole **131**.

This is because active alignment may not be performed by moving the lens barrel 110 when the outer circumferential surface 139 of the third seating portion P3 of the lens barrel 110 inserted into the hole 131 is brought into contact with the inner circumferential surface 119 of the hole 131 or when the outer circumferential surface 139 of the third seating portion P3 is fastened to the inner circumferential surface 119 of the hole 131 via screw-threads or the like.

Subsequently, as illustrated in FIG. 7, the focal point of the lens array 120 may be adjusted to the target focal point through active alignment, and then, the adhesive material may be cured by thermal curing or UV curing so that the first adhesive member 140 is formed.

FIG. 8 illustrates the first adhesive member 140-1 according to another embodiment.

The first adhesive member 140 illustrated in FIG. 5 has a ring shape, but the adhesive member 140-1 illustrated in FIG. 8 may have the opening 501 formed by removing a portion of the ring-shaped first adhesive member 140.

The first adhesive member 140 includes one end 11a and the other end 11b arranged so as to surround the hole 131. The one end 11a and the other end 11b of the first adhesive member 140 are spaced apart from each other. For example, the first adhesive member 140 may take the form of a ring having the opening 501, which is located between the one end 11a and the other end 11b spaced apart from each other and is formed in the transverse direction. Here, the transverse direction may be the direction from the inner circumferential surface to the outer circumferential surface of the first adhesive member 140 and/or the direction opposite thereto.

For example, one end of the opening 501 may be open to the inner circumferential surface of the first adhesive member 140, and the other end of the opening 501 may be open to the outer circumferential surface of the first adhesive member 140.

For example, in order to ensure easy and efficient gas discharge, the distance between the one end 11a and the other end 11b of the first adhesive member 140 may gradually increase in the direction from the inner circumferential surface to the outer circumferential surface of the first adhesive member 140, but is not limited thereto. In another embodiment, the distance between the one end 11a and the other end 11b of the first adhesive member 140 may be constant in the direction from the inner circumferential surface to the outer circumferential surface of the first adhesive member 140. For example, the distance between the one end 11a and the other end 11b of the first adhesive member 140 may be indicated by "W1", which is the width of the opening 501 in FIG. 8.

The length of the entire first adhesive member 140 may be greater than the distance between the one end 11a and the other end 11b of the first adhesive member 140. For example, the distance between the one end 11a and the other end 11b of the first adhesive member 140 may be equal to or less than $\frac{1}{4}$ of the length of the entire first adhesive member 140. The reason for this is that, when the distance between the one end 11a and the other end 11b of the first adhesive member 140 exceeds $\frac{1}{4}$ of the length of the entire first adhesive member 140, adhesion performance of the first adhesive member 140 may deteriorate, thus causing separation of the lens barrel 110 and the holder 130.

When the adhesive material 140' is subjected to thermal curing or UV curing, a gas may be generated from the adhesive material 140'.

In the case of FIG. 5, since the lens barrel 110 and the holder 130 are bonded to each other by the first adhesive

member 140 after the protrusion of the lens barrel 110 is inserted into the hole 131 in the holder 130 in the state in which the circuit board 150 and the holder 130 are coupled, the space defined by the protrusion of the lens barrel 110, the holder 130, and the circuit board 150 may be hermetically sealed.

That is, in the case of FIG. 5, due to a sealed structure in which the gas generated during the thermal curing or UV curing of the first adhesive member 140 cannot escape to the outside, the adhesive material 140' may swell and consequently push the lens barrel 110 upwards. Thereby, the focal point of the lens array 120 mounted in the lens barrel 110 may change, which may deteriorate the resolution of the camera module 100.

The first adhesive member 140-1 of FIG. 8 has the opening 501, through which the gas generated during the thermal curing or UV curing of the adhesive material 140' may escape to the outside.

Since the gas generated during the thermal curing or UV curing is discharged to the outside through the opening in the first adhesive member 140-1, the embodiment may prevent the focal point of the lens array 120 from deviating due to the gas generated during the curing of the adhesive material, and consequently, may prevent deterioration in resolution.

FIG. 9 illustrates the first and second adhesive members 140-1 and 145 according to another embodiment. The same reference numerals as those in FIG. 8 denote the same components, and a description of the same components will be simplified or omitted.

Referring to FIG. 9, the embodiment may further include the second adhesive member 145 in addition to the first adhesive member 140-1 illustrated in FIG. 8.

The second adhesive member 145 may be disposed in the opening 501, which is located between the upper surface 410 of the support portion 130b of the holder 130 and the lower surface 324 of the second seating portion P2 of the lens barrel 110. The openings 501 may be located between the one end 11a and the other end 11b of the first adhesive member 140-1, which are spaced apart from each other.

The second adhesive member 145 may be in contact with the outer surface of the one end 11a of the first adhesive member 140-1 and the outer surface of the other end 11b, which are adjacent to the opening 501, and may be spaced apart from the inner surface of the one end 11a and the inner surface of the other end 11b of the first adhesive member 140-1.

For example, the second adhesive member 145 may be disposed on the upper surface of the support portion 130b of the holder 130, which is adjacent to the outer surfaces of the one end 11a and the other end 11b of the first adhesive member 140-1, and may be disposed in a gap, which is generated between the upper surface 410 of the support portion 130b of the holder 130 and the lower surface 324 of the second seating portion P2 of the lens barrel 110 due to the opening 501 in the first adhesive member 140-1.

For example, the second adhesive member 145 may be disposed in the opening 501 in the first adhesive member 140-1 between the upper surface 410 of the support portion 130b of the holder 130 and the lower surface 324 of the second seating portion P2 of the lens barrel 110.

After the curing of the first adhesive member 140-1 of FIG. 8 is completed, the second adhesive member 145 may be formed by air-vent sealing an adhesive material through the opening 501 in the first adhesive member 140-1 so as to cover the gap between the upper surface 410 of the support portion 130b of the holder 130 and the lower surface 324 of the second seating portion P2 of the lens barrel 110. Thus,

as illustrated in FIG. 9, the second adhesive member 145 may be formed so as to connect only the outer surfaces of the one end 11a and the other end 11b of the first adhesive member 140-1 to each other, and may not cover the inner surfaces of the one end 11a and the other end 11b of the first adhesive member 140-1.

For example, the second adhesive member 145 may be formed of a UV-curable adhesive member, for example, UV epoxy.

The second adhesive member 145 serves only to prevent the opening 501 between the upper surface 410 of the support portion 130b of the holder 130 and the lower surface 324 of the second seating portion P2 of the lens barrel 110 from being open to the outside. Therefore, the width of the second adhesive member 145 in the first direction may be less than the width of the first adhesive member 140-1 in the first direction.

For example, the width in the first direction may be a length in a direction perpendicular to the longitudinal direction. For example, the width of the first adhesive member 140-1 may be a length in the direction from the inner surface to the outer surface of the first adhesive member 140-1, and the width of the second adhesive member 145 may be a length in the direction from a first surface to a second surface of the second adhesive member 145, which face each other. Here, the first surface may be a surface that faces the hole 131.

Since the gap, which is formed between the upper surface 410 of the support portion 130b of the holder 130 and the lower surface 324 of the second seating portion P2 of the lens barrel 110 due to the opening 501, is sealed by the second adhesive member 145, the embodiment may prevent, for example, moisture or foreign substances from being introduced into the lens barrel 110 through the opening.

FIG. 10 illustrates a holder 130-1 according to another embodiment, and FIG. 11 illustrates first and second adhesive members according to another embodiment.

Referring to FIG. 10, in addition to the first groove 410a, a second groove 410b may be formed in the upper surface of the support portion 130b1 of the holder 130-1.

The first groove 410a may be located between the first opening 131a of the hole 131 in the support portion 130b and the edge of the upper surface 410 of the support portion 130b and may take the form of a ring so as to surround the hole 131. On the other hand, the second groove 410b may be formed so as to extend from the edge of the upper surface 410 of the support portion 130b to the hole 131, one end of the second groove 410b may be exposed or open to the hole 131, and the other end of the second groove 410b may be exposed or open to the outside of the side surface of the support portion 130b.

A portion of the second groove 410b may overlap the first groove 410a, and the depth of the second groove 410b may be greater than the depth of the first groove 410a. The depth of each of the first and second grooves 410a and 410b may be the depth from the upper surface 410 of the support portion 130b to the bottom of the first and second grooves 410a and 410b.

Referring to FIG. 11, the first adhesive member 140-1a may be disposed on the upper surface 410 of the support portion 130b1 so as to fill the first groove 410a, but not the second groove 410b. For example, the first adhesive member 140-1a may have a ring shape having an opening 501a in the transverse direction, and the opening 501a in the first adhesive member 140-1a may be located so as to correspond to or be aligned with the second groove 410a. Here, the transverse direction may be the direction from the inner

circumferential surface to the outer circumferential surface of the first adhesive member 140-1a and/or the direction opposite thereto.

For example, one end and the other end of the first adhesive member 140-1a may be in contact with the second groove 410a.

The second adhesive member 145a illustrated in FIG. 11 may be formed through air-vent sealing after the curing of the first adhesive member 140-1a is completed.

The second adhesive member 145a may be disposed in the gap, which is formed between the upper surface 410 of the support portion 130b of the holder 130 and the lower surface 324 of the second seating portion P2 of the lens barrel 110 due to the opening 501a and the second groove 410a.

For example, the second adhesive member 145a may be disposed in the opening 501a and the second groove 410a between the upper surface 410 of the support portion 130b of the holder 130 and the lower surface 324 of the second seating portion P2 of the lens barrel 110.

For example, the second adhesive member 145a may be disposed at the other end of the second groove 410b, which is open to the outside of the side surface of the support portion 130b, and may be spaced apart from one end of the second groove 410b, which is open to the hole 131.

In addition, the second adhesive member 145a may be in contact with the outer circumferential surface of the one end 11a of the first adhesive member 140-1a and the outer circumferential surface of the other end 11b, and may be spaced apart from the inner circumferential surface of the one end 11a and the inner circumferential surface of the other end 11b of the first adhesive member 140-1a.

For example, the second adhesive member 145a may be disposed closer to the other end than the one end of the second groove 410b.

Compared with the embodiments illustrated in FIGS. 8 and 9, the embodiment illustrated in FIG. 11 may allow the gas generated during the curing of the first adhesive member 140-1a to be easily discharged through the second groove 410b in the holder 130-1. Thereby, even if the width W2 of the opening 501a in the first adhesive member 140-1a is less than the width W1 of the opening 501 in the first adhesive member 140-1, the gas generated during the curing of the first adhesive member 140-1a may be easily discharged.

In addition, since the width W2 of the opening 501a in the first adhesive member 140-1a is less than the width W1 of the opening 501 in the first adhesive member 140-1, the adhesive force of the first adhesive member 140-1a may be enhanced.

In addition, since the width W2 of the opening 501a in the first adhesive member 140-1a is less than the width W1 of the opening 501 in the first adhesive member 140-1, the second adhesive member 145a, which serves to prevent the introduction of moisture and foreign substances, may be easily formed and air-tightness may be improved.

In FIGS. 4a, 8, and 10, the first groove 410a is formed in the upper surface 410 of the support portion 130b of the holder 130 or 130-1, but is not limited thereto. In another embodiment, the first grooves 410a may be omitted, and the first adhesive member 140, 140-1 or 140-1a may be disposed on the upper surface 410 of the support portion 130b of the holder 130 or 130-1 in which the first groove 410a is omitted.

FIG. 12 illustrates a first perspective view of the circuit board 150, the image sensor 160, the filter 170, a third adhesive member 147, and the connector 180 illustrated in FIG. 1, and FIG. 13 is a second perspective view of the

circuit board **150**, the image sensor **160**, the filter **170**, the third adhesive member **147**, and the connector **180** illustrated in FIG. 1.

Referring to FIGS. 12 and 13, the filter **170** may be located between the lens array **120** of the lens barrel **110** and the image sensor, and may be disposed in the accommodating groove **132** in the holder **130**.

The filter **170** blocks light in a specific frequency band of the light which has passed through the lens barrel **110** from being incident on the image sensor **810**. For example, the filter **170** may be an infrared-ray blocking filter, without limitation thereto.

The image sensor **160** is mounted or placed on the circuit board **150** so as to be located under the holder **130**, and serves to detect an image included in the light which has passed through the filter **170**, to convert the detected image into an electric signal, and to output the electric signal. The lens array **120**, the filter **170**, and the image sensor **160** may be aligned with each other in a direction parallel to the optical axis.

The circuit board **150** is coupled to the body portion **130a** of the holder **130**.

For example, the circuit board **150** may be disposed with one or more holes **152** and **154**, into which the one or more coupling bosses **135a** and **135b** disposed on the lower surface of the body portion **130a** of the holder **130** are coupled.

A fourth adhesive member **632** (see FIG. 17) may be disposed between the lower surface of the body portion **130a** of the circuit board **150** and the upper surface of the circuit board **150** for coupling the circuit board **150** and the body portion **130a** of the holder **130** to each other. The fourth adhesive member **632** will be described below with reference to FIG. 17.

Various elements or circuit patterns may be disposed on the circuit board **150** in order to convert an image formed on the image sensor **160** into an electric signal and transmit the electric signal to an external device.

The connector **180** may be electrically connected to the circuit board **150**, and may include a port **180a** to be electrically connected to an external device. In the embodiment, the circuit board **150** may include a flexible substrate **151**, which connects the image sensor **160** and the connector **180** to each other.

The embodiment may further include the third adhesive member **147** for bonding one end of the flexible substrate **151** of the circuit board **150** to the side surface of the body portion **130a** of the holder **130**. The third adhesive member **147** serves to fix the flexible substrate **151** connected to the connector **180** to the holder **130**.

FIG. 14 illustrates a perspective view of a holder **130-2** according to another embodiment, FIG. 15a illustrates a cross-sectional view of the holder **130-2** illustrated in FIG. 14 taken in the direction AB, and FIG. 15B illustrates a cross-sectional view of the holder **130-2** illustrated in FIG. 14 taken in the direction CD.

Referring to FIGS. 14 to 15b, the holder **130-2** may further include reinforcement support portions **610a** and **610b**, in contrast with the embodiment illustrated in FIG. 4a.

The reinforcement support portions **610a** and **610b** are spaced apart from each other on the upper surface of the body **130a** of the holder **130-2**. The reinforcement support portions **610a** and **610b** may protrude from the upper surface of the body **130a** of the holder **130-2**, and one end of each of the reinforcement support portions **610a** and **610b** is in contact with the side surface of the support portion **130b** of the holder **130-2**.

The vertical distance to the upper surface of the reinforcement support portions **610a** and **610b** from the upper surface of the body portion **130a** may be less than the vertical distance to the upper surface of the support portion **130b**. As illustrated in FIG. 15, the cross section of the reinforcement support portion and the support portion **130b** from the upper surface of the body portion **130a** may have a stepped structure in the direction AB.

In FIGS. 14 to 15b, the reinforcement support portions **610a** and **610b** may be disposed so as to face each other in a direction parallel to the long side of the upper surface of the body portion **130a**, and may protrude in the horizontal direction from the side surface of the support portion **130b** of the holder **130-2**.

In another embodiment, the reinforcement support portions may be radially arranged around the support portion **130b** so as to be connected to the support portion **130b**.

For example, the reinforcement support portions **610a** and **610b** of FIG. 14 may be parallel to the long side of the upper surface of the body portion **130a**, but are not limited thereto. In another embodiment, the reinforcement support portions may be parallel to the short side of the upper surface of the body portion **130a**.

In addition, another embodiment may include reinforcement support portions, which are parallel to the long side of the upper surface of the body portion **130a**, and reinforcement support portions, which are parallel to the short side of the upper surface of the body portion **130a**. In this case, the length of the reinforcement support portions parallel to the long side of the upper surface of the body portion **130a** may be greater than the length of the reinforcement support portions parallel to the short side of the upper surface of the body portion **130a**.

The reinforcement support portions **610a** and **610b** may serve to prevent the holder **130-2** from being damaged or warped due to impact or stress received by the holder **130-2** in a direction perpendicular to the optical axis OA, for example, in the X-axis or Y-axis direction.

Since the lens array for realizing a wide angle is generally heavier than a lens for realizing a narrow angle, the holder may be broken or warp by external impact or stress applied to the lens array.

In addition, in the structure in which the lens barrel **110** and the holder **130** are fixed by the adhesive members **140** formed of, for example, epoxy in order to realize the active alignment as in the embodiment, since the strength of the holder may be poor due to external impact or stress, the embodiment illustrated in FIG. 14 prevents the holder **130** from being damaged or warped by external impact or stress through the use of the reinforcement support portions **610a** and **610b**.

FIG. 16 illustrates a perspective view of a holder **130-3** including a reinforcement support portion **620** according to another embodiment.

In the embodiment of FIG. 14, the multiple reinforcement support portions **610a** and **610b** are spaced apart from each other and are disposed on the upper surface of the body portion **130a**. In contrast, the reinforcement support portion **620** in the embodiment of FIG. 16 may take the form of a single ring that surrounds the side surface of the support portion **130b**.

The vertical distance to the upper surface of the reinforcement support portion **620** from the upper surface of the body portion **130a** may be less than the vertical distance to the upper surface of the support portion.

The reinforcement support portions **610a** and **610b** of FIG. 14 may be suitable for resistance against impact in the

X-axis direction, whereas the reinforcement support portion **620** illustrated in FIG. **16** may function to resist impact and prevent warping in any direction within 360 degrees in the XY plane.

FIG. **17** illustrates a fourth adhesive member **632** disposed on the lower surface of the body portion **130a** of any one of the holders **130** and **130-1** to **130-3**.

Referring to FIG. **17**, the fourth adhesive member **632** may be disposed on the edge of the lower surface of the body portion **130a** of the holders **130** and **130-1** to **130-3** so as to be spaced apart from the filter **170**, which is disposed in the central area of the lower surface of the body portion **130a** of the holders **130** and **130-1** to **130-3**, and serves to bond the circuit board **150** to the body portion **130a** of the holder **130**.

In addition, in order to fix or attach the coupling bosses **135a** and **135b** of the holders **130** and **130-1** to **130-3** to the holes **152** and **154** in the circuit board **150**, the fourth adhesive member **632** may be disposed on the coupling bosses and the lower surface of the body portion **130a** around the coupling bosses **135a** and **135b**.

The fourth adhesive member **632** may be an air-vent sealing adhesive member, for example, epoxy, without limitation thereto.

The embodiment may further include a reinforcement adhesive member for enhancing the adhesive force between the holders **130** and **130-1** to **130-3** and the circuit board **150** and for preventing warping of the holder or strengthening the holder, in addition to the fourth adhesive member **632**.

FIG. **18a** illustrates an embodiment of first reinforcement adhesive members **634** and **636** disposed on the lower surface of the holders **130** and **130-1** to **130-3**.

Referring to FIG. **18a**, the first reinforcement adhesive members **634** and **636** may be disposed on the lower surface of the body portion **130a** so that one end thereof is connected to a first area of the fourth adhesive member **632** and the other end thereof extends in a direction parallel to the long side of the lower surface of the body portion **130a** of the holders **130** and **130-1** to **130-3**.

For example, the first reinforcement adhesive members **634** and **636** may be connected at one end thereof to the coupling bosses **135a** and **135b**, and the other end thereof may extend in a direction parallel to the long side of the lower surface of the body portion **130a** of the holders **130** and **130-1** to **130-3**.

The width **W1** of the first reinforcement adhesive members **634** and **636** may be greater than or equal to the width **W2** of the fourth adhesive member **632** ($W1 \geq W2$). Each of the widths **W1** and **W2** may be a length in a direction perpendicular to the long side of the lower surface of the body portion **130a**.

FIG. **18a** illustrates two first reinforcement adhesive members **634** and **636**, which face each other, without limitation thereto. In another embodiment, the number of first reinforcement adhesive members may be one or more.

The first reinforcement adhesive members **634** and **636** may be an air-vent sealing adhesive member, for example, epoxy, without limitation thereto.

FIG. **18b** illustrates an embodiment of the first reinforcement adhesive members **634** and **636** and second reinforcement adhesive members **642** and **644** disposed on the lower surface of the holders **130** and **130-1** to **130-3**.

The embodiment may further include the second reinforcement adhesive member **644** and **646** in addition to the first reinforcement adhesive members **634** and **636** illustrated in FIG. **18a**.

In order to enhance the strength and prevent warping, the second reinforcement adhesive members **642** and **644** may

be connected at one end thereof to a second area of the fourth adhesive member **632**, and the other end thereof may extend in a direction parallel to the short side of the lower surface of the body portion **130a** of the holders **130** and **130-1** to **130-3** so as to be connected to a third area of the fourth adhesive member **632**. The first to third areas of the fourth adhesive member **632** may be different areas spaced apart from each other.

In addition, the first and second reinforcement adhesive members **634**, **636**, **642** and **644** may be spaced apart from the filter **170** disposed on the lower surface of the holders **130** and **130-1** to **130-3**. In addition, in order to increase strength and prevent warping, an area between one end and the other end of each of the second reinforcement adhesive members **642** and **644** may be connected to the other end of a corresponding one of the first reinforcement adhesive members **634** and **636**.

The width of the second reinforcement adhesive members **642** and **644** may be less than or equal to the width of the fourth adhesive member **632**. The width of the second reinforcement adhesive members **642** and **644** may be a length in a direction parallel to the long side of the lower surface of the body portion **130a**.

FIG. **18b** illustrates two second reinforcement adhesive members **642** and **644**, which face each other, without limitation thereto. In another embodiment, the number of second reinforcement adhesive members may be one or more.

The second reinforcement adhesive members **644** and **646** may be an air-vent sealing adhesive member, for example, epoxy, without limitation thereto.

Another embodiment may include only the fourth adhesive member **632** and the second reinforcement adhesive members **644** and **646** except for the first reinforcement adhesive members **634** and **636**.

Through the provision of the first and second reinforcement adhesive members **634** and **636** and **642** and **644**, it is possible to improve the strength of the holders **130** and **130-1** to **130-3** for overcoming external impact and to prevent warping of the holders **130** and **130-1** to **130-3** due to external impact. Thereby, the embodiment may achieve enhanced reliability.

FIG. **19** illustrates a cross-sectional view of a camera module **100-1** according to another embodiment.

Referring to FIG. **19**, the camera module **100-1** may correspond to an embodiment in which the retainer **125** and the O-ring **210** are omitted from the camera module **100** described above. In the lens barrel **110** of the camera module **100-1**, the screw thread **321** to be fastened with the retainer **125** is omitted.

The description of FIGS. **1** to **18** may be applied to the camera module **100-1** illustrated in FIG. **19**, except for the description of the retainer **125** and the O-ring **210**.

FIG. **20** illustrates a perspective view of a camera module **200** according to another embodiment.

Referring to FIG. **20**, the camera module **200** includes a first imaging unit **100A**, a second imaging unit **100B**, and a bracket **300**.

In FIG. **20**, each of the first imaging unit **100A** and the second imaging unit **110B** exemplifies the camera module having the holder **130-2** illustrated in FIG. **14**, but is not limited thereto.

In another embodiment, each of the first imaging unit **100A** and the second imaging unit **110B** may be the camera module **100** according to the embodiments described in FIGS. **1** to **18** or the camera module **100-1** of FIG. **19**.

The embodiment may realize a 360-degree view using the first imaging unit **100A** having a wide angle and the second imaging unit **100B** having a wide angle.

The bracket **300** couples the first imaging unit **100A** and the second imaging unit **110B** to each other.

For example, the bracket **300** may be coupled to the circuit board **150** of the first imaging unit **100A**, and may be coupled to the circuit board **150** of the second imaging unit **110B**.

FIG. **21a** illustrates a first perspective view of the bracket **300** illustrated in FIG. **20**, and FIG. **21b** illustrates a second perspective view of the bracket **300** illustrated in FIG. **20**.

Referring to FIGS. **21a** and **21b**, the bracket **300** includes a body **20** and guide portions **20-1** to **20-4**.

The body **20** includes an upper surface **20a** to be coupled to the first imaging unit **100A**, a lower surface **20b** to be coupled to the second imaging unit **110B**, and a side surface **20c** located between the upper surface **20a** and the lower surface **20b**.

The upper surface **20a** of the body **20** may face the circuit board **150** of the first imaging unit **100A**, and may be brought into contact with the lower surface of the circuit board **150** of the first imaging unit **100A**.

The lower surface **20b** of the body **20** may face the circuit board **150** of the second imaging unit **100B**, and may be brought into contact with the lower surface of the circuit board **150** of the second imaging unit **100A**.

The body **20** may include a first area **S1**, which corresponds to the lower surface of the circuit board **150** of each of the first and second imaging units **100A** and **100B**, and second areas **S21** and **S22**, which are the remaining area excluding the first area **S1**.

The first area **S1** of the body **20** may be disposed with holes **21** and **22**, into which the coupling bosses **135a** and **135b** disposed on the lower surface of the holder (e.g., **130-2**) of the first imaging unit **100A** and the coupling bosses **135a** and **135b** disposed on the lower surface of the holder **130-2** of the second imaging unit **100B** are inserted.

For example, the holes **21** and **22** may include a first opening, which is open to the upper surface **20a** of the first area **S1** of the body **20**, and a second opening, which is open to the lower surface **20b** of the first area **S1** of the body **20**.

The coupling bosses **135a** and **135b** of the holder (e.g., **130-2**) of the first imaging unit **100A** may pass through the holes **152** and **154** in the circuit board **150** to thereby be inserted into the first opening of the respective holes **21** and **22** in the bracket **300**, and the coupling bosses **135a** and **135b** of the holder (e.g., **130-2**) of the second imaging unit **100B** may pass through the holes **152** and **154** in the circuit board **150** to thereby be inserted into the second opening of the respective holes **21** and **22** in the bracket **300**.

Since the coupling bosses **135a** and **1** of the holder (e.g., **130-2**) of each of the first and second imaging units **110A** and **100B** are inserted into the same holes **21** and **22** disposed in the bracket **300**, the optical axes (OA in FIG. **1**) or the optical centers of the first and second imaging units **110A** and **100B** may be easily and accurately aligned with each other. This may prevent image distortion that occurs when alignment fails when realizing a 360-degree view.

The guide portions **20-1** to **20-4** are connected to the body **20**, and support or guide the circuit boards **150** and the holder (e.g., **130-2**) of the first and second imaging units **100A** and **100B** seated on the first area **S1** of the body **20**.

For example, the guide portions **20-1** to **20-4** may be in contact with the side surface of the body **20**, one end of the respective guide portions **20-1** to **20-4** may protrude from the upper surface **20a** of the body **20**, and the other end of

the respective guide portions **20-1** to **20-4** may protrude from the lower surface **20b** of the body **20**.

For example, the guide portions **20-1** to **20-4** may be positioned so as to abut the corners of the first area **S1** of the body **20**, and may respectively include bent portions **24a**, which are bent to surround the corners of the first area **S1**.

For example, the number of guide portions **20-1** to **20-4** may be plural, and each of the plurality of guide portions **20-1** to **20-4** may include the bent portion **24a**, which surrounds a corresponding one of the corners of the first area **S1**.

The side surface of the circuit board **150** of each of the first and second imaging units **100A** and **100B** may be in contact with the inner side surfaces of the plurality of guide portions **20-1** to **20-4**. In addition, the side surface of the body portion **130a** of the holder (e.g., **130-2**) of each of the first and second imaging units **100A** and **100B** may be in contact with the inner side surfaces of the plurality of guide portions **20-1** to **20-4**.

That is, the plurality of guide portions **20-1** to **20-4** may support or guide the side surface of the circuit board **150** and/or the side surface of the body portion **130a** of the holder (e.g., **130-2**), thereby being capable of preventing the second imaging units **100A** and **100B** from being separated from the bracket **300** or preventing deviation of the optical axis or the focal length of the first and second imaging units **100A** and **100B**.

Each of the second areas **S21** and **S22** of the body **20** of the bracket **300** may extend in a direction perpendicular to the optical axis from a corresponding end of the first area **S1**. The second area **S21** and **S22** of the body **20** may be disposed with holes **23** and **24** for coupling with an external device, for example, an optical device such as a mobile phone.

For example, the second areas **S21** and **S22** of the body **20** of the bracket **300** may include a second-first area **S21**, which extends leftwards from one side surface of the first area **S1** of the body **20** located between two adjacent guide portions **20-2** and **20-3**, and a second-second area **S22**, which extends rightwards from the other side of the first area **S1** of the body **20** located between the other two adjacent guide portions **20-1** and **20-4**. The second-first area **S21** and the second-second area **S22** may be parallel to the first area **S1**, but the embodiment is not limited thereto.

The bracket **330** may be formed of a metal material, for example, aluminum, copper, or the like, in order to easily withstand the weight of the first and second imaging units **100A** and **100B**, to protect the first and second imaging units **100A** and **100B** from external impact, and to easily dissipate heat generated from the image sensor **160** or various elements mounted on the circuit board of the first and second imaging units **100A** and **100B**.

FIG. **22** illustrates a bottom view of another embodiment **150-1** of the circuit board illustrated in FIG. **20**.

Referring to FIG. **22**, the circuit board **150-1** of each of the first and second imaging units **100A** and **100B** may be a double-sided printed circuit board including an insulating plate and a copper foil or copper wire, and may include a first area **158** and a second area **159**.

The first area **158** of the circuit board **150-1** may be an area in which a circuit pattern or a wiring pattern, to which the image sensor **160** and various elements are electrically connected, is formed.

The second area **159** of the circuit board **150-2** may be an area which is not electrically connected to the image sensor

160 and various elements, or an area, which corresponds to a common ground of the image sensor **160** and various elements.

The copper foil in the area **159** of the circuit board **150-1** may be exposed from the lower surface of the circuit board **150-1**, which is an insulating plate.

The copper foil of the second area **159** of the circuit board **150-1** exposed from the lower surface of the circuit board **150-1** of the first imaging unit **100A** may be in contact with the upper surface of the bracket **300**, and the copper foil of the second area **159** of the circuit board **150-1** exposed from the lower surface of the circuit board **150-1** of the second imaging unit **100B** may be in contact with the lower surface **20b** of the bracket **300**.

The copper foil of the first area **158** of the circuit board **150-1** is not exposed from the lower surface of the circuit board **150-1**. This is because short-circuiting may occur between the image sensor **160** and various elements when the copper foil of the first area **158** of the circuit board **150-1** is exposed.

Since the image sensors **160** of the first and second imaging units **100A**, **100B** are positioned adjacent to each other and have a structure in which they are coupled to each other, when the bracket **300** does not easily dissipate the heat generated from the image sensors **160** of the first and second imaging units **100A** and **100B**, the image sensors and various elements may be subjected to heat damage or may malfunction.

Since the heat generated from the image sensors **160** of the first and second imaging units **100A** and **100B** is transferred to the bracket **300** through the exposed copper foil of the second area **159** of the circuit board **150-1**, the embodiment may enhance thermal conductivity and heat dissipation efficiency.

The circuit board **150-1** of FIG. **22** may be applied to the camera modules **100** and **100-1** according to the embodiments.

In order to enhance thermal conductivity from the image sensors **160** to the bracket **300**, a thermally conductive pad or a thermally conductive tape may be additionally disposed between the exposed copper foil of the second area **159** of the circuit board **150-1** and the upper or lower surface of the bracket **300**.

FIG. **23** illustrates a thermally conductive tape **320** according to an embodiment.

Referring to FIG. **23**, the thermally conductive tape **320** may be disposed between the exposed copper foil of the second area **159** of the circuit board **150-1** of each of the first and second imaging units **100A** and **100B** and the upper surface **20a** or the lower surface **29b** of the bracket **300**. The thermally conductive tape **320** may enhance the adhesive force between the circuit board **150-1** of each of the first and second imaging units **100A** and **100B** and the upper surface **20a** or the lower surface **20b** of the bracket **300** and may enhance thermal conductivity and efficiency of heat dissipation from the image sensor **160** to the bracket **300**.

In addition, the thermally conductive tape **320** may be an electrical insulator for electrical insulation between the second area **159** of the circuit board **150-1** exposed from the lower surface of the circuit board **150-1** and the bracket **300**.

In addition, the camera module **100** or **100-1** according to the embodiment may be included in an optical instrument, which forms an image of an object in a space using reflection, refraction, absorption, interference, diffraction, or the like, which are characteristics of light, and may have the purpose of increasing visibility to the eyes, of recording and forming an image using a lens, or of performing optical

measurement or image propagation or transmission, for example. Examples of the optical instrument according to the embodiment may include a smart phone and a portable terminal equipped with a camera.

FIG. **24** illustrates a perspective view of a portable terminal **200A** according to the embodiment, and FIG. **25** illustrates a view of the configuration of the portable terminal illustrated in FIG. **24**.

Referring to FIGS. **24** and **25**, the portable terminal **200A** (hereinafter referred to as "terminal") may include a body **850**, a wireless communication unit **710**, an A/V input unit **720**, a sensing unit **740**, an input/output unit **750**, a memory **760**, an interface unit **770**, a controller **780**, and a power supply unit **790**.

The body **850** illustrated in FIG. **24** has a bar shape, but is not limited thereto. The body may have any of various structures such as a slide type, a folder type, a swing type, or a swivel type, in which two or more sub-bodies are coupled so as to be movable relative to each other.

The body **850** may include a case (e.g., a casing, a housing, or a cover) forming the external appearance thereof. For example, the body **850** may be divided into a front case **851** and a rear case **852**. Various electronic components of the terminal may be mounted in the space formed between the front case **851** and the rear case **852**.

The wireless communication unit **710** may include one or more modules, which enable wireless communication between the terminal **200A** and a wireless communication system or between the terminal **200A** and the network in which the terminal **200A** is located. For example, the wireless communication unit **710** may include a broadcast receiving module **711**, a mobile communication module **712**, a wireless Internet module **713**, a near field communication module **714**, and a location information module **715**.

The audio/video (A/V) input unit **720** serves to input an audio signal or a video signal, and may include a camera **721** and a microphone **722**.

The camera **721** may be the camera module **100** or **100-1** according to the embodiment.

The sensing unit **740** may sense the current state of the terminal **200A**, such as the opening/closing state of the terminal **200A**, the position of the terminal **200A**, the presence or absence of a user touch, the orientation of the terminal **200A**, and the acceleration/deceleration of the terminal **200A**, and may generate a sensing signal for controlling the operation of the terminal **200A**. For example, when the terminal **200A** is in the form of a slide phone, the sensing unit may sense whether the slide phone is opened or closed. In addition, the sensing unit functions to sense whether or not the power supply unit **790** supplies a voltage, or whether or not the interface unit **770** is connected to an external device.

The input/output unit **750** serves to generate input or output related to a visual sense, auditory sense, tactile sense, or the like. The input/output unit **750** may generate input data for controlling the operation of the terminal **200A**, and may also display information processed in the terminal **200A**.

The input/output unit **750** may include a keypad unit **730**, a display module **751**, a sound output module **752**, and a touchscreen panel **753**. The keypad unit **730** may generate input data in response to input made on a keypad.

The display module **751** may include a plurality of pixels, the color of which changes in response to an electric signal. For example, the display module **751** may include at least one selected from among a liquid crystal display, a thin film

27

transistor-liquid crystal display, an organic light-emitting diode, a flexible display, and a three-dimensional display (3D display).

The sound output module **752** may output audio data received from the wireless communication unit **710** in a call signal reception mode, a call mode, a recording mode, a voice recognition mode, a broadcast reception mode, or the like, or may output audio data stored in the memory **760**.

The touchscreen panel **753** may convert a change in capacitance caused by a user's touch on a specific area of a touchscreen into an electric input signal.

The memory **760** may store a program for processing and controlling the controller **780**, and may temporarily store input/output data (e.g., a telephone directory, messages, audio, still images, photographs, and moving images). For example, the memory **760** may store an image photographed by the camera **721**, for example, a photograph or a moving image.

The interface unit **770** serves as a connection path for an external device connected to the terminal **200A**. The interface unit **770** receives data from the external device, or receives a voltage and transmits the voltage to each component in the terminal **200A**, or allows data in the terminal **200A** to be transmitted to the external device. For example, the interface unit **770** may include a wired/wireless headset port, an external charger port, a wired/wireless data port, a memory card port, a port for connecting a device equipped with an identification module, an audio input/output (I/O) port, a video input/output (I/P) port, an earphone port, and the like.

The controller **780** may control the overall operation of the terminal **200A**. For example, the controller **780** may perform related control and processing for voice call, data communication, video call, and the like. The controller **780** may include a multimedia module **781** for multimedia playback.

The controller **780** may perform a pattern recognition process for recognizing handwriting input or drawing input performed on the touchscreen as characters and images, respectively.

The power supply unit **790** may supply external power or internal power according to the control of the controller **780**, and may supply the voltage required for the operation of the respective components.

The above described features, configurations, effects, and the like are included in at least one of the embodiments, and should not be limited to only one embodiment. In addition, the features, configurations, effects, and the like as illustrated in each embodiment may be implemented with regard to other embodiments as they are combined with one another or modified by those skilled in the art. Thus, content related to these combinations and modifications should be construed as including in the scope and spirit of the embodiments as disclosed in the accompanying claims.

INDUSTRIAL APPLICABILITY

Embodiments may be used for a camera module, which enables active alignment of a lens array unit and is capable of preventing the lens array unit from being out of focus, and an optical apparatus including the camera module.

The invention claimed is:

1. A camera module comprising:

- a first lens barrel comprising a lower surface and a first protrusion protruding from the lower surface;
- a first lens array comprising a plurality of first lenses disposed in the first lens barrel;

28

a first holder comprising a first hole into which the first protrusion is inserted;

a first adhesive member disposed between a first portion of a lower surface of the first lens barrel around the first protrusion and a second portion of an upper surface of the first holder around the first hole; and

a first image sensor disposed under the first hole, wherein the first portion is opposite to the second portion in an optical axis direction and the first adhesive member is configured to couple the first portion and the second portion, and

wherein the first adhesive member comprises one end and a remaining end, which are disposed so as to surround the first hole, and the one end and the remaining end of the first adhesive member are spaced apart from each other.

2. The camera module according to claim **1**, wherein an outer circumferential surface of the first protrusion inserted into the first hole and an inner circumferential surface of the first hole are spaced apart from each other.

3. The camera module according to claim **1**, wherein the first holder comprises:

a body portion accommodating the first image sensor therein; and

a support portion protruding from an upper surface of the body portion, and

wherein the first hole penetrates the body portion and the support portion, and the first adhesive member is disposed on an upper surface of the support portion.

4. The camera module according to claim **1**, wherein the first adhesive member has a ring shape having an opening in a transverse direction between the one end and the remaining end thereof which are spaced apart from each other.

5. The camera module according to claim **3**, wherein the upper surface of the support portion is disposed with a first groove, which is filled with a portion of the first adhesive member.

6. The camera module according to claim **4**, further comprising a second adhesive member disposed in the opening in the first adhesive member between the first lens barrel and an upper surface of the support portion of the first holder.

7. The camera module according to claim **6**, wherein the second adhesive member is in contact with outer surfaces of the one end and the remaining end of the first adhesive member, and is spaced apart from inner surfaces of the one end and the remaining end of the first adhesive member.

8. The camera module according to claim **5**, wherein the first groove takes the form of a ring disposed on the upper surface of the support portion around the first hole.

9. The camera module according to claim **7**, wherein a length of the second adhesive member in a direction perpendicular to a longitudinal direction of the second adhesive member is less than a length of the first adhesive member in a direction perpendicular to a longitudinal direction of the first adhesive member.

10. The camera module according to claim **6**, wherein a second groove is disposed in the upper surface of the support portion of the first holder corresponding to the opening in the first adhesive member, and the second adhesive member is disposed in the second groove, and the opening in the first adhesive member between the first lens barrel and the upper surface of the support portion of the first holder.

11. The camera module according to claim **10**, wherein one end of the second groove is open to the first hole, and a remaining end of the second groove is open to an outside of a side surface of the support portion.

29

12. The camera module according to claim 11, wherein the second adhesive member is disposed closer to the remaining end of the second groove than the one end of the second groove.

13. The camera module according to claim 1, wherein a part of the plurality of first lenses is disposed inside the first protrusion.

14. The camera module according to claim 6, wherein the first adhesive member is a UV-curable and thermosetting adhesive member and the second adhesive member is a UV-curable adhesive member.

15. The camera module according to claim 1, wherein a distance between the one end of the first adhesive member and the remaining end of the first adhesive member gradually increases in a direction from an inner circumferential surface to an outer circumferential surface of the first adhesive member.

16. A camera module comprising:

a lens barrel including a plurality of seating portions defining hollow regions having different diameters;

a lens array including a plurality of lenses disposed on the plurality of seating portions;

a holder including a body portion, a support portion protruding from the body portion, and a hole penetrating the body portion and the support portion, a lowermost seating portion among the plurality of seating portions being inserted into the hole;

a first adhesive member disposed between a first portion of a lower surface of the lens barrel around the lowermost seating portion and a second portion of an upper surface of the holder; and

an image sensor disposed under the hole,

wherein the first portion is opposite to the second portion in an optical axis direction and the first adhesive member is configured to couple the first portion and the second portion,

wherein one end and a remaining end of the first adhesive member are disposed on an upper surface of the support portion around the hole and the one end, and the remaining end of the first adhesive member are spaced apart from each other, and

wherein an outer circumferential surface of the lowermost seating portion inserted into the hole and an inner circumferential surface of the hole are spaced apart from each other.

17. The camera module according to claim 16, wherein the lens barrel includes:

a first seating portion defining a first hollow region having a first diameter;

30

a second seating portion protruding from a lower surface of the first seating portion and defining a second hollow region having a second diameter; and

a third seating portion protruding from a lower surface of the second seating portion and having a third diameter, wherein the third seating portion is inserted into the hole, and the first adhesive member is disposed between the lower surface of the second seating portion and the upper surface of the support portion of the holder.

18. The camera module according to claim 16, wherein the first adhesive member has an opening in a transverse direction,

wherein a groove is formed in the upper surface of the support portion of the holder corresponding to the opening in the first adhesive member, and

wherein one end of the groove is open to the hole, and a remaining end of the groove is open to an outside of a side surface of the support portion.

19. The camera module according to claim 18, further comprising a second adhesive member disposed in the groove and the opening in the first adhesive member between the lower surface of the second seating portion and the upper surface of the support portion of the holder.

20. A camera module comprising:

a lens barrel including a protrusion protruding from a center portion of a lower surface;

a plurality of lenses disposed in the lens barrel;

a holder including a hole into which the protrusion is inserted;

a first adhesive member disposed between a first portion of the lower surface of the lens barrel around the protrusion and a second portion of an upper surface of the holder around the hole; and

an image sensor disposed under the holder,

wherein the first portion is opposite to the second portion in an optical axis direction and the first adhesive member is configured to couple the first portion and the second portion,

wherein the first adhesive member takes the form of a ring having one end and a remaining end which are spaced apart from each other,

wherein an opening is disposed between the one end and the remaining end of the first adhesive member, and

wherein one end of the opening is open to an inner circumferential surface of the first adhesive member, and a remaining end of the opening is open to an outer circumferential surface of the first adhesive member.

* * * * *