

US010965678B2

(12) **United States Patent  
Pike**

(10) **Patent No.: US 10,965,678 B2**  
(45) **Date of Patent: Mar. 30, 2021**

(54) **ROLLING SECURITY PLATFORM**  
(71) Applicant: **Cyemptive Technologies, Inc.**  
(72) Inventor: **Robert Pike**, Woodinville, WA (US)  
(73) Assignee: **CYEMPTIVE TECHNOLOGIES, INC.**, Woodinville, WA (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/820,618**

(22) Filed: **Mar. 16, 2020**

(65) **Prior Publication Data**  
US 2020/0358772 A1 Nov. 12, 2020

**Related U.S. Application Data**  
(63) Continuation of application No. 15/875,894, filed on Jan. 19, 2018, now Pat. No. 10,616,229, which is a (Continued)

(51) **Int. Cl.**  
**G06F 21/57** (2013.01)  
**G06F 21/62** (2013.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... **H04L 63/10** (2013.01); **G06F 9/5077** (2013.01); **G06F 21/57** (2013.01);  
(Continued)

(58) **Field of Classification Search**  
CPC ... H04L 63/10; H04L 63/0846; H04L 63/102; H04L 63/108; H04L 63/1408;  
(Continued)

(56) **References Cited**  
U.S. PATENT DOCUMENTS  
7,260,640 B1 8/2007 Kramer et al.  
7,757,226 B2\* 7/2010 Srivastava ..... G06F 8/65  
717/170


(Continued)  
**FOREIGN PATENT DOCUMENTS**  
CN 1328744 A 12/2001  
CN 1780219 A 5/2006  
(Continued)

**OTHER PUBLICATIONS**  
European Extended Search Report, European Application No. 16740600.8, dated Oct. 16, 2018, 4 pages.  
(Continued)

*Primary Examiner* — Techane Gergiso  
(74) *Attorney, Agent, or Firm* — Fenwick & West LLP

(57) **ABSTRACT**  
A method of rolling security for a system that includes multiple server groups, such as a first server group of one or more servers and a second server group of one or more servers. The method includes repeatedly initiating rebuilding of the first server group of one or more servers. The method also includes repeatedly initiating rebuilding of the second server group of one or more servers. The rebuilding of the first server group of one or more servers is staggered in time from the rebuilding of the second server group of one or more servers. The servers may be physical servers or virtual machines. Rolling security may also be applied to software containers, computing devices within a data center, and computing devices outside of a datacenter.

**18 Claims, 10 Drawing Sheets**



**Related U.S. Application Data**

continuation of application No. 14/857,775, filed on Sep. 17, 2015, now Pat. No. 9,906,530.

(60) Provisional application No. 62/105,685, filed on Jan. 20, 2015.

(51) **Int. Cl.**  
*H04L 29/06* (2006.01)  
*H04L 29/08* (2006.01)  
*G06F 9/50* (2006.01)

(52) **U.S. Cl.**  
 CPC ..... *G06F 21/6218* (2013.01); *H04L 63/0846* (2013.01); *H04L 63/102* (2013.01); *H04L 63/108* (2013.01); *H04L 63/1408* (2013.01); *H04L 63/1416* (2013.01); *H04L 63/1425* (2013.01); *H04L 63/1441* (2013.01); *H04L 63/1466* (2013.01); *H04L 63/20* (2013.01); *H04L 67/148* (2013.01); *H04L 63/0263* (2013.01); *H04L 67/42* (2013.01)

(58) **Field of Classification Search**  
 CPC ..... H04L 63/1416; H04L 63/1425; H04L 63/1441; H04L 63/1466; H04L 63/20; H04L 67/148; H04L 63/0263; H04L 67/42; G06F 9/5077; G06F 21/57; G06F 21/6218

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

8,108,734	B2 *	1/2012	Andrews .....	G06F 3/0653 714/47.1
8,510,807	B1	8/2013	Elazary et al.	
8,966,474	B2 *	2/2015	Herington .....	G06F 9/45558 718/1
9,219,705	B2 *	12/2015	Heinson .....	H04L 29/12066
9,614,853	B2	4/2017	Pike	
9,740,472	B1 *	8/2017	Sohi .....	G06F 8/65
9,960,963	B2 *	5/2018	Selvaraj .....	H04L 41/0889
10,341,349	B2	7/2019	Pike	
2001/0037399	A1	11/2001	Eylon et al.	
2002/0087994	A1	7/2002	Gomez	
2002/0188706	A1	12/2002	Richards et al.	
2003/0126202	A1	7/2003	Watt	
2003/0208612	A1	11/2003	Harris et al.	
2004/0103337	A1	5/2004	Smith	
2004/0117622	A1	6/2004	Marquet et al.	
2004/0210582	A1 *	10/2004	Chatterjee .....	G06F 16/27
2004/0255189	A1	12/2004	Chu et al.	
2005/0188222	A1	8/2005	Motsinger et al.	
2005/0210461	A1 *	9/2005	Srivastava .....	G06F 8/656 717/170
2005/0257211	A1 *	11/2005	Chatterjee .....	G06F 8/656 717/170
2007/0106798	A1	5/2007	Masumitsu et al.	
2008/0046982	A1	2/2008	Parkinson	
2008/0104411	A1	5/2008	Agrawal et al.	
2008/0183975	A1	7/2008	Foster et al.	
2008/0250419	A1 *	10/2008	Kasten .....	H04L 67/32 718/104
2010/0274885	A1	10/2010	Yoo et al.	
2010/0281102	A1	11/2010	Chinta et al.	

2010/0306578	A1	12/2010	Thornton et al.	
2011/0055921	A1	3/2011	Narayanaswamy et al.	
2011/0219437	A1	9/2011	Ohkado	
2011/0238924	A1	9/2011	Hampton et al.	
2011/0296245	A1 *	12/2011	Alberi .....	G06F 11/3664 714/38.1
2011/0302653	A1	12/2011	Frantz et al.	
2012/0209977	A1	8/2012	Nakajo	
2012/0240185	A1	9/2012	Kapoor et al.	
2013/0111497	A1	5/2013	Chen et al.	
2013/0160122	A1	6/2013	Choi et al.	
2013/0238928	A1	9/2013	Watanabe et al.	
2014/0108775	A1	4/2014	Kludy et al.	
2016/0092308	A1	3/2016	Bates	
2016/0156611	A1	6/2016	Rozman	

FOREIGN PATENT DOCUMENTS

CN	101741832	A	6/2010
CN	101960824	A	1/2011
CN	103051623	A	4/2013
CN	104133730	A	11/2014
JP	2001249908	A	9/2001
JP	2002/111727	A	4/2002
JP	2007/116405	A	5/2007
JP	2007172093	A	7/2007
JP	2009/232111	A	10/2009
JP	2010244515	A	10/2010
JP	2010277143	A	12/2010
JP	2013008322	A	1/2013
WO	WO-2016118517	A1	7/2016

OTHER PUBLICATIONS

National Intellectual Property Administration, Office Action, Chinese Patent Application No. 201680006089.X, dated Nov. 4, 2019, 18 pages.

National Intellectual Property Administration, Office Action, Chinese Patent Application No. 201680006399.1, dated Nov. 29, 2019, 26 pages.

Neamtiu, I. et al., "Cloud Software Upgrades: Challenges and Opportunities," 2011 International Workshop on the Maintenance and Evolution of Service-Oriented and Cloud-Based Systems (MESOCA), IEEE, Sep. 26, 2011, pp. 1-10.

Openstack: "Upgrade-with-minimal-downtime," Sep. 28, 2011, 9 pages, [Online] [Retrieved on Oct. 5, 2018] Retrieved from the Internet<URL:https://wiki.openstack.org/wiki/Upgrade-with-minimal-down-time>.

PCT International Search Report and Written Opinion, PCT Application No. PCT/US16/13942, dated Apr. 19, 2016, 14 pages.

PCT International Search Report and Written Opinion, PCT Application No. PCT/US16/13944, dated Mar. 28, 2016, 15 pages.

PCT/US16/13942, dated Apr. 19, 2016, 14 pages.

United States Office Action, U.S. Appl. No. 14/857,775, dated Dec. 1, 2016, 16 pages.

United States Office Action, U.S. Appl. No. 14/857,775, dated Jun. 14, 2017, 16 pages.

China National Intellectual Property Administration, Chinese Patent Application No. 201680006089.X, Apr. 30, 2020, 6 pages.

United States Office Action, U.S. Appl. No. 15/875,894, dated May 29, 2019, 17 pages.

United States Office Action, U.S. Appl. No. 15/875,894, dated Sep. 21, 2018, 21 pages.

United States Office Action, U.S. Appl. No. 16/416,946, dated Oct. 30, 2020, 12 pages.

\* cited by examiner




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 2A




FIG. 2B




FIG. 2C






FIG. 3




FIG. 4




FIG. 5




FIG. 6

**ROLLING SECURITY PLATFORM****CROSS REFERENCE TO RELATED APPLICATIONS**

This application is a continuation of U.S. application Ser. No. 15/875,894, filed Jan. 19, 2018, which is a continuation of U.S. application Ser. No. 14/857,775, filed Sep. 17, 2015, which claims priority from U.S. Provisional Patent Application No. 62/105,685, filed on Jan. 20, 2015, the contents of which are incorporated by reference in its entirety.

**BACKGROUND**

## 1. Field

The present disclosure relates to computer security against unauthorized access to resources, and more specifically to a rolling security platform for increased security.

## 2. Description of Related Art

In network communications there are many forms of software and hardware security, including firewalls and intrusion detection and prevention systems. But they all fault on one core issue, that if rules are not applied correctly they can open opportunities for unauthorized access. Operating systems and applications today also have many bugs which if exposed to the internet, can enable remote access to servers hosting the applications.

**SUMMARY**

Embodiments of the present disclosure include intelligent methods and systems of providing online security against hackers. In one embodiment, disclosed is a system for rolling security. The system comprises a first server group of servers and a second server group of servers. Each server in the first server group and second server group includes software that includes an operating system and application that supports user sessions. A non-transitory computer readable medium stores instructions that, when executed by at least one processor cause the at least one processor to access rolling timing information indicating rebuild timings for the first server group and rebuild timings for the second server group. The rebuild timings for the first server group are staggered in time from the rebuild timings of the second server group. The instructions also cause the processor to periodically initiate rebuilding of the software of each server of the first server group of servers according to the rebuild timings for the first server group. The instructions also cause the processor to periodically initiate rebuilding of the software of each server in the second server group of servers according to the second rebuild timings for the second server group. The rebuilding of the first server group of servers is staggered in time from the rebuilding of the second server group of servers.

In one embodiment, a method of rolling security for a system that includes multiple server groups is disclosed. The method includes repeatedly initiating rebuilding of the first server group of one or more servers. The method also includes repeatedly initiating rebuilding of the second server group of one or more servers. The rebuilding of the first server group of one or more servers is staggered in time from the rebuilding of the second server group of one or more servers.

In one embodiment, each of the servers in the first and second group include software that is rebuilt repeatedly, such as on a periodic basis. The software that is rebuilt can include an operating system, application, and other software.

In one embodiment, each of the servers in the first and second server group includes a respective firmware. Repeatedly initiating rebuilding of the first server group comprises initiating a rebuilding of the respective firmware in each server of the first server group. Repeatedly initiating rebuilding of the second server group comprises initiating a rebuilding of the respective firmware in each server of the second server group.

In one embodiment, each of the servers in the first and second server group includes a respective password. The method also comprises repeatedly initiating a password change of each server in the first server group when rebuilding the first server group; and repeatedly initiating a password change of each server in the second server group when rebuilding the second server group.

In one embodiment, the method comprises accessing rolling timing information indicating rebuild timings for rebuilding the first server group and second server group. The first server group and the second server group are repeatedly rebuilt according to the rolling timing information. Additionally, each of the servers in the first server group and the second server group host respective applications and support user sessions for the applications, and the method further comprises monitoring durations of the user sessions for the respective applications; and generating the rolling timing information indicating rebuild timings for the first server group and the second server group based on the monitored durations of the user sessions.

In one embodiment, the servers in the first server group and the second server group that are repeatedly rebuilt are physical servers. In one embodiment, the servers in the first server group and the second server group that are repeatedly rebuilt are virtual machines.

In one embodiment, the system further comprises one or more load balancers to balance network traffic between the first server group and the second server group. The method also comprises repeatedly initiating shutdown preparation mode of the first server group prior to each rebuilding of the first server group, the load balancers preventing new sessions from being established with applications of the first server group while the first server group is in shutdown preparation mode. The method also comprises repeatedly initiating shutdown preparation mode of the second server group prior to each rebuilding of the second server group, the load balancers preventing new sessions from being established with applications of the second server group while the second server group is in shutdown preparation mode.

Other embodiments include a non-transitory computer readable medium storing instructions. The instructions are executable by at least one processor to cause the at least one processor to perform the method of rolling security. Other embodiments may apply rolling security to software containers. Other embodiments may apply rolling security to networked computing devices within a datacenter, or computing devices outside of a datacenter.

**BRIEF DESCRIPTION OF THE DRAWINGS**

FIG. 1A is a block diagram of networked communication system with components of a secured datacenter for rolling security, according to an embodiment.

## 3

FIG. 1B is a block diagram of networked communication system with components of a secured datacenter for rolling security, according to another embodiment.

FIG. 1C is a block diagram of networked communication system with components of a secured datacenter for rolling security, according to a further embodiment.

FIG. 2A is a block diagram of a frontend server from FIG. 1A, according to an embodiment.

FIG. 2B is a block diagram of a server with virtual machines, according to an embodiment.

FIG. 2C is a block diagram of a server with software containers, according to an embodiment.

FIG. 3 is a diagram of rolling server groups, according to an embodiment.

FIG. 4 is a block diagram of a security control module, according to an embodiment.

FIG. 5 is a flowchart for a method of rolling security, according to an embodiment.

FIG. 6 illustrates the hardware architecture of a computing device.

## DETAILED DESCRIPTION

Reference will now be made in detail to several embodiments of the present disclosure, examples of which are illustrated in the accompanying figures. It is noted that wherever practicable similar or like reference numbers may be used in the figures and may indicate similar or like functionality. The figures depict embodiments of the present disclosure for purposes of illustration only. One skilled in the art will readily recognize from the following description that alternative embodiments of the structures and methods illustrated herein may be employed without departing from the principles, or benefits touted, of the disclosure described herein.

The present disclosure relates to a system platform that prevents hackers from gaining access to backend datasets and prevents ongoing access to any dataset. More particularly, this invention can stop escalating access to unauthorized resources for a higher security solution.

In one embodiment, a security platform for a datacenter is disclosed. The security platform continually and repeatedly rebuilds itself in a rolling manner based on specific metrics of time. The rolling security will automatically replace server software in short periods of time to completely wipe out any configuration or holes found in operating systems or applications, thereby limiting access to any server to a short period of time. For example, this time can be as short as 10 seconds or as long as hours. In one embodiment, a standard configuration will default to 10 min between rebuilds. Hackers will have such a short window in which to learn the hack, figure out what the architecture is in the backend, compromise the server and try to install a root kit for further access. Thus, it is pointless for the hackers to attempt to complete their hack as the replacement of the server happens so often. By the time a hacker discovers a password or public key infrastructure (PKI) key, the operating system (OS) is being replaced along with new passwords and keys.

The system can, but is not limited to, replace the whole software stack on a device including the OS, applications, content, data and cache within a short period of time. The system can be fully integrated with multiple devices in a network (e.g. load balancer, firewalls, etc) to seamlessly manage both real users and hacker users. In other embodiments, session count, connection count, unique sensor triggers and other security indications can be used to trigger rebuilds. In other embodiments, a session can be dynami-

## 4

cally contained into an isolated environment and a time of the session can extended to learn the hacks being performed in an isolated environment.

The system can dynamically learn the applications average session counter and time and adjust the rebuild timing dynamically or have a manual configuration to enable tighter security policies. The system limits the time any single session can be connected to a front end application and dataset to prevent long term remote access to any system.

FIG. 1A is a block diagram of networked communication system with components of a secured datacenter for rolling security, according to an embodiment. The system includes several client devices **105**, a network **110**, a router **115**, frontend firewalls **120A-C**, load balancers **125A-C**, frontend server groups **130A-130D**, backend firewalls or load balancers **132A-C**, backend server groups **135A-135D**, storage systems **140A-140D** and security server **148**. Routers, firewalls **120**, load balancer **125**, frontend servers **130**, firewall **132**, backend server **135**, and storage systems **140** may be components of a datacenter. Only a limited number of devices are shown in FIG. 1A, but in other embodiments there may be a larger number of devices (e.g. >four frontend server groups).

Client devices **105** can be computing devices, such as smartphones, tablet computers, laptop computers, and desktop computers, among others. A user interacts with software of the client devices **105** through an interface, such as a touchscreen or mouse and keyboard. The client devices **105** are controlled by the user to establish application sessions and connections with various applications hosted by the frontend server groups **130**.

The router **115** routes network traffic between the network **110** and the rest of the components in the datacenter. The frontend firewalls **120** are hardware based firewall devices that control incoming and outgoing network traffic using an applied rule set. A firewall establishes a barrier between the internal network of the datacenter and the external network **110**. The load balancers **125** distribute network traffic across a large number of frontend server groups **130**. The load balancers increase capacity and reliability of applications by decreasing the burden on any one particular frontend server group **130**.

Each frontend server group **130** includes several physical frontend servers. A server is a server class computing device that can include one or more processors and executes an operating system. A server hosts several software applications. The clients **105** can establish networking connections and application sessions with the applications hosted by the frontend servers. For security purposes, each server group can be rolled (i.e. by rebuilding the server group) after expiration of an amount of time and the server groups can be rolled in staggered manner. Copies of the same application are hosted by multiple server groups **130** so that, even as the server groups are rolled, the application is still available to the client devices **105**. In one embodiment there are a total of nine frontend server groups **130** and each frontend server group **130** includes thousands of frontend servers.

The backend firewalls **132** are hardware based firewall devices, or virtual firewalls, that control traffic between the frontend server groups **130** and backend server groups **135** using an applied rule set. Each backend server group **135** includes one or more backend servers. Backend servers permit access to the data stored in the storage systems **140**. Backend servers store and retrieve data from the storage systems **140** as requested by the applications hosted by the

frontend servers groups **130**. An example of a backend server is a SQL server that provides access to a SQL database.

Security server **148** includes a security control module **150** that coordinates rolling operation of the frontend server groups **130**. Specifically, the security control module **150** repeatedly initiates rebuilds of the frontend server groups **130** at periodic and staggered intervals. Rebuilding a server can include replacing the entire software stack of a server, including the operating system (OS), applications, content, data and caches by replacing a hard drive image of the server with a known good replacement image. Rebuilding a server can also include replacing the firmware of a server. Rebuilding may also include other operations in addition to these operations. The time between rebuilds can be as short as 10 seconds or as long as hours. In other embodiments the standard rebuild time will default to 10 min.

Repeatedly rebuilding servers on a periodic and frequent basis forces hackers to complete their hack in a short amount of time (e.g. under 5 seconds) which is near impossible as response times and upload times usually require a greater amount of time. For example, for a DNS server, the DNS server can be rebuilt every 10 seconds with a new OS and DNS database cache. In this situation, hackers will not have time to hack the protocol and upload bogus data by cache spoofing. Any malicious code uploaded by the hackers will also be eliminated. Everything tied to the server will be replaced, making it impossible to remote into the OS from outside. At the same time, all the content needed for standard customer requests are served correctly. This completely solves any holes found in today's software.

The security control module **150** also initiates the rebuilds on a rolling basis by staggering the rebuilding of each frontend server group (e.g. **130A**) in time relative to the other frontend server groups (e.g. **130B**). Each frontend server group **130** will start servicing user sessions at different times creating a staggering approach to when a server group **130** will come online and start serving traffic. The process from which a session starts and ends all happens within a single server or group of servers **130**. This allows for simple load balancing within the group but also allows for termination of a session to happen within the group. The servers within a server group **130** will replace their OS at the same time while other server groups **130** are just coming online and servicing the new user sessions. The timeframe to rebuild a server group **130** can vary depending on the functionality of the applications in the server groups **130**.

The security control module **150** also communicates with the load balancers **125** such that the load balancers **125** are aware of the server group being shut down for new OS installs, thereby allowing the load balancers **125** to distribute network traffic only to server groups **130** that are online. The security control module **150** can transmit information to the load balancers **125** to indicate when a server group **130** is beginning preparation for shutting down. In response, the load balancers **125** take the server group **130** offline and prevent new connections from being established with the server group **130**. Once the server group **130** is rebuilt, the security control module **150** can transmit information to the load balancers **125** indicating that the server group **130** is ready to accept new connections. In response, the load balancers **125** put the server group **130** back online and allows new connections to be established with the server group **130**.

The security control module **150** can also change the password of the server groups **130** when rebuilding the

server groups **130**. Frequent password changes make it impossible to do password attacks on servers.

The security control module **150** can be implemented as software, hardware, or as a combination of hardware and software. In other embodiments, the security control module **150** can be distributed across one or more components of the datacenter other than the security server **148**.

FIG. **1B** is a block diagram of networked communication system with components of a secured datacenter for rolling security, according to another embodiment. FIG. **1B** is similar to FIG. **1A** except that it now includes frontend virtual machine (VM) groups **160** and hypervisors **190**. Each VM group **160** includes one or more VMs. A VM is an emulation of a computer system, such as an emulation of a computer server. Each VM may be attached to its own virtual disk. A VM may be referred to herein as a virtual server.

Hypervisor **190** creates and manages the VMs groups **160**. Each hypervisor **190** may be located on its own physical front end server **159**, and also control a group of VMs **160** that are located on the same physical front end server. For example, Hypervisor **190A** and VM group **160A** are located on a single physical server **159A**.

In this embodiment, the security control module **150** provides rolling security to the networked communication system by periodically initiating rebuilds of the frontend VM groups **160** (i.e. virtual server groups). Copies of the same application are hosted by multiple VM groups **160** so that the application is always online even as the VM groups **160** are being rebuilt. Rebuilding a VM can include restoring the state of a VM to an original known good state. Rebuilding will be explained in greater detail below.

Otherwise the operation of the security control module **150** is the same as that described in conjunction with FIG. **1A**. In one embodiment, the networked communication system may include both physical server groups and virtual server groups that are rebuilt on a periodic and staggered basis.

FIG. **1C** is a block diagram of networked communication system with components of a secured datacenter for rolling security, according to a further embodiment. FIG. **1C** is similar to FIG. **1B** except that it now includes container groups **960** and container engines **990** located on the servers **159**.

Each container group **960** includes one or more software containers used for operating system level virtualization. A software container includes an application, its dependencies, libraries and binaries bundled into a single package. A software container shares an operating system (not shown) with other software containers on the same server **159**. A software container is instantiated within the kernel of the operation system and virtualizes the instance of the application. Software containers allow for rapid creation of an application or service to be put into a block of resources. The deployment of a container is fast because containers can share core library files from the core OS. The software containers are managed by a container engine **990**. In one embodiment, the software containers **960** are DOCKER containers or are compliant with the open container project standard.

In this embodiment, the security control module **150** provides rolling security to the networked communication system by periodically initiating rebuilds of the container groups **960** on a rolling basis. Copies of the same application are included in multiple container groups **960** so that the application is always online even as some of the container groups **960** are being rebuilt. A container can be rebuilt by

restoring the container to a known good state. Rebuilding will be explained in greater detail below.

Otherwise the operation of the security control module **150** is the same as that described in conjunction with FIGS. **1A** and **1B**. In one embodiment, rebuilding containers can be more efficient than rebuilding physical servers and virtual machines. For example, containers can be restored and deployed in ~30 seconds. By contrast, rebuilding servers and virtual machines can take much longer. Although rolling containers can be easier than rolling physical servers and VMs, they have higher risks due to the use of shared core OS files. Hypervisor architectures also have risk, but because the OS is dedicated to each VM, it reduces the risk compared to a container platform. The risk is lower again when rolling physical servers as a hacker will need to have BIOS level control of a server to do server hijacking, or the hacker will need remote management tools access.

The description herein may primarily focus on the rolling of physical servers or virtual machines. However, the principles of rolling security described herein are applicable to rolling of physical servers, virtual machines, or containers.

FIG. **2A** is a block diagram of a frontend server **200**, according to an embodiment. Frontend server **200** may represent a frontend server from the frontend server groups **130** of FIG. **1A**. Frontend server **200** includes several software applications **250A-C**, an OS **152**, firmware **154** and a frontend security module **156**. Examples of OS **152** include LINUX and MICROSOFT WINDOWS, among others. The applications **250** are executed on top of the OS **152**. The firmware **154** includes software that is stored in a programmable memory chip.

The client devices **105** can establish networking connections **C1-C6** with the applications **250**. A connection is used as a bidirectional communication channel between sockets at the client devices **105** and the server **200**. The connection is established at a certain point in time using a handshake process, and then terminated at a later point in time. The connection may include several states defined by a protocol. An example of a connection is a transmission control protocol (TCP) connection of the transport layer of the Open Systems Interconnect (OSI) model.

The client devices **105** also establish application user sessions **S1-S6** with the applications **250** over the connections **C1-C6**. A user session is an interactive information exchange between two or more communicating entities for a given application. The user session is established at a certain point in time, and then terminated at a later point in time. During the user session, one or more messages may be sent in each direction over a connection that has been established for the session. In one embodiment, the application sessions are sessions of the OSI session layer that sit above the transport layer.

In one example, a credit card authentication session (e.g. **S1**, **S2**) can be initiated when a user swipes a credit card at a client device **105A**, and the client device **105A** establishes a connection and session with credit card payment application **250A**. Credit card payment application **250A** communicates with the client device **105A** to obtain the credit card number and charge amount from the client device **105A**. The credit card payment application **250** then accesses the database **140** via backend server **135** to determine if the credit card number has sufficient credit to process the payment. The credit card payment application **250** then provides a yes/no response to the client device **105A**. The connection and session are then terminated after providing the response to the client device **105A**.

In another example, a web form session (e.g. **S3**, **S4**) can be initiated when a user enters a URL into a browser at a client **105B**. The client device **105B** establishes a session with website **250B**. The server **200** may be processing multiple sessions. The server **200** starts a time counter per session. The user has x amount of time to fill out a form before the session closes. A different server may process the form submission from the initial session due to the time it takes to fill out the web form data.

In a further example, an online banking session (e.g. **S5**, **S6**) can be initiated when a user opens a mobile banking application at the client device **105B**, and the client device **105B** establishes a connection and session with online banking application **250C**. Online banking application **250C** communicates with the client device **105B** to obtain authentication information from the client device **105B**. Once authenticated, the client device **105B** can request account balances, upload copies of checks for deposit, and make other banking requests. The banking application **250C** can access account information stored in database **140** via backend server **135** to process these requests. The connection and session are eventually terminated at the end of the session.

Frontend security module **156** can communicate with the security control module **150** to send and receive security information to implement rolling security. The security module **156** can receive commands to initiate a rebuild of the frontend server **200**. The commands can include a name of a golden image, which is a known good master software image that is to be used as a template for the rebuild. The security module **156** then rebuilds the frontend server **200** in accordance with the commands, such as by replacing the OS **152**, applications and/or firmware **154**. The OS **152**, applications **250** and/or firmware **154** can be replaced by overwriting existing software on the server **200** with the golden image, deleting existing software on the server **200** and copying new software onto the server **200** from the golden image, etc. The golden image can be stored locally on a disc within the server **200** or elsewhere on a network.

Different rebuild techniques with varying rebuild times can be used. In one embodiment, a single golden image can be used to rebuild multiple servers **200**. Data from the golden image can be copied onto the frontend server **200**, and then post process configurations are executed on each frontend server **200** to configure the OS **152** or applications **250**. For example, a different script may be executed on each frontend server **200** to establish a unique name for the server and an IP address for the server. In one embodiment, there may be multiple golden images that are specific and unique to each frontend server **200**. The data from a golden image can be copied onto a respective server without the need for post process configurations, which reduces rebuild time.

In another embodiment, a data differencing technique is used to rebuild the frontend server **200**. Specifically, data blocks or files of the software of a frontend server **200** can be compared to data blocks or files of a golden image. Only the data blocks or files that are different are restored from the golden image. By leveraging block or file based differencing, rapid deployment of preconfigured OS and app configurations via local disk, remote SAN disks or NAS disks is possible. It should be noted that other rebuild techniques may be possible and still fall within the scope of the disclosure.

In one embodiment, various hash or encryption models or block state comparisons can be applied to a rebuilt software image to verify the rebuild is of standard expected configuration and the state is of a good known configuration. For example, the rebuilt software can be hashed and then com-



pared to the hash of the golden image to verify that the rebuild was performed as expected.

In one embodiment, the frontend security module **156** places a frontend server **200** into a lock down security mode during rebuilds for protection against tampering. During rebuilds, the frontend security module **156** may set its internal firewall access control lists (ACL) with permissions that block any traffic to certain ports other than communications with the security control module **150** of the security server **148**. An ACL can be a list of network ports, along with specific entities permitted to use the network ports. Other 3<sup>rd</sup> party applications may also be given access on a need basis for verification of state of compliance.

The security module **156** can also receive a command to change the password of the OS **152** and then replace the password in accordance with the command. In one embodiment, the security information is communicated via an intelligent platform management interface (IPMI).

FIG. 2B is a block diagram of a frontend server **202** with VMs **204**, according to an embodiment. Frontend server **202** may represent a frontend server **159** from FIG. 1B. Frontend server **202** includes several VMs **204**, hypervisor **208**, OS **152**, and frontend security module **156A**. Each VM includes a virtualized OS **206** and applications **250**.

Frontend security module **156A** is similar to frontend module **156**, but now rebuilds VMs in response to commands to rebuild the VMs **204**. The rebuilding of VMs **204** is similar to the rebuilding described with respect to FIG. 2A, and can also utilize a golden image of a VM **204** to generate a VM **204**, utilize data differencing, and/or perform rebuild verification after rebuilding the VM **204**.

FIG. 2C is a block diagram of a frontend server **290** with containers **292**, according to an embodiment. Frontend server **290** may represent a frontend server **159** from FIG. 1C. Frontend server **290** includes several containers **292**, container engine **294**, OS **152**, and frontend security module **156B**. Each container includes virtualized applications **250**.

Frontend security module **156B** is similar to frontend module **156**, but now rebuilds containers **292** on a rolling basis in response to commands to rebuild the containers **292**. The rebuilding of containers **292** is similar to the rebuilding described with respect to FIG. 2A, and can also utilize a golden image of a container **292** to generate a container **292**, utilize data differencing, and/or perform rebuild verification after rebuilding the container **292**.

FIG. 3 is a diagram of rolling server groups, according to an embodiment. The rolling operation of four server groups **130A-130D** is illustrated in FIG. 3. In other embodiments, the rolling operation shown in FIG. 3 is also applicable to rolling of VM groups **160** and software container groups **960**.

Each server group **130** operates in different rolling security modes: (1) a normal operation mode (2) a shutdown preparation mode and (3) a rebuilding mode. During the normal operation mode a server group **130** accepts and services new user sessions and connections. During the shutdown preparation mode the server group **130** does not accept new sessions and connections. Existing sessions and connections are allowed to finish. In one embodiment, the load balancers **125** may be notified that a particular server group **130** is being placed into shutdown preparation mode and is not accepting new sessions and connections. The load balancers **125** respond by removing the server group **130** from the possible server groups **130** to which new sessions and connections can be made. During the rebuilding mode the server group **130** is removed from service and is rebuilt

by replacing the software of the server group **130**. The modes repeat periodically, such as every 60 seconds.

The server groups **130** are operated in a rolling manner such that the rebuilding of different server groups is initiated at different times. For example, server group **130A** is rebuilt at 1:00:50, server group **130B** is rebuilt at 1:01:00, server group **130C** is rebuilt at 1:01:10, and server group **130D** is rebuilt at 1:01:20. The rebuild times are staggered from each other by ten seconds. The staggering of rebuild times ensures that there is always at least one server group **130** in service and available to accept new connections and user sessions for applications hosted by the server group **130**. In other words, there is always at least one server group **130** that is in normal operation mode.

In one embodiment, shutdown preparation mode may be delayed for a server group **130** if a security condition indicating the presence of a hacker is triggered. A security condition may be triggered, for example, if session is associated with a suspicious IP or has kept the session open for too long. In that situation, the security control module **150** may implement deep analytics of the session, containment of the session and recording of the session to better understand a hacker's actions. Alternatively, if a security condition is triggered, the security module **150** may take a hacked server, on which hacked session is detected, out of a server group **130**. A new server is then hot swapped in place of the hacked server such that the rolling of the server groups **130** is not interrupted.

FIG. 4 is a block diagram of a security control module **130**, according to an embodiment. Security control module **130** includes a communication module **405**, rolling timing module **410**, rolling control module **415**, and password change module **420**. In other embodiments the security control module **130** may have additional modules not shown in FIG. 4.

The rolling timing module **410** maintains rolling timing information indicating staggered timings for when the physical server groups **130**, VM groups **160**, or container groups **960** (collectively referred to herein as "rolling entity groups") should enter different modes, such as normal operation mode, shutdown preparation mode and rebuilding mode. The timing information may be in the form of a timing schedule that includes a list of rolling entity groups and specific times for when each rolling entity group should enter different modes. The following table is an example of a timing schedule.

Server Group	Mode: Normal Operation	Mode: Shutdown Preparation	Mode: Rebuilding
1	1:00:00	1:00:30	1:00:50
	1:01:00	1:01:30	1:01:50
	...	...	...
2	1:00:10	1:00:40	1:01:00
	1:01:10	1:01:40	1:02:00
	...	...	...
3	1:00:20	1:00:50	1:01:10
	1:01:20	1:01:50	1:02:10
	...	...	...
4	1:00:30	1:01:00	1:01:20
	1:01:30	1:02:00	1:02:20
	...	...	...

The first column of the table identifies a server group. The second column identifies start times for when the server group should enter the normal operation mode. The third column identifies when the server group should enter shut-

## 11

down preparation mode. The fourth column identifies when the rebuilding process should begin.

In other embodiments, the timing information may be in the form of maximum time limits instead of a timing schedule. For example, the timing information may include a maximum uptime of a rolling entity group, a maximum duration of a normal operation mode, a maximum duration of a shutdown preparation mode, and/or a maximum duration of a rebuild mode. The timing information may also include information describing an amount of staggered delay between the rolling entity groups.

The rolling timing information for the rolling modes may be manually set by a user. In another embodiment, the timing information may be machine learned by monitoring the durations of previous application sessions or connections on the servers and generating application profiles that include the monitored durations. A statistical measure of the durations (e.g. average duration, maximum duration) can be determined from the monitored durations. The statistical measure is then multiplied by a multiplier (e.g. 8x, 10x) to determine the maximum duration of each rolling mode. The result is that the time between rebuilds is sufficient for new user sessions and connections to be established and completed before a rolling entity group is rebuilt. For example, if user sessions tend to be 6 seconds long, this value may be multiplied by 8x to result in a duration between periodic rebuilds of 48 seconds, which is much greater than the session duration.

Rolling control module **415** controls the rolling operation of the rolling entity groups in accordance with the rolling timing information, such as the rolling timing schedule or the maximum time limits described above. The rolling control module **415** uses the rolling timing information to determine the rolling mode that a server group should be in. The rolling control module **415** then sends control commands to the load balancers **125** and rolling entity groups via the communication module **405** that cause the rolling entity groups to operate in a rolling manner as shown in FIG. 3. The commands for each rolling entity group may be staggered in time relative to commands for the other rolling entity groups to ensure that the rolling entity groups are rolled at controlled and staggered times.

To initiate normal operation mode, the rolling control module **415** may transmit a normal operation initiation command to the load balancers **125**. The command identifies a particular rolling entity group and also indicates that normal operation mode is to begin for that rolling entity group. The load balancer **125** responds to the command by allowing sessions and connections to be established with the identified rolling entity group. In one embodiment the normal operation initiation command may also be transmitted to the appropriate rolling entity group for which normal operation is being initiated.

To initiate shutdown preparation mode, the rolling control module **415** may transmit a shutdown preparation initiation command to the load balancers **125**. The command identifies a particular rolling entity group and also indicates that shutdown preparation mode is to begin for that rolling entity group. The load balancer **125** responds to the command by preventing any new sessions and connections to be established with the identified rolling entity group. Existing sessions and connections of the rolling entity group are permitted to complete. In one embodiment the shutdown preparation initiation command may also be transmitted to the appropriate servers for a rolling entity group.

To initiate rebuilding, the rolling control module **415** may send a rebuild initiation command to the appropriate front

## 12

end server(s) associated with a rolling entity group that is to be rebuilt. The command can include a name of a known good software image that is to be used for the rebuild. In response, the rolling entity group can be rebuilt with the known good software image. The rolling control module **415** may also receive rebuild confirmation information from the appropriate front end servers once the rebuild is completed.

Additionally, prior to rebuilding, rolling control module **415** can copy data from a rolling entity group to a separate storage drive. Machine learning can be used to monitor for changes in the data and do an inline analysis of the changes for global comparison across other servers. This allows for understanding of all the changes made by a hacker to the OS, applications, or files while an entity was online. Machine learning the rebuild state and timing is important but delaying the rebuild state over a hacked situation to enable more advanced learning is also part of the system controls managed via the rolling control module **415**. Rolling control module **415** can also communicate with the local server groups, router **115** and firewall **120** to continue servicing a hacker with the intention of learning and collection more data to learn the hackers capabilities and learn more about new attacks.

Password change module **420** initiates password changes for the server groups **130**. The passwords can be OS, database, or application passwords, among others. The passwords can be changed with every rebuild as indicated by the rolling timing information, or can be rebuilt at specific timestamps (i.e. at certain intervals). The frequency of the password changes can be the same as or different than the frequency of the rolling entity group rebuilds. In one embodiment, the password change module **420** can initiate a password change by generating new passwords and transmitting the passwords to the servers. In another embodiment, the password change module **420** can initiate a password change by sending a password change command to the servers. The servers then generate new passwords in response to the command. Any of a number of algorithms can be used to generate the password. In one embodiment, a timestamp is one of the elements used to generate the password.

Communication module **405** communicates with the servers, load balancers **125**, and other devices in the networked communication system. The communication module **405** may transmit rolling security commands that cause the rolling entity groups to operate in a rolling and staggered manner. The communication module **405** may send commands that initiate password changes at the rolling entity groups. The communication module **405** may also receive other types of information from the devices in the networked communication system.

FIG. 5 is a flowchart for a method of rolling security, according to an embodiment. In step **505**, previous connections or user sessions for applications hosted by the rolling entity groups are monitored. The durations are stored in application profiles. Once sufficient information is collected, the durations for the previous connections and user sessions is used to generate rolling timing information that describes staggered timings for different rolling security modes of the rolling entity groups, such as staggered timing for when different rolling entity groups should be rebuilt.

In step **510**, the security control module **150** initiates normal operation of the first rolling entity group at a timing specified by the rolling timing information. In step **512**, the security control module **150** initiates shutdown preparation mode of the rolling entity group at a timing specified by the rolling timing information. In step **514**, the security control

## 13

module **150** initiates rebuilding of the first rolling entity group at a timing specified by the rolling timing information. Additionally, the security control module **150** initiates a password change of the first rolling entity group at the same time. Steps **510-514** repeat continuously, such as at periodic intervals.

In step **520**, the security control module **150** initiates normal operation of the second rolling entity group at a timing specified by the rolling timing information. In step **522**, the security control module **150** initiates shutdown preparation mode of the second rolling entity group at a timing specified by the rolling timing information. In step **524**, the security control module **150** initiates rebuilding of the second rolling entity group at a timing specified by the rolling timing information. Additionally, the security control module **150** initiates a password change of the second rolling entity group at the same time. Steps **520-524** repeat continuously, such as at periodic intervals.

Other rolling entity groups may also be controlled in a similar manner as steps **510-514** and **520-524**. Additionally, for each rolling entity group, the initiation of the rebuilding, normal operation modes, and shutdown preparation modes is staggered in time relative to the other rolling entity groups. Staggering of the security modes results in the rolling security illustrated in FIG. **3**.

FIG. **6** illustrates the hardware architecture of a computing device, such as a firewall **120**, router **115**, load balancer **125**, client device **105**, frontend server **130** or **159**, backend server **135**, or security server **148**, according to one embodiment. In one embodiment, the computing device is a computer including components such as a processor **602**, a memory **603**, a storage module **604**, an input module (e.g., keyboard, mouse, and the like) **606**, a display module **607** and a communication interface **605**, exchanging data and control signals with one another through a bus **601**. The storage module **604** is implemented as one or more non-transitory computer readable storage media (e.g., hard disk or solid state drive), and stores software instructions **640** (e.g. modules) that are executed by the processor **602** in conjunction with the memory **603** to implement the rolling security features described herein. Operating system software and other application software may also be stored in the storage module **604** to run on the processor **602**.

The rolling security described herein is not only limited to front end servers **130**, virtual machines **160**, and containers **960**. In other embodiments the rolling security can be used to periodically rebuild other groups of computing systems in a datacenter, such as firewalls **120**, load balancers **125**, switches, backend servers **135** and backend storage **140**. Additionally, the functions of the modules described herein may be combined into a single module or distributed across additional modules.

In other embodiments, the rolling security described herein may be applied to other groups of computing systems outside of datacenters that provide common software functionality. The computing systems can be desktops, laptops, ipads, iphones, and computing systems in vehicles (cars, trains, planes) and computing systems in power plants, generators, etc. In the example of a plane, the plane may include several parallel flight control systems, each of which can provide flight control for the plane. Rolling the flight control systems on a staggered basis can protect the flight control systems from being hacked while ensuring that at least one flight control system is always online.

Upon reading this disclosure, those of skill in the art may appreciate still additional alternative designs for rolling security. Thus, while particular embodiments and applica-

## 14

tions of the present disclosure have been illustrated and described, it is to be understood that the disclosure is not limited to the precise construction and components disclosed herein. Various modifications, changes and variations which may be apparent to those skilled in the art may be made in the arrangement, operation and details of the method and apparatus of the present disclosure herein without departing from the spirit and scope of the disclosure as defined in the appended claims.

What is claimed is:

**1.** A computer implemented method to generate rolling timing information, comprising:

monitoring, using one or more processors a first plurality of application sessions on a first server group and a second plurality of application sessions on a second server group;

determining, using the one or more processors based on monitoring the first plurality of sessions, a first plurality of durations for the first plurality of sessions, and, based on monitoring the second plurality of sessions, a second plurality of durations for the second plurality of sessions;

determining, using the one or more processors based the first plurality of durations, a first rebuild interval for the first server group;

determining, using the one or more processors based on second plurality of durations, a second rebuild interval for the second server group;

generating, using the one or more processors, rolling timing information indicating rebuild timings for the first server group based on the first rebuild interval and rebuild timings for the second server group based on the second rebuild interval, wherein the rebuilt timings for the first server group and the second server group are staggered;

storing, in memory, a first entry for the first server group, wherein the first entry comprises a time for normal operation mode, a time for shutdown preparation mode, and a time for rebuilding mode; and

causing the first server group to be rebuilt and the second server group to be rebuilt based on the rolling timing information.

**2.** The method of claim **1**, wherein determining the first rebuild interval for the first server group comprises:

calculating a statistical measure based on the first plurality of durations of the first plurality of application sessions; and

determining the first rebuild interval by applying a multiplier to the statistical measure.

**3.** The method of claim **2**, wherein the statistical measure is one of an average duration and a maximum duration.

**4.** The method of claim **1**, wherein causing the first server group to be rebuilt comprises causing the first server group to enter a shutdown preparation mode from a normal operation mode.

**5.** The method of claim **4**, wherein generating rolling timing information comprises generating a maximum duration of the normal operation mode.

**6.** The method of claim **4**, wherein causing the first server group to enter a shutdown preparation mode comprises transmitting a shutdown preparation initiation command to one or more load balancers, wherein the shutdown preparation initiation command comprises an identifier of the first server group.

**7.** The method of claim **1**, wherein causing the first server group to be rebuilt and the second server group to be rebuilt

## 15

comprises determining that the first server group has been rebuilt before initializing a rebuild of the second server group.

**8.** A non-transitory computer readable medium comprising stored instructions, the instructions when executed by one or more processors cause the one or more processors to:

- monitor a first plurality of application sessions on a first server group and a second plurality of application sessions on a second server group;
- determine, based on monitoring the first plurality of sessions, a first plurality of durations for the first plurality of sessions, and, based on monitoring the second plurality of sessions, a second plurality of durations for the second plurality of sessions;
- determine, based the first plurality of durations, a first rebuild interval for the first server group;
- determine, based on second plurality of durations, a second rebuild interval for the second server group;
- generate rolling timing information indicating rebuild timings for the first server group based on the first rebuild interval and rebuild timings for the second server group based on the second rebuild interval, wherein the rebuilt timings for the first server group and the second server group are staggered;
- store, in memory, a first entry for the first server group, wherein the first entry comprises a time for normal operation mode, a time for shutdown preparation mode, and a time for rebuilding mode; and
- cause the first server group to be rebuilt and the second server group to be rebuilt based on the rolling timing information.

**9.** The non-transitory computer readable medium of claim **8**, wherein the instructions that cause the one or more processors to determine the first rebuild interval for the first server group comprise further instructions to cause the one or more processors to:

- calculate a statistical measure based on the first plurality of durations of the first plurality of application sessions; and
- determine the first rebuild interval by applying a multiplier to the statistical measure.

**10.** The non-transitory computer readable medium of claim **9**, wherein the statistical measure is one of an average duration and a maximum duration.

**11.** The non-transitory computer readable medium of claim **8**, wherein the instructions that cause the one or more processors to rebuild the first server group comprise further instructions that cause the one or more processors to cause the first server group to enter the shutdown preparation mode from the normal operation mode.

**12.** The non-transitory computer readable medium of claim **11**, wherein the instructions that cause the one or more processors to generate rolling timing information, comprise further instructions that cause the one or more processors to generate a maximum duration of the normal operation mode.

**13.** The non-transitory computer readable medium of claim **11**, wherein the instructions to cause the first server group to enter the shutdown preparation mode, comprise further instructions that cause the one or more processors to execute a shutdown preparation initiation command to one or more load balancers, wherein the shutdown preparation initiation command comprises an identifier of the first server group.

## 16

**14.** The non-transitory computer readable medium of claim **8**, wherein the instructions to cause the first server group to be rebuilt and the second server group to be rebuilt comprise further instructions that when executed by the one or more processors determines whether the first server group has been rebuilt before initializing a rebuild of the second server group.

**15.** A system to generate rolling timing information, comprising:

- a first server group of servers;
- a second server group of servers, each server in the first server group and second server group including software that includes an operating system and an application that supports user sessions;
- one or more processors; and
- a non-transitory computer readable medium storing instructions, the instructions when executed by the one or more processors cause the one or more processors to:
  - monitor a first plurality of application sessions on a first server group and a second plurality of application sessions on a second server group;
  - determine, based on monitoring the first plurality of sessions, a first plurality of durations for the first plurality of sessions, and, based on monitoring the second plurality of sessions, a second plurality of durations for the second plurality of sessions;
  - determine, based the first plurality of durations, a first rebuild interval for the first server group;
  - determine, based on second plurality of durations, a second rebuild interval for the second server group;
  - generate rolling timing information indicating rebuild timings for the first server group based on the first rebuild interval and rebuild timings for the second server group based on the second rebuild interval, wherein the rebuilt timings for the first server group and the second server group are staggered;
  - store, in memory, a first entry for the first server group, wherein the first entry comprises a time for normal operation mode, a time for shutdown preparation mode, and a time for rebuilding mode; and
  - cause the first server group to be rebuilt and the second server group to be rebuilt based on the rolling timing information.

**16.** The system of claim **15**, wherein the instructions that cause the one or more processors to determine the first rebuild interval for the first server group, cause the one or more processors to:

- calculate a statistical measure based on the first plurality of durations of the first plurality of application sessions; and
- determine the first rebuild interval by applying a multiplier to the statistical measure.

**17.** The system of claim **16**, wherein the statistical measure is one of an average duration and a maximum duration.

**18.** The system of claim **15**, wherein the instructions that cause the one or more processors to rebuild the first server group, cause the one or more processors to cause the first server group to enter the shutdown preparation mode from the normal operation mode.

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : 10,965,678 B2  
APPLICATION NO. : 16/820618  
DATED : March 30, 2021  
INVENTOR(S) : Robert Pike

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

On the Title Page

Item (71), in Column 1, in "Applicant", Line 1, delete "Inc." and insert -- Inc., Woodinville, WA (US) --, therefor.

In the Claims

In Column 14, in Claim 1, Line 14, after "processors" insert -- , --.

In Column 14, in Claim 1, Line 24, delete "based the" and insert -- based on the --, therefor.

In Column 14, in Claim 1, Line 27, delete "based on" and insert -- based on the --, therefor.

In Column 15, in Claim 8, Line 15, delete "based the" and insert -- based on the --, therefor.

In Column 15, in Claim 8, Line 17, delete "based on" and insert -- based on the --, therefor.

In Column 16, in Claim 15, Line 28, delete "based the" and insert -- based on the --, therefor.

In Column 16, in Claim 15, Line 30, delete "based on" and insert -- based on the --, therefor.

Signed and Sealed this  
Twenty-fourth Day of August, 2021



Drew Hirshfeld  
*Performing the Functions and Duties of the  
Under Secretary of Commerce for Intellectual Property and  
Director of the United States Patent and Trademark Office*