

US010973354B1

(12) **United States Patent**  
**Tsai**

(10) **Patent No.:** **US 10,973,354 B1**  
(45) **Date of Patent:** **Apr. 13, 2021**

(54) **MODULAR ELECTRICAL DISTRIBUTION  
SYSTEM FOR AN ILLUMINABLE  
DECORATION, AND ILLUMINABLE  
DECORATION WITH MODULAR  
ELECTRICAL DISTRIBUTION SYSTEM**

(71) Applicant: **Chang Fu Tsai**, Taichung (TW)

(72) Inventor: **Chang Fu Tsai**, Taichung (TW)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/994,991**

(22) Filed: **Aug. 17, 2020**

(51) **Int. Cl.**

*A47G 33/06* (2006.01)  
*A47G 33/08* (2006.01)  
*H01R 33/06* (2006.01)  
*H01R 24/38* (2011.01)  
*H01R 13/10* (2006.01)  
*H01R 103/00* (2006.01)  
*F21W 121/04* (2006.01)

(52) **U.S. Cl.**

CPC ..... *A47G 33/06* (2013.01); *A47G 33/08*  
(2013.01); *H01R 13/10* (2013.01); *H01R*  
*24/38* (2013.01); *H01R 33/06* (2013.01);  
*A47G 2033/0827* (2013.01); *F21W 2121/04*  
(2013.01); *H01R 2103/00* (2013.01)

(58) **Field of Classification Search**

CPC ..... H01R 24/38; A47G 33/06  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,188,529 A 1/1940 Corina  
2,558,029 A 6/1951 Wood

2,826,845 A 3/1958 Warren  
3,277,291 A 10/1966 Holbrook  
3,603,780 A 9/1971 Lu  
3,985,924 A 10/1976 Pritza  
4,020,201 A 4/1977 Miller  
4,072,857 A 2/1978 DeVicaris  
5,550,720 A 8/1996 Carroll  
5,776,559 A 7/1998 Woolford  
7,066,739 B2 \* 6/2006 McLeish ..... H01R 13/6205  
439/39  
8,454,186 B2 6/2013 Chen  
(Continued)

FOREIGN PATENT DOCUMENTS

DE 8436328 U1 4/1985  
GB 2137086 A 10/1984


*Primary Examiner* — Evan P Dzierzynski

(74) *Attorney, Agent, or Firm* — Thomas E. Lees, LLC

(57) **ABSTRACT**

An illuminable decoration comprises at least two trunk sections, each trunk section includes a hollow tube and a cable assembly coupled to each trunk section. Each cable assembly comprises a first modular electrical connector end that has an inner socket and an outer plug that circumscribes the inner socket. Further, each cable assembly comprises a second modular electrical connector end that has an inner plug and an outer socket that circumscribes the inner plug. A first electrical wire electrically couples between the inner socket of the first modular electrical connector and the inner plug of the second modular electrical connector. Also, a second electrical wire electrically couples between the outer plug of the first modular electrical connector and the outer socket of the second modular electrical connector. When two trunk sections are assembled together end-to-end, the trunk sections are mechanically and electrically coupled to form a modular electrical distribution system.

**23 Claims, 21 Drawing Sheets**



(56)                      **References Cited**

U.S. PATENT DOCUMENTS

8,454,187	B2	6/2013	Chen	
8,863,416	B2	10/2014	Leung et al.	
8,936,379	B1	1/2015	Chen	
8,959,810	B1	2/2015	Leung et al.	
8,974,072	B2	3/2015	Chen	
9,044,056	B2	6/2015	Chen	
9,066,617	B2	6/2015	Chen	
9,119,495	B2	9/2015	Leung et al.	
9,839,315	B2	12/2017	Leung et al.	
9,843,147	B2	12/2017	Leung et al.	
9,912,109	B2	3/2018	Leung et al.	
9,960,558	B2	5/2018	Ocegueda Gallaga et al.	
2006/0063409	A1 *	3/2006	Wang .....	H01R 13/7033 439/188
2007/0230174	A1	10/2007	Hicks et al.	
2007/0253191	A1	11/2007	Chin et al.	
2013/0301247	A1 *	11/2013	Chen .....	H01R 13/502 362/123
2015/0099391	A1 *	4/2015	Hashimoto .....	H01R 13/629 439/380
2016/0043505	A1 *	2/2016	Wu .....	H01R 35/02 439/217
2016/0278559	A1 *	9/2016	Leung .....	A47G 33/06

\* cited by examiner




FIG. 1A




FIG. 1B




FIG. 1C






FIG. 1D




FIG. 1E




FIG. 2A






FIG. 2B




FIG. 2C




FIG. 2D




FIG. 2E




FIG. 3




FIG. 4A






FIG. 4B




FIG. 4C




FIG. 5




FIG. 6




FIG. 7







FIG. 8A








FIG. 9




FIG. 10



1

# MODULAR ELECTRICAL DISTRIBUTION SYSTEM FOR AN ILLUMINABLE DECORATION, AND ILLUMINABLE DECORATION WITH MODULAR ELECTRICAL DISTRIBUTION SYSTEM

## BACKGROUND

### Field of the Invention

Various aspects of the present invention relate generally to electrical distribution systems that are suitable for use with illuminable decorations. In particular, aspects relate to a modular electrical distribution system usable with illuminable decorations, such as artificial illuminated trees, and to illuminable decorations, such as artificial trees, having a modular electrical distribution system integrated therewith.

### Description of Related Art

Decorations such as artificial trees, can be provided in segmented components that are assembled into a final form. The segments provide convenience for packing, storing, and transportation. However, the segments require assembly when it is desirable to place the decoration out for display.

For instance, in a decoration such as a holiday tree, a user typically mounts a first section resembling a tree trunk to a base, e.g., a tree stand. The first section may have branches pre-installed, or the branches themselves may be separate components. After assembling the first section to the base, the individual continues, assembling a second section to the first section. This process continues, stacking sections until the decoration is fully assembled into an artificial tree. In some implementations, the individual can then decorate the tree with lights. In other implementations, lights are pre-strung on the segments and/or branches.

## BRIEF SUMMARY

According to aspects of the present disclosure, an illuminable decoration is provided. The illuminable decoration comprises a first trunk section and a second trunk section. Here, the first trunk section and the second trunk section are each comprised of a hollow tube. Additionally, a first cable assembly is coupled to the first trunk section. The first cable assembly comprises a first modular electrical connector end, where the first modular electrical connector end has an inner socket and an outer plug that at least partially circumscribes the inner socket. The first cable assembly also includes a second modular electrical connector end. The second modular electrical connector end has an inner plug and an outer socket that at least partially circumscribes the inner plug. A first electrical wire is electrically coupled between an electrical contact of the inner socket of the first modular electrical connector end, and an electrical contact of the inner plug of the second modular electrical connector end. Likewise, a second electrical wire is electrically coupled between an electrical contact of the outer plug of the first modular electrical connector end, and an electrical contact of the outer socket of the second modular electrical connector end. A second cable assembly is coupled to the second trunk section. Here, the second cable assembly comprises at least one of a first modular electrical connector end and a second modular electrical connector end. Here, the first modular electrical connector end has an inner socket and an outer plug that circumscribes the inner socket. Correspondingly, the second modular electrical connector end having an inner

2

plug and an outer socket that circumscribes the inner plug. When the first trunk section is assembled to the second trunk section end-to-end, the first trunk section and the second trunk section are mechanically connected along an axial dimension, and the first cable assembly is mechanically and electrically connected to the second cable assembly so as to form a modular electrical distribution system.

According to further aspects of the present disclosure, a cable assembly is provided. The cable assembly comprises a first modular electrical connector end, and a second modular electrical connector end. The first modular electrical connector end has an inner socket and an outer plug that circumscribes and is spaced from the inner socket. Correspondingly, the second modular electrical connector end has an inner plug and an outer socket that circumscribes and is spaced from the inner plug. A first electrical wire is electrically coupled between an electrical contact of the inner socket of the first modular electrical connector end, and an electrical contact of the inner plug of the second modular electrical connector end. Analogously, a second electrical wire is electrically coupled between an electrical contact of the outer plug of the first modular electrical connector end, and an electrical contact of the outer socket of the second modular electrical connector end. When two cable assemblies are assembled together end-to-end, the two cable assemblies are mechanically connected along an axial dimension so as to form a modular electrical distribution system, such that the inner socket of the first modular electrical connector end of a first one of the cable assemblies electrically and mechanically connects to the inner plug of the second modular electrical connector end of a second one of the cable assemblies, and the outer plug of the first modular electrical connector end of the first one of the cable assemblies electrically and mechanically connects to the outer socket of the second modular electrical connector end of the second one of the cable assemblies.

## BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

FIG. 1A illustrates a first modular electrical connector end usable with a modular electrical distribution system;

FIG. 1B illustrates an alternative embodiment of a first modular electrical connector end usable with a modular electrical distribution system;

FIG. 1C illustrates another alternative embodiment of a first modular electrical connector end usable with a modular electrical distribution system;

FIG. 1D illustrates yet another alternative embodiment of a first modular electrical connector end usable with a modular electrical distribution system;

FIG. 1E illustrates still another alternative embodiment of a first modular electrical connector end usable with a modular electrical distribution system;

FIG. 2A illustrates a second modular electrical connector end usable with a modular electrical distribution system;

FIG. 2B illustrates an alternative embodiment of a second modular electrical connector end usable with a modular electrical distribution system;

FIG. 2C illustrates another alternative embodiment of a second modular electrical connector end usable with a modular electrical distribution system;

FIG. 2D illustrates yet another alternative embodiment of a second modular electrical connector end usable with a modular electrical distribution system;



3

FIG. 2E illustrates still another alternative embodiment of a second modular electrical connector end usable with a modular electrical distribution system;

FIG. 3 illustrates a partial view of the first modular electrical connector end of FIG. 1 electrically connected to the second modular electrical connector end of FIG. 2A or FIG. 2B, according to aspects of the present disclosure;

FIG. 4A illustrates an example electrical cable that can form part of a modular electrical distribution system, the electrical cable including a first modular electrical connector end and a second modular electrical connector end, according to aspects of the present disclosure;

FIG. 4B illustrates an example electrical cable that can form part of a modular electrical distribution system, the electrical cable including a first modular electrical connector end, a second modular electrical connector end, and a power cord extending therefrom, according to aspects of the present disclosure;

FIG. 4C illustrates an example electrical cable that can form part of a modular electrical distribution system, the electrical cable including a first modular electrical connector end, a second modular electrical connector end, and a power outlet, according to aspects of the present disclosure;

FIG. 5 illustrates another example modular electrical connector end usable with a modular electrical distribution system, according to aspects herein;

FIG. 6 illustrates yet another example modular electrical connector end usable with a modular electrical distribution system, according to aspects herein;

FIG. 7 illustrates an exploded view showing that a first electrical cable is installed into a first trunk section of an illuminable decoration such as an artificial tree, a second electrical cable is installed into a second trunk section of the decoration, and when connected, the first trunk section mechanically couples to the second trunk section, and the first electrical cable mechanically and electrically couples to the second electrical cable, according to aspects of the present disclosure;

FIG. 8A illustrates a schematic cross-section of an example trunk connection showing a first trunk section of an illuminable decoration mechanically coupled to a second trunk section, and a first electrical cable mechanically and electrically coupled to a second electrical cable, according to aspects of the present disclosure;

FIG. 8B illustrates another example schematic cross-section of an example trunk connection showing a first trunk section of an illuminable decoration mechanically coupled to a second trunk section, and a first electrical cable mechanically and electrically coupled to a second electrical cable, according to aspects of the present disclosure;

FIG. 9 illustrates an exploded view showing that a first electrical cable is installed into a first trunk section of an illuminable decoration such as an artificial tree, a second electrical cable is installed into a second trunk section of the decoration, and when connected, the first trunk section mechanically couples to the second trunk section, and the first electrical cable mechanically and electrically couples to the second electrical cable, according to aspects of the present disclosure; and

FIG. 10 illustrates an example decoration, implemented as an artificial illuminated tree, according to aspects of the present disclosure.

#### DETAILED DESCRIPTION

Aspects herein provide a modular electrical distribution system usable with illuminable decorations, such as artificial

4

illuminated trees. Aspects also provide illuminable decorations, such as artificial trees, having a modular electrical distribution system integrated therewith.

By way of example, an illuminable decoration implemented as an artificial tree may include lights thereon, or the artificial tree may include provisions for an individual to add lights, e.g., to the branches of the artificial tree. In view of the above, power must be provided to the lights. Accordingly, aspects herein provide a modular electrical distribution system uses an interior hollow of a trunk of the artificial tree as a conduit. In this configuration, an electrical connection is made substantially simultaneously with the joining of the trunk sections to form the trunk of the artificial tree. That is, assembly of the trunk sections automatically forms the electrical connections necessary to provide power through the trunk.

Moreover, in some embodiments, a rotational orientation of the trunk sections is independent of forming the electrical connections. As such, an individual does not need to align the electrical connectors or have any special knowledge of electrical connections. Moreover, in some embodiments, the electrical connectors are positioned proximate to the axial ends of each trunk section. For instance, the electrical connectors can be recessed into the hollow of the trunk sections proximate to the axial ends of each trunk section. As such, the individual assembling the trunk sections need not even be aware of how to make electrical connections, because the electrical connections are made positively and automatically for the user by virtue of the mechanical assembly of the trunk sections.

By providing power through the trunk, the decoration herein can include built in lights that receive power. Alternatively, an individual may be able to add lights, or to plug lights into one or more connectors (such as outlets or plugs) conveniently provided on or near the trunk. Here, each connector receives power via the modular electrical distribution system. In other embodiments, one or more power cables may extend from the trunk, where the power cables each include at least one connector (e.g., outlet or plug).

First Modular Electrical Connector End

Referring now to the drawings, and in particular to FIG. 1A, an example embodiment of a first modular electrical connector end 100 is illustrated.

The illustrated first modular electrical connector end 100 includes in general, a body 102 that supports an inner socket 104 and an outer plug 106. The outer plug 106 at least partially circumscribes and is spaced outwardly from the inner socket 104 and is spaced therefrom by a tubular insulator 108. As illustrated, the tubular insulator 108 is a generally cylindrical projection that extends from an end face of the body 102. Moreover, the tubular insulator 108 defines a body or portion thereof for the inner socket 104, and a body or portion thereof for the outer plug 106. As illustrated, the end face of the tubular insulator 108 forms an annular ring of insulative material that provides stiffness and strength to the inner socket 104 and outer plug 106.

More particularly, the inner socket 104 of the first modular electrical connector end 100 is defined by an interior or hollow of the tubular insulator 108. For instance, as illustrated, the diameter of the inner socket 104 is defined by the inside diameter of the annular ring (or hollow) of the tubular insulator 108. The inside diameter of the annular ring, along with the depth of the hollow, thus form a receptacle of the inner socket 104. The inner socket 104 comprises an electrical contact 110, e.g., a conductive tab on an inside surface of the tubular insulator 108, a flat conductive pad, a conductive ring or band that circumscribes the inside diameter



## 5

of the tubular insulator **108**, an arcuate conductive surface that covers only a portion of the inside diameter of the tubular insulator **108**, a conductive structure having a spring characteristic, etc.

Notably, a spring characteristic can be provided in any of the above-structures. For instance, the spring characteristic of the electrical contact **110**, when implemented, can be one or more of a spring finger contact, clip, multi-directional spring contact, a spring tab, etc. As further examples, the spring characteristic can be built into a ring or band of metal surrounding the inside diameter of the tubular insulator **108**, which is implemented as a set of leaf springs, a cylinder with at least one leaf spring, a band having a set of axial slits with a central, radially inward bulge, a spring or clip that applies force (radially inward or radially outward) to ensure good electrical contact with a mating contact, etc.

As will be described in greater detail herein, the electrical contact **110** facilitates an electrical connection to a wire of the modular electrical distribution system. In the illustrated example, because of the hollow and the positioning of the tubular insulator **108**, there is no conductor that is coaxial with the first modular electrical connector end **100**. Rather, the electrical contact **110** is offset relative to a coaxial dimension.

The outer plug **106** of the first modular electrical connector end **100** is defined by an exterior surface of the tubular insulator **108**. For instance, as illustrated, the diameter of the outer plug **106** is defined by the outside diameter of the annular ring of the tubular insulator **108**. The distance from the annular ring (end face of the tubular insulator **108**) to the body **102** (height of the tubular insulator **108** projecting from the body **102**) thus defines a length of the outer plug **106**. An electrical contact **114**, e.g., a conductive material is positioned on at least a portion of an outside surface of the tubular insulator **108**, thus defining the conductor of the outer plug **106**. As will be described in greater detail herein, the conductive material of the outer plug **106** facilitates an electrical connection to a wire of the modular electrical distribution system. In practice, the electrical contact **114** can be implemented as a conductive tab on the outside surface of the tubular insulator **108**, a conductive pad, a conductive ring or band that circumscribes the outside diameter of the tubular insulator **108**, an arcuate conductive surface that covers only a portion of the outside diameter of the tubular insulator **108**, a conductive structure having a spring characteristic, etc.

Notably, a spring characteristic can be provided in any of the above-structures. For instance, the spring characteristic, where provided, can be built into a ring or band of metal surrounding the outside diameter of the tubular insulator **108**, which is implemented as a set of leaf springs, a cylinder with at least one leaf spring, a band having a set of axial slits with a central bulge, a spring that applies outward force to ensure good electrical contact with a mating contact, etc. Also, the electrical contact **114** can be implemented with a spring characteristic by providing one or more of a spring finger contact, clip, multi-directional spring contact, spring tab, etc.

As noted above, the tubular insulator **108** serves as a body for both the inner socket **104** and the outer plug **106**. Thus, the tubular insulator **108** enables a plug with an internal, coaxially aligned and recessed socket. In other embodiments (not illustrated in FIG. 1A), the inner socket **104** and the outer plug **106** are each on a separate insulator body, e.g., concentric tubular projections. In yet other embodiments, the outer plug **106** is implemented on a tubular projection

## 6

away from the body **102**, and the inner socket **104** is recessed into a cylindrical aperture that extends into the body **102**.

The first modular electrical connector end **100** of FIG. 1A also includes an optional outer wall **116**. In this regard, the outer wall **116** is an insulator that forms a concentric outer ring that circumscribes and is spaced outwardly from both the inner socket **104** and the outer plug **106** of the first modular electrical connector end **100**. The outer wall **116** can be utilized for example, to isolate any conductive portion of the first modular electrical connector end **100**, to provide a guide surface or abutment surface for mechanical coupling, to provide alignment of trunk sections, or for other purposes.

Referring to FIG. 1B, another example embodiment of a first modular electrical connector end **100** is illustrated. The illustrated first modular electrical connector end **100** is similar to the first modular electrical connector end **100** of FIG. 1A unless otherwise noted. As such, like elements are illustrated with like reference numbers. Moreover, similar elements will not be described in detail. Rather, the disclosure with regard to similar elements to that of FIG. 1A is adopted by analogy.

Analogous to FIG. 1A, the illustrated first modular electrical connector end **100** includes a body **102** having an inner socket **104** and an outer plug **106**. The outer plug **106** at least partially circumscribes and is spaced outwardly from the inner socket **104** and is spaced therefrom by a tubular insulator **108**. The inner socket **104** comprises an electrical contact **110**, e.g., a conductive tab as illustrated on an inside surface of the tubular insulator **108**. However, the electrical contact **110** can take any form or structure as set out in greater detail with reference to FIG. 1A. Also, the outer plug **106** comprises an electrical contact **114**, e.g., a conductive material positioned on an outside surface of the tubular insulator **108**. However, the electrical contact **114** can take any form or structure as set out in greater detail with reference to FIG. 1A.

The embodiment of FIG. 1B differs from the embodiment of FIG. 1A in that the outer wall **116** of FIG. 1A is replaced by outer wall segments, illustrated by a first outer wall segment **116A** and a second outer wall segment **116B**. The first outer wall segment **116A** is spaced from the second outer wall segment **116B** by a gap at each end. Thus, there is no annular ring formed entirely around the tubular insulator **108** like the outer wall **116** of FIG. 1A. Rather, the segments form spaced projections of non-conductive material. The use of outer wall segments may be utilized, for instance, to provide a tolerance with regard to a mating component by allowing a "spring action" of the segments to create a solid mechanical coupling. In practice, there can be more segments than the first and second segments illustrated.

Referring to FIG. 1C, yet another example embodiment of a first modular electrical connector end **100** is illustrated. The illustrated first modular electrical connector end **100** is similar to the first modular electrical connector end **100** of FIG. 1A unless otherwise noted. As such, like elements are illustrated with like reference numbers. Moreover, similar elements will not be described in detail. Rather, the disclosure with regard to similar elements to that of FIG. 1A is adopted by analogy.

Analogous to FIG. 1A, the illustrated first modular electrical connector end **100** includes a body **102** having an inner socket **104** and an outer plug **106**. The outer plug **106** at least partially circumscribes and is spaced outwardly from the inner socket **104** and is spaced therefrom by a tubular



insulator **108**. The inner socket **104** comprises an electrical contact **110**, e.g., a conductive tab illustrated on an inside surface of the tubular insulator **108**. However, the electrical contact **110** can take any form or structure as set out in greater detail with reference to FIG. 1A. Also, the outer plug **106** comprises an electrical contact **114**, e.g., a conductive material positioned on an outside surface of the tubular insulator **108**. However, the electrical contact **114** can take any form or structure as set out in greater detail with reference to FIG. 1A.

Notably, in the embodiment of FIG. 1C, there is no outer wall analogous to the outer wall **116** of FIG. 1A. Rather, the embodiment of FIG. 1C includes a single projection (i.e., the tubular insulator **108**) from the face of the body **102**. Here, the tubular insulator **108** provides the electrical connection and can form, or contribute to the mechanical coupling to a corresponding connector end as described in greater detail herein.

Referring to FIG. 1D, yet another example embodiment of a first modular electrical connector end **100** is illustrated. The illustrated first modular electrical connector end **100** is similar to the first modular electrical connector end **100** of FIG. 1A unless otherwise noted. As such, like elements are illustrated with like reference numbers. Moreover, similar elements will not be described in detail. Rather, the disclosure with regard to similar elements to that of FIG. 1A is adopted by analogy.

Analogous to FIG. 1A, the illustrated first modular electrical connector end **100** includes a body **102** having an inner socket **104** and an outer plug **106**. Notably however, the outer plug **106** only partially circumscribes and is spaced outwardly from the inner socket **104**. More particularly, the outer plug **106** is spaced from the inner socket **104** by a split insulator defined by a first insulator segment **108A** and a second insulator segment **108B**. In practice, there can be more segments than that shown. Moreover, the electrical contact **214** can be provided on any one or more insulator segments.

The inner socket **104** comprises an electrical contact **110**, e.g., a conductive tab as illustrated on an inside surface of the first insulator segment **108A**. However, the electrical contact **110** can take any form or structure as set out in greater detail with reference to FIG. 1A. Also, the outer plug **106** comprises an electrical contact **114**, e.g., a electrical contact **114A** positioned on an outside surface of the first insulator segment **108A**, and an electrical contact, e.g., a electrical contact **114B** positioned on an outside surface of the second insulator segment **108B**. However, the electrical contact **114** can take an alternative form or structure as set out in greater detail with reference to FIG. 1A. Also, in the embodiment of FIG. 1D, there is no outer wall analogous to the outer wall **116** of FIG. 1A (much like the embodiment of FIG. 1C).

As illustrated, the first insulator segment **108A** is spaced from the second insulator segment **108B** by a gap at each end. Thus, there is no annular ring formed by the insulator segments. The use of insulator segments can be utilized to provide a tolerance with regard to a mating component by allowing a "spring action" of the segments to create a solid mechanical coupling.

Referring to FIG. 1E, still another example embodiment of a first modular electrical connector end **100** is illustrated. The illustrated first modular electrical connector end **100** is similar to the first modular electrical connector end **100** of FIG. 1A unless otherwise noted. As such, like elements are illustrated with like reference numbers. Moreover, similar

elements will not be described in detail. Rather, the disclosure with regard to similar elements to that of FIG. 1A is adopted by analogy.

Analogous to FIG. 1A, the illustrated first modular electrical connector end **100** includes a body **102** having an inner socket **104** and an outer plug **106**. The outer plug **106** at least partially circumscribes and is spaced outwardly from the inner socket **104** and is spaced therefrom by a tubular insulator **108**. The inner socket **104** comprises an electrical contact **110**, e.g., a conductive tab as illustrated on an inside surface of the tubular insulator **108**. However, the electrical contact **110** can take any form or structure as set out in greater detail with reference to FIG. 1A. Also, the outer plug **106** comprises an electrical contact **114**, e.g., a conductive material positioned on an outside surface of the tubular insulator **108**. However, the electrical contact **114** can take any form or structure as set out in greater detail with reference to FIG. 1A.

The embodiment of FIG. 1E differs from the embodiment of FIG. 1A in that the outer wall **116** of FIG. 1A is replaced by an outer wall **116** that further includes a key **118** and/or a notch **120**. The key **118** and/or notch **120** can be utilized for configurations that require a specific alignment of the first modular electrical connector end **100** to a mating component. The key **118** and/or notch **120** can also be integrated into other embodiments that include an outer wall, e.g., the embodiment of FIG. 1B.

#### Second Modular Electrical Connector End

Referring to FIG. 2A, an example second modular electrical connector end **200** is illustrated. The second modular electrical connector end **200** is usable with a modular electrical distribution system, and can be utilized in cooperation with any of the first modular electrical connector end **100** (FIG. 1A-FIG. 1E), as will be described in greater detail herein.

The example second modular electrical connector end **200** includes in general, a body **202** that supports an outer socket **204** and an inner plug **206**. The outer socket **204** at least partially circumscribes, and is spaced outwardly from the inner plug **206**. In some embodiments, the spacing between the outer socket **204** and the inner plug **206** corresponds to the dimensions of the annular ring of the tubular insulator **108** (FIG. 1A), the first insulator segment **108A** and the second insulator segment **108B** (FIG. 1D), etc.

The outer socket **204** of the second modular electrical connector end **200** is defined by a tubular insulator **208** that projects from the body **202**. A space within an inside diameter of the tubular insulator **208**, along with the depth of the space within the tubular insulator **208**, forms a receptacle of the outer socket **204**. In this regard, an electrical contact **210** is positioned on an inside surface of the tubular insulator **208**. The electrical contact **210** can comprise a conductive tab, a flat conductive pad, a conductive ring or band that circumscribes the inside diameter of the tubular insulator **208**, an arcuate conductive surface that covers only a portion of the inside diameter of the tubular insulator **208**, a conductive structure having a spring characteristic, etc.

Notably, a spring characteristics can be provided in any of the above-structures. For example, the spring characteristic of the electrical contact **210**, where provided, can be implemented as one or more of a spring finger contact, clip, multi-directional spring contact, tab spring, etc. As additional examples, the spring characteristic can be built into a ring or band of metal surrounding the inside diameter of the tubular insulator **208**, which is implemented as a set of leaf springs, a cylinder with at least one leaf spring, a band



having a set of axial slits with a central, radially inward bulge, a spring or clip that applies force (radially inward or radially outward) to ensure good electrical contact with a mating contact, etc. As will be described in greater detail herein, the electrical contact **210** facilitates an electrical connection to a wire of the modular electrical distribution system.

The inner plug **206** of the second modular electrical connector end **200** is defined by an exterior surface of an insulator **212** that projects from the body **202**. In some embodiments, the insulator **212** is coaxial with, and is circumscribed at least partially by the tubular insulator **208**. Thus, the insulator **212** is within the tubular insulator **208**. For instance, the insulator **212** is illustrated as having an outside diameter that projects from the body **202**, thus exposing an outside surface thereof. In some embodiments, the insulator **212** is a tubular insulator, and is thus hollow. In other embodiments, the insulator **212** is solid.

An electrical contact **214** is positioned on at least a portion of the outside surface of the insulator **212**, thus defining the conductor of the inner plug **206**. As will be described in greater detail herein, the electrical contact **214** of the inner plug **206** facilitates an electrical connection to a wire of the modular electrical distribution system. Analogous to that described more fully herein, the electrical contact **214** can be implemented as a conductive material, a conductive tab on the outside surface of the insulator **212**, a conductive pad, a conductive ring or band that circumscribes the outside diameter of the insulator **212**, an arcuate conductive surface that covers only a portion of the outside diameter of the insulator **212**, a conductive structure having a spring characteristic, etc.

Notably, a spring characteristics can be provided in any of the above-structures. For instance, the spring characteristic, where provided, can be built into a ring or band of metal surrounding the outside diameter of the insulator **212**, which is implemented as a set of leaf springs, a cylinder with at least one leaf spring, a band having a set of axial slits with a central bulge, a spring that applies outward force to ensure good electrical contact with a mating contact, etc. Also, the electrical contact **214** can be implemented as one or more of a spring finger contact, clip, multi-directional spring contact, spring tab, etc.

Since the outer socket **204** circumscribes and is spaced outwardly from the inner plug **206**, the outer socket **204** and the inner plug **206** can be each formed on separate insulators (i.e., tubular insulator **208** and insulator **212** respectively). In the example the tubular insulator **208** and insulator **212** are formed as concentric tubular rings extending from the housing. In other embodiments, the plug **206** is implemented on a projection, and the socket **204** is recessed into a cylindrical aperture that extends into the body **102**.

Referring to FIG. 2B, an alternative configuration is illustrated. The configuration of FIG. 2B is identical to that of FIG. 2A except that the tubular insulator **208** of FIG. 2A is replaced by two or more arcuate sections (e.g., **208A**, **208B**) such that there is an air gap between each arcuate section. At least one of the arcuate sections includes the electrical contact **210**.

Analogous to FIG. 2A, the illustrated second modular electrical connector end **200** includes a body **202** having an outer socket **204** and an inner plug **206**. The outer socket **204** comprises an electrical contact, e.g., a electrical contact **210**. Also, the inner plug **106** comprises an electrical contact, e.g., a electrical contact **214** positioned on an outside surface of an insulator **212**.

However, the embodiment of FIG. 2B differs from the embodiment of FIG. 2A in that tubular insulator **208** of FIG. 2A is replaced by insulator segments, illustrated by a first insulator segment **208A** and a second insulator segment **208B**. The electrical contact **210** is positioned on the first insulator segment **208A** solely for clarity of illustration. In practice, there can be a electrical contact **210** on each insulator segment. Moreover, there can be more than two insulator segments.

The first insulator segment **208A** is spaced from the second insulator segment **208B** by a gap at each end. Thus, there is no annular ring formed entirely around the tubular insulator **212** like the tubular insulator **208** of FIG. 1A. Rather, the segments form spaced projections of non-conductive material. The use of insulator segments may be utilized, for instance, to provide a tolerance with regard to a mating component by allowing a “spring action” of the segments to create a solid mechanical coupling. In practice, there can be more segments than the first and second segments illustrated.

Referring to FIG. 2C, another example embodiment of a second modular electrical connector end **200** is illustrated. The illustrated second modular electrical connector end **200** is similar to the second modular electrical connector end **200** of FIG. 2A unless otherwise noted. As such, like elements are illustrated with like reference numbers. Moreover, similar elements will not be described in detail. Rather, the disclosure with regard to similar elements to that of FIG. 2A is adopted by analogy. The second modular electrical connector end **200** of FIG. 2C is usable with a modular electrical distribution system, and can be utilized in cooperation with any of the first modular electrical connector end **100** (FIG. 1A-FIG. 1E).

Analogous to FIG. 2A, the illustrated second modular electrical connector end **200** includes a body **202** having an outer socket **204** and an inner plug **206**. The outer socket **204** comprises an electrical contact, e.g., a electrical contact **210**. Also, the inner plug **106** comprises an electrical contact, e.g., a electrical contact **214** positioned on an outside surface of an insulator **212**.

However, the embodiment of FIG. 2C differs from the embodiment of FIG. 2A in that insulator **212** of FIG. 2A is replaced by insulator segments, illustrated by a first insulator segment **212A** and a second insulator segment **212B**. The electrical contact **214** is positioned on the first insulator segment **212A** solely for clarity of illustration. In practice, there can be a electrical contact **214** on each insulator segment. Moreover, there can be more than two insulator segments.

The first insulator segment **212A** is spaced from the second insulator segment **212B** by a gap at each end. Thus, there is no annular ring formed like the tubular insulator **212** of FIG. 1A. Rather, the segments form spaced projections of non-conductive material. The use of insulator segments may be utilized, for instance, to provide a tolerance with regard to a mating component by allowing a “spring action” of the segments to create a solid mechanical coupling. In practice, there can be more segments than the first and second segments illustrated.

Referring to FIG. 2D, yet another example embodiment of a second modular electrical connector end **200** is illustrated. The illustrated second modular electrical connector end **200** is similar to the second modular electrical connector end **200** of FIG. 2A unless otherwise noted. As such, like elements are illustrated with like reference numbers. Moreover, similar elements will not be described in detail. Rather, the disclosure with regard to similar elements to that of FIG. 2A



## 11

is adopted by analogy. The second modular electrical connector end **200** of FIG. 2D is usable with a modular electrical distribution system, and can be utilized in cooperation with any of the first modular electrical connector end **100** (FIG. 1A-FIG. 1E).

Analogous to FIG. 2A, the illustrated second modular electrical connector end **200** includes a body **202** having an outer socket **204** and an inner plug **206**. The outer socket **204** comprises an electrical contact, e.g., a electrical contact **210**. Also, the inner plug **206** comprises an electrical contact, e.g., a electrical contact **214** positioned on an outside surface of an insulator **212**.

However, the embodiment of FIG. 2D differs from the embodiment of FIG. 2A in that tubular insulator **208** of FIG. 2A is replaced by insulator segments, illustrated by a first insulator segment **208A** and a second insulator segment **208B** (analogous to FIG. 2B). The electrical contact **210** is positioned on the first insulator segment **208A** solely for clarity of illustration. In practice, there can be a electrical contact **210** on each insulator segment. Moreover, there can be more than two insulator segments.

Also, the embodiment of FIG. 2D differs from the embodiment of FIG. 2A in that insulator **212** of FIG. 2A is replaced by insulator segments, illustrated by a first insulator segment **212A** and a second insulator segment **212B** (analogous to FIG. 2C). The electrical contact **214** is positioned on the first insulator segment **212A** solely for clarity of illustration. In practice, there can be a electrical contact **214** on each insulator segment. Moreover, there can be more than two insulator segments.

Referring to FIG. 2E, another example embodiment of a second modular electrical connector end **200** is illustrated. The illustrated second modular electrical connector end **200** is similar to the second modular electrical connector end **200** of FIG. 2A unless otherwise noted. As such, like elements are illustrated with like reference numbers. Moreover, similar elements will not be described in detail. Rather, the disclosure with regard to similar elements to that of FIG. 2A is adopted by analogy. The second modular electrical connector end **200** of FIG. 2E is usable with a modular electrical distribution system, and can be utilized in cooperation with any of the first modular electrical connector end **100** (FIG. 1A-FIG. 1E).

Analogous to FIG. 2A, the illustrated second modular electrical connector end **200** includes a body **202** having an outer socket **204** and an inner plug **206**. The outer socket **204** comprises a tubular insulator **108** that supports an electrical contact, e.g., a electrical contact **210**. Also, the inner plug **206** comprises an insulator **212** that supports an electrical contact, e.g., a electrical contact **214**.

However, the embodiment of FIG. 2E differs from the embodiment of FIG. 2A in that tubular insulator **208** of FIG. 2E includes a key slot **218** that receives the key **118** (FIG. 1E).

Referring to FIG. 2A through 2E, any configuration can also alternatively include an outer wall, e.g., analogous to the tubular insulator **108** of FIG. 1A.

#### Distribution Connection

FIG. 3 illustrates a partial view of a distribution connection **300**. As illustrated, a first modular electrical connector end **302** (of a first cable assembly, not shown for conciseness) is electrically and mechanically connected to a second modular electrical connector end **304** (of a second cable assembly, not shown for conciseness).

By way of example, the first modular electrical connector end **302** can be implemented by any one of the first modular electrical connector end **100** described with reference to

## 12

FIGS. 1A-1E. As such, the disclosure of FIGS. 1A-1E is incorporated herein and the details of the first modular electrical connector end **302** will not be further described.

Analogously, the second modular electrical connector end **304** can be implemented by any one of the second modular electrical connector end **200** described with reference to FIGS. 2A-2E. As such, the disclosure of FIGS. 2A-2E is also incorporated herein and the details of the second modular electrical connector end **304** will not be further described.

With reference to FIGS. 1A-3 generally, the inner plug **206** of the second modular electrical connector end **200** is received into the socket **104** of the first modular electrical connector end **100**. More particularly, the electrical contact **214** on the outer surface of the tubular insulator **212** of the inner plug **206** makes direct and physical/mechanical contact with the electrical contact **110**, e.g. conductive tab on the inside diameter of the tubular insulator **108** of the inner socket **104**.

Notably, in some embodiments, either the electrical contact **214**, the electrical contact **110** or both form a complete circle/annular ring such that the first modular electrical connector end **100** can be in any rotational orientation relative to the second modular electrical connector end **200** and can still maintain electrical contact. In other embodiments, one or both of the electrical contact **214** and the electrical contact **110** do not form a complete circle/annular ring such that the first modular electrical connector end **100** must be rotated into a proper rotational orientation relative to the second modular electrical connector end **200** to form an electrical contact. Here, there can be one or more discrete rotational positions where electrical contact is formed. For example, the electrical contact **214** can have one or more breaks so as to define discrete conductive positions, any one of which can be rotated into contact with the electrical contact **110**. Other configurations can alternatively be implemented.

Likewise, the outer plug **106** of the first modular electrical connector end is received into the outer socket **204** of the second modular electrical connector end **200**. More particularly, the electrical contact **114** on the outside surface of the tubular insulator **108** of the outer plug **106** makes direct and physical/mechanical contact with the electrical contact **210** on the inside diameter of the tubular insulator **208** of the outer socket **204**.

Analogous to that above, in some embodiments, either the electrical contact **114**, the electrical contact **210** or both form a complete circle/annular ring such that the first modular electrical connector end **100** can be in any rotational orientation relative to the second modular electrical connector end **200** and can still maintain electrical contact. In other embodiments, one or both of the electrical contact **114** and the electrical contact **210** do not form a complete circle/annular ring such that the first modular electrical connector end **100** must be rotated into a proper rotational orientation relative to the second modular electrical connector end **200** to form an electrical contact. Here, there can be one or more discrete rotational positions where electrical contact is formed. For example, the electrical contact **114** can have one or more breaks so as to define discrete conductive positions, any one of which can be rotated into contact with the electrical contact **110**. Other configurations can alternatively be implemented.

Notably, in some embodiments, e.g., the embodiment of FIG. 1A, the first modular electrical connector end **100** includes an outer wall **116**, which is an insulative outer ring. Where provided, this outer wall **116** forms a mechanical fit with the outer wall of the tubular insulator **208**. This is not



13

strictly required, but may be provided, for example, to create added mechanical coupling of the first modular electrical connector end **100** to the modular electrical connector end **200**.

#### Cable Assembly

Referring now to FIG. **4A**, an electrical cable **400** is illustrated according to aspects of the present disclosure. The illustrated electrical cable **400** can form part of a modular electrical distribution system. In this regard, the electrical cable **400** includes a first modular electrical connector end **402**, a second modular electrical connector end **404**, and a wire bundle **406** that forms an electrical connection between the first modular electrical connector end **402** and the second modular electrical connector end **404**.

By way of example, the first modular electrical connector end **402** can be implemented by any one of the first modular electrical connector end **100** described with reference to FIGS. **1A-1E**. As such, the disclosure of FIGS. **1A-1E** is incorporated herein and the details of the first modular electrical connector end **402** will not be further described.

Analogously, the second modular electrical connector end **404** can be implemented by any one of the second modular electrical connector end **200** described with reference to FIGS. **2A-2E**. As such, the disclosure of FIGS. **2A-2E** is incorporated herein and the details of the second modular electrical connector end **404** will not be further described.

As noted above, the wire bundle **406** forms an electrical connection between the first modular electrical connector end **402** and the second modular electrical connector end **404**. With reference briefly to FIGS. **1A-4A**, in the illustrated example, the first modular electrical connector end **402** and the second modular electrical connector end **404** each include a single plug and a single socket. In this regard, the wire bundle **406** includes a first wire **406A** that electrically connects the conductive tab of the inner socket (e.g., see the electrical contact **110** illustrated as a conductive tab of the inner socket **104** of the first modular electrical connector end **100** (FIGS. **1A-1E**) of the first modular electrical connector end **402** to the conductive material on the inner plug of the second modular electrical connector end **404** (e.g., electrical contact **214** of the inner plug **206** of the second modular electrical connector end **200**, FIGS. **2A-2E**).

The wire bundle **406** also includes a second wire **406B** that electrically connects the conductive tab of the outer socket of the second modular electrical connector end **404** (e.g., the electrical contact **210** of the outer socket **204** of the second modular electrical connector end **200**, FIGS. **2A-2E**) to the conductive material on the outer plug of the first modular electrical connector end **402** (e.g., electrical contact **114** of the outer plug **106** of the first modular electrical connector end **100**, FIGS. **1A-1E**).

In this regard, wire, conductive material, and conductive tab configurations are selected for the power requirements of the device. For instance, in some embodiments, the electrical cable **400** passes 120 VAC. In other embodiments, e.g., where light emitting diode (LED) lighting is provided, the electrical cable **400** may pass 12 VDC, 5 VDC or other suitable voltage, as dictated by the lighting requirements.

As such, a series of electrical cables **400** can be strung together to form a modular electrical distribution system by plugging the second modular electrical connector end **404** of a first electrical cable **400** into a corresponding first modular electrical connector end **402** of a second electrical cable **400**, or vice-versa. This process can be repeated for as many cables as desired.

14

With reference to FIG. **4B**, an electrical cable **400** is illustrated, which is analogous to the electrical cable **400** of FIG. **4A**. As such, like structure is illustrated with like reference numbers. Since like elements are included, only differences are discussed in detail. Notably, the electrical cable **400** of FIG. **4B** is identical to the electrical cable **400** of FIG. **4A**, except that the electrical cable **400** of FIG. **4B** also includes a courtesy extension cable **410** that extends therefrom. The courtesy extension cable **410** includes a first extension wire **412A**, a second extension wire **412B**, and an electrical connector **414**. Here, the extension wire **412A** is electrically connected to the first wire **406A**, and the second extension wire **412B** is electrically connected to the second wire **406B**. The electrical connector **414** is any coupling means to attach power to a light or other powered device. For instance, the electrical connector **414** can be implemented as a conventional AC (alternating current) plug, such as a dual blade configuration, where a first blade is a conductive blade **416A** that is electrically connected to the first extension wire **412A**, and hence is electrically connected to the first wire **406A**. Analogously, the second blade is a conductive blade **414B** that is electrically connected to the second extension wire **412B**, and is hence, electrically connected to the second wire **406B**. In alternative embodiments, the electrical connector **414** can be an outlet or other configuration.

In practical applications, the courtesy extension cable **410** can be electrically and/or mechanically coupled to the electrical cable **400** in any practical location, including the first modular electrical connector end **402**, the second modular electrical connector end **404**, anywhere along the length of the wire bundle **406**, etc. Moreover, there can be more than one courtesy extension cable **410**, each courtesy extension cable **410** anywhere on the electrical cable **400**.

With reference to FIG. **4C**, an electrical cable **400** is illustrated, which is analogous to the electrical cable **400** of FIG. **4A**. As such, like structure is illustrated with like reference numbers. Since like elements are included, only differences are discussed in detail. Notably, the electrical cable **400** of FIG. **4C** is identical to the electrical cable **400** of FIG. **4A**, except that the electrical cable **400** of FIG. **4C** also includes a courtesy outlet **420**. The courtesy outlet **420** includes an electrical socket having a first socket connector **422A** and a second socket connector **422B**. Here, the first socket connector **422A** includes a conductive portion that is electrically connected to the first wire **406A**, and the second socket connector **422B** includes a conductive portion that is electrically connected to the second wire **406B**. The electrical socket is any socket configuration, and can include a conventional AC (alternating current) socket.

In practical applications, the courtesy outlet **420** can be electrically and/or mechanically coupled to the cable in any practical location, including the first modular electrical connector end **402**, the second modular electrical connector end **404**, anywhere along the length of the wire bundle **406**, etc. Moreover, there can be more than one courtesy outlet **420**, each courtesy outlet **420** anywhere on the electrical cable **400**.

With reference to FIG. **4A**, FIG. **4B**, and FIG. **4C** generally, as illustrated, the wire bundle **406** is illustrated with two wires. In practice, the wire bundle **406** can support multiple wires, e.g., to create multiple discrete circuits. Here, each courtesy extension cable **410** (e.g., as illustrated in FIG. **4B**) and/or courtesy outlet **420** (e.g., as illustrated in FIG. **4C**) can connect to the same or different circuit. Here,



## 15

the number of necessary wires can depend upon the number of plugs and corresponding sockets provided on the body of the electrical connector ends.

#### First Modular Electrical Connector End With Parallel Circuits

Referring to FIG. 5, another example modular electrical connector end 500 is illustrated. The modular electrical connector end 500 is usable with a modular electrical distribution system, described more fully herein.

The modular electrical connector end 500 is largely analogous to the first modular electrical connector end 100 of FIGS. 1A-1E. As such, like elements are illustrated with like reference numbers 400 higher. Moreover, the description of FIGS. 1A-1E is incorporated into the modular electrical connector end 500. As such, for sake of conciseness, only differences are discussed in detail.

The example first modular electrical connector end 500 includes in general, a body 502 that houses an inner socket 504 and a plurality of outer plugs 506 that all at least partially circumscribe the inner socket 504.

The inner socket 504 of the first modular electrical connector end 500 is defined by an interior of a tubular insulator 508. For instance, as illustrated, a tubular insulator 508 is illustrated as having an inside diameter that defines a cross-section of a hollow of the tubular insulator 508. The inside diameter, along with the depth of the hollow, thus form a receptacle for the inner socket 504. The inner socket 504 comprises a conductive tab 510 on an inside surface thereof. The conductive tab 510 can comprise for example, a flat metal pad, a metal having a spring characteristic, etc. As will be described in greater detail herein, the conductive tab 510 facilitates an electrical connection to a wire of the modular electrical distribution system.

The outer plugs 506 of the first modular electrical connector end 500 are defined by surfaces of one or more insulators (e.g., tubular insulators, insulator segments, etc.) that project from the body 102. Here, so long as the insulator forms a projection from the body 502, a corresponding outer plug 506 can be on the inside surface or outside surface. Regardless, each plug is defined by an electrical contact 512, thus defining the conductor of the outer plug 506. As described in greater detail herein, the electrical contact 512 of each outer plug 506 facilitates an electrical connection to a corresponding wire of the modular electrical distribution system, and can comprise any structure, e.g., analogous to the electrical contact 110, electrical contact 114 (FIGS. 1A-1E), electrical contact 210, electrical contact 214 (FIGS. 2A-2E), combinations thereof, etc.

#### Second Modular Electrical Connector End With Parallel Circuits

Referring to FIG. 6, another example modular electrical connector end 600 is illustrated. The modular electrical connector end 600 is usable with a modular electrical distribution system, described more fully herein, and is particularly suited for use with the modular electrical connector end 500 (FIG. 5).

The modular electrical connector end 600 is largely analogous to the second modular electrical connector end 200 of FIGS. 2A-2E. As such, like elements are illustrated with like reference numbers 400 higher. Moreover, the description of FIGS. 2A-2E are incorporated into the modular electrical connector end 600. As such, for sake of conciseness, only differences are discussed in detail.

The example second modular electrical connector end 600 includes in general, a body 602 that houses a plurality of outer sockets 604 and one or more inner plugs 606, where the outer sockets 604 all circumscribe the inner plug(s) 606.

## 16

Each outer socket 604 of the second modular electrical connector end 600 is defined by volume formed by one or more corresponding insulators. For instance, as illustrated, a first insulator 608A at least partially circumscribes and is spaced outwardly from a second insulator 608B. As such, a receptacle is defined by the gap between an inside major surface of the first insulator 608A and an outside major surface of the second insulator 608B. This provides an opportunity to accommodate two or more plugs into the same void.

Each outer socket 604 comprises an electrical contact 610. The electrical contact 610 can comprise any structure, e.g., analogous to the electrical contact 110, electrical contact 114 (FIGS. 1A-1E), electrical contact 210, electrical contact 214 (FIGS. 2A-2E), combinations thereof, etc. As will be described in greater detail herein, each electrical contact 610 facilitates an electrical connection to a corresponding wire of the modular electrical distribution system. Because of the thickness of the second insulator 608B, one or more electrical contacts 610 can be positioned on an outside major surface thereof, and one or more electrical contacts 610 can be positioned on an inside major surface thereof.

The inner plug(s) 606 of the second modular electrical connector end 600 is/are defined by an exterior surface of an insulator that projects from the housing 602. For instance, as illustrated, the insulator 612A is illustrated as having an outside surface that projects from the housing 602, thus exposing an outside surface. The outside surface includes an electrical contact 614, e.g., is covered with a conductive material, thus defining the conductor of a first plug 606. In practice, the electrical contact 614 can comprise any structure, e.g., as analogous to the electrical contact 110, electrical contact 114 (FIGS. 1A-1E), electrical contact 210, electrical contact 214 (FIGS. 2A-2E), combinations thereof, etc. Analogously, an insulator 612B is illustrated as having an outside surface that projects from the housing 602 (e.g., at least partially circumscribing the insulator 612A), thus exposing an outside surface. The outside surface is covered with a electrical contact 614, thus defining the conductor of a second plug 606. As described in greater detail herein, the electrical contact 614 of the plugs 606 and the electrical contact 610 of the sockets 604 facilitate corresponding electrical connections to associated wires of the modular electrical distribution system.

Referring to FIG. 5 and FIG. 6 taken together, the first modular electrical connector end 500 and the second modular electrical connector end 600 support four parallel circuits, and are formed as mating connectors. Thus, a cable bundle formed in an electrical cable including the first modular electrical connector end 500 and the second modular electrical connector end 600 would include a minimum of five wires, including four signal carrying wires and a common ground. In other applications, each wire can carry its own ground, or multiple wires can be provided per circuit. For instance, where color changing LEDs are used, each circuit can carry five or more wires, such as two wires for power, and three wires for sending control signals such as to control a red, green, blue (RGB) controller of an LED string. A wire may also be provided for a white LED, etc. In example applications, the number of wires per circuit will depend upon the illumination requirements of a corresponding decoration. In this regard, the modular distribution system can adapt to handle a variety of illumination requirements, e.g., by changing the number of electrical connector on the modular electrical connector ends and associated number of wires.



## Example Illuminable Artificial Tree

An example application is an illuminable decoration such as an artificial tree. The artificial tree includes trunk section formed by hollow tubes that stack together to form a “trunk” of the artificial tree. An electrical cable is installed within each trunk section. In this regard, when the trunk sections are assembled together, power can be passed up the truck.

Referring to FIG. 7, an exploded view shows that a first electrical cable **700A** includes a first modular electrical connector end **702A**, a second modular electrical connector end **704A**, and a wire bundle **706A** that forms an electrical connection between the first modular electrical connector end **702A** and the second modular electrical connector end **704A**. Here, the electrical cable **700A** can be analogous to the electrical cable **400** (e.g., any embodiment shown in FIGS. 4A-4C) and/or include a cable assembly that includes any of the modular connector ends of other features, capabilities, etc., described more fully herein with reference to FIGS. 1A-6. The first electrical cable **700A** is installed inside a hollow of a first trunk section **708A**. For instance, the first modular electrical connector end **702A** can be analogous to the first modular electrical connector end **100** (FIGS. 1A-1E), the first modular electrical connector end **500** (FIG. 5) or other suitable configuration. Similarly, the second modular electrical connector end **704A** can be analogous to the second modular electrical connector end **200** (FIGS. 2A-2E), the second modular electrical connector end **600** (FIG. 6) or other suitable configuration.

Analogously, a second electrical cable **700B** includes a first modular electrical connector end **702B**, a second modular electrical connector end **704B**, and a wire bundle **706B** that forms an electrical connection between the first modular electrical connector end **702B** and the second modular electrical connector end **704B**. Here, the electrical cable **700B** can be analogous to the electrical cable **400** (e.g., any embodiment shown in FIGS. 4A-4C) and/or include a cable assembly that includes any of the modular connector ends of other features, capabilities, etc., described more fully herein with reference to FIGS. 1A-6. The second electrical cable **700B** is installed inside a hollow of a second trunk section **708B**. For instance, the first modular electrical connector end **702B** can be analogous to the first modular electrical connector end **100** (FIGS. 1A-1E), the first modular electrical connector end **500** (FIG. 5) or other suitable configuration. Similarly, the second modular electrical connector end **704B** can be analogous to the second modular electrical connector end **200** (FIGS. 2A-2E), the second modular electrical connector end **600** (FIG. 6) or other suitable configuration.

Although only two trunk sections **708A** and **708B** are illustrated for sake of conciseness, in practice the artificial tree can include as many trunk sections as is necessary to define an overall height of the artificial tree. Notably, a first electrical cable is installed into a first trunk section of a decoration such as an artificial tree, a second electrical cable is installed into a second trunk section of the decoration, etc. Moreover, in some embodiments, when the trunk sections are connected, the first trunk section mechanically couples to the second trunk section, and the first electrical cable mechanically and electrically couples to the second electrical cable.

In some embodiments, the cable ends are positioned in the respective trunk sections such that no step is required to make the electrical connection beyond mechanically connecting the respective trunk sections. That is, as a second trunk section is slid axially into a first trunk section, a corresponding second modular electrical connector end of

the second trunk section simultaneously and automatically connects (e.g., mechanically and electrically) to a first modular electrical connector end of the first trunk section. Thus, a modular electrical distribution system is automatically built (both mechanically and electrically) as trunk sections are mechanically connected to form a trunk.

## Another Example Trunk Section Connection

FIG. 8A illustrates a schematic cross-section of an example trunk connection showing a first trunk section **802A** mechanically coupling to a second trunk section **802B**, and a first electrical cable **804A** mechanically and electrically coupling to a second electrical cable **804B**, according to aspects of the present disclosure. In general, FIG. 8A illustrates partial views of the first trunk section **802A**, the second trunk section **802B**, first electrical cable **804A**, and second electrical cable **804B** for convenience of illustration and discussion.

The second trunk section **802B** is illustrated sliding downward axially onto the first trunk section **802A**. When the second trunk section **802B** is inserted into the first trunk section **802A**, the mechanical coupling of the trunk sections simultaneously and automatically forms the electrical connections between the first electrical cable **804A** and second electrical cable **804B** as described more fully herein.

The first electrical cable **804A** includes a first modular electrical connector end **806A**. A second modular electrical connector end is not illustrated for conciseness of discussion herein. However, a wire bundle **808A** forms an electrical connection between the first modular electrical connector end **806A** and the second modular electrical connector end (not shown). Here, the electrical cable **804A** is be analogous to the electrical cable **400** (any embodiment of FIGS. 4A-4C); electrical cable **706A**, **706B** (FIG. 7) and/or can include a cable assembly that includes any of the modular connector ends of other features, capabilities, etc., described more fully herein, e.g., with reference to FIG. 1A-FIG. 7. The first electrical cable **804A** is installed inside a hollow of a first trunk section **802A**. In this embodiment, the first modular electrical connector end **806A** can be analogous to the first modular electrical connector end **100** (any embodiment in FIGS. 1A-1E), the first modular electrical connector end **500** (FIG. 5) or other suitable configuration. Similarly, the second modular electrical connector end (not shown) can be analogous to the second modular electrical connector end **200** (any embodiment in FIGS. 2A-2E), the second modular electrical connector end **600** (FIG. 6) or other suitable configuration.

Analogously, the second electrical cable **804B** includes a first modular electrical connector end (not shown for conciseness), a second modular electrical connector end **806B**, and a wire bundle **808B** that forms an electrical connection between the first modular electrical connector end and the second modular electrical connector end **806B**. Here, the electrical cable **804B** can be analogous to the electrical cable **400** (FIGS. 4A-4C); electrical cable **706A**, **706B** (FIG. 7) and/or include a cable assembly that includes any of the modular connector ends of other features, capabilities, etc., described more fully herein with reference to FIGS. 1A-7. Analogous to the first electrical cable **804A**, the first modular electrical connector end (not shown) can be analogous to the first modular electrical connector end **100** (any embodiment in FIGS. 1A-1E), the first modular electrical connector end **500** (FIG. 5) or other suitable configuration. Similarly, the second modular electrical connector end **806B** can be analogous to the second modular electrical connector end



**200** (any embodiment in FIGS. **2A-2E**), the second modular electrical connector end **600** (FIG. **6**) or other suitable configuration.

Also illustrated in FIG. **8A**, at least one of the cable ends includes additional distribution capability. For instance, as illustrated, the second electrical cable **800B** includes an outlet **810**. The outlet **810** can be exposed through the outside surface of the corresponding trunk section **802A**. The outlet **810** can be used to plug in lights, e.g., lights wrapped around branches of the trunk section **802A**.

In FIG. **8A**, conductive elements are illustrated in solid fill and are connected by conductive wires. Insulative material is illustrated by hatched shading. The electrical connections are analogous to those described with reference to FIGS. **1A-7**.

Referring now to FIG. **8B**, a schematic cross-section of another example trunk connection is illustrated, showing a first trunk section **802A** mechanically coupling to a second trunk section **802B**, and a first electrical cable **804A** mechanically and electrically coupling to a second electrical cable **804B**, according to aspects of the present disclosure. In general, FIG. **8B** is analogous to that of FIG. **8A**, and as such, like structure is illustrated with like reference numbers. Therefore, only differences will be discussed. As illustrated, FIG. **8B** includes a courtesy extension cable **812** rather than an outlet **810** of FIG. **8A**. Thus, by way of comparison, in FIG. **8B**, the first electrical cable **804A** can be implemented by the cable **400** of FIG. **4B**. Analogously, the first electrical cable **804A** in FIG. **8A** can be implemented by the cable **400** of FIG. **4C**. The extension cable **812** can be used to plug in string lights or other items requiring electrical power.

Referring to FIG. **9**, a schematic cross-section of an example trunk connection illustrates a first trunk section **902A** mechanically couplable to a second trunk section **902B**, and a first electrical cable **904A** mechanically and electrically coupled to a second electrical cable **904B**, according to aspects of the present disclosure. In general, FIG. **9** is analogous to that described with reference to FIG. **7**, FIG. **8A** and FIG. **8B** except that in FIG. **9**, the connector ends of each electrical cable are offset within the corresponding trunk section. Notably, one end of each trunk section includes a taper to enable stacking of the trunk sections. The electrical connector end in the taper extends into the taper, and in some embodiments, outside the taper of the corresponding trunk section. On the other hand, the electrical end opposite the taper is recessed into the trunk such that when a taper of one trunk section is received into the open end of another trunk section, the electrical connectors mate.

In some embodiments, both electrical connector ends can extend outside the trunk section, e.g., to define adapters that couple the trunk sections. By comparison, as best illustrated in FIG. **8A**, and FIG. **8B**, in alternative embodiments, the connector ends are located within the trunk sections.

Regardless of cable configuration (FIG. **8A**, FIG. **8B**, FIG. **9**), the cables can be connected to the respective trunk sections via one or more screws, glue, or other fastening means. Moreover, each modular electrical connector end **100** (FIG. **1A-1E**) and/or modular electrical connector end **200** (FIG. **2A-2E**) can be formed as a clamshell housing to facilitate manufacture. The clamshell sections can be ultrasonically welded, glued, mechanically fastened, etc. at the time of manufacture.

FIG. **10** illustrates an example decoration, implemented as an artificial illuminated tree **1000**, according to aspects of the present disclosure. The artificial tree **1000** includes a

stand **1002** to which power is provided via a power cord **1004**. The power cord **1004** can mate with a connector in the stand **1002**, which includes an electrical connector that correspondingly mates with an end of a trunk section **1006**.

As illustrated, three trunk sections **1006** are stacked together to form the trunk of the artificial tree. Each trunk section **1006** includes a cable assembly, which can be implemented according to any combination of embodiments disclosed in any of the preceding FIGS. **1A-9**. Moreover, artificial tree branches **1008** are coupled to each trunk section **1006**. In the illustrated view the cable assembly within each trunk section **1006** is not visible. However, the cable assemblies in this embodiment include a courtesy extension cable **1012**, which can be analogous that described with reference to FIG. **4B**, **8B**, combination thereof, etc. In this regard, each courtesy extension cable **1012** can electrically connect to one or more light strings **1014** strung along the artificial tree branches **1008**. Alternatively, the light strings **1014** can plug into an outlet, which can be analogous that described with reference to FIG. **4C**, **8A**, combination thereof, etc.

Thus, electrical power is provided via the power cord **1004** to the base of the bottom-most trunk section **1006** via an electrical connector in the stand **1002**. Power flows up the bottom-most trunk section **1006** via a bottom-most cable assembly (not shown). Power travels from the bottom-most cable assembly via the courtesy electrical extension cable **1012** to corresponding light string(s) on the artificial tree branches **1008** of the bottom-most trunk section. Power also travels to the intermediate trunk section **1006** via the corresponding intermediate cable assembly. Power travels from the intermediate cable assembly via the courtesy electrical extension cable **1012** to corresponding light string(s) on the artificial tree branches **1008** of the middle trunk section. Power also travels to the top-most trunk section **1006** via the corresponding top-most cable assembly. Power travels from the top-most cable assembly via the courtesy electrical extension cable **1012** to corresponding light string(s) on the artificial tree branches **1008** of the top-most trunk section. Power also travels to a star or other illuminable ornament at the top of the artificial tree.

Notably, where the trunk sections include branches thereof, and the branches include strings of lights pre-strung, the entire artificial tree can be set up in five steps, namely, by installing the bottom-most trunk section into the stand, stacking the intermediate trunk section into the bottom-most trunk section, stacking the top-most trunk section into the intermediate trunk section, adorning the top of the tree with a decoration (e.g., a star as shown), and plugging the power cord of the stand into a wall outlet.

The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the invention. As used herein, the singular forms “a”, “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “comprises” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

The corresponding structures, materials, acts, and equivalents of all means or step plus function elements in the claims below are intended to include any structure, material, or act for performing the function in combination with other claimed elements as specifically claimed. The description of the present invention has been presented for purposes of illustration and description, but is not intended to be exhaus-



## 21

tive or limited to the invention in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art without departing from the scope and spirit of the invention. Aspects of the invention were chosen and described in order to best explain the principles of the invention and the practical application, and to enable others of ordinary skill in the art to understand the invention for various embodiments with various modifications as are suited to the particular use contemplated.

What is claimed is:

1. An illuminable decoration comprising:

- a first trunk section and a second trunk section, the first trunk section and the second trunk section each comprising of a hollow tube;
- a first cable assembly coupled to the first trunk section, the first cable assembly comprising:
  - a first modular electrical connector end, the first modular electrical connector end having an inner socket and an outer plug that at least partially circumscribes the inner socket;
  - a second modular electrical connector end, the second modular electrical connector end having an inner plug and an outer socket that at least partially circumscribes the inner plug;
  - a first electrical wire electrically coupled between an electrical contact of the inner socket of the first modular electrical connector end and an electrical contact of the inner plug of the second modular electrical connector end; and
  - a second electrical wire electrically coupled between an electrical contact of the outer plug of the first modular electrical connector end and an electrical contact of the outer socket of the second modular electrical connector end;
- wherein, the inner socket of the first modular electrical connector end comprises a tubular insulator and the electrical contact of the inner socket is implemented as a conductive tab on an inside surface of the tubular insulator, and the electrical contact of the outer plug of the first modular electrical connector end comprises a conductive material on an outside surface of the tubular insulator;
- a second cable assembly coupled to the second trunk section, the second cable assembly comprising at least one of:
  - a first modular electrical connector end, the first modular electrical connector end having an inner socket and an outer plug that circumscribes the inner socket; and
  - a second modular electrical connector end, the second modular electrical connector end having an inner plug and an outer socket that circumscribes the inner plug;
- wherein, when the first trunk section is assembled to the second trunk section end-to-end, the first trunk section and the second trunk section are mechanically connected along an axial dimension, and the first cable assembly is mechanically and electrically connected to the second cable assembly so as to form a modular electrical distribution system.

2. The illuminable decoration of claim 1, wherein:

- when the first cable assembly is mechanically and electrically connected to the second cable assembly:
  - the inner socket of the first modular electrical connector end of the first cable assembly electrically and

## 22

mechanically connects to the inner plug of the second modular electrical connector end of the second electrical assembly; and

the outer plug of the first modular electrical connector end of the first cable assembly electrically and mechanically connects to the outer socket of the second modular electrical connector end of the second electrical assembly.

3. The illuminable decoration of claim 1 further comprising:

- an outer wall defined by an insulator that forms a concentric outer ring circumscribing and spaced outwardly from the tubular insulator.

4. The illuminable decoration of claim 1 further comprising:

- at least two outer wall segments, each outer wall segment spaced by a gap at each end thereof, the at least two outer wall segments spaced outwardly from the tubular insulator.

5. The illuminable decoration of claim 1, wherein:

- the first modular electrical connector end further comprises a body, wherein:

- the tubular insulator is the only projection extending from a face of the body.

6. The illuminable decoration of claim 1, wherein:

- the second modular electrical connector end further comprises a body;

- the inner plug of the second modular electrical connector end comprises an inner insulator projecting from the body;

- the electrical contact of the inner plug comprises a conductive material on an outside surface of the inner insulator;

- the outer socket of the second modular electrical connector end comprises a tubular insulator that at least partially circumscribes and is spaced outwardly from the inner plug;

- the electrical contact of the outer socket of the second modular electrical connector end comprises a conductive tab on an inside surface of the tubular insulator.

7. The illuminable decoration of claim 1, wherein:

- the second modular electrical connector end further comprises a body;

- the inner plug of the second modular electrical connector end comprises an inner insulator projecting from the body;

- the electrical contact of the inner plug comprises a conductive material on an outside surface of the inner insulator;

- the outer socket of the second modular electrical connector end comprises at least two arcuate sections that are spaced apart from each other, and together at least partially circumscribe the inner plug;

- the electrical contact of the outer socket of the second modular electrical connector end comprises a conductive tab, on a select one of the at least two arcuate sections.

8. The illuminable decoration of claim 1, wherein:

- the first cable assembly further comprises an electrical outlet electrically coupled to the first electrical wire and the second electrical wire.

9. The illuminable decoration of claim 8, wherein:

- the outlet is physically coupled to a select one of the first modular electrical connector end or the second modular electrical connector end; and



## 23

the electrical outlet comprises a receptacle that is exposed through an outside surface of the corresponding trunk section.

10. The illuminable decoration of claim 1, wherein:  
the first cable assembly further comprises an extension  
cable electrically coupled to the first electrical wire and  
the second electrical wire.

11. The illuminable decoration of claim 10, wherein:  
the extension cable is physically coupled to a select one  
of the first modular electrical connector end or the  
second modular electrical connector end; and  
the extension cable is exposed through an outside surface  
of the corresponding trunk section.

12. The illuminable decoration of claim 1, wherein the  
inner socket of the first modular electrical connector end, the  
inner plug of the second modular electrical connector end,  
the outer plug of the first modular electrical connector end,  
and the outer socket of the second modular electrical con-  
nector end have a cross-section orthogonal to an axial axis  
that defines concentric rings.

13. The illuminable decoration of claim 1 further com-  
prising a string of lights electrically coupled to the first and  
second electrical wires of the first cable assembly.

14. A cable assembly comprising:

a first modular electrical connector end, the first modular  
electrical connector end having an inner socket and an  
outer plug that circumscribes and is spaced from the  
inner socket;

a second modular electrical connector end, the second  
modular electrical connector end having an inner plug  
and an outer socket that circumscribes and is spaced  
from the inner plug;

a first electrical wire electrically coupled between an  
electrical contact of the inner socket of the first modular  
electrical connector end and an electrical contact of the  
inner plug of the second modular electrical connector  
end; and

a second electrical wire electrically coupled between an  
electrical contact of the outer plug of the first modular  
electrical connector end and an electrical contact of the  
outer socket of the second modular electrical connector  
end;

wherein:

the inner socket of the first modular electrical connector  
end comprises a tubular insulator, the electrical contact  
of the inner socket is implemented as a conductive tab  
on an inside surface of the tubular insulator, and the  
electrical contact of the outer plug of the first modular  
electrical connector end comprises a conductive mate-  
rial on an outside surface of the tubular insulator; and  
when two cable assemblies are assembled together  
end-to-end, the two cable assemblies are mechanically  
connected along an axial dimension so as to form a  
modular electrical distribution system, such that the  
inner socket of the first modular electrical connector  
end of a first one of the cable assemblies electrically  
and mechanically connects to the inner plug of the  
second modular electrical connector end of a second  
one of the cable assemblies, and the outer plug of the  
first modular electrical connector end of the first one of  
the cable assemblies electrically and mechanically con-  
nects to the outer socket of the second modular elec-  
trical connector end of the second one of the cable  
assemblies.

## 24

15. The cable assembly of claim 14 further comprising:  
an outer wall defined by an insulator that forms a con-  
centric outer ring circumscribing and spaced outwardly  
from the tubular insulator.

16. The cable assembly of claim 14 further comprising:  
at least two outer wall segments, each outer wall segment  
spaced by a gap at each end thereof, the at least two  
outer wall segments spaced outwardly from the tubular  
insulator.

17. The cable assembly of claim 14, wherein:  
the first modular electrical connector end further com-  
prises a body, wherein:  
the tubular insulator is the only projection extending  
from a face of the body.

18. The cable assembly of claim 14, wherein:  
the first cable assembly further comprises an electrical  
outlet electrically coupled to the first electrical wire and  
the second electrical wire.

19. The cable assembly of claim 18, wherein:  
the outlet is physically coupled to a select one of the first  
modular electrical connector end or the second modular  
electrical connector end; and  
the electrical outlet comprises a receptacle that is exposed  
through an outside surface of the corresponding trunk  
section.

20. The cable assembly of claim 14, wherein:  
the first cable assembly further comprises an extension  
cable electrically coupled to the first electrical wire and  
the second electrical wire.

21. The cable assembly of claim 20, wherein:  
the extension cable is physically coupled to a select one  
of the first modular electrical connector end or the  
second modular electrical connector end; and  
the extension cable is exposed through an outside surface  
of the corresponding trunk section.

22. A cable assembly comprising:

a first modular electrical connector end, the first modular  
electrical connector end having an inner socket and an  
outer plug that circumscribes and is spaced from the  
inner socket;

a second modular electrical connector end, the second  
modular electrical connector end having a body, an  
inner plug and an outer socket that circumscribes and is  
spaced from the inner plug, wherein the inner plug of  
the second modular electrical connector end comprises  
an inner insulator projecting from the body, and the  
outer socket of the second modular electrical connector  
end comprises a tubular insulator that at least partially  
circumscribes and is spaced outwardly from the inner  
plug;

a first electrical wire electrically coupled between an  
electrical contact of the inner socket of the first modular  
electrical connector end and an electrical contact of the  
inner plug of the second modular electrical connector  
end; and

a second electrical wire electrically coupled between an  
electrical contact of the outer plug of the first modular  
electrical connector end and an electrical contact of the  
outer socket of the second modular electrical connector  
end;

wherein:

the electrical contact of the inner plug comprises a con-  
ductive material on an outside surface of the inner  
insulator;



## 25

the electrical contact of the outer socket of the second modular electrical connector end comprises a conductive tab on an inside surface of the tubular insulator; and

when two cable assemblies are assembled together end-to-end, the two cable assemblies are mechanically connected along an axial dimension so as to form a modular electrical distribution system, such that the inner socket of the first modular electrical connector end of a first one of the cable assemblies electrically and mechanically connects to the inner plug of the second modular electrical connector end of a second one of the cable assemblies, and the outer plug of the first modular electrical connector end of the first one of the cable assemblies electrically and mechanically connects to the outer socket of the second modular electrical connector end of the second one of the cable assemblies.

23. A cable assembly comprising:

a first modular electrical connector end, the first modular electrical connector end having an inner socket and an outer plug that circumscribes and is spaced from the inner socket;

a second modular electrical connector end, the second modular electrical connector end having a body, an inner plug and an outer socket that circumscribes and is spaced from the inner plug, wherein the inner plug of the second modular electrical connector end comprises an inner insulator projecting from the body and the outer socket of the second modular electrical connector end comprises at least two arcuate sections that are spaced apart from each other, and together at least partially circumscribe the inner plug;

## 26

a first electrical wire electrically coupled between an electrical contact of the inner socket of the first modular electrical connector end and an electrical contact of the inner plug of the second modular electrical connector end; and

a second electrical wire electrically coupled between an electrical contact of the outer plug of the first modular electrical connector end and an electrical contact of the outer socket of the second modular electrical connector end;

wherein:

the electrical contact of the inner plug comprises a conductive material on an outside surface of the inner insulator;

the electrical contact of the outer socket of the second modular electrical connector end comprises a conductive tab, on a select one of the at least two arcuate sections; and

when two cable assemblies are assembled together end-to-end, the two cable assemblies are mechanically connected along an axial dimension so as to form a modular electrical distribution system, such that the inner socket of the first modular electrical connector end of a first one of the cable assemblies electrically and mechanically connects to the inner plug of the second modular electrical connector end of a second one of the cable assemblies, and the outer plug of the first modular electrical connector end of the first one of the cable assemblies electrically and mechanically connects to the outer socket of the second modular electrical connector end of the second one of the cable assemblies.

\* \* \* \* \*