



US010981700B2

(12) **United States Patent**
Migas et al.

(10) **Patent No.:** **US 10,981,700 B2**
(45) **Date of Patent:** ***Apr. 20, 2021**

(54) **TWIST AND FLIP LOCK CLOSURE**

(56) **References Cited**

- (71) Applicant: **Closure Systems International Inc.**,
Memphis, TN (US)
- (72) Inventors: **Jeremiah Migas**, Crawfordsville, IN
(US); **Jeremy Morin**, Zionsville, IN
(US); **Aravind Murali**, West Lafayette,
IN (US)
- (73) Assignee: **Closure Systems International Inc.**,
Indianapolis, IN (US)

- U.S. PATENT DOCUMENTS
- | | | |
|-------------|--------|---------|
| 3,904,062 A | 9/1975 | Grussen |
| 4,394,918 A | 7/1983 | Grussen |
- (Continued)

FOREIGN PATENT DOCUMENTS

- | | | |
|----|--------------|--------|
| EP | 2 308 772 A1 | 4/2011 |
| FR | 2785264 A1 | 5/2000 |
- (Continued)

- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

OTHER PUBLICATIONS

International Search Report and Written Opinion in International Application No. PCT/US2019/055744, dated Feb. 18, 2020 (14 pages).

Primary Examiner — J. Gregory Pickett
Assistant Examiner — Niki M Eloshway

(74) *Attorney, Agent, or Firm* — Nixon Peabody LLP

(21) Appl. No.: **16/863,313**

(22) Filed: **Apr. 30, 2020**

(65) **Prior Publication Data**
US 2020/0283201 A1 Sep. 10, 2020

Related U.S. Application Data

(63) Continuation of application No. 16/158,475, filed on Oct. 12, 2018, now Pat. No. 10,654,625.

(51) **Int. Cl.**
B65D 41/34 (2006.01)
B65D 1/02 (2006.01)
B65D 55/16 (2006.01)


(52) **U.S. Cl.**
CPC **B65D 41/3428** (2013.01); **B65D 1/0246**
(2013.01); **B65D 55/16** (2013.01)

(58) **Field of Classification Search**
CPC ... B65D 41/3428; B65D 1/0246; B65D 55/16
(Continued)

(57) **ABSTRACT**

A twist and flip closure includes first and second closure portions. The first closure portion includes a top wall portion, a skirt portion, and first and second frangible connections. The first frangible connection extends around the closure circumference. The second frangible connection has first and second sections. The second frangible connection is spaced from the first frangible connection. At least a portion of the second frangible connection is located further from the top wall portion than a portion of the first frangible connection. The second frangible connection defines an area adapted to form a tab. The second closure portion includes a tamper-evident band. The closure is adapted to be opened by twisting to break the frangible connections and expose the tab and then flipping the first closure portion from the second closure portion via the exposed tab. The closure is adapted to be locked when flipped.

19 Claims, 8 Drawing Sheets



US 10,981,700 B2

Page 2

(58) **Field of Classification Search**
USPC 215/44, 252, 235, 256, 258
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,805,792 A 2/1989 Lecinski
5,215,204 A 6/1993 Beck
5,246,125 A 9/1993 Julian
5,725,115 A 3/1998 Bösl
6,123,212 A 9/2000 Russell
6,474,491 B1 11/2002 Benoit-Gonin
6,481,588 B1 11/2002 Wagner
D593,856 S 6/2009 Kubler
8,469,213 B2 6/2013 Ishii
8,485,374 B2 7/2013 Gevers
8,763,830 B2 7/2014 Sadiq
9,010,555 B2 4/2015 Luzzato
9,085,385 B1 7/2015 Costanzo
9,126,726 B2 9/2015 Edie
9,643,762 B2 5/2017 Maguire
2002/0088813 A1 7/2002 Nyman
2005/0045578 A1* 3/2005 Schwarz B65D 41/3428
215/252
2006/0163188 A1 7/2006 Lagler
2008/0011704 A1 1/2008 Van Ryn
2009/0045158 A1 2/2009 Suriol
2010/0005641 A1 1/2010 Druitt
2010/0326948 A1 12/2010 Campbell

2011/0000871 A1 1/2011 Bernard
2011/0114593 A1 5/2011 Ishii
2011/0174760 A1* 7/2011 Luzzato B65D 41/48
215/252
2011/0278299 A1* 11/2011 Schueller B65D 41/3428
220/288
2012/0024815 A1 2/2012 Kwon
2012/0285921 A1* 11/2012 Kwon B65D 55/16
215/243
2012/0298666 A1 11/2012 Kwon
2012/0305564 A1* 12/2012 Hayashi B65D 41/3428
220/288
2013/0001185 A1* 1/2013 Antier B65D 41/3442
215/252
2015/0251827 A1 9/2015 Campbell
2015/0368009 A1* 12/2015 Loukov B65D 41/485
215/43
2016/0288961 A1 10/2016 Maguire
2017/0349336 A1 12/2017 Sadiq
2018/0009979 A1 1/2018 Nishiyama
2018/0155094 A1* 6/2018 Loukov B65D 41/485
2018/0162605 A1* 6/2018 Zeng B65D 41/34
2018/0170625 A1* 6/2018 Sung B65D 55/16
2019/0185233 A1* 6/2019 Wang B65D 41/34

FOREIGN PATENT DOCUMENTS

KR 20090005746 A 1/2009
KR 100942642 B1 2/2010

* cited by examiner




Fig. 1A




Fig. 1B




Fig. 1C




Fig. 1D




Fig. 2A




Fig. 2B




Fig. 2C




Fig. 3




Fig. 5




Fig. 6A




Fig. 6B

TWIST AND FLIP LOCK CLOSURE**CROSS REFERENCE TO RELATED APPLICATION**

This application is a continuation of and claims the benefit of priority of allowed U.S. patent application Ser. No. 16/158,475 filed on Oct. 12, 2018, which is incorporated by reference in its entirety.

FIELD OF THE INVENTION

The present invention relates generally to a polymeric closure for a package. More specifically, the present invention relates to a twist and flip polymeric closure that is maintained in a locked position after opening.

BACKGROUND OF THE INVENTION

Polymeric closures have been used in many applications over the years in conjunction with containers. One type of polymeric closure that has been used with containers is a tamper-evident polymeric closure. Tamper-evident closures are used to prevent or inhibit tampering by providing a visible indication to a user if the closure has been opened. This visual indication typically divides the closure into two separate components after the tamper-evident feature has been broken. The top portion of the closure is then removed from the container to gain access to the contents of the containers. One drawback of tamper-evident closures being separated into two individual components is that the top portion may not be recycled along with the remainder of the closure and container. This scenario raises potential environmental concerns with so many containers having tamper-evident features on its closures that can be separated into two individual components.

It would be desirable to provide a flip closure that has tamper-evident features that address these above-noted environmental concerns, while still performing desirable properties of a closure including securely positioning the lid when drinking from the container.

SUMMARY

According to one embodiment, a twist and flip closure comprises a first closure portion and a second closure portion. The first closure portion includes a polymeric top wall portion, a polymeric annular skirt portion depending from the polymeric top wall portion, and first and second frangible connections. The annular skirt portion includes an internal thread formation for mating engagement with an external thread formation of a container. The first frangible connection extends around the circumference of the closure. The first frangible connection has a first end and a second end. The first end and the second end are spaced apart. The second frangible connection has a first section and a second section. The first section is located a first distance from the top wall portion. The second section is located a second distance from the top wall portion. The second distance is greater than the first distance. The second frangible connection is spaced from the first frangible connection. At least a portion of the second frangible connection is located further from the top wall portion than a portion of the first frangible connection. The first and second sections of the second frangible connection define an area that is adapted to form a tab. The area adapted to form the tab is between the first and second ends of the first frangible connection in an

unopened position. The second closure portion includes a polymeric tamper-evident band depending from and being partially detachably connected to the polymeric annular skirt portion by the first frangible connection. The closure is adapted to be opened by twisting so as to break the first and second frangible connections and expose the tab, and then flipping the first closure portion from the second closure portion via the exposed tab. The closure is adapted to be locked via the tab during the flipping of the first closure portion from the second closure portion.

According to another embodiment, a twist and flip closure includes a first closure portion and a second closure portion. The first closure portion includes a polymeric top wall portion, a polymeric annular skirt portion, a first frangible connection and a second frangible connection. The polymeric annular skirt portion depends from the polymeric top wall portion. The annular skirt portion includes an internal thread formation for mating engagement with an external thread formation of a container. The first frangible connection extends around the circumference of the closure. The first frangible connection has a first end and a second end. The first end and the second end are spaced apart. The second frangible connection has a first section and a second section. The first section is located a first distance from the top wall portion. The second section is located a second distance from the top wall portion. The second distance is greater than the first distance. The second frangible connection is spaced from the first frangible connection. At least a portion of the second frangible connection is located further from the top wall portion than a portion of the first frangible connection. The first and second sections of the second frangible connection define an area that is adapted to form a tab. The area adapted to form the tab is between the first and second ends of the first frangible connection in an unopened position. An area between the first frangible connection and the second frangible connection forms hinged areas to assist in moving and locking the tab.

The second closure portion includes a polymeric tamper-evident band depending from and being partially detachably connected to the polymeric annular skirt portion by the first frangible connection. The polymeric tamper-evident including at least one band extension, the at least one band extension assisting in positioning the first closure portion in a locked position after flipping. The closure is adapted to be opened by twisting so as to break the first and second frangible connections and expose the tab and then flipping the first closure portion from the second closure portion via the exposed tab. The closure is adapted to be locked via the tab during the flipping of the first closure portion from the second closure portion.

According to a further embodiment, a package includes a container and twist and flip closure. The container has a neck portion defining an opening. The container has an external thread formation on the neck portion. The twist and flip closure is configured for fitment to the neck portion of the container for closing the opening. The twist and flip closure comprises a first closure portion and a second closure portion. The first closure portion includes a polymeric top wall portion, a polymeric annular skirt portion, a first frangible connection and a second frangible connection. The polymeric annular skirt portion depends from the polymeric top wall portion. The annular skirt portion includes an internal thread formation for mating engagement with an external thread formation of the container. The first frangible connection extends around the circumference of the closure. The first frangible connection has a first end and a second end. The first end and the second end are spaced apart. The

3

second frangible connection has a first section and a second section. The first section is located a first distance from the top wall portion. The second section is located a second distance from the top wall portion. The second distance is greater than the first distance. The second frangible connection is spaced from the first frangible connection. At least a portion of the second frangible connection is located further from the top wall portion than a portion of the first frangible connection. The first and second sections of the second frangible connection define an area that is adapted to form a tab. The area adapted to form the tab is between the first and second ends of the first frangible connection in an unopened position.

The second closure portion includes a polymeric tamper-evident band depending from and being partially detachably connected to the polymeric annular skirt portion by the first frangible connection. The closure is adapted to be opened by twisting so as to break the first and second frangible connections and expose the tab and then flipping the first closure portion from the second closure portion via the exposed tab. The closure is adapted to be locked via the tab during the flipping of the first closure portion from the second closure portion.

The above summary is not intended to represent each embodiment or every aspect of the present invention. Additional features and benefits of the present invention are apparent from the detailed description and figures set forth below.

BRIEF DESCRIPTION OF THE DRAWINGS

Other advantages of the invention will become apparent upon reading the following detailed description and upon reference to the drawings in which:

FIG. 1A is a top perspective view of a closure in an unopened position on a container according to one embodiment.

FIG. 1B is a top perspective view of the closure on the container of FIG. 1A after the closure has been partially twisted with respect to the container.

FIG. 1C is a top perspective view of the closure on the container of FIG. 1A after the closure has been fully twisted with respect to the container.

FIG. 1D is a top perspective view of the closure on the container of FIG. 1A after a lid of the container has been flipped.

FIG. 2A is a side view of the closure of FIG. 1A in an unopened position on a container according to another embodiment.

FIG. 2B is a side view of the closure on the container of FIG. 2A after the closure has been fully twisted with respect to the container.

FIG. 2C is a side view of the closure on the container of FIG. 2A after a lid of the container has been flipped.

FIG. 3 is a cross-sectional view taken of the closure and the container of FIG. 1A when the closure is in an unopened position.

FIG. 4 is a flattened schematic side view of the circumference of the closure of FIG. 1A depicting the first and second frangible connections in an unbroken position.

FIG. 5 is a bottom perspective view from the back of the closure depicted in FIG. 1A.

FIG. 6A is a cross-sectional view (without the cross-hatching) showing the lid in various positions or stages during flipping according to one embodiment.

4

FIG. 6B is an enlarged view of a generally circular area *6b* of FIG. 6A showing one position of the lid during the flipping process.

While the invention is susceptible to various modifications and alternative forms, specific embodiments thereof have been shown by way of example in the drawings and will herein be described in detail. It should be understood, however, that it is not intended to limit the invention to the particular forms disclosed, but on the contrary, the intention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the invention as defined by the appended claims.

DETAILED DESCRIPTION

FIGS. 1A-D illustrate a package **100** including a polymeric twist and flip closure **10** and a container **108** according to one embodiment of the present invention. The twist and flip closures of the present invention are configured to be placed on a container or bottle that contain product. The product is typically a liquid product, but also may be a solid product or a combination of a liquid and solid product. The polymeric twist and flip closure **10** of FIGS. 1A-D is generally cylindrically shaped. The twist and flip closure is configured to remain with the container so as to reduce environmental waste, while still providing desirable tamper-evident features. The twist and flip closure is configured to lock after opening so as to enjoy an uninhibited drinking experience.

The polymeric twist and flip closure **10** includes a first closure portion or lid **12** and a second closure portion or base **14**. The twist and flip closure **10** is a one-piece closure. The first closure portion **12** and the second closure portion **14** are adapted to be twisted and then flipped with respect to each other via a tab as will be discussed in detail below. It is contemplated that the twist and flip closure may be a two-piece closure in another embodiment.

The first closure portion **12** includes a polymeric top wall portion **22** and a polymeric annular skirt portion **32**. The second closure portion **14** includes a polymeric tamper-evident band **34**. The polymeric tamper-evident band **34** depends from and is partially detachably connected to the polymeric annular skirt portion **32** by a first frangible connection **50** (FIG. 1A).

Referring to FIG. 3, a cross-sectional view of the package **100** is shown. The first closure portion **12** further includes a polymeric continuous plug seal **24** and an outer seal **26**. As shown in FIG. 3, the polymeric continuous plug seal **24** and the outer seal **26** depend from the polymeric top wall portion **22** and provide a sealing mechanism. The continuous plug seal **24** of FIG. 3 is spaced from an interior surface **32a** of the polymeric annular skirt portion **32**. The outer seal **26** provides an outer seal with respect to an outer finish surface of the container **108**.

In another embodiment, the twist and flip closure may include other sealing mechanisms. For example, the closure may include a polymeric lining material that provides a seal to the closure. In this embodiment, the closure would be formed from separate components, but would function as the closure except with a different sealing mechanism. In another embodiment, the closure may include only a polymeric outer seal or a continuous plug seal. It is contemplated that the twist and flip closure may include other sealing mechanisms.

Referring still to FIG. 3, the polymeric annular skirt portion **32** includes an internal thread formation **40** for mating engagement with an external thread formation of a

container. The internal thread formation **40** includes a first closure lead **42** and a second closure lead **44**. The first and second closure leads **42**, **44** are referred collectively as a double lead closure thread. Each of the first and second closure leads **42**, **44** is continuous. The first positions of the first and second closure leads **42**, **44** may be located roughly 180 degrees apart from each other and, thus, begin on generally opposing sides of the closure **10**.

It is contemplated that the first and second closure leads may be discontinuous. It is also contemplated that the internal thread formation of the closure may differ from a helical thread formation. It is also contemplated that other internal thread formations may be used in the closure. For example, the internal thread formation may include a triple-threaded structure having first, second and third closure leads.

Referring back to FIGS. 1A-D, an outer surface **32b** of the polymeric annular skirt portion **32** may also include a plurality of ridges **32c** thereon. The plurality of ridges **32c** assists a user in gripping when moving the twist and flip closure **10** between closed and open positions.

The twist and flip closure **10** of FIG. 1A include the first frangible connection **50** and the second frangible connection **60**. FIG. 1A depicts the closure **10** and the container **108** in an unopened position. FIG. 1B depicts the closure **10** and the container **108** in a partially open position. FIG. 1C depicts the closure **10** and the container **108** in an open, but not flipped, position. FIG. 1D depicts the closure **10** and the container **108** in the flipped and locked position. It is noted that FIG. 1C is a top perspective view of the front, while FIGS. 1A, B and D are slightly offset as compared to the view of FIG. 1C.

Referring to FIGS. 2A-2C, the twist and flip closure **10** is shown with a container **208** from a side perspective view that forms a package **200**. The twist and flip closure **10** of FIG. 2A includes the first and second frangible connections **50** and **60**. FIG. 2A depicts the closure **10** and the container **208** in an unopened position. FIG. 2B depicts the closure **10** and the container **208** in an open, but not flipped, position. FIG. 2C depicts the closure **10** and the container **208** in the flipped and locked position.

FIG. 4 depicts the entire circumference of the closure **10** in a flatten side view in an unopened position. The first frangible connection **50** extends around the circumference of the twist and flip closure **10**. The first frangible connection generally extends from about 280 to about 330 degrees around the circumference of the twist and flip closure **10**. More specifically, the first frangible connection extends from about 300 to about 325 degrees or, more specifically, from about 310 to about 320 degrees around the circumference of the twist and flip closure **10**. The distance of the first frangible connection is shown in FIG. 4 as length **L1** plus length **L2**.

The first frangible connection **50** has a first end **50a** and a second end **50b**. The first and second ends **50a**, **50b** are spaced apart. This is shown in FIG. 4 as a gap **52**. The gap **52** is generally from about 30 to about 80 degrees and, more specifically, from about 40 to about 60 degrees around the circumference of the closure. This is shown as length **L3** in FIG. 4. The first frangible connection **50** of FIG. 4 has a distance **D1** (distance to the top wall portion) of from about 7 to about 14 mm and, more specifically, from about 8 to about 11 mm. The first frangible connection **50** of FIG. 4 has a distance **D2** (distance to the end opposite of the top wall portion) of from about 5 to about 12 mm and, more specifically, from about 6 to about 9 mm.

The second frangible connection **60** has a first section **62** and a second section **64**. As shown in FIG. 4, the second frangible connection **60** extends generally from about 120 to about 180 degrees around the circumference of the closure **10**. More specifically, the second frangible connection extends from about 130 to about 170 degrees around the circumference of the closure **10**. The distance of the second frangible connection **60** is shown in FIG. 4 as length **L4**.

As shown in FIG. 4, the first section **62** has a plurality of segments **62a**, **62b**. The segments **62a**, **62b** of the second frangible connection **60** are located a distance **D3** (distance to the top wall portion **22**) of from about 8 to about 16 mm and, more specifically, from about 9 to about 12 mm. The segments **62a**, **62b** of the second frangible connection **60** are located a distance **D4** (distance to the end opposite of the top wall portion) of from about 3 to about 8 mm and, more specifically, from about 4 to about 7 mm.

The segment **62a** of the second frangible connection **60** has a length **L5** of from about 30 to about 90 degrees and, more specifically, from about 40 to about 70 degrees. The segment **64b** of the second frangible connection **60** has a length **L6** of from about 30 to about 90 degrees and, more specifically, from about 40 to about 70 degrees.

As shown in FIG. 4, the second section **64** of the second frangible connection **60** is located a distance **D5** (distance to the top wall portion) of from about 11 to about 17 mm and, more specifically, from about 12 to about 15 mm. The distance **D5** is greater than the distance **D3**. The second section **64** of the second frangible connection **60** is located a distance **D6** (distance to the end opposite of the top wall portion) of from about 1 to about 6 mm and, more specifically, from about 2 to about 4 mm. The second section **64** of the second frangible connection **60** has a distance **D8** of from about 1 to about 4 mm and, more specifically, from about 2 to about 3 mm. The second section **64** of the second frangible connection has a length **L7** of from about 30 to about 80 degrees and, more specifically, from about 40 to 60 degrees.

The second frangible connection **60** has a configuration that includes the first section **62** and the second section **64**. The first section **62** has two segments **62a**, **62b** and the second section **64** has three segments **64a-c**. The first section **62** and the second section **64** are connected as shown in FIG. 4. The two segments **62a**, **62b** are generally horizontal. The segments **64a**, **64c** are generally vertical, while the segment **64b** is generally horizontal. The segments **64a-c** are connected with each other and form an area **66**. The segments **64a-c** form a general U-shape.

It is contemplated that the second section of the second frangible connection may be of shapes other than U-shaped. For example, the second section of the second frangible connection may be an elongated oval section or a W-shape.

The second frangible connection **60** is spaced from the first frangible connection **50**. This is shown in FIG. 4 as distance **D7**. At least a portion of the second frangible connection is located further from the top wall portion than a portion of the first frangible connection. In FIG. 4, the entire second frangible connection **60** is located further from the top wall portion **22** than the first frangible connection **50**. It is contemplated that the second frangible connection may be formed differently than depicted in FIG. 4.

The first and second frangible connections **50**, **60** may be formed by molded-in-bridges in one embodiment. In this embodiment, the molded-in-bridges are formed using a feature in the mold. The first and second frangible connections are in the form of scoring or scored lines, notches, leaders, nicks or other lines of weaknesses.

In another method, the first and second frangible connections are formed by a slitting technology that is independent from the formation of the remainder of the twist and flip closure. The first and second frangible connections are formed using scoring or scored lines, notches, leaders, nicks or other lines of weaknesses.

The area **66** is formed between the first section **62** and the second section **64** of the second frangible connection **60** as shown in FIG. 4. The area **66** is adapted to form a tab **70** after the closure has been fully twisted (i.e., fully unthreaded) as shown, for example, in FIG. 1C. The tab **70** is located between the first and second ends **50a**, **50b** as shown in FIG. 4. The area that forms a tab is generally aligned with a gap formed between first and second ends of a first frangible connection. In FIG. 4, the area **66** is substantially aligned with the gap **52** formed between the first and second ends **50a**, **50b** of the first frangible connection **50**. It is contemplated that the area to form the tab should be located in such a manner that the tab acts as a hinge when the closure is flipped and then acts as a lock when the closure has been flipped.

As will be discussed below in more detail, areas **68a**, **68b** are formed between the first frangible connection **50** and the second frangible connection **60** as shown in FIG. 4. The areas **68a**, **68b** form hinged arms **72a**, **72b** after the first and second frangible connections are broken. The hinged arms **72a**, **72b** (see, e.g., FIG. 1C) assist in: (1) keeping the first closure portion **12** and the second closure portion **14** together; (2) flipping the first closure portion **12** with respect to the second closure portion **14** in conjunction with the tab **70**; and (3) locking the first closure portion **12** with the tab **70**. The hinged arms **72a**, **72b** are sized and shaped to be twisted and stretched.

The stretching of the hinged arms **72a**, **72b** is shown, for example, in FIG. 1C by a gap **76** created from the movement of the tab **70**. The gap **76** of FIG. 1C is larger than a gap **78** shown in FIG. 1B. The growth of this gap assists in providing a spatial relationship for providing clearance to flip the first closure portion **12** with respect to the second closure portion **14**. The spatial relationship for clearance of the first closure portion **12** with respect to the second closure portion **14** is also dependent on other features such as the length of the annular skirt portion **34**, the positioning and type of internal and external threads, and the size and shape of the tab **70**.

Referring specifically to FIG. 1A, the polymeric tamper-evident band **34** of the closure **10** is located at the bottom thereof (i.e., an end opposite of the polymeric top wall portion **22**). The tamper-evident band **34** depends from and is at least partially detachably connected to the annular skirt portion **32** by the first frangible connection **50**. As viewed in FIG. 1A, the polymeric tamper-evident band **34** is a lower tamper-evident feature. The tamper-evident band **34** works in conjunction with the container to indicate to a user that the contents of the container may have been accessed. More specifically, the tamper-evident band **34** is designed to partially separate from the annular skirt portion **32** when a user opens the package by twisting the first closure portion **12** with respect to the second closure portion **14**. This twisting unthreads the closure **10** with respect to the container **108**.

In one embodiment, the tamper-evident band includes at least one band extension. For example, the closure **10** is shown in FIG. 5 depicts the tamper-evident band **34** including a plurality of band extensions **36a-c**. As will be discussed in more detail below, the plurality of band extensions

36a-c assists in positioning the first closure portion or lid **12** in a locked position after the flipping process.

One non-limiting example of a twist and flip closure and a container forming a package is shown and previously discussed in conjunction with FIGS. 1A-1D. FIGS. 1A-1D depict the closure **10** and the container **108** forming the package **100**. A portion of the container **108** is shown in FIGS. 1A-D and includes a neck portion **102** (FIG. 1D) that defines an opening. Referring to FIG. 1D, the neck portion **102** of the container **108** includes an external thread formation **104**, an A-collar **106** (FIG. 1C) and a continuous outer ring **110**.

The external thread formation **104** includes a first finish lead **142** and a second finish lead **144**. The external thread formation **104** (finish leads **142**, **144**) engages with the corresponding internal thread formation **40** (closure leads **42**, **44**) (FIG. 3) to seal the package **100**. The first finish lead **142**, **144** may extend in a helical fashion such as shown in FIG. 1D. Each of the first and second finish leads **142**, **144** is discontinuous.

In another embodiment, the first positions of the first and second finish leads are located roughly 180 degrees apart from each other and, thus, begin on opposing sides of the neck portion of the container. When opening the container, a first closure lead is desirably in contact with the first finish lead and the second closure lead is desirably in contact with the second finish lead. It is contemplated that the external thread formation of the container may have discontinuous leads.

It is contemplated that the external thread formation of the container may be different than depicted in FIG. 1D. Another non-limiting example is depicted in FIG. 2C with the container **208** having a continuous helical external thread formation **204**.

The A-collar **106** (FIG. 1C) prevents or inhibits a tamper-evident band **34** from being removed after the first and second frangible connections **50**, **60** are broken. The continuous outer ring **110** assists in positioning the tamper-evident band **34**.

The closures of the present invention may include an oxygen-scavenger material. This oxygen-scavenger material may be distributed within the closure or may be a separate layer. The oxygen-scavenger material may be any material that assists in removing oxygen within the container, while having little or no effect on the contents within the container.

Alternatively, or in addition to, the closures may include an oxygen-barrier material. The oxygen-barrier material may be added as a separate layer or may be integrated within the closure itself. The oxygen-barrier materials assist in preventing or inhibiting oxygen from entering the container through the closure. These materials may include, but are not limited to, ethylene vinyl alcohol (EVOH). It is contemplated that other oxygen-barrier materials may be used in the closure.

Additionally, it is contemplated that other features may be included in the closure described above. For example, U.S. Publication No. 2018/009979, U.S. Publication No. 2017/0349336, U.S. Pat. Nos. 9,126,726, 9,085,385, 8,763,830, 8,485,374, U.S. Publication No. 2009/0045158 and U.S. Pat. No. 6,123,212 all include features that could be incorporated in the closures of the present invention. All of these references are hereby incorporated by reference in their entireties.

The top wall portion **22** and the annular skirt portion **32** are made of polymeric material. The top wall portion **22** and the annular skirt portion **32** are typically made of an olefin (e.g., polyethylene (PE), polypropylene (PP)), polyethylene

terephthalate (PET) or blends thereof. One example of a polyethylene that may be used in high density polyethylene (HDPE). It is contemplated that the top wall portion and the annular skirt portion may be made of other polymeric materials. The tamper-evident band **34** is typically made of the same materials as the top wall portion **22** and the annular skirt portion **32**.

The closures are typically formed by processes such as injection or compression molding, extrusion or the combination thereof.

The container **108** is typically made of polymeric material. One non-limiting example of a material to be used in forming a polymeric container is polyethylene terephthalate (PET), polypropylene (PP) or blends using the same. It is contemplated that the container may be formed of other polymeric or copolymer materials. It is also contemplated that the container may be formed of glass. The container **108** typically has an encapsulated oxygen-barrier layer or oxygen barrier material incorporated therein.

In one method to open the container **108** and gain access to the product therein, the first closure portion **12** is initially twisted and then flipped with respect to the second closure portion **14**. Referring initially to FIGS. **1A-1D** and FIGS. **2A-2C**, methods of opening the twist and flip closure are shown. FIGS. **1A** and **2A** depict the first and second frangible connections **50**, **60** in an unopened position after the closure **10** has been applied onto the container **108**. A user then twists the closure **10** generally along the first and second frangible connections **50**, **60**, which begins breaking the first and second frangible connections **50**, **60**. The user will continue twisting the closure until there are no more thread engagements between the closure and the container and the first and second frangible connections have been fully broken. FIGS. **1C** and **2B** depict the closure **10** and respective containers **108**, **208** after the twisting has been completed (i.e., unthreaded completely).

After the twisting has been completed, then a user flips the first closure portion **12** with respect to the second closure portion **14**. The first closure portion **12** and the second closure portion **14** are flipped using the tab **70**, which acts as a hinge after the first and second frangible connections **50**, **60** have been fully broken. The tab **70** is shown in FIGS. **1C**, **1D** and **2C**. The hinged arms **72a**, **72b** during the flipping process are twisted and stretched as the tab **70** is moved.

The movement of the first closure portion or lid during the flipping process is best shown in FIGS. **6A** and **6B**. FIG. **6A** shows a side cross-sectional view (without cross-hatching) of the closure **10** and the container **108** in various positions or stages during the flipping process. The initial position of the first closure portion or lid **12** is designated as **12a** in FIG. **6A**. After a user begins flipping the lid **12** back in the general direction of arrow **A**, the lid moves to a second position (designated as **12b**), a third position (designated as **12c**), to a fourth position (designated as **12d**) and to a fifth position (designated as **12e**).

The first closure portion or lid **12** is adapted to flip or rotate at least about 115 degrees from a closed position to an open position generally along the arrow **A** of FIG. **6**. It is desirable for the first closure portion or lid **12** to flip or rotate at least about 125 degrees or even more desirably at least 135 degrees from a closed position to an open position until being locked.

FIG. **6B** shows an enlarged view of area **6b** taken from FIG. **6A**. FIG. **6B** depicts a portion of the first closure portion or lid **12** in the third position **12c** and shows the functionality of the band extension **36b** with respect to the A-collar **106** of the container **108**. The tamper-evident

feature **34** engages the A-collar **106** to prevent or inhibit the tamper-evident band **34** from being removed after the first and second frangible connections **50**, **60** are broken.

As shown in FIG. **6B**, the band extension **36b** prevents or inhibits the tab **70** from slipping under the A-collar **106** of the container **108** during movement from the third position (designated as **12c**) to the fourth position (designated as **12d**) of FIG. **6A**. More specifically, during the flipping of the first closure portion **12** during the product opening, the band extension **36b** provides a transition lip over the A-collar **106** of the container **108** preventing or inhibiting the tab **70** from slipping under the A-collar **106** and becoming stuck, which prevents or inhibits full rotation of the first closure portion **12**. The forces in rotation along arrow **B** (see FIG. **6B**) allows the tab **70** to slip over the A-collar **106** across the band extension **36b**.

As the tab **70** is rotated during the movement of the first closure portion **12**, the hinged arms **72a**, **72b** are twisted and stretched. The tab **70** contacts an outer surface of the neck portion **102**. In one method, the tab **70** is generally perpendicular to the outer surface of the neck portion **102**, which causes the hinged arms **72a**, **72b** to be greatly stretched. The force required to move the tab to this position is greater than during initial movement of the tab during the flipping process. As the first closure portion **12** is continued to be flipped, an edge **70a** of the tab **70** continues moving upwardly (toward the top of the neck portion **102**) to a position shown in, for example, FIG. **1D**. The tab **70** is sized, and formed to be resilient, but capable of flexing during this movement. At this point, the hinged arms **72a**, **72b** are not as stretched and are in stable positions.

After the first closure portion **12** has been flipped, the tab **70** in conjunction with the hinged arms **72a**, **72b** lock the first closure portion **12** with respect to the second closure portion **14** as shown in FIGS. **1D** and **2C**. The hinged arms **72a**, **72b** are stable and maintain the tab in a locked position. To overcome this stable position and return the tab **70** back to the generally perpendicular position with respect to the neck portion **102**, the first closure portion **12** would need some force applied to cause the hinged arms **72a**, **72b** to be returned to this greatly stretched position. The closure **10** is adapted to be returned to its initial position by flipping back the first closure portion **12** and then threaded the closure **10** onto the container **108**.

The polymeric closures of the present invention are desirable in both low-temperature and high-temperature applications. The polymeric closures may be used in low-temperature applications such as an ambient or a cold fill. These applications include water, sports drinks, aseptic applications such as dairy products, and pressurized products such as carbonated soft drinks. It is contemplated that other low-temperature applications may be used with the polymeric closures formed by the processes of the present invention.

The polymeric closures of the present invention may be exposed to high-temperature applications such as hot-fill, pasteurization, and retort applications. A hot fill application is generally performed at temperatures around 185° F., while a hot-fill with pasteurization is generally performed at temperatures around 205° F. Retort applications are typically done at temperatures greater than 250° F. It is contemplated that the polymeric closures of the present invention can be used in other high-temperature applications.

While the foregoing written description of the invention enables one of ordinary skill to make and use what is considered presently to be the best mode thereof, those of ordinary skill will understand and appreciate the existence of

11

variations, combinations, and equivalents of the specific embodiment, method, and examples herein. The invention should therefore not be limited by the above described embodiment, method, and examples, but by all embodiments and methods within the scope and spirit of the invention.

What is claimed is:

1. A package comprising:
 - a container having a neck portion defining an opening, the container having an external thread formation on the neck portion; and
 - a closure being configured for fitment to the neck portion of the container for closing the opening, the closure comprising:
 - a first closure portion including:
 - a polymeric top wall portion, and
 - a polymeric annular skirt portion depending from the polymeric top wall portion, the annular skirt portion including an internal thread formation for mating engagement with an external thread formation of a container;
 - a second closure portion including:
 - a first frangible connection extending around the circumference of the closure from about 280 degrees to about 330 degrees, the first frangible connection having a first end and a second end defining a gap therebetween, the gap extending from about 30 degrees to 80 degrees around the circumference of the closure, the first frangible connection spaced from about 7 mm to about 14 mm from the top wall portion and spaced from about 5 mm to 12 mm from an end opposite the top wall portion;
 - a second frangible connection extending around the circumference of the closure from about 120 degrees to about 180 degrees, the second frangible connection spaced from about 8 mm to about 16 mm from the top wall portion, the second frangible connection spaced further from the top wall portion than the first frangible connection;
 - wherein a portion of the second frangible connection acts as a hinge when the first closure portion is flipped and then acts as a lock when the first closure portion has been flipped;
 - wherein areas formed between the first frangible connection and the second frangible connection form hinged arms after the first and second frangible connections are broken.
2. The package of claim 1, wherein the hinged arms keep the first closure portion and the second closure portion together.
3. The package of claim 2, wherein the hinged arms assist in flipping the first closure portion with respect to the second closure portion.
4. The package of claim 2, wherein the hinged arms are sized and shaped to be twisted and stretched.
5. The package of claim 1, wherein the second frangible connection further comprises a first additional frangible portion and a second additional frangible portion, the area between the first and second additional frangible portions defining a tab.
6. The package of claim 1, wherein the first frangible connection is spaced from about 8 mm to about 11 mm from the top wall portion.
7. The package of claim 1, wherein the first frangible connection is spaced from about 6 mm to about 9 mm from an end opposite the top wall portion.

12

8. The package of claim 1, wherein the second frangible connection is spaced from about 9 mm to about 12 mm from the top wall portion.

9. The package of claim 1, wherein the second frangible connection extends around the circumference of the closure from about 130 to about 170 degrees.

10. The package of claim 1, wherein the first frangible connection extends around the circumference of the closure from about 300 degrees to about 325 degrees.

11. A package comprising:
 - a container having a neck portion defining an opening, the container having an external thread formation on the neck portion; and
 - a closure being configured for fitment to the neck portion of the container for closing the opening, the closure comprising:
 - a first closure portion including:
 - a polymeric top wall portion, and
 - a polymeric annular skirt portion depending from the polymeric top wall portion, the annular skirt portion including an internal thread formation for mating engagement with an external thread formation of a container;
 - a second closure portion including:
 - a first frangible connection extending around the circumference of the closure from about 280 degrees to about 330 degrees, the first frangible connection having a first end and a second end defining a gap therebetween, the gap extending from about 30 degrees to 80 degrees around the circumference of the closure, the first frangible connection spaced from about 7 mm to about 14 mm from the top wall portion and spaced from about 5 mm to 12 mm from an end opposite the top wall portion;
 - a second frangible connection extending around the circumference of the closure from about 120 degrees to about 180 degrees, the second frangible connection spaced from about 8 mm to about 16 mm from the top wall portion, the second frangible connection spaced further from the top wall portion than the first frangible connection;
 - wherein areas formed between the first frangible connection and the second frangible connection form hinged arms after the first and second frangible connections are broken,
 - wherein the closure is configured to lock after being moved to an open position.
12. The package of claim 11, wherein the hinged arms keep the first closure portion and the second closure portion together.
13. The package of claim 12, wherein the hinged arms are sized and shaped to be twisted and stretched.
14. The package of claim 11, wherein the second frangible connection further comprises a first additional frangible portion and a second additional frangible portion, the area between the first and second additional frangible portions defining a tab.
15. The package of claim 11, wherein the first frangible connection is spaced from about 8 mm to about 11 mm from the top wall portion.
16. The package of claim 11, wherein the first frangible connection is spaced from about 6 mm to about 9 mm from an end opposite the top wall portion.
17. The package of claim 11, wherein the second frangible connection is spaced from about 9 mm to about 12 mm from the top wall portion.

18. The package of claim 11, wherein the second frangible connection extends around the circumference of the closure from about 130 to about 170 degrees.

19. The package of claim 11, wherein the first frangible connection extends around the circumference of the closure 5 from about 300 degrees to about 325 degrees.

* * * * *