



US010994177B2

(12) **United States Patent**
Solheim et al.

(10) **Patent No.:** **US 10,994,177 B2**
(45) **Date of Patent:** **May 4, 2021**

(54) **GOLF CLUB HEADS WITH APERTURES AND METHODS TO MANUFACTURE GOLF CLUB HEADS**

(71) Applicant: **KARSTEN MANUFACTURING CORPORATION**, Phoenix, AZ (US)

(72) Inventors: **John A. Solheim**, Phoenix, AZ (US);
Eric J. Morales, Phoenix, AZ (US);
Erik M. Henrikson, Phoenix, AZ (US);
Eric V. Cole, Phoenix, AZ (US); **Paul D. Wood**, Phoenix, AZ (US); **Bradley D. Schweigert**, Phoenix, AZ (US);
Marty R. Jertson, Phoenix, AZ (US);
Tyler A. Shaw, Phoenix, AZ (US)

(73) Assignee: **Karsten Manufacturing Corporation**, Phoenix, AZ (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/808,229**

(22) Filed: **Mar. 3, 2020**

(65) **Prior Publication Data**

US 2020/0197765 A1 Jun. 25, 2020

Related U.S. Application Data

(63) Continuation of application No. 16/230,931, filed on Dec. 21, 2018, now Pat. No. 10,576,336, which is a continuation of application No. 15/490,161, filed on Apr. 18, 2017, now Pat. No. 10,195,498, which is a continuation of application No. 14/815,275, filed on Jul. 31, 2015, now Pat. No. 10,238,927, which is a continuation of application No. 14/312,087, filed on Jun. 23, 2014, now Pat. No. 9,776,052, which is a continuation of application No. 14/064,528, filed on Oct. 28, 2013, now Pat. No. 8,790,196, which is a

(Continued)

(51) **Int. Cl.**
A63B 53/04 (2015.01)
A63B 60/00 (2015.01)
A63B 53/08 (2015.01)
A63B 60/52 (2015.01)

(52) **U.S. Cl.**
CPC *A63B 53/0466* (2013.01); *A63B 53/08* (2013.01); *A63B 60/00* (2015.10); *A63B 60/52* (2015.10); *A63B 53/045* (2020.08); *A63B 53/0408* (2020.08); *A63B 53/0433* (2020.08); *A63B 53/0437* (2020.08); *A63B 2209/00* (2013.01); *A63B 2209/023* (2013.01); *Y10T 29/4998* (2015.01); *Y10T 29/49826* (2015.01)

(58) **Field of Classification Search**
CPC *A63B 53/0437*; *A63B 53/0433*
USPC 473/324–350
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,695,618 A 10/1972 Woolley et al.
3,997,170 A 12/1976 Goldberg
4,065,133 A 12/1977 Gordos

(Continued)

FOREIGN PATENT DOCUMENTS

GB 2417909 9/2005
GB 2450764 1/2009


(Continued)

Primary Examiner — Alvin A Hunter

(57) **ABSTRACT**

Embodiments of golf club heads with apertures and methods to manufacture golf club heads are generally described herein. Other embodiments may be described and claimed.

15 Claims, 25 Drawing Sheets



Related U.S. Application Data

continuation-in-part of application No. 13/342,847, filed on Jan. 3, 2012, now Pat. No. 8,777,778.

- (60) Provisional application No. 61/774,224, filed on Mar. 7, 2013, provisional application No. 61/429,692, filed on Jan. 4, 2011.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,754,974	A	7/1988	Kobayashi
5,518,243	A	5/1996	Redman
5,700,208	A	12/1997	Nelms
5,718,641	A	2/1998	Lin
5,772,529	A	6/1998	Ruth, Jr.
5,797,807	A	8/1998	Moore
5,800,285	A	9/1998	Thorne
5,921,872	A	7/1999	Kobayashi
5,997,415	A	12/1999	Wood
6,001,029	A	12/1999	Kobayashi
6,027,414	A	2/2000	Koebler
6,089,070	A	7/2000	Hancock
6,354,963	B1	3/2002	Kodama et al.
6,381,828	B1	5/2002	Boyce
6,623,378	B2	9/2003	Beach et al.
6,776,725	B1	8/2004	Miura
6,783,465	B2	8/2004	Matsunaga
6,896,006	B2	5/2005	Lindsay
6,932,716	B2	8/2005	Ehlers
6,945,876	B2	9/2005	Nakahara et al.
6,955,612	B2	10/2005	Lu
7,025,692	B2	4/2006	Erickson et al.
7,074,136	B2	7/2006	Noguchi et al.
7,108,614	B2	9/2006	Lo
7,147,575	B2	12/2006	Galloway et al.
7,166,041	B2	1/2007	Evans
7,250,007	B2	7/2007	Lu
7,258,624	B2	8/2007	Kobayashi
7,303,487	B2	12/2007	Kumamoto
7,338,390	B2	3/2008	Lindsay
7,445,564	B2	11/2008	Kusumoto
7,448,961	B2	11/2008	Lin
7,510,485	B2	3/2009	Yamamoto
7,510,486	B2	3/2009	Werner
7,641,568	B2	1/2010	Hoffman
7,699,719	B2	4/2010	Sugimoto
7,892,111	B2	2/2011	Morales et al.
8,172,697	B2	5/2012	Cackett

8,540,590	B2	9/2013	Tsukada et al.
8,556,742	B2	10/2013	John
8,608,587	B2	12/2013	Henrikson
8,632,419	B2	1/2014	Tang
8,678,946	B2	3/2014	Boyd
8,721,471	B2	5/2014	Albertsen
8,777,778	B2	7/2014	Solheim
8,790,196	B2	7/2014	Solheim
9,138,619	B2	9/2015	Takechi
9,174,100	B2	11/2015	Takechi
9,694,254	B2	7/2017	Ashino
10,343,030	B2 *	7/2019	Funaki A63B 60/52
10,350,464	B2 *	7/2019	Myrhum A63B 60/52
10,434,380	B2 *	10/2019	Kawaguchi A63B 53/0466
10,569,143	B2 *	2/2020	Funaki A63B 53/0466
2002/0019265	A1	2/2002	Allen
2004/0192468	A1	9/2004	Onoda
2004/0266551	A1 *	12/2004	Noguchi A63B 53/0466 473/345
2005/0096154	A1	5/2005	Chen
2005/0143189	A1	6/2005	Lai
2005/0278931	A1 *	12/2005	Deshmukh A63B 53/0466 29/469
2006/0052177	A1 *	3/2006	Nakahara A63B 53/0466 473/329
2006/0052181	A1	3/2006	Serrano et al.
2007/0032313	A1	2/2007	Serrano et al.
2007/0155533	A1	7/2007	Solheim et al.
2008/0070721	A1	3/2008	Chen
2008/0113825	A1	5/2008	Funayama

FOREIGN PATENT DOCUMENTS

JP	3028211	8/1996
JP	1119253	7/1997
JP	2000005353	1/2000
JP	2002272883	9/2002
JP	2003111874	4/2003
JP	2004159794	6/2004
JP	2004305724	11/2004
JP	2005230472	9/2005
JP	2005323686	11/2005
JP	2005329154	12/2005
JP	2006020860	1/2006
JP	2006230953	9/2006
JP	2007325859	12/2007
JP	2008035963	2/2008
JP	2009011839	1/2009
JP	2009022571	2/2009

* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig. 6




Fig. 7




Fig. 8










Fig. 9






Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16




Fig. 17




Fig. 18

Fig. 19




Fig. 20




Fig. 21





Fig. 22





Fig. 23







Fig. 27






Fig. 28

Fig. 29






Fig. 30




Fig. 31




Fig. 32




Fig. 33




Fig. 34





Fig. 35

Fig. 36






Fig. 37




Fig. 38




Fig. 39






Fig. 40






Fig. 43

MOLDING A COVER WITH A GOLF CLUB HEAD TO FORM A MOLDED COVER 5000

ATTACHING THE MOLDED COVER TO THE GOLF CLUB HEAD 5002

Fig. 44

MOLDING A COVER WITH A MOLD 6000

ATTACHING THE MOLDED COVER TO A GOLF CLUB HEAD 6002

Fig. 48




Fig. 45




Fig. 46







Fig. 47






Fig. 52

**GOLF CLUB HEADS WITH APERTURES
AND METHODS TO MANUFACTURE GOLF
CLUB HEADS**

RELATED APPLICATIONS

This is a continuation of U.S. patent application Ser. No. 16/230,931, now U.S. Pat. No. 10,576,336, filed Dec. 21, 2018, which is a continuation of U.S. patent application Ser. No. 15/490,161, now U.S. Pat. No. 10,195,498, filed Apr. 18, 2017, which is a continuation of U.S. patent application Ser. No. 14/815,275, now U.S. Pat. No. 100,238,927, filed Jul. 31, 2015, which is a continuation of U.S. patent application Ser. No. 14/312,087, now U.S. Pat. No. 9,776,052, filed Jun. 23, 2014, which is a continuation of U.S. patent application Ser. No. 14/064,528, now U.S. Pat. No. 8,790,196, filed Oct. 28, 2013, which claims the benefit of U.S. Provisional Patent Application Ser. No. 61/774,224, filed on Mar. 7, 2013, and is a continuation-in-part of U.S. patent application Ser. No. 13/342,847, now U.S. Pat. No. 8,777,778, filed Jan. 3, 2012, which claims the benefit of U.S. Provisional Patent Application Ser. No. 61/429,692, filed on Jan. 4, 2011. All of the above applications are incorporated by reference herein.

FIELD

The present application generally relates to golf clubs, and more particularly, to golf club heads with apertures and methods to manufacture golf club heads.

BACKGROUND

A golf club head, and in particular the crown of the golf club head, may be divided into several regions for purposes of illustrating the effects of forces generated by the impact of a golf ball against the face of the golf club head. The first region is in communication with the impact surface defined by the face of the golf club head such that the impact of a golf ball at the face directly causes internal stresses to be generated by the impact force of the golf ball that travels through and directly affects the first region of the crown. In addition, a second region of the golf club head may be defined along the crown between the first region and the back of the golf club head such that relatively lower stress and vibration should be felt in the second region by the forces generated after the impact of a golf ball against the face in comparison to the first region of the golf club head.

Many golf club heads are formed with a number of relatively large apertures defined along the second region of the crown in order to lessen the weight of the golf club head and/or change its center of gravity. However, this arrangement of large apertures can cause a disproportionate or uneven distribution of internal stresses through the second region of the crown when a golf ball strikes the face of the golf club head. In particular, stress risers, which are pockets of concentrated stress, can develop in the material of the crown between the apertures. Stress risers are caused when internal stresses generated by the impact force of a golf ball are distributed unevenly through the second region of the crown and focused on particular portions of the golf club head. This disproportional distribution of internal stresses through the second region of the crown can cause the structural failure of the golf club head over time as the area between the apertures crack or otherwise fail because of the excessive internal stresses being generated in the second

region of the crown due to the bending forces being focused on a particular area of the crown after repeated impacts with a golf ball.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective front view of one embodiment of a golf club head illustrating a plurality of apertures.

FIG. 2 is a perspective rear view of the golf club head of FIG. 1.

FIG. 3 is a perspective side view of the golf club head of FIG. 1.

FIG. 4 is a top view of the golf club head of FIG. 1 illustrating the arrangement of the plurality of apertures along the crown of the golf club head.

FIG. 5 is a bottom view of the golf club head of FIG. 1.

FIG. 6 is a cross-sectional view of the golf club head of FIG. 1.

FIG. 7 is an enlarged view of FIG. 6 illustrating the plurality of apertures defined within a recess of the golf club head.

FIG. 8 is a simplified illustration of the golf club head of FIG. 1 showing a first plane and the parallel association of the first plane with a loft plane defined by a face of the golf club head for illustrating the division between a first region and a second region of the golf club head.

FIG. 9 is a top view of the golf club head of FIG. 1 showing the division of the golf club head into the first region and the second region by a bell-shaped curve established by the first plane.

FIG. 10 is a schematic diagram of four apertures of the plurality of apertures of the golf club head of FIG. 1.

FIGS. 11A-E are schematic diagrams of a plurality of apertures according to various embodiments.

FIG. 12 is a flow chart illustrating a method of manufacturing the golf club head of FIG. 1.

FIG. 13 is a top view of a portion of a crown of a golf club head according to another embodiment illustrating the arrangement of the plurality of apertures along the crown of the golf club head.

FIG. 14 is a bottom view of the golf club head of FIG. 13.

FIG. 15 is a simplified illustration of the golf club head of FIG. 13 showing a first plane and the parallel association of the first plane with a loft plane defined by a face of the golf club head for illustrating the division between a first region and a second region of the golf club head.

FIG. 16 is a top view of the golf club head of FIG. 13 showing the division of the golf club head into the first region and the second region by a bell-shaped curve established by the first plane.

FIG. 17 is a flow chart illustrating a method of manufacturing the golf club head of FIG. 13.

FIG. 18 is a top view of a golf club head according to another embodiment illustrating the arrangement of the plurality of apertures along the crown of the golf club head.

FIG. 19 is a bottom view of the golf club head of FIG. 18.

FIG. 20 is a simplified illustration of the golf club head of FIG. 18 showing a first plane and the parallel association of the first plane with a loft plane defined by a face of the golf club head for illustrating the division between a first region and a second region of the golf club head.

FIG. 21 is a top view of the golf club head of FIG. 18 showing the division of the golf club head into the first region and the second region by a bell-shaped curve established by the first plane.

FIG. 22 is a schematic diagram of several apertures of the plurality of apertures of the golf club head of FIG. 18.

FIG. 23 is a flow chart illustrating a method of manufacturing the golf club head of FIG. 18.

FIG. 24 is a top view of a golf club head according to another embodiment illustrating the arrangement of the plurality of apertures along the crown of the golf club head.

FIG. 25 is a bottom view of the golf club head of FIG. 24.

FIG. 26 is a simplified illustration of the golf club head of FIG. 24 showing a first plane and the parallel association of the first plane with a loft plane defined by a face of the golf club head for illustrating the division between a first region and a second region of the golf club head.

FIG. 27 is a top view of the golf club head of FIG. 24 showing the division of the golf club head into the first region and the second region by a bell-shaped curve established by the first plane.

FIG. 28 is a flow chart illustrating a method of manufacturing the golf club head of FIG. 24.

FIG. 29 is a graph illustrating stress profiles of golf club heads according to several embodiments.

FIGS. 30-35 are several embodiments of golf club heads used for the stress profiles illustrated in FIG. 29.

FIG. 36 is another graph illustrating stress profiles of golf club heads according to several embodiments.

FIG. 37 shows a golf club head according to one embodiment.

FIGS. 38-40 show a golf club head according to one embodiment.

FIGS. 41-43 show a golf club head according to one embodiment.

FIG. 44 shows a flow chart illustrating a method of manufacturing a cover for a golf club head according to one embodiment.

FIG. 45 shows an exemplary composite fabric cover for manufacturing a cover for a golf club head according to one embodiment.

FIG. 46 shows an exemplary golf club head used as a mold for manufacturing a cover for a golf club according to one embodiment.

FIG. 47 shows a composite cover manufactured from the composite fabric cover of FIG. 45 molded with the golf club head of FIG. 46.

FIG. 48 shows a flow chart illustrating a method of manufacturing a cover for a golf club head according to one embodiment.

FIG. 49 shows an exemplary composite fabric cover for manufacturing a cover for a golf club head according to one embodiment.

FIG. 50 shows an exemplary mold used as a mold for manufacturing a cover for a golf club according to one embodiment.

FIG. 51 shows a composite cover manufactured from the composite fabric cover of FIG. 49 molded with the mold of FIG. 46.

FIG. 52 is a side cross-sectional view of a golf club head according to one embodiment.

Corresponding reference characters indicate corresponding elements among the view of the drawings. The headings used in the figures should not be interpreted to limit the scope of the claims.

DETAILED DESCRIPTION

A golf club head may be divided into several regions for purposes of illustrating the effects of forces generated by the impact of a golf ball against face of the golf club head. As noted above, the first region is in communication with the impact surface defined by the face of the golf club head such

that the impact of a golf ball at the face directly causes internal stresses generated by the force of the impact with the golf ball to travel through and directly affect the first region of the golf club head. A second region of the golf club head may be defined between the first region and the back of the golf club head such that a relatively lower stress and vibration are experienced in the second region by the forces generated after the impact of a golf ball against the face in comparison to the first region.

Referring to the drawings, an embodiment of a golf club head is illustrated and generally indicated as 100 in FIG. 1. In general, the golf club head 100 may include a face 102, a sole 105, a heel 106, a toe 110, and a plurality of grooves 115. The golf club head 100 may be a single piece or include multiple portions manufactured together. In one example, the golf club head 100 may be a hollow body formed by a casting process or other suitable type of manufacturing process. In addition, the face 102 may be an integral part of the golf club head 100. Alternatively, the face 102 may be a separate piece from or an insert for a body of the golf club head 100.

The golf club head 100 includes a hosel 108 that defines an aperture 113 configured to engage a shaft (not shown). In particular, the shaft may engage the golf club head 100 on one end and engage a grip (not shown) on an opposite end. For example, the golf club head 100 may be a wood-type golf club, such as a driver-type golf club head, a fairway wood-type golf club head (e.g., 2-wood golf club, 3-wood golf club, 4-wood golf club, 5-wood golf club, 6-wood golf club, 7-wood golf club, 8-wood golf club, or a 9-wood golf club), a hybrid-type golf club head or any other suitable type of golf club head with a hollow body or a body with one or more cavities, apertures, recesses or channels. Although the above examples may depict and/or describe a wood-type golf club head (e.g., driver-type golf club head, a fairway-type golf club head, a hybrid-type golf club head), the apparatus, articles of manufacture, and methods described herein may be applicable to other suitable types of golf club heads.

In addition, the face 102 may be formed adjacent the hosel 108 and provides a surface for striking a golf ball (not shown). The face 102 may be made from one or more metals or metal alloys such as a steel material, a titanium material, a titanium alloy material, a titanium-based material, a combination thereof, one or more composite materials, one or more plastic materials, or other suitable type of materials; however, the face 102 may be made from the same material(s) that constitute the golf club head 100 as described in greater detail below. In particular, the face 102 may include a plurality of grooves, generally shown as 115 in FIG. 1. The golf club head 100 further includes a back 111 formed opposite the face 102 with the sole 105 being defined between the back 111 and the face 102. As further shown, a crown 109 is formed opposite the sole 105, while the face 102 is defined by the heel 106 formed adjacent the hosel 108 and the toe 110 defined at the far end of the face 102. The face 102 further includes a top edge 104 defined between the crown 109 and the face 102 as well as a leading edge 103 defined between the sole 105 and the face 102. In one embodiment, the back 111 may define a cavity 132 configured to receive an insert 134 in order to change the center of gravity and the moment of inertia of the golf club head 100; however, the apparatus, articles of manufacture, and methods described herein are not limited in this regard. Although the golf club head 100 may conform to rules and/or standards of golf defined by various golf standard organizations, governing bodies, and/or rule establishing entities, the appa-

ratus, articles of manufacture, and methods described herein are not limited in this regard.

Referring to FIG. 9, in one embodiment the crown 109 may include a first region 118 and a second region 120 with a bell-shaped curve 122 that may define the boundary 5 between the first and second regions 118 and 120. Details of the bell-shaped curve are provided in U.S. Pat. No. 7,892, 111, the entire disclosure of which is incorporated by reference. The first region 118 may sustain and endure relatively more stress than the second region 120 in response to an impact on the face 102 of the golf club head 100 by an object such as a golf ball (not shown). In one example, the bell-shaped curve 122 may include a first point 125, a second point 126 and a third point 127. The first point 125 may be located at or proximate the toe 110 of the golf club head 100, while the second point 126 may be located at or proximate the heel 106 of the golf club head 100. The third point 127 may be located at or proximate a midpoint defined between the first and second points 125 and 126 with the third point 127 being defined closer to the back 111 of the golf club head 100 than first and second points 125 and 126.

As shown in FIG. 8, the bell-shaped curve 122 that defines the boundary between the first and second regions 118 and 120 of the crown 109 may be determined by the relationship between a loft angle 114 of the face 102 and a first plane 116 separated by a predetermined distance D1. In one embodiment, the predetermined distance D1 may be defined as the distance between the top edge 104 of the face 102 and the first plane 116 at the location where first plane 116 intersects the crown 109. For example, the predetermined distance D1 may be greater than one inch. Alternatively, the predetermined distance D1 may be defined as the distance between the leading edge 103 of the face 102 and the location of the first plane 116 where the first plane 116 intersects the sole 105. In addition, the position of the first plane 116 may be established by the orientation or angle of the loft angle 114 of the golf club head 100. In one embodiment, the loft angle 114 may be established by the angle of the face 102 for a particular golf club head 100. For example, the loft angle 114 for a driver-type golf club head may range between 6° to 16°, while the loft angle 114 for a fairway-type golf club head may range between 12° to 30°. The loft angle 114 for a hybrid-type golf club head may range between 16° to 34°. As such, the location of the bell-shaped curve 122 along the crown 109, may be determined by the intersection of the first plane 116 with the crown 109 to establish the location of either the first and second points 125 and 126 (FIG. 9), or the third point 127 of the bell-shaped curve 122.

Referring to FIGS. 1-7, one embodiment of the golf club head 100 may further include a plurality of apertures 112 formed within a recess 128 defined by a perimeter 124 located in the second region 120 of the crown 109. In one example, the bell-shaped curve 122 may define a portion of the perimeter 124 that communicates with the first region 118. The recess 128 may also form a recess lip 136 defined along the perimeter 124 such that the recess 128 is positioned relatively lower on the crown 109 than the first region 118.

FIG. 10 shows a schematic view of four of the apertures 112. Each aperture 112 may have a diameter DA and be spaced apart from an adjacent aperture by a perimeter-to-perimeter distance PP and a center-to-center distance CC. If the apertures 112 are spaced apart at a fixed distance CC, the diameter DA and the distance PP inversely affect each other since increasing the diameter DA reduces the distance PP and decreasing the diameter DA increases the distance PP. For example, as shown by the apertures 112A (i.e., larger

aperture shown with dashed lines), the diameter DA1 is larger than the diameter DA of the apertures 112. Accordingly, the distance PP1 is smaller than the distance PP. In another example, as shown by apertures 112B (i.e., smaller aperture shown with dashed lines); the diameter DA2 is smaller than the diameter DA of the apertures 112. Accordingly, the distance PP2 is larger than the distance PP.

The apertures 112A may represent a maximum aperture size for the fixed distance CC. Any aperture size larger than the noted maximum may reduce the distance PP to such an extent that the strength and structural resilience of the golf club head 100 may be compromised. The maximum aperture size, however, may vary depending on physical properties of the golf club head, such as materials from which the crown 109 is constructed and/or thickness of the crown 109. For example, increased rigidity in the material from which the crown 109 is constructed may allow a greater maximum aperture size.

The apertures 112B may represent a minimum aperture size for the fixed distance CC. Any aperture size smaller than the noted minimum may diminish the properties imparted on the golf club head due to having the apertures 112 on the crown 109 as described herein. The minimum aperture size, however, may vary depending on physical properties of the golf club head, such as materials from which the crown is constructed and/or thickness of the crown. For example, reduced rigidity in the material from which the crown 109 is constructed may reduce the minimum allowable aperture size.

Referring to FIG. 10, a line 119 schematically and generally represents the face 102. The apertures 112 are arranged in a diamond pattern relative to the line 119. However, any aperture pattern and/or orientation may be used to provide the properties for the golf club head as described herein.

Referring to FIGS. 11A-E, several examples of different aperture patterns are shown. In FIG. 11A, the apertures 112 are arranged in a square pattern. In FIG. 11B, six apertures 112 surround a center aperture 112 to resemble a hexagonal pattern. In FIG. 11C, the apertures 112 are arranged in a triangular pattern. In FIG. 11D, the apertures 112 are arranged in a large square pattern with a large center section 121 that does not include any apertures. In FIG. 11E, the apertures 112 are arranged in a random pattern. The patterns of FIGS. 11A-E are exemplary and illustrate the numerous possibilities for aperture patterns on the crown. Furthermore, if the apertures 112 have different sizes, then the number of possible aperture patterns may increase.

In the above exemplary description of FIG. 10, the distance CC was assumed to be fixed while the diameter DA and the distance PP are varied. However, as illustrated in FIGS. 11A-E, any of the parameters DA, PP or CC may be varied or fixed to provide a certain aperture size, distance, pattern, orientation and/or distribution on the crown 109. For example, if the diameter DA is fixed, i.e., a certain aperture size is preferred, then the distance CC and the distance PP directly affect each other. For example, reducing the distance CC also reduces the distance PP. In another example, if the distance PP is fixed, i.e., apertures having the same perimeter-to-perimeter distance PP are preferred, then both the distance CC and the diameter DA may be varied to provide a preferred distribution configuration of apertures 112 on the crown 109. Thus, any one or more of the parameters DA, PP and CC can be changed for each pair of adjacent apertures 112 to provide certain aperture sizes, inter-aperture distances, patterns, orientation and/or distribution patterns on the crown 109.

In one example, a ratio of the distance PP to the diameter DA may be fixed according to the following formula:

$$PP=DA \cdot R$$

Where R represents a constant. R may be determined based on experimental results, some of which are provided in detail below. According to one example, experimental results with different aperture configurations have pointed to R having a value of 1.23 for a golf club head having certain physical characteristics and material properties to provide sufficient strength and structural resilience to the golf club head while removing near optimum or optimum amount of mass from the crown. The noted experimental results are described in detail herein. Accordingly, if the diameter DA is 0.093" (0.2 cm), the distance PP is 0.115" (0.3 cm).

In one aspect, the plurality of apertures 112 located in the recess within the second region 120 of the crown 109 removes mass from one portion of the golf club head 100 and moves that mass to another more optimal location of the golf club head 100, while still providing sufficient strength and structural resilience to the golf club head 100. In addition, the plurality of apertures 112 provides a generally more even distribution of forces through the crown 109 after impact of the face 102 with a golf ball (not shown) as compared to a crown 109 without having any apertures. This structural arrangement of a plurality of apertures 112 prevents impact forces on the face 102 from being focused at particular portions of the golf club head 100 during travel of these forces through the second region 120 of the crown 109, and in particular to those portions of the crown 109 defined between the plurality of apertures 112. This generally more even distribution of force through the crown 109 after impact by the plurality of apertures 112 also prevents structural failure of the golf club head 100 over time that can be caused by stress risers or stress collectors focusing impact forces at particular areas of the crown 109 caused by the uneven distribution of these forces through the second region 120 after impact as discussed above.

In one embodiment, a protective cover 130 may be engaged to the crown 109 to cover the plurality of apertures 112. The protective cover 130 may be constructed from any type of metallic, artificial or natural materials. For example, the protective cover 130 may be a film or tape made from a polycarbonate or polymeric material having an adhesive on one side that permits the protective cover 130 to adhere to and cover either a portion or the entire crown 109. In some embodiments, the protective cover 130 may be made from a polycarbonate material that exhibits high impact-resistance, while also having low scratch-resistance. In other embodiments, the protective cover 130 may be made from any type of polymeric material, such as polyethylene, neoprene, nylon, polystyrene, polypropylene or combinations thereof. In another embodiment the protective cover 130 may be a rigid cover made from the same material(s) discussed above that allow for structural engagement of the protective cover 130 along the perimeter 124 of the recess 128 to cover the plurality of apertures 112. In either of these arrangements, the protective cover 130 permits the area of the second region 120 of the crown 109, for example the area of the recess 128, to be at the same level as the first region 118 of the crown 109; however, the protective cover 130 does not have to provide any structural reinforcement to the crown 109 that is necessary for protective covers used with prior art golf club heads having larger apertures. The apparatus, articles of manufacture, and methods described herein are not limited in this regard.

While the above embodiments may describe a golf club head 100 including a recess (e.g., recess 128), the apparatus, articles of manufacture, and methods described herein may not include a recess. For example, the plurality of apertures 112 may be defined along the second region 120 of the crown 109 such that the second region 120 is flush with the first region 118. As such, some embodiments of the golf club head 100 do not require either a recess 128 to define an area for forming the plurality of apertures 112 and/or a protective cover 130 to encase or otherwise cover the plurality of apertures 112.

In other embodiments, each of the plurality of apertures 112 may have a range of diameters. The diameter of each aperture 112 of the plurality of apertures 112 may be between 0.005 inches to 0.40 inches (e.g., 0.0127 cm to 1.016 cm). The lower range values may be 0.005 inches (0.0127 cm), 0.006 inches (0.0152 cm), 0.007 inches (0.0178 cm), 0.008 inches (0.0203 cm), 0.009 inches (0.0229 cm), 0.01 inches (0.0254 cm), 0.02 inches (0.0508 cm), 0.03 inches (0.0762 cm), or 0.04 inches (0.1016 cm). The upper range of the diameter of the apertures 112 may be 0.32 inches (0.813 cm), 0.33 inches (0.838 cm), 0.34 inches (0.864 cm), 0.35 inches (0.889 cm), 0.36 inches (0.914 cm), 0.37 inches (0.940 cm), 0.39 inches (0.991 cm), or 0.40 inches (0.1016 cm).

In another example, the range of the diameter of each aperture 112 of the plurality of apertures 112 may be between 0.05 inches (0.127 cm) to 0.31 inches (e.g., 0.05 inches (0.127 cm), 0.06 inches (0.152 cm), 0.07 inches (0.179 cm), 0.08 inches (0.203 cm), 0.09 inches (0.229 cm), 0.10 inches (0.254 cm), 0.11 inches (0.279 cm), 0.12 inches (0.305 cm), 0.13 inches (0.330 cm), 0.14 inches (0.356 cm), 0.15 inches (0.381 cm), 0.16 inches (0.406 cm), 0.17 inches (0.432 cm), 0.18 inches (0.457 cm), 0.19 inches (0.483 cm), 0.20 inches (0.508 cm), 0.21 inches (0.533 cm), 0.22 inches (0.559 cm), 0.23 inches (0.584 cm), 0.24 inches (0.610 cm), 0.25 inches (0.635 cm), 0.26 inches (0.660 cm), 0.27 inches (0.686 cm), 0.28 inches (0.711 cm), 0.29 inches (0.737 cm), 0.30 inches (0.762 cm), or 0.31 inches (0.787 cm)). In yet another example, the diameter of each aperture 112 of the plurality of apertures 112 may be 0.022 inches (0.0559 cm), 0.020 inches (0.0508 cm), 0.018 inches (0.0457), or 0.016 inches (0.0406 cm), or may be 0.26 inches (0.660 cm), 0.27 inches (0.689), 0.28 inches (0.711 cm), or 0.29 inches (0.737 cm). In another embodiment, the diameter of each aperture 112 of the plurality of apertures 112 may be 0.093 inches (0.236 cm).

Although some of the above examples may describe all of the plurality of apertures 112 having an identical diameter or a substantially similar diameter, the apparatus, articles of manufacture, and methods are not limited in this regard. For example, two or more apertures of the plurality of apertures 112 may have different diameters (e.g., the diameters of the plurality of apertures 112 may vary from one aperture to another). In particular, as described in detail below, a first aperture may be associated with a first diameter and a second aperture may be associated with a second diameter. The first diameter being greater than the second diameter.

In one embodiment, each aperture 112 of the plurality of apertures 112 may have a diameter no greater than 0.30 inches (0.762 cm). In another embodiment, each aperture 112 of the plurality of apertures 112 may have a diameter no greater than 0.25 inches (0.635 cm). In other embodiments, the plurality of apertures 112 may have diameters no greater than 0.20 inches (0.508 cm), while other embodiments, each of the plurality of apertures 112 may have diameters no greater than 0.175 inches (0.444 cm), 0.150 inches (0.381

cm), 0.125 inches (0.312 cm), 0.100 inches (0.254), 0.093 inches (0.236 cm), 0.075 (0.191 cm), or 0.050 (0.127 cm), respectively. In addition, the number of apertures **112** defined along the second region **120** of the crown **109** depends on the diameter of the plurality of apertures **112**. For example, a golf club head **100** having an aperture diameter of 0.25 inches (0.635 cm) may have about 60 apertures, while a golf club head **100** having an aperture diameter of 0.093 inches (0.236 cm) may have about 576 apertures. In another example, a golf club head **100** having a combination of aperture diameters of 0.093 inches (0.236 cm) and 0.040 inches (0.102 cm) may have about 1500 apertures; however, the apparatus, articles of manufacture, and methods described herein are not limited in this regard. In particular, the number and/or size of the plurality of apertures **112** may vary based on the volume of the golf club head **100** (e.g., a golf club head less than or equal to 470 cc).

The plurality of apertures **112** may also define different configurations and sizes. For example, the plurality of apertures **112** may have a round-shaped configuration, an oval-shaped configuration, a diamond-shaped configuration, a square-shaped configuration, a rectangular-shaped configuration, a hexagon-shaped configuration, a pentagon-shaped configuration, a linear-shaped configuration, and/or a non-linear-shaped configuration. In addition, the plurality of apertures **112** may have different diameters or configurations within a particular pattern. Finally, the pattern of the apertures **112** within the second region **120** may define a repeating pattern, non-repeating pattern, symmetrical pattern and/or non-symmetrical pattern; however, the apparatus, articles of manufacture, and methods described herein are not limited in this regard. Further, while the above examples may describe the plurality of apertures **112** being located on the crown **109** of the golf club head **100**, the plurality of apertures **112** may be located on other portion(s) of a golf club head (e.g., the sole only, the crown and the sole, etc).

In one embodiment, the golf club head **100** may be made from steel, steel alloy, titanium, titanium alloy (e.g., titanium 6-4 or titanium 8-1-1). In other embodiments, the golf club head **100** may be made from one or more materials including titanium, titanium alloys, magnesium, magnesium alloys, titanium aluminides, fiber-based composites, and metal matrix composites or mixtures thereof. In some embodiments, the fiber-based composite may be carbon fiber, fiberglass, or KEVLAR® or combinations thereof. In some embodiments, the percentage of titanium may be 10%, 20%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, or 99% for titanium alloys and 100% for a golf club head **100** made entirely of 100% titanium. In other embodiments, the percentage of fiberglass may be 10%, 20%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, or 100%. In yet other embodiments, the percentage of KEVLAR® may be 10%, 20%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, or 100%. In some embodiments, the KEVLAR® may be any type of para-aramid synthetic fiber. In some embodiments the percentage of carbon fiber may be 10%, 20%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, or 100%. In some embodiments, the golf club head **100** may be 50% titanium and 50% of one or more of the fiber-based composite(s), although in other embodiments a golf club head according to the disclosure may constitute any of the percentages for titanium noted above in combination with one or more respective percentages of the fiber-based composite(s).

Referring to FIG. **12**, a flow chart illustrates one method for manufacturing the golf club head **100** with a plurality of apertures **112**. At block **1000**, a mold (not shown) is provided for forming the golf club head **100**. At block **1002**, the

golf club head **100** is formed using the mold having the face **102**, sole **105**, heel **106**, toe **110**, back **111**, crown **109**, and hosel **108** defining the aperture **113** configured to engage the shaft. In one embodiment, the crown **109** formed by the mold is defined between the back **111** and front edge **104** of the golf club head **100**. In addition, the recess **128** may be defined along the crown **109** using the mold. At block **1004**, the plurality of apertures **112** is formed along the crown **109**. The plurality of apertures **112** may be formed using a stamping process that forms the apertures **112** entirely through the material of the crown **109**. In the alternative, a plurality of small recesses (not shown) may be formed into but not entirely through the material of the crown **109** rather than the plurality of apertures **112**; however, the apparatus, articles of manufacture, and methods described herein are not limited in this regard. At block **1006**, the protective cover **130** may be configured to engage and cover the plurality of apertures **112** within the perimeter **124** defined along the portion of the crown **109**. As discussed above, the protective cover **130** may be a film or tape made from a polycarbonate or plastic material having an adhesive on one side that permits the protective cover **130** to adhere to and cover either a portion or the entire crown **109**, while in another embodiment the protective cover **130** may be rigid cover that is structurally engaged along the perimeter **124** defined by the recess **128** to cover the plurality of apertures **112**. In either of these arrangements, the protective cover **130** permits the area of the second region **120** of the crown **109**, for example the recess **128**, to be at the same level as the first region **118** of the crown **109**; however, the apparatus, articles of manufacture, and methods described herein are not limited in this regard.

Although a particular order of actions is illustrated in FIG. **12**, these actions may be performed in other temporal sequences. For example, two or more actions depicted in FIG. **12** may be performed sequentially, concurrently, or simultaneously. Alternatively, two or more actions depicted may be performed in reversed order. Further, one or more actions depicted in FIG. **12** may not be performed at all. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

Referring to FIG. **13-17**, another embodiment of a golf club head is illustrated and generally indicated as **200**. In general, the golf club head **200** may include a face **202**, a sole **205**, a heel **206**, and a toe **210**. The golf club head **200** may also include a plurality of grooves **215** on the face **202**. The golf club head **200** may be a single piece or include multiple portions manufactured together. In one example, the golf club head **200** may be a hollow body formed by a casting process or other suitable type of manufacturing process. In addition, the face **202** may be an integral part of the golf club head **200**. Alternatively, the face **202** may be a separate piece from or an insert for a body of the golf club head **200**.

The golf club head **200** includes a hosel **208** that defines an aperture **213** configured to engage a shaft (not shown). In particular, the shaft may engage the golf club head **200** on one end and engage a grip (not shown) on an opposite end. For example, the golf club head **200** may be a wood-type golf club, such as a driver-type golf club head, a fairway wood-type golf club head (e.g., 2-wood golf club, 3-wood golf club, 4-wood golf club, 5-wood golf club, 6-wood golf club, 7-wood golf club, 8-wood golf club, or a 9-wood golf club), a hybrid-type golf club head or any other suitable type of golf club head with a hollow body or a body with one or more cavities, apertures, recesses or channels. Although the above examples may depict and/or describe a wood-type

11

golf club head (e.g., driver-type golf club head, a fairway-type golf club head, a hybrid-type golf club head), the apparatus, articles of manufacture, and methods described herein may be applicable to other suitable types of golf club heads.

In addition, the face **202** may be formed adjacent the hosel **208** and provides a surface for striking a golf ball (not shown). The face **202** may be made from one or more metals or metal alloys such as a steel material, a titanium material, a titanium alloy material, a titanium-based material, a combination thereof, one or more composite materials, one or more plastic materials, or other suitable type of materials; however, the face **202** may be made from the same material(s) that constitute the golf club head **200** as described in greater detail below. In particular, the face **202** may include a plurality of grooves **215**. The golf club head **200** further includes a back **211** formed opposite the face **202** with the sole **205** being defined between the back **211** and the face **202**. As further shown, a crown **209** is formed opposite the sole **205**, while the face **202** is defined by the heel **206** formed adjacent the hosel **208** and the toe **210** defined at the far end of the face **202**. The face **202** further includes a top edge **204** defined between the crown **209** and the face **202** as well as a leading edge **203** defined between the sole **205** and the face **202**. Although the golf club head **200** may conform to rules and/or standards of golf defined by various golf standard organizations, governing bodies, and/or rule establishing entities, the apparatus, articles of manufacture, and methods described herein are not limited in this regard.

Referring to FIG. 16, in one embodiment the crown **209** may include a first region **218** and a second region **220** with a bell-shaped curve **222** that may define the boundary between the first and second regions **218** and **220**. Details of the bell-shaped curve are provided in U.S. Pat. No. 7,892, 111. The first region **218** may sustain and endure relatively more stress than the second region **220** in response to an impact on the face **202** of the golf club head **200** by an object such as a golf ball (not shown). In one example, the bell-shaped curve **222** may include a first point **225**, a second point **226** and a third point **227**. The first point **225** may be located at or proximate the toe **210** of the golf club head **200**, while the second point **226** may be located at or proximate the heel **206** of the golf club head **200**. The third point **227** may be located at or proximate a midpoint defined between the first and second points **225** and **226** with the third point **227** being defined closer to the back **211** of the golf club head **200** than first and second points **225** and **226**.

As shown in FIG. 15, the bell-shaped curve **222** that defines the boundary between the first and second regions **218** and **220** of the crown **209** may be determined by the relationship between a loft angle **214** of the face **202** and a first plane **216** separated by a predetermined distance **D1**. In one embodiment, the predetermined distance **D1** may be defined as the distance between the top edge **204** of the face **202** and the first plane **216** at the location where first plane **216** intersects the crown **209**. For example, the predetermined distance **D1** may be greater than one inch. Alternatively, the predetermined distance **D1** may be defined as the distance between the leading edge **203** of the face **202** and the location of the first plane **216** where the first plane **216** intersects the sole **205**. In addition, the position of the first plane **216** may be established by the orientation or angle of the loft angle **214** of the golf club head **200**. In one embodiment, the loft angle **214** may be established by the angle of the face **102** for a particular golf club head **200**. For example, the loft angle **214** for a driver-type golf club head

12

may range between 6° to 16° , while the loft angle **214** for a fairway-type golf club head may range between 12° to 30° . The loft angle **214** for a hybrid-type golf club head may range between 16° to 34° . As such, the location of the bell-shaped curve **222** along the crown **209**, may be determined by the intersection of the first plane **216** with the crown **209** to establish the location of either the first and second points **225** and **226** (FIG. 16), or the third point **227** of the bell-shaped curve **222**.

Referring to FIG. 13, one embodiment of the golf club head **200** may further include a plurality of apertures **212** formed within a recess **228** defined by a perimeter **224** located in the second region **220** of the crown **209**. In one example, the bell-shaped curve **222** may define a portion of the perimeter **224** that communicates with the first region **218**. The recess **228** may also form a recess lip **236** defined along the perimeter **224** such that the recess **228** is positioned relatively lower on the crown **209** than the first region **218**. The golf club head **200** also may include reinforcing ribs **219** in the second region **220** for increasing rigidity of the crown **209** at certain locations on the crown **209**. In the example of FIG. 13, three reinforcing ribs, which are referred to as reinforcing ribs **219A-C** are provided on the crown **209**. The reinforcing ribs **219A-C** may be defined by areas of the crown **209** that do not include the apertures **212**. Accordingly, the reinforcing ribs **219** may be formed on the crown **209** by not forming apertures **212** on portions of the crown **209** that define the reinforcing ribs **219**.

As shown in the example of FIG. 13, the reinforcing rib **219A** may be generally perpendicular to the face **202** and bifurcate into the reinforcing ribs **219B** and **219C** to form a generally Y-shaped reinforcing structure. The reinforcing rib **219A** may extend from the proximate to the third point **227** of the bell-shaped curve **222** toward the back **211**. Accordingly, the impact force on the face **202** may be partly transferred to the reinforcing rib **219A**. At a certain location in the second region **220**, the reinforcing ribs **219B** and **219C** disperse or spread the impact force to the back **211**. FIG. 13 shows one example of the reinforcing ribs **219**, which are specifically shown as reinforcing ribs **219A-C**. However, any reinforcing rib configuration can be provided on the crown **209**. The width, length, orientation of each reinforcing rib **219** may depend on the size of the crown **209**, the thickness of the crown **209**, the sizes, distribution patterns, and other properties of the apertures **212**, and/or the materials from which the crown **209** is constructed. For example, the reinforcing ribs **219A-C** can be strategically located on the crown **220** to coincide with the highest stress locations on the crown **209** resulting from impact forces on the face **202**. Generally, the width of a reinforcing rib may be greater than the greatest dimension of the apertures **212**. For example, if the apertures **212** are circular, then the width of the reinforcing ribs **219** may be greater than the diameter of the apertures **212**. Furthermore, the width of the reinforcing ribs **219** may be greater than the largest distance between any two adjacent apertures **212**.

The reinforcing ribs **219** provide structural reinforcement for the crown **209** or regions of the crown **209** that experience large impact forces or high stresses. The reinforcing ribs **219** may also assist in evenly distributing the high stresses throughout the crown **209**. Accordingly, due to the presence of the reinforcing ribs **219**, the sizes, patterns, orientations, shapes and/or distribution of the apertures **212** may be different as compared to the apertures **112** of the embodiment described above according to FIGS. 1-12. For example, having reinforcement ribs **219** on the crown **209** may allow a larger aperture density (i.e., apertures per area), which may be achieved by having a larger number of

apertures that are closer to each other. In another example, the size of the apertures **212** may be increased while the distance between the apertures **212** may be reduced as compared to the apertures **112** due to the presence of the reinforcing ribs **219**. Therefore, the shapes, sizes, orientations, patterns or other characteristics of the reinforcing ribs **219** may directly affect the shapes, sizes, orientations, distribution patterns, or other characteristics of the apertures **212** to achieve similar results as the embodiments of FIGS. 1-12.

In one aspect, the plurality of apertures **212** located within the second region **220** of the crown **209** removes mass from one portion of the golf club head **200** and moves that mass to another more optimal location of the golf club head **200**, while still providing sufficient strength and structural resilience to the golf club head **200**. In addition, the plurality of apertures **212** provides a generally more even distribution of forces through the crown **209** after impact of the face **202** with a golf ball (not shown) as compared to a crown **209** without having any apertures. This structural arrangement of a plurality of apertures **212** prevents impact forces on the face **202** from being focused at particular portions of the golf club head **200** during travel of these forces through the second region **220** of the crown **209**, and in particular to those portions of the crown **209** defined between the plurality of apertures **212**. However, at the particular locations where stresses are high relative to other regions of the crown **209**, reinforcing ribs **219** can be provided. This generally more even distribution of force through the crown **209** after impact by the plurality of apertures **212** and the reinforcing ribs **219** also prevents structural failure of the golf club head **200** over time that can be caused by stress risers or stress collectors focusing impact forces at particular areas of the crown **209** caused by the uneven distribution of these forces through the second region **220** after impact as discussed above.

In one embodiment, a protective cover **230** may be engaged to the crown **209** to cover the plurality of apertures **212**. The protective cover **230** may be constructed from any type of metallic, artificial or natural materials. For example, the protective cover **230** may be a film or tape made from a polycarbonate or polymeric material having an adhesive on one side that permits the protective cover **230** to adhere to and cover either a portion or the entire crown **209**. In some embodiments, the protective cover **230** may be made from a polycarbonate material that exhibits high impact-resistance, while also having low scratch-resistance. In other embodiments, the protective cover **230** may be made from any type of polymeric material, such as polyethylene, neoprene, nylon, polystyrene, polypropylene or combinations thereof. In another embodiment the protective cover **230** may be a rigid cover made from the same material(s) discussed above that allow for structural engagement of the protective cover **230** along the perimeter **224** of the recess **228** to cover the plurality of apertures **212**. In either of these arrangements, the protective cover **230** permits the area of the second region **220** of the crown **209**, for example the area of the recess **228**, to be at the same level as the first region **218** of the crown **209**; however, the protective cover **230** does not have to provide any structural reinforcement to the crown **209** that is necessary for protective covers used with prior art golf club heads having larger apertures. The apparatus, articles of manufacture, and methods described herein are not limited in this regard.

While the above embodiments may describe a golf club head **200** including a recess (e.g., recess **228**), the apparatus, articles of manufacture, and methods described herein may

not include a recess. For example, the plurality of apertures **212** and the reinforcing ribs **219** may be defined along the second region **220** of the crown **209** such that the second region **220** is flush with the first region **218**. As such, some embodiments of the golf club head **200** do not require either a recess **228** to define an area for forming the plurality of apertures **212** and the reinforcing ribs **219** and/or a protective cover **230** to encase or otherwise cover the plurality of apertures **212**.

In other embodiments, each of the plurality of apertures **212** may have a range of diameters. The diameter of each aperture **212** of the plurality of apertures **212** may be between 0.005 inches to 0.40 inches (e.g., 0.0127 cm to 1.016 cm). The lower range values may be 0.005 inches (0.0127 cm), 0.006 inches (0.0152 cm), 0.007 inches (0.0178 cm), 0.008 inches (0.0203 cm), 0.009 inches (0.0229 cm), 0.01 inches (0.0254 cm), 0.02 inches (0.0508 cm), 0.03 inches (0.0762 cm), or 0.04 inches (0.1016 cm). The upper range of the diameter of the apertures **112** may be 0.32 inches (0.813 cm), 0.33 inches (0.838 cm), 0.34 inches (0.864 cm), 0.35 inches (0.889 cm), 0.36 inches (0.914 cm), 0.37 inches (0.940 cm), 0.39 inches (0.991 cm), or 0.40 inches (1.016 cm).

In another example, the range of the diameter of each aperture **212** of the plurality of apertures **212** may be between 0.05 inches (0.127 cm) to 0.31 inches (e.g., 0.05 inches (0.127 cm), 0.06 inches (0.152 cm), 0.07 inches (0.179 cm), 0.08 inches (0.203 cm), 0.09 inches (0.229 cm), 0.10 inches (0.254 cm), 0.11 inches (0.279 cm), 0.12 inches (0.305 cm), 0.13 inches (0.330 cm), 0.14 inches (0.356 cm), 0.15 inches (0.381 cm), 0.16 inches (0.406 cm), 0.17 inches (0.432 cm), 0.18 inches (0.457 cm), 0.19 inches (0.483 cm), 0.20 inches (0.508 cm), 0.21 inches (0.533 cm), 0.22 inches (0.559 cm), 0.23 inches (0.584 cm) 0.24 inches (0.610 cm), 0.25 inches (0.635 cm), 0.26 inches (0.660 cm), 0.27 inches (0.686 cm), 0.28 inches (0.711 cm), 0.29 inches (0.737 cm), 0.30 inches (0.762 cm), or 0.31 inches (0.787 cm)).

In yet another example, the diameter of each aperture **212** of the plurality of apertures **212** may be 0.022 inches (0.0559 cm), 0.020 inches (0.0508 cm), 0.018 inches (0.0457), or 0.016 inches (0.0406 cm), or may be 0.26 inches (0.660 cm), 0.27 inches (0.689), 0.28 inches (0.711 cm), or 0.29 inches (0.737 cm). In another embodiment, the diameter of each aperture **212** of the plurality of apertures **212** may be 0.093 inches (0.236 cm).

Although some of the above examples may describe all of the plurality of apertures **212** having an identical diameter or a substantially similar diameter, the apparatus, articles of manufacture, and methods are not limited in this regard. For example, two or more apertures of the plurality of apertures **212** may have different diameters (e.g., the diameters of the plurality of apertures **212** may vary from one aperture to another). In particular, as described in detail below, a first aperture may be associated with a first diameter and a second aperture may be associated with a second diameter. The first diameter being greater than the second diameter.

In one embodiment, each aperture **212** may have a diameter no greater than 0.30 inches (0.762 cm). In another embodiment, each aperture **212** may have a diameter no greater than 0.25 inches (0.635 cm). In other embodiments, the plurality of apertures **212** may have diameters no greater than 0.20 inches (0.508 cm), while other embodiments, each of the plurality of apertures **212** may have diameters no greater than 0.175 inches (0.444 cm), 0.150 inches (0.381 cm), 0.125 inches (0.312 cm), 0.100 inches (0.254), 0.093 inches (0.236 cm), 0.075 (0.191 cm), or 0.050 (0.127 cm), respectively. In addition, the number of apertures **212**

defined along the second region **220** of the crown **209** depends on the diameter of the plurality of apertures **212**. For example, a golf club head **200** having an aperture diameter of 0.25 inches (0.635 cm) may have about 60 apertures, while a golf club head **200** having an aperture diameter of 0.093 inches (0.236 cm) may have about 576 apertures. In another example, a golf club head **100** having a combination of aperture diameters of 0.093 inches (0.236 cm) and 0.040 inches (0.102 cm) may have about 1500 apertures; however, the apparatus, articles of manufacture, and methods described herein are not limited in this regard. In particular, the number and/or size of the plurality of apertures **212** may vary based on the volume of the golf club head **200** (e.g., a golf club head less than or equal to 470 cc).

The plurality of apertures **212** may also define different configurations and sizes. For example, the plurality of apertures **212** may have a round-shaped configuration, an oval-shaped configuration, a diamond-shaped configuration, a square-shaped configuration, a rectangular-shaped configuration, a hexagon-shaped configuration, a pentagon-shaped configuration, a linear-shaped configuration, and/or a non-linear-shaped configuration. In addition, the plurality of apertures **212** may have different diameters or configurations within a particular pattern. Furthermore, the apertures may be in any shape, size and/or configuration. Finally, the pattern of the apertures **212** within the second region **220** may define a repeating pattern, non-repeating pattern, symmetrical pattern and/or non-symmetrical pattern; however, the apparatus, articles of manufacture, and methods described herein are not limited in this regard. Further, while the above examples may describe the plurality of apertures **212** being located on the crown **209** of the golf club head **200**, the plurality of apertures **212** may be located on other portion(s) of a golf club head (e.g., the sole only, the crown and the sole, etc).

The number and size of the apertures **212** and the number and size of the reinforcing ribs **219** may affect each other. For example, a crown having large apertures that are relatively close to each other may require a greater number of reinforcing ribs or wider/larger reinforcing ribs to provide sufficient strength and structural resilience for the golf club head. Smaller apertures that are relatively far apart from each other, however, may not need a larger number of reinforcing ribs or wider/larger reinforcing ribs to provide sufficient strength and structural resilience for the crown.

In one embodiment, the golf club head **200** may be made from steel, steel alloy, titanium, titanium alloy (e.g., titanium 6-4 or titanium 8-1-1). In other embodiments, the golf club heads according to the disclosure may be made from one or more materials including titanium, titanium alloys, magnesium, magnesium alloys, titanium aluminides, fiber-based composites, and metal matrix composites or mixtures thereof. In some embodiments, the fiber-based composite may be carbon fiber, fiberglass, or KEVLAR® or combinations thereof. In some embodiments, the percentage of titanium may be 10%, 20%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, or 99% for titanium alloys and 100% for a golf club head **200** made entirely of 100% titanium. In other embodiments, the percentage of fiberglass may be 10%, 20%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, or 100%. In yet other embodiments, the percentage of KEVLAR® may be 10%, 20%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, or 100%. In some embodiments, the KEVLAR® may be any type of para-aramid synthetic fiber. In some embodiments the percentage of carbon fiber may be 10%, 20%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, or 100%. In some embodiments, the golf club head **200** may be 50% titanium and 50%

of one or more of the fiber-based composite(s), although in other embodiments a golf club head according to the disclosure may constitute any of the percentages for titanium noted above in combination with one or more respective percentages of the fiber-based composite(s).

Referring to FIG. **17**, a flow chart illustrates one method for manufacturing a golf club head **200** with a plurality of apertures **212**. At block **2000**, a mold (not shown) is provided for forming the golf club head **200**. At block **2002**, the golf club head **200** is formed using the mold having the face **202**, sole **205**, heel **206**, toe **210**, back **211**, crown **209**, and hosel **208** defining the aperture **213** configured to engage the shaft. In one embodiment, the crown **209** formed by the mold is defined between the back **211** and front edge **204** of the golf club head **200**. In addition, the recess **228** may be defined along the crown **209** using the mold. At block **2004**, the plurality of apertures **212** is formed along the crown **109**. The plurality of apertures **212** may be formed using a stamping process that forms the apertures **212** entirely through the material of the crown **209**. In the alternative, a plurality of small recesses (not shown) may be formed into but not entirely through the material of the crown **209** rather than the plurality of apertures **212**; however, the apparatus, articles of manufacture, and methods described herein are not limited in this regard. In one example, the reinforcing ribs **219** may be formed at block **2004** by not forming the apertures **212** on sections of the crown **209** that correspond to the locations of the reinforcing ribs **219**. However, other methods for providing the reinforcing ribs **219** may be used. For example, after forming the plurality of apertures at block **2004**, the reinforcing ribs **219** may be formed by attaching rib-shaped pieces to the crown **209** with an adhesive, by welding, soldering or other fixation methods.

At block **2006**, the protective cover **230** may be configured to engage and cover the plurality of apertures **212** within the perimeter **224** defined along the portion of the crown **209**. As discussed above, the protective cover **230** may be a film or tape made from a polycarbonate or plastic material having an adhesive on one side that permits the protective cover **230** to adhere to and cover either a portion or the entire crown **209**, while in another embodiment the protective cover **230** may be rigid cover that is structurally engaged along the perimeter **224** defined by the recess **228** to cover the plurality of apertures **212**. In either of these arrangements, the protective cover **230** permits the area of the second region **220** of the crown **209**, for example the recess **228**, to be at the same level as the first region **218** of the crown **209**; however, the apparatus, articles of manufacture, and methods described herein are not limited in this regard.

Although a particular order of actions is illustrated in FIG. **17**, these actions may be performed in other temporal sequences. For example, two or more actions depicted in FIG. **17** may be performed sequentially, concurrently, or simultaneously. Alternatively, two or more actions depicted may be performed in reversed order. Further, one or more actions depicted in FIG. **17** may not be performed at all. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

Referring to FIG. **18-23**, another embodiment of a golf club head is illustrated and generally indicated as **300**. In general, the golf club head **300** may include a face **302**, a sole **305**, a heel **306**, and a toe **310**. The golf club **300** may also include a plurality of grooves **315** on the face **302**. The golf club head **300** may be a single piece or include multiple portions manufactured together. In one example, the golf club head **300** may be a hollow body formed by a casting

process or other suitable type of manufacturing process. In addition, the face **302** may be an integral part of the golf club head **300**. Alternatively, the face **302** may be a separate piece from or an insert for a body of the golf club head **300**.

The golf club head **300** includes a hosel **308** that defines an aperture **317** configured to engage a shaft (not shown). In particular, the shaft may engage the golf club head **300** on one end and engage a grip (not shown) on an opposite end. For example, the golf club head **300** may be a wood-type golf club, such as a driver-type golf club head, a fairway wood-type golf club head (e.g., 2-wood golf club, 3-wood golf club, 4-wood golf club, 5-wood golf club, 6-wood golf club, 7-wood golf club, 8-wood golf club, or a 9-wood golf club), a hybrid-type golf club head or any other suitable type of golf club head with a hollow body or a body with one or more cavities, apertures, recesses or channels. Although the above examples may depict and/or describe a wood-type golf club head (e.g., driver-type golf club head, a fairway-type golf club head, a hybrid-type golf club head), the apparatus, articles of manufacture, and methods described herein may be applicable to other suitable types of golf club heads.

In addition, the face **302** may be formed adjacent the hosel **308** and provides a surface for striking a golf ball (not shown). The face **302** may be made from one or more metals or metal alloys such as a steel material, a titanium material, a titanium alloy material, a titanium-based material, a combination thereof, one or more composite materials, one or more plastic materials, or other suitable type of materials; however, the face **302** may be made from the same material(s) that constitute the golf club head **300** as described in greater detail below. In particular, the face **302** may include a plurality of grooves **315**. The golf club head **300** further includes a back **311** formed opposite the face **302** with the sole **305** being defined between the back **311** and the face **302**. As further shown, a crown **309** is formed opposite the sole **305**, while the face **302** is defined by the heel **306** formed adjacent the hosel **308** and the toe **310** defined at the far end of the face **302**. The face **302** further includes a top edge **304** defined between the crown **309** and the face **302** as well as a leading edge **303** defined between the sole **305** and the face **302**. Although the golf club head **300** may conform to rules and/or standards of golf defined by various golf standard organizations, governing bodies, and/or rule establishing entities, the apparatus, articles of manufacture, and methods described herein are not limited in this regard.

Referring to FIG. 21, in one embodiment the crown **309** may include a first region **318** and a second region **320** with a bell-shaped curve **322** that may define the boundary between the first and second regions **318** and **320**. Details of the bell-shaped curve are provided in U.S. Pat. No. 7,892, 111. The first region **318** may sustain and endure relatively more stress than the second region **320** in response to an impact on the face **302** of the golf club head **300** by an object such as a golf ball (not shown). In one example, the bell-shaped curve **322** may include a first point **325**, a second point **326** and a third point **327**. The first point **325** may be located at or proximate the toe **310** of the golf club head **300**, while the second point **326** may be located at or proximate the heel **306** of the golf club head **300**. The third point **327** may be located at or proximate a midpoint defined between the first and second points **325** and **326** with the third point **327** being defined closer to the back **311** of the golf club head **300** than first and second points **325** and **326**.

As shown in FIG. 21, the bell-shaped curve **322** that defines the boundary between the first and second regions

318 and **320** of the crown **309** may be determined by the relationship between a loft angle **314** of the face **302** and a first plane **316** separated by a predetermined distance **D1**. In one embodiment, the predetermined distance **D1** may be defined as the distance between the top edge **304** of the face **302** and the first plane **316** at the location where first plane **316** intersects the crown **309**. For example, the predetermined distance **D1** may be greater than one inch. Alternatively, the predetermined distance **D1** may be defined as the distance between the leading edge **303** of the face **302** and the location of the first plane **316** where the first plane **316** intersects the sole **305**. In addition, the position of the first plane **316** may be established by the orientation or angle of the loft angle **314** of the golf club head **300**. In one embodiment, the loft angle **314** may be established by the angle of the face **302** for a particular golf club head **300**. For example, the loft angle **314** for a driver-type golf club head may range between 6° to 16°, while the loft angle **314** for a fairway-type golf club head may range between 12° to 30°. The loft angle **314** for a hybrid-type golf club head may range between 16° to 34°. As such, the location of the bell-shaped curve **322** along the crown **309**, may be determined by the intersection of the first plane **316** with the crown **309** to establish the location of either the first and second points **325** and **326** (FIG. 21), or the third point **327** of the bell-shaped curve **322**.

Referring to FIGS. 18 and 22, one embodiment of the golf club head **300** may further include a plurality of first apertures **312** and a plurality of second apertures **317** formed within a recess **328** defined by a perimeter **234** located in the second region **320** of the crown **309**. The second apertures **317** are smaller than the first apertures **312** as described in detail below. In one example, the bell-shaped curve **322** may define a portion of the perimeter **334** that communicates with the first region **318**. The recess **328** may also form a recess lip **336** defined along the perimeter **334** such that the recess **328** is positioned relatively lower on the crown **309** than the first region **318**.

In one aspect, the plurality of apertures **312** and **317** located within the second region **320** of the crown **309** removes mass from one portion of the golf club head **300** and moves that mass to another more optimal location of the golf club head **300**, while still providing sufficient strength and structural resilience to the golf club head **300**. In addition, the plurality of apertures **312** and **317** provides a generally even distribution of forces through the crown **309** after impact of the face **302** with a golf ball (not shown) as compared to a crown **309** without having any apertures. This structural arrangement of a plurality of apertures **312** and **317** prevents impact forces on the face **302** from being focused at particular portions of the golf club head **300** during travel of these forces through the second region **320** of the crown **309**, and in particular to those portions of the crown **309** defined between the plurality of apertures **312** and **317**. This generally even distribution of force through the crown **309** after impact by the plurality of apertures **312** also prevents structural failure of the golf club head **300** over time that can be caused by stress risers or stress collectors focusing impact forces at particular areas of the crown **309** caused by the uneven distribution of these forces through the second region **320** after impact as discussed above.

Referring to FIG. 22, an enlarged schematic view showing the arrangement of the apertures **312** and **317** is shown. The configuration and arrangement of the apertures **312** may be similar to the apertures **112** described above. Accordingly, each aperture **312** may have a diameter **DA1**, be spaced apart from an adjacent aperture **312** by a perimeter-to-perimeter distance **PP1**, and have a center-to-center dis-

tance CC1 with an adjacent aperture 312. A group of four apertures 312 defines a center section 319 (shown with dashed lines), which may be smaller, as large as, or larger than each aperture 312. Depending on the physical properties of a club head 300 and/or the crown 309, such as materials of construction, dimensions, thicknesses, etc., additional mass may be removed from the center sections 319 without degrading the strength and structural resilience of the crown 309. The additional mass to be removed from the crown 309 may be realized by the apertures 317 in the center sections 319. The apertures 317 may be sized according to the physical properties of the club head so that the remaining portions of the center sections 319 can provide sufficient strength and structural resilience for the crown 309. Thus, the sizes, spacing, patterns, orientations, distribution and other characteristics of the apertures 312 and 317 can be determined to provide optimum or near optimum removal of mass from the crown 309 without negatively affecting the strength and structural resilience of the crown 209.

In one embodiment, a protective cover 330 may be engaged to the crown 309 to cover the plurality of apertures 312 and 317. The protective cover 330 may be constructed from any type of metallic, artificial or natural materials. For example, the protective cover 330 may be a film or tape made from a polycarbonate or polymeric material having an adhesive on one side that permits the protective cover 330 to adhere to and cover either a portion or the entire crown 309. In some embodiments, the protective cover 330 may be made from a polycarbonate material that exhibits high impact-resistance, while also having low scratch-resistance. In other embodiments, the protective cover 330 may be made from any type of polymeric material, such as polyethylene, neoprene, nylon, polystyrene, polypropylene or combinations thereof. In another embodiment the protective cover 330 may be a rigid cover made from the same material(s) discussed above that allow for structural engagement of the protective cover 330 along the perimeter 234 of the recess 328 to cover the plurality of apertures 312 and 317. In either of these arrangements, the protective cover 330 permits the area of the second region 320 of the crown 309, for example the area of the recess 328, to be at the same level as the first region 318 of the crown 309; however, the protective cover 330 does not have to provide any structural reinforcement to the crown 309 that is necessary for protective covers used with prior art golf club heads having larger apertures. The apparatus, articles of manufacture, and methods described herein are not limited in this regard.

While the above embodiments may describe a golf club head 300 including a recess (e.g., recess 328), the apparatus, articles of manufacture, and methods described herein may not include a recess. For example, the plurality of apertures 312 and 317 may be defined along the second region 320 of the crown 309 such that the second region 320 is flush with the first region 318. As such, some embodiments of the golf club head 300 do not require either a recess 328 to define an area for forming the plurality of apertures 312 and 317 and/or a protective cover 330 to encase or otherwise cover the plurality of apertures 312 and 317.

In other embodiments, each of the plurality of apertures 312 and 317 may have a range of diameters. The diameter of each aperture 312 may be between 0.005 inches to 0.40 inches (e.g., 0.0127 cm to 1.016 cm). The lower range values may be 0.005 inches (0.0127 cm), 0.006 inches (0.0152 cm), 0.007 inches (0.0178 cm), 0.008 inches (0.0203 cm), 0.009 inches (0.0229 cm), 0.01 inches (0.0254 cm), 0.02 inches (0.0508 cm), 0.03 inches (0.0762 cm), or 0.04 inches

(0.1016 cm). The upper range of the diameter of the apertures 312 may be 0.32 inches (0.813 cm), 0.33 inches (0.838 cm), 0.34 inches (0.864 cm), 0.35 inches (0.889 cm), 0.36 inches (0.914 cm), 0.37 inches (0.940 cm), 0.39 inches (0.991 cm), or 0.40 inches (1.016 cm). In another embodiment, the diameter of each aperture 312 of the plurality of apertures 312 may be 0.093 inches (0.236 cm).

In another example, the range of the diameter of each aperture 312 may be between 0.05 inches (0.127 cm) to 0.31 inches (e.g., 0.05 inches (0.127 cm), 0.06 inches (0.152 cm), 0.07 inches (0.179 cm), 0.08 inches (0.203 cm), 0.09 inches (0.229 cm), 0.10 inches (0.254 cm), 0.11 inches (0.279 cm), 0.12 inches (0.305 cm), 0.13 inches (0.330 cm), 0.14 inches (0.356 cm), 0.15 inches (0.381 cm), 0.16 inches (0.406 cm), 0.17 inches (0.432 cm), 0.18 inches (0.457 cm), 0.19 inches (0.483 cm), 0.30 inches (0.508 cm), 0.31 inches (0.533 cm), 0.32 inches (0.559 cm), 0.33 inches (0.584 cm) 0.34 inches (0.610 cm), 0.25 inches (0.635 cm), 0.26 inches (0.660 cm), 0.27 inches (0.686 cm), 0.28 inches (0.711 cm), 0.29 inches (0.737 cm), 0.30 inches (0.762 cm), or 0.31 inches (0.787 cm)).

In yet another example, the diameter of each aperture 312 may be 0.022 inches (0.0559 cm), 0.020 inches (0.0508 cm), 0.018 inches (0.0457), or 0.016 inches (0.0406 cm), or may be 0.26 inches (0.660 cm), 0.27 inches (0.689), 0.28 inches (0.711 cm), or 0.29 inches (0.737 cm). In another embodiment, the diameter of each aperture 312 of the plurality of apertures 312 may be 0.093 inches (0.236 cm).

As described above, the apertures 317 are formed in the center sections 319, which are regions that are defined by four of the apertures 312. The size of the apertures 317 may be based upon the size of the center sections 319 and/or the size of the apertures 312. For example, the diameter of the apertures 317 may be a fraction of the diameter of the apertures 312, such as $\frac{2}{3}$, $\frac{1}{2}$, or $\frac{1}{3}$ the diameter of the apertures 312. Accordingly, with reference to FIG. 22, the size of the apertures 312 and 317 may be based on the following formula:

$$DA2 = F \cdot DA1$$

Where DA2 is the diameter of the apertures 317, DA1 is the diameter of the apertures 312 and F is a factor that defines the relationship between the diameters DA2 and DA1. For example, F can have any value from 0.001 to approximately 1. However, F=1 would result in the apertures 312 and 317 having the same diameter, which is similar to the embodiment of FIGS. 1-12. In another example, with reference to FIG. 22, the size of the apertures 317 may be determined so that the perimeter-to-perimeter distance PP1 between an aperture 312 and an adjacent aperture 317 is the same as the perimeter-to-perimeter distance PP1 between two adjacent apertures 312. Thus, the size of the apertures 312 and 317 may be determined in any manner or based on any mathematical relationship so that mass is removed from the crown 309 without negatively affecting the performance, the strength and the structural resilience of the club head 300 and/or optimizing or near optimizing the performance of the club head 300.

Although some of the above examples may describe all of the plurality of apertures 312 having an identical diameter or a substantially similar diameter, and/or the plurality of apertures 317 having an identical diameter or substantially similar diameter, the apparatus, articles of manufacture, and methods are not limited in this regard. For example, two or more apertures of the plurality of apertures 312 may have different diameters (e.g., the diameters of the plurality of apertures 312 may vary from one aperture to another). In

another example, two or more apertures of the plurality of apertures **317** may have different diameters (e.g., the diameters of the apertures **317** may vary from one aperture to another).

In one embodiment, each aperture **312** may have a diameter no greater than 0.30 inches (0.762 cm). In another embodiment, each aperture **312** may have a diameter no greater than 0.25 inches (0.635 cm). In other embodiments, the plurality of apertures **312** may have diameters no greater than 0.20 inches (0.508 cm), while other embodiments, each of the plurality of apertures **312** may have diameters no greater than 0.175 inches (0.444 cm), 0.150 inches (0.381 cm), 0.125 inches (0.312 cm), 0.100 inches (0.254), 0.093 inches (0.236 cm), 0.075 (0.191 cm), or 0.050 (0.127 cm), respectively. Because the apertures **312** defined the size of the center section **319**, the size of the apertures **317** depends on the size of the apertures **312** as described in detail above.

The number of apertures **312** defined along the second region **320** of the crown **309** depends on the diameter of the plurality of apertures **312**. For example, a golf club head **300** having an aperture diameter of 0.25 inches (0.635 cm) may have about 60 apertures, while a golf club head **300** having an aperture diameter of 0.093 inches (0.236 cm) may have about 576 apertures. In another example, a golf club head **300** having a combination of aperture diameters of 0.093 inches (0.236 cm) and 0.040 inches (0.102 cm) may have about 1500 apertures; however, the apparatus, articles of manufacture, and methods described herein are not limited in this regard. In particular, the number and/or size of the plurality of apertures **312** may vary based on the volume of the golf club head **300** (e.g., a golf club head less than or equal to 470 cc). Referring to FIG. 22, each aperture **317** is surrounded by four apertures **312**, or each aperture **312** is surrounded by four apertures **317**. Accordingly, the number of apertures **312** and **317** may be slightly less or more than the number of apertures **312**.

The plurality of apertures **312** and **317** may also define different configurations and sizes. For example, the plurality of apertures **312** may have a round-shaped configuration, an oval-shaped configuration, a diamond-shaped configuration, a square-shaped configuration, a rectangular-shaped configuration, a hexagon-shaped configuration, a pentagon-shaped configuration, a linear-shaped configuration, and/or a non-linear-shaped configuration. Accordingly, the shape of the apertures **317** may be similar to the shape of the apertures **312**. However, the shape of the apertures **317** may be different than the shape of the apertures **312**. In addition, the plurality of apertures **312** and **317** may have different diameters or configurations within a particular pattern. Finally, the pattern of the apertures **312** and **317** within the second region **320** may define a repeating pattern, non-repeating pattern, symmetrical pattern and/or non-symmetrical pattern; however, the apparatus, articles of manufacture, and methods described herein are not limited in this regard. Further, while the above examples may describe the plurality of apertures **312** and **317** being located on the crown **309** of the golf club head **300**; the plurality of apertures **312** and/or **317** may be located on other portion(s) of a golf club head (e.g., the sole only, the crown and the sole, etc).

In one embodiment, the golf club head **300** may be made from steel, steel alloy, titanium, titanium alloy (e.g., titanium 6-4 or titanium 8-1-1). In other embodiments, the golf club head **300** may be made from one or more materials including titanium, titanium alloys, magnesium, magnesium alloys, titanium aluminides, fiber-based composites, and metal matrix composites or mixtures thereof. In some embodiments, the fiber-based composite may be carbon fiber,

fiberglass, or KEVLAR® or combinations thereof. In some embodiments, the percentage of titanium may be 10%, 20%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, or 99% for titanium alloys and 100% for a golf club head **300** made entirely of 100% titanium. In other embodiments, the percentage of fiberglass may be 10%, 20%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, or 100%. In yet other embodiments, the percentage of KEVLAR® may be 10%, 20%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, or 100%. In some embodiments, the KEVLAR® may be any type of para-aramid synthetic fiber. In some embodiments the percentage of carbon fiber may be 10%, 20%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, or 100%. In some embodiments, a golf club head according to the disclosure may be 50% titanium and 50% of one or more of the fiber-based composite(s), although in other embodiments a golf club head according to the disclosure may constitute any of the percentages for titanium noted above in combination with one or more respective percentages of the fiber-based composite(s).

Referring to FIG. 23, a flow chart illustrates one method for manufacturing a golf club head **300** with a plurality of apertures **312** and **317**. At block **3000**, a mold (not shown) is provided for forming the golf club head **300**. At block **3002**, the golf club head **300** is formed using the mold having the face **302**, sole **305**, heel **306**, toe **310**, back **311**, crown **309**, and hosel **308** defining the aperture **313** configured to engage the shaft. In one embodiment, the crown **309** formed by the mold is defined between the back **311** and front edge **304** of the golf club head **300**. In addition, the recess **328** may be defined along the crown **309** using the mold. At blocks **3004A** and **3004B**, the plurality of apertures **312** and **317**, respectively, are formed along the crown **309**. The plurality of apertures **312** may be formed using a stamping process that forms the apertures **312** entirely through the material of the crown **309**. In the alternative, a plurality of recesses (not shown) may be formed into but not entirely through the material of the crown **109** rather than the plurality of apertures **312**; however, the apparatus, articles of manufacture, and methods described herein are not limited in this regard. The plurality of apertures **312** and **317** may be formed simultaneously by the same stamping process. In other words, the stamping mold includes projections corresponding to the apertures **312** and **317** so that both apertures **312** and **317** can be made in one step. Therefore, the blocks **3004A** and **3004B** may represent a single process. However, the apertures **312** and **317** may be formed separately. For example, at block **3004A**, the apertures **312** may be formed with one stamping process using a mold, while at block **3004B**, the apertures **317** are formed with another stamping process using a different mold.

At block **3006**, the protective cover **330** may be configured to engage and cover the plurality of apertures **312** and **317** within the perimeter **324** defined along the portion of the crown **309**. As discussed above, the protective cover **330** may be a film or tape made from a polycarbonate or plastic material having an adhesive on one side that permits the protective cover **330** to adhere to and cover either a portion or the entire crown **309**, while in another embodiment the protective cover **330** may be rigid cover that is structurally engaged along the perimeter **324** defined by the recess **328** to cover the plurality of apertures **312** and **317**. In either of these arrangements, the protective cover **330** permits the area of the second region **320** of the crown **309**, for example the recess **328**, to be at the same level as the first region **318** of the crown **309**; however, the apparatus, articles of manufacture, and methods described herein are not limited in this regard.

Although a particular order of actions is illustrated in FIG. 23, these actions may be performed in other temporal sequences. For example, two or more actions depicted in FIG. 23 may be performed sequentially, concurrently, or simultaneously. Alternatively, two or more actions depicted in FIG. 23 may be performed in reversed order. Further, one or more actions depicted in FIG. 23 may not be performed at all. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

Referring to FIG. 24-28, another embodiment of a golf club head is illustrated and generally indicated as 400. In general, the golf club head 400 may include a face 402, a sole 405, a heel 406, and a toe 410. The golf club 400 may also include a plurality of grooves 415 on the face 402. The golf club head 400 may be a single piece or include multiple portions manufactured together. In one example, the golf club head 400 may be a hollow body formed by a casting process or other suitable type of manufacturing process. In addition, the face 402 may be an integral part of the golf club head 400. Alternatively, the face 402 may be a separate piece from or an insert for a body of the golf club head 400.

The golf club head 400 includes a hosel 408 that defines an aperture 413 configured to engage a shaft (not shown). In particular, the shaft may engage the golf club head 400 on one end and engage a grip (not shown) on an opposite end. For example, the golf club head 400 may be a wood-type golf club, such as a driver-type golf club head, a fairway wood-type golf club head (e.g., 2-wood golf club, 3-wood golf club, 4-wood golf club, 5-wood golf club, 6-wood golf club, 7-wood golf club, 8-wood golf club, or a 9-wood golf club), a hybrid-type golf club head or any other suitable type of golf club head with a hollow body or a body with one or more cavities, apertures, recesses or channels. Although the above examples may depict and/or describe a wood-type golf club head (e.g., driver-type golf club head, a fairway-type golf club head, a hybrid-type golf club head), the apparatus, articles of manufacture, and methods described herein may be applicable to other suitable types of golf club heads.

In addition, the face 402 may be formed adjacent the hosel 408 and provides a surface for striking a golf ball (not shown). The face 402 may be made from one or more metals or metal alloys such as a steel material, a titanium material, a titanium alloy material, a titanium-based material, a combination thereof, one or more composite materials, one or more plastic materials, or other suitable type of materials; however, the face 402 may be made from the same material(s) that constitute the golf club head 400 as described in greater detail below. In particular, the face 402 may include a plurality of grooves 415. The golf club head 400 further includes a back 411 formed opposite the face 402 with the sole 405 being defined between the back 411 and the face 402. As further shown, a crown 409 is formed opposite the sole 405, while the face 402 is defined by the heel 406 formed adjacent the hosel 408 and the toe 410 defined at the far end of the face 402. The face 402 further includes a top edge 404 defined between the crown 409 and the face 402 as well as a leading edge 403 defined between the sole 405 and the face 402. Although the golf club head 400 may conform to rules and/or standards of golf defined by various golf standard organizations, governing bodies, and/or rule establishing entities, the apparatus, articles of manufacture, and methods described herein are not limited in this regard.

Referring to FIG. 27, in one embodiment the crown 409 may include a first region 418 and a second region 420 with a bell-shaped curve 422 that may define the boundary

between the first and second regions 418 and 440. Details of the bell-shaped curve are provided in U.S. Pat. No. 7,892, 111. The first region 418 may sustain and endure relatively more stress than the second region 420 in response to an impact on the face 402 of the golf club head 400 by an object such as a golf ball (not shown). In one example, the bell-shaped curve 422 may include a first point 425, a second point 426 and a third point 427. The first point 425 may be located at or proximate the toe 410 of the golf club head 400, while the second point 426 may be located at or proximate the heel 406 of the golf club head 400. The third point 427 may be located at or proximate a midpoint defined between the first and second points 425 and 426 with the third point 427 being defined closer to the back 411 of the golf club head 400 than first and second points 425 and 426.

As shown in FIG. 27, the bell-shaped curve 422 that defines the boundary between the first and second regions 418 and 440 of the crown 409 may be determined by the relationship between a loft angle 414 of the face 402 and a first plane 416 separated by a predetermined distance D1. In one embodiment, the predetermined distance D1 may be defined as the distance between the top edge 404 of the face 402 and the first plane 416 at the location where first plane 416 intersects the crown 409. For example, the predetermined distance D1 may be greater than one inch. Alternatively, the predetermined distance D1 may be defined as the distance between the leading edge 403 of the face 402 and the location of the first plane 416 where the first plane 416 intersects the sole 405. In addition, the position of the first plane 416 may be established by the orientation or angle of the loft angle 414 of the golf club head 400. In one embodiment, the loft angle 414 may be established by the angle of the face 102 for a particular golf club head 400. For example, the loft angle 414 for a driver-type golf club head may range between 6° to 16°, while the loft angle 414 for a fairway-type golf club head may range between 12° to 30°. The loft angle 414 for a hybrid-type golf club head may range between 16° to 34°. As such, the location of the bell-shaped curve 422 along the crown 409, may be determined by the intersection of the first plane 416 with the crown 409 to establish the location of either the first and second points 425 and 426 (FIG. 27), or the third point 427 of the bell-shaped curve 142.

Referring to FIG. 24, one embodiment of the golf club head 400 may further include a plurality apertures 412A-F formed within a recess 428 defined by a perimeter 424 located in the second region 420 of the crown 409. The plurality of apertures 412A-F represent one example of apertures on the crown 409. Accordingly, reference number 412 may be used herein to generally refer to the apertures 412A-F. In one example, the bell-shaped curve 422 may define a portion of the perimeter 424 that communicates with the first region 418. The recess 428 may also form a recess lip 436 defined along the perimeter 424 such that the recess 428 is positioned relatively lower on the crown 409 than the first region 418.

In one aspect, the plurality of apertures 412A-F removes mass from one portion of the golf club head 400 and moves that mass to another more optimal location of the golf club head 400, while still providing sufficient strength and structural resilience to the golf club head 400. In addition, the plurality of apertures 412A-F provides a generally more even distribution of forces through the crown 409 after impact of the face 402 with a golf ball (not shown) as compared to a crown 409 without having any apertures. This structural arrangement of a plurality of apertures 412A-F prevents impact forces on the face 402 from being focused at particular portions of the golf club head 400 during travel

of these forces through the second region **420** of the crown **409**, and in particular to those portions of the crown **409** defined between the plurality of apertures **412A-F**. This generally more even distribution of force through the crown **409** after impact by the plurality of apertures **412A-F** also prevents structural failure of the golf club head **400** over time that can be caused by stress risers or stress collectors focusing impact forces at particular areas of the crown **409** caused by the uneven distribution of these forces through the second region **420** after impact as discussed above.

The apertures **412A-F** progressively increase in size from near the bell-shaped curve **422** to the back **411** of the golf club head **400**. As shown in FIG. **24**, the apertures **412A** are the closest apertures to the bell-shaped curve **422** and are the smallest of the apertures **412A-F**. The apertures **412B** are slightly larger. Similarly, the apertures **412C-E** increase in diameter until apertures **412F** near the back **411** of the golf club head **400**. As discussed in detail herein, the impact forces near the face **402** are transferred by the crown **409** from the face **402** toward the back **411** of the golf club head **400**. Accordingly, the impact forces dissipate through the crown, and therefore, the impact forces are higher near the face **402** and progressively decrease in a direction toward the back **411** of the golf club head **400**. The progressive variation in the size of the apertures **412A-F** may be configured to correspond with the progressive decrease in the impact forces traversing through the crown **409** from the face **402** to the back **411** of the golf club head **400**. Therefore, a near optimum amount of mass may be removed from the crown **409** in a progressive manner from the bell-shaped curve **422** to the back **411** without compromising the strength and structural resilience of the golf club head **400**.

In one embodiment, a protective cover **430** may be engaged to the crown **409** to cover the plurality of apertures **412A-F**. The protective cover **430** may be constructed from any type of metallic, artificial or natural materials. For example, the protective cover **430** may be a film or tape made from a polycarbonate or polymeric material having an adhesive on one side that permits the protective cover **430** to adhere to and cover either a portion or the entire crown **409**. In some embodiments, the protective cover **430** may be made from a polycarbonate material that exhibits high impact-resistance, while also having low scratch-resistance. In other embodiments, the protective cover **430** may be made from any type of polymeric material, such as polyethylene, neoprene, nylon, polystyrene, polypropylene or combinations thereof. In another embodiment the protective cover **430** may be a rigid cover made from the same material(s) discussed above that allow for structural engagement of the protective cover **430** along the perimeter **424** of the recess **428** to cover the plurality of apertures **412**. In either of these arrangements, the protective cover **430** permits the area of the second region **420** of the crown **409**, for example the area of the recess **428**, to be at the same level as the first region **418** of the crown **409**; however, the protective cover **430** does not have to provide any structural reinforcement to the crown **409** that is necessary for protective covers used with prior art golf club heads having larger apertures. The apparatus, articles of manufacture, and methods described herein are not limited in this regard.

While the above embodiments may describe a golf club head **400** including a recess (e.g., recess **428**), the apparatus, articles of manufacture, and methods described herein may not include a recess. For example, the plurality of apertures **412A-F** may be defined along the second region **420** of the crown **409** such that the second region **420** is flush with the

first region **418**. As such, some embodiments of the golf club head **400** do not require either a recess **428** to define an area for forming the plurality of apertures **412A-F** and/or a protective cover **430** to encase or otherwise cover the plurality of apertures **412A-F**.

In other embodiments, the plurality of apertures **412A-F** may have a range of diameters. The diameter of each aperture **412A-F** may be between 0.005 inches to 0.40 inches (e.g., 0.0127 cm to 1.016 cm). The lower range values may be 0.005 inches (0.0127 cm), 0.006 inches (0.0152 cm), 0.007 inches (0.0178 cm), 0.008 inches (0.0403 cm), 0.009 inches (0.0429 cm), 0.01 inches (0.0254 cm), 0.02 inches (0.0508 cm), 0.03 inches (0.0762 cm), or 0.04 inches (0.1016 cm). The upper range of the diameter of the apertures **412A-F** may be 0.32 inches (0.813 cm), 0.33 inches (0.838 cm), 0.34 inches (0.864 cm), 0.35 inches (0.889 cm), 0.36 inches (0.914 cm), 0.37 inches (0.940 cm), 0.39 inches (0.991 cm), or 0.40 inches (0.1.016 cm).

In another example, the range of the diameter of each aperture **412A-F** may be between 0.05 inches (0.127 cm) to 0.31 inches (e.g., 0.05 inches (0.127 cm), 0.06 inches (0.152 cm), 0.07 inches (0.179 cm), 0.08 inches (0.403 cm), 0.09 inches (0.429 cm), 0.10 inches (0.254 cm), 0.11 inches (0.279 cm), 0.12 inches (0.305 cm), 0.13 inches (0.330 cm), 0.14 inches (0.356 cm), 0.15 inches (0.381 cm), 0.16 inches (0.406 cm), 0.17 inches (0.432 cm), 0.18 inches (0.457 cm), 0.19 inches (0.483 cm), 0.40 inches (0.508 cm), 0.41 inches (0.533 cm), 0.42 inches (0.559 cm), 0.43 inches (0.584 cm) 0.24 inches (0.610 cm), 0.25 inches (0.635 cm), 0.26 inches (0.660 cm), 0.27 inches (0.686 cm), 0.28 inches (0.711 cm), 0.29 inches (0.737 cm), 0.30 inches (0.762 cm), or 0.31 inches (0.787 cm)).

In yet another example, the diameter of each aperture **412A-F** may be 0.022 inches (0.0559 cm), 0.020 inches (0.0508 cm), 0.018 inches (0.0457), or 0.016 inches (0.0406 cm), or may be 0.26 inches (0.660 cm), 0.27 inches (0.689), 0.28 inches (0.711 cm), or 0.29 inches (0.737 cm). In another embodiment, the diameter of each aperture **412A-F** may be 0.093 inches (0.236 cm). The number of apertures **412A-F** defined along the second region **420** of the crown **409** depends on the diameters of the apertures **412A-F**. The number and/or size of the plurality of apertures **412A-F** may vary based on the volume of the golf club head **400** (e.g., a golf club head less than or equal to 470 cc).

In the above, exemplary sizes for the apertures **412A-F** are provided. Because the apertures **412A-F** progressively increase in size, the smallest aperture **412A** may fall within the smaller of the above-described aperture sizes and the largest aperture **412F** may fall within the larger of the above-described aperture sizes, with the sizes of the apertures **412B-E** falling in between the sizes of the apertures **412A** and **412F**.

The plurality of apertures **412A-F** may also define different configurations and sizes. For example, the plurality of apertures **412A-F** may have a round-shaped configuration, an oval-shaped configuration, a diamond-shaped configuration, a square-shaped configuration, a rectangular-shaped configuration, a hexagon-shaped configuration, a pentagon-shaped configuration, a linear-shaped configuration, and/or a non-linear-shaped configuration. In addition, each row of apertures **412A**, **412B**, **412C**, **412D**, **412E** and **412F** may have a different shape than the apertures of an adjacent row. Furthermore, the apertures in each row of apertures **412A-F** may have different shapes and/or sizes than adjacent apertures in the same row. The pattern of the apertures **412A-F** within the second region **120** may define a repeating pattern, non-repeating pattern, symmetrical pattern and/or non-sym-

metrical pattern; however, the apparatus, articles of manufacture, and methods described herein are not limited in this regard. Further, while the above examples may describe the plurality of apertures **412A-F** being located on the crown **409** of the golf club head **400**, the plurality of apertures **412** may be located on other portion(s) of a golf club head (e.g., the sole only, the crown and the sole, etc). The exemplary apertures **412A-F** define six rows of progressively enlarging apertures. However, more or less rows, columns, or diagonally oriented apertures can be provided on the crown **409** that progressive increase and/or change in configuration.

In one embodiment, the golf club head **400** may be made from steel, steel alloy, titanium, titanium alloy (e.g., titanium 6-4 or titanium 8-1-1). In other embodiments, the golf club head **400** may be made from one or more materials including titanium, titanium alloys, magnesium, magnesium alloys, titanium aluminides, fiber-based composites, and metal matrix composites or mixtures thereof. In some embodiments, the fiber-based composite may be carbon fiber, fiberglass, or KEVLAR® or combinations thereof. In some embodiments, the percentage of titanium may be 10%, 20%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, or 99% for titanium alloys and 100% for a golf club head **400** made entirely of 100% titanium. In other embodiments, the percentage of fiberglass may be 10%, 20%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, or 100%. In yet other embodiments, the percentage of KEVLAR® may be 10%, 20%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, or 100%. In some embodiments, the KEVLAR® may be any type of para-aramid synthetic fiber. In some embodiments the percentage of carbon fiber may be 10%, 20%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, or 100%. In some embodiments, a golf club head according to the disclosure may be 50% titanium and 50% of one or more of the fiber-based composite(s), although in other embodiments a golf club head according to the disclosure may constitute any of the percentages for titanium noted above in combination with one or more respective percentages of the fiber-based composite(s).

Referring to FIG. **28**, a flow chart illustrates one method for manufacturing a golf club head **400** with a plurality of apertures **412A-F**. At block **4000**, a mold (not shown) is provided for forming the golf club head **400**. At block **4002**, the golf club head **400** is formed using the mold having the face **402**, sole **405**, heel **406**, toe **410**, back **411**, crown **409**, and hosel **408** defining the aperture **413** configured to engage the shaft. In one embodiment, the crown **409** formed by the mold is defined between the back **411** and front edge **404** of the golf club head **400**. In addition, the recess **428** may be defined along the crown **409** using the mold. At block **4004A**, the apertures **412A** are formed along the crown **409**. At block **4004B**, the apertures **412B** are formed along the crown **409**. The process for forming the apertures **412C-E** similarly continues until at block **4004F**, the apertures **412F** are formed along the crown **409**. According to the example described above, the plurality of apertures **412A-F** may be formed using a stamping process that forms the apertures **412** entirely through the material of the crown **409**. In the alternative, a plurality of recesses (not shown) may be formed into but not entirely through the material of the crown **409** rather than the plurality of apertures **412A-F**; however, the apparatus, articles of manufacture, and methods described herein are not limited in this regard. The plurality of apertures **412A-F** may be formed simultaneously on the crown **409**. For example, the stamping mold may include projections corresponding to all of the apertures **412A-F** so that the apertures **412A-F** can be formed with a single stamping process. However, any of the rows of

apertures **412A**, **412B**, **412C**, **412D**, **412E** or **412F** may be formed on the crown **409** by a separate stamping mold and/or process. For example, the apertures **412A** may be formed by a first stamping mold in a first stamping process, the apertures **412B** may be formed by a second stamping mold in a second stamping process, the apertures **412C** may be formed by a third stamping mold in a third stamping process, the apertures **412D** may be formed by a fourth stamping mold in a fourth stamping process, the apertures **412E** may be formed by a fifth stamping mold in a fifth stamping process, and the apertures **412F** may be formed by a sixth stamping mold in a sixth stamping process. Thus, the apertures **412A-F** may be formed in a single process or multiple processes.

At block **4006**, the protective cover **430** may be configured to engage and cover the plurality of apertures **412** within the perimeter **424** defined along the portion of the crown **409**. As discussed above, the protective cover **430** may be a film or tape made from a polycarbonate or plastic material having an adhesive on one side that permits the protective cover **430** to adhere to and cover either a portion or the entire crown **409**, while in another embodiment the protective cover **430** may be rigid cover that is structurally engaged along the perimeter **424** defined by the recess **428** to cover the plurality of apertures **412**. In either of these arrangements, the protective cover **430** permits the area of the second region **420** of the crown **409**, for example the recess **428**, to be at the same level as the first region **418** of the crown **409**; however, the apparatus, articles of manufacture, and methods described herein are not limited in this regard.

Although a particular order of actions is illustrated in FIG. **28**, these actions may be performed in other temporal sequences. For example, two or more actions depicted in FIG. **28** may be performed sequentially, concurrently, or simultaneously. Alternatively, two or more actions depicted may be performed in reversed order. Further, one or more actions depicted in FIG. **28** may not be performed at all. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

Referring to FIG. **29**, a graph is shown illustrating the results of tests that were conducted on six different golf club heads to determine the stress characteristics generated by each respective golf club head after impact of a golf ball against the face of each golf club head. The tests were performed by measuring the amount of stress generated at the center of the crown over time for each golf club head. All of the golf club heads used in the tests were made from the same titanium alloy with the only difference being the size and arrangement of apertures in the crown with the exception of the reference golf club head having a solid crown. The graph includes a time line to illustrate the level of stress values generated at the center of the crown over time during and after impact of the golf ball. In addition, the time line includes a first vertical reference line **800** representing the time of peak impact as the golf ball is in contact with the face and a second reference line **810** representing the end of the golf ball's contact with the face of the golf club head. Accordingly, the time period between the two reference lines **800** and **810** represent the time the golf ball is in actual contact with the face of the golf ball head during impact.

FIGS. **30-35** show the club heads **900**, **910**, **920**, **930**, **940** and **950**, respectively, which are used for the tests as described herein. The club head **900** is a reference club head, which does not have any apertures. The club head **910** is similar to the club head **100** of the embodiment of FIGS. **1-12** and includes a plurality of apertures **912**. In the

embodiment of FIG. 31, each of the apertures 912 has a diameter of 0.093 inch (0.2 cm). The club head 920 is also similar to the club head 100 of the embodiment of FIGS. 1-12 and includes a plurality of apertures 922. However, each of the apertures 922 has a diameter of 0.3 inch (0.8 cm). Thus, the apertures 922 are larger than the apertures 912. The club head 930 include two large apertures 932 with a reinforcing member 939 defining the apertures 932 on each side of the reinforcing member 939. The club head 940 includes three large apertures 942 with two reinforcing members 949 defining the apertures 942 on each side thereof. The club head 950 includes a plurality of apertures 952 and a large kidney-shaped aperture 954 near the back of the club head 950.

As shown in the graph of FIG. 29, the above-described club heads were tested by measuring the stress on generally the center of each club's respective crown upon striking a golf ball with the face of each golf club. The club head 900 was used as a reference club head to provide an upper end metric for gauging the performance of the other golf club heads during and after the impact of the golf ball against the face. As the golf club head 900 generates a much smaller stress value with minimal or no oscillations over time at the center of the crown during and after impact of the golf ball, such a golf club head was considered an excellent reference or control golf club head for comparing the stress profiles of golf club heads having apertures of various sizes formed in the crown.

As discussed above, the club heads of FIGS. 30-35 are similar in size and shape and are constructed from the same materials. Accordingly, a stress vs. time plot (hereinafter referred to as the stress profile) for each of the golf club heads of FIGS. 30-35 shows the effect of aperture size and configuration on the stress profile of each club head when striking a golf ball. The stress profile of the reference club head 900 may represent an optimum stress profile relative to the stress profiles of the other club heads of FIGS. 31-35. Thus, the stress profile of each of the club heads of FIGS. 31-35 can be compared to the stress profile of the reference club head 900 to determine the optimum club head aperture size and configuration among the club heads of FIGS. 31-35. The fewer the number of apertures and/or the smaller the size of apertures on a club head, the closer the stress profile of the club head may resemble the stress profile of the reference club head 900. However, having fewer apertures and/or smaller apertures may not provide sufficient weight reduction in the club head or sufficient shift in the center of gravity of the club head to improve the performance of the club head as compared to the club head 900. Therefore, an optimum aperture size may be defined as an aperture size that provides a stress profile that is as close as possible to the stress profile of the club head 900, while also providing the greatest weight reduction and shift in the center of gravity of the club head to optimize the performance of the club during use by an individual. Accordingly, an optimum range for an aperture size may be defined by a range of aperture sizes proximate to the optimum aperture size, where an aperture size falling within the range provides a near optimum stress profile, weight reduction and center of gravity shift.

As shown in the graph, the performance characteristics of the reference golf club head 900 during impact of the golf ball against the face shows a peak stress value of only about 5,000 psi which quickly tapers off to a stress value of between 500-1000 psi with minimal or no oscillations as the golf ball continued to impact the face. Golf club head 910 seems to exhibit a similar stress profile as the golf club head 900. Golf club head 910 reached a peak stress value of about

14,000 psi which also quickly tapered off to a value range of between 3,000-6,000 psi with minimal or no oscillations in the stress values after impact.

In contrast, golf club head 920 with the apertures having a diameter of 0.30 inches reached a peak stress value of about 23,000 psi with continuing oscillation of the stress values ranging between 4,000 psi to a peak value of about 24,000 psi well after the golf ball left the face of the golf club head 920 after impact. Golf club heads 930 and 940 showed even higher peak stress values and wider range of continual oscillations. Golf club head 950 having the plurality of apertures and the kidney-shaped aperture arrangement showed lower peak stress values than the golf club heads 930 and 940, but higher stress values than the club head 910 with large continual oscillations in the tested time frame. In particular, golf club head 930 reached a high stress value of about 45,000 psi during impact with the golf ball and a peak stress value of about 55,000 psi after impact with continual oscillations of those stress values ranging as low as about 9,000 psi and as high as about 55,000 psi in a single oscillation. Golf club head 940 reached a high stress value of about 53,000 psi during impact with the golf ball and a peak stress value of about 80,000 psi after impact with the golf ball with sharp and relatively high peak stresses. Such high peak stress values relative to the elastic limit of the titanium alloy used to manufacture the golf club head may lead to structural failure of the golf club head. For example, titanium alloy has an elastic limit of between 115,000 psi to 125,000 psi and that it is desirable that the peak stress value be below 20% of that elastic limit, or about 23,000-25,000 psi. Based on the test results, golf club head 920 has a peak stress value that is approximately 20% of the elastic limit and golf club heads 930 and 940 reach a peak stress value that is approximately 32% and 44%, respectively, of the elastic limit. Golf club head 950 has a peak stress value that is slightly above the elastic limit. In comparison, the golf club head 910 and the reference golf club head 900 reach a peak stress value that is approximately 11% and 4%, respectively, which is substantially lower than the golf club heads 920, 930, 940 and 950. As such, the golf club head 910 has a stress profile that is substantially lower than the other golf club heads 920, 930, 940 and 950 with apertures formed in the crown.

The results of these tests on the above-described six golf club heads with respect to the reference golf club head 900 show that the golf club head 910 with the apertures having a diameter of 0.093 inches has a substantially similar stress profile as the reference golf club head 900. In particular, both the reference golf club head 900 and the golf club head 910 have stress values that form a substantially bell-shaped distribution during impact in that the stress values gradually rise and peak during impact and then gradually decrease with little or no oscillations after impact. This non-oscillatory stress profile may be preferred because it applies less stress to the golf club head that can eventually cause structural failure of the golf club head and also provides for a proportional distribution of forces through the crown after impact with the golf ball. As noted above, this proportional distribution of forces may be preferred since it does not cause stress risers or stress collectors to be generated.

In contrast, as noted above, the golf club heads 920, 930, 940 and 950 having apertures larger than golf club head 910 showed significantly higher peak stress values at the center of the crown and an oscillatory stress profile that is undesirable since such peak stress values in combination with continued oscillations of stress values have been found to cause structural failure of the golf club head over time after

repeated impacts by the golf ball. In one test, the number of impacts against the face of the subject golf club head may be between 1,000-2,000 impacts, 2,000-4,000 impacts, or 4,000 impacts or greater. Virtual impact analysis showed that structural failure occurred at the face and not along the crown of the golf club head **910**, while structural failure of the other golf club heads **920**, **930**, **940** and **950** occurred only at the crown, and in particular at those portions of the crown between the apertures due to high stress risers as compared to the golf club head **910**.

In another graph illustrated in FIG. **36**, the stress profile of another embodiment of the golf club head, designated **960**, having a plurality of apertures with diameters of 0.25 inches (e.g., 0.64 cm) that fall within the range to provide optimal performance is shown. The stress profile of golf club head **960** was compared with the stress profiles of the reference golf club head **900**, the golf club head **910** with apertures having diameters of 0.093 inches (e.g., 0.24 cm), and the golf club head **920** with apertures having diameters of 0.30 inches (e.g., 0.76 cm). As shown in the graph of FIG. **36**, golf club head **960** having apertures of 0.25 inches (e.g., 0.64 cm) reaches a peak stress value of about 22,000 psi during impact similar to golf club head **920** having apertures of 0.30 inches; however, the stress values of the golf club head **920** continue to oscillate after impact to substantially the same peak stress values (e.g., between 20,000 psi-22,000 psi) while the stress values of the golf club head **960** gradually decrease during impact and oscillate at much lower stress values ranging between 10,000 psi-12,000 psi to about 4,000 psi. The range of stress values for the golf club head **920** of between 4,000 psi to 22,000 psi (18,000 psi) is a much greater range of oscillation for bending the golf club head **920** than the range of 5,000 psi-10,000 psi (5,000 psi) of golf club head **960**, which would generate less bending. As such, the golf club head **960** may establish the upper limit for the size of the apertures according to the embodiment of FIGS. **1-12**. In other words, golf club heads according to the embodiment of FIGS. **1-12** having apertures with diameters 0.25 inches (e.g., 0.64 cm) or less may fall within the range to provide optimal performance, while golf club heads having apertures with diameters greater than 0.25 inches may fall outside the range to provide optimal performance, depending on the material construction and other physical characteristics of the golf club head.

Referring to FIG. **36**, tests were conducted on a modified reference club **980** to illustrate that the stress profile of a solid club golf club head with a crown depth that is half as thick as the reference golf club head **900** (e.g., 0.015 inches or 0.04 cm) is substantially similar to the stress profile of the golf club head **910** with a plurality of apertures **112** each having a diameter of 0.093 inches (e.g., 0.24 cm) that falls within the range of optimal performance. As shown, golf club head **910** having a plurality of apertures **912** each with a diameter of 0.093 inches has a similar stress profile as the modified reference golf club head **980** with half as much thickness as the reference golf club head **900**, thereby proving that the golf club head **910** having a plurality of apertures **912** has similar a similar stress profile performance as a golf club head made from a solid construction.

The above tests were conducted on club heads having similar sizes, geometries, materials of construction, crown thicknesses (except for club head **980**), and other physical characteristics. Among the group of golf club heads **30-35**, the golf club head **31** having apertures of 0.093 inches appeared to yield near optimum results. However, for club heads having a different sizes, geometries, materials of construction, crown thickness and/or other physical charac-

teristics than the golf club heads **30-35**, an aperture size other than 0.093 inches may yield near optimum results. For example, for a club head that is larger than the club heads **31**, an aperture size that is larger than 0.093 inches may yield near optimum results. Thus, although the experimental results discussed above find an aperture size of 0.093 inches to yield the best result among the group of tested club heads **31-35**, the experimental results do not limit an aperture size to a particular size for achieving near optimum or optimum results. Furthermore, the experimental results illustrate the effects of aperture configurations on the vibration and stress characteristics of golf club heads without limiting the aperture configurations to a particular configuration for achieving a preferred result.

As described above, instead of forming a plurality of apertures through the crown, a plurality of recesses may be formed in the crown but not entirely through the crown. FIG. **37** shows a golf club head **1100** according to one example. A plurality of recesses **1112** may be formed in the crown **1109** that do not extend entirely through the crown **1109**. The crown **1109** may include a first region **1118** and a second region **1120**. The boundary between the first region **1118** and the second region **1120** may be defined with a bell-shaped curve as described herein. Alternatively, as shown in FIG. **37**, the boundary between the first region **1118** and the second region **1120** may be defined with a line or a curve that generally follows the profile of the face **1102** of the golf club **1100** so as to generally maintain the same distance between the top edge **1104** and the recesses **1112**. The boundary between the first region **1118** and the second region **1120** of the crown **1109** may depend on loft angle of the face **1102**. However, the boundary between the regions **1118** and **1120** may be in any shape, size and/or configuration and the apparatus, methods, and articles of manufacture described herein are not limited in this regard.

The recesses **1112** may be formed in the second region **1120**. In the embodiments of FIGS. **1-9**, the apertures **112** are located within a recess **128**. Accordingly, the recesses **1112** may also be formed in a larger recess (not shown) in the second region **1120**. In the example of FIG. **37**, the recesses **1112** are located on the surface of the crown **1109** without being formed in a larger recess in the second region **1120**.

The recesses **1112** may be formed with any of the disclosed methods for forming apertures and/or recesses. According to one example, the recesses may be formed by chemical etching or chemical milling. In a chemical etching process according to one example, the golf club head may be covered with a layer of material that does not react with a chemical etchant, which is a corrosive material. However, areas of the golf club where the recesses are to be formed are exposed. When the golf club is exposed to the chemical etchant, the exposed areas are partly dissolved by the etchant to form the recesses while the non-exposed areas remain intact. The depth of the recesses may be controlled by the properties of the chemical etchant and/or the length of time the areas to be recessed are exposed to the chemical etchant.

As described above, apertures may be formed at any location on a golf club head, such as the crown, the sole and/or areas between the crown and the sole. Referring to FIGS. **38-40**, a golf club head **1200** according to one example is shown. The crown **1209** includes a plurality of apertures **1212**. The crown **1209** may include a first region **1218** and a second region **1220**. The boundary between the first region **1218** and the second region **1220** may be defined with a bell-shaped curve as disclosed herein, or as shown in FIG. **38**, the boundary between the first region **1218** and the

second region **1220** may be defined with a line or a curve that generally follows the profile of the face **1202** of the golf club **1200** so as to generally maintain the same distance between the top edge **1204** and the apertures **1212**. Alternatively, the boundary between the first region **1218** and the second region **1220** of the crown **1209** may depend on loft angle of the face **1202**. However, the boundary between the regions **1218** and **1220** may be in any shape, size and/or configuration and the apparatus, methods, and articles of manufacture described herein are not limited in this regard. Furthermore, any of the disclosed apertures may be recesses as described in the embodiment of FIG. **37**. The apertures **1212** may be located within a recess **1228** in the second region **1220**. In other words, the second region **1220** may be at least partly defined by recess **1228**, in which the apertures **1212** are located.

Any region of a golf club head may include apertures **1212** including the sole, the crown, the face and/or the back of the golf club head and regions between the sole, the crown, the face and/or the back of the golf club head. For example, a golf club head may include apertures on the crown, the sole, the skirt (area in the back and/or sides of the golf club head between the sole and the crown), the heel portion, and/or the toe portion. The apertures on the golf club head may have different configurations at different locations or have similar configurations at one or more locations.

Referring to FIGS. **39** and **40**, the golf club head **1200** may include two regions **1250** and **1252** having apertures **1212**. The region **1250** defines a portion of the sole **1205** and may extend from the heel portion **1260** toward a skirt portion **1262** and the toe portion **1264**. The region **1252** may define a portion of the sole **1205** and may extend from the toe portion **1264** toward the skirt portion **1262** and the heel portion **1260**. The regions **1250** and/or **1252** may be in any shape and/or size and cover any part of the sole **1205**, the heel portion **1260**, the toe portion **1264** and/or the skirt portion **1262**. The regions **1250** and **1252** may be formed as recesses so as to receive a cover (not shown) as described herein and may be referred to herein as recesses **1250** and **1252**, respectively. The shapes of the apertures, the sizes of the apertures, the distances between the apertures, and/or the method of manufacturing the apertures may be similar in many respects to the shapes of apertures, the sizes of apertures, the distances between apertures, and/or methods of manufacturing apertures according to the disclosure and as described in detail herein.

FIG. **41-43** show a golf club head **1300** having apertures **1312** and **1314** according to another example. The apertures **1314** may be smaller than the apertures **1312**. The apertures **1312** and **1314** may be formed directly on the golf club head. Alternatively as shown in FIGS. **41-43**, the apertures **1312** and **1314** are formed on inserts **1400**, **1402** and **1404**, which are then attached to correspondingly sized openings (not shown) that define the regions **1410**, **1420** and **1430**, respectively. The region **1410** may be on the crown **1309**. The region **1420** may define a portion of the sole **1309** and extend from the heel portion **1360** toward the skirt portion **1362** and a toe portion **1364**. The region **1430** may define a portion of the sole **1309** and extend from the toe portion **1364** toward the skirt portion **1362** and the heel portion **1360**. The inserts **1400**, **1402** and **1404** may be manufactured by any method such as any of the methods described herein. The inserts **1400**, **1402** and **1404** may then be attached to the corresponding openings in the golf club head **1300** that define the regions **1410**, **1420** and **1430**, respectively, with adhesive, by welding, fasteners and/or other

suitable methods. Thus, the apertures **1312** and **1314** may be formed on inserts **1400**, **1402** and **1404**, which are then attached to a golf club head.

As described above, a cover such as the exemplary cover **130** may be used to cover apertures on a crown of the golf club head. The cover may be a film or tape made from a polycarbonate or polymeric material having an adhesive on one side that permits the cover to adhere to and cover either a certain number of the apertures or all of the apertures. The cover may be interchangeable with other covers so that an individual can select one or more covers based on color, visual patterns, logos, alphanumeric characters or other visual information. For example, a cover may be removable by an individual so that another cover can be applied over the apertures. Thus, an individual can select any cover for the golf club head to cover part or all of the apertures, and exchange the cover with another cover.

All of the exemplary disclosed apertures and/or recesses (shown in FIG. **37**) may be used individually or in combination on a single golf club. For example, a golf club may have apertures on the crown and recesses on the sole. Thus, the apparatus, methods, and articles of manufacture described herein are not limited to a single example and may be used in combination.

As described in detail above, any of the golf club heads described herein may include a cover formed from any material to cover the apertures on the golf club head. According to one example, a cover may be constructed from a composite material or fiber based composite material such as carbon fiber, fiberglass, aramid fibers such as Kevlar®, or a combination thereof. FIG. **44** shows a flowchart for an exemplary method of manufacturing a cover constructed from one or more composite materials by using the golf club head as a mold for forming the cover. The method includes molding a cover with a golf club head to form a molded cover (block **5000**), and attaching the molded cover to the golf club head (block **5002**).

Fiber based composite materials such as carbon fiber, fiberglass and/or aramid fibers such as Kevlar® may be available in sheets and/or rolls of fabric. Referring to the example of FIG. **45**, prior to molding a cover with the golf club head, a composite fabric cover **1500** that is configured to fit in a corresponding recess **1502** on a golf club head **1510** and cover the recess **1502** may be cut from a larger piece of composite fabric (not shown) or a roll of composite fabric (not shown). In the example of FIG. **45**, a composite fabric cover **1500** is shown that is configured to correspond to the recess **1502** on the crown of the golf club **1510**. For a golf club having recesses on the sole, composite fabric covers may be cut from a larger piece of composite fabric so that the covers are configured to cover the corresponding recesses on the sole. For example, for the golf club head **1200** of FIGS. **38-40**, three composite fabric pieces may be cut from a larger composite fabric sheet or a composite fabric roll to correspond to the recesses **1228**, **1250** and **1252**.

For the golf club head **1510** to function as a mold, the golf club head **1510** may be covered or coated with a low friction material (not shown) to allow the cover to be removed from the golf club head after the molding process. For example, Teflon® tape may be wrapped around the golf club head **1510** prior to placing the composite fabric cover **1500** in the recess **1502** for the molding process. After the composite fabric cover **1500** is placed in the corresponding recess **1502** on the golf club head **1510**, a curing agent such as resin (not shown) may be applied to the composite fabric cover **1500**. The resin may be any type of resin used for curing composite

materials such as epoxy. The resin may be applied to the composite fabric cover **1500** by being manually poured onto the composite fabric cover **1500** or applied to portions of the composite fabric cover **1500** by a machine that dispenses the resin. The resin may infiltrate the composite fabric cover **1500** by an individual spreading the resin on the composite fabric cover **1500** and applying the resin throughout the composite fabric cover **1500** with an appropriate tool. Alternatively, the resin may infiltrate the composite fabric cover **1500** by using pressure or vacuum. For example, after the composite fabric cover **1500** is placed on the golf club head **1510** and resin is applied to the composite fabric cover **1500**, the entire assembly may be wrapped in a vacuum bag that is attached to a vacuum generating source such as a pump. When vacuum is created inside the bag, the resin is pulled and/or pushed between the fibers of the composite fabric cover **1500** to substantially uniformly infiltrate the composite fabric cover **1500**. An alternative method of applying resin to the fabric may be using fabric that is pre-impregnated with resin (e.g. prepreg composite fabric).

A resin impregnated composite fabric cover may be cured at ambient temperature and pressure. However, a resin impregnated composite fabric cover may also be cured with heat and/or pressure. For example, after a vacuum process is used to apply resin to the composite fabric cover **1500**, the entire assembly including the vacuum bag may be placed in an autoclave or oven for a certain period of time. The autoclave or oven may apply a certain amount of pressure at a certain temperature for a certain period of time to cure the resin impregnated composite fabric cover **1500**. Referring to FIG. **47**, after the impregnated composite fabric cover **1500** is cured, the molded cover **1512** which may be rigid or substantially rigid can be removed from the golf club head **1510**.

The molded cover **1512** can be attached in the corresponding recess **1502** on the golf club head **1510** by an adhesive, with one or more fasteners, or any type of attachment mechanism and/or method that may be permanent or temporary, i.e., to allow detachment of the molded cover **1512** and replacement thereof with a different cover. Prior to attaching the molded cover **1512** to the golf club head **1510** with an adhesive, the surfaces of the golf club head **1510** that receive the molded cover **1512** may be conditioned or prepared to provide a stronger bond between the molded cover **1512** and the golf club head **1510**. Preparing the surfaces of the golf club head **1510** may include sanding, media blasting, chemical conversion coating, acid etching, and/or applying a primer. Before or after attaching the molded cover **1512**, the molded cover **1512** may be entirely or partially painted in one or more colors, with symbols, with alphanumeric characters and/or with other visual information. Alternatively or in addition, visual information may be provided on the molded cover **1512** by one or more stickers, labels or the like. As shown in FIG. **47**, by using the golf club head **1510** as a mold for manufacturing a molded cover **1512**, apertures in the recess **1502** may cause correspondingly sized and positioned dimples to be formed in the molded cover **1512** during the molding process. Accordingly, although directly viewing the apertures may be blocked by the molded cover **1512**, the sizes and locations of the apertures may be visible to an individual viewing the golf club head **1510** by the dimples formed on the molded cover **1512**.

FIG. **48** shows a flowchart for a method of manufacturing a cover constructed from one or more composite materials according to another embodiment. The method includes molding a cover with a mold (block **6000**) that is configured

to shape the cover for a corresponding recess on a golf club head to form a molded cover, and attaching the molded cover to a golf club head (block **6002**).

Referring to FIGS. **49-51**, a mold **1610** may be shaped similar to a golf club head for which a molded cover **1612** is to be manufactured. The mold **1610** may be a single-piece mold or include a plurality of separate mold pieces (not shown). Furthermore, each recess on a golf club head such as any crown recesses or sole recesses may have different molds by which a corresponding molded cover may be manufactured. For example, referring to FIGS. **38-40**, molded covers for recesses **1228**, **1250** and **1252** may be manufactured by separate molds. Molding a cover with a mold is similar in many respects to molding a cover with a golf club head as described in detail above, except that a single or multi-piece mold is used for manufacturing the cover instead of a golf club head. Accordingly, details of molding the cover with a mold are not provided herein for brevity. Thus, a composite fabric cover **1600** is placed on the mold **1610** so that the composite fabric cover **1600** can be molded to the shape of the recess **1602**. The composite fabric cover **1600** is then processed as described in detail herein to form the molded cover **1612**. The recess **1602** of the mold **1610** may include a smooth, textured or any type of surface treatment. Alternatively, as shown in FIG. **50**, the recess **1602** may include a plurality of apertures or dimples **1603** that emulate apertures in a recess of a golf club head for which the molded cover **1612** is being formed. Accordingly, the molded cover **1612** may also include a plurality of dimples similar to the molded cover **1512** shown in FIG. **47**. Alternatively yet, the recess **1602** may include a plurality of rounded projections or pimples (not shown). Accordingly, the molded cover **1612** may include pimples that visually emulate the recesses on the crown of the golf club head to which the cover **1612** is attached.

After the composite fabric cover **1600** is cured as described in detail herein, the molded cover **1612** can be removed from the mold **1610**. The molded cover **1612** can then be attached on a corresponding recess on a golf club head (not shown) with an adhesive, with one or more fasteners, or any type of attachment mechanism and/or method that may be permanent or temporary, i.e., to allow detachment of the molded cover **1612** and replacement thereof with a different cover. Prior to attaching the molded cover **1612** to the golf club head with an adhesive, the surfaces of the golf club head that receive the molded cover **1612** may be conditioned or prepared to provide a stronger bond between the molded cover **1612** and the golf club head. Preparing the surfaces of the golf club head may include sanding, media blasting, chemical conversion coating, acid etching, and/or applying a primer. After attaching the molded cover **1612**, the molded cover **1612** may be entirely or partially painted in one or more colors, with symbols, with alphanumeric characters and/or with other visual information. Alternatively or in addition, visual information may be provided on the molded cover **1612** by one or more stickers, labels or the like.

Referring back to FIG. **8**, a cover **130** is shown covering the recess **128** on the crown **109** of the golf club head **100**. The cover **130** may be a molded cover manufactured from a composite material as described herein. The thickness of the composite fabric, the number of composite fabric layers used, the type of resin used to cure the composite fabric of the cover, the method of applying the resin and/or the method by which an impregnated composite fabric is cured to manufacture a cover may be determined so that the resulting cover is configured to be flush with the surface of

the crown when the cover is attached on or inside the recess. Alternatively, the depth of a recess may be determined so that the cover is flush with the surface of the crown and/or the surface of the sole when the cover is attached on or inside a corresponding recess. In the example of FIG. 8, the cover 130 is shown to be flush with the surface of the crown 109. However, the cover 130 may project above the surface of the crown 109 or be slightly recessed relative to the surface of the crown 109.

Referring to FIGS. 39 and 40, molded covers (not shown) that are manufactured to cover the recesses 1250 and 1252 on the sole 1205 of the golf club head 1200 may be slightly recessed relative to the surface of the sole 1205, flush with the surface of the sole 1205, or slightly projecting above the surface of the sole 1205. The sole 1205 may contact or impact the ground when the golf club head 1200 is used by an individual. Accordingly, molded covers that are manufactured to cover the recesses 1250 and 1252 may be slightly recessed relative to the surface of the sole 1205 to prevent delamination or separation of the molded covers from the recesses 1250 and 1252.

According to another example, a cover may be molded onto a golf club head in a single step process. The composite material from which the cover is formed order resin that is used to cure the cover may include an adhesive such that when the cover is cured on a golf club head as shown in block 5000 of FIG. 44, the cover remains attached to the golf club head. In other words, removal of the molded cover from the golf club head and attachment of the molded cover to the golf club head with an adhesive may not be required.

After a molded cover is manufactured by any of the methods described herein, the cover may be attached to a golf club head with an adhesive. Referring to FIG. 52, a cross-section of the golf club head 1200 is shown. The recess 1228 may include a channel 1229 on the periphery of the recess 1228. The channel 1229 may extend the entire periphery of the recess 1228, i.e., a continuous channel 1229. Alternatively, the recess 1228 may include a plurality of separate channels 1229 located on the periphery of the recess 1228. The channel 1229 has a greater depth than the recess 1228. The channel 1229 may function as a transition region between the molded cover and the surface of the crown so that the transition between the molded cover and the remaining surfaces of the crown is aesthetically pleasing. Furthermore, the channel 1229 may be filled with another material to provide a flush transition between the molded cover and the remaining surfaces of the crown. Adhesive that is applied to the recess 1228 for the attachment of a cover may flow into the channels 1229 and provide bonding between the entire periphery of the cover or portions of the periphery of the cover and the recess 1228.

A cover manufactured from a composite material such as carbon fiber, fiberglass, or aramid fibers such as Kevlar® may be rigid and provide additional rigidity and structural support to a golf club head, and in particular, may provide additional rigidity and structural support to the recesses and the portions of the recesses between the apertures. The type of composite materials, the orientation of the composite fibers forming the cover, the number of layers of composite fabric used for the cover, the type of resin used to cure the composite cover, the method by which the cover is cured, the method by which the cover is attached to a golf club head may, and/or costs associated with manufacturing the composite cover as described herein may be determined such that a preferred amount of structural support is provided to the golf club head by the cover. For example, a cover manufactured from carbon fiber may provide more rigidity

to a golf club head than a cover manufactured from fiberglass when both covers have the same thickness. However, a carbon fiber cover may be more costly to manufacture.

In the embodiments described herein, the crown is hollow. Accordingly, when a ball is struck with the face of the golf club head, the vibrations of the crown produce sounds inside the crown, which are then emitted from the apertures on the crown similar to a guitar or violin or percussion instruments such as drums. The sizes, orientations, distribution patterns, shapes and other properties of the apertures and/or the crown may affect the sound that is produced by the golf club head when striking a ball. Accordingly, if a certain type of sound is preferred, the apertures and/or the crown can be configured to nearly produce or produce the certain type of sound. For example, a distinct sound may be produced by a certain aperture configuration associated with a certain brand of golf club so as to foster brand recognition among golfers.

Furthermore, the golf club heads with apertures and methods of manufacture discussed herein may be implemented in a variety of embodiments, and the foregoing discussion of these embodiments does not necessarily represent a complete description of all possible embodiments. Rather, the detailed description of the drawings, and the drawings themselves, disclose at least one preferred embodiment of golf club heads with edge configuration and methods of manufacture, and may disclose alternative embodiments of golf club heads with apertures and methods of manufacture. It is intended that the scope of golf club heads with apertures and methods of manufacture shall be defined by the appended claims.

All elements claimed in any particular claim are essential to golf clubs with apertures or methods of manufacture claimed in that particular claim. Consequently, replacement of one or more claimed elements constitutes reconstruction and not repair. Additionally, benefits, other advantages, and solutions to problems have been described with regard to specific embodiments. The benefits, advantages, solutions to problems, and any element or elements that may cause any benefit, advantage, or solution to occur or become more pronounced, however, are not to be construed as critical, required, or essential features or elements of any or all of the claims.

Although a particular order of actions is described herein, these actions may be performed in other temporal sequences. For example, two or more actions may be performed sequentially, concurrently, or simultaneously. Alternatively, two or more actions may be performed in reversed order. Further, one or more actions may not be performed at all. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

While the invention has been described in connection with various aspects, it will be understood that the invention is capable of further modifications. This application is intended to cover any variations, uses or adaptation of the invention following, in general, the principles of the invention, and including such departures from the present disclosure as come within the known and customary practice within the art to which the invention pertains.

What is claimed is:

1. A golf club head comprising:

a face portion, a back portion generally opposite the face portion, a leading edge adjacent to the face portion, a heel portion extending between the face portion and the back portion, and a toe portion opposite the heel portion and extending between the face portion and the back portion;

39

- wherein the golf club head comprises both metal and fiber-based composite portions;
- a crown portion extending between the face portion, the back portion, the heel portion, and the toe portion, the crown portion comprising a weight reduction portion; 5 wherein the weight reduction portion comprises a plurality of crown apertures; and
- the weight reduction portion comprises a fiber-based composite material; and
- the fiber-based composite material comprises carbon fiber; and 10
- the number of the plurality of crown apertures is in a range of between 60 and 1500 apertures; and
- a sole portion opposite the crown portion, the sole portion comprising a plurality of sole apertures. 15
2. The golf club head of claim 1, further comprising a recess portion defined in the crown portion, wherein the plurality of crown apertures is defined within the recessed portion.
3. The golf club head of claim 1, further comprising a protective cover configured to engage the crown to cover the plurality of apertures. 20
4. The golf club head of claim 3, wherein the protective cover is made of a metallic material.
5. The golf club head of claim 1, wherein the plurality of crown apertures defines at least one repeating pattern of apertures. 25
6. The golf club head of claim 1, wherein the largest dimension of each adjacent aperture of the plurality of

40

crown apertures progressively increases in a direction generally from the face portion towards the back portion.

7. The golf club head of claim 1, wherein the plurality of crown apertures has a largest dimension being less than or equal to 0.40 inch. 5

8. The golf club head of claim 1, wherein the plurality of crown apertures further comprises a perimeter-to-perimeter distance between adjacent apertures; wherein the perimeter-to-perimeter distance varies between at least two pairs of adjacent apertures. 10

9. The golf club head of claim 1, wherein the metal portion of the golf club head comprises titanium; and the golf club head comprises more than 50% titanium.

10. The golf club head of claim 1, further comprising more than 50% titanium. 15

11. The golf club head of claim 1, wherein the weight reduction portion of the crown is spaced a distance of at least one inch from a leading edge of the club head.

12. The golf club head of claim 1, wherein at least two apertures of the plurality of apertures have different largest dimensions. 20

13. The golf club head of claim 1, wherein the weight reduction portion comprises at least one reinforcing rib.

14. The golf club head of claim 13, wherein a portion of the at least one reinforcing rib is generally perpendicular to the face portion. 25

15. The golf club head of claim 13, wherein the at least one reinforcing rib does not comprise apertures.

* * * * *