

US010995563B2

(12) **United States Patent**
Søe et al.

(10) **Patent No.:** **US 10,995,563 B2**
(45) **Date of Patent:** **May 4, 2021**

(54) **ROTARY DRILL HEAD FOR COILED TUBING DRILLING APPARATUS**

(71) Applicant: **MINEX CRC LTD**, Kensington (AU)

(72) Inventors: **Søren Pham Søe**, South Australia (AU); **Shane Lee Fox**, South Australia (AU)

(73) Assignee: **MINEX CRC LTD**, Kensington (AU)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/476,786**

(22) PCT Filed: **Oct. 11, 2017**

(86) PCT No.: **PCT/AU2017/051098**

§ 371 (c)(1),

(2) Date: **Jul. 9, 2019**

(87) PCT Pub. No.: **WO2018/132862**

PCT Pub. Date: **Jul. 26, 2018**

(65) **Prior Publication Data**

US 2019/0360283 A1 Nov. 28, 2019

(30) **Foreign Application Priority Data**

Jan. 18, 2017 (AU) 2017900143

May 30, 2017 (WO) PCT/AU2017/050508

(51) **Int. Cl.**

E21B 19/08 (2006.01)

E21B 3/04 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **E21B 19/08** (2013.01); **B65H 75/425**

(2013.01); **B65H 75/4405** (2013.01); **E21B**

3/02 (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC . E21B 7/02; E21B 7/023; E21B 17/02; E21B 17/041; E21B 19/08; E21B 19/22; E21B 3/045

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,848,196 A 8/1958 Simmonds

3,517,760 A 6/1970 Kehrberger

(Continued)

FOREIGN PATENT DOCUMENTS

AU 2010100358 A4 5/2010

AU 2011101137 A4 10/2011

(Continued)

OTHER PUBLICATIONS

International Search Report for PCT/AU2017/051098, dated Dec. 6, 2017.

(Continued)

Primary Examiner — Robert E Fuller


Assistant Examiner — Lamia Quaim

(74) *Attorney, Agent, or Firm* — Marshall, Gerstein & Borun LLP

(57) **ABSTRACT**

A mobile, coiled tubing drilling apparatus with a rotary drill head, includes a non-rotating mast on a mobile platform. The mast has mounted thereon an injector below a coiled tubing reel. The injector defines an operational axis for the coiled tubing. The rotary drill head is pivotally mounted on the injector so as to be movable between a retracted position away from the operational axis and an operating position in line with the operational axis. The rotary drill head includes a top swivel for non-rotating connection to the coiled tubing and a bottom spindle for rotating connection to a pipe section. The top swivel and the bottom spindle provide fluid

(Continued)



communication between connected coiled tubing and connected pipe section during operation.

9 Claims, 8 Drawing Sheets

(51) **Int. Cl.**

B65H 75/42 (2006.01)
B65H 75/44 (2006.01)
E21B 7/02 (2006.01)
E21B 19/24 (2006.01)
E21B 19/22 (2006.01)
E21B 3/02 (2006.01)
E21B 15/00 (2006.01)

(52) **U.S. Cl.**

CPC **E21B 3/045** (2013.01); **E21B 7/02** (2013.01); **E21B 7/021** (2013.01); **E21B 7/023** (2013.01); **E21B 15/00** (2013.01); **E21B 19/22** (2013.01); **E21B 19/24** (2013.01); **B65H 2701/33** (2013.01)

(56)

References Cited

U.S. PATENT DOCUMENTS

3,557,885	A	1/1971	Cales	5,439,066	A	8/1995	Gipson
3,631,933	A	1/1972	Bryant	5,515,925	A	5/1996	Boychuk
3,658,270	A	4/1972	Slator et al.	5,515,926	A	5/1996	Boychuk
3,690,136	A	9/1972	Slator et al.	5,524,708	A	6/1996	Isaacs
3,765,486	A	10/1973	Dittmer et al.	5,524,716	A	6/1996	Wachholz
3,817,466	A	6/1974	Reynard et al.	5,547,314	A	8/1996	Ames
3,936,733	A	2/1976	Clary	5,553,668	A	9/1996	Council et al.
3,965,685	A	6/1976	D'Amiano	5,566,764	A	10/1996	Elliston
3,980,144	A	9/1976	Roos et al.	5,566,769	A	10/1996	Stuart
3,991,837	A	11/1976	Crickmer	5,575,332	A	11/1996	Wasterval, Jr.
3,995,701	A	12/1976	Kelly, Jr.	5,727,631	A	3/1998	Baker et al.
3,995,829	A	12/1976	Foik	5,738,173	A	4/1998	Burge et al.
4,015,672	A	4/1977	Kinnison	5,775,417	A	7/1998	Council
4,102,411	A	7/1978	Webb et al.	5,839,514	A	11/1998	Gipson
4,145,014	A	3/1979	Chatard et al.	5,865,392	A	2/1999	Blount et al.
4,173,130	A	11/1979	Downen et al.	5,875,850	A	3/1999	Burge et al.
4,248,312	A	2/1981	Jinno et al.	5,918,671	A	7/1999	Bridges et al.
4,249,600	A	2/1981	Bailey	5,931,229	A	8/1999	Lehr et al.
4,265,304	A	5/1981	Baugh	5,937,943	A	8/1999	Butler
4,279,314	A	7/1981	Taub	5,988,274	A	11/1999	Funk
4,304,310	A	12/1981	Garrett	6,000,480	A	12/1999	Eik
4,336,840	A	6/1982	Bailey	6,003,598	A	12/1999	Andreychuk
4,341,270	A	7/1982	Ferguson	6,009,941	A	1/2000	Haynes
4,476,945	A	10/1984	Hearn	6,142,406	A	11/2000	Newman
4,515,211	A	5/1985	Reed et al.	6,158,516	A	12/2000	Smith et al.
4,515,220	A	5/1985	Sizer et al.	6,209,633	B1	4/2001	Haynes
4,553,612	A	11/1985	Durham	6,209,634	B1	4/2001	Avakov et al.
4,585,061	A	4/1986	Lyons et al.	6,230,805	B1	5/2001	Vercaemer et al.
4,591,131	A	5/1986	Rhoads	6,431,286	B1	8/2002	Andreychuk
4,667,750	A	5/1987	Wise et al.	6,481,507	B1	11/2002	Kromray, Jr.
4,697,648	A	10/1987	Brandt	6,527,055	B1	3/2003	Gipson
4,756,366	A	7/1988	Maroney et al.	6,868,902	B1	3/2005	Roodenburg et al.
4,878,546	A	11/1989	Shaw et al.	6,932,553	B1	8/2005	Roodenburg et al.
4,889,193	A	12/1989	Shy	6,951,256	B1	10/2005	Xiao
4,923,005	A	5/1990	Laky et al.	7,152,672	B1	12/2006	Gipson
4,949,791	A	8/1990	Hopmann et al.	7,284,618	B2	10/2007	Geddes et al.
5,027,903	A	7/1991	Gipson	7,341,101	B1	3/2008	Moretz
5,090,039	A	2/1992	Gard et al.	7,681,632	B2	3/2010	Wood
5,094,302	A	3/1992	Back	7,753,344	B1	7/2010	Moretz et al.
5,115,861	A	5/1992	Laky	7,810,556	B2	10/2010	Havinga
5,133,405	A	7/1992	Elliston	8,544,537	B1	10/2013	Keast
H001116	H	12/1992	Love, Jr.	9,074,432	B1	7/2015	Crosby et al.
5,186,253	A	2/1993	Gustafson et al.	9,151,116	B1	10/2015	Galvez
5,211,203	A	5/1993	Vollweiler et al.	9,309,730	B2	4/2016	Korach et al.
5,211,248	A	5/1993	Nosewicz et al.	9,316,067	B1	4/2016	Lu et al.
5,303,783	A	4/1994	Begnaud et al.	2002/0000332	A1	1/2002	Merecka et al.
5,360,075	A	11/1994	Gray	2002/0074125	A1	6/2002	Fikes et al.
5,435,385	A	7/1995	Wilson	2002/0117308	A1	8/2002	Dallas
				2003/0006034	A1	1/2003	Neal
				2003/0010505	A1	1/2003	Gipson
				2003/0070841	A1	4/2003	Merecka et al.
				2003/0079883	A1	5/2003	McCulloch et al.
				2003/0106695	A1	6/2003	Fikes et al.
				2003/0121682	A1	7/2003	Carrancho
				2003/0159821	A1	8/2003	Andersen et al.
				2003/0168218	A1	9/2003	Head
				2003/0221822	A1	12/2003	Polsky et al.
				2003/0226667	A1	12/2003	Hill
				2004/0159443	A1	8/2004	Austbo et al.
				2004/0163805	A1	8/2004	Smith et al.
				2004/0173347	A1	9/2004	Dallas
				2004/0182574	A1	9/2004	Adnan et al.
				2004/0195007	A1	10/2004	Eppink
				2004/0206551	A1	10/2004	Carriere et al.
				2004/0211555	A1	10/2004	Austbo et al.
				2004/0211598	A1	10/2004	Palidis
				2004/0221994	A1	11/2004	Kauffman et al.
				2004/0244993	A1	12/2004	Crawford et al.
				2004/0262015	A1	12/2004	Mazzella et al.
				2005/0000693	A1	1/2005	Ravensbergen et al.
				2005/0051344	A1	3/2005	Goss
				2005/0072587	A1	4/2005	Clelland
				2005/0077039	A1	4/2005	Shahin et al.
				2005/0103529	A1	5/2005	Rossi
				2005/0126821	A1	6/2005	Davies
				2005/0161225	A1	7/2005	Cole et al.
				2005/0161230	A1	7/2005	Webre et al.
				2005/0205267	A1	9/2005	Dallas
				2005/0211430	A1	9/2005	Patton et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2005/0247455	A1	11/2005	Domann	2010/0032209	A1	2/2010	Rainey et al.
2005/0247456	A1	11/2005	Wise et al.	2010/0181078	A1	7/2010	McKee
2005/0252654	A1	11/2005	Watson	2010/0206583	A1	8/2010	Swietlik et al.
2005/0263281	A1	12/2005	Lovell et al.	2010/0254784	A1	10/2010	Orgeron et al.
2005/0269072	A1	12/2005	Folk et al.	2010/0270033	A1	10/2010	Angelle et al.
2005/0279507	A1	12/2005	Folk et al.	2010/0288868	A1	11/2010	Rutledge, Sr.
2006/0000619	A1	1/2006	Borst et al.	2011/0006149	A1	1/2011	Baugh
2006/0011350	A1	1/2006	Wiggins et al.	2011/0006150	A1	1/2011	Baugh
2006/0048933	A1	3/2006	Van Way	2011/0011320	A1	1/2011	Yemington
2006/0054315	A1	3/2006	Newman	2011/0036559	A1	2/2011	Wood et al.
2006/0065407	A1	3/2006	Rufey	2011/0048693	A1	3/2011	Wood
2006/0081368	A1	4/2006	Rosine et al.	2011/0048804	A1	3/2011	Weixler et al.
2006/0207767	A1	9/2006	Andreychuk	2011/0067887	A1	3/2011	Moncus et al.
2006/0231267	A1	10/2006	Wood	2011/0073299	A1	3/2011	Havinga
2006/0231268	A1*	10/2006	Wood	2011/0176874	A1	7/2011	Hebert
			E21B 7/02	2011/0188942	A1	8/2011	Millheim
			166/379	2011/0209651	A1	9/2011	Yemington
2006/0231269	A1	10/2006	Wood	2011/0253361	A1	10/2011	Matherne et al.
2006/0243490	A1	11/2006	Riel	2011/0253390	A1	10/2011	Boutwell et al.
2006/0249292	A1	11/2006	Guidry	2011/0278015	A1	11/2011	Mazzanti
2006/0254780	A1	11/2006	McWhorter et al.	2011/0280104	A1	11/2011	McClung, III
2006/0260844	A1	11/2006	Patton et al.	2011/0289994	A1	12/2011	Smith et al.
2006/0273213	A1	12/2006	Turk et al.	2012/0080180	A1	4/2012	Wood et al.
2006/0278387	A1	12/2006	Parker	2012/0103632	A1	5/2012	Havinga
2006/0283587	A1	12/2006	Wood et al.	2012/0103633	A1	5/2012	Korach et al.
2006/0283588	A1	12/2006	Wood et al.	2012/0145455	A1	6/2012	Mock et al.
2006/0283605	A1	12/2006	Wood et al.	2012/0247787	A1	10/2012	Lancaster
2006/0289170	A1	12/2006	Wood	2012/0275882	A1	11/2012	Orgeron et al.
2006/0289171	A1	12/2006	Wood et al.	2012/0301225	A1	11/2012	Millheim
2007/0095525	A1	5/2007	Austbo et al.	2012/0318531	A1	12/2012	Shampine et al.
2007/0113640	A1	5/2007	De et al.	2012/0325486	A1	12/2012	Gilmore et al.
2007/0114041	A1	5/2007	Wood et al.	2013/0068494	A1	3/2013	Hung
2007/0125549	A1	6/2007	Wood	2013/0092388	A1	4/2013	Gilmore et al.
2007/0125551	A1	6/2007	Havinga	2013/0121801	A1	5/2013	Gipson
2007/0125552	A1	6/2007	Wood et al.	2013/0133898	A1	5/2013	Travis et al.
2007/0131432	A1	6/2007	Pleskie	2013/0145718	A1	6/2013	Bryant et al.
2007/0137855	A1	6/2007	Nielsen et al.	2013/0175048	A1	7/2013	Goode et al.
2007/0187108	A1	8/2007	Zheng	2013/0181719	A1	7/2013	Wilson
2007/0193734	A1	8/2007	Dallas	2013/0186640	A1	7/2013	Webre et al.
2007/0193749	A1	8/2007	Folk	2013/0264837	A1	10/2013	Liess et al.
2007/0209791	A1	9/2007	Havinga	2013/0284459	A1	10/2013	Weintraub et al.
2007/0209840	A1	9/2007	Boys	2013/0299189	A1	11/2013	Reddy et al.
2007/0215359	A1	9/2007	Wood et al.	2013/0299244	A1	11/2013	Reddy et al.
2007/0221386	A1	9/2007	Rock et al.	2013/0302114	A1	11/2013	Reddy et al.
2007/0251700	A1	11/2007	Mason et al.	2013/0313846	A1	11/2013	Liess et al.
2007/0295497	A1	12/2007	Pleskie et al.	2013/0327543	A1	12/2013	Reddy et al.
2008/0006400	A1	1/2008	Coyle, Jr.	2013/0330132	A1	12/2013	Thommesen
2008/0023227	A1	1/2008	Patton	2013/0341000	A1	12/2013	Flusche
2008/0135228	A1	6/2008	Wells et al.	2013/0341002	A1	12/2013	Flusche
2008/0185184	A1	8/2008	Maguire	2013/0341003	A1	12/2013	Flusche
2008/0202812	A1	8/2008	Childers et al.	2013/0341013	A1	12/2013	Flusche
2008/0217061	A1	9/2008	Barbera	2013/0341040	A1	12/2013	Flusche
2008/0245575	A1	10/2008	Guidry	2013/0343837	A1	12/2013	Flusche
2008/0264626	A1	10/2008	Patton	2014/0000867	A1	1/2014	Andreychuk et al.
2008/0296013	A1	12/2008	Pleskie	2014/0000895	A1	1/2014	Misselbrook
2008/0302530	A1	12/2008	Shampine et al.	2014/0030025	A1	1/2014	Bernardoni
2008/0308281	A1	12/2008	Boutwell et al.	2014/0041853	A1	2/2014	Dineen
2009/0025980	A1	1/2009	Callander et al.	2014/0048247	A1	2/2014	Watson et al.
2009/0095491	A1	4/2009	Wood et al.	2014/0048276	A1	2/2014	Yemington
2009/0101361	A1	4/2009	Mason et al.	2014/0076533	A1	3/2014	Witte et al.
2009/0114403	A1	5/2009	Borst et al.	2014/0090674	A1	4/2014	Thomas et al.
2009/0126946	A1	5/2009	Borst et al.	2014/0116676	A1	5/2014	Placer et al.
2009/0129868	A1	5/2009	Millheim	2014/0116724	A1	5/2014	McDougall et al.
2009/0178853	A1	7/2009	Pavlik	2014/0138081	A1	5/2014	Yorga et al.
2009/0178854	A1	7/2009	Pavlik	2014/0140791	A1	5/2014	Yorga et al.
2009/0218106	A1	9/2009	Stukey et al.	2014/0151021	A1	6/2014	Yorga et al.
2009/0223679	A1	9/2009	Moncus et al.	2014/0230229	A1	8/2014	Dixson et al.
2009/0255688	A1	10/2009	Pleskie	2014/0238696	A1	8/2014	Borst et al.
2009/0272522	A1	11/2009	Ring et al.	2014/0238698	A1	8/2014	Jones et al.
2009/0288832	A1	11/2009	Comeaux et al.	2014/0241809	A1	8/2014	Millheim
2009/0294134	A1	12/2009	Jones et al.	2014/0305632	A1	10/2014	Pendleton
2009/0294136	A1	12/2009	Jones et al.	2015/0000894	A1	1/2015	Henderson
2009/0308618	A1	12/2009	Collie	2015/0027733	A1	1/2015	Sipos
2009/0321134	A1	12/2009	Matthews et al.	2015/0034391	A1	2/2015	McLain
2010/0000796	A1	1/2010	Boeck	2015/0060049	A1	3/2015	Saurer et al.
2010/0018721	A1	1/2010	Jennings et al.	2015/0075803	A1	3/2015	Remedio et al.
				2015/0129316	A1	5/2015	Harrington et al.
				2015/0159445	A1	6/2015	Smith et al.
				2015/0159447	A1	6/2015	Miller et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2015/0159452 A1 6/2015 Miller et al.
 2015/0176355 A1 6/2015 Trinh et al.
 2015/0184480 A1 7/2015 Welsh et al.
 2015/0240577 A1 8/2015 Hassard et al.
 2015/0267483 A1 9/2015 Bujold et al.
 2015/0267485 A1 9/2015 Bujold et al.
 2015/0300106 A1 10/2015 Martin et al.
 2015/0330161 A1 11/2015 Lancaster
 2016/0076314 A1 3/2016 Begnaud
 2016/0108674 A1 4/2016 Von et al.
 2016/0138347 A1 5/2016 Bjrnenak
 2016/0175906 A1 6/2016 Butler
 2016/0177640 A1 6/2016 Dixson et al.
 2017/0044838 A1 2/2017 Pionetti et al.

FOREIGN PATENT DOCUMENTS

AU 2012207042 B2 5/2013
 BR PI0602644 A 11/2006
 CA 953644 A 8/1974
 CA 1056808 A 6/1979
 CA 1190851 A 7/1985
 CA 2014121 A1 10/1990
 CA 2175267 A1 8/1997
 CA 2217413 A1 11/1997
 CA 2183033 A1 2/1998
 CA 2268597 A1 5/2000
 CA 2268557 A1 9/2000
 CA 2292214 A1 6/2001
 CA 2567855 A1 6/2001
 CA 2299765 A1 8/2001
 CA 2322916 A1 4/2002
 CA 2425448 A1 8/2004
 CA 2461977 A1 9/2005
 CA 2465927 A1 11/2005
 CA 2536945 A1 8/2007
 CA 2619207 A1 8/2008
 CA 2633883 A1 12/2008
 CA 2637330 A1 1/2010
 CA 2715613 A1 3/2012
 CA 2728494 A1 6/2012
 CA 2818286 A1 12/2013
 CA 2841375 A1 4/2015
 CA 2838221 A1 6/2015
 CA 2864254 A1 10/2015
 CA 2899223 A1 1/2016
 CA 2860717 A1 2/2016
 CA 2871298 A1 3/2016
 CA 2871825 A1 5/2016
 CA 2898701 A1 5/2016
 CN 2878646 Y 3/2007
 CN 1987038 A 6/2007
 CN 1995689 A 7/2007
 CN 2937438 Y 8/2007
 CN 200964788 Y 10/2007
 CN 201003369 Y 1/2008
 CN 101424163 A 5/2009
 CN 101525978 A 9/2009
 CN 201326376 Y 10/2009
 CN 201486489 U 5/2010
 CN 101737009 A 6/2010
 CN 201574686 U 9/2010
 CN 201581800 U 9/2010
 CN 101858196 A 10/2010
 CN 201606001 U 10/2010
 CN 201650164 U 11/2010
 CN 201679452 U 12/2010
 CN 201730538 U 2/2011
 CN 102003143 A 4/2011
 CN 102031784 A 4/2011
 CN 102220848 A 10/2011
 CN 102287151 A 11/2011
 CN 202047764 U 11/2011
 CN 102287132 A 12/2011
 CN 202073514 U 12/2011

CN 202090870 U 12/2011
 CN 102364028 A 2/2012
 CN 202156464 U 3/2012
 CN 202165034 U 3/2012
 CN 202228019 U 5/2012
 CN 202249735 U 5/2012
 CN 202325234 U 7/2012
 CN 202370427 U 8/2012
 CN 102756952 A 10/2012
 CN 202578488 U 12/2012
 CN 102996065 A 3/2013
 CN 102996084 A 3/2013
 CN 202810717 U 3/2013
 CN 202832281 U 3/2013
 CN 202833897 U 3/2013
 CN 103016044 A 4/2013
 CN 202913941 U 5/2013
 CN 202913988 U 5/2013
 CN 202946054 U 5/2013
 CN 103147702 A 6/2013
 CN 203050487 U 7/2013
 CN 203114156 U 8/2013
 CN 203114158 U 8/2013
 CN 203161129 U 8/2013
 CN 203161130 U 8/2013
 CN 203175407 U 9/2013
 CN 103334708 A 10/2013
 CN 103352668 A 10/2013
 CN 103362437 A 10/2013
 CN 203239255 U 10/2013
 CN 103382809 A 11/2013
 CN 203285328 U 11/2013
 CN 103670264 A 3/2014
 CN 103670272 A 3/2014
 CN 203475431 U 3/2014
 CN 203487527 U 3/2014
 CN 203531804 U 4/2014
 CN 203547524 U 4/2014
 CN 203603802 U 5/2014
 CN 103865500 A 6/2014
 CN 103939006 A 7/2014
 CN 203701988 U 7/2014
 CN 203769643 U 8/2014
 CN 203783492 U 8/2014
 CN 104047554 A 9/2014
 CN 203822224 U 9/2014
 CN 203879423 U 10/2014
 CN 203891755 U 10/2014
 CN 203905805 U 10/2014
 CN 203905853 U 10/2014
 CN 203905862 U 10/2014
 CN 104153727 A 11/2014
 CN 203961820 U 11/2014
 CN 104295229 A 1/2015
 CN 104295241 A 1/2015
 CN 204126562 U 1/2015
 CN 204163657 U 2/2015
 CN 104420843 A 3/2015
 CN 204212686 U 3/2015
 CN 104533280 A 4/2015
 CN 204311968 U 5/2015
 CN 204357378 U 5/2015
 CN 104775773 A 7/2015
 CN 104790890 A 7/2015
 CN 204457496 U 7/2015
 CN 104863122 A 8/2015
 CN 204532161 U 8/2015
 CN 204571885 U 8/2015
 CN 204609789 U 9/2015
 CN 204691673 U 10/2015
 CN 105041203 A 11/2015
 CN 105064908 A 11/2015
 CN 105064934 A 11/2015
 CN 105114011 A 12/2015
 CN 105156029 A 12/2015
 CN 105178847 A 12/2015
 CN 105178849 A 12/2015
 CN 204827270 U 12/2015
 CN 204960798 U 1/2016

(56)

References Cited

FOREIGN PATENT DOCUMENTS

CN	205012942	U	2/2016	GB	1482441	A	8/1977
CN	205100870	U	3/2016	GB	2032494	A	5/1980
CN	105484663	A	4/2016	GB	2235229	A	2/1991
CN	205259970	U	5/2016	GB	2283517	A	5/1995
CN	105625967	A	6/2016	GB	2286847	A	8/1995
DE	2241527	A1	3/1973	GB	2289296	A	11/1995
DE	2420016	A1	10/1975	GB	2296518	A	7/1996
DE	2500614	A1	7/1976	GB	2299600	A	10/1996
DE	2614920	A1	10/1976	GB	2302076	A	1/1997
DE	2751564	A1	5/1978	GB	2315083	A	1/1998
DE	2815149	A1	11/1978	GB	2336864	A	11/1999
DE	2731170	A1	1/1979	GB	2343466	A	5/2000
DE	2801132	A1	7/1979	GB	2345708	A	7/2000
DE	2845878	A1	4/1980	GB	2349660	A	11/2000
DE	2947837	A1	7/1981	GB	2362405	A	11/2001
DE	3326350	A1	1/1984	GB	2391239	A	2/2004
DE	3329313	A1	2/1984	GB	2401354	A	11/2004
DE	3249432	A1	7/1984	GB	2411157	A	8/2005
DE	3503893	C1	10/1985	GB	2431418	A	4/2007
DE	3511846	A1	10/1986	GB	2431419	A	4/2007
DE	3521148	A1	12/1986	GB	2434819	A	8/2007
DE	3612762	A1	10/1987	GB	2447115	A	9/2008
DE	4018735	A1	11/1991	GB	2460311	A	12/2009
DE	4333114	C1	10/1994	GB	2460318	A	12/2009
DE	19813902	C1	6/1999	GB	2472310	A	2/2011
DE	29914363	U1	1/2000	GB	2520512	A	5/2015
DE	19947497	A1	4/2001	JP	06-050074	A	2/1994
DE	10144809	A1	3/2003	JP	06-235216	A	8/1994
DE	202004016711	U1	3/2005	JP	08-326456	A	12/1996
DE	102005039790	B3	1/2007	JP	09-250287	A	9/1997
DE	202008009050	U1	9/2008	JP	11-350864	A	12/1999
DE	102009054183	A1	11/2010	JP	2008-075287	A	4/2008
DE	102011000320	A1	7/2012	KR	10-2005-0120551	A	12/2005
DE	202011100196	U1	8/2012	KR	10-0728103	B1	6/2007
DE	202012007532	U1	9/2012	KR	10-2009-0028200	A	3/2009
DE	102011100358	A1	11/2012	KR	10-2009-0090886	A	8/2009
DK	201370253	A1	11/2014	KR	10-0942174	B1	2/2010
EP	0100230	A2	2/1984	KR	10-2013-0122121	A	11/2013
EP	0103283	A2	3/1984	KR	10-1613313	B1	4/2016
EP	0150977	A2	8/1985	NL	7405988	A	1/1975
EP	0162001	A1	11/1985	NL	145010	B	2/1975
EP	0190669	A2	8/1986	NL	8802005	A	3/1990
EP	0192253	A1	8/1986	NL	1020310	C2	10/2003
EP	0353152	A1	1/1990	NO	19996260	L	6/2000
EP	0427304	A1	5/1991	RU	1774985	A	11/1992
EP	0517329	A1	12/1992	RU	01813163	A	4/1993
EP	0526743	A1	2/1993	RU	2002022	C1	10/1993
EP	0534919	A1	3/1993	RU	2004769	C1	12/1993
EP	0740049	A2	10/1996	RU	2018656	C1	8/1994
EP	0953725	A2	11/1999	RU	2061834	C1	6/1996
EP	1020616	A2	7/2000	RU	2067153	C1	9/1996
EP	1098064	A1	5/2001	RU	2078902	C1	5/1997
EP	1990502	A2	11/2008	RU	2081293	C1	6/1997
EP	2236734	A1	10/2010	RU	2109915	C1	4/1998
EP	2757229	A1	7/2014	RU	2225825	C2	3/2004
EP	2806098	A2	11/2014	RU	2235185	C2	8/2004
EP	2818626	A1	12/2014	RU	2235186	C2	8/2004
EP	2930299	A1	10/2015	RU	2352751	C2	4/2009
EP	3034778	A1	6/2016	RU	2366791	C2	9/2009
FR	2243322	A1	4/1975	RU	2369713	C1	10/2009
FR	2283301	A1	3/1976	RU	101485	U1	1/2011
FR	2422773	A1	11/1979	RU	2435922	C1	12/2011
FR	2430385	A1	2/1980	RU	2010144731	A	5/2012
FR	2469551	A1	5/1981	RU	2453673	C1	6/2012
FR	2491043	A1	4/1982	SE	8406491	L	6/1986
FR	2492043	A1	4/1982	SE	8702686	L	12/1988
FR	2509783	A1	1/1983	SU	477234	A1	7/1975
FR	2512495	A1	3/1983	SU	487996	A1	10/1975
FR	2650335	A1	2/1991	SU	540032	A1	12/1976
FR	2702563	A1	9/1994	SU	613096	A1	6/1978
FR	2721348	A1	12/1995	SU	621866	A1	8/1978
FR	2741907	A1	6/1997	SU	649837	A1	2/1979
FR	2975121	A1	11/2012	SU	713991	A2	2/1980
FR	2986247	A1	8/2013	SU	732488	A1	5/1980
FR	3020396	A1	10/2015	SU	840279	A1	6/1981
				SU	939721	A1	6/1982
				SU	972077	A1	11/1982
				SU	1078049	A1	3/1984
				SU	1092272	A1	5/1984

(56)

References Cited

FOREIGN PATENT DOCUMENTS

SU 1137178 A1 1/1985
 SU 1265279 A1 10/1986
 SU 1411426 A1 7/1988
 SU 1469093 A1 3/1989
 SU 1566004 A1 5/1990
 SU 1620592 A1 1/1991
 SU 1686119 A1 10/1991
 SU 1761946 A2 9/1992
 WO 96/11322 A1 4/1996
 WO 96/28633 A2 9/1996
 WO 96/30624 A1 10/1996
 WO 97/10411 A1 3/1997
 WO 97/40255 A2 10/1997
 WO 97/42394 A1 11/1997
 WO 98/07954 A1 2/1998
 WO 98/07957 A1 2/1998
 WO 98/12410 A1 3/1998
 WO 98/13555 A1 4/1998
 WO 98/15713 A1 4/1998
 WO 98/33619 A1 8/1998
 WO 98/34005 A1 8/1998
 WO 99/11902 A1 3/1999
 WO 99/58810 A2 11/1999
 WO 00/03600 A2 1/2000
 WO 00/04269 A2 1/2000
 WO 00/05483 A1 2/2000
 WO 00/06868 A1 2/2000
 WO 00/22277 A1 4/2000
 WO 00/22278 A1 4/2000
 WO 00/34620 A1 6/2000
 WO 00/43632 A2 7/2000
 WO 00/47863 A1 8/2000
 WO 01/33033 A1 5/2001
 WO 01/34934 A2 5/2001
 WO 01/57355 A1 8/2001
 WO 01/69034 A2 9/2001
 WO 01/79652 A1 10/2001
 WO 01/89771 A1 11/2001
 WO 02/20938 A1 3/2002
 WO 02/79602 A1 10/2002
 WO 03/70565 A2 8/2003
 WO 03/80990 A1 10/2003
 WO 2004/044374 A1 5/2004
 WO 2004/048249 A1 6/2004
 WO 2004/057147 A2 7/2004
 WO 2004/070161 A1 8/2004
 WO 2004/074631 A1 9/2004
 WO 2005/021927 A1 3/2005
 WO 2005/038192 A1 4/2005
 WO 2005/100737 A1 10/2005
 WO 2005/110020 A2 11/2005
 WO 2006/027553 A1 3/2006
 WO 2006/133350 A2 12/2006
 WO 2007/093787 A1 8/2007
 WO 2007/106999 A1 9/2007
 WO 2008/068546 A1 6/2008
 WO 2008/127740 A2 10/2008
 WO 2009/001088 A1 12/2008

WO 2009/026449 A1 2/2009
 WO 2009/040569 A2 4/2009
 WO 2009/048319 A2 4/2009
 WO 2009/135217 A2 11/2009
 WO 2009/147040 A2 12/2009
 WO 2009/156722 A2 12/2009
 WO 2010/010326 A2 1/2010
 WO 2010/089573 A1 8/2010
 WO 2011/014440 A1 2/2011
 WO 2011/016719 A1 2/2011
 WO WO-2011097380 A1 8/2011
 WO 2011/103674 A1 9/2011
 WO 2011/135541 A2 11/2011
 WO 2012/060920 A1 5/2012
 WO 2012/075585 A1 6/2012
 WO 2013/022449 A1 2/2013
 WO 2013/081468 A1 6/2013
 WO 2013/101512 A1 7/2013
 WO 2013/125961 A1 8/2013
 WO 2013/142874 A1 9/2013
 WO 2013/173459 A1 11/2013
 WO 2014/025335 A1 2/2014
 WO 2014/066368 A2 5/2014
 WO 2014/073959 A1 5/2014
 WO 2014/089615 A1 6/2014
 WO 2014/179727 A1 11/2014
 WO 2014/179740 A1 11/2014
 WO 2014/186889 A1 11/2014
 WO 2015/016757 A1 2/2015
 WO 2015/016758 A1 2/2015
 WO 2015/057130 A2 4/2015
 WO 2015/076775 A1 5/2015
 WO 2015/086656 A2 6/2015
 WO 2015/093969 A1 6/2015
 WO 2015/100380 A1 7/2015
 WO 2015/113896 A2 8/2015
 WO 2015/113899 A2 8/2015
 WO 2015/113901 A2 8/2015
 WO 2015/117240 A1 8/2015
 WO 2015/164911 A1 11/2015
 WO 2016/081215 A1 5/2016

OTHER PUBLICATIONS

International Search Report for PCT/AU2017/050508, dated Sep. 11, 2017.
 First Office Action for Chile Application No. 201901979, dated Nov. 5, 2020.
 First Office Action and Search Report for Application No. 201780084038.3 issued to China, dated Sep. 22, 2020.
 Extended European Search Report for Application No. EPO 17892541.8, dated Sep. 18, 2020.
 First Office Action for Application No. 201901977 to Chile, dated Oct. 26, 2020.
 First Office Action for Application No. 201780084037.9 to China, dated Sep. 22, 2020.
 Extended European Search Report for European Application No. 17893326.3, dated Sep. 18, 2020.

* cited by examiner




FIGURE 1




FIGURE 2




FIGURE 3(a)




FIGURE 3(b)




FIGURE 4(a)




FIGURE 4(b)




Figure 5(a)




Figure 5(b)




Figure 6




Figure 7

ROTARY DRILL HEAD FOR COILED TUBING DRILLING APPARATUS

RELATED APPLICATION

This is the United States national phase of International Patent Application No. PCT/AU2017/051098, filed Oct. 11, 2017, which claims the priority benefit of Australian provisional patent application 2017900143 filed on 18 Jan. 2017 and International patent application PCT/AU2017/050508 filed on 30 May 2017. The entire contents of each of the foregoing are expressly incorporated herein by reference.

TECHNICAL FIELD

The present invention relates to a rotary drill head for a coiled tubing drilling apparatus, primarily for use in mineral exploration, the drilling apparatus being of the type where the coiled tubing is not required to rotate about its longitudinal axis in order for the drilling apparatus to operate.

BACKGROUND OF INVENTION

Mineral exploration has historically used rotating drill strings (being a series of attached, rigid, pipe sections) with drill bits attached at one end to drill subterranean holes in an effort to locate valuable mineral deposits. As a rotating drill bit drills into the earth to form a borehole, additional pipe sections are added in order to drill deeper, while the opposite occurs as the drill bit is withdrawn from the borehole. A significant amount of time and energy (and thus cost) are consumed in adding and removing these pipe sections to assemble and disassemble drill strings during drilling.

Coiled tubing has been developed as an alternative to the use of drill strings (albeit typically for use in the oil industry not for mineral exploration), the coiled tubing typically being a ductile metal available in virtually unlimited lengths. The use of coiled tubing involves the uncoiling of a tube from a reel carrying such tubing, typically by an injector located above and close to a borehole, the injector being responsible for raising and lowering the tubing. The reel is typically located horizontally away from the injector and the borehole, and a curved guide (often referred to as a “goose-neck”) is used between the reel and the injector to guide the tubing from the reel across the apparatus to the injector. An example of this can be seen in FIG. 6 of US patent publication 2013/0341001 A1.

In most coiled tubing drilling, a bottom hole assembly (BHA) located at the bottom of the tubing typically includes a mud motor that powers and rotates a drill bit (given that the coiled tubing does not rotate about its own longitudinal axis), the mud motor being powered by the motion of drilling fluid pumped from the surface through the coiled tubing. In other forms of coiled tubing drilling, above-ground apparatus has been developed to allow for the rotation of the coiled tubing about its longitudinal axis. Needless to say, substantial and complex above-ground apparatus is required to be able to rotate an entire reel of coiled tubing to achieve such rotation of the tubing, and the present invention does not relate to rotating coiled tubing drilling of this type.

However, in the normal operation cycle of even a “non-rotating” coiled tubing drilling apparatus, there is still often a need for drilling of the conventional type that uses rotating drill strings and thus the insertion and connection of multiple pipe sections down a borehole. Typically this need occurs at the commencement of drilling a borehole, such as during

drilling through the regolith. Also, it will be appreciated that even with coiled tubing drilling apparatus, there is still a need for the installation of casing, which typically requires the ability to insert and rotate multiple casing sleeves into a borehole and to subsequently inject cement or the like down the borehole through the casing sleeve to subsequently pass back up the borehole between the walls of the borehole and the exterior of the casing sleeve.

With coiled tubing drilling to date, this has typically required the use of additional fluid handling equipment associated with a traditional rotary drill head, such as that used to drill with conventional drill strings, so as to be able to provide both torque and drilling fluid to a bottom hole assembly. It is an aim of the present invention to avoid the use of such additional fluid handling equipment in non-rotating coiled tubing drilling apparatus.

Before turning to a summary of the present invention, it must be appreciated that throughout this description, terms such as “horizontal” and “vertical”, “upper” and “lower”, and “before” and “after” will be used. It should be understood that these and other similar orientation-type descriptive terms are made in relation to the orientation of an operational drill rig, which would normally be located on a reasonably flat (and thus horizontal) surface at ground level, and with respect to a normal tubing pathway on and off a reel and down and up a borehole. The terms are not, however, intended to bring operational limitations, or a requirement for parts of the apparatus to be perfectly horizontal or perfectly vertical.

Finally, it should also be noted that discussion of the background to the invention herein is included to explain the context of the invention. This is not to be taken as an admission that any of the material referred to was published, known or part of the common general knowledge as at the priority date of this application.

SUMMARY OF INVENTION

The present invention provides a mobile, coiled tubing drilling apparatus with a rotary drill head, the apparatus including a non-rotating mast on a mobile platform, the mast having mounted thereon an injector below a coiled tubing reel, the injector defining an operational axis for the coiled tubing, wherein the rotary drill head is pivotally mounted on the injector so as to be movable between a retracted position away from the operational axis and an operating position in line with the operational axis, the rotary drill head including a top swivel for non-rotating connection to the coiled tubing and a bottom spindle for rotating connection to a pipe section, the top swivel and the bottom spindle providing fluid communication between connected coiled tubing and connected pipe section during operation.

In another form, the present invention provides a mobile, coiled tubing drilling apparatus, the apparatus including a non-rotating mast on a mobile platform, the mast having mounted thereon an injector, a coiled tubing reel having a tubing pay-off point associated therewith, and a tubing control system, the injector defining an operational axis for the coiled tubing, wherein:

the tubing control system is between the reel and the injector, and includes a tubing abutment adjacent the tubing pay-off point for applying an opposite bend to the tubing during pay-out of the tubing; and the reel is mounted for horizontal (x,y) movement such that, during pay-out of the tubing, the tubing pay-off

point can be maintained generally above the injector, and can also be moved towards or away from the tubing abutment;

the apparatus also including a rotary drill head pivotally mounted on the injector so as to be movable between a retracted position away from the operational axis and an operating position in line with the operational axis, the rotary drill head including a top swivel for non-rotating connection to the coiled tubing and a bottom spindle for rotating connection to a pipe section, the top swivel and the bottom spindle providing fluid communication between connected coiled tubing and connected pipe section during operation.

During further description of the present invention, two modes of operation will be referred to. The first mode will be a coiled tubing drilling mode, where the coiled tubing is inserted down the borehole and fluid passed down the tubing powers the bottom hole assembly. The second mode will be a conventional rotating drill string mode where the coiled tubing connects to the top swivel of the rotary drill head and moves no further than that, while pipe sections are connected to the bottom spindle of the rotary drill head forming a rotating drill string for the bottom hole assembly. The use of the present invention allows for a relatively simple transition between the two operation modes, with relatively simple apparatus.

During the first mode of operation, the reel may be mounted for horizontal (x,y) movement such that, during pay-out of the tubing, the tubing pay-off point can be maintained generally above the injector but away from the injector's operational axis, the operational axis being defined by the pathway through the injector of the longitudinal axis of the tubing.

In contrast, and in relation to the re-coiling of the tubing that would occur during the first mode when the tubing is being withdrawn from the borehole, given that the tubing entering the injector from below has already been straightened, and thus is not subjected to the existing bend that is present with coiled tubing being uncoiled, it is envisaged that the tubing abutment need not be utilised by the apparatus during tubing take-up, and that a tubing take-on point (being essentially the same point during re-coiling as the tubing pay-off point during uncoiling) will actually be as close as operationally possible to a point along the injector's operational axis, and thus will be directly above the injector. During take-up, it will be appreciated that the only bend event that need be applied to the tubing is the bending created by the re-coiling itself.

Therefore, the reel may also mounted for horizontal (x,y) movement such that, during take-up of the tubing, the tubing take-on point can be maintained directly above the injector at a point along the injector's operational axis.

The tubing control system may include an adjustable tubing straightener after the tubing abutment and before the injector, the tubing straightener being adjustable such that it can engage tubing entering or exiting the injector and be utilised to provide more or less (or no) force to tubing entering or exiting the injector. For example, in one form, the adjustable tubing straightener will engage with tubing entering the injector (during pay-out), but not with tubing exiting the straightener (during take-up), for reasons that will be outlined below.

The tubing abutment may be fixed with respect to the mast so that the movement of the reel to maintain the tubing pay-off point generally above the injector during pay-out of the tubing also positions the tubing pay-off point of the reel adjacent the tubing abutment so that the tubing engages with

the tubing abutment. In this respect, this engagement with the tubing abutment places an opposite bend in the tubing during pay-out (such a bend being "opposite" to the bend in the tubing that already exists in the coiled tubing from it being coiled on the reel), which in the preferred form occurs before the tubing passes through the adjustable tubing straightener and the injector.

Still in relation to the first mode of operation, the application of this opposite bend to the tubing at a location closely adjacent to the tubing pay-off point has been found to minimise stress on the tubing (and thus increase the operational life of the tubing) while reasonably accurately aligning the tubing with the injector and, if present, the adjustable tubing straightener. Indeed, although an adjustable tubing straightener is required to be adjustable and is referred to as a straightener, in practice, because of the arrangement of the tubing abutment in the manner outlined above, it has been found that only minimal further stresses are added to the tubing if an adjustable tubing straightener is adopted, and which then tends to actually only require minimal adjusting and minimal straightening.

Additionally, the application of the opposite bend to the tubing at a location closely adjacent to the tubing pay-off point has been found to reduce any residual plastic bend remaining in the tubing before entering the injector and the borehole, assisting in avoiding subsequent difficulties with the control and direction of the borehole.

In contrast to this engagement of the tubing with the tubing abutment during pay-out, during take-up of the tubing it is preferred to avoid such engagement by moving the reel away from the tubing abutment (and out of engagement with it) such that, as mentioned above, the take-on point is maintained generally above the injector at a point along the injector's operational axis. Additionally, the tubing is ideally not engaged by the adjustable straightener during take-up. In this way, no additional bend event occurs to the tubing during take-up (via either the adjustable straightener or the tubing abutment), other than the bending of the tubing that occurs as the tubing is re-coiled back on to the reel.

In one form, the tubing abutment may be an elongate abutment beam, fixed generally vertically to the mast with an upper end and a lower end, and with the upper end being the end located adjacent the tubing pay-off point of the reel during operation. In this form, the uncoiling tubing will engage with the upper end of the abutment beam and will ideally be guided along the abutment beam to the injector (or an adjustable straightener, if present) during pay-out of the tubing. Preferably, the elongate abutment beam will be a substantially straight and elongate abutment beam, having a channel therealong that is capable of receiving and guiding therealong tubing from the reel.

In relation to the second mode of operation, being a rotating drill string mode where the coiled tubing connects to the top swivel of the rotary drill head and moves no further than that, while pipe sections are connected to the bottom spindle of the rotary drill head forming therebelow a rotating drill string, the fluid communication provided between connected coiled tubing and connected pipe section during operation permits drilling fluid to be provided for drilling via the coiled tubing rather than having to provide alternative fluid handling equipment and an alternative fluid source. By pivotally mounting the rotary drill head on the injector, the rotary drill head may be moved out of the way of the coiled tubing during the first mode of operation and may be moved back into an operational position for this second mode of operation.

5

The pivotal mounting of the rotary drill head may be achieved by any suitable means, such as by the use of elongate arms mounted at one end to the injector for pivotal movement and at the other end to opposing sides of the rotary drill head, so as to swing the drill head into and out of position. The movement of the drill head into and out of position may also be achieved by any suitable means, such as by a hydraulic ram or the like.

The present invention thus also provides a method of operating a mobile, coiled tubing drilling apparatus with a rotary drill head, the apparatus including a non-rotating mast on a mobile platform, the mast having mounted thereon an injector below a coiled tubing reel, the injector defining an operational axis for the coiled tubing, wherein the rotary drill head is pivotally mounted on the injector and is moved between a retracted position away from the operational axis and an operating position in line with the operational axis, the rotary drill head including a top swivel for non-rotating connection to the coiled tubing and a bottom spindle for rotating connection to a pipe section, the top swivel and the bottom spindle providing fluid communication between connected coiled tubing and connected pipe section during operation.

The present invention thus also provides a method of operating a mobile, coiled tubing drilling apparatus, the apparatus including a non-rotating mast on a mobile platform, the mast having mounted thereon an injector, a coiled tubing reel having a tubing pay-off point associated therewith, and a tubing control system between the reel and the injector, the injector defining an operational axis for the coiled tubing, wherein the reel is mounted for horizontal (x,y) movement and the tubing control system includes a tubing abutment adjacent the tubing pay-off point, the apparatus also including a rotary drill head pivotally mounted on the injector, the rotary drill head including a top swivel for non-rotating connection to the coiled tubing and a bottom spindle for rotating connection to a pipe section, the method including:

maintaining the tubing pay-off point generally above the injector and adjacent to the tubing abutment during pay-out of the tubing by way of the horizontal (x,y) movement of the reel;

applying an opposite bend to the tubing during pay-out of the tubing by engagement of the tubing adjacent the pay-off point with the tubing abutment;

maintaining a tubing take-on point above the injector and away from the tubing abutment during take-up of the tubing by way of the horizontal (x,y) movement of the reel; and

moving the rotary drill head between a retracted position away from the operational axis and an operating position in line with the operational axis, the top swivel and the bottom spindle providing fluid communication between connected coiled tubing and connected pipe section during operation.

In relation to the mobile platform and the requirement for the mast to be non-rotating, in a preferred form the mast is mounted on the mobile platform so as to be movable between an upright drilling position where the reel is above the injector, and a lowered transport position, and also so as to be non-rotatable.

In relation to the mast being mounted so as to be non-rotatable, some drilling rigs that utilise coiled tubing are designed to allow for the rotation of a reel about the vertical axis of the tubing down a borehole. Apparatus of that type has differing design requirements than apparatus of the type that the present invention relates to, being apparatus with non-rotating masts.

6

Further, the movability of the mast between an upright drilling position where the reel is above the injector, and a lowered transport position, assists with the mobility of the apparatus, allowing for transport to occur by road or by rail in traditional forms. Also, the mobility of the platform itself can of course be provided by any known and desirable means for movement on land, such as by a continuous track propulsion system or a traditional wheel-based propulsion system, while the ancillary drilling equipment that may additionally be provided on the mobile platform may include any of fluid pumps, air compressors, nitrogen purge systems, a diesel engine, hydraulic pumps and valves, and suitable control and operating systems, including remotely controlled systems as necessary.

In another preferred form, not only is the reel mounted on the mast for horizontal (x,y) movement during drilling, but the reel is preferably also mounted on the mast for vertical (z) movement. This vertical movement may be provided by the mast including, for example, a telescoping type of configuration.

Such vertical movement of the reel is advantageous in providing for relatively small vertical movement of a drill bit (for example), located at the bottom of the tubing in a borehole, into and out of contact with the bottom of the borehole, or simply for connecting the coiled tubing with the top swivel of the rotary drill head when transitioning from the first mode of operation to the second mode of operation. This is in preference to such movement having to be provided by rotating the reel, which, if avoided, can further reduce the stresses placed on the tubing, further increasing the operating life of the tubing.

Turning now to a description of the reel and its mounting, which is particularly relevant for the first mode of operation, as mentioned above the reel is mounted on the mast for horizontal (x,y) movement such that the tubing pay-off point can be maintained generally above the injector during pay-out and, preferably, directly above the injector during take-up of the tubing. In this respect, and identifying movement in the x direction as being movement of the reel towards and away from the mast, and movement in the y direction as being movement of the reel along its own longitudinal axis, the x direction movement is preferably provided by mounting the reel on the mast via pivoting arms that are controlled to pivot towards and away from the mast.

Such pivoting movement therefore moves the entire reel towards and away from the mast (as required, either before, during or after drilling) and thus towards and away from the tubing abutment mentioned above. Mounting the reel in this manner thus essentially provides for movement of the longitudinal axis of the reel towards and away from the tubing abutment, and of the coiled tubing on the reel towards and away from the tubing abutment, and thus of the pay-off point of the tubing towards and away from the tubing abutment. Indeed, during drilling, this movement permits the tubing at the pay-off point to be continually urged towards and against the tubing abutment as the tubing uncoils from the reel and as the diameter of the tubing coiled on the reel decreases.

The y direction movement is movement of the reel along its own longitudinal axis, again so as to maintain the pay-off point of the tubing adjacent to the tubing abutment as the tubing uncoils from the reel. In this respect, it will be appreciated that the pay-off point of the tubing will move along the longitudinal axis of the reel as the reel rotates about its longitudinal axis and as the tubing uncoils. With the reel being adapted to provide for continual adjustability of the reel along its longitudinal axis, the reel can be moved in the y direction in response to the pay-off point moving in the

y-direction, thus keeping the pay-off point adjacent to the tubing abutment as required, and also keeping the tubing at that point in engagement with the tubing abutment to apply the requisite opposite bend thereto.

BRIEF DESCRIPTION OF DRAWINGS

Having briefly described the general concepts involved with the present invention, a preferred embodiment of a mobile coiled tubing drilling apparatus will now be described that is in accordance with the present invention. However, it is to be understood that the following description is not to limit the generality of the above description.

In the drawings:

FIG. 1 is a perspective view from above of a mobile, coiled tubing drilling apparatus in accordance with a preferred embodiment of the present invention, deployed in its drilling position;

FIG. 2 is a side view of the apparatus of FIG. 1 in a transport position;

FIGS. 3(a) and 3(b) are schematic side views of the mast and reel of the apparatus of FIG. 1 when in tubing pay-out mode (FIG. 3(a)) and tubing take-up mode (FIG. 3(b));

FIGS. 4(a) and 4(b) are schematic top views of a preferred reel mounting configuration for use with the apparatus of FIG. 1 when in tubing pay-out mode (FIG. 4(a));

FIGS. 5(a) and 5(b) are perspective and side views of an embodiment of a rotary drill head pivotally mounted on an injector, being suitable for use with the apparatus of FIGS. 1 to 4, showing the rotary drill head in its retracted position away from the operational axis (in the first mode of operation for the drilling apparatus);

FIG. 6 is a perspective view similar to FIG. 5(a) but showing the rotary drill head in its operating position in line with the operational axis (in the second mode of operation for the drilling apparatus); and

FIG. 7 is a section view through the rotary drill head of FIG. 5(a).

DETAILED DESCRIPTION

Illustrated in FIG. 1 is a mobile, coiled tubing drilling apparatus 10 in its upright drilling position, while FIG. 2 shows the same apparatus 10 in its lowered transport position. The apparatus 10 generally includes a mast 12 mounted on a mobile platform 14 in a manner such that the mast is not rotatable about a vertical axis when in its upright drilling position. The apparatus also includes a coiled tubing reel 16, an injector 18 (with injector guide rollers 19) and a tubing control system in the form of an elongate tubing abutment 20. As will be better understood from the following description, point A in FIG. 1 is a point on the reel and is the general location of both a tubing pay-off point and a tubing take-up point (referred to later as A').

The vertical axis mentioned above is designated in FIG. 1 as the z axis in the identified x-y-z coordinate system, with the x axis (or x direction) being the direction of movement for the tubing pay-off point A (and thus also the reel 16) towards and away from the tubing abutment 20. The y axis (or y direction) is then the direction of movement for the tubing pay-off point A (and again also the reel 16) along the longitudinal axis of the reel 16. It will be appreciated that references to pay-off and take-up of the tubing are references to the first mode of operation of the apparatus, utilising the coiled tubing as the primary drilling means.

The mobility of the platform 14 is provided in this embodiment by a continuous track propulsion system 15,

while much of the ancillary drilling equipment provided on the mobile platform (such as fluid pumps, air compressors, nitrogen purge systems, a diesel engine, hydraulic pumps and valves, and suitable control and operating systems) have been omitted from FIG. 1 and FIG. 2 for ease of illustration. Additionally, in this embodiment, the reel 16 is mounted on the mast 12 for vertical (z) movement by way of the mast 12 having a telescoping configuration (not shown).

As mentioned above, such vertical movement of the reel 16 is advantageous in providing for relatively small vertical movement of a drill bit (for example), located at the bottom of the tubing in a borehole, into and out of contact with the bottom of the borehole. This is in preference to such movement having to be provided by rotating the reel 16 to raise or lower the drill bit, which, if avoided, can further reduce the stresses placed on the tubing, further increasing the operating life of the tubing.

The mast 12 of the apparatus 10 also includes, below the injector 18, a pivotally mounted, retractable, rotary drill head 22 (only partly shown) that can be used for drilling with a conventional rotating drill string in a second mode of operation. In this second mode, the apparatus 10 can be used to install casing or the like to the borehole, or to connect and disconnect the different elements of a bottomhole assembly, or simply to drill with a rotating drill string, using fluid provided through the coiled tubing, which will be described in more detail below with reference to FIGS. 5(a), 5(b), 6 and 7.

Referring now to FIGS. 3a and 3b, the reel 16 can be seen mounted for horizontal (x,y) movement, with the x direction being left-right across the page and the y direction being into and out of the page, such that, during pay-out of the tubing 30, the tubing pay-off point A can be maintained generally above the injector 18 but away from the injector's operational axis, the operational axis being defined by the pathway through the injector 18 of the longitudinal axis of the tubing 30 therein.

In this embodiment, the tubing control system of the apparatus 10 also includes an adjustable tubing straightener 32 after the tubing abutment 20 and before the injector 18, the tubing straightener 32 being adjustable such that it can engage tubing 30 entering or exiting the injector 18 and be utilised to provide more or less (or no) force to tubing 30 entering or exiting the injector 18. In this embodiment, the adjustable tubing straightener 32 is shown in FIG. 3(a) as being in engagement with the tubing 30 entering the injector 18 (during pay-out), but in FIG. 3(b) is shown not engaging with the tubing 30 exiting the injector 18 (during take-up), for reasons that will be outlined below. The adjustable straightener 32 is a single hydraulic powered roller configured to engage with tubing against a fixed abutment.

The tubing abutment 20 is shown fixed with respect to the mast 12 so that the movement of the reel 16 to maintain the tubing 30 pay-off point A generally above the injector 18 during pay-out of the tubing 30 also positions the tubing pay-off point A adjacent the tubing abutment 20 so that the tubing 30 engages with the tubing abutment 20. As mentioned above, this engagement with the tubing abutment 20 places an opposite bend in the tubing 30 during pay-out (such a bend being "opposite" to the bend in the tubing 30 that already exists in the coiled tubing from it being coiled on the reel 16), which in this embodiment occurs before the tubing 30 passes through the adjustable tubing straightener 32 and the injector 18.

The tubing abutment 20 is an elongate abutment beam, fixed generally vertically to the mast 12 with an upper end 20a and a lower end 20b, and with the upper end 20a being

the end located above the tubing pay-off point A of the reel **16** during operation. The uncoiling tubing **30** engages with the abutment beam and is guided along the abutment beam to the adjustable straightener **32** and then to the injector **18** during pay-out of the tubing **30**. The elongate abutment beam is substantially straight and elongate, and has a channel **36** therealong that is capable of receiving and guiding therealong tubing **30** from the reel **16**.

As mentioned above, the application of this opposite bend to the tubing **30** at a location closely adjacent to the tubing pay-off point A has been found to minimise stress on the tubing **30** (and thus increase the operational life of the tubing **30**) while reasonably accurately aligning the tubing **30** with the adjustable tubing straightener **32** and the injector **18**. The application of the opposite bend has also been found to reduce any residual plastic bend remaining in the tubing **30** before entering the borehole, assisting in avoiding subsequent difficulties with the control and direction of the borehole.

In contrast, and referring to FIG. **3b** which shows the re-coiling of the tubing **30** when the tubing **30** is being withdrawn from the borehole (not shown), the tubing **30** entering the injector **18** from below has of course already been straightened, and thus is not subjected to the same existing bend that is present with coiled tubing **30** being uncoiled (FIG. **3(a)**). In this phase, the tubing abutment **20** is not utilised by the apparatus **10** during tubing take-up, and a tubing take-on point A' (being essentially the same point during re-coiling as the tubing pay-off point A during uncoiling) is made as close as operationally possible to a point along the injector's operational axis, and thus will be directly above the injector **18**.

With reference to FIGS. **4(a)** and **4(b)**, as mentioned above the reel **16** is mounted on the mast **12** for horizontal (x,y) movement such that the tubing pay-off point A can be maintained generally above the injector **18** during pay-out of the tubing **30** and such that the tubing take-on point A' can be maintained directly above the injector **18** during take-up of the tubing **30**.

In this respect, and identifying movement in the x direction as being movement of the reel towards and away from the mast **12** (left and right on the page), and movement in the y direction as being movement of the reel **16** along its own longitudinal axis (axis Y-Y in FIGS. **4(a)** and **4(b)**), the x direction movement is provided by mounting the reel **16** on the mast **12** via pivoting arms **40** that are controlled to pivot towards and away from the mast **12**.

Such pivoting movement therefore moves the entire reel **16** towards and away from the mast **12** (as required, either before, during or after drilling) and thus towards and away from the tubing abutment **20**. Mounting the reel **16** in this manner provides for movement of the longitudinal axis Y-Y of the reel **16** towards and away from the tubing abutment **20**, and of the coiled tubing **30a**, **30b** on the reel **16** towards and away from the tubing abutment **20**, and thus of the pay-off point A of the tubing towards and away from the tubing abutment **20**.

Indeed, during drilling, this movement permits the tubing **30a**, **30b** at the pay-off point A to be continually urged towards and against the tubing abutment **20** as the tubing **30a**, **30b** uncoils from the reel **16** and as the diameter of the tubing **30a**, **30b** coiled on the reel **16** decreases, as is shown from FIG. **4(a)** where the reel **16** is full of tubing **30a** through to FIG. **4(b)** where the tubing **30b** is almost entirely unwound from the reel **16**.

In this respect, it will be appreciated that the pay-off point A of the tubing **30a**, **30b** will move along the longitudinal

axis Y-Y of the reel **16** as the reel rotates about its longitudinal axis Y-Y and as the tubing **30a**, **30b** uncoils. With the reel **16** being adapted to provide for continual adjustability of the reel **16** along its longitudinal axis Y-Y, the reel can be moved in the y direction in response to the pay-off point A moving in the y-direction, thus keeping the pay-off point A adjacent to the tubing abutment **20** as required, and also keeping the tubing **30a**, **30b** at that point in engagement with the tubing abutment **20** to apply the requisite opposite bend thereto.

FIGS. **5(a)**, **5(b)**, **6** and **7** illustrate an embodiment of a rotary drill head **22** pivotally mounted on an injector **18**, being suitable for use with the apparatus of FIGS. **1** to **4**, showing the rotary drill head in its retracted position (FIGS. **5(a)** and **5(b)**) away from the operational axis (in the first mode of operation for the drilling apparatus, as described above) and in its operating position (FIGS. **6** and **7**) in line with the operational axis (in the second mode of operation for the drilling apparatus, as will now be described).

FIG. **5(a)** illustrates the use of elongate arms **50** mounted at one end **52** to the injector **18** for pivotal movement and at the other end **54** to opposing sides of the rotary drill head **22**, so as to allow movement of the drill head **22** between the retracted position of FIGS. **5(a)** and **5(b)** and the operating position of FIG. **6**.

FIG. **5(b)** also shows that movement of the drill head **22** between the retracted position and the operating position is achieved by a hydraulic ram **56** mounted between the injector **18** and the drill head **22**.

The second mode of operation illustrated in FIGS. **6** and **7** is a rotating drill string mode where the coiled tubing **30c** connects to a top swivel **60** of the rotary drill head **22** and moves no further than that, while pipe sections (not shown) are connected to a bottom spindle **62** of the drill head **22** forming therebelow a rotating drill string. In this respect, the swivel **60** is fixed and does not itself rotate, with the bottom portion thereof being received within the upper portion **63** of the main shaft **64** in a manner that permits the swivel **60** to move axially within the upper portion **63** and the main shaft **64** to rotate relatively to the swivel **60**, while maintaining a suitable fluid/air seal therebetween.

Of course, the main shaft **64** is powered by hydraulic motors **65** connected thereto via gears, providing rotation for the bottom spindle **62**. The main shaft **64** can be floating to allow for axial movement thereof while, for example, drill rods are being threaded onto the spindle **62**.

Fluid communication is provided between the connected coiled tubing **30** and the connected pipe sections (not shown) during operation to permit drilling fluid to be provided for drilling via the coiled tubing **30**, through the bore of the top swivel **60**, through the hollow drive shaft **64**, and through the bore of the bottom spindle **62**, there thus being no need to provide alternative fluid handling equipment or an alternative fluid source. By pivotally mounting the rotary drill head **22** on the injector **18**, the rotary drill head **22** may be moved out of the way of the coiled tubing **30** during the first mode of operation and may be moved back into an operational position for this second mode of operation.

Finally, there may be other variations and modifications made to the configurations described herein that are also within the scope of the present invention.

The invention claimed is:

1. A mobile, coiled tubing drilling apparatus with a rotary drill head, the apparatus including a non-rotating mast on a mobile platform, the mast having mounted thereon an injector below a coiled tubing reel, the injector defining an

11

operational axis for the coiled tubing, wherein the rotary drill head is pivotally mounted on the injector so as to be movable between a retracted position away from the operational axis and an operating position in line with the operational axis, the rotary drill head including a top swivel for non-rotating connection to the coiled tubing and a bottom spindle for rotating connection to a pipe section, the top swivel and the bottom spindle providing fluid communication between connected coiled tubing and connected pipe section during operation.

2. Apparatus according to claim 1, including elongate arms mounted at one end to the injector for pivotal movement and at the other end to opposing sides of the rotary drill head, so as to allow movement of the drill head between the retracted position and the operating position.

3. Apparatus according to claim 1, wherein movement of the drill head between the retracted position and the operating position is achieved by a hydraulic ram mounted between the injector and the drill head.

4. Apparatus according to claim 1, wherein the top swivel is fixed with a bottom portion thereof received within an upper portion of a main shaft in a manner that permits the swivel to move axially within the upper portion and the main shaft to rotate relatively to the swivel.

5. Apparatus according to claim 4, wherein the main shaft is floating to allow for axial movement thereof while pipe section is connected to the bottom spindle.

12

6. Apparatus according to claim 1, the coiled tubing reel having a tubing pay-off point associated therewith, and a tubing control system, wherein:

the tubing control system is between the reel and the injector, and includes a tubing abutment adjacent the tubing pay-off point for applying an opposite bend to the tubing during pay-out of the tubing; and

the reel is mounted for horizontal (x,y) movement such that, during pay-out of the tubing, the tubing pay-off point can be maintained generally above the injector, and can also be moved towards or away from the tubing abutment.

7. Apparatus according to claim 1, wherein the reel is mounted for horizontal (x,y) movement such that, during pay-out of the tubing, the tubing pay-off point can be maintained generally above the injector but away from the injector's operational axis.

8. Apparatus according to claim 7, wherein the reel is mounted for horizontal (x,y) movement such that, during take-up of the tubing, the tubing take-on point can be maintained directly above the injector at a point along the injector's operational axis.

9. Apparatus according to claim 1, wherein the tubing control system also includes an adjustable tubing straightener after the tubing abutment and before the injector.

* * * * *