



US011002415B2

(12) **United States Patent**  
**Romano et al.**

(10) **Patent No.:** **US 11,002,415 B2**  
(45) **Date of Patent:** **May 11, 2021**

(54) **REDUCED GLARE LIGHT FIXTURE**

(2015.01); *F21S 8/08* (2013.01); *F21V 5/007*  
(2013.01); *F21W 2131/105* (2013.01); *F21W*  
*2131/407* (2013.01);

(71) Applicant: **Hubbell Incorporated**, Shelton, CT  
(US)

(Continued)

(72) Inventors: **Perry Romano**, Bradenton, FL (US);  
**Adam J. Clark**, Bradenton, FL (US)

(58) **Field of Classification Search**

CPC ..... *F21V 29/74*; *F21V 29/763*; *F21V 3/0625*;  
*F21V 21/30*; *F21V 23/007*; *F21V 11/06*;  
*F21V 11/14*; *F21Y 2115/10*; *F21Y*  
*2105/12*; *F21Y 2113/13*

(73) Assignee: **Hubbell Incorporated**, Shelton, CT  
(US)

See application file for complete search history.

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,036,248 A \* 7/1991 McEwan ..... G09F 9/33  
313/110  
5,555,161 A \* 9/1996 Roe ..... F16H 63/42  
116/202

(Continued)

(21) Appl. No.: **16/919,916**

(22) Filed: **Jul. 2, 2020**

(65) **Prior Publication Data**

US 2020/0370718 A1 Nov. 26, 2020

OTHER PUBLICATIONS

Sievers, "Fundamentals of LED Light Pipes," *Electronic Design*  
2013, Retrieved from the Internet <https://www.electronicdesign.com/components/fundamentals-led-light-pipes>, May 8, 2013, 7 pages.

*Primary Examiner* — Anabel Ton

(74) *Attorney, Agent, or Firm* — Michael Best &  
Friedrich, LLP

**Related U.S. Application Data**

(63) Continuation of application No. 16/752,912, filed on  
Jan. 27, 2020, now Pat. No. 10,704,747, which is a  
(Continued)

(51) **Int. Cl.**

*F21S 2/00* (2016.01)  
*F21V 29/74* (2015.01)  
*F21V 21/30* (2006.01)  
*F21V 17/00* (2006.01)  
*F21V 3/06* (2018.01)

(Continued)


(57) **ABSTRACT**

Reduced glare light fixtures are provided. In one example  
implementation, a reduced glare light fixture includes a light  
emitting diode (LED) system. The LED system includes at  
least one LED module having one or more LED devices. The  
reduced glare light fixture further includes a bezel physically  
coupled to the LED system engine. The bezel has one or  
more glare reduction openings. At least one of the one or  
more glare reduction openings is configured to be approxi-  
mately coaxial with one LED of the one or more LED  
devices.

(52) **U.S. Cl.**

CPC ..... *F21S 2/005* (2013.01); *F21V 3/0625*  
(2018.02); *F21V 17/002* (2013.01); *F21V*  
*21/30* (2013.01); *F21V 23/007* (2013.01);  
*F21V 29/74* (2015.01); *F21V 29/763*

**18 Claims, 14 Drawing Sheets**



<b>Related U.S. Application Data</b>					
	continuation of application No. 15/964,153, filed on Apr. 27, 2018, now Pat. No. 10,551,015.	8,317,361	B2 *	11/2012	Lee ..... F21V 7/0008 362/235
		8,585,250	B1	11/2013	Kim
		8,864,336	B2 *	10/2014	Yasuoka ..... F21V 21/00 362/267
		9,115,857	B2	8/2015	Beausoleil
		9,273,856	B2 *	3/2016	Yang ..... F21S 8/00
		9,759,407	B2 *	9/2017	Yang ..... F21V 21/30
		9,869,464	B2 *	1/2018	Manahan ..... F21V 31/005
		9,995,439	B1	6/2018	Shum
		10,036,534	B2	7/2018	Morello
		10,228,098	B2	3/2019	Berkeljon
		10,337,704	B2 *	7/2019	Yokotani ..... F21K 9/232
		10,352,506	B1 *	7/2019	Nickum ..... H05B 41/38
		10,386,057	B2	8/2019	Harvey
		10,551,015	B2 *	2/2020	Romano ..... F21V 29/74
		10,620,350	B2 *	4/2020	Chern ..... G02B 5/18
		2009/0219732	A1 *	9/2009	Gingrich, III ..... F21V 29/773 362/555
		2011/0234076	A1 *	9/2011	Simon ..... F21V 29/74 313/46
		2012/0155080	A1 *	6/2012	Schupple ..... F21V 29/80 362/235
		2012/0206918	A1	8/2012	Lee
		2013/0176707	A1	7/2013	Audette
		2013/0329409	A1	12/2013	Windom et al.
		2014/0168991	A1	6/2014	Kim
		2014/0210357	A1	7/2014	Yan et al.
		2014/0293603	A1	10/2014	Barnard et al.
		2015/0167931	A1	6/2015	Borgarelli
		2016/0047538	A1	2/2016	Peck
		2016/0319996	A1	11/2016	Moon
		2017/0184288	A1	6/2017	Owens
		2018/0224111	A1	8/2018	Emerson
		2018/0340683	A1	11/2018	Harvey et al.
		2019/0086047	A1	3/2019	Jiang
		2019/0120445	A1	4/2019	Casper
		2019/0195485	A1	6/2019	Harvey
					* cited by examiner
(60)	Provisional application No. 62/501,959, filed on May 5, 2017, provisional application No. 62/613,959, filed on Jan. 5, 2018.				
(51)	<b>Int. Cl.</b>				
	<i>F21S 8/08</i> (2006.01)				
	<i>F21V 5/00</i> (2018.01)				
	<i>F21V 23/00</i> (2015.01)				
	<i>F21V 29/76</i> (2015.01)				
	<i>F21Y 115/10</i> (2016.01)				
	<i>F21W 131/105</i> (2006.01)				
	<i>F21W 131/407</i> (2006.01)				
	<i>F21Y 105/12</i> (2016.01)				
	<i>F21Y 113/13</i> (2016.01)				
(52)	<b>U.S. Cl.</b>				
	CPC ..... <i>F21Y 2105/12</i> (2016.08); <i>F21Y 2113/13</i> (2016.08); <i>F21Y 2115/10</i> (2016.08)				
(56)	<b>References Cited</b>				
	<b>U.S. PATENT DOCUMENTS</b>				
	5,599,091 A 2/1997 Kira				
	5,938,324 A 8/1999 Salmon et al.				
	5,988,842 A 11/1999 Johnsen et al.				
	6,428,216 B1 * 8/2002 Savage, Jr. .... G02B 6/4219 385/33				
	6,779,907 B2 8/2004 Beadle				
	6,942,363 B1 9/2005 LeVasseur				
	7,182,486 B1 2/2007 Miracle				




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6






FIG. 7




FIG. 8







FIG. 10



**FIG. 11**




FIG. 123A




FIG. 123B




FIG. 124A




FIG. 125B




FIG. 14




FIG. 15



**REDUCED GLARE LIGHT FIXTURE**

## REFERENCE TO RELATED APPLICATIONS

This application claims priority to U.S. application Ser. No. 16/752,912 filed on Jan. 27, 2020, which is a continuation of U.S. application Ser. No. 15/964,153 filed on Apr. 27, 2018, now U.S. Pat. No. 10,551,015, which claims priority to U.S. Provisional Application No. 62/501,959 filed on May 5, 2017 and to U.S. Provisional Application No. 62/613,959 filed on Jan. 5, 2018, all of which are incorporated herein by reference.

## FIELD

The present disclosure relates generally to artificial lighting.

## BACKGROUND

Artificial lighting is important to many aspects of modern life. For example, artificial lighting can be important for many different sporting competitions and sporting venues. While artificial lighting often allows participation in indoor sports, and outdoor sports in darkened conditions, artificial lighting is not without drawbacks. Glare is currently one of the biggest complaints about sports lighting. The problem of glare is not limited to sporting venues either. For example, flood lighting used around various structures and airport ramp lighting are often the subject of complaints about glare.

Glare and related light trespass are of special concern when installing floodlights. Disability glare reduces visual performance and visibility. Discomfort glare produces physical discomfort. It is possible to experience disability without discomfort, and conversely, discomfort without disability, however, one often accompanies the other. Regarding light that we actually see, brightness can be measured as the light leaving a lamp, or the light reflecting from an object's surface. It is measured in footlamberts (English) or candelas/square meter (metric). In practice, glare is usually a situation where a source of unshielded light is at least 1,000 times brighter than the average visual field. For instance, because the night sky is dark, almost all outdoor light sources, such as a street luminaire or automobile headlight, cause glare. To evaluate glare, however, one may use luminance, which typically is measured in candelas per square meter (cd/m<sup>2</sup>) or nits.

As used herein, the term glare includes all forms of glare, including discomfort glare and disability glare, as well as light trespass, and related stray light problems. For example, ocular stray light is a phenomenon where parts of the human eye scatter light that reaches the retina, but do not contribute to forming a correct image.

One approach to reducing glare is to decrease light intensity of the artificial light source. However, if the decreased light intensity cannot be offset with additional lighting fixtures, overall lighting may drop below acceptable levels. Even if decreased light intensity is offset with additional lighting fixtures, such additional lighting fixtures typically incur a corresponding increase in costs.

Another approach to reducing glare is to use louvers, such as various types of blade and concentric louvers. Unfortunately, louvers have the effect of reducing light output and correspondingly increasing costs to compensate for the loss of light by producing additional lumens of light to offset the losses.

**SUMMARY**

Aspects and advantages of embodiments of the present disclosure will be set forth in part in the following description, or may be learned from the description, or may be learned through practice of the embodiments.

One example aspect of the present disclosure is directed to a light engine module having at least one light emitting source. The light engine module can include a bezel comprising at least one glare reduction tube configured to be approximately coaxial with the at least one light emitting source.

These and other features, aspects and advantages of various embodiments will become better understood with reference to the following description and appended claims. The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate embodiments of the present disclosure and, together with the description, serve to explain the related principles.

## BRIEF DESCRIPTION OF THE DRAWINGS

Detailed discussion of embodiments directed to one of ordinary skill in the art are set forth in the specification, which makes reference to the appended figures, in which:

FIG. 1 is a front, perspective view of an example reduced glare light fixture according to example embodiments of the present disclosure;

FIG. 2 is an exploded, perspective view of an example reduced glare light fixture according to example embodiments of the present disclosure;

FIG. 3 is a rear, perspective view of an example reduced glare light fixture according to example embodiments of the present disclosure;

FIG. 4 is a side, elevation view of an example reduced glare light fixture according to example embodiments of the present disclosure;

FIG. 5 is a front, elevation view of an example reduced glare light fixture according to example embodiments of the present disclosure;

FIG. 6 is a rear, perspective view of certain components of an example reduced glare light fixture according to example embodiments of the present disclosure;

FIG. 7 is a rear, elevation view of certain components of an example reduced glare light fixture according to example embodiments of the present disclosure;

FIG. 8 is a front, exploded view of an example reduced glare light fixture according to the present disclosure;

FIG. 9 is a front, exploded view of an example reduced glare light fixture according to example embodiments of the present disclosure;

FIG. 10 is a front, perspective view of a module of an example reduced glare light fixture according to example embodiments of the present disclosure;

FIG. 11 is a rear, perspective view of an optic of an example reduced glare light fixture according to example embodiments of the present disclosure;

FIG. 12A is a front, perspective view of an inactive module support board of an example reduced glare light fixture according to example embodiments of the present disclosure;

FIG. 12B is a front, perspective view of an active module support board of an example reduced glare light fixture according to example embodiments of the present disclosure;

3

FIG. 13A is a front, perspective view of an inactive light engine module of an example reduced glare light fixture according to example embodiments of the present disclosure;

FIG. 13B is a front, perspective view of an active light engine module of an example reduced glare light fixture according to example embodiments of the present disclosure;

FIG. 14 is a front, perspective view of an active light engine module of an example reduced glare light fixture according to example embodiments of the present disclosure; and

FIG. 15 is photographic view of an example reduced glare light fixture mounted in an outdoor environment according to example embodiments of the present disclosure.

### DETAILED DESCRIPTION

Reference now will be made in detail to embodiments, one or more examples of which are illustrated in the drawings. Each example is provided by way of explanation of the embodiments, not limitation of the present disclosure. In fact, it will be apparent to those skilled in the art that various modifications and variations can be made to the embodiments without departing from the scope or spirit of the present disclosure. For instance, features illustrated or described as part of one embodiment can be used with another embodiment to yield a still further embodiment. Thus, it is intended that aspects of the present disclosure cover such modifications and variations.

Example aspects of the present disclosure are directed to reduced glare light fixtures mitigating glare associated with LED lighting. As described herein, some embodiments include a bezel having glare reducing tubes formed therein positioned over a light engine module having LED devices such that the LED devices are approximately coaxial with the glare reducing tubes to reduce glare. In some embodiments, reduced glare light fixtures described herein mitigate or prevent direct view of particularly bright parts of lighting, such as with floodlights. In some embodiments, the reduced glare light fixtures mitigate or eliminate stray lumens that cause glare without overly reducing the lumens in a main light beam otherwise intended for illumination purposes.

Referring to FIGS. 1-15, and in particular to FIG. 1, a front, perspective view of an example embodiment of a reduced glare light fixture 100 according to the present disclosure is shown. The reduced glare light fixture 100 includes a mounting yoke 105. In some embodiments, the mounting yoke 105 enables the reduced glare light fixture 100 to be physically coupled through a pole to a large structure or ground support. In some embodiments, the mounting yoke 105 is physically coupled to a housing 110 through an optional yoke mount portion 111 of the housing 110. In some embodiments, the reduced glare light fixture 100 includes a plurality of heat sinks 112 each having a plurality of fins 114 generally disposed in front of an upper driver casing 116a and a lower driver casing 116b. In some alternative embodiments, the upper driver casing 116a and the lower driver casing 116b are omitted. For orientation purposes, the physically coupled upper driver casing 116a and the lower driver casing 116b are positioned towards a rear portion 119 of the reduced glare light fixture 100 and the heatsinks 112 are positioned towards a front portion 118 of the reduced glare light fixture 100.

In some embodiments, the upper driver casing 116a is physically coupled to the lower driver casing 116b through fasteners, such as bolts, and recessed sockets. However,

4

unless specifically stated otherwise, neither physically connected components, nor physically coupled components, are not limited to any particular form of component attachment. For example, in some embodiments, the upper driver casing 116a is physically coupled to the lower driver casing 116b through mating surfaces. In some embodiments, the upper driver casing 116a is physically coupled to the lower driver casing 116b with adhesives. In some embodiments, the upper driver casing 116a and the lower driver casing 116b are formed as a single driver casing 116 component.

In some embodiments, the housing 110 can include a grill 113. To provide air flow to heat sinks 112, the grill 113 can extend around the heat sinks 112 along a circumferential direction C on housing 110, and the grill 113 can also be aligned with the heat sinks 112 along a radial direction R. As an example, the grill 113 can be positioned coplanar with the heat sinks 112, e.g., in a plane that is perpendicular to an axial direction A such that the plane intersects both the grill 113 and the heat sinks 112. In some embodiments, a length of the grill 113, e.g., along the axial direction A, may also be about equal to a length of the fins 114 of the heat sinks 112, e.g., along the axial direction A. In this manner, the grill 113 can facilitate cooling air flow into and out of housing 110. For example, the grill 113 can be perforated such that air may flow through the housing 110 at the grill 113 to and/or from the heat sinks 112. In particular, cooler air may flow through the grill 113 into the housing 110 below the heat sinks 112, whereas warmer air may flow through the grill 113 out of housing 110 above the heat sinks 112.

The reduced glare light fixture 100 includes a light-emitting diode (LED) system 120. The LED system 120 includes a plurality of light engine modules 122. While six light engine modules 122 are shown in FIG. 1, and two to twelve light engine modules are preferred, the particular number of light engine modules is not expressly limited. In some embodiments, each light engine module has a common shape such that an integral number of modules placed adjacent to each other form a ring. Although the plurality of light engine modules 122 are not limited to a common shape, the use of a common shape simplifies certain manufacturing and assembly steps.

Each light engine module 122 includes a bezel 123, a plurality of optics 124, and a plurality of LED devices (not illustrated). In some embodiments, the bezel 123 is formed separately from the light engine modules 122 and attached after formation. In some embodiments, the bezel 123 includes a plurality of glare reduction tubes 126. More specifically, each glare reduction tube of the plurality of glare reduction tubes 126 is hollow and enables light to pass from the one optic 124 and one LED device. In some embodiments, the plurality of glare reduction tubes 126 are integrally formed with the bezel 123. For instance, the plurality of glare reduction tubes 126 and the bezel 123 can be formed as a single monolithic component. Alternatively, the plurality of glare reduction tubes 126 and the bezel 123 can be formed as separate components. In this manner, the plurality of glare reduction tubes 126 can be removably coupled to the bezel 123.

In some embodiments, as shown in FIG. 1, the bezel 123 contains 21 glare reduction tubes 126, 21 optics 124 and 21 LED devices. In some embodiments, as shown in FIG. 1, one optic 124 and one LED device can be recessed within one glare reduction tube 126 for all of the optics, LED devices and tubes. In some embodiments, each optic 124 and LED device are recessed within each glare reduction tube 126 such that a light beam from the LED device in an active state has an approximately 50 degree spread from a coaxial

center axis, i.e., approximately 25 degrees spread on each of 2 opposing sides of the coaxial center axis. In some embodiments, the plurality of optics **124** are fabricated together as a single component separate from the bezel **123**. In some alternative embodiments, the plurality of optics **124** are each fabricated as separate, individual components.

As shown in FIG. 1, the bezel **123** includes a surface **127**. In some embodiments, the surface **127** can be a base of the bezel **123**. The plurality of glare reduction tubes **126** can be associated with the surface **127** of the bezel **123**. For example, the plurality of glare reduction tubes **126** can extend from the surface **127**. Alternatively, the plurality of glare reduction tubes **126** can extend through the surface **127**. In some embodiments, the surface **127** of the bezel **123** can be comprised of opaque material. Alternatively, the surface **127** of the bezel **123** can be comprised of translucent material. In some embodiments, the surface **127** of the bezel **123** can be positioned over a plurality of light emitting sources (e.g., LED devices) such that each glare reduction tube **126** is aligned with one light emitting source of the plurality of light emitting sources.

As used herein, the terms “about,” “approximately,” “approximately,” and the like, when used in conjunction with a numerical value are intended to refer to any number within twenty five percent (25%) of the stated numerical value. In some embodiments, each optic **124** and LED device are recessed approximately 0.8 inches within each tube **126**. In general, in some embodiments, the depth of the recess is a variable dependent on the width of the light beam spread. For example, a more narrow light beam has a deeper recess than a wider light beam. In some embodiments, to reduce glare, the bezel **123**, including each glare reduction tube of the plurality of glare reduction tubes **126** in the bezel **123**, are formed from a translucent material that diffuses light from the LED devices. In some embodiments, the bezel **123** is formed from a material selected from an acrylic compound and polycarbonate. Some light from the LED devices passes through and is diffused by the translucent material in the bezel **123** before being emitted by the reduced glare light fixture **100**. It has been discovered that, under certain conditions, observers viewing the reduced glare light fixture **100** from some angles offset to an outward axial direction A, i.e., the normal axis for the reduced glare light fixture **100**, report a significant reduction in glare from the reduced glare light fixture as opposed to comparable light fixtures without the bezel **123**. Note that the outward axial direction A is generally in the direction from the rear portion **119** to the front portion **118**. One possible explanation for the apparent reduction in glare is thought to be due to smoothing contrast between light from the LED devices passing through each of the glare reduction tubes **126** effectively reduces glare for an observer at certain distances and angles.

In some embodiments, to reduce glare, the bezel **123**, including each of the plurality of glare reduction tubes **126** in the bezel **123**, are formed from an opaque material that blocks light from the LED devices. In some embodiments, the opaque material is black. In this manner, the bezel **123** can block light emitted from the LED devices before said light can be emitted by the reduced glare light fixture **100**. It has been discovered that, under certain conditions, observers viewing the reduced glare light fixture **100** from some angles offset to axial direction A, i.e., the normal axis for the reduced glare light fixture **100**, report a significant reduction in glare from the reduced glare light fixture as opposed to comparable light fixtures without the bezel **123**. It is thought that the reduction of light emitted at angles offset to the axial

direction A passing through the tubes **126** from the LED devices reduces glare for an observer.

Each optic **124** in the reduced glare light fixture **100** is optically coupled with one of the plurality of LED devices. In some embodiments, each optic **124** is a lens used to help direct light from the plurality of LED devices in the axial direction A out of the reduced glare light fixture **100**. One or more examples of the optic **124** are shown in the figures, but the optic **124** is not limited to any particular shape. Each optic **124** is positioned over one LED device of the plurality of LED devices. For example, the optic **124** shown in FIG. **11** includes a LED receptacle portion **128** for receiving one LED device of the plurality of LED devices. In some embodiments, the arrangement of optics **124**, the LED devices and the glare reduction tubes **126** are configured to provide a variety of different light distributions, such as a type I distribution, type II distribution, type III distribution, type IV distribution, type V distribution, e.g., round, square, round wide, other light distribution, or combination of light distributions. In some embodiments, the optics **124**, the LED devices and the glare reduction tubes **126** are configured to provide one of flood optics, such as a 2x2 beam pattern, a 3x3 beam pattern, a 4x4 beam pattern, a 5x5 beam, pattern, and a 6x6 beam pattern. In some embodiments, the LED devices on each light engine module **122** may have different individualized light distributions. In some embodiments, the plurality of optics **124** are connected and/or formed together on the module support board **170** such that the optics **124** are formed from one separate piece of material.

Turning to FIGS. **12A** and **12B**, in some embodiments, the reduced glare light fixture **100** includes the plurality of light engine modules **122**, and each of the plurality of light engine modules **122** includes the plurality of LED devices mounted on a module support board **170**. In some embodiments, the module support board **170** is a printed circuit board (PCB). In some embodiments, the module support board **170** is an LED board. The plurality of LED devices are configured to emit visible light because of movement of electrons between p-type and n-type semiconductor materials. The plurality of LED devices can have any suitable size, color, color temperature, etc. for the desired light applications. In some embodiments, the plurality of LED devices are selected from color temperatures of 3000K, 4000K, 5000K and other suitable color temperatures, however, the LEDs are not restricted to any particular color temperature. In some embodiments, the plurality of LED devices include sub-groups each having a different set of color temperatures. As shown in FIG. **12A**, the 21 LEDs in the plurality of LED devices are in an “off” (inactive state) condition. As shown in FIG. **12B**, the 21 LEDs in the plurality of LED devices are in an “on” (active state) condition suitable for illumination purposes.

While some embodiments are described herein as including an LED system **120** as a light engine, it is understood that halogen lights are substituted for the LED system in some alternative embodiments and incandescent lights are substituted for the LED system in some other alternative embodiments. The reduced glare light fixture **100** is not limited to any particular form of light emitting source.

Turning to FIGS. **13A** and **13B**, in some embodiments, each of the plurality of light engine modules **122** includes the bezel **123** that is attached to the module support board **170** such that each of the plurality of glare reduction tubes **126** coaxially aligns with an optic **124** and an LED device. In some embodiments, the bezel **123** includes the plurality of glare reduction tubes **126**, each glare reduction tube being optically coupled with one optic **124** and one LED device

such that each of the plurality of glare reduction tubes **126** enables light to pass from the one optic **124** and one LED device. In some embodiments, as shown in FIGS. **13A** and **13B**, the bezel **123** contains 21 glare reduction tubes **126**, 21 optics **124** and 21 LED devices. As shown in FIG. **13A**, the 21 LEDs included in the plurality of LED devices are in an “off” (inactive state) condition. As shown in FIG. **13B**, the 21 LEDs included in the plurality of LED devices are in an “on” (active state) condition suitable for illumination purposes. FIGS. **12B** and **13B** are positioned side-by-side to help illustrate the reduction in glare between the LEDs **125** without the bezel **123** as shown in FIG. **12B** and the LEDs with the bezel as shown in FIG. **13B**.

Referring to FIGS. **1-15**, and in particular to FIG. **10**, in some embodiments, the plurality of light engine modules **122** all have a common size and shape, and are interchangeable with one another, however, the light engines modules are not limited to uniform sizes or uniform shapes. In some embodiments, each of the plurality of light engine modules **122** is wedge shaped and has an inner edge **130** and an outer edge **132**. In some embodiments, the inner edge **130** and the outer edge **132** of module **122** are spaced from each other along the radial direction R. In some embodiments, the inner and outer edges **130**, **132** of each of the plurality of light engine modules **122** are positioned opposite each other along the radial direction R. For example, as shown in FIG. **9**, the inner edge **130** of each of the plurality of light engine modules **122** is radially positioned closest to the center axis A of the LED system **120**, and the outer edge **132** of each of the plurality of light modules **122** is radially positioned furthest away from the center axis A of the LED system **120**. In some embodiments, the inner edge **130** is disposed proximate a central axis X of housing **110** that extends through the center of LED system **120**. In some embodiments, a width W of each of the plurality of light engine modules **122** tapers (e.g., decreases) along the circumferential direction C from the outer edge **132** to the inner edge **130**. In some embodiments, each of the plurality of light engine module **122** is narrower along the circumferential direction C, at or adjacent to the center axis of the LED system **120** and wider along circumferential direction C away from the center of LED system **120**, such that each of the plurality of light engine modules **122** tapers along the radial direction R. In some embodiments, each of the plurality of light engine modules **122** has a pair of opposing side edges **134**. The opposing side edges **134** of each of the plurality of light engine modules **122** may be spaced from each other, e.g., along the circumferential direction C. Thus, the opposing side edges **134** of each of the plurality of light engine modules **122** may be positioned opposite each other along the circumferential direction C. The opposing side edges **134** of each of the plurality of light engine modules **122** may extend, e.g., linearly, along the radial direction R between the inner and outer edges **130**, **132**. Collectively, inner edge **130**, outer edge **132** and side edges **134** of each of the plurality of light engine modules **122** may form a wedge-shaped perimeter, e.g., in a plane that is perpendicular to the axial direction A. When the plurality of lighting modules **122** are wedge shaped and positioned adjacent one another, the plurality of lighting modules **122** may collectively form a circular or arcuate pattern within housing **110**. In particular, the opposing side edges **134** of adjacent light engine modules of the plurality of light engine modules **122** may be positioned adjacent and/or contact each other to, as shown in FIG. **5**, form the circular or arcuate pattern within housing **110**.

Referring to FIGS. **1-15**, and in particular to FIG. **2**, an exploded, perspective view of an example embodiment of the reduced glare light fixture **100** according to the present disclosure is shown. In addition to the components introduced above, the reduced glare light fixture **100** includes a support body **140**. The plurality of light engine modules **122** can be attached to the support body **140** within the housing **110**. In some embodiments, the housing **110** is decorative. In some embodiments, for example, the plurality of light engine modules **122** are attached within housing **110** by one or more of fastening, snap-fitting, adhering, and other mechanisms of attachment. The support body **140** provides a shared structure for mounting and/or bearing the plurality of light engine modules **122** and/or plugs **150** within housing **110**. In some embodiments, fasteners **142**, such as bolts, extend through the support body **140** into the plurality of light engine modules **122** to mount the plurality of light engine modules **122** to the support body **140**. In some embodiments, the fasteners **142** extend through support body **140** into the fins **114** on the heat sinks **112** to mount the plurality of light engine modules **122** to the support body **140**. In some embodiments, the support body **140** forms a plurality of through-holes for the fasteners **142**. In some embodiments, the reduced glare light fixture **100** includes a module back plate **144** positioned behind the support body **140**. In some embodiments, the module back plate **144** includes a plurality of apertures for receiving the fasteners **142**. In some embodiments, the through-holes are distributed in a pattern that provides a plurality of different mounting locations for the plurality of light engine modules **122** such that the plurality of light engine modules **122** are suitably spaced and/or oriented when mounted to the support body **140**. In this fashion, the support body **140** provides a convenient layout and guide for mounting the plurality of light engine modules **122** within the housing **110**. When the plurality of lighting modules **122** have a common shape, the plurality of lighting modules **122** may be interchangeable with one another and/or manufactured with the same process.

In some embodiments, the upper driver casing **116a** and the lower driver casing **116b** include vertical fins **117**, also known as ribs. In some embodiments, the vertical fins **117** are for heat dissipation, while in other embodiments the vertical fins **117** are decorative. In some embodiments, some of the upper driver casing **116a**, lower driver casing **116b**, housing **110**, mounting yoke **105**, yoke mount portion **111** of the housing, a back panel **115**, the heat sinks **112**, the bezel **123** and the optics **124** are made of materials suitable for direct exposure to outside conditions that include one or more of fresh water, salt water, temperature extremes, sunlight, animals, dust, debris, corrosive chemicals, combustible materials and explosive materials. In some embodiments, the housing **110** substantially protects the interior from at least one such outside condition.

As introduced above, in some embodiments the reduced glare light fixture **100** includes at least one spacer module known as a plug **150**. In some embodiments, with less than the maximum number of the plurality of light engine modules **122** positioned within the housing **110**, e.g., mounted on support plate **140**, a separate plug **150** is positioned at a location of each omitted light engine module **122** within housing **110**. In some embodiments, a plurality of plugs **150** are interspersed between the plurality of light engine modules **122**. Thus, each plug **150** replaces each omitted light engine module **122** within housing **110**. In some embodiments, the plug **150** is sized to match the light engine modules **122** such that plug **150** and the light engine

modules **122** are interchangeable. In some embodiments, the plug **150** has suitable holes for receiving fasteners **142** at support plate **140** and/or a wedge shaped outer plate **152** that is positioned coplanar with LED devices. In this manner, the plug **150** enhances an appearance of the reduced glare light fixture **100** as opposed to leaving a void in place of the omitted light engine module **122**. In some embodiments, one or more plugs **150** and one or more light engine modules **122** are distributed along the circumferential direction C at the front portion **118** of housing **110**, and the one or more plugs **150** and light engine modules **122** cooperate to collectively form a front face of the reduced glare light fixture **100**. In some embodiments, the plug(s) **150** and the light engine module(s) **122** collectively extend three hundred and sixty degrees (360°) along the circumferential direction C at the front portion **118** of housing **110**. In some embodiments, the plugs **150** have an outer appearance that is identical to the light engine modules **122** except that the plugs **150** do not include LED devices. In some embodiments, each plug **150** is connected between adjacent light engine modules **122**.

In some embodiments, the plurality of fins **114** on the heat sinks **112** are vertically aligned with the light engine modules **122** and are mounted on the support body **140** to provide the vertical flow paths **160**. Vertical air flow paths **160** facilitate cooling air flow through the heat sinks **112** by enabling air heated by the LED devices to flow upwardly along vertical air flow paths **160** between fins **114** and cooler outside air is drawn into the vertical air flow paths **160**.

In some embodiments, the reduced glare light fixture **100** includes an upper power circuit **200a** and a lower power circuit **200b**. In some embodiments, the reduced glare light fixture **100** combines the upper power circuit **200a** and the lower power circuit **200b** into a single power circuit **200**. In some embodiments, the upper power circuit **200a** and the lower power circuit **200b** receive alternating current (AC) electrical power at a higher voltage and convert it to direct current (DC) electrical power at a lower voltage to energize the plurality of light engine modules **122**. In some embodiments, the upper power circuit **200a** and the lower power circuit **200b** include one or more surge protective devices, transformers, and drivers. In some embodiments, the surge protector is configured to receive electrical current from an external power source such as a power grid or battery while protecting the reduced glare light fixture from one or more of electrical noise, spikes, lightning-induced surges and electrical anomalies.

In some embodiments, the reduced glare light fixture **100** includes a laser emitter **211**. In some embodiments, the laser emitter **211** emits a laser beam used to assist with orienting the reduced glare light fixture **100**. For example, a direction of the beam emitted by laser emitter **211** may generally correspond the direction of light emitted by LED system **120**. An installer operates the laser emitter **211** and observes the beam emitted by laser emitter **211** to align the reduced glare the reduced glare light fixture **100** towards a desired location. In such a manner, LED system **120** may emit light in a desired direction after installation of the reduced glare light fixture **100**.

Referring to FIG. **14**, a front, perspective view of active light engine modules of an embodiment of a reduced glare light fixture **100** according to the present disclosure is shown. For illustration purposes, the reduced glare light fixture **100** includes three modules each having a translucent bezel **123a** and three modules each having an opaque bezel **123b**. In some embodiments, the translucent bezel **123a** is white. In some embodiments, the opaque bezel **123b** is black. In some embodiments, the opaque bezel **123b** is

formed from a black material. In some embodiments, the opaque bezel **123b** is coated with a black material. As shown in FIG. **14**, the glare reduction tubes in the bezels **123a** and **123b** are positioned over and aligned with active LEDs emitting light. Glare is reduced as described herein in both the translucent bezels **123a** and the opaque bezels **123b**.

Referring to FIG. **15**, a photographic view of an illustrative embodiment of the reduced glare light fixture **100** mounted in an outdoor environment according to the present disclosure is shown. The reduced glare light fixture **100** mounted via a connecting pole (arm) **172** to a support pole **174**. The arm **172** is positioned approximately horizontal with respect level ground and the support pole is positioned approximately vertical with respect to level ground. The reduced glare light fixture **100** is shown in an illuminated state against a mostly cloudy background.

Some embodiments herein describe a reduced glare light fixture including a light emitting diode (LED) system, wherein the LED system includes at least one LED module having a plurality of LED devices and a bezel physically coupled to the LED system engine, the bezel having a plurality of glare reduction tubes formed therein, at least one glare reduction tube configured to be approximately coaxial with one LED device.

Some other embodiments herein describe a reduced glare light fixture including a light emitting diode (LED) system, wherein the LED system includes a plurality of LED modules each including a plurality of LED devices. The reduced glare light fixture also includes a bezel physically coupled to the LED system, the bezel having a plurality of glare reduction tubes formed therein, at least one glare reduction tube configured to be approximately coaxial with one LED device and an optic, the optic configured to be approximately coaxial and optically coupled between the at least one glare reduction tube and the one LED device.

Some still other embodiments herein describe a reduced glare light fixture including a light emitting diode (LED) system, wherein the LED system includes a plurality of LED modules each including a plurality of LED devices and a plurality of plugs, wherein the plurality of LED modules and plurality of plugs are interspersed and arranged in a ring. The reduced glare light fixture also includes a bezel physically coupled to the LED system, the bezel having a plurality of glare reduction tubes formed therein, at least one glare reduction tube configured to be approximately coaxial with one LED device, and an optic, the optic configured to be approximately coaxial and optically coupled between the at least one glare reduction tube and the one LED device.

While the present subject matter has been described in detail with respect to specific example embodiments thereof, it will be appreciated that those skilled in the art, upon attaining an understanding of the foregoing may readily produce alterations to, variations of, and equivalents to such embodiments. Accordingly, the scope of the present disclosure is by way of example rather than by way of limitation, and the subject disclosure does not preclude inclusion of such modifications, variations and/or additions to the present subject matter as would be readily apparent to one of ordinary skill in the art.

What is claimed is:

1. A light engine module, the light engine module comprising:
  - a circuit board including a first light emitting source;
  - a bezel; and
  - a plurality of openings disposed on the bezel, the openings configured to reduce glare from the first light emitting source,

## 11

wherein the first light emitting source emits light into a first opening of the plurality of openings, and wherein the first opening is configured to mitigate or prevent stray lumens that cause glare without otherwise negatively affecting the lumens in a main light beam of the first light emitting source.

2. The light engine module of claim 1, wherein the first light emitting source is aligned coaxially with the first opening.

3. The light engine module of claim 1, wherein the first opening is configured to mitigate or prevent direct view of a portion of the first light emitting source that is brighter than a second portion of the first light emitting source.

4. The light engine module of claim 1, wherein the first light emitting source is positioned within a receptacle of an optic, the optic being disposed on the circuit board.

5. The light engine module of claim 1, wherein the circuit board includes a second light emitting source, and wherein the second light emitting source emits light into a second opening of the plurality of openings.

6. The light engine module of claim 1, wherein the first light emitting is a light emitting diode (LED) light source.

7. A light engine module, the light engine module comprising:

a circuit board including a first light emitting source; a bezel; and

a plurality of openings disposed on the bezel, the openings configured to reduce glare from the first light emitting source,

wherein the first light emitting source emits light into a first opening of the plurality of openings, and wherein the bezel is formed from a translucent material.

8. A light engine module, the light engine module comprising:

a circuit board including a first light emitting source; a bezel; and

a plurality of openings disposed on the bezel, the openings configured to reduce glare from the first light emitting source,

wherein the first light emitting source emits light into a first opening of the plurality of openings, and wherein the bezel is formed from an opaque material.

9. The light engine module of claim 8, wherein the opaque material is black.

10. A bezel for a reduced glare light fixture, the bezel comprising:

a surface; and

a plurality of glare reduction openings disposed on the surface,

wherein the bezel is mounted to a circuit board including a first light emitting source,

wherein the first light emitting source emits light into a first glare reduction opening of the plurality of glare reduction openings, and

wherein the first light emitting source is aligned coaxially with the first glare reduction opening.

11. A bezel for a reduced glare light fixture, the bezel comprising:

a surface; and

a plurality of glare reduction openings disposed on the surface,

wherein the bezel is mounted to a circuit board including a first light emitting source,

## 12

wherein the first light emitting source emits light into a first glare reduction opening of the plurality of glare reduction openings, and

wherein the first glare reduction opening is configured to mitigate or prevent direct view of a portion of the first light emitting source that is brighter than a second portion of the first light emitting source.

12. A bezel for a reduced glare light fixture, the bezel comprising:

a surface; and

a plurality of glare reduction openings disposed on the surface,

wherein the bezel is mounted to a circuit board including a first light emitting source,

wherein the first light emitting source emits light into a first glare reduction opening of the plurality of glare reduction openings, and

wherein the first glare reduction opening is configured to mitigate or prevent stray lumens that cause glare without otherwise negatively affecting the lumens in a main light beam of the first light emitting source.

13. A bezel for a reduced glare light fixture, the bezel comprising:

a surface; and

a plurality of glare reduction openings disposed on the surface,

wherein the bezel is mounted to a circuit board including a first light emitting source,

wherein the first light emitting source emits light into a first glare reduction opening of the plurality of glare reduction openings, and

wherein the first light emitting source is positioned within a receptacle of an optic, the optic being disposed on the circuit board.

14. The bezel of claim 10, wherein the circuit board includes a second light emitting source, and wherein the second light emitting source emits light into a second glare reduction opening of the plurality of glare reduction openings.

15. The bezel of claim 10, wherein the first light emitting is a light emitting diode (LED) light source.

16. The bezel of claim 10, wherein the bezel is formed from an opaque material.

17. A reduced glare light fixture, the light fixture comprising:

a housing; and

a light emitting diode (LED) module positioned within the housing, the LED module including:

a circuit board having a first LED and a second LED;

a bezel; and

a plurality of glare reduction openings disposed on the bezel,

wherein the first LED emits light into a first glare reduction opening of the plurality of glare reduction openings; and

wherein the second LED emits light into a second glare reduction opening of the plurality of glare reduction openings.

18. The reduced glare light fixture of claim 17, wherein the first light LED is aligned coaxially with the first glare reduction opening and the second LED is aligned coaxially with the second glare reduction opening.