

US011014513B2

(12) **United States Patent**
Klemen et al.

(10) **Patent No.:** **US 11,014,513 B2**
(45) **Date of Patent:** **May 25, 2021**

(54) **CONTROL OF LOW PRESSURE GENERATOR FOR GAS TURBINE ENGINE**

7/32 (2013.01); *F02C 7/36* (2013.01); *F02K 3/06* (2013.01); *H02K 5/1732* (2013.01);
(Continued)

(71) Applicant: **Rolls-Royce North American Technologies, Inc.**, Indianapolis, IN (US)

(58) **Field of Classification Search**
CPC *B64D 2027/026*; *F01D 15/10*; *F02K 3/06*
See application file for complete search history.

(72) Inventors: **Donald Klemen**, Carmel, IN (US);
Michael J. Armstrong, Avon, IN (US)

(56) **References Cited**

(73) Assignee: **Rolls-Royce North American Technologies Inc.**, Indianapolis, IN (US)

U.S. PATENT DOCUMENTS

2,803,943 A 8/1957 Rainbow et al.
4,497,171 A 2/1985 Corrigan et al.
(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 169 days.

FOREIGN PATENT DOCUMENTS

EP 798454 A2 10/1997
EP 1936238 A2 6/2008
(Continued)

(21) Appl. No.: **15/590,606**

(22) Filed: **May 9, 2017**

OTHER PUBLICATIONS

(65) **Prior Publication Data**
US 2017/0335710 A1 Nov. 23, 2017

Extended European Search Report, European Application No. 17170030. 5-1610, dated Oct. 17, 2017, 9 pages.
(Continued)

Related U.S. Application Data

(60) Provisional application No. 62/338,201, filed on May 18, 2016, provisional application No. 62/338,204,
(Continued)

Primary Examiner — Arun Goyal
Assistant Examiner — Henry Ng
(74) *Attorney, Agent, or Firm* — Barnes & Thornburg LLP


(51) **Int. Cl.**
F01D 15/10 (2006.01)
F02C 7/32 (2006.01)
(Continued)

(57) **ABSTRACT**

A turbofan gas turbine engine includes low pressure (LP) motor-generator operable in either a generation mode or a drive mode, an high pressure (HP) motor-generator operable in a either a generation mode or a drive mode, and a power control module for selectively operating the LP and HP motor-generators according to operational conditions of the engine.

(52) **U.S. Cl.**
CPC *B60R 16/03* (2013.01); *B64D 27/10* (2013.01); *F01D 15/10* (2013.01); *F01D 17/02* (2013.01); *F01D 17/24* (2013.01); *F02C 3/04* (2013.01); *F02C 3/10* (2013.01); *F02C 7/06* (2013.01); *F02C 7/275* (2013.01); *F02C*

9 Claims, 10 Drawing Sheets



Related U.S. Application Data

filed on May 18, 2016, provisional application No. 62/338,205, filed on May 18, 2016, provisional application No. 62/433,576, filed on Dec. 13, 2016.

(51) **Int. Cl.**

F02C 3/10 (2006.01)
F02K 3/06 (2006.01)
F02C 3/04 (2006.01)
F02C 7/06 (2006.01)
F02C 7/275 (2006.01)
F02C 7/36 (2006.01)
F01D 17/02 (2006.01)
F01D 17/24 (2006.01)
B60R 16/03 (2006.01)
H02K 7/18 (2006.01)
H02K 5/173 (2006.01)
H02K 9/19 (2006.01)
B64D 27/10 (2006.01)
H02P 9/04 (2006.01)

(52) **U.S. Cl.**

CPC **H02K 7/1823** (2013.01); **H02K 9/19** (2013.01); **H02P 9/04** (2013.01); **F05D 2220/323** (2013.01); **F05D 2220/36** (2013.01); **F05D 2220/76** (2013.01); **H02K 2203/09** (2013.01)

(56)

References Cited

U.S. PATENT DOCUMENTS

5,867,979 A 2/1999 Newton et al.
 6,064,123 A 5/2000 Gislason et al.
 6,729,140 B2 5/2004 Care et al.
 6,851,267 B2 2/2005 Bruno et al.
 6,914,344 B2 7/2005 Franchet et al.
 7,484,354 B2 2/2009 Stretton
 8,198,744 B2 6/2012 Kern et al.

8,424,280 B2 4/2013 Moore et al.
 9,121,351 B2 9/2015 Ress, Jr. et al.
 9,273,610 B2* 3/2016 Fingleton F02C 3/107
 9,657,646 B2 5/2017 Wotzak
 2005/0132693 A1 6/2005 Macfarlane et al.
 2006/0101804 A1 5/2006 Stretton
 2006/0225431 A1 10/2006 Kupratis
 2006/0260323 A1 11/2006 Moulebhar
 2007/0137219 A1 6/2007 Linet et al.
 2007/0151258 A1 7/2007 Gaines et al.
 2008/0120980 A1 5/2008 Gemin et al.
 2008/0148881 A1 6/2008 Moniz et al.
 2008/0265580 A1 10/2008 Sharp
 2009/0007568 A1 1/2009 Eccles et al.
 2009/0175716 A1 7/2009 Vettters
 2009/0290976 A1 11/2009 Suci et al.
 2014/0263820 A1* 9/2014 Smith B64C 27/006
 244/17.13
 2014/0271117 A1* 9/2014 Armstrong F02C 7/32
 415/1
 2014/0356135 A1 12/2014 French et al.
 2016/0053690 A1* 2/2016 Perkinson F02C 3/10
 60/778
 2016/0332740 A1* 11/2016 Eisenhauer F02C 9/00

FOREIGN PATENT DOCUMENTS

EP 1947311 A2 7/2008
 EP 1990519 A2 11/2008
 EP 2887536 A1 6/2015
 EP 2889452 A1 7/2015
 GB 1127659 A 9/1968
 WO 1995002120 A1 1/1995

OTHER PUBLICATIONS

European Office Action, dated Feb. 25, 2019 in connection with European Application No. 17170030.5, 7 pages.
 European Office Action, dated Mar. 12, 2020 in connection with European Application No. 17170030.5, 4 pages.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15

1

CONTROL OF LOW PRESSURE GENERATOR FOR GAS TURBINE ENGINE

CROSS REFERENCE TO RELATED APPLICATIONS

This application claims priority to and the benefit of U.S. Provisional Patent Application Nos. 62/338,201, filed 18 May 2016; 62/338,204, filed 18 May 2016; 62/338,205, filed 18 May 2016; and 62/433,576, filed 13 Dec. 2016, the disclosures of which are now expressly incorporated herein by reference.

FIELD OF THE DISCLOSURE

The present disclosure relates generally to gas turbine engines, and more specifically to auxiliary electric power generators of gas turbine engines.

BACKGROUND

Gas turbine engines are used to power aircraft, watercraft, electrical generators, and the like. Gas turbine engines typically include a compressor, a combustor, and a turbine. The compressor compresses air drawn into the engine and delivers high pressure air to the combustor. In the combustor, fuel is mixed with the high pressure air and is ignited. Exhaust products of the combustion reaction in the combustor are directed into the turbine where work is extracted to drive the compressor and, sometimes, an output shaft, fan, or propeller. Portions of the work extracted from the turbine can be used to drive various subsystems such as generators.

SUMMARY

The present disclosure may comprise one or more of the following features and combinations thereof.

According to an aspect of the present disclosure, a turbofan gas turbine engine may include a low pressure spool including a fan rotor, a low pressure turbine rotor, a low pressure drive shaft extending along an axis and rotationally coupling the fan rotor to receive driven rotation about the axis from the low pressure turbine rotor, and a low pressure motor-generator mounted on the low pressure drive shaft and adapted for selective operation between a generation mode to generate electric power from driven rotation of the low pressure turbine rotor and a drive mode to electrically drive rotation of the low pressure drive shaft, a high pressure spool including a compressor rotor, a high pressure turbine rotor, a high pressure drive shaft extending along the axis and rotationally coupling the compressor rotor to receive driven rotation about the axis from the high pressure turbine rotor, and an high pressure motor-generator adapted for selective operation between a generation mode to generate electric power from driven rotation of the high pressure turbine rotor and a drive mode to electrically drive rotation of the high pressure drive shaft, and a power control module electrically connected to each of the low pressure motor-generator and the high pressure motor-generator and configured to determine operational conditions of the engine and to selectively operate each of the low pressure motor-generator and the high pressure motor-generator in either of the generation mode and the drive mode based on the determined operational conditions of the engine.

In some embodiments, in response to determination that the operational conditions are steady state operational con-

2

ditions, the power control module may be configured to operate the low pressure motor-generator in the generation mode under.

In some embodiments, in response to determination that the operational conditions include an efficiency of the high pressure spool that is below a predetermined threshold, the power control module may be configured to operate the low pressure motor-generator in the generation mode and to operate the high pressure motor-generator in the drive mode to assist rotation of the high pressure drive shaft.

In some embodiments, the predetermined threshold may be a predetermined fuel efficiency of the high pressure spool.

In some embodiments, in response to determination that the operational conditions include an efficiency of the low pressure spool that is below a predetermined threshold, the power control module may be configured to operate the high pressure motor-generator in the generation mode and to operate the low pressure motor-generator in the drive mode to assist rotation of the low pressure drive shaft.

In some embodiments, in response to determination that the operational conditions are high demand operational conditions, the power control module is configured to operate the low pressure motor-generator in the generation mode and to operate the high pressure motor-generator in the drive mode to assist the rotation of the high pressure drive shaft.

In some embodiments, high demand operational conditions may include determination that a compressor surge margin is below a predetermined threshold value.

In some embodiments, the turbofan gas turbine engine may be adapted for use in an aircraft and high demand operational conditions include determination that a flight altitude is above a predetermined threshold value.

In some embodiments, high demand operational conditions may include determination of a disruption of rotation of the fan rotor.

In some embodiments, the engine may be adapted for use in an aircraft and, in response to determination that the operational conditions include in-flight restart, the power control module is configured to operate the low pressure motor-generator in the generation mode and to operate the high pressure motor-generator in the drive mode to assist restart of the engine.

In some embodiments, in response to determination that the operational conditions include loss of engine power, the power control module may be configured to selectively operate the low pressure motor-generator in the drive mode to provide thrust assist.

In some embodiments, the turbofan gas turbine engine may include an energy storage device electrically connected to the power control module to selectively communicate electric power with the power control module.

According to another aspect of the disclosure, a method of operating a turbofan gas turbine engine of an aircraft having a low pressure spool and a high pressure spool may include determining operational conditions of the aircraft, selectively operating a low pressure motor-generator of the low pressure spool between a generation mode to generate electric power from driven rotation of a low pressure turbine rotor of the low pressure spool and a drive mode to electrically drive rotation of a low pressure drive shaft of the low pressure spool based on the determined operational conditions of the aircraft, and selectively operating a high pressure motor-generator of the high pressure spool between a generation mode to generate electric power from driven rotation of an high pressure turbine rotor of the high pressure spool and a drive mode to electrically drive rotation of a high

pressure drive shaft of the high pressure spool based on the determined operational conditions of the aircraft.

In some embodiments, selectively operating the low pressure motor-generator may include, in response to determination that operational conditions are steady state, operating the low pressure motor-generator in the generation mode.

In some embodiments, selectively operating the low pressure motor-generator and selectively operating the high pressure motor-generator respectively may include, in response to determination that the operational conditions include an efficiency of the high pressure spool that is below a predetermined threshold, operating the low pressure motor-generator in the generation mode and operating the high pressure motor-generator in the drive mode, to assist rotation of the high pressure drive shaft.

In some embodiments, the predetermined threshold may be a predetermined fuel efficiency of the high pressure spool.

In some embodiments, selectively operating the high pressure motor-generator and selectively operating the low pressure motor-generator respectively may include, in response to a determination that operational conditions include an efficiency of the low pressure turbine section is below a predetermined threshold, operating the high pressure motor-generator in the generation mode, and operating the low pressure motor-generator in the drive mode, to assist rotation of the low pressure drive shaft.

In some embodiments, selectively operating the high pressure motor-generator and selectively operating the low pressure motor-generator respectively may include, in response to a determination that the operational conditions include high demand conditions, operating the high pressure motor-generator in the drive mode to assist rotation of the high pressure drive shaft, and operating the low pressure motor-generator in the generation mode to supply electric power to the high pressure motor-generator.

In some embodiments, the high demand conditions may include compressor surge margin being below a threshold value.

In some embodiments, the high demand conditions may include flight altitude being above a predetermined threshold value.

In some embodiments, the method may include selectively storing electric power from one of the low pressure motor-generator and the high pressure motor-generator in an energy storage device based on the determined operational conditions of the aircraft.

These and other features of the present disclosure will become more apparent from the following description of the illustrative embodiments.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of an illustrative embodiment of a turbofan gas turbine engine with a portion cut away to show that the gas turbine engine includes a low pressure turbine spool and a high pressure spool, and showing that the low pressure spool includes a fan disposed on a forward end of the engine, a low pressure turbine rotor disposed on an aft end of the engine, and a low pressure drive shaft that extends along an axis between the forward and aft ends and is connected to each of the fan rotor and the low pressure turbine rotor to transfer rotational drive from the low pressure turbine rotor to the fan, and showing that the high pressure spool includes a compressor, a high pressure turbine rotor, and a high pressure drive shaft that extends concentrically with the low pressure drive shaft and is connected to each of the high pressure turbine rotor and the

compressor to transfer rotational drive from the high pressure turbine rotor to the compressor, and showing that the engine includes a low pressure electric motor-generator that is positioned between the fan and the compressor along the axis and is rotationally coupled to the low pressure drive shaft for selective operation as a generator to generate electric power from rotation of the low pressure drive shaft or as an electric motor to assist rotation of the low pressure drive shaft;

FIG. 2 is a perspective view of a portion of the turbofan gas turbine engine of FIG. 1 in cross-section taken along the cross-sectional plane 2-2 showing that the low pressure drive shaft includes a fan shaft and a quill shaft that is rotationally coupled to the fan shaft by a quill connection that allows movement of the fan shaft relative to the quill shaft while transferring rotational drive, and showing that the low pressure motor-generator includes a generator core having a rotor rotationally coupled with the quill shaft and a stator arranged outside of the rotor and fixed against rotation relative to the rotor, and showing that the low pressure motor-generator includes a generator housing positioned radially outside of the quill shaft and bearings disposed radially between the generator housing and the quill shaft, and a number of coolant pathways for distributing lubricant to the low pressure motor-generator;

FIG. 3 is a perspective view of the low pressure motor-generator of FIG. 2 showing that the generator housing includes a can receptacle and a cover attached to the aft end of the can receptacle, and showing that the turbofan gas turbine engine includes an electrical assembly connected to the cover of generator housing and extending radially outward from the low pressure motor-generator for connection with other loads;

FIG. 4 is an exploded perspective view of the low pressure motor generator of FIGS. 2 and 3 showing that the generator housing includes an interior cavity for housing the low pressure motor-generator core and a shaft opening therethrough for receiving the low pressure drive shaft, and showing that the quill shaft includes splines extending inwardly to form the quill connection with the fan shaft;

FIG. 5 is a perspective view of a support frame of the turbofan gas turbine engine of FIG. 1 showing that the support frame includes a number of struts extending radially to connect with a number of support collars of the support frame, and showing that the low pressure motor-generator is positioned between the fan and the support frame along the axis;

FIG. 6 is a perspective cross-sectional view of the support frame of FIG. 6 taken along the line 6-6 and showing that the electrical assembly of the LP motor-generator includes a connector electrically connected to the stator and attached to the housing of the low pressure motor-generator, a terminal base attached to an outer collar of the support frame, and a number of busbars that extend between and connect to each of the connector and the terminal base, and showing that the busbars extend radially through one of the struts to electrically connect the connector to the terminal base;

FIG. 7 is a partially diagrammatic view of the turbofan gas turbine engine of FIG. 1 showing that the engine includes a high pressure motor-generator adapted to be driven for rotation by the high pressure drive shaft, and showing that the engine includes a power control module that is electrically connected to each of the low pressure motor-generator and the high pressure motor-generator and is arranged for selectively operating each of the low pressure and high pressure motor-generators independently between the generation modes and the drive modes, and showing that

5

the power control module is connected to communicate electrical power with an optional energy storage device, and showing by example that the power control module determines that steady state operational conditions exist, and in response to steady state conditions, the power control module operates the low pressure motor-generator in the generation mode and distributes electrical power generated by the low pressure motor-generator to an electrical user and selectively exchanges electrical power with the energy storage device;

FIG. 8 is a partially diagrammatic view of the turbofan gas turbine engine of FIGS. 1 and 7 showing by example that the power control module can exchange power between low pressure motor-generator and high pressure motor-generator to adjust loads applied to low pressure and high pressure spools in order to improve engine efficiency;

FIG. 9 is a partially diagrammatic view of the turbofan gas turbine engine of FIGS. 1, 7, and 8 showing by example that the power control module determines that high demand operational conditions exist and in response the power control module operates the low pressure motor-generator in the generation mode and operates the high pressure motor-generator in the drive mode to assist rotation of the high pressure drive shaft and reduce load on the high pressure spool, and showing that the power control module selectively exchanges electrical power with the energy storage device;

FIG. 10 is a partially diagrammatic view of the turbofan gas turbine engine of FIGS. 1 and 7-9 showing by example that the power control module determines that in-flight restart operational conditions exist and in, the power control module operates the low pressure motor-generator in the generation mode and operates the high pressure motor-generator in the drive mode to assist in-flight restart of the engine, and showing that the power control module receives electrical power from the energy storage device;

FIG. 11 is a partially diagrammatic view of the turbofan gas turbine engine of FIGS. 1 and 7-10 showing by example that the power control module determines that loss of engine power operational conditions exist and in response, the power control module selectively operates the low pressure motor-generator in the drive mode to provide thrust assist;

FIG. 12 is a partially diagrammatic view of the turbofan gas turbine engine of FIGS. 1 and 7-11 showing by example that the power control module determines that hot engine off operational conditions exist in which the engine is desirably shut down but remains at relatively high temperature and in response the power control module operates the low pressure motor-generator in the drive mode to provide electrically driven rotation of the fan to provide air to the engine for cooling engine components and expelling fumes;

FIG. 13 is a partially diagrammatic view of the turbofan gas turbine engine of FIGS. 1 and 7-12 showing that the power control module is electrically connected to a second high pressure motor-generator of a second gas turbine engine for individual selective operation between generation and drive modes to permit selective distribution of power between the engine and the second engine, and showing by example that the power control module determines that operational conditions do not meet threshold efficiencies, and in response to determination that operational conditions do not meet a threshold efficiency of the low pressure spool of the engine, the power control module receives electric power from the second engine and operates the low pressure motor-generator in the drive mode;

FIG. 14 is a partially diagrammatic view of the turbofan gas turbine engine of FIGS. 1 and 7-13 showing that the

6

power control module is electrically connected to ground power source and determines that cool engine off operational conditions exist in which the engine is desirably shut down and remains at relatively cool temperature and in the power control module operates the low pressure motor-generator in the drive mode to inhibit rotation of the fan rotor to prevent rotation of the engine; and

FIG. 15 is a perspective view of a cross-section of another illustrative embodiment of the low pressure electric motor-generator of the turbofan gas turbine engine of FIG. 1 taken along the plane 2-2 and showing that the low pressure drive shaft includes a fan shaft and a quill shaft that is rotationally coupled to the fan shaft and extends from the fan shaft to rotationally connect the fan shaft and the rotor of the low pressure motor-generator for rotation.

DETAILED DESCRIPTION OF THE DRAWINGS

For the purposes of promoting an understanding of the principles of the disclosure, reference will now be made to a number of illustrative embodiments illustrated in the drawings and specific language will be used to describe the same.

Gas turbine engines may be adapted for various uses, such as to propel aircraft, watercraft, and/or for power generation. The electrical power demands on gas turbine engines adapted for such uses are rapidly increasing due to the growing number and power requirement of processors, actuators, and accessories. However, drawing additional electric power from high pressure (HP) driven electric generators can limit the operation of the gas turbine engine, for example, by decreasing certain operating margins at peak demand.

The present disclosure includes descriptions of gas turbine engines that include low pressure (LP) motor-generators configured to supply of electric power. In certain adapted uses of the engines, for example, when adapted for use in an aircraft, the present disclosure includes devices, systems, and methods for integration of low pressure (LP) motor-generators into turbofan gas turbine engines. Motor-generators include devices that can be selectively operated in a first mode to generate electricity for use in other systems and in a second mode to drive mechanical rotation by consumption of electrical power. Coordinated operation of low pressure (LP) and/or high pressure (HP) motor-generators in response to various operational conditions promotes operational flexibility and power management optimization.

As shown in FIG. 1, an illustrative turbofan gas turbine engine 10 includes a fan 12, a compressor 14 having a compressor rotor 15, a combustor 16, and a turbine 18 having a high pressure (HP) turbine rotor 20 and a low pressure (LP) turbine rotor 22, housed within a casing 24 as shown in FIG. 1. The fan 12 draws air into the compressor 14 that compresses and delivers the air to the combustor 16. The combustor 16 mixes fuel with the compressed air from the compressor 14 and combusts the mixture. The hot, high-pressure exhaust products of the combustion reaction in the combustor 16 are directed into the turbine 18 to cause rotation of the HP and LP turbine rotors 20, 22 about an axis 25 to drive the compressor 14 and the fan 12, respectively.

In the illustrative embodiment, the gas turbine engine 10 includes a high pressure (HP) spool 26 illustratively comprising the compressor rotor 15, the HP turbine rotor 20, and a high pressure (HP) drive shaft 28 that extends along the axis 25 to couple the compressor 14 for rotation with the HP turbine rotor 20. In the illustrative embodiment, the gas turbine engine 10 includes a low pressure (LP) spool 30

illustratively comprising the fan 12, the LP turbine rotor 22, and a low pressure drive shaft 32 that extends along the axis 25 to couple the fan 12 for rotation with the LP turbine rotor 22. In the illustrative embodiment, the drive shafts 28, 32 are concentric shafts that extend along the axis 25 between forward 34 and aft ends 36 of the engine 10.

In the illustrative embodiment as shown in FIG. 1, the engine 10 includes a low pressure (LP) motor-generator 38 positioned between the fan 12 and the compressor 14 along the axis 25. As shown in FIG. 2, the LP motor-generator 38 illustratively includes a motor-generator core 40 having a stator 42 fixed against rotation relative to the LP drive shaft 32 and a rotor 44 coupled to the LP drive shaft 32 for rotation. The stator 42 is illustratively includes a number of stator windings 43 positioned radially outward of the rotor 44, such that each is illustratively arranged in electromagnetic communication. In some embodiments, the motor-generator core 40 may include any suitable type and/or arrangement of electro-mechanical motor and/or generator. The LP motor-generator 38 is illustratively adapted for selective operation between a generation mode to generate electrical power from rotation of the LP turbine 22 and in a drive mode to receive electrical power for applying rotational force to the LP drive shaft 32.

As shown in FIG. 2, the LP drive shaft 32 illustratively includes a fan shaft 46 and a quill shaft 48 forming quill connections with each of the fan shaft 46 and a rotor hub 106 (on which the rotor 44 is illustratively mounted) to connect the rotor 44 for rotation with the fan shaft 46 while permitting relative movement therebetween. The quill shaft 48 illustratively includes a base 50 coupled to the fan shaft 46 and a flange 52 extending from the base 50 for connection with the rotor hub 106. The rotor 44 of the LP motor generator 38 is illustratively mounted on the rotor hub 106, which is supported by bearings 152, 154 (as discussed below), while being connected for rotation with the LP drive shaft 32 through the quill shaft 48. In some embodiments, a single quill connection may be used to rotationally connect the LP drive shaft 32 with the rotor 44 while permitting relative movement.

As best shown in FIGS. 3 and 6, the LP motor generator 38 illustratively includes an electrical assembly 58 that electrically connects the LP motor-generator 38 to electrical loads of the engine 10. The electrical assembly 58 illustratively includes a connector 62 attached to the LP motor-generator 38, a set of three busbars 64 each having an end coupled with the connector 62, and a terminal base 66 coupled to an opposite end of each of the busbars 64. As shown in FIG. 6, the busbars 64 illustratively extend radially outward from the LP motor generator 38 through a strut 56 of a support frame 54 of the engine 10 for connection with the terminal base 66 to communicate electric power to and from the LP motor-generator 38.

As shown in FIGS. 7-14, the turbofan gas turbine engine 10 illustratively includes a high pressure (HP) motor-generator 68. The HP motor-generator 68 is illustratively embodied as being coupled to an auxiliary shaft 69 to receive driven rotation from the HP drive shaft 28. The HP motor-generator 68 is illustratively adapted for selective operation in a generation mode to generate electrical power from rotation of the HP turbine rotor 20 or in a drive mode to receive electrical power to assist rotation of the HP drive shaft 28.

In the illustrative embodiment, the turbofan gas turbine engine 10 includes a power control module 70 for governing electric power distribution within the engine 10. The power control module 70 is illustratively electrically connected to

each of the LP motor-generator 38 and HP motor-generator 68. The power control module 70 is adapted to selectively receive and distribute electric power between the LP and HP motor-generators 38, 68, electric power users 72 (such as an airframe of a vehicle (aircraft) in adapted use of the engine 10), and an energy storage device 74 (such as a battery), according to operational conditions of the engine 10 (and/or the vehicle).

As explained in detail below, the power control module 70 governs electric power management based on the operational conditions of the engine 10. Under some conditions, the power control module 70 can direct electric power to the HP motor-generator 68 to assist rotation of the HP drive shaft 28 and/or reduce load on the HP turbine rotor 20. Under some conditions, the power control module 70 directs electric power to the LP motor-generator 38 to assist rotation of the LP drive shaft 32 and/or reduce load on the LP turbine rotor 22. Under some conditions, the power control module 70 communicates electrical power between one or both of the motor-generators 38, 68 and the energy storage device 74, and/or from any of the motor-generators 38, 68 and the energy storage device 74 to electric power users 72. As shown in FIG. 13, the power control module 70 can be electrically connected to a second engine 111 to govern electric power management between engines 10, 111.

Returning now to FIGS. 1 and 2, the fan 12 is illustratively disposed at the forward end 34 of the engine 10. The fan 12 is illustratively attached to a fan shaft 46 of the LP drive shaft 32 for rotation about axis 25. The fan 12 illustratively includes a fan rotor 76 and fan blades 78 that extend radially from the fan rotor 76. The fan rotor 76 illustratively rotates the fan blades 78 about axis 25 to direct air axially into the engine 10.

In the illustrative embodiment as shown in FIG. 2, the fan shaft 46 of the LP drive shaft 32 is embodied as a hollow shaft that extends through the LP motor-generator 38 for connection with the fan rotor 76. The fan shaft 46 is illustratively configured for splined connection with the LP drive shaft 32, but in some embodiments may be integral with the LP drive shaft 32. The fan shaft 46 of the LP drive shaft 32 receives driven rotation from the LP turbine rotor 22.

As shown in FIG. 2, the fan shaft 46 illustratively includes a first section 80 having an outer diameter, a tapered section 82 that extends from the first section 80 along the direction of the axis 25 towards the forward end 34, and a hub 84 extending from the tapered section 82 along the axis 25 for connection with the fan 12.

In the illustrative embodiment, the first section 80 of the fan shaft 46 is illustratively coupled with the LP turbine rotor 22 to receive driven rotation. The first section 80 illustratively includes an outer surface 86 having splines 88 that each extend along the direction of the axis 25 and have a radial height for connection with the quill shaft 48 (also shown in FIG. 3). The outer surface 86 aftward of the splines 88 illustratively contacts a shaft bearing 92 to provide rotational support to the fan shaft 46.

As shown in FIG. 2, the first section 80 is illustratively positioned to extend axially through the LP motor-generator 38 to connect with the tapered section 82. The tapered section 82 illustratively includes a tapered outer diameter that increases in size along the axial direction moving towards the forward end 34. The tapered section 82 is illustratively positioned to extend axially through the LP motor-generator 38 to connect with the hub 84.

As shown in FIG. 2, the hub 84 illustratively includes a tiered section 90 adapted for contact with a shaft bearing 93

to support the LP drive shaft **32** for rotation within the engine **10**. Each of the shaft bearings **92, 93** are illustratively arranged to receive lubricant from a lubricant distribution system **94** of the engine **10**. The tiered section **90** illustratively includes a constant outer diameter that contacts a shaft bearing **93** to reduce friction of the fan shaft **46** during rotation.

As shown in FIG. 2, the fan shaft **46** is coupled with the quill shaft **48** for rotation. The quill shaft **48** is illustratively embodied as a hollow coupler forming a quill connection with the fan shaft **46** and the rotor hub **106** on which the rotor **44** is mounted. The base **50** of the quill shaft **48** illustratively includes a hollow cylinder **96** having an inner surface **98** and splines **100** that each extend along the direction of the axis **25** and have a radial height (also shown in FIG. 4). The splines **100** of the quill shaft **48** are illustratively arranged complimentary to the splines **88** of the first section **80** of the fan shaft **46** to form the quill connection to allow relative movement between the fan shaft **46** and the quill shaft **48** while providing rotational coupling therebetween. The quill connection provides an offset from the fan shaft **46** to accommodate non-concentric rotation of the fan shaft **46** during a fan imbalance and/or blade off event, and/or axial misalignment therebetween.

The quill shaft **48** illustratively includes the flange **52** that extends radially outward from the base **50** for rotational connection with the LP motor-generator **38**. The flange **52** illustratively includes a neck **102** extending radially from the base **50** and a stem **104** connected to the neck **102** and partitioned radially spaced apart from the base **50**. The stem **104** illustratively forms another quill connection to the rotor hub **106** of the LP motor generator **38** that supports the rotor **44** for rotation with the LP drive shaft **32**. The stem **104** illustratively includes splines **105** formed on an outer surface thereof and complimentary to splines **107** form on an inner surface of the rotor hub **106** to form the quill connection to allow relative movement between the rotor hub **106** and the quill shaft **48** while providing rotational coupling therebetween.

Referring to FIG. 3, the LP motor-generator **38** illustratively includes a housing **108** having a receptacle **110** and a cover **112** attached to the receptacle **110** and together defining an interior cavity **114** (as shown in FIG. 2) for receiving the motor-generator core **40**. As best shown in FIG. 2, the receptacle **110** illustratively includes an annular shell **116** extending along the direction of the axis **25** between a forward end **118** and an aft end **120**, a mount flange **122** attached to the aft end **120** of the annular shell **116**, and an overhang **124** attached to the forward end **118** of the annular shell **116**.

As best shown in FIG. 2, the overhang **124** includes a limb **126** that extends radially inward from the forward end **118** of the annular shell **116** and an extension **128** connected to a radially inward end **130** of the limb **126**. The extension **128** illustratively extends from the limb **126** parallel to the axis **25** towards the aft end **120** spaced apart from the annular shell **116** by the radial length of the limb **126** to define a portion of the interior cavity **114**. The mount flange **122** is illustratively embodied as an annular flange extending perpendicularly to the axis **25** to receive connection of the cover **112**.

The cover **112** illustratively includes a cover flange **132** for connection to the mount flange **122** of the receptacle **110**, an annular section **134** extending from the cover flange **132** towards the aft end **36** of the engine **10**, and an overhang **136** extending from the annular section **134**. In the illustrative embodiment, the annular section **134** has a tapered outer

diameter increasing in size move towards the forward end **34** along the axis **25**. The overhang **136** of the cover **112** illustratively includes a limb **138** extending radially inward from the aft end of the annular section **134** and an extension **140** connected to the radially inward end **142** of the limb **138**. The extension **140** illustratively extends from the limb **138** parallel to the axis **25** towards the cover flange **132** spaced apart from the annular section **134** to define a portion of the interior cavity **114** of the housing **108**.

In the illustrative embodiment as shown in FIG. 2, the extensions **128, 140** are radially aligned and define a gap **142** axially therebetween. When the motor-generator core **40** is received within the interior cavity **114**, the rotor **44** is illustratively positioned within the gap **142** in electromagnetic communication with the stator **42**. The extensions **128, 140** each respectively include an inner surface **144, 146** and an outer surface **148, 150** adapted to support a respective bearing **152, 154** of the LP motor-generator **38**.

The bearings **152, 154** are each illustratively embodied as a roller ball bearing having an outer race **156** that contacts the inner surface **144, 146** of the respective extension **128, 140** and an inner race **158** that contacts an outer surface **160** of the inner shaft **106** on which the rotor **44** is mounted. In the illustrative embodiment, the rotor **44** is coupled to the inner shaft **106** at a position between the bearings **152, 154** for rotation with the fan shaft **46**.

As shown in FIG. 2, the turbofan gas turbine engine **10** illustratively includes the lubricant distribution system **94** embodied as lubricant conduits formed within portions of the casing **24** for communicating lubricant, such as oil, to the bearings **92, 93, 152, 154** and the stator **42**. In the illustrative embodiment, the housing **108** of the LP motor-generator **38** includes lubrication pathways **162** defined therein. The lubrication pathways **162** illustratively extend radially through the annular shell **116** to provide communication of lubricant from the lubricant distribution system **94** to the stator **42**.

As shown in the illustrative embodiment of FIG. 3, the electrical assembly **58** is electrically connected to the LP motor-generator **38** to provide three electrically isolated busses for 3-phase power communication. In some embodiments, the electrical assembly **58** may be configured to communicate any suitable number of phase power. The connector **62** of the electrical assembly **58** is illustratively attached to the cover **112** at an aft side **164** of the LP motor-generator **38**. The connector **62** includes a mount **166** connected to the cover **112** and a body **168** that extends from the mount **166** to connect with the busbars **64**.

In the illustrative embodiment, the mount **166** extends generally for a length between opposite ends **170, 172** thereof and includes a mount hole **174** defined therethrough on each end **170, 172** to receive a fastener for connection to the cover **112**. The mount **166** is illustratively arranged generally tangential to the annular section **134**. The body **168** illustratively extends from the mount **166** at a position between the ends **170, 172** and in a direction perpendicular to the length of the mount **166**. The body **168** illustratively includes a side **176** facing radially outward from the axis **25** having three recesses **176** defined therein for connection with one of the busbars **64**.

As best show in FIGS. 2 and 6, the connector **62** illustratively includes three electrical connections **178** each comprising a socket **180** disposed within the body **168** and wires **182** connected to the socket **180**. Each socket **180** is illustratively embodied as a receptacle formed of conductive material and including interior threads **183** complimentary to exterior threads **184** of the busbars **64** to form a threaded

connection between the connector **62** and the busbars **64**. In some embodiments, the connector **62** may include a floating connection with the busbars **64** to allow thermal movement therebetween while maintaining electrical connection.

In the illustrative embodiment as shown in FIG. 2, each of the wires **182** is illustratively attached to one of the sockets **180** and is isolated from the other wires **182**. The wires **182** each illustratively extend through the body **168** and the mount **166** for connection with the stator **42** of the LP motor-generator **38**. The busbars **64** are illustratively electrically connected to the LP motor-generator **38** via the electrical connections **178**.

Referring now to the illustrative embodiment as shown in FIGS. 5 and 6, the LP motor-generator **38** is positioned forward of the support frame **54** of the engine **10** along the axis **25**. The support frame **54** illustratively includes a hub **186** surrounding the axis **25** for receiving the LP motor-generator **38**, a collar **188** arranged radially outward of the hub **186**, and the strut **56** extending radially between the hub **186** and the collar **188**.

As shown in FIG. 6, the hub **186** illustratively defines an interior space **190** therethrough to receive the aft end of the LP motor-generator **38**. The LP drive shaft **32** penetrates through the interior space **190** of the hub **186** for connection with the LP motor-generator **38**. The strut **56** illustratively connects with the hub **186** at an angular position of the connector **62** relative to the axis **25** that is complimentary, and illustratively equal, to the angular position about the axis **25**.

As best shown in FIG. 5, the strut **56** illustratively includes a smooth outer surface **192** to minimize flow resistance. The strut **56** illustratively includes an interior cavity **194** defined therein that extends radially between the hub **186** and the collar **188**. The interior cavity **194** illustratively receives the busbars **64** therethrough to extend between the connector **62** and the terminal base **66**. Positioning the busbars **64** within the strut **56** provides physical protection while permitting conductive cooling of the busbars **64** by air passed over the strut **56**.

In the illustrative embodiment, the busbars **64** are each embodied as a rod formed of electrically conductive material, for example, copper. The busbars **64** each illustratively include the exterior threads **184** disposed on one end for fixed connection to one of the connector **62** and the terminal base **66**, and a cylindrical shape on the opposite end to slidably connect with the other of the connector **62** and the terminal base **66** to form a floating connection to accommodate thermal expansion. The busbars **64** are illustratively embodied to be secured within the interior cavity **194** surrounded with potting compound **196** to electrically isolate the busbars **64** from each other. The busbars **64** illustratively extend radially between the connector **62** and the terminal base **66** at an angle relative to a plane that is perpendicular to the axis **25**.

As best shown in FIG. 6, the terminal base **66** is illustratively attached to the collar **188** at a position spaced apart from the connector along the axis **25**. The terminal base **66** illustratively includes a body **198** having three slots **200** defined radially therethrough each including a terminal socket **202** arranged therein to slidably receive one of the busbars **64** therein for electrical connection. The terminal sockets **202** are each illustratively embodied to include a hollow cylinder section **204** disposed within the body **198** and a stem **206** extending from the hollow cylinder section **204** radially outside of the body **198** as a terminal post for connection to electrical loads of the engine **10**. The terminal sockets **202** are illustratively formed of electrically conduc-

tive material to communicate electric power between the LP motor-generator **38** and electrical loads of the engine **10**. In some embodiments, the busbars **64** may be fixedly connected to the terminal base **66** and have a floating connection with the connector **62**.

Referring now to the illustrative embodiments of FIGS. 7-14, the gas turbine engine **10** includes the power control module **70** that is electrically connected to each of the LP motor-generator **38** and HP motor-generator **68**. As mentioned above, the power control module **70** governs electric power management of the engine **10** based on the operational conditions of the engine **10**.

The power control module **70** is illustratively embodied as a main control unit including a processor **208**, a memory device **210** that stores instructions for execution by the processor **208**, communications circuitry **212** adapted to communicate signals with various components of engine **10** as directed by the processor **208**, and power distribution circuitry **214** adapted to communicate electric power with any of the motor-generators **38**, **68**, power users **72**, and the energy storage device **74** as directed by the processor **208**. The power control module **70** determines operational conditions of the engine based on signals received from various engine components and selectively operates the LP and HP motor-generators **38**, **68** based on the determined operational conditions.

In the illustrative embodiment as shown in FIG. 7, the power control module **70** determines that the current operational conditions are steady state conditions. The steady state conditions illustratively include operational conditions in which the loads on the HP spool and the LP spool are within normal operating ranges such that no electrically-driven force of rotation on the drive shafts **28**, **32** is provided. Examples of such steady state conditions when the turbofan gas turbine engine **10** is adapted for use in an aircraft include ground idle, flight idle conditions, and/or flight cruise conditions.

In the illustrative embodiment, in response to steady state conditions, the power control module **70** is configured to operate the LP motor-generator **38** in the generation mode. The power control module **70** illustratively directs electric power generated by the LP motor-generator **38** to the power users **72** and selectively communicates electric power with the energy storage device **74**. The power control module **70** is illustratively embodied to selectively communicate electric power with the energy storage device **74** based on the operational conditions and the power storage levels of the energy storage device **74**.

In the illustrative embodiment as shown in FIG. 8, the power control module **70** determines that the current operational conditions include low efficiency conditions. Low efficiency conditions include efficiencies of either of the HP spool **26** or LP spool **30** that are less than respective predetermined threshold efficiencies. In the illustrative embodiment, the efficiency of the HP spool **26** includes a fuel efficiency of the HP spool **26** as represented by an operating point of the compressor **14** along an operating curve as reflected on a plot of pressure ratio versus corrected flow.

In the illustrative embodiment, in response to determination of low efficiency conditions, the power control module **70** can selectively direct electric power generated from the LP motor-generator **38** in the generator mode to the HP motor-generator **68** in the drive mode to adjust the operating point of the compressor **14** along the operating curve to improve fuel efficiency of the HP spool **26**. In the illustrative embodiment, the power control module **70** can selectively

13

direct electric power generated from the HP motor-generator **68** in the generator mode to the LP motor-generator **38** in the drive mode to adjust the operating point of the compressor **14** along the operating curve to improve fuel efficiency of the HP spool **26**. Thus, the power control module can selectively adjust the operating point of the compressor **14** along its operating curve to improve engine fuel efficiency. In some embodiments, such low efficiency conditions when the turbofan gas turbine engine **10** is adapted for use in an aircraft include conditions in which any of the fuel efficiency and/or heat rate are less than a predetermined fuel efficiency and/or predetermined heat rate for either of the HP spool **26** or the LP spool **30**.

In the illustrative embodiment as shown in FIG. **9**, the power control module **70** determines that the operational conditions include high demand operational conditions. The high demand operational conditions illustratively include low compressor surge margin conditions and/or disruption of rotation of the fan **12**. Low compressor surge margin illustratively includes the amount of operating margin between the current compressor operating conditions and compressor surge conditions being below a predetermined threshold value. Examples of such high demand operational conditions when the turbofan gas turbine engine **10** is adapted for use in an aircraft include high altitude flight, fan **12** disruption events (e.g., fan rotor and/or blade damage from ice, birds, debris, etc.).

In the illustrative embodiment, in response to high demand operational conditions, the power control module **70** is configured to operate the LP motor-generator **38** in the generation mode and to direct electric power to the HP motor-generator **68** in the drive mode. For example, when the high demand operational conditions exist due to low compressor surge margin, the power control module **70** illustratively reduces the load on the HP Spool **26** by assisting rotation of the HP drive shaft **32** with the LP motor generator **38**, and increasing the operating margin between the current compressor operating conditions and compressor surge conditions.

In the illustrative embodiment as shown in FIG. **10**, the power control module **70** determines that the operational conditions include hot restart. When the engine **10** is adapted for use in an aircraft, hot restart operational conditions include in-flight restart conditions. Under such in-flight restart conditions, some ram air flow is illustratively received by the fan **12** because the aircraft is currently in flight. In response to hot restart operational conditions, the power control module **70** is illustratively configured to operate the LP motor-generator **38** in the generation mode and to direct electric power to the HP motor-generator **68** in the drive mode to assist restart of the engine **10**. The power control module **70** illustratively directs electric power from the power storage device **74** to the HP motor-generator **68**.

In the illustrative embodiment as shown in FIG. **11**, the power control module **70** determines that the operational conditions include loss of engine power. Loss of engine power illustratively includes an operational shut down of the engine **10**, where operational shut down includes elective shut down and unexpected shut down. In response to determination of loss of engine power operational conditions, the power control module **70** is configured to selectively operate the LP motor-generator **38** in the drive mode to selectively rotate the LP spool **30** to provide thrust assist. The power control module **70** illustratively directs electric power from the power storage device **74** to the LP motor-generator **38**. When the engine **10** is adapted for use in an aircraft, thrust

14

assist can provide light and/or pulse thrust for additional stability control, navigational control, range extension, and/or landing assist.

In the illustrative embodiment as shown in FIG. **12**, the power control module **70** determines that operational conditions include hot engine off conditions. Hot engine off conditions illustratively include engine **10** being electively shut down while an operating temperature remains above a threshold temperature. In the illustrative embodiment, the operating temperature includes a lubricant temperature. In response to determination of hot engine off conditions, the power control module **70** operates the LP motor-generator in the drive mode to drive air through the engine **10**. Passing air through the engine **10** can cool engine components and can provide pressure to prevent accumulation of exhaust products into certain areas.

In the illustrative embodiment as shown in FIG. **13**, the power control module **70** is electrically connected with other turbo fan gas turbine engines **111**, illustratively three other engines **111**. Engines **111** are illustratively embodied as similar to engine **10** and each of the engines **10**, **111** are illustratively adapted for use in the aircraft. In some embodiments, the engines **111** may be any type of engine adapted for use in the aircraft and capable of generating electric power. The power control module **70** illustratively determines that electric high bypass conditions exist in engine **10**. Electric high bypass conditions illustratively include disengagement of engine **10** and one of the other engines **111** but with electrically driven rotation of their fans **12** to maintain high fan area.

In the illustrative embodiment, in response to determination of electric high bypass conditions, the power control module **70** operates the LP motor-generator **38** of the engines **10**, **111** in the drive mode to electrically drive rotation of their respective fans **12**. The power control module **70** illustratively directs electric power from any of the operating engines **111** and the energy storage device **74** to the disengaged engines **10**, **111**. Such selective electric high bypass operation promotes efficiency and flexibility across engines **10**, **111** and their platforms.

In the illustrative embodiment as shown in FIG. **14**, the power control module **70** operates the LP motor-generator **38** to inhibit rotation of the fan **12** while the engine **10** is powered off. The power control module **70** is illustratively connected to a stationary power source as indicated by ground power **113**. The power control module **70** illustratively directs power from the ground power **113** to the LP motor-generator **38** to inhibit rotation of the fan **12**. Such operation can prevent accidental rotation of the engine **10** components from natural wind which can be damaging without operation of the engine **10**.

In the illustrative embodiment, the power control module **70** determines the operational conditions based on signals received from various engine components. The various engine components illustratively include at least rotational speed sensors configured to detect the rotational speed of the LP and HP spools, compressor input and output pressure sensors adapted to determine inlet and outlet pressures of the compressor **14**. In some embodiments, the various engine components may include any of compressor surge margin sensors adapted to detect the amount of operating margin between the current compressor operating pressure and a compressor surge pressure, fuel rate sensors, and/or efficiency sensors (including at least temperature and pressure sensors for determining differentials across the LP turbine rotor **20** and HP turbine rotor **22**) adapted to determine operating efficiency of the HP spool **26** and LP spool **30**. In

15

some embodiment, the engine **10** may include any number and/or arrangement of sensors for detecting and/or determining current operational parameters. In some embodiment, the 3-phase power arrangement may be used to determine LP shaft **32** speed indirectly.

In another illustrative embodiment as shown in FIG. **15**, the gas turbine engine **10** includes low pressure (LP) motor-generator **1038** having a motor-generator core **1040** configured for selective operation between a generation mode to generate electrical power from rotation of the LP turbine **22** and in a drive mode to receive electrical power for applying rotational force to a LP drive shaft **1032**. The LP motor-generator **1038** is similar to the LP motor-generator **38** as disclosed herein. Accordingly, similar reference numbers in the 1000 series indicate features that are common between the LP motor-generator **1038** and the LP motor-generator **38** unless indicated otherwise. The description of the LP motor-generator **38** is hereby incorporated by reference to apply to the LP motor-generator **1038** except in instances of conflict with the specific disclosure of the LP motor-generator **1038**.

The LP drive shaft **1032** illustratively includes a fan shaft **1046** including a generator mount **1048** that extends radially from the fan shaft **1046** to support the motor-generator core **1040**. In the illustrative embodiment, the motor-generator mount **1048** is fixedly connected with the fan shaft **1046** both in rotation and radial movement. The motor-generator core **1040** illustratively includes a stator **1042** and a permanent magnet rotor **1044** that can operate in electromagnetic communication with the stator **1042** with radial spacing **1045** between the rotor **1044** and the stator **1042**.

Unlike the LP motor-generator **38**, the LP motor-generator **1038** does not include bearings **152**, **154** independent from the shaft bearings **92**, **93**. Upon degradation and/or failure of any of the shaft bearings **92**, **93** such that the fan shaft **1046** does not rotate concentrically with the axis **25** such that the radial spacing **1045** is relatively large, the LP motor-generator **1038** is adapted to continue to support operation despite the increase in radial spacing **1045**.

In some embodiments, the motor-generators disclosed herein may be configured for operation in only one of a power mode and/or a generator mode.

While the disclosure has been illustrated and described in detail in the foregoing drawings and description, the same is to be considered as exemplary and not restrictive in character, it being understood that only illustrative embodiments thereof have been shown and described and that all changes and modifications that come within the spirit of the disclosure are desired to be protected.

What is claimed is:

1. A system of turbofan gas turbine engines, each of the turbofan gas turbine engines comprises

a low pressure spool including a fan rotor, a low pressure turbine rotor, a low pressure drive shaft extending along an axis and rotationally coupling the fan rotor to receive driven rotation about the axis from the low pressure turbine rotor, and a low pressure motor-generator mounted on the low pressure drive shaft and adapted for selective operation between a generation mode to generate electric power from driven rotation of the low pressure turbine rotor and a drive mode to electrically drive rotation of the low pressure drive shaft, and

a high pressure spool including a compressor rotor, a high pressure turbine rotor, a high pressure drive shaft extending along the axis and rotationally coupling the compressor rotor to receive driven rotation about the axis from the high pressure turbine rotor, and a high

16

pressure motor-generator adapted for selective operation between a generation mode to generate electric power from driven rotation of the high pressure turbine rotor and a drive mode to electrically drive rotation of the high pressure drive shaft,

wherein the system comprises a power control module including at least one processor for executing instructions stored on memory and an energy storage device electrically connected to the power control module to selectively communicate electric power with the power control module, the power control module electrically connected to each of the low pressure motor-generator and the high pressure motor-generator of each of the turbofan gas turbine engines and configured to determine operational conditions of each of the turbofan gas turbine engines and to selectively operate each of the low pressure motor-generators and the high pressure motor-generators in either of the generation mode and the drive mode based on the determined operational conditions of the corresponding turbofan gas turbine engine,

wherein the power control module is configured to selectively operate the low pressure motor-generator of a select one of the turbofan gas turbine engines in the drive mode to provide propulsion thrust assist in response to determination that the operational conditions include loss of engine power of the select one of the turbofan gas turbine engines,

wherein the power control module is configured to provide electrical power for operating the low pressure motor-generator of the select one of the turbofan gas turbine engines by operation of at least one of the low pressure motor-generator and the high pressure motor-generator of at least one other turbofan gas turbine engine in the generation mode,

wherein the power control module is configured to selectively store electric power from one of the low pressure motor-generator and the high pressure motor-generator in the energy storage device based on the determined operational conditions of the aircraft,

wherein the power control module is configured to determine that electric high bypass conditions exist in a select two turbofan gas turbine engines, the electric high bypass conditions comprising disengagement of the select two turbofan gas turbine engines,

wherein the power control module is configured to provide electrical power from the energy storage device for operating the low pressure motor-generator and the fan of each of the select two turbofan gas turbine engines in response to determination that the operational conditions include electric high bypass conditions, and

wherein each of the turbofan gas turbine engines is adapted for use in an aircraft, and the power control module is configured to operate the low pressure motor-generator in the generation mode and to operate the high pressure motor-generator in the drive mode to assist restart of the select one of turbofan gas turbine engines in response to determination that the operational conditions include in-flight restart.

2. The turbofan gas turbine engine of claim **1**, wherein the power control module is configured to operate the low pressure motor-generator in the generation mode in response to determination that the operational conditions are steady state operational conditions.

3. The turbofan gas turbine engine of claim **1**, wherein the power control module is configured to operate the low

17

pressure motor-generator in the generation mode and to operate the high pressure motor-generator in the drive mode to assist rotation of the high pressure drive shaft in response to determination that the operational conditions include an efficiency of the high pressure spool that is below a predetermined threshold.

4. The turbofan gas turbine engine of claim 3, wherein the predetermined threshold is a predetermined fuel efficiency of the high pressure spool.

5. The turbofan gas turbine engine of claim 3, wherein the power control module is configured to operate the high pressure motor-generator in the generation mode and to operate the low pressure motor-generator in the drive mode to assist rotation of the low pressure drive shaft in response to determination that the operational conditions include an efficiency of the low pressure spool that is below a predetermined threshold.

6. The turbofan gas turbine engine of claim 1, wherein the power control module is configured to operate the low

18

pressure motor-generator in the generation mode and to operate the high pressure motor-generator in the drive mode to assist the rotation of the high pressure drive shaft in response to determination that the operational conditions are high demand operational conditions.

7. The turbofan gas turbine engine of claim 6, wherein high demand operational conditions include determination that a compressor surge margin is below a predetermined threshold value.

8. The turbofan gas turbine engine of claim 6, wherein the turbofan gas turbine engine is adapted for use in an aircraft and high demand operational conditions include determination that a flight altitude is above a predetermined threshold value.

9. The turbofan gas turbine engine of claim 6, wherein high demand operational conditions include determination of a disruption of rotation of the fan rotor.

* * * * *