



US011018553B2

(12) **United States Patent**
Behling et al.

(10) **Patent No.:** **US 11,018,553 B2**
(45) **Date of Patent:** **May 25, 2021**

(54) **ELECTRICAL MACHINE DISCONNECTION SYSTEMS**

(71) Applicant: **Hamilton Sundstrand Corporation**,
Charlotte, NC (US)

(72) Inventors: **David S. Behling**, Belvidere, IL (US);
Todd A. Spierling, Rockford, IL (US)

(73) Assignee: **Hamilton Sundstrand Corporation**,
Charlotte, NC (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 30 days.

(21) Appl. No.: **16/242,719**

(22) Filed: **Jan. 8, 2019**

(65) **Prior Publication Data**

US 2020/0220427 A1 Jul. 9, 2020

(51) **Int. Cl.**

H02K 16/02 (2006.01)
H02K 7/108 (2006.01)
F16D 11/14 (2006.01)
F16D 13/40 (2006.01)
F16D 33/06 (2006.01)
F16D 41/00 (2006.01)
F16H 1/28 (2006.01)
F16H 57/08 (2006.01)
H02K 7/08 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **H02K 7/108** (2013.01); **F16D 11/14**
(2013.01); **F16D 13/40** (2013.01); **F16D**
33/06 (2013.01); **F16D 41/00** (2013.01);
F16H 1/28 (2013.01); **F16H 57/08** (2013.01);
H02K 7/083 (2013.01); **H02K 7/116**

(2013.01); **H02K 21/14** (2013.01); **F16D**
2011/002 (2013.01); **F16H 2057/087** (2013.01)

(58) **Field of Classification Search**

CPC ... **H02K 16/02**; **H02K 7/116**; **B60K 2006/262**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,864,017 A * 12/1958 Waltscheff **H02K 16/025**
310/126
5,357,180 A * 10/1994 Speicher **H02K 16/025**
310/114

(Continued)

FOREIGN PATENT DOCUMENTS

DE 9111129 U1 1/1993
DE 102013214502 A1 1/2015

(Continued)

OTHER PUBLICATIONS

Extended European Search Report dated May 19, 2020, issued
during the prosecution of European Patent Application No. EP
19209186.6.


Primary Examiner — Dang D Le

(74) *Attorney, Agent, or Firm* — Locke Lord LLP; Daniel
J. Fiorello; Scott D. Wofsy

(57) **ABSTRACT**

A hybrid drive system can include a shaft, an electrical
machine comprising a rotor and a stator, and a mechanical
disconnect system connecting the rotor to the shaft. The
mechanical disconnect system is configured to mechanically
connect the rotor to the shaft in a first state and to mechani-
cally disconnect the rotor from the shaft in a second state
such that rotor does not drive the shaft or such that the rotor
is not driven by the shaft. The rotor can be a permanent
magnet rotor, for example.

10 Claims, 8 Drawing Sheets



- (51) **Int. Cl.**
H02K 7/116 (2006.01)
H02K 21/14 (2006.01)
F16D 11/00 (2006.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,771,000 B2 *	8/2004	Kim	F01D 15/10 310/156.16
8,733,480 B2 *	5/2014	Watanabe	B60W 10/10 180/65.22
9,193,451 B2	11/2015	Salyer	
9,493,245 B2	11/2016	Salyer	
9,567,922 B2	2/2017	Lofgren	
9,920,689 B2	3/2018	Nalim	
2014/0091681 A1	4/2014	Tauchi	
2018/0015817 A1	1/2018	Samie et al.	
2018/0072154 A1	3/2018	Thompson	

FOREIGN PATENT DOCUMENTS

DE	102018106653	A1	9/2018
EP	3232084	A1	10/2017
GB	1153997	A	6/1969
WO	200711204		10/2007

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8

1**ELECTRICAL MACHINE DISCONNECTION SYSTEMS****BACKGROUND****1. Field**

This disclosure relates to electrical machine systems, e.g., systems for selectively disconnecting an electrical machine from a shaft.

2. Description of Related Art

Hybrid propulsion concepts combine a fossil fuel driven motor with an electrically driven motor to drive a propeller or fan. Potential system failure modes precipitate the need to be able to disconnect the electrically driven motor from the shaft, e.g., when driven by a fuel powered engine.

Such conventional methods and systems have generally been considered satisfactory for their intended purpose. However, there is still a need in the art for electrical machine disconnection systems. The present disclosure provides a solution for this need.

SUMMARY

In accordance with at least one aspect of this disclosure, a hybrid drive system can include a shaft, an electrical machine comprising a rotor and a stator, and a mechanical disconnect system connecting the rotor to the shaft. The mechanical disconnect system is configured to mechanically connect the rotor to the shaft in a first state and to mechanically disconnect the rotor from the shaft in a second state such that rotor does not drive the shaft or such that the rotor is not driven by the shaft.

The rotor can be a permanent magnet rotor, for example. The mechanical disconnect system can include a clutch mechanism configured to mechanically connect and disconnect the rotor from the shaft.

In certain embodiments, the mechanical disconnect system can include a gearing assembly configured to be engaged by the clutch mechanism in the first state and disengaged by the clutch mechanism in the second state to provide a geared connection between the rotor and the shaft in the first state. The gearing assembly can be configured to provide a freewheeling connection between the rotor and the shaft in the second state to mechanically disconnect the rotor from the shaft.

The gearing assembly can include a carrier shaft configured to be engaged by the clutch mechanism to stop motion of the carrier shaft in the first state, and to be disengaged by the clutch mechanism to allow freewheeling in the second state. The carrier shaft can include a plurality of planet gears rotatably attached to the carrier shaft. The shaft can include a sun gear disposed thereon meshed with the planet gears. The rotor can include a ring gear disposed thereon meshed with the planet gears.

In certain embodiments, the clutch mechanism can be an over-running clutch connected between the shaft and the rotor. The over-running clutch can be configured to allow torque to be applied in only one direction such that the rotor can drive the shaft, but shaft cannot drive the rotor.

In certain embodiments, the clutch mechanism can be a face clutch mechanism configured to slidably actuate a face clutch member that rotates with the shaft to engage the rotor in the first state and to disengage the rotor in the second state to mechanically disconnect the rotor from the shaft. For

2

example, the rotor can include one or more rotor splines configured to engage with one or more face splines of the face clutch member in the first state. The face clutch member can be splined to the shaft via one or more shaft splines in connection with one or more axial splines of the face clutch member.

The face clutch mechanism can include a biasing member configured to bias the face clutch member toward the first position. The clutch mechanism can include a friction clutch mechanism having an actuator and a friction member. For example, the actuator can connect to the shaft to rotate with the shaft. The friction member can be configured to be pushed by the actuator to contact a rotor face to provide a frictional mechanical connection between the shaft and the rotor in the first state and to not push on the friction member in the second state to mechanically disconnect the shaft and the rotor in the second state.

In certain embodiments, the clutch mechanism can include a hydraulic coupling disposed around a rotor fan and a shaft fan. The hydraulic coupling can be configured to be sealed to the rotor and the shaft to retain a liquid therein when in a flooded state. The rotor fan and the shaft fan can be configured to be fluidly coupled in the flooded state such that the rotor fan drives the shaft fan, and the rotor fan and the shaft fan can be configured to be fluidly decoupled in a drained state (e.g., when sufficient liquid, e.g., all is drained from the coupling, e.g., and the couple is filled with air or vacuum).

Certain embodiments can include one or more bearings disposed between the rotor and the shaft to allow the shaft to rotate relative to the rotor in the second state. Certain embodiments can include a fuel powered engine operatively connected to the shaft to drive the shaft. While certain embodiments of mechanical disconnection systems are disclosed above, any suitable mechanical disconnection system as appreciated by those having ordinary skill in the art in view of this disclosure is contemplated herein.

In accordance with at least one aspect of this disclosure, a method can include mechanically disconnecting a rotor of an electrical machine from a shaft when an engine is driving the shaft. The method can include mechanically disconnecting the rotor of the electrical machine includes releasing a clutch mechanism. Any other suitable methods and/or portion thereof are contemplated herein.

In accordance with at least one aspect of this disclosure, a hybrid drive system can include a shaft, an electrical machine having a stator, and a rotor attached to the shaft to rotate with the shaft relative to the stator, and a rotor electromagnetic property modifying system configured to modify an electromagnetic property of the rotor to cause the rotor and the stator to be at least partially electromagnetically inactivated. For example, the rotor electromagnetic property modifying system can include a pole modification device configured to modify one or more magnetic poles of the rotor to at least partially electromagnetically inactivate the electrical machine.

In certain embodiments, the rotor can be a permanent magnet rotor. The rotor can include a first portion and a second portion rotatable relative to the first portion. The rotor can include plurality of first permanent magnet poles disposed on the first portion and a plurality of second permanent magnet poles disposed on the second portion. For example, a clocking mechanism can be configured to rotate one or both of the first portion and the second portion to change a relative position between the first poles of the first

portion and the second poles of the second portion to at least partially electromagnetically inactivate the electrical machine.

The clocking mechanism can be configured to move the plurality of poles from an aligned state to a misaligned state to at least partially electromagnetically inactivate the electrical machine. For example, the first poles and the second poles can include circumferentially alternating north poles and south poles. The aligned state can be defined by each north pole of the first poles aligning with each north pole of the second poles, and each south pole of the first poles aligning with the each south pole of the second poles. The misaligned state can be defined by opposite pole alignment such that north poles of each portion align with south poles of each portion. The aligned state can correspond to an activated state, and the misaligned state can correspond to an inactivated state where rotor rotation does not cause output from the stator and such that input to the stator does not cause rotor rotation.

In accordance with at least one aspect of this disclosure, a rotor, e.g., as described above, for an electrical machine can include a first portion and a second portion configured to connect to a shaft and to rotate relative to each other on the shaft. At least one clocking mechanism, e.g., as described above, can be defined by or connected to the first portion and the second portion and configured to move the first portion and second portion relative to each other to modify an electromagnetic property of the rotor. The rotor can include any other suitable component as disclosed herein. While embodiments are described above, any suitable electromagnetic inactivation (e.g., preventing generation or output of electrical current from the stator due to rotation of the rotor, and/or preventing rotor motion due to input current to the stator) is contemplated herein as appreciated by those having ordinary skill in the art in view of this disclosure.

In accordance with at least one aspect of this disclosure, a method, can include modifying an electromagnetic property of a magnet rotor of an electrical machine to at least partially electromagnetically inactivate an electrical machine having a rotor attached to a rotating shaft and a stator without stopping rotation of the rotor. Modifying the electromagnetic property can include rotating at least a first portion of the rotor relative to a second portion of the rotor. In certain embodiments, modifying the electromagnetic property can include modifying magnetic pole alignment of one or more permanent magnetic poles of the rotor. Any other suitable methods and/or portions thereof are contemplated herein.

In accordance with at least one aspect of this disclosure, a hybrid drive system can include a shaft and an electrical machine having a stator and a rotor attached to the shaft to rotate with the shaft relative to the stator. The system can include an electromagnetic disconnect system configured to modify a position of the rotor to cause the rotor and the stator to be at least partially electromagnetically decoupled. The rotor can include a permanent magnet, for example.

The electromagnetic disconnect system can be configured to move the rotor relative to the stator to at least partially electromagnetically decouple the rotor and the stator. The electromagnetic disconnect system can be configured to move at least a portion of the rotor axially along the shaft.

The electromagnetic disconnect system can include at least one hydraulic actuator assembly configured to selectively move at least a portion of the rotor axially along the shaft to at least partially electromagnetically decouple the rotor and the stator. For example, the rotor can include a first

portion and a second portion configured to move relative to each other between an electromagnetically coupled position and an at least partially electromagnetically decoupled position.

In certain embodiments, the first portion and the second portion can define at least one hydraulic cavity of the at least one hydraulic actuator assembly. In certain embodiments, the at least one hydraulic cavity is a single annular cavity.

The first portion and the second portion can be slidably splined to the shaft via one or more mating splines on the shaft. The first portion and the second portion can be sealed to each other and to the shaft with one or more seals. In certain embodiments, the at least one cavity can be in fluid communication with a shaft cavity through a shaft hole to provide hydraulic pressure to the at least one cavity through the shaft. The system can include one or more backstops configured to limit motion and prevent separation of the first portion and the second portion in the at least partially electromagnetically decoupled position.

In certain embodiments, the at least one hydraulic actuator assembly can include at least one nested piston assembly comprising a cylinder and a piston in a sealed sliding connection within the cylinder. The piston and the cylinder can be configured to move relative to each other to move the first portion and the second portion. The at least one hydraulic actuator assembly can include a plurality of hydraulic actuator assemblies disposed circumferentially around at least one of the first portion or the second portion of the rotor to provide multiple actuation points.

In accordance with at least one aspect of this disclosure, a rotor for an electrical machine can include a first portion and a second portion configured to slidably connect to a shaft and to move relative to each other on the shaft. The rotor can include at least one hydraulic actuator assembly at least partially defined by or connected to the first portion and the second portion and configured to move the first portion and second portion between an electromagnetically coupled position and an at least partially electromagnetically decoupled position on the shaft. In certain embodiments, the first portion and the second portion can define at least one hydraulic cavity of the at least one hydraulic actuator assembly.

In accordance with at least one aspect of this disclosure, a method can include at least partially electromagnetically decoupling a rotor attached to a rotating shaft from a stator of an electrical machine without stopping rotation of the rotor. At least partially electromagnetically decoupling can include axially moving at least a portion of the rotor relative to the stator.

In certain embodiments, axially moving at least a portion of the rotor relative to the stator can include actuating a hydraulic actuator to move at least a portion of the rotor relative to the stator. Axially moving at least a portion of the rotor relative to the stator can include moving a first portion of the rotor and a second portion of the rotor apart from each other to at least partially electromagnetically decouple the first portion and the second portion from the stator.

These and other features of the embodiments of the subject disclosure will become more readily apparent to those skilled in the art from the following detailed description taken in conjunction with the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

So that those skilled in the art to which the subject disclosure appertains will readily understand how to make and use the devices and methods of the subject disclosure

5

without undue experimentation, embodiments thereof will be described in detail herein below with reference to certain figures, wherein:

FIG. 1 is a cross-sectional schematic view of an embodiment of a system in accordance with this disclosure, showing an embodiment of a mechanical disconnect system in accordance with this disclosure;

FIG. 2 is a cross-sectional schematic view of an embodiment of a system in accordance with this disclosure, showing an embodiment of a mechanical disconnect system in accordance with this disclosure;

FIG. 3 is a cross-sectional schematic view of an embodiment of a system in accordance with this disclosure, showing an embodiment of a mechanical disconnect system in accordance with this disclosure;

FIG. 4 is a cross-sectional schematic view of an embodiment of a system in accordance with this disclosure, showing an embodiment of a mechanical disconnect system in accordance with this disclosure;

FIG. 5 is a cross-sectional schematic view of an embodiment of a system in accordance with this disclosure, showing an embodiment of a mechanical disconnect system in accordance with this disclosure;

FIG. 6 is a perspective schematic view of an embodiment of a rotor electromagnetic property modifying system in accordance with this disclosure, showing an embodiment of a rotor attached to a shaft;

FIG. 7 is a cross-sectional schematic view of an embodiment of a system in accordance with this disclosure, showing an embodiment of an electromagnetic disconnect system in accordance with this disclosure; and

FIG. 8 is a cross-sectional schematic view of an embodiment of a system in accordance with this disclosure, showing an embodiment of an electromagnetic disconnect system in accordance with this disclosure.

DETAILED DESCRIPTION

Reference will now be made to the drawings wherein like reference numerals identify similar structural features or aspects of the subject disclosure. For purposes of explanation and illustration, and not limitation, an illustrative view of an embodiment of a system in accordance with the disclosure is shown in FIG. 1 and is designated generally by reference character 100. Other embodiments and/or aspects of this disclosure are shown in FIGS. 2-8. Certain embodiments described herein can be used cause an electrical machine to not produce electricity due to rotation of a rotor or to prevent force transfer to the rotor when current is applied to the stator.

In accordance with at least one aspect of this disclosure, referring to FIGS. 1-5, a hybrid drive system 100, 200, 300, 400, 500 can include a shaft 101, 201, 301, 401, 501, an electrical machine 103, 203, 303, 403, 503 comprising a rotor 105, 205, 305, 405, 505 and a stator 107. The system 100, 200, 300, 400, 500 can include a mechanical disconnect system 109, 209, 309, 409, 509 connecting the rotor 105, 205, 305, 405, 505 to the shaft. The mechanical disconnect system 109, 209, 309, 409, 509 can be configured to mechanically connect the rotor 105, 205, 305, 405, 505 to the shaft 101, 201, 301, 401, 501 in a first state and to mechanically disconnect the rotor 105, 205, 305, 405, 505 from the shaft 101, 201, 301, 401, 501 in a second state such that rotor 105, 205, 305, 405, 505 does not drive the shaft 101, 201, 301, 401, 501 or such that the rotor 105, 205, 305, 405, 505 is not driven by the shaft 101, 201, 301, 401, 501.

6

As shown the rotor 105, 205, 305, 405, 505 can be a permanent magnet rotor (e.g., including one or more permanent magnets 111), for example. However, any suitable type of rotor (e.g., an electromagnet rotor) for any suitable type of electrical machine is contemplated herein (e.g., synchronous, induction, etc.). The mechanical disconnect system 109, 209, 309, 409, 509 can include a clutch mechanism 113, 213, 313, 413, 513 configured to mechanically connect and disconnect the rotor 105, 205, 305, 405, 505 from the shaft 101, 201, 301, 401, 501.

As shown in FIG. 1, in certain embodiments, the mechanical disconnect system 109 can include a gearing assembly 109a configured to be engaged by the clutch mechanism 113 in the first state and disengaged by the clutch mechanism 113 in the second state to provide a geared connection between the rotor 105 and the shaft 101 in the first state. The gearing assembly 109a can be configured to provide a freewheeling connection between the rotor 105 and the shaft 101 in the second state to mechanically disconnect the rotor 105 from the shaft 101.

The gearing assembly can include a carrier shaft 115 configured to be engaged by the clutch mechanism 113 to stop motion of the carrier shaft 115 in the first state, and to be disengaged by the clutch mechanism 113 to allow freewheeling in the second state. The carrier shaft 115 can include a plurality of planet gears 117 rotatably attached (e.g., pinned to rotate on) to the carrier shaft 115. The shaft 101 can include a sun gear 119 disposed thereon (e.g., integrally formed therewith) and meshed with the planet gears 117. The rotor 105 can include a ring gear 121 disposed thereon (e.g., integrally formed therewith) and meshed with the planet gears 117. In the first state (e.g., where the electrical machine 103 is driving the shaft 101), the clutch mechanism 113 can grip a portion of the carrier shaft 115 to stop the carrier shaft 115 relative to the shaft 101, which causes the planet gears 117 to be in a fixed position circumferentially relative to the rotating shaft 101, which causes planet gears 117 to rotate about their own axis and to transfer torque from the ring gear 121 to the shaft 101. In the second state (e.g., where the fuel powered engine drives shaft 101 without the electrical machine 103), the clutch mechanism 113 can be released which causes the carrier shaft 115 to freewheel such that planet gears 117 can rotate circumferentially around the shaft 101 and about their own axis which prevents transfer of torque from the shaft 101 to the ring gear 121 and, thus, the rotor 105.

Any suitable rotor to shaft gear ratio (e.g., 1:1, 1:1.5) is contemplated herein. Any other suitable gearing architecture and/or components to selectively prevent power transfer between the rotor 105 and the shaft 101 are contemplated herein.

Referring to FIG. 2, in certain embodiments, the clutch mechanism 213 can be an over-running clutch 213 connected between the shaft 201 and the rotor 205. The over-running clutch can be configured to allow torque to be applied in only one direction such that the rotor 205 can drive the shaft 201, but shaft 201 cannot drive the rotor 205 (e.g., so that when the electrical machine 203 is not in use, the fuel powered engine cannot drive the electrical machine 203 to act as a generator). Any suitable over running clutch as appreciated by those having ordinary skill in the art, in view of this disclosure, is contemplated herein. For example, the over running clutch 213 can directly connect between the shaft 201 and the rotor 205, e.g., as shown.

Referring to FIG. 3, in certain embodiments, the clutch mechanism 313 can be a face clutch mechanism 313 configured to slidably actuate (e.g., axially along the shaft 301)

a face clutch member **315** that rotates with the shaft **301** to engage the rotor **305** in the first state and to disengage the rotor **305** in the second state to mechanically disconnect the rotor **305** from the shaft **301**. For example, the rotor **305** can include one or more rotor splines **317** configured to engage with one or more face splines **319** of the face clutch member **315** in the first state (e.g., as shown). The face clutch member **315** can be splined to the shaft **301** via one or more shaft splines **321** in connection with one or more axial splines **323** of the face clutch member **315**.

The face clutch mechanism **313** can include a biasing member **325** (e.g., biased in a downward direction as shown) configured to bias the face clutch member **315** (e.g., using a ramped face as shown to provide a camming action) toward the first state (e.g., in engagement with the rotor **305**). The face clutch member **315** can be actuated by any suitable actuator connected thereto to pull the face clutch member **315** against the bias of the biasing member **325** (e.g., to pull to the right as shown). Any other suitable face clutch assembly and/or components therefor are contemplated herein.

In certain embodiments, referring to FIG. 4, the clutch mechanism **413** can be a friction clutch mechanism **413** having an actuator **415** and a friction member **417** (e.g., an elastic material disk). For example, the actuator **415** can connect to the shaft **401** (e.g., via a spline connection) to rotate with the shaft **401** and to slide axially on the shaft **401**. The friction member **417** can be configured to be pushed by the actuator **415** (e.g., to the left as shown) to contact a rotor face **419** (e.g., an end portion of the rotor **405** that is wider radially) to provide a frictional mechanical connection between the shaft **401** and the rotor **405** in the first state and to not push on the friction member **417** in the second state to mechanically disconnect the shaft **401** and the rotor **405** in the second state. Any suitable actuator and/or frictional member is contemplated herein as appreciated by those having ordinary skill in the art in view of this disclosure.

Referring to FIG. 5, in certain embodiments, the clutch mechanism **513** can be a hydraulic coupling **513** disposed around a rotor fan **517** and a shaft fan **515**. The hydraulic coupling **513** can be configured to be sealed to the rotor **505** and the shaft **501** to retain a liquid (e.g., hydraulic fluid) therein when in a flooded state. The rotor fan **517** and the shaft fan **515** can be configured to be fluidly coupled in the flooded state (where liquid fills the cavity defined by the hydraulic coupling) such that the rotor fan **517** drives the shaft fan **515** (and thus drives the shaft **501**). The rotor fan **517** and the shaft fan **515** can be configured to be fluidly decoupled in a drained state (e.g., when sufficient liquid, e.g., all, is drained from the coupling, e.g., and the couple is filled with air or vacuum). Any suitable fluid connections, pumps, and/or fluid sources to selectively fill and drain the hydraulic coupling **513** are contemplated herein. Any other suitable design and/or components for the hydraulic coupling **513** as appreciated by those having ordinary skill in the art in view of this disclosure is contemplated herein.

As shown in FIGS. 1-5, certain embodiments can include one or more bearings **135** disposed between the rotor **105**, **205**, **305**, **405**, **505** and the shaft **101**, **201**, **301**, **401**, **501** to allow the shaft to rotate relative to the rotor in the second state. Certain embodiments can include a fuel powered engine **137** (e.g., fossil fuel powered, e.g., a turbomachine) operatively connected to the shaft to drive the shaft. While certain embodiments of mechanical disconnection systems are disclosed above, any suitable mechanical disconnection system as appreciated by those having ordinary skill in the art in view of this disclosure is contemplated herein.

In accordance with at least one aspect of this disclosure, a method can include mechanically disconnecting a rotor of an electrical machine from a shaft when an engine is driving the shaft. The method can include mechanically disconnecting the rotor of the electrical machine includes releasing a clutch mechanism. Any other suitable methods and/or portion thereof are contemplated herein.

In accordance with at least one aspect of this disclosure, referring to FIG. 6, a hybrid drive system **600** can include a shaft **601**, an electrical machine **603** having a stator **107**, and a rotor **605** attached to the shaft **601** to rotate with the shaft **601** relative to the stator **107**. The system **600** can include a rotor electromagnetic property modifying system **609** configured to modify an electromagnetic property of the rotor **605** to cause the rotor **605** and the stator **107** to be at least partially electromagnetically inactivated (e.g., either at least partially decoupled or caused to internally cancel output). For example, the rotor electromagnetic property modifying system **109** can include a pole modification device (e.g., clocking mechanism **615**) configured to modify one or more magnetic poles (e.g., change the location of relative to one or more other poles), e.g., **611N**, **611S**, **613N**, **613S** of the rotor **605** to at least partially electromagnetically inactivate the electrical machine **603**.

In certain embodiments, the rotor **605** can be a permanent magnet rotor, as shown. The rotor **605** can include a first portion **605a**, and a second portion **605b** rotatable relative to the first portion **605a**. The rotor **605** can include plurality of first permanent magnet poles **611N**, **611S** disposed on the first portion **605a** and a plurality of second permanent magnet poles **613N**, **613S** disposed on the second portion **605b**. The system **609** can include a clocking mechanism **615** configured to rotate one or both of the first portion **605a** and the second portion **605b** to change a relative position between the first poles **611N**, **611S** of the first portion **605a** and the second poles **613N**, **613S** of the second portion **605b** to at least partially electromagnetically inactivate the electrical machine **603**. The clocking mechanism **615** can include any suitable actuator (e.g., an electric motor) and/or component(s) configured to connect to both portions **605a**, **605b** and to selectively allow rotatable motion therebetween. For example, the actuator can include an electric motor that is controlled in any suitable manner (e.g., by a controller as a function of electrical output from the stator **107**). In certain embodiments, the clocking mechanism **615** can be a biased coaxial bearing that is configured to be biased to the misaligned position, and having a releasable mechanism to allow rotation to the misaligned position. Any suitable structure and/or component(s) are contemplated herein.

The clocking mechanism **615** can be configured to move the plurality of poles from an aligned state (e.g., as shown in FIG. 6) to a misaligned state to at least partially electromagnetically inactivate the electrical machine **603**. For example, the first poles **611N**, **611S** and the second poles **613N**, **613S** can include circumferentially alternating north poles **611N**, **613N** and south poles **611S**, **613S**. The aligned state can be defined by each north pole **611N** of the first poles **611N**, **611S** aligning with each north pole **613N** of the second poles **613N**, **613S**, and each south pole **611S** of the first poles **611N**, **611S** aligning with the each south pole **613S** of the second poles **613N**, **613S**. The misaligned state can be defined by opposite pole alignment such that north poles **611N**, **613N** of each portion **605a**, **605b** align with south poles **613S**, **611S** of the other portion **605b**, **605a**. The aligned state can correspond to an activated state, and the misaligned state can correspond to an inactivated state

where rotor **605** rotation does not cause output from the stator **107** and such that input to the stator **107** does not cause rotor **105** rotation. Any other suitable aligned and misaligned states to prevent output from the stator **107** due to rotation of the rotor **605** and/or to prevent driving the rotor **605** with input to the stator **107** is contemplated herein. As appreciated by those having ordinary skill in the art in view of this disclosure, misaligning poles can prevent production of electrical output by creating two opposite outputs in the stator **107**, thereby cancelling out electrical production from the stator **107**. Such embodiments may have no mechanical disconnect, and may still provide a resistance to an engine **137** driving shaft **601**, for example.

In accordance with at least one aspect of this disclosure, a rotor **605**, e.g., as described above, for an electrical machine can include a first portion **605a** (e.g., a first half) and a second portion **605b** (e.g., a second half) configured to connect to a shaft **601** and to rotate relative to each other on the shaft **601**. At least one clocking mechanism **615**, e.g., as described above, can be defined by or connected to the first portion and the second portion and configured to move the first portion and second portion relative to each other to modify an electromagnetic property of the rotor. The rotor **605** can include any other suitable components, e.g., as appreciated by those having ordinary skill in the art in accordance with this disclosure (e.g., more than two portions **605a**, **605b**). While embodiments are described above, any suitable electromagnetic inactivation (e.g., preventing generation or output of electrical current from the stator due to rotation of the rotor, and/or preventing rotor motion due to input current to the stator) is contemplated herein as appreciated by those having ordinary skill in the art in view of this disclosure.

In accordance with at least one aspect of this disclosure, a method, can include modifying an electromagnetic property of a permanent magnet rotor of an electrical machine to at least partially electromagnetically inactivate an electrical machine having a rotor attached to a rotating shaft and a stator without stopping rotation of the rotor. Modifying the electromagnetic property can include rotating at least a first portion of the rotor relative to a second portion of the rotor. In certain embodiments, modifying the electromagnetic property can include modifying magnetic pole alignment of one or more permanent magnetic poles of the rotor. Any other suitable methods and/or portions thereof are contemplated herein.

In accordance with at least one aspect of this disclosure, referring to FIGS. **7** and **8**, a hybrid drive system **700**, **800** can include a shaft **701**, **801** and an electrical machine **703**, **803** having a stator **107** and a rotor **705**, **805** attached to the shaft **701**, **801** to rotate with the shaft **701**, **801** relative to the stator **107**. The system **700**, **800** can include an electromagnetic disconnect system **709**, **809** configured to modify a position of the rotor **705**, **805** to cause the rotor **705**, **805** and the stator **107** to be at least partially electromagnetically decoupled. As shown, the rotor **705**, **805** can include a permanent magnet **711**, **811** (e.g., one or more), for example. Any other suitable type of magnet (e.g., an electromagnet) is contemplated herein.

The electromagnetic disconnect system **709**, **809** can be configured to move the rotor **705**, **805** relative (e.g., axially) to the stator **107** to at least partially (e.g., fully) electromagnetically decouple the rotor **705**, **805** and the stator **107**. The electromagnetic disconnect system **709**, **809** can be configured to move at least a portion of the rotor **705**, **805** axially along the shaft **701**, **801**, for example.

The electromagnetic disconnect system **709**, **809** can include at least one hydraulic actuator assembly **713**, **813** configured to selectively move at least a portion of the rotor **705**, **805** axially along the shaft **701**, **801** to at least partially electromagnetically decouple the rotor **705**, **805** and the stator **107**. For example, the rotor **705**, **805** can include a first portion **705a**, **805a** (e.g., a first half) and a second portion **705b**, **805b** (e.g., second half) configured to move relative to each other between an electromagnetically coupled position (e.g., as shown in FIGS. **7** and **8**) and an at least partially electromagnetically decoupled position (e.g., where first portion **705a**, **805a** is separated from second portion **705b**, **805b**).

Referring to FIG. **7**, in certain embodiments, the first portion **705a** and the second portion **705b** can define at least one hydraulic cavity **715** of the at least one hydraulic actuator assembly **713**. In certain embodiments, the at least one hydraulic cavity **715** can be a single annular cavity, for example.

The first portion **705a** and the second portion **705b** can be sealed to each other and to the shaft **701** with one or more seals **717** as shown. In certain embodiments, each of the first portion **705a** and the second portion **705b** can include a long leg **719a**, **719b** and/or a short leg **721a**, **721b** forming at least part of the hydraulic actuator assembly **713**. As shown, the short legs **721a**, **721b** may be dimensioned to leave a gap in the electromagnetically coupled state to always have a hydraulic pathway to the at least one hydraulic cavity **715**, e.g., as described below. In certain embodiments, the long legs **719a**, **719b** can be sealed to each other with at least one seal **717**.

Referring to both FIGS. **7** and **8**, the first portion **705a**, **805a** and the second portion **705b**, **805b** can be slidably splined to the shaft **701**, **801** via one or more mating splines **723**, **823** on the shaft **701**, **801** and one or more rotor splines **725a**, **825a**, **725b**, **825b**. As shown in FIG. **7**, in certain embodiments, the at least one cavity **715** can be in fluid communication with a shaft cavity **727** through a shaft hole **729** to provide hydraulic pressure to the at least one cavity **715** through the shaft **701**. The system as shown in FIG. **8** and further described below can include a similar hydraulic pathway through the shaft **801** as shown. Any other suitable hydraulic system and/or pathway is contemplated herein.

As shown, the system **700** can include one or more backstops **731** configured to limit motion of the rotor **705** and/or portions **705a**, **705b** thereof, e.g., to prevent separation of the first portion **705a** and the second portion **705b** in the at least partially electromagnetically decoupled position. For example, backstops **731** can stop further separation of the rotor portions **705a**, **705b** before long legs **719a**, **719b** move out of contact to maintain a seal.

Referring to FIG. **8**, in certain embodiments, the at least one hydraulic actuator assembly **809** can include at least one nested piston assembly comprising a cylinder **833** and a piston **835** in a sealed sliding connection within the cylinder **833**. The piston **835** and the cylinder **833** can define a hydraulic cavity **837** as shown (e.g., in fluid communication with a shaft cavity **827** through shaft opening **829**, similar to the embodiment of FIG. **7** as described above). The piston **835** and the cylinder **833** can be configured to move relative to each other to move the first portion **805a** and the second portion **805b** relative to each other. For example, the cylinder **833** can be connected to the second portion **805b** and the piston **835** can be connected to or at least be in contact with the first portion **805a** to push the portions apart when expanded.

11

In certain embodiments, the at least one hydraulic actuator assembly **809** can include a plurality of hydraulic actuator assemblies **809** disposed circumferentially around at least one of the first portion **805a** and/or the second portion **805b** of the rotor **805** to provide multiple actuation points. In certain embodiments, one or more mirrored actuators (a mirror image of that shown FIG. **8**) can be connected to provide opposing actuation when desired to provide push actuation in both directions to allow the portions **805a**, **805b** to be both separated and pushed back together. Any suitable assembly and/or hydraulic components are contemplated herein.

In accordance with at least one aspect of this disclosure, a rotor **705**, **805** for an electrical machine can include a first portion and a second portion configured to slidably connect to a shaft and to move relative to each other on the shaft. The rotor can include at least one hydraulic actuator assembly at least partially defined by or connected to the first portion and the second portion and configured to move the first portion and second portion between an electromagnetically coupled position and an at least partially electromagnetically decoupled position on the shaft. In certain embodiments, as shown in FIG. **7**, the first portion **705a** and the second portion **705b** can define at least one hydraulic cavity of the at least one hydraulic actuator assembly. Embodiments, e.g., as disclosed in FIGS. **7** and **8**, can remove the magnet from the inside of an electrical machine thereby at least partially, if not fully, decoupling the rotor and the stator for example.

In accordance with at least one aspect of this disclosure, a method can include at least partially electromagnetically decoupling a rotor attached to a rotating shaft from a stator of an electrical machine without stopping rotation of the rotor. At least partially electromagnetically decoupling can include axially moving at least a portion of the rotor relative to the stator.

In certain embodiments, axially moving at least a portion of the rotor relative to the stator can include actuating a hydraulic actuator to move at least a portion of the rotor relative to the stator. Axially moving at least a portion of the rotor relative to the stator can include moving a first portion of the rotor and a second portion of the rotor apart from each other to at least partially electromagnetically decouple the first portion and the second portion from the stator.

Traditional systems have no means to shut off the electrically driven motor from the driveline of a hybrid propulsion system. Certain embodiments disclosed hereinabove include systems configured to mechanically or otherwise disconnect an electrically driven motor from a fuel driven motor driveline, e.g., in the event of a system failure. Embodiments allow a fossil fuel driven motor to continue to provide propulsion without the electrically driven motor acting as a generator, for example.

Those having ordinary skill in the art understand that any numerical values disclosed herein can be exact values or can be values within a range. Further, any terms of approximation (e.g., “about”, “approximately”, “around”) used in this disclosure can mean the stated value within a range. For example, in certain embodiments, the range can be within (plus or minus) 20%, or within 10%, or within 5%, or within 2%, or within any other suitable percentage or number as appreciated by those having ordinary skill in the art (e.g., for known tolerance limits or error ranges).

Any suitable combination(s) of any disclosed embodiments and/or any suitable portion(s) thereof are contemplated herein as appreciated by those having ordinary skill in the art.

12

The embodiments of the present disclosure, as described above and shown in the drawings, provide for improvement in the art to which they pertain. While the subject disclosure includes reference to certain embodiments, those skilled in the art will readily appreciate that changes and/or modifications may be made thereto without departing from the spirit and scope of the subject disclosure.

What is claimed is:

1. A hybrid drive system, comprising:

a shaft; and

an electrical machine comprising a rotor and a stator; and a mechanical disconnect system connecting the rotor to the shaft, wherein the mechanical disconnect system is configured to mechanically connect the rotor to the shaft in a first state and to mechanically disconnect the rotor from the shaft in a second state such that rotor does not drive the shaft or such that the rotor is not driven by the shaft,

wherein the mechanical disconnect system includes a clutch mechanism configured to mechanically connect and disconnect the rotor from the shaft, wherein the mechanical disconnect system includes a gearing assembly configured to be engaged by the clutch mechanism in the first state and disengaged by the clutch mechanism in the second state to provide a geared connection between the rotor and the shaft in the first state, wherein the gearing assembly is configured to provide a freewheeling connection between the rotor and the shaft in the second state to mechanically disconnect the rotor from the shaft, wherein the gearing assembly includes a carrier shaft configured to be engaged by the clutch mechanism to stop motion of the carrier shaft in the first state, and to be disengaged by the clutch mechanism to allow freewheeling in the second state, wherein the carrier shaft includes a plurality of planet gears rotatably attached to the carrier shaft, wherein the shaft includes a sun gear disposed thereon meshed with the planet gears, and wherein the rotor includes a ring gear disposed thereon meshed with the planet gears.

2. The system of claim 1, wherein the rotor is a permanent magnet rotor.

3. The system of claim 1, further comprising one or more bearings disposed between the rotor and the shaft to allow the shaft to rotate relative to the rotor in the second state.

4. The system of claim 1, further comprising a fuel powered engine operatively connected to the shaft to drive the shaft.

5. A hybrid drive system, comprising:

a shaft;

an electrical machine comprising a rotor and a stator; and a mechanical disconnect system connecting the rotor to the shaft, wherein the mechanical disconnect system is configured to mechanically connect the rotor to the shaft in a first state and to mechanically disconnect the rotor from the shaft in a second state such that rotor does not drive the shaft or such that the rotor is not driven by the shaft, wherein the mechanical disconnect system includes a clutch mechanism configured to mechanically connect and disconnect the rotor from the shaft, wherein the clutch mechanism is a face clutch mechanism configured to slidably actuate a face clutch member that rotates with the shaft to engage the rotor in the first state and to disengage the rotor in the second state to mechanically disconnect the rotor from the shaft.

13

6. The system of claim 5, wherein the rotor includes one or more rotor splines configured to engage with one or more face splines of the face clutch member in the first state.

7. The system of claim 6, wherein the face clutch member is splined to the shaft via one or more shaft splines in connection with one or more axial splines of the face clutch member.

8. The system of claim 7, wherein the face clutch mechanism includes a biasing member configured to bias the face clutch member toward the first position.

9. A hybrid drive system, comprising:

a shaft; and

an electrical machine comprising a rotor and a stator;

a mechanical disconnect system connecting the rotor to

the shaft, wherein the mechanical disconnect system is configured to mechanically connect the rotor to the shaft in a first state and to mechanically disconnect the rotor from the shaft in a second state such that rotor does not drive the shaft or such that the rotor is not

driven by the shaft, wherein the mechanical disconnect system includes a clutch mechanism configured to mechanically connect and disconnect the rotor from the shaft, wherein the clutch mechanism includes a friction

clutch mechanism having an actuator and a friction member, wherein the actuator is connected to the shaft to rotate with the shaft, wherein the friction member is

configured to be pushed by the actuator to contact a

14

rotor face to provide a frictional mechanical connection between the shaft and the rotor in the first state and to not push on the friction member in the second state to mechanically disconnect the shaft and the rotor in the second state.

10. A hybrid drive system, comprising:

a shaft; and

an electrical machine comprising a rotor and a stator; and

a mechanical disconnect system connecting the rotor to the shaft, wherein the mechanical disconnect system is

configured to mechanically connect the rotor to the shaft in a first state and to mechanically disconnect the rotor from the shaft in a second state such that rotor does not drive the shaft or such that the rotor is not

driven by the shaft, wherein the mechanical disconnect system includes a clutch mechanism configured to

mechanically connect and disconnect the rotor from the shaft, wherein the clutch mechanism includes a hydraulic coupling disposed around a rotor fan and a shaft fan,

wherein the hydraulic coupling is configured to be sealed to the rotor and the shaft to retain a liquid therein

when in a flooded state, wherein the rotor fan and the shaft fan are configured to be fluidly coupled in the flooded state such that the rotor fan drives the shaft fan,

and wherein the rotor fan and the shaft fan are configured to be fluidly decoupled in a drained state.

* * * * *