

#### US011020526B2

### (12) United States Patent Dirac et al.

### (10) Patent No.: US 11,020,526 B2

#### (45) Date of Patent: Jun. 1, 2021

#### SPRINKLER CANNULA

Inventors: Holger Dirac, Birkerød (DK); John

Myhre Frederiksen, Borup (DK); Søren Thorup, Frederiksberg C (DK); Bo L. Justesen, Ringsted (DK)

Assignee: Unomedical A/S, Birkerød (DK)

Subject to any disclaimer, the term of this Notice:

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

13/823,236 Appl. No.: (21)

PCT Filed: Sep. 30, 2011 (22)

PCT No.: PCT/EP2011/067066 (86)

§ 371 (c)(1),

(2), (4) Date: Jun. 10, 2013

PCT Pub. No.: **WO2012/045667** 

PCT Pub. Date: **Apr. 12, 2012** 

#### (65)**Prior Publication Data**

US 2013/0245555 A1 Sep. 19, 2013

### Related U.S. Application Data

Provisional application No. 61/389,595, filed on Oct. 4, 2010.

#### Foreign Application Priority Data (30)

(EP) ...... 10186437 Oct. 4, 2010

Int. Cl. (51)

A61M 5/158 (2006.01)A61M 5/32 (2006.01)

(Continued)

U.S. Cl. (52)

> A61M 5/158 (2013.01); A61M 5/3291 (2013.01); A61M 25/007 (2013.01);

(Continued)

#### Field of Classification Search

CPC ..... A61M 5/14; A61M 5/158; A61M 5/3291; A61M 2025/0081; A61M 2025/0253 (Continued)

#### **References Cited** (56)

#### U.S. PATENT DOCUMENTS

1,592,462 A 7/1926 MacGregor 2,047,010 A 7/1936 Dickinson (Continued)

#### FOREIGN PATENT DOCUMENTS

DE 4 342 329 A1 6/1994 DE 196 31 921 A1 3/1997 (Continued)

#### OTHER PUBLICATIONS

International Search Report completed Jun. 27, 2012 for International Application No. PCT/EP2011/067066.


(Continued)

Primary Examiner — Manuel A Mendez Assistant Examiner — Justin L Zamory (74) Attorney, Agent, or Firm — Taft Stettinius & Hollister LLP; Ryan O. White; Derek B. Lavender

#### (57)ABSTRACT

An infusion device (50) incl. a preferably soft cannula (1) configured to be inserted by means of an insertion needle. The cannula has a tubular body member having a proximal end and a subcutaneously placed distal portion having a distal end where the distal portion is provided with an opening (2) allowing a portion of a drug conveyed through the tubular body member to discharge. The cannula further comprise, in the distal portion, a radial opening allowing a portion of a drug conveyed through the tubular body member to discharge.

### 14 Claims, 6 Drawing Sheets



(51)	T4 (C1)		4 950 006	<b>A</b>	7/1000	Crass
(51)	Int. Cl.	(2006 01)	4,850,996 4,863,016		7/1989	
	A61M 25/00	(2006.01)	4,803,010		11/1989	Fong et al. Katzin
	A61M 5/142	(2006.01)	4,890,608		1/1990	
(52)	U.S. Cl.		4,894,054			Miskinyar
` /	CPC A6	51M 25/0015 (2013.01); A61M	4,895,570			Larkin
		2 (2013.01); A61M 2005/1586	4,917,669			Bonaldo
	2005/1725		4,935,010			Cox et al.
( <b>5</b> 0)		(2013.01)	4,950,163			Zimble
(58)	Field of Classification	n Search	4,950,252	A	8/1990	Luther et al.
	USPC	604/117, 151, 174, 272	4,956,989	A	9/1990	Nakajima
	See application file fo	or complete search history.	, ,			Weir et al.
	* *	•				Melsky et al.
(56)	Referen	ices Cited	4,982,842			Hollister
(00)			4,986,817			
	U.S. PATENT	DOCUMENTS	4,994,042			
			4,994,045			Ranford
	2,295,849 A 9/1942	Kayden	5,011,475 5,020,665			
	2,690,529 A 9/1954	-	, ,			Menes et al.
	2,972,779 A 2/1961	Cowley	5,067,496			
	3,059,802 A 10/1962	Mitchell	5,092,853			Couvertier, II
	3,074,541 A 1/1963		5,098,389			Cappucci
	3,149,186 A 9/1964		5,112,313			
	3,221,739 A 12/1965		5,116,319	A	5/1992	Van den Haak
	3,221,740 A 12/1965		5,116,325	A	5/1992	Paterson
	3,306,291 A 2/1967		5,121,751	A	6/1992	Panalletta
	3,485,352 A 12/1969	•	5,129,884			•
	3,509,879 A 5/1970 3,519,158 A 7/1970		5,135,502			Koenig, Jr. et al.
	3,547,119 A 12/1970		5,137,516			Rand et al.
	3,575,337 A 4/1971		•			Lynn et al.
	3,610,240 A 10/1971		5,141,496			Dalto et al.
	3,615,039 A 10/1971		5,163,915			Sullivan et al.
	3,670,727 A 6/1972		5,172,808			
	3,783,895 A 1/1974	Weichselbaum	, ,			Kramer et al.
	3,788,374 A 1/1974	Saijo	5,176,650			
		Hurschman	5,176,662			Bartholomew et al.
	3,835,862 A 9/1974		5,186,712			Kelso et al.
	3,840,011 A 10/1974	~	5,188,611			
	3,893,448 A 7/1975		RE34,223	E	4/1993	Bonaldo
		Karakashian	5,205,820		4/1993	Kriesel
	3,986,507 A 10/1976		5,222,947			D'Amico
	3,986,508 A 10/1976 3,995,518 A 12/1976		5,232,454			Hollister
		Tenczar	5,248,301			Koenig et al.
		Wardlaw	5,256,149			Banik et al.
	4,201,406 A 5/1980		5,256,152		10/1993	
		Wardlaw				Van Antwerp et al. Bachynsky
	4,259,276 A 3/1981	Rawlings				Appling et al.
	4,267,836 A 5/1981	Whitney et al.	5,269,799			
	4,296,786 A 10/1981		5,271,744			Kramer et al.
		Crandall et al.	5,279,579			D'Amico
	4,333,455 A 6/1982	_	5,279,591	A	1/1994	Simon
	4,334,551 A 6/1982		5,282,793	A	2/1994	Larson
	D267,199 S 12/1982	Wardlaw	5,300,030			Crossman et al.
	4,378,015 A 3/1983 4,402,407 A 9/1983		5,312,359			Wallace
	4,415,393 A 11/1983	•	5,312,369			Arcusin et al.
	· · · · · · · · · · · · · · · · · · ·	Frankhouser et al.	5,316,246			Scott et al.
	4,464,178 A 8/1984		5,324,302 5,342,319			Watson et al.
	4,473,369 A 9/1984	Lueders et al.	5,342,319			
	4,484,910 A 11/1984	Sarnoff et al.	5,344,007			Nakamura et al.
	4,500,312 A 2/1985	McFarlane	5,350,392			Purcell et al.
		Oreopoulos et al.	, ,			Haber et al.
		Vaillancourt	5,354,337	A	10/1994	Hoy
		Phillips et al.	5,366,469	A	11/1994	Steg et al.
	4,531,937 A 7/1985	_	5,372,592	A	12/1994	Gambale
		Bootman et al.	5,372,787			
	4,563,177 A 1/1986 4,610,469 A 9/1986	Kamen Wolff-Mooii	5,376,082			-
	4,617,019 A 9/1986		5,379,895			Foslien
		Bickelhaupt et al.	, ,			Chee et al 604/264
		Millerd	5,384,174			Ward et al.
		Konopka et al.	5,387,197			Smith et al.
		Turner et al.	5,390,669			Stuart et al.
		Levin et al.	5,391,151			Wilmot
	4,838,871 A 6/1989		5,403,288			Stanners
		Balbierz	5,405,332		4/1995	•
	4,850,974 A 7/1989	Bickelhaupt et al.	5,425,715	A	6/1995	Dalling et al.

(56)		Referen	ces Cited	5,954,643			VanAntwerp et al	. •
	U.S.	PATENT	DOCUMENTS	5,957,892 5,957,897	A	9/1999	_	
				, ,			Larsen et al.	
5,429,60			McPhee	5,971,966 5,975,120		10/1999 11/1999		
5,429,613 5,439,473			D'Amico Jorgensen	5,980,488				
D362,71			Deily et al.	,			Mathiasen	
5,449,34			Sallee et al.	5,984,224			•	
5,451,21			Kramer et al.				Petersen et al.	
5,478,31			Bitdinger et al.	,			Howell et al.	
5,490,84		2/1996		6,017,528			Fischell et al. Kreischer et al.	
5,501,67. 5,505,709			Erskine Funderburk et al.	D421,119			Musgrave et al.	
5,507,73			Haber et al.	6,024,727			Thorne et al.	
5,514,11		5/1996		6,039,629	A	3/2000	Mitchell	
5,520,65			Wahlberg	6,042,570			Bell et al.	
5,522,80			Teissen-Simony	6,045,533			Kriesel et al.	
5,527,28			Miskinyar et al.	6,045,534 6,050,976			Jacobsen et al. Thorne et al.	
5,533,974 5,540,709		7/1996 7/1996		6,053,893			Bucher	
5,545,14			Fischell	6,053,930			Ruppert	
5,545,15			Funderburk et al.	6,056,718			Funderburk et al.	
5,549,57	7 A		Siegel et al.	6,056,726			Isaacson	
5,554,130			McDonald et al.	6,074,369			Sage et al. Fischell	
5,558,650			McPhee	6,077,244			Botich et al.	
5,562,629 5,562,639			Haughton et al. Utterberg	6,079,432		6/2000		
5,573,510		11/1996	•	6,086,008			Gray et al.	
, ,			Cover et al.	6,086,575	$\mathbf{A}$		Mejslov	
, ,			Livingston et al.	6,090,068			Chanut	
5,586,55			Halili et al.	6,093,172 6,093,179			Funderburk et al. O'Hara et al.	
5,591,18		1/1997		6,099,503			Stradella	
5,599,309 5,599,31		2/1997 2/1997	Marshall et al.	6,105,218			Reekie	
5,599,31			Sweeney et al.	6,106,498			Friedli et al.	
5,628,76		5/1997	_	6,120,482		9/2000		
5,643,21		7/1997		6,123,690			-	
5,643,21		7/1997		6,132,755			Eicher et al.	
5,643,229		7/1997		6,139,534 6,159,181			Niedospial, Jr. Crossman et al.	
5,658,256 5,662,61			Shields Odell et al.	6,183,464			Sharp et al.	
5,665,07			Wyrick	6,191,338		2/2001	<b>-</b>	
5,665,07			Gyure et al.	6,193,694			Bell et al.	
5,676,15	6 A	10/1997	Yoon	6,210,420			Mauze et al.	
5,681,32		10/1997		6,219,574 6,221,058			Cormier et al. Kao et al.	
5,695,470 5,697,000		12/1997		6,248,093			Moberg	
5,697,90° 5,700,25°		12/1997 12/1997		6,261,272			Gross et al.	
5,702,37		12/1997		6,280,434	B1 *	8/2001	Kinoshita	A61M 25/0041
5,704,92	0 A	1/1998	Gyure	£ 202 02 £	D.1	0/2001	~ ~ 1 1 . 1	600/435
5,709,66			Olive et al.	6,293,925			Safabash et al.	
5,714,22			Hansen et al.	6,302,866		10/2001	Kashmer	
5,738,64 5,741,28		4/1998	Watson et al.	6,322,535			Hitchins et al.	
5,752,92			Terwilliger	6,322,808			Trautman et al.	
5,807,31	6 A	9/1998	Teeple	, ,			Allen et al.	
5,807,34			Zinger et al.	6,355,021			Nielsen et al.	
5,810,83			Ryan et al.	6,364,113 6,378,218			Faasse et al. Sigwart et al.	
5,817,059 5,820,599		10/1998	Gazza et al.	6,379,335			Rigon et al.	
5,827,23			Takahashi	6,387,076			Van Landuyt	
5,833,66			Davis et al.	6,387,078	B1	5/2002	Gillespie, III	
			Goldenberg	6,405,876			Seshimoto et al.	
5,848,99			Cirelli et al.	6,440,096 6,447,482			Lastovich et al. Rønborg et al.	
5,851,19° 5,858,00			Marano et al. Tsals et al.	6,450,992			Cassidy, Jr.	
5,865,80		2/1999		6,485,461			Mason et al.	
5,899,886			Cosme	6,488,663	B1	12/2002	Steg	
5,911,70		6/1999	Howell	6,503,222		1/2003		
5,913,84		6/1999		6,517,517			Farrugia et al.	
5,916,199 5,010,169		6/1999		6,517,521		2/2003	Ly Funderburk et al.	
5,919,16° 5,919,17°			Mulhauser et al. Woessner	6,520,938 D472,316			Douglas et al.	
5,925,03			Clements	6,533,763			Schneiter	A61M 25/007
5,935,10			Donnan	2,222,703	1	5,2005		604/264
5,947,93			Bierman	D472,630	S	4/2003	Douglas et al.	
5,947,93			Rhinehart et al.	6,572,586		6/2003	•	
5,951,52		9/1999	Osterlind et al.	6,579,267	B2	6/2003	Lynch et al.	

(56)		Referen	ces Cited	7,322,473 B2	1/2008	
	ЦS	PATENT	DOCUMENTS	7,407,491 B2 7,407,493 B2	8/2008	Fangrow, Jr. Cane'
	0.5.		DOCOME	7,431,876 B2		Mejlhede et al.
6,582,3	97 B2	6/2003	Alesi et al.	7,441,655 B1		Hoftman
, ,		7/2003	Perthu	7,569,262 B2		Szabo et al.
6,607,5			Bobroff et al.	7,648,494 B2		Kornerup et al.
6,607,5			Halseth et al.	7,766,867 B2 7,846,132 B2		Lynch et al. Gravesen et al.
6,613,0			Rutynowski et al.	7,840,132 B2 7,850,652 B2		Liniger et al.
6,620,1	36 B1	9/2003	Pressly, Sr. et al.	8,012,126 B2		Tipsmark et al.
6,620,1			Metzger	8,087,333 B2		±
		10/2003		8,123,724 B2		<b>-</b>
,			Lavi et al.			Mejlhede et al.
, ,		11/2003		8,323,250 B2		Chong et al. Hollister et al.
, ,			Douglas et al.	2001/0004970 A1 2001/0016714 A1		Bell et al.
, ,	18 B2 *		Douglas et al. Alohas et al 604/506	2001/0010711 711 2001/0021827 A1		Ferguson et al.
, ,			Flaherty et al.	2001/0039387 A1		•
·			Connelly et al.			Ferguson et al.
· ·	49 B2		Swenson et al.			Higuchi et al.
, ,	97 B1		Larsen et al.	2001/0049496 A1		Kirchhofer
, ,	03 B1		Pickhard			Purcell et al.
, ,		6/2004	•	2001/0030204 A1 2002/0022798 A1		Connelly et al.
/ /	89 B1 05 B1	6/2004	Douglas et al. Reid	2002/0022855 A1		Bobroff et al.
, ,			Mohammad	2002/0026152 A1	2/2002	Bierman
, ,			Gianakos	2002/0055711 A1		Lavi et al.
6,805,6	86 B1	10/2004	Fathallah et al.	2002/0068904 A1		Bierman et al.
, ,			Lastovich et al.	2002/0072720 A1 2002/0074345 A1		Hague et al. Schneider et al.
, ,			Vaillancourt	2002/0074545 A1 2002/0077599 A1		Wojcik
, ,			Olsen et al. Wagner et al.	2002/0077555 711 2002/0082543 A1		Park et al.
			Zecha, Jr. et al.	2002/0095138 A1		Lynch et al.
, ,			Mogensen et al.	2002/0107489 A1	8/2002	
6,837,8	77 B2	1/2005	Zurcher	2002/0111581 A1	8/2002	
			Smutney et al.	2002/0156424 A1 2002/0156427 A1		
, ,			Nielsen et al.	2002/0130427 A1 2002/0161322 A1		Utterberg et al.
6,880,7		4/2005 8/2005	Bergeron et al.	2002/0161322 A1		•
, ,	94 B2		Marano-Ford et al.	2002/0161386 A1		
, ,	24 B2		Gonnelli et al.	2002/0165493 A1		
, ,		9/2005	Ohshima	2002/0169419 A1		
· ·			Marggi et al.	2002/0173748 A1		
, , ,			Reif et al.	2002/0173769 A1 2002/0183688 A1		
, ,			Rosenberg Rubin et al.	2002/0189688 A1	12/2002	
, ,			Marano-Ford et al.	2002/0193737 A1		Popovsky
, ,			Marano-Ford et al.	2002/0193744 A1		Alesi et al.
, ,			Giard et al.	2003/0014018 A1		Giambattista et al.
, ,			Safabash et al.	2003/0060781 A1 2003/0069548 A1		Mogensen et al. Connelly et al.
, ,	25 B2		Bengtsson  Broggler et el	2003/0009348 A1		Poulsen et al.
, ,	44 B2 08 B2		Bressler et al. Marano-Ford et al.	2003/0105430 A1		Lavi et al.
, ,	70 B2		Wilkinson et al.	2003/0109829 A1		Mogensen et al.
, ,	83 B2	5/2006	Wojcik	2003/0125669 A1		Safabash et al.
, ,	13 B2		Rea et al.	2003/0125678 A1 2003/0130619 A1		Swenson et al. Safabash et al.
, , , , , , , , , , , , , , , , , , , ,		6/2006		2003/0130019 A1 2003/0139704 A1	7/2003	
, ,	80 B2 08 B2		Nielsen Pajunk et al.	2003/0158701 A1		Safabash et al.
/ /			Nielsen et al.	2003/0176843 A1		Wilkinson
7,083,5			Lastovich et al.	2003/0176852 A1		Lynch et al.
7,083,5	97 B2	8/2006	Lynch et al.	2003/0181863 A1		Ackley et al.
, ,			Trautman et al.	2003/0181868 A1 2003/0181873 A1		Swenson Swenson
, ,			Mann et al.	2003/0181873 A1 2003/0181874 A1		
, ,			Wilkinson et al. Mogensen et al.	2003/0187394 A1		
			Burrell et al.	2003/0187395 A1		
, ,			Diermann et al.	2003/0199823 A1		
7,147,6	23 B2	12/2006	Mathiasen	2003/0216686 A1		
, ,			Gibson et al.	2003/0220610 A1		
· ·		5/2007	<u> </u>	2003/0225373 A1		
,	07 B2 15 B2		Lynch et al. Heinzerling et al.	2003/0225374 A1 2003/0229308 A1		
7,214,2			Shermer et al.	2003/0229308 A1 2003/0229316 A1		
, ,			Mogensen et al.	2003/0223310 A1 2004/0002682 A1		Kovelman et al.
D554,2			Kornerup	2004/0006316 A1		
,			Maule et al.			Hamm 600/156
7,309,3	26 B2	12/2007	Fangrow, Jr.	2004/0044306 A1	3/2004	Lynch et al.

(56)	Referei	nces Cited	2006/0095			Marano-Ford et al.
U	S. PATENT	DOCUMENTS	2006/0095 2006/0106			Ethelfeld Sullivan et al.
			2006/0129			Wojcik
2004/0049159 A		Barrus et al.	2006/0135 2006/0135			Liniger et al. Ethelfeld
2004/0055711 A 2004/0059316 A		Martin et al. Smedegaard	2006/0133			Ethelfeld
2004/0068231 A		Blondeau	2006/0161			Mogensen et al.
2004/0069044 A		Lavi et al.	2006/0173			Moberg et al.
2004/0087913 A		Rogers et al.	2006/0173 2006/0184		8/2006 8/2006	Cheney, II et al.
2004/0092865 A 2004/0092875 A		Flaherty et al. Kochamba	2006/0184			Okiyama
2004/0111068 A		Swenson	2006/0200			Radmer et al.
2004/0112781 A		Hofverberg et al.	2006/0241 2006/0247			Lynch et al. Diermann et al.
2004/0116865 A 2004/0133164 A		Bengtsson Funderburk et al.	2006/0247			Maule et al.
2004/0133104 A		Shermer et al.	2006/0253			Geismar et al.
2004/0138620 A		Douglas et al.	2006/0253			Moberg et al.
2004/0143216 A 2004/0143218 A		Douglas et al.	2006/0264 2006/0264			Nielsen et al. Moberg et al.
2004/0143218 A 2004/0158202 A		Jensen	2007/0005			Alchas et al.
2004/0158207 A		Hunn et al.	2007/0016			Liniger et al.
2004/0162518 A		Connelly et al.	2007/0016 2007/0021			Sparholt et al. Mogensen et al.
2004/0162521 A 2004/0171989 A		Bengtsson Horner et al.	2007/0049			Radmer et al.
2004/0178098 A		Swenson et al.	2007/0049			Gray et al.
2004/0186446 A		Ohshima	2007/0051			Money et al.
2004/0193143 A 2004/0199123 A		Sauer Nielsen	2007/0066 2007/0066			Sparholt et al. Wright
2004/0199123 A 2004/0204673 A		Flaherty et al.	2007/0088			Richards et al.
2004/0204687 A		Mogensen et al.	2007/0093			Mogensen et al.
2004/0204690 A		Yashiro et al.	2007/0104 2007/0112			Preuthun et al. Preuthun et al.
2004/0215151 A 2004/0220528 A		Marshall et al. Garcia, Jr.	2007/0112			Liniger
2004/0236284 A		Hoste et al.	2007/0129			Scheurer et al.
2004/0238392 A		Peterson et al.	2007/0129			Sage, Jr. et al.
2004/0243065 A 2004/0254433 A		McConnell et al.	2007/0173 2007/0191			Lynch et al. Wojcik
2004/0254435 A 2004/0260235 A		Douglas	2007/0191			Wojcik
2004/0260250 A		Harris et al.	2007/0203			Shermer et al.
2005/0035014 A			2007/0185 2007/0213			Fangrow, Jr. Douglas
2005/0038378 A 2005/0043687 A		Lastovich et al. Mogensen et al.	2007/0213			Causey et al.
2005/0049571 A		Lastovich et al.	2007/0244			Lastovich et al.
2005/0065466 A		Vedrine	2007/0282 2007/0299			Carter et al. Whitbourne et al.
2005/0065472 A 2005/0075606 A		Cindrich et al. Botich et al.	2007/0255	_		Burns A61M 5/31526
2005/0075000 A						604/27
2005/0101910 A		Bowman et al.	2008/0058			Propp et al.
2005/0101912 A 2005/0101932 A		Faust et al. Cote et al.	2008/0119 2008/0200			Stafford Hoss et al.
2005/0101932 A 2005/0101933 A		Marrs et al.	2008/0269		10/2008	
2005/0107743 A	1 5/2005	Fangrow, Jr.	2008/0312		12/2008	
2005/0113761 A		Faust et al.	2009/0062 2009/0118			Van Antwerp et al. Klitgaard
2005/0119611 A 2005/0119619 A		Marano-Ford et al. Haining	2009/0326			Cross et al.
2005/0119637 A		Lundgren et al.	2010/0004			Gyrn et al.
2005/0124936 A		Mogensen et al.	2010/0022 2010/0137			Tipsmark et al. Nielsen et al.
2005/0131347 A 2005/0159709 A		Marano-Ford et al. Wilkinson	2010/0137			Nielsen
2005/0159714 A		Gibson	2010/0262			Blomquist
2005/0165382 A		Fulford	2011/0054			Chong et al.
2005/0192560 A 2005/0203461 A		Walls et al. Flaherty et al.	2013/0024	555 A1	1/2013	Bartfai-Walcott et al.
2005/0205401 A 2005/0215979 A		Kornerup et al.		FOREIG	N PATE	NT DOCUMENTS
2005/0240154 A	1 10/2005	Mogensen et al.		TOTALIC	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	THE DOCUMENTS
2005/0251098 A		Wyss et al.	DE		072 U1	9/1999
2005/0256456 A 2005/0261629 A		Marano-Ford et al. Marano-Ford et al.	DE		285 A1	11/2002
2005/0277892 A	1 12/2005	Chen	DE EP		207 U1 7632 B1	11/2004 9/1984
2005/0283114 A		Bresina et al.	EP		9244 B1	2/1987
2006/0015063 A 2006/0015076 A		Butikofer et al. Heinzerling et al.	EP		2530 A2	6/1988
2006/0013070 A		Csincsura et al.	EP EP		1040 A1 4837 B1	10/1991 6/1993
2006/0036214 A	1 2/2006	Mogensen et al.	EP		5768 A2	9/1994
2006/0041224 A		Jensen Safahaah at al	EP		1662 B1	5/1995
2006/0069351 A 2006/0069382 A		Safabash et al. Pedersen	EP EP		2027 A1 7184 A1	5/1995 6/1995
2006/0069382 A		Bogaerts et al.	EP		8232 B1	12/1995
	_ <b>-</b>					

(56)	Reference	es Cited	WO	WO 02/068014 A2	9/2002
()			WO	WO 02/081012 A2	10/2002
	FOREIGN PATEN	T DOCUMENTS	WO	WO 02/081013 A2	10/2002
			WO	WO 02/083206 A2	10/2002
EP	0714631 B1	6/1996	WO	WO 02/083228 A2	10/2002
EP	0744183 A2	11/1996	WO WO	WO-02083228 A2 WO 02/094352 A2	10/2002 11/2002
EP	0747006 A1	12/1996	WO	WO 02/094332 A2 WO 02/100457 A2	12/2002
EP	0775501 B1	5/1997	WO	WO 02/100437 A2 WO 02/102442 A1	12/2002
EP EP	0799626 A1 0937475 A2	10/1997 8/1999	WO	WO 03/015860 A1	2/2003
EP EP	095/475 A2 0956879 A1	11/1999	WO	WO 03/026728 A1	4/2003
EP	1086718 A1	3/2001	WO	WO 03/068305 A1	8/2003
EP	1125593 A1	8/2001	WO	WO 03/075980 A2	9/2003
EP	1329233 B1	7/2003	WO	WO 03/095003 A1	11/2003
EP	1350537 A1	10/2003	WO	WO 2004/012796 A1	2/2004
EP	1360970 A1	11/2003	WO	WO 2004/024219 A1	3/2004
$\stackrel{\text{EP}}{=}$	1380315 A1	1/2004	WO	WO-2004/026275 A1	3/2004
EP	1407747 A1	4/2004	WO WO	WO 2004/026375 A1 WO 2004/029457 A1	4/2004 4/2004
EP	1407793 A1	4/2004	WO	WO 2004/029437 A1 WO 2004/030726 A1	4/2004
EP EP	1421968 A2 1177802 B1	5/2004 9/2004	WO	WO 2004/056412 A2	4/2004
EP	1475113 A1	11/2004	WO	WO 2004/037325 A1	5/2004
EP	1495775 A1	1/2005	WO	WO 2004/054644 A1	7/2004
EP	1502613 A1	2/2005	WO	WO 2004/064593 A2	8/2004
EP	1525873 A1	4/2005	WO	WO 2004/071308 A1	8/2004
EP	1527792 A1	5/2005	WO	WO 2004/087240 A1	10/2004
EP	1559442 A2	8/2005	WO	WO 2004/098683 A1	11/2004
EP	1616594 A1	1/2006	WO	WO 2004/101016 A1	11/2004
EP	1704889 A1	9/2006	WO	WO 2004/101071 A2	11/2004
EP	1719537 A2	11/2006	WO WO	WO 2004/110527 A1 WO 2005/002649 A1	12/2004 1/2005
EP	1762259 A1	3/2007	WO	WO 2005/002049 A1 WO 2005/004973 A1	1/2005
EP	1764125 A1	3/2007 4/2007	WO	WO 2005/004373 A1 WO 2005/018703 A2	3/2005
EP EP	1776980 A1 1970091 A1	4/2007 9/2008	WO	WO 2005/037184 A2	4/2005
EP	2272559 A1	1/2011	WO	WO 2005/037350 A2	4/2005
FR	2725902 A1	10/1994	WO	WO 2005/039673 A2	5/2005
FR	2 752 164 A1	2/1998	WO	WO 2005/046780 A1	5/2005
GB	906574	9/1962	WO	WO 2005/065748 A1	7/2005
GB	2 088 215 A	6/1982	WO	WO 2005/068006 A1	7/2005
GB	2 230 702 A	10/1990	WO	WO 2005/072795 A2	8/2005
GB	2 423 267 A	8/2006	WO	WO 2005/092410 A1	10/2005
GB	2 450 872 A	7/2007	WO WO	WO 2005/094920 A1 WO 2005/112800 A2	10/2005 12/2005
GB	2 459 101 A	10/2009	WO	WO 2005/112800 A2 WO 2005/118055 A1	12/2005
GB JP	2459101 A 10179734 A	10/2009 8/1991	WO	WO 2006/003130 A1	1/2006
JP	7051251 A	11/1995	WO	WO 2006/015507 A2	2/2006
JP	8187286 A	7/1996	WO	WO 2006/015600 A2	2/2006
JP	03-191965 A	7/1998	WO	WO 2006/024650 A2	3/2006
JP	2002-028246 A	1/2002	WO	WO 2006/032689 A1	3/2006
RU	2 238 111 C2	12/2003	WO	WO 2006/032692 A1	3/2006
SU	933 100	6/1982	WO WO	WO 2006/061027 A2	6/2006
WO	WO 81/01795 A1	7/1981	WO	WO 2006/061354 A1 WO 2006/062680 A1	6/2006 6/2006
WO	WO 82/03558 A1	10/1982	WO	WO 2006/062912 A1	6/2006
WO WO	WO 92/04062 A1 WO 93/05840 A2	3/1992 4/1993	WO	WO 2006/075016 A1	7/2006
WO	WO 93/03840 A2 WO 93/11709 A1	6/1993	WO	WO 2006/077262 A1	7/2006
WO	WO 94/20160 A1	9/1994	WO	WO 2006/077263 A1	7/2006
WO	WO 95/19194 A1	7/1995	WO	WO 2006/089958 A1	8/2006
WO	WO 96/20021 A1	7/1996	WO	WO 2006/097111 A2	9/2006
WO	WO 96/32981 A1	10/1996	WO	WO 2006/108775 A2	10/2006
WO	WO 98/26835 A1	6/1998	WO WO	WO 2006/120253 A2 WO 2006/121921 A2	11/2006 11/2006
WO	WO 98/33549 A1	8/1998	WO	WO 2006/121921 A2 WO 2006/122048 A1	11/2006
WO	WO 98/58693 A1	12/1998	WO	WO 2007/000162 A2	1/2007
WO WO	WO 99/07435 A1 WO 99/22789 A1	2/1999 5/1999	WO	WO 2007/002523 A2	1/2007
WO	WO 99/22/89 A1 WO 99/33504 A1	7/1999	WO	WO 2007/020090 A1	2/2007
WO	WO 00/02614 A1	1/2000	WO	WO 2007/065944 A1	6/2007
WO	WO 00/03757 A1	1/2000	WO	WO 2007/071255 A1	6/2007
WO	WO 00/44324 A1	8/2000	WO	WO 2007/071258 A1	6/2007
WO	WO 01/12746 A1	2/2001	WO	WO 2007/093051 A1	8/2007
WO	WO 01/30419 A2	5/2001	WO	WO 2007/093182 A2	8/2007
WO	WO 01/68180 A1	9/2001	WO	WO 2007/122207 A1	11/2007
WO	WO 01/72353 A2	10/2001	WO	WO 2007/140631 A1	12/2007
WO	WO 01/76684 A1	10/2001	WO	WO 2007/140783 A2	12/2007
WO	WO 01/93926 A2	12/2001	WO	WO 2007/140785 A1	12/2007
WO	WO 02/02165 A2	1/2002	WO	WO 2007/141210 A1	12/2007
WO	WO 02/07804 A1	1/2002	WO	WO 2008/014791 A1	2/2008
WO WO	WO 02/040083 A2	5/2002 7/2002	WO WO	WO 2008/014792 A1 WO 2008/133702 A1	2/2008 3/2008
<b>** •</b>	WO 02/053220 A2	7/2002	VV O	11 O Z000/133/02 A1	5/2000

/ <b>=</b> ->			****	TTTO 0000 (4.4.0 TO 1.1.	10/0000		
(56)	Reference	es Cited	WO	WO 2009/144272 A1	12/2009		
			WO	WO 2010/003885 A1	1/2010		
	FOREIGN PATEN	T DOCUMENTS	WO	WO 2010/003886 A1	1/2010		
			WO	WO 2010/030602 A1	3/2010		
WO	WO 2008/048631 A1	4/2008	WO	WO 2010/034830 A1	4/2010		
WO	WO 2008/052545 A1	5/2008	WO	WO 2010/072664 A1	7/2010		
WO	WO 2008/065646 A1	6/2008	WO	WO 2010/080715 A1	7/2010		
WO	WO 2008/092782 A1	8/2008	WO	WO-2010080715 A1	7/2010		
WO	WO 2008/092958 A2	8/2008	WO	WO 2010/112521 A1	10/2010		
WO	WO 2008/092959 A1	8/2008	WO	WO 2011/012465 A1	2/2011		
WO	WO 2008/135098 A1	11/2008	WO	WO 2011/015659 A1	2/2011		
WO	WO 2008/147600 A1	12/2008	WO	WO 2011/121023 A1	10/2011		
WO	WO 2008/148714 A1	12/2008	WO	WO 2012/041784 A1	4/2012		
WO	WO 2008/155145 A1	12/2008	WO	WO 2012/041923 A2	4/2012		
WO	WO 2008/155377 A1	12/2008	WO	WO 2012/045667 A2	4/2012		
WO	WO 2009/004026 A1	1/2009	WO	WO 2012/107440 A1	8/2012		
WO	WO 2009/007287 A1	1/2009					
WO	WO 2009/010396 A1	1/2009		OTHER PIT	BLICATIONS		
WO	WO 2009/010399 A1	1/2009		OTTIERTO	DLICATIONS		
WO	WO 2009/016635 A2	2/2009	"Wher	ingot®?" ingot® influsion	ant product assersions danselanded		
WO	WO 2009/033032 A1	3/2009	"Why inset®?" inset® infusion set product overview; downloaded				
WO	WO 2009/039013 A1	3/2009	from the internet at http://web.archive.org/web/20040906102448/				
WO	WO 2009/098291 A1	8/2009	http://www.infusion-set.com/Default.asp?ID=108 on Jan. 1, 2008;				
WO	WO 2009/098306 A1	8/2009	two pages.				
WO	WO 2009/101130 A1	8/2009	Interna	ational Application No. I	PCT/EP2011/067066 International		
WO	WO 2009/101145 A1	8/2009		Report and Written Opin			
WO	WO 2009/103759 A1	8/2009		1	,		
WO	WO 2009/106517 A1	9/2009	* cite	d by examiner			
,,, 🔾	11 0 2005, 100517 711	J, <b>200</b>	CITO	a by Chaimmer			




Fig. 1





Fig. 2






Fig. 4




Fig. 5




Fig. 6

### SPRINKLER CANNULA

This application claims the benefit under 35 U.S.C. § 371 of International Application No. PCT/EP2011/067066, filed Sep. 30, 2011, which claims the benefit of U.S. Provisional Application Ser. No. 61/389,595, filed Oct. 4, 2010 and European Application No. 10186437.9, filed Oct. 4, 2010, which are incorporated by reference herein in their entirety.

The present invention relates to an infusion device configured for introduction of a fluid drug into the human body. Specifically, the present invention relates to an infusion including a cannula configured for this purpose.

According to one aspect, the present invention relates to an infusion device including a cannula having a tubular body member with a proximal end and a subcutaneously placed 15 distal portion having a distal end. The distal portion is provided with a radial opening allowing a portion of a drug conveyed through the tubular body member to discharge.

In general terms, an infusion device inter alia comprises following sub components:

- a hub like part comprising a body of hard material fastened to a patients skin via a mounting pad,
- a pump, and
- a cannula.

The proximal portion of a cannula is in this specification 25 defined as a portion placed above the skin surface of the patient during use, and the distal portion of a cannula is in this specification defined as the portion which, after mounting, is placed subcutaneously i.e. below the skin surface of the patient. The distal end opening will normally be open 30 allowing fluid to discharge, however according to certain applications and embodiments, the opening may be closed thereby increasing the fluid pressure on the radial opening or openings.

#### BACKGROUND

Hypodermic cannulas or needles have been used to introduce fluid drugs to the body of human beings as well as animals for over a century.

The use of these cannulas for this purpose has long been the method of last resort, especially for the injection of medications because of the pain associated with the forcing of the needle into the body. Over the years, manufacturers of these cannulas learned that the smaller the diameter of the 45 cannula, and the sharper the point of the introducing needle, the more comfortable the injection would be, and as a consequence, it is today common practise to inject drugs by means of very fine cannulas.

There is, however, a limit to the degree to which the diameter of these cannulas may be reduced. One limitation is established by the flow rate of fluid drug along the cannula which is related to the fourth power of the diameter of the conduit. As the diameter is reduced, the flow rate, at similar pressure, rapidly decreases. If a certain volume of fluid is to be injected and the diameter of the conduit to be reduced, either the pressure used to move the fluid along within the cannula, or the time allotted for introducing the fluid, will increase.

Fluids such as insulin for treatment of diabetes are usually 60 injected in the home by the patent. Such individuals may be unable to exert sufficient pressure to inject their insulin in a satisfactorily short period of time if the diameter of the cannula is too small.

One way to increase the flow rate of a fluid passing 65 through a cannula is to place openings along the side of the needle. Such needles, known as sprinkler needles, are

2

known in the art and are described, for example, by Gross in U.S. Pat. No. 6,261,272. The additional openings on the side of the needle provide additional access to the tissue creating a shorter fluid path to the tissue and also increasing the area of access to the tissue whereby the effective area of the outlet of the needle is increased. These advantages exist both in the delivery of the fluid to the tissue and in the extraction of fluid from the tissue.

A direct result of the sprinkler needle being able to deliver the fluid to a larger volume or area of tissue is a reduction of the pressure required to deliver the fluid. Further, and equally important, increasing the surface area of tissue exposed to the fluid enhances the absorption rate of the fluid by the body.

GB 2459101 A discloses a subcutaneous port and fenestrated catheter for the administration of fluids subcutaneously to be infused over a large volume of tissue. The port contains a subcutaneous chamber covered by a septum through which fluid is received from a hypodermic needle. 20 The chamber has an exit hole with a nipple which connects to a catheter which has perforations. The port and catheter is implanted under the skin of the patient. According to the document, the port may have more than one exit hole connected to other catheters. GB 2459101 A is considered to represent relevant prior art with respect to the present invention because the reference is directed to frequent subcutanous infusion of a medicament by means of a cannula or catheter comprising one or more radial openings such that the fluid administered are received by a large tissue area.

US 2007/0129691 A disclose a laminated sprinkler needle for introduction and extraction of liquids from an animal. The needle comprising a substrate, a micro machined photo resistive layer and a micro porous layer. The structure is of simple construction and fabrication and, according to the document, provides higher flow rates than standard hollow cannulas.

While sprinkler needles have a performance advantage over straight cannula needles, this performance advantage comes at a significantly higher manufacturing cost. The additional openings must be cut in the sides of the needle which requires more time for manufacturing as well as additional manufacturing setups, and further, the openings must further be deburred in order to make sure the pain of insertion is low.

US 2005/0107743 A disclose an infusion set comprising a base member, an introducer cap and an infusion cap. The base member comprises a soft cannula extending from a lower side of the base member and a port on an upper side thereof. The port is configured to be in fluid communication with the soft cannula. The port also comprises a septum adapted to seal the port against unwanted fluid flow. The introducer cap is adapted to be mounted to the base member and has a needle adapted to extend through the septum and said soft cannula in an assembled position. The infusion cap comprises a lumen adapted to receive a flexible tube. The infusion cap also comprises a hard cannula adapted to be inserted through the septum and to place said soft cannula in fluid communication with said lumen. The soft cannula according to US 2005/0107743 A give rise to two problems, one being that the soft cannula is disposed for kinking and the another is that the soft cannula according to US 2005/ 0107743 A suffers from similar delivery restrictions as already mentioned above.

WO 2002/083228 A2 discloses a fairly advanced syringe or catheter system capable of injecting, manually or automatically; precisely measured quantities of liquids into a

body. A plurality of needle designs is disclosed and according to the reference, the designs create advantageously shaped or diffused clouds, streams, or jets of medicament and the like. Generally, the reference seeks to set forth a syringe or catheter allowing for controlled injection of a medicament without substantial damage to tissue. According to the reference, the teachings of the reference may be applied to a relatively long and soft catheter or a rigid needle.

WO 2004/024219 A1 discloses a method and apparatus for epidermal or intradermal delivery of a medicament. A needle having at least one side port is used to penetrate the skin of a subject. The medicament is delivered through the side port and into the skin.

US 2010/0022956 A, by the applicant of the present invention, discloses an infusion set improvable by the teachings of the present application.

An infusion device comprising a cannula to be inserted by means of an insertion needle having following characteris- 20 tics is much desired:

The cannula which is cheap and simple to manufacture, The cannula which is user friendly and cause as little pain as possible to the end user, and

The cannula which is configured such that it will mitigate 25 the effects of kinking.

#### BRIEF DESCRIPTION OF THE INVENTION

The present invention seeks generally to improve today's infusion devices such that the abovementioned insufficiencies and drawbacks of today's infusion devices are overcome.

Up to this day, prior art has failed to teach a simple and yet reliable and inexpensive infusion device which in a safe and reliable manner, without substantially increasing the cost of the device, is able to satisfy the abovementioned much desired characteristics of the mentioned infusion device.

According to the invention, there is provided an infusion device as per the introductory part of this specification, and in particular, upon configuring the infusion device such that the infusion device further comprise a hub part configured to be fastened onto an outside surface of a patients skin via a 45 mounting pad, an infusion device resolving the abovementioned drawbacks are provided.

According to one embodiment, the infusion device may further include a pump configured to be in fluid connection with a reservoir configured to store or hold medication.

According to one embodiment, the subcutaneously placed distal portion may be made from soft material.

According to one embodiment, the cannula may be configured to be inserted by means of an insertion needle.

According to one embodiment the radial opening or openings may, when the cannula is inserted, be provided at least 1 millimeter below the skin surface.

According to one embodiment, the radial opening or openings may, when the cannula is inserted, be provided no more than 9 millimeter below the skin surface.

According to one embodiment, the radial opening may, when the cannula is inserted, be provided below the basal membrane.

According to one embodiment, the radial opening or 65 openings may, when the cannula is inserted, be provided no more than 3 millimeter below the skin surface.

4

According to one embodiment, the cannula may further comprise a plurality of radial openings allowing a portion of a drug conveyed through the tubular body member to discharge.

According to one embodiment, the radial openings may be apportioned such that the radial openings extend only through one wall of the tubular body member. Further, the radial openings may or may not extend axially along a straight line along the tubular body member.

According to one embodiment, one or more radial openings may extend through the tubular body member in an angle lying approximately perpendicular to a longitudinal axis of the cannula.

According to one embodiment, one or more radial openings may extend through the tubular body member in at least one angle oriented different from an angle lying perpendicular to a longitudinal axis of the cannula.

According to one embodiment, the radial openings that may extend through the tubular body member may have substantially equal diameter.

According to one embodiment, the radial openings that may extend through the tubular body member may have varying diameter.

According to one embodiment, the radial openings which may have varying diameter may be arranged such that the opening having the largest diameter is arranged nearest the distal portion of the cannula.

According to one embodiment, the radial openings, which may have varying diameter, further may be arranged such that the radial opening having the smallest diameter is arranged nearest the proximal end of the cannula.

According to one embodiment, the length of the distal portion of the cannula may be less than 15 mm and the outer diameter of the distal portion may be less than 1.5 mm and the diameter of the one or more radial openings may be between 15  $\mu$ m and 0.3 mm.

According to one embodiment, the infusion device may be configured for subcutaneous infusion of drugs such as insulin and the like.

### BRIEF DESCRIPTION OF THE DRAWINGS

- FIG. 1 is a plane view of an embodiment of a cannula applicable to the infusion device according to the present invention.
- FIG. 2 is an infusion device according to the present invention.
- FIG. 3 is a plane view of a cannula applicable to the infusion device according to the present invention, here shown together with a part of an insertion needle.
- FIG. 4 is a plane view of an embodiment of a cannula applicable to the infusion device according to the present invention.
- FIG. **5** is a plane view of an embodiment of a cannula applicable to the infusion device according to the present invention.
  - FIG. **6** is an end view of an embodiment of a cannula applicable to the infusion device according to the present invention.

# DETAILED DESCRIPTION OF THE INVENTION WITH REFERENCE TO THE FIGURES

FIG. 1 shows a plane view of one embodiment of a cannula 1 applicable to an infusion device according to the present invention.

The remaining parts and components of the infusion device is considered well known to those skilled in the relevant art, and therefore, such parts and components will only be briefly described in this specification, see FIG. 2.

As can be seen in FIG. 1 the cannula 1 is provided with 5 a tubular body member 3 having a conduit shown by the dashed lines. The conduit interconnects the in this figure not shown infusion device with the openings 2 and 5. The cannula 1 includes a proximal end 10 configured for interconnection with the not shown infusion device as well as a 10 distal portion 21 configured for subcutaneously placement by means of the insertion needle 70 shown in FIG. 3.

Numeral 5 refers to an outlet arranged in the distal portion 21, opposite the interconnection with the infusion device. The outlet 5 may or may not be considered the primary 15 outlet for drugs 4. In addition to the outlet 5, the cannula 1 is provided with at least one further opening 2.

Although FIGS. 1-4 disclose the cannula 1 including a plurality of openings 2, the present invention is not in any way limited to embodiments of the cannula 1 comprising 20 eter. more than one opening 2, see FIG. 5.

The subcutaneously placed distal portion 21, alternatively the entire cannula 1, may be made from a soft material such as PTFE (Teflon), FEP, rubber, PE material or silicone base materials and the like.

At least one of the radial openings 2 may, when the cannula 1 is inserted, be provided at between 1 and 9 millimeter below the skin surface 55, see FIG. 2.

FIG. 2 illustrates schematically an infusion device according to the present invention. The infusion device 50 includes a cannula 1 having a tubular body member 3 with a proximal end 10 and a subcutaneously placed distal portion 21 having a distal end 20. The distal portion 21 of the cannula may be provided with a radial opening 2 allowing a portion of a drug 4 conveyed through the tubular body member 3 to discharge. 35

The infusion device according to FIG. 2 further include a hub part 51 configured to be fastened onto an outside surface of a patients skin 55 via a mounting pad 52. The mounting pad 52 may be provided with an adhesive layer, configured to adhere to a patient's skin, and a not shown removable 40 release liner which covers the adhesive layer. The mounting pad 52 may be a dressing, a plaster, an adhesive pad or the like and the mounting pad may be configured in various shapes such as oval, circular, triangular rectangular etc.

According to one embodiment, the infusion device may 45 include a hub part 51 having a main plane being essentially parallel to the skin of the patient, when the infusion set is attached to a patient. The hub part 51 may have a main 54 surface being closest to the skin of a patient, and the main surface may be provided with fastening means such as the 50 mounting pad 52 for fastening the infusion device to the skin 55 of a patient.

In the embodiment according to FIG. 2, the cannula 1 extends from the hub part 51 through the fastening means or mounting pad 52. Alternatively the cannula 1 may extend 55 from the hub part 51 of the infusion device essentially along an inclined axis of insertion (not shown).

As shown in FIG. 2, the hub part 51 may include a septum or barrier 53.

As can be seen in FIGS. 1-4, the cannula 1 may be 60 provided with a plurality of radial openings 2 allowing the drug 4, conveyed through the tubular body member or hollow 3, to discharge. The openings 2 may be apportioned such that the openings 2 extend through one wall of the tubular body member 3 only, see FIG. 4. Further, the radial 65 openings 2 may extend axially along a not shown straight line along the cannula 1. The radial openings 2 may, in other

6

embodiments, be placed on different quarters of the cannula 1 such that all the holes are not blocked when pressure is applied to one side of the cannula 1.

The opening or openings 2 may or may not extend through said tubular body member in an angle lying approximately perpendicular to a longitudinal axis of the cannula 1. Further, the opening or openings 2 may extend through the tubular body member in at least one angle oriented different from an angle lying perpendicular to the longitudinal axis 100 of the cannula 1, as shown in FIG. 4.

The angles may constitute any angle between 0° and 180° relative to the longitudinal axis **100**; however angles lying in-between 30° and 150°, alternatively 60° and 120° or even 90° may be preferred.

The radial opening or openings 2 may have substantially equal diameter, although this is not in any way a requirement of the present invention. The opening or openings 2 may, according to certain embodiments, also have varying diameter.

It may be preferred to apply the radial opening or openings 2 as a spherical opening or openings; however other forms of opening or openings may equally be applied as long as the opening or openings do not adversely affect the strength and functionality of the cannula 1.

In case the cannula is provided with radial openings 2 having varying diameter, the openings 2 may be arranged such that the opening 2 having the largest diameter is arranged nearest the distal portion 21 of the cannula 1, whereby a substantially uniform outlet of fluid may be obtained over the length of the cannulas distal portion 21.

The length 30 of the distal portion 21 of the cannula 1 may be less than 30 mm, preferably 15 mm, and the outer diameter 35 of the distal portion 20 may be less that 2 mm, preferably less than 1.5 mm and the diameter of the opening or openings 2 may be between 10  $\mu$ m and 0.5 mm, preferably between 25  $\mu$ m and 0.3 mm.

The distal end 20 of the cannula 1 may or may not be tapered such as shown in FIG. 4. Providing the distal end 20 of the cannula 1 with a tapered end may facilitate insertion of the cannula 1. Although only the embodiment according to FIG. 4 is shown with a slant and tapered end, this may not in any way be considered limiting to other embodiments according to this specification.

The number of radial openings may, as already mentioned, vary from only one, such as shown in FIG. 5, to any number of openings, however according to one preferred embodiment, the cannula is provided with two radial openings, such as shown in the end view according to FIG. 6.

According to a well functioning embodiment, the cannula may be provided with two radial openings, or sprinkler holes, which are not located opposite each other, i.e. the openings are offset longitudinally as well as with respect to an angle seen from the end or circular cross section. A well functioning angle between the opening are considered to be 120 degree, see FIG. **6**.

The opening or openings may be provided, by means of drilling, punching, cutting or equivalent, in any angle to the longitudinal axis 100 of the cannula 1.

Generally seen, the cannula for the infusion device according to the present invention allows a drug such as insulin to be absorbed faster in the blood of the patient than the "one-outlet" soft cannulas according to today's infusion devices comprising cannulas made from a soft material.

According to certain aspects of the present invention, it has been found that one or more radial openings reduce soft cannulas well known tendency to occlude, e.g. due to

kinking. Hence the cannula for the infusion device according to the present invention is less inclined to malfunction as a result of kinking.

The application and combination of features and solutions presented by the present invention is not limited to the presented embodiments. One or more features of one embodiment can and may be combined with one or more not disclosed features of other embodiments, whereby not described, but valid, embodiments of the present invention may be obtained. One example is that the cannula according to the present invention may form part of an infusion device provided with means for monitoring or asserting whether or not the cannula of the infusion set is inserted as intended. Such means could inter alia constitute means configured for measuring impedance, where one option of performing the measurement by means of measuring impedance could be by using a drug such as insulin present in the cannula as an electrode.

The term "comprises/comprising/comprised of" when used in this specification incl. claims is taken to specify the presence of stated features, integers, steps or components but does not preclude the presence or addition of one or more other features, integers, steps, components or groups thereof.

The invention claimed is:

- 1. An infusion device configured for subcutaneous placement by an insertion needle and infusion of a drug comprising:
  - a cannula having a tubular body member, defining a conduit, with a proximal end and a subcutaneously placed distal portion having a wall and a distal end, wherein said distal portion comprises a soft material, wherein the soft material comprises a material selected  $_{35}$ from PTFE, FEP, rubber, PE material or silicone base materials, and wherein said distal portion further comprises at least two radial openings along the wall of the distal portion and an outlet at the distal end allowing a portion of the drug conveyed through said tubular body 40 member to discharge into subcutaneous tissue of a patient, wherein the at least two radial openings discharge the drug towards the distal end of the cannula, and wherein the at least two radial openings along the wall of the distal portion have a diameter between 10 45 μm and 0.5 mm and the outlet at the distal end has an outer diameter of less than 1.5 mm, and wherein two of the at least two radial openings are not located opposite each other including where the two radial openings are offset from each other along a longitudinal axis, and  $_{50}$ with respect to an angle seen from the outlet;

wherein a length of said distal portion of said cannula is less than 15 mm and the length permits a portion of the insertion needle to extend past the outlet of the distal end during placement of the infusion device; 8

- a hub part configured to be fastened onto an outside surface of a patient's skin via a mounting pad, wherein the at least two radial openings reduce occlusion due to kinking of the cannula;
- wherein the outlet of said cannula is tapered to facilitate insertion of the cannula with the insertion needle and the angle between two of the at least two radial openings is substantially 120 degrees.
- 2. The infusion device according to claim 1, wherein said at least two radial openings are positioned at least 1 millimeter below the skin surface when said cannula is subcutaneously placed.
- 3. The infusion device according to claim 1, wherein said at least two radial openings are positioned no more than 9 millimeters below the skin surface when said cannula is subcutaneously placed.
- 4. The infusion device according to claim 1, wherein said at least two radial openings are positioned below the basal membrane when said cannula is subcutaneously placed.
- 5. The infusion device according to claim 1, wherein said at least two radial openings are positioned no more than 3 millimeters below the skin surface when said cannula is subcutaneously placed.
- 6. The infusion device according to claim 1, wherein said device further comprises a pump in fluid connection with a reservoir configured to store medication.
  - 7. The infusion device according to claim 1, wherein said infusion device is configured for subcutaneous infusion of one or more drugs.
  - 8. The infusion device according to claim 7, wherein said one or more drugs comprise insulin.
  - 9. The infusion device according to claim 1 wherein the at least two radial openings include a first radial opening inclined with respect to the longitudinal axis and toward the outlet, a second radial opening substantially perpendicular to the longitudinal axis, and a third radial opening inclined with respect to the longitudinal axis and away from the outlet.
  - 10. The infusion device according to claim 1, wherein the infusion device comprises three or more radial openings.
  - 11. The infusion device according to claim 10, wherein said plurality of radial openings extending through said tubular body member have substantially equal diameter.
  - 12. The infusion device according to claim 10, wherein said plurality of radial openings extending through said tubular body member have varying diameters.
  - 13. The infusion device according to claim 12, wherein said plurality of radial openings having varying diameters are configured such that the radial opening having a smallest diameter is arranged nearest said distal portion of said cannula.
  - 14. The infusion device according to claim 12, wherein said plurality of radial openings having varying diameters are configured such that the radial opening having a smallest diameter is arranged nearest said proximal end of said cannula.

\* \* \* \*