



US011020621B2

(12) **United States Patent**
Betz et al.

(10) **Patent No.:** **US 11,020,621 B2**
(45) **Date of Patent:** **Jun. 1, 2021**

(54) **STABILITY SYSTEM FOR A FIRE APPARATUS**

(71) Applicant: **Oshkosh Corporation**, Oshkosh, WI (US)

(72) Inventors: **Eric D. Betz**, Oshkosh, WI (US);
David W. Archer, Oshkosh, WI (US)

(73) Assignee: **Oshkosh Corporation**, Oshkosh, WI (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/653,377**

(22) Filed: **Oct. 15, 2019**

(65) **Prior Publication Data**

US 2020/0038700 A1 Feb. 6, 2020

Related U.S. Application Data

(63) Continuation of application No. 16/389,570, filed on Apr. 19, 2019, now Pat. No. 10,456,610.

(60) Provisional application No. 62/661,384, filed on Apr. 23, 2018.

(51) **Int. Cl.**
A62C 27/00 (2006.01)
B66C 23/78 (2006.01)
B60S 9/04 (2006.01)

(52) **U.S. Cl.**
CPC *A62C 27/00* (2013.01); *B60S 9/04* (2013.01); *B66C 23/78* (2013.01); *B66C 2700/0378* (2013.01)

(58) **Field of Classification Search**
CPC *A62C 27/00*; *B60S 9/04*; *B66C 23/78*;
B66C 2700/0378

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,021,016 A *	2/1962	Noll	E02F 9/085 212/304
3,073,467 A *	1/1963	Parks	B60S 9/02 254/45
3,194,414 A *	7/1965	Letourneau	B66C 23/78 212/303
3,338,426 A *	8/1967	Grove	B66C 23/80 212/304
3,716,252 A *	2/1973	Johnson	B66C 23/80 280/766.1
3,953,052 A *	4/1976	Palmcrantz	B66C 23/78 280/763.1
4,084,777 A *	4/1978	Lambert	B66C 23/80 212/304

(Continued)


Primary Examiner — Erez Gurari

(74) *Attorney, Agent, or Firm* — Foley & Lardner LLP

(57) **ABSTRACT**

A vehicle includes a chassis, a front axle coupled to a front end of the chassis, a rear axle coupled to a rear end of the chassis, a pair of front downriggers coupled to the front end of the chassis forward of the front axle, a pair of rear downriggers coupled to the rear end of the chassis rearward of the rear axle, and an outrigger assembly coupled to the chassis between the front axle and the rear axle. The pair of front downriggers is selectively extendable to engage a ground surface. The pair of rear downriggers is selectively extendable to engage the ground surface. The outrigger assembly includes a pair of outriggers that are selectively extendable laterally outward at an angle relative to a horizontal.

19 Claims, 37 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

4,142,710	A *	3/1979	Okuda	B66C 23/80 212/304	2006/0065451	A1	3/2006	Morrow et al.	
4,276,985	A *	7/1981	Newman	B66C 23/62 212/177	2006/0065453	A1	3/2006	Morrow et al.	
4,397,396	A *	8/1983	Kay	B66C 23/78 212/195	2006/0070776	A1	4/2006	Morrow et al.	
4,444,416	A *	4/1984	Soderstrom	B66F 11/044 280/763.1	2006/0071466	A1	4/2006	Rowe et al.	
4,454,952	A *	6/1984	McGhie	B66C 23/78 212/302	2006/0180322	A1	8/2006	Archer et al.	
4,461,490	A *	7/1984	Fritel	B66C 23/78 212/302	2006/0267326	A1 *	11/2006	Richard B66C 23/78 280/763.1
4,746,133	A *	5/1988	Hanser	B60S 9/12 180/41	2009/0127010	A1	5/2009	Morrow et al.	
5,820,150	A	10/1998	Archer et al.			2010/0116569	A1	5/2010	Morrow et al.	
5,897,123	A	4/1999	Cherney et al.			2011/0062695	A1 *	3/2011	Bergemann B66C 23/905 280/763.1
5,934,409	A *	8/1999	Citron	B66F 11/044 182/17	2012/0049499	A1 *	3/2012	Hartweg B66C 23/80 280/763.1
5,961,145	A *	10/1999	Schillinger	B60S 9/10 280/764.1	2012/0173094	A1 *	7/2012	Steinich B66C 23/78 701/50
6,138,845	A *	10/2000	Kaspar	B62D 33/0633 212/302	2014/0032060	A1 *	1/2014	Zinke B66C 23/78 701/50
6,247,713	B1	6/2001	Konop			2014/0246265	A1	9/2014	Archer et al.	
6,276,718	B1 *	8/2001	Wolfram	B60S 9/12 212/302	2014/0334169	A1 *	11/2014	Ewert E06C 5/04 362/485
6,341,705	B1 *	1/2002	Kaspar	B62D 33/0633 212/291	2015/0159564	A1	6/2015	Wildgrube et al.	
6,516,917	B1 *	2/2003	Mayer	B66C 23/80 182/17	2015/0330146	A1 *	11/2015	Kraemer E06C 5/38 701/34.4
6,561,718	B1	5/2003	Archer et al.			2016/0023548	A1	1/2016	Crist et al.	
6,811,161	B1 *	11/2004	Anderson	E06C 5/04 182/19	2016/0059690	A1	3/2016	Wildgrube	
6,860,332	B1	3/2005	Archer et al.			2016/0144210	A1	5/2016	Betz et al.	
7,331,748	B2 *	2/2008	Knepp	E02F 3/96 212/301	2016/0144211	A1	5/2016	Betz et al.	
8,087,695	B2 *	1/2012	Fugel	E04G 21/0436 280/766.1	2016/0145940	A1	5/2016	Aiken et al.	
8,757,663	B1 *	6/2014	Glazer	B66C 23/80 280/766.1	2016/0145941	A1 *	5/2016	Betz A62C 27/00 182/66.1
8,839,968	B2 *	9/2014	Seales	B60P 1/483 212/294	2016/0158587	A1 *	6/2016	Ge A62C 3/00 169/56
9,302,129	B1 *	4/2016	Betz	A62C 27/00	2016/0215560	A1	7/2016	Aiken et al.	
9,695,604	B2 *	7/2017	Trumper	G01B 7/30	2016/0304051	A1	10/2016	Archer et al.	
10,308,487	B2 *	6/2019	Ost	B66C 23/78	2016/0340156	A1 *	11/2016	Ost B66C 23/905
2002/0014754	A1	2/2002	Konop			2016/0347590	A1 *	12/2016	Daum B66C 23/78
2003/0205422	A1	11/2003	Morrow et al.			2017/0036628	A1	2/2017	Nelson et al.	
2003/0230412	A1	12/2003	Archer			2017/0158050	A1	6/2017	Crist et al.	
2003/0230863	A1	12/2003	Archer			2017/0217737	A1 *	8/2017	Rudy G06T 7/0004
2004/0039510	A1	2/2004	Archer et al.			2017/0225888	A1	8/2017	Betz et al.	
2005/0001400	A1	1/2005	Archer et al.			2017/0349374	A1	12/2017	Haddick et al.	
2005/0109549	A1	5/2005	Morrow			2017/0362065	A1 *	12/2017	Shan B66C 23/344
2005/0285365	A1	12/2005	Manser et al.			2018/0215354	A1 *	8/2018	Linsmeier E06C 5/04
2006/0065411	A1	3/2006	Linsmeier et al.			2018/0215597	A1 *	8/2018	Linsmeier A62C 27/00
						2018/0244508	A1 *	8/2018	Kosterke B66C 23/40
						2018/0297597	A1	10/2018	Linsmeier et al.	
						2018/0334324	A1	11/2018	Haddick et al.	
						2019/0047413	A1	2/2019	Crist et al.	
						2019/0047831	A1 *	2/2019	Moose B66C 23/36
						2019/0055112	A1 *	2/2019	Kosterke B66C 23/54
						2019/0106083	A1	4/2019	Archer et al.	
						2019/0118721	A1	4/2019	Handschke et al.	
						2019/0134440	A1 *	5/2019	Carter F04B 17/06
						2019/0161272	A1	5/2019	Betz et al.	
						2019/0185077	A1	6/2019	Smith et al.	

* cited by examiner




FIG. 1




FIG. 3




FIG. 4




FIG. 5





FIG. 6






FIG. 8




FIG. 9




FIG. 11




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 31

FIG. 30




FIG. 33




FIG. 35






FIG. 36






FIG. 39




FIG. 40




FIG. 41




FIG. 42

STABILITY SYSTEM FOR A FIRE APPARATUS

CROSS-REFERENCE TO RELATED PATENT APPLICATIONS

This application (a) is a continuation of U.S. patent application Ser. No. 16/389,570, filed Apr. 19, 2019, which claims the benefit of U.S. Provisional Patent Application No. 62/661,384, filed Apr. 23, 2018, and (b) is related to (i) U.S. patent application Ser. No. 16/389,630, filed Apr. 19, 2019, which claims the benefit of U.S. Provisional Patent Application No. 62/661,382, filed Apr. 23, 2018, (ii) U.S. patent application Ser. No. 16/389,653, filed Apr. 19, 2019, which claims the benefit of U.S. Provisional Patent Application No. 62/661,420, filed Apr. 23, 2018, (iii) U.S. patent application Ser. No. 16/389,600, filed Apr. 19, 2019, which claims the benefit of U.S. Provisional Patent Application No. 62/661,414, filed Apr. 23, 2018, (iv) U.S. patent application Ser. No. 16/389,143, filed Apr. 19, 2019, which claims the benefit of U.S. Provisional Patent Application No. 62/661,419, filed Apr. 23, 2018, (v) U.S. patent application Ser. No. 16/389,176, filed Apr. 19, 2019, which claims the benefit of U.S. Provisional Patent Application No. 62/661,426, filed Apr. 23, 2018, (vi) U.S. patent application Ser. No. 16/389,029, filed Apr. 19, 2019, which claims the benefit of U.S. Provisional Patent Application No. 62/661,335, filed Apr. 23, 2018, and U.S. Provisional Patent Application No. 62/829,922, filed Apr. 5, 2019, and (vii) U.S. patent application Ser. No. 16/389,072, filed Apr. 19, 2019, which claims the benefit of U.S. Provisional Patent Application No. 62/661,330, filed Apr. 23, 2018, all of which are incorporated herein by reference in their entireties.

BACKGROUND

Fire apparatuses may be configured as rear-mount aerial fire apparatuses or mid-mount aerial fire apparatuses. Further, such fire apparatuses may be configured as quint configuration fire apparatuses including an aerial ladder, a water tank, a water pump, ground ladder storage, and hose storage. Typically, such fire apparatuses may also include outriggers. However, the outriggers extend directly horizontal from a body of the fire apparatuses and prevent the aerial ladder from being continuously operable at a depression angle without being impeded by the extended outriggers.

SUMMARY

One embodiment relates to a vehicle. The vehicle includes a chassis, a front axle coupled to a front end of the chassis, a rear axle coupled to a rear end of the chassis, a pair of front downriggers coupled to the front end of the chassis forward of the front axle, a pair of rear downriggers coupled to the rear end of the chassis rearward of the rear axle, and an outrigger assembly coupled to the chassis between the front axle and the rear axle. The pair of front downriggers is selectively extendable to engage a ground surface. The pair of rear downriggers is selectively extendable to engage the ground surface. The outrigger assembly includes a pair of outriggers that are selectively extendable laterally outward at an angle relative to a horizontal.

Another embodiment relates to a stability system for a vehicle. The stability system includes an outrigger assembly including a first housing tube, a second housing tube, and one or more collars. The first housing tube has a first end and an opposing second end. The first housing tube is configured

to extend laterally across the vehicle along a positive slope. The second housing tube has a third end and an opposing fourth end. The first housing tube is configured to extend laterally across the vehicle along a negative slope such that (i) the first end of the first housing tube and the third end of the second housing tube and (ii) the opposing second end of the first housing tube and the opposing fourth end of the second housing tube are vertically offset. The one or more collars are positioned to couple at least one of (i) the first end of the first housing tube and the third end of the second housing tube or (ii) the opposing second end of the first housing tube and the opposing fourth end of the second housing tube together.

Still another embodiment relates to a stability system for a vehicle. The stability system include a first front downrigger configured to be coupled proximate a first lateral side of a front end of a chassis of the vehicle and a second front downrigger configured to be coupled proximate an opposing second lateral side of the front end of the chassis of the vehicle. The first front downrigger and the second front downrigger are selectively extendable to engage a ground surface.

This summary is illustrative only and is not intended to be in any way limiting. Other aspects, inventive features, and advantages of the devices or processes described herein will become apparent in the detailed description set forth herein, taken in conjunction with the accompanying figures, wherein like reference numerals refer to like elements.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a left side view of a mid-mount fire apparatus, according to an exemplary embodiment.

FIG. 2 is a right side view of the mid-mount fire apparatus of FIG. 1, according to an exemplary embodiment.

FIG. 3 is a top view of the mid-mount fire apparatus of FIG. 1, according to an exemplary embodiment.

FIG. 4 is a bottom view of the mid-mount fire apparatus of FIG. 1, according to an exemplary embodiment.

FIG. 5 is a rear view of the mid-mount fire apparatus of FIG. 1, according to an exemplary embodiment.

FIG. 6 is a rear view of the mid-mount fire apparatus of FIG. 1 having outriggers in an extended configuration, according to an exemplary embodiment.

FIG. 7 is a front view of the mid-mount fire apparatus of FIG. 1 having outriggers in an extended configuration, according to an exemplary embodiment.

FIG. 8 is a side view of the mid-mount fire apparatus of FIG. 1 relative to a traditional mid-mount fire apparatus, according to an exemplary embodiment.

FIG. 9 is a side view of the mid-mount fire apparatus of FIG. 1 relative to a traditional rear-mount fire apparatus, according to an exemplary embodiment.

FIG. 10 is a rear perspective view of a rear assembly of the mid-mount fire apparatus of FIG. 1, according to an exemplary embodiment.

FIG. 11 is detailed rear perspective view of the rear assembly of FIG. 10, according to an exemplary embodiment.

FIG. 12 is another rear perspective view of the rear assembly of FIG. 10 without a ladder assembly, according to an exemplary embodiment.

FIG. 13 is a top view of the rear assembly of FIG. 12, according to an exemplary embodiment.

FIG. 14 is a perspective view of a torque box of the mid-mount fire apparatus of FIG. 1, according to an exemplary embodiment.

FIG. 15 is a side view of the torque box of FIG. 14, according to an exemplary embodiment.

FIG. 16 is a perspective view of an aerial ladder assembly and turntable of the mid-mount fire apparatus of FIG. 1, according to an exemplary embodiment.

FIG. 17 is a side view of a pump housing of the mid-mount fire apparatus of FIG. 1 in a first configuration, according to an exemplary embodiment.

FIG. 18 is a side perspective view of a pump system within the pump housing of FIG. 17 in a second configuration, according to an exemplary embodiment.

FIG. 19 is a side perspective view of the pump system of FIG. 18 with a platform in a deployed configuration, according to an exemplary embodiment.

FIGS. 20 and 21 are opposing side views of the pump system of FIG. 18, according to an exemplary embodiment.

FIG. 22 is a detailed perspective view of an aerial assembly recess of the mid-mount fire apparatus of FIG. 1, according to an exemplary embodiment.

FIGS. 23 and 24 are various perspective views of a scrub area of an aerial assembly of the mid-mount fire apparatus of FIG. 1, according to an exemplary embodiment.

FIG. 25 is a rear view of the mid-mount fire apparatus of FIG. 1 having an aerial assembly at a negative depression angle, according to an exemplary embodiment.

FIG. 26 is a front view of an aerial assembly of the mid-mount fire apparatus of FIG. 1 in a plurality of configurations, according to an exemplary embodiment.

FIG. 27 is a block diagram of a control system of the mid-mount fire apparatus of FIG. 1, according to an exemplary embodiment.

FIG. 28 is a perspective view of a front downrigger assembly of the mid-mount fire apparatus of FIG. 1, according to an exemplary embodiment.

FIG. 29 is a front view of the front downrigger assembly of FIG. 28, according to an exemplary embodiment.

FIG. 30 is a top view of the front downrigger assembly of FIG. 28, according to an exemplary embodiment.

FIG. 31 is a perspective front view of the front downrigger assembly of FIG. 28, according to an exemplary embodiment.

FIG. 32 is a perspective view of a front downrigger assembly of the of the mid-mount fire apparatus of FIG. 1 in a first orientation, according to another exemplary embodiment.

FIG. 33 is a perspective view of the front downrigger assembly of FIG. 32 in a second orientation, according to an exemplary embodiment.

FIG. 34 is a perspective view of a cab of the mid-mount fire apparatus of FIG. 1 pivoted with the front downrigger assembly of FIG. 32 in the second orientation, according to an exemplary embodiment.

FIGS. 35-37 are various views of a rear downrigger assembly of the mid-mount fire apparatus of FIG. 1, according to an exemplary embodiment.

FIGS. 38-40 are various views of an outrigger assembly of the mid-mount fire apparatus of FIG. 1, according to an exemplary embodiment.

FIG. 41 is a detailed schematic rear view of an outrigger housing of the outrigger assembly of FIGS. 38-40, according to an exemplary embodiment.

FIG. 42 is a detailed view of a collar for the outrigger housing of the outrigger assembly of FIG. 41, according to an exemplary embodiment.

DETAILED DESCRIPTION

Before turning to the figures, which illustrate certain exemplary embodiments in detail, it should be understood

that the present disclosure is not limited to the details or methodology set forth in the description or illustrated in the figures. It should also be understood that the terminology used herein is for the purpose of description only and should not be regarded as limiting.

According to an exemplary embodiment, a vehicle includes various components that improve performance relative to traditional systems. In one embodiment, the vehicle is a mid-mount quint configuration fire apparatus that includes a water tank, an aerial ladder, hose storage, ground ladder storage, and a water pump. The fire apparatus includes a stability system including front downriggers coupled to a front end of the fire apparatus, rear downriggers coupled to a rear end of the fire apparatus, and outriggers coupled to the fire apparatus rearward of a vertical pivot axis of the aerial ladder. In some embodiments, the front downriggers are selectively pivotable to facilitate pivoting a front cabin of the fire apparatus. In some embodiments, the outriggers extend laterally from a body of the fire apparatus at an angle (e.g., a negative angle, a depression angle, etc.).

Overall Vehicle

According to the exemplary embodiment shown in FIGS. 1-21, a vehicle, shown as fire apparatus 10, is configured as a mid-mount quint fire truck having a tandem rear axle. A “quint” fire truck as used herein may refer to a fire truck that includes a water tank, an aerial ladder, hose storage, ground ladder storage, and a water pump. In other embodiments, the fire apparatus 10 is configured as a mid-mount quint fire truck having a single rear axle. A tandem rear axle may include two solid axle configurations or may include two pairs of axles (e.g., two pairs of half shafts, etc.) each having a set of constant velocity joints and coupling two differentials to two pairs of hub assemblies. A single rear axle chassis may include one solid axle configuration or may include one pair of axles each having a set of constant velocity joints and coupling a differential to a pair of hub assemblies, according to various alternative embodiments. In still other embodiments, the fire apparatus 10 is configured as a non-quint mid-mount fire truck having a single rear axle or a tandem rear axle. In yet other embodiments, the fire apparatus 10 is configured as a rear-mount, quint or non-quint, single rear axle or tandem rear axle, fire truck.

As shown in FIGS. 1-7, 10-13, 17, and 18, the fire apparatus 10 includes a chassis, shown as frame 12, having longitudinal frame rails that define an axis, shown as longitudinal axis 14, that extends between a first end, shown as front end 2, and an opposing second end, shown as rear end 4, of the fire apparatus 10; a first axle, shown as front axle 16, coupled to the frame 12; one or more second axles, shown as rear axles 18, coupled to the frame 12; a first assembly, shown as front cabin 20, coupled to and supported by the frame 12 and having a bumper, shown as front bumper 22; a prime mover, shown as engine 60, coupled to and supported by the frame 12; and a second assembly, shown as rear assembly 100, coupled to and supported by the frame 12.

As shown in FIGS. 1-7, 10, and 12, the front axle 16 and the rear axles 18 include tractive assemblies, shown as wheel and tire assemblies 30. As shown in FIGS. 1-4, the front cabin 20 is positioned forward of the rear assembly 100 (e.g., with respect to a forward direction of travel for the fire apparatus 10 along the longitudinal axis 14, etc.). According to an alternative embodiment, the cab assembly may be positioned behind the rear assembly 100 (e.g., with respect to a forward direction of travel for the fire apparatus 10 along the longitudinal axis 14, etc.). The cab assembly may be positioned behind the rear assembly 100 on, by way of

example, a rear tiller fire apparatus. In some embodiments, the fire apparatus **10** is a ladder truck with a front portion that includes the front cabin **20** pivotally coupled to a rear portion that includes the rear assembly **100**.

According to an exemplary embodiment, the engine **60** receives fuel (e.g., gasoline, diesel, etc.) from a fuel tank and combusts the fuel to generate mechanical energy. A transmission receives the mechanical energy and provides an output to a drive shaft. The rotating drive shaft is received by a differential, which conveys the rotational energy of the drive shaft to a final drive (e.g., the front axle **16**, the rear axles **18**, the wheel and tire assemblies **30**, etc.). The final drive then propels or moves the fire apparatus **10**. According to an exemplary embodiment, the engine **60** is a compression-ignition internal combustion engine that utilizes diesel fuel. In alternative embodiments, the engine **60** is another type of prime mover (e.g., a spark-ignition engine, a fuel cell, an electric motor, etc.) that is otherwise powered (e.g., with gasoline, compressed natural gas, propane, hydrogen, electricity, etc.).

As shown in FIGS. **1-7**, **10-13**, and **17-19**, the rear assembly **100** includes a body assembly, shown as body **110**, coupled to and supported by the frame **12**; a fluid driver, shown as pump system **200**, coupled to and supported by the frame **12**; a chassis support member, shown as torque box **300**, coupled to and supported by the frame **12**; a fluid reservoir, shown as water tank **400**, coupled to the body **110** and supported by the torque box **300** and/or the frame **12**; and an aerial assembly, shown as aerial assembly **500**, pivotally coupled to the torque box **300** and supported by the torque box **300** and/or the frame **12**. In some embodiments, the rear assembly **100** does not include the water tank **400**. In some embodiments, the rear assembly **100** additionally or alternatively includes an agent or foam tank (e.g., that receives and stores a fire suppressing agent, foam, etc.).

As shown in FIGS. **1**, **2**, and **10-12**, the sides of the body **110** define a plurality of compartments, shown as storage compartments **112**. The storage compartments **112** may receive and store miscellaneous items and gear used by emergency response personnel (e.g., helmets, axes, oxygen tanks, hoses, medical kits, etc.). As shown in FIGS. **5**, **6**, and **10-12**, the rear end **4** of the body **110** defines a longitudinal storage compartment that extends along the longitudinal axis **14**, shown as ground ladder compartment **114**. The ground ladder compartment **114** may receive and store one or more ground ladders. As shown in FIGS. **3**, **5**, and **10-13**, a top surface, shown as top platform **122**, of the body **110** defines a cavity, shown as hose storage platform **116**, and a channel, shown as hose chute **118**, extending from the hose storage platform **116** to the rear end **4** of the body **110**. The hose storage platform **116** may receive and store one or more hoses (e.g., up to 1000 feet of 5 inch diameter hose, etc.), which may be pulled from the hose storage platform **116** through the hose chute **118**.

As shown in FIGS. **1-6** and **10-13**, the rear end **4** of the body **110** has notched or clipped corners, shown as chamfered corners **120**. In other embodiments, the rear end **4** of the body **110** does not have notched or clipped corners (e.g., the rear end **4** of the body **110** may have square corners, etc.). According to an exemplary embodiment, the chamfered corners **120** provide for increased turning clearance relative to fire apparatuses that have non-notched or non-clipped (e.g., square, etc.) corners. As shown in FIGS. **1-3**, **5**, **6**, and **10-13**, the rear assembly **100** includes a first selectively deployable ladder, shown as rear ladder **130**, coupled to each of the chamfered corners **120** of the body **110**. According to an exemplary embodiment, the rear

ladders **130** are hingedly coupled to the chamfered corners **120** and repositionable between a stowed position (see, e.g., FIGS. **1-3**, **5**, **12**, **13**, etc.) and a deployed position (see, e.g., FIGS. **6**, **10**, **11**, etc.). The rear ladders **130** may be selectively deployed such that a user may climb the rear ladder **130** to access the top platform **122** of the body **110** and/or one or more components of the aerial assembly **500** (e.g., a work basket, an implement, an aerial ladder assembly, the hose storage platform **116**, etc.). In other embodiments, the body **110** has stairs in addition to or in place of the rear ladders **130**.

As shown in FIGS. **1**, **12**, **17**, and **18**, the rear assembly **100** includes a second selectively deployable ladder, shown as side ladder **132**, coupled to a side (e.g., a left side, a right side, a driver's side, a passenger's side, etc.) of the body **110**. In some embodiments, the rear assembly **100** includes two side ladders **132**, one coupled to each side of the body **110**. According to an exemplary embodiment, the side ladder **132** is hingedly coupled to the body **110** and repositionable between a stowed position (see, e.g., FIGS. **1**, **2**, **17**, **18**, etc.) and a deployed position. The side ladder **132** may be selectively deployed such that a user may climb the side ladder **132** to access one or more components of the aerial assembly **500** (e.g., a work platform, an aerial ladder assembly, a control console, etc.).

As shown in FIGS. **1**, **2**, **12** and **13**, the body **110** defines a recessed portion, shown as aerial assembly recess **140**, positioned (i) rearward of the front cabin **20** and (ii) forward of the water tank **400** and/or the rear axles **18**. The aerial assembly recess **140** defines an aperture, shown as pedestal opening **142**, rearward of the pump system **200**.

According to an exemplary embodiment the water tank **400** is coupled to the frame **12** with a superstructure (e.g., disposed along a top surface of the torque box **300**, etc.). As shown in FIGS. **1**, **2**, **12**, and **13**, the water tank **400** is positioned below the aerial ladder assembly **700** and forward of the hose storage platform **116**. As shown in FIGS. **1**, **2**, **12** and **13**, the water tank **400** is positioned such that the water tank **400** defines a rear wall of the aerial assembly recess **140**. In one embodiment, the water tank **400** stores up to 300 gallons of water. In another embodiment, the water tank **400** stores more than or less than 300 gallons of water (e.g., **100**, **200**, **250**, **350**, **400**, **500**, etc. gallons). In other embodiments, fire apparatus **10** additionally or alternatively includes a second reservoir that stores another firefighting agent (e.g., foam, etc.). In still other embodiments, the fire apparatus **10** does not include the water tank **400** (e.g., in a non-quiet configuration, etc.).

As shown in FIGS. **1-3**, **5-7**, **10**, **17**, and **18**, the aerial assembly **500** includes a turntable assembly, shown as turntable **510**, pivotally coupled to the torque box **300**; a platform, shown work platform **550**, coupled to the turntable **510**; a console, shown as control console **600**, coupled to the turntable **510**; a ladder assembly, shown as aerial ladder assembly **700**, having a first end (e.g., a base end, a proximal end, a pivot end, etc.), shown as proximal end **702**, pivotally coupled to the turntable **510**, and an opposing second end (e.g., a free end, a distal end, a platform end, an implement end, etc.), shown as distal end **704**; and an implement, shown as work basket **1300**, coupled to the distal end **704**.

As shown in FIGS. **1**, **2**, **4**, **14**, and **15**, the torque box **300** is coupled to the frame **12**. In one embodiment, the torque box **300** extends laterally the full width between the lateral outsides of the frame rails of the frame **12**. As shown in FIGS. **14** and **15**, the torque box **300** includes a body portion, shown as body **302**, having a first end, shown as front end **304**, and an opposing second end, shown as rear end **306**. As

shown in FIGS. 12, 14, and 15, the torque box 300 includes a support, shown as pedestal 308, coupled (e.g., attached, fixed, bolted, welded, etc.) to the front end 304 of the torque box 300. As shown in FIG. 12, the pedestal 308 extends through the pedestal opening 142 into the aerial assembly recess 140 such that the pedestal 308 is positioned (i) forward of the water tank 400 and the rear axles 18 and (ii) rearward of pump system 200, the front axle 16, and the front cabin 20.

According to the exemplary embodiment shown in FIGS. 1, 2, and 12, the aerial assembly 500 (e.g., the turntable 510, the work platform 550, the control console 600, the aerial ladder assembly 700, the work basket 1300, etc.) is rotatably coupled to the pedestal 308 such that the aerial assembly 500 is selectively repositionable into a plurality of operating orientations about a vertical axis, shown as vertical pivot axis 40. As shown in FIGS. 12, 14, and 15, the torque box 300 includes a pivotal connector, shown as slewing bearing 310, coupled to the pedestal 308. The slewing bearing 310 is a rotational rolling-element bearing with an inner element, shown as bearing element 312, and an outer element, shown as driven gear 314. The bearing element 312 may be coupled to the pedestal 308 with a plurality of fasteners (e.g., bolts, etc.).

As shown in FIGS. 14 and 15, a drive actuator, shown as rotation actuator 320, is coupled to the pedestal 308 (e.g., by an intermediate bracket, etc.). The rotation actuator 320 is positioned to drive (e.g., rotate, turn, etc.) the driven gear 314 of the slewing bearing 310. In one embodiment, the rotation actuator 320 is an electric motor (e.g., an alternating current (AC) motor, a direct current motor (DC), etc.) configured to convert electrical energy into mechanical energy. In other embodiments, the rotation actuator 320 is powered by air (e.g., pneumatic, etc.), a fluid (e.g., a hydraulic cylinder, etc.), mechanically (e.g., a flywheel, etc.), or still another power source.

As shown in FIGS. 14 and 15, the rotation actuator 320 includes a driver, shown as drive pinion 322. The drive pinion 322 is mechanically coupled with the driven gear 314 of the slewing bearing 310. In one embodiment, a plurality of teeth of the drive pinion 322 engage a plurality of teeth on the driven gear 314. By way of example, when the rotation actuator 320 is engaged (e.g., powered, turned on, etc.), the rotation actuator 320 may provide rotational energy (e.g., mechanical energy, etc.) to an output shaft. The drive pinion 322 may be coupled to the output shaft such that the rotational energy of the output shaft drives (e.g., rotates, etc.) the drive pinion 322. The rotational energy of the drive pinion 322 may be transferred to the driven gear 314 in response to the engaging teeth of both the drive pinion 322 and the driven gear 314. The driven gear 314 thereby rotates about the vertical pivot axis 40, while the bearing element 312 remains in a fixed position relative to the driven gear 314.

As shown in FIGS. 1, 2, and 16-18, the turntable 510 includes a first portion, shown as rotation base 512, and a second portion, shown as side supports 514, that extend vertically upward from opposing lateral sides of the rotation base 512. According to an exemplary embodiment, (i) the work platform 550 is coupled to the side supports 514, (ii) the aerial ladder assembly 700 is pivotally coupled to the side supports 514, (iii) the control console 600 is coupled to the rotation base 512, and (iv) the rotation base 512 is disposed within the aerial assembly recess 140 and interfaces with and is coupled to the driven gear 314 of slewing bearing 310 such that (i) the aerial assembly 500 is selectively pivotable about the vertical pivot axis 40 using the

rotation actuator 320, (ii) at least a portion of the work platform 550 and the aerial ladder assembly 700 is positioned below the roof of the front cabin 20, and (iii) the turntable 510 is coupled rearward of the front cabin 20 and between the front axle 16 and the tandem rear axles 18 (e.g., the turntable 510 is coupled to the frame 12 such that the vertical pivot axis 40 is positioned rearward of a centerline of the front axle 16, forward of a centerline of the tandem rear axle 18, rearward of a rear edge of a tire of the front axle 16, forward of a front edge of a wheel of the front axle of the tandem rear axles 18, rearward of a front edge of a tire of the front axle 16, forward of a rear edge of a wheel of the rear axle of the tandem rear axles 18, etc.). Accordingly, loading from the work basket 1300, the aerial ladder assembly 700, and/or the work platform 550 may transfer through the turntable 510 into the torque box 300 and the frame 12.

As shown in FIG. 12, the rear assembly 100 includes a rotation swivel, shown as rotation swivel 316, that includes a conduit. According to an exemplary embodiment, the conduit of the rotation swivel 316 extends upward from the pedestal 308 and into the turntable 510. The rotation swivel 316 may couple (e.g., electrically, hydraulically, fluidly, etc.) the aerial assembly 500 with other components of the fire apparatus 10. By way of example, the conduit may define a passageway for water to flow into the aerial ladder assembly 700. Various lines may provide electricity, hydraulic fluid, and/or water to the aerial ladder assembly 700, actuators, and/or the control console 600.

According to an exemplary embodiment, the work platform 550 provides a surface upon which operators (e.g., fire fighters, rescue workers, etc.) may stand while operating the aerial assembly 500 (e.g., with the control console 600, etc.). The control console 600 may be communicably coupled to various components of the fire apparatus 10 (e.g., actuators of the aerial ladder assembly 700, rotation actuator 320, water turret, etc.) such that information or signals (e.g., command signals, fluid controls, etc.) may be exchanged from the control console 600. The information or signals may relate to one or more components of the fire apparatus 10. According to an exemplary embodiment, the control console 600 enables an operator (e.g., a fire fighter, etc.) of the fire apparatus 10 to communicate with one or more components of the fire apparatus 10. By way of example, the control console 600 may include at least one of an interactive display, a touchscreen device, one or more buttons (e.g., a stop button configured to cease water flow through a water nozzle, etc.), joysticks, switches, and voice command receivers. An operator may use a joystick associated with the control console 600 to trigger the actuation of the turntable 510 and/or the aerial ladder assembly 700 to a desired angular position (e.g., to the front, back, or side of fire apparatus 10, etc.). By way of another example, an operator may engage a lever associated with the control console 600 to trigger the extension or retraction of the aerial ladder assembly 700.

As shown in FIG. 16, the aerial ladder assembly 700 has a plurality of nesting ladder sections that telescope with respect to one another including a first section, shown as base section 800; a second section, shown as lower middle section 900; a third ladder section, shown as middle section 1000; a fourth section, shown as upper middle section 1100; and a fifth section, shown as fly section 1200. As shown in FIGS. 16 and 17, the side supports 514 of the turntable 510 define a first interface, shown as ladder interface 516, and a second interface, shown as actuator interface 518. As shown in FIG. 16, the base section 800 of the aerial ladder assembly 700 defines first interfaces, shown as pivot interfaces 802,

and second interfaces, shown as actuator interfaces **804**. As shown in FIGS. **16** and **17**, the ladder interfaces **516** of the side supports **514** of the turntable **510** and the pivot interfaces **802** of the base section **800** are positioned to align and cooperatively receive a pin, shown as heel pin **520**, to pivotally couple the proximal end **702** of the aerial ladder assembly **700** to the turntable **510**. As shown in FIG. **17**, the aerial ladder assembly **700** includes first ladder actuators (e.g., hydraulic cylinders, etc.), shown as pivot actuators **710**. Each of the pivot actuators **710** has a first end, shown as end **712**, coupled to a respective actuator interface **518** of the side supports **514** of the turntable **510** and an opposing second end, shown as end **714**, coupled to a respective actuator interface **804** of the base section **800**. According to an exemplary embodiment, the pivot actuators **710** are kept in tension such that retraction thereof lifts and rotates the distal end **704** of the aerial ladder assembly **700** about a lateral axis, shown as lateral pivot axis **42**, defined by the heel pin **520**. In other embodiments, the pivot actuators **710** are kept in compression such that extension thereof lifts and rotates the distal end **704** of the aerial ladder assembly **700** about the lateral pivot axis **42**. In an alternative embodiment, the aerial ladder assembly only includes one pivot actuator **710**.

As shown in FIG. **16**, the aerial ladder assembly **700** includes one or more second ladders actuators, shown as extension actuators **720**. According to an exemplary embodiment, the extension actuators **720** are positioned to facilitate selectively reconfiguring the aerial ladder assembly **700** between an extended configuration and a retracted/stowed configuration (see, e.g., FIGS. **1-3**, **16**, etc.). In the extended configuration (e.g., deployed position, use position, etc.), the aerial ladder assembly **700** is lengthened, and the distal end **704** is extended away from the proximal end **702**. In the retracted configuration (e.g., storage position, transport position, etc.), the aerial ladder assembly **700** is shortened, and the distal end **704** is withdrawn towards the proximal end **702**.

According to the exemplary embodiment shown in FIGS. **1-3** and **16**, the aerial ladder assembly **700** has over-retracted ladder sections such that the proximal ends of the lower middle section **900**, the middle section **1000**, the upper middle section **1100**, and the fly section **1200** extend forward of (i) the heel pin **520** and (ii) the proximal end of the base section **800** along the longitudinal axis **14** of the fire apparatus **10** when the aerial ladder assembly **700** is retracted and stowed. According to an exemplary embodiment, the distal end **704** of the aerial ladder assembly **700** (e.g., the distal end of the fly section **1200**, etc.) is extensible to the horizontal reach of at least 88 feet (e.g., 93 feet, etc.) and/or or a vertical reach of at least 95 feet (e.g., 100 feet, etc.). According to an exemplary embodiment, the aerial ladder assembly **700** is operable below grade (e.g., at a negative depression angle relative to a horizontal, etc.) within an aerial work envelope or scrub area. In one embodiment, the aerial ladder assembly **700** is operable in the scrub area such that it may pivot about the vertical pivot axis **40** up to 50 degrees (e.g., 20 degrees forward and 30 degrees rearward from a position perpendicular to the longitudinal axis **14**, etc.) on each side of the body **110** while at a negative depression angle (e.g., up to negative 15 degrees, more than negative 15 degrees, up to negative 20 degrees, etc. below level, below a horizontal defined by the top platform **122** of the body **110**, etc.).

According to an exemplary embodiment, the work basket **1300** is configured to hold at least one of fire fighters and persons being aided by the fire fighters. As shown in FIGS. **3**, **5**, and **10**, the work basket **1300** includes a platform,

shown as basket platform **1310**; a support, shown as railing **1320**, extending around the periphery of the basket platform **1310**; and angled doors, shown as basket doors **1330**, coupled to the corners of the railing **1320** proximate the rear end **4** of the fire apparatus **10**. According to an exemplary embodiment, the basket doors **1330** are angled to correspond with the chamfered corners **120** of the body **110**.

In other embodiments, the aerial assembly **500** does not include the work basket **1300**. In some embodiments, the work basket **1300** is replaced with or additionally includes a nozzle (e.g., a deluge gun, a water cannon, a water turret, etc.) or other tool. By way of example, the nozzle may be connected to a water source (e.g., the water tank **400**, an external source, etc.) with a conduit extending along the aerial ladder assembly **700** (e.g., along the side of the aerial ladder assembly **700**, beneath the aerial ladder assembly **700**, in a channel provided in the aerial ladder assembly **700**, etc.). By pivoting the aerial ladder assembly **700** into a raised position, the nozzle may be elevated to expel water from a higher elevation to facilitate suppressing a fire.

According to an exemplary embodiment, the pump system **200** (e.g., a pump house, etc.) is a mid-ship pump assembly. As shown in FIGS. **1**, **2**, **12**, **17**, and **18**, the pump system **200** is positioned along the rear assembly **100** behind the front cabin **20** and forward of the vertical pivot axis **40** (e.g., forward of the turntable **510**, the torque box **300**, the pedestal **308**, the slewing bearing **310**, the heel pin **520**, a front end of the body **110**, etc.) such that the work platform **550** and the over-retracted portions of the aerial ladder assembly **700** overhang above the pump system **200** when the aerial ladder assembly **700** is retracted and stowed. According to an exemplary embodiment, the position of the pump system **200** forward of the vertical pivot axis **40** facilitates ease of install and serviceability. In other embodiments, the pump system **200** is positioned rearward of the vertical pivot axis **40**.

As shown in FIGS. **17-21**, the pump system **200** includes a housing, shown as pump house **202**. As shown in FIG. **17**, the pump house **202** includes a selectively openable door, shown as pump door **204**. As shown in FIGS. **18-21**, the pump system **200** includes a pumping device, shown as pump assembly **210**, disposed within the pump house **202**. By way of example, the pump assembly **210** may include a pump panel having an inlet for the entrance of water from an external source (e.g., a fire hydrant, etc.), a pump, an outlet configured to engage a hose, various gauges, etc. The pump of the pump assembly **210** may pump fluid (e.g., water, agent, etc.) through a hose to extinguish a fire (e.g., water received at an inlet of the pump house **202**, water stored in the water tank **400**, etc.). As shown in FIGS. **19-21**, the pump system **200** includes a selectively deployable (e.g., foldable, pivotable, collapsible, etc.) platform, shown as pump platform **220**, pivotally coupled to the pump house **202**. As shown in FIGS. **20** and **21**, the pump platform **220** is in a first configuration, shown as stowed configuration **222**, and as shown in FIG. **19**, the pump platform **220** is in a second configuration, shown as deployed configuration **224**.

As shown in FIGS. **1**, **2**, **4**, **6**, **7**, **10-12**, **14**, and **15**, the fire apparatus **10** includes a stability system, shown as stability assembly **1400**. As shown in FIGS. **1**, **2**, **4**, and **7**, the stability assembly **1400** includes first stabilizers, shown as front downriggers **1500**, coupled to each lateral side of the front bumper **22** at the front end **2** of the front cabin **20**. In other embodiments, the front downriggers **1500** are otherwise coupled to the fire apparatus **10** (e.g., to the front end **2** of the frame **12**, etc.). According to an exemplary embodi-

11

ment, the front downriggers **1500** are selectively deployable (e.g., extendable, etc.) downward to engage a ground surface. As shown in FIGS. **1**, **2**, **4-6**, **10-12**, **14**, and **15**, the stability assembly **1400** includes second stabilizers, shown as rear downriggers **1600**, coupled to each lateral side of the rear end **4** of the frame **12** and/or the rear end **306** of the torque box **300**. According to an exemplary embodiment, the rear downriggers **1600** are selectively deployable (e.g., extendable, etc.) downward to engage a ground surface. As shown in FIGS. **1**, **2**, **4**, **6**, **7**, **10**, **12**, **14**, **15**, **17**, and **18**, the stability assembly **1400** includes third stabilizers, shown outriggers **1700**, coupled to the front end **304** of the torque box **300** between the pedestal **308** and the body **302**. As shown in FIGS. **6** and **7**, the outriggers **1700** are selectively deployable (e.g., extendable, etc.) outward from each of the lateral sides of the body **110** and/or downward to engage a ground surface. According to an exemplary embodiment, the outriggers **1700** are extendable up to a distance of eighteen feet (e.g., measured between the center of a pad of a first outrigger and the center of a pad of a second outrigger, etc.). In other embodiments, the outriggers **1700** are extendable up to a distance of less than or greater than eighteen feet.

According to an exemplary embodiment, the front downriggers **1500**, the rear downriggers **1600**, and the outriggers **1700** are positioned to transfer the loading from the aerial ladder assembly **700** to the ground. For example, a load applied to the aerial ladder assembly **700** (e.g., a fire fighter at the distal end **704**, a wind load, etc.) may be conveyed into to the turntable **510**, through the pedestal **308** and the torque box **300**, to the frame **12**, and into the ground through the front downriggers **1500**, the rear downriggers **1600**, and/or the outriggers **1700**. When the front downriggers **1500**, the rear downriggers **1600**, and/or the outriggers **1700** engage with a ground surface, portions of the fire apparatus **10** (e.g., the front end **2**, the rear end **4**, etc.) may be elevated relative to the ground surface. One or more of the wheel and tire assemblies **30** may remain in contact with the ground surface, but may not provide any load bearing support. While the fire apparatus **10** is being driven or not in use, the front downriggers **1500**, the rear downriggers **1600**, and the outriggers **1700** may be retracted into a stored position.

According to an exemplary embodiment, with (i) the front downriggers **1500**, the rear downriggers **1600**, and/or the outriggers **1700** extended and (ii) the aerial ladder assembly **700** fully extended (e.g., at a horizontal reach of 88 feet, at a vertical reach of 95 feet, etc.), the fire apparatus **10** withstands a rated tip load (e.g., rated meaning that the fire apparatus **10** can, from a design-engineering perspective, withstand a greater tip load, with an associated factor of safety of at least two, meets National Fire Protection Association ("NFPA") requirements, etc.) of at least 1,000 pounds applied to the work basket **1300**, in addition to the weight of the work basket **1300** itself (e.g., approximately 700 pounds, etc.). In embodiments where the aerial assembly **500** does not include the work basket **1300**, the fire apparatus **10** may have a rated tip load of more than 1,000 pounds (e.g., 1,250 pounds, etc.) when the aerial ladder assembly **700** is fully extended.

According to an exemplary embodiment, the tandem rear axles **18** have a gross axle weight rating of up to 48,000 pounds and the fire apparatus **10** does not exceed the 48,000 pound tandem-rear axle rating. The front axle **16** may have a 24,000 pound axle rating. Traditionally, mid-mount fire trucks have greater than a 48,000 pound loading on the tandem rear-axes thereof. However, some state regulations prevent vehicles having such a high axle loading, and, therefore, the vehicles are unable to be sold and operated in

12

such states. Advantageously, the fire apparatus **10** of the present disclosure has a gross axle weight loading of at most 48,000 pounds on the tandem rear axles **18**, and, therefore, the fire apparatus **10** may be sold and operated in any state of the United States.

As shown in FIGS. **5** and **9**, the fire apparatus **10** has a height H . According to an exemplary embodiment, the height H of the fire apparatus **10** is at most 128 inches (i.e., 10 feet, 8 inches). In other embodiments, the fire apparatus **10** has a height greater than 128 inches. As shown in FIGS. **8** and **9**, the fire apparatus **10** has a longitudinal length L . According to an exemplary embodiment, the longitudinal length L of the fire apparatus **10** is at most 502 inches (i.e., 41 feet, 10 inches). In other embodiments, the fire apparatus **10** has a length L greater than 502 inches. As shown in FIGS. **8** and **9**, the fire apparatus **10** has a distance D_1 between the rear end **4** of the body **110** and the middle of the tandem rear axles **18** (e.g., a body rear overhang portion, etc.). According to an exemplary embodiment, the distance D_1 of the fire apparatus **10** is at most 160 inches (i.e., 13 feet, 4 inches). In other embodiments, the fire apparatus **10** has a distance D_1 greater than 160 inches. As shown in FIGS. **8** and **9**, the fire apparatus **10** has a distance D_2 between the front end **2** of the front cabin **20** (excluding the front bumper **22**) and the middle of the tandem rear axles **18**. According to an exemplary embodiment, the distance D_2 of the fire apparatus **10** is approximately twice or at least twice that of the distance D_1 (e.g., approximately 321 inches, approximately 323 inches, at least 320 inches, etc.).

As shown in FIG. **8**, the longitudinal length L of the fire apparatus **10** is compared to the longitudinal length L' of a traditional mid-mount fire apparatus **10'**. As shown in FIG. **8**, when the front axles of the fire apparatus **10** and the fire apparatus **10'** are aligned, the fire apparatus **10'** extends beyond the longitudinal length L of the fire apparatus **10** a distance A' . The distance A' may be approximately the same as the amount of the body **110** rearward of the tandem rear axles **18** of the fire apparatus **10** such that the amount of body rearward of the tandem rear axle of the fire apparatus **10'** is approximately double that of the fire apparatus **10**. Decreasing the amount of the body **110** rearward of the tandem rear axles **18** improves drivability and maneuverability, and substantially reduces the amount of damage that fire departments may inflict on public and/or private property throughout a year of operating their fire trucks.

One solution to reducing the overall length of a fire truck is to configure the fire truck as a rear-mount fire truck with the ladder assembly overhanging the front cabin (e.g., in order to provide a ladder assembly with comparable extension capabilities, etc.). As shown in FIG. **9**, the longitudinal length L of the fire apparatus **10** is compared to the longitudinal length L'' of a traditional rear-mount fire apparatus **10''**. As shown in FIG. **9**, when the front axles of the fire apparatus **10** and the fire apparatus **10''** are aligned, the ladder assembly of the fire apparatus **10''** extends beyond the longitudinal length L of the fire apparatus **10** a distance A'' such that the ladder assembly overhangs past the front cabin. Overhanging the ladder assembly reduces driver visibility, as well as rear-mount fire trucks do not provide as much freedom when arriving at a scene on where and how to position the truck, which typically requires the truck to be reversed into position to provide the desired amount of reach (e.g., which wastes valuable time, etc.). Further, the height H'' of the fire apparatus **10''** is required to be higher than the height H of the fire apparatus **10** (e.g., by approximately one foot, etc.) so that the ladder assembly of the fire apparatus **10''** can clear the front cabin thereof.

Aerial Configuration

As shown in FIGS. 1-3, the over-retracted portions of the aerial ladder assembly 700 (e.g., the proximal ends of the lower middle section 900, the middle section 1000, the upper middle section 1100, the fly section 1200, etc.) extend forward of (i.e., past) (i) the lateral pivot axis 42 defined by the heel pin 520 and (ii) the proximal end of the base section 800 (i.e., the portion of the base section 800 that is coupled to the heel pin 520) along the longitudinal axis 14 of the fire apparatus 10 when the aerial ladder assembly 700 is retracted and stowed (e.g., such that at least one of the lower middle section 900, the middle section 1000, the upper middle section 1100, the fly section 1200, etc. spans across the lateral pivot axis 42 when the aerial ladder assembly 700 is retracted and stowed). Such over-retraction disposes the over-retracted portions of the aerial ladder assembly 700 to extend over the pump house 202 adjacent (i.e., rearward of) a rearmost wall of the front cabin 20. In other embodiments, at least a portion of the over-retracted portions of the aerial ladder assembly 700 extend past and forward of the rearmost wall of the front cabin 20 (e.g., in an embodiment where the rearmost cab wall is angled, notched, etc.). As shown in FIGS. 1 and 2, at least a portion of the plurality of nesting ladders sections (e.g., at least a base rail of the base section 800, the lower middle section 900, the middle section 1000, the upper middle section 1100, the fly section 1200, etc.) of the aerial ladder assembly 700 is positioned below the top (i.e., roof) of the front cabin 20 (e.g., when the aerial ladder assembly 700 is not pivoted/raised about the lateral pivot axis 42, etc.).

As shown in FIGS. 22-25, (i) the body 110 of the rear assembly 100 within the aerial assembly recess 140 is shaped, (ii) the pump house 202 adjacent the aerial assembly recess 140 is shaped, (iii) the water tank 400 adjacent the aerial assembly recess 140 is shaped, and/or (iv) the outriggers 1700 extend at negative depression angle γ from the body 110 to facilitate a substantial aerial work envelope of the aerial ladder assembly 700, shown as scrub area 730. Such component configurations facilitate operation of the aerial ladder assembly 700 at a negative depression angle below grade (e.g., below horizontal, etc.) of up to an angle θ . According to an exemplary embodiment, the angle θ is approximately negative fifteen degrees. In other embodiments, the angle θ is greater than fifteen degrees (e.g., eighteen, twenty, etc. degrees) or less than fifteen degrees (e.g., ten, twelve, fourteen, etc. degrees). In some embodiments, the angle θ is at least greater than eight degrees.

As shown in FIG. 22, the body 110 of the rear assembly 100 includes first angled portions, shown as angled body panels 144, extending at a negative, downward angle within the aerial assembly recess 140. The pump house 202 of the pump system 200 includes second angled portions, shown as angled pump house panels 206, extending at a negative, downward angle within the aerial assembly recess 140. As shown in FIGS. 22 and 24, the water tank 400 has a wall, shown as frontmost wall 402, adjacent the aerial assembly recess 140. The frontmost wall 402 includes a pair of third angled portions, shown as angled wall portions 406, extending from a wall portion perpendicular to the longitudinal axis 14, shown as perpendicular wall portion 404, at a rearward angle (e.g., towards the rear end 4 of the fire apparatus 10, etc.). According to an exemplary embodiment, the angle γ of the outriggers 1700 is approximately in the range of negative eight to negative twelve degrees relative to a horizontal axis. In other embodiments, the angle γ is greater than twelve degrees (e.g., fifteen degrees, etc.) or less than eight degrees (e.g., five degrees, zero degrees, etc.).

According to an exemplary embodiment, the angled body panels 144 of the body 110, the angled pump house panels 206 of the pump house 202, the angled wall portions 406 of the water tank 400, and/or the angle γ of the outriggers 1700 facilitate operating the aerial ladder assembly within the scrub area 730 up to the angle θ . As shown in FIGS. 23 and 24, the aerial ladder assembly 700 is operable within the scrub area 730 below grade (e.g., at any angle below zero degrees up to angle θ , etc.) about the vertical pivot axis 40 up to (i) an angle α forward of the aerial ladder assembly 700 being perpendicular to the longitudinal axis 14 and (ii) an angle β rearward of the aerial ladder assembly 700 being perpendicular to the longitudinal axis 14. According to an exemplary embodiment, the angle α is approximately twenty degrees. In other embodiments, the angle α is greater than twenty degrees (e.g., twenty-two, twenty-five, thirty, etc. degrees) or less than twenty degrees (e.g., ten, fifteen, eighteen, etc. degrees). According to an exemplary embodiment, the angle β is approximately thirty degrees. In other embodiments, the angle β is greater than thirty degrees (e.g., thirty-two, thirty-five, etc. degrees) or less than thirty degrees (e.g., fifteen, twenty, twenty-five, etc. degrees). The scrub area 730 may therefore have a total sweep angle (e.g., the aggregate of the angle α and the angle β , etc.) of approximately fifty degrees. In other embodiments, the sweep angle of the scrub area 730 is at least more than fifteen degrees. In still other embodiments, the sweep angle of the scrub area 730 is at least more than thirty degrees.

As shown in FIG. 25, the aerial ladder assembly 700 is oriented to extend perpendicularly from the body 110 of the rear assembly 100 (e.g., the aerial ladder assembly 700 is perpendicular relative to the longitudinal axis 14, etc.) and is positioned below grade at the angle θ (e.g., negative fifteen degrees, etc.). When configured in such a position, the aerial ladder assembly 700 extends from the side of the body 110 a distance D_3 , and the basket platform 1310 of the work basket 1300 is positioned at a height h above a ground surface while none of the plurality of nesting ladder sections (e.g., the lower middle section 900, the middle section 1000, the upper middle section 1100, the fly section 1200, etc.) are extended (e.g., the lower middle section 900, the middle section 1000, the upper middle section 1100, and the fly section 1200 are over-retracted relative to the base section 800 and the heel pin 520, etc.). According to an exemplary embodiment, being able to operate at the angle θ and the over-retracting configuration of the plurality of nesting ladder sections of the aerial ladder assembly 700 facilitate accessing the work basket 1300 from the ground surface without requiring the extension of the aerial ladder assembly 700. The height h of the basket platform 1310 is at most 20.3 inches, according to an exemplary embodiment (e.g., meeting the maximum step height limit as set by NFPA regulations, without requiring extension of the aerial ladder assembly 700, etc.). In some embodiments, the height h is less than 20.3 inches (e.g., in embodiments where the stability assembly 1400 of the fire apparatus 10 has a leaning capability, etc.). According to an exemplary embodiment, the distance D_3 is approximately 19.5 feet. In other embodiments, the distance D_3 is greater than 19.5 feet (e.g., 20 feet, 22 feet, in embodiments with a longer aerial ladder assembly 700, etc.) or less than 19.5 feet (e.g., 19 feet, 18.5 feet, etc.).

As shown in FIG. 26, the aerial ladder assembly 700 is pivotable about the lateral pivot axis 42 to reposition the aerial ladder assembly 700 at a plurality of different positions including a horizontal position, shown as horizontal set-back configuration 740, a below grade position, shown as blitz configuration 742, and a plurality of above grade

positions, shown as raised configurations **744**. As shown in FIG. **26**, when the aerial ladder assembly **700** is arranged in the horizontal set-back configuration **740** and the longitudinal axis **14** of the fire apparatus **10** is positioned parallel or substantially parallel with a fire scene (e.g., a house, a building, an apartment, etc.), the aerial ladder assembly **700** extends from the side of the body **110** a set-back distance D_4 . According to an exemplary embodiment, the set-back distance D_4 is approximately twenty feet. In other embodiments, the set-back distance D_4 is greater than twenty feet (e.g., twenty-seven feet, in an embodiment where the aerial ladder assembly **700** includes a side-mounted e-trac versus a rung-mounted e-trac, etc.) or less than twenty feet (e.g., in embodiments where the fire apparatus **10** includes a shorter aerial ladder assembly **700**, in embodiments where the aerial ladder assembly **700** does not include the work basket **1300**, etc.; fifteen, sixteen, seventeen, eighteen, nineteen, etc. feet).

As shown in FIG. **26**, when the aerial ladder assembly **700** is arranged in the blitz configuration **742**, the aerial ladder assembly **700** is oriented at a negative depression angle (e.g., up to the angle θ , etc.) such that the work basket **1300** is positioned substantially close to the ground surface and adjacent the fire scene (e.g., the first level of a building, a store front, etc.). In the blitz configuration **742**, the work basket **1300** may be extended from the rear assembly **100** by pivoting the aerial ladder assembly **700** about the vertical pivot axis **40** toward the fire scene and then pivoting aerial ladder assembly **700** about the lateral pivot axis **42** such that the work basket **1300** clears any obstacles **750** (e.g., cars, etc.) positioned in front of the fire scene. A turret, shown as water turret **1340**, that is coupled to the work basket **1300** may be manipulated (e.g., using a user input device of the fire apparatus **10**, the control console **600**, etc.) to expel water or another fire surprising agent from the water tank **400** or other source (e.g., a fire hydrant, an agent tank, etc.) into the first level of the fire scene upward at the ceiling thereof to expel a fire therein (e.g., to prevent a fire from spreading to the upper levels of the building, etc.). In other embodiments, the water turret **1340** is otherwise positioned (e.g., coupled to the distal end of the fly section **1200**, in embodiments where the aerial ladder assembly **700** does not include the work basket **1300**, etc.).

As shown in FIG. **26**, when the aerial ladder assembly **700** is arranged in the raised configurations **744**, the aerial ladder assembly **700** is oriented at a positive angle such that the work basket **1300** is positioned above the fire apparatus **10**. To extend further in the vertical direction, the plurality of nesting sections of the aerial ladder assembly **700** may begin to be extended. In order to un-bed the aerial ladder assembly **700** (e.g., pivot the aerial ladder assembly **700** upward, etc.), the over-retracted portions of the aerial ladder assembly **700** may need to be extended past the heel pin **520**. Such may require that the fire apparatus **10** be set back a distance slightly further than the set-back distance D_4 (e.g., twenty-four feet, etc.).

According to the exemplary embodiment shown in FIG. **27**, a control system, shown as fire apparatus control system **2000**, for the fire apparatus **10** includes a controller **2010**. In one embodiment, the controller **2010** is configured to selectively engage, selectively disengage, control, and/or otherwise communicate with components of the fire apparatus **10**. As shown in FIG. **27**, the controller **2010** is coupled to the rotation actuator **320**, the pivot actuator(s) **710**, the extension actuator(s) **720**, the water turret **1340**, basket actuator(s) **1350** positioned to manipulate the work basket **1300** (e.g., a rotation actuator, a pivot actuator, a lift actuator, an extension actuator, etc.) relative to the distal end of the fly section

1200 of the aerial ladder assembly **700**, and a user input/output (“I/O”) device **2020**. In other embodiments, the controller **2010** is coupled to more or fewer components (e.g., the stability assembly **1400**, etc.). By way of example, the controller **2010** may send and/or receive signals with the rotation actuator **320**, the pivot actuator(s) **710**, the extension actuator(s) **720**, the water turret **1340**, the basket actuator(s) **1350**, and/or the user I/O device **2020**.

The controller **2010** may be implemented as a general-purpose processor, an application specific integrated circuit (ASIC), one or more field programmable gate arrays (FPGAs), a digital-signal-processor (DSP), circuits containing one or more processing components, circuitry for supporting a microprocessor, a group of processing components, or other suitable electronic processing components. According to the exemplary embodiment shown in FIG. **27**, the controller **2010** includes a processing circuit **2012** and a memory **2014**. The processing circuit **2012** may include an ASIC, one or more FPGAs, a DSP, circuits containing one or more processing components, circuitry for supporting a microprocessor, a group of processing components, or other suitable electronic processing components. In some embodiments, the processing circuit **2012** is configured to execute computer code stored in the memory **2014** to facilitate the activities described herein. The memory **2014** may be any volatile or non-volatile computer-readable storage medium capable of storing data or computer code relating to the activities described herein. According to an exemplary embodiment, the memory **2014** includes computer code modules (e.g., executable code, object code, source code, script code, machine code, etc.) configured for execution by the processing circuit **2012**. In some embodiments, controller **2010** represents a collection of processing devices (e.g., servers, data centers, etc.). In such cases, the processing circuit **2012** represents the collective processors of the devices, and the memory **2014** represents the collective storage devices of the devices.

In one embodiment, the user I/O device **2020** includes a display and an operator input. The display may be configured to display a graphical user interface, an image, an icon, and/or still other information. In one embodiment, the display includes a graphical user interface configured to provide general information about the fire apparatus **10** (e.g., vehicle speed, fuel level, warning lights, battery level, etc.). The graphical user interface may also be configured to display a current position of the aerial ladder assembly **700**, a current position of the work basket **1300**, a current position of the turntable **510**, an orientation of the fire apparatus **10** (e.g., an angle relative to a ground surface, etc.), and/or still other information relating to the fire apparatus **10** and/or the aerial assembly **500**. The user I/O device **2020** may be or include the control console **600**, a user interface within the front cabin **20**, a user interface in the work basket **1300**, a user interface on the side of the body **110**, and/or a portable device wirelessly connected to the controller **2010** (e.g., a mobile device, a smartphone, a tablet, etc.).

The operator input may be used by an operator to provide commands to at least one of the rotation actuator **320**, the pivot actuator(s) **710**, the extension actuator(s) **720**, the water turret **1340**, and the basket actuator(s) **1350**. The operator input may include one or more buttons, knobs, touchscreens, switches, levers, joysticks, pedals, a steering wheel, or handles. The operator input may facilitate manual control of some or all aspects of the operation of the fire apparatus **10**. It should be understood that any type of display or input controls may be implemented with the systems and methods described herein.

According to an exemplary embodiment, the controller 2010 is configured to prevent or limit activation of the pivot actuators 710 while the proximal ends of the plurality of nesting ladder sections of the aerial ladder assembly 700 are over-retracted beyond the heel pin 520. By way of example, 5 the controller 2010 may be configured to automatically extend the plurality of nesting ladder sections forward until the proximal ends of each extends along the base section 800 beyond the heel pin 520 (e.g., in response to a lift command while the ladder sections are over-retracted), and then begin 10 pivoting the aerial ladder assembly about the lateral pivot axis 42 and/or continue extending the plurality of nesting ladder sections (e.g., if an extension command is being provided by an operator using the user I/O device 2020, to prevent the over-retracted portions from pivoting into the work platform 550, etc.).

Stability Assembly

According to an exemplary embodiment, the front downriggers 1500, the rear downriggers 1600, and the outriggers 1700 of the stability assembly 1400 are configured to assist 20 in providing the horizontal and vertical reach capabilities of the aerial ladder assembly 700 and facilitate leveling the fire apparatus 10 when on uneven ground.

As shown in FIGS. 28-31, the front downriggers 1500 include a first downrigger, shown as first front downrigger 25 1510, and a second downrigger, shown second front downrigger 1520. In an alternative embodiment, the front downriggers 1500 are replaced with a single front stability foot or the fire apparatus 10 does not include the front downriggers 1500. As shown in FIGS. 28-31, each of the first front downrigger 1510 and the second front downrigger 1520 includes a first actuator assembly, shown as front actuator assembly 1530. According to an exemplary embodiment, the front actuator assemblies 1530 are or include hydraulic actuators. In other embodiments, the front actuator assemblies 1530 are or include pneumatic actuators, electric actuators, and/or mechanically-driven actuators. As shown in FIGS. 28,29, and 31, each of the front actuator assemblies 1530 includes a front extension actuator having a first portion, shown as cylinder housing 1532, and a second 40 portion, shown as rod 1534, with a plate, shown as foot plate 1536, coupled to an end of the rod 1534. According to an exemplary embodiment, the rods 1534 are selectively extendable from the cylinder housings 1532 such that the foot plates 1536 and/or ground pads coupled thereto engage 45 a ground surface.

As shown in FIGS. 28-32, the front bumper 22 has a first lateral end, shown as left end 24, and an opposing second lateral end, shown as right end 26. As shown in FIGS. 28,29, and 31, the front bumper 22 include a coupler, shown as 50 bracket 28, coupled to each of the left end 24 and the right end 26 of the front bumper 22. A first bracket 28 couples the first front downrigger 1510 to the left end 24 of the front bumper 22 and a second bracket 28 couples the second front downrigger 1520 to the right end 26 of the front bumper 22. 55

As shown in FIGS. 32-34, the front downriggers 1500 are pivotally coupled to the frame 12 of the fire apparatus 10. Specifically, the first front downrigger 1510 is pivotally coupled to a first frame rail 13 of the frame 12 and the second front downrigger is pivotally coupled to a second 60 frame rail 15 of the frame 12. As shown in FIGS. 32-34, the first frame rail 13 has a plate, shown as coupling plate 32, coupled to the front end 2 thereof. A housing, shown as bracket housing 34, is coupled to the coupling plate 32. A bracket, shown as pivotal bracket 36, is received by and pivotally coupled to the bracket housing 34. The pivotal bracket 36 is coupled to the front actuator assembly 1530 of

the first front downrigger 1510 such that the first front downrigger 1510 is selectively pivotable therewith between an extension orientation (see, e.g., FIG. 32) and a pivoted orientation (see, e.g., FIGS. 33 and 34). An actuator, shown 5 as pivoting actuator 1540, is positioned to facilitate selectively actuating the first front downrigger 1510 between the extension orientation and the pivoted orientation (e.g., automatically, etc.). In other embodiments, the first front downrigger 1510 is manually pivotable between the extension 10 orientation and the pivoted orientation. According to an exemplary embodiment, the second front downrigger 1520 is similarly coupled to and pivotable relative to the second frame rail 15.

As shown in FIG. 34, the front cabin 20 is pivotable about 15 the front end 2 of the frame 12 when the front downriggers 1500 are pivoted into the pivoted orientation. According to an exemplary embodiment, the first front downrigger 1510 and the second front downrigger 1520 are configured to automatically pivot into the pivoted orientation when the 20 front cabin 20 is pivoted upward about the front end 2 of the frame 12 (e.g., such that the front downriggers 1500 do not impede the lifting of the front cabin 20, etc.). By way of example, the pivoting actuators 1540 positioned to pivot the front downriggers 1500 and an actuator that is positioned to pivot the front cabin 20 may be linked (e.g., hydraulically 25 coupled, fluidly coupled, etc.) such that activation of one activates the other or both are driven by a common source. By way of another example, the controller 2010 may be configured to prevent or limit pivoting of the front cabin 20 until the pivoting actuators 1540 have been engaged to pivot 30 the front downriggers 1500 into the pivoted orientation.

According to an exemplary embodiment, the pivoting capability of the front downriggers 1500 facilitates raising the front downriggers 1500 higher up the front the front 35 cabin 20 relative to a ground surface (e.g., compared to the arrangement in FIGS. 28-31 coupled to the front bumper 22, etc.), effectively increasing the ground clearance of the fire apparatus 10 and thereby the angle of inclines that the fire apparatus 10 may traverse (e.g., increasing drivability, maneuverability, etc. of the fire apparatus 10). 40

As shown in FIGS. 35-37, the rear downriggers 1600 include a third downrigger, shown as first rear downrigger 1610, and a fourth downrigger, shown second rear downrigger 1620. In an alternative embodiment, the rear downriggers 1600 are replaced with a single rear stability foot. As shown in FIGS. 35-37, each of the first rear downrigger 1610 and the second rear downrigger 1620 includes a second 45 actuator assembly, shown as rear actuator assembly 1630. Each of the rear actuator assemblies 1630 includes a housing, shown as rear actuator receiver 1632, defining an internal cavity that receives an actuator, shown as rear extension actuator 1634. According to an exemplary embodiment, the rear extension actuators 1634 are or include hydraulic actuators. In other embodiments, the rear extension actuators 1634 are or include pneumatic actuators, electric actuators, and/or mechanically-driven actuators. As shown in FIGS. 35 and 36, each of the rear actuator assemblies 1630 includes a foot, shown as rear foot 1636, 50 coupled to an end of the rear extension actuator 1634 and a pad, shown as rear ground pad 1638, coupled to the rear foot 1636. According to an exemplary embodiment, the rear extension actuators 1634 are selectively extendable from the rear actuator receivers 1632 such that the rear ground pads 1638 engage a ground surface.

As shown in FIGS. 35-37, each of the rear actuator assemblies 1630 includes a bracket, shown as rear bracket 1640, extending laterally from each of the rear actuator 65

receivers 1632. The rear brackets 1640 are configured to couple the first rear downrigger 1610 and the second rear downrigger 1620, respectively, to opposing lateral sides of a support, shown as rear downrigger support 1602, coupled the rear end 4 of the frame 12, beneath the body 302 of the torque box 300, and forward of the rear end 306 of the torque box 300. The rear downrigger support 1602 is therefore configured to secure the rear downriggers 1600 to the frame 12, rearward of the rear axles 18.

As shown in FIGS. 7 and 38-42, the outrigger assembly of the outriggers 1700 includes a housing, shown as outrigger housing 1702; a pair of first actuator assemblies, shown as lateral actuator assemblies 1740, having components thereof slidably coupled within and selectively laterally extendable from the outrigger housing 1702 and the body 110; and a pair of second actuator assemblies, shown as vertical actuator assemblies 1750, coupled to distal ends of lateral actuator assemblies 1740. As shown in FIGS. 38 and 39, the outrigger housing 1702 is coupled the frame 12, rearward of the vertical pivot axis 40 defined by the pedestal 308 (e.g., not forward of the turntable 510, etc.). As shown in FIG. 39, at least a portion of the outrigger housing 1702 (e.g., a front tube thereof, etc.) extends at least partially through the pedestal 308 (e.g., a rear portion thereof, etc.).

As shown in FIGS. 38-42, the outrigger housing 1702 includes a first tube, shown as first track 1710, and a second tube, shown as second track 1720. According to the exemplary embodiment shown in FIGS. 38-42, the first track 1710 is positioned longitudinally forward of the second track 1720. In other embodiments, the first track 1710 is positioned longitudinally rearward of the second track 1720. As shown in FIG. 41, the first track 1710 has a first end, shown as left end 1712, and an opposing second end, shown as right end 1714. The first track 1710 defines a first internal cavity, shown as first internal slot 1716, and a first lateral axis, shown as first lateral extension axis 1718. The second track 1720 has a first end, shown as right end 1722, and an opposing second end, shown as left end 1724. The second track 1720 defines a second internal cavity, shown as second internal slot 1726, and a second lateral axis, shown as second lateral extension axis 1728.

According to an exemplary embodiment, the first track 1710 and the second track 1720 extend laterally across the body 110 of the fire apparatus 10. As shown in FIGS. 40-42, the left end 1712 of the first track 1710 is elevated relative the right end 1714 of the first track 1710 such that the first lateral extension axis 1718 of the first track 1710 is oriented with a negative slope (e.g., when viewed from the rear, etc.) having the angle γ (e.g., five to fifteen degrees below a horizontal, eight to twelve degree below a horizontal, etc.). The right end 1722 of the second track 1720 is elevated relative the left end 1724 of the second track 1720 such that the second lateral extension axis 1728 of the second track 1720 is oriented with a positive slope (e.g., when viewed from the rear, etc.) having the angle γ .

As shown in FIGS. 40-42, the outrigger housing 1702 includes a first connector, shown as first collar 1730, and a second connector, shown as second collar 1732. The first collar 1730 is positioned to secure the left end 1724 of the second track 1720 to the left end 1712 of the first track 1710 that is elevated relative to the second track 1720 (i.e., because of the opposite slopes thereof). The second collar 1732 is positioned to secure the right end 1714 of the first track 1710 to the right end 1722 of the second track 1720 that is elevated relative to the first track 1710 (i.e., because of the opposite slopes thereof). As shown in FIG. 42, the first collar 1730 and the second collar 1732 have a z-shaped

structure with a first vertical leg, shown as upper leg 1734; a horizontal leg, shown as connector 1736, extending horizontally from a lower end of the upper leg 1734; and a second vertical leg, shown as lower leg 1738, extending vertically downward from an end of the connector 1736 opposite the upper leg 1734. The upper leg 1734 of the first collar 1730 is configured to be secured (e.g., fastened, welded, etc.) to a sidewall of the first track 1710, the connector 1736 of the first collar 1730 is configured to be secured to a top surface of the second track 1720, and the lower leg 1738 of the first collar 1730 is configured to be secured to a sidewall of the second track 1720. The upper leg 1734 of the second collar 1732 is configured to be secured to a sidewall of the second track 1720, the connector 1736 of the second collar 1732 is configured to be secured to a top surface of the first track 1710, and the lower leg 1738 of the second collar 1732 is configured to be secured to a sidewall of the first track 1710.

As shown in FIGS. 7 and 38-40, each of the lateral actuator assemblies 1740 includes an arm, shown as telescoping arm 1742, and an actuator, shown as lateral extension actuator 1744. One of the telescoping arms 1742 is slidably received within the first internal slot 1716 of the first track 1710 and the other of the telescoping arms 1742 is slidably received within the second internal slot 1726 of the second track 1720. The lateral extension actuators 1744 are positioned to facilitate selectively extending the telescoping arms 1742 from the first track 1710 and the second track 1720 along the first lateral extension axis 1718 and the second lateral extension axis 1728, respectively, at the angle γ . According to an exemplary embodiment, the lateral extension actuators 1744 are or include hydraulic actuators. In other embodiments, the lateral extension actuators 1744 are or include pneumatic actuators, electric actuators, and/or mechanically-driven actuators. According to an exemplary embodiment, the angle γ at which the telescoping arms 1742 extend from the first track 1710 and the second track 1720 facilitates pivoting the aerial ladder assembly 700 continuously to a side of the fire apparatus 10 at the maximum depression angle θ without requiring the aerial ladder assembly 700 to be lifted over the telescoping arms 1742 as the aerial ladder assembly 700 passes thereover.

As shown in FIGS. 7 and 38-40, each of the vertical actuator assemblies 1750 includes a housing, shown as vertical actuator receiver 1752, coupled to a distal end of one of the telescoping arms 1742 and defines an internal cavity that receives an actuator, shown as vertical extension actuator 1754. According to an exemplary embodiment, the vertical extension actuators 1754 are or include hydraulic actuators. In other embodiments, the vertical extension actuators 1754 are or include pneumatic actuators, electric actuators, and/or mechanically-driven actuators. As shown in FIGS. 38-40, each of the vertical actuator assemblies 1750 includes a foot, shown as outrigger foot 1756, coupled to an end of each of the vertical extension actuators 1754. According to an exemplary embodiment, the vertical extension actuators 1754 are selectively extendable from the vertical actuator receivers 1752 such that the outrigger feet 1756 and/or ground pads coupled thereto engage a ground surface.

According to an exemplary embodiment, each of the front actuator assemblies 1530 (i.e., the front extension actuators thereof), each of the rear extension actuators 1634, each of the lateral extension actuators 1744, and/or each of the vertical extension actuators 1754 are independently controllable (e.g., by the controller 2010, etc.) to level the fire apparatus 10 (e.g., during use of the aerial ladder assembly

700, etc.). The front actuator assemblies 1530, the rear extension actuators 1634, the lateral extension actuators 1744, and/or the vertical extension actuators 1754 may be actively controllable (e.g., by the controller 2010, etc.) as the aerial ladder assembly 700 is pivoted about the vertical pivot axis 40, as the aerial ladder assembly 700 is pivoted about the lateral pivot axis 42, and/or as the plurality of nesting ladder sections of the aerial ladder assembly 700 are extended or retracted to maintain stability of the fire apparatus 10. If a scenario were to arise where the aerial ladder assembly 700 is moved into a position that approaches a limit of the aerial ladder assembly 700 and/or the fire apparatus 10, the controller 2010 may (i) prevent or limit further extension and/or pivoting of the aerial ladder assembly 700, (ii) retract the plurality of nesting ladder sections, and/or (iii) dynamically adjust the front downriggers 1500, the rear downriggers 1600, and/or the outriggers 1700 to increase the current capability of the aerial ladder assembly 700 and/or the fire apparatus 10.

As utilized herein, the terms “approximately,” “about,” “substantially,” and similar terms are intended to have a broad meaning in harmony with the common and accepted usage by those of ordinary skill in the art to which the subject matter of this disclosure pertains. It should be understood by those of skill in the art who review this disclosure that these terms are intended to allow a description of certain features described and claimed without restricting the scope of these features to the precise numerical ranges provided. Accordingly, these terms should be interpreted as indicating that insubstantial or inconsequential modifications or alterations of the subject matter described and claimed are considered to be within the scope of the disclosure as recited in the appended claims.

It should be noted that the term “exemplary” and variations thereof, as used herein to describe various embodiments, are intended to indicate that such embodiments are possible examples, representations, or illustrations of possible embodiments (and such terms are not intended to connote that such embodiments are necessarily extraordinary or superlative examples).

The term “coupled” and variations thereof, as used herein, means the joining of two members directly or indirectly to one another. Such joining may be stationary (e.g., permanent or fixed) or moveable (e.g., removable or releasable). Such joining may be achieved with the two members coupled directly to each other, with the two members coupled to each other using a separate intervening member and any additional intermediate members coupled with one another, or with the two members coupled to each other using an intervening member that is integrally formed as a single unitary body with one of the two members. If “coupled” or variations thereof are modified by an additional term (e.g., directly coupled), the generic definition of “coupled” provided above is modified by the plain language meaning of the additional term (e.g., “directly coupled” means the joining of two members without any separate intervening member), resulting in a narrower definition than the generic definition of “coupled” provided above. Such coupling may be mechanical, electrical, or fluidic.

The term “or,” as used herein, is used in its inclusive sense (and not in its exclusive sense) so that when used to connect a list of elements, the term “or” means one, some, or all of the elements in the list. Conjunctive language such as the phrase “at least one of X, Y, and Z,” unless specifically stated otherwise, is understood to convey that an element may be either X; Y; Z; X and Y; X and Z; Y and Z; or X, Y, and Z (i.e., any combination of X, Y, and Z). Thus, such conjunc-

tive language is not generally intended to imply that certain embodiments require at least one of X, at least one of Y, and at least one of Z to each be present, unless otherwise indicated.

References herein to the positions of elements (e.g., “top,” “bottom,” “above,” “below”) are merely used to describe the orientation of various elements in the FIGURES. It should be noted that the orientation of various elements may differ according to other exemplary embodiments, and that such variations are intended to be encompassed by the present disclosure.

The hardware and data processing components used to implement the various processes, operations, illustrative logics, logical blocks, modules and circuits described in connection with the embodiments disclosed herein may be implemented or performed with a general purpose single- or multi-chip processor, a digital signal processor (DSP), an application specific integrated circuit (ASIC), a field programmable gate array (FPGA), or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general purpose processor may be a microprocessor, or, any conventional processor, controller, microcontroller, or state machine. A processor also may be implemented as a combination of computing devices, such as a combination of a DSP and a microprocessor, a plurality of microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration. In some embodiments, particular processes and methods may be performed by circuitry that is specific to a given function. The memory (e.g., memory, memory unit, storage device) may include one or more devices (e.g., RAM, ROM, Flash memory, hard disk storage) for storing data and/or computer code for completing or facilitating the various processes, layers and modules described in the present disclosure. The memory may be or include volatile memory or non-volatile memory, and may include database components, object code components, script components, or any other type of information structure for supporting the various activities and information structures described in the present disclosure. According to an exemplary embodiment, the memory is communicably connected to the processor via a processing circuit and includes computer code for executing (e.g., by the processing circuit or the processor) the one or more processes described herein.

The present disclosure contemplates methods, systems and program products on any machine-readable media for accomplishing various operations. The embodiments of the present disclosure may be implemented using existing computer processors, or by a special purpose computer processor for an appropriate system, incorporated for this or another purpose, or by a hardwired system. Embodiments within the scope of the present disclosure include program products comprising machine-readable media for carrying or having machine-executable instructions or data structures stored thereon. Such machine-readable media can be any available media that can be accessed by a general purpose or special purpose computer or other machine with a processor. By way of example, such machine-readable media can comprise RAM, ROM, EPROM, EEPROM, or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to carry or store desired program code in the form of machine-executable instructions or data structures and which can be accessed by a general purpose or special purpose computer or other machine with a processor. Combinations of the

23

above are also included within the scope of machine-readable media. Machine-executable instructions include, for example, instructions and data which cause a general purpose computer, special purpose computer, or special purpose processing machines to perform a certain function or group of functions. 5

Although the figures and description may illustrate a specific order of method steps, the order of such steps may differ from what is depicted and described, unless specified differently above. Also, two or more steps may be performed concurrently or with partial concurrence, unless specified differently above. Such variation may depend, for example, on the software and hardware systems chosen and on designer choice. All such variations are within the scope of the disclosure. Likewise, software implementations of the described methods could be accomplished with standard programming techniques with rule-based logic and other logic to accomplish the various connection steps, processing steps, comparison steps, and decision steps. 10

It is important to note that the construction and arrangement of the fire apparatus **10** and the systems and components thereof as shown in the various exemplary embodiments is illustrative only. Additionally, any element disclosed in one embodiment may be incorporated or utilized with any other embodiment disclosed herein. Although only one example of an element from one embodiment that can be incorporated or utilized in another embodiment has been described above, it should be appreciated that other elements of the various embodiments may be incorporated or utilized with any of the other embodiments disclosed herein. 20

The invention claimed is:

1. A vehicle comprising:

a chassis;

a front axle coupled to a front end of the chassis;

a rear axle coupled to a rear end of the chassis; and

a stability system including:

a pair of front downriggers coupled to the front end of the chassis forward of the front axle, the pair of front downriggers selectively extendable to engage a ground surface; and 40

an outrigger assembly coupled to the chassis between the front axle and the rear axle, the outrigger assembly including a pair of outriggers, wherein each outrigger of the pair of outriggers includes an arm and a support foot, wherein the arm is selectively extendable laterally outward at a first angle relative to a horizontal, and wherein at least one of (i) the first angle is a fixed angle or (ii) the foot is extendable at a second angle relative to the arm that is different than the first angle. 50

2. The vehicle of claim **1**, wherein the outrigger assembly includes an outrigger housing having a first tube and a second tube, wherein the first tube and the second tube extend laterally across the chassis, and wherein the first tube is oriented at the fixed angle with a positive slope and the second tube is oriented at the fixed angle with a negative slope. 55

3. The vehicle of claim **2**, wherein the fixed angle is within a range of five to fifteen degrees below the horizontal. 60

4. The vehicle of claim **2**, wherein the pair of outriggers include:

a first outrigger having (i) a first arm slidably received within and selectively extendable from the first tube and (ii) a first support foot coupled to and vertically extendable from a first distal end of the first arm to engage the ground surface; and 65

24

a second outrigger having (i) a second arm slidably received within and selectively extendable from the second tube and (ii) a second support foot coupled to and vertically extendable from a second distal end of the second arm to engage the ground surface.

5. The vehicle of claim **1**, further comprising a front bumper coupled to the front end of the chassis, the front bumper having a first lateral end and an opposing second lateral end, wherein a first downrigger of the pair of front downriggers is coupled to the first lateral end of the front bumper and a second downrigger of the pair of front downriggers is coupled to the opposing second lateral end of the front bumper.

6. The vehicle of claim **1**, wherein the pair of front downriggers is pivotally coupled to the front end of the chassis. 15

7. The vehicle of claim **1**, wherein the pair of front downriggers include:

a first front downrigger coupled proximate a first lateral side of the front end of the chassis; and

a second front downrigger coupled proximate an opposing second lateral side of the front end of the chassis;

wherein the first front downrigger and the second front downrigger are selectively extendable to engage the ground surface. 25

8. The vehicle of claim **7**, further comprising a front bumper coupled to the front end of the chassis, wherein the first front downrigger is directly coupled to a first lateral end of the front bumper and the second front downrigger is directly coupled to an opposing second lateral end of the front bumper. 30

9. The vehicle of claim **7**, wherein the first front downrigger and the second front downrigger are selectively pivotable between a first position and a second position.

10. The vehicle of claim **9**, further comprising:

a first bracket coupled to the first front downrigger, wherein the first bracket pivotally couples the first front downrigger to a first frame rail of the chassis; and

a second bracket coupled to the second front downrigger, wherein the second bracket pivotally couples the second front downrigger to a second frame rail of the chassis. 35

11. The vehicle of claim **9**, further comprising a front cabin pivotally coupled to the front end of the chassis, wherein the first front downrigger and the second front downrigger are configured to automatically pivot from the first position to the second position when the front cabin of the vehicle is pivoted relative to the front end of the chassis.

12. The vehicle of claim **9**, further comprising:

a first pivot actuator positioned to facilitate pivoting the first front downrigger between the first position and the second position; and

a second pivot actuator positioned to facilitate pivoting the second front downrigger between the first position and the second position. 40

13. The vehicle of claim **7**, wherein the outrigger assembly includes an outrigger housing having a first tube and a second tube that extend laterally across the chassis at the fixed angle, and wherein the pair of outriggers includes:

a first outrigger having (i) a first arm slidably received within and selectively extendable from the first tube and (ii) a first support foot coupled to and vertically extendable from a first distal end of the first arm to engage the ground surface; and

a second outrigger having (i) a second arm slidably received within and selectively extendable from the second tube and (ii) a second support foot coupled to 65

25

and vertically extendable from a second distal end of the second arm to engage the ground surface.

14. The vehicle of claim 13, at least one of (i) further comprising a collar positioned to couple proximate ends of the first tube and the second tube together, or (ii) wherein the first tube is oriented at the fixed angle with a positive slope and the second tube is oriented at the fixed angle with a negative slope.

15. The vehicle of claim 1, wherein the stability system includes a pair of rear downriggers coupled to the rear end of the chassis rearward of the rear axle, the pair of rear downriggers selectively extendable to engage the ground surface.

16. A vehicle comprising:

a chassis;

a front axle coupled to a front end of the chassis;

a rear axle coupled to a rear end of the chassis; and

a stability system including an outrigger assembly coupled to the chassis between the front axle and the rear axle, the outrigger assembly including:

a pair of outriggers, wherein each outrigger of the pair of outriggers includes an arm and a support foot, wherein the arm is selectively extendable laterally outward at a first angle relative to a horizontal, and wherein at least one of (i) the first angle is a fixed angle or (ii) the foot is extendable at a second angle relative to the arm that is different than the first angle;

an outrigger housing having a first tube and a second tube, wherein the first tube and the second tube extend laterally across the chassis, and wherein the first tube is oriented at the fixed angle with a positive slope and the second tube is oriented at the fixed angle with a negative slope; and

a collar positioned to couple proximate ends of the first tube and the second tube together.

17. A vehicle comprising:

a chassis;

a front axle coupled to a front end of the chassis;

a rear axle coupled to a rear end of the chassis; and

a stability system including an outrigger assembly coupled to the chassis between the front axle and the rear axle, the outrigger assembly including:

26

a pair of outriggers, wherein each outrigger of the pair of outriggers includes an arm and a support foot, wherein the arm is selectively extendable laterally outward at a first angle relative to a horizontal, and wherein at least one of (i) the first angle is a fixed angle or (ii) the foot is extendable at a second angle relative to the arm that is different than the first angle;

a first housing tube having a first end and an opposing second end, the first housing tube extending laterally across the chassis along a positive slope;

a second housing tube having a third end and an opposing fourth end, the second housing tube extending laterally across the chassis along a negative slope such that (i) the first end of the first housing tube and the third end of the second housing tube and (ii) the opposing second end of the first housing tube and the opposing fourth end of the second housing tube are vertically offset; and

one or more collars positioned to couple at least one of (i) the first end of the first housing tube and the third end of the second housing tube or (ii) the opposing second end of the first housing tube and the opposing fourth end of the second housing tube together.

18. The vehicle of claim 17, wherein the pair of outriggers includes:

a first outrigger having (i) a first arm slidably received within and selectively extendable from the first housing tube and (ii) a first support foot coupled to and vertically extendable from a first distal end of the first arm to engage the ground surface; and

a second outrigger having (i) a second arm slidably received within and selectively extendable from the second housing tube and (ii) a second support foot coupled to and vertically extendable from a second distal end of the second arm to engage the ground surface.

19. The vehicle of claim 17, wherein the one or more collars have a z-shaped structure.

* * * * *