



US011051519B2

(12) **United States Patent**
Speck et al.

(10) **Patent No.:** **US 11,051,519 B2**
(45) **Date of Patent:** **Jul. 6, 2021**

(54) **ENDLESS CONVEYOR BELT FOR A CONVEYOR BAKING OVEN AND BELT LINK FOR SAID ENDLESS CONVEYOR BELT**

B65G 17/12; B65G 23/14; B65G 15/42;
B65G 23/02; B65G 67/08; B65G 17/064;
A21B 1/48; A21B 1/24; B65B 35/14;
B65B 35/24; A22C 11/008; F27B 9/24;
F27B 9/00; F28F 9/0243; F28F 9/002;
F28F 9/0224; F28F 9/0246

(71) Applicant: **Werner & Pfleiderer Industrielle Backtechnik GmbH**, Tamm (DE)

See application file for complete search history.

(72) Inventors: **Ulrich Speck**, Ludwigsburg (DE); **Josef Tschida**, Freiberg (DE)

(56) **References Cited**

(73) Assignee: **Werner & Pfleiderer Industrielle Backtechnik GmbH**, Tamm (DE)

U.S. PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 100 days.

2,149,537 A * 3/1939 Morton A21B 5/02
99/443 R
3,478,705 A * 11/1969 Lanham, Jr. A21C 13/02
99/353

(Continued)

(21) Appl. No.: **16/432,121**

FOREIGN PATENT DOCUMENTS

(22) Filed: **Jun. 5, 2019**

DE 2403488 A1 8/1974
DE 69112035 1/1996

(Continued)

(65) **Prior Publication Data**

US 2019/0373900 A1 Dec. 12, 2019

Primary Examiner — Gregory A Wilson

(74) *Attorney, Agent, or Firm* — Smartpat PLC

(30) **Foreign Application Priority Data**

Jun. 6, 2018 (DE) 10 2018 208 960.4

(57) **ABSTRACT**

(51) **Int. Cl.**

B65G 17/06 (2006.01)

F27B 9/24 (2006.01)

(Continued)

An endless conveyor belt for a conveyor baking oven has a conveyor run with a plurality of belt links configured in one piece, the belt links extending transversely to a conveying direction and being mounted between lateral guides. Seen in projection in a plane perpendicular to a conveying plane, each of the belt links has gas passage openings. These gas passage openings have a total opening surface area, which amounts to at least 30% of a total surface area of the projection of the belt link. The result is an endless conveyor belt, which allows a baking space of a conveyor baking oven equipped with an endless conveyor belt of this type to be heated more efficiently and flexibly.

(52) **U.S. Cl.**

CPC **A21B 1/48** (2013.01); **A21B 1/26**



(2013.01); **A21B 3/04** (2013.01); **A23L 3/185**

(2013.01); **A23L 5/17** (2016.08)

(58) **Field of Classification Search**

CPC B65G 15/30; B65G 17/36; B65G 17/46;

5 Claims, 9 Drawing Sheets



- (51) **Int. Cl.**
A21B 1/48 (2006.01)
A23L 5/10 (2016.01)
A21B 1/26 (2006.01)
A21B 3/04 (2006.01)
A23L 3/18 (2006.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

- 4,118,181 A 10/1978 Onodera et al.
4,493,308 A * 1/1985 Hurley A47J 37/067
122/17.2
5,010,808 A * 4/1991 Lanham A21B 1/48
198/778
5,078,120 A 1/1992 Hwang et al.
5,906,485 A * 5/1999 Groff A21B 1/48
432/121
7,325,486 B1 2/2008 Nordby et al.
10,605,330 B2 * 3/2020 Dalgaard-Nielsen F16G 1/28
2008/0164006 A1 * 7/2008 Karamanos F28F 9/0246
165/67
2010/0112169 A1 5/2010 Gunawardena et al.
2015/0047952 A1 2/2015 Talsma et al.
2019/0113103 A1 * 4/2019 Shaw F16G 3/003
2019/1643212 12/2019 Speck
2020/0277141 A1 * 9/2020 Ga Ner B65G 47/763

FOREIGN PATENT DOCUMENTS

- DE 201810208960 12/2019
EP 1621484 A1 * 2/2006 B65G 17/068
GB 1439971 A 6/1976
WO 2013142136 A1 9/2013

* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9

1

**ENDLESS CONVEYOR BELT FOR A
CONVEYOR BAKING OVEN AND BELT
LINK FOR SAID ENDLESS CONVEYOR
BELT**

CROSS-REFERENCES TO RELATED
APPLICATIONS

This application claims the priority of German Patent Application. Serial No. DE 10 2018 208 960.4, filed Jun. 6, 2018, pursuant to 35 U.S.C. 119 (a)-(d), the content of which is incorporated herein by reference in its entirety as if fully set forth herein.

TECHNICAL FIELD

The invention relates to an endless conveyor belt for a conveyor baking oven. The invention further relates to a belt link for an endless conveyor belt of this type, to a baking oven module with an endless conveyor belt of this type, and to a baking oven with an endless conveyor belt of this type.

BACKGROUND

An endless conveyor belt for a conveyor baking oven is generally known. There the belt links are provided as tubes running transversely to the conveying direction, with a wire mesh being welded thereupon to carry bakery products or bakery product carriers. DE 691 12 035 T2 describes an oven assembly for large-scale cooking where food is transported continuously through a cooking chamber along a spiral, vertically ascending path. Similar oven assemblies are shown in U.S. Pat. No. 4,118,181 A and in US 2010/0 112 169 A1. U.S. Pat. No. 7,325,486 B1 discloses an apparatus for food preparation. DE-OS 2 403 488 discloses a process and a continuous oven for the treatment of foodstuffs. WO 2013/142 136 A1 describes a spiral conveyor. US Pat. No. 5,906,485 A discloses a tunnel belt oven that uses radiant heat and convection heat to prepare food. EP 1 621 484 A1 discloses a modular grid structure that can be interconnected as a cladding element, encasing rods of a conveyor belt.

SUMMARY

It is an object of the present invention to refine an endless conveyor belt of the type named at the outset in such a way that a baking space of a conveyor baking oven equipped with an endless conveyor belt of this type can be heated more efficiently and flexibly.

This object is achieved by an endless conveyor belt for a conveyor baking oven, having a conveyor run with a plurality of belt links configured in one piece, the belt links extending transversely to a conveying direction and being mounted between lateral guides, wherein each of the belt links, seen in projection in a direction perpendicular to a conveying plane, has gas passage openings with a total opening surface area, which amounts to at least 30% of a total surface area of the projection of the belt link.

The inventors found that a size of a total opening surface area of gas passage openings in the belt links, seen in a projection perpendicular to a conveying plane, helps to enhance the efficiency of a baking space heating in such a way that a flow resistance for a fluid, for example air, which passes through the baking space after passing through the conveyor run of the endless conveyor belt, is reduced. In relation to the total projection surface area of the belt link on

2

the conveying plane, the total opening surface area of the gas passage openings when seen in the same projection direction may be greater than 30%, may be greater than 40%, may be greater than 50% and may even be greater. A belt path of the endless conveyor belt can be such that a conveyor run passing through a baking space of the conveyor baking oven runs along a straight line in one plane. The one-piece configuration of the belt links increases the stability of the endless conveyor belt. An unwanted displacement between support members and frame members, which may occur in multi-part configurations of prior-art belt links, is avoided. The one-piece belt links may form self-supporting cross-members of the conveyor belt.

Link planes in which respective gas passage openings are formed, the link planes being spaced from each other in a direction perpendicular to the conveying plane, increase a stability of the respective belt link.

Longitudinal extensions of the gas passage openings of one of the link planes along the belt link extension and/or transverse to the belt link extension ensure a defined stability of the belt link in relation to load forces occurring in particular directions. The longitudinally extending through-openings allow the belt link to be reinforced in a longitudinal direction. Correspondingly, the transversely extending through-openings allow the belt link to be reinforced in a transverse direction.

A self-supporting design of the belt links between suspension mounting plates by which they are mounted to the lateral guides, prevents undesirable wear as an undesirable contact between the belt links and a non-moving base plate of the baking oven can be avoided.

The advantages of the disclosed belt link, of a baking oven module with an endless conveyor belt and with a baking space through which a conveyor run of the conveyor belt runs and of a baking oven with an endless conveyor belt and with a baking space through which a conveyor run of the conveyor belt runs, correspond to those that have already been explained above with reference to the endless conveyor belt. The baking oven can be a conveyor baking oven, in particular a tunnel oven. The baking oven can be made up of a plurality of baking oven modules, which may in particular have the same design.

An exemplary embodiment of the invention will hereinafter be explained in more detail by means of the drawing.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows a side view of a modular baking oven;

FIG. 2 shows a sectional view along line II-II in FIG. 1;

FIG. 3 shows a perspective view of a pipe coil heat exchanger for a baking oven module of the baking oven as shown in FIG. 1;

FIG. 4 shows an enlarged sectional view of a perspective view of the pipe heat exchanger as shown in FIG. 3 in the region of 180° deflection sections of two coil line paths;

FIG. 5 shows another perspective view, similar to FIG. 4, of the 180° deflection sections, seen approximately from a viewing direction counter to that in FIG. 4;

FIG. 6 shows a top view, similar to FIGS. 4 and 5, of a section of a pipe heat exchanger to illustrate a distance between in each case two adjacent pipe sections;

FIG. 7 shows a schematic view of flow relationships generated when a gas exposed to heat emitted by the pipe heat exchanger is flowing through passages between two adjacent pipe sections, shown in cross-section, of the pipe heat exchanger;

FIG. 8 shows a perspective view of a belt link of an endless conveyor belt of the baking oven; and

FIG. 9 shows a top view of the belt link shown in FIG. 8.

DETAILED DESCRIPTION

FIG. 1 shows a total side view of a conveyor baking oven 1 configured as a tunnel oven, which allows long-life bakery products such as soft biscuits, crispy biscuits or lye pastries to be produced. Other bakery products such as toast can also be processed in the baking oven. The baking oven 1 also allows roasting and special applications such as drying or sterilizing. In the embodiment shown, the baking oven 1 is shown in an interrupted view and has a plurality of oven modules $2_i, 3_i$ with baking spaces, which combine to form two conveyor baking spaces arranged on top of one another between a respective initial oven module $2_1, 3_1$ arranged in a leading manner in a bakery product conveying direction and a respective final oven module $2_N, 3_N$, which forms the last oven module in the bakery product conveying direction ($i=1, \dots, N$, N : number of oven modules). FIG. 1 shows a total of eight oven modules 2_1 to 2_8 , which belong to an upper conveyor baking space, and eight oven modules 3_1 to 3_8 arranged therebelow, which belong to a lower conveyor baking space of the conveyor baking oven 1. In other words, the oven modules of the conveyor baking oven 1 are arranged on two levels.

The oven modules 2_1 to 2_8 and 3_1 to 3_8 each have the same basic design, in particular in terms of a support frame design and receptacles for attached and mounted parts. The oven modules 2_1 to 2_8 and 3_1 to 3_8 therefore have the same dimensions, in other words they generally have the same spatial requirements in terms of height, width and depth.

The oven modules 2_1 to 2_8 and 3_1 to 3_8 are provided as separate modules first, which are connected to each other when the baking oven 1 is being assembled. In each of the baking oven modules 2_1 to 2_8 and 3_1 to 3_8 , heated circulating air is guided in circulation by heat exchangers, which will be described below. The upper oven modules 2_1 to 2_8 are carried by the lower oven modules 3_1 to 3_8 . The lower oven modules 3_1 to 3_8 are carried by a machine base.

In front of an initial baking oven module 2_1 and 3_1 each arranged in a leading manner in the bakery product conveying direction, a loading module 4 for the bakery products is arranged, which also has a two-level design and communicates with the two conveyor baking spaces. Behind a final oven module 2_i and 3_i , which is the last one when seen in the bakery product conveying direction, a discharge module 5 of the conveyor baking oven 1 is arranged to receive and discharge the bakery product from the conveyor baking spaces after baking, the discharge module 5 having a two-level design as well and communicating with the two conveyor baking spaces. The loading module 4 on the one hand and the discharge module 5 on the other close the circulating air cycle at the beginning and at the end of the conveyor baking spaces.

Between the oven modules $2_8, 3_8$ and the discharge module 5, the conveyor baking oven 1 is shown in an interrupted view in FIG. 1 to indicate that the number of oven modules $2_i, 3_i$ may be greater than that shown in FIG. 1. For example, the number N of the oven modules $2_i, 3_i$ may vary between 5 and 20 in practical application.

Bakery products to be baked enters, via the loading module 4, the respective conveyor baking space 7, 8, in other words the respective initial oven module $2_1, 3_1$ arranged in a leading manner, passes through the respective conveyor baking space 7, 8 along the bakery product con-

veying direction 9 and, having passed through the respective final oven modules $2_i, 3_i$, exits the conveyor baking spaces 7, 8 via the discharge module 5 as a freshly baked product.

In the side view of the conveyor baking oven as shown in FIG. 1, some or all of the oven modules $2_i, 3_i$ are further provided with in each case one cleaning opening 6a, in each case one inspection opening 6b, and in each case one fume opening 6c. The respective fume opening 6c allows fumes to be introduced into and removed from the respective baking space of the oven module $2_i, 3_i$.

FIG. 2 shows a sectional view of two baking oven modules $2_i, 3_i$; arranged on top of one another. The conveying direction 9 is perpendicular to the sectional or drawing plane of FIG. 2. FIG. 3 shows an exemplary and more detailed view of one of the oven modules 2_i . The oven modules 3_i have the same design so it is sufficient to show, in the detailed illustration of FIG. 3, only one of the oven modules 2_i to serve as example. Details not shown in FIG. 2 can then be found in FIG. 3.

The baking oven modules $2_i, 3_i$ each have a baking space 10, which is heated, on the one hand, directly by the circulating air, and, on the other hand, by radiant heat, which is generated by heat exchangers configured as two pipe coil heat exchangers 11, 12. The baking spaces 10 each form part of the two conveyor baking spaces 7, 8 arranged on top of one another, which are formed by the upper oven modules 2_i on the one hand and by the lower oven modules 3_i on the other. The pipe heat exchanger 11 arranged above the respective baking space 10 generates top heat for the baking space 10. The pipe heat exchanger 12 arranged below the baking space generates bottom heat for the baking space 10.

The heat carrier fluid flowing through the pipe heat exchangers 11, 12 is thermal oil. Together with a thermal oil source not shown, the two heat exchangers 11, 12 form a thermal oil heating device.

The upper pipe heat exchanger 11 is carried by a retaining frame 13 mounted to lateral frame sidewalls 14, 15 of the baking oven module $2_i, 3_i$. Together with an upper retaining plate 16 and a lower retaining plate 17, the two frame sidewalls 14, 15 form a baking oven module 18, which houses—amongst other things—the two pipe heat exchangers 11, 12 of the baking oven module $2_i, 3_i$. Between the upper retaining plate 16 and the upper pipe heat exchanger 11, an air baffle 18a is arranged. Said air baffle 18a serves to ensure a uniformity of a circulating airflow in the baking space 10. The air baffle 18a is also capable of absorbing thermal energy from the pipe heat exchanger 11 and of releasing said thermal energy to the circulating air, in other words it may be used as an additional indirect heat exchanger component. A corresponding air baffle 18a is arranged between the lower pipe heat exchanger 12 and the lower retaining plate 17.

An upper conveyor run 19 of an endless conveyor belt 20 runs between the two pipe heat exchangers 11, 12, said upper conveyor run 19 being used to convey the bakery products through the respective conveyor baking space 7, 8 between the loading module 4 and the discharge module 5. In accordance with its two-level design, the conveyor baking oven 1 has two endless conveyor belts 20, namely an upper endless conveyor belt 20 for the baking oven modules 2_i , and a lower endless conveyor belt 20 configured in the same way for the lower oven modules 3_i . Therefore, it is sufficient to describe one of these conveyor belts in the following sections.

The conveyor belt 20 has a plurality of belt links 21 of which an upper belt link 21_o and a lower belt link 21_u are shown in FIG. 2. In its current operating position, the upper

belt link 21_o is part of the upper conveyor run **19** and is arranged in the baking space **10**. The lower belt link 21_u is part of a lower belt run **22**, which is part of the endless conveyor belt **20** running through a return conveyor belt space **23** in a direction counter to the conveying direction **9** below the baking space **10** and the lower pipe heat exchanger **11**.

Between the upper retaining plate **16** of the baking space module **18** and an upper module plate 23_a of the baking oven module $2_i, 3_i$, an upper circulating air duct **24** is arranged. Between the lower retaining plate **17** of the baking space module **18** and a lower module plate **25**, a lower circulating air duct **26** is arranged. The two circulating air ducts **24, 26** extend across the entire width of the baking oven module $2_i, 3_i$.

The two circulating air ducts **24, 26** are in a fluidic connection, via inlet and exhaust air ducts **27, 28, 29, 30**, with two axial/radial fans **31, 32**. Altogether, they produce a respective circulating air cycle in the respective oven module $2_i, 3_i$. The baking space **10** of the respective oven module $2_i, 3_i$ is part of this circulating air cycle. Together with the respective circulating air cycle, the fans **31** and **32**, respectively, are components of a circulating air system of the conveyor baking oven **1**.

The two fans **31, 32** and the inlet and exhaust air ducts **27** to **30** are mounted to vertically extending lateral frame plates **33, 34** of the baking oven module $2_i, 3_i$.

Taking the example of the upper pipe coil heat exchanger **11**, FIG. **3** shows one of the two pipe heat exchangers used in the baking oven module 2_1 . All pipe heat exchangers **11, 12** of the baking oven modules $2_i, 3_i$ of the baking oven **1** have the same design so it is sufficient to describe, in the following sections, this upper pipe heat exchanger **11**.

The pipe heat exchanger **11** has a plurality of, strictly speaking thirty-six in the exemplary embodiment shown, heat exchanger pipe sections **36** arranged adjacent to each other in an arrangement plane (cf. plane **35** in FIG. **2**) to guide a heat carrier fluid. The heat carrier fluid used may in particular be thermal oil.

The adjacent arrangement of the heat exchanger pipe sections **36** in the arrangement plane **35** may be such that in an actual side view as shown in FIG. **2**, all heat exchanger pipe sections are entirely flush with each other. Alternatively, longitudinal axes of in particular adjacent pipe sections **36** may have various distances from the arrangement plane **35**. However, a bandwidth of the distances of the longitudinal axes of the pipe sections **36** from the arrangement plane **35** is still smaller than a diameter of the individual pipe sections **36**, and is in particular smaller than a fraction of this diameter, for example smaller than 80%, smaller than 70%, smaller than 60%, smaller than 50%, smaller than 40%, smaller than 30%, smaller than 20%, and may in particular be smaller than 10% of the diameter of the pipe sections **36**. The pipe diameter of the pipe sections **36** may be in the range between 10 mm and 150 mm, and may for example be in the range between 25 mm and 50 mm, for example 35 mm, 38 mm or 40 mm. If the pipe sections **36** are not entirely flush with each other when seen in a side view, for example that of FIG. **2**, the longitudinal axes of the pipe sections **36** may in this case have a distance from the arrangement plane, which is in the range between 0 mm and ± 20 mm.

A distance **A** between two adjacent pipe sections is, on the one hand, smaller than the pipe diameter, and, on the other hand, greater than 1% of the pipe diameter. This distance **A**

is illustrated in FIG. **6**, which shows a top view of a section of the pipe heat exchanger **11**, for two exemplary adjacent pipe sections **36**.

An absolute distance between two adjacent pipe sections **36** may be in the range between 1 mm and 50 mm, in particular in the range between 1 mm and 10 mm, in the range between 1 mm and 5 mm, and may be 2 mm, for example.

This distance between the adjacent pipe sections **36** provides a passage between these pipe sections. A passage of this type runs along a total extension of the pipe sections **36** through the baking space **10** in a direction transverse to the conveying direction **9**, and is interrupted—if at all—only by mounting components. Compared to the total extension of the pipe sections **36**, these interruptions are very small, usually amounting to less than 5% of the total extension of the pipe sections **36**. These passages obtained as a result of the distance between adjacent pipe sections **36** lead to an effective heat transfer from the pipe sections **36** to fluid flowing between two adjacent pipe sections **36**.

Corresponding heat transfer relationships are shown in a greatly schematic view in FIG. **7** for two adjacent pipe sections **36** of the pipe heat exchanger **12**. FIG. **7** shows the flow relationships for the lower pipe coil heat exchanger **12**. The heat carrier fluid **37** flows through the pipe sections **36**. Another heat absorption fluid, which is air **39** in the embodiment described, flows against and around circumferential walls **38** of the pipe sections **36** as shown schematically by some flow arrows. Because of the distance **A** between the adjacent pipe sections **36**, which is in the range between 1% and 100% of the pipe diameter **D**, the in-flowing air **39** flows between the adjacent pipe sections after contacting circumferential sections **U** of the circumferential walls **38**. Having passed through the narrowest point of the passage between the adjacent pipe sections **36** where the distance **A** is provided, the flow of air **39** separates from the circumferential wall **37** as it continues to flow, causing the air **39** to flow upwardly in a turbulent manner in such a way that the air that has flown through the observed passage between the adjacent pipe sections mixes effectively with the air **39** that has passed through adjacent passages between the pipe sections **36** shown and adjacent pipe sections on the left- and right-hand sides thereof, which are not shown. Above the arrangement plane **35**, in the case of the airflow from bottom to top as shown, a closed and essentially non-interrupted volume airflow is achieved very rapidly towards the baking space **10** arranged at the top, which is represented by flow arrows **40** in FIG. **2**. The turbulences ensure that the pipe sections **36** themselves do not serve as baffles for the airflow, thus resulting in a closed air curtain flowing through the baking space **10** above the heat exchanger **12** without gaps.

The pipe heat exchanger **11** is configured as a pipe coil heat exchanger. A first coil line path **41** runs between a first coil line inlet **42** and a first coil line outlet **43**. A second coil line path **44** runs between a second coil line inlet **45** and a second coil line outlet **46**. The pipe heat exchanger **11** shown in FIG. **3** therefore has precisely two coil line paths **41** and **44**. It is generally conceivable to provide a greater number of corresponding coil line paths.

In each case two pipe sections **36** arranged adjacent to each other in the arrangement plane **35** belong to different coil line paths. In the representation as shown in FIG. **3**, the pipe section **36** shown at the very bottom left is part of the first coil line path **41**. The pipe section **36** arranged directly adjacent thereto in the upper right direction is part of the second coil line path **44**. The pipe section in turn arranged adjacent thereto in the upper right direction is then part of

the first coil line path **41** again. The other pipe sections **36** arranged adjacent thereto alternately belong to the second coil line path **44** and to the first coil line path **41**. The pipe section **36** shown at the very upper right then belongs to the second coil line path **44** and leads into the second coil line outlet **46**.

As the pipe sections **36** are associated to the two coil line paths **41** and **44** in an alternating manner, a minimum bending radius of the pipe sections **36** are made of increases along a respective one of the two coil line paths **41**, **44**. This increased bending radius is illustrated by the arrangement of 180° deflection sections **47**, **48** of the two coil line paths **41**, **44**, which is shown in particular in FIGS. **4** to **6** each showing enlarged views of the coil line paths **41**, **44** of the pipe heat exchanger **11**. An inner bending radius of the 180° deflection sections **47**, **48** is greater than the pipe radius, in other words it is greater than half of the pipe diameter D . On the other hand, this inner bending radius of the 180° deflection sections **47**, **48** is smaller than the pipe diameter D .

By a respective Y-pipe section **49**, **50**, the two coil line inlets **42**, **45** on the one hand and the two coil line outlets **43** and **46** on the other are in a fluidic connection with one another and with a collective inlet **49a** on the one hand and a collective outlet **50a** on the other.

The two coil line inlets **42**, **45** are in a fluidic connection with the collective line inlet **49a** by the Y-pipe section **49**. The collective line inlet **49a** in turn is in a fluidic connection with a heat carrier fluid source not shown in the drawing. The two collective line outlets **43**, **46** are in a fluidic connection with the collective line outlet **50a** by the additional Y-pipe section **50**. The collective line outlet **50a** may be in a fluidic connection with the collective line inlet **49a** to form a heat carrier fluid cycle. A pump for the heat carrier fluid **37**, which is not shown in the drawing either, can be part of this cycle.

The 180° deflection sections **47** for the coil line path **41** are guided out of the arrangement plane **35** between the two pipe sections **36** connected by them in such a way that an obtuse angle is obtained therebetween. A bending angle β between the arrangement plane **35** and an arrangement plane of the 180° deflection sections **47** (cf. FIG. **2** for the pipe heat exchanger **12**) is approximately 150° in the embodiment shown. This bending angle can be in the range between 120° and 165° .

Guiding the 180° deflection sections **47** out of the arrangement plane **35** prevents spatial conflicts between the 180° deflection sections **47**, **48** of the various coil line paths **41**, **44**.

A pipe coil heat exchanger configured as the pipe coil heat exchangers **11** and **12** of the baking oven module **6** is produced as follows:

In a first step, a pipe is provided, which has a multiple of the length of one of the pipe sections **36** between the respective deflection sections **47**, **48**. Then a first coil line path, for example the coil line path **41**, is produced by bending the pipe in the region of the deflection sections **47** between the pipe sections **36**. Then a second coil line path, in this case the coil line path **44**, is produced by bending the pipe of the deflecting sections **48** between the pipe sections **36**. As soon as the end of the pipe is reached after these bending steps, another pipe with the same diameter is attached thereto if necessary, in other words it is connected to the pipe that has just been processed, for example it is welded to the front end thereof.

Having produced the two coil line paths **41**, **44**, the two coil line paths **41**, **44** are inserted into one another in the arrangement plane **35**. Then the Y-pipe sections **49**, **50** can

be connected, for example by welding, to the coil line inlets **42**, **45** and the coil line outlets **43**, **46** to create, if necessary, a fluid passage between the respective Y-pipe section **49**, **50** and the respective line inlets **42**, **45** on the one hand and outlets **43**, **46** on the other.

In a variation of the production method, the 180° deflection sections **47** are bent out of the arrangement plane **35** between the pipe sections **36** of the same coil line path **41** before inserting the two coil line paths **41**, **44** into one another. This bending process can take place at the same time when producing this coil line path **41** by using a corresponding, in particular flat, bending tool.

When a baking process is performed using the tunnel conveyor baking oven **1**, the bakery product passed through the oven modules **2** to **6** along the conveyor run **19** is heated, on the one hand, by radiant heat emitted by the pipe heat exchangers **11**, **12**, which are housed in the respective oven modules **2** to **6**, and by the circulating air on the other, which flows through the respective baking space **10** of the oven module **2** to **6**. The heat contributions "radiant heat" on the one hand and "circulating air heat" (emission of heat to fluid flowing through the baking space) on the other can be predefined by designing the pipe heat exchangers **11**, **12** correspondingly, and by the temperature and the flow of the heat carrier fluid **37** passing through the pipe heat exchangers **11**, **12**, and also by the amount of air flowing through each of the baking spaces **10**.

Depending on the design of the oven module **2** to **6**, an airflow through the baking space **10** (cf. for example the airflow **40** in FIG. **2**) can be directed from bottom to top or, alternatively, from top to bottom.

In the flow example shown in FIG. **2**, the left-hand fan **31** in FIG. **2** ensures that the circulating air flows through the inlet air duct **27** and into the lower circulating air duct **26** first. At the same time, the right-hand fan **32** in FIG. **2** ensures that the circulating air flows through the right-hand inlet air duct into the lower circulating air duct **26**. The excess pressure, which is then generated in the lower circulating air duct **26**, causes the circulating air to flow upwardly from the lower circulating air duct **26** so as to pass through between the adjacent pipe sections **36** of the lower pipe heat exchanger **12** as already described above with reference to FIG. **6**. The circulating air then flows through the upper conveyor run **19** of the endless conveyor belt **20** where it flows around the dough pieces conveyed thereon through the baking space **10**. The circulating air then flows through the passages between the pipe sections **36** of the upper pipe heat exchanger **11** before flowing into the upper circulating air duct **24** from which the circulating air **31** **32** is extracted again by the fans **31**, **32** and the outlet air ducts **29**, **30** to close the respective circulating air cycle. An excess pressure in the circulating air cycle is able to escape via a flap-controlled exhaust gas pipe **51** (cf. FIG. **2**).

Depending on the design of the oven module **2** to **6**, the oven module **2** may have fans such as in the embodiment shown in FIG. **2** or, alternatively, only one axial-radial fan, which may then be mounted on one side or on the other side of the oven module. If more than one oven modules arranged one behind the other in the conveying direction **9** are equipped with precisely one fan of this type, the arrangement of this fan may alternate between the two sides of the conveyor baking oven **1**, for example, in such a way that the fan in the oven module **3** is arranged on the right-hand side in the manner of the fan **32** while it is arranged on the left-hand side in the following oven module **4** and on the right-hand side again in the following oven module **5**, for example. As an alternative or in addition thereto, the flow

direction of the circulating air through the baking space **10** may be predefined by correspondingly operating the respective fan **31**, **32** from bottom to top or from top to bottom.

It is conceivable to define various temperature zones in the oven modules **2** to **6**. This can be done by setting the temperature and/or the flow rate of the thermal oil and/or the amount of circulating air and by setting the flow direction of the circulating air from bottom to top/from top to bottom. This is done using a central control device of the baking oven **1**.

One of the belt links **21** of the endless conveyor belt **20** will hereinafter be explained in more detail by means of FIGS. **8** and **9**. As all belt links **21** of the endless conveyor belt **20** are designed identically, it is sufficient to describe one of the belt links **21**.

The belt link **21** extends transversely to the conveying direction **9** between lateral guides **53**, **54** for the endless conveyor belt **20**, the guides **53**, **54** being housed in the baking oven module **18** for the upper conveyor run **19**. The respective belt link **21** is connected to these guides **53**, **54** by suspension mounting plates **55**.

The upper conveyor run **19** extends in a conveying plane **56**, which is parallel to the arrangement planes of the pipe heat exchangers **11**, **12** (cf. arrangement plane **35**).

In a projection in a direction perpendicular to the conveying plane **56**, in other words seen in the viewing direction of FIG. **9**, the belt link **21** has gas passage openings **57**, **58**. These gas passage openings **57**, **58** have total opening surface area, which amounts to at least 30% of a total surface area of the projection of the belt link **21**.

Between the lateral guides, in other words between the two suspension mounting plates **55**, the belt link **21** has a plurality of link planes **59**, **60**, which—in the embodiment **2** shown—are spaced from each other in a direction perpendicular to the conveying plane **56**.

The first, upper link plane **59** coincides with the conveying plane **56** and is defined by a plurality of double link brackets **63** extending along the conveying direction **9** between lateral link side walls **61**, **62**. The gas passage openings **58** are formed between the brackets of the respective double link bracket **63**. Further gas passage openings in the upper link plane **59** are formed between in each case two adjacent double link brackets **63**.

For the belt links **21**, which form the upper conveyor run **19** at a particular instant, the second, lower link plane **60** is formed below the first link plane **59**. There, a reinforcement plate **64** runs between the link side walls **61**, **62** in which the gas passage openings **57** are formed.

The gas passage openings **57** in the reinforcement plate **64** extend in the manner of elongate holes. The gas passage openings **57** have a longitudinal extension in the direction of the longitudinal extension of the belt link **21**.

The gas passage openings **58** between the brackets of the respective double link bracket **63** are designed in the manner of elongate holes. The gas passage openings **58** have a longitudinal extension transverse to the longitudinal extension of the belt link **21**, in other words parallel to the conveying direction **9**, as long as the belt link **21** is part of the upper conveyor run **19**.

Between the suspension mounting plates **55**, the belt link **21** is designed in a self-supporting manner.

In the operation of the tunnel conveyor baking oven **1**, the belt links **21** circulate endlessly between the guides **53**, **54** in the manner of chain links, with the upper conveyor run **19** running in the conveying direction **9** and the lower conveyor run **22** running counter to the conveying direction **9**. In the region of the leading baking oven module **2₁** and the last

baking oven module **2_N**, a 180° deflection takes place between the upper conveyor run **19** and the lower conveyor run **22** via the guides **53**, **54**, which are designed correspondingly.

What is claimed is:

1. An endless conveyor belt for a conveyor baking oven, having a conveyor run with a plurality of belt links, the belt links having link side walls extending transversely to a conveying direction that are connected by a plurality of double link brackets and being mounted between lateral guides that extend in the conveying direction,
 - wherein each of the belt links, seen in projection in a direction perpendicular to a conveying plane, has gas passage openings with a total opening surface area, which amounts to at least 30% of a total surface area of the projection of the belt link,
 - wherein between the lateral guides, each of the belt links has a lower link plane and an upper link plane in which respective gas passage openings are formed, the lower link plane and the upper link plane being spaced from each other in a direction perpendicular to the conveying plane,
 - wherein the gas passage openings of one of the lower link plane and the upper link plane have a longitudinal extension along the extension of the belt link,
 - wherein the gas passage openings of another one of the lower link plane and the upper link plane have a longitudinal extension transverse to the extension of the belt link,
 - wherein the gas passage openings in a reinforcement plate in the lower link plane are shaped as elongated holes, wherein the gas passage openings between brackets of the respective double link brackets in the upper link plane are shaped as elongated holes.
2. The endless conveyor belt as claimed in claim 1, wherein the belt links are configured in a self-supporting manner between suspension mounting plates by which they are mounted to the lateral guides.
3. A baking oven module with an endless conveyor belt as claimed in claim 1, and with a baking space through which a conveyor run of the conveyor belt runs.
4. A baking oven with an endless conveyor belt as claimed in claim 1 and with a baking space through which a conveyor run of the conveyor belt runs.
5. A belt link for an endless conveyor belt, comprising:
 - link side walls extending transversely to a conveying direction;
 - a plurality of double link brackets connecting the link side walls; and
 - suspension mounting plates for mounting the belt link between lateral guides that extend in the conveying direction of a conveyor baking oven,
 - wherein the belt link, seen in projection in a direction perpendicular to a conveying plane, has gas passage openings with a total opening surface area, which amounts to at least 30% of a total surface area of the projection of the belt link,
 - wherein the belt link has a lower link plane and an upper link plane in which respective gas passage openings are formed, the lower link plane and the upper link plane being spaced from each other in a direction perpendicular to the conveying plane,
 - wherein the gas passage openings of one of the lower link plane and the upper link plane have a longitudinal extension along the extension of the belt link,

11

12

wherein the gas passage openings of another one of the lower link plane and the upper link plane have a longitudinal extension transverse to the extension of the belt link,

wherein the gas passage openings in a reinforcement plate 5 in the lower link plane are shaped as elongated holes, and

wherein the gas passage openings between brackets of the respective double link brackets in the upper link plane are shaped as elongated holes. 10

* * * * *