



US011053875B2

(12) **United States Patent**
Pachner et al.

(10) **Patent No.:** **US 11,053,875 B2**
(45) **Date of Patent:** **Jul. 6, 2021**

(54) **SYSTEM AND METHOD FOR ESTIMATING TURBO SPEED OF AN ENGINE**

2037/122 (2013.01); F02D 2041/1416 (2013.01); F02D 2041/1433 (2013.01); F02D 2200/0402 (2013.01);

(71) Applicant: **GARRETT TRANSPORTATION I INC.**, Torrance, CA (US)

(Continued)

(72) Inventors: **Daniel Pachner**, Prague (CZ); **Yuejiang Liu**, Beijing (CN); **François-Xavier Brulhart**, Cartigny (CH); **Michael Robert Uchanski**, Vevey (CH)

(58) **Field of Classification Search**

CPC F02D 41/1401
See application file for complete search history.

(73) Assignee: **Garrett Transportation I Inc.**, Torrance, CA (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,155,050 A 12/2000 Blanz et al.
6,401,457 B1 6/2002 Wang et al.
(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 764 days.

FOREIGN PATENT DOCUMENTS

DE 102005007558 9/2005
DE 102005008030 3/2006

(Continued)

(21) Appl. No.: **15/040,960**

(22) Filed: **Feb. 10, 2016**

OTHER PUBLICATIONS

(65) **Prior Publication Data**

US 2017/0226948 A1 Aug. 10, 2017

Andersson, "Air Charge Estimation in Turbocharged Spark Ignition Engines," Linkoping Studies in Science and Technology, Thesis No. 989, 245 pages, 2005.

(Continued)

(51) **Int. Cl.**

F02D 41/14 (2006.01)
F02D 41/00 (2006.01)
F02B 37/12 (2006.01)
F02D 9/02 (2006.01)
F02D 9/10 (2006.01)

(Continued)

Primary Examiner — John E Breene

Assistant Examiner — Jeffrey C Morgan

(74) *Attorney, Agent, or Firm* — Seager, Tufte & Wickhem LLP


(52) **U.S. Cl.**

CPC **F02D 41/1401** (2013.01); **F02B 37/12** (2013.01); **F02D 9/02** (2013.01); **F02D 9/105** (2013.01); **F02D 41/0007** (2013.01); **F02D 41/263** (2013.01); **F02M 35/104** (2013.01); **F02M 35/1038** (2013.01); **F02M 35/10386** (2013.01); **G01M 15/14** (2013.01); **F02B**

(57) **ABSTRACT**

The speed of a turbocharger may be estimated using data from sensors that are readily available in most engine management systems. In some cases, a pressure measurement from a MAP sensor may be used, in combination with one or more computational models, to provide an efficient, lower cost estimate of turbo speed that can be used to control operation of the engine and/or the turbocharger.

20 Claims, 6 Drawing Sheets



- (51) **Int. Cl.**
F02D 41/26 (2006.01)
F02M 35/10 (2006.01)
F02M 35/104 (2006.01)
G01M 15/14 (2006.01)
- (52) **U.S. Cl.**
 CPC *F02D 2200/0404* (2013.01); *F02D 2200/0406* (2013.01); *F02D 2200/0414* (2013.01); *Y02T 10/12* (2013.01)
- (56) **References Cited**

U.S. PATENT DOCUMENTS

6,530,754 B2 3/2003 Vogel
 6,539,714 B1 4/2003 Wang
 6,557,347 B1 5/2003 Alvarez et al.
 6,804,601 B2 10/2004 Wang et al.
 7,007,472 B2 3/2006 Baize et al.
 7,100,375 B2 9/2006 Baize et al.
 7,127,892 B2 10/2006 Akins et al.
 7,265,542 B2 9/2007 Hrubes
 7,283,923 B2 10/2007 Barila et al.
 7,296,562 B2 11/2007 Withrow et al.
 7,372,553 B2 5/2008 Aoshima et al.
 7,380,401 B2 6/2008 Henn et al.
 7,380,446 B2 6/2008 Baeuerle et al.
 7,730,724 B2 6/2010 Shu et al.
 7,748,217 B2 7/2010 Muller
 7,769,522 B2 8/2010 Adreae et al.
 7,861,580 B2 1/2011 Sujan et al.
 8,061,137 B2 11/2011 Evans
 8,191,370 B2 6/2012 Shimizu et al.
 8,205,503 B2 6/2012 Cox
 8,291,752 B2 10/2012 Bierl et al.
 8,504,321 B2 8/2013 Seidel et al.
 8,567,192 B2 10/2013 Chi et al.
 8,567,238 B2 10/2013 Serra et al.
 8,640,459 B2 2/2014 Ge et al.
 8,676,534 B2 3/2014 Serra et al.
 8,769,936 B2 7/2014 Petrovic et al.
 8,892,332 B2 11/2014 Chi et al.
 9,010,180 B2 4/2015 Petrovic et al.
 9,121,862 B2 9/2015 Reitmeier et al.
 9,133,792 B2 9/2015 Cianflone et al.
 9,175,597 B2 11/2015 Katsumata et al.
 2006/0064231 A1 3/2006 Fekete et al.
 2007/0068159 A1* 3/2007 Ueno F02D 41/1401
 60/605.2

2008/0053087 A1 3/2008 Swenson et al.
 2009/0133399 A1 5/2009 Keyes et al.
 2012/0016602 A1 1/2012 Fontvieille et al.
 2012/0179356 A1 7/2012 Ide et al.
 2014/0123938 A1 5/2014 Whitney et al.
 2015/0034046 A1 2/2015 Takahashi et al.
 2015/0057909 A1 2/2015 Chi et al.
 2015/0101578 A1 4/2015 Suchy et al.
 2015/0110650 A1 4/2015 Christmann
 2015/0114096 A1 4/2015 Eichel
 2015/0159544 A1 6/2015 Cowgill et al.
 2015/0204341 A1 7/2015 Chekansky
 2015/0276785 A1 10/2015 Nau et al.
 2015/0308859 A1 10/2015 Lerchenmueller
 2015/0337747 A1 11/2015 De Cesare et al.

FOREIGN PATENT DOCUMENTS

DE 102008022083 A1 11/2008
 DE 102010039532 2/2012
 DE 102012213961 3/2014
 DE 10201401947 1/2015
 EP 1837512 * 9/2007
 EP 1837512 A1 9/2007
 EP 1977086 5/2009
 EP 2648001 9/2013
 GB 2499852 4/2013
 WO 2008068098 6/2008
 WO 2009028003 3/2009
 WO 2009056725 5/2009
 WO 2013031919 3/2013
 WO 2014002464 1/2014
 WO 2015027348 3/2015
 WO 2015097505 7/2015

OTHER PUBLICATIONS

Garrett, "Turbo Tech 103 (Expert)," 12 pages, downloaded Feb. 23, 2016.
 Muller, "Estimation and Control of Turbocharged Engines," SAE Technical Paper Series 2008-01-1013, 2008 World Congress, 16 pages, Apr. 14-17, 2008.
 Storset et al., "Adaptive Air Charge Estimation for Turbocharged Diesel Engine," 39 pages, Sep. 15, 2003.
 Extended European Search Report for EP Application No. 17152074.5, dated Jun. 30, 2017.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6

1

**SYSTEM AND METHOD FOR ESTIMATING
TURBO SPEED OF AN ENGINE**

TECHNICAL FIELD

The present disclosure pertains generally to automotive engine controls, and more particularly pertains to estimating the rotation speed of a turbocharger of the engine.

BACKGROUND

The speed at which a turbocharger rotates is an important parameter in controlling operation of turbocharged engines. The maximum turbo speed may define a maximum achievable air flow, which in turn defines a maximum achievable torque of the engine. Exceeding the maximum turbo speed can lead to mechanical damage to the turbocharger and can ultimately lead to engine failure. A goal in controlling operation of some turbocharged engines, therefore, is the ability to achieve a high turbo speed without exceeding the maximum allowed speed.

In some cases, the turbo speed may be directly measured by a dedicated speed sensor that may, for example, utilize blade counting or the like. This tends to be an expensive solution. In some cases, a less expensive alternative is to estimate the turbo speed using inputs from other sensors utilized in engine management. For example, the turbo speed may be estimated using mass air flow, compressor inlet pressure, compressor outlet pressure and compressor inlet temperature. In some cases, these values may be related via a compressor map in which the turbo speed may simply be looked up once the other values are measured and known.

A shortcoming of this estimation method is that a compressor outlet pressure sensor must be placed at the output of the turbo's compressor. Most contemporary engine designs do not include a compressor outlet pressure sensor. Thus, the addition of the compressor outlet pressure sensor may increase the cost of the engine management system, and may even reduce the reliability of the system since there is an additional failure mechanism.

SUMMARY

Modern vehicles often include a Manifold Absolute Pressure (MAP) sensor for sensing the pressure at the intake manifold of the engine. The MAP sensor is often used to control the operation of the engine. The MAP sensor is typically located at the intake manifold of the engine, and for engines with a turbocharger, the MAP sensor is typically located downstream of the turbocharger's compressor outlet, and in most cases downstream of the engine's throttle valve. In some cases, a charge air cooler is disposed between the compressor outlet and the throttle valve. The charge air cooler, when provided, may cool the compressed air provided by the compressor in order to provide a more dense intake charge into the engine, which can increase the power output of the engine. The present disclosure relates to techniques for estimating the turbo speed of a turbocharger using data from a pressure sensor that is located downstream of the throttle valve, such as the MAP sensor, instead of a compressor outlet pressure sensor that is located at the output of the compressor. This approach may reduce the cost and increase the reliability of the engine management system.

In a particular example of the present disclosure, a controller may be used to estimate an operating speed of a turbocharger that has a compressor with an air inlet and an

2

air outlet. The compressor feeds compressed air to a downstream throttle that provides a throttled air flow to an air intake manifold of an engine. The controller may include an inlet port, an outlet port and a processor that is operatively coupled to the inlet port and the outlet port. In some cases, the inlet port may receive one or more of a compressor air flow signal that represents a measure of air flow through the compressor, a compressor air inlet pressure signal that represents a measure of pressure at the air inlet of the compressor, an intake manifold pressure signal that represents a measure of pressure at the air intake manifold of the engine, a temperature signal that represents the temperature of the air at the throttle, and a throttle signal that represents the throttle position of the throttle. In some cases, the controller may include a memory that stores instructions that are executable by the processor to estimate the operating speed of the turbocharger based at least in part on the values received by the inlet port. In some cases, the processor may provide one or more control signals via the output port to control an operation of the turbocharger and/or the engine in response to the estimated operating speed of the turbocharger.

In another example of the present disclosure, a controller may be used to estimate an operating speed of a turbocharger that has a compressor with an air inlet and an air outlet. The compressor feeds compressed air to a downstream throttle that provides a throttled air flow to an air intake manifold of an engine. The controller may include an inlet port, an outlet port and a processor that is operatively coupled to the inlet port and the outlet port. In some cases, the inlet port may receive one or more of a compressor air flow signal that represents a measure of air flow through the compressor, a compressor air inlet pressure signal that represents a measure of pressure at the air inlet of the compressor, an intake manifold pressure signal that represents a measure of pressure at the air intake manifold of the engine and a throttle signal that represents the throttle position of the throttle. In some cases, the controller may include a memory that stores instructions that are executable by the processor to estimate an air pressure at the air outlet of the compressor using a throttle model that references at least the throttle signal and the measure of pressure at the air intake manifold of the engine. The controller may further estimate the operating speed of the turbocharger using a turbocharger model that references at least the measure of air flow through the compressor, the measure of pressure at the air inlet of the compressor and the estimated air pressure at the air outlet of the compressor. In some cases, the processor may provide one or more control signals via the output port to control an operation of the turbocharger and/or the engine in response to the estimated operating speed of the turbocharger.

The above summary is not intended to describe each disclosed embodiment or every implementation of the present disclosure. The Figures, and Detailed Description, which follow, more particularly exemplify some of these embodiments.

BRIEF DESCRIPTION OF THE FIGURES

The disclosure may be more completely understood in consideration of the following detailed description in connection with the accompanying drawings, in which:

FIG. 1 is a schematic diagram of an air inlet system of an engine encompassing a turbocharger in accordance with an illustrative embodiment of the present disclosure;

FIG. 2 is a schematic diagram of the air inlet system of FIG. 1, with the addition of particular sensors;

FIG. 3 is a schematic diagram of the air inlet system of FIG. 1, showing particular measured and estimated parameters;

FIG. 4 is a schematic diagram of a controller that may be used in combination with the air inlet system of FIG. 1 to estimate the turbocharger speed of the turbocharger;

FIG. 5 is a schematic diagram of the controller of FIG. 4, showing illustrative inputs and outputs of the controller; and

FIG. 6 is a flow diagram showing an illustrative method of operating an engine and/or turbocharger.

While the disclosure is amenable to various modifications and alternative forms, specifics thereof have been shown by way of example in the drawings and will be described in detail. It should be understood, however, that the intention is not to limit the disclosure to the particular embodiments described. On the contrary, the intention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the disclosure.

DESCRIPTION

For the following defined terms, these definitions shall be applied, unless a different definition is given in the claims or elsewhere in this specification.

All numeric values are herein assumed to be modified by the term “about,” whether or not explicitly indicated. The term “about” generally refers to a range of numbers that one of skill in the art would consider equivalent to the recited value (i.e., having the same function or result). In many instances, the terms “about” may include numbers that are rounded to the nearest significant figure.

The recitation of numerical ranges by endpoints includes all numbers within that range (e.g. 1 to 5 includes 1, 1.5, 2, 2.75, 3, 3.80, 4, and 5).

As used in this specification and the appended claims, the singular forms “a”, “an”, and “the” include plural referents unless the content clearly dictates otherwise. As used in this specification and the appended claims, the term “or” is generally employed in its sense including “and/or” unless the content clearly dictates otherwise.

It is noted that references in the specification to “an embodiment”, “some embodiments”, “other embodiments”, etc., indicate that the embodiment described may include one or more particular features, structures, and/or characteristics. However, such recitations do not necessarily mean that all embodiments include the particular features, structures, and/or characteristics. Additionally, when particular features, structures, and/or characteristics are described in connection with one embodiment, it should be understood that such features, structures, and/or characteristics may also be used connection with other embodiments whether or not explicitly described unless clearly stated to the contrary.

The following description should be read with reference to the drawings in which similar structures in different drawings are numbered the same. The drawings, which are not necessarily to scale, depict illustrative embodiments and are not intended to limit the scope of the disclosure. FIG. 1 is a schematic illustration of an air inlet system 10 that may, for example, be used in combination with any suitable gasoline and/or diesel-powered engine. It will be appreciated that in some cases the air inlet system 10 may include additional components not shown in FIG. 1. As illustrated, the air inlet system 10 may include a throttle valve 12 that is positioned upstream of an air intake manifold 14. The throttle valve has an air inlet 11 and an air outlet 13. Air entering the air intake manifold 14 can be mixed with fuel and fed into the combustion chambers via one or more intake

valves disposed atop each engine cylinder. In some engines, known as direct injection engines, fuel may be directly injected into each engine cylinder. In these engines, fuel is not mixed with air within the air intake manifold 14 itself.

In some cases, the throttle valve 12 may be opened further, to provide additional air, or at least partially closed, to provide less air, in response to a throttle command signal emanating from an engine management system (not shown). The engine management system may provide a command signal to change the position of the throttle valve 12 in response to the driver pushing harder on the accelerator pedal, or perhaps taking their foot off the accelerator pedal. In some cases, the engine management system may provide a throttle command signal to change the position of the throttle valve 12 in order to maintain a desired speed in response to a cruise control system (not shown). While the engine management system is generally referenced herein as a unitary control structure, it will be appreciated that in actuality, the engine management system may include a number of distinct computers, controllers, processors, sensors and the like.

Moving upstream in the illustrative air inlet system 10, air entering the air inlet system 10 is provided to a compressor 16 of a turbocharger. The compressor 16 includes an air inlet 15 and an air outlet 17. It will be appreciated that compressor 16 is disposed within the air intake flow. The turbocharger will typically also include a drive turbine (not shown) that is disposed within an exhaust gas flow of the engine. Gases within the exhaust flow cause the drive turbine to rotate. The drive turbine typically drives the compressor 16 via a compressor drive shaft. The compressor 16, which is disposed within the air intake flow, rotates via the aforementioned shaft. As the compressor 16 rotates, it draws air through the air inlet 15, compresses the air, and provides the compressed air to the air outlet 17. Air entering the compressor 16 at the air inlet 15 is generally at or close to ambient pressure, while air exiting the compressor 16 at the air outlet 17 is at an increased pressure relative to ambient pressure. The air passing through the compressor 16 may be heated as a result of being compressed, as well through some engine heating. Accordingly, in some cases, while not required, a charge air cooler 18 may be disposed downstream of the compressor 16 in order to cool the air before it reaches the throttle valve 12 and the air intake manifold 14 of the engine. The charge air cooler 18, when provided, may cool the compressed air provided by the compressor 16 in order to provide a more dense intake charge into the engine, which can increase the power output of the engine.

FIG. 2 provides another view of the illustrative air inlet system 10 of FIG. 1, with several sensors added as part of the engine management system. Many engines include a mass airflow sensor 20 that provides a mass flow rate for air entering the air inlet system 10, which may be used by an engine management system to determine a proper amount of fuel to add for proper combustion. An inlet pressure sensor 22 provides an indication of the air pressure upstream of the compressor 16. In some cases, this may provide an indication of ambient air pressure, but it will be recognized that ambient air pressure can vary with weather systems, altitude, temperature and other factors. An inlet temperature sensor 24 provides an indication of the air temperature of the air entering the compressor 16. In the example shown, a throttle inlet temperature sensor 26 provides an indication of the temperature of the air within the air inlet system 10 downstream of the compressor 16, near the air inlet 11 of the throttle valve 12. A Manifold Absolute Pressure (MAP) sensor 28 provides an indication of air pressure downstream

5

of the throttle valve 12, such as at or in the intake manifold 14 of the engine. The MAP sensor 28 is commonly used on many modern engines for controlling the operation of the engine, such as controlling the operation of the fuel injectors (if present), engine timing, turbo speed, and/or other engine parameters.

FIG. 3 provides a view of the air inlet system 10, identifying some of the parameters useful in estimating turbocharger speed. The parameters shown in FIG. 3 may be measured using the sensors identified in FIG. 2. FIG. 3 also identifies parameters useful in estimating turbocharger speed that are not directly measured, but rather are calculated using the measured parameters. Moving left to right in FIG. 3, the parameter \dot{m}_C represents an uncorrected mass flow rate, and may be measured via, for example, the mass airflow sensor 20 (see FIG. 2). The parameter $T_{C,in}$ represents a temperature of the air entering the air inlet 15 of the compressor 16, and may be measured using, for example, the inlet temperature sensor 24 (see FIG. 2). The parameter $p_{C,in}$ represents a pressure of the air entering the air inlet 15 of the compressor 16, and may be measured using, for example, the inlet pressure sensor 22 (see, FIG. 2). A corrected mass flow rate $\dot{m}_{C,Cor}$ may be calculated using the uncorrected mass flow rate \dot{m}_C , $p_{C,in}$, and $T_{C,in}$. Downstream of the charge air cooler 18 (if present), the parameter \dot{m}_T is the mass flow rate through the throttle valve 12. In some cases, the parameter \dot{m}_T is not measured, but rather is set equal to the mass flow rate \dot{m}_C discussed above.

The parameter $p_{T,out}$ represents the pressure at the outlet of the throttle valve 12 and may be measured by the MAP sensor 28. The parameter u_T represents a throttle command signal, which may provide an indication of a commanded throttle position, or perhaps an actual throttle position if different from the commanded throttle position. The throttle command signal u_T may be provided by an engine management system.

These measured parameters, along with several reference values as will be further detailed below, may be used to calculate additional parameters. For example, the parameter $p_{T,in}$, which represents the pressure at the inlet of the throttle valve 12, may be calculated. The parameter $p_{C,out}$, which represents the pressure at the air outlet 17 of the compressor 16, may in some cases be set equal to the parameter $p_{T,in}$. In some cases, these calculated parameters, and ultimately the turbocharger speed, may be determined by simultaneously or sequentially solving several equations.

For example, in some cases the following turbocharger model expressed as a continuous function may be solved to calculate the turbocharger operating speed:

$$\dot{N}_{T,Cor} = \text{SOLVE}\{\Psi P_2(\Phi, M) - P_1(\Phi, M) = 0; P_2(\Phi, M) > 0\} \quad (\text{Equation 1})$$

where P_1 and P_2 are bi-variate polynomials obtained by fitting compressor map data (often provided by the compressor manufacturer). In this equation, Φ , Ψ , and M represent the following functions:

$$\Phi = \frac{4\dot{m}_{C,Cor} R T_{C,in}^{reference}}{p_{C,in}^{reference} \pi d_C^2 U_C}$$

$$\Psi = \frac{c_p T_{C,in}^{reference} \left(\left(\frac{p_{C,out}}{p_{C,in}} \right)^{\frac{\gamma-1}{\gamma}} - 1 \right)}{1/2 U_C^2}$$

6

-continued

$$M = \frac{U_C}{\sqrt{\gamma R T_{C,in}^{reference}}}$$

In these equations, the following variables are defined, in addition to those discussed above:

$\dot{m}_{C,Cor}$ is the corrected compressor mass flow rate, which is based on an uncorrected mass flow rate \dot{m}_C that can be provided by a mass flow sensor positioned at the inlet of the compressor:

$$\dot{m}_{C,Cor} = \dot{m}_C \frac{p_{C,in}^{reference}}{p_{C,in}} \sqrt{\frac{T_{C,in}}{T_{C,in}^{reference}}}$$

$T_{C,in}^{reference}$ is a reference compressor inlet temperature that corresponds to the compressor map, and is often provided by the compressor manufacturer along with the compressor map.

$p_{C,in}^{reference}$ is a reference compressor inlet pressure that corresponds to the compressor map, and is often provided by the compressor manufacturer along with the compressor map.

U_C is (corrected) blade tip speed $\pi d_C \dot{N}_{T,Cor} / 60$, where d_C is the rotor wheel diameter.

c_p is the specific heat of dry throttle command air, which is approximately 1006 J/(kg K).

γ is the heat capacity ratio of the air, which is approximately 1.4.

R is the specific gas constant, which is approximately 287.058 J/(kg K) for the dry air.

In some cases, there may not be a pressure sensor that is positioned at the air outlet 17 of the compressor 16 to provide a value for $p_{C,out}$. Rather, in some cases, the parameter $p_{C,out}$ may be calculated using a throttle model, which solves for the parameter $p_{C,out}$. The throttle model solves for the compressor outlet pressure $p_{C,out}$ which is then used to determine the compressor speed as discussed above using the turbocharger model expressed in Equation 1. The following throttle model, expressed as a continuous function, may be solved to calculate the throttle input pressure $p_{T,in}$:

$$p_{T,in} = \text{Solve} \left\{ \dot{m}_T - \frac{C_d(u_T)}{\sqrt{R}} \Psi_T \left(\frac{p_{T,in}}{p_{T,out}} \right) \frac{p_{T,in}}{\sqrt{T_{T,in}}} = 0 \right\} \quad (\text{Equation 2})$$

where $C_d(u)$ is the throttle discharge coefficient which is modeled as a rational polynomial function of the throttle command signal u_T . Ψ_T represents the flow function valid for isentropic expansion of the fluid as follows:

$$\Psi_T = \left(\frac{p_{T,in}}{p_{T,out}} \right)^{-\frac{1}{\gamma}} \sqrt{\frac{2\gamma}{\gamma-1} \left(1 - \left(\frac{p_{T,in}}{p_{T,out}} \right)^{\frac{1-\gamma}{\gamma}} \right)}$$

In these equations, the following variables are utilized:
 \dot{m}_T is the mass flow rate through the throttle valve, which is set equal to the mass flow rate through the compres-

7

sor \dot{m}_C . As detailed above, \dot{m}_C is based on the output of a mass airflow sensor **20** positioned at the inlet of the compressor **16**.

$p_{T,in}$ is the pressure at the air inlet **11** of the throttle valve **12**, which is calculated by the throttle model (e.g. Equation 2).

The above flow function Ψ_T saturates (becomes constant) for supersonic flows, i.e. when:

$$\frac{p_{T,in}}{p_{T,out}} > \left(\frac{2}{\gamma + 1} \right)^{\frac{\gamma}{1-\gamma}}.$$

In some cases, once the throttle input pressure $p_{T,in}$ is calculated using the throttle model (e.g. via Equation 2), the throttle input pressure $p_{T,in}$ is used as the compressor outlet pressure $p_{C,out}$ when determining the compressor speed using the illustrative turbocharger model expressed in Equation 1.

FIG. 4 is a schematic diagram of a controller **30** that may be used in combination with the air inlet system of FIG. 1 to process the above-referenced parameters to calculate the turbocharger speed. In some cases, the controller **30** may be a standalone controller or computer. In some cases, the controller **30** may be manifested as a component of the aforementioned engine management system. The controller **30** may include an input port **32** and an output port **34**. A processor **36** may be operatively coupled to the input port **32** and to the output port **34**. A memory **38** may be coupled to the processor **36** and may, for example, store instructions that are executable by the processor **36** to estimate the speed of the compressor **16**. In some cases, the processor **36** may estimate the turbocharger speed within the confines of a unitary model. In some cases, the processor **36** may estimate an air pressure at an outlet of the compressor **16** using a throttle model, and estimate the turbocharger speed using the air pressure provided by the throttle model in combination with a turbocharger model.

In FIG. 5, it can be seen that there are several inputs to the input port **32**. For example, the inputs to the input port **32** may include a compressor air flow signal **40** representing a measure of air flow through the compressor **16**, a compressor air inlet pressure signal **42** representing a measure of pressure at the air inlet **15** of the compressor **16**, an intake manifold pressure signal **44** representing a measure of pressure at the air intake manifold **14**, and a throttle position signal **46** that represents the throttle position of the throttle valve **12**. In some cases, processor **36**, utilizing the throttle model (e.g. Equation 2), estimates an air pressure at the air outlet **17** of the compressor **16** referencing at least the throttle signal and the measure of pressure at the air intake manifold **14** of the engine. In some cases, the throttle model also references a measure of temperature of the air at the throttle valve **12**. In some cases, the throttle model also references a measure of air flow through the compressor **16**. In some instances, the throttle model models the effects of the charge air cooler **18**, when present. In some cases, the throttle model further references a measure of a temperature of the air in the throttle valve **12**, where the measure is taken downstream of the charge air cooler **18** and upstream of the throttle valve **12**.

In some cases, the processor **36** of the controller **30**, utilizing the turbocharger model (e.g. Equation 1), estimates the operating speed of the turbocharger referencing at least the measure of air flow through the compressor **16**, the measure of pressure at the air inlet **15** of the compressor **16**

8

and the estimated air pressure at the air outlet **17** of the compressor **16** (e.g. as estimated by the throttle model). In some cases, the turbocharger model also references a measure of temperature of the air at the air inlet **15** of the compressor **16**. In some instances, the turbocharger model further references one or more of the specific heat of air, the heat capacity of air and/or the specific gas constant of air. In some cases, the processor **36** provides, via the output port **34**, one or more control signals **48** that may be used to control an operation of the turbocharger and/or the engine in response to the estimated operating speed of the turbocharger.

FIG. 6 is a flow diagram of an illustrative method for estimating an operating speed of a turbocharger that has a compressor **16** with an air inlet **15** and an air outlet **17**. The compressor **16** feeds compressed air to a downstream throttle, such as the throttle valve **12**, which provides a throttled air flow to an air intake manifold of an engine, such as the air intake manifold **14**. As generally referenced at block **50**, the operating speed of the turbocharger may be estimated. In some cases, the estimated operating speed of the turbocharger may be based, at least in part, upon one or more of a measure of air flow through the compressor **16**, a measure of pressure at the air inlet **15** of the compressor **16**, a measure of pressure at the air intake manifold **14** of the engine, and/or a throttle signal that represents the throttle position of the throttle. As generally referenced at block **52**, operation of the turbocharger and/or the engine may be controlled in response to the estimated operating speed of the turbocharger.

In some cases, estimating the operating speed of the turbocharger as referenced at block **50** may also be based on a measure of temperature of the air at the air inlet **15** of the compressor **16**. In some cases, estimating the operating speed of the turbocharger as referenced at block **50** may also be based on a measure of temperature of the air at the throttle. In some cases, estimating the operating speed of the turbocharger as referenced at block **50** may also be based on a measure of temperature of the air at the air inlet of the compressor and a measure of temperature of the air at the throttle.

It should be understood that this disclosure is, in many respects, only illustrative. Changes may be made in details, particularly in matters of shape, size, and arrangement of steps without exceeding the scope of the disclosure. This may include, to the extent that it is appropriate, the use of any of the features of one example embodiment being used in other embodiments.

What is claimed is:

1. A controller for estimating an operating speed of a turbocharger that has a compressor with an air inlet and an air outlet, the compressor feeding compressed air to a downstream throttle that provides a throttled air flow to an air intake manifold of an engine, the controller comprising:
 - an input port for receiving:
 - a compressor air flow signal that represents a measure of air flow through the compressor;
 - a compressor air inlet pressure signal that represents a measure of pressure at the air inlet of the compressor;
 - an intake manifold pressure signal that represents a measure of pressure at the air intake manifold of the engine;
 - a throttle signal that represents the throttle position of the throttle;
 - an output port;

9

a processor operatively coupled to the input port and the output port;
 memory having instructions stored therein that are executable by the processor to:

- estimate an air pressure at the air outlet of the compressor by solving a throttle model expressed as a continuous function including a throttle discharge coefficient modeled as a rational polynomial function of the throttle command signal;
- estimate the operating speed of the turbocharger using a turbocharger model expressed as a continuous function including two bi-variate polynomials obtained by fitting compressor map data; and
- provide one or more control signals via the output port to control an operation of the turbocharger in response to the estimated operating speed of the turbocharger.

2. The controller of claim 1, wherein the turbocharger model further references a measure of temperature of the air at the air inlet of the compressor.

3. The controller of claim 1, wherein the turbocharger model further references the specific heat of air, the heat capacity ratio of air, and the specific gas constant of air.

4. The controller of claim 1, wherein the throttle model further references a measure of temperature of the air at the throttle.

5. The controller of claim 1, wherein the throttle model further references the measure of air flow through the compressor.

6. The controller of claim 1, wherein the measure of pressure at the air intake manifold of the engine is provided by a Manifold Air Pressure (MAP) sensor.

7. The controller of claim 1, wherein the measure of air flow through the compressor is provided by a flow sensor at the air inlet of the compressor.

8. The controller of claim 1, wherein the measure of pressure at the air inlet of the compressor is provided by a pressure sensor at the air inlet of the compressor.

9. The controller of claim 1, wherein:

- the throttle model references at least a current value of the throttle signal and a current value of the measure of pressure at the air intake manifold of the engine;
- estimating the air pressure at the air outlet of the compressor using the throttle model includes solving the one or more equations of the throttle model without iterating over a time variable;
- the turbocharger model reference at least a current value of the measure of air flow through the compressor, a current value of the measure of pressure at the air inlet of the compressor, and a current value of the estimated air pressure at the air outlet of the compressor; and
- estimating the operating speed of the turbocharger using the turbocharger model includes solving the one or more equations for the turbocharger model without iterating over a time variable.

10. A controller for estimating an operating speed of a turbocharger that has a compressor with an air inlet and an air outlet, the compressor feeding compressed air to a downstream throttle that provides a throttled air flow to an air intake manifold of an engine, the controller comprising:

- an input port for receiving:
 - a compressor air flow signal that represents a measure of air flow through the compressor;
 - a compressor air inlet pressure signal that represents a measure of pressure at the air inlet of the compressor;

10

- an intake manifold pressure signal that represents a measure of pressure at the air intake manifold of the engine;
- a throttle signal that represents the throttle position of the throttle;

an output port;

a processor operatively coupled to the input port and the output port;

memory having instructions stored therein that are executable by the processor to:

- estimate the operating speed of the turbocharger based at least in part on a continuous function including two bi-variate polynomials obtained by fitting compressor map data, wherein the continuous function references at least:
 - a current value of the measure of air flow through the compressor; and
 - a current value of the measure of pressure at the air inlet of the compressor; and
- provide one or more control signals via the output port to control an operation of the turbocharger and/or the engine in response to the estimated operating speed of the turbocharger.

11. The controller of claim 10, wherein estimating the operating speed of the turbocharger is also based on a measure of temperature of the air at the air inlet of the compressor.

12. The controller of claim 10, wherein estimating the operating speed of the turbocharger is also based on a measure of temperature of the air at the throttle.

13. The controller of claim 10, wherein the measure of pressure at the air intake manifold of the engine is provided by a Manifold Air Pressure (MAP) sensor.

14. The controller of claim 10, wherein the measure of air flow through the compressor is provided by a flow sensor at the air inlet of the compressor.

15. The controller of claim 10, wherein the measure of pressure at the air inlet of the compressor is provided by a pressure sensor at the air inlet of the compressor.

16. The controller of claim 10, wherein estimating the operating speed of the turbocharger includes solving the continuous function, wherein the continuous function references at least:

- a current value of the measure of pressure at the air intake manifold of the engine; and
- a current value of the throttle signal.

17. A method for estimating an operating speed of a turbocharger that has a compressor with an air inlet and an air outlet, the compressor feeding compressed air to a downstream throttle that provides a throttled air flow to an air intake manifold of an engine, the method comprising:

- estimating the operating speed of the turbocharger based at least in part on:
 - a measure of air flow through the compressor;
 - a measure of pressure at the air inlet of the compressor;
 - a measure of pressure at the air intake manifold of the engine;
 - a throttle signal that represents the throttle position of the throttle;
- wherein estimating the operating speed of the turbocharger includes solving a turbocharger model expressed as a continuous function including two bi-variate polynomials obtained by fitting compressor map data, wherein the continuous function references at least a current value of the measure of air flow

through the compressor and a current value of the
measure of pressure at the air inlet of the compressor;
and
controlling an operation of the turbocharger and/or the
engine in response to the estimated operating speed of 5
the turbocharger.

18. The method of claim **17**, wherein the estimating the
operating speed of the turbocharger is also based on a
measure of temperature of the air at the air inlet of the
compressor. 10

19. The method of claim **17**, wherein the estimated
operating speed of the turbocharger is also based on a
measure of temperature of the air at the throttle.

20. The method of claim **17**, wherein the estimated
operating speed of the turbocharger is also based on a 15
measure of temperature of the air at the air inlet of the
compressor and a measure of temperature of the air at the
throttle.

* * * * *