



US011056468B1

(12) **United States Patent**  
**Or-Bach**

(10) **Patent No.:** **US 11,056,468 B1**  
(45) **Date of Patent:** **\*Jul. 6, 2021**

(54) **3D SEMICONDUCTOR DEVICE AND STRUCTURE**

(71) Applicant: **Monolithic 3D Inc.**, Klamath Falls, OR (US)

(72) Inventor: **Zvi Or-Bach**, Haifa (IL)

(73) Assignee: **Monolithic 3D Inc.**, Klamath Falls, OR (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **17/174,344**

(22) Filed: **Feb. 11, 2021**

**Related U.S. Application Data**

(63) Continuation of application No. 17/147,989, filed on Jan. 13, 2021, which is a continuation-in-part of (Continued)

(51) **Int. Cl.**  
*H01L 23/02* (2006.01)  
*H01L 21/00* (2006.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... *H01L 25/0657* (2013.01); *H01L 23/481* (2013.01); *H01L 23/544* (2013.01);  
(Continued)

(58) **Field of Classification Search**  
CPC ..... *H01L 23/544*; *H01L 25/0657*  
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,007,090 A 10/1961 Rutz  
3,819,959 A 6/1974 Chang et al.

(Continued)

FOREIGN PATENT DOCUMENTS

EP 1267594 A2 12/2002  
WO PCT/US2008/063483 5/2008

OTHER PUBLICATIONS

Topol, A.W., et al., "Enabling SOI-Based Assembly Technology for Three-Dimensional (3D) Integrated Circuits (ICs)," IEDM Tech. Digest, Dec. 5, 2005, pp. 363-366.

(Continued)


*Primary Examiner* — Calvin Lee

(74) *Attorney, Agent, or Firm* — Patent Law Office; Bao Tran

(57) **ABSTRACT**

A 3D semiconductor device, the device including: a first die including first transistors and a first interconnect; a second die including second transistors and a second interconnect; and a third die including third transistors and a third interconnect, where the first die is overlaid by the second die, where the first die is overlaid by the third die, where the first die has a first die area and the second die has a second die area, where the first die area is at least 20% larger than the second die area, where the second die is pretested, where the second die is bonded to the first die, where the bonded includes metal to metal bonding, where the first die includes at least two first alignment marks positioned close to a first die edge of the first die, where the second die is aligned to the first die with less than 800 nm alignment error, where the second die includes at least two second alignment marks positioned close to a second die edge of the second die, and where the third die is bonded to the first die.

**14 Claims, 7 Drawing Sheets**



**Related U.S. Application Data**

application No. 17/019,162, filed on Sep. 11, 2020, now Pat. No. 10,930,608, which is a continuation-in-part of application No. 16/907,234, filed on Jun. 20, 2020, now Pat. No. 10,825,779, which is a continuation-in-part of application No. 16/450,728, filed on Jun. 24, 2019, now Pat. No. 10,777,540, which is a continuation-in-part of application No. 15/632,325, filed on Jun. 24, 2017, now Pat. No. 10,381,328, which is a continuation-in-part of application No. 15/095,187, filed on Apr. 11, 2016, now Pat. No. 9,721,927.

(60) Provisional application No. 62/149,651, filed on Apr. 19, 2015.

(51) **Int. Cl.**

*H01L 25/065* (2006.01)  
*H01L 23/00* (2006.01)  
*H01L 23/48* (2006.01)  
*H01L 23/544* (2006.01)  
*H01L 25/00* (2006.01)  
*H01L 25/18* (2006.01)

(52) **U.S. Cl.**

CPC ..... *H01L 24/08* (2013.01); *H01L 24/80* (2013.01); *H01L 25/18* (2013.01); *H01L 25/50* (2013.01); *H01L 2223/54426* (2013.01); *H01L 2224/0217* (2013.01); *H01L 2224/08145* (2013.01); *H01L 2224/8013* (2013.01); *H01L 2224/80895* (2013.01); *H01L 2224/80896* (2013.01); *H01L 2225/06541* (2013.01); *H01L 2225/06593* (2013.01); *H01L 2924/1431* (2013.01); *H01L 2924/1434* (2013.01)

(58) **Field of Classification Search**

USPC ..... 438/108, 109; 257/686  
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,009,483 A 2/1977 Clark  
 4,197,555 A 4/1980 Uehara et al.  
 4,213,139 A 7/1980 Rao et al.  
 4,400,715 A 8/1983 Barbee et al.  
 4,487,635 A 12/1984 Kugimiya et al.  
 4,510,670 A 4/1985 Schwabe  
 4,522,657 A 6/1985 Rohatgi et al.  
 4,612,083 A 9/1986 Yasumoto et al.  
 4,643,950 A 2/1987 Ogura et al.  
 4,704,785 A 11/1987 Curran  
 4,711,858 A 12/1987 Harder et al.  
 4,721,885 A 1/1988 Brodie  
 4,732,312 A 3/1988 Kennedy et al.  
 4,733,288 A 3/1988 Sato  
 4,829,018 A 5/1989 Wahlstrom  
 4,854,986 A 8/1989 Raby  
 4,866,304 A 9/1989 Yu  
 4,939,568 A 7/1990 Kato et al.  
 4,956,307 A 9/1990 Pollack et al.  
 5,012,153 A 4/1991 Atkinson et al.  
 5,032,007 A 7/1991 Silverstein et al.  
 5,047,979 A 9/1991 Leung  
 5,087,585 A 2/1992 Hayashi  
 5,093,704 A 3/1992 Sato et al.  
 5,106,775 A 4/1992 Kaga et al.  
 5,152,857 A 10/1992 Ito et al.  
 5,162,879 A 11/1992 Gill  
 5,189,500 A 2/1993 Kusunoki  
 5,217,916 A 6/1993 Anderson et al.  
 5,250,460 A 10/1993 Yamagata et al.

5,258,643 A 11/1993 Cohen  
 5,265,047 A 11/1993 Leung et al.  
 5,266,511 A 11/1993 Takao  
 5,277,748 A 1/1994 Sakaguchi et al.  
 5,286,670 A 2/1994 Kang et al.  
 5,294,556 A 3/1994 Kawamura  
 5,308,782 A 5/1994 Mazure et al.  
 5,312,771 A 5/1994 Yonehara  
 5,317,236 A 5/1994 Zavracky et al.  
 5,324,980 A 6/1994 Kusunoki  
 5,355,022 A 10/1994 Sugahara et al.  
 5,371,037 A 12/1994 Yonehara  
 5,374,564 A 12/1994 Bruel  
 5,374,581 A 12/1994 Ichikawa et al.  
 5,424,560 A 6/1995 Norman et al.  
 5,475,280 A 12/1995 Jones et al.  
 5,478,762 A 12/1995 Chao  
 5,485,031 A 1/1996 Zhang et al.  
 5,498,978 A 3/1996 Takahashi et al.  
 5,527,423 A 6/1996 Neville et al.  
 5,535,342 A 7/1996 Taylor  
 5,554,870 A 9/1996 Fitch et al.  
 5,563,084 A 10/1996 Ramm et al.  
 5,583,349 A 12/1996 Norman et al.  
 5,583,350 A 12/1996 Norman et al.  
 5,586,291 A 12/1996 Lasker  
 5,594,563 A 1/1997 Larson  
 5,604,137 A 2/1997 Yamazaki et al.  
 5,617,991 A 4/1997 Pramanick et al.  
 5,627,106 A 5/1997 Hsu  
 5,656,548 A 8/1997 Zavracky et al.  
 5,656,553 A 8/1997 Leas et al.  
 5,659,194 A 8/1997 Iwamatsu  
 5,670,411 A 9/1997 Yonehara  
 5,681,756 A 10/1997 Norman et al.  
 5,695,557 A 12/1997 Yamagata et al.  
 5,701,027 A 12/1997 Gordon et al.  
 5,707,745 A 1/1998 Forrest et al.  
 5,714,395 A 2/1998 Bruel  
 5,721,160 A 2/1998 Forrest et al.  
 5,737,748 A 4/1998 Shigeeda  
 5,739,552 A 4/1998 Kimura et al.  
 5,744,979 A 4/1998 Goetting  
 5,748,161 A 5/1998 Lebby et al.  
 5,757,026 A 5/1998 Forrest et al.  
 5,770,483 A 6/1998 Kadosh  
 5,770,881 A 6/1998 Pelella et al.  
 5,781,031 A 7/1998 Bertin et al.  
 5,817,574 A 10/1998 Gardner  
 5,829,026 A 10/1998 Leung et al.  
 5,835,396 A 11/1998 Zhang  
 5,854,123 A 12/1998 Sato et al.  
 5,861,929 A 1/1999 Spitzer  
 5,877,034 A 3/1999 Ramm  
 5,877,070 A 3/1999 Goesele et al.  
 5,882,987 A 3/1999 Srikrishnan  
 5,883,525 A 3/1999 Tavana et al.  
 5,889,903 A 3/1999 Rao  
 5,893,721 A 4/1999 Huang et al.  
 5,915,167 A 6/1999 Leedy  
 5,920,788 A 7/1999 Reinberg  
 5,937,312 A 8/1999 Iyer et al.  
 5,943,574 A 8/1999 Tehrani et al.  
 5,952,680 A 9/1999 Strite  
 5,952,681 A 9/1999 Chen  
 5,965,875 A 10/1999 Merrill  
 5,977,579 A 11/1999 Noble  
 5,977,961 A 11/1999 Rindal  
 5,980,633 A 11/1999 Yamagata et al.  
 5,985,742 A 11/1999 Henley et al.  
 5,994,746 A 11/1999 Reisinger  
 5,998,808 A 12/1999 Matsushita  
 6,001,693 A 12/1999 Yeouchung et al.  
 6,009,496 A 12/1999 Tsai  
 6,020,252 A 2/2000 Aspar et al.  
 6,020,263 A 2/2000 Shih et al.  
 6,027,958 A 2/2000 Vu et al.  
 6,030,700 A 2/2000 Forrest et al.  
 6,052,498 A 4/2000 Panicia



(56)

References Cited

U.S. PATENT DOCUMENTS

|                |         |                             |                |         |                           |
|----------------|---------|-----------------------------|----------------|---------|---------------------------|
| 7,265,421 B2   | 9/2007  | Madurawe                    | 7,674,687 B2   | 3/2010  | Henley                    |
| 7,271,420 B2   | 9/2007  | Cao                         | 7,687,372 B2   | 3/2010  | Jain                      |
| 7,274,207 B2   | 9/2007  | Sugawara et al.             | 7,687,872 B2   | 3/2010  | Cazaux                    |
| 7,282,951 B2   | 10/2007 | Huppenthal et al.           | 7,688,619 B2   | 3/2010  | Lung et al.               |
| 7,284,226 B1   | 10/2007 | Kondapalli                  | 7,692,202 B2   | 4/2010  | Bensch                    |
| 7,296,201 B2   | 11/2007 | Abramovici                  | 7,692,448 B2   | 4/2010  | Solomon                   |
| 7,304,355 B2   | 12/2007 | Zhang                       | 7,692,944 B2   | 4/2010  | Bernstein et al.          |
| 7,312,109 B2   | 12/2007 | Madurawe                    | 7,697,316 B2   | 4/2010  | Lai et al.                |
| 7,312,487 B2   | 12/2007 | Alam et al.                 | 7,709,932 B2   | 5/2010  | Nemoto et al.             |
| 7,314,788 B2   | 1/2008  | Shaw                        | 7,718,508 B2   | 5/2010  | Lee                       |
| 7,335,573 B2   | 2/2008  | Takayama et al.             | 7,719,876 B2   | 5/2010  | Chevallier                |
| 7,337,425 B2   | 2/2008  | Kirk                        | 7,723,207 B2   | 5/2010  | Alam et al.               |
| 7,338,884 B2   | 3/2008  | Shimoto et al.              | 7,728,326 B2   | 6/2010  | Yamazaki et al.           |
| 7,342,415 B2   | 3/2008  | Teig et al.                 | 7,732,301 B1   | 6/2010  | Pinnington et al.         |
| 7,351,644 B2   | 4/2008  | Henley                      | 7,741,673 B2   | 6/2010  | Tak et al.                |
| 7,358,601 B1   | 4/2008  | Plants et al.               | 7,742,331 B2   | 6/2010  | Watanabe                  |
| 7,362,133 B2   | 4/2008  | Madurawe                    | 7,745,250 B2   | 6/2010  | Han                       |
| 7,369,213 B2 * | 5/2008  | Noudo ..... B82Y 10/00      | 7,749,884 B2   | 7/2010  | Mathew et al.             |
|                |         | 355/53                      | 7,750,669 B2   | 7/2010  | Spangaro                  |
| 7,369,435 B2   | 5/2008  | Forbes                      | 7,755,622 B2   | 7/2010  | Yvon                      |
| 7,371,660 B2   | 5/2008  | Henley et al.               | 7,759,043 B2   | 7/2010  | Tanabe et al.             |
| 7,378,702 B2   | 5/2008  | Lee                         | 7,768,115 B2   | 8/2010  | Lee et al.                |
| 7,381,989 B2   | 6/2008  | Kim                         | 7,772,039 B2   | 8/2010  | Kerber                    |
| 7,385,283 B2   | 6/2008  | Wu                          | 7,772,096 B2   | 8/2010  | DeSouza et al.            |
| 7,393,722 B1   | 7/2008  | Issaq et al.                | 7,774,735 B1   | 8/2010  | Sood                      |
| 7,402,483 B2   | 7/2008  | Yu et al.                   | 7,776,715 B2   | 8/2010  | Wells et al.              |
| 7,402,897 B2   | 7/2008  | Leedy                       | 7,777,330 B2   | 8/2010  | Pelley et al.             |
| 7,419,844 B2   | 9/2008  | Lee et al.                  | 7,786,460 B2   | 8/2010  | Lung et al.               |
| 7,432,185 B2   | 10/2008 | Kim                         | 7,786,535 B2   | 8/2010  | Abou-Khalil et al.        |
| 7,436,027 B2   | 10/2008 | Ogawa et al.                | 7,790,524 B2   | 9/2010  | Abadeer et al.            |
| 7,439,773 B2   | 10/2008 | Or-Bach et al.              | 7,795,619 B2   | 9/2010  | Hara                      |
| 7,446,563 B2   | 11/2008 | Madurawe                    | 7,799,675 B2   | 9/2010  | Lee                       |
| 7,459,752 B2   | 12/2008 | Doris et al.                | 7,800,099 B2   | 9/2010  | Yamazaki et al.           |
| 7,459,763 B1   | 12/2008 | Issaq et al.                | 7,800,148 B2   | 9/2010  | Lee et al.                |
| 7,459,772 B2   | 12/2008 | Speers                      | 7,800,163 B2   | 9/2010  | Izumi et al.              |
| 7,463,062 B2   | 12/2008 | Or-Bach et al.              | 7,800,199 B2   | 9/2010  | Oh et al.                 |
| 7,463,502 B2   | 12/2008 | Stipe                       | 7,816,721 B2   | 10/2010 | Yamazaki                  |
| 7,470,142 B2   | 12/2008 | Lee                         | 7,843,718 B2   | 11/2010 | Koh et al.                |
| 7,470,598 B2   | 12/2008 | Lee                         | 7,846,814 B2   | 12/2010 | Lee                       |
| 7,476,939 B2   | 1/2009  | Okhonin et al.              | 7,863,095 B2 * | 1/2011  | Sasaki ..... H01L 21/6835 |
| 7,477,540 B2   | 1/2009  | Okhonin et al.              |                |         | 438/107                   |
| 7,485,968 B2   | 2/2009  | Enquist et al.              | 7,864,568 B2   | 1/2011  | Fujisaki et al.           |
| 7,486,563 B2   | 2/2009  | Waller et al.               | 7,867,822 B2   | 1/2011  | Lee                       |
| 7,488,980 B2   | 2/2009  | Takafuji et al.             | 7,888,764 B2   | 2/2011  | Lee                       |
| 7,492,632 B2   | 2/2009  | Carman                      | 7,910,432 B2   | 3/2011  | Tanaka et al.             |
| 7,495,473 B2   | 2/2009  | McCollum et al.             | 7,915,164 B2   | 3/2011  | Konevecki et al.          |
| 7,498,675 B2   | 3/2009  | Farnworth et al.            | 7,919,845 B2   | 4/2011  | Karp                      |
| 7,499,352 B2   | 3/2009  | Singh                       | 7,965,102 B1   | 6/2011  | Bauer et al.              |
| 7,499,358 B2   | 3/2009  | Bauser                      | 7,968,965 B2   | 6/2011  | Kim                       |
| 7,508,034 B2   | 3/2009  | Takafuji et al.             | 7,969,193 B1   | 6/2011  | Wu et al.                 |
| 7,514,748 B2   | 4/2009  | Fazan et al.                | 7,973,314 B2   | 7/2011  | Yang                      |
| 7,521,806 B2   | 4/2009  | Trezza                      | 7,982,250 B2   | 7/2011  | Yamazaki et al.           |
| 7,525,186 B2   | 4/2009  | Kim et al.                  | 7,983,065 B2   | 7/2011  | Samachisa                 |
| 7,535,089 B2   | 5/2009  | Fitzgerald                  | 8,008,732 B2   | 8/2011  | Kiyotoshi                 |
| 7,541,616 B2   | 6/2009  | Fazan et al.                | 8,013,399 B2   | 9/2011  | Thomas et al.             |
| 7,547,589 B2 * | 6/2009  | Iriguchi ..... H01L 27/1214 | 8,014,166 B2   | 9/2011  | Yazdani                   |
|                |         | 438/149                     | 8,014,195 B2   | 9/2011  | Okhonin et al.            |
| 7,553,745 B2   | 6/2009  | Lim                         | 8,022,493 B2   | 9/2011  | Bang                      |
| 7,557,367 B2   | 7/2009  | Rogers et al.               | 8,030,780 B2   | 10/2011 | Kirby et al.              |
| 7,558,141 B2   | 7/2009  | Katsumata et al.            | 8,031,544 B2   | 10/2011 | Kim et al.                |
| 7,563,659 B2   | 7/2009  | Kwon et al.                 | 8,032,857 B2   | 10/2011 | McIlrath                  |
| 7,566,855 B2   | 7/2009  | Olsen et al.                | 8,044,448 B2   | 10/2011 | Kamigaichi et al.         |
| 7,566,974 B2   | 7/2009  | Konevecki                   | 8,044,464 B2   | 10/2011 | Yamazaki et al.           |
| 7,586,778 B2   | 9/2009  | Ho et al.                   | 8,068,364 B2   | 11/2011 | Maejima                   |
| 7,589,375 B2   | 9/2009  | Jang et al.                 | 8,106,520 B2   | 1/2012  | Keeth et al.              |
| 7,608,848 B2   | 10/2009 | Ho et al.                   | 8,107,276 B2   | 1/2012  | Breitwisch et al.         |
| 7,612,411 B2   | 11/2009 | Walker                      | 8,129,256 B2   | 3/2012  | Farooq et al.             |
| 7,615,462 B2   | 11/2009 | Kim et al.                  | 8,129,258 B2   | 3/2012  | Hosier et al.             |
| 7,622,367 B1   | 11/2009 | Nuzzo et al.                | 8,130,547 B2   | 3/2012  | Widjaja et al.            |
| 7,632,738 B2   | 12/2009 | Lee                         | 8,136,071 B2   | 3/2012  | Solomon                   |
| 7,633,162 B2   | 12/2009 | Lee                         | 8,138,502 B2   | 3/2012  | Nakamura et al.           |
| 7,666,723 B2   | 2/2010  | Frank et al.                | 8,153,520 B1   | 4/2012  | Chandrashekar             |
| 7,670,912 B2   | 3/2010  | Yeo                         | 8,158,515 B2   | 4/2012  | Farooq et al.             |
| 7,671,371 B2   | 3/2010  | Lee                         | 8,178,919 B2   | 5/2012  | Fujiwara et al.           |
| 7,671,460 B2   | 3/2010  | Lauxtermann et al.          | 8,183,630 B2   | 5/2012  | Batude et al.             |
|                |         |                             | 8,184,463 B2   | 5/2012  | Saen et al.               |
|                |         |                             | 8,185,685 B2   | 5/2012  | Selinger                  |
|                |         |                             | 8,203,187 B2   | 6/2012  | Lung et al.               |
|                |         |                             | 8,208,279 B2   | 6/2012  | Lue                       |

(56)

## References Cited

## U.S. PATENT DOCUMENTS

|                 |         |                   |                         |                 |         |                   |
|-----------------|---------|-------------------|-------------------------|-----------------|---------|-------------------|
| 8,209,649 B2    | 6/2012  | McIlrath          |                         | 2002/0074668 A1 | 6/2002  | Hofstee et al.    |
| 8,228,684 B2    | 7/2012  | Losavio et al.    |                         | 2002/0081823 A1 | 6/2002  | Cheung et al.     |
| 8,264,065 B2    | 9/2012  | Su et al.         |                         | 2002/0090758 A1 | 7/2002  | Henley et al.     |
| 8,266,560 B2    | 9/2012  | McIlrath          |                         | 2002/0096681 A1 | 7/2002  | Yamazaki et al.   |
| 8,288,816 B2    | 10/2012 | Komori et al.     |                         | 2002/0113289 A1 | 8/2002  | Cordes et al.     |
| 8,294,199 B2    | 10/2012 | Yahashi et al.    |                         | 2002/0132465 A1 | 9/2002  | Leedy             |
| 8,324,680 B2    | 12/2012 | Izumi et al.      |                         | 2002/0140091 A1 | 10/2002 | Callahan          |
| 8,338,882 B2    | 12/2012 | Tanaka et al.     |                         | 2002/0141233 A1 | 10/2002 | Hosotani et al.   |
| 8,343,851 B2    | 1/2013  | Kim et al.        |                         | 2002/0153243 A1 | 10/2002 | Forrest et al.    |
| 8,354,308 B2    | 1/2013  | Kang et al.       |                         | 2002/0153569 A1 | 10/2002 | Katayama          |
| 8,355,273 B2    | 1/2013  | Liu               |                         | 2002/0175401 A1 | 11/2002 | Huang et al.      |
| 8,374,033 B2    | 2/2013  | Kito et al.       |                         | 2002/0180069 A1 | 12/2002 | Houston           |
| 8,426,294 B2    | 4/2013  | Lung et al.       |                         | 2002/0190232 A1 | 12/2002 | Chason            |
| 8,432,719 B2    | 4/2013  | Lue               |                         | 2002/0199110 A1 | 12/2002 | Kean              |
| 8,432,751 B2    | 4/2013  | Hafez             |                         | 2003/0015713 A1 | 1/2003  | Yoo               |
| 8,455,941 B2    | 6/2013  | Ishihara et al.   |                         | 2003/0032262 A1 | 2/2003  | Dennison et al.   |
| 8,470,689 B2    | 6/2013  | Desplobain et al. |                         | 2003/0059999 A1 | 3/2003  | Gonzalez          |
| 8,497,512 B2    | 7/2013  | Nakamura et al.   |                         | 2003/0060034 A1 | 3/2003  | Beyne et al.      |
| 8,501,564 B2    | 8/2013  | Suzawa            |                         | 2003/0061555 A1 | 3/2003  | Kamei             |
| 8,507,972 B2    | 8/2013  | Oota et al.       |                         | 2003/0067043 A1 | 4/2003  | Zhang             |
| 8,508,994 B2    | 8/2013  | Okhonin           |                         | 2003/0076706 A1 | 4/2003  | Andoh             |
| 8,513,725 B2    | 8/2013  | Sakuma et al.     |                         | 2003/0102079 A1 | 6/2003  | Kalvesten et al.  |
| 8,514,623 B2    | 8/2013  | Widjaja et al.    |                         | 2003/0107117 A1 | 6/2003  | Antonelli et al.  |
| 8,516,408 B2    | 8/2013  | Dell              |                         | 2003/0113963 A1 | 6/2003  | Wurzer            |
| 8,536,572 B2 *  | 9/2013  | Chen .....        | H01L 24/81<br>257/48    | 2003/0119279 A1 | 6/2003  | Enquist           |
| 8,525,342 B2    | 10/2013 | Chandrasekaran    |                         | 2003/0139011 A1 | 7/2003  | Cleeves et al.    |
| 8,546,956 B2    | 10/2013 | Nguyen            |                         | 2003/0153163 A1 | 8/2003  | Letertre          |
| 8,566,762 B2    | 10/2013 | Morimoto et al.   |                         | 2003/0157748 A1 | 8/2003  | Kim et al.        |
| 8,603,888 B2    | 12/2013 | Liu               |                         | 2003/0160888 A1 | 8/2003  | Yoshikawa         |
| 8,611,388 B2    | 12/2013 | Krasulick et al.  |                         | 2003/0173631 A1 | 9/2003  | Murakami          |
| 8,619,490 B2    | 12/2013 | Yu                |                         | 2003/0206036 A1 | 11/2003 | Or-Bach           |
| 8,630,326 B2    | 1/2014  | Krasulick et al.  |                         | 2003/0213967 A1 | 11/2003 | Forrest et al.    |
| 8,643,162 B2    | 2/2014  | Madurawe          |                         | 2003/0224582 A1 | 12/2003 | Shimoda et al.    |
| 8,650,516 B2    | 2/2014  | McIlrath          |                         | 2003/0224596 A1 | 12/2003 | Marxsen et al.    |
| 8,654,584 B2    | 2/2014  | Kim et al.        |                         | 2004/0007376 A1 | 1/2004  | Urdahl et al.     |
| 8,679,861 B2    | 3/2014  | Bose              |                         | 2004/0014299 A1 | 1/2004  | Moriceau et al.   |
| 8,736,068 B2    | 5/2014  | Bartley et al.    |                         | 2004/0033676 A1 | 2/2004  | Coronel et al.    |
| 8,773,562 B1    | 7/2014  | Fan               |                         | 2004/0036126 A1 | 2/2004  | Chau et al.       |
| 8,775,998 B2    | 7/2014  | Morimoto          |                         | 2004/0047539 A1 | 3/2004  | Okubora et al.    |
| 8,824,183 B2    | 9/2014  | Samachisa et al.  |                         | 2004/0061176 A1 | 4/2004  | Takafuji et al.   |
| 8,841,777 B2    | 9/2014  | Farooq            |                         | 2004/0113207 A1 | 6/2004  | Hsu et al.        |
| 8,853,785 B2    | 10/2014 | Augendre          |                         | 2004/0143797 A1 | 7/2004  | Nguyen            |
| 8,896,054 B2    | 11/2014 | Sakuma et al.     |                         | 2004/0150068 A1 | 8/2004  | Leedy             |
| 8,928,119 B2    | 1/2015  | Leedy             |                         | 2004/0150070 A1 | 8/2004  | Okada             |
| 8,971,114 B2    | 3/2015  | Kang              |                         | 2004/0152272 A1 | 8/2004  | Fladre et al.     |
| 9,105,689 B1    | 8/2015  | Fanelli           |                         | 2004/0155301 A1 | 8/2004  | Zhang             |
| 9,172,008 B2    | 10/2015 | Hwang             |                         | 2004/0156172 A1 | 8/2004  | Lin et al.        |
| 9,227,456 B2    | 1/2016  | Chien             |                         | 2004/0156233 A1 | 8/2004  | Bhattacharyya     |
| 9,230,973 B2    | 1/2016  | Pachamuthu et al. |                         | 2004/0164425 A1 | 8/2004  | Urakawa           |
| 9,269,608 B2    | 2/2016  | Fanelli           |                         | 2004/0166649 A1 | 8/2004  | Bressot et al.    |
| 9,334,582 B2    | 5/2016  | See               |                         | 2004/0174732 A1 | 9/2004  | Morimoto          |
| 9,391,090 B2    | 7/2016  | Manorotkul et al. |                         | 2004/0175902 A1 | 9/2004  | Rayssac et al.    |
| 9,472,568 B2    | 10/2016 | Shin et al.       |                         | 2004/0178819 A1 | 9/2004  | New               |
| 9,564,450 B2    | 2/2017  | Sakuma et al.     |                         | 2004/0195572 A1 | 10/2004 | Kato et al.       |
| 9,570,683 B1    | 2/2017  | Jo                |                         | 2004/0219765 A1 | 11/2004 | Reif et al.       |
| 9,589,982 B1    | 3/2017  | Cheng et al.      |                         | 2004/0229444 A1 | 11/2004 | Couillard         |
| 9,595,530 B1    | 3/2017  | Zhou              |                         | 2004/0259312 A1 | 12/2004 | Schlosser et al.  |
| 9,627,287 B2    | 4/2017  | Engelhardt et al. |                         | 2004/0262635 A1 | 12/2004 | Lee               |
| 9,673,257 B1    | 6/2017  | Takaki            |                         | 2004/0262772 A1 | 12/2004 | Ramanathan et al. |
| 9,721,927 B1 *  | 8/2017  | Or-Bach .....     | H01L 27/0688<br>257/686 | 2005/0003592 A1 | 1/2005  | Jones             |
| 9,997,530 B2    | 6/2018  | Yon et al.        |                         | 2005/0010725 A1 | 1/2005  | Eilert            |
| 10,199,354 B2   | 2/2019  | Modi et al.       |                         | 2005/0023656 A1 | 2/2005  | Leedy             |
| 10,381,328 B2 * | 8/2019  | Or-Bach .....     | H01L 25/0652<br>438/109 | 2005/0045919 A1 | 3/2005  | Kaeriyama et al.  |
| 10,629,510 B2 * | 4/2020  | Hung .....        | H01L 25/50              | 2005/0067620 A1 | 3/2005  | Chan et al.       |
| 10,777,540 B2 * | 9/2020  | Or-Bach .....     | H01L 25/0652            | 2005/0067625 A1 | 3/2005  | Hata              |
| 10,825,779 B2 * | 11/2020 | Or-Bach .....     | H01L 25/50              | 2005/0073060 A1 | 4/2005  | Datta et al.      |
| 10,930,608 B2 * | 2/2021  | Or-Bach .....     | H01L 25/18              | 2005/0082526 A1 | 4/2005  | Bedell et al.     |
| 2001/0000005 A1 | 3/2001  | Forrest et al.    |                         | 2005/0098822 A1 | 5/2005  | Mathew            |
| 2001/0014391 A1 | 8/2001  | Forrest et al.    |                         | 2005/0110041 A1 | 5/2005  | Boutros et al.    |
| 2001/0028059 A1 | 10/2001 | Emma et al.       |                         | 2005/0121676 A1 | 6/2005  | Fried et al.      |
| 2002/0024140 A1 | 2/2002  | Nakajima et al.   |                         | 2005/0121789 A1 | 6/2005  | Madurawe          |
| 2002/0025604 A1 | 2/2002  | Tiwari            |                         | 2005/0130351 A1 | 6/2005  | Leedy             |
|                 |         |                   |                         | 2005/0130429 A1 | 6/2005  | Rayssac et al.    |
|                 |         |                   |                         | 2005/0148137 A1 | 7/2005  | Brask et al.      |
|                 |         |                   |                         | 2005/0176174 A1 | 8/2005  | Leedy             |
|                 |         |                   |                         | 2005/0218521 A1 | 10/2005 | Lee               |
|                 |         |                   |                         | 2005/0225237 A1 | 10/2005 | Winters           |
|                 |         |                   |                         | 2005/0266659 A1 | 12/2005 | Ghyselen et al.   |
|                 |         |                   |                         | 2005/0273749 A1 | 12/2005 | Kirk              |



(56)

**References Cited**

## U.S. PATENT DOCUMENTS

- 2009/0087759 A1 4/2009 Matsumoto et al.  
 2009/0096009 A1 4/2009 Dong et al.  
 2009/0096024 A1 4/2009 Shingu et al.  
 2009/0108318 A1 4/2009 Yoon et al.  
 2009/0115042 A1 5/2009 Koyanagi  
 2009/0128189 A1 5/2009 Madurawe et al.  
 2009/0134397 A1 5/2009 Yokoi et al.  
 2009/0144669 A1 6/2009 Bose et al.  
 2009/0144678 A1 6/2009 Bose et al.  
 2009/0146172 A1 6/2009 Pumyea  
 2009/0159870 A1 6/2009 Lin et al.  
 2009/0160482 A1 6/2009 Karp et al.  
 2009/0161401 A1 6/2009 Bigler et al.  
 2009/0162993 A1 6/2009 Yui et al.  
 2009/0166627 A1 7/2009 Han  
 2009/0174018 A1 7/2009 Dungan  
 2009/0179268 A1 7/2009 Abou-Khalil et al.  
 2009/0185407 A1 7/2009 Park  
 2009/0194152 A1 8/2009 Liu et al.  
 2009/0194768 A1 8/2009 Leedy  
 2009/0194829 A1 8/2009 Chung  
 2009/0194836 A1 8/2009 Kim  
 2009/0204933 A1 8/2009 Rezgui  
 2009/0212317 A1 8/2009 Kolodin et al.  
 2009/0218627 A1 9/2009 Zhu  
 2009/0221110 A1 9/2009 Lee et al.  
 2009/0224330 A1 9/2009 Hong  
 2009/0224364 A1 9/2009 Oh et al.  
 2009/0230462 A1 9/2009 Tanaka et al.  
 2009/0234331 A1 9/2009 Langereis et al.  
 2009/0236749 A1 9/2009 Otemba et al.  
 2009/0242893 A1 10/2009 Tomiyasu  
 2009/0242935 A1 10/2009 Fitzgerald  
 2009/0250686 A1 10/2009 Sato et al.  
 2009/0262572 A1 10/2009 Krusin-Elbaum  
 2009/0262583 A1 10/2009 Lue  
 2009/0263942 A1 10/2009 Ohnuma et al.  
 2009/0267233 A1 10/2009 Lee  
 2009/0268983 A1 10/2009 Stone et al.  
 2009/0272989 A1 11/2009 Shum et al.  
 2009/0290434 A1 11/2009 Kurjanowicz  
 2009/0294822 A1 12/2009 Batude et al.  
 2009/0294836 A1 12/2009 Kiyotoshi  
 2009/0294861 A1 12/2009 Thomas et al.  
 2009/0294990 A1 12/2009 Ishino et al.  
 2009/0302294 A1 12/2009 Kim  
 2009/0302387 A1 12/2009 Joshi et al.  
 2009/0302394 A1 12/2009 Fujita  
 2009/0309152 A1 12/2009 Knoefler et al.  
 2009/0315095 A1 12/2009 Kim  
 2009/0317950 A1 12/2009 Okihara  
 2009/0321830 A1 12/2009 Maly  
 2009/0321853 A1 12/2009 Cheng  
 2009/0321948 A1 12/2009 Wang et al.  
 2009/0325343 A1 12/2009 Lee  
 2010/0001282 A1 1/2010 Mieno  
 2010/0013049 A1 1/2010 Tanaka  
 2010/0025766 A1 2/2010 Nuttinck et al.  
 2010/0025825 A1 2/2010 DeGraw et al.  
 2010/0031217 A1 2/2010 Sinha et al.  
 2010/0032635 A1 2/2010 Schwerin U  
 2010/0038699 A1 2/2010 Katsumata et al.  
 2010/0038743 A1 2/2010 Lee  
 2010/0045849 A1 2/2010 Yamasaki  
 2010/0052134 A1 3/2010 Werner et al.  
 2010/0058580 A1 3/2010 Yazdani  
 2010/0059796 A1 3/2010 Scheuerlein  
 2010/0059864 A1 3/2010 Mahler et al.  
 2010/0078770 A1 4/2010 Purushothaman et al.  
 2010/0081232 A1 4/2010 Furman et al.  
 2010/0089627 A1 4/2010 Huang et al.  
 2010/0090188 A1 4/2010 Fatasuyama  
 2010/0112753 A1 5/2010 Lee  
 2010/0112810 A1 5/2010 Lee et al.  
 2010/0117048 A1 5/2010 Lung et al.  
 2010/0123202 A1 5/2010 Hofmann  
 2010/0123480 A1 5/2010 Kitada et al.  
 2010/0133695 A1 6/2010 Lee  
 2010/0133704 A1 6/2010 Marimuthu et al.  
 2010/0137143 A1 6/2010 Rothberg et al.  
 2010/0139836 A1 6/2010 Horikoshi  
 2010/0140790 A1 6/2010 Setiadi et al.  
 2010/0155932 A1 6/2010 Gambino  
 2010/0157117 A1 6/2010 Wang  
 2010/0159650 A1 6/2010 Song  
 2010/0181600 A1 7/2010 Law  
 2010/0190334 A1 7/2010 Lee  
 2010/0193884 A1 8/2010 Park et al.  
 2010/0193964 A1 8/2010 Farooq et al.  
 2010/0219392 A1 9/2010 Awaya  
 2010/0221867 A1 9/2010 Bedell et al.  
 2010/0224876 A1 9/2010 Zhu  
 2010/0224915 A1 9/2010 Kawashima et al.  
 2010/0225002 A1 9/2010 Law et al.  
 2010/0232200 A1 9/2010 Shepard  
 2010/0252934 A1 10/2010 Law  
 2010/0264551 A1 10/2010 Farooq  
 2010/0276662 A1 11/2010 Colinge  
 2010/0289144 A1 11/2010 Farooq  
 2010/0297844 A1 11/2010 Yelehanka  
 2010/0307572 A1 12/2010 Bedell et al.  
 2010/0308211 A1 12/2010 Cho et al.  
 2010/0308863 A1 12/2010 Gliese et al.  
 2010/0320514 A1 12/2010 Tredwell  
 2010/0320526 A1 12/2010 Kidoh et al.  
 2010/0330728 A1 12/2010 McCarten  
 2010/0330752 A1 12/2010 Jeong  
 2011/0001172 A1 1/2011 Lee  
 2011/0003438 A1 1/2011 Lee  
 2011/0024724 A1 2/2011 Frolov et al.  
 2011/0026263 A1 2/2011 Xu  
 2011/0027967 A1 2/2011 Beyne  
 2011/0037052 A1 2/2011 Schmidt et al.  
 2011/0042696 A1 2/2011 Smith et al.  
 2011/0049336 A1 3/2011 Matsunuma  
 2011/0050125 A1 3/2011 Medendorp et al.  
 2011/0053332 A1 3/2011 Lee  
 2011/0101537 A1 5/2011 Barth et al.  
 2011/0102014 A1 5/2011 Madurawe  
 2011/0111560 A1 5/2011 Purushothaman  
 2011/0115023 A1 5/2011 Cheng  
 2011/0128777 A1 6/2011 Yamazaki  
 2011/0134683 A1 6/2011 Yamazaki  
 2011/0143506 A1 6/2011 Lee  
 2011/0147791 A1 6/2011 Norman et al.  
 2011/0147849 A1 6/2011 Augendre et al.  
 2011/0159635 A1 6/2011 Doan et al.  
 2011/0170331 A1 7/2011 Oh  
 2011/0204917 A1 8/2011 O'Neill  
 2011/0221022 A1 9/2011 Toda  
 2011/0222356 A1 9/2011 Banna  
 2011/0227158 A1 9/2011 Zhu  
 2011/0241082 A1 10/2011 Bernstein et al.  
 2011/0284946 A1 11/2011 Kiyotoshi  
 2011/0284992 A1 11/2011 Zhu  
 2011/0286283 A1 11/2011 Lung et al.  
 2011/0304765 A1 12/2011 Yogo et al.  
 2011/0309432 A1 12/2011 Ishihara et al.  
 2011/0314437 A1 12/2011 McIlrath  
 2012/0001184 A1 1/2012 Ha et al.  
 2012/0003815 A1 1/2012 Lee  
 2012/0013013 A1 1/2012 Sadaka et al.  
 2012/0025388 A1 2/2012 Law et al.  
 2012/0032250 A1 2/2012 Son et al.  
 2012/0034759 A1 2/2012 Sakaguchi et al.  
 2012/0063090 A1 3/2012 Hsiao et al.  
 2012/0074466 A1 3/2012 Setiadi et al.  
 2012/0086100 A1 4/2012 Andry  
 2012/0126197 A1 5/2012 Chung  
 2012/0146193 A1 6/2012 Stuber et al.  
 2012/0161310 A1 6/2012 Brindle et al.  
 2012/0169319 A1 7/2012 Dennard  
 2012/0178211 A1 7/2012 Hebert  
 2012/0181654 A1 7/2012 Lue

(56)

## References Cited

## U.S. PATENT DOCUMENTS

2012/0182801 A1 7/2012 Lue  
 2012/0187444 A1 7/2012 Oh  
 2012/0193785 A1 8/2012 Lin  
 2012/0241919 A1 9/2012 Mitani  
 2012/0286822 A1 11/2012 Madurawe  
 2012/0304142 A1 11/2012 Morimoto  
 2012/0317528 A1 12/2012 McIlrath  
 2012/0319728 A1 12/2012 Madurawe  
 2013/0026663 A1 1/2013 Radu et al.  
 2013/0037802 A1 2/2013 England  
 2013/0049796 A1 2/2013 Pang  
 2013/0070506 A1 3/2013 Kajigaya  
 2013/0082235 A1 4/2013 Gu et al.  
 2013/0097574 A1 4/2013 Balabanov et al.  
 2013/0100743 A1 4/2013 Lue  
 2013/0128666 A1 5/2013 Avila  
 2013/0187720 A1 7/2013 Ishii  
 2013/0193550 A1 8/2013 Sklenard et al.  
 2013/0196500 A1 8/2013 Batude et al.  
 2013/0203248 A1 8/2013 Ernst et al.  
 2013/0207243 A1 8/2013 Fuergut  
 2013/0263393 A1 10/2013 Mazumder  
 2013/0337601 A1 12/2013 Kapur  
 2014/0015136 A1 1/2014 Gan et al.  
 2014/0030871 A1 1/2014 Arriagada et al.  
 2014/0035616 A1 2/2014 Oda et al.  
 2014/0048867 A1 2/2014 Toh  
 2014/0099761 A1 4/2014 Kim et al.  
 2014/0103959 A1 4/2014 Andreev  
 2014/0117413 A1 5/2014 Madurawe  
 2014/0120695 A1 5/2014 Ohtsuki  
 2014/0131885 A1 5/2014 Samadi et al.  
 2014/0137061 A1 5/2014 McIlrath  
 2014/0145347 A1 5/2014 Samadi et al.  
 2014/0146630 A1 5/2014 Xie et al.  
 2014/0149958 A1 5/2014 Samadi et al.  
 2014/0151774 A1 6/2014 Rhie  
 2014/0191357 A1 7/2014 Lee  
 2014/0225218 A1 8/2014 Du  
 2014/0225235 A1 8/2014 Du  
 2014/0252306 A1 9/2014 Du  
 2014/0253196 A1 9/2014 Du et al.  
 2014/0264228 A1 9/2014 Toh  
 2014/0357054 A1 12/2014 Son et al.  
 2015/0021785 A1 1/2015 Lin  
 2015/0034898 A1 2/2015 Wang  
 2015/0243887 A1 8/2015 Saitoh  
 2015/0255418 A1 9/2015 Gowda  
 2015/0279829 A1 10/2015 Kuo  
 2015/0340369 A1 11/2015 Lue  
 2016/0049201 A1 2/2016 Lue  
 2016/0104780 A1 4/2016 Mauder  
 2016/0133603 A1 5/2016 Ahn  
 2016/0141299 A1 5/2016 Hong  
 2016/0141334 A1 5/2016 Takaki  
 2016/0307952 A1 10/2016 Huang  
 2016/0343687 A1 11/2016 Vadhavkar  
 2017/0069601 A1 3/2017 Park  
 2017/0092371 A1 3/2017 Harari  
 2017/0098596 A1 4/2017 Lin  
 2017/0148517 A1 5/2017 Harari  
 2017/0179146 A1 6/2017 Park  
 2017/0221900 A1 8/2017 Widjaja  
 2017/0278858 A1 9/2017 Walker  
 2018/0090219 A1 3/2018 Harari  
 2018/0090368 A1 3/2018 Kim  
 2018/0108416 A1 4/2018 Harari  
 2018/0294284 A1 10/2018 Tarakji  
 2019/0006009 A1 1/2019 Harari  
 2019/0043836 A1 2/2019 Fastow et al.  
 2019/0067327 A1 2/2019 Herner  
 2019/0157296 A1 5/2019 Harari et al.  
 2020/0020408 A1 1/2020 Norman  
 2020/0020718 A1 1/2020 Harari et al.  
 2020/0051990 A1 2/2020 Harari et al.

2020/0105773 A1 4/2020 Morris et al.  
 2020/0227123 A1 7/2020 Salahuddin et al.  
 2020/0243486 A1 7/2020 Quader et al.

## OTHER PUBLICATIONS

Demeester, P. et al., "Epitaxial lift-off and its applications," *Semicond. Sci. Technol.*, 1993, pp. 1124-1135, vol. 8.  
 Yoon, J., et al., "GaAs Photovoltaics and optoelectronics using releasable multilayer epitaxial assemblies", *Nature*, vol. 465, May 20, 2010, pp. 329-334.  
 Bakir and Meindl, "Integrated Interconnect Technologies for 3D Nanoelectronic Systems", Artech House, 2009, Chapter 13, pp. 389-419.  
 Tanaka, H., et al., "Bit Cost Scalable Technology with Punch and Plug Process for Ultra High Density Flash Memory," *VLSI Technology, 2007 IEEE Symposium on*, vol., No., pp. 14-15, Jun. 12-14, 2007.  
 Lue, H.-T., et al., "A Highly Scalable 8-Layer 3D Vertical-Gate (VG) TFT NAND Flash Using Junction-Free Buried Channel BE-SONOS Device," *Symposium on VLSI Technology*, 2010, pp. 131-132.  
 Kim, W., et al., "Multi-layered Vertical Gate NAND Flash overcoming stacking limit for terabit density storage", *Symposium on VLSI Technology Digest of Technical Papers*, 2009, pp. 188-189.  
 Dicioccio, L., et al., "Direct bonding for wafer level 3D integration", *ICICDT 2010*, pp. 110-113.  
 Kim, W., et al., "Multi-Layered Vertical Gate NAND Flash Overcoming Stacking Limit for Terabit Density Storage," *Symposium on VLSI Technology*, 2009, pp. 188-189.  
 Walker, A. J., "Sub-50nm Dual-Gate Thin-Film Transistors for Monolithic 3-D Flash", *IEEE Trans. Elect. Dev.*, vol. 56, No. 11, pp. 2703-2710, Nov. 2009.  
 Hubert, A., et al., "A Stacked SONOS Technology, Up to 4 Levels and 6nm Crystalline Nanowires, with Gate-All-Around or Independent Gates ( $\Phi$ Flash), Suitable for Full 3D Integration", *International Electron Devices Meeting*, 2009, pp. 637-640.  
 Celler, G.K. et al., "Frontiers of silicon-on-insulator," *J. App. Phys.*, May 1, 2003, pp. 4955-4978, vol. 93, No. 9.  
 Rajendran, B., et al., "Electrical Integrity of MOS Devices in Laser Annealed 3D IC Structures", *proceedings VLSI Multi Level Interconnect Conference 2004*, pp. 73-74.  
 Rajendran, B., "Sequential 3D IC Fabrication: Challenges and Prospects", *Proceedings of VLSI Multi Level Interconnect Conference 2006*, pp. 57-64.  
 Jung, S.-M., et al., "The revolutionary and truly 3-dimensional 25F2 SRAM technology with the smallest S3 (stacked single-crystal Si) cell, 0.16 $\mu$ m<sup>2</sup>, and SSTFT (stacked single-crystal thin film transistor) for ultra high density SRAM," *VLSI Technology, 2004. Digest of Technical Papers*, pp. 228-229, Jun. 15-17, 2004.  
 Hui, K. N., et al., "Design of vertically-stacked polychromatic light-emitting diodes," *Optics Express*, Jun. 8, 2009, pp. 9873-9878, vol. 17, No. 12.  
 Chuai, D. X., et al., "A Trichromatic Phosphor-Free White Light-Emitting Diode by Using Adhesive Bonding Scheme," *Proc. SPIE*, 2009, vol. 7635.  
 Suntharalingam, V. et al., "Megapixel CMOS Image Sensor Fabricated in Three-Dimensional Integrated Circuit Technology," *Solid-State Circuits Conference, Digest of Technical Papers, ISSCC*, Aug. 29, 2005, pp. 356-357, vol. 1.  
 Coudrain, P. et al., "Setting up 3D Sequential Integration for Back-Illuminated CMOS Image Sensors with Highly Miniaturized Pixels with Low Temperature Fully-Depleted SOI Transistors," *IEDM*, 2008, pp. 1-4.  
 Flamand, G. et al., "Towards Highly Efficient 4-Terminal Mechanical Photovoltaic Stacks," *III-Vs Review*, Sep.-Oct. 2006, pp. 24-27, vol. 19, Issue 7.  
 Zahler, J.M. et al., "Wafer Bonding and Layer Transfer Processes for High Efficiency Solar Cells," *Photovoltaic Specialists Conference, Conference Record of the Twenty-Ninth IEEE*, May 19-24, 2002, pp. 1039-1042.



(56)

## References Cited

## OTHER PUBLICATIONS

- Sekar, D. C., et al., "A 3D-IC Technology with Integrated Microchannel Cooling", Proc. Intl. Interconnect Technology Conference, 2008, pp. 13-15.
- Brunschweiler, T., et al., "Forced Convective Interlayer Cooling in Vertically Integrated Packages," Proc. Intersoc. Conference on Thermal Management (ITHERM), 2008, pp. 1114-1125.
- Yu, H., et al., "Allocating Power Ground Vias in 3D ICs for Simultaneous Power and Thermal Integrity" ACM Transactions on Design Automation of Electronic Systems (TODAES), vol. 14, No. 3, Article 41, May 2009, pp. 41.1-41.31.
- Motoyoshi, M., "3D-IC Integration," 3rd Stanford and Tohoku University Joint Open Workshop, Dec. 4, 2009, pp. 1-52.
- Wong, S., et al., "Monolithic 3D Integrated Circuits," VLSI Technology, Systems and Applications, 2007, International Symposium on VLSI-TSA 2007, pp. 1-4.
- Batude, P., et al., "Advances in 3D CMOS Sequential Integration," 2009 IEEE International Electron Devices Meeting (Baltimore, Maryland), Dec. 7-9, 2009, pp. 345-348.
- Tan, C.S., et al., "Wafer Level 3-D ICs Process Technology," ISBN-10: 0387765328, Springer, 1st Ed., Sep. 19, 2008, pp. v-xii, 34, 58, and 59.
- Yoon, S.W. et al., "Fabrication and Packaging of Microbump Interconnections for 3D TSV," IEEE International Conference on 3D System Integration (3DIC), Sep. 28-30, 2009, pp. 1-5.
- Franzon, P.D. et al., "Design and CAD for 3D Integrated Circuits," 45th ACM/IEEE Design, Automation Conference (DAC), Jun. 8-13, 2008, pp. 668-673.
- Lajevardi, P., "Design of a 3-Dimension FPGA," Thesis paper, University of British Columbia, Submitted to Dept. of Electrical Engineering and Computer Science, Massachusetts Institute of Technology, Jul. 2005, pp. 1-71.
- Dong, C. et al., "Reconfigurable Circuit Design with Nanomaterials," Design, Automation & Test in Europe Conference & Exhibition, Apr. 20-24, 2009, pp. 442-447.
- Razavi, S.A., et al., "A Tileable Switch Module Architecture for Homogeneous 3D FPGAs," IEEE International Conference on 3D System Integration (3DIC), Sep. 28-30, 2009, 4 pages.
- Bakir M., et al., "3D Device-Stacking Technology for Memory," Chptr. 13.4, pp. 407-410, in "Integrated Interconnect Technologies for 3D Nano Electronic Systems", 2009, Artech House.
- Weis, M. et al., "Stacked 3-Dimensional 6T SRAM Cell with Independent Double Gate Transistors," IC Design and Technology, May 18-20, 2009.
- Doucette, P., "Integrating Photonics: Hitachi, Oki Put LEDs on Silicon," Solid State Technology, Jan. 2007, p. 22, vol. 50, No. 1.
- Luo, Z.S. et al., "Enhancement of (In, Ga)N Light-emitting Diode Performance by Laser Lifting and Transfer from Sapphire to Silicon," Photonics Technology Letters, Oct. 2002, pp. 1400-1402, vol. 14, No. 10.
- Zahler, J.M. et al., "Wafer Bonding and Layer Transfer Processes for High Efficiency Solar Cells," NCPV and Solar Program Review Meeting, 2003, pp. 723-726.
- Kada, M., "Updated results of R&D on functionally innovative 3D-integrated circuit (dream chip) technology in FY2009", (2010) International Microsystems Packaging Assembly and Circuits Technology Conference, IMPACT 2010 and International 3D IC Conference, Proceedings.
- Kada, M., "Development of functionally innovative 3D-integrated circuit (dream chip) technology / high-density 3D-integration technology for multifunctional devices", (2009) IEEE International Conference on 3D System Integration, 3DIC 2009.
- Marchal, P., et al., "3-D technology assessment: Path-finding the technology/design sweet-spot", (2009) Proceedings of the IEEE, 97 (1), pp. 96-107.
- Xie, Y., et al., "Design space exploration for 3D architectures", (2006) ACM Journal on Emerging Technologies in Computing Systems, 2 (2), Apr. 2006, pp. 65-103.
- Souri, S., et al., "Multiple Si layers ICs: motivation, performance analysis, and design Implications", (2000) Proceedings—Design Automation Conference, pp. 213-220.
- Vinet, M., et al., "3D monolithic integration: Technological challenges and electrical results", Microelectronic Engineering Apr. 2011 vol. 88, Issue 4, pp. 331-335.
- Bobba, S. et al., "CELONCEL: Effective Design Technique for 3-D Monolithic Integration targeting High Performance Integrated Circuits", Asia Pacific DAC 2011, paper 4A-4.
- Choudhury, D., "3D Integration Technologies for Emerging Microsystems", IEEE Proceedings of the IMS 2010, pp. 1-4.
- Lee, Y.-J., et al., "3D 65nm CMOS with 320° C. Microwave Dopant Activation", IEDM 2010, pp. 1-4.
- Crnogorac, F., et al., "Semiconductor crystal islands for three-dimensional integration", J. Vac. Sci. Technol. B 28(6), Nov./Dec. 2010, pp. C6P53-C6P58.
- Park, J.-H., et al., "N-Channel Germanium MOSFET Fabricated Below 360° C. by Cobalt-Induced Dopant Activation for Monolithic Three-Dimensional-ICs", IEEE Electron Device Letters, vol. 32, No. 3, Mar. 2011, pp. 234-236.
- Jung, S.-M., et al., "Highly Area Efficient and Cost Effective Double Stacked S3( Stacked Single-crystal Si ) Peripheral CMOS SSTFT and SRAM Cell Technology for 512M bit density SRAM", IEDM 2003, pp. 265-268.
- Joyner, J.W., "Opportunities and Limitations of Three-dimensional Integration for Interconnect Design", PhD Thesis, Georgia Institute of Technology, Jul. 2003.
- Choi, S.-J., "A Novel TFT with a Laterally Engineered Bandgap for of 3D Logic and Flash Memory", 2010 Symposium of VLSI Technology Digest, pp. 111-112.
- Radu, I., et al., "Recent Developments of Cu—Cu non-thermo compression bonding for wafer-to-wafer 3D stacking", IEEE 3D Systems Integration Conference (3DIC), Nov. 16-18, 2010.
- Gaudin, G., et al., "Low temperature direct wafer to wafer bonding for 3D integration", 3D Systems Integration Conference (3DIC), IEEE, 2010, Munich, Nov. 16-18, 2010, pp. 1-4.
- Jung, S.-M., et al., "Three Dimensionally Stacked NAND Flash Memory Technology Using Stacking Single Crystal Si Layers on ILD and TANOS Structure for Beyond 30nm Node", IEDM 2006, Dec. 11-13, 2006.
- Souri, S. J., "Interconnect Performance in 3-Dimensional Integrated Circuits", PhD Thesis, Stanford, Jul. 2003.
- Uemoto, Y., et al., "A High-Performance Stacked-CMOS SRAM Cell by Solid Phase Growth Technique", Symposium on VLSI Technology, 2010, pp. 21-22.
- Jung, S.-M., et al., "Highly Cost Effective and High Performance 65nm S3( Stacked Single-crystal Si ) SRAM Technology with 25F2, 0.16um<sup>2</sup> cell and doubly Stacked SSTFT Cell Transistors for Ultra High Density and High Speed Applications", 2005 Symposium on VLSI Technology Digest of Technical papers, pp. 220-221.
- Steen, S.E., et al., "Overlay as the key to drive wafer scale 3D integration", Microelectronic Engineering 84 (2007) 1412-1415.
- Maeda, N., et al., "Development of Sub 10-μm Ultra-Thinning Technology using Device Wafers for 3D Manufacturing of Terabit Memory", 2010 Symposium on VLSI Technology Digest of Technical Papers, pp. 105-106.
- Chan, M., et al., "3-Dimensional Integration for Interconnect Reduction in for Nano-CMOS Technologies", IEEE Tencon, Nov. 23, 2006, Hong Kong.
- Dong, X., et al., "Chapter 10: System-Level 3D IC Cost Analysis and Design Exploration", in Xie, Y., et al., "Three-Dimensional Integrated Circuit Design", book in series "Integrated Circuits and Systems" ed. A. Andrakasan, Springer 2010.
- Naito, T., et al., "World's first monolithic 3D-FPGA with TFT SRAM over 90nm 9 layer Cu CMOS", 2010 Symposium on VLSI Technology Digest of Technical Papers, pp. 219-220.
- Bernard, E., et al., "Novel integration process and performances analysis of Low Standby Power (LSTP) 3D Multi-Channel CMOSFET (MCFET) on SOI with Metal / High-K Gate stack", 2008 Symposium on VLSI Technology Digest of Technical Papers, pp. 16-17.
- Cong, J., et al., "Quantitative Studies of Impact of 3D IC Design on Repeater Usage", Proceedings of International VLSI/ULSI Multi-level Interconnection Conference, pp. 344-348, 2008.

(56)

## References Cited

## OTHER PUBLICATIONS

- Gutmann, R.J., et al., "Wafer-Level Three-Dimensional Monolithic Integration for Intelligent Wireless Terminals", *Journal of Semiconductor Technology and Science*, vol. 4, No. 3, Sep. 2004, pp. 196-203.
- Crnogorac, F., et al., "Nano-graphoepitaxy of semiconductors for 3D integration", *Microelectronic Engineering* 84 (2007) 891-894.
- Koyanagi, M., "Different Approaches to 3D Chips", 3D IC Review, Stanford University, May 2005.
- Koyanagi, M., "Three-Dimensional Integration Technology and Integrated Systems", ASPDAC 2009 presentation.
- Koyanagi, M., et al., "Three-Dimensional Integration Technology and Integrated Systems", ASPDAC 2009, paper 4D-1, pp. 409-415.
- Hayashi, Y., et al., "A New Three Dimensional IC Fabrication Technology Stacking Thin Film Dual-CMOS Layers", IEDM 1991, paper 25.6.1, pp. 657-660.
- Clavelier, L., et al., "Engineered Substrates for Future More Moore and More Than Moore Integrated Devices", IEDM 2010, paper 2.6.1, pp. 42-45.
- Kim, K., "From the Future Si Technology Perspective: Challenges and Opportunities", IEDM 2010, pp. 1.1.1-1.1.9.
- Ababei, C., et al., "Exploring Potential Benefits of 3D FPGA Integration", in book by Becker, J. et al. Eds., "Field Programmable Logic 2004", LNCS 3203, pp. 874-880, 2004, Springer-Verlag Berlin Heidelberg.
- Ramaswami, S., "3D TSV IC Processing", 3DIC Technology Forum Semicon Taiwan 2010, Sep. 9, 2010.
- Davis, W.R., et al., "Demystifying 3D Ics: Pros and Cons of Going Vertical", *IEEE Design and Test of Computers*, Nov.-Dec. 2005, pp. 498-510.
- Lin, M., et al., "Performance Benefits of Monolithically Stacked 3DFPGA", *FPGA06*, Feb. 22-24, 2006, Monterey, California, pp. 113-122.
- Dong, C., et al., "Performance and Power Evaluation of a 3D CMOS/Nanomaterial Reconfigurable Architecture", *ICCAD 2007*, pp. 758-764.
- Gojman, B., et al., "3D Nanowire-Based Programmable Logic", *International Conference on Nano-Networks (Nanonets 2006)*, Sep. 14-16, 2006.
- Dong, C., et al., "3-D nFPGA: A Reconfigurable Architecture for 3-D CMOS/Nanomaterial Hybrid Digital Circuits", *IEEE Transactions on Circuits and Systems*, vol. 54, No. 11, Nov. 2007, pp. 2489-2501.
- Golshani, N., et al., "Monolithic 3D Integration of SRAM and Image Sensor Using Two Layers of Single Grain Silicon", 2010 *IEEE International 3D Systems Integration Conference (3DIC)*, Nov. 16-18, 2010, pp. 1-4.
- Rajendran, B., et al., "Thermal Simulation of laser Annealing for 3D Integration", *Proceedings VMIC 2003*.
- Woo, H.-J., et al., "Hydrogen Ion Implantation Mechanism in GaAs-on-insulator Wafer Formation by Ion-cut Process", *Journal of Semiconductor Technology and Science*, vol. 6, No. 2, Jun. 2006, pp. 95-100.
- Sadaka, M., et al., "Building Blocks for wafer level 3D integration", [www.electroiq.com](http://www.electroiq.com), Aug. 18, 2010, last accessed Aug. 18, 2010.
- Madan, N., et al., "Leveraging 3D Technology for Improved Reliability", *Proceedings of the 40th Annual IEEE/ACM International Symposium on Microarchitecture (MICRO 2007)*, IEEE Computer Society.
- Hayashi, Y., et al., "Fabrication of Three Dimensional IC Using 'Cumulatively Bonded IC' (CUBIC) Technology", 1990 *Symposium on VLSI Technology*, pp. 95-96.
- Akasaka, Y., "Three Dimensional IC Trends", *Proceedings of the IEEE*, vol. 24, No. 12, Dec. 1986.
- Guarini, K. W., et al., "Electrical Integrity of State-of-the-Art 0.13um SOI Device and Circuits Transferred for Three-Dimensional (3D) Integrated Circuit (IC) Fabrication", IEDM 2002, paper 16.6, pp. 943-945.
- Kunio, T., et al., "Three Dimensional Ics, Having Four Stacked Active Device Layers," IEDM 1989, paper 34.6, pp. 837-840.
- Gaillardon, P.-E., et al., "Can We Go Towards True 3-D Architectures?," DAC 2011, paper 58, pp. 282-283.
- Yun, J.-G., et al., "Single-Crystalline Si Stacked Array (STAR) NAND Flash Memory," *IEEE Transactions on Electron Devices*, vol. 58, No. 4, Apr. 2011, pp. 1006-1014.
- Kim, Y., et al., "Three-Dimensional NAND Flash Architecture Design Based on Single-Crystalline Stacked Array," *IEEE Transactions on Electron Devices*, vol. 59, No. 1, Jan. 2012, pp. 35-45.
- Goplen, B., et al., "Thermal Via Placement in 3DICs," *Proceedings of the International Symposium on Physical Design*, Apr. 3-6, 2005, San Francisco.
- Bobba, S., et al., "Performance Analysis of 3-D Monolithic Integrated Circuits," 2010 *IEEE International 3D Systems Integration Conference (3DIC)*, Nov. 2010, Munich, pp. 1-4.
- Batude, P., et al., "Demonstration of low temperature 3D sequential FDSOI integration down to 50nm gate length," 2011 *Symposium on VLSI Technology Digest of Technical Papers*, pp. 158-159.
- Batude, P., et al., "Advances, Challenges and Opportunities in 3D CMOS Sequential Integration," 2011 *IEEE International Electron Devices Meeting*, paper 7.3, Dec. 2011, pp. 151-154.
- Yun, C. H., et al., "Transfer of patterned ion-cut silicon layers", *Applied Physics Letters*, vol. 73, No. 19, Nov. 1998, pp. 2772-2774.
- Ishihara, R., et al., "Monolithic 3D-ICs with single grain Si thin film transistors," *Solid-State Electronics* 71 (2012) pp. 80-87.
- Lee, S. Y., et al., "Architecture of 3D Memory Cell Array on 3D IC," *IEEE International Memory Workshop*, May 20, 2012, Monterey, CA.
- Lee, S. Y., et al., "3D IC Architecture for High Density Memories," *IEEE International Memory Workshop*, p. 1-6, May 2010.
- Rajendran, B., et al., "CMOS transistor processing compatible with monolithic 3-D Integration," *Proceedings VMIC 2005*.
- Huet, K., "Ultra Low Thermal Budget Laser Thermal Annealing for 3D Semiconductor and Photovoltaic Applications," *NCCAVS 2012 Junction Technology Group, Semicon West, San Francisco*, Jul. 12, 2012.
- Derakhshandeh, J., et al., "A Study of the CMPE Effect on the Quality of Thin Silicon Films Crystallized by Using the u-Czochralski Process," *Journal of the Korean Physical Society*, vol. 54, No. 1, 2009, pp. 432-436.
- Kim, J., et al., "A Stacked Memory Device on Logic 3D Technology for Ultra-high-density Data Storage," *Nanotechnology*, vol. 22, 254006 (2011).
- Lee, K. W., et al., "Three-dimensional shared memory fabricated using wafer stacking technology," *IEDM Tech. Dig.*, 2000, pp. 165-168.
- Chen, H. Y., et al., "HfOx Based Vertical Resistive Random Access Memory for Cost Effective 3D Cross-Point Architecture without Cell Selector," *Proceedings IEDM 2012*, pp. 497-499.
- Huet, K., et al., "Ultra Low Thermal Budget Anneals for 3D Memories: Access Device Formation," *Ion Implantation Technology 2012, AIP Conf Proceedings 1496*, 135-138 (2012).
- Batude, P., et al., "3D Monolithic Integration," *ISCAS 2011* pp. 2233-2236.
- Batude, P., et al., "3D Sequential Integration: A Key Enabling Technology for Heterogeneous C-Integration of New Function With CMOS," *IEEE Journal on Emerging and Selected Topics in Circuits and Systems (JETCAS)*, vol. 2, No. 4, Dec. 2012, pp. 714-722.
- Vinet, M., et al., "Germanium on Insulator and new 3D architectures opportunities for integration", *International Journal of Nanotechnology*, vol. 7, No. 4, (Aug. 2010) pp. 304-319.
- Bernstein, K., et al., "Interconnects in the Third Dimension: Design Challenges for 3DICs," *Design Automation Conference, 2007, DAC'07, 44th ACM/IEEE*, vol., No., pp. 562-567, Jun. 4-8, 2007.
- Kuroda, T., "ThruChip Interface for Heterogeneous Chip Stacking," *ElectroChemical Society Transactions*, 50 (14) 63-68 (2012).
- Miura, N., et al., "A Scalable 3D Heterogeneous Multi-Core Processor with Inductive-Coupling ThruChip Interface," *IEEE Micro Cool Chips XVI, Yokohama*, Apr. 17-19, 2013, pp. 1-3(2013).
- Kuroda, T., "Wireless Proximity Communications for 3D System Integration," *Future Directions in IC and Package Design Workshop*, Oct. 29, 2007.

(56)

## References Cited

## OTHER PUBLICATIONS

- Qiang, J-Q, "3-D Hyperintegration and Packaging Technologies for Micro-Nano Systems," Proceedings of the IEEE, 97.1 (2009) pp. 18-30.
- Lee, B.H., et al., "A Novel Pattern Transfer Process for Bonded SOI Giga-bit DRAMs," Proceedings 1996 IEEE International SOI Conference, Oct. 1996, pp. 114-115.
- Wu, B., et al., "Extreme ultraviolet lithography and three dimensional circuits," Applied Physics Reviews, 1, 011104 (2014).
- Delhougne, R., et al., "First Demonstration of Monocrystalline Silicon Macaroni Channel for 3-D NAND Memory Devices" IEEE VLSI Tech Digest, 2018, pp. 203-204.
- Kim, J., et al.; "A stacked memory device on logic 3D technology for ultra-high-density data storage"; Nanotechnology 22 (2011) 254006 (7pp).
- Hsieh, P-Y, et al., "Monolithic 3D BEOL FinFET switch arrays using location-controlled-grain technique in voltage regulator with better FOM than 2D regulators", IEDM paper 3.1, pp. IEDM19-46 to IEDM19-49.
- Then, Han Wui, et al., "3D heterogeneous integration of high performance high-K metal gate GaN NMOS and Si PMOS transistors on 300mm high resistivity Si substrate for energy-efficient and compact power delivery, RF (5G and beyond) and SoC applications", IEDM 2019, paper 17.3, pp. IEDM19-402 to IEDM19-405.
- Rachmady, W., et al., "300mm Heterogeneous 3D Integration of Record Performance Layer Transfer Germanium PMOS with Silicon NMOS for Low Power High Performance Logic Applications", IEDM 2019, paper 29.7, pp. IEDM19-697 to IEDM19-700.
- Colinge, J. P., et al., "Nanowire transistors without Junctions", Nature Nanotechnology, Feb. 21, 2010, pp. 1-5.
- Kim, J.Y., et al., "The breakthrough in data retention time of DRAM using Recess-Channel-Array Transistor (RCAT) for 88 nm feature size and beyond," 2003 Symposium on VLSI Technology Digest of Technical Papers, pp. 11-12, Jun. 10-12, 2003.
- Kim, J.Y., et al., "The excellent scalability of the RCAT (recess-channel-array-transistor) technology for sub-70nm DRAM feature size and beyond," 2005 IEEE VLSI-TSA International Symposium, pp. 33-34, Apr. 25-27, 2005.
- Abramovici, Breuer and Friedman, Digital Systems Testing and Testable Design, Computer Science Press, 1990, pp. 432-447.
- Yonehara, T., et al., "ELTRAN: SOI-Epi Wafer by Epitaxial Layer transfer from porous Silicon", the 198th Electrochemical Society Meeting, abstract No. 438 (2000).
- Yonehara, T. et al., "Elton®, Novel SOI Wafer Technology," JSAP International, Jul. 2001, pp. 10-16, No. 4.
- Suk, S. D., et al., "High performance 5 nm radius twin silicon nanowire MOSFET(TSNWFET): Fabrication on bulk Si wafer, characteristics, and reliability," in Proc. IEDM Tech. Dig., 2005, pp. 717-720.
- Bangsaruntip, S., et al., "High performance and highly uniform gate-all-around silicon nanowire MOSFETs with wire size dependent scaling," Electron Devices Meeting (IEDM), 2009 IEEE International, pp. 297-300, Dec. 7-9, 2009.
- Burr, G. W., et al., "Overview of candidate device technologies for storage-class memory," IBM Journal of Research and Development, vol. 52, No. 4.5, pp. 449-464, Jul. 2008.
- Bez, R., et al., "Introduction to Flash memory," Proceedings IEEE, 91(4), 489-502 (2003).
- Auth, C., et al., "45nm High-k + Metal Gate Strain-Enhanced Transistors," Symposium on VLSI Technology Digest of Technical Papers, 2008, pp. 128-129.
- Jan, C. H., et al., "A 32nm SoC Platform Technology with 2nd Generation High-k/Metal Gate Transistors Optimized for Ultra Low Power, High Performance, and High Density Product Applications," IEEE International Electronic Devices Meeting (IEDM), Dec. 7-9, 2009, pp. 1-4.
- Mistry, K., "A 45nm Logic Technology With High-K+Metal Gate Transistors, Strained Silicon, 9 Cu Interconnect Layers, 193nm Dry Patterning, and 100% Pb-Free Packaging," Electron Devices Meeting, 2007, IEDM 2007, IEEE International, Dec. 10-12, 2007, p. 247.
- Ragnarsson, L., et al., "Ultralow-EOT (5 Å) Gate-First and Gate-Last High Performance CMOS Achieved by Gate-Electrode Optimization," IEDM Tech. Dig., pp. 663-666, 2009.
- Sen, P & Kim, C.J., "A Fast Liquid-Metal Droplet Microswitch Using EWOD-Driven Contact-Line Sliding", Journal of Microelectromechanical Systems, vol. 18, No. 1, Feb. 2009, pp. 174-185.
- Iwai, H., et al., "NiSi Salicide Technology for Scaled CMOS," Microelectronic Engineering, 60 (2002), pp. 157-169.
- Froment, B., et al., "Nickel vs. Cobalt Silicide integration for sub-50nm CMOS", IMEC ESS Circuits, 2003. pp. 215-219.
- James, D., "65 and 45-nm Devices—an Overview", Semicon West, Jul. 2008, paper No. ctr\_024377.
- Davis, J.A., et al., "Interconnect Limits on Gigascale Integration(GSI) in the 21st Century", Proc. IEEE, vol. 89, No. 3, pp. 305-324, Mar. 2001.
- Shino, T., et al., "Floating Body RAM Technology and its Scalability to 32nm Node and Beyond," Electron Devices Meeting, 2006, IEDM '06, International, pp. 1-4, Dec. 11-13, 2006.
- Hamamoto, T., et al., "Overview and future challenges of floating body RAM (FBRAM) technology for 32 nm technology node and beyond", Solid-State Electronics, vol. 53, Issue 7, Papers Selected from the 38th European Solid-State Device Research Conference—ESSDERC'08, Jul. 2009, pp. 676-683.
- Okhonin, S., et al., "New Generation of Z-RAM", Electron Devices Meeting, 2007. IEDM 2007. IEEE International, pp. 925-928, Dec. 10-12, 2007.
- Henttinen, K. et al., "Mechanically Induced Si Layer Transfer in Hydrogen-Implanted Si Wafers," Applied Physics Letters, Apr. 24, 2000, p. 2370-2372, vol. 76, No. 17.
- Lee, C.-W., et al., "Junctionless multigate field-effect transistor," Applied Physics Letters, vol. 94, pp. 053511-1 to 053511-2, 2009.
- Park, S. G., et al., "Implementation of HfSiON gate dielectric for sub-60nm DRAM dual gate oxide with recess channel array transistor (RCAT) and tungsten gate," International Electron Devices Meeting, IEDM 2004, pp. 515- 518, Dec. 13-15, 2004.
- Kim, J.Y., et al., "S-RCAT (sphere-shaped-recess-channel-array transistor) technology for 70nm DRAM feature size and beyond," 2005 Symposium on VLSI Technology Digest of Technical Papers, 2005 pp. 34-35, Jun. 14-16, 2005.
- Oh, H.J., et al., "High-density low-power-operating DRAM device adopting 6F2 cell scheme with novel S-RCAT structure on 80nm feature size and beyond," Solid-State Device Research Conference, ESSDERC 2005. Proceedings of 35th European, pp. 177-180, Sep. 12-16, 2005.
- Chung, S.-W., et al., "Highly Scalable Saddle-Fin (S-Fin) Transistor for Sub-50nm DRAM Technology," 2006 Symposium on VLSI Technology Digest of Technical Papers, pp. 32-33.
- Lee, M. J., et al., "A Proposal on an Optimized Device Structure With Experimental Studies on Recent Devices for the DRAM Cell Transistor," IEEE Transactions on Electron Devices, vol. 54, No. 12, pp. 3325-3335, Dec. 2007.
- Henttinen, K. et al., "Cold ion-cutting of hydrogen implanted Si," J. Nucl. Instr. and Meth. in Phys. Res. B, 2002, pp. 761-766, vol. 190.
- Brumfiel, G., "Solar cells sliced and diced", May 19, 2010, Nature News.
- Dragoi, et al., "Plasma-activated wafer bonding: the new low-temperature tool for MEMS fabrication", Proc. SPIE, vol. 6589, 65890T (2007).
- Vengurlekar, A., et al., "Mechanism of Dopant Activation Enhancement in Shallow Junctions by Hydrogen", Proceedings of the Materials Research Society, vol. 864, Spring 2005, E9.28.1-6.
- Yamada, M. et al., "Phosphor Free High-Luminous-Efficiency White Light-Emitting Diodes Composed of InGaN Multi-Quantum Well," Japanese Journal of Applied Physics, 2002, pp. L246-L248, vol. 41.
- Guo, X. et al., "Cascade single-chip phosphor-free white light emitting diodes," Applied Physics Letters, 2008, pp. 013507-1-013507-3, vol. 92.

(56)

## References Cited

## OTHER PUBLICATIONS

- Takafuji, Y. et al., "Integration of Single Crystal Si TFTs and Circuits on a Large Glass Substrate," IEEE International Electron Devices Meeting (IEDM), Dec. 7-9, 2009, pp. 1-4.
- Wierer, J.J. et al., "High-power AlGaInN flip-chip light-emitting diodes," Applied Physics Letters, May 28, 2001, pp. 3379-3381, vol. 78, No. 22.
- El-Gamal, A., "Trends in CMOS Image Sensor Technology and Design," International Electron Devices Meeting Digest of Technical Papers, Dec. 2002.
- Ahn, S.W., "Fabrication of a 50 nm half-pitch wire grid polarizer using nanoimprint lithography," Nanotechnology, 2005, pp. 1874-1877, vol. 16, No. 9.
- Johnson, R.C., "Switching LEDs on and off to enlighten wireless communications," EE Times, Jun. 2010, last accessed Oct. 11, 2010, <<http://www.embeddedinternetdesign.com/design/225402094>>.
- Ohsawa, et al., "Autonomous Refresh of Floating Body Cell (FBC)," International Electron Device Meeting, 2008, pp. 801-804.
- Chen, P., et al., "Effects of Hydrogen Implantation Damage on the Performance of InP/InGaAs/InP p-i-n Photodiodes, Transferred on Silicon," Applied Physics Letters, vol. 94, No. 1, Jan. 2009, pp. 012101-1 to 012101-3.
- Lee, D., et al., "Single-Crystalline Silicon Micromirrors Actuated by Self-Aligned Vertical Electrostatic Combedrives with Piston-Motion and Rotation Capability," Sensors and Actuators A114, 2004, pp. 423-428.
- Shi, X., et al., "Characterization of Low-Temperature Processed Single-Crystalline Silicon Thin-Film Transistor on Glass," IEEE Electron Device Letters, vol. 24, No. 9, Sep. 2003, pp. 574-576.
- Chen, W., et al., "InP Layer Transfer with Masked Implantation," Electrochemical and Solid-State Letters, Issue 12, No. 4, Apr. 2009, H149-150.
- Feng, J., et al., "Integration of Germanium-on-Insulator and Silicon MOSFETs on a Silicon Substrate," IEEE Electron Device Letters, vol. 27, No. 11, Nov. 2006, pp. 911-913.
- Zhang, S., et al., "Stacked CMOS Technology on SOI Substrate," IEEE Electron Device Letters, vol. 25, No. 9, Sep. 2004, pp. 661-663.
- Brebner, G., "Tooling up for Reconfigurable System Design," IEE Colloquium on Reconfigurable Systems, 1999, Ref. No. 1999/061, pp. 2/1-2/4.
- Bae, Y.-D., "A Single-Chip Programmable Platform Based on a Multithreaded Processor and Configurable Logic Clusters," 2002 IEEE International Solid-State Circuits Conference, Feb. 3-7, 2002, Digest of Technical Papers, ISSCC, vol. 1, pp. 336-337.
- Lu, N.C.C., et al., "A Buried-Trench DRAM Cell Using a Self-aligned Epitaxy Over Trench Technology," Electron Devices Meeting, IEDM '88 Technical Digest, International, 1988, pp. 588-591.
- Valsamakias, E.A., "Generator for a Custom Statistical Bipolar Transistor Model," IEEE Journal of Solid-State Circuits, Apr. 1985, pp. 586-589, vol. SC-20, No. 2.
- Srivastava, P. et al., "Silicon Substrate Removal of GaN DHFETs for enhanced (>1100V) Breakdown Voltage," Aug. 2010, IEEE Electron Device Letters, vol. 31, No. 8, pp. 851-852.
- Gosele, U., et al., "Semiconductor Wafer Bonding," Annual Review of Materials Science, Aug. 1998, pp. 215-241, vol. 28.
- Spangler, L.J. et al., "A Technology for High Performance Single-Crystal Silicon-on-Insulator Transistors," IEEE Electron Device Letters, Apr. 1987, pp. 137-139, vol. 8, No. 4.
- Larrieu, G. et al., "Low Temperature Implementation of Dopant-Segregated Band-edger Metallic S/D junctions in Thin-Body SOI p-MOSFETs," Proceedings IEDM, 2007, pp. 147-150.
- Qui, Z., et al., "A Comparative Study of Two Different Schemes to Dopant Segregation at NiSi/Si and PtSi/Si Interfaces for Schottky Barrier Height Lowering," IEEE Transactions on Electron Devices, vol. 55, No. 1, Jan. 2008, pp. 396-403.
- Khater, M.H., et al., "High-k/Metal-Gate Fully Depleted SOI CMOS With Single-Silicide Schottky Source/Drain With Sub-30-nm Gate Length," IEEE Electron Device Letters, vol. 31, No. 4, Apr. 2010, pp. 275-277.
- Abramovici, M., "In-system silicon validation and debug", (2008) IEEE Design and Test of Computers, 25 (3), pp. 216-223.
- Saxena, P., et al., "Repeater Scaling and Its Impact on CAD", IEEE Transactions on Computer-Aided Design of Integrated Circuits and Systems, vol. 23, No. 4, Apr. 2004.
- Abrmovici, M., et al., A reconfigurable design-for-debug infrastructure for SoCs, (2006) Proceedings—Design Automation Conference, pp. 7-12.
- Anis, E., et al., "Low cost debug architecture using lossy compression for silicon debug", (2007) Proceedings of the IEEE/ACM Design, pp. 225-230.
- Anis, E., et al., "On using lossless compression of debug data in embedded logic analysis", (2007) Proceedings of the IEEE International Test Conference, paper 18.3, pp. 1-10.
- Boule, M., et al., "Adding debug enhancements to assertion checkers for hardware emulation and silicon debug", (2006) Proceedings of the IEEE International Conference on Computer Design, pp. 294-299.
- Boule, M., et al., "Assertion checkers in verification, silicon debug and in-field diagnosis", (2007) Proceedings—Eighth International Symposium on Quality Electronic Design, ISQED 2007, pp. 613-618.
- Burtscher, M., et al., "The VPC trace-compression algorithms", (2005) IEEE Transactions on Computers, 54 (11), Nov. 2005, pp. 1329-1344.
- Frieden, B., "Trace port on powerPC 405 cores", (2007) Electronic Product Design, 28 (6), pp. 12-14.
- Hopkins, A.B.T., et al., "Debug support for complex systems on-chip: A review", (2006) IEEE Proceedings: Computers and Digital Techniques, 153 (4), Jul. 2006, pp. 197-207.
- Hsu, Y.-C., et al., "Visibility enhancement for silicon debug", (2006) Proceedings—Design Automation Conference, Jul. 24-28, 2006, San Francisco, pp. 13-18.
- Josephson, D., et al., "The crazy mixed up world of silicon debug", (2004) Proceedings of the Custom Integrated Circuits Conference, paper 30-1, pp. 665-670.
- Josephson, D.D., "The manic depression of microprocessor debug", (2002) IEEE International Test Conference (TC), paper 23.4, pp. 657-663.
- Ko, H.F., et al., "Algorithms for state restoration and trace-signal selection for data acquisition in silicon debug", (2009) IEEE Transactions on Computer-Aided Design of Integrated Circuits and Systems, 28 (2), pp. 285-297.
- Ko, H.F., et al., "Distributed embedded logic analysis for post-silicon validation of SOCs", (2008) Proceedings of the IEEE International Test Conference, paper 16.3, pp. 755-763.
- Ko, H.F., et al., "Functional scan chain design at RTL for skewed-load delay fault testing", (2004) Proceedings of the Asian Test Symposium, pp. 454-459.
- Ko, H.F., et al., "Resource-efficient programmable trigger units for post-silicon validation", (2009) Proceedings of the 14th IEEE European Test Symposium, ETS 2009, pp. 17-22.
- Liu, X., et al., "On reusing test access mechanisms for debug data transfer in SoC post-silicon validation", (2008) Proceedings of the Asian Test Symposium, pp. 303-308.
- Liu, X., et al., "Trace signal selection for visibility enhancement in post-silicon validation", (2009) Proceedings Date, pp. 1338-1343.
- McLaughlin, R., et al., "Automated debug of speed path failures using functional tests", (2009) Proceedings of the IEEE VLSI Test Symposium, pp. 91-96.
- Morris, K., "On-Chip Debugging—Built-in Logic Analyzers on your FPGA", (2004) Journal of FPGA and Structured ASIC, 2 (3).
- Nicolici, N., et al., "Design-for-debug for post-silicon validation: Can high-level descriptions help?", (2009) Proceedings—IEEE International High-Level Design Validation and Test Workshop, HLDVT, pp. 172-175.
- Park, S.-B., et al., "IFRA: Instruction Footprint Recording and Analysis for Post-Silicon Bug Localization", (2008) Design Automation Conference (DAC08), Jun. 8-13, 2008, Anaheim, CA, USA, pp. 373-378.
- Park, S.-B., et al., "Post-silicon bug localization in processors using instruction footprint recording and analysis (IFRA)", (2009) IEEE

(56)

## References Cited

## OTHER PUBLICATIONS

Transactions on Computer-Aided Design of Integrated Circuits and Systems, 28 (10), pp. 1545-1558.

Moore, B., et al., "High Throughput Non-contact SiP Testing", (2007) Proceedings—International Test Conference, paper 12.3.

Riley, M.W., et al., "Cell broadband engine debugging for unknown events", (2007) IEEE Design and Test of Computers, 24 (5), pp. 486-493.

Vermeulen, B., "Functional debug techniques for embedded systems", (2008) IEEE Design and Test of Computers, 25 (3), pp. 208-215.

Vermeulen, B., et al., "Automatic Generation of Breakpoint Hardware for Silicon Debug", Proceeding of the 41st Design Automation Conference, Jun. 7-11, 2004, p. 514-517.

Vermeulen, B., et al., "Design for debug: Catching design errors in digital chips", (2002) IEEE Design and Test of Computers, 19 (3), pp. 37-45.

Vermeulen, B., et al., "Core-based scan architecture for silicon debug", (2002) IEEE International Test Conference (TC), pp. 638-647.

Vanrootselaar, G. J., et al., "Silicon debug: scan chains alone are not enough", (1999) IEEE International Test Conference (TC), pp. 892-902.

Kim, G.-S., et al., "A 25-mV-sensitivity 2-Gb/s optimum-logic-threshold capacitive-coupling receiver for wireless wafer probing systems", (2009) IEEE Transactions on Circuits and Systems II: Express Briefs, 56 (9), pp. 709-713.

Sellathamby, C.V., et al., "Non-contact wafer probe using wireless probe cards", (2005) Proceedings—International Test Conference, 2005, pp. 447-452.

Jung, S.-M., et al., "Soft Error Immune 0.46pm<sup>2</sup> SRAM Cell with MIM Node Capacitor by 65nm CMOS Technology for Ultra High Speed SRAM", IEDM 2003, pp. 289-292.

Brillouet, M., "Emerging Technologies on Silicon", IEDM 2004, pp. 17-24.

Meindl, J. D., "Beyond Moore's Law: The Interconnect Era", IEEE Computing in Science & Engineering, Jan./Feb. 2003, pp. 20-24.

Lin, X., et al., "Local Clustering 3-D Stacked CMOS Technology for Interconnect Loading Reduction", IEEE Transactions on Electron Devices, vol. 53, No. 6, Jun. 2006, pp. 1405-1410.

He, T., et al., "Controllable Molecular Modulation of Conductivity in Silicon-Based Devices", J. Am. Chem. Soc. 2009, 131, 10023-10030.

Henley, F., "Engineered Substrates Using the Nanocleave Process", SemiconWest, TechXPOT Conference—Challenges in Device Scaling, Jul. 19, 2006, San Francisco.

Diamant, G., et al., "Integrated Circuits based on Nanoscale Vacuum Phototubes", Applied Physics Letters 92, 262903-1 to 262903-3 (2008).

Landesberger, C., et al., "Carrier techniques for thin wafer processing", CS MANTECH Conference, May 14-17, 2007 Austin, Texas, pp. 33-36.

Shen, W., et al., "Mercury Droplet Micro switch for Re-configurable Circuit Interconnect", The 12th International Conference on Solid State Sensors, Actuators and Microsystems. Boston, Jun. 8-12, 2003, pp. 464-467.

Bangsaruntip, S., et al., "Gate-all-around Silicon Nanowire 25-Stage CMOS Ring Oscillators with Diameter Down to 3 nm", 2010 Symposium on VLSI Technology Digest of papers, pp. 21-22.

Borland, J.O., "Low Temperature Activation of Ion Implanted Dopants: A Review", International Workshop on Junction technology 2002, S7-3, Japan Society of Applied Physics, pp. 85-88.

Vengurlekar, A., et al., "Hydrogen Plasma Enhancement of Boron Activation in Shallow Junctions", Applied Physics Letters, vol. 85, No. 18, Nov. 1, 2004, pp. 4052-4054.

El-Maleh, A. H., et al., "Transistor-Level Defect Tolerant Digital System Design at the Nanoscale", Research Proposal Submitted to Internal Track Research Grant Programs, 2007. Internal Track Research Grant Programs.

Austin, T., et al., "Reliable Systems on Unreliable Fabrics", IEEE Design & Test of Computers, Jul./Aug. 2008, vol. 25, issue 4, pp. 322-332.

Borkar, S., "Designing Reliable Systems from Unreliable Components: The Challenges of Transistor Variability and Degradation", IEEE Micro, IEEE Computer Society, Nov.-Dec. 2005, pp. 10-16.

Zhu, S., et al., "N-Type Schottky Barrier Source/Drain MOSFET Using Ytterbium Silicide", IEEE Electron Device Letters, vol. 25, No. 8, Aug. 2004, pp. 565-567.

Zhang, Z., et al., "Sharp Reduction of Contact Resistivities by Effective Schottky Barrier Lowering With Silicides as Diffusion Sources," IEEE Electron Device Letters, vol. 31, No. 7, Jul. 2010, pp. 731-733.

Lee, R. T.P., et al., "Novel Epitaxial Nickel Aluminide-Silicide with Low Schottky-Barrier and Series Resistance for Enhanced Performance of Dopant-Segregated Source/Drain N-channel MuGFETs", 2007 Symposium on VLSI Technology Digest of Technical Papers, pp. 108-109.

Awano, M., et al., "Advanced DSS MOSFET Technology for Ultrahigh Performance Applications", 2008 Symposium on VLSI Technology Digest of Technical Papers, pp. 24-25.

Choi, S.-J., et al., "Performance Breakthrough in NOR Flash Memory with Dopant-Segregated Schottky-Barrier (DSSB) SONOS Devices", 2009 Symposium of VLSI Technology Digest, pp. 222-223.

Zhang, M., et al., "Schottky barrier height modulation using dopant segregation in Schottky-barrier SOI-MOSFETs", Proceeding of ESSDERC, Grenoble, France, 2005, pp. 457-460.

Larrieu, G., et al., "Arsenic-Segregated Rare-Earth Silicide Junctions: Reduction of Schottky Barrier and Integration in Metallic n-MOSFETs on SOI", IEEE Electron Device Letters, vol. 30, No. 12, Dec. 2009, pp. 1266-1268.

Ko, C.H., et al., "NiSi Schottky Barrier Process-Strained Si (SB-PSS) CMOS Technology for High Performance Applications", 2006 Symposium on VLSI Technology Digest of Technical Papers.

Kinoshita, A., et al., "Solution for High-Performance Schottky-Source/Drain MOSFETs: Schottky Barrier Height Engineering with Dopant Segregation Technique", 2004 Symposium on VLSI Technology Digest of Technical Papers, pp. 168-169.

Kinoshita, A., et al., "High-performance 50-nm-Gate-Length Schottky-Source/Drain MOSFETs with Dopant-Segregation Junctions", 2005 Symposium on VLSI Technology Digest of Technical Papers, pp. 158-159.

Kaneko, A., et al., "High-Performance FinFET with Dopant-Segregated Schottky Source/Drain", IEDM 2006.

Kinoshita, A., et al., "Ultra Low Voltage Operations in Bulk CMOS Logic Circuits with Dopant Segregated Schottky Source/Drain Transistors", IEDM 2006.

Kinoshita, A., et al., "Comprehensive Study on Injection Velocity Enhancement in Dopant-Segregated Schottky MOSFETs", IEDM 2006.

Choi, S.-J., et al., "High Speed Flash Memory and 1T-DRAM on Dopant Segregated Schottky Barrier (DSSB) FinFET SONOS Device for Multi-functional SoC Applications", 2008 IEDM, pp. 223-226.

Chin, Y.K., et al., "Excimer Laser-Annealed Dopant Segregated Schottky (ELA-DSS) Si Nanowire Gate-All-Around (GAA) pFET with Near Zero Effective Schottky Barrier Height (SBH)", IEDM 2009, pp. 935-938.

Agoura Technologies white paper, "Wire Grid Polarizers: a New High Contrast Polarizer Technology for Liquid Crystal Displays", 2008, pp. 1-12.

Unipixel Displays, Inc. white paper, "Time Multi-plexed Optical Shutter (TMOS) Displays", Jun. 2007, pp. 1-49.

Azevedo, I. L., et al., "The Transition to Solid-State Lighting", Proc. IEEE, vol. 97, No. 3, Mar. 2009, pp. 481-510.

Crawford, M.H., "LEDs for Solid-State Lighting: Performance Challenges and Recent Advances", IEEE Journal of Selected Topics in Quantum Electronics, vol. 15, No. 4, Jul./Aug. 2009, pp. 1028-1040.

Tong, Q.-Y., et al., "A "smarter-cut" approach to low temperature silicon layer transfer", Applied Physics Letters, vol. 72, No. 1, Jan. 5, 1998, pp. 49-51.

(56)

## References Cited

## OTHER PUBLICATIONS

- Tong, Q.-Y., et al., "Low Temperature Si Layer Splitting", Proceedings 1997 IEEE International SOI Conference, Oct. 1997, pp. 126-127.
- Nguyen, P., et al., "Systematic study of the splitting kinetic of H/He co-implanted substrate", SOI Conference, 2003, pp. 132-134.
- Ma, X., et al., "A high-quality SOI structure fabricated by low-temperature technology with B<sup>+</sup>/H<sup>+</sup> co-implantation and plasma bonding", Semiconductor Science and Technology, vol. 21, 2006, pp. 959-963.
- Yu, C.Y., et al., "Low-temperature fabrication and characterization of Ge-on-insulator structures", Applied Physics Letters, vol. 89, 101913-1 to 101913-2 (2006).
- Li, Y. A., et al., "Surface Roughness of Hydrogen Ion Cut Low Temperature Bonded Thin Film Layers", Japan Journal of Applied Physics, vol. 39 (2000), Part 1, No. 1, pp. 275-276.
- Hoechbauer, T., et al., "Comparison of thermally and mechanically induced Si layer transfer in hydrogen-implanted Si wafers", Nuclear Instruments and Methods in Physics Research B, vol. 216 (2004), pp. 257-263.
- Aspar, B., et al., "Transfer of structured and patterned thin silicon films using the Smart-Cut process", Electronics Letters, Oct. 10, 1996, vol. 32, No. 21, pp. 1985-1986.
- Agarwal, A., et al., "Efficient production of silicon-on-insulator films by co-implantation of He<sup>+</sup> with H<sup>+</sup>", Applied Physics Letters, vol. 72, No. 9, Mar. 1998, pp. 1086-1088.
- Cook III, G. O., et al., "Overview of transient liquid phase and partial transient liquid phase bonding", Journal of Material Science, vol. 46, 2011, pp. 5305-5323.
- Moustris, G. P., et al., "Evolution of autonomous and semi-autonomous robotic surgical systems: a review of the literature," International Journal of Medical Robotics and Computer Assisted Surgery, Wiley Online Library, 2011, DOI: 10.1002/rcs.408.
- Subbarao, M., et al., "Depth from Defocus: A Spatial Domain Approach," International Journal of Computer Vision, vol. 13, No. 3, pp. 271-294 (1994).
- Subbarao, M., et al., "Focused Image Recovery from Two Defocused Images Recorded with Different Camera Settings," IEEE Transactions on Image Processing, vol. 4, No. 12, Dec. 1995, pp. 1613-1628.
- Guseynov, N. A., et al., "Ultrasonic Treatment Restores the Photoelectric Parameters of Silicon Solar Cells Degraded under the Action of 60Cobalt Gamma Radiation," Technical Physics Letters, vol. 33, No. 1, pp. 18-21 (2007).
- Gawlik, G., et al., "GaAs on Si: towards a low-temperature "smart-cut" technology", Vacuum, vol. 70, pp. 103-107 (2003).
- Weldon, M. K., et al., "Mechanism of Silicon Exfoliation Induced by Hydrogen/Helium Co-implantation," Applied Physics Letters, vol. 73, No. 25, pp. 3721-3723 (1998).
- Miller, D.A.B., "Optical interconnects to electronic chips," Applied Optics, vol. 49, No. 25, Sep. 1, 2010, pp. F59-F70.
- En, W. G., et al., "The Genesis Process": A New SOI wafer fabrication method, Proceedings 1998 IEEE International SOI Conference, Oct. 1998, pp. 163-164.
- Uchikoga, S., et al., "Low temperature poly-Si TFT-LCD by excimer laser anneal," Thin Solid Films, vol. 383 (2001), pp. 19-24.
- He, M., et al., "Large Polycrystalline Silicon Grains Prepared by Excimer Laser Crystallization of Sputtered Amorphous Silicon Film with Process Temperature at 100 C," Japanese Journal of Applied Physics, vol. 46, No. 3B, 2007, pp. 1245-1249.
- Kim, S.D., et al., "Advanced source/drain engineering for box-shaped ultra shallow junction formation using laser annealing and pre-amorphization implantation in sub-100-nm SOI CMOS," IEEE Trans. Electron Devices, vol. 49, No. 10, pp. 1748-1754, Oct. 2002.
- Ahn, J., et al., "High-quality MOSFET's with ultrathin LPCVD gate SiO<sub>2</sub>," IEEE Electron Device Lett., vol. 13, No. 4, pp. 186-188, Apr. 1992.
- Yang, M., et al., "High Performance CMOS Fabricated on Hybrid Substrate with Different Crystal Orientation," Proceedings IEDM 2003.
- Yin, H., et al., "Scalable 3-D finlike poly-Si TFT and its nonvolatile memory application," IEEE Trans. Electron Devices, vol. 55, No. 2, pp. 578-584, Feb. 2008.
- Kawaguchi, N., et al., "Pulsed Green-Laser Annealing for Single-Crystalline Silicon Film Transferred onto Silicon wafer and Non-alkaline Glass by Hydrogen-Induced Exfoliation," Japanese Journal of Applied Physics, vol. 46, No. 1, 2007, pp. 21-23.
- Faynot, O. et al., "Planar Fully depleted SOI technology: A Powerful architecture for the 20nm node and beyond," Electron Devices Meeting (IEDM), 2010 IEEE International, vol., No., pp. 3.2.1, 3.2.4, Dec. 6-8, 2010.
- Khaki Firooz, A., "ETSOI Technology for 20nm and Beyond", SOI Consortium Workshop: Fully Depleted SOI, Apr. 28, 2011, Hsinchu Taiwan.
- Kim, I.-K., et al., "Advanced Integration Technology for a Highly Scalable SOI DRAM with SOC (Silicon-On-Capacitors)", IEDM 1996, pp. 96-605-608, 22.5.4.
- Lee, B.H., et al., "A Novel CMP Method for cost-effective Bonded SOI Wafer Fabrication," Proceedings 1995 IEEE International SOI Conference, Oct. 1995, pp. 60-61.
- Choi, Sung-Jin, et al., "Performance Breakthrough in NOR Flash Memory with Dopant-Segregated Schottky-Barrier (DSSB) SONOS Devices," paper 11B-3, 2009 Symposium on VLSI Technology, Digest of Technical Papers, pp. 222-223.
- Chang, Wei, et al., "Drain-induced Schottky barrier source-side hot carriers and its application to program local bits of nanowire charge-trapping memories," Japanese Journal of Applied Physics 53, 094001 (2014) pp. 094001-1 to 094001-5.

\* cited by examiner




Fig. 1A

120




Fig. 1B




Fig. 1C






Fig. 2A




Fig. 2B




Fig. 2C




Fig. 2D




Fig. 2E

110

114

112

118

200

200

211

132

114

118

230

214

200




Fig. 3






Fig. 4



### 3D SEMICONDUCTOR DEVICE AND STRUCTURE

#### CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation-in-part application of U.S. patent application Ser. No. 17/147,989, which was filed on Jan. 13, 2021, which is a continuation-in-part application of U.S. patent application Ser. No. 17/019,162, which was filed on Sep. 11, 2020 (now U.S. Pat. No. 10,930,608 issued on Feb. 23, 2021), which is a continuation-in-part application of U.S. patent application Ser. No. 16/907,234, which was filed on Jun. 20, 2020 (now U.S. Pat. No. 10,825,779 issued on Nov. 3, 2020), which is a continuation-in-part application of U.S. patent application Ser. No. 16/450,728, which was filed on Jun. 24, 2019 (now U.S. Pat. No. 10,777,540 issued on Sep. 15, 2020), which is a continuation-in-part application of U.S. patent application Ser. No. 15/632,325, which was filed on Jun. 24, 2017 (now U.S. Pat. No. 10,381,328 issued on Aug. 13, 2019), which is a continuation-in-part application of U.S. patent application Ser. No. 15/095,187, which was filed on Apr. 11, 2016 (now U.S. Pat. No. 9,721,927 issued on Aug. 1, 2017), which claims benefit of provisional U.S. patent application Ser. No. 62/149,651, filed on Apr. 19, 2015. The entire contents of the foregoing applications are incorporated herein by reference.

#### BACKGROUND OF THE INVENTION

##### 1. Field of the Invention

This application relates to the general field of Integrated Circuit (IC) devices, fabrication methods, and die bonding and die stacking devices and methods, and more particularly to multilayer or Three Dimensional Integrated Circuit (3D-IC) devices, fabrication methods, and die bonding and die stacking devices and methods.

##### 2. Discussion of Background Art

Over the past 40 years, there has been a dramatic increase in functionality and performance of Integrated Circuits (ICs). This has largely been due to the phenomenon of “scaling”; i.e., component sizes within ICs have been reduced (“scaled”) with every successive generation of technology. There are two main classes of components in Complementary Metal Oxide Semiconductor (CMOS) ICs, namely transistors and wires. With “scaling”, transistor performance and density typically improve and this has contributed to the previously-mentioned increases in IC performance and functionality. However, wires (interconnects) that connect together transistors degrade in performance with “scaling”. The situation today is that wires dominate the performance, functionality and power consumption of ICs.

3D stacking of semiconductor devices or chips is one avenue to tackle the wire issues. By arranging transistors in 3 dimensions instead of 2 dimensions (as was the case in the 1990s), the transistors in ICs can be placed closer to each other. This reduces wire lengths and keeps wiring delay low.

There are many techniques to construct 3D stacked integrated circuits or chips including:

Through-silicon via (TSV) technology: Multiple layers of transistors (with or without wiring levels) can be con-

structed separately. Following this, they can be bonded to each other and connected to each other with through-silicon vias (TSVs).

Monolithic 3D technology: With this approach, multiple layers of transistors and wires can be monolithically constructed. Some monolithic 3D and 3DIC approaches are described in U.S. Pat. Nos. 8,273,610, 8,298,875, 8,362,482, 8,378,715, 8,379,458, 8,450,804, 8,557,632, 8,574,929, 8,581,349, 8,642,416, 8,669,778, 8,674,470, 8,687,399, 8,742,476, 8,803,206, 8,836,073, 8,902,663, 8,994,404, 9,023,688, 9,029,173, 9,030,858, 9,117,749, 9,142,553, 9,219,005, 9,385,058, 9,406,670, 9,460,978, 9,509,313, 9,640,531, 9,691,760, 9,711,407, 9,721,927, 9,799,761, 9,871,034, 9,953,870, 9,953,994, 10,014,292, 10,014,318, 10,515,981, 10,892,016; and pending U.S. Patent Application Publications and applications, 14/642,724, 15/150,395, 15/173,686, 16/337,665, 16/558,304, 16/649,660, 16/836,659, 17/151,867, 62/651,722; 62/681,249, 62/713,345, 62/770,751, 62/952,222, 62/824,288, 63/075,067, 63/091,307, 63/115,000, 2020/0013791, 16/558,304; and PCT Applications (and Publications): PCT/US2010/052093, PCT/US2011/042071 (WO2012/015550), PCT/US2016/52726 (WO2017053329), PCT/U52017/052359 (WO2018/071143), PCT/US2018/016759 (WL2018144957), and PCT/U52018/52332(WO 2019/060798). The entire contents of the foregoing patents, publications, and applications are incorporated herein by reference.

Electro-Optics: There is also work done for integrated monolithic 3D including layers of different crystals, such as U.S. Pat. Nos. 8,283,215, 8,163,581, 8,753,913, 8,823,122, 9,197,804, 9,419,031, 9,941,319, and 10,679,977. The entire contents of the foregoing patents, publications, and applications are incorporated herein by reference.

In addition, the entire contents of U.S. Pat. Nos. 10,930,608, 10,777,540, 9,721,927, 10,381,328, 10,777,540, 10,825,779; U.S. patent application publication; and U.S. patent application Ser. Nos. 17,147,989, 62/149,651 are incorporated herein by reference.

An early work on monolithic 3D was presented in U.S. Pat. No. 7,052,941 and follow-on work in related patents includes U.S. Pat. No. 7,470,598. A technique which has been used over the last 20 years to build SOI wafers, called “Smart-Cut” or “Ion-Cut”, was presented in U.S. Pat. No. 7,470,598 as one of the options to perform layer transfer for the formation of a monolithic 3D device. Yet in a related patent disclosure, by the same inventor of 7,470,598, U.S. application Ser. No. 12/618,542 it states: “In one embodiment of the previous art, exfoliating implant method in which ion-implanting Hydrogen into the wafer surface is known. But this exfoliating implant method can destroy lattice structure of the doped layer **400** by heavy ion-implanting. In this case, to recover the destroyed lattice structure, a long time thermal treatment in very high temperature is required. This long time/high temperature thermal treatment can severely deform the cell devices of the lower region.” Moreover, in U.S. application Ser. No. 12/635,496 by the same inventor is stated: [0034] Among the technologies to form the detaching layer, one of the well-known technologies is Hydrogen Exfoliating Implant. This method has a critical disadvantage which can destroy lattice structures of the substrate because it uses high amount of ion implantation. In order to recover the destroyed lattice structures, the substrate should be cured by heat treatment in very high temperature long time. This kind of high tempera-

ture heat treatment can damage cell devices in the lower regions.” Furthermore, in U.S. application Ser. No. 13/175,652 it is stated: “Among the technologies to form the detaching layer **207**, one technology is called as exfoliating implant in which gas phase ions such as hydrogen is implanted to form the detaching layer, but in this technology, the crystal lattice structure of the multiple doped layers **201**, **203**, **205** can be damaged. In order to recover the crystal lattice damage, a thermal treatment under very high temperature and longtime should be performed, and this can strongly damage the cell devices underneath.” In fact the Inventor had posted a video infomercial on his corporate website, and was up-loaded on YouTube on Jun. 1, 2011, clearly stating in reference to the Smart Cut process: “The wafer bonding and detaching method is well-known SOI or Semiconductor-On-Insulator technology. Compared to conventional bulk semiconductor substrates, SOI has been introduced to increase transistor performance. However, it is not designed for 3D IC either. Let me explain the reasons . . . . The dose of hydrogen is too high and, therefore, semiconductor crystalline lattices are demolished by the hydrogen ion bombardment during the hydrogen ion implantation. Therefore, typically annealing at more than 1,100 Celsius is required for curing the lattice damage after wafer detaching. Such high temperature processing certainly destroys underlying devices and interconnect layers. Without high temperature annealing, the transferred layer should be the same as a highly defective amorphous layer. It seems that there is no way to cure the lattice damage at low temperatures. BeSang has disruptive 3D layer formation technology and it enables formation of defect-free single crystalline semiconductor layer at low temperatures . . . .”

In at least one embodiment presented herein, at least one innovative method and device structure to repair the crystal lattice damage caused by the hydrogen implant is described.

Regardless of the technique used to construct 3D stacked integrated circuits or chips, heat removal is a serious issue for this technology. For example, when a layer of circuits with power density P is stacked atop another layer with power density P, the net power density is 2 P. Removing the heat produced due to this power density is a significant challenge. In addition, many heat producing regions in 3D stacked integrated circuits or chips have a high thermal resistance to the heat sink, and this makes heat removal even more difficult.

Several solutions have been proposed to tackle this issue of heat removal in 3D stacked integrated circuits and chips. These are described in the following paragraphs.

Publications have suggested passing liquid coolant through multiple device layers of a 3D-IC to remove heat. This is described in “Microchannel Cooled 3D Integrated Systems”, Proc. Intl. Interconnect Technology Conference, 2008 by D. C. Sekar, et al., and “Forced Convective Inter-layer Cooling in Vertically Integrated Packages,” Proc. Intersoc. Conference on Thermal Management (ITHERM), 2008 by T. Brunschweiler, et al. and “High Performance Heat Sinking for VLSI,” IEEE Electron Device Letters, vol. EDL-2, No. 5, May 1981, by D. B. Tuckerman and R. F. Pease.

Thermal vias have been suggested as techniques to transfer heat from stacked device layers to the heat sink. Use of power and ground vias for thermal conduction in 3D-ICs has also been suggested. These techniques are described in “Allocating Power Ground Vias in 3D ICs for Simultaneous Power and Thermal Integrity” ACM Transactions on Design Automation of Electronic Systems (TODAES), May 2009 by Hao Yu, Joanna Ho and Lei He.

In addition, thermal limitations during IC fabrication have been a big obstacle on the road to monolithic three-dimensional ICs. The semiconductor and microelectronic processing techniques to form transistors, circuits, and devices, for example to form some silicon oxides or nitrides, repair damages from processes such as etching and ion-implantation, annealing and activation of ion implanted species, and epitaxial regrow techniques, have processing temperatures (for example, greater than 400° C.) and times at temperature that would damage and harm the underlying metallization and/or device layers and structures. These processes may involve transient (short timescales, such as less than 500 ns short wavelength laser pulses) heat exposures to the wafer being processed, or steady state applications (such as RTA, RTO, spike, flash, CVD, ALD) of heat and/or heated material or gases that may have processing times of seconds, minutes, or hours.

Techniques to remove heat from 3D Integrated Circuits and Chips and protect sensitive metallization and circuit elements from either the heat of processing of the 3D layers or the operationally generated heat from an active circuit, will be beneficial.

There are many advantages to constructing a 3D IC system using die to wafer integration, such as, for example, as presented in U.S. application Ser. No. 14/642,724 with respect to at least FIGS. **44A-B** and FIGS. **45A-C**. A severe limitation in respect to such die to wafer integration is the throughput of such processing and its implication on the end 3D device cost. Herein we seek to present alternative process flows to support higher throughput and lower cost for such die to wafer integration including processes to allow ultra-thin die which further reduces cost and increases integration.

Additionally the 3D technology according to some embodiments of the invention may enable some very innovative IC devices alternatives with reduced development costs, novel and simpler process flows, increased yield, and other illustrative benefits.

#### SUMMARY

The invention may be directed to multilayer or Three Dimensional Integrated Circuit (3D IC) devices, fabrication methods, and die bonding and die stacking devices and methods.

In one aspect, a 3D semiconductor device, the device comprising: a first die comprising first transistors and a first interconnect; and a second die comprising second transistors and a second interconnect, wherein said first die is overlaid by said second die, wherein said first die has a first die area and said second die has a second die area, wherein said first die area is at least 10% larger than said second die area, wherein said second die is pretested, wherein said second die is bonded to said first die, wherein said bonded comprises metal to metal bonding, wherein said first die comprises at least two first alignment marks positioned close to a first die edge of said first die, and wherein said second die comprises at least two second alignment marks positioned close to a second die edge of said second die.

In another aspect, a 3D semiconductor device, the device comprising: a first wafer comprising a first die, said first die comprising first transistors and a first interconnect; and a second die comprising second transistors and a second interconnect, wherein said first die is overlaid by said second die, wherein said second die is bonded to said first die, wherein said bonded comprises hybrid bonding, wherein said first die comprises at least two first alignment marks

5

positioned close to a first die edge of said first die, and wherein said second die comprises at least two second alignment marks positioned close to a second die edge of said second die.

In another aspect, a 3D semiconductor device, the device comprising: a first die comprising first transistors and a first interconnect; and a second die comprising second transistors and a second interconnect, wherein said first die is overlaid by said second die, wherein said second die is bonded to said first die, wherein said bonded comprises hybrid bonding, and wherein said first die comprises at least two first alignment marks positioned close to a first die edge of said first die, wherein said second die comprises at least two second alignment marks positioned close to a second die edge of said second die, wherein said second die comprises an array of memory cells, and wherein said first die comprises a control logic.

In another aspect, a 3D semiconductor device, the device comprising: a first die comprising first transistors and a first interconnect; a second die comprising second transistors and a second interconnect; and a third die comprising third transistors and a third interconnect, wherein said first die is overlaid by said second die, wherein said first die is overlaid by said third die, wherein said first die has a first die area and said second die has a second die area, wherein said first die area is at least 20% larger than said second die area, wherein said second die is pretested, wherein said second die is bonded to said first die, wherein said bonded comprises metal to metal bonding, wherein said first die comprises at least two first alignment marks positioned close to a first die edge of said first die, and wherein said third die is bonded to said first die.

In another aspect, a 3D semiconductor device, the device comprising: a first die comprising first transistors and a first interconnect; a second die comprising second transistors and a second interconnect; and a third die comprising third transistors and a third interconnect, wherein said first die is overlaid by said second die, wherein said first die is overlaid by said third die, wherein said second die is bonded to said first die, wherein said bonded comprises hybrid bonding, wherein said first die comprises at least two first alignment marks positioned close to a first die edge of said first die, and wherein said third die is bonded to said first die.

In another aspect, a 3D semiconductor device, the device comprising: a first die comprising first transistors and a first interconnect; a second die comprising second transistors and a second interconnect; and a third die comprising third transistors and a third interconnect, wherein said first die is overlaid by said second die, wherein said first die is overlaid by said third die, wherein said second die is bonded to said first die, wherein said bonded comprises hybrid bonding, wherein said second die comprises an array of memory cells, wherein said first die comprises a control logic, and wherein said third die is bonded to said first die.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Various embodiments of the invention will be understood and appreciated more fully from the following detailed description, taken in conjunction with the drawings in which:

FIGS. 1A and 1B are exemplary illustrations of a processed wafer;

FIG. 1C is an exemplary illustration of a processed wafer with an added layer;

FIGS. 2A-2E are exemplary illustrations of a process flow for die to wafer manufacturing;

6

FIG. 3 is an exemplary illustration of an exemplary processed wafer with streets;

FIG. 4 is an exemplary illustration of an exemplary dice with streets and alignment marks/structures; and

FIG. 5A and 5B are exemplary illustrations of a 3D semiconductor device.

#### DETAILED DESCRIPTION

An embodiment of the invention is now described with reference to the drawing figures. Persons of ordinary skill in the art will appreciate that the description and figures illustrate rather than limit the invention and that in general the figures are not drawn to scale for clarity of presentation.

Such skilled persons will also realize that many more embodiments are possible by applying the inventive principles contained herein and that such embodiments fall within the scope of the invention which is not to be limited except by the appended claims.

Some drawing figures may describe process flows for building devices or die bonding and die stacking devices and methods. The process flows, which may be a sequence of steps for building a device or die bonding and die stacking devices and methods, may have many structures, numerals and labels that may be common between two or more adjacent steps. In such cases, some labels, numerals and structures used for a certain step's figure may have been described in the previous steps' figures.

There are many advantages to constructing a 3D IC system using die to wafer integration. A severe limitation in respect to such die to wafer integration is the throughput of such processing and its implication on the end 3D device cost. Herein we seek to present alternative process flows to support higher throughput and lower cost for such die to wafer integration including processes to allow ultra-thin die which further reduces cost and increases integration.

It is known in the art that die to wafer processing could be done with dies having thickness of less than about 20 micron to about a die thickness of about 6 micron. Such has been presented in a paper by Christine Harendt, Evangelos A. Angelopoulos, Stefan Endler, Mahadi-Ul Hassan, Tu Hoang, Joachim N. Burghartz, "Mechanical Stability of Ultra-thin Chips down to 6  $\mu\text{m}$ ," in Forum 'be-flexible' 2010, 11th International Workshop, Munich, Germany, (Vortrag), Vortrage nur für Teilnehmer, Dec. 1, 2010 (2010); and a paper by Saleh Ferwana, et al., "Self-Aligned Through Silicon Vias in Ultra-Thin Chips for 3D-Integration," Proc. of 4th Electronics System Integration Technology Conferences (ESTC), Amsterdam, Netherlands, (Vortrag), 2012, both incorporated herein by reference. As well, in the book *Ultra-thin Chip Technology and Applications*, Joachim N. Burghartz, ed. Berlin, Germany: Springer, December, 2010, ISBN: 978-1-4419-7275-0, p. 467 (2010), incorporated herein by reference. Additionally, in U.S. Patents 8,466,037 and 7,951,691, both incorporated herein by reference.

As illustrated in FIG. 1A, a wafer, such as a silicon substrate, may be processed to support a die to wafer 3D process flow. Using processes described in U.S. patent application Ser. No. 14/642,724, in at least FIGS. 22-24, a base wafer 110 may be processed to construct a top high quality epitaxial layer 116 for future device layers on top of a relatively thick low porosity layer 114. Low porosity layer 114 may have less than 50% porous structure and even about 20% porosity and would have thickness of less than 20 micron or even with die thickness of about 6 micron. Underneath low porosity layer 114 a high porosity layer 112 may be constructed to support future 'cut' or 'cleave' for a



layer transfer as was previously presented in at least U.S. patent application Ser. No. 14/642,724. Epitaxial layer **116** could be grown to a few nm thick layer, for example, such as 5 nm or 10 nm, to a moderately thick layer, such as, for example, 100 nm or 200 nm, to a relatively thick layer, such as, for example, 1 micron, or 3 microns thick.

The low porosity layer **114** could be partially oxidized to give it stronger mechanical strength. For example, dry oxidation of the porous silicon may be carried out at a low temperature of about 400° C. This results in oxidization of about 1-3 nm of the inner walls of the pores, thus preventing the structure of the porous silicon from changing under a subsequent high-temperature treatment.

As illustrated in FIG. 1B, the wafer of FIG. 1A may be processed to construct a full stratum of device layer **118** utilizing a portion of or a substantial majority of epitaxial layer **116**. Device layer **118** could have full circuits including P type and N type transistors with their metal layers interconnection processed as known in semiconductor industry processes. Device layer **118** could include thru layer vias or preparatory structures for TLVs, which may have diameters of less than about 1 um, less than about 400 nm, less than about 200 nm, or less than about 100 nm. Processed wafer **120** could then be at least electrically and functionally tested (a die within processed wafer **120** may be said to be 'pretested') and made ready for the following steps. Processed wafer **120** may include device layer **118**, low porosity layer **114**, high porosity layer **112**, and base wafer **110**.

As illustrated in FIG. 1C, an additional embodiment is shown wherein a similar base wafer structure as illustrated in FIG. 1A may be processed with the addition of solid silicon layer **126**. Solid silicon layer **126** may be disposed between low porosity layer **114** and high porosity layer **112**. The structure of FIG. 1C could be fabricated using methods such as described in U.S. patent application Ser. No. 14/642,724 such as in respect to at least FIG. 30D. Second porous layer **3024** may correspond to low porosity layer **114**, remaining monocrystalline layer **3022** may correspond to solid silicon layer **126**, and cut double layer lower layer of porous silicon **3012** and upper layer of porous silicon **3014** may correspond to high porosity layer **112**. Solid silicon layer **126** may have a thickness similar to layer epitaxial **116** and may have two main functions. First, solid silicon layer **126** helps stabilize the structure later-on as the structure is etched to allow pulling out of individual dies. And second it helps in providing a better interface to the pulling out apparatus which could use, for example, vacuum suction to provide the holding of the individual dies. The structure illustrated in FIG. 1C could be further processed to form a full stratum of device layer **118** as illustrated in FIG. 1B and so forth.

As illustrated in FIG. 2A, a customized carrier wafer **210** may be designed and formed to support the die being pulling out of, for example, processed wafer **120** in FIG. 1B. The customized carrier wafer **210** may be formed by etching die sized cavities **212** of about 1 micron depth (z direction) into a substrate wafer **200**. The die size (x and y direction) may be defined according to the size of the dies on processed wafer **120**. In most cases the dies are rectangular shaped with lengths and widths of a few mm up to about reticle size of 20x30 mm. As illustrated in FIG. 2B, which is an enlargement of bubble **220** of FIG. 2A, streets **214** may be disposed between the die sized cavities **212**. Streets **214** could be few microns in width up to about 100 micron in width. Substrate wafer **200** may include a conventional monocrystalline silicon wafer, or may be formed from other

materials, for example, such as aluminum, ceramic, and so on that may provide dimensional stability and bondability.

As illustrated in FIG. 2C, processed wafer **120** in FIG. 1B may be bonded onto customized carrier wafer **210** and may include alignment of streets **214** so that the processed dies of processed wafer **120** may be floating over die sized cavities **212** of customized carrier wafer **210** while the bonding may be done at the streets of both wafers. The actual processed circuits of device layer **118** are aligned to the die sized cavities **212** of the customized carrier wafer **210**.

As illustrated in FIG. 2D, base wafer **110** of processed wafer **120** may be cut-off or cleaved from the bonded structure utilizing the cut porous layer high porosity layer **112**.

As illustrated in FIG. 2E, structure **211** may be formed after cleaning the porous cut residues and etching the streets **132** of the remaining portion of processed wafer **120**, thus leaving the dies **230** almost floating and lightly connected to the customized carrier wafer **210**. Structure **211** may include custom carrier **210** with streets **214** lightly bonded to the edge of customized carrier wafer **120** dies **230**. These dies **230** would include functional circuits from device layer **118** and support porous structure **114**. Porous support structure **114** may have a thickness of about 6 to 20 microns.

In general a 6-20 micron thick silicon-porous silicon structure would be transparent enough to enable good detection of the individual die (such as dies **230**) alignment marks for the following steps of precise die alignment. Alternatively the alignment marks could be exposed with an etch step. Selectivity for such a step would not be an issue as the alignment mark could be formed with metal layers while the 6-20 micron etch is of silicon and silicon oxide.

The dies **230** from the structure **211** could be pulled out for integration into a 3D IC structure. This step could be done one die at a time at a relatively slow throughput. An improved process was suggested in a paper titled "Simultaneous Cu-Cu and Compliant Dielectric Bonding for 3D Stacking of ICs," A. Jourdain et al, II TC07, and paper by A. Sigl et al, "Throughput Enhanced Flip-Chip to Wafer Bonding: The Advanced Chip to Wafer Bonding," ECS09; both incorporated herein by reference. They suggested a modification of the bonding process into two steps, first tacking the individual dies, and second, collectively bonding all stacked dies in a wafer-level bonding process. U.S. Pat. Nos. 8,597,980 and 8,697,542, incorporated herein by reference, also teach two step die to wafer bonding.

In a die to wafer bonding flow it could be desired to test the dies so that only good dies get bonded and also the target base circuit could be tested so bonding could be saved and be done to a good yielded circuit die(s) on either or both.

The die tacking could be done, for example, by using a glue, temporary copper to copper bonding or ultrasound techniques. Some glue would evaporate during the second step of the simultaneous bonding leaving no residue. Some of the tacking techniques do form metal to metal connection that would allow testing and rework to make sure all die to target base circuit connections are good before moving to the longer process for simultaneous permanent bonding of all dies.

For the known processes for metal to metal, copper to copper bonding, a short cycle of such processes could provide enough holding force to hold the die once placed until all the dies are placed, and then continue with the full permanent bonding performed for all dies on the wafer simultaneously. The short bonding/tacking should take less than a minute as it is done a die at a time, the permanent bonding could take more than 30 minutes as it is done to

many dies such as full wafer populated structure simultaneously. Such bonding is presented in a paper by Y. H. Hu, et al., "Cu—Cu Hybrid Bonding as Option for 3D IC Stacking," IEEE ITC 2012, incorporated herein by reference.

Tacking using glue has been presented in a paper by J. Van Olmen, et al., "3D Stacked IC demonstrator using Hybrid Collective Die-to-Wafer Bonding with copper Through Silicon Vias (TSV)," IEEE 3DIC 2009, and in a paper by A Jourdain, et al., "Mechanical and electrical characterization of BCB as a bond and seal material for cavities housing (RF-)MEMS devices," J. Micromech. Microeng. 15 (2005), both incorporated herein by reference.

Tacking could be done using ultrasound for bonding. Ultrasound could be use for tacking and also for permanent bonding. Ultrasound bonding processing is presented in a paper by Yanhong Tian, "Investigation of ultrasonic copper wire wedge bonding on Au/Ni plated Cu substrates at ambient temperature," Journal of Materials Processing Technology (2008), incorporated herein by reference.

Equipment for picking a die and placing it on a wafer is available in the market by multiple vendors such as the FC 300 by SET, and similar equipment by EV Group. Both companies support two step bonding as been described herein.

These die bonders are designed to support fast placement of about 5-10 micron alignment accuracy or slower placement with alignment accuracy of about 1 micron.

While 1 micron accuracy is good enough for TSV based 3D IC system, a much higher precision would be desirable for monolithic 3D applications as been presented in U.S. patent application Ser. No. 14/642,724. An embodiment for such monolithic 3D applications is a three phase die to wafer bonding scheme.

The first step would be to lightly tack dies to the target wafer using existing die to wafer bonders such as the before mentioned FC 300. Such placement would be done with better than 10 micron accuracy.

The second step could use a precision die to wafer bonder to relocate the dies that had been placed at 10 micron accuracy to better than about 400 nm, or to better than about 100 nm, or better than about 50 nm, or better than about 10 nm. The step could be done following the completion of the above first step. This precise tacking could use a stronger type of tacking than the first step. Following this stronger tacking second step a sub-step of testing and rework as needed could be done to support a higher yielding process. The equipment for such small step of dies realignment is not currently available as standard industry equipment. A co-pending application details a possible construction of such precise high throughput die realignment equipment. This new type equipment would be leveraging the pre-placement of dies at about 10 micron accuracy so the realignment movement is for only about 10 micron or less, making it easier to achieve 100 nm precision at the end of such small movement and doing so at a good throughput.

For this second step of precise alignment of the individual dies, die level alignment could be used.

Once the second step is complete and all dies on the target wafer/substrate are placed at the required precision such as 100 nm, and possibly tested to validate good tacking connection, the third step of simultaneous bonding could commence.

In the third step all dies are permanently bonded at their precise position. Some bonding techniques would leverage the surface tension of the bonding surface to hold the dies at their precise location and to achieve a self-alignment to

complete the third step of having all the die precisely and permanently boded to the target wafer.

Once all die had been bonded the wafer could be moved to further the process of 3D integration. A follow-on step could etch the low porosity layer 114. The porous layer etch rate is about 100,000 faster than the etch rate of solid (substantially non-porous) silicon. Low porosity layer 114 could be removed completely leaving the thin active circuits of device layer 118. Through layer vias could now be made to support the following steps of the 3D integration.

When the starting material structure used is the one illustrated in FIG. 1C, then the thinning process would start first by etching the top thin solid silicon layer 126 and then thick low porosity layer 114.

As illustrated in FIG. 3, exemplary processed wafer 300 may include multiple processed dies 302 and 'dicing streets' between dies such as horizontal street 310 and vertical street 312. As presented before for die to wafer bonding, the cutting of dies off exemplary processed wafer 310 would be done by etching rather than saw dicing. The etch would be relatively shallow at about 6-20 micron depth as the layers of multiple processed dies 302 was already thinned by cutting off the base wafer using, for example, the porous cutting layer 112. A typical wafer is circle (with or without a notch, etc.) with diameter size of about 150 mm to 300 mm, but may be greater than 300 mm. Typical dies are a rectangular size of 3x3 mm to 20x30 mm. Typical street widths are 50 micron to 200 micron.

As illustrated in FIG. 4, exemplary 4 dies 402 with streets for 'dicing'/etching such as horizontal street 410 and vertical street 412, and exemplary die alignment marks/structures 420. Typical die alignment mark/structure size could be 1-5 micron. The alignment area would be small relevant to the die size area so this additional overhead cost would be very small. The die alignment marks/structures 420 could be part of the metal layers of the active circuits of device layer 118 within each die 402. The die alignment marks/structures 420 could be formed by multiple metal layers. The die alignment marks/structures 420 could be formed close to the die edge 408, within about 20% of a die length/width, within about 10% of a die length/width, within about 5% of a die length/width.

The target wafer for which these dies would be precisely bonded to could have also die alignment marks. Those could be placed in the street area as those streets would not be etched or diced prior to the precise die bonding of step 2, especially if the design is that the die bonding would be toward the target bonding die edge. The target alignment marks/structures could correspond to the size of the die to be bonded if that die is smaller than the target die it is bonded to. If it is desired to bond smaller die to a target die and not toward the edge of that target die than it could be desired to have the target die alignment marks/structures inside the target die.

The target wafer could be processed with patterns according to the planed bonded dies so that all the areas which are not going to be covered with bonded dies would be protected from the planned die thinning etch step. Silicon nitride could be used for such or other layers with good etch selectivity to the underlying structure and to silicon and silicon oxide which would be etched for the thinning step.

After the thinning step, an oxide deposition and CMP planarization could be used to form a flat top surface for the follow-on 3D integration steps.

FIG. 5A illustrates some of the advantages of die level bonding. FIG. 5A illustrates a 3D semiconductor device 500 which includes a first die 502 and a smaller (by area) second

die 504, where the second die 504 is bonded and connected to first die 502. Second die 504 may be bonded and connected to first die 502 utilizing the techniques and methods herein. Second die 504 may be electrically connected to first die 502 using thru layer vias, such as is described herein and in the incorporated references, and these thru layer vias may have diameters less than about 1  $\mu\text{m}$ , or less than about 400 nm, or less than about 200 nm, or less than about 100 nm, or less than about 40 nm. The area of first die 502 may be greater than the area of second die 504 by a least about 5%, or by at least about 10%, or by at least about 25%, or by at least about 50%. Second die 504 may include alignment marks 520. FIG. 5A also illustrates a third die 506 bonded to the first die 502 and may be placed side by side to the second die 504 showing flexible heterogeneous integration of a 3D device.

FIG. 5B illustrates a side view of FIG. 5A's top view of a 3D device/system. While the first die 512 could have a thickness of 50 micron or even the original thickness of the original wafer plus processing (for example, about 775  $\mu\text{m}$  for a 300 mm wafer) the upper second die 514 and third die 516 could have a thickness of less than 10 micron or even thinner than 200 nm using the process described herein.

An advantage of the die level bonding is the flexibility with wafer size integration. Most modern fabs currently use larger than 280 mm wafers, commonly known as 300 mm or 12 inch wafers. In most cases it would be very hard to find a fab having a smaller wafer size being used for advance process nodes such as 28 nm or more advanced. Likewise it is very hard to find an old process nodes fab with 300 mm wafers. Old nodes such as 250 nm or older use smaller than 240 mm wafer size such wafer commonly known as 200 mm or 8 inch wafers. Smaller wafer size are also used for non-digital CMOS such as RF, high power, electro-optics and so forth. Most of the wafers that are non-silicon are only available with smaller than 240 mm wafer size. Die level 3D integration opens the ability to form 3D device with mixed technologies and overcomes the differing wafer diameter/size barrier.

An advantage of the die level bonding is the ability to pre-test the die before bonding and accordingly use what is commonly called Known Good Dies ("KGD"). In U.S. Pat. No. 9,142,55, incorporated herein by reference, a method for contact-less testing is described in reference to FIG. 24A-C. Such testing could be advantageous for very thin die bonding method as has been described herein.

While concepts in this patent application have been described with respect to 3D-ICs with two stacked device layers, those of ordinary skill in the art will appreciate that it can be valid for 3D-ICs with more than two stacked device layers. Additionally, some of the concepts may be applied to 2D ICs.

Some embodiments of the invention may include alternative techniques to build IC (Integrated Circuit) devices including techniques and methods to construct 3D IC systems. Some embodiments of the invention may enable device solutions with far less power consumption than prior art. The device solutions could be very useful for the growing application of mobile electronic devices and mobile systems such as, for example, mobile phones, smart phone, and cameras, those mobile systems may also connect to the internet. For example, incorporating the 3D IC semiconductor devices according to some embodiments of the invention within the mobile electronic devices and mobile systems could provide superior mobile units that could operate much more efficiently and for a much longer time than with prior art technology.

Smart mobile systems may be greatly enhanced by complex electronics at a limited power budget. The 3D technology described in the multiple embodiments of the invention would allow the construction of low power high complexity mobile electronic systems. For example, it would be possible to integrate into a small form function a complex logic circuit with high density high speed memory utilizing some of the 3D DRAM embodiments of the invention and add some non-volatile 3D NAND charge trap or RRAM described in some embodiments of the invention. Mobile system applications of the 3D IC technology described herein may be found at least in FIG. 156 of U.S. Pat. No. 8,273,610, the contents of which are incorporated by reference.

Furthermore, some embodiments of the invention may include alternative techniques to build systems based on integrated 3D devices including techniques and methods to construct 3D IC based systems that communicate with other 3DIC based systems. Some embodiments of the invention may enable system solutions with far less power consumption and intercommunication abilities at lower power than prior art. These systems may be called "Internet of Things", or IoT, systems, wherein the system enabler is a 3DIC device which may provide at least three functions: a sensing capability, a digital and signal processing capability, and communication capability. For example, the sensing capability may include a region or regions, layer or layers within the 3DIC device which may include, for example, a MEMS accelerometer (single or multi-axis), gas sensor, electric or magnetic field sensor, microphone or sound sensing (air pressure changes), image sensor of one or many wavelengths (for example, as disclosed in at least U.S. Pat. Nos. 8,283,215 and 8,163,581, incorporated herein by reference), chemical sensing, gyroscopes, resonant structures, cantilever structures, ultrasonic transducers (capacitive & piezoelectric). Digital and signal processing capability may include a region or regions, layer or layers within the 3D IC device which may include, for example, a microprocessor, digital signal processor, micro-controller, FPGA, and other digital and/or analog logic circuits, devices, and subsystems. Communication capability, such as communication from at least one 3D IC of IoT system to another, or to a host controller/nexus node, may include a region or regions, layer or layers within the 3D IC device which may include, for example, an RF circuit and antenna or antennas for wireless communication which might utilize standard wireless communication protocols such as G4, WiFi or Bluetooth, I/O buffers and either mechanical bond pads/wires and/or optical devices/transistors for optical communication, transmitters, receivers, codecs, DACs, digital or analog filters, modulators.

Energy harvesting, device cooling and other capabilities may also be included in the system. The 3DIC inventions disclosed herein and in the incorporated referenced documents enable the IoT system to closely integrate different crystal devices, for example a layer or layers of devices/transistors formed on and/or within mono or poly crystalline silicon combined with a layer or layers of devices/transistors formed on and/or within Ge, or a layer or layers of GaAs, InP, differing silicon crystal orientations, and so on. For example, incorporating the 3D IC semiconductor devices according to some embodiments of the invention as or within the IoT systems and mobile systems could provide superior IoT or mobile systems that could operate much more efficiently and for a much longer time than with prior art technology. The 3D IC technology herein disclosed provides a most efficient path for heterogeneous integration

with very effective integration reducing cost and operating power with the ability to support redundancy for long field life and other advantages which could make such an IoT System commercially successful.

Alignment is a basic step in semiconductor processing. For most cases it is part of the overall process flow that every successive layer is patterned when it is aligned to the layer below it. These alignments could all be done to one common alignment mark, or to some other alignment mark or marks that are embedded in a layer underneath. In today's equipment such alignment would be precise to below a few nanometers and better than 40 nm or better than 20 nm and even better than 10 nm. In general such alignment could be observed by comparing two devices processed using the same mask set. If two layers in one device maintain their relative relationship in both devices—to few nanometers—it is clear indication that these layers are aligned each to the other. This could be achieved by either aligning to the same alignment mark (sometimes called a zero mark alignment scheme), or one layer is using an alignment mark embedded in the other layer (sometimes called a direct alignment), or using different alignment marks of layers that are aligned to each other (sometimes called an indirect alignment).

In this document, the connection made between layers of, generally, single crystal, transistors, which may be variously named for example as thermal contacts and vias, Thru Layer Via (TLV), TSV (Thru Silicon Via), may be made and include electrically and thermally conducting material or may be made and include an electrically non-conducting but thermally conducting material or materials. A device or method may include formation of both of these types of connections, or just one type. By varying the size, number, composition, placement, shape, or depth of these connection structures, the coefficient of thermal expansion exhibited by a layer or layers may be tailored to a desired value. For example, the coefficient of thermal expansion of the second layer of transistors may be tailored to substantially match the coefficient of thermal expansion of the first layer, or base layer of transistors, which may include its (first layer) interconnect layers.

Base wafers or substrates, or acceptor wafers or substrates, or target wafers substrates herein may be substantially comprised of a crystalline material, for example, mono-crystalline silicon or germanium, or may be an engineered substrate/wafer such as, for example, an SOI (Silicon on Insulator) wafer or GeOI (Germanium on Insulator) substrate. Similarly, donor wafers herein may be substantially comprised of a crystalline material and may include, for example, mono-crystalline silicon or germanium, or may be an engineered substrate/wafer such as, for example, an SOI (Silicon on Insulator) wafer or GeOI (Germanium on Insulator) substrate, depending on design and process flow choices.

While mono-crystalline silicon has been mentioned as a transistor material in this document, other options are possible including, for example, poly-crystalline silicon, mono-crystalline germanium, mono-crystalline III-V semiconductors, graphene, and various other semiconductor materials with which devices, such as transistors, may be constructed within. Moreover, thermal contacts and vias may or may not be stacked in a substantially vertical line through multiple stacks, layers, strata of circuits. Thermal contacts and vias may include materials such as sp<sup>2</sup> carbon as conducting and sp<sup>3</sup> carbon as non-conducting of electrical current. Thermal contacts and vias may include materials such as carbon nano-tubes. Thermal contacts and vias may include materials such as, for example, copper, aluminum, tungsten, tita-

nium, tantalum, cobalt metals and/or silicides of the metals. First silicon layers or transistor channels and second silicon layers or transistor channels may be may be substantially absent of semiconductor dopants to form an undoped silicon region or layer, or doped, such as, for example, with elemental or compound species that form a p+, or p, or p-, or n+, or n, or n- silicon layer or region. A heat removal apparatus may include an external surface from which heat transfer may take place by methods such as air cooling, liquid cooling, or attachment to another heat sink or heat spreader structure. Furthermore, raised source and drain contact structures, such as etch and epi SiGe and SiC, and implanted S/Ds (such as C) may be utilized for strain control of transistor channel to enhance carrier mobility and may provide contact resistance improvements. Damage from the processes may be optically annealed. Strain on a transistor channel to enhance carrier mobility may be accomplished by a stressor layer or layers as well.

In this specification the terms stratum, tier or layer might be used for the same structure and they may refer to transistors or other device structures (such as capacitors, resistors, inductors) that may lie substantially in a plane format and in most cases such stratum, tier or layer may include the interconnection layers used to interconnect the transistors on each. In a 3D device as herein described there may at least two such planes called tier, or stratum or layer.

In a 3D IC system stack, each layer/stratum may include a different operating voltage than other layers/stratum, for example, one stratum may have V<sub>cc</sub> of 1.0 v and another may have a V<sub>cc</sub> of 0.7 v. For example, one stratum may be designed for logic and have the appropriate V<sub>cc</sub> for that process/device node, and another stratum in the stack may be designed for analog devices, and have a different V<sub>cc</sub>, likely substantially higher in value—for example, greater than 3 volts, greater than 5 volts, greater than 8 volts, greater than 10 volts. In a 3D IC system stack, each layer/stratum may include a different gate dielectric thickness than other layers/stratum. For example, one stratum may include a gate dielectric thickness of 2 nm and another 10 nm. The definition of dielectric thickness may include both a physical definition of material thickness and an electrically 'effective' thickness of the material, given differing permittivity of the materials. In a 3D IC system stack, each layer/stratum may include different gate stack materials than other layers/stratum. For example, one stratum may include a HKMG (High k metal gate) stack and another stratum may include a polycide/silicon oxide gate stack. In a 3D IC system stack, each layer/stratum may include a different junction depth than other layers/stratum. For example, the depth of the junctions may include a FET transistor source or drain, bipolar emitter and contact junctions, vertical device junctions, resistor or capacitor junctions, and so on. For example, one stratum may include junctions of a fully depleted MOSFET, thus its junction depth may be defined by the thickness of the stratum device silicon to the vertical isolation, and the other stratum may also be fully depleted devices with a junction depth defined similarly, but one stratum has a thicker silicon layer than the other with respect to the respective edges of the vertical isolation. In a 3D IC system stack, each layer/stratum may include a different junction composition and/or structure than other layers/stratum. For example, one stratum may include raised source drains that may be constructed from an etch and epitaxial deposition processing, another stratum in the stack may have implanted and annealed junctions or may employ dopant segregation techniques, such as those utilized to form DSS Schottky transistors.

It should be noted that one of the design requirements for a monolithic 3D IC design may be that substantially all of the stacked layers and the base or substrate would have their respective dice lines (may be called scribe-lines) aligned. As the base wafer or substrate is processed and multiple circuits may be constructed on semiconductor layers that overlay each other, the overall device may be designed wherein each overlaying layer would have its respective dice lines overlying the dice lines of the layer underneath, thus at the end of processing the entire layer stacked wafer/substrate could be diced in a single dicing step. There may be test structures in the streets between dice lines, which overall may be called scribe-lanes or dice-lanes. These scribe-lanes or dice-lanes may be 10 um wide, 20 um wide, 50 um wide 100 um wide, or greater than 100 um wide depending on design choice and die singulation process capability. The scribe-lanes or dice-lanes may include guard-ring structures and/or other die border structures. In a monolithic 3D design each layer test structure could be connected through each of the overlying layers and then to the top surface to allow access to these 'buried' test structure before dicing the wafer. Accordingly the design may include these vertical connections and may offset the layer test structures to enable such connection. In many cases the die borders comprise a protection structure, such as, for example, a guard-ring structure, die seal structure, ESD structure, and others elements. Accordingly in a monolithic 3D device these structures, such as guard rings, would be designed to overlay each other and may be aligned to each other during the course of processing. The die edges may be sealed by a process and structure such as, for example, described in relation to FIG. 183C of incorporated U.S. Pat. No. 8,273,610, and may include aspects as described in relation to FIG. 183A and 183B of same reference. One skilled in the art would recognize that the die seal can be passive or electrically active. On each 3D stack layer, or stratum, the electronic circuits within one die, that may be circumscribed by a dice-lane, may not be connected to the electronic circuits of a second die on that same wafer, that second die also may be circumscribed by a dice-lane. Further, the dice-lane/scribe-lane of one stratum in the 3D stack may be aligned to the dice-lane/scribe-lane of another stratum in the 3D stack, thus providing a direct die singulation vector for the 3D stack of strata/layers.

It will also be appreciated by persons of ordinary skill in the art that the invention is not limited to what has been particularly shown and described hereinabove. For example, drawings or illustrations may not show n or p wells for clarity in illustration. Moreover, transistor channels illustrated or discussed herein may include doped semiconductor material, but may instead include undoped semiconductor material. Further, any transferred layer or donor substrate or wafer preparation illustrated or discussed herein may include one or more undoped regions or layers of semiconductor material. Moreover, epitaxial regrow of source and drains may utilize processes such as liquid phase epitaxial regrowth or solid phase epitaxial regrowth, and may utilize flash or laser processes to freeze dopant profiles in place and may also permit non-equilibrium enhanced activation (superactivation). Further, transferred layer or layers may have regions of STI or other transistor elements within it or on it when transferred. Rather, the scope of the invention includes combinations and sub-combinations of the various features described hereinabove as well as modifications and variations which would occur to such skilled persons upon reading the foregoing description. Thus the invention is to be limited only by the appended claims.

I claim:

1. A 3D semiconductor device, the device comprising:
  - a first die comprising first transistors and a first interconnect;
  - a second die comprising second transistors and a second interconnect; and
  - a third die comprising third transistors and a third interconnect,
    - wherein said first die is overlaid by said second die,
    - wherein said first die is overlaid by said third die,
    - wherein said second die is bonded to said first die,
    - wherein said bonded comprises hybrid bonding,
    - wherein said first die comprises at least two first alignment marks positioned close to a first die edge of said first die,
    - wherein said second die is aligned to said first die with less than 800 nm alignment error,
    - wherein said second die comprises at least two second alignment marks positioned close to a second die edge of said second die, and
    - wherein said third die is bonded to said first die.
2. The 3D semiconductor device according to claim 1, wherein said second die comprises an array of memory cells,
  - wherein said first die comprises a control logic to control reads and writes to said array of memory cells, and
  - wherein said control logic comprises memory decoders.
3. The 3D semiconductor device according to claim 1, wherein said first die has a first die area and said second die has a second die area, and
  - wherein said first die area is at least 20% larger than said second die area.
4. The 3D semiconductor device according to claim 1, wherein said first wafer has a first diameter greater than 280 mm, and
  - wherein said second die is sourced from a second wafer with a second diameter less than 240 mm.
5. The 3D semiconductor device according to claim 1, further comprising:
  - a through second die via having a diameter of less than 400 nm.
6. A 3D semiconductor device, the device comprising:
  - a first die comprising first transistors and a first interconnect;
  - a second die comprising second transistors and a second interconnect; and
  - a third die comprising third transistors and a third interconnect,
    - wherein said first die is overlaid by said second die,
    - wherein said first die is overlaid by said third die,
    - wherein said second die is bonded to said first die,
    - wherein said bonded comprises hybrid bonding,
    - wherein said second die comprises an array of memory cells,
    - wherein said first die comprises a control logic,
    - wherein said second die is aligned to said first die with less than 800 nm alignment error,
    - wherein said first die comprises at least two first alignment marks positioned close to a first die edge of said first die,
    - wherein said second die comprises at least two second alignment marks positioned close to a second die edge of said second die, and
    - wherein said third die is bonded to said first die.
7. The 3D semiconductor device according to claim 6, wherein said first die is sourced from a first wafer with a diameter greater than 280 mm, and

## 17

wherein said second die is sourced from a second wafer with a diameter less than 240 mm.

8. The 3D semiconductor device according to claim 6, wherein said first die has a first die area and said second die has a second die area,  
5 wherein said first die area is at least 20% larger than said second die area.

9. The 3D semiconductor device according to claim 6, further comprising:

a through second die via having a diameter of less than 400 nm.

10. The 3D semiconductor device according to claim 6, wherein said control logic controls reads and writes to said array of memory cells.

11. A 3D semiconductor device, the device comprising:  
15 a first die comprising first transistors and a first interconnect;

a second die comprising second transistors and a second interconnect; and

20 a third die comprising third transistors and a third interconnect,

wherein said first die is overlaid by said second die,

wherein said first die is overlaid by said third die,

wherein said first die has a first die area and said second die has a second die area,

## 18

wherein said first die area is at least 20% larger than said second die area,

wherein said second die is pretested,

wherein said second die is bonded to said first die,

wherein said bonded comprises metal to metal bonding, wherein said first die comprises at least two first alignment marks positioned close to a first die edge of said first die,

wherein said second die is aligned to said first die with less than 800 nm alignment error,

wherein said second die comprises at least two second alignment marks positioned close to a second die edge of said second die, and

wherein said third die is bonded to said first die.

12. The 3D semiconductor device according to claim 11, wherein said second die comprises an array of memory cells,

wherein said first die comprises a control logic to control reads and writes to said array of memory cells.

13. The 3D semiconductor device according to claim 11, further comprising:

a through second die via having a diameter of less than 400 nm.

14. The 3D semiconductor device according to claim 11, wherein said bonded comprises hybrid bonding.

\* \* \* \* \*