

US011060845B2

(12) **United States Patent**  
**Amit et al.**

(10) **Patent No.:** **US 11,060,845 B2**  
(45) **Date of Patent:** **\*Jul. 13, 2021**

(54) **POLARIZATION MEASUREMENTS OF METROLOGY TARGETS AND CORRESPONDING TARGET DESIGNS**

(71) Applicant: **KLA-Tencor Corporation**, Milpitas, CA (US)

(72) Inventors: **Eran Amit**, Haifa (IL); **Barry Loevsky**, Milpitas, CA (US); **Andrew Hill**, Milpitas, CA (US); **Amnon Manassen**, Haifa (IL); **Nuriel Amir**, Milpitas, CA (US); **Vladimir Levinski**, Milpitas, CA (US); **Roie Volkovich**, Milpitas, CA (US)

(73) Assignee: **KLA Corporation**, Milpitas, CA (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **16/665,759**

(22) Filed: **Oct. 28, 2019**

(65) **Prior Publication Data**

US 2020/0158492 A1 May 21, 2020

**Related U.S. Application Data**

(63) Continuation of application No. 14/949,444, filed on Nov. 23, 2015, now Pat. No. 10,458,777, which is a (Continued)

(51) **Int. Cl.**

**G01B 11/06** (2006.01)

**G01B 11/27** (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC ..... **G01B 11/06** (2013.01); **G01B 11/272** (2013.01); **G01N 21/9501** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC ... G02F 1/00; G01B 2210/56; G01B 2290/70; G01B 11/06; G01B 11/272;

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,023,338 A 2/2000 Bareket  
7,528,941 B2 5/2009 Kandel et al.

(Continued)

FOREIGN PATENT DOCUMENTS

CN 1312466 A 9/2001  
CN 1632518 A 6/2005

(Continued)

OTHER PUBLICATIONS

Office Action dated Apr. 28, 2020 for Korean Application No. 10-2016-7001849.

(Continued)


*Primary Examiner* — Isiaka O Akanbi

(74) *Attorney, Agent, or Firm* — Suiter Swantz pc llo

(57) **ABSTRACT**

Targets, target elements and target design method are provided, which comprise designing a target structure to have a high contrast above a specific contrast threshold to its background in polarized light while having a low contrast below the specific contrast threshold to its background in non-polarized light. The targets may have details at device feature scale and be compatible with device design rules yet maintain optical contrast when measured with polarized illumination and thus be used effectively as metrology targets. Design variants and respective measurement optical systems are likewise provided.

**42 Claims, 22 Drawing Sheets**



**Related U.S. Application Data**

continuation of application No. PCT/US2014/044440, filed on Jun. 26, 2014.

(60) Provisional application No. 61/916,018, filed on Dec. 13, 2013, provisional application No. 61/840,339, filed on Jun. 27, 2013.

(51) **Int. Cl.**

**G01N 21/95** (2006.01)  
**G01N 21/956** (2006.01)  
**G06F 30/392** (2020.01)  
**G06F 30/398** (2020.01)  
**H01L 21/66** (2006.01)  
**G01N 21/88** (2006.01)

(52) **U.S. Cl.**

CPC ..... **G01N 21/956** (2013.01); **G06F 30/392** (2020.01); **G06F 30/398** (2020.01); **G01B 2210/56** (2013.01); **G01B 2290/70** (2013.01); **G01N 2021/8848** (2013.01); **H01L 22/30** (2013.01)

(58) **Field of Classification Search**

CPC ..... G01N 2021/8848; G01N 21/9501; G01N 21/956; H01L 22/30; G06F 30/392; G06F 30/398  
 USPC ..... 356/399-401, 237.2-237.6, 243.4, 356/601-614  
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

9,093,458 B2 7/2015 Amir et al.  
 9,934,353 B2 4/2018 El Kodadi et al.  
 2003/0021465 A1 1/2003 Adel et al.  
 2003/0133102 A1\* 7/2003 Opsal ..... G01N 21/956  
 356/237.1  
 2005/0012928 A1 1/2005 Sezginer et al.  
 2005/0286052 A1 12/2005 Huggins et al.  
 2006/0028957 A1\* 2/2006 Kim ..... G03F 7/70158  
 369/110.01  
 2007/0048629 A1 3/2007 Marokkey  
 2007/0279630 A1 12/2007 Kandel et al.  
 2008/0094630 A1 4/2008 Mieher et al.

2009/0002706 A1 1/2009 Weiss et al.  
 2010/0328636 A1 12/2010 Quaedackers et al.  
 2010/0330469 A1 12/2010 Marokkey  
 2012/0033215 A1 2/2012 Kandel et al.  
 2012/0123581 A1 5/2012 Smilde et al.  
 2012/0327503 A1\* 12/2012 Manassen ..... G02B 21/0016  
 359/291  
 2014/0240705 A1 8/2014 Takimoto  
 2015/0204664 A1\* 7/2015 Bringoltz ..... G02B 27/4272  
 356/492

FOREIGN PATENT DOCUMENTS

CN 101416043 A 4/2009  
 CN 101458464 A 6/2009  
 CN 101473219 A 7/2009  
 CN 101513366 A 8/2009  
 CN 101720450 A 6/2010  
 CN 101915556 A 12/2010  
 CN 102332165 A 8/2013  
 EP 2071402 A2 6/2009  
 JP 2003247807 A 9/2003  
 JP 2004508711 A 3/2004  
 JP 2006518942 A 8/2006  
 JP 2007096292 A 4/2007  
 JP 2009539109 A 11/2009  
 TW 201220447 A 5/2012

OTHER PUBLICATIONS

Office Action dated Aug. 29, 2018 for Taiwan Application No. 103122413.  
 Office Action dated Jan. 8, 2019 for JP Patent Application No. 2016-524217.  
 Brown, Dean P., 2010. Polarization and coherence-engineered illumination with applications in imaging (Doctoral dissertation, University of Rochester).  
 Smith, B.W. and Cashmore, J.S., Jul. 2002. Challenges in high NA, polarization, and photoresists. In SPIE's 27th Annual International Symposium on Microlithography (pp. 11-24). International Society for Optics and Photonics.  
 Office Action received in Chinese Application No. 201911299611.X, dated Jan. 5, 2021, 11 pages (with Translation).  
 Wang QiChao etc. Polarimetric contrast characteristics of camouflage target and background, Issue 6, vol. 25, "High Power Laser and Particle Beams," Issued Jun. 15, 2013, pp. 1355-1358.

\* cited by examiner






Figure 1A  
PRIOR ART

Figure 1B  
PRIOR ART




Figure 2






Figure 3A




Figure 3B





Figure 3C






Figure 4B




Figure 4A




Figure 4C








Figure 5A






Figure 5B








Figure 5C






Figure 5D






Figure 5D (cont. 1)






Figure 5D (cont. 2)






Figure 5E






Figure 5F






Figure 6A






Figure 6B






Figure 6C




Figure 6D






Figure 6E






Figure 6F

Figure 6G

Figure 6H






Figure 6J




Figure 6I






Figure 6K




Figure 6L






Figure 6M



300




Figure 7






Figure 7 (cont. 1)






Figure 7 (cont. 2)



## POLARIZATION MEASUREMENTS OF METROLOGY TARGETS AND CORRESPONDING TARGET DESIGNS

### CROSS-REFERENCE TO RELATED APPLICATIONS

The present application constitutes a continuation application of U.S. patent application Ser. No. 14/949,444, filed on Nov. 23, 2015, which application is a continuation of International Patent Application Serial No. PCT/US14/44440, filed on Jun. 26, 2014, which application claims the benefit under 35 U.S.C. 119(e) of U.S. Provisional Patent Application No. 61/840,339, filed on Jun. 27, 2013 and U.S. Provisional Patent Application No. 61/916,018, filed on Dec. 13, 2013, which applications are incorporated herein by reference in their entirety.

### FIELD OF THE INVENTION

The present invention relates to the field of metrology, and more particularly, to metrology targets.

### BACKGROUND OF THE INVENTION

Metrology targets are designed to enable the measurement of parameters that indicate the quality of wafer production steps and quantify the correspondence between design and implementation of structures on the wafer. Metrology targets as specific structures optimize the requirements for device similarity and for optical measurability. Compliance of targets to semiconductor manufacturing design rules contributes to accurate production of the targets but may reduce the optical measurability of the targets.

### BRIEF SUMMARY OF THE INVENTION

One aspect of the present invention provides a method comprising designing a target structure to have a high contrast above a specific contrast threshold to its background in polarized light while having a low contrast below the specific contrast threshold to its background in non-polarized light.

These, additional, and/or other aspects and/or advantages of the present invention are set forth in the detailed description which follows; possibly inferable from the detailed description; and/or learnable by practice of the present invention.

### BRIEF DESCRIPTION OF THE DRAWINGS

For a better understanding of embodiments of the invention and to show how the same may be carried into effect, reference will now be made, purely by way of example, to the accompanying drawings in which like numerals designate corresponding elements or sections throughout. In the accompanying drawings:

FIG. 1A is a high level schematic illustration of a target element according to the prior art;

FIG. 1B is a high level schematic illustration of a target element according to the prior art;

FIG. 2 is a high level schematic illustration of a target structure and its background, being part of a metrology target element, according to some embodiments of the invention;

FIG. 3A is a high level schematic illustration of a target designed to have contrast in polarized illumination, according to some embodiments of the invention;

FIG. 3B is a high level schematic illustration of a target designed to have contrast in polarized illumination, according to some embodiments of the invention;

FIG. 3C is a high level schematic illustration of a target designed to have contrast in polarized illumination, according to some embodiments of the invention;

FIG. 4A is a high level schematic illustration of segmentation modifications in a target, according to some embodiments of the invention;

FIG. 4B is a high level schematic illustration of segmentation modifications in a target, according to some embodiments of the invention;

FIG. 4C is a schematic illustration of simulation results of measurements of segmented target structure on continuous and on segmented background in polarized and non-polarized light, illustrating a much better contrast of the former, according to some embodiments of the invention;

FIG. 5A is a high level schematic illustration of process compatible target designs that maintain contrast by utilizing measurement by polarized light, according to some embodiments of the invention;

FIG. 5B is a high level schematic illustration of process compatible target designs that maintain contrast by utilizing measurement by polarized light, according to some embodiments of the invention;

FIG. 5C is a high level schematic illustration of process compatible target designs that maintain contrast by utilizing measurement by polarized light, according to some embodiments of the invention;

FIG. 5D is a high level schematic illustration of process compatible target designs that maintain contrast by utilizing measurement by polarized light, according to some embodiments of the invention;

FIG. 5E is a high level schematic illustration of process compatible target designs that maintain contrast by utilizing measurement by polarized light, according to some embodiments of the invention;

FIG. 5F is a high level schematic illustration of process compatible target designs that maintain contrast by utilizing measurement by polarized light, according to some embodiments of the invention;

FIG. 6A is a high level schematic illustration of optical illumination and measurement systems, according to some embodiments of the invention;

FIG. 6B is a high level schematic illustration of optical illumination and measurement systems, according to some embodiments of the invention;

FIG. 6C is a high level schematic illustration of optical illumination and measurement systems, according to some embodiments of the invention;

FIG. 6D is a high level schematic illustration of optical illumination and measurement systems, according to some embodiments of the invention;

FIG. 6E is a high level schematic illustration of optical illumination and measurement systems, according to some embodiments of the invention;

FIG. 6F is a high level schematic illustration of optical illumination and measurement systems, according to some embodiments of the invention;

FIG. 6G is a high level schematic illustration of optical illumination and measurement systems, according to some embodiments of the invention;



FIG. 6H is a high level schematic illustration of optical illumination and measurement systems, according to some embodiments of the invention;

FIG. 6I is a high level schematic illustration of optical illumination and measurement systems, according to some embodiments of the invention;

FIG. 6J is a high level schematic illustration of optical illumination and measurement systems, according to some embodiments of the invention;

FIG. 6K is a high level schematic illustration of optical illumination and measurement systems, according to some embodiments of the invention;

FIG. 6L is a high level schematic illustration of optical illumination and measurement systems, according to some embodiments of the invention;

FIG. 6M is a high level schematic illustration of optical illumination and measurement systems, according to some embodiments of the invention; and,

FIG. 7 is a high level flowchart illustrating a method, according to some embodiments of the invention.

### DETAILED DESCRIPTION OF THE INVENTION

Prior to the detailed description being set forth, it may be helpful to set forth definitions of certain terms that will be used hereinafter.

The terms “metrology target” or “target” as used herein in this application, are defined as structures designed or produced on a wafer which is used for metrological purposes. Non-limiting examples for metrology targets are imaging targets such as AIM (Advanced Imaging Metrology), BiB (Box-in-Box), AIMid and BLOSSOM and their corresponding variations and alternatives; and scatterometry targets such as SCOL (Scatterometry Overlay) and their corresponding variations and alternatives. The term “target element” is used herein in this application to refer to a part of a full target, which is designed according to the disclosed principles. Thus, any target element may be immediately used to design a full target; hence targets are referred to in the current application in terms of their target element designs and interchangeably therewith.

The term “target structure” as used herein in this application, is defined as a feature in the metrology target such as individual target areas or boxes, grating bars etc. Target structures may be full or empty (gaps), and may also be segmented, i.e., may comprise multiple smaller features which cumulatively constitute the target structure. A target and/or a periodic structure is referred to as comprising target structure, each “target structure” being a feature of the target that is to be distinguished from its background, the “background” being a wafer area proximate to a target structure on the same or on a different layer (above or below the target structure). The term “layer” as used herein in this application, is defined as any of the layers used in a photolithography process in any of its steps. The terms “continuous structure”, “empty region” or “full bar” as used herein in this application, are defined as continuous target structures such as empty regions or full bars having dimensions which are large with respect to typical device features. While most of the description refers to empty background regions rather than to full ones, it is explicitly noted that similar design principles are applicable to full backgrounds and respectively designed targets are likewise part of the disclosed invention.

The terms “metrology measurement” or “measurement” as used herein in this application, are defined as any metrology

measurement procedure used to extract information from metrology targets. For example, metrology measurements may be imaging of the targets or scatterometry measurements of the targets. Non-limiting examples for metrology measurements include overlay measurement (imaging or scatterometry), critical dimension (CD) measurement, focus and dose measurement etc. The term “overlay” as used herein in this application, is defined as a shift between layers which includes an unintentional component (e.g., due to process inaccuracies) that may cause production inaccuracies and is thus aim of a metrology measurement. The term “measurement direction” as used in this application refers to the direction along which a target structure is measured, for example, a direction along which the periodic structure is periodic. For example, the measurement direction of a grid as the periodic structure is perpendicular to the target elements (e.g., bars or segmented bars) which constitute the grid.

With specific reference now to the drawings in detail, it is stressed that the particulars shown are by way of example and for purposes of illustrative discussion of the preferred embodiments of the present invention only, and are presented in the cause of providing what is believed to be the most useful and readily understood description of the principles and conceptual aspects of the invention. In this regard, no attempt is made to show structural details of the invention in more detail than is necessary for a fundamental understanding of the invention, the description taken with the drawings making apparent to those skilled in the art how the several forms of the invention may be embodied in practice.

Before at least one embodiment of the invention is explained in detail, it is to be understood that the invention is not limited in its application to the details of construction and the arrangement of the components set forth in the following description or illustrated in the drawings. The invention is applicable to other embodiments or of being practiced or carried out in various ways. Also, it is to be understood that the phraseology and terminology employed herein is for the purpose of description and should not be regarded as limiting.

Targets, target elements and target design methods are provided, which comprise designing a target structure to have a high contrast above a specific contrast threshold to its background in polarized light while having a low contrast below the specific contrast threshold to its background in non-polarized light. The targets may have details at device feature scale and be compatible with device design rules, yet maintain optical contrast when measured with polarized illumination and thus be used effectively as metrology targets. Design variants and respective measurement optical systems are likewise provided. While current optical overlay targets contain features which are much bigger than the device and as a result suffer from more process damages, the disclosed targets provide contrast from polarization properties, are more process compatible and therefore represent the device overlay more accurately. Additional techniques to improve the contrast are also described below.

FIGS. 1A and 1B are high level schematic illustrations of target elements **90** according to the prior art. Currently used target structures **92** are continuous, either full (FIG. 1A) or empty (FIG. 1B) and exhibit optical contrast in coherent (or incoherent) illumination with respect to their backgrounds **91**, to enable imaging metrology (e.g., overlay measurements). For example, FIG. 1A schematically illustrates target structure **92** in a current layer over background **91** in a previous layer, with both target element **92** and background **91** being continuous. Target structures **92** may be



## 5

areas made mostly of one material while backgrounds **91** may be areas made mostly of a different material. In another example, FIG. 1B schematically illustrates target structure **92** as a gap in the same layer as background **91**, which is segmented. Background segmentation (termed “dummification”) is applied to make target elements **90** more process compatible, and the segmentation is usually carried out in an unresolved manner, i.e., using a small pitch (e.g., in the order of magnitude of 50 nm). As the typical dimension for currently used continuous target structures **92** is 1 μm, production processes such as etch and polish tend to introduce process-related production inaccuracies which are very sensitive to the process. Additionally, imaging targets may not represent the device correctly (e.g., the measured overlay may differ from the actual overlay) and even scatterometry targets may have target structures which are too big with respect to actual device features (e.g., several hundred nm vs. tens of nm, respectively). In imaging, the required contrast arises from the difference in the “filling factor” of different areas, which is the difference in reflection between target structures **92** and their backgrounds **91**. Thus, if target structures **92** are segmented to overcome the process-related inaccuracies, their contrast to their backgrounds **91** fades and they are not useful as targets.

FIG. 2 is a high level schematic illustration of a target structure **120** and its background **110**, being part of a metrology target element **100**, according to some embodiments of the invention. In contrast to prior art target elements **90**, disclosed metrology target elements **100** comprise segmented target structures **120** as well as segmented backgrounds **110**, and use polarized illumination to distinguish therebetween, thereby overcoming the problem of fading contrast upon introduction of segmentation. Advantageously, the disclosed invention uses the difference in the polarization activities of different areas rather than the difference in reflection properties. The disclosed design principles may be applied to any periodic or non-periodic target element **100** in any design metrology target.

Disclosed metrology targets comprise at least target structure **120** arranged to have a high contrast above a specific contrast threshold to its background **110** in polarized light while having a low contrast below the specific contrast threshold to its background **110** in non-polarized light. The specific contrast threshold is given by the used optical equipment or may be configured by adjusting the optical equipment to target specifications. For example, in the example illustrated in FIG. 2, target element **100** may be illuminated with linearly polarized light having a polarization **130** that is parallel to the segmentation lines of target structure **120**. The reflection difference between target structure **120** and background **110** arises from the interaction of the polarized illumination with the segmentation features and the influence of their respective directions on the measured signal. For example, segmentation pitch, critical dimension of segments, segmentation direction and segmentation pattern may vary between target structure **120** and background **110**.

In certain embodiments, target structure **120** comprises features which are perpendicular to background features of target element **100**. Other angles may be set between segmentation features of target structure **120** and background **110**. For example, segmentation of any of the elements and/or backgrounds may be diagonal. In certain embodiments, different polarization-altering patterns may be applied to target structure **120** and to background **110**. Illumination polarization must not be linear but may also be of any other specified characteristics (e.g., circular, modu-

## 6

lated etc.) and segmentation features may respectively be adapted to yield a difference in changing the illumination polarization in a way that enables distinguishing target structure **120** from background **110**.

In certain embodiments, the disclosed invention allows segmenting both target structure **120** and background **110** at a fine pitch, which may be selected to resemble device features. Such targets **100** represent device features better than existing targets, thus providing more accurate measurements, and are still well measurable using polarized illumination, thus not compromising accuracy and contrast as prior art targets do.

In certain embodiments, the ends of the segmentation lines at the border regions between target structures **120** and their respective background **110** are produced to control and enhance contrast between target structures **120** and backgrounds **110** in polarized illumination. In certain embodiments, target structure **120** may be spaced from background features thereof to a specified extent (see e.g., FIG. 4B below).

In certain embodiments, targets **100** are disclosed which further comprise additional layers in a region of target structure **100**, to maintain or to enhance the contrast of target structure **120** to its background **110** in polarized light.

FIGS. 3A-3C are high level schematic illustrations of targets **100** designed to have contrast in polarized illumination, according to some embodiments of the invention. Starting from target structures such as bars in layers **140**, **150** (previous and current layer, respectively, see FIG. 3A), targets structures **120** and their backgrounds **110** are segmented, e.g., perpendicularly, to yield contrast when illuminated in polarized illumination. FIG. 3B schematically illustrates an example in which targets structures **120** and their backgrounds **110** are segmented in previous layer **140** while backgrounds **110** in current layer **150** are left unsegmented (with target structure **120** in current layer segmented). FIG. 3C schematically illustrates an example in which targets structures **120** and their backgrounds **110** are segmented at both previous layer **140** and current layer **150**. In FIG. 3C, previous layer **140** and current layer **150** are shown separately in addition to target element **100** in which layers **140**, **150** are superposed. Segments **142** of targets structures **120** at previous layer **140** and segments **152** of targets structures **120** at current layer **150** may have the same or differing dimensions and characteristics (like pitch, end configuration etc.). Segments **141** of background **110** at previous layer **140** and segments **151** of background **110** at current layer **150** may have the same or differing dimensions and characteristics (like pitch, end configuration etc.). Furthermore, segmentation in different measurement directions (e.g., x and y) may have different characteristics.

In certain embodiments, first (or higher) order diffraction patterns of targets **100** may be measured to enhance the contrast between targets structures **120** and their backgrounds **110**. Measuring first order SCOL (at the pupil plane) or first order images (at the field plane) may enhance the information which is derived from the polarized illumination. Zeroth order diffraction pattern may be blocked or removed by interference to further enhance contrast.

FIGS. 4A and 4B are high level schematic illustrations of segmentation modifications in targets **100**, according to some embodiments of the invention. FIG. 4B schematically illustrates spacing segmentation of target structures **120** from segmentation of background **110**, with respect to FIG. 4A in which the segments interconnect. Introducing spaces **160** may improve the contrast therebetween under illumination with polarized light. Exact configuration of spaces



160 and line ends may be carried out to further enhance the contrast, using simulation or experimental settings. Segmentation pitches  $p_1$ ,  $p_2$  of target structures **120** and background **110** may be equal or differ, and segmentation pitches in X and Y directions may be equal or differ.

In certain embodiments, spaces **160** may be arranged to be measurable with or without use of polarized illumination. For example, spaces **160** may be in the order of magnitude of 100 nm wide. Spaces **160** may be configured to further enhance the contrast for polarized illumination measurements.

In certain embodiments, using polarized light measurements enables segmenting target structures **120** and/or background **110** and makes them thus more process compatible, while using polarized light instead of non-polarized illumination for measurements maintains or even enhances the contrast between target structures **120** and background **110** with respect to unsegmented target structures **120** and/or background **110**.

For example, FIG. 4C is a schematic illustration of simulation results (for AIM-like targets) of measurements of segmented target structure **92** on continuous background **91** (comparable to FIG. 1B above) in polarized and non-polarized light, illustrating a much better contrast of the former. FIG. 4C further illustrates measurements with polarized illumination of segmented target structure **120** on segmented background **110** (comparable to FIG. 2), which under non-polarized illumination produce no contrast at all. While polarized light measurements yield less contrast for target structure **120** than for target structure **92**, they still yield higher contrast than measurements of target structure **92** on non-segmented background **91**, and have the significant advantage of being more process compatible than the latter. Moreover, adjustment of segmentation pitch enables adjustment of contrast with respect to measurement conditions, as illustrated by the varying contrast with respect to three background pitches  $p$ ,  $p_3 < p_2 < p_1$  (in the illustrated case, the smaller the pitch the higher the contrast under polarized illumination). Furthermore, in case the contrast threshold is at or below the values achieved by non-polarized illumination, any of the polarized light measurements is below the threshold, thus providing sufficient contrast for measurements.

In certain embodiments, metrology measurements of targets **100** may be carried out by multiple acquisition techniques and under different measurement conditions, for example, using any of: different polarization directions (e.g., reducing results for orthogonal polarization with respect to direction **130**), spectral variation (color), focus variation, different numerical aperture (NA) size, etc. Several measurements with polarized illumination may be combined to enhance the contrast of target structures in composite images. For example, altering the focus between the measurements, or changing the wavelength between the measurements may provide further information that enhances contrast under polarized light measurements.

FIGS. 5A-5F are high level schematic illustrations of process compatible target designs **100** that maintain contrast by utilizing measurement by polarized light, according to some embodiments of the invention. Difference in the polarization activities of different areas in targets **100** may be used to derive metrology measurements instead or in addition to differences in reflection properties. For example, linear polarized light may be used to distinguish areas having horizontal lines from areas having vertical lines, depending on the polarization activity of the materials and the segmentation pitch. Using polarized light may thus

enable designing targets with features and intermediate spaces which have dimensions in the order or magnitude of the device features and spaces to improve the correspondence of measured target overlays and device overlays.

FIGS. 5A-5E schematically illustrate common target designs, modified according to the present invention, by illustrating previous layer **140**, current layer **150** and resulting compound targets **100**. Target structures in either layer are denoted by the numeral **120**, while segmented backgrounds are denoted by the numeral **110** as above. The examples are non-limiting with respect to segmentation details, which may be modified and adapted according to specific requirements, nor are they limiting with respect to exact target designs, but serve to illustrate the implementation of the disclosed design principles to common target designs.

FIGS. 5A-5C schematically illustrate alternative designs for AIMID-like targets that enable two dimensional overlay measurements. Similar principles may be applied to other target designs such as BiB and Blossom targets. While, in a non-limiting manner, all three designs have the same background segmentation **110** and target segmentation **120** at previous layer **140**, they differ in the segmentation of targets **120** in current layer **150**, which may be missing (FIG. 5B), parallel (FIG. 5A), or perpendicular (FIG. 5C) to the segmentation of targets **120** in previous layer **140**. Clearly, any segmentation feature of any of the elements may be modified according to requirements and pitch in either direction and in either structure may be varied. Appropriate measurement conditions (e.g., polarization details, wavelengths) may be applied to yield contrast between target structures **120** and their background **110**. In certain embodiments, an overlay may be induced between elements of layers **140**, **150** (see e.g., target structures **120** in target **100** in FIG. 5C) to enable scatterometry measurements of target **100** as well as imaging measurements thereof.

FIG. 5D schematically illustrates a segmented design for AIM-like targets that enable two one-dimensional overlay measurements. FIG. 5E schematically illustrates a segmented design for scatterometry targets that enable scatterometry measurements. FIG. 5F schematically illustrates a segmented design with enlarged features, which may be applicable to any of the above designs. FIGS. 5D and 5E represent merely single examples for the application of the disclosed design principles to such respective targets, and the whole variety of possible designs according to the guidelines disclosed above is considered to be disclosed herein. In the illustrated cases, background **110** and target structures **120** in previous layer **140** are segmented perpendicularly, while target structures in current layer **150** are continuous (i.e., full or gap bars). Segmentation may be applied to either or both background and targets structures in current layer **150**, in different orientations with respect to the segmentation of background **110** and target structures **120** in previous layer **140**. Relative segmentation orientation background **110** and target structures **120** in previous layer **140** may also be modified, and measurement conditions (e.g., polarization details, wavelengths) may be adjusted accordingly.

Referring to FIG. 5F, the distances  $d$  between segmentation features of background **110** and target structures **120** may be selected to optimize the measurements associated with target structures **120** using polarized light having specified characteristics (wavelengths, type and direction of polarization etc.).

The reflection of the boundary between target structures **120** and background **110** having different orientations may



be strongly dependent on the quality and characteristics of the line ends, line edge roughness and the distance between the lines. Targets **100** similar to those illustrated in FIG. **5F** may be used to quantify and monitor these parameters. For example, the side wall angle (SWA) may be indicative of distances  $d$ , e.g., identical SWAs may indicate identical distances  $d$  for all lines while differences in line SWA may be used as indication for pattern placement error or big variations in the line ends and edges quality. In certain embodiments, distances  $d$  may be varied among parallel lines (by design), within a small range of a few nanometers. Under such small changes, the side wall angle should be proportional to the change in distance  $d$ , and any deviation from such proportional behavior may be used to indicate the quality of the lithography process, and, as the patterning is at the device's scale, the dependency SWA( $d$ ) may be used as a direct indication for the device quality. In certain embodiments, intentional variation of distances  $d$  may be used in optical CD targets to enhance target sensitivity to scanner focus and dose variations for monitoring and control purposes. In certain embodiments, polarization parameters may be changed to extract additional information from the targets different responses to different polarization parameters.

FIGS. **6A-6M** are high level schematic illustrations of optical illumination and measurement systems **200**, according to some embodiments of the invention. In all figures, a non-polarized light source **70** is modified to provide polarized illumination of target **100** on wafer **75** via objective **77**. The collected illumination directed via lens **79** to detector **80** (such as a CCD camera) may be polarized similarly to or differently from the illumination.

For example, FIG. **6A** schematically illustrates using a Polarizing Beam Splitter (PBS) **210** with shutters **220**, **230** and mirrors **225**, **235** respectively for handling two types of polarization (e.g., s- and p-polarization) in the respective arms. The resulting illumination beam is combined from the two arms through beam splitter **240** and conducted to the optical axis of the measurement via beam splitter **78**. In this configuration, the polarization of the illumination beam is controlled by shutters **220**, **230**. In another example, FIG. **6B** illustrates implementing illumination polarization by controlling polarizers **220**, **230** which may be embedded in a rotating or translating plate **255** associated with an actuator **250** used to modify illumination beam polarization.

FIGS. **6C** and **6D** are high level schematic illustrations of optical systems **200** using an interferometer **260** to control illumination beam polarization and remove zeroth order patterns from the measurements. Illumination is provided from source **70** via lens **72** and through beam splitter **78** to interferometer **260**, which may comprise a focusing or non-focusing optical elements (**262**, **263** in FIGS. **6C**, **6D**, respectively) and a mirror **261**, used to yield destructive interference of the zeroth element component (as mirror **261** lacks a periodic structure and hence reflects only the zeroth order of illumination). The illumination beam may additionally be polarized, e.g., according to FIGS. **6A**, **6B** or otherwise.

FIG. **6E** schematically illustrates a physical zeroth order blocker **270**, designed according to principles taught in U.S. Pat. No. 7,528,941. For this optical configuration target **100** must be periodic; the illumination wavelength and target pitch are chosen to create spatial separation between the reflected orders at pupil plane **275** (after focusing by lens **274**). The zeroth order is then blocked geometrically (note that the central section of the measurement beam is blocked after pupil plane **275**—the arrow is drawn in the blocked

region). The illumination beam may additionally be polarized, e.g., according to FIGS. **6A**, **6B** or otherwise.

FIGS. **6F-6J** are high level schematic illustrations of optical systems having a variable retarder polarizer **280**, for measuring targets **100** using polarized light, according to some embodiments of the invention. FIGS. **6F-6H** schematically illustrate embodiments in which the reflected (collection) beam is polarized by variable retarder polarizer **280**, while FIGS. **6I-6J** schematically illustrate embodiments in which the incident beam is polarized by variable retarder polarizer **280**. Notation of the components and the optical elements (source **70**, lens **72**, beam splitter **78**, objective **77**, wafer **75**, lens **79** and detector **80**) is similar to the notation in FIGS. **6A-6E**, the numeral **79A** denotes an aperture at the pupil plane. FIG. **6F** illustrates an optical system which may be used for imaging measurements, while FIGS. **6G-6H** illustrates optical systems which may be used for scatterometry measurements. FIGS. **6I** and **6J** illustrate optical systems which may be used for imaging and scatterometry measurements, respectively.

FIGS. **6K-6M** are high level schematic illustrations of optical systems having a variable retarder polarizer **280**, for measuring targets **100** using polarized light, according to some embodiments of the invention. FIGS. **6K** and **6L** schematically illustrate sources for polarized illumination, resulting in two types of polarized light, e.g., s-polarized and p-polarized **70A**, **70B** respectively. FIG. **6K** illustrates use of Polarizing Beam Splitter (PBS) **210** with shutters **220**, **230** (as in FIG. **6A**) and FIG. **6L** illustrates use of variable retarder polarizer **280** instead of shutters **220**, **230**, in both cases differently polarized light is delivered via respective couplers and fibers **70A**, **70B** to the measurement part schematically illustrated in FIG. **6M**. FIG. **6M** schematically illustrates the measuring part, in which the s- and p-polarized beams from respective sources **70A**, **70B** are delivered via respective lenses **72A**, **72B**, s- and p-apodizers **73A**, **73B**, respective mirrors **225**, **235** to PBS **240A**, **240B** which introduce the polarized beams into beam splitter **78** and upon target **100** and deliver the reflected beams to respective s- and p-detectors **80A**, **80B**.

Advantageously, disclosed optical metrology targets in which the contrast comes from different polarization properties rather than or in addition to difference in the filling factor of different materials may be designed to be fully process compatible and designed according to the device parameters (e.g., with respect to critical dimension and pitch). Polarization of the illumination and/or the collection beam in different configurations may be used to enhance the contrast of the disclosed targets. The targets and measurement with polarized light may furthermore facilitate estimation of the line ends' uniformity and the line edge roughness of device-like features using optical overlay metrology. Moreover, each group of orientation line spaces or combination of different orientation lines may be used as targets for OCD applications, e.g., for monitor and control of scanner focus and dose.

FIG. **7** is a high level flowchart illustrating a method **300**, according to some embodiments of the invention. Method **300** may comprise stages for designing, producing and/or measuring targets **100**, such as any of the following stages, irrespective of their order. Stages of method **300** may be at least partly carried out by at least one computer processor (stage **370**). Certain embodiments comprise computer program products comprising a computer readable storage medium having computer readable program embodied therewith. The computer readable program may be configured to carry out, at least partially, any of the stages of



## 11

method 300. The disclosed invention comprises target design files and targets designed and produced according to stages of method 300, as well as metrology measurements of any of the disclosed metrology targets.

Method 300 comprises designing a target structure to have a high contrast above a specific contrast threshold to its background in polarized light while having a low contrast below the specific contrast threshold to its background in non-polarized light (stage 310). Method 300 may further comprise configuring the target structure to have features which are perpendicular to background features of the target structure (stage 320). Method 300 comprises designing the target structure to be fully process-compatible with respect to a production process thereof and thus achieve process compatibility while maintaining contrast through the use of polarized illumination (stage 325).

In certain embodiments, method 300 may further comprise designing additional layers in a region of the target structure to maintain (stage 330) or to enhance (stage 340) the contrast of the target structure to its background in polarized light. In certain embodiments, method 300 further comprises selecting segmentation pitches to enhance contrast (stage 345). Method 300 may further comprise spacing the target structure from background features thereof to a specified extent (stage 350). In certain embodiments, method 300 further comprises using two or more measurements, possibly with different illumination characteristics (such as polarization, wavelengths, focus etc.) to enhance the contrast and to derive additional information from comparison of the measurements (stage 355). Respective metrology measurements of target 100 and/or according to method 300 are likewise part of the present disclosure. Method 300 may comprise measuring the target structure repeatedly under varying illumination conditions and deriving additional measurement data from the multiple measurements, and the metrology measurements may comprise respective multiple measurements under varying illumination conditions and the derived additional measurement data.

Method 300 may further comprise producing the designed target structure (stage 375) and respective target design files. Such design files are part of the present disclosure as well. Method 300 may further comprise adapting any target type to be process compatible and exhibit contrast under polarized illumination (stage 365).

In certain embodiments, method 300 may further comprise measuring the target structure in polarized light to distinguish it from its background (stage 380) and possibly adjusting measurement conditions for each layer to enhance the contrast between the target structure contrast and its background (stage 360). Measuring 380 may be carried out using any of: coupled polarizers, alternating polarizers in an optical path of the measurement, an interferometer, variable retarder polarizers (applied to the illumination and/or collection beams, a zero order blocker at a pupil plane and/or polarized light sources or combinations thereof (stage 390).

Advantageously, the disclosed invention provides optical metrology targets 100 in which the contrast comes from different polarization properties rather than (or in addition to) a difference in the filling factor of different materials. Respective methods 300 provide guidelines to design principles of such targets. The optical metrology targets may be designed to be fully process compatible by being fully designed according to the device parameters (e.g., with respect to critical dimension and pitch). The disclosed invention further provides an optical system capable of measuring such targets using polarization and/or zero order blocking and/or zero order destructive interference. Polar-

## 12

ization of the illumination and/or the collection beam may be implemented in different configurations to enhance the contrast of target structures 120 with respect to their backgrounds 110.

In the above description, an embodiment is an example or implementation of the invention. The various appearances of “one embodiment”, “an embodiment”, “certain embodiments” or “some embodiments” do not necessarily all refer to the same embodiments.

Although various features of the invention may be described in the context of a single embodiment, the features may also be provided separately or in any suitable combination. Conversely, although the invention may be described herein in the context of separate embodiments for clarity, the invention may also be implemented in a single embodiment.

Certain embodiments of the invention may include features from different embodiments disclosed above, and certain embodiments may incorporate elements from other embodiments disclosed above. The disclosure of elements of the invention in the context of a specific embodiment is not to be taken as limiting their use in the specific embodiment alone.

Furthermore, it is to be understood that the invention can be carried out or practiced in various ways and that the invention can be implemented in certain embodiments other than the ones outlined in the description above.

The invention is not limited to those diagrams or to the corresponding descriptions. For example, flow need not move through each illustrated box or state, or in exactly the same order as illustrated and described.

Meanings of technical and scientific terms used herein are to be commonly understood as by one of ordinary skill in the art to which the invention belongs, unless otherwise defined.

While the invention has been described with respect to a limited number of embodiments, these should not be construed as limitations on the scope of the invention, but rather as exemplifications of some of the preferred embodiments. Other possible variations, modifications, and applications are also within the scope of the invention. Accordingly, the scope of the invention should not be limited by what has thus far been described, but by the appended claims and their legal equivalents.

What is claimed:

1. A system for measuring a metrology target element comprising:
  - a light source for generating illumination;
  - a set of optical elements configured to modify the illumination from the light source to form illumination of a selected polarization, wherein the set of optical elements are configured to direct the illumination of the selected polarization to a metrology target element, wherein the set of optical elements are configured to collect illumination reflected from the metrology target element,
  - wherein the metrology target element includes a segmented target structure and a segmented background region which provides the segmented target structure a first contrast above a specific contrast threshold to the segmented background region in polarized light and a second contrast below the specific contrast threshold to the segmented background region in non-polarized light;
  - a detector for measuring the illumination reflected from the metrology target element; and
  - at least one computer processor configured to:
    - acquire a first set of measurements of the target element using a first set of one or more illumination charac-



## 13

- teristics configured to produce a first contrast between the segmented target structure and the segmented background region; and  
 acquire a second set of measurements of the target element using a second set of one or more illumination characteristics configured to produce a second contrast between the segmented target structure and the segmented background region different from the first contrast.
2. The system of claim 1, wherein the at least one computer processor is further configured to:  
 derive one or more characteristics of the target element based on the first set of measurements and the second set of measurements.
3. The system of claim 2, wherein the one or more characteristics of the target element comprise at least one of an optical overlay measurement, a line uniformity measurement, or a line edge roughness measurement.
4. The system of claim 1, wherein acquiring a second set of measurements of the target element using a second set of one or more illumination characteristics comprises:  
 selectively adjusting one or more illumination characteristics of the first set of one or more illumination characteristics in order to enhance a contrast between the segmented target structure and the segmented background region.
5. The system of claim 1, wherein the first set of one or more illumination characteristics includes polarized light, and the second set of one or more illumination characteristics includes non-polarized light.
6. The system of claim 1, wherein at least one of the first set of one or more illumination characteristics and the second set of one or more illumination characteristics comprise at least one of a selected polarization, a selected wavelength, or a selected focus.
7. The system of claim 1, wherein the segmented target structure includes a first segmentation direction and a first pitch and the segmented background region includes a second segmentation direction and a second pitch.
8. The system of claim 1, wherein one or more segmentation features of the segmented target structure and one or more segmentation features of the segmented background region provide a selected contrast level between the segmented target structure and the segmented background region when illuminated with light of a selected polarization.
9. The system of claim 1, wherein a difference between the one or more segmentation features of the segmented target structure and the one or more segmentation features of the segmented background region provide the selected contrast level between the segmented target structure and the segmented background region when illuminated with light of a selected polarization.
10. The system of claim 8, wherein at least one of the one or more segmentation features of the segmented target structure or the one or more segmentation features of the segmented background region comprise:  
 at least one of segmentation pitch, critical dimension of segments, segmentation direction or segmentation pattern.
11. The system of claim 1, wherein the segmented background region is formed within the segmented target structure at one or more additional layers such that the segmented background region overlaps the segmented target structure.
12. The system of claim 1, wherein the segmented background region is spaced from the segmented target structure by a selected distance.

## 14

13. The system of claim 1, wherein the selected polarization comprises:  
 at least one of linear polarization, circular polarization, s-polarization, p-polarization, or modulated polarization.
14. The system of claim 1, further comprising an interferometer configured to remove zeroth order diffraction patterns from the reflected illumination.
15. The system of claim 14, wherein the detector is further configured to measure one or more first order diffraction patterns from the reflected illumination following the removal of the one or more zeroth order diffraction patterns from the reflected illumination.
16. A metrology target, comprising:  
 a first metrology target element formed in a first layer, the first metrology target element comprising:  
 a plurality of segmented target structures having a first segmentation direction and a first pitch, wherein the segmented target structures exhibit a first polarization activity, and  
 a segmented background region having a second segmentation direction different from the first segmentation direction and a second pitch different from the first pitch, wherein the segmented background region exhibits a second polarization activity different from the first polarization activity, wherein the segmented background region and the segmented target structure are formed such that at least one of the first pitch or the second pitch provides the segmented target structure a first contrast above a specific contrast threshold to the segmented background region in polarized light and a second contrast below the specific contrast threshold to the segmented background region in non-polarized light; and  
 a second metrology target element formed in a second layer, the second metrology target comprising:  
 a plurality of target structures,  
 wherein the first metrology target element and the second metrology target element are at least partially overlapping, wherein the plurality of segmented target structures of the first metrology target element and the plurality of target structures of the second metrology target element are not overlapping.
17. The metrology target of claim 16, wherein the plurality of target structures of the second metrology target element formed in the second layer comprise a plurality of segmented target structures.
18. The metrology target of claim 17, wherein the plurality of segmented target structures of the second metrology target element have a segmentation direction parallel to the first segmentation direction, and a pitch equivalent to the first pitch.
19. The metrology target of claim 17, wherein the plurality of segmented target structures of the second metrology target element have a segmentation direction perpendicular to the first segmentation direction.
20. The metrology target of claim 16, wherein the plurality of target structures of the second metrology target element formed in the second layer comprise a plurality of unsegmented target structures.
21. The metrology target of claim 16, wherein the first pitch is perpendicular to the second pitch.
22. The metrology target of claim 16, wherein one or more segmentation features of the plurality of segmented target structures and one or more segmentation features of the segmented background region provide a selected contrast level between the plurality of segmented target struc-



## 15

tures and the segmented background region when illuminated with light of a selected polarization.

**23.** The metrology target of claim **22**, wherein the selected polarization comprises:

at least one of linear polarization, circular polarization, s-polarization, p-polarization, or modulated polarization.

**24.** The metrology target of claim **22**, wherein at least one of the one or more segmentation features of the plurality of segmented target structures or the one or more segmentation features of the segmented background region comprise:

at least one of segmentation pitch, critical dimension of segments, segmentation direction, or segmentation pattern.

**25.** The metrology target of claim **22**, wherein the plurality of segmented target structures of the first metrology target and the segmented background region of the first metrology target are separated by a boundary between each segmented target structure and the segmented background region.

**26.** A metrology target, comprising:

a first metrology target element formed in a first layer, the first metrology target element comprising:

a plurality of segmented target structures, the plurality of segmented target structures comprising:

a first sub-set of segmented target structures within a first quadrant of the metrology target, the first sub-set of segmented target structures having a first segmentation direction and a first pitch;

a second sub-set of segmented target structures within a second quadrant of the metrology target, the second sub-set of segmented target structures having a second segmentation direction perpendicular to the first segmentation direction;

a third sub-set of segmented target structures within a third quadrant of the metrology target, the third sub-set of segmented target structures having a third segmentation direction parallel to the first segmentation direction;

a fourth sub-set of segmented target structures within a fourth quadrant of the metrology target, the fourth sub-set of segmented target structures having a fourth segmentation direction parallel to the second segmentation direction; and

a segmented background region having a fifth segmentation direction perpendicular to the first segmentation direction in the first quadrant and the third quadrant, and a sixth segmentation direction perpendicular to the second segmentation direction in the second quadrant and the fourth quadrant.

**27.** The metrology target of claim **26**,

wherein the first sub-set of segmented target structures and the third sub-set of segmented target structures are separated along a direction which is perpendicular to the first segmentation direction and the third segmentation direction, and

wherein the second sub-set of segmented target structures and the fourth sub-set of segmented target structures are separated along a direction which is perpendicular to the second segmentation direction and the fourth segmentation direction.

**28.** The metrology target of claim **26**, further comprising:

a second metrology target element formed in a second layer, the second metrology target element comprising: a plurality of target structures, the plurality of target structures comprising:

## 16

a first sub-set of target structures within the first quadrant of the metrology target separated along a direction which is parallel to the fifth segmentation direction;

a second sub-set of target structures within the second quadrant of the metrology target separated along a direction which is parallel to the sixth segmentation direction;

a third sub-set of target structures within the third quadrant of the metrology target separated along a direction which is parallel to the fifth segmentation direction;

a fourth sub-set of target structures within the fourth quadrant of the metrology target separated along a direction which is parallel to the sixth segmentation direction,

wherein the first metrology target element and the second metrology target element are at least partially overlapping, wherein the plurality of segmented target structures of the first metrology target element and the plurality of target structures of the second metrology target element are not overlapping.

**29.** The metrology target of claim **26**, wherein one or more segmentation features of the plurality of segmented target structures and one or more segmentation features of the segmented background region provide a selected contrast level between the plurality of segmented target structures and the segmented background region when illuminated with light of a selected polarization.

**30.** The metrology target of claim **29**, wherein the selected polarization comprises:

at least one of linear polarization, circular polarization, s-polarization, p-polarization, or modulated polarization.

**31.** The metrology target of claim **29**, wherein at least one of the one or more segmentation features of the plurality of segmented target structures or the one or more segmentation features of the segmented background region comprise:

at least one of segmentation pitch, critical dimension of segments, segmentation direction or segmentation pattern.

**32.** The metrology target of claim **29**, wherein the plurality of segmented target structures of the first metrology target and the segmented background region of the first metrology target are separated by a boundary between each segmented target structure and the segmented background region.

**33.** A method of measuring a metrology target element comprising:

illuminating the metrology target element with illumination including a first set of one or more illumination characteristics, the target element including a segmented target structure having a first segmentation direction, a segmented background region having a second segmentation direction perpendicular to the first segmentation direction, wherein at least one of a segmentation pitch of the segmented background region or a segmentation pitch of the segmented target structure provide a first contrast above a specified contrast threshold under polarized light and a second contrast below the specific contrast threshold to the segmented background region in non-polarized light,

acquiring a first set of measurements of the target element based on illumination reflected from the target element, the illumination including the first set of one or more illumination characteristics;



17

illuminating the metrology target element with illumination including a second set of one or more illumination characteristics; and

acquiring a second set of measurements of the target element based on illumination reflected from the target element, the illumination including the second set of one or more illumination characteristics.

**34.** The method of claim **33**, further comprising: deriving one or more characteristics of the target element based on the first set of measurements and the second set of measurements.

**35.** The method of claim **34**, wherein the one or more characteristics of the target element comprise at least one of an optical overlay measurement, a line uniformity measurement, or a line edge roughness measurement.

**36.** The method of claim **33**, wherein acquiring a second set of measurements of the target element comprises: selectively adjusting one or more illumination characteristics of the first set of one or more illumination characteristics in order to enhance a contrast between the segmented target structure and the segmented background region.

**37.** The method of claim **33**, wherein the first set of one or more illumination characteristics includes polarized light, and the second set of one or more illumination characteristics includes non-polarized light.

**38.** The method of claim **33**, wherein one or more segmentation features of the segmented target structure and one or more segmentation features of the segmented back-

18

ground region provide a selected contrast level between the segmented target structure and the segmented background region when illuminated with light of a selected polarization.

**39.** The method of claim **38**, wherein a difference between the one or more segmentation features of the segmented target structure and the one or more segmentation features of the segmented background region provide the selected contrast level between the segmented target structure and the segmented background region when illuminated with light of a selected polarization.

**40.** The method of claim **39**, wherein at least one of the one or more segmentation features of the segmented target structure or the one or more segmentation features of the segmented background region comprise:

at least one of segmentation pitch, critical dimension of segments, segmentation direction or segmentation pattern.

**41.** The method of claim **38**, wherein the illuminating the metrology target element with illumination including a first set of one or more illumination characteristics comprises: illuminating the metrology target element with illumination of at least one of linear polarization, circular polarization, s-polarization, p-polarization, or modulated polarization.

**42.** The method of claim **38**, further comprising: removing of one or more zeroth order diffraction patterns from the reflected illumination.

\* \* \* \* \*