

US011068836B2

(12) **United States Patent**
Burch, V et al.

(10) **Patent No.: US 11,068,836 B2**
(45) **Date of Patent: Jul. 20, 2021**

(54) **SYSTEMS AND METHODS FOR
MONITORING THE INTERNAL STORAGE
CONTENTS OF A SHIPMENT STORAGE
USING ONE OR MORE INTERNAL
MONITOR DRONES**

(58) **Field of Classification Search**
CPC G06Q 10/08; G06Q 10/0832; G06Q
10/0833; G06Q 50/28; G06Q 50/30;
(Continued)

(71) Applicant: **FEDERAL EXPRESS
CORPORATION**, Memphis, TN (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

(72) Inventors: **Reuben F. Burch, V**, Mississippi State,
MS (US); **David A. Doyle**, Hernando,
MS (US); **Brian D. Popp**, Southaven,
MS (US)

6,948,681 B2 * 9/2005 Stupakis B64C 39/02
244/117 R
8,982,207 B2 3/2015 Jang
(Continued)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **FEDERAL EXPRESS
CORPORATION**, Memphis, TN (US)

JP 2015131713 A 7/2015
WO 2017019728 A1 2/2017

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

OTHER PUBLICATIONS

Japanese Patent Application No. 2019-512708 Office Action dated
Sep. 15, 2020.

(21) Appl. No.: **16/849,207**

(Continued)

(22) Filed: **Apr. 15, 2020**

Primary Examiner — Tan Q Nguyen

(74) *Attorney, Agent, or Firm* — Withers & Keys, LLC

(65) **Prior Publication Data**

US 2020/0258039 A1 Aug. 13, 2020

(57) **ABSTRACT**

A drone-based monitored storage system includes a shipment storage with an interior storage area and a drone storage area, an internal docking station, and an internal monitor drone disposed within the shipment storage that aerially monitors the items being shipped within the interior storage area. The monitor drone includes an airframe, battery, onboard controller, lifting engines and lifting rotors responsive to flight control input, communication interface, sensor array that gathers sensory information as the drone moves within the interior shipment storage area of the shipment storage, and a drone capture interface that can selectively mate to the internal docking station to hold the monitor drone in a secure position. The monitor drone can gather the sensory information (such as environment information, image information, multidimensional mapping information, and scanned symbol information) and autono-

(Continued)

Related U.S. Application Data

(62) Division of application No. 15/710,957, filed on Sep.
21, 2017, now Pat. No. 10,664,791.


(Continued)

(51) **Int. Cl.**
G06Q 10/08 (2012.01)
G01S 5/00 (2006.01)

(Continued)

(52) **U.S. Cl.**
CPC **G06Q 10/0833** (2013.01); **B64C 39/024**
(2013.01); **B64D 47/08** (2013.01);

(Continued)



mously detect conditions of items being shipped based upon the sensory information from the sensor array.

51 Claims, 46 Drawing Sheets

Related U.S. Application Data

(60) Provisional application No. 62/400,906, filed on Sep. 28, 2016.

(51) Int. Cl.

G06Q 50/30 (2012.01)
H04W 4/48 (2018.01)
G01S 19/49 (2010.01)
B64C 39/02 (2006.01)
G05D 1/00 (2006.01)
B64F 1/22 (2006.01)
B64D 47/08 (2006.01)
G06Q 50/28 (2012.01)

(52) U.S. Cl.

CPC *B64F 1/222* (2013.01); *G01S 5/0018* (2013.01); *G01S 19/49* (2013.01); *G05D 1/0094* (2013.01); *G06Q 10/08* (2013.01); *G06Q 10/083* (2013.01); *G06Q 10/0832* (2013.01); *G06Q 50/28* (2013.01); *G06Q 50/30* (2013.01); *H04W 4/48* (2018.02); *B64C 2201/123* (2013.01); *B64C 2201/127* (2013.01); *B64C 2201/128* (2013.01); *B64C 2201/141* (2013.01)

(58) Field of Classification Search

CPC *G01S 5/0018*; *G01S 19/49*; *B64C 39/024*; *B64C 2201/123*; *B64C 2201/127*; *B64C 2201/128*; *B64C 2201/141*

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

8,989,053 B1 3/2015 Skaaksrud et al.
 9,096,189 B2 8/2015 Golden
 9,373,014 B1 6/2016 Mehranfar
 9,487,356 B1 11/2016 Aggarwal
 9,609,288 B1 3/2017 Richman et al.
 9,718,564 B1 8/2017 Beckman et al.
 9,928,749 B2 3/2018 Gil et al.
 10,102,586 B1 10/2018 Marlow et al.
 10,301,018 B2 5/2019 Mucci
 10,384,777 B1 8/2019 Welsh
 10,453,348 B2 10/2019 Speasl et al.
 10,482,418 B2 11/2019 Burch, V et al.
 10,657,485 B2 5/2020 Burch et al.
 10,664,791 B2 5/2020 Burch et al.
 10,679,172 B2 6/2020 Burch et al.
 10,878,365 B2 12/2020 Burch, V et al.
 2008/0165047 A1 7/2008 Fisher et al.

2010/0250022 A1 9/2010 Hines et al.
 2013/0033381 A1* 2/2013 Breed B60T 7/16
 340/568.1
 2013/0157611 A1 6/2013 Small
 2013/0233964 A1 9/2013 Woodworth et al.
 2014/0032034 A1 1/2014 Raptopoulos et al.
 2014/0277854 A1 9/2014 Jones et al.
 2014/0323038 A1 10/2014 Hubbell et al.
 2014/0354809 A1 12/2014 Shondel
 2015/0120094 A1 4/2015 Kimchi et al.
 2015/0158513 A1 6/2015 Costa et al.
 2015/0302669 A1 10/2015 Gonnissen et al.
 2015/0349917 A1 12/2015 Skaaksrud
 2016/0039436 A1 2/2016 Bhagwatkar et al.
 2016/0129999 A1 5/2016 Mays
 2016/0159496 A1 6/2016 O'Toole
 2016/0185466 A1 6/2016 Dreano, Jr.
 2016/0200438 A1 7/2016 Bokeno et al.
 2016/0207627 A1 7/2016 Hoareau et al.
 2016/0244187 A1 8/2016 Byers et al.
 2016/0253907 A1 9/2016 Taveira
 2016/0253908 A1 9/2016 Chambers et al.
 2016/0266579 A1 9/2016 Chen et al.
 2016/0272317 A1 9/2016 Cho et al.
 2016/0275801 A1 9/2016 Kopardekar
 2016/0309341 A1 10/2016 Priest et al.
 2016/0339277 A1 11/2016 Angelopoulos
 2016/0364989 A1 12/2016 Speasl et al.
 2017/0041949 A1 2/2017 Ngo et al.
 2017/0045894 A1 2/2017 Canoy et al.
 2017/0092109 A1 3/2017 Trundle et al.
 2017/0129603 A1 5/2017 Raptopoulos et al.
 2017/0139409 A1 5/2017 Clarke
 2017/0181117 A1 6/2017 Dowlatkhah et al.
 2017/0199520 A1 7/2017 Glatfelter
 2017/0253330 A1 9/2017 Saigh et al.
 2017/0257779 A1 9/2017 Zerick et al.
 2017/0337510 A1 11/2017 Shroff et al.
 2017/0349283 A1 12/2017 Paunicka et al.
 2018/0033315 A1 2/2018 Winkle
 2018/0047295 A1 2/2018 Ricci
 2018/0050798 A1 2/2018 Kapuria
 2018/0089622 A1 3/2018 Burch, V et al.
 2018/0170540 A1 6/2018 Claybrough
 2018/0245365 A1 8/2018 Wankewycz
 2018/0346120 A1 12/2018 Hoareau et al.
 2019/0039731 A1 2/2019 Marcath et al.
 2019/0120929 A1 4/2019 Meadow
 2019/0122455 A1 4/2019 Howard et al.
 2019/0176862 A1 6/2019 Kumar et al.
 2019/0220819 A1 7/2019 Banvait et al.
 2020/0017210 A1 1/2020 Neubecker et al.
 2020/0017218 A1 1/2020 Ahmad et al.
 2020/0346736 A1* 11/2020 Krasnoff B64C 27/52

OTHER PUBLICATIONS

FMCSA, "Driver's Handbook on Cargo Securement", Nov. 2003.
 Dhital et al., "A Fully Non-Contact Ultrasonic Propagation Imaging System for Closed Surface Crack Evaluation", *Experimental Mechanics*, Nov. 1, 2011, pp. 1111-1122.
 FAA, "Air Cargo Operations", Advisory Circular, Jun. 25, 2015, U.S. Department of Transportation, AC No. 120-85A.

* cited by examiner

FIG. 1A




FIG. 1B




FIG. 1C




FIG. 2




FIG. 3




FIG. 4A




FIG. 4B




FIG. 5




FIG. 6




FIG. 7




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 8D




FIG. 8E




FIG. 8F




FIG. 8G




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18A




FIG. 18B




FIG. 18C




FIG. 18D




FIG. 18E




FIG. 18F




FIG. 19A




FIG. 19B




FIG. 20




FIG. 21




FIG. 22




FIG. 23A




FIG. 23B




FIG. 24




Fig. 25A




Fig. 25B




Fig. 25C




FIG. 26A




FIG. 26B




FIG. 27




FIG. 28




FIG. 29





FIG. 30



1

**SYSTEMS AND METHODS FOR
MONITORING THE INTERNAL STORAGE
CONTENTS OF A SHIPMENT STORAGE
USING ONE OR MORE INTERNAL
MONITOR DRONES**

PRIORITY AND RELATED APPLICATIONS

The present application hereby claims the benefit of priority to related U.S. Provisional Patent Application No. 62/400,906 and entitled "Drone-based Monitoring of Shipped Items in a Delivery Vehicle, Drone-based Inspections of the Delivery Vehicle, and Providing Adaptive Extension of Communications With One or More Items Shipped Within the Delivery Vehicle Using a Drone-based Aerial Communication Hub."

The present divisional application is also related in subject matter to the following U.S. non-provisional patent applications where each also claims the benefit of priority to the same above-referenced provisional patent application: (1) Non-Provisional patent application Ser. No. 15/711,980 entitled "Systems and Methods for Inspecting a Delivery Vehicle Using a Paired Inspection Drone"; (2) Non-Provisional patent application Ser. No. 15/711,005 entitled "Aerial Drone-based Systems and Methods for Adaptively Providing an Aerial Relocatable Communication Hub Within a Delivery Vehicle"; (3) Non-Provisional patent application Ser. No. 15/711,136 entitled "Enhanced Systems, Apparatus, and Methods for Positioning of an Airborne Relocatable Communication Hub Supporting a Plurality of Wireless Devices"; (4) Non-Provisional patent application Ser. No. 15/711,167 entitled "Paired Drone-based Systems and Methods for Conducting a Modified Inspection of a Delivery Vehicle"; (5) Non-Provisional patent application Ser. No. 15/711,244 entitled "Paired Drone-based Systems and Methods for Conducting a Verified Inspection of a Delivery Vehicle."

FIELD OF THE DISCLOSURE

The present disclosure generally relates to systems, apparatus, and methods in the field of airborne drones integrally applied to different logistics operations and, more particularly, to various aspects of systems, apparatus, and methods related to logistics operations using an aerial inspection or communication drone to enhance monitoring of shipped items in a delivery vehicle, perform various types of inspections of the delivery vehicle, and providing a drone-based airborne relocatable communication hub within a delivery vehicle as the drone is exclusively paired with the delivery vehicle.

BACKGROUND

Delivery vehicles are often used as part of a logistics operation that ships one or more items from one location to another. Examples of such a delivery vehicle may include an aircraft, an automotive vehicle (such as a delivery van or a tractor trailer), a rail car, or a marine vessel. Logistics operations that ship items from one location to another depend upon a sufficient operational status of the delivery vehicle in order to safely and securely move such items as well as for the delivery vehicle to safely and securely maintain the items in a desired configuration while being transported within a storage area of the delivery vehicle. Such a storage area (more generally referred to as a shipment storage) may, for example, come in the form of a storage

2

compartment of an aircraft, a storage area on a delivery van, a trailer that is moved by a truck, a train car capable of being moved by a locomotive on a railway system, or a cargo hold of a marine vessel.

One problem commonly faced when maintaining items within such a storage area or shipment storage is how to monitor such items. In some instances, the items may be equipped with radio frequency identification (RFID) tags and interrogated by multiple RFID readers disposed within different parts of the shipment storage. While an RFID reader and its reader antenna has a characteristic read range for communicating with RFID tags, the read range may pose a limitation given the size of the shipment storage as well as for items that are not equipped with such RFID tags. There remains a need to monitor the internal storage contents of a shipment storage in a more robust and inclusive manner as well as in an adaptive way that avoids the need for large numbers of fixed monitors.

Beyond the challenges with monitoring items maintained within a shipment storage, further problems may be encountered with delivery vehicle based logistics operations that involve inspecting key parts of the delivery vehicle. For example, manual inspection of parts of a delivery vehicle can be undesirably expensive and time consuming for logistics personnel, such as flight crew personnel responsible for operating an aircraft type of delivery vehicle or maintenance personnel responsible for servicing such an aircraft. In some situations, the point to be inspected may not be easily reached or viewed by such personnel and may unfortunately require deployment of support structures, such as a ladder or gantry in order to gain access to such an inspection point. Doing so undesirably slows down the delivery vehicle based logistics operation.

Further still, problems may be encountered with limited communications with and/or between one or more items being shipped within the delivery vehicle. For example, in some instances, the communication range of a respective item is not far enough to allow communication with another item or other network device (such as a wireless transceiver onboard the delivery vehicle or disposed relative to a logistics facility). This may, in some instances, result in the loss of communication with an item in total or periodically while the item is being transported or maintained within the delivery vehicle.

To address one or more of these issues, there is a need for a technical solution that may be deployed as part of delivery logistics operations to enhance monitoring of shipped items in a delivery vehicle, inspections of the delivery vehicle, and providing adaptively extended and enhanced communications with one or more items shipped within a delivery vehicle.

SUMMARY

In the following description, certain aspects and embodiments will become evident. It should be understood that the aspects and embodiments, in their broadest sense, could be practiced without having one or more features of these aspects and embodiments. It should be understood that these aspects and embodiments are merely exemplary.

In general, aspects of the disclosure relate to drone-based improvements to the technology of logistics operations that involve monitoring of broadcast-enabled items being shipped in a delivery vehicle. Methods, apparatus, and systems are described herein for drone-based monitored storage where one or more internal monitor drones may be deployed from one or more respective internal docking

3

stations of a delivery vehicle's shipment storage to monitor and detect the condition of items being shipped within the shipment storage. Embodiments related to this aspect focus on an applied technical solution that enhances how to unconventionally monitor and intelligently notify others about a condition related to what may be in a delivery vehicle's shipment storage compartment.

In more detail, one aspect of the disclosure is directed to a drone-based monitored storage system. The system, generally, includes a shipment storage, an internal docking station, and an internal monitor drone. The shipment storage has a closable entry providing access to within the shipment storage, an interior shipment storage area for items being shipped within the shipment storage, and a drone storage area accessible through the closable entry and separate from the interior shipment storage area. The internal docking station is fixed within the drone storage area of the shipment storage, and includes a physical docking interface, an electronic charging connection interface, and an electronic data connection interface. The internal monitor drone is disposed within the shipment storage and operative to aurally monitor the items being shipped within the interior storage area. More specifically, the internal monitor drone includes at least an airframe, an onboard controller disposed on the airframe, lifting engines, a communication interface, a sensor array, a drone capture interface, and a battery. The lifting engines are coupled with respective lifting rotors, fixed to a different portion of the airframe, and responsive to flight control input generated by the onboard controller as part of maintaining a desired flight profile. The communication interface is coupled to the onboard controller of the internal monitor drone and is operative to transmit a monitoring update message in response to a transmission instruction from the onboard controller. The sensor array is also coupled to the onboard controller and is operative to gather sensory information as the internal monitor drone moves from an initial airborne position along an airborne monitoring path within the interior shipment storage area and providing the sensory information to the onboard controller. The drone capture interface is responsive to the onboard controller so that it is operative to selectively mate to the physical docking interface of the internal docking station in response to a docking command from the onboard controller. As such, the drone capture interface holds the internal monitor drone in a secure position when selectively mated to the physical docking interface of the internal docking station. And the onboard battery provides electrical power to each of the onboard controller, the lifting engines, the communication interface, the sensor array, and the drone capture interface.

During system operation, the onboard controller of the first internal monitor drone is operative, in response to receiving an activation command over the communication interface while in the secured position on the internal docking station, to transition from at least a low power state to an active monitoring state as part of a logistics operation related to the shipment storage; cause the drone capture interface to automatically uncouple the internal monitor drone from the physical docking interface of internal docking station once the internal monitor drone transitions to the active monitoring state; change the desired flight profile to first cause the lifting engines to move the internal monitor drone from the secured position on the internal docking station to the initial airborne position within the shipment storage and then move internal monitor drone from the initial airborne position along the airborne monitoring path within the interior shipment storage area of the shipment storage; receive the sensory information from the sensor

4

array, and autonomously detect a condition of the items being shipped based upon the sensory information provided by the sensor array.

In another aspect of the disclosure, an aerial drone-based method is described for monitoring the internal storage contents of a shipment storage. In general, the method begins by receiving an activation command by an internal monitor drone while in a secured position on an internal docking station fixed to the shipment storage in a drone storage area of the shipment storage. The method continues with the internal monitor drone transitioning from at least a low power state to an active monitoring state as part of a logistics operation related to the shipment storage, automatically uncoupling the internal monitor drone from the internal docking station once the internal monitor drone transitions to the active monitoring state, and then moving from the secured position on the internal docking station to an initial airborne position within the shipment storage. The method proceeds with a sensor array on the internal monitor drone gathering sensory information as the internal monitor drone moves from the initial airborne position along an airborne monitoring path within a shipment storage area of the shipment storage. The sensory information is provided from the sensory array to an onboard processor on the internal monitor drone where the onboard processor autonomously detects a condition of the internal storage contents based upon the sensory information provided by the sensor array.

In still another aspect of the disclosure, a multiple drone-based monitored storage system is described as including at least a shipment storage, multiple internal docking stations, and multiple internal monitor drones. More specifically, the shipment storage has a closable entry providing access to within the shipment storage, and an interior shipment storage area within the shipment storage where the interior shipment storage area is accessible through the closable entry and can temporarily maintain custody of a plurality of items being shipped within the shipment storage. The shipment storage also includes a plurality of drone storage areas respectively disposed at different locations within the shipment storage. The internal docking stations are fixed within respectively different ones of the drone storage areas, while the internal monitor drones are initially disposed on respective ones of the internal docking stations. Each of the internal monitor drones has a sensor array that gathers sensory information as the respective internal monitor drone moves within a part of the interior shipment storage area of the shipment storage.

During system operation, a first of the internal monitor drones is operative to move from a first of the internal docking stations to a first initial airborne position within the shipment storage as part of a first airborne monitoring path within a first part of the interior shipment storage area. The first internal monitor drone then aurally monitor a first part of the items being shipped within the interior shipment storage area using the sensor array on the first of the internal monitor drones as the first of the internal monitor drones transits the first airborne monitoring path within the shipment storage from the first initial airborne position. A second of the internal monitor drones is operative, as part of the system, to move from a second of the internal docking stations to a second initial airborne position within the shipment storage as part of a second airborne monitoring path within a second part of the interior shipment storage area within the shipment storage, and aurally monitor a second part of the items being shipped within the interior shipment storage area using the sensor array on the second of the internal monitor drones as the second of the internal

5

monitor drones transits the second airborne monitoring path within the shipment storage from the second initial airborne position. As part of the system operation, at least one of the first or second internal monitor drones then autonomously detects a condition of the items being shipped based upon sensory information generated when monitoring the items being shipped within the interior shipment storage area.

In yet another aspect of the disclosure, a multiple aerial drone-based method is described for monitoring the internal storage contents of a shipment storage. The method begins by moving a first internal monitor drone to a first initial airborne position within the shipment storage as part of a first airborne monitoring path within the shipment storage. The first internal monitor drone is disposed within a first drone storage area of the shipment storage and the first airborne monitoring path corresponds to a first part of an interior shipment storage area within the shipment storage. The method then moves a second internal monitor drone to a second initial airborne position within the shipment storage as part of a second airborne monitoring path within the shipment storage. The second internal drone is disposed within a second drone storage area of the shipment storage, and the second airborne monitoring path corresponds to a second part of the interior shipment storage area within the shipment storage. The method proceeds by aerially monitoring a first part of the internal storage contents of the shipment storage with a first sensor array on the first internal monitor drone as the first internal monitor drone transits the first airborne monitoring path within the shipment storage from the first initial airborne position, and aerially monitoring a second part of the internal storage contents of the shipment storage with a second sensor array on the second internal monitor drone as the second internal monitor drone transits the second airborne monitoring path within the shipment storage from the second initial airborne position. The method then detects a condition of the internal storage contents based upon at least one of (1) first sensory information generated when monitoring with the first sensor array of the first internal monitor drone and (2) second sensory information generated when monitoring with the second sensor array of the second internal monitor drone.

Additional advantages of these and other aspects of the disclosed embodiments and examples will be set forth in part in the description which follows, and in part will be evident from the description, or may be learned by practice of the invention. It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory only and are not restrictive of the invention, as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate several embodiments according to one or more principles of the invention and together with the description, serve to explain one or more principles of the invention. In the drawings,

FIG. 1A is a diagram of an exemplary aircraft having a shipment storage with a closable entry for access to within the shipment storage in accordance with an embodiment of the invention;

FIG. 1B is a diagram of an exemplary drone-based monitored storage system, including an exemplary shipment storage having an internal docking station and internal monitor drone in a secured position on the docking station in accordance with an embodiment of the invention;

6

FIG. 1C is another diagram of the exemplary drone-based monitored storage system shown in FIG. 1A where the internal monitor drone has transitioned off the secured position on the docking station to an exemplary airborne position within the shipment storage, in accordance with an embodiment of the invention;

FIG. 2 is a detailed diagram providing further details of an exemplary internal monitor drone in accordance with an embodiment of the invention;

FIG. 3 is a schematic illustration of connected electronic and sensory components of an exemplary internal monitor drone in accordance with an embodiment of the invention;

FIGS. 4A and 4B are more detailed diagrams providing further details of an exemplary internal docking station that can interface with an internal monitor drone in accordance with an embodiment of the invention;

FIG. 5 is a flow diagram illustrating an exemplary aerial drone-based method for monitoring the internal storage contents of a shipment storage in accordance with an embodiment of the invention;

FIG. 6 is a diagram of an exemplary multiple drone-based monitored storage system in accordance with an embodiment of the invention;

FIG. 7 is a flow diagram illustrating an exemplary multiple aerial drone-based method for monitoring the internal storage contents of a shipment storage in accordance with an embodiment of the invention;

FIGS. 8A-8G are diagrams of an exemplary drone-based inspection system using an exemplary paired inspection drone that inspects targeted points on a delivery vehicle from inside the delivery vehicle and outside the delivery vehicle in accordance with an embodiment of the invention;

FIG. 9 is a schematic illustration of connected electronic and sensory components of an exemplary paired inspection drone in accordance with an embodiment of the invention;

FIG. 10 is a diagram illustrating an exemplary paired inspection drone coupled to an exemplary control tether in accordance with an embodiment of the invention;

FIG. 11 is a flow diagram illustrating an exemplary drone-based method for inspecting a delivery vehicle in accordance with an embodiment of the invention;

FIG. 12 is a diagram of an exemplary delivery vehicle inspection system that includes an aerial inspection drone paired to a delivery vehicle and exemplary mobile interactive transceivers operated by different personnel associated with the delivery vehicle in accordance with an embodiment of the invention;

FIG. 13 is a diagram of an exemplary drone-based system for conducting a modified inspection of a delivery vehicle in accordance with an embodiment of the invention;

FIG. 14 is a schematic illustration of components of an exemplary delivery vehicle transceiver in accordance with an embodiment of the invention;

FIG. 15 is a diagram of an exemplary drone-based system for conducting a modified inspection of a delivery vehicle that includes a mobile transceiver device used in support of delivery vehicle operations that is physically separate from the delivery vehicle in accordance with an embodiment of the invention;

FIG. 16 is a flow diagram illustrating an exemplary drone-based method for conducting a modified inspection of a delivery vehicle in accordance with an embodiment of the invention;

FIG. 17 is a diagram of an exemplary drone-based system used to conduct a verified inspection of a delivery vehicle in accordance with an embodiment of the invention;

FIGS. 18A-18F are diagrams of the exemplary drone-based system of FIG. 17 using an exemplary paired inspection drone to communicate with a delivery vehicle transceiver related to an interactive intervention request and interaction with the transceiver's user interface related to conducting the modified inspection with additional sensor-based inspection information and relevant verification result input in accordance with an embodiment of the invention;

FIGS. 19A-19B are flow diagrams that collectively illustrate an exemplary drone-based method for conducting a verified inspection of a delivery vehicle that involves an automatically generated interactive intervention request in accordance with an embodiment of the invention;

FIG. 20 is a diagram of an exemplary paired aerial drone-based system used to provide an airborne relocatable communication hub within a delivery vehicle for a plurality of broadcast-enabled devices maintained within the delivery vehicle in accordance with an embodiment of the invention;

FIG. 21 is a schematic illustration of connected electronic and sensory components of an exemplary paired aerial communication drone in accordance with an embodiment of the invention;

FIG. 22 is a diagram of another exemplary paired aerial drone-based system used to provide an airborne relocatable communication hub within a delivery vehicle between a central communication station and a broadcast-enabled device maintained within the delivery vehicle in accordance with an embodiment of the invention;

FIGS. 23A and 23B are diagrams of another exemplary paired aerial drone-based system used to provide an airborne relocatable communication hub within a delivery vehicle where at least one of the broadcast-enabled devices maintained within the delivery vehicle is a mobile personal communication device in accordance with an embodiment of the invention;

FIG. 24 is a diagram of another exemplary paired aerial drone-based system used to provide an airborne relocatable communication hub within a delivery vehicle where two of the broadcast-enabled devices maintained within the delivery vehicle are mobile personal communication devices in accordance with an embodiment of the invention;

FIGS. 25A-25C are logical diagrams illustrating exemplary relationships between an exemplary paired aerial communication drone and multiple broadcast-enabled devices maintained within a delivery vehicle at different network levels in accordance with an embodiment of the invention;

FIG. 26A is a diagram of an exemplary paired aerial communication drone at a first deployed airborne position within a delivery vehicle and multiple broadcast-enabled devices maintained within the delivery vehicle in accordance with an embodiment of the invention;

FIG. 26B is a diagram of an exemplary paired aerial communication drone at a second deployed airborne position within a delivery vehicle and multiple broadcast-enabled devices maintained within the delivery vehicle in accordance with an embodiment of the invention;

FIG. 27 is a flow diagram illustrating an exemplary aerial drone-based method for providing an airborne relocatable communication hub within a delivery vehicle for a plurality of broadcast-enabled devices maintained within the delivery vehicle in accordance with an embodiment of the invention;

FIG. 28 is a flow diagram illustrating an improved method for enhanced positioning of an airborne relocatable communication hub supporting a plurality of wireless devices and based on connection signal strength in accordance with an embodiment of the invention;

FIG. 29 is a flow diagram illustrating another improved method for enhanced positioning of an airborne relocatable communication hub supporting a plurality of wireless devices and based on device concentration in accordance with an embodiment of the invention; and

FIG. 30 is a flow diagram illustrating yet another improved method for enhanced positioning of an airborne relocatable communication hub supporting a plurality of wireless devices and based on directional sensing of the wireless devices in accordance with an embodiment of the invention.

DESCRIPTION OF THE EMBODIMENTS

Reference will now be made in detail to various exemplary embodiments. Wherever possible, the same reference numbers are used in the drawings and the description to refer to the same or like parts. However, those skilled in the art will appreciate that different embodiments may implement a particular part in different ways according to the needs of the intended deployment and operating environment for the respective embodiments.

In general, the following describes various embodiments of different systems, apparatus, and applied methods that deploy an aerial monitor, inspection and/or communication drone as an extension of a delivery vehicle. These embodiments provide advantageous and unconventional technical solutions focused on improving how to monitor the delivery vehicle's contents, inspect parts of the delivery vehicle, and/or how to allow for robust communications between devices within the delivery vehicle. Many of these embodiments rely on such an aerial drone that may be internally docked onboard the delivery vehicle and exclusively assigned as a paired device to the delivery vehicle. As such, the paired drone travels with and operates solely with respect to the delivery vehicle and the contents maintained therein.

The below described drone-based embodiments may individually relate to improvements on monitoring the delivery vehicle's contents, inspecting parts of the delivery vehicle, or how to allow for robust communications between devices within the delivery vehicle. Furthermore, those skilled in the art will appreciate that additional embodiments may combine some of these otherwise independent drone-based solutions to provide for an even more robust paired logistics drone that is exclusively assigned to a delivery vehicle and can provide two or more of such monitoring, inspecting, and communication hub service functionality as described in more detail below.

Drone-Based Monitored Shipment Storage

In more detail, FIGS. 1A-7 relate to embodiments of drone-based monitored storage systems where one or more internal monitor drones may be deployed from one or more respective internal docking stations of a shipment storage to monitor and detect the condition of items being shipped within the shipment storage. Referring now to FIG. 1A, an exemplary delivery vehicle having a shipment storage is shown as a logistics aircraft 100 that transports items between different locations. Those skilled in the art will appreciate that the exemplary aircraft 100 is shown in a simplified form having an operational control section 105 (e.g., a cockpit from which flight personnel can control and fly the aircraft 100) and a shipment storage 110 used for maintaining items being shipped within aircraft 100 between different locations. The shipment storage 110 may, for example, encompass one or more internal compartments of the aircraft, such as a central shipment storage area or

different internal compartmentalized shipment storage areas where each storage area is configured to maintain items being shipped within the aircraft **100**. Aside from a storage compartment within an aircraft, such as aircraft **100**, other embodiments of a shipment storage may comprise a trailer capable of being moved by a truck, a train car capable of being moved on a railway system.

In the exemplary aircraft **100** shown in FIG. 1A, an exemplary closable entry **112** is illustrated that provides access to within the onboard shipment storage **110**. Such a closable entry may take the form of door **112**, which may be opened for loading and unloading operations and then secured for in-flight operations. Such a closable entry may, for example, also take the form of a rear ramp that may be opened and securely closed to provide access to the aircraft's shipment storage from the rear of the aircraft. In another example, such a closeable entry may be implemented with a belly door of the aircraft so as to provide access from beneath the aircraft. Further still, those skilled in the art will appreciate that different types of entry or access structure (e.g., doors, hatches, ramps, etc.) may be deployed on different kinds of delivery vehicles (e.g., tractor trailer, marine vessel, railroad car, etc.) in other embodiments that provide access to a shipment storage area within the delivery vehicle.

As shown in FIG. 1B, the operational control section **105** of exemplary aircraft **100** may also include a vehicle transceiver **135**. In general, such a vehicle transceiver **135** may be implemented as a standalone unit (e.g., a ruggedized radio-based tablet or smartphone used by aircraft crew personnel) or an integrated part of the aircraft's avionics suite. Vehicle transceiver **135** may be used in embodiments to communicate with devices located inside and outside of aircraft **100**. For example, vehicle transceiver **135** may communicate with a local logistics operation server (not shown), a remote cloud-based logistics management system (not shown), loading/unloading logistics personnel via radio-based transceivers (not shown), or vehicle maintenance personnel via similar types of radio-based transceivers (not shown)). Those skilled in the art will understand that such radio-based transceivers deployed with such personnel may be implemented as wireless handheld devices (such as smartphones, ruggedized tablets, UHF/VHF handheld radios, and the like) that communicate with vehicle transceiver **135** over a compatible communication path (e.g., a designated radio frequency, a cellular network, a data communication network, and the like). Additionally, vehicle transceiver **135** may be used in embodiments to communicate with an internal docking station **130** (e.g., via a wired or wireless connection) and/or an internal monitor drone **125** (e.g., via a wireless connection) disposed within aircraft **100** as described in more detail below. Further still, vehicle transceiver **135** may in some embodiments, provide an intermediary role between two other devices, such as between the internal monitor drone **125** and a radio-based transceiver operated by maintenance personnel assigned to the aircraft **100** or between the internal monitor drone **125** and a cloud-based logistics management system (i.e., a network of remote servers hosted on the Internet that can store, manage, and process shipment management information (such as loading plan data, messaging data related to the status of shipping items on aircraft **100**, and the like) rather than a locally hosted logistics server).

As shown in FIG. 1B, exemplary shipment storage **110** within aircraft **100** includes an interior shipment storage area **120** and a drone storage area **115**. While closable entry **112** from FIG. 1A is not shown in FIG. 1B, those skilled in the

art will appreciate that interior shipment storage area **120** is both accessible through the closable entry **112** (directly or, in some embodiments indirectly) and used to temporarily maintain custody of one or more items being shipped within the interior shipment storage area **120** (as the internal storage contents of shipment storage **120**), such as shipping items **140a-140b** or broadcast-enabled types of shipping items **145a-145e**. Exemplary shipping items **140a-140b**, **145a-145e** may include packaged or unpackaged items being transported alone or as part of a group of items (e.g., the group of items **145b-145e** strapped and fixed relative to shipping pallet **150** or a group of items maintained within a single packaged shipping item, such as a crate, box, or other logistics container). Likewise, those skilled in the art will appreciate that a shipping item may be implemented with a unit load device (ULD) used with aircraft-based logistics operations. Additionally, one or more shipping items may be placed within a single ULD or other logistics container prior to loading into shipment storage area **120**. Thus, a shipping item maintained within interior shipment storage area **120** may be implemented as a single item, a packaged item, a group of items being shipped together in a package, or a group of separately packaged items being shipped together as a unit (e.g., a multi-piece shipment on a pallet **150**).

While some shipping items maintained within interior shipment storage area **120** do not emit broadcast signals (such as items **140a-140b**), exemplary broadcast-enabled shipping items **145a-145e** may be deployed in some embodiments within interior shipment storage area **120** to broadcast signals related to the condition of the respective item or items being shipped. For example, broadcast-enabled shipping items **145a-145e** may accomplish such broadcast functionality with a sensor-based tag (such as an RFID tag) that requires interrogation, prompting, or polling in order to initiate the broadcast of such signals. However, in other embodiments, broadcast-enabled shipping items **145a-145e** may accomplish such broadcast functionality with a more independent node type of active sensor-based device that has a radio-based wireless transmitter or transceiver and that can broadcast the condition of item (e.g., an environmental condition of the item using one or more sensors on the device) without being polled or interrogated to do so. In particular, such sensor-based devices deployed as part of the broadcast-enabled shipping items **145a-145e** may, for example, transmit or receive Bluetooth®, Zigbee, cellular, or other wireless formatted signals. Such devices or tags may be attached or otherwise secured to the shipping item, included in a package with the shipping item, or embedded as part of the package or packaging material used with the shipping item.

The drone storage area **115** within the shipment storage **110** is also accessible through the closable entry **112** and is separate from the interior shipment storage area **120**. In particular, drone storage area **115** is located in a designated area within the shipment storage **110** that houses an internal docking station **130** for an internal monitor drone **125** paired with the aircraft **100**. The separation of area **115** from area **120** allows for the internal monitor drone **125** to have open access to the internal docking station **130**, where the internal monitor drone **125** may land, be secured within the shipment storage **110**, receive charging power for flight operations within the shipment storage **110**, and receive other data from the docking station **130** as described in more detail herein.

FIG. 1B shows internal monitor drone **125** in a secured position on the internal docking station **130**. Such a secured position may be accomplished, as described in more detail below, by selectively mating parts of the internal monitor

11

drone **125** to parts of the internal docking station **130**. In some embodiments, certain parts of the internal monitor drone **125** may be actuated to couple or uncouple the drone **125** relative to parts of the docking station **130**. In other embodiments, certain parts of the internal docking station **130** may be actuated to couple or uncouple the docking station **130** relative to parts of the internal monitor drone **125**. Further still, other embodiments may selectively mate the drone **125** and the docking station **130** with actuated parts on both of the drone **125** and the docking station **130**. Thus, various embodiments may have parts of the internal monitor drone **125** selectively mated to a physical docking interface of the internal docking station **130** in order to achieve a secure position of the internal monitor drone **125**. For example, selectively energized magnetic attachments may be utilized to secure drone **125** and docking station **130** in other embodiments.

In this secured position, the internal monitor drone **125** may be powered off or in a low power state where drone **125** may be charging and/or communicating with either or both of internal docking station **130** and vehicle transceiver **135** (e.g., downloading data off of drone **125** while secured to docking station **130**, uploading data related to flight control instructions for the internal monitor drone **125**, etc.). When the internal monitor drone **125** is activated (e.g., by receiving an activation command via a wired signal from the internal docking station **130** or via reception of a wireless signal), the internal monitor drone **125** transitions to an active monitoring state as part of a logistics operation related to the shipment storage (e.g., during a loading or unloading operation of the internal shipment storage area **120**, or during an in-transit monitoring operation of the internal shipment storage area **120** of the shipment storage **110** while the shipment storage **110** is moving). The internal monitor drone **125** then is automatically uncoupled from the internal docking station **130**, and moves from the secured position to an initial airborne position so that the drone **125** may then move along an airborne monitoring path within the interior shipment storage area **120** as shown in FIG. 1C. While moving along the airborne monitoring path within area **120**, the internal monitor drone uses guidance components, such as proximity sensors, to help guide the drone **125** along the path while deploying an onboard sensor array to gather sensory information (such as environmental information) as a way of autonomously detecting a condition of one or more items being shipped within the storage area **120**.

FIG. 2 is a diagram of exemplary internal monitor drone **125** in accordance with an embodiment of the invention. Referring now to FIG. 2, an exterior of exemplary internal monitor drone **125** is shown having an airframe **200**; rotors **205a**, **205b**; lifting engines **210a**, **210b**; proximity sensors **215a**, **215b**; landing gear **220a**, **220b**; a sensor array **230**; and an electronic docking connection **235**. In more detail, the airframe **200** provides a core structure or housing for drone **125**, which may be implemented as an unmanned aerial vehicle (UAV) having two or more sources of propulsion (e.g., lifting engines). The airframe **200** may be equipped with a central portion (or main deck) at its core that houses many of the drone's internal components and with multiple arms of the airframe extending between the central portion and each lifting engine **210a**, **210b**. The airframe **200** may be implemented with an enclosure/housing or may be implemented without such an enclosure/housing. Those skilled in the art will appreciate that airframe **200** may be implemented using low weight carbon fiber or other light weight rigid materials. Further, while FIG. 2 presents airframe **200** in a two-dimensional view, those skilled in the art

12

will appreciate that airframe **200** may be implemented in a tri-copter, quad-copter, or hex-copter configuration to accommodate a desired number of lifting engines as needed for a particular embodiment. Examples of such an airframe **200** may include Model **680** UC Pro Hexa-Copter Umbrella Carbon airframe from Qanum that has an articulating/retractable landing gear wheelbase, a Turnigy H.A.L. (Heavy Aerial Lift) Quadcopter Frame 585 mm airframe, a Turnigy Talon Carbon Fiber Quadcopter airframe, or a more simplified Qanum Chaotic 3D Quad airframe.

Rotors **205a**, **205b** are respectively coupled to each of lifting engines **210a**, **210b**, which are fixed to different portions of airframe **200** to provide selectively controlled sources of propulsion for internal monitor drone **125**. An embodiment of lifting engines **210a**, **210b** may be implemented using multiple brushless electric motors (e.g., NTM Prop Drive Series 35-30 electric motors, LDPOWER brushless multirotor motors, and the like). In some embodiments, rotors **205a**, **205b** are also protected with rotor guards (also known as prop guards but not shown in FIG. 2) to avoid damage to rotors **205a**, **205b** during operation of drone **125**. Some prop guards may encircle the entire rotational area for a respective rotor, while other types of prop guards may only provide a radius of protection along the outward facing edges of where a respective rotor operates. The lifting engines **210a**, **210b**, as coupled with respective rotors **205a**, **205b**, are responsive to flight control input generated onboard internal monitor drone **125** as part of maintaining a desired flight profile for the drone **125**.

In the embodiment illustrated in FIG. 2, the exemplary airframe **200** has proximity sensors **215a**, **215b** disposed at multiple locations around the airframe **200** that serve as location indicators. Proximity sensors **215a**, **215b** may be configured on airframe **200** to focus outwardly in different directions relative to the airframe **200**—e.g., up, down, and along different sides of airframe **200**. The output of such proximity sensors **215a**, **215b** may be provided to a flight controller within internal monitor drone **125** as a positional warning for any desired or current flight path. Different embodiments of proximity sensors **215a**, **215b** may use one or more different technologies—e.g., magnetic proximity sensors, visual proximity sensors, photoelectric proximity sensors, ultrasonic proximity sensors, laser range finding proximity sensors, capacitive proximity sensors, and/or inductive proximity sensors.

Landing gear **220a**, **220b** is disposed along the bottom of the internal monitor drone **125**. Landing gear **220a**, **220b** may be in the form of legs, skids, articulating wheels, and the like used to support the drone **125** when landing on internal docking station **130** and as at least part of holding drone **125** secure relative to the docking station **130**. In one embodiment, landing gear **220a**, **220b** may be articulated by a docking control interface on internal monitor drone **125** that may move, rotate, and/or retract the landing gear **220a**, **220b** with servos or other actuators onboard the internal monitor drone **125**. In this way, the drone **125** may cause the landing gear **220a**, **220b** to move or rotate in order to hold the drone **125** in a secure position relative to moving or non-moving parts of the internal docking station **130**; and/or retract upon transitioning from the secure position to an airborne position. Those skilled in the art will appreciate that extending the landing gear **220a**, **220b** helps to support the drone **125** and protect the sensor array **230** and electronic docking connection **235** positioned beneath the drone **125**, while retracting the landing gear **220a**, **220b** helps to clear obstructions from the sensory view of the sensor array **230**.

13

A further embodiment, may have selectively energized magnets that may be extended to operate as landing gear **220a**, **220b** such that the extended magnetic structure may act as a physical protective structure as well as to provide structure that can be articulated and then energized so to make a secure magnetic connection with a surface (such as a surface on internal docking station **130**).

Sensor array **230** is generally two or more sensor elements that are mounted on one or more points of the airframe **200** (such as along the bottom of the airframe **200**). In such a configuration, sensor array **230** gathers sensory information relative to shipping items (such as items **140a-145e**) as the internal monitor drone **125** moves from an initial airborne position along an airborne monitoring path within the interior shipment storage area **120** of the shipment storage **110**. Such an airborne monitoring path may be preprogrammed into the internal monitor drone **125** to account for the size, boundaries, and any fixed obstacles relative to the interior shipment storage area **120** and a loading plan for the interior shipment storage area **120** that spatially accounts for what should be loaded within area **120**.

In various embodiments, sensor array **230** may be implemented with one or more different types of sensors or receivers. In one example, sensor array **230** may use one or more environmental sensors where each sensor detects environmental information when positioned at and relative to the environmental surroundings existing at multiple airborne locations (e.g., within effective sensor range of particular shipping items) within the shipment storage **110**. Such environmental information is detected as the internal monitor drone **125** transits the airborne monitoring path within the interior shipment storage area **120**. Based upon the detected environmental information obtained by the group of environmental sensors in sensor array **230**, the internal monitor drone **125** can autonomously detect an environmental condition of items being shipped within shipment storage **110**. In more detail, the environmental condition detected may be a movement condition as sensed by a motion sensor operating as the environmental sensor, a light condition as sensed by a light sensor operating as the environmental sensor, a sound condition as sensed by a microphone operating as the environmental sensor, a temperature condition as sensed by a temperature sensor operating as the environmental sensor, a smoke condition as sensed by a smoke sensor operating as the environmental sensor, a humidity condition as sensed by a moisture sensor operating as the environmental sensor, and a pressure condition as sensed by a pressure sensor operating as the environmental sensor. Thus, an embodiment of sensor array **230** may deploy multiple different types of environmental sensors (as noted above) so are to provide a robust and multi-faceted environmental monitoring capability to the internal monitor drone **125**.

In some embodiments, sensor array **230** may also include an image sensor as another type of sensing element. Such an image sensor, as part of sensor array **230**, may capture images of the items being shipped as the internal monitor drone **125** transits the airborne monitoring path within the interior shipment storage area **120**. In other words, the images captured by such an image sensor are from different airborne locations within the shipment storage **110** as the internal monitor drone **125** transits the airborne monitoring path within the interior shipment storage area **120**. For example, as internal monitor drone **125** enters an active monitoring state and moves from a secured position on internal docking station **130** to above shipping item **140b**, an image sensor from sensor array **230** may capture images

14

(e.g., still pictures or video; visual images; and/or thermal images) that may be used as sensory information for detecting a condition of the shipping item **140b** (e.g., a broken package for shipping item **140b**, a leak coming from shipping item **140b**, etc.). Exemplary image sensor may be implemented with a type of camera that captures images, thermal images, video images, or other types of filtered or enhanced images that reflect the contents of the interior shipment storage area **120** and provide information about the status of the shipping items within that area **120**. Exemplary image sensor may also read and provide imagery or other information that identifies an asset number on an item maintained within the interior shipment storage area **120** (which may eliminate the need for barcode scanning).

In further embodiments, sensor array **230** may also include a depth sensor as a further type of sensing element that may make up the array. This depth sensor may be a depth-sensing camera or stereo camera that can interactively capture or map a configuration of the interior shipment storage area **120** of the shipment storage **110** as the internal monitor drone **125** transits the airborne monitoring path within the interior shipment storage area **120**. This configuration of the interior shipment storage area represents a multi-dimensional mapping of at least the items being shipped within the interior shipment storage area **120** of the shipment storage **110** (i.e., shipping items **140a-145e** as shown in FIGS. **1B** and **1C**). As will be discussed in more detail below, comparisons of such mapped configurations of the interior shipment storage area **120** over time allow for detection of a movement condition for one or more items in the area **120** as monitored from the aerial positions by the internal monitor drone **125**. This may be especially helpful during transit as aircraft **100** is airborne and emerges from rough weather conditions where turbulence may have been experienced, and robust monitoring with aerially coordinated depth sensing can check for loose shipping items and help avoid dangerous in-flight cargo scenarios. Additional embodiments may use an ultrasonic transducer as a type of depth sensor that uses sound ways to map surfaces or to help validate data received by a depth sensor camera.

In still other embodiments, sensor array **230** may include a scanning sensor, such as a barcode reader, that scans an identification symbol fixed to one of the items being shipped as the internal monitor drone **125** transits the airborne monitoring path within the interior shipment storage area **120** of the shipment storage **110**. If an embodiment implements such a scanning sensor with a barcode reader, the identification symbol may be a barcode symbol identifying shipping information related to the item being shipped. In another embodiment, such an identification symbol may be a sign affixed to the shipping item where the sign identifies shipment loading information related to placement of the item when being shipped within the shipment storage **110**. As will be described in more detail below, scanning of a shipping item (such as items **140a-145e**) by a scanning sensor within the sensor array **230** of internal monitor drone **125** may be used as part of determining a loading status of that shipping item relative to a loading plan for the shipment storage **110**.

In another embodiment, sensory array **230** may also include a radio-based receiver that functions to monitor for signals broadcast from different shipping items. For example, sensory array **230** may have a Bluetooth or Zigbee radio transceiver that can scan and listen for wireless signals being broadcast from one of the broadcast-enabled shipping items **145a-145e** being loaded, unloaded, or existing within the interior shipment storage area **120**. Such wireless signals

15

may include condition information (e.g., environmental sensory information) so that the internal monitor drone **125** may autonomously detect a condition of one of the broadcast-enabled shipping items via such wireless signals.

Further still, it is contemplated that an embodiment of sensor array **230** may include multiple different types of sensor elements—e.g., one or more different types of environmental sensors, one or more image sensors, one or more depth sensors, and one or more scanning sensors. In this way, different embodiments of the exemplary internal monitor drone **125** may deploy a rich and robust variety of different types of sensing elements to make up the sensor array **230**.

Different embodiments of sensor array **230** may be connected to the airframe **200** of internal monitor drone **125** in various different ways. For example, in one embodiment, the sensor array **230** may be fixed relative to the airframe **200** of internal monitor drone **125**. This may be limited to a lower or bottom surface of the airframe **200**, but other embodiments may deploy some sensing elements of the sensor array **230** on other parts of the airframe so as to allow the internal monitor drone **125** to continue capturing relevant sensory information even if the drone **125** descends between two shipping items. In still other embodiments, the sensor array **230** may be fixed relative to the airframe **200** but still have selective movement capabilities controlled by the internal monitor drone **125**—e.g., moving lenses that allow for selective focusing abilities for an image sensor, articulating scanning sensors that allow for selective aiming of a barcode scanning laser, etc. Further still, the sensory array **230** may be deployed on an entirely movable structure relative to the airframe **200**, such as a gimbaled platform that may be controlled to maintain a reference orientation. Thus, in such an embodiment where some or all sensor elements of the sensor array **230** are on a gimbaled platform part of airframe **200** (not shown in FIG. 2), the circuitry within the internal monitor drone **125** may use a separate gimbal controller, such as an AlexMos brushless gimbal controller (BGC) from Quanum or an H4-3D GoPro gimbal from DJI, to interface to a dedicated brushless gimbal motor that articulates such a platform in order to keep those sensors of the sensor array **230** deployed on that platform in a reference orientation and attitude.

Finally, FIG. 2 illustrates an electronic docking connection **235** on the lower part of internal monitor drone **125**. The electronic docking connection **235** is generally a type of connection for multiple electronic interfaces between the internal monitor drone **125** and the internal docking station **130**. In one embodiment, as explained in more detail with respect to FIGS. 3, 4A, and 4B, electronic docking connection **235** provides a connection for electronic charging of the drone's onboard battery and for wired data communications to and from the drone **125** through connection **235**. For example, when the internal monitor drone **125** is in a secured position on internal docking station **130**, the electronic docking connection **235** may be mated with a complementary connection on the docking station **130** so as to charge the drone **125**, upload data to the drone **125** (e.g., updated flight commands for onboard flight profile data maintained in the drone's memory, updated loading plan data for an upcoming loading operation for aircraft **100**, and the like), and download data from the drone **125** (e.g., gathered sensory information stored as sensor data in the drone's memory).

Further to the explanation of components shown in FIG. 2 that make up an exemplary internal monitor drone **125**, FIG. 3 presents further details in the form of a block diagram

16

illustration of different connected electronic and sensory components of an embodiment of an exemplary internal monitor drone **125**. Referring now to FIG. 3, exemplary internal monitor drone **125** includes an onboard controller (OBC) **300** (having one or more processors and memory) at its core along with memory **315** (e.g., volatile, non-volatile, or both depending on the configuration of the OBC **300**). The OBC **300** interfaces or connects with motor control circuitry (such as electronic speed controllers **360a**, **360b**), guidance related circuitry (such as global positioning system (GPS) chip **350**, inertial measurement unit (IMU) **355**, and proximity sensors **215a**, **215b**), dedicated docking circuitry (such as drone capture interface **370** and the electronic docking connection **235**), communication related circuitry (such as communication interface **365**), payload electronics (such as the onboard sensor array **230**), and an onboard power source that provides power for all of the onboard active electronics (such as onboard battery **385**). An embodiment of OBC **300** may interface or connect with such circuitry by deploying various onboard peripherals (e.g., timer circuitry, USB, USART, general-purpose I/O pins, IR interface circuitry, DMA circuitry, buffers, registers, and the like) that implement an interface (e.g., a plug type or connectorized interface) to the different components disposed within internal monitor drone **125** (e.g., mounted on different parts of airframe **200**).

As part of the exemplary internal monitor drone **125**, the OBC **300** generally controls autonomous flying and docking of the drone **125** as well as monitoring and data gathering tasks related to the shipment storage area **120** using sensory array **230**. In some embodiments, OBC **300** may be implemented with a single processor, multi-core processor, or multiple processors and have different programs concurrently running to manage and control the different autonomous flying/docking and internal monitoring tasks. For example, in the embodiment shown in FIG. 3, flight/docking control and monitoring operations may be divided between an onboard flight controller (OFC) **305** and an onboard monitoring processor (OMP) **310**. In such an embodiment, OFC **305** and OMP **310** may have access to the same memory, such as memory storage **315** or, alternatively, OBC **300** may be implemented with separate dedicated memories that are accessible by each of OFC **305** and OMP **310**. Those skilled in the art will appreciate that memory accessible by OFC **305** may have different accessibility and size requirements compared to memory accessible by OMP **310** given the different memory demands for the different responsibilities. For example, memory accessible by OMP **310** may be significantly large given the anticipated size of sensory information gathered through sensory array **230** when compared to the size of memory needed for tasks performed by OFC **305**. As will be explained further, each of OFC **305** and OMP **310** may include peripheral interface circuitry that couples the processing element(s) to the different onboard peripheral circuitry, such as the GPS **350**, inertial measurement unit **355**, the communication interface **365**, the electronic speed controllers **360a**, **360b** that control each lifting engine **210a**, **210b**, and the like.

In general, the OFC **305** is a flight controller capable of autonomous flying of drone **125**. Such autonomous flying may involve automatic take off, transiting an airborne monitoring path (e.g., via waypoint flying), and data communication or telemetry while airborne and while secured to the docking station **130**. For example, exemplary OFC **305** may be responsible for generating flight control input to change the drone's desired flight profile by causing the lifting engines **210a**, **210b** to move the internal monitor drone **125**

from a secured position on the internal docking station **130** to an initial airborne position within the shipment storage **110** and then move internal monitor drone **125** from the initial airborne position along the airborne monitoring path within the interior shipment storage area **120** of the shipment storage **110**. As such, the OFC **305** controls movement and flight stability of drone **125** while navigating and avoiding collisions during movement. In more detail, an embodiment of OFC **305** includes peripheral interface circuitry (not shown in FIG. **3**, but those skilled in the art will appreciate that it may be implemented with buffers, registers, buses, and other communication and command pathways) for interacting with guidance related circuitry, motor control circuitry, dedicated docking circuitry, and communication circuitry onboard the internal monitor drone **125** as part of controlling movement and flight stability of drone **125** while navigating and avoiding collisions during movement. Examples of such an OFC **305** include multi-rotor flight controllers from Turnigy, NAZA flight controllers from DJI, and Pixhawk flight controllers from 3D Robotics specifically designed for autonomous flying.

OFC **305** uses electronic speed controllers (ESC) **360a**, **360b** to control respective lifting engines **210a**, **210b**. Generally, an electronic speed controller varies the speed of a particular electronic motor (such as the motor in lifting engine **210a**) as a type of throttle control. In this way, the OFC **305** provides flight control input as throttle control to each of the different ESCs **360a**, **360b** in order to vary the speed of the lifting rotors **205a**, **205b**. Those skilled in the art will appreciate that having the OFC **305** generate flight control input that changes the power to all lifting engines **210a**, **210b** results in the internal monitor drone **125** moving higher or lower, while other flight control input for the ESCs may cause horizontal movement or changes in attitude for the internal monitor drone **125**. An example of such an ESC may be a Turnigy Multistar multi-rotor speed controller, however those skilled in the art will appreciate there are a variety of other models used depending on the current and current ranges required to drive the respective lifting engines.

For flight operations and navigation, OFC **305** may be implemented with integrated global positioning system (GPS) onboard as well as an integrated inertial measurement unit (IMU) (including one or more gyroscopes) onboard. The integrated GPS and IMU provide OFC **305** with current position information in the form of a satellite-based location and/or a relative location using the IMU based on a resettable position fix. Alternatively, as shown in the embodiment illustrated in FIG. **3**, the OFC **305** may be implemented by separately interfacing with external guidance related circuitry, such as a GPS module/chip **350** (including a GPS compatible antenna), inertial measurement unit (IMU) **355**, and proximity sensors **215a**, **215b**. The GPS unit **350** provides similar satellite-based location information in the form of coordinates usable by OFC **305** for navigating the airborne monitoring path or a portion thereof. IMU **355** is a device that comprises at least a gyroscope and accelerometer to measure acceleration and angle of tilt. As such, IMU **355** may provide such measured positional information (e.g., acceleration, attitude, orientation, and the like) to OFC **305** for use in navigating within internal shipment storage area **120**. IMU **355** may also have its reference position reset via the current position information provided by GPS **350**. Proximity sensors **215a**, **215b** sense the presence of different targets in close relation to the drone's airframe **200** and provide OFC **305** with detection telemetry as a positional warning as the drone **125** is moved by OFC **305** via flight

control commands and input generated. In a further embodiment, proximity sensors **215a**, **215b** or other sensors in the sensor array **230** (such as a scanning sensor) may detect reflective or otherwise known reference points as part of navigating the space within the shipment storage.

In one embodiment, the internal monitor drone **125** may use fixed landing gear **220a**, **220b** such that securing the drone **125** to the docking station **130** is accomplished by actuating movable structure (e.g., clamps, pins, locking arms) on the internal docking station **130** to hold and secure the drone **125** in place via its fixed landing gear **220a**, **220b**. In such an embodiment, landing gear **220a**, **220b** are considered part of the drone capture interface **370** that selectively mate to a physical docking interface of the internal docking station **130**. However, in another embodiment, the drone capture interface (DCI) **370** as shown in FIG. **3** may include selectively activated servos or actuators that move, rotate, and/or retract/extend the landing gear **220a**, **220b** in a controlled manner. As such, the OFC **305** may generate commands (such as a docking command) to cause the DCI **370** to electronically and selectively cause the landing gear **220a**, **220b** to mate to the physical docking interface of the internal docking station by moving, rotating, and/or retract/extend the landing gear **220a**, **220b** (such as shown in FIG. **4A**).

The OBC **300** shown in FIG. **3** is also operatively coupled to several communication circuits. In general, the OBC **300** is coupled to a wireless communication interface **365** as well as a wired data interface **375** (as part of electronic docking connection **235**). The OBC **300** may send messages or information over one or both of the wireless communication interface **365** and the wired data interface **375**. When the internal monitor drone **125** is docked on docking station **130** and electronic docking connection **235** is mated to another connection on docking station **130**, the wired data interface **375** may be connected to another wired communication path and be useful for transmitting messages, downloading/uploading data (such as sensory data, new flight profile data, or new loading plan data), or updating program files stored in memory **315** of the OBC **300**. When airborne, wireless communication interface **365** allows for similar over the air communications. For example, communication interface **365** may transmit a monitoring update message in response to a transmission instruction from the OBC **300** while monitoring the internal shipment storage area **120** along an airborne monitoring path. Such a monitoring update message may, for example, be received by the vehicle transceiver **135** operated by flight personnel associated with aircraft **100**. Additionally, the monitoring update message may, in other embodiments, be received by wireless-enabled transceivers outside of aircraft **100**, such as one or more of loading/unloading logistics personnel via radio-based transceivers (not shown), and/or vehicle maintenance personnel via similar types of radio-based transceivers (not shown). Depending upon the specific embodiment of OBC **300**, those skilled in the art will appreciate that such communication circuits (i.e., wireless communication interface **365** and wired data interface **375**) may be accessible by either or both of the OFC **305** or the OMP **310** depending on which of these processor devices are tasked with communication functionality.

An exemplary onboard monitor processor (OMP) **310** is generally considered a low power microprocessor or processor-based microcontroller that at least receives sensory information from the sensory array **230** and autonomously detects the condition of an item being shipped within the interior shipment storage area **120** based upon the received

sensor information. OMP 310 may be deployed in an embodiment of internal monitor drone 125 as a task-dedicated processor that executes operational and application program code (e.g., operating system 320, monitoring program 325) and other program modules maintained in memory 315 useful in monitoring the shipping items on aircraft 100 in accordance with embodiments of the invention.

More specifically, operating system 320 may be loaded by OMP 310 upon power up and provide basic functions, such as program task scheduling, executing of application program code (such as exemplary monitoring program 325), and controlling lower level circuitry (e.g., registers, buffers, buses, counters, timers, and the like) on OMP 310 that interface with other peripheral circuitry onboard internal monitor drone 125 (such as the sensory array 230, proximity sensors 215a, 215b, the electronic docking connection 235, GPS 350, IMU 355, ESC 360a, 360b, communication interface 365, and DCI 370).

During operation and once operating system 320 is loaded, monitoring program code 325 may be run as part of implementing an aerial drone-based method for monitoring the internal storage contents of shipment storage 110. Exemplary monitoring program code 325 is a set of executable instructions in the form of one or more machine-readable program code modules or applications. The program code module(s) may be loaded and executed by OBC 300 (or at least the OMP 310) to adapt the drone 125 into a specially adapted and configured aerial monitoring apparatus. This specially configured OBC 300 of drone 125, as described in more detail herein as a part of an embodiment, implements operative process steps and provides functionality that is unconventional, especially when the process steps are considered collectively as a whole. Such a specially adapted and configured drone 125 helps, as a part of an embodiment, to address and improve targeted and technical monitoring of the condition of shipping items during all phases of logistics transport of such items as described in more detail below.

During operation, the OBC 300 (or at least the OMP 310) may access and/or generate data maintained within memory 315, such as sensory data 330, flight profile data 335, messaging data 340, and loading plan data 345. In general, sensory data 330 comprises sensory information gathered by different sensors (described above) on the sensory array 230 and may take different forms depending on the type of sensor used and the type of information gathered (e.g., numeric measurements of temperature or pressure, images, video, depth sensing measurements, etc.).

Flight profile data 335 comprises information that defines how the internal monitor drone 125 is to be flying. This data may include navigational data on an airborne monitoring path for the drone 125 to transit, as well as flight control setting information to use when generating flight control input for the ESCs 360a, 360b.

Messaging data 340 is generally a type of data used when the internal monitor drone generates and/or transmits a notification or other type of message related to the condition of one or more of the shipping items on aircraft 100. Such messaging data 340 may include information on messages received or generated onboard to be sent outside the drone 125.

Loading plan data 345 provides information on what is expected to be loaded within the shipment storage 110 and may also include information on what has actually been loaded and where such items are located within the internal shipment storage area 120.

Those skilled in the art will appreciate that the above identification of particular program code 325 and data 330-345 are not exhaustive and that embodiments may include further executable program code or modules as well as other data relevant to operations of a specially programmed processing-based internal monitor drone 125. Furthermore, those skilled in the art will appreciate that not all data elements illustrated in FIG. 3 as being within memory 315 must appear in memory 315 at the same time.

Those skilled in the art will further appreciate that OBC 300 (as well as OFC 305 and/or OMP 310) may be implemented with a low power embedded processor as part of a single-board computer having a system-on-chip (SoC) device operating at its core. In such an embodiment, the SoC device may include different types of memory (e.g., a removable memory card slot, such as a Secure Digital (SD) card slot, as removable memory; flash memory operating as onboard non-volatile memory storage; and RAM memory operating as onboard volatile memory); an operating system (such as Linux) stored on the non-volatile memory storage and running in volatile RAM memory; and peripherals that may implement any of the GPS 350, IMU 355, ESC 360a, 360b, communication interface 365, DCI 370, wired data interface 375 and charging interface 380.

Additionally, the exemplary internal monitor drone 125 includes an onboard power source, such as onboard battery 385. Onboard battery 385 provides electrical power to the active electric circuitry described above disposed on the internal monitor drone 125. Onboard battery 385 may be charged via charging interface 380 (one part of the electronic docking connection 235), which may be connected to an external power supply via the internal docking station 130. Such an onboard battery 385 may, for example, be implemented with a lightweight lithium-ion polymer battery.

FIGS. 4A and 4B are diagrams providing further details of an exemplary internal docking station 130 as it interfaces with and supports an internal monitor drone 125 in accordance with an embodiment of the invention. Referring now to FIG. 4A, exemplary internal monitor drone 125 is shown in a configuration and position relative to exemplary internal docking station 130 where the drone 125 is being secured to the docking station 130. Exemplary internal docking station 130 is shown in FIG. 4A having a housing 400, a set of securing clamps 405a, 405b disposed on the top of housing 400 as part of a physical docking interface that mates with the internal monitoring drone 125, and a wired communication line 410 (which may also include a power line providing power to the station 130).

As shown in FIG. 4A, exemplary landing gear 220a, 220b supports the drone 125 when landing on internal docking station 130 and as at least helps to hold drone 125 secure relative to the docking station 130 via exemplary securing clamps 405a, 405b. Such a secure configuration may be achieved in one embodiment that may have fixed landing gear 220a, 220b being grabbed and held securely by movable securing clamps 405a, 405b. In another embodiment, the securing clamps 405a, 405b may be fixed relative to the docking station 130 while the landing gear 220a, 220b is moved to grab the securing clamps 405a, 405b. In still a further embodiment, each of securing clamps 405a, 405b may be articulated or actuated to grab a bottom portion of each landing gear 220a, 220b while the landing gear 220a, 220b may also be articulated or actuated to mate with the securing clamps 405a, 405b. Further, the electronic docking connection 235 may be implemented so as to be an actuated connector that mates with a complementary connector on the docking station 130.

FIG. 4B provides a block diagram of elements within the housing 400 of an exemplary internal docking station 130. Referring now to FIG. 4B, a physical docking interface 415 is disposed along the top surface of the housing 400 to physically mate with parts of the internal monitor drone 125, and includes at least the securing clamps 405a, 405b. While some embodiments may have the securing clamps 405a, 405b in a fixed arrangement relative to the housing 400, other embodiments may deploy the securing clamps 405a, 405b as being movable and capable of being articulated using actuators 420a, 420b under the control of physical docking interface (PDI) control 425. In this later embodiment, a docking command may be received by the PDI control circuit 425 (e.g., a switch or relay) over wired communication line 410. In response to receiving the docking command, the PDI control circuit 425 controls the actuators 420a, 420b coupled to the securing clamps 405a, 405b. In an alternate embodiment, the PDI control circuit 425 may have a wireless linear actuator control that allows for remote wireless control of actuators 420a, 420b and, as a result, securing clamps 405a, 405b. For example, internal monitor drone 125 may rely on proximity sensors 215a, 215b and send the docking command to PDI control circuit 425 via a wireless message from communication interface 365.

Further still, an embodiment of internal docking station 130 includes its own communication interface 430 that mates with wired communication line 410. Communication interface 410 is coupled to an electronic data connection interface (EDCI) 435, which connects to wired data interface 375 when the internal monitor drone 125 is secured on the docking station 130 and when the electronic docking connection 235 is extended to mate with at least the EDCI 435. Communication interface 430 on the docking station 130 may include a compatible radio-based transceiver for wirelessly communicating with the communication interface 365 on internal monitor drone 125. This allows the docking station 130 to wireless communicate with the drone 125 without having the drone 125 secured to the docking station 130. For example, using such wireless communication functionality of interface 430 may allow the docking station 130 to act as a local base station for the internal monitor drone 125 and act as a communication intermediary with the vehicle transceiver 135 (e.g., when the drone 125 reports a detected condition of a shipping item by wireless transmission from interface 365 to the docking stations' wireless transceiver in interface 430, and then forwarding of the relevant reported condition information to vehicle transceiver 135).

Additionally, the internal docking station 130 may use an onboard power source 445, such as an AC/DC power supply or larger capacity battery that can provide current through electronic charging connection interface (ECCI) 440 to charge onboard battery 385 when the drone 125 is secured to the docking station 130.

FIG. 5 is a flow diagram illustrating an exemplary aerial drone-based method for monitoring the internal storage contents of a shipment storage in accordance with an embodiment of the invention. Referring now to FIG. 5, exemplary method 500 begins at step 505 with an internal monitor drone, such as internal monitor drone 125, receiving an activation command while in a secured position on an internal docking station fixed to the shipment storage in a drone storage area of the shipment storage. The activation command may be in the form of a wireless message received by the internal monitor drone from the docking station 130, the vehicle transceiver 135, or from a radio-based trans-

ceiver operated by logistics personnel involved in a logistics operation (such as loading or unloading the shipment storage). Alternatively, the activation command may be received in the form of a time-based command generated onboard the internal monitor drone where, for example, the internal monitor drone may be deployed to activate from the secured position periodically rather than stay airborne for a lengthy duration. As noted with reference to FIGS. 1A-1C, the shipment storage may be implemented by a storage compartment within an aircraft (e.g., shipment storage 110 within aircraft 100), a trailer capable of being moved by a truck, or a train car capable of being moved on a railway system. When the shipment storage is within an aircraft, the internal storage contents may include one or more shipping items, such as a unit load device (ULD) container. Such a ULD container may be broadcast-enabled with a sensor-based radio transceiver that can broadcast a signal (as detected by the internal monitor drone's sensor array) without a preliminary interrogation of the ULD container to prompt broadcast of the signal. For example, rather than rely on an RFID tag that must be polled or prompted in order to broadcast a signal, the ULD container may be deployed with a sensor-based radio transceiver that may periodically broadcast signals having information within it that pertains to a condition of the ULD container and its contents.

At step 510, method 500 continues with the internal monitor drone transitioning from at least a low power state to an active monitoring state as part of a logistics operation related to the shipment storage. Such a logistics operation related to the shipment storage may be a loading operation of the shipment storage area of the shipment storage; an unloading operation of the shipment storage area of the shipment storage; or an in-transit monitoring operation of the shipment storage area of the shipment storage while the shipment storage is moving. The low power state may be a complete shut off condition where the internal monitor drone is unpowered. In other embodiments, the low power state may be a sleep type of state where some circuitry is off (e.g., lifting engines 210a, 210b, etc.) while another subset of the onboard circuitry remains powered on (e.g., GPS 350 and IMU 355 to help avoid delays prior to lift off from the docking station 130). When transitioning to the active monitoring state, where the internal monitor drone will be ready for airborne sensor activities along an airborne monitoring path within the shipment storage, the internal monitor drone prepares to separate from the internal docking station. For example, as shown in FIG. 1B, internal monitor drone (1 MB) 125 transitions to the active monitoring state from the low power state in preparation for flying above the shipping items 140a-145e within the internal shipment storage area 120.

At step 515, method 500 proceeds with the internal monitor drone automatically uncoupling from the internal docking station once the internal monitor drone transitions to the active monitoring state. For example, internal monitor drone 125 may automatically uncouple from the internal docking station 130, as depicted and described with respect to FIGS. 1C and 4A. In this embodiment, the drone's landing gear 220a, 220b separates from being mated with the securing clamps 405a, 405b of the docking station 130 to accomplish such automatic uncoupling. This may be implemented by articulating the landing gear 220a, 220b, articulating the securing clamps 405a, 405b, or both depending on the complexity of the internal monitor drone, docking station, and anticipated vibrational environment within the

drone storage area **115** (which may warrant articulating both the securing structure on the drone **125** and the docking station **130**).

At step **520**, method **500** continues with the internal monitor drone moving from the secured position on the internal docking station to an initial airborne position within the shipment storage. For example, internal monitor drone **125** is shown in FIGS. **1B** and **1C** moving to an initial airborne position. Such a position may be just above the docking station **130** and still within drone storage area **115** or, may be at a first waypoint or location along an airborne monitoring path within the internal shipment storage area **120** of aircraft **100**.

At step **525**, method **500** continues with the internal monitor drone deploying its sensor array to gather sensory information as the internal monitor drone flies/moves from the initial airborne position along an airborne monitoring path within a shipment storage area of the shipment storage. The gathered sensory information is provided from the sensor array to an onboard processor on the internal monitor drone, such as the OBC **300** or OMP **310**, where it may be processed, reviewed, and analyzed onboard the internal monitor drone as part of detecting a condition of the contents of the shipment storage area.

In one embodiment, the gathered sensory information may be identification-related information involving barcodes, signs, and/or labels related to different contents within the shipment storage (e.g., different shipping items **140a-145e**). For example, step **525** may implement gathering the sensory information by using a scanning sensor element of the sensor array to scan an identification symbol fixed to an item of the internal storage contents as the internal monitor drone transits the airborne monitoring path within the shipment storage. For example, as **1 MB 125** shown in FIG. **1C** transits an airborne path above or near shipping item **140b**, a scanning sensor element of sensor array **230** may scan an identification symbol on the top or side of shipping item **140b**. Such an identification symbol may be a barcode symbol identifying shipping information related to shipping item **140b** (e.g., recipient, destination address, tracking number, shipment loading information, weight, and the like). In another example, the identification symbol may be a sign (such as a shipping label) affixed to the shipping item where the sign identifies the shipment information related to the item (such as loading information on placement of the item when being shipped within the shipment storage).

At step **530**, method **500** has the onboard processor on the internal monitor drone autonomously detecting a condition of the internal storage contents (e.g., at least one item being shipped within the internal shipment storage) based upon the sensory information provided by the sensor array. For example, when the sensory array gathers environmental information in step **525** relative to different airborne locations (e.g., particular waypoints, locations near particular shipping items, or locations near groups of shipping items maintained within the shipment storage) while transiting the airborne monitoring path within the shipment storage, the internal monitor drone's onboard processor may automatically identify an environmental condition as the condition of the internal storage contents in step **530**.

Different types of environmental conditions may be automatically identified depending on the type of sensing element used within an embodiment of the internal monitor drone's sensor array. For example, the environmental condition identified may be a movement condition as sensed by a motion sensor element of the sensor array; a light condition

as sensed by a light sensor element of the sensor array; a sound condition as sensed by a microphone element of the sensor array; a temperature condition as sensed by a temperature sensor element of the sensor array; a smoke condition as sensed by a smoke sensor element of the sensor array; a humidity condition as sensed by a moisture sensor element of the sensor array; and a pressure condition as sensed by a pressure sensor element of the sensor array. In other words, the sensor array deployed on the internal monitor drone implementing method **500** may include one or a wide variety of different types of sensors used to identify different environmental conditions relative to one or more items being shipped within the shipment storage (such as shipping items **140a-145e** within internal shipment storage area **120**).

Further embodiments may use multiple types of sensor-based environmental information as part of automatically identifying the environmental condition as the condition of the internal storage contents in step **530**. For example, using a smoke sensor, a light sensor, and a temperature sensor in the sensor array may allow the onboard processor to automatically identify a fire condition relative to a particular shipping item. In another example, using a moisture sensor and a microphone in the sensory array may allow the onboard processor to automatically identify a breakage/leak condition relative to a particular shipping item. Those skilled in the art will appreciate that the onboard processor of the internal monitoring drone may cross reference the gathered environmental information against parameters that fit different types of environmental conditions as a way of automatically identifying the environmental condition based on one or more types of environmental information gathered through one or more sensing elements of the sensor array. This may involve a multi-variate table lookup in a simpler internal monitoring drone implementation or, in another embodiment, may involve having monitoring program **325** including a database for matching the gathered environmental information to different environmental conditions as part of automatically identifying the environmental condition in step **530**.

In another embodiment, method **500** may have the sensory information and detected condition related to captured images and detection of a configuration change of what is maintained within the shipment storage. More specifically, a further embodiment of method **500** may implement the gathering step **525** as using an image sensor as an element of the sensor array to capture different images of the internal storage contents from one or more airborne locations within the shipment storage as the internal monitor drone transits the airborne monitoring path within the shipment storage. As such, the autonomously detecting step **530** may then be implemented by automatically identifying a configuration change as the condition of the internal storage contents. The configuration change may be automatically identified by the onboard processor of the internal monitor drone based upon a comparison of at least two of the captured images. For example, the captured different images may include one or more images of a portion of the internal storage contents from the same airborne location at different times as the internal monitor drone repeatedly transits the airborne monitoring path within the shipment storage. In doing so, the internal monitor drone captures what may be a time sequence of images related to the same item or items being shipped within the shipment storage or a sequence of images over time of the same item or items from more than one perspective (e.g., images of a top of a shipping item **140a** and a side of the shipping item **140a** over time). Using such

25

a sequence of images, the onboard controller of the internal monitor drone may image process the different images to find what has changed relative to what should be the same image of the same item or items. If shipping item **140a** unintentionally moves during flight, this comparison of images allows the internal monitor drone's onboard controller (such as the OMP **310**) to automatically identify a configuration change relative to item **140a** given its movement. Likewise, if shipping item **145d** is unintentionally crushed due to the weight of item **145b**, this comparison of images allows the internal monitor drone's onboard controller (such as the OMP **310**) to automatically identify a configuration change relative to item **145d** given its damaged exterior.

In still another embodiment, method **500** may have the sensory information and detected condition related to depth sensor information and multi-dimensional mappings of what is maintained within the shipment storage. More specifically, a further embodiment of method **500** may implement the gathering step **525** using a depth sensor as an element of the sensor array to map a configuration of the shipment storage area of the shipment storage as the internal monitor drone transits the airborne monitoring path within the shipment storage. The mapped configuration of the shipment storage area is, in more detail, a multi-dimensional mapping of the internal storage contents of the shipment storage. For example, internal monitor drone **125** may fly within the internal shipment storage area **120** and use a depth sensor as part of sensor array **230** to map this area **120** and the shipping items **140a-145e** maintained within it. As such, the autonomously detecting step **530** may then be implemented by automatically identifying a change in the multi-dimensional mapping of the internal storage contents over time as the internal monitor drone repeatedly transits the airborne monitoring path within the shipment storage to be the autonomously detected condition of the internal storage contents. Thus, the autonomously detected condition may reflect a shift in location for some of the contents (such as after experiencing turbulence during in-flight monitoring), or may reflect a loading status for what has been loaded within or unloaded from the shipment storage (such as during loading or unloading logistics operations of aircraft **100**).

In an embodiment where one or more of the internal storage contents of the shipment storage include broadcast enabled shipping items (e.g., items **145c-145e**), a further embodiment of method **500** may have the gathering step **525** implemented by receiving a wireless signal broadcast from a broadcast-enabled package of the internal storage contents and then proceed as part of step **530** to automatically identifying the condition of the internal storage contents based upon the received wireless signal broadcast from the broadcast-enabled package. This wireless signal may be received by a radio-based receiver operating as at least part of the sensor array. In some implementations, the radio-based receiver part of the sensor array may operate as an RFID tag reader where it first interrogates the broadcast-enabled package in order to prompt the broadcast of such a wireless signal. However, in other implementations, the radio-based receiver part of the sensor array may receive the wireless signal without interrogating the broadcast-enabled package to prompt the broadcast of the wireless signal and merely be a listening type of radio-based receiver element of the sensor array.

At step **535**, an embodiment of method **500** may have the onboard processor of the internal monitor drone transmitting a monitoring update message indicating the autonomously

26

detected condition of the internal storage contents. In more detail, the transmitted monitoring update message may be transmitted to a wireless receiver on the internal docking station (e.g., the wireless part of communication interface **430** as described above), which then may pass along the message to another transceiver (e.g., vehicle transceiver **135** operated by flight crew personnel, or a radio-based receiver operated by maintenance personnel assigned to the aircraft **100** or logistics personnel responsible for loading/unloading the aircraft **100**). Alternatively, the transmitted monitoring update message may be wirelessly sent directly at least one of the vehicle transceiver **135** operated by flight crew personnel, or a radio-based receiver operated by maintenance personnel assigned to the aircraft **100** or logistics personnel responsible for loading/unloading the aircraft **100**.

In a further embodiment of step **535**, any such transmission of the monitoring update message may be delayed and transmitted at a later time. In particular, the onboard processor of the internal monitor drone may opt to transmit the monitoring update message to a shipment storage transceiver (e.g., vehicular transceiver **135** or a radio-based receiver operated by personnel that load/unload the shipment storage or perform maintenance on the aircraft having the shipment storage) only if the onboard processor autonomously confirms a communication channel to the shipment storage transceiver is active. This may be accomplished by scanning for such a transceiver and receiving a wireless signal indicating that the transceiver is active and able to receive transmissions from another device, such as the internal monitor drone. If the onboard processor cannot confirm the communication channel is active, the onboard processor of the internal monitor drone may store the monitoring update message for later transmission to the shipment storage transceiver. Such a delay may be useful when the internal monitor drone is transiting a distant part of the airborne monitor path that may be outside the acceptable reception range of vehicular transceiver **135** or a radio-based receiver operated by personnel that load/unload the shipment storage or perform maintenance on the aircraft having the shipment storage. For example, the internal monitor drone may delay transmission of the monitoring update message to a radio-based receiver operated by logistics personnel loading the shipment storage for when the personnel are back within the shipment storage attempting to load another item. Such a delayed message helps avoid missed messages and enhances how the shipment storage is being loaded so that quicker corrective actions may be initiated and completed.

Steps **540-550** of method **500** involve monitoring for a loading plan inconsistency while steps **555-565** involve monitoring for an orientation inconsistency for logistics operations related to the shipment storage. In more detail, an embodiment of method **500** may continue at step **540** to have the onboard processor of the internal monitor drone autonomously determining a loading status of the item by comparing the item's identification symbol (as scanned by the scanning sensor of the sensor array) to a loading plan for the shipment storage maintained within a memory of the internal monitor drone. Such a loading plan (e.g., loading plan data **345**) may have been preloaded into the internal monitor drone's memory, or alternatively, method **500** may include the step of downloading the loading plan into the memory of the internal monitor drone. In such an embodiment, downloading the relevant loading plan for what is supposed to be loaded and carried within the shipment storage may take place prior to or right after scanning the item's identification symbol. In this way, the internal monitor drone has a current

and up-to-date loading plan and can reference such information to the scanned identification symbol in step 545 to detect a loading plan inconsistency (e.g., a loading status for the item showing it is loaded within the shipment storage but should not be according to the loading plan). Thus, at step 545, method 500 may proceed directly to step 555 if there is no inconsistency detected. However, if method 500 detects a loading plan inconsistency at step 545 (i.e., when the loading status of the item indicates the presence of the item within the shipment storage area of the shipment storage is inconsistent with the loading plan), method 500 proceeds to step 550 where the onboard processor of the internal monitor drone automatically transmits a loading warning.

For example, as shown in FIG. 1C, exemplary internal monitor drone 125 may have a scanning sensor within sensory array 230 and use that to capture an identification symbol (e.g., a barcode symbol or the like) from shipping item 140b while transiting an airborne monitoring path within internal shipment storage area 120. The internal monitor drone 125 may then compare the captured identification symbol for shipping item 140b with the loading plan data 345 kept in memory 315 to identify or detect that item 140b should not be present within internal shipment storage area 120. This may occur when loading personnel mistakenly load item 140b thinking it actually belongs on aircraft 100, or when loading personnel mistakenly load item 140b on aircraft 100 accidentally believing aircraft 100 was another aircraft. A further embodiment may have separate loading plans for separate internal shipment storage areas when such is available on another delivery vehicle, and unintended loading into an incorrect one of the different storage areas may be more prevalent.

Like the transmitted monitoring update message from step 535, an embodiment of method 500 may transmit the loading warning to a wireless receiver on the internal docking station (e.g., the wireless part of communication interface 430 as described above), which then may pass along the message to another transceiver (e.g., vehicle transceiver 135 operated by flight crew personnel, or a radio-based receiver operated by logistics personnel responsible for loading the aircraft 100). Alternatively, the transmitted loading warning may be wirelessly sent directly at least one of the vehicle transceiver 135 operated by flight crew personnel, or the radio-based receiver operated by logistics personnel responsible for loading the aircraft 100. In such a manner, an embodiment may rapidly detect a loading plan inconsistency and allow for faster resolution of this issue—especially while the loading operation is still ongoing and correction can be prompted automatically in response to the transmitted loading warning. Method 500 then proceeds from step 550 to step 555.

As stated above, steps 555-565 generally involve monitoring for an orientation inconsistency for logistics operations related to the shipment storage. In particular, at step 555, an embodiment of method 500 continues with the onboard processor of the internal monitor drone autonomously determining a position status of a shipping item based upon item's identification symbol as scanned by the sensor array (e.g., a barcode reader or image sensor that captures information on the identification symbol). In this embodiment, the identification symbol scanned may include a directional sign, image, or symbol indicating a desired item orientation (e.g., a graphic image denoting a desired orientation, such as which surface should be facing up, and the like). Here, the position status of the item relies on such orientation-related information on the identification symbol

and the current orientation of the item as scanned to reflect whether the current orientation of the identification symbol as scanned is inconsistent with the desired item orientation.

Thus, at step 560, method 500 may proceed directly to step 570 if there is no inconsistency detected relative to the orientation of the shipping item. However, if method 500 detects an orientation inconsistency for the item at step 560 (i.e., when the current orientation of the item is different from the desired orientation per the scanned information), method 500 proceeds to step 565 where the onboard processor of the internal monitor drone automatically transmits a positional warning.

Like the transmitted monitoring update message from step 535 and the loading warning in step 550, an embodiment of method 500 may transmit the positional warning to a wireless receiver on the internal docking station (e.g., the wireless part of communication interface 430 as described above), which then may pass along the message to another transceiver (e.g., vehicle transceiver 135 operated by flight crew personnel, or a radio-based receiver operated by logistics personnel responsible for loading the aircraft 100). Alternatively, the transmitted positional warning may be wirelessly sent directly at least one of the vehicle transceiver 135 operated by flight crew personnel, or the radio-based receiver operated by logistics personnel responsible for loading/unloading the aircraft 100. In such a manner, an embodiment may rapidly detect that one or more shipping items placed within the interior shipment storage area are not placed correctly (which may cause damage—especially if not corrected before the shipment storage moves (e.g., the aircraft 100 takes off, flies, and experiences vibrations and turbulence in-flight)).

Method 500 then proceeds from step 565 to step 570 where the internal monitor drone moves to the next airborne position on the airborne monitoring path. Method 500 then proceeds back to step 525 to continue aerial drone-based monitoring of the internal storage contents of the shipment storage.

In some embodiments, the internal monitor drone may transit the airborne monitoring path once and then autonomously land back on the internal docking station (where it may recharge, download sensory information gathered, and upload revised flight profile data). In other embodiments, the internal monitor drone may transit the airborne monitoring path multiple times and then autonomously land back on the internal docking station. The complexity and length of the airborne monitoring path as well as the weight of the internal monitor drone (with its onboard suite of sensors in the sensory array) will impact a time aloft factor that impacts airborne monitoring operations of the internal monitor drone.

In still other embodiments, the internal monitor drone may operate as explained with respect method 500, and then further receive a follow-up monitor command. The follow-up monitor command causes the internal monitor drone to return to at least a particular airborne position in the monitoring path and gather further sensory information using the sensor array. The further sensory information may be enhanced sensory information to gather additional details, such as additional sensory information taken in higher resolution, taken over a longer time period, taken with more than one sensing element of the sensor array, and/or taken from a broader range of perspectives relative to one or more shipping items. In a more specific embodiment, the internal monitor drone may receive such a follow-up monitor command as feedback from the vehicle transceiver 135 operated by flight crew personnel, the radio-based receiver operated

by logistics personnel responsible for loading/unloading the aircraft **100**, or the radio-based receiver operated by maintenance personnel responsible for servicing the aircraft **100**. Such feedback may be in response to a monitoring update message, a loading warning, or a positional warning where the broadcaster of the follow-up message may desire more sensory information before taken any corrective action (e.g., having personnel enter the internal shipment storage area **120** to physically inspect one of the shipping items **140a-145e**, rearrange placement of such an item, or remove such an item).

Those skilled in the art will appreciate that method **500** as disclosed and explained above in various embodiments may be implemented with an apparatus, such as exemplary internal monitor drone **125**, running an embodiment of airborne monitoring program code **325**, and as a part of a drone-based monitored storage system including the shipment storage, docking station, and internal monitor drone. Such code **325** may be stored on a non-transitory computer-readable medium such as memory storage **315** on internal monitor drone **125**. Thus, when executing code **325**, the OBC **300** (or OMP **310**) of internal monitor drone **125** (in cooperation with other circuitry onboard the drone **125**, such as elements of the sensor array **230**) may be operative to perform certain operations or steps from the exemplary methods disclosed above, including method **500** and variations of that method.

FIG. **1C**, as discussed above, illustrates a general example of such a drone-based monitored storage system that relies on a single internal monitor drone. However, other embodiments may deploy multiple internal monitor drones to monitor a shipment storage, such as shipment storage **110**. Using multiple internal monitor drones to monitor a shipment storage may enhance monitoring of the shipment storage, for example, by allowing for divided monitoring responsibilities, allowing the different internal monitor drones to use different types of sensors in their respective sensor arrays, and employ a more robust level of monitoring in a given time within the shipment storage. By deploying a swarm of internal monitor drones to monitor the shipment storage, the task of monitoring what is maintained in the shipment storage is coordinated and accomplished in a much quicker way.

FIG. **6** is a diagram of an exemplary multiple drone-based monitored storage system that includes shipment storage **110**, two internal docking stations **630a**, **630b**, and two internal monitor drones **625a**, **625b**. Referring now to FIG. **6**, exemplary shipment storage **110** is similar to that described with respect to FIGS. **1A-1C** in that it includes a closable entry similar to entry **112** shown in FIG. **1A** that provides access to within the shipment storage, and an interior shipment storage area **120** within shipment storage **110** that temporarily maintains custody of items being shipped (e.g., shipping items **140a**, **140b**, and **145b-145e**). The shipment storage **110** further includes multiple drone storage areas as part of area **115** (e.g., different parts of drone storage area **115** where two internal docking stations **630a**, **630b** are respectively disposed). In other words, each of the internal docking stations **630a**, **630b** are fixed within respectively different areas or part of drone storage area **115**. The internal monitor drones **625a**, **625b** are initially disposed on respective ones of the internal docking stations **630a**, **630b**. Each of the internal monitor drones **625a**, **625b** has a sensor array that gathers sensory information as the respective internal monitor drone moves within a part of the interior shipment storage area of the shipment storage. As mentioned above, in some embodiments, the sensor array in one

internal monitor drone may be equipped with similar sensing elements as the sensor array in the other internal monitor drone. However, in other embodiments, the different sensor arrays in the different internal monitor drones may include sensor elements that do not entirely overlap. For example, exemplary internal monitor drone **625a** may include a suite of sensors in its sensor array that includes a scanning sensor or image sensor capable of capturing identification information from labels, signs, or barcodes on the exterior of shipping items **140a**, **140b** while exemplary internal monitor drone **625b** may deploy with a different suite of sensors in its array better suited to monitor broadcast-enabled shipping items **145b-145e** (where some surfaces of items **145b-145e** are not visible or scannable).

As deployed as part of such an exemplary multiple drone-based monitored storage system, one of the internal monitor drones (e.g., drone **625a**) may operate as part of the system to move from one of the internal docking stations (e.g., docking station **630a**) to a first initial airborne position within the shipment storage as part of a first airborne monitoring path within a first part of the interior shipment storage area of the shipment storage (e.g., an airborne monitoring path that takes drone **625a** over items **140a** and **140b**). At this first initial airborne position, this first internal monitor drone aerially monitors a first part of the items being shipped within the interior shipment storage area using the sensor array on the first of the internal monitor drones. As such, this first internal monitor drone begins aerial monitoring of items at the first initial airborne position and as the drone transits the first airborne monitoring path from the first initial airborne position. A second of the internal monitor drones (e.g., drone **625b**) may operate as part of the system to move from one of the internal docking stations (e.g., docking station **630b**) to a second initial airborne position within the shipment storage as part of a second airborne monitoring path within a second part of the interior shipment storage area of the shipment storage (e.g., a second airborne monitoring path that takes drone **625b** over items **145b-145e**). At this second initial airborne position, the second internal monitor drone aerially monitors the second part of the items being shipped within the interior shipment storage area using the sensor array on the second of the internal monitor drones.

As the different internal monitor drones are using their respective sensory arrays to gather sensory information and monitor the first part of the items being shipped and the second part of the items being shipped, at least one of the first and second internal monitor drones autonomously detects a condition of an item being shipped based upon sensory information generated when monitoring the items being shipped within the interior shipment storage area by the first of the internal monitor drones and the second of the internal monitor drones. Such a condition may generally be related to the sensory information gathered by one or both internal monitor drones, or may be related how such sensory information gathered is beyond a threshold or range of acceptable values. The types of sensors that may be deployed on the respective first and second internal monitor drones are similar to those discussed above as being part of exemplary sensor array **230** and those that may be used as part of embodiments of method **500**.

Likewise, one or more of the internal monitor drones may be operative to autonomously determine a loading status for an item being monitored relative to a loading plan for that drone's monitored part of the internal shipment storage and to automatically transmit a loading warning when the loading status of the item indicates the item's presence within the

interior shipment storage area of the shipment storage is inconsistent with that particular loading plan used by that internal monitor drone (similar to steps **540-550** of method **500**). Additionally, one or more of the internal monitor drones may be operative to autonomously determine a position status for an item being monitored. That internal monitor drone may determine the position status of the item based upon an identification symbol as scanned by that monitor drone's scanning sensor (where the identification symbol comprises a directional sign indicating a desired item orientation for the one item and where the position status of the item reflects whether a current orientation of the identification symbol as scanned is inconsistent with the desired item orientation) and then automatically transmit a positional warning when the position status indicates the current orientation of the identification symbol is inconsistent with the desired item orientation (similar to steps **555-565** of method **500**).

Explaining how such a system may operate in more detail, FIG. 7 is a flow diagram illustrating an exemplary multiple aerial drone-based method for monitoring the internal storage contents of a shipment storage in accordance with an embodiment of the invention. Such a shipment storage may, for example, be implemented by a storage compartment within an aircraft, a trailer capable of being moved by a truck, a storage or cargo compartment of a marine vessel, or a train car capable of being moved on a railway system. Referring now to FIG. 7, exemplary method **700** begins at step **705** by moving a first internal monitor drone to a first initial airborne position within the shipment storage as part of a first airborne monitoring path within the shipment storage. The first internal monitor drone (e.g., drone **625a** shown in FIG. 6) is disposed within a first drone storage area of the shipment storage (e.g., a first part of drone storage area **115** where internal docking station **630a** is located). In more detail, an embodiment of step **705** may have the first internal monitor drone being selectively uncoupled from a first internal docking station (e.g., internal docking station **630a**) disposed at a fixed location within the first drone storage area of the shipment storage prior to moving the first internal monitor drone from its secured position on the first internal docking station to its initial airborne position of the first airborne monitoring path.

In one embodiment, the first airborne monitoring path used by the first internal monitor drone in this embodiment corresponds to a first part of an interior shipment storage area within the shipment storage. However, in other embodiments, the different internal monitor drones may have different monitoring paths that overlap or transit through overlapping or coexistent parts of the internal shipment storage area (but that would not have one of the drones being at a location too close to another drone at the same time).

At step **710**, method **700** continues by moving a second internal monitor drone to an initial airborne position for that drone within the shipment storage as part of a second airborne monitoring path within the shipment storage. The second internal monitor drone (e.g., drone **625b** shown in FIG. 6) is disposed within a second drone storage area of the shipment storage (e.g., a second part of drone storage area **115** where internal docking station **630b** is located). In more detail, an embodiment of step **710** may have the second internal monitor drone being selectively uncoupled from a second internal docking station (e.g., internal docking station **630b**) disposed at a fixed location within the second drone storage area of the shipment storage prior to moving the second internal monitor drone from its secured position on the second internal docking station to its initial airborne

position of the second airborne monitoring path. As such, steps **705** and **710** have the first and second internal monitoring drones airborne and ready to begin gathering sensory information as part of aerially monitoring the internal contents of the shipment storage.

At steps **715** and **720**, the different internal monitor drones are deployed to aerially gather different sensory information related to what is loaded and maintained within the shipment storage. In particular, method **700** proceeds at step **715** with aerially monitoring a first part of the internal storage contents of the shipment storage with a first sensor array on the first internal monitor drone as the first internal monitor drone transits the first airborne monitoring path within the shipment storage from the first initial airborne position. This aerially monitoring action may take the form or be implemented with the first sensor array sensing environmental information relative to one or more airborne locations within the shipment storage as the first internal monitor drone transits the first airborne monitoring path within the shipment storage.

Similarly, at step **720**, method **700** proceeds with aerially monitoring a second part of the internal storage contents of the shipment storage with a second sensor array on the second internal monitor drone as the second internal monitor drone transits the second airborne monitoring path within the shipment storage from the second initial airborne position. And like step **715**, the aerial monitoring in step **720** may be implemented with the second sensor array sensing environmental information as the second sensory information relative to one or more airborne locations within the shipment storage as the second internal monitor drone transits the second airborne monitoring path within the shipment storage.

An embodiment of method **700** may continue to step **725** where method **700** may take action based upon the sensory information gathered by the different internal monitor drones. In particular, at step **725**, method **700** may proceed by determining if any of the sensory information gathered by the first and second internal monitor drones is out of range or beyond what may be anticipated for the items maintained within the shipment storage. For example, the sensory data maintained within each of the first and second internal monitor drones may include range/threshold data (e.g., range/threshold information maintained as part of sensory data **330** in drones **625a** and **625b**). Such range/threshold data may define expected sensor value ranges or sensor value thresholds relevant to the sensor elements that make up the drones' respective sensor array. For example, such range/threshold data may be specific to temperature and light conditions anticipated to be experienced relative to the items in the respective parts of internal shipment storage area **120** monitored by each of internal monitor drone **625a** and internal monitor drone **625b**. Further examples of what may be considered out of range in step **725** may, in some embodiments, extend to inconsistencies with loading plan data (e.g., the gathered sensor information includes identification information on a shipping item that should be present within that part of the internal shipment storage area and, thus, reflects an out of range situation relative to the loading plan data for that part of the internal shipment storage area). Likewise, what may be considered out of range in step **725** may, in some embodiments, extend to inconsistencies with item orientations. For example, sensory information gathered by a first of the internal monitor drones **625a** may include an image of a sign denoting a desired orientation for a particular shipping item. When comparing the orientation of that image to the current orientation of the

33

item, such gathered sign information (as gathered sensory information) may indicate an out of range situation between the current orientation and the desired orientation. The particular item may have been loaded incorrectly, shifted while the aircraft **100** taxied for takeoff, during takeoff, during airborne flight (such as after experiencing turbulence), or upon landing. Thus, if the sensory information gathered by the first and second internal monitor drones is not out of range, method **700** continues from step **725** to step **730** where the first and second internal monitor drones may further transit and aerially monitor their respective parts of the internal storage contents along their respective airborne monitor paths. Otherwise, step **725** proceeds directly to step **735** where method **700** detects a condition of the internal storage contents based upon at least one of (1) first sensory information generated when monitoring with the first sensor array of the first internal monitor drone and (2) second sensory information generated when monitoring with the second sensor array of the second internal monitor drone.

In one embodiment of method **700**, detecting the condition of the internal storage contents in step **735** may be accomplished by automatically identifying an environmental condition as the condition of the internal storage contents based upon at least one of environmental information gathered by the first internal monitor drone and environmental information gathered by the second internal monitor drone. As previously explained, different types of environmental conditions may be automatically identified depending on the type of sensing element used within the particular internal monitor drone's sensor array. For example, the environmental condition identified may be a movement condition as sensed by a motion sensor element of the sensor array on the first or second internal monitor drone; a light condition as sensed by a light sensor element of the sensor array on the first or second internal monitor drone; a sound condition as sensed by a microphone element of the sensor array on the first or second internal monitor drone; a temperature condition as sensed by a temperature sensor element of the sensor array on the first or second internal monitor drone; a smoke condition as sensed by a smoke sensor element of the sensor array on the first or second internal monitor drone; a humidity condition as sensed by a moisture sensor element of the sensor array on the first or second internal monitor drone; and a pressure condition as sensed by a pressure sensor element of the sensor array on the first or second internal monitor drone. In other words, the respective sensor arrays deployed on the different internal monitor drones implementing method **700** may include one or a wide variety of different types of sensors used to identify different environmental conditions relative to one or more items being shipped within the shipment storage (such as shipping items **140a-145e** within internal shipment storage area **120**). And further embodiments may use multiple types of sensor-based environmental information as part of automatically identifying the environmental condition by one or the first or second internal monitor drones as the condition of the internal storage contents in step **735**.

After step **735**, method **700** may transmit a monitoring update message to a shipment storage transceiver, such as vehicle transceiver **135**, in step **740**. Such a monitoring update message indicates the detected condition of the internal storage contents and is transmitted either by the first internal monitor drone when the detected condition is based upon the first sensory information, or by the second internal monitor drone when the detected condition is based upon the second sensory information.

34

Similar to that disclosed relative to method **500**, a further embodiment of method **700** may also include steps that verify proper loading of the shipment storage using one or more of the multiple internal monitor drones. For example, the first internal monitor drone may determine a loading status of a first monitored shipping item based upon comparing an identification symbol as scanned by the first internal monitor drone to a downloaded loading plan for the shipment storage maintained within memory of the first internal monitor drone. The first internal monitor drone may then generate a first loading warning when the loading status of this first item indicates the presence of the first item within the shipment storage is inconsistent with the loading plan, and transmit the first loading warning to a shipment storage transceiver (such as vehicle transceiver **135**). Likewise, the second internal monitor drone may determine a loading status of a second monitored shipping item based upon comparing the second identification symbol as scanned by the second internal monitor drone to the loading plan for the shipment storage maintained within memory of the second internal monitor drone. The second internal monitor drone may then generate a second loading warning when the loading status of the second item indicates that the presence of the second item within the shipment storage is inconsistent with the loading plan, and transmit the second loading warning to a shipment storage transceiver (such as vehicle transceiver **135**).

And similar to that disclosed relative to method **500**, a further embodiment of method **700** may also include steps that verify proper positioning of items within the shipment storage using one or more of the multiple internal monitor drones. For example, the first internal monitor drone may determine a position status of a first shipping item based upon the first identification symbol as scanned by the first internal monitor drone. This first identification symbol includes at least a first directional sign indicating a desired item orientation for the first item, and the position status of the first item reflects whether a current orientation of the first item is inconsistent with the desired item orientation as reflected by the identification symbol's directional sign. The first monitor drone then generates a first positional warning when the position status of the first item indicates the current orientation of the first item is inconsistent with the desired item orientation for the first item, and then transmits the first positional warning to a shipment storage transceiver (such as the vehicle transceiver **135**). Additionally, the second internal monitor drone may determine a position status of a second item based upon a second identification symbol as scanned by the second internal monitor drone. The second identification symbol includes a second directional sign indicating a desired item orientation for the second item, and the position status of the second item reflects whether a current orientation of the second item is inconsistent with the desired item orientation for the second item. The second internal monitor drone then generates a second positional warning when the position status of the second item indicates the current orientation of the second item is inconsistent with the desired item orientation for the second item, and transmits the second positional warning to the shipment storage transceiver (such as vehicle transceiver **135**). With such loading and/or positional warnings, the shipment storage transceiver may respond as part of an embodiment of such a multiple internal monitor drone system to notify logistics radio-based transceivers operated by loading personnel that can then address the loading or positional related issue underlying such warnings.

35

In steps **715** and **720** of method **700**, the aerial monitoring may be more specifically implemented using further types of sensor elements. For example, in a further embodiment of method **700**, aerially monitoring the first part of the internal storage contents with the first sensor array in step **715** may involve capturing, with a first image sensor part of the first sensor array, at least one image of the first part of the internal storage contents from each of a first plurality of airborne locations within the shipment storage as the first internal monitor drone transits the first airborne monitoring path within the shipment storage. In like fashion, aerially monitoring the second part of the internal storage contents with the second sensor array in step **720** may involve capturing, with a second image sensor part of the second sensor array, at least one image of the second part of the internal storage contents from each of a second plurality of airborne locations within the shipment storage as the second internal monitor drone transits the second airborne monitoring path within the shipment storage. As such, step **735** may then involve automatically identifying the condition of the internal storage contents based upon at least one of the at least one image captured by the first image sensor or the at least one image captured by the second image sensor.

In a further embodiment, method **700** may have step **735** automatically identifying a configuration change as the condition of the internal storage contents based upon at least one of (1) a comparison of multiple images over time from the first image sensor as the first internal monitor drone repeatedly transits the first airborne monitoring path and (2) a comparison of multiple images over time from the second image sensor as the second internal monitor drone repeatedly transits the second airborne monitoring path.

In still another more detailed embodiment, a depth sensor may be used in the first and/or second internal monitor drone's sensor array so as to gather multi-dimensional mapping information as the relevant monitored sensory information related to the internal storage contents. In particular, an embodiment of method **700** may implement aerially monitoring the first part of the internal storage contents with the first sensor array in step **715** by mapping, with a first depth sensor part of the first sensor array, a first configuration of a first storage area within the shipment storage that maintains the first part of the internal storage contents as the first internal monitor drone transits the first airborne monitoring path within the shipment storage. The first configuration represented as a multi-dimensional mapping of at least the first part of the internal storage contents. For example, internal monitor drone **625a** may use a depth sensor on its sensor array to map the part of the internal shipment storage area **120** patrolled by internal monitor drone **625a**. The mapping produced by such a depth sensor may take the form of a three-dimensional mapping of shipping items **140a** and **140b** as they exist within the front part of internal shipment storage area **120**. Such a mapping can be referred to as a configuration of shipping items **140a** and **140b** as that particular time. In similar fashion, aerially monitoring the second part of the internal storage contents with the second sensor array in step **720** may involve using a second depth sensor part of the second sensor array to map a second configuration of a second storage area within the shipment storage that maintains the second part of the internal storage contents as the second internal monitor drone transits the second airborne monitoring path within the shipment storage. As such, step **735** in this further embodiment of method **700** may be done by automatically identifying the condition of the internal storage contents based upon at least one of the multi-dimensional mapping of

36

at least the first part of the internal storage contents and the multi-dimensional mapping of at least the second part of the internal storage contents. More specifically, step **735** may be implemented by automatically identifying a configuration change as the condition of the internal storage contents based upon at least one of (1) a comparison of the multi-dimensional mapping of the first part of the internal storage contents over time and (2) a comparison of the multi-dimensional mapping of the second part of the internal storage contents over time.

As a result, a configuration change notification may be transmitted by the first internal monitor drone to a shipment storage transceiver in response to identifying the configuration change as part of step **735** when the identified configuration change is based upon the comparison of the multi-dimensional mapping of the first part of the internal storage contents over time. Such a configuration change notification provides a prompted intervention request message from the first internal monitor drone related to the particular configuration change identified.

In a further embodiment of method **700**, steps **715** and **720** may involve scanning for identification symbols when aerially monitoring the internal storage contents of the shipment storage. This may involve scanning, for example, the name of a shipping item printed on the side of the item or the actual dimensions of a shipping item indicated on the item (such as on a ULD loaded within the internal storage area). In more detail, step **715** may aerially monitor the first part of the internal storage contents with the first sensor array by scanning a first identification symbol fixed to a first item within the first part of the internal storage contents using a first scanner part of the first sensor array (e.g., a barcode scanner or image sensor) as the first internal monitor drone transits the first airborne monitoring path within the shipment storage. Likewise, step **720** may aerially monitor the second part of the internal storage contents with the second sensor array by scanning a second identification symbol fixed to a second item within the second part of the internal storage contents using a second scanner part of the first sensor array (e.g., a barcode scanner or image sensor) as the second internal monitor drone transits the second airborne monitoring path within the shipment storage. Thereafter, step **735** may be implemented by automatically identifying the condition of the internal storage contents based upon at least one of the first identification symbol scanned by the first scanner or the second identification symbol scanned by the second scanner. These identification symbols may be barcode symbols that identify shipping information related to their respective item, or may be a sign affixed to the respective item that identifies shipment loading information (e.g., a desired orientation for the item, or other placement information for the item, such as a hazardous material warning label for the item).

Those skilled in the art will appreciate that method **700** as disclosed and explained above in various embodiments may be implemented with an apparatus, such as exemplary internal monitor drones **625a**, **625b**, running an embodiment of airborne monitoring program code **325**, and as a part of a multiple drone-based monitored storage system including the shipment storage, internal docking stations **630a**, **630b**, and internal monitor drones **625a**, **625b**. Such code **325** may be stored on a non-transitory computer-readable medium in each of the drones, such as memory storage **315** disposed within each of internal monitor drones **625a**, **625b**. Thus, when executing code **325**, the OBC **300** (or OMP **310**) of internal monitor drones **625a**, **625b** (in cooperation with other circuitry onboard the drones **625a**, **625b**, such as

elements of their respective sensor arrays **230**) may be operative to perform certain operations or steps from the exemplary methods disclosed above, including method **700** and variations of that method.

Drone-Based Delivery Vehicle Part Inspections

While the above description focuses on embodiments of an applied technical solution that enhances how to unconventionally monitor and intelligently notify others about a condition related to what may be in a delivery vehicle's shipment storage compartment, the following describes various embodiments that deploy an aerial inspection drone paired as an exclusive part of a delivery vehicle. In general, an embodiment of an aerial inspection drone paired to the delivery vehicle may perform airborne inspections of specific parts of the delivery vehicle and transmit messages based upon the airborne inspections to other logistics entities, such as vehicle operators (such as flight crew personnel) and/or logistics personnel assigned to the vehicle that may service the vehicle. This type of airborne extension of the delivery vehicle improves how a delivery vehicle may be self-inspecting using an exclusively paired aerial inspection drone.

In more detail, FIGS. **8A-12** relate to embodiments of a drone-based delivery vehicle inspection system and its operation where a paired aerial inspection drone may be deployed to aurally gather sensor-based inspection information related to targeted inspection points on the delivery vehicle, automatically identify an inspection condition if the inspection point is out of range, and transmit a notification to others about such an inspection condition. FIG. **8A** illustrates an exemplary aircraft **100** as a type delivery vehicle similar to that shown in earlier Figures. In FIG. **8A**, aircraft **100** has operational control section **105** (e.g., a cockpit from which flight personnel can control and fly the aircraft **100**) and a shipment storage **810** used for maintaining items being shipped within aircraft **100** between different locations.

Similar to that shown in FIGS. **1A-1C**, exemplary operational control section **105** includes a vehicle transceiver **135**. As previously explained, such a vehicle transceiver **135** may be implemented as a standalone unit (e.g., a ruggedized radio-based tablet or smartphone used by aircraft crew personnel) or an integrated part of the aircraft's avionics suite. In more detail, an embodiment of exemplary vehicle transceiver **135** may include a display (such as a touch screen display or avionics display unit); a control input interface with buttons, switches, or touch sensitive receptors on the touch screen display; and a radio. The exemplary delivery vehicle transceiver **135** communicates with a paired aerial inspection drone (PID) **825** and other radio-based devices over the radio, receives user/operator input via the control input interface, and generates vehicle related information for presenting to the user/operator on the display. Thus, as explained in more detail below, an embodiment of exemplary delivery vehicle transceiver **135** may be used as a base station type of device that interacts with PID **825** as well as other radio-based devices operated by flight personnel, logistics personnel, and maintenance personnel.

Exemplary shipment storage **810**, as shown in FIG. **8A**, includes a drone storage area **815**, an interior shipment storage area **820**, and an onboard safety system area **822**. Exemplary drone storage area **815** includes an internal docking station **830** that provides secure storage for the PID **825** when PID **825** is not flying. Exemplary docking station **830** may be implemented similar to internal docking station **130** as described above and shown in FIGS. **4A** and **4B**. Thus, similar to docking station **130**, internal docking station

830 also includes a physical docking interface, an electronic charging connection interface, and an electronic data connection interface similar to PDI **415**, ECCI **435**, and EDCI **440**.

An exemplary PID **825** (as shown and explained in more detail below with respect to FIG. **9**) secured within the drone storage area **815** is a linked part of aircraft **100** that travels with the aircraft **100** during a delivery vehicle based shipment operation (e.g., shipping one or more items from a first location to a second location while the items are maintained within a cargo storage area (such as internal shipment storage area **820**)). Exemplary PID **825**, as shown in FIG. **9**, may be implemented with similar component elements as that of internal monitor drone **125** for providing an airborne sensory platform capable of maneuvering and navigating in close proximity to aircraft **100**. PID **825** may generally use a similar drone capture interface (DCI) with which to become secured relative to internal docking station **830** within drone storage area **815**. Additionally, the sensor array deployed on PID **825** typically includes at least one type of image sensor with which to capture images relative to different inspection points on the delivery vehicle **100** targeted for aerial review. As will be explained in more detail below, such an aerial inspection review may be autonomously conducted by the PID **825** or may be controlled with flight commands wirelessly provided to the PID **825** from a wireless base controller or through a wired control tether connection to a base controller on the aircraft **100** (as shown and explained in more detail with reference to FIG. **10**). Furthermore, such an aerial inspection review may be conducted by the PID **825** on inspection points targeted within the delivery vehicle as well as inspection points outside the delivery vehicle.

The interior shipment storage area **820** is generally an accessible storage compartment of aircraft **100** where items being shipped (also generally referred to as cargo) may be loaded, moved, secured, and maintained during flight operations of the aircraft **100**. For example, packaged shipping item **845** is shown in FIG. **8A** secured within aircraft **100** within internal shipment storage area **820**. Packaged shipped item **845** may be moved as cargo within this storage area **820** using different types of cargo handling points (e.g., a roller, a caster, a portion of a roller deck, a roller ball mat, a castor mat, a turntable, a conveyor, and the like) deployed on aircraft **100**. Such exemplary cargo handling points facilitate moving cargo into, within, and out of the storage area **820** so that cargo can safely and more easily moved into, within, and out of the aircraft **100**. For example, package shipping item **845** is shown in FIG. **8A** on a portion of a roller ball mat **835** having rollers **840**. Such rollers **840** may be fixed or articulated to provide a motion-capable surface interface for cargo but later be retracted. The exemplary rollers **840** shown in FIG. **8A** allow for logistics personnel to move item **845** as cargo from outside the aircraft **100** and into a desired location within area **820** where the item **845** may be secured. Securing cargo may be accomplished with a cargo attachment point, such as tie down attachment **852** (e.g., a hole, slot, hook, or loop in the mat **835**) configured to receive a tie down strap **850**. Generally, such a cargo attachment point may be located within the storage area **820** (including ramp accesses) and used as a type of anchor that helps maintain and secure cargo in its desired location. In one embodiment, the cargo attachment point may be configured to receive a cargo netting that may be placed over the item **845** as part of securing the item within storage area **820**. Another embodiment may use an exemplary cargo attachment point in the form of a pin disposed on a support floor (such as

roller mat **835**) that directly contacts and securely holds part of the structure of a ULD as the item **845**. Thus, cargo handling points and cargo attachment points are types of mechanical structure that interface with what is being shipped within storage area **820** and may need periodic inspection to ensure proper operation. However, a typical cargo aircraft (such as aircraft **100**) may have a very large number of cargo handling points and cargo attachment points.

A delivery vehicle's shipment storage (such as storage **810**) may also have one or more designated areas where an enhanced level of inspection may be desired or warranted. An enhanced level of inspection generally is an inspection with more detail or scrutiny, such as when using tighter ranges of tolerance for the applicable acceptable range of sensor data gathered, when spending more time doing the inspection than for other areas, when deploying a greater number of sensor types in order to conduct the inspection, and the like. In general, such designated areas may be associated with particular systems, equipment, or materials that are important from a safety aspect on what is being transported or from a mission critical aspect of the aircraft itself. For example, as shown in FIG. **8A**, exemplary storage **810** includes an onboard safety system area **822** deemed appropriate for an enhanced level inspection of points within that area. In other words, areas for certain types of equipment and/or storage for certain types of materials (e.g., hazardous materials, caustic materials, corrosive materials, mission-critical equipment or systems, and the like) may be considered designated areas in an embodiment and receive an enhanced level of inspection for those inspection points related to such a designated area. Thus, in the illustrated example, PID **825** may spend more time, use special tolerances, or deploy a more robust set of sensors when detecting sensor-based inspection information from an aerial position near fire suppression equipment **855** and fire suppressant storage **860** located in the designated onboard safety system area **822**.

As mentioned above, embodiments of the delivery vehicle have targeted inspection points associated with the delivery vehicle. The targeted inspection points correspond to respective parts of the delivery vehicle to be inspected in an unconventionally advantageous manner. Such targeted inspection points may be different for different delivery vehicles, such as for different models and configurations of a particular cargo aircraft (such as aircraft **100**), and may comprise multiple designated inspection areas inside the aircraft and outside the aircraft. For example, as shown in FIGS. **8A-8G**, exemplary PID **825** conducts inspections from aerial positions proximate different targeted inspection points for aircraft **100**—both inside and outside aircraft **100**.

Targeted inspection points inside aircraft **100** may, for example, include designated inspection areas of an accessible cargo storage area (such as area **820**) as well as cargo handling and attachment points. This may include tie down attachment **852** within storage area **820** as a type of cargo attachment point that would be inspected by PID **825**; roller **840** and roller ball mat **845** as a type of cargo handling point that facilitates movement of cargo (such as item **845**) within the aircraft **100**. Further examples of cargo handling points may include, but are not limited to a caster, a portion of a roller deck, a castor mat, a turntable, and a conveyor.

Targeted inspection points inside the aircraft **100** (i.e., a type of delivery vehicle) may also include other designated inspection areas inside the aircraft, such as the onboard safety system area **822** having onboard safety system equipment (such as fire suppression equipment **855** or fire extin-

guishing equipment) and related storage **860** for related material (such as fire suppression or fire extinguishing material). Further designated inspection areas that may be targeted inspection point within the aircraft **100** may be for storing hazardous materials or other sensitive materials (e.g., areas for temperature sensitive materials that need to be kept within a tight temperature range, areas for moisture sensitive materials, areas for other environmentally sensitive materials) that may have strict regulations on how such materials are to be stored and transported.

Exemplary targeted inspection points may also include designated inspection areas externally exposed on the delivery vehicle. For example, such exterior viewable targeted inspection points may include, but are not limited to, a panel on the aircraft; a rivet that joins structure together; a seam or joint between parts; an engine (such as a jet or propeller driven engine for an aircraft); a flight control surface disposed on a leading or trailing edge of wing, stabilizer, or tail (such as a flap, aileron, tab, spoiler, and the like); a window seal; a closable entry to within the aircraft (such as a door to the interior of the aircraft, a belly or side door to a cargo bay, an access door or hatch to an avionics bay, landing gear doors, and the like); aircraft lighting disposed on the exterior of the aircraft; an antenna that may be conformally mounted or that extends from the body of the aircraft; and landing gear and tires that may be fixed or retractable. Furthermore, some exemplary targeted inspection points may be otherwise exceptionally difficult and time consuming to inspect as they may only be accessible from above the aircraft delivery vehicle such that those points (e.g. aircraft lights, control surfaces, window seals, or other components mounted on top of the body of the aircraft) are not visible from a ground level perspective.

In one embodiment, the exemplary targeted inspection points may include a prioritized subset designated for an enhanced level of sensor-based inspection (such as a subset of targeted inspection points for aircraft **100** for a designated inspection area having an onboard safety system **855**, **860** for the aircraft **100**). Thus, an embodiment with a paired inspection drone conducting aerial inspections of a delivery vehicle (such as aircraft **100**) may use different levels of inspection scrutiny based on whether a particular targeted inspection point is part of the prioritized subset.

For example, FIGS. **8A-8G** generally show an embodiment of a drone-based system for inspecting an aircraft (as an exemplary delivery vehicle) involving an exclusively paired inspection drone (PID **825**) and targeted inspection points both within the aircraft **100** and externally exposed on the aircraft **100**. Referring back to FIG. **8A**, PID **825** (as paired and exclusively assigned to aircraft **100** as a dedicated inspection tool for that delivery vehicle and used only for aircraft **100**) is shown in a secure position on docking station **830**. Similar to internal docking station **130**, docking station **830** in this embodiment uses a physical docking interface that facilitates maintaining a PID **825** in a secure position on the station **830**, an electronic charging connection interface that can provide power to PID **825**, and an electronic data connection interface that can provide a wired bi-direction data link with PID **825**. Docking station **830** may be connected to vehicle transceiver **135**, which may generate an activation command to initiate an aerial inspection of targeted inspection points on aircraft **100**. In another embodiment, the activation command may be provided by docking station **830** to PID **825** in response to a wireless signal from another device (e.g., a signal received over a communication interface on docking station **830** similar to communication interface **430**). Further still, another

embodiment may have the activation command provided wirelessly directly to the PID 825 rather than through the docking station 830.

Upon receiving an activation command, PID 825 transitions from at least a low power state to an active power state as part of a targeted inspection operation of the delivery vehicle. In the active power state, PID 825 causes its drone capture interface to automatically uncouple PID 825 from the physical docking interface of internal docking station 830. This may be accomplished with articulating or actuated components on the PID 825, the docking station 830, or both. The PID 825 accesses its memory to identify the targeted inspection points from an onboard inspection profile record related to the aircraft 100. In particular, the targeted inspection points correspond to respective parts of the aircraft 100—both inside and outside the aircraft 100.

In FIG. 8B, exemplary PID 825 has used its lifting engines to take off from the docking station 830, moved to an initial airborne position within the drone storage area 815, and then moved to an aerial position proximate one of the targeted inspection points, such as the roller mat 835. At this aerial position above the roller mat 835, PID 825 uses an onboard sensor array to detect sensor-based inspection information relative to this targeted inspection point. In more detail, PID 825 can automatically identify an unacceptably out of range inspection condition about the roller mat 835 (a targeted inspection point for aircraft 100) based upon the sensor-based inspection information detected from the aerial position above the roller mat 835. The out of range inspection condition is specific to the particular targeted inspection point and identified relative to an acceptable range for that inspection point. An inspection profile record maintained on the PID 825 may identify each targeted inspection point, indicate whether the inspection point is prioritized for an enhanced level of inspection, indicate what sensors may be used to perform the inspection of that point, and an associated acceptable range for sensor-based inspection information gathered relative to that point. For example, in FIG. 8B, if PID 825 moves to an airborne position above roller 840 from an initial position above docking station 830, PID 825 can automatically identify an inspection condition related to roller 840 (as one of the aircraft's targeted inspection points) based on sensor-based inspection information detected relative to roller 840. Such sensor-based inspection information gathered may be imagery of the roller 840 that may be processed to identify damage or encumbrances and/or depth mapping information that may be processed to identify whether roller 840 has been damaged, shifted from an anticipated position relative to other nearby reference objects (e.g., other rollers), or simply no longer where it anticipated to be located. If roller 840 does not appear to be damaged and is present, PID 825 may move to another targeted inspection point in the aircraft 100. However, if PID 825 identifies an inspection condition that roller 840 is outside the acceptable range for that point (e.g., roller is not located, roller appears encumbered, roller appear damaged or shifted relative to its anticipated position), the PID 825 can transmit an inspection notification message to a delivery vehicle receiver, such as vehicle transceiver 135, so that the inspection condition may be acted upon. Similar types of aerial inspections may be conducted within aircraft 100 for other targeted inspection points within the aircraft, such as tie down attachment 852, fire suppression equipment 855, or fire suppressant storage 860.

As noted above, some of the targeted inspection points for a delivery vehicle may be externally exposed to the vehicle. As shown in FIG. 8C, a closeable entry or access hatch 865

for aircraft 100 may be opened (or be remotely actuated to open) to allow PID 825 to move to airborne positions proximate to targeted inspection points accessible and viewable from outside aircraft 100. In the example shown in FIG. 8D, once out the closable entry or access hatch 865 (whether a cargo ramp opening, belly storage hold doors, or a dedicated drone hatch), PID 825 may move to an aerial position near wing 875 and proximate the air intake fan 885 of jet engine 880. From this aerial position, PID 825 may detect sensor-based inspection information to automatically identify an out of range inspection condition about the air intake fan 885 as a targeted inspection point (and transmit a related inspection notification message to vehicle transceiver 135 if such a condition is automatically identified).

In like manner, as shown in FIG. 8E, PID 825 may move to an aerial position above wing 875 and proximate the control surface aileron 890. From this further aerial position, PID 825 may detect sensor-based inspection information about the control surface 890 (e.g., its rivets, seams, joints, actuating structure, range of motion, etc.) to automatically identify an out of range inspection condition about the control surface 890 as a targeted inspection point (and transmit a related inspection notification message to vehicle transceiver 135 if such a condition is automatically identified). In an embodiment where range of motion action for control surface 890 is to be inspected, PID 825 may directly or indirectly communicate with vehicle transceiver 135 to request actuated movement of the control surface being inspected as part of the inspection and while PID 825 is in the aerial position above wing 875 and proximate the control surface aileron 890. The vehicle transceiver 135 may then request human actuation of aircraft controls to responsively cause the control surface to move (e.g., via messaging to flight personnel, display of a message on a transceiver display, or the like), or may responsively interface with the aircraft's avionics system to electronically cause the control surface to move without human intervention.

PID 825 may also inspect targeted inspection points below aircraft 100, such as landing gear 870a, 870b shown in FIGS. 8C-8G. For example, as shown in FIG. 8F, PID 825 may move to an aerial position below aircraft 100 and proximate rear landing gear 870b. From this position, PID 825 may use its sensor array to detect sensor-based inspection information about the rear landing gear 870b (e.g., its tires, suspension, actuating structure, landing gear doors, etc.) to automatically identify an out of range inspection condition about the landing gear 870b as a targeted inspection point. And if there is an out of range inspection condition identified, PID 825 may transmit a related inspection notification message to vehicle transceiver 135. From there, PID 825 may re-enter aircraft 100 through entry hatch 865 and may either continue moving to other positions near further targeted inspection points or return to land on docking station 830 within drone storage area 815.

As part of automatically identifying inspection conditions, exemplary PID 825 may be implemented with connected electronic and sensory components as shown in FIG. 9. Referring now to FIG. 9, exemplary PID 825 includes similar components shown and explained with reference to FIGS. 2 and 3 for exemplary internal monitor drone 125. Beyond those similar components, exemplary PID 825 includes an onboard controller (OBC) 900, which is similar to OBC 300. Like OBC 300, OBC 900 uses one or more processors at its core along with memory 315 (e.g., volatile, non-volatile, or both depending on the configuration of the OBC 900). And like OBC 300, OBC 900 interfaces or connects with motor control circuitry (such as electronic

speed controllers **360a**, **360b**), guidance related circuitry (such as global positioning system (GPS) chip **350**, inertial measurement unit (IMU) **355**, and proximity sensors **215a**, **215b**), dedicated docking circuitry (such as drone capture interface **370** and the electronic docking connection **235**), communication related circuitry (such as communication interface **365**), payload electronics (such as the onboard sensor array **230**), and an onboard power source that provides power for all of the onboard active electronics (such as onboard battery **385**). An embodiment of OBC **900** may interface or connect with such circuitry by deploying various onboard peripherals (e.g., timer circuitry, USB, USART, general-purpose I/O pins, IR interface circuitry, DMA circuitry, buffers, registers, and the like) that implement interfaces (e.g., a plug type or connectorized interface) to the different components disposed within PID **825** (e.g., mounted on different parts of airframe **200**).

As part of the exemplary PID **825**, the OBC **900** generally controls autonomous flying and docking of the drone **825** as well as data gathering tasks related to different targeted inspection points using sensory array **230**. In some embodiments, OBC **900** may be implemented with a single processor, multi-core processor, or multiple processors and have different programs concurrently running to manage and control the different autonomous flying/docking and sensor-based inspection information detecting tasks. For example, in the embodiment shown in FIG. 9, flight/docking control and inspection data gathering/assessment operations may be divided between an onboard flight controller (OFC) **305** and an onboard inspection processor (OIP) **910**, respectively. In such an embodiment, OFC **305** and OIP **910** may have access to the same memory, such as memory storage **315** or, alternatively, OBC **900** may be implemented with separate dedicated memories that are accessible by each of OFC **305** and OIP **910**. Those skilled in the art will appreciate that memory accessible by OFC **305** in an embodiment may have different accessibility and size requirements compared to memory accessible by OIP **910** given the different memory demands for the different responsibilities. For example, memory accessible by OIP **910** may be significantly large given the anticipated size of sensor-based inspection information gathered through sensory array **230** (e.g., imagery, video, depth mappings, etc.) when compared to the size of memory needed for tasks performed by OFC **305**. As will be explained further, each of OFC **305** and OIP **910** may include peripheral interface circuitry that couples the processing element(s) to the different onboard peripheral circuitry, such as the GPS **350**, inertial measurement unit **355**, the communication interface **365**, the electronic speed controllers **360a**, **360b** that control each lifting engine **210a**, **210b**, and the like.

In more detail, exemplary OIP **910** may be implemented with a low power microprocessor or processor-based microcontroller that is tasked/programmed to gather or receive sensor-based inspection information from the sensory array **230** and automatically identify an out of range inspection condition about a targeted inspection point based upon the sensor-based inspection information detected from an aerial position proximate the targeted inspection point. The out of range inspection condition generally indicates the detected sensor-based inspection information is outside an acceptable range for safe or desired operation of the delivery vehicle relative to that particular targeted inspection point. As such, OIP **910** may be deployed in an embodiment of PID **825** as a task-dedicated processor that executes operational and application program code (e.g., operating system **320**, delivery vehicle inspection program **925**) and other program

modules maintained in memory **315** useful in aurally inspecting different targeted inspection points within and on its paired aircraft **100** in accordance with embodiments of the invention.

More specifically, operating system **320** may be loaded by OIP **910** upon power up and provide basic functions, such as program task scheduling, executing of application program code (such as exemplary inspection program **925**), and controlling lower level circuitry (e.g., registers, buffers, buses, counters, timers, and the like) on OIP **310** that interface with other peripheral circuitry onboard PID **825** (such as the sensory array **230**, proximity sensors **215a**, **215b**, the electronic docking connection **235**, GPS **350**, IMU **355**, ESC **360a**, **360b**, communication interface **365**, and DCI **370**).

Once operating system **320** is loaded, inspection program code **925** may be loaded and execute as part of implementing an aerial drone-based method for inspecting a delivery vehicle, such as aircraft **100**. Exemplary inspection program code **925** is a set of executable instructions in the form of one or more machine-readable, non-transient program code modules or applications. The program code module(s) may be loaded and executed by OBC **900** (or by OIP **910** when flight control is dedicated to a separate OFC **305**) to adapt the PID **825** into an unconventionally configured aerial inspection apparatus exclusively paired to the aircraft as a linked part of the aircraft that travels with the aircraft during shipment operations providing quick and assured inspection functionality for the aircraft wherever the aircraft is located. This specially configured OBC **900** of PID **825**, as described in more detail herein as a part of an embodiment, implements operative process steps and provides functionality that is unconventional, especially when the overall inspection process steps performed by the PID **825** are considered collectively as a whole. Such a specially adapted and configured paired inspection drone **825** helps, as a part of an embodiment, to improve the speed and robust nature of inspection operations for parts of the related delivery vehicle—both for designated inspection areas within the delivery vehicle, outside the delivery vehicle, and areas aurally accessible from above the delivery vehicle but that are not visible from a ground level perspective relative to the delivery vehicle.

During operation, the OBC **900** (or at least the OIP **910**) may access and/or generate data maintained within memory **315**, such as sensory data **930**, flight profile data **935**, messaging data **940**, and an inspection profile record **945**. In general, sensory data **930** comprises sensor-based inspection information gathered by different sensors (described above) deployed as part of the sensory array **230** and may take different forms depending on the type of sensor used and the type of information gathered (e.g., numeric measurements of temperature, images, video, depth sensing measurements, etc.). For example, the different sensors that may be used on the sensory array **230** of PID **825** may include an image sensor (e.g., a visual imaging sensor, an infrared (IR) imaging sensor, and/or a thermal imaging sensor), a temperature sensor, and/or a depth sensor (e.g., a LIIDAR sensor and/or an ultrasonic transducer). The sensor-based inspection information detected making up sensory data **930** may be generated by one of these sensors on sensor array **230** or by multiple sensors on the sensor array **230** depending on the type of inspection desired for a particular inspection point.

Flight profile data **935** comprises information that defines how the PID **825** is to be flying. This data **935** may include navigational data on an airborne inspection path for the PID

45

825 to transit that includes an aerial position proximate each of the respective targeted inspection points for this aircraft **100**, as well as flight control setting information to use when generating flight control input for the ESCs **360a**, **360b** when moving relative to these aerial positions.

Messaging data **940** is generally a type of data used when the paired inspection drone generates and/or transmits a notification or other type of message related to the condition of one or more of the targeted inspection points on aircraft **100**. Such messaging data **940** may include information on messages received or generated onboard to be sent outside PID **825**.

Inspection profile record **945** maintains delivery vehicle dependent information accessed and used by inspection program **925**. Inspection profile record **945** may be initially loaded into memory **315** or later updated via a download received by PID **825** and stored into memory **315** so as to provide inspection-related information specific to the particular delivery vehicle, such as aircraft **100**. Inspection profile record **945** at least includes data indicating the different targeted inspection points corresponding to parts of the delivery vehicle to be inspected and an acceptable range of sensor-based inspection information for each of the targeted inspection points for operation of the delivery vehicle. Using the information in the inspection profile record **945** and the sensor-based inspection information gathered, the OIP **910** may automatically identify an unacceptable condition related to the one of the targeted inspection points (i.e., an out of range inspection condition), such as a missing condition, a loose condition, a damaged condition, a cracked condition, a worn condition, a leaking condition, and a thermal related condition.

In one embodiment, the inspection profile record **945** may also include prior sensor-based inspection information detected for one or more of the targeted inspection points. The PID **825** may store such prior detected information as a benchmark or local reference condition. In this way, the OIP **910** may use relative measurements (in addition to or instead of absolute measurements) when comparing the sensor-based inspection information for one of the targeted inspection points to prior sensor-based inspection information detected for the same targeted inspection points as part of automatically identifying an inspection condition for that targeted inspection point.

In another embodiment, the targeted inspection points defined within the inspection profile record **945** may include a prioritized subset of the targeted inspection points designated for an enhanced level of sensor-based inspection. Such a subset may be designated in the inspection profile record as, for example, including parts of the delivery vehicle serviced within a threshold period of time and/or including parts of the delivery vehicle exceeding an age threshold. As noted above, the enhanced level of sensor-based inspection may involve more detail or scrutiny, such as using tighter ranges of tolerance for the applicable acceptable range of sensor-based inspection information gathered, spending more time doing the inspection compared to that for other areas, deploying a greater number of sensor types in order to conduct the inspection, and the like.

After PID **825** conducts an aerial inspection of relevant targeted inspection points of aircraft **100**, the inspection profile record **945** maintained in the memory **315** may be updated by OIP **910** based upon the sensor-based inspection information gathered. As a result, the updated inspection profile record **945** may reflect an electronic catalog of aerial inspections relative to each of the targeted inspection points on the specific delivery vehicle. Such a catalog may be

46

referenced and used by OIP **910** to identify a condition trend for particular targeted inspection points that may not yet outside the acceptable range, but may be increasingly approaching the out of range or unacceptable inspection condition to warrant issuing a relevant inspection notification message. Furthermore, the updated inspection profile record **945** (which may include trend information on particular targeted inspection points) may be transmitted by OIP **910** to other devices outside of the PID **825**, such as a vehicle transceiver **135** or maintenance related receivers operated by maintenance personnel responsible for the delivery vehicle—i.e., aircraft **100**.

Those skilled in the art will appreciate that the above identification of particular inspection program code **925** and related data **930-945** used by such code **925** are not exhaustive and that embodiments may include further executable program code or modules as well as other data relevant to operations of a specially programmed processing-based paired inspection drone **825**. Furthermore, those skilled in the art will appreciate that not all data elements illustrated in FIG. **9** as being within memory **315** must appear in memory **315** at the same time.

As discussed above relative to FIG. **3**, OFC **305** (as part of OBC **900**) is a flight controller capable of autonomous flying of drone **825**. In other words, OFC **305** (as part of OBC **900**) may generate the flight control input autonomously to enable the PID **825** to self-control aerial movements of the PID **825** from the secured position on the internal docking station **830** to respective aerial positions proximate each of the targeted inspection points identified in inspection profile record **945**. Such autonomous flying may involve automatic take off, transiting an airborne monitoring path (e.g., via waypoint flying), and data communication or telemetry while airborne and while secured to the docking station **830**. In more detail, an embodiment of OFC **305** (as part of OBC **900**) includes peripheral interface circuitry (not shown in FIG. **9**, but those skilled in the art will appreciate that it may be implemented with buffers, registers, buses, and other communication and command pathways) for interacting with guidance related circuitry, motor control circuitry, dedicated docking circuitry, and communication circuitry onboard the PID **825** as part of controlling movement and flight stability of drone **825** while navigating and avoiding collisions during movement.

Like that of OBC **300**, OBC **900** (as well as OFC **305** and/or OIP **910**) may be implemented with a low power embedded processor as part of a single-board computer having a system-on-chip (SoC) device operating at its core. In such an embodiment, the SoC device may include different types of memory (e.g., a removable memory card slot, such as a Secure Digital (SD) card slot, as removable memory; flash memory operating as onboard non-volatile memory storage; and RAM memory operating as onboard volatile memory); an operating system (such as Linux) stored on the non-volatile memory storage and running in volatile RAM memory; and peripherals that may implement any of the GPS **350**, IMU **355**, ESC **360a**, **360b**, communication interface **365**, DCI **370**, wired data interface **375** and charging interface **380**.

In some embodiments, the PID **825** may be coupled to a base controller on the delivery vehicle via a type of control tether. For example, FIG. **10** illustrates an embodiment where exemplary PID **825** is coupled to an exemplary base controller **1000** with an exemplary control tether **1005** in accordance with an embodiment of the invention. In particular, the base controller **1000** shown in FIG. **10** fixed to aircraft **100** and providing at least data (e.g., flight com-

mands) and, in some embodiments, power to the PID **825** through the control tether **1005** (e.g., an electric and/or fiber optic conduit between PID **825** and base controller **1000**). As such, the PID **825** shown in the embodiment of FIG. **10** may also include a control receiver coupled to the OBC **900** of PID **825** (or implemented as part of OFC **305**) where the control receiver has an input connected to tether **1005**. Such a control receiver (e.g., a receiver interface for OFC **305** operating as the PID's control receiver) receives the flight command from the base controller **1000**, and passes the received flight command to the onboard controller (e.g., to the OFC **305**), which then generates the appropriate flight control input for the lifting engines **210a**, **210b** based upon the received flight command. With such a control tether **1005**, PID **825** is more limited in its flight range, and has its flight to the different aerial positions proximate targeted inspection points controlled in a non-autonomous way via the control tether **1005** and base controller **1000**.

In a further embodiment involving flight operations of PID **825** controlled by base controller **1000**, the OFC **305** of PID **825** may be configured and operative to self-generate landing control input for the lifting engines **210a**, **210b** (via signals provided to ESC **360a**, **360b**) if the control tether **1005** breaks. In such a situation, the landing control input provided by OFC **305** helps to safely return PID **825** to the internal docking station **830** and secure the DCI **370** of PID **825** to the physical docking interface of the internal docking station **830**.

From a process perspective of inspecting a delivery vehicle, an embodiment of a drone-based method for inspecting the delivery vehicle, such as aircraft **100**, involves operations of an exclusively paired inspection drone, such as PID **825**. FIG. **11** is a flow diagram illustrating such an exemplary drone-based method for inspecting a delivery vehicle in accordance with an embodiment of the invention. Referring now to FIG. **11**, method **1100** begins at step **1105** with the paired inspection done (PID) transitioning from at least a low power state to an active power state as part of a targeted inspection operation of the delivery vehicle. The PID may transition from an unpowered state or, alternatively, transition from a low power state such as a sleep mode that conserves power and does not have the full complement of onboard circuitry powered up for normal airborne operations. As explained above with respect to exemplary PID **825**, the PID is exclusively assigned to the delivery vehicle (e.g., an aircraft (such as aircraft **100**), a delivery van, a truck coupled with a cargo hauling trailer, or a marine vessel) and travels with the delivery vehicle during a delivery vehicle based shipment operation. Such an operation may be one where the delivery vehicle ships one or more items from a first location to a second location while those items are maintained within a cargo storage area of the delivery vehicle. Thus, the PID is an extension of the delivery vehicle given this linked relationship and physical coupling between the PID and its assigned delivery vehicle.

At step **1110**, method **1100** continues by automatically uncoupling the PID from a secured position on an internal docking station fixed within the delivery vehicle (e.g., within an accessible cargo storage compartment of an aircraft) once the paired inspection drone transitions to the active power state. For example, as shown in FIG. **8A**, PID **825** may be automatically uncoupled from internal docking station **830**. This may involve actuating a drone capture interface (and articulating landing gear) on PID **825** to release PID **825** from stationary structure on docking station **830**, actuating a physical docking interface on docking station **830** to release PID **825** using movable securing

clamps on the docking station **830**, or actuating movable structure on both the PID **825** and the docking station **830** to release PID **825** from its secured position on docking station **830**. In a further embodiment, step **1110** may also involve opening at least one access door (not shown) to the accessible storage compartment where the access door may separate a drone storage area from the accessible storage compartment. In still another embodiment, step **1110** may also involve opening a closable entry door or hatch (such as hatch **865**) that allows the PID to move outside of the delivery vehicle to conduct aerial inspections of certain targeted inspection points for the delivery vehicle.

At step **1115**, method **1100** proceeds with an onboard processor on the PID identifying targeted inspection points corresponding to respective parts of the delivery vehicle. This step may involve downloading an inspection profile record for the delivery vehicle into a memory of the PID, where the inspection profile record (such as record **945** as explained with respect to FIG. **9**) identifies designated inspection areas specific to the delivery vehicle as the targeted inspection points. Alternatively, this step may have the PID simply accessing an existing inspection profile record in the PID's memory. As explained above, such targeted inspection points may be designated inspection areas specific to inside of the vehicle (e.g., an accessible cargo storage area within an aircraft, a cargo attachment point, a cargo handling point, an onboard safety system area for equipment and material used for fire extinguishing and suppression, an onboard areas for hazardous material storage, and the like). Further, such targeted inspection points may be designated areas externally exposed on the delivery vehicle (e.g., a designated inspection area aurally accessible from above the delivery vehicle but that is not visible from a ground level perspective relative to the delivery vehicle, one or more aircraft components of an aircraft type of delivery vehicle (such as a panel, a rivet, a seam, an engine, a flight control surface, a window seal, a closable entry to within the aircraft, aircraft lighting, an antenna, landing gear, and tires), and the like).

In a further embodiment of method **1100**, one or more of the identified targeted inspection points for the delivery vehicle may be identified as a prioritized subset of the targeted inspection points. As explained above, such a prioritized subset is automatically designated for an enhanced level of sensor-based inspection as part of detecting the sensor-based inspection information for the prioritized group of the targeted inspection points. For example, an exemplary prioritized subset of the delivery vehicle's targeted inspection points may include certain parts of the delivery vehicle not serviced within a threshold period of time or certain parts of the delivery vehicle exceeding an age threshold. Thus, if landing gear **870b** as shown in FIG. **8F** has not been serviced within a designated maintenance period of time, the inspection conducted by PID **825** as shown in FIG. **8F** may be an enhanced level of inspection because landing gear **870b** is identified as within such a prioritized subset of targeted inspection points for aircraft **100**. An enhanced level of inspection for a targeted inspection point identified as one of the prioritized subset may occur over an enhanced inspection period of time (compared to the time taken by the PID to detect sensor-based inspection information for those not in the prioritized group of the targeted inspection points), may involve multiple sensors on the PID (for a more robust type of inspection—imagery, temperature, IR, etc.).

At step **1120**, method **1100** proceeds with aurally moving the PID from the secured position on the internal docking

station fixed within the delivery vehicle to an aerial position proximate one of the targeted inspection points. This may be a position within the delivery vehicle (such as that shown in FIG. 8B proximate roller **840** inside aircraft **100**) or a position outside the delivery vehicle (such as that shown in FIG. 8D proximate air intake fan **885** of engine **880** outside of aircraft **100**). If the position is outside the delivery vehicle, step **1120** may involve causing a closeable entry access hatch, door, or panel to open so that the PID may move from inside the delivery vehicle's docking station to the aerial position proximate one of the targeted inspection points outside the delivery vehicle.

At step **1125**, method **1100** has the PID detecting and gathering sensor-based inspection information related to the targeted inspection point. Specifically, this involves having at least one sensor on the PID detecting the sensor-based inspection information once the PID has aerially moved to the aerial position proximate one of the targeted inspection points. The sensor(s) used to detect such sensor-based inspection information may be identified by information in the PID's inspection profile record (e.g., inspection profile record **945** of exemplary PID **825** shown in FIG. 9). For example, the PID's sensor array may include an image sensor (e.g., a visual imaging sensor, an infrared (IR) imaging sensor, and a thermal imaging sensor) used to capture one or more images relative to a targeted inspection point; a temperature sensor used to measure a temperature relative to a targeted inspection point; or a depth sensor (e.g., a LIDAR sensor, a radar sensor, an ultrasonic transducer) used to surface map a targeted inspection point.

At step **1130**, method **1100** has the onboard processor of the PID (e.g., OIP **910**) compare the detected sensor-based inspection information gathered at step **1125** to information (e.g., reference parameters) maintained as part of the PID's inspection profile record. Such a comparison is part of automatically finding differences between the anticipated condition of the targeted inspection point and the actual condition of the targeted inspection point and quantifying those differences. In one embodiment, the reference information or parameters may be prior sensor-based inspection information for this targeted inspection point. In another embodiment, the reference information or parameters may be measurement or sensor based ranges for the targeted inspection point that corresponds with acceptable operation of that part of the delivery vehicle. In a further embodiment, such reference information or parameters may include both prior sensor-based inspection information for this targeted inspection point and sensor data ranges that may be used in the comparison. In other words, the comparison at step **1130** may involve a more simplistic comparison of sensor information detected to a limit or range, but may also involve multiple comparisons of different types of detected sensor information to various types of reference information.

At step **1135**, method **1100** automatically identifies an inspection condition related to the targeted inspection point based upon the results of the comparison in step **1130**. In other words, the processing of the currently gathered sensor-based inspection information for this targeted inspection point may yield a result that the targeted inspection point is now outside an acceptable range for operation of the delivery vehicle. In more detail, this may be due to the comparison indicating the current state of the targeted inspection point is different enough from prior sensor-based inspection information gathered on the same point so that the result indicates an inspection condition for the point. Such an inspection condition may indicate the targeted inspection point is in an unacceptable condition for proper operation of

the inspection point itself and/or proper operation of the delivery vehicle. For example, the unacceptable condition related to the targeted inspection point may be a missing condition, a loose condition, a damaged condition, a cracked condition, a worn condition, a leaking condition, and a thermal related condition. Thus, if step **1135** fails to automatically identify an inspection condition for the targeted inspection point, step **1135** proceeds directly to step **1155**. However, if step **1135** does automatically identify an inspection condition based upon the sensor-based inspection information detected (e.g., the comparison of such sensor-based inspection information to reference information for the targeted inspection point), step **1135** proceeds to step **1140**.

At step **1140**, the PID responsively transmits an inspection notification message to a delivery vehicle receiver disposed on the delivery vehicle (such as vehicle transceiver **135**). The inspection notification message is a type of feedback for a paired inspection drone-based system associated with the delivery vehicle (or including the delivery vehicle). As such, the delivery vehicle receiver is able to alert personnel associated with the delivery vehicle. In more detail, an embodiment may have step **1140** also (or alternatively) transmit the inspection notification message to a mobile interactive transceiver operated by vehicle crew personnel for the delivery vehicle to notify the vehicle crew personnel that operate the delivery vehicle (e.g., a flight engineer that uses a ruggedized tablet as a type of mobile interactive transceiver and can view the inspection notification message as well as relevant sensor-based inspection information about the related targeted inspection point). Likewise, an embodiment may have step **1140** also (or alternatively) transmit the inspection notification message to a maintenance receiver operated by maintenance personnel for the delivery vehicle to notify the maintenance personnel that service the delivery vehicle (e.g., an aircraft mechanic that uses a ruggedized tablet as a type of maintenance receiver and can view the inspection notification message as well as relevant sensor-based inspection information about the related targeted inspection point).

At step **1145**, an embodiment of method **1100** may have the PID receive a flight command in response to the transmitted inspection notification message. Such a flight command may be received so as to effectively redirect aerial movement of the PID from moving to another of the targeted inspection points and, instead, head back to the prior targeted inspection point for re-inspection of that targeted inspection point. Such a flight command may be sent to the PID from, for example, a delivery vehicle transceiver, a mobile interactive transceiver, or a maintenance receiver—i.e., any of those radio-based devices that received the transmitted inspection notification message. Thus, if the PID did not receive a flight command in step **1145**, method **1100** proceeds directly to step **1155**. Otherwise, step **1145** continued to step **1150** where the PID prepares to re-inspect the targeted inspection point. In other words, at step **1150**, the PID has received a flight command and the PID re-assesses the reference information about the targeted inspection point in order to prepare to re-inspect the targeted inspection point. In this step, re-assessing the reference information may have the PID using further information from the inspection profile record and/or information provided in or with the flight command relevant to an enhanced level of inspection so that the PID can proceed back to step **1125** from step **1150** to conduct the re-inspection. Such an enhanced level may gather further detailed sensor-based inspection information that than performed previously, such as more images, more views or gathering images from

51

different perspectives relative to the targeted inspection point. Thus, method 1100 continues back to step 1125 from step 1150 for the re-inspection of the targeted inspection point.

However, if no flight command was received in step 1145, method 1100 continued at step 1155 to determine if the PID is at the end of an inspection associated with each of the targeted inspection points for the delivery vehicle. If not, then step 1155 proceeds to step 1160 where the PID moves to the next aerial position proximate another of the targeted inspection points and then continues back to step 1125. Otherwise, the PID is at the end of the inspection and method 1100 continued from step 1155 to step 1165.

At step 1165, method 1100 may proceed with the onboard processor of the PID updating the inspection profile record stored in a memory of the PID based upon the sensor-based inspection information provided by the sensor to the onboard processor (i.e., the sensor-based inspection information detected at step 1125). In a more detailed embodiment, the updated inspection profile record may reflect an electronic catalog of aerial inspections relative to each of the targeted inspection points on the delivery vehicle. This type of catalog may, thus, provide a part-by-part inspection history with which to identify trends and pre-failure conditions as types of inspection conditions to automatically identify as part of step 1135. In some embodiments, this update step may be performed as part of another embodiment of method 1100 after the inspections for all of the delivery vehicle's targeted inspection points have been conducted. However, in other embodiment, this update step may be implemented incrementally after the sensor-based inspection information is detected for anything less than all of the delivery vehicle's targeted inspection points. For example, the PID may update the inspection profile record in its memory based upon the sensor-based inspection information gathered after inspecting different subsets of the targeted inspection points or after inspecting each of the targeted inspection points for the delivery vehicle.

At step 1170, method 1100 may proceed with the PID transmitting the updated inspection profile record to a second radio-based receiver, such as a maintenance receiver separate from the delivery vehicle, to the delivery vehicle receiver, and/or to a mobile interactive transceiver operated by vehicle crew personnel for the delivery vehicle. Similar to that described above related to step 1165, in some embodiments, step 1170 may be performed as part of a further embodiment of method 1100 after all inspections for the delivery vehicle's targeted inspection points have been conducted. However, in other embodiment, this update step may be implemented incrementally after the sensor-based inspection information is detected relative to each of the delivery vehicle's targeted inspection points.

At step 1175, method 1100 has the PID returning to the internal docking station to land and be secured relative to the docking station, such as when PID 825 lands on internal docking station 830 and PID 825 transitions to a secured position on docking station 830. In a further embodiment, the PID may return to the internal docking station prior to the end of the delivery vehicle's inspection—e.g., while awaiting a flight command from another radio-based device used by personnel involved with the delivery vehicle, such as flight personnel or maintenance personnel.

FIG. 12 is a diagram of another embodiment that more explicitly shows additional radio-based devices that may interact with PID 825 as part of a more detailed drone-based system for inspecting aircraft 100 and that may implement embodiments of method 1100. Referring now to FIG. 12,

52

exemplary aircraft 100 is shown as a type of delivery vehicle for transporting items (e.g., packaged shipping item 845) as part of a shipment operation. Similar to that shown in FIG. 8B, FIG. 12 shows exemplary PID 825 in an aerial position proximate a targeted inspection point (e.g., roller 840) within a cargo storage area 820 of aircraft 100. Exemplary PID 825, as described above, may transmit messages (e.g., an inspection notification message) to and receive messages/commands from a variety of radio-based devices, such as delivery vehicle transceiver 135 and radio-based transceivers 1200, 1205, and 1210.

As noted above, delivery vehicle transceiver 135 is a radio-based device that may be implemented as a standalone unit (e.g., a ruggedized radio-based tablet or smartphone used by aircraft crew personnel) or an integrated part of the aircraft's avionics suite disposed within the aircraft's operation control section 105 (e.g., a cockpit compartment from which flight personnel can control and fly the aircraft 100). In more detail, an embodiment of the vehicle transceiver 135 may be fixed within operation control section 105 and have at least a display, a control input interface, and a radio. As such, the delivery vehicle transceiver 135 may generate vehicle related information for presenting on the display (such as information related to any received inspection notification messages on a particular targeted inspection point), receive user input via the control input interface (such as a selective follow-up action (e.g., re-inspection at an enhanced level) to take relative to a targeted inspection point), and communicate with PID 825 over the radio (or communicate with any of radio-based transceivers 1200, 1205, and 1210 used by flight personnel responsible for operating the aircraft 100, maintenance personnel, or logistics personnel).

As shown in FIG. 12, radio-based transceivers 1200, 1205, and 1210 are exemplary types of mobile interactive transceivers that may communicate with at least the delivery vehicle transceiver 135 or each other. For example, radio-based transceiver 1200 is shown as an exemplary mobile interactive transceiver associated with and operated by an aircraft operator (e.g., pilot, co-pilot, flight engineer, cargo specialist, and the like) in compartment 105 that is responsible for controlling the aircraft 100. Exemplary radio-based transceiver 1200 may be implemented as a ruggedized radio-based tablet or smartphone used by aircraft crew personnel and carried with them while performing duties within aircraft 100.

Radio-based transceiver 1205 is shown as an exemplary maintenance transceiver separate from the aircraft 100 and the delivery vehicle transceiver 135 onboard aircraft 100. Radio-based transceiver 1205, as a maintenance transceiver, is operated by maintenance personnel (e.g., a mechanic) associated with servicing the aircraft 100. In some embodiments, delivery vehicle transceiver 135 (or flight personnel radio-based mobile interactive transceiver 1200) may forward information related to the inspection notification message to the maintenance transceiver 1205. This may occur automatically when the inspection notification message meets an automatically identifiable criteria (e.g., a relevant targeted inspection point associated with the inspection notification message is not found or is demonstrably damaged as indicated by the identified inspection condition). However, in other embodiments, the forwarding of information to the maintenance transceiver 1205 may occur based upon user input provided to the delivery vehicle transceiver 135 (or transceiver 1200), such as when flight personnel reviews the inspection notification message from an initial aerial inspection by PID 825 and provides user

input to cause transceiver **135** (or transceiver **1200**) to forward such information to maintenance transceiver **1205** as a type of maintenance request specific to the targeted inspection point at issue in the inspection notification message. Further still, other embodiments may forward information related to an inspection notification message after a re-inspection of the targeted inspection point of interest is performed. This may also occur based upon user input received by the delivery vehicle transceiver **135** (or transceiver **1200**) or automatically based upon information related to the re-inspection. For example, delivery vehicle transceiver **135** (or transceiver **1200**) may automatically forward a re-inspection related notification message to maintenance transceiver **1205** after flight personnel reviews another inspection notification message from a re-inspection performed by PID **825**.

In further embodiments, the PID **825** may directly transmit the relevant inspection notification message to the maintenance transceiver and avoid the need to use the delivery vehicle transceiver **135** (or transceiver **1200**) as an intermediary component in such an enhanced drone-based inspection system for aircraft **100**.

Those skilled in the art will appreciate that the advantageous and unconventional integration of a maintenance transceiver as part of a paired inspection drone-based system for inspecting a delivery vehicle, such as aircraft **100**, yields an improved and enhanced inspection system that reduces the inspection and related maintenance time it takes to keep the delivery vehicle operating as part of logistics operations.

Likewise, exemplary radio-based transceiver **1210** may be implemented as a ruggedized radio-based tablet or smartphone used by logistics personnel responsible for loading and unloading shipping items (such as item **845**) within aircraft **100**. Radio-based transceiver **1210** is shown as another mobile interactive logistics transceiver separate from the aircraft **100** and the delivery vehicle transceiver **135** onboard aircraft **100**. As with transceiver **1205**, in some embodiments, delivery vehicle transceiver **135** (or flight personnel radio-based mobile interactive transceiver **1200**) may forward information related to the inspection notification message to the mobile logistics transceiver **1210**. This may occur automatically when the inspection notification message meets an automatically identifiable criteria (e.g., a relevant targeted inspection point associated with the inspection notification message is not found or is demonstrably damaged as indicated by the identified inspection condition). However, in other embodiments, the forwarding of information to the mobile logistics transceiver **1210** may occur based upon user input provided to the delivery vehicle transceiver **135** (or transceiver **1200**), such as when flight personnel reviews the inspection notification message from an initial aerial inspection by PID **825** and provides user input to cause transceiver **135** (or transceiver **1200**) to forward such information to mobile logistics transceiver **1210** as a type of logistics request specific to the targeted inspection point at issue in the inspection notification message. This may, for example, inform logistics personnel responsible for loading/unloading the delivery vehicle of an issue with a cargo handling point that is missing or otherwise may be malfunctioning. Further still, other embodiments may forward information related to an inspection notification message after a re-inspection of the targeted inspection point of interest is performed. This may also occur based upon user input received by the delivery vehicle transceiver **135** (or transceiver **1200**) or automatically based upon information related to the re-inspection. For example, delivery vehicle transceiver **135** (or transceiver **1200**) may auto-

atically forward a re-inspection related notification message to mobile logistics transceiver **1210** after flight personnel reviews another inspection notification message from a re-inspection performed by PID **825**. In further embodiments, the PID **825** may directly transmit the relevant inspection notification message to the mobile logistics transceiver **1210** and avoid the need to involve the delivery vehicle transceiver **135** (or transceiver **1200**) as an intermediary component in such an enhanced drone-based inspection system for aircraft **100**.

With reference to the embodiment illustrated in FIG. **12** (and the earlier descriptions of embodiments that aerially inspect targeted inspection points on a delivery vehicle in FIGS. **8A-11**), an exemplary enhanced drone-based inspection system may include the paired aerial inspection drone (e.g., PID **825**), an internal docking station (e.g., station **830**), a delivery vehicle transceiver (e.g., vehicle transceiver **135**), and a mobile interactive transceiver (e.g., such as one or the radio-based transceivers **1200-1210**). Some embodiments of this system may also include the delivery vehicle itself as part of the system—especially, as the paired inspection drone is essentially an exclusively assigned extension of the vehicle as a sensor-based monitor that travels with the delivery vehicle during shipment operations. Examples of such a relevant delivery vehicle may include an aircraft (such as aircraft **100**), a delivery van, a truck coupled with a cargo hauling trailer, or a marine vessel.

Regarding operation of such a system, the system's paired aerial inspection drone in this embodiment automatically uncouples from the internal docking station at the beginning of a targeted inspection flight to inspect targeted inspection points of the delivery vehicle; automatically identifies an inspection condition about at least one of the targeted inspection points based upon sensor-based inspection information gathered related to at least one of the targeted inspection points (where such an inspection condition indicates a situation that is outside an acceptable range for operation of the delivery vehicle); and transmits an inspection notification message to the delivery vehicle transceiver upon identifying the inspection condition. In response, the system's delivery vehicle transceiver is configured to forward information related to the inspection notification message to the mobile interactive transceiver (e.g., where delivery vehicle transceiver **135** forwards information related an inspection notification message about roller **840** to mobile interactive transceiver **100** operated by flight personnel that control aircraft **100**). In further response, the mobile interactive transceiver is configured to receive the information related to the inspection notification message from the delivery vehicle transceiver and display at least a portion of the forwarded information related to the inspection notification message to the delivery vehicle personnel associated with the delivery vehicle (e.g., a pilot, co-pilot, flight engineer, cargo specialist, or other flight personnel that control aspects of the operation of aircraft **100**).

In a more detailed embodiment, the delivery vehicle transceiver may generate inspection notification information related to the inspection condition as vehicle related information for presenting on the display of the delivery vehicle transceiver. In response, the delivery vehicle transceiver may receive inspection condition feedback input as user input received via the control input interface of the delivery vehicle transceiver. This inspection condition feedback may indicate an instruction to forward information related to the inspection notification message to the mobile interactive transceiver. Based upon such an instruction, the delivery vehicle transceiver may then selectively transmit the infor-

55

mation related to the inspection notification message to the mobile interactive transceiver.

Relative to interactive display aspects of the mobile interactive transceiver in this exemplary system embodiment, the mobile interactive transceiver may display at least a portion of the forwarded information it receives related to the inspection notification message as a prompt for an enhanced inspection of the at least one of the targeted inspection points. Furthermore, the mobile interactive transceiver (such as transceiver **1200** used by flight personnel or transceiver **1210** used by logistics personnel) may receive input from such personnel in response to the displayed prompt. Such input may take the form of a verified result indication related to the enhanced inspection of the relevant targeted inspection point(s). Thereafter, the system's mobile interactive transceiver may transmit a confirmation message to the delivery vehicle transceiver, where the confirmation message indicate the result of the enhanced inspection of the at least one of the targeted inspection points.

In still a further embodiment of an enhanced drone-based inspection system, a separate maintenance transceiver (e.g., transceiver **1205** operated by a mechanic that services aircraft **100**) may be added as part of the system. As such, the system's delivery vehicle transceiver may forward information related to the inspection notification message to the maintenance transceiver as a type of maintenance request. However, in another embodiment, the system's maintenance receiver may directly receive such information from the paired aerial inspection drone directly without relying upon an intermediary element, such as the delivery vehicle transceiver or the mobile interactive transceiver.

In particular, another embodiment of such an enhanced drone-based inspection system may focus more on such a direct communication link between the paired inspection drone (e.g., PID **825** as shown in FIG. **12**) and a mobile interactive transceiver. Here, the aerial inspection drone is paired to the delivery vehicle as an exclusively assigned sensor-based monitor that travels with the delivery vehicle during a delivery vehicle based shipment operation. The paired aerial inspection drone deploys multiple sensors to detect sensor-based inspection information about targeted inspection points on the delivery vehicle similar to that discussed above. In this embodiment, the system's paired aerial inspection drone is configured and operative to control its internal flight control elements (e.g., lifting engines **210a**, **210b**) to fly proximate each of the targeted inspection points as part of a targeted inspection flight. During this targeted inspection flight, the system's paired aerial inspection drone detects, senses, or otherwise gathers sensor-based inspection information from one or more of the sensors relative to each of the targeted inspection points. While doing so (or in some embodiments after gathering all such sensor-based inspection information relative to each of the targeted inspection points), the system's paired aerial inspection drone automatically identifies an inspection condition about one or more of the targeted inspection points based upon the sensor-based inspection information gathered. Such an inspection condition indicating the one or more of the targeted inspection points are outside an acceptable range for operation of the delivery vehicle. Thereafter, the system's paired aerial inspection drone broadcasts an inspection notification message over a wireless communication channel.

The system's mobile interactive transceiver in this embodiment is disposed as a system element that is generally in communication with the paired aerial inspection drone and being operated by delivery vehicle personnel

56

associated with the delivery vehicle, such as flight operator personnel, maintenance personnel, or logistics personnel. In more detail, the system's mobile interactive transceiver has a graphical display (e.g., a touchscreen) that presents visual information to the delivery vehicle personnel, a control input receiver that receives user input from the delivery vehicle personnel (e.g., buttons, switches, or a touchscreen part of the graphical display), and a wireless radio operative to communicate with the paired aerial inspection drone over the wireless communication channel (e.g., a cellular or other formatted wireless communication path). As part of the system, the system's mobile interactive transceiver receives the inspection notification message directly from the paired aerial inspection drone through the wireless radio, and generates a prompt message as the graphical display on the interactive display interface. The prompt message provides information related to the inspection notification message and the identified inspection condition related to at least one of the targeted inspection points. The system's mobile interactive transceiver may also receive input on the control input receiver from the delivery vehicle personnel in response to the generated prompt message. Such input may be provided as a verified result indication related to the enhanced inspection of at least one of the targeted inspection points. Further, the system's mobile interactive transceiver may transmit a confirmation message directly back to the paired aerial inspection drone. Such a confirmation message may indicates the result of the enhanced inspection of the at least one of the targeted inspection points, and allow the paired aerial inspection drone to quickly and efficiently continue to conduct its inspection of the remaining targeted inspection points.

In another embodiment, the system may include two different mobile interactive transceivers (e.g., transceiver **1200** operated by flight personnel and transceiver **1210** operated by logistics personnel associated with loading or unloading the delivery vehicle). Each of these different mobile interactive transceivers have a direct communication path to the paired aerial inspection drone and, thus, are capable of respectively receiving the inspection notification message directly from the paired aerial inspection drone through the wireless radio (and responding as described herein).

In still a further embodiment of this exemplary enhanced drone-based inspection system, a separate maintenance transceiver (e.g., transceiver **1205** operated by a mechanic that services aircraft **100**) may be added as part of the system. As such, the system's delivery vehicle transceiver may forward information related to the inspection notification message to the maintenance transceiver as a type of maintenance request. However, in another embodiment, the system's maintenance receiver may directly receive such information from the paired aerial inspection drone directly without relying upon an intermediary element, such as the delivery vehicle transceiver or the mobile interactive transceiver.

Updating for Modified Inspections Using a Paired Inspection Drone

While the above described embodiments generally deploy an aerial inspection drone paired as an exclusive part of a delivery vehicle, further embodiments may include exemplary paired-drone based systems and methods for conducting a modified inspection of the delivery vehicle when the paired inspection drone receives an inspection update message. In general, an embodiment of an aerial inspection drone paired to the delivery vehicle may advantageously and unconventionally be re-tasked to conduct a modified air-

57

borne inspection of a different set of delivery vehicle parts, change how to inspect a given set of delivery vehicle parts, or both. Such a dynamic ability to update, modify, or change what should be inspected and how such inspection points should be inspected provides a further improvement on how a delivery vehicle is inspected. As such, the embodiments shown in FIGS. 13-16 and described below provide a technical solution that improves how a delivery vehicle may be more efficiently self-inspecting using an exclusively paired aerial inspection drone that can be updated on-the-fly to modify how the delivery vehicle is to be inspected or alter how an ongoing inspection is to be completed by such a paired aerial inspection drone.

In more detail, FIG. 13 is a diagram of an exemplary drone-based system for conducting a modified inspection of a delivery vehicle in accordance with an embodiment of the invention. As shown in FIG. 13, this exemplary system embodiment includes an inspection drone 1325 paired to the delivery vehicle (e.g., an aircraft, a trailer pulled with a motorized vehicle, a marine vessel, and a railroad car) that communicates with a delivery vehicle transceiver 1335. Exemplary PID 1325 is configured similar to PID 825 (as described above) with some functional differences in its inspection program 925 as it operates as an element of an exemplary system for conducting a modified inspection of a delivery vehicle. In more detail and with similar parts as explained and shown for exemplary PID 825, exemplary PID 1325 is used to aurally inspect parts of aircraft 100 and includes a main housing, an onboard controller disposed within the main housing, a memory storage coupled to the onboard controller, and multiple lifting engines that are coupled with respective lifting rotors fixed to a different portions of the main housing. Each of the lifting engines on PID 1325 is responsive to flight control input generated by the onboard controller as part of maintaining a desired flight profile. Exemplary PID 1325 further includes one or more sensors (such as sensors from sensor array 230) along with a communication interface that each are coupled to the onboard controller. The sensor detects or gathers sensor-based inspection information while the PID 1325 is airborne and then provides the detected sensor-based inspection information to the onboard controller. The communication interface is deployed, in this example, as a wireless radio-based communication interface (similar to communication interface 365) that can send and receive wireless signals (such as signals 1305, 1310) from other radio-based devices, such as delivery vehicle transceiver 1335. For example, signal 1305 may be an inspection update message transmitted by delivery vehicle transceiver 1335 and received by the communication interface on PID 1325, while signal 1310 may be an inspection notification message transmitted by the communication interface on PID 1325 to the delivery vehicle transceiver 1335.

FIG. 14 presents further details about exemplary components that may be used to implement an exemplary delivery vehicle transceiver 1335 in accordance with an embodiment of the invention. Referring now to FIG. 14, exemplary delivery vehicle transceiver 1335 is shown having a housing 1400 that maintains elements on it or within it that make up the transceiver 1335. For example, housing 1400 supports an exemplary user interface that includes a display 1410 (e.g., a CRT display, flat screen display, dot matrix display, interactive touchscreen display, and the like); a panel 1420 of buttons 1425 (e.g., power button, illumination button, and the like) and control knobs/switches 1430-1440; and a set of keys 1415 that function as a type of keyboard for user input. Generally, such user interface components for delivery

58

vehicle transceiver 1335 may display information to a user via display 1410 and accept input from the user via keys 1415 and panel 1420 to use in interactions with the PID 1325.

Exemplary delivery vehicle transceiver 1335 further includes a transceiver microcontroller 1405 having one or more processors and memory at its core along with memory disposed within housing 1400. Transceiver microcontroller 1405 interfaces with the user interface components described above along with a wireless radio 1445, an external data interface 1450, and an avionics interface 1455. An embodiment of transceiver microcontroller 1405 may interface or connect with such circuitry by deploying various onboard peripherals (e.g., timer circuitry, USB, USART, general-purpose I/O pins, IR interface circuitry, DMA circuitry, buffers, registers, and the like) that implement an interface (e.g., a plug type or connectorized interface) to these different components disposed within delivery vehicle transceiver 1335.

Wireless radio 1445 is generally a radio-based transceiver that may use one or more wireless formats (e.g., Wi-Fi frequencies and formats, cellular frequencies and formats, ISM radio frequencies and formats for RF data signaling, LMR and SMR wireless frequencies and formats, and the like) to broadcast and receive through its associated antenna. Wireless radio 1445 accepts control input and messaging input from transceiver microcontroller 1405 (such as information used for an inspection update message) and provides received messages and/or data received to transceiver microcontroller 1405 (such as an inspection notification message) for processing and appropriate display tasks performed by the transceiver microcontroller 1405 in conjunction with, for example, display 1410.

The exemplary delivery vehicle transceiver 1335 may deploy the external data interface 1450 coupled to the transceiver microcontroller 1405 as a general type of externally accessible interface, such as a USB interface or other data interface. Using such an external data interface 1450, delivery vehicle transceiver 1335 may interact with external peripherals, such as an external display (not shown) to show information related to an inspection notification message received or an external memory storage (not shown) that may maintain and provide access to updated information on additional inspection points for a delivery vehicle (e.g., a different or modified set of parts of the aircraft 100 to be inspected, changes in how to inspect one or more of such delivery vehicle parts, or both).

Likewise, exemplary delivery vehicle transceiver 1335 may use an avionics interface 1455 coupled to the transceiver microcontroller 1405 as a type interface to the avionics suite of electronics disposed on the delivery vehicle. For example, avionics interface 1445 may allow delivery vehicle transceiver 1335 to communicate over an avionics bus deployed on the delivery vehicle, such as an ARINC 429 data bus, a MIL-STD-1553 bus, a Honeywell SAFEBus backplane data bus used on different types of aircraft. Similar to the external data interface 1450, such an avionics interface 1455 may allow delivery vehicle transceiver 1335 to interact with avionics equipment, such as a cockpit multi-function display (not shown) to show information related to an inspection notification message received or an onboard avionics memory storage (not shown) that may maintain and provide access to updated information on additional inspection points for a delivery vehicle (e.g., a different or modified set of parts of the aircraft 100 to be inspected, changes in how to inspect one or more of such delivery vehicle parts, or both).

Those skilled in the art will further appreciate that transceiver microcontroller **1405** may be implemented with a low power embedded processor as part of a single-board computer having a system-on-chip (SoC) device operating at its core. In such an embodiment, the SoC device may include different types of memory (e.g., a removable memory card slot, such as a Secure Digital (SD) card slot, as removable memory; flash memory operating as onboard non-volatile memory storage; and RAM memory operating as onboard volatile memory); an operating system (such as Linux) stored on the non-volatile memory storage and running in volatile RAM memory; and peripherals that may implement any of wireless radio **1445**, external data interface **1450**, and avionics interface **1455**.

Additionally, exemplary delivery vehicle transceiver **1335** includes a power interface and transformer **1460** that provides electrical power to the active circuitry within exemplary delivery vehicle transceiver **1335** using externally supplied electricity (which may be transformed to the desired voltage for use by the active circuitry within exemplary delivery vehicle transceiver **1335**) or an onboard battery **1465**. Onboard battery **1465** may be charged via the power interface and transformer **1460**, which may be connected to an external power supply on the delivery vehicle (e.g., aircraft **100**).

In an exemplary system embodiment that includes PID **1325** and delivery vehicle transceiver **1335**, the delivery vehicle transceiver **1335** may generate an inspection update message identifying information about at least one or more additional inspection points. The additional inspection points for a delivery vehicle generally include updated information used for a modified inspection of the delivery vehicle. As noted above, this may include a different or modified set of parts of the delivery vehicle (e.g., aircraft **100**) to be inspected, changes in how to inspect one or more of the delivery vehicle parts, or both. The updated information for the additional inspection points may be accepted as input on the user interface (e.g., via touchscreen interactions on display **1410**, via alphanumeric input provided on keys **1415**, via user input provided on panel **1420** of buttons **1425** and/or control knobs/switches **1430-1440**). Such updated information may be accepted as raw data input manually through such user interface interactions or, in some instances, may be accepted as prompted interactions via the user interface elements that cause delivery vehicle transceiver **1335** to access either onboard memory or externally accessible memory to retrieve such updated information. Once generated, the delivery vehicle transceiver **1335** transmits the inspection update message via its wireless radio **1445**.

The system's PID **1325** is then operative to receive the inspection update message from the delivery vehicle transceiver **1335**. This may occur prior to the PID **1325** lifting off from docking station **830** (shown in FIG. **13**) or may occur once PID **1325** is airborne. Furthermore, reception of the inspection update message by the airborne PID **1325** may occur before the PID **1325** has begun conducting an inspection of certain targeted inspection points on the aircraft **100** or, alternatively, may occur after the PID **1325** has begun conducting its aerial inspection of targeted inspection points on the aircraft **100**.

The onboard controller (e.g., transceiver microcontroller **1405**) of PID **1325** receives the inspection update message from its onboard wireless communication interface and PID **1325** accesses its memory storage to identify existing delivery vehicle inspection points from the inspection profile record stored in the memory storage (e.g., existing delivery

vehicle inspection points for aircraft **100** identified in inspection profile record **945** within memory **315**). The identification of existing delivery vehicle inspection points may, in some instances, occur before receiving the inspection update message or, in other instances, may occur after and as a result of receiving the inspection update message. The delivery vehicle transceiver's onboard controller then updates the existing delivery vehicle inspection points with the information related to the additional inspection points to yield updated information that identifies relevant targeted inspection points corresponding to respective parts of the delivery vehicle to use in a modified inspection of the delivery vehicle. For example, the transceiver microcontroller **1405** of PID **1325** may modify the inspection profile record to identify the targeted inspection points (which include information on the additional inspection points) and store the modified inspection profile record in memory accessible by microcontroller **1405**.

Such updated information on the additional inspection points may include the same parts to be inspected but with different inspection parameters (e.g., which sensor or sensors to use, how to position the PID **1325** when using such sensor(s), and how much data to gather using the sensor(s) over periods of time) and/or different parts to be inspected using new inspection parameters for such parts. Some of the additional inspection points may be specific to inside of the delivery vehicle (such as an accessible cargo storage area within an aircraft, a cargo attachment point located within an accessible cargo storage area, a cargo handling point that helps move cargo shipments within an accessible cargo storage area (e.g., a roller, a caster, a portion of a roller deck, a roller ball mat, a castor mat, a turntable, and a conveyor)). Other additional inspection points may be externally exposed on the delivery vehicle, such as a designated inspection area aerially accessible from above the delivery vehicle that is not visible from a ground level perspective relative to the delivery vehicle or an aircraft component (e.g., a panel, a rivet, a seam, an engine, a flight control surface, a window seal, a closable entry to within the aircraft, aircraft lighting, an antenna, landing gear, and a tire).

The PID **1325** then conducts the modified inspection of the delivery vehicle by gathering sensor-based inspection information related to each of the targeted inspection points (based upon the additional inspection points information). The PID **1325** may use one or more sensors when gathering this inspection information, such as an image sensor (e.g., visual imaging sensor, an infrared (IR) imaging sensor, and a thermal imaging sensor) that captures one or more images relative to the additional inspection points and in accordance with information related to the additional inspection points, or a depth measuring sensor (e.g., a LIDAR sensor and a sound transducer) that maps a surface relative to an additional inspection point in accordance with information related to that additional inspection point. In a further embodiment, the PID **1325** may use two sensors of different types a particular additional inspection point or use different types of sensors for different ones of the additional inspection points in accordance with the updated information stored in the modified inspection profile record that indicates the type of sensor to use with the targeted inspection points (including any additional inspection points).

A further embodiment may, for example, have the onboard controller of PID **1325** autonomously send flight control input to the lifting engines to cause PID **1325** to traverse respective aerial positions proximate each of the targeted inspection points as part of conducting the modified

61

inspection of the delivery vehicle. When doing so, the onboard controller of PID 1325 may automatically identify an inspection condition about at least one of the targeted inspection points when the sensor-based inspection information for the at least one of the targeted inspection points is outside of an acceptable range related to that particular targeted inspection point, and then cause the communication interface of PID 1325 to responsively transmit an inspection notification message to the delivery vehicle transceiver upon identifying the inspection condition for that targeted inspection point.

As shown in FIG. 13, the delivery vehicle transceiver 1335 is disposed in a control compartment 105 for the aircraft 100 and, in some implementations, may be implemented as an integrated part of aircraft 100. However, in other embodiments, such as that shown in FIG. 15, the above described system's delivery vehicle transceiver may be a mobile transceiver device used in support of delivery vehicle operations that is physically separate from the delivery vehicle. Referring now to FIG. 15, radio-based transceiver 1200 is shown as an exemplary mobile interactive transceiver associated with and operated by an aircraft operator (e.g., pilot, co-pilot, flight engineer, cargo specialist, and the like) in compartment 105 that is responsible for controlling the aircraft 100. As noted above, exemplary radio-based transceiver 1200 may be implemented as a ruggedized radio-based tablet or smartphone used by aircraft crew personnel and carried with them while performing duties within aircraft 100. Relative to a system embodiment for conducting a modified inspection, exemplary radio-based transceiver 1200 may interact with PID 1325 in the same role as transceiver 1335 is described above. In this manner, an operator of radio-based transceiver 1200 may provide input on one or more additional inspection points related to the delivery vehicle so that radio-based transceiver 1200 transmits the inspection updated message to PID 1325. In one example, this may allow the operator of radio-based transceiver 1200 to have received a prior inspection notification message from PID 1325 and provide further detailed and changed inspection parameters for a particular targeted inspection point (e.g., updated information considered as an additional inspection point) or provide further relevant parts of the aircraft 100 that are to be inspected as additional inspection points. In another example, this may allow the operator of radio-based transceiver 1200 to update PID 1325 to reflect new cargo attachment points are being used within aircraft 100 or certain cargo handling points have been changed or configured differently to accommodate the current cargo of items to be shipped within the aircraft's internal shipment storage area 820. In this manner, interactive signaling 1305, 1310 may be used between radio-based transceiver 1200 (operating as a type of delivery vehicle transceiver) and PID 1325 as part of an exemplary drone-based system for conducting a modified inspection of the delivery vehicle. Furthermore, while not shown in FIG. 15, those skilled in the art will appreciate that one or more of exemplary radio-based transceivers 1205 and 1210 may similarly interact with PID 1325 in the same role as transceiver 1335 is described above in other embodiments of a drone-based system for conducting a modified inspection of the delivery vehicle.

In similar fashion, this type of system embodiment may operate in accordance with an exemplary drone-based method for conducting a modified inspection of a delivery vehicle. FIG. 16 is a flow diagram illustrating such an exemplary drone-based method for conducting a modified inspection of a delivery vehicle in accordance with an

62

embodiment of the invention. Referring now to FIG. 16, method 1600 begins at step 1605 where a first transceiver receives input that identifies at least one or more additional inspection points. For example, the first transceiver (e.g., delivery vehicle transceiver 1335 or one of the mobile radio-based transceivers 1200, 1205, 1210 physically separate from the delivery vehicle) may receive such input through its user interface components, where the input accepted identifies information about the additional inspection points. Such information may include the identification of further parts of the delivery vehicle to inspect as well as further or different inspection parameters to use when inspecting those further parts or the existing parts to be inspected. Such information may reflect a change in the configuration of the delivery vehicle or the addition of new equipment used onboard the delivery vehicle. In another example, the first transceiver may receive information about the additional inspection points as data from an external source, such as a memory storage coupled to the first transceiver (e.g., an update file that includes the information about the additional inspection points). The external information may be accepted through a prompted input using the user interface elements of the first transceiver (e.g., depressing a switch or button, or tapping an interactive touchscreen display interface when selecting such information or when downloading such information).

At step 1610, method 1600 proceeds by generating and transmitting an inspection update message by the first transceiver to a paired inspection drone (PID), such as PID 1325, which is a linked part of the delivery vehicle and that travels with the delivery vehicle during delivery vehicle based shipment operations (such as when shipping cargo items maintained within a cargo storage area of the delivery vehicle). The inspection update message essentially identifies at least one or more additional inspection points associated with the delivery vehicle using the information obtained and accepted in step 1605.

At step 1615, method 1600 has the PID receiving the inspection update message transmitted by the first transceiver. For example, as shown in FIG. 13, exemplary delivery vehicle transceiver 1335 transmits a wireless signal 1305 to PID 1325 that includes an inspection update message that has information identifying additional inspection points relative to what is to be inspected on aircraft 100.

At step 1620, method 1600 proceeds with the PID accessing memory to identify existing delivery vehicle inspection points from an inspection profile record stored in memory. The inspection profile record, such as record 945, essentially maintains delivery vehicle dependent information in the form of data indicating the different targeted delivery vehicle inspection points corresponding to parts of the delivery vehicle to be inspected and an acceptable range of sensor-based inspection information for each of the targeted inspection points for operation of the delivery vehicle. This existing set of information may also include prior sensor-based inspection information detected for one or more of the targeted delivery vehicle inspection points and, in some instances, may include a prioritized subset of the targeted delivery vehicle inspection points designated for an enhanced level of sensor-based inspection.

At step 1625, method 1600 proceeds with the PID updating the existing delivery vehicle inspection points with the information on additional inspection points to yield an updated set of targeted inspection points corresponding to respective parts of the delivery vehicle. In more detail, the PID may generate a modified inspection profile record that identifies the updated targeted inspection points as a first

63

group of designated inspection areas specific to the delivery vehicle as the existing delivery vehicle inspection points and identifies a second group of designated inspection areas specific to the delivery vehicle as the additional inspection points. Embodiments may collectively identify both groups as the new targeted set of inspection points, which may include a changed set of inspection points, a set of inspection points having changed inspection parameters on how to inspect such points, and/or a set of inspection points having changed inspection thresholds for acceptable operation.

At step **1630**, method **1600** proceeds to use at least one sensor on the PID to conduct the modified inspection of the delivery vehicle by gathering sensor-based inspection information related to each of the targeted inspection points and provide the sensor-based inspection information by the sensor to an onboard processor on the PID. For example, this may involve capturing one or more images relative to a targeted inspection point using an image sensor (e.g., a visual imaging sensor, an infrared (IR) imaging sensor, and a thermal imaging sensor), or surface mapping relative to a targeted inspection point using a depth sensor (e.g., a LIDAR sensor and a sound transducer). In another example, this may involve detecting the sensor-based inspection information for one targeted inspection point with a first type of sensor and detecting the sensor-based inspection information for a second targeted inspection point with a second type of sensor according to the modified inspection profile record.

When the relevant sensor-based inspection information for a particular targeted inspection point identified in the modified inspection profile record has been gathered, steps **1635** and **1640** automatically identify an inspection condition about that targeted inspection point (which may be one of the additional inspection points). In particular, at step **1635**, method **1600** proceeds with the PID comparing the gathered sensor-based inspection information to reference parameters for that targeted inspection point (which may be one of the additional inspection points) in accordance with information in the modified inspection profile record. In one embodiment, the reference information or parameters may be prior sensor-based inspection information for this targeted inspection point. In another embodiment, the reference information or parameters may be measurement or sensor based ranges for the targeted inspection point that corresponds with acceptable operation of that part of the delivery vehicle. In a further embodiment, such reference information or parameters may include both prior sensor-based inspection information for this targeted inspection point and sensor data ranges that may be used in the comparison. In other words, the comparison at step **1635** may involve a more simplistic comparison of sensor information detected to a limit or range, but may also involve multiple comparisons of different types of detected sensor information to various types of reference information as reflected in the modified inspection profile record for that targeted inspection point.

At step **1640**, method **1600** automatically identifies an inspection condition related to the targeted inspection point (which may be one of the additional inspection points) based upon the results of the comparison in step **1635**. In other words, the processing of the currently gathered sensor-based inspection information for this targeted inspection point may yield a result that the targeted inspection point is now outside an acceptable range for operation of the delivery vehicle according to the modified information in the inspection profile record. Thus, if step **1640** fails to automatically

64

identify an inspection condition for the targeted inspection point, step **1640** proceeds directly to step **1650**. However, if step **1640** does automatically identify an inspection condition based upon the sensor-based inspection information detected (e.g., the comparison of such sensor-based inspection information to reference information for the targeted inspection point), step **1640** proceeds to step **1645**.

At step **1645**, an embodiment of method **1600** may have the PID responsively transmit an inspection notification message to a delivery vehicle receiver disposed on the delivery vehicle (such as exemplary delivery vehicle transceiver **1335**). This inspection notification message is a type of feedback for a paired inspection drone-based system associated with the delivery vehicle (or including the delivery vehicle) as the PID conducts the modified inspection of the delivery vehicle. As such, the delivery vehicle receiver is able to alert personnel associated with the delivery vehicle, such as an aircraft operator (e.g., pilot, co-pilot, flight engineer, cargo specialist, and the like) in compartment **105** that is responsible for controlling the aircraft **100**. A further embodiment may have step **1645** also (or alternatively) transmit the inspection notification message to a mobile interactive radio-based transceiver **1200** separate from the delivery vehicle but operated by vehicle crew personnel for the delivery vehicle to notify the vehicle crew personnel that operate the delivery vehicle (e.g., a flight engineer that uses a ruggedized tablet as a type of mobile interactive transceiver and can view the inspection notification message as well as relevant sensor-based inspection information about the related targeted inspection point). Likewise, another embodiment may have step **1645** also (or alternatively) transmit the inspection notification message to a maintenance radio-based transceiver **1205** operated by maintenance personnel for the delivery vehicle to notify the maintenance personnel that service the delivery vehicle (e.g., an aircraft mechanic that uses a ruggedized tablet as a type of maintenance receiver and can view the inspection notification message as well as relevant sensor-based inspection information about the related targeted inspection point). Furthermore, an embodiment may have step **1645** also (or alternatively) transmit the inspection notification message to a logistics radio-based transceiver **1210** (operated by maintenance personnel for the delivery vehicle to notify the maintenance personnel that service the delivery vehicle (e.g., an aircraft mechanic that uses a ruggedized tablet as a type of maintenance receiver and can view the inspection notification message as well as relevant sensor-based inspection information about the related targeted inspection point).

At step **1650**, method **1600** has the PID determine if it is at the end of the modified inspection associated with each of the targeted inspection points (including any additional inspection points) for the delivery vehicle. If not, then step **1650** proceeds to step **1655** where the PID moves to the next aerial position proximate another of the targeted inspection points and then continues to step **1660**. Otherwise, the PID is at the end of the modified inspection and method **1600** concludes after step **1650**.

At step **1660**, the PID determines if another inspection update message has been received mid-stream during the modified inspection of the delivery vehicle. If so, step **1660** proceeds back to step **1625** to further update the currently targeted inspection points (e.g., the information identifying relevant parts to be inspected and how they are to be inspected including their related reference parameters). If not, step **1660** proceeds back to step **1635** to gather sensor-based inspection information for the next targeted inspection point in the modified inspection of the delivery vehicle.

Verified Inspection Using a Paired Inspection Drone

Expanding upon the embodiments described above that use an aerial inspection drone exclusively paired as part of a delivery vehicle, further embodiments may implement exemplary paired-drone based systems and methods for conducting a verified inspection of the delivery vehicle. In general, a verified inspection is one that is performed after an initial inspection identifies a potential adverse issue with a part of the delivery vehicle, and further inspection is warranted in order to make a determination related to the part's acceptability for proper delivery vehicle operation. In a verified inspection embodiment, a radio-based transceiver (such as a delivery vehicle transceiver or a mobile interactive transceiver operated by delivery vehicle related personnel) generally provides a unique interface for interactively intervening to verify an issue related to a potential adverse inspection condition automatically discovered by the paired inspection drone. The transceiver presents information about an interactive intervention request about the potential adverse inspection condition, generates a visual interface that unconventionally assists with conducting the verified inspection related to the request, and integrates with operations of the exclusively paired inspection drone to help implement or conduct the desired verified inspection. This dynamic and unconventional ability to verify what may be wrong with a previously inspected inspection point that may be problematic using an inspection drone exclusively paired to the delivery vehicle provides a yet another improvement on how a delivery vehicle is inspected and how such inspections may be enhanced. Thus, the embodiments shown in FIGS. 17-19 and described below provide a technical solution that improves how a potential adverse inspection condition with part of a delivery vehicle may be interactively addressed in a manner that leverages the exclusively paired inspection drone and advantageous user interface interactions via a separate transceiver operated by delivery vehicle personnel that speed up and enhance the delivery vehicle inspection process.

FIG. 17 is a diagram of an exemplary drone-based system used to conduct a verified inspection of a delivery vehicle in accordance with an embodiment of the invention. As shown in FIG. 17, this exemplary system embodiment includes an inspection drone (PID) 1725 paired to aircraft 100 that interfaces with a radio-based transceiver, such as delivery vehicle transceiver 1735. Exemplary PID 1725 is configured similar to PID 825 and PID 1325 (as described above) with some functional differences in its inspection program 925 as it operates as an element of an exemplary system for conducting a verified inspection of a delivery vehicle. In more detail and with similar parts as explained and shown for exemplary PID 825, exemplary PID 1725 is used to aurally inspect parts of aircraft 100 and includes a main housing, an onboard controller disposed within the main housing, a memory storage coupled to the onboard controller, and multiple lifting engines that are coupled with respective lifting rotors fixed to a different portions of the main housing. Each of the lifting engines on PID 1725 is responsive to flight control input generated by the onboard controller as part of maintaining a desired flight profile. Exemplary PID 1725 further includes one or more sensors (such as sensors from sensor array 230) along with a communication interface that each are coupled to the onboard controller. The sensor detects or gathers sensor-based inspection information while the PID 1725 is airborne and then provides the detected sensor-based inspection information to the onboard controller. The communication interface is deployed, in this example, as a wireless radio-based com-

munication interface (similar to communication interface 365) that can send and receive wireless signals (such as signals 1705, 1710) from other radio-based devices, such as delivery vehicle transceiver 1735. For example, signal 1705 may be a verification command or other drone control input transmitted by delivery vehicle transceiver 1735 and received by the communication interface on PID 1725, while signal 1710 may be an interactive intervention request or additional sensor-based inspection information transmitted by the communication interface on PID 1725 to the delivery vehicle transceiver 1735.

Exemplary delivery vehicle transceiver 1735, as shown in FIGS. 17-18E and explained with reference to embodiments that conduct a verified inspection of a delivery vehicle, is configured similar to delivery vehicle transceiver 1325 (as described above and with the details shown in FIG. 14) with further details as explained below regarding its operation as an element of an exemplary system for conducting a verified inspection of a delivery vehicle. In general, delivery vehicle transceiver 1735 functions as a type of radio-based interactive transceiver where the operator may receive different types of information from PID 1725 about a potential adverse inspection condition for part of the delivery vehicle, interact with the PID 1725 as part of conducting a follow-up verified inspection, and use the transceiver to rapidly and efficiently view and review information related to additional sensor-based inspection information gathered about that part of the delivery vehicle. In doing so, the delivery vehicle transceiver 1735 allows the operator to input a verification result and then update the PID 1725 with feedback on the verification result.

As with exemplary delivery vehicle transceiver 1335, delivery vehicle transceiver 1735 shown in FIGS. 17-18E has a housing that supports a user interface that includes a display 1410 (e.g., a CRT display, flat screen display, dot matrix LCD display, interactive touchscreen display, and the like); a panel 1420 of buttons 1425 (e.g., power button, illumination button, and the like) and control knobs/switches 1430-1440; and a set of keys 1415 that function as a type of keyboard for user input. In some instances, the interactive touchscreen display 1410 may show graphic images representing the delivery vehicle and highlighted parts of the delivery vehicle. The display 1410 may also show additional sensor-based inspection information gathered relative to parts of the delivery vehicle, which may, for example, be in the form of one or more still images, a video, numeric sensor data, or a depth sensor mapping of part of the delivery vehicle (e.g., a 3D generated model representing the part being subjected to the verified inspection). The user interface components for delivery vehicle transceiver 1735 may display such information to a user via display 1410 and accept input from the user via keys 1415 and panel 1420.

Referring now to FIGS. 18A-18F, the exemplary drone-based system of FIG. 17 is shown in a general example involving a modified inspection for a part of the delivery vehicle. As shown in FIG. 17, the system's PID 1725 has detected sensor-based inspection information related to a targeted inspection point on aircraft—for example, the tie down strap 850 that is part of a cargo attachment point securing packaged shipping item 845. However, as such sensor-based inspection information is gathered, PID 1725 automatically identified a potential adverse inspection condition related to the tie down strap 850 because the strap is not where it was in a prior inspection of that cargo attachment point. As a result, PID 1725 transmits an interactive intervention request in signal 1710 sent to delivery vehicle transceiver 1735. In response, as shown in FIG. 18A, the

delivery vehicle transceiver **1735** displays a notification on its user interface—e.g., a graphic model **1800** representing aircraft **100** on display **1410** of the transceiver **1735**. The graphic model **1800** shows areas of the delivery vehicle, such as a cargo mat **1840** where items **1845** may be secured using tie down strap **1850** via cargo attachment points **1852**. Additionally, the graphic model **1800** generated on display **1410** includes a highlighted area **1860** where the tie down strap is located. This highlighted area **1860** is a selectable region of the displayed graphic model of the aircraft **1800**. As such, the operator of the delivery vehicle transceiver **1735** is notified about the potential adverse inspection condition related to the tie down strap **850** and that there is a need for a verified inspection to be conducted relative to area **1860**.

The operator, at this point, may personally perform such a verified inspection by physically moving to the actual area of the aircraft **100** where the PID **1725** has identified such a potential adverse inspection condition. While this may be done for some parts of the aircraft, this often is time consuming or difficult to do given the location and/or exposure of that part to human inspection. Therefore, an embodiment may have the operator initiate such a verified inspection by selecting the highlighted area **1860** (as a selectable region) with user interface elements, such as a touch interface or buttons/knobs that allow the operator to identify the area **1860** and then select it for further automated inspection via a verification type of inspection that provides enhanced additional sensor-based inspection information. For example, as shown in FIG. **18B**, flight personnel may select area **1860** on display **1410** of delivery vehicle transceiver **1735**. Delivery vehicle transceiver **1735** detects this selection action and generates a verification command that is then transmitted via signal **1705** to PID **1725**. Upon receipt of the verification command (which may identify parameters or drone control input to be used as part of this follow-up inspection of the tie down strap **850**), PID **1725** moves to a different aerial position to provide a different perspective relative to the tie down strap **850**, and engages select sensors to gather more detailed additional sensor-based inspection information **1865**. As shown in FIG. **18C**, PID **1725** moves to another aerial position to provide yet another perspective relative to the tie down strap **850** (an exemplary inspection point), and again engages select sensors to gather more detailed additional sensor-based inspection information **1870**. Such additional sensor-based inspection information **1865**, **1870** may include still images and/or video imagery, which are then fed back to the delivery vehicle transceiver **1735** and shown on display **1410**. Specifically, as shown in FIG. **18D**, a live-feed video **1890** may be shown in one frame **1875** on display **1410** while still images **1895** may be shown in another frame **1880**. Flight personnel may interactively control PID **1725** while viewing the live-feed video **1890** in order to refine what additional sensor-based inspection information is gathered. Thus, the flight personnel can then better view and review the tie down strap **850** as positioned on shipping item **845** and can make a verification result determination—e.g., about whether the extent the tie down strap **850** has moved as indicated by the video inspection information **1890** and still imagery **1895** is, in fact, problematic and needs addressing or whether such movement is sufficiently small or minor indicative of continued safe operation of the aircraft.

Depending upon the particular inspection point at issue, the system may use different sensors, different perspectives, and/or different limits for the additional sensor-based inspection information gathered in a verified inspection. For

example, a verification command sent by delivery vehicle transceiver **1735** to PID **1725** may identify parameters that have PID **1725** using a depth sensor to surface map the area around the inspection point at issue as part of the verified inspection. In another example, the verification command may identify parameters that have PID **1725** using an ultrasonic transducer as another type of sensor that uses sound waves to map surfaces, which can help validate or supplement data received by a depth sensor that maps the area around the inspection point at issue.

For example, as shown in FIG. **18E**, PID **1725** has deployed its onboard depth sensor to map the relevant area around the tie down strap **850** that was identified in the potential adverse inspection condition. Such a mapping may be performed from multiple vantage points or perspectives relative to the location of the tie down strap **850**. As such, the mapping information may be used, in this example, to generate a three-dimensional (3D) model of the current state of that inspection point, such as exemplary 3D model **1896** shown in frame **1897** of an interactive touchscreen display **1410** on delivery vehicle transceiver **1735**. Personnel operating the delivery vehicle transceiver **1735** may select different onscreen touch icons **1898** to manipulate and move the 3D model **1896** on display **1410** (without requiring remote control or interacting further with PID **1725**). In this manner, such personnel operating the delivery vehicle transceiver **1735** may zoom in and out, and change perspectives when investigating the potential adverse inspection condition related to the tie down strap **850** used on shipping item **845** as part of a verified inspection.

While the example shown and explained above used delivery vehicle transceiver **1735** as the particular transceiver interacting with PID **1725** related to conducting a verified inspection, those skilled in the art will appreciate that other transceivers may be substituted for transceiver **1735** (such as mobile interactive radio-based transceivers **1200**, **1205**, and **1210** that may communicate with each other, PID **1725**, and/or delivery vehicle transceiver **1735**). For example, mobile interactive radio-based transceiver **1210** may be a ruggedized radio-based tablet or smartphone used by logistics personnel responsible for loading and unloading shipping items (such as item **845**) within aircraft **100**. Mobile interactive transceiver **1210** may operate the same as delivery vehicle transceiver **1735** described above in FIGS. **17-18E** related to verified inspections and having the mobile interactive transceiver **1210** interacting with PID **1725** in the manner described above. Alternatively, an embodiment may deploy mobile interactive transceiver **1210** where delivery vehicle transceiver **1735** operates as a communication hub related to verified inspections conducted by PID **1725** and interactive user input and displayed verification related additional sensor-based inspection information are received and shown on mobile interactive transceiver **1210**, as shown in FIG. **18F**.

In light of the example described above relative to FIGS. **17-18F**, details about an exemplary drone-based system used to conduct a verified inspection of a delivery vehicle (e.g., an aircraft, a trailer and related motorized vehicle, a marine vessel, and a railroad car) may be further explained. An embodiment of such a system may include a paired inspection drone and a display-enabled transceiver (such as PID **1725** and delivery vehicle transceiver **1735** that has display **1410**). The inspection drone is exclusively paired to the delivery vehicle and has one or more sensors (such as a still image camera, a video camera, and/or a depth sensor) used to gather inspection information related to parts of the delivery vehicle. As part of this system, the paired inspection

drone aerially inspects targeted inspection points defined in an inspection profile record for the delivery vehicle (e.g., inspection profile record **945**) and corresponding to respective parts of the delivery vehicle (such as a roller **840** or tie down strap **850**). The display-enabled transceiver, which communicates with the paired inspection drone via a wireless communication interface, is operated through an interactive user interface (such as interactive touchscreen display **1410** on transceiver **1735**), which accepts input from the operator and displays notification information, such as that shown on display **1410** in FIGS. **18A-18E**. The display-enabled transceiver may be fixed and part of the delivery vehicle (such as how transceiver **1735** is fixed and located in the control compartment **105** of the aircraft **100**) or it may be implemented as a mobile display-enabled transceiver device physically separate from the delivery vehicle (such as mobile interactive transceiver **1210** operated by logistics personnel related to aircraft **100**).

In this system embodiment, the paired inspection drone executes its inspection program stored onboard. Execution of this particular exemplary inspection program allows for particular functionality in the paired inspection drone so that the drone becomes configured to identify the relevant targeted inspection points from the inspection profile record stored within the paired inspection drone, and then detect sensor-based inspection information using one or more sensors relative to one of the targeted inspection points once the paired inspection drone has aerially moved to a first aerial position proximate that targeted inspection point (such as when PID **1725** has moved to an aerial position proximate tie down strap **850** and then uses a camera to take pictures of the tie down strap **850**). The paired inspection drone then automatically identifies a potential adverse inspection condition regarding that targeted inspection point based upon the detected sensor-based inspection information (such as when PID **1725** automatically identifies there is a potential adverse inspection condition with the tie down strap **850** given the currently gathered image shows movement of the strap relative to a prior inspection of the strap. As such, the paired inspection drone automatically generates and responsively transmits an interactive intervention request to the display-enabled transceiver so that an appropriate level of follow-up inspecting may occur to quickly determine whether the identified potential adverse inspection condition warrants finding that the targeted inspection point needs attention by fixing or replacement. In general, an exemplary interactive intervention request identifies the potential adverse inspection condition regarding the targeted inspection point, which indicates a need for a verified inspection, and requests feedback regarding the one of the targeted inspection points. Such an interactive intervention request may, for example, identify the tie down strap **850** and indicate a need for a verified inspection from the results of comparing sensor-based inspection information gathered (e.g., camera imagery) with reference parameters (e.g., a prior image showing a previous configuration of the tie down strap **850**) with a feedback request. Depending on how the system implements such an interactive intervention request, the feedback request may be automatic and, thus, inherent in any interactive intervention request transmitted by the paired inspection drone given the drone updates its own inspection profile record based on the verification results that follow from the interactive intervention request.

Upon receipt of the interactive intervention request, the display-enabled transceiver displays a notification related to the interactive intervention request on the user interface. Such a displayed notification presents information about the

potential adverse inspection condition regarding the targeted inspection point at issue, the need for the verified inspection regarding that targeted inspection point. For example, as shown in FIG. **18A**, the touchscreen user interface **1410** of transceiver **1735** displays the notification in the form of graphic model **1800** representing aircraft **100** and identifying the targeted inspection point related to the interactive intervention request with a highlighted area **1860** of the aircraft **100** associated with that tie down strap **850**. This presents the highlighted area **1860** as a type of user selectable region of the displayed graphic model **1800** of the aircraft **100**.

When the operator of transceiver **1735** selects this region, the transceiver's user interface detects the selection action and generates a verification command to be sent to the paired inspection drone. The verification command may be generated based upon verification inspection input received by the user interface of the display-enabled transceiver, which may identify parameters related to the task of obtaining additional sensor-based inspection information as part of the verification follow-up inspection performed by the paired inspection drone. For example, the verification inspection input may include parameters identifying the type of sensor to be used, the different vantage points from which the paired inspection drone should be positioned to gather the additional sensor-based inspection information, and/or different reference information to use when gathering the additional sensor-based inspection information. In more detail, the parameters identified by the verification inspection input and related to the additional sensor-based inspection information may include specific autonomous or interactive drone control input for the paired inspection drone that causes the paired inspection drone to gather such additional sensor-based inspection information from a set of different aerial positions relative to and proximate to the inspection point at issue. In an embodiment, the drone control input may put the paired inspection drone in a given orbit moving around the inspection point. In another embodiment, the drone control input may place the paired inspection drone in specific aerial locations so as to view the inspection point from defined perspectives.

In one embodiment, exemplary verification inspection input may be selectively input using the user interface of the display-enabled transceiver; but in another embodiment, the verification inspection input may be a set of default or customizable default settings and parameters for that inspection point.

Once generated, the display-enabled transceiver transmits the verification command to the paired inspection drone, where the paired inspection drone initiates the follow-up verification inspection of the inspection point at issue using the parameters included with the verification command. When or as the paired inspection drone obtains the additional sensor-based inspection information (e.g., using particular sensors as identified by the parameters of the verification command), the paired inspection drone provides the additional sensor-based inspection information back to the display-enabled transceiver as part of the verified inspection. From there, the display-enabled transceiver generates information on its display with the additional sensor-based inspection information. For example, as shown in FIG. **18D**, the displayed additional sensor-based inspection information may include a still image **1895** or video images **1890** (e.g., real-time imagery) related to the targeted inspection point at issue. In a further embodiment, the displayed additional sensor-based inspection information may take the form of three-dimensional mapping related information

about the targeted inspection point at issue, such as the 3D model **1896** shown in FIG. **18E** that may be interactively manipulated to review the potential adverse inspection condition found related to the targeted inspection point at issue.

Based upon the presented additional sensor-based inspection information obtained in this type of follow-up verification inspection using the paired inspection drone, the display-enabled transceiver receives verification result input related to or associated with a result of the verified inspection of the one of the targeted inspection points. For example, an operator of transceiver **1735** may view the video **1890** or still image **1895** or manipulate the 3D model **1896** and determine that the tie down strap **850** has not sufficiently moved to cause a problem with safe operation of the aircraft **100**. With this verification result input, the display-enabled transceiver can then transmit the requested feedback to the paired inspection drone to reflect the operator's determined result of the verified inspection.

A further embodiment of a drone-based system for verified inspection of the delivery vehicle may extend such an exemplary system to include a paired inspection drone, a drone docking station, and one or more display-enabled transceivers (e.g., one of which may be part of the delivery vehicle while another may be a mobile interactive display-enabled transceiver). A first display-enabled transceiver has an interactive user interface (such as a touchscreen display **1410**) and communicates with the paired inspection drone. Similar to what is described above, the system's paired inspection drone (such as PID **1725**) is exclusively paired to the delivery vehicle and operative to aurally inspect a plurality of targeted inspection points corresponding to respective parts of the delivery vehicle. The paired inspection drone includes at least a main housing, an onboard controller, a memory storage, lifting engines, a sensor array, a wireless communication interface, and a drone capture interface disposed on the main house that helps secure the paired inspection drone to the drone docking station. The memory storage is coupled to the onboard controller and maintains an inspection profile record that defines targeted inspection points corresponding to respective parts of the delivery vehicle to be inspected. The lifting engines are each coupled with respective lifting rotors, are fixed to different portions of the main housing, and are responsive to flight control input generated by the onboard controller as part of maintaining a desired flight profile. The sensor array may include one or more different types of sensors coupled to the onboard controller and that (a) detect sensor-based inspection information while the paired inspection drone is airborne and has aurally moved relative to different parts of the delivery vehicle and (b) provide the detected sensor-based inspection information to the onboard controller. The wireless communication interface of the paired inspection drone is also coupled to the onboard controller, and configured to transmit messages (e.g., an inspection notification message or an interactive intervention request message) in response to a transmission command from the onboard controller.

The drone docking station (such as docking station **830** shown in at least FIGS. **8A**, **8B**, and **17**) is fixed to the delivery vehicle. As part of the system, the drone docking station provides a physical mating interface to the paired inspection drone's drone capture interface. In this way, the drone docking station and the drone capture interface can selectively maintain the paired inspection drone in a secured position within a delivery vehicle, such as within a drone storage area **815** of aircraft **100**.

In operation, the onboard controller of the system's paired inspection drone identifies the targeted inspection points

from the inspection profile record stored within the memory storage, causes the lifting engines to position the paired inspection drone at a first aerial position proximate to one of the targeted inspection points, and then proceeds to have one or more sensors detect sensor-based inspection information about the targeted inspection point while the paired inspection drone is in the first aerial position. If the onboard controller of the paired inspection drone automatically identifies a potential adverse inspection condition regarding the targeted inspection point based upon the detected sensor-based inspection information, the controller responsively generates and has the wireless communication interface transmit the interactive intervention request to the first display-enabled transceiver. The system's first display-enabled transceiver (e.g., delivery vehicle transceiver **1735** as shown and explained relative to FIGS. **17-18E**) receives the interactive intervention request from the paired inspection drone, and responds by displaying a notification related to the interactive intervention request on the interactive user interface. In particular, the displayed notification includes a highlighted region of a displayed graphic model (such as model **1800**) representing the delivery vehicle, where the highlighted region (such as region **1860**) is associated with the targeted inspection point identified in the interactive intervention request. The system's first display-enabled transceiver then generates a prompt on its interactive user interface for the need for the verified inspection regarding the one of the targeted inspection points. In response to operator input, the system's first display-enabled transceiver detects a selection action relative to the highlighted region of the displayed graphic model. Such a selection action indicates the operator's desire to begin the verified inspection of the targeted inspection point that has the potential adverse inspection condition.

After reviewing additional sensor-based inspection information gathered as part of the follow-up verified inspection (such as an image related to the targeted inspection point, a video related to the targeted inspection point, and/or other sensor-based information such as three-dimensional mapping information about the targeted inspection point), the interactive user interface of the first display-enabled transceiver receives verification result input related to a result of the verified inspection of the one of the targeted inspection points. Such verification result input may be a detected selection of a button or key that indicates the targeted inspection point at issue needs replacement or maintenance intervention based on the additional sensor-based inspection information shown to the operator of the first display-enabled transceiver, or indicates that the targeted inspection point at issue is in a satisfactory condition after the scrutiny of the automated verification inspection conducted by the paired inspection drone and under the enhanced inspection parameters associated with that verification inspection. Thereafter, the first display-enabled transceiver then transmits a feedback message to the paired inspection drone, where the feedback message corresponds to the result of the verified inspection as reflected by the received verification result input.

Those skilled in the art will appreciate that the first display-enabled transceiver may be a radio-based interactive transceiver fixed to the delivery vehicle, such as exemplary delivery vehicle transceiver **1735**, or may be a mobile display-enabled transceiver separate from the delivery vehicle, such as one of transceivers **1200-1210** as described above. Each of such exemplary mobile display-enabled transceivers may be used in such a system as directly communicating and interacting with the paired inspection

drone. However, in other embodiments, such as that shown in FIG. 18F, exemplary mobile display-enabled transceivers may be deployed as mobile interactive display platforms that rely on and communicate with a primary transceiver on the delivery vehicle when conducting verified inspections of parts.

In more detail and with reference to FIG. 18F showing an extension of this system embodiment, the system may include a second mobile display-enabled transceiver (e.g., the mobile ruggedized tablet-based transceiver **1210** used by logistics personnel loading aircraft **100**) in communication with the first display-enabled transceiver (e.g., delivery vehicle transceiver **1735**). This second mobile display-enabled transceiver is physically separate from the delivery vehicle while the first display-enabled transceiver is disposed in a control compartment of the delivery vehicle, such as compartment **105** where flight personnel operate the aircraft **100**. In this extended system embodiment, the first display-enabled transceiver may be programmatically configured to receive the additional sensor-based inspection information related to the targeted inspection point at issue directly from the paired inspection drone and then provide the received additional sensor-based inspection information to the second mobile display-enabled transceiver. The first display-enabled transceiver may prompt the second mobile display-enabled transceiver for the verification result input based upon at least the additional sensor-based inspection information sent and receive the verification result input from the second mobile display-enabled transceiver. In doing so, the second mobile display-enabled transceiver has a user interface and allows an operator of the second mobile display-enabled transceiver to view a display of the additional sensor-based inspection information on the user interface of the second mobile display-enabled transceiver. In particular, the second mobile display-enabled transceiver may generate a user notification prompting a user of the second mobile display-enabled transceiver to provide the verification result stemming from the verified inspection of the targeted inspection point at issue. With such a prompt appearing on the display of the second mobile display-enabled transceiver, the second mobile display-enabled transceiver receives the verification result input (e.g., yes—the targeted inspection point is within range for safe operation of the delivery vehicle or, no—the targeted inspection point is outside of an acceptable range and needs services or replacement), and transmits the verification result input to the first display-enabled transceiver (which may then relay that verification result back to the paired inspection drone so that the drone may update the drone's inspection profile record accurately).

Additionally, this extended system embodiment may have the verification command generated by the second display-enabled transceiver and sent to the paired inspection drone via the first display-enabled transceiver. As part of the verification command, the interactive drone control input provided to the paired inspection drone by the first display-enabled transceiver (as generated by the second mobile display-enabled transceiver) is based upon remote drone control input provided to the first display-enabled transceiver by the second mobile display-enabled transceiver. In other words, the second mobile display-enabled transceiver may be responsible for generating interactive drone control input remotely through its mobile interactive user interface.

The system embodiments described above may be used as part of a drone-based method embodiment for verified inspection of a delivery vehicle involving an automatically generated interactive intervention request. In more detail,

FIGS. 19A-19B are flow diagrams that collectively illustrate an exemplary drone-based method for conducting a verified inspection of parts of a delivery vehicle that involves an automatically generated interactive intervention request. Referring now to FIG. 19A, method **1900** begins at step **1905** where a paired inspection drone (PID) exclusively assigned to the delivery vehicle identifies multiple targeted inspection points related to the delivery vehicle's parts from an inspection profile record stored within the PID (such as inspection profile record **945** as explained above). The delivery vehicle may be implemented as an aircraft (such as aircraft **100**), a cargo trailer and related motorized vehicle, a marine vessel, or a railroad car.

At step **1910**, method **1900** has at least one sensor on the PID detecting sensor-based inspection information relative to one of the targeted inspection points once the paired inspection drone has aerially moved to a first aerial position proximate the one of the targeted inspection points. For example, as shown in FIG. 17, PID **1725** moves to an aerial position proximate the tie down strap **850** and commences to use a camera sensor on PID **1725** to detect imagery inspection information about the current state of the tie down strap **850** as one of the targeted inspection points on aircraft **100**.

At step **1915**, method **1900** may automatically identify a potential adverse inspection condition related to the targeted inspection point based upon the detected sensor-based inspection information. More specifically, processing and comparison of the currently detected sensor-based inspection information for this targeted inspection point may yield a result that indicates the targeted inspection point is now outside an acceptable range for operation of the delivery vehicle. Thus, if step **1915** fails to automatically identify an inspection condition for the targeted inspection point, step **1915** proceeds directly to step **1920** where the PID moves to the next aerial position for gathering sensor-based inspection information on the next inspection point, and method **1900** then proceeds back to step **1910**. However, if step **1915** does automatically identify an inspection condition based upon the sensor-based inspection information detected (e.g., a comparison of such sensor-based inspection information to reference information for the targeted inspection point indicates an out of range situation), step **1915** proceeds to step **1925**.

At step **1925**, the PID responsively transmits the interactive intervention request to a display-enabled transceiver, which may be part of the delivery vehicle or a mobile interactive radio-based transceiver (such as a wireless enabled tablet device, a smartphone device, or a laptop computer device). In this embodiment, the interactive intervention request at least identifies the potential adverse inspection condition regarding the one of the targeted inspection points. The interactive intervention request may also indicate a need for or explicitly request a verified inspection on the targeted inspection point at issue and request feedback regarding that targeted inspection point.

At step **1930**, the display-enabled transceiver receives the interactive intervention request from the PID and then, at step **1935**, method **1900** has the display-enabled transceiver displaying a notification related to the interactive intervention request on a user interface of the display-enabled transceiver (e.g., an interactive touchscreen display interface). The notification generally presents information on the user interface about the potential adverse inspection condition regarding the one of the targeted inspection points and the need for the verified inspection regarding the one of the targeted inspection points (e.g., via displaying a graphic model representing the delivery vehicle on the user interface

75

of the display-enabled transceiver, where the displayed graphic model identifies the particular targeted inspection point at issue, may highlight an area of the delivery vehicle associated with that targeted inspection point, and may have the highlighted area of the delivery vehicle presented as a selectable region of the displayed graphic model).

At step 1940, method 1900 determines whether the user interface of the display-enabled transceiver has detected a selection action relative to the selectable region of the displayed graphic model. For example, an operator of the display-enabled transceiver 1735 or 1210 may touch a particular section of that transceiver's interactive touch-screen interface as a selection action. Thus, if the selection action is detected relative to the selectable region of the model, step 1940 proceeds to step 1945. Otherwise, step 1940 proceeds back to step 1935.

At step 1945, the display-enabled transceiver generates a verification command based upon verification inspection input received by the display-enabled transceiver. In particular, the verification inspection input received identifies one or more parameters related to the additional sensor-based inspection information to be gathered by the PID. This may be received via further prompted inputs from the operator of the transceiver, or may be received as a set of defaults or customizable default verification inspection parameters on, for example, what sensors to use, how long to measure the inspection point, what reference information to use when conducting the verification inspection, and what the desired aerial position for the PID should be when making the verified inspection. Accordingly, such parameters related to the additional sensor-based inspection information to be gathered as part of the verification inspection may include autonomous or interactive drone control input to be received by the PID from the display-enabled transceiver when the PID is gathering such additional sensor-based inspection information for the verification inspection.

At step 1950, method 1900 has the PID receiving the verification command and, in response, repositioning the PID to begin the verified inspection according to the parameters identified in the verification command. At step 1955, the sensor or set of sensors on the PID detect the additional sensor-based inspection information in accordance with the verification command and parameters identified as part of the command. In more detail, the additional sensor-based inspection information detected may include an image related to the targeted inspection point at issue, a video related to that targeted inspection point, or real-time imagery of an area of the delivery vehicle proximate that targeted inspection point to provide a broader view of the current state of the inspection point and its surroundings. Further still, the additional sensor-based inspection information may be three-dimensional mapping information about the targeted inspection point at issue, such as the 3D model 1896 shown in FIG. 18E where the operator of the display-enabled transceiver 1735 can artificially manipulate this 3D image built from the depth sensor mappings of the targeted tie down strap 850 and its surrounding area. After step 1955, method 1900 transitions through point A on FIG. 19A to point A on FIG. 19B.

At step 1960 on FIG. 19B, method 1900 proceeds with the PID transmitting the additional sensor-based inspection information detected to the display-enabled transceiver. Such a transmission may, in some cases, be a singular event type of transmission. But in other cases and with other types of data, the transmission may be repeated, periodic, or streaming depending on the extent of inspection information desired for this verification inspection. For example, still

76

images may be transmitted by PID back to the display-enabled transceiver one by one or in groups, while video information may be transmitted to the display-enabled transceiver in a streaming format where it may be buffered on the display-enabled transceiver or as a single video recording file. Three-dimensional mapping information may also be transmitted by the PID in parts as the depth sensor is detecting the mapping information or in a final group of three-dimensional mapping information after the PID performs the necessary aerial maneuvers relative to the targeted inspection point to capture depth information on the point itself and the surrounding area.

At step 1965, the display-enabled transceiver has received the additional sensor-based inspection information from the verification inspection and displays the additional sensor-based inspection information relative to the targeted inspection point at issue in response to the detected selection action relative to the selectable region of the displayed graphic model. Thus, if the selection action had the verification inspection to be performed on tie down strap 850, the display-enabled transceiver displays the additional sensor-based inspection on the tie down strap 850 (e.g., still images of the tie down strap 850 from an increased number and variety of different camera angles; video of the tie down strap 850 from one or more camera angles; or a 3D model representing the tie down strap 850 and the proximate area near the strap 850 on packaged shipping item 845 and cargo attachment points 852).

At step 1970, method 1900 may determine if verification result input has been received on the user interface of the display-enabled transceiver, where the verification result input relates to a result of the verified inspection of the one of the targeted inspection points. For example, the verification result input may be provided by the operator of the display-enabled transceiver that is essentially an "intervening" party judging the results of the verification inspection. Such verification result input may reflect or indicate that the particular targeted inspection point at issue is fine and can still be used on the delivery or, alternatively, may reflect or indicate that the particular targeted inspection point at issue has been confirmed or otherwise verified to be in an adverse inspection condition where it is out of range for safe or desired operation of the delivery vehicle.

At step 1975, method 1900 may have the display-enabled transceiver transmitting feedback to the PID, where the feedback corresponds to the result of the verified inspection as reflected by the verification result input received by the display-enabled transceiver. At step 1980, the PID may receive the feedback and then, at step 1985, modify the inspection profile record to reflect the feedback on the verification result input. Thus, the inspection profile record may be updated with the result of the verification inspection so that the inspection profile record keeps a record of what happened relative to inspections of this particular targeted inspection point. Thereafter, step 1985 transitions through point B on FIG. 19B back to point B on FIG. 19A where method 1900 continues at step 1920 to move on to the next targeted inspection point.

Airborne Relocatable Communication Hub Using a Paired Communication Drone

As explained above, an exemplary delivery vehicle may temporarily maintain custody of items being shipped that are broadcast-enabled. In more detail, an embodiment of such a broadcast-enabled item has an associated radio-based device that is configured to communicate with other broadcast-enabled items maintained within the delivery vehicle or radio-based devices external to the delivery vehicle. How-

ever, the broadcast-enabled device may encounter issues with having a limited reception or transmission range. In other words, while two broadcast-enabled items adjacent one another may have no issue communicating with each other, two broadcast-enabled items physically separated from each other by a large enough distance within the delivery vehicle may experience communication difficulties due to inconsistent reception to no reception at all given their respective transmission and reception ranges and the dynamic movement of structure being placed within the delivery vehicle (e.g., placement of one or more metal containers or other items that may shield or otherwise attenuate signals being transmitted a broadcast-enabled item from one side of such structure to another broadcast-enabled item on the other side). For example, a package outfitted with a broadcast-enabled radio transceiver for monitoring the package's contents may be located in the rear of the delivery vehicle's internal shipment storage. This particular broadcast-enabled package may have a limited communication range, and be unable to communicate with other broadcast-enabled items or a central communication station located at the front of the delivery vehicle's internal shipment storage. This inability to communicate with other devices on the delivery vehicle may become even more acute when the broadcast-enabled radio transceiver in the package uses low broadcast power as a way of conserving battery life or when the broadcast-enabled radio transceiver is designed to be low power, such as a Bluetooth® Low Energy (BLE) radio or ZigBee radio transceiver.

To help unconventionally and adaptively facilitate communication between such broadcast-enabled devices and so they may handle longer distances between devices as they are disposed within the delivery vehicle and to accommodate the changing internal environment of the delivery vehicle, embodiments described below generally deploy an aerial communication drone that is exclusively paired with the delivery vehicle and operates in an airborne mode within the delivery vehicle (such as within an internal shipment storage area of the delivery vehicle). This type of exclusively paired drone is advantageously used within the delivery vehicle as a repositionable communication hub to improve the onboard communication environment for what is being transported within the delivery vehicle and for what may be a changing communication environment. Accordingly, the embodiments shown in FIGS. 20-27 and described below provide a technical solution with systems and methods that improve how different broadcast-enabled devices within a delivery vehicle can establish and maintain adequate communications with each other using a paired aerial communication hub drone strategically deployed within the delivery vehicle.

FIG. 20 is a diagram of an exemplary paired aerial drone-based system used to provide an airborne relocatable communication hub within a delivery vehicle for broadcast-enabled devices maintained within the delivery vehicle in accordance with an embodiment of the invention. Referring now to FIG. 20, exemplary aircraft 100 (a type of delivery vehicle) has an exemplary control compartment 105 and an exemplary shipment storage 110. As explained above, the exemplary shipment storage 110 includes interior shipment storage area 120 and drone storage area 115. In the embodiment shown in FIG. 20, a vehicle transceiver 2135 is disposed within the control compartment 105, an internal docking station 2130 is disposed within the drone storage area 115, and an aerial communication drone 2125 is shown as flying within the interior shipment storage area 120 but may be secured on docking station 2130 when not flying.

Aerial communication drone 2125 is exclusively paired to the aircraft 100 and is also referred to as a paired communication hub drone or PHD herein.

In general, vehicle transceiver 2135 of FIG. 20 is a type of central communication station on the aircraft 100 and may be implemented as a standalone radio-based unit or an integrated part of the aircraft's avionics suite. Vehicle transceiver 2135 may be used in embodiments as a network element that may communicate with devices located inside of aircraft 100 (such as broadcast-enabled shipping items 145a-145e) and devices located outside of aircraft 100. For example, vehicle transceiver 2135 may communicate externally disposed radio-based communication devices, such as a local logistics operation server that has a wireless network interface (not shown), a remote cloud-based logistics management system (i.e., a network of remote servers hosted on the Internet that can store, manage, and process shipment management information (such as updated sensor data related to the status of broadcast-enabled shipping items on aircraft 100, and the like)) accessible through a wireless network interface (not shown), or flight operations personnel via other radio-based transceivers (such as handheld transceiver 2300 shown in FIG. 23). In more detail, such radio-based transceivers that communicate with broadcast-enabled devices within the delivery vehicle 100 may be implemented as wireless handheld devices (such as smartphones, ruggedized tablets, UHF/VHF handheld radios, and the like) that communicate with vehicle transceiver 2135 over a compatible communication path (e.g., a designated radio frequency, a cellular network, a data communication network, and the like). Additionally, an embodiment of exemplary vehicle transceiver 2135 shown in FIG. 20 may be used to communicate with internal docking station 2130 (e.g., via a wired or wireless connection) and/or PHD 2125 (e.g., via a wireless connection) disposed within aircraft 100 as described in more detail below. Further still, exemplary vehicle transceiver 2135 may provide an intermediary role between two other devices, such as between the PHD 2125 and a local server or a remote cloud-based logistics management system.

As noted above, exemplary broadcast-enabled shipping items 145a-145e may communicate with each other and with exemplary vehicle transceiver 2135 in an embodiment. In general, exemplary broadcast-enabled shipping items 145a-145e may include packaged or unpackaged items being transported alone or as part of a group of items (e.g., the group of items 145b-145e strapped and fixed relative to shipping pallet 150 or a group of items maintained within a single packaged shipping item, such as a crate, box, or other logistics container). Likewise, those skilled in the art will appreciate that a shipping item may be implemented with a unit load device (ULD) used with aircraft-based logistics operations and, when equipped with a broadcast-enabled device, exemplary ULD 2145 becomes a type of broadcast-enabled shipping item.

Exemplary broadcast-enabled shipping items 145a-145e as well as exemplary broadcast-enabled ULD 2145 (a type of broadcast-enabled shipping container) may be deployed in some embodiments within interior shipment storage area 120 as intercommunicating devices. For example, such broadcast-enabled shipping items 145a-145e and exemplary broadcast-enabled ULD 2145 may be configured, via their respective radios, to broadcast signals related to the condition of the respective item or items being shipped and function as different network elements at different levels of a hierarchically structured communication network. Exemplary broadcast-enabled shipping items 145a-145e and ULD

2145 may accomplish such broadcast functionality with a radio-based wireless transmitter or transceiver and that can broadcast messages about, for example, the condition of item (e.g., an environmental condition of the item using one or more sensors on the device) without being polled or interrogated to do so. In particular, such radio-based devices deployed as part of the broadcast-enabled shipping items **145a-145e** and ULD **2145** may, for example, transmit or receive Bluetooth®, Zigbee, cellular, or other wireless formatted signals. Such devices may be attached or otherwise secured to the shipping item, included in a package with the shipping item, or embedded as part of the package or packaging material used with the shipping item.

Exemplary internal docking station **2130** shown in FIG. **20** is structurally similar to internal docking stations **130** and **830** described above and shown relative to FIGS. **4A** and **4B**. As such, docking station **2130** uses a physical docking interface (similar to PDI **415**) that facilitates maintaining PHD **2125** in a secure position on the station **2130**, an electronic charging connection interface (similar to ECCI **440**) that can provide power to PHD **2125**, and an electronic data connection interface (similar to EDCI **435**) that can provide a wired bi-direction data link with PHD **2125**. Docking station **2130** may also be implemented to communicate with vehicle transceiver **2135**—e.g., via a wired data connection (similar to the wired connection of communication interface **430**) to transceiver **2135** and/or a wireless communication path (accessed via a similar wireless interface part of communication interface **430**) to vehicle transceiver **2135**. Thus, docking station **2130** may be deployed as yet another type of broadcast-enabled device that operates as a network element of networked broadcast-enabled devices.

Exemplary PHD **2125** shown in FIG. **20** may be initially secured to exemplary docking station **2130** within the drone storage area **115** as a linked part of aircraft **100**. In general, PHD **2125** is a paired aerial communication drone that travels with the aircraft **100** (or other type of delivery vehicle, such as a trailer hauled by a truck, a train car moved by a locomotive on a railway system, or a marine vessel that has an internal storage compartment or hold for transporting broadcast-enabled items). Furthermore, exemplary PID **2125** is configured with hardware similar to IMD **125** and PID **825** (as described above) with the exception of the sensors carried on IMD **125** and PID **825**, which are basically replaced with a wireless communication hub interface that can establish one or more wireless data communication paths to different broadcast-enabled devices within the aircraft **100**, such as to ULD **2145** and BESI **145d**. In this way, PHD **2125** operates as an airborne relocatable communication hub deployed within such a delivery vehicle that enhances how broadcast-enabled devices may communicate while being maintained within the delivery vehicle and as the interior configuration of the shipment storage of the delivery vehicle changes with new items that may inhibit or interfere with communications between such broadcast-enabled devices.

In more detail, as shown in FIG. **21**, exemplary PHD **2125** includes similar core parts as explained and shown for IMD **125** and PID **825**, such as a main housing **200**, an onboard controller (OBC) **2100** disposed within the main housing, a memory storage **315** coupled to the OBC **2100**, and multiple lifting engines **210a**, **210b** that are coupled with respective lifting rotors **205a**, **205b** fixed to a different portions of the main housing **200**. Each of the lifting engines on PID **2125** is responsive to flight control input generated by the OBC **2100** as part of maintaining a desired flight profile according to flight profile data **2155**. As part of the exemplary PHD

2125, the OBC **2100** generally controls autonomous flying and docking of the drone **2125** as well as communication hub management tasks related to broadcast-enabled devices located within the shipment storage area **120** using multi-transceiver communication hub interface **2160** and communication hub management program **2150**.

In some embodiments, OBC **2100** may be implemented with a single processor, multi-core processor, or multiple processors and have different programs concurrently running to manage and control the different autonomous flying/docking and internal communication hub management tasks. For example, in the embodiment shown in FIG. **21**, flight/docking control and monitoring operations may be divided between onboard flight controller (OFC) **305** and an onboard communication management processor (OCP) **2110**. In such an embodiment, OFC **305** and OCP **2110** may have access to the same memory, such as memory storage **315** or, alternatively, OBC **2100** may be implemented with separate dedicated memories that are accessible by each of OFC **305** and OCP **2110**. Those skilled in the art will appreciate that memory accessible by OFC **305** may have different accessibility and size requirements compared to memory accessible by OCP **2110** given the different memory demands for the different responsibilities. Furthermore, OFC **305** and OCP **2110** may include peripheral interface circuitry that couples the processing element(s) to the different onboard peripheral circuitry, such as the GPS **350**, inertial measurement unit **355**, the proximity sensors **215a**, **215b**, the electronic speed controllers **360a**, **360b** that control each lifting engine **210a**, **210b**, and the like.

In general, exemplary multi-transceiver communication hub interface **2160** includes multiple independent radio-based transceivers controlled by the OBC **2100** (e.g., by OCP **2110** when executing the communication hub management program **2150**) that collectively provide a communication access and extension functionality between two or more broadcast-enabled devices. Essentially, the OBC **2100** is configured to cause interface **2160** to establish different wireless data communication paths with different broadcast-enabled devices so that the interface **2160** may couple the paths with the broadcast-enabled devices so as to allow the devices to connect and communicate. Such connections may appear as peer-to-peer connections for devices at the same network level or wireless access point connections to a higher network level in a hierarchically structured communication network. For example, an exemplary multi-transceiver communication hub interface **2160** to be used during flight of the PHD **2125** may be implemented with a MIMO type (multiple in, multiple out, multiple antenna technology) communication transceiver disposed on PHD **2125** and coupled to the OBC **2100**. Such an exemplary multi-transceiver communication hub interface **2160** may use one or more different communication protocols, such as a Wi-Fi communication protocol (e.g., supporting an IEEE 802.11 a/b/g/n and 802.11ac standard), a cellular communication protocol, a Bluetooth® communication protocol, or a Zigbee communication protocol. When coupling different protocols, the multi-transceiver communication hub interface **2160** uses an onboard protocol converter (implemented in hardware or firmware) to transform communications of data and commands (including coding, framing, and timing) between the distinct protocols. Using such a converter, the exemplary multi-transceiver communication hub interface **2160** may bridge communications between different broadcast-enabled devices even when the devices use different communication protocols in their respective paths to the PHD **2125**.

81

Referring back to FIG. 21 and consistent with the discussions above relative to IMB 125 and PID 825, the operating system 320 stored in PHD 2125 may provide basic functions, such as program task scheduling, executing of application program code (such as exemplary communication hub management program 2160), and controlling lower level circuitry (e.g., registers, buffers, buses, counters, timers, and the like) on OCP 2110 that interface with other peripheral circuitry onboard PHD 2125 (such as the multi-transceiver communication hub interface 2160, proximity sensors 215a, 215b, the electronic docking connection 235, GPS 350, IMU 355, ESC 360a, 360b, and DCI 370).

Once operating system 320 is loaded, exemplary communication hub management program 2160 may load and be executed as part of implementing a method for adaptively deploying an airborne relocatable communication hub within a delivery vehicle, such as aircraft 100, that improves communication between broadcast-enabled devices maintained within the delivery vehicle. Exemplary communication hub management program 2150 is a set of executable instructions in the form of one or more machine-readable, non-transient program code modules or applications. The program code module(s) may be loaded and executed by OBC 2100 (or by OCP 2110 when flight control is dedicated to a separate OFC 305) to adapt the PHD 2125 into an unconventionally configured aerial communication hub apparatus exclusively paired to the aircraft 100 as a linked part of the aircraft that travels with the aircraft during shipment operations providing quick and assured inspection functionality for the aircraft wherever the aircraft is located. This specially configured OBC 2100 of PHD 2125, as described in more detail herein as a part of an embodiment, implements operative process steps and provides functionality that is unconventional, especially when the overall steps that provide extended communication access functionality using the PHD 2125 are considered collectively as a whole. Such a specially adapted and configured paired communication hub drone (e.g., PHD 2125) helps, as a part of an embodiment, to improve how broadcast-enabled devices on the delivery vehicle (e.g., radio-based transceivers associated with shipping items (such as the transceivers in BESI 145a-145e) and associated with shipping containers (such as the transceiver in ULD 2145)) communicate with each other while being disposed in the delivery vehicle and as the storage within the delivery vehicle may change presenting further difficulties to maintaining adequate communications between such devices.

In addition to the exemplary communication hub management program 2150, memory storage 315 of PHD 2125 also maintains flight profile data 2155. Flight profile data 2155 comprises information that defines how the PHD 2125 is to be flying. This data may include navigational data on an airborne monitoring path for the drone 2125 to transit, as well as flight control setting information to use when generating flight control input for the ESCs 360a, 360b. In some embodiments, remote flight control commands may be received by PHD 2125 and kept as a type of flight profile data 2155 that provides the OFC 305 with flight control input to control aerial movement of the PHD 2125. In other embodiments, OFC 305 is able to generate the flight control input autonomously to enable the PHD 2125 to self-control aerial movements of the aerial communication drone from the secured position on the internal docking station to at least the first deployed airborne position. Thus, PHD 2125 maintains and uses flight profile data 2155 as part of moving about the

82

interior 110 of aircraft 100 when providing relocatable communication hub services for broadcast-enabled devices maintained on aircraft 100.

Using components shown in FIGS. 20 and 21 and described above, an exemplary embodiment may be described in more detail of an airborne drone-based system that adaptively provides communication hub services within a delivery vehicle. In particular, such an exemplary system adaptively provides communication hub services within the delivery vehicle to broadcast-enabled devices maintained within the delivery vehicle and essentially includes internal docking station 2130 and PHD 2125 as described above. In operation, the OBC 2100 of PHD 2125 executes at least the communication hub management program 2150 in order to adaptively provide such relocatable communication hub services within the aircraft 100 (as a type of delivery vehicle). In more detail, the OBC 2100 of PHD 2125 is configured and operative to transition from at least a low power state to an active power state and then cause the DCI 370 of PHD 2125 to automatically uncouple PHD 2125 from a secured position on the internal docking station 2130 fixed within the delivery vehicle 100 once the PHD 2125 transitions to the active power state. The OBC 2100 of PHD 2125 (or OFC 305 of PHD 2125) changes the desired flight profile to cause the lifting engines 210a, 210b to move PHD 2125 from the secured position on the internal docking station 2130 to a deployed airborne position within an interior shipment storage area 120 of the aircraft 100. For example, as shown in FIG. 20, exemplary PHD 2125 has moved from being secured to docking station 2130 to being airborne at a deployed position within the internal shipment storage area 120 of aircraft 100 located above and between ULD 2145 and BESI 145d. Such a movement from the docking station 2130 to an airborne deployed position within and relative to aircraft 100 may occur when aircraft 100 is in motion (e.g., during taxi on the ground or when airborne) or when the aircraft 100 is not moving (e.g., is being loaded, unloaded, or just sitting on the tarmac of an airport).

Once at this deployed position relative to the aircraft 100, the OBC 2100 of PHD 2125 causes its onboard communication hub interface 2160 to establish a first wireless data communication path to one of the broadcast-enabled devices on the aircraft 100—such as the broadcast-enabled device associated with UDL 2145 (denoted by the triangular symbol within ULD 2145). The OBC 2100 of PHD 2125 then causes its onboard communication hub interface 2160 to establish a second wireless data communication path to another of the broadcast-enabled devices on the aircraft 100—such as the broadcast-enabled device associated with BESI 145d. Thereafter, the OBC 2100 of PHD 2125 causes its onboard communication hub interface 2160 to couple the first wireless data communication path and the second wireless data communication path. This has a tangible result of adaptively facilitating communications between the broadcast-enabled device on ULD 2145 and the broadcast-enabled device associated with BESI 145d. This may be especially advantageous because, for example, direct communications between the broadcast-enabled device on ULD 2145 and the broadcast-enabled device associated with BESI 145d may not be possible given the respective devices may be geographically separated by a large enough distance relative to their respective transmission and reception ranges. Furthermore, in another example, direct communication between the broadcast-enabled device on ULD 2145 and the broadcast-enabled device associated with BESI 145d may be hindered or rendered impossible when BESI 145a is placed in-between ULD 245 and BESI 145d (e.g., a dynamic

change in the configuration occurs with respect to what is maintained within the shipment storage area **120**, which may alter the communication environment and related connectivity for different broadcast-enabled devices within area **120**).

FIG. **22** is a diagram of another exemplary paired aerial drone-based system used to provide an airborne relocatable communication hub within a delivery vehicle between other types of broadcast-enabled devices within aircraft **100**. Referring now to FIG. **22**, the illustrated exemplary paired aerial drone-based system includes a central communication station **2200** disposed within aircraft **100** that may communicate with vehicle transceiver **2135** (similar to basic transceiver **135** or display enabled interactive vehicle transceiver **1335** as described above). Central communication station **2200** may be deployed in this embodiment as a hub that may forward data from vehicle transceiver **2135** or as a hub to an external communication device (not shown), such as a satellite or other remote communication transceiver. Further, central communication station **2200** may be used to directly communicate with any of the broadcast-enabled devices on the aircraft **100** (such as BESI **145d** as shown in FIG. **22**), but may also interact with PHD **2125** when direct communication with BESI **145d** is hindered or not possible. As such, central communication station **2200** may operate as one of the broadcast-enabled devices on aircraft **100** and the OBC **2100** of PHD **2125** causes its onboard communication hub interface **2160** to couple a wireless data communication path with the central communication station **2200** with a second wireless data communication path established with another broadcast-enabled device (such as BESI **145d** shown in FIG. **22**). Likewise, another embodiment may deploy vehicle transceiver **2135** as one of the broadcast-enabled devices on the aircraft that communicates with BESI **145d** via two wireless data communication paths adaptively established and coupled by PHD **2125**.

FIGS. **23A** and **23B** are diagrams of another exemplary paired aerial drone-based system used to provide an airborne relocatable communication hub within aircraft **100** where at least one of the broadcast-enabled devices maintained within the aircraft **100** is a mobile personal communication device **2300** in accordance with an embodiment of the invention. Referring now to FIG. **23A** in particular, the illustrated embodiment may deploy mobile personal communication device **2300** as one of the broadcast-enabled devices on the aircraft **1000** that communicates with BESI **145d** via two wireless data communication paths adaptively established and coupled by PHD **2125**. An exemplary mobile personal communication device **2300** may be implemented similar to radio-based transceivers **1200**, **1205**, and **1210** as described above. As such, for example, the mobile personal communication device **2300** shown in FIG. **23A** may be implemented as a ruggedized radio-based tablet or smartphone used by aircraft crew personnel and carried with them while performing duties within aircraft **100**.

However, changes in the configuration of what is stored within aircraft **100** may dynamically create undesirable communication environments that further hinder communications along the coupled first and second wireless communications paths that are coupled by PHD **2125**. For example, as shown in FIG. **23B**, aircraft **100** may receive BESI **145a**, which has been placed between BESI **145d** and mobile personal communication device **2300** (operating as an exemplary broadcast-enabled device). The material making up BESI **145a** may, as a result, cause attenuation and shielding relative to the communication path established between PHD **2125** and BESI **145d**. Thus, a further system embodi-

ment may have PHD **2125** adaptively reposition itself upon detecting such a change in the configuration of what is stored within aircraft **100**. In more detail, the OBC **2100** of PHD **2125** may be operative and configured to cause the multi-transceiver communication hub interface **2160** to actively monitor the strength of communications received from the different coupled broadcast-enabled devices (such as mobile personal communication device **2300** and/or BESI **145d**) so that PHD **2125** may detect any change in such signal strengths. When a sufficient change in signal strength is detected relative to one of the broadcast-enabled devices, PHD **2125** may then responsively control its lifting engines **210a**, **210b** to move itself from an initial airborne deployed position to a different airborne position where PHD **2125** can better communicate with the broadcast-enabled device experiencing a drop in signal strength (e.g., such as BESI **145d** after BESI **145a** has been placed between ULD **2145** and BESI **145d**). Thus, as shown in FIG. **23B**, PHD **2125** may move and re-position itself as part of such a system embodiment to provide further adaptive communication hub services to different broadcast-enabled devices on aircraft **100** based upon a detect change in the configuration of what is stored within the delivery vehicle.

In another embodiment, both of the broadcast-enabled devices may be mobile personal communication devices and one or more of them may be moving in the delivery vehicle. Here, for example and as shown in FIG. **24**, one of the mobile personal communication devices **2300** may be located within the control compartment **105** of the aircraft **100** while the other mobile personal communication device **2400** may be moving within the shipment storage area **120** of aircraft **100**. This may occur, for example, when the operator of mobile personal communication device **2400** conducts a pre-flight or in-flight inspection of what is stored within area **120**. As the operator of mobile personal communication device **2400** moves within the storage area **120**, direct communications between mobile personal communication device **2400** and mobile personal communication device **2300** may become hindered or otherwise problematic. In this situation, PHD **2125** may relocate to a different deployed airborne position within the interior of the aircraft **100**; establish a wireless data communication path to each of the mobile personal communication devices **2300** and **2400**; and couple the different wireless data communication paths as part of providing a relocatable airborne communication hub service for devices **2300** and **2400**. This different deployed position may continue to be updated as one or more of the devices move (e.g., by monitoring signal strengths from each of devices **2300** and **2400**). Thus, instead of losing communication between device **2300** and **2400** as the operator of device **2400** moves further back into the internal shipment storage area **120** (where more and more shielding structure may be placed between devices **2300** and **2400**), this type of system embodiment that deploys at least a docking station **2130** and PHD **2125** may provide a technical airborne solution within the aircraft **100** to avoid lost communications.

Those skilled in the art will appreciate that embodiments may deploy a paired aerial communication drone (such as PHD **2125**) as part of a network of communicating devices that may have different network levels and where the paired communication drone provides bridging and upper level access point types of functionality as part of the network. For example, FIG. **25A** is a logical diagram illustrating a network level configuration of two such communicating devices—i.e., an exemplary paired aerial communication drone and multiple broadcast-enabled devices maintained

85

within a delivery vehicle in accordance with an embodiment of the invention. As shown in FIG. 25A, the broadcast-enabled devices BESI 145a with BESI 145d are logically disposed at a same network level of a hierarchically structured communication network, but may be sufficiently physically separate so that they are unable to reliably communicate directly with each other or may have structure between them that degrades the electronic reception of one or both of them. As such, an embodiment may have broadcast-enabled devices BESI 145a and BESI 145d each being in communication with each other via different wireless communication paths established and coupled together by PHD 2125. Thus, BESI 145d and BESI 145a are in a peer-to-peer relationship at the same network level of the hierarchically structured communication network, but rely upon the airborne relocatable communication hub services provided by PHD 2125 to realize this peer-to-peer relationship and communicate with each other.

In another example, the broadcast-enabled devices may be logically disposed at different network levels of a hierarchically structured communication network. For example, as shown in FIG. 25B, mobile personal communication device 2300 may be disposed at a higher level of the hierarchically structure communication network of broadcast-enabled devices than BESI 145d. In this example configuration of the devices, PHD 2125 may also be deployed at the higher level and be disposed as to provide airborne relocatable communication hub services to establish different wireless communication paths to device 2300 as well as to BESI 145d, and to couple the communication paths together to allow device 2300 and BESI 145d to communicate while being on different network levels. As such, PHD 2125 may operate as a type of wireless access point for BESI 145d on the lower level of the network so that BESI 145d can communicate with one or more devices at higher levels in the network.

In the example shown in FIG. 25C, PHD 2125 may be deployed at the lower level but provide airborne relocatable communication hub services to establish different wireless communication paths to central communication station 2200 (on the higher network level) and to BESI 145d (on the lower network level), and to couple the communication paths together to allow central communication station 2200 and BESI 145d to communicate while being on different network levels but with PHD 2125 operating as more of a bridging extension device to extend communications out to BESI 145d on the same lower network level. As such, the central communication station 2200 may operate as a type of wireless access point for BESI 145d (as coupled through PHD 2125 operating as an airborne relocatable communication bridge to BESI 145d).

Beyond moving PHD 2125 to accommodate changes in the configuration of what is stored within the storage area 120 of aircraft 100 or movement of at least one of the different broadcast-enabled devices that PHD 2125 may provide adaptive airborne communication hub services to, further embodiments may provide systems and methods that provide an airborne relocatable communication hub within the aircraft 100 for more than two broadcast-enabled devices. For example, FIGS. 26A and 26B are perspective diagrams showing an exemplary paired aerial communication drone (e.g., PHD 2125) at a first deployed airborne position within a delivery vehicle and amidst multiple broadcast-enabled devices maintained within the delivery vehicle in accordance with an embodiment of the invention. Referring now to FIG. 26A, exemplary PHD 2125 is shown in a first deployed airborne position within the aircraft 100

86

with established communications with ULD 2145 and BESI 145a that are then coupled so that ULD 2145 and BESI 145a may communicated.

However, as shown in FIG. 26B, the onboard controller of PHD 2125 may cause PHD 2125 to move so as to accommodate providing aerial communication hub services to one or more of BESI 145c and/or BESI 145d. In more detail, the embodiment shown in FIG. 26B has the onboard controller of the PHD 2125 programmatically operating (e.g., by executing the communication hub management program 2150) to change the desired flight profile for PHD 2125 to causing its lifting engines 210a, 210b to move PHD 2125 from the first deployed airborne position within the interior of the aircraft 100 to a second deployed airborne position closer to at least one of BESI 145c and/or BESI 145d. While at this second deployed airborne position, the onboard controller of PHD 2125 then causes its communication hub interface 2160 to establish a third wireless data communication path to a third of the broadcast-enabled devices within the aircraft 100, such as BESI 145c. Thereafter, PHD 2125 has its communication hub interface 2160 couple the established wireless data communication path with BESI 145c to one or more of ULD 2145 and/or BESI 145a.

Furthermore, in some embodiments, airborne communication hub services may be provided to more than three broadcast-enabled devices using PHD 2125. For example, the onboard controller of PHD may cause its communication hub interface 2160 to establish a fourth wireless data communication path to a fourth of the broadcast-enabled devices within the aircraft 100, such as BESI 145d. Thereafter, PHD 2125 has its communication hub interface 2160 couple the established wireless data communication path with BESI 145d to one or more of ULD 2145, BESI 145a, and/or BESI 145c. In this way, PHD 2125 may move to adaptively facilitate wireless communications amongst different ones of three or more broadcast-enabled devices as an airborne communication hub platform.

In more detail, the PHD 2125 may move to go within range of the other as part of moving on an airborne communication path of waypoints, or in response to a change in what power is received from a particular transmitting BESI (e.g., when structure is moved to cause interference or shielding of between the BESI and the PHD).

As the PHD 2125 establishes wireless communication paths to different broadcast-enabled devices, its onboard communication hub interface 2160 may also collect data generated on of the broadcast-enabled devices and retransmit the collected data to another of the broadcast-enabled devices as part of its aerial communication hub services. Such collected data may include scan data generated by a scanner on the broadcast-enabled device (e.g., scan data related to what is contained within with a shipping container associated with the broadcast-enabled device), sensor data generated by one or more sensors on the broadcast-enabled devices (e.g., temperature, moisture, or other environmental data sensed by an onboard broadcast-enabled devices associated with a packaged item being shipped), and shared data generated in a memory on a broadcast-enabled device representing information provided to that broadcast-enabled device by another broadcast-enabled device.

In a further embodiment of systems and methods for adaptively providing communication hub services within a delivery vehicle using an aerial communication drone (such as PHD 2125), the system may use a type of tether for flight control. In particular, a system embodiment may include the delivery vehicle, an aerial communication drone paired to the delivery vehicle (such as PHD 2125 as described above),

plus a base controller and tether. The base controller (such as base controller **1000** as similarly shown in FIG. **10**) is fixed to the delivery vehicle and provides flight commands to the onboard controller on the aerial communication drone through a tether linking the base controller and the aerial communication drone. In more detail, such a control tether may provide an electrical conduit for data (e.g., flight control data or flight commands) and power related to the aerial communication drone. An exemplary control tether may provide a fiber optic conduit, which allows for movement of information from the aerial communication drone to the base controller. For example, such a control tether having a fiber optic conduit may allow image type of sensor-based inspection information (e.g., video feed data stream or still image pictures) to be moved or otherwise transferred from the aerial communication drone to the base controller. In more detail, the aerial communication drone may include a control receiver coupled to the onboard controller, where the control receiver has an input connected to the control tether. The control receiver as deployed on such an aerial communication drone is configured and operative to receive, for example, a flight command from the base controller on the input and pass the received flight command to the onboard controller (such as the OFC **305** part of the OBC **2100** in PHD **2125**), which then may generate the flight control input for the lifting engines based upon the received flight command.

In another detailed example, the onboard controller of the aerial communication drone (such as the OFC **305** part of the OBC **2100** in PHD **2125**) may responsively generate landing control input for the lifting engines **210a**, **210b** if the aerial communication drone detects that the control tether is broken. In response to detecting the tether is broken (e.g., an anticipated signal or signal level is not received by the control receiver on the drone from the base controller), the landing control input generated by the aerial communication drone facilitates and causes the drone to return to the internal docking station and securing of the drone capture interface on the drone (e.g., DCI **370** on PHD **2125**) to the physical docking interface of the internal docking station. Alternatively, the landing control input generated when detecting the tether is broken may have the drone land in a designated part of the delivery vehicle and wirelessly broadcast a message indicating so, which may be received by vehicle transceiver **2135** or mobile device **2300**.

In still another embodiment, the aerial communication may further include a restrictive tether connected to the aerial communication drone and to the delivery vehicle. In this manner, the restrictive tether may place a control on where the aerial communication drone moves and, as a result, limit movement of the aerial communication drone. Such a restrictive tether may help to avoid unintentional collisions with objects within the delivery vehicle or act as a fallback physical barrier to help limit overlap if an embodiment has multiple aerial communication drones active within the same delivery vehicle.

Thus, various system embodiments have been described that rely on an aerial communication drone (such as PHD **2125**) when adaptively providing communication hub services to one or a multitude of similar or different types of broadcast-enabled devices. Some system embodiments may include the PHD and its associated docking station, while other system embodiments may include the delivery vehicle and its paired PHD. Further system embodiments that provide similar adaptive communication hub services within a delivery vehicle may include the PHD and the delivery vehicle transceiver, which may operate as one of the broad-

cast-enabled devices and provide a communication path outside of the vehicle for the PHD and the other of the broadcast-enabled devices (see FIG. **22**). Indeed, still another system embodiment may include the PHD (such as PHD **2125**), a central communication station disposed within the delivery vehicle (such as central communication station **2200**) where the central communication station may provide a communication path outside of the vehicle for the PHD and other broadcast-enabled devices coupled to the PHD.

FIG. **27** is a flow diagram illustrating an exemplary aerial drone-based method for providing an airborne relocatable communication hub within a delivery vehicle for a plurality of broadcast-enabled devices maintained within the delivery vehicle in accordance with an embodiment of the invention. As discussed above, an exemplary delivery vehicle may be an aircraft (such as aircraft **100**), a trailer capable of being moved by a truck, a train car capable of being moved on a railway system, a marine vessel, or an automotive vehicle (such as a delivery van). And as also discussed above, exemplary broadcast-enabled devices that may use the paired aerial communication drone in such a method may come in different forms, such as an RF transceiver-based device (e.g., a transceiver-based Zigbee device that communicates using IEEE 802.15 formatted communications, a transceiver-based Wi-Fi device that communicates using IEEE 802.11 formatted communications, and the like), a central communication station on the delivery vehicle, a delivery vehicle transceiver disposed in a control compartment (e.g., a cockpit, truck cab, etc.) of the delivery vehicle, a broadcast-enabled shipping container maintained within the delivery vehicle, a broadcast-enabled network device associated with an item being shipped within the delivery vehicle, or a mobile personal communication device (e.g., wireless handheld devices such as smartphones, ruggedized tablets, UHF/VHF handheld radios, and the like). In this method embodiment, consistent with the systems and system components described above, the broadcast-enabled devices that may be coupled by the paired aerial communication drone may be geographically separated and incapable of direct communication with each other without the first wireless data communication path and the second wireless data communication path established by the paired aerial communication drone.

Referring now to FIG. **27**, exemplary method **2700** begins at step **2705** where the aerial communication drone paired with the delivery vehicle (referred to as PHD in FIG. **27**) may receive an activation command while in a secured position within the delivery vehicle. The activation command for the PHD, for example, may be in the form of a wireless message received by PHD **2125** from the internal docking station **2130**, the vehicle transceiver **2135**, central communication station **2200**, or from a radio-based transceiver **2300** operated by personnel within the operational control section of the vehicle or within the internal shipment storage for the vehicle. Alternatively, the activation command may be received in the form of a time-based command generated onboard the PHD **2125** where, for example, the PHD may be deployed to activate from the secured position so that the airborne relocatable communication hub services provided to the broadcast-enabled devices within the delivery vehicle may occur after recharging of PHD **2125**. In other words, the PHD **2125** may recharge while on internal docking station **2130** and, upon detecting a threshold charging status (which may operate as the activation command), deploy from the docking station **2130**.

Generally, steps 2710 through 2720 prepare and deploy the PHD within the delivery vehicle. In particular, at step 2710, method 2700 continues with the PHD transitioning from at least a low power state to an active power state as part of deploying into the interior of the delivery vehicle. The low power state of the PHD may be a complete shut off condition where the PHD is unpowered. In other embodiments, the low power state may be a sleep type of state where some circuitry within the PHD is off (e.g., the lifting engines 210a, 210b of PHD 2125 shown in FIG. 21) while another subset of the onboard circuitry remains powered on (e.g., GPS 350 and IMU 355 to help avoid delays prior to lift off from the docking station 2130). When transitioning to the active monitoring state, where the PHD will be ready for airborne communication hub activities within the shipment storage of the delivery vehicle, the PHD prepares to separate from the internal docking station.

At step 2715, method 2700 continues by automatically uncoupling the PHD from a secured position on an internal docking station fixed within the delivery vehicle once the PHD transitions to the active power state. For example, PHD 2125 may automatically uncouple from the internal docking station 2130 as a precursor to flying into the internal shipment storage 120 shown in FIG. 20. In this embodiment, the PHD's landing gear (similar to landing gear 220a, 220b shown in FIG. 4A) separates from being mated with the securing clamps (similar to the securing claims 405a, 405b shown in FIG. 4B) of the docking station 2130 to accomplish such automatic uncoupling. This may be implemented by articulating the landing gear articulating the securing clamps, or both the landing gear and the securing clamps being moved to articulate to different positions that, as a result, uncouple the PHD 2125 from docking station 2130 depending on the complexity of the PHD, docking station, and anticipated vibrational environment within the drone storage area 115.

At step 2720, method 2700 continues with the PHD moving from the secured position on the internal docking station to a first deployed airborne position within an interior of the delivery vehicle. Moving off the docking station to the first deployed airborne position may be done in response to receiving a flight command to redirect aerial movement of the PHD from being on the docking station to be aloft and flying to the first deployed position. In some embodiments, such a flight command may be received over a control tether connected to the PHD (similar to tether 1005 shown in FIG. 10) or may be received wirelessly through the PHD's multi-transceiver communication hub interface (such as interface 2160 on PHD 2125).

At step 2725, method 2700 continues with the PHD establishing a first wireless data communication path to a first of the broadcast-enabled devices within the delivery vehicle, such as ULD 2145 as shown in FIG. 20. At step 2730, method 2700 has the PHD establishing a second wireless data communication path to a second of the broadcast-enabled devices within the delivery vehicle, such as BESI 145d as shown in FIG. 20. Such communication paths may be a common wireless data communication protocol (e.g., a 2G/3G/4G/5G cellular communication protocol, a Bluetooth communication protocol, a Wi-Fi communication protocol, a Zigbee communication protocol, and the like). However, in other embodiments the multi-transceiver communication hub interface 2160 of PHD 2125 may deploy different types of transceivers establish communication paths with different broadcast-enabled devices using different wireless communication protocols and use a protocol converter device installed as part of the communication hub

interface 2160 to help manage the coupling of differently formatted wireless communication paths (as performed in step 2735).

At step 2735, method 2700 continues with the PHD coupling the first wireless data communication path and the second wireless data communication path for at least the first of the broadcast-enabled devices and the second of the broadcast-enabled devices. As noted, this may be accomplished, in particular, using such an embedded protocol converter device deployed within the PHD's multi-transceiver communication hub interface. The two coupled broadcast-enabled communication devices may be logically disposed at a same network level of a hierarchically structured communication network (e.g., in a peer-to-peer relationship at the same network level of the hierarchically structured communication network), or be logically disposed at different network levels of the network where (e.g., where the first of the broadcast-enabled devices and the second of the broadcast-enabled devices are coupled by the aerial communication drone operating as a wireless access point for the first of the broadcast-enabled devices). Furthermore, those skilled in the art will appreciate that at least the steps 2725-2735 may be performed as the delivery vehicle is in motion and while the PHD is airborne within the delivery vehicle.

In some embodiments, the coupling of communication paths done by PHD at step 2735 (as well as the below described steps 2775 and 2785) allows for communications off the delivery vehicle. In particular, a further embodiment of step 2735 may have the PHD couple one of the broadcast-enabled devices to a delivery vehicle transceiver operating as one of the broadcast-enabled device (and which is in communication with a remote transceiver external to the delivery vehicle over an external wireless data communication path). In this manner, the delivery vehicle transceiver effectively couples the first wireless data communication path (established between it and the PHD) and the external wireless data communication.

Moving forward, method 2700 continues to step 2740 where the PHD may collect data generated on the first of the broadcast-enabled devices. This type of data generated on the first of the broadcast-enabled devices may include scan data, sensor data, or shared data. In more detail, scan data may be generated by a scanner on the first of the broadcast-enabled devices, such as barcode data generated by a laser scanner component on a broadcast-enabled barcode device. Sensor data may, for example, be generated by one or more environmental sensors on the first of the broadcast-enabled devices (e.g., temperature sensors, light sensors, moisture sensors, motion sensors, and the like). Shared data may be generated in a memory on the first of the broadcast-enabled devices, and represent information provided to that first broadcast-enabled device by another broadcast-enabled device. For example, ULD 2145 may include a first broadcast-enabled device having shared data in its memory representing information provided by a broadcast-enabled device embedded in a package within ULD 2145. The broadcast-enabled device in the package within ULD 2145 may have temperature information generated by onboard temperature sensors, and provide that temperature information to the ULD's broadcast-enabled device, which then is collected by the PHD 2125. Thus, if the PHD collects such data from the first of the broadcast-enabled devices in step 2740, then the PHD retransmits the collected data to the second of the broadcast-enabled devices at step 2745. Otherwise, method 2700 proceeds from step 2740 directly to step 2750.

At step 2750, method 2700 continues with the PHD determining whether it has received a flight command that may redirect the drone to another airborne position. If so, then step 2750 moves directly to step 2765. But if not, then step 2750 proceeds to step 2755 where the PHD monitors for changes that impact communications with the first of the broadcast-enabled devices. In more detail, at step 2755, exemplary method 2700 continues with the PHD monitoring a first strength level of what is received from the first of the broadcast-enabled devices over the first wireless data communication path. Then, at step 2760, method 2700 has the PHD detecting if there is a threshold drop in the first strength level of what is received from the first of the broadcast-enabled devices as monitored in step 2755. For example, the threshold drop in the first strength level may be associated with a changed configuration of what is maintained within the delivery vehicle. A configuration of what is maintained within the delivery vehicle may change, which then causes the threshold drop in signal strength resulting from the placement of attenuating structure between the first of the broadcast-enabled devices and the PHD. In other words, changes to the physical environment between the first broadcast-enabled device and the PHD may cause interference or attenuation on the first wireless data communication path. Such changes may come from movement of the first broadcast-enabled device relative to the PHD (which may thrust different structure in a line of sight distances between the first broadcast-enabled device and the PHD), or may come from placing new attenuating structure between the first broadcast-enabled device and the PHD. Upon detecting such a threshold drop at step 2760, method 2700 proceeds to step 2765. Otherwise, method 2700 proceeds back to step 2740. Those skilled in that art will understand that steps 2755 and 2760 may also be performed relative to the second of the broadcast-enabled devices as well in some embodiments.

At step 2765, a change in aerial position is warranted due to a flight command or as a result of detecting lower signal strengths from one of the broadcast-enabled devices coupled by the PHD. Thus, method 2700 continues at step 2765 with the PHD moving from the first deployed airborne position within the interior of the delivery vehicle to a second deployed airborne position. Such a second deployed airborne position may be one of a number of airborne positions on an airborne communication path flown by the PHD within the interior of the delivery vehicle. For example, PHD 2125 may typically fly on an airborne communication path above the shipping items maintained within the internal shipment storage area 120, such that PHD 2125 may move to a position closer to BESI 145d after BESI 145a is placed between mobile device 2300 and BESI 145d as shown in FIG. 23 B. Similarly, in another example, PHD 2125 may move to a position closer to mobile device 2400 as the operator of device 240 moves within the internal shipment storage area 120 away from the initial position of PHD 2125 as shown in FIG. 24.

At this second deployed airborne position, step 2770 of method 2700 has the PHD establishing a third wireless data communication path to a third of the broadcast-enabled devices within the delivery vehicle. For example, as shown in FIG. 26 B, PHD 2125 has moved to the second deployed airborne position and may establish another communication path to another broadcast-enabled device, such as BESI 145c. Then, at step 2775, method 2700 has the PHD coupling the first wireless data communication path and the third wireless data communication path. Alternatively, step 2775 may couple the second and third wireless data communications paths or couple the first, second, and third

wireless data communication paths together. In this manner, the third broadcast-enabled device (e.g., BESI 145c shown in FIG. 26B) may communication with one or more of the first two broadcast-enabled devices.

At step 2780, method 2700 continues with the PHD establishing a fourth wireless data communication path to a fourth of the broadcast-enabled devices within the delivery vehicle (such as BESI 145d shown in FIG. 26B). Then, at step 2785, method 2700 has the PHD coupling the third wireless data communication path and the fourth wireless data communication path by the aerial communication drone operating as the airborne relocatable communication hub for at least the third of the broadcast-enabled devices and the fourth of the broadcast-enabled devices.

Those skilled in the art will appreciate that method 2700 as disclosed and explained above in various embodiments may be implemented by an apparatus, such as exemplary PHD 2125, running an embodiment of communication hub management program code 2150, and as a part of a system including the internal docking station 2130 and PHD 2125 or a system that includes the delivery vehicle 100 and the PHD 2125. Such code 2150 may be stored on a non-transitory computer-readable medium in the PHD, such as memory storage 315 as shown on FIG. 21. Thus, when executing code 2150, the OBC 2100 (or OCP 2110) of PHD 2125 (in cooperation with other circuitry onboard the PHD 2125, such as the multi-transceiver communication hub interface 2160) may be operative to perform certain operations or steps from the exemplary methods disclosed above, including method 2700 and variations of that method.

Enhanced Positioning of a Paired Aerial Communication Hub Drone

As noted above, there are times when an exemplary paired aerial communication hub drone (i.e., an exemplary PHD) may be flown, redirected, or repositioned to a different aerial deployed position so that the PHD may more effectively link two or more wireless devices. For example, a communications environment relative to the PHD's delivery vehicle may dynamically change, which may cause problems on where to most effectively position the PHD. Items placed within the delivery vehicle may interfere with communications between broadcast-enabled wireless devices on the delivery vehicle or the devices themselves may be moving within or relative to the delivery vehicle. In another example, the PHD may detect two such wireless devices that should be linked, but the PHD may currently be in an inconvenient position to reliably establish and couple the wireless devices. In such an environment, linking wireless devices using the PHD may be better accomplished with intelligent positioning of the PHD based on having the PHD perform certain types of assessments while airborne. Thus, a further set of embodiments involves enhanced airborne relocatable communication hub systems and improved methods for positioning an airborne relocatable communication hub that supports multiple wireless devices.

Referring back to FIG. 21, exemplary PHD 2125 is shown as a type of communication drone apparatus that may be further enhanced as part of an embodiment so that it can advantageously and intelligently repositions itself while supporting wireless devices disposed within a delivery vehicle. As explained above, exemplary PHD 2125 includes lifting engines 210a, 210b that are responsive to flight control input generated by the onboard controller 2100 as part of maintaining a desired flight profile within the delivery vehicle (such as aircraft 100). In an embodiment of PHD 2125, repositioning may generally be based upon a comparison of connection signal strengths for different signals

detected by multi-transceiver communication hub interface **2160** as the PHD **2125** executes an enhanced embodiment of communication hub management program **2150**. As noted above, implementations of exemplary communication hub management program **2150** may be a set of executable instructions in the form of one or more machine-readable, non-transient program code modules or applications. The communication hub management program **2150** adapts the PHD **2125** into an unconventionally configured aerial communication hub apparatus exclusively paired to the aircraft **100** as a linked part of the aircraft that travels with the aircraft during shipment operations providing improved repositionable airborne communication hub services to wireless devices within and around the delivery vehicle. This specially configured OBC **2100** of PHD **2125**, as described in more detail herein as a part of an embodiment, implements operative process steps and provides functionality that is unconventional, especially when the overall steps that provide extended communication access functionality using the PHD **2125** and how it can be intelligently repositioned to solve a technical communication issue. In other words, a specially adapted and configured paired communication hub drone (e.g., PHD **2125**) helps, as a part of an embodiment, to improve how wireless devices in and around the delivery vehicle (e.g., radio-based transceivers associated with shipping items (such as the transceivers in **BESI 145a-145e**) and associated with shipping containers (such as the transceiver in **ULD 2145**)) communicate with each other while being disposed in or being around the delivery vehicle.

In an exemplary apparatus embodiment, PHD **2125** may be deployed to include at least an aerial drone main housing (such as housing **200**), an onboard controller disposed within the housing (such as OBC **2100**), multiple lifting engines (such as engines **210a, 210b**), and a communication hub interface (such as multi-transceiver communication hub interface **2160**). Generally, this PHD **2125** controls and uses its communication hub interface **2160** in this repositioning embodiment to detect one or more signals broadcast from the wireless devices in or around the delivery vehicle, compare such signals, change the PHD's flight profile to reposition the PHD based on the comparison, and then link the wireless devices via wireless data communication paths to the wireless devices. Such wireless devices may, for example, include a central communication station on the delivery vehicle (e.g., station **2200** or vehicle transceiver **2135**), a broadcast-enabled shipping container (e.g., **ULD 2145**), a broadcast-enabled network device associated with an item being shipped within the delivery vehicle (e.g., **BESI 145d**), or a mobile personal communication device (e.g., devices **2300, 2400**).

In more detail, as the onboard controller **2100** of PHD **2125** executes the communication hub management program **2150** in this embodiment, the onboard controller first changes the desired flight profile to cause the lifting engines to move the PHD from a secured position within an interior of the delivery vehicle to a first deployed airborne position within a different part of the interior of the delivery vehicle (such as in the position shown in **FIG. 24** where PHD **2125** may have moved from a secured position on docking station **2130** to the illustrated airborne position of PHD **2125** above **ULD 2145** within the interior shipment storage **120** of aircraft **100**). At this first deployed airborne position, the onboard controller of the PHD receives a first signal from the communication hub interface. This first signal is broadcast by a first wireless device and detected by the communication hub interface. The onboard controller then receives

a second signal from the communication hub interface, where the second signal is broadcast by a second wireless device and detected by the communication hub interface. With these two detected signals, the onboard controller compares their respective connection signal strengths (e.g., power levels as detected by multi-transceiver communication hub interface **2160**). Based upon the comparison of connection signal strengths, the onboard controller can change the desired flight profile to cause the lifting engines to reposition the PHD to a second deployed airborne position within the delivery vehicle. For example, when the first connection signal strength is lower than the second connection signal strength, the PHD may reposition to a different deployed airborne position closer to the first wireless device and not as close to the second wireless device. In a more detailed embodiment, the lifting engines reposition the PHD to the second deployed airborne position based upon a detected balance between the first connection signal strength and the second connection signal strength as the PHD moves within the delivery vehicle. In other words, the PHD may iteratively monitor the connection signal strength of each signal while moving so as to balance those signal strengths. Further embodiments may balance and attempt to move to a second position that minimized the balanced connection signal strengths.

Thereafter, the onboard controller causes the communication hub interface to link the first wireless device and the second wireless device after the aerial communication drone is repositioned at the second deployed airborne position. Thus, this apparatus embodiment of PHD **2125** enables an intelligent physical movement and repositioning of the PHD that supports linking the two wireless devices and maintaining that link in an improved way that solves a technical problem dealing with how and where to position such a paired airborne communication hub drone device when actively and dynamically supporting different wireless devices in and around the delivery vehicle.

In a further embodiment of such a PHD apparatus, repositioning may be based on comparing three signals from three devices. For example, the onboard controller may further receive a third signal from the communication hub interface, where the third signal was broadcast by a third wireless device and detected by the communication hub interface. Then, as part of repositioning, the onboard controller may cause the lifting engines to reposition the PHD to a third deployed airborne position within the delivery vehicle based upon a comparison of the first connection signal strength, the second connection signal strength, and a third connection signal strength for the third signal. In other words, this third deployed airborne position may be a point within the delivery vehicle where the communication hub interface detects a balance between the first connection signal strength, the second connection signal strength, and the third connection signal strength.

In still another embodiment of such a PHD apparatus, adaptive repositioning may be implemented when one of the wireless devices changes signal strength. In more detail, as the PHD is airborne and has linked the first and second wireless devices, the communication hub interface may detect a change in the first connection signal strength. This may, for example, be due to a change in what may be stored within the delivery vehicle or if the first wireless device is moving. As such, the onboard controller may be responsive to the detected change in the first connection signal strength to alter the desired flight profile and cause the lifting engines to reposition the PHD to a third deployed airborne position

based upon a comparison of an updated value of the first connection signal strength and the second connection signal strength.

In yet another embodiment, adaptive repositioning may be implemented when both wireless devices change signal strength. In more detail, the PHD's communication hub interface may be further operative to detect a first change in the first connection signal strength and a second change in the second connection signal strength. The onboard controller may be responsive to the detected first change and second change to then alter the desired flight profile and cause the lifting engines to reposition the PHD to a third deployed airborne position based upon a comparison of a first updated value of the first connection signal strength and a second updated value of the second connection signal strength. Such changes may, for example, be due to changes within the delivery vehicle or movement of the different wireless devices relative to the current location of the PHD and its communication hub interface or an altered broadcast signal level as changed by the broadcasting device.

Such a PHD-based apparatus embodiment that repositions based on comparing connection signal strengths may be further used as part of a system embodiment. Such an enhanced airborne relocatable communication hub system generally includes a delivery vehicle and that delivery vehicle's paired aerial communication drone. The delivery vehicle (e.g., aircraft **100** as shown in FIGS. **20**, **22**, **23A**, **23B**, and **24**) maintains multiple wireless devices while transporting the wireless devices. The delivery vehicle has an interior storage area (such as shipment storage **120**) for maintaining the wireless devices and a drone storage area (such as drone storage area **115**) disposed within the delivery vehicle. The system's paired aerial communication drone (referred to as PHD) can be secured within the drone storage area and may be implemented consistent with the apparatus embodiments described above as having at least an onboard controller, lifting engines, and a communication hub interface. The system's PHD generally operates to detect signals from different wireless devices, compare the connection signal strength of such detected signals, and reposition the PHD based on that comparison before linking the two wireless devices as described in more detail above. Thus, such an enhanced airborne relocatable communication hub system collectively provides a movable storage system that has a dynamically repositionable PHD that enhances how wireless devices maintained within the storage system may communicate with each other.

Consistent with the exemplary enhanced aerial communication drone apparatus that supports wireless devices disposed within and near a delivery vehicle and the exemplary enhanced airborne relocatable communication hub system as described above, a further embodiment may take the form of a drone-based method for repositioning the airborne relocatable communication hub drone while providing communication hub services to the wireless devices. In particular, FIG. **28** is a flow diagram illustrating an improved method for enhanced positioning of an airborne relocatable communication hub (e.g., PHD **2125**) supporting a group of wireless devices and based on connection signal strength in accordance with an embodiment of the invention. Such wireless devices may, for example, be on a delivery vehicle (e.g., aircraft **100**) and include a central communication station on the delivery vehicle (e.g., station **2200** or vehicle transceiver **2135**), a broadcast-enabled shipping container (e.g., ULD **2145**), a broadcast-enabled network device associated with an item being shipped within the delivery vehicle (e.g., BESI **145d**), or a mobile personal

communication device (e.g., devices **2300**, **2400**) operating within or near the delivery vehicle. Another exemplary wireless device that may interact with the airborne relocatable communication drone or PHD may be a broadcast-enabled network device associated with a fixed physical location, such as a wireless access point device disposed at the fixed physical location within a building (e.g., a warehouse, storage hanger, and the like).

Referring now to FIG. **28**, exemplary method **2800** begins at step **2805** where the aerial communication drone operating as the airborne relocatable communication hub moves to a first deployed airborne position. The aerial communication drone (such as PHD **2125** shown in FIG. **21**) may be exclusively paired to specific delivery vehicle (such as aircraft **100**). As such, moving the aerial communication drone may be done by moving to a deployed airborne position within a delivery vehicle as the first position.

At step **2810**, method **2800** has the aerial communication drone monitoring for broadcast signals from wireless devices while deployed at the first airborne position. At step **2815**, method **2800** proceeds by detecting a first signal broadcast by a first of the wireless devices using a communication hub interface on the aerial communication drone, such as the multi-transceiver communication hub interface **2160** on PHD **2125**. When this first signal is detected, step **2815** proceeds to step **2820**. Otherwise, step **2815** proceeds back to step **2810** to continue monitoring for such a first detected signal. At step **2820**, method **2800** continues by detecting a second signal broadcast by a second of the wireless devices using the communication hub interface on the aerial communication drone. When this second signal is detected, step **2820** proceeds to step **2825**. Otherwise, step **2820** remains searching for the second detected signal.

At step **2825**, two different signals from two different wireless devices have been detected and method **2800** uses the onboard controller of the aerial communication drone (such as OBC **2100** of PHD **2125**) to compare a first connection signal strength for the first signal and a second connection signal strength for the second signal. The connection signal strength may, for example, be an absolute power level as measured by the aerial communication drone's communication interface or an RSSI level indicative of how well the drone is receiving the related signal from the particular wireless device.

At step **2830**, method **2800** proceeds with repositioning the aerial communication drone operating as the airborne relocatable communication hub to a second deployed airborne position based upon the comparison of the first connection signal strength and the second connection signal strength. For example, PHD **2125** may compare the different connection signal strengths of the first and second signals as the PHD **2125** is moving. In other words, the PHD may compare such connection signal strengths while moving as a type of feedback, which has the effect of improving a balance between the first and second connection signal strengths as the PHD approaches the second deployed airborne position. Thus, when there is an equal balance of connection signal strengths, the PHD may be considered to have been repositioned at the second deployed airborne position.

At step **2835**, method **2800** proceeds with the aerial communication drone linking the first of the wireless devices and the second of the wireless devices using the communication hub interface on the aerial communication drone once repositioned at the second deployed airborne position. Such linking may allow signals of the same or different format to effectively let information flow from the

first wireless device to the second wireless device and vice versa by leveraging use of the aerial communication drone as intelligently positioned to improve the reliability and robust nature of such linked information flow from the second deployed airborne position. In one embodiment, the linking in step **2845** has the communication hub interface establishing a peer-to-peer connection between the first and second wireless devices. In another embodiment, the linking in step **2845** has the communication hub interface establishes a wireless access point connection from the first wireless device to the second wireless device

In general, steps **2840** through **2855** of an embodiment of method **2800** further account for changes in the connection signal strengths. In more detail, at step **2840**, method **2800** proceeds with detecting a change in the first connection signal strength. The detected change in the first connection signal strength may be caused by and correspond to movement of the first of the wireless devices relative to the communication hub interface on the aerial communication drone. For example, as shown in FIG. **24**, mobile personal communication device **2400** may be moving within the internal shipment storage **120** of aircraft **100**, which may cause PHD **2125** to detect a change (higher or lower) of the connection signal strength of signals received from mobile personal communication device **2400**.

At step **2845**, method **2800** proceeds to compare an updated value of the first connection signal strength for the first signal and the second connection signal strength for the second signal, and then at step **2850**, reposition the aerial communication drone operating as the airborne relocatable communication hub to a third deployed airborne position based upon the comparison of step **2845**. Then, at step **2855**, method **2800** links the first wireless device and the second wireless device using the communication hub interface on the aerial communication drone once repositioned at the third deployed airborne position.

In some embodiments of method **2800**, the aerial communication drone (PHD) may interact with three or more different wireless devices. For example, a further embodiment of method **2800** may have the aerial communication drone detecting a third signal broadcast by a third wireless device using the communication hub interface on the aerial communication drone. As such, the comparing of step **2825** may be implemented as comparing the first connection signal strength, the second connection signal strength, and a third connection signal strength for the third signal. The results of this comparison may then be used as a basis for repositioning the aerial communication drone to another deployed airborne position where the three different connection signal strengths may be within a tolerable range or substantially balanced.

Furthermore, an embodiment of method **2800**'s steps **2840-2855** may be modified to handle when both wireless devices change signal strength, which may be attributed to movement of the first and second wireless devices (e.g., when they are mobile devices, such as mobile personal communication device devices **2300**, **2400**). As such and in that modified method, the aerial communication drone may detect a first change in the first connection signal strength, detect a second change in the second connection signal strength, and then compare a first updated value of the first connection signal strength and a second updated value for the second connection signal strength. This comparison of both updated values (given the dynamic situation of where both devices are located or how both devices may be transmitting), may be used to reposition the aerial communication drone operating as the airborne relocatable com-

munication hub to a fourth deployed airborne position. Once repositioned at the fourth deployed airborne position, the aerial communication drone may link the first and second wireless devices using the communication hub interface on the aerial communication drone.

Those skilled in the art will appreciate that method **2800** as disclosed and explained above in various embodiments may be implemented by an apparatus, such as exemplary PHD **2125** as already described above, running an embodiment of communication hub management program code **2150**, and as a part of a system including the internal docking station **2130** and PHD **2125** or a system that includes the delivery vehicle **100** and the PHD **2125**. Such code **2150** may be stored on a non-transitory computer-readable medium in the PHD, such as memory storage **315** as shown on FIG. **21**. Thus, when executing code **2150**, the OBC **2100** (or OCP **2110**) of PHD **2125** (in cooperation with other circuitry onboard the PHD **2125**, such as the multi-transceiver communication hub interface **2160**) may be operative to perform certain operations or steps from the exemplary methods disclosed above, including method **2800** and variations of that method.

While the embodiments of method **2800** (and related apparatus and system embodiments) described above involve actively positioning the aerial communication drone based upon detecting and comparing connection signal strengths of different wireless devices, other embodiments of enhanced positioning may reposition or relocate based upon detecting wireless device concentrations. In general, an embodiment may have an aerial communication drone detect different concentrations of wireless devices along an airborne scanning path, and then relocate the drone to the airborne position near the highest concentration of detected wireless devices so that it may be in a position to most effectively serve wireless devices that need to be linked in order to communicate with each other. The drone may periodically resurvey the concentration of detected wireless devices and then update its deployed position near where the updated highest concentration of detected wireless devices are now currently located so to account for movement of wireless devices or changes in what may be shielding such devices.

FIG. **29** is a flow diagram illustrating such an exemplary improved method for enhanced positioning of an airborne relocatable communication hub that supports multiple wireless devices and is based on device concentration in accordance with an embodiment of the invention. As noted above, such exemplary wireless devices may be on a delivery vehicle (e.g., aircraft **100**) and include a central communication station on the delivery vehicle (e.g., station **2200** or vehicle transceiver **2135**), a broadcast-enabled shipping container (e.g., ULD **2145**), a broadcast-enabled network device associated with an item being shipped within the delivery vehicle (e.g., BESI **145d**), or a mobile personal communication device (e.g., devices **2300**, **2400**) operating within or near the delivery vehicle. Another exemplary wireless device that may interact with the airborne relocatable communication drone or PHD may be a broadcast-enabled network device associated with a fixed physical location that may be on the delivery vehicle or simply near the delivery vehicle, such as a wireless access point device disposed at the fixed physical location within a building (e.g., a warehouse, storage hanger, and the like).

Referring now to FIG. **29**, method **2900** begins at step **2905** where the aerial communication drone operating as the airborne relocatable communication hub (generally referred to as "PHD" in FIG. **29**) is moved on an airborne scanning

path with multiple airborne deployed positions, which begins with moving to a first position. For example, the PHD may be deployed within a delivery vehicle where the airborne scanning path is one that extends along different airborne positions within the delivery vehicle's shipment storage area. The delivery vehicle (such as aircraft **100** shown in FIG. **24**), which may be exclusively paired with the PHD, may house a docking station for the PHD (such as docking station **2130**) from which the PHD may initially move as it begins to move to the first position on its airborne scanning path programmed into its flight profile data (such as data **2155** in memory **315** of exemplary PHD **2125**).

In general, steps **2910** through **2920** have the PHD using its communication hub interface to detect different concentrations of the wireless devices as the PHD moves to each of the airborne deployed positions on the airborne scanning path. In particular, at step **2910**, method **2900** has the PHD detecting a concentration of wireless devices at its current airborne deployed position along the programmed airborne scanning path. The detected concentration represents at least a portion of the wireless devices actively broadcasting within a detection range of the communication hub interface proximate to that specific airborne deployed position. At step **2915**, method **2900** determines whether the current position of the PHD on the airborne scanning path is the last position for detecting wireless device concentrations. If so, step **2915** proceeds to step **2925**. But if not, step **2915** proceeds to step **2920** where the PHD moves to the next airborne deployed position on the airborne scanning path before moving again to step **2910** to detect concentrations at that next airborne deployed position. In this manner, an embodiment may have the PHD essentially surveying how the wireless devices it may support are located relative to each other, which may then be used for positioning the PHD when providing airborne communication hub services.

At step **2925**, method **2900** continues with the PHD relocating to the position on the airborne scanning path that was detected to have a highest concentration of the wireless devices within its detection range. Then, at step **2930**, method **2900** has the PHD linking at least two of the wireless devices using the PHD's communication hub interface once repositioned at the airborne deployed position corresponding to the highest concentration of the wireless devices. In more detail, this linking of the wireless devices may establish a peer-to-peer connection between the at least two wireless devices or establish a wireless access point connection from one wireless device to another (e.g., providing access to a higher level in a hierarchical wireless device network).

An embodiment of method **2900** may also respond to the dynamic nature of the wireless devices, which may have the PHD further relocating based on an updated detection of wireless device concentrations. In more detail, method **2900** may continue from step **2930** to step **2935**, where the PHD monitors for a threshold change in the previously detected highest of the concentrations of the wireless devices. For example, while PHD may hover at a position within the internal shipment storage **120** of aircraft **100**, some of the wireless devices may no longer be broadcasting or additional wireless devices within range of PHD **2125** may begin broadcasting that alters the prior concentration detected back in step **2910**. Accordingly, at step **2940**, method **2900** proceeds to back to step **2935** if no threshold change was detected, but proceeds back to step **2910** if there was a threshold change in device concentration. This allows the PHD to re-survey the updated wireless device concentrations. In more detail, the PHD's communication hub inter-

face may redetect the different concentrations of the wireless devices at each of the airborne deployed positions on the airborne scanning path; the PHD then is repositioned to the airborne deployed position having a highest of the updated concentrations of the wireless devices; and then the PHD proceeds to link at least two of the wireless devices using its communication hub interface once repositioned at the airborne deployed position corresponding to the highest updated concentration of the wireless devices.

A further embodiment may also perform this type of update response or at least periodically perform such tasks (rather than wait for a threshold change detection) given the PHD may be unable to sense or detect changes in the number of broadcasting wireless devices outside the PHD's immediate detection range. Thus, an embodiment of method **2900** may skip steps **2935** and **2940** and, instead, simply proceed back to step **2910** from step **2930** after some defined period of time (or once the linked wireless devices are no longer communicating through the airborne communication hub services provided by the PHD).

Those skilled in the art will appreciate that method **2900** as disclosed and explained above in various embodiments may be implemented by an apparatus, such as exemplary PHD **2125**, running an embodiment of communication hub management program code **2150**, and as a part of a system including the internal docking station **2130** and PHD **2125** or a system that includes the delivery vehicle **100** and the PHD **2125**. Such code **2150** may be stored on a non-transitory computer-readable medium in the PHD, such as memory storage **315** as shown on FIG. **21**. Thus, when executing code **2150**, the OBC **2100** (or OCP **2110**) of PHD **2125** (in cooperation with other circuitry onboard the PHD **2125**, such as the multi-transceiver communication hub interface **2160**) may be operative to perform certain operations or steps from the exemplary methods disclosed above, including method **2900** and variations of that method.

While the above described embodiments of method **2900** (and related apparatus and system embodiments) involve actively positioning the aerial communication drone based upon detected concentrations of different wireless devices when moving along an airborne scanning path, another embodiment may strategically position the PHD using a directional antenna deployed as part of the PHD's communication hub interface. In general, an embodiment of the aerial communication drone or PHD may use a communication hub interface having a directional antenna that allows for directional detection of signals broadcast by wireless devices supported by the PHD. For example, the multi-transceiver communication hub interface **2160** of exemplary PHD **2125** may include one or more directional antennas. Such a directional antenna may, for example, be implemented with a beam forming antenna that can electronically steer and change its reception pattern in different directions from a stationary PHD **2125**. However, in another example, the directional antenna may have a characteristic reception pattern that is directional in a fixed direction (not omnidirectional nor electronically steering/shaping the antenna's reception pattern). Here, the PHD **2125** may physically spin or rotate to steer the directional reception pattern in different directions relative to the location of the PHD **2125**. As such, the PHD **2125** is able to survey different concentrations of operating wireless devices in different locations relative to the current deployed airborne position of PHD **2125** without the need to first traverse and move through different positions on an airborne scanning path.

FIG. **30** is a flow diagram illustrating yet another improved method for enhanced positioning of an airborne

101

relocatable communication hub supporting a plurality of wireless devices and based on directional sensing of the wireless devices in accordance with an embodiment of the invention. Again, as noted above, such exemplary wireless devices may be on a delivery vehicle (e.g., aircraft **100**) and include a central communication station on the delivery vehicle (e.g., station **2200** or vehicle transceiver **2135**), a broadcast-enabled shipping container (e.g., ULD **2145**), a broadcast-enabled network device associated with an item being shipped within the delivery vehicle (e.g., BESI **145d**), or a mobile personal communication device (e.g., devices **2300**, **2400**) operating within or near the delivery vehicle. Another exemplary wireless device that may interact with the airborne relocatable communication drone or PHD may be a broadcast-enabled network device associated with a fixed physical location that may be on the delivery vehicle or simply near the delivery vehicle, such as a wireless access point device disposed at the fixed physical location within a building (e.g., a warehouse, storage hanger, and the like).

Referring now to FIG. **30**, method **3000** begins at step **3005** where the aerial communication drone operating as the airborne relocatable communication hub (generally referred to as “PHD” in FIG. **30**) is moved to a first airborne deployed position. For example, the PHD may be deployed within a delivery vehicle’s shipment storage area at an initial central airborne position relative to where wireless devices may be located in the shipment storage area. The delivery vehicle (such as aircraft **100** shown in FIG. **24**), which may be exclusively paired with the PHD, may house a docking station for the PHD (such as docking station **2130**) from which the PHD may initially move as it begins to move to this first airborne deployed position programmed into its flight profile data (such as data **2155** in memory **315** of exemplary PHD **2125**). Such a position may be a geographic coordinate or a relative proximity location as detected by the PHD’s proximity sensors.

In general, step **3010** has the PHD using the directional antenna of its communication hub interface to detect different concentrations of the wireless devices relative to different directions while at the current airborne deployed position. Each detected concentration is thus a portion of the wireless devices actively broadcasting within a detection range of the communication hub interface proximate to the first airborne deployed position.

For example, PHD **2125** may have a phased array directional antenna as part of its multi-transceiver communication hub interface **2160**. Using this phased array directional antenna, the PHD **2125** may perform a focused survey at different directions out from the PHD **2125** looking for a concentration of operating wireless devices (e.g., how many signals are detected from wireless devices operating in that direction from the PHD **2125**). To do this, the PHD **2125** may cause the directional antenna of the communication hub interface **2160** to change the reception pattern so as to focus on a particular direction relative to where the PHD **2125** is currently located. In other words, the PHD **2125** may electronically steer the reception pattern of the communication hub interface’s phased array directional antenna to focus on different directions relative to the PHD’s location. Thus, in this example, PHD **2125** may have the directional antenna focus straight ahead of PHD **2125** to detect a concentration of operating wireless devices at that direction relative to the current airborne deployed position of the PHD **2125**. This may be repeated for other directions—such as to the right, left, and behind the PHD **2125**. Depending on the steering granularity and ability to tightly focus the reception pattern, another embodiment may do this type of electronic

102

steering of the directional reception pattern at set degrees of a compass, such as at every 15 degrees of the 360 degree view relative to the PHD’s location. Thus, such examples allow the PHD to detect wireless device concentrations from different directions without requiring the PHD to rotate in place.

Another embodiment implementing step **3010** may use a fixed directional antenna as part of the PHD’s communication hub interface. Here, the PHD may rotate its airborne hovering position on a vertical axis so as to alter where the fixed directional antenna is aimed as part of detecting wireless device concentrations from different directions. Thus, the PHD in this embodiment physically moves rather than causing the reception pattern to electronically change.

At step **3015**, method **3000** continues with the PHD relocating to a second airborne deployed position based upon a highest of the concentrations of the wireless devices. In particular, the second airborne deployed position to which the PHD is relocated is in the direction corresponding to the highest detected concentration of the wireless devices. In other words, the PHD relocates to this second position in the direction of the highest wireless device concentration. Then, at step **3020**, method **3000** has the PHD linking at least two of the wireless devices using the PHD’s communication hub interface once the PHD has been relocated to this second position. In more detail, this linking of the wireless devices may establish a peer-to-peer connection between the at least two wireless devices or establish a wireless access point connection from one wireless device to another (e.g., providing access to a higher level in a hierarchical wireless device network).

An embodiment of method **3000** may further include steps, such as steps **3025-3035**, that have the PHD reassessing or resurveying the current concentrations of active wireless devices and repositioning based on that updated concentration information. This may be done after a set time at the second position or be based upon monitored activity that indicates a threshold change in actively broadcasting wireless devices at the second position. In more detail, method **3000** moves to step **3025** where the directional antenna coupled to the communication hub interface on the PHD detects updated concentrations of the wireless devices while the PHD is located at the second deployed position. The mechanism and process for detecting updated concentrations is similar to that explained above relative to step **3010**. Each of these updated concentrations corresponds to active and operating wireless devices in a particular direction from the second deployed airborne position.

At step **3030**, method **3000** relocates the PHD to a third airborne deployed position based upon the highest updated concentrations of the wireless devices. Generally, this third airborne deployed position is located in a direction corresponding to the highest detected updated concentrations of the wireless devices.

In a further embodiment, this type of relocation to the third position may be accomplished when the PHD moves from the second airborne deployed position along the direction corresponding to the highest detected updated concentrations of the wireless devices while monitoring for operating wireless devices by the directional antenna coupled to the communication hub interface. Thereafter, this type of sensory focused manner of intelligent airborne relocation then may have the PHD hovering (or transitioning to a hover) at the third airborne position when the PHD has moved at least a predetermined distance from the second airborne position and monitoring for operating wireless devices indicates at least one of the actively operating

103

wireless devices has a received connection strength above a threshold level. Similarly, the PHD may finish relocating by hovering (or transitioning to a hover) at the third airborne position once the PHD has moved along the direction corresponding to the highest detected updated concentrations of the wireless devices and then detected a threshold number of operating wireless devices. At that point, the PHD may stop on its transit out from the second position and along that direction, so as to situate itself in an intelligent manner that compensates for changes in the operating environment of wireless devices.

Thereafter, at step **3035**, method **3000** concludes with the PHD linking at least two of the wireless devices using the PHD's communication hub interface once the PHD has been relocated to this third position. Those skilled in the art will appreciate that the PHD may repeatedly go through such a concentration assessment via direction antenna operations and updating of where to relocate based on the latest assessment in order to actively adapt to a changing environment of operating wireless devices.

Those skilled in the art will also appreciate that method **3000** as disclosed and explained above in various embodiments may be implemented by an apparatus, such as exemplary PHD **2125**, running an embodiment of communication hub management program code **2150**, and as a part of a system including the internal docking station **2130** and PHD **2125** or a system that includes the delivery vehicle **100** and the PHD **2125**. Such code **2150** may be stored on a non-transitory computer-readable medium in the PHD, such as memory storage **315** as shown on FIG. **21**. Thus, when executing code **2150**, the OBC **2100** (or OCP **2110**) of PHD **2125** (in cooperation with other circuitry onboard the PHD **2125**, such as the multi-transceiver communication hub interface **2160** and its directional antenna) may be operative to perform certain operations or steps from the exemplary methods disclosed above, including method **3000** and variations of that method.

In summary, it should be emphasized that the sequence of operations to perform any of the methods and variations of the methods described in the embodiments herein are merely exemplary, and that a variety of sequences of operations may be followed while still being true and in accordance with the principles of the present invention as understood by one skilled in the art.

At least some portions of exemplary embodiments outlined above may be used in association with portions of other exemplary embodiments to enhance and improve logistics using an aerial monitor, inspection or communication drone to enhance monitoring of shipped items in a delivery vehicle, perform various types of inspections of the delivery vehicle, and providing a drone-based airborne relocatable communication hub within a delivery vehicle. As noted above, the exemplary embodiments disclosed herein may be used independently from one another and/or in combination with one another and may have applications to devices and methods not disclosed herein. However, those skilled in the art will appreciate that the exemplary monitor/inspection/communication drone as deployed with a delivery vehicle, systems using such an apparatus, and methods of how such an apparatus may operate as part of a logistics operation as described above provide enhancements and improvements to technology used in logistics and shipment operations, such as loading, unloading, and in-flight monitoring of a delivery vehicle.

Those skilled in the art will appreciate that embodiments may provide one or more advantages, and not all embodiments necessarily provide all or more than one particular

104

advantage as set forth here. Additionally, it will be apparent to those skilled in the art that various modifications and variations can be made to the structures and methodologies described herein. Thus, it should be understood that the invention is not limited to the subject matter discussed in the description. Rather, the present invention, as recited in the claims below, is intended to cover modifications and variations.

What is claimed:

1. A multiple drone-based monitored storage system, comprising:

a shipment storage comprising

a closable entry providing access to within the shipment storage,

an interior shipment storage area within the shipment storage, the interior shipment storage area being accessible through the closable entry and operative to temporarily maintain custody of a plurality of items being shipped within the shipment storage, and a plurality of drone storage areas respectively disposed at different locations within the shipment storage;

a plurality of internal docking stations fixed within respectively different ones of the drone storage areas;

a plurality of internal monitor drones initially disposed on respective ones of the internal docking stations, wherein each of the internal monitor drones having a sensor array that gathers sensory information as the respective internal monitor drone moves within a part of the interior shipment storage area of the shipment storage; and

wherein a first of the internal monitor drones is operative, as part of the system, to

move from a first of the internal docking stations to a first initial airborne position within the shipment storage as part of a first airborne monitoring path within a first part of the interior shipment storage area of the shipment storage, and

aerially monitor a first part of the items being shipped within the interior shipment storage area using the sensor array on the first of the internal monitor drones as the first of the internal monitor drones transits the first airborne monitoring path within the shipment storage from the first initial airborne position;

wherein a second of the internal monitor drones is operative, as part of the system, to

move from a second of the internal docking stations to a second initial airborne position within the shipment storage as part of a second airborne monitoring path within a second part of the interior shipment storage area within the shipment storage, and

aerially monitor a second part of the items being shipped within the interior shipment storage area using the sensor array on the second of the internal monitor drones as the second of the internal monitor drones transits the second airborne monitoring path within the shipment storage from the second initial airborne position; and

wherein one of the first of the internal monitor drones and the second of the internal monitor drones autonomously detects a condition of the items being shipped based upon sensory information generated when monitoring the items being shipped within the interior shipment storage area by the first of the internal monitor drones and the second of the internal monitor drones.

2. The system of claim **1**, wherein the sensor array of at least the first of the internal monitor drones comprises an

105

environment sensor that detects environmental information as the gathered sensory information, wherein the sensed environmental information is relative to a plurality of airborne locations within the shipment storage as the first of the internal monitor drones transits the first airborne monitoring path; and

wherein the first of the internal monitor drones autonomously detects the condition of the items being shipped by being further operative to automatically identify an environmental condition related to the first part of the items being shipped based upon the sensed environmental information.

3. The system of claim 2, wherein the sensor array of the second of the internal monitor drones comprises a second environment sensor that detects environmental information as the gathered sensory information, wherein the environmental information sensed by the second environment sensor is relative to a second plurality of airborne locations within the shipment storage as the second of the internal monitor drones transits the second airborne monitoring path; and

wherein the second of the internal monitor drones autonomously detects the condition of the items being shipped by being further operative to automatically identify an environmental condition related to the second part of the items being shipped based upon the environmental information sensed by the second environment sensor.

4. The system of claim 2, wherein the environmental condition related to the first part of the items being shipped comprises at least one of a movement condition as sensed by at least three from a group consisting of a motion sensor operating as part of the environmental sensor, a light condition as sensed by a light sensor operating as part of the environmental sensor, a sound condition as sensed by a microphone operating as part of the environmental sensor, a temperature condition as sensed by a temperature sensor operating as part of the environmental sensor, a smoke condition as sensed by a smoke sensor operating as part of the environmental sensor, a humidity condition as sensed by a moisture sensor operating as part of the environmental sensor, and a pressure condition as sensed by a pressure sensor operating as part of the environmental sensor.

5. The system of claim 1, wherein the sensor array of at least the first of the internal monitor drones comprises an image sensor that captures a plurality of images of the first part of the items being shipped while the first of the internal monitor drones transits the first airborne monitoring path; and

wherein the first of the internal monitor drones autonomously detects the condition of the items being shipped by being further operative to automatically identify a configuration change as the condition of the first part of the items being shipped based upon a comparison of at least two of the captured images as performed by the first of the internal monitor drones.

6. The system of claim 1, wherein the sensor array of at least the first of the internal monitor drones comprises a depth sensor that maps a configuration of at least the first part of the interior shipment storage area of the shipment storage as the first of the internal monitor drones transits the first airborne monitoring path within the first part of the interior shipment storage area of the shipment storage, the configuration of the first part of the interior shipment storage area represented as a multi-dimensional mapping of at least the first part of the items being shipped within the first part of the interior shipment storage area of the shipment storage; and

106

wherein the first of the internal monitor drones autonomously detects the condition of the items being shipped by being further operative to automatically identify a change in the multi-dimensional mapping of at least the first part of the items being shipped over time as the first of the internal monitor drones repeatedly transits the first airborne monitoring path.

7. The system of claim 1, wherein the sensor array of at least the first of the internal monitor drones comprises a scanning sensor that scans an identification symbol fixed to one of the first part of the items being shipped as the first of the internal monitor drones transits the first airborne monitoring path.

8. The system of claim 7, wherein the identification symbol comprises a barcode symbol identifying shipping information related to the one item.

9. The system of claim 7, wherein the identification symbol comprises a sign affixed to the one item, the sign identifying shipment loading information related to placement of the one item when being shipped within the shipment storage.

10. The system of claim 7, wherein the first of the internal monitor drones is further operative to:

autonomously determine a loading status of the one item based by comparing the identification symbol as scanned by the scanning sensor to a loading plan for the first part of the interior shipment storage area of the shipment storage; and

automatically transmit a loading warning to a transceiver related to the shipment storage when the loading status of the one item indicates the presence of the one item within the interior shipment storage area of the shipment storage is inconsistent with the loading plan.

11. The system of claim 7, wherein the first of the internal monitor drones is further operative to:

autonomously determine a position status of the one item based upon the identification symbol as scanned by the scanning sensor, the identification symbol comprising a directional sign indicating a desired item orientation for the one item, wherein the position status of the one item reflecting whether a current orientation of the identification symbol as scanned is inconsistent with the desired item orientation; and

automatically transmit a positional warning to a transceiver related to the shipment storage when the position status indicates the current orientation of the identification symbol is inconsistent with the desired item orientation.

12. The system of claim 1, wherein the sensor array on the first of the internal monitor drones comprises a radio-based receiver that receives a wireless signal broadcast from a broadcast-enabled item from the first part of the items being shipped as the first of the internal monitor drones transits the first airborne monitoring path; and

wherein the first of the internal monitor drones autonomously detects the condition of the items being shipped by being further operative to automatically identify the condition of at least the broadcast-enabled item based upon the wireless signal received by the radio-based wireless receiver on the first of the internal monitor drones.

13. The system of claim 12, wherein the wireless signal received by the first of the internal monitor drones is broadcast without interrogating the broadcast-enabled item to prompt the broadcast of the wireless signal.

14. The system of claim 1, wherein each of the first of the internal monitor drones and the second of the monitor

107

drones is further operative to transmit a monitoring update message to a transceiver related to the shipment storage, the monitoring update message indicating the autonomously detected condition of the items being shipped.

15. The system of claim 1, wherein at least the first of the internal monitor drones is further operative to:

transmit a monitoring update message to a shipment storage transceiver only if the first of the internal monitor drones autonomously confirms a communication channel to the shipment storage transceiver is active, the monitoring update message indicating the autonomously detected condition of the items being shipped, and

store the monitoring update message within the first of the internal monitor drones for later transmission to the shipment storage transceiver when the first of the internal monitor drones cannot confirm the communication channel is active.

16. The system of claim 1, wherein the shipment storage comprises a storage compartment within an aircraft.

17. The system of claim 16,

wherein the interior shipment storage area comprises a first aircraft belly section within which to store the items being shipped; and

wherein the supplemental interior shipment storage area comprises a second aircraft belly section within which to store the additional items being shipped.

18. The system of claim 17, wherein the items being shipped comprise at least a plurality of unit load device (ULD) containers.

19. The system of claim 18, wherein each of the ULD containers is operative to broadcast a signal for gathering as sensory information by the sensor array without a preliminary interrogation of the ULD container to prompt broadcast of the signal.

20. The system of claim 1, wherein the shipment storage comprises a trailer capable of being moved by a truck.

21. The system of claim 1, wherein the shipment storage comprises a train car capable of being moved on a railway system.

22. The system of claim 1, wherein the logistics operation related to the shipment storage comprises a loading operation of the internal shipment storage area of the shipment storage.

23. The system of claim 1, wherein the logistics operation related to the shipment storage comprises an unloading operation of the internal shipment storage area of the shipment storage.

24. The system of claim 1, wherein the logistics operation related to the shipment storage comprises an in-transit monitoring operation of the internal shipment storage area of the shipment storage while the shipment storage is moving.

25. A multiple aerial drone-based method for monitoring the internal storage contents of a shipment storage, the method comprising the steps of:

(a) moving a first internal monitor drone to a first initial airborne position within the shipment storage as part of a first airborne monitoring path within the shipment storage, the first internal monitor drone being disposed within a first drone storage area of the shipment storage, the first airborne monitoring path corresponding to a first part of an interior shipment storage area within the shipment storage;

(b) moving a second internal monitor drone to a second initial airborne position within the shipment storage as part of a second airborne monitoring path within the shipment storage, the second internal drone being dis-

108

posed within a second drone storage area of the shipment storage, the second airborne monitoring path corresponding to a second part of the interior shipment storage area within the shipment storage;

(c) aerially monitoring a first part of the internal storage contents of the shipment storage with a first sensor array on the first internal monitor drone as the first internal monitor drone transits the first airborne monitoring path within the shipment storage from the first initial airborne position;

(d) aerially monitoring a second part of the internal storage contents of the shipment storage with a second sensor array on the second internal monitor drone as the second internal monitor drone transits the second airborne monitoring path within the shipment storage from the second initial airborne position; and

(e) detecting a condition of the internal storage contents based upon at least one of (1) first sensory information generated when monitoring with the first sensor array of the first internal monitor drone and (2) second sensory information generated when monitoring with the second sensor array of the second internal monitor drone.

26. The method of claim 25, wherein step (a) further comprises selectively uncoupling the first internal monitor drone from a first internal docking station disposed at a first fixed location within the first drone storage area of the shipment storage prior to moving the first internal monitor drone from a first secured position on the first internal docking station to the first initial airborne position; and

wherein step (b) further comprises selectively uncoupling the second internal monitor drone from a second internal docking station disposed at a second fixed location within a second drone storage area of the shipment storage prior to moving the second internal monitor drone from a second secured position on the secured internal docking station to the second initial airborne position.

27. The method of claim 25, wherein step (c) comprises sensing, with the first sensor array, first environmental information as the first sensory information, wherein the first environmental information is relative to a plurality of airborne locations within the shipment storage as the first internal monitor drone transits the first airborne monitoring path within the shipment storage;

wherein step (d) comprises sensing, with the second sensor array, second environmental information as the second sensory information, wherein the second environmental information is relative to a plurality of airborne locations within the shipment storage as the second internal monitor drone transits the second airborne monitoring path within the shipment storage; and wherein step (e) further comprises automatically identifying an environmental condition as the condition of the internal storage contents based upon at least one of the first environmental information and the second environmental information.

28. The method of claim 27, wherein the environmental condition comprises at least one of a movement condition as sensed by a motion sensor operating as at least part of the first sensor array or the second sensor array, a light condition as sensed by a light sensor operating as at least part of the first sensor array or the second sensor array, a sound condition as sensed by a microphone operating as at least part of the first sensor array or the second sensor array, a temperature condition as sensed by a temperature sensor operating as at least part of the first sensor array or the

109

second sensor array, a smoke condition as sensed by a smoke sensor operating as at least part of the first sensor array or the second sensor array, a humidity condition as sensed by a moisture sensor operating as at least part of the first sensor array or the second sensor array, and a pressure condition as sensed by a pressure sensor operating as at least part of the first sensor array or the second sensor array.

29. The method of claim **25**, wherein aerially monitoring the first part of the internal storage contents with the first sensor array in step (c) further comprises capturing, with a first image sensor part of the first sensor array, at least one image of the first part of the internal storage contents from each of a first plurality of airborne locations within the shipment storage as the first internal monitor drone transits the first airborne monitoring path within the shipment storage;

wherein aerially monitoring the second part of the internal storage contents with the second sensor array in step (d) further comprises capturing, with a second image sensor part of the second sensor array, at least one image of the second part of the internal storage contents from each of a second plurality of airborne locations within the shipment storage as the second internal monitor drone transits the second airborne monitoring path within the shipment storage; and

wherein step (e) further comprises automatically identifying the condition of the internal storage contents based upon at least one of the at least one image captured by the first image sensor or the at least one image captured by the second image sensor.

30. The method of claim **29**, wherein step (e) further comprises automatically identifying a configuration change as the condition of the internal storage contents based upon at least one of (1) a comparison of multiple images over time from the first image sensor as the first internal monitor drone repeatedly transits the first airborne monitoring path and (2) a comparison of multiple images over time from the second image sensor as the second internal monitor drone repeatedly transits the second airborne monitoring path.

31. The method of claim **25**, wherein aerially monitoring the first part of the internal storage contents with the first sensor array in step (c) further comprises mapping, with a first depth sensor part of the first sensor array, a first configuration of a first storage area within the shipment storage that maintains the first part of the internal storage contents as the first internal monitor drone transits the first airborne monitoring path within the shipment storage, the first configuration represented as a multi-dimensional mapping of at least the first part of the internal storage contents;

wherein aerially monitoring the second part of the internal storage contents with the second sensor array in step (d) further comprises mapping, with a second depth sensor part of the second sensor array, a second configuration of a second storage area within the shipment storage that maintains the second part of the internal storage contents as the second internal monitor drone transits the second airborne monitoring path within the shipment storage, the second configuration represented as a multi-dimensional mapping of at least the second part of the internal storage contents; and

wherein step (e) further comprises automatically identifying the condition of the internal storage contents based upon at least one of the multi-dimensional mapping of at least the first part of the internal storage contents and the multi-dimensional mapping of at least the second part of the internal storage contents.

110

32. The method of claim **31**, wherein step (e) further comprises automatically identifying a configuration change as the condition of the internal storage contents based upon at least one of (1) a comparison of the multi-dimensional mapping of the first part of the internal storage contents over time and (2) a comparison of the multi-dimensional mapping of the second part of the internal storage contents over time.

33. The method of claim **32** further comprising the step of transmitting a configuration change notification by the first internal monitor drone to a shipment storage transceiver in response to identifying the configuration change when the identified configuration change is based upon the comparison of the multi-dimensional mapping of the first part of the internal storage contents over time.

34. The method of claim **33**, wherein the configuration change notification provides a prompted intervention request message related to the configuration change identified.

35. The method of claim **32** further comprising the step of transmitting a configuration change notification by the first internal monitor drone when the identified configuration change is based upon the comparison of the multi-dimensional mapping of the first part of the internal storage contents over time.

36. The method of claim **35**, wherein the configuration change notification provides a prompted intervention request message related to the configuration change identified.

37. The method of claim **25**, wherein aerially monitoring the first part of the internal storage contents with the first sensor array in step (c) further comprises scanning a first identification symbol fixed to a first item within the first part of the internal storage contents using a first scanner part of the first sensor array of the first internal monitor drone as the first internal monitor drone transits the first airborne monitoring path within the shipment storage;

wherein aerially monitoring the second part of the internal storage contents with the second sensor array in step (d) further comprises scanning a second identification symbol fixed to a second item within the second part of the internal storage contents using a second scanner part of the second sensor array of the second internal monitor drone as the second internal monitor drone transits the second airborne monitoring path within the shipment storage; and

wherein step (e) further comprises automatically identifying the condition of the internal storage contents based upon at least one of the first identification symbol scanned by the first scanner or the second identification symbol scanned by the second scanner.

38. The method of claim **37**, wherein the first identification symbol comprises a first barcode symbol identifying shipping information related to the first item and the second identification symbol comprises a second barcode symbol identifying shipping information related to the second item.

39. The method of claim **37**, wherein the first identification symbol comprises a first sign affixed to the first item where the first sign identifies shipment loading information related to placement of the first item when being shipped within the shipment storage; and

wherein the second identification symbol comprises a second sign affixed to the second item where the second sign identifies shipment loading information related to placement of the second item when being shipped within the shipment storage.

40. The method of claim **37** further comprising the steps of:

111

determining, by the first internal monitor drone, a loading status of the first item based upon comparing the first identification symbol as scanned by the first internal monitor drone to a loading plan for the shipment storage maintained within memory of the first internal monitor drone; and

generating a first loading warning by the first internal monitor drone when the loading status of the first item indicates the presence of the first item within the shipment storage is inconsistent with the loading plan.

41. The method of claim 40 further comprising the step of downloading the loading plan into the memory of the first internal monitor drone.

42. The method of claim 41 further comprising the step of transmitting the first loading warning by the first internal monitor drone to a shipment storage transceiver.

43. The method of claim 40 further comprising the steps of:

determining, by the second internal monitor drone, a loading status of the second item based upon comparing the second identification symbol as scanned by the second internal monitor drone to the loading plan for the shipment storage maintained within memory of the second internal monitor drone; and

generating a second loading warning by the second internal monitor drone when the loading status of the second item indicates the presence of the second item within the shipment storage is inconsistent with the loading plan.

44. The method of claim 43 further comprising the step of downloading the loading plan into the memory of the second internal monitor drone.

45. The method of claim 44 further comprising the step of transmitting the second loading warning by the second internal monitor drone to a shipment storage transceiver.

46. The method of claim 37 further comprising the steps of:

determining, by the first internal monitor drone, a position status of the first item based upon the first identification symbol as scanned by the first internal monitor drone, the first identification symbol comprising a first directional sign indicating a desired item orientation for the first item, and where the position status of the first item reflects whether a current orientation of the first item is inconsistent with the desired item orientation for the first item; and

112

generating a first positional warning by the first internal monitor drone when the position status of the first item indicates the current orientation of the first item is inconsistent with the desired item orientation for the first item; and

transmitting the first positional warning by the first internal monitor drone to a shipment storage transceiver.

47. The method of claim 46 further comprising the steps of:

determining, by the second internal monitor drone, a position status of the second item based upon the second identification symbol as scanned by the second internal monitor drone, the second identification symbol comprising a second directional sign indicating a desired item orientation for the second item, and where the position status of the second item reflects whether a current orientation of the second item is inconsistent with the desired item orientation for the second item; and

generating a second positional warning by the second internal monitor drone when the position status of the second item indicates the current orientation of the second item is inconsistent with the desired item orientation for the second item; and

transmitting the second positional warning by the second internal monitor drone to the shipment storage transceiver.

48. The method of claim 25 further comprising the step of transmitting a monitoring update message to a shipment storage transceiver, wherein the monitoring update message indicates the detected condition of the internal storage contents, the transmitting of the monitoring update message being performed by (1) the first internal monitor drone when the detected condition is based upon the first sensory information and (2) the second internal monitor drone when the detected condition is based upon the second sensory information.

49. The method of claim 25, wherein the shipment storage comprises a storage compartment within an aircraft.

50. The method of claim 25, wherein the shipment storage comprises a trailer capable of being moved by a truck.

51. The method of claim 25, wherein the shipment storage comprises a train car capable of being moved on a railway system.

* * * * *