



US011076028B2

(12) **United States Patent**
Wright et al.

(10) **Patent No.:** **US 11,076,028 B2**
(45) **Date of Patent:** **Jul. 27, 2021**

(54) **SWITCH ASSEMBLY FOR ENGAGING A SWITCH OF AN ELECTRONIC DEVICE**

(71) Applicant: **CATALYST LIFESTYLE LIMITED**,
Hong Kong (CN)

(72) Inventors: **Joshua Wright**, Hong Kong (CN);
June Lai, Hong Kong (CN)

(73) Assignee: **CATALYST LIFESTYLE LIMITED**,
North Point (HK)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/557,364**

(22) Filed: **Aug. 30, 2019**

(65) **Prior Publication Data**

US 2021/0067615 A1 Mar. 4, 2021

(51) **Int. Cl.**

H04M 1/02 (2006.01)
A44B 19/26 (2006.01)
H01H 13/705 (2006.01)
H04B 1/3888 (2015.01)
H04M 1/18 (2006.01)

(52) **U.S. Cl.**

CPC **H04M 1/0249** (2013.01); **A44B 19/265** (2013.01); **H01H 13/705** (2013.01); **H04B 1/3888** (2013.01); **H04M 1/026** (2013.01); **H04M 1/185** (2013.01); **G06F 2200/1633** (2013.01)

(58) **Field of Classification Search**

CPC H04M 1/0249; H04M 1/026; H04M 1/185; H01H 13/705; H04B 1/3888; A44B 19/265; G06F 2200/1633
USPC 455/575.8
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,195,299 A 8/1916 Wachter
1,205,217 A 11/1916 Kaufman
1,986,328 A 1/1935 Dreyfus
2,136,625 A 11/1938 Lasko

(Continued)

FOREIGN PATENT DOCUMENTS

AU 2013101187 A4 10/2013
CN 201042019 Y 3/2008

(Continued)

OTHER PUBLICATIONS

Extended European Search Report for European Application No. 19203848.7 dated Feb. 27, 2020, 9 pages.

(Continued)


Primary Examiner — Eugene Yun

(74) *Attorney, Agent, or Firm* — Dinsmore & Shohl LLP

(57) **ABSTRACT**

A switch assembly for engaging a switch of an electronic device includes a rotatable knob having an axis of rotation, a pin mechanism engaged with the rotatable knob, and a slider body. The pin mechanism includes a pin, the pin being offset from the axis of rotation of the rotatable knob. The slider body is shaped to include a slot in which the pin of the pin mechanism is positioned and a switch recess shaped to receive and selectively contact the switch of the electronic device. Rotation of the rotatable knob in a first direction causes the slider body toward contact with a first portion of the switch to urge the switch into a first position, and rotation of the rotatable knob in a second direction causes the slider body toward contact with a second portion of the switch to urge the switch into a second position.

20 Claims, 8 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2,392,787	A	1/1946	Vermot	6,388,877	B1	5/2002	Canova et al.
D157,606	S	3/1950	Lachman	6,415,138	B2	7/2002	Sirola et al.
3,590,988	A	7/1971	Hollar	6,445,577	B1	9/2002	Madsen et al.
3,737,605	A	6/1973	Tobey et al.	6,456,487	B1	9/2002	Hetterick
3,746,206	A	7/1973	Utz	6,468,619	B1	10/2002	Larroche
3,789,601	A	2/1974	Bergey	6,471,056	B1	10/2002	Tzeng
3,800,525	A	4/1974	Bergey	D465,163	S	11/2002	Bodino
3,992,874	A	11/1976	Collins	D465,330	S	11/2002	Parker
4,236,239	A	11/1980	Imgruth et al.	D470,659	S	2/2003	Story et al.
4,390,288	A	6/1983	Amoux	6,519,141	B2	2/2003	Tseng et al.
D275,822	S	10/1984	Gatland et al.	6,536,589	B2	3/2003	Chang
D278,685	S	5/1985	Suzuki et al.	D472,384	S	4/2003	Richardson
D279,081	S	6/1985	Suzuki et al.	6,568,619	B1	5/2003	Shiga et al.
D283,014	S	3/1986	Suzuki et al.	6,617,973	B1	9/2003	Osterman
4,584,718	A	4/1986	Fuller	6,646,864	B2	11/2003	Richardson
D290,234	S	6/1987	Komatsu	6,659,274	B2	12/2003	Enners
4,703,161	A	10/1987	McLean	6,665,174	B1	12/2003	Derr et al.
D293,417	S	12/1987	Sakamaki	D484,874	S	1/2004	Chang et al.
4,733,776	A	3/1988	Ward	6,701,159	B1	3/2004	Powell
4,736,418	A	4/1988	Steadman	D507,975	S	8/2005	Dreyfuss
4,762,227	A	8/1988	Patterson	D513,123	S	12/2005	Richardson et al.
4,836,256	A	6/1989	Meliconi	6,980,777	B2	12/2005	Shepherd et al.
5,025,921	A	6/1991	Gasparaitis	D513,451	S	1/2006	Richardson et al.
5,092,459	A	3/1992	Uljanic et al.	D514,808	S	2/2006	Morine et al.
D327,646	S	7/1992	Hardigg et al.	D515,588	S	2/2006	Kirkwood
D329,747	S	9/1992	Embree	6,995,976	B2	2/2006	Richardson
D330,329	S	10/1992	Brightbill	D516,309	S	3/2006	Richardson et al.
5,175,873	A	12/1992	Goldenberg et al.	D516,553	S	3/2006	Richardson et al.
D335,220	S	5/1993	Ward et al.	D516,554	S	3/2006	Richardson et al.
5,211,471	A	5/1993	Rohrs	D516,807	S	3/2006	Richardson et al.
5,239,968	A	8/1993	Rodriguez-Amaya et al.	D517,430	S	3/2006	TerMeer et al.
D341,092	S	11/1993	Wild	7,054,441	B2	5/2006	Pletikosa
5,258,592	A	11/1993	Nishikawa et al.	7,069,063	B2	6/2006	Halkosaari et al.
D342,609	S	12/1993	Brightbill	D526,780	S	8/2006	Richardson et al.
5,280,146	A	1/1994	Inagaki et al.	D528,440	S	9/2006	Lovegrove
D347,324	S	5/1994	Dickinson	D528,441	S	9/2006	Burton
D347,732	S	6/1994	Wentz	D528,928	S	9/2006	Burton
D348,472	S	7/1994	Cyfko	D530,079	S	10/2006	Thomas et al.
D351,799	S	10/1994	Bulgari	7,158,376	B2	1/2007	Richardson et al.
D353,048	S	12/1994	VanSkiver et al.	7,180,735	B2	2/2007	Thomas et al.
5,388,692	A	2/1995	Withrow et al.	7,194,291	B2	3/2007	Peng
5,477,508	A	12/1995	Will	D539,671	S	4/2007	Lassigne
5,491,311	A	2/1996	Muscat et al.	D542,524	S	5/2007	Richardson et al.
D381,512	S	7/1997	Green	7,230,823	B2	6/2007	Richardson et al.
5,648,757	A	7/1997	Vernace et al.	7,290,654	B2	11/2007	Hodges
D386,094	S	11/1997	Ventrella	D557,264	S	12/2007	Richardson et al.
D386,611	S	11/1997	Sheu	D557,897	S	12/2007	Richardson et al.
D402,105	S	12/1998	Erickson	7,312,984	B2	12/2007	Richardson et al.
5,850,915	A	12/1998	Tajima	D564,367	S	3/2008	Molyneux
D409,374	S	5/1999	Laba et al.	D581,155	S	11/2008	Richardson et al.
D412,062	S	7/1999	Potter et al.	D581,421	S	11/2008	Richardson et al.
D413,202	S	8/1999	Schmitt et al.	7,449,650	B2	11/2008	Richardson et al.
D413,203	S	8/1999	Zurwelle et al.	D587,008	S	2/2009	Richardson et al.
D419,297	S	1/2000	Richardson et al.	7,495,895	B2	2/2009	Carnevali
D419,767	S	2/2000	Richardson et al.	D589,016	S	3/2009	Richardson et al.
D419,768	S	2/2000	Richardson et al.	D593,319	S	6/2009	Richardson et al.
6,031,524	A	2/2000	Kunert	D593,746	S	6/2009	Richardson et al.
6,041,924	A	3/2000	Tajima	D597,089	S	7/2009	Khan et al.
6,049,813	A	4/2000	Danielson et al.	D597,301	S	8/2009	Richardson et al.
D423,772	S	5/2000	Cooper et al.	7,609,512	B2	10/2009	Richardson et al.
6,068,119	A	5/2000	Derr et al.	D603,602	S	11/2009	Richardson et al.
6,094,785	A	8/2000	Montgomery et al.	D603,827	S	11/2009	Tompkin et al.
D433,798	S	11/2000	Weinstock	D605,850	S	12/2009	Richardson et al.
D439,407	S	3/2001	Parker	7,647,082	B2	1/2010	Holmberg
6,201,667	B1	3/2001	Yamamoto et al.	7,663,879	B2	2/2010	Richardson et al.
6,201,867	B1	3/2001	Koike	7,688,580	B2	3/2010	Richardson et al.
6,215,474	B1	4/2001	Shah	D613,282	S	4/2010	Richardson et al.
6,239,968	B1	5/2001	Kim et al.	7,705,255	B2	4/2010	Yokote
D443,133	S	6/2001	Richardson et al.	D616,430	S	5/2010	Fathollahi
6,273,252	B1	8/2001	Mitchell	D616,879	S	6/2010	Kim et al.
6,301,100	B1	10/2001	Iwata	D622,716	S	8/2010	Andre et al.
6,313,892	B2	11/2001	Gleckman	D623,180	S	9/2010	Diebel
6,313,982	B1	11/2001	Hino	D624,064	S	9/2010	Esposito
6,317,313	B1	11/2001	Mosgrove et al.	D625,303	S	10/2010	Kim
6,349,824	B1	2/2002	Yamada	D627,778	S	11/2010	Akana et al.
				7,889,489	B2	2/2011	Richardson et al.
				7,907,394	B2	3/2011	Richardson et al.
				7,933,122	B2	4/2011	Richardson et al.
				D638,312	S	5/2011	Jacobs

(56)

References Cited

U.S. PATENT DOCUMENTS

D638,324 S	5/2011	Tang	D694,227 S	11/2013	Rayner
7,941,196 B2	5/2011	Kawasaki et al.	D694,244 S	11/2013	Magness et al.
7,946,758 B2	5/2011	Mooring	8,576,031 B2	11/2013	Lauder et al.
D643,029 S	8/2011	Feng	D694,759 S	12/2013	Chang et al.
D645,031 S	9/2011	Richardson et al.	D695,731 S	12/2013	Adami
8,045,323 B2	10/2011	Murakata	D696,234 S	12/2013	Wright
D654,069 S	2/2012	Kwon et al.	8,616,422 B2	12/2013	Adelman et al.
8,143,982 B1	3/2012	Lauder et al.	D697,504 S	1/2014	Yang
8,143,983 B1	3/2012	Lauder et al.	8,624,695 B2	1/2014	Cretella, Jr. et al.
D657,262 S	4/2012	Pulli	D698,772 S	2/2014	Merenda
D657,354 S	4/2012	Kim	D700,598 S	3/2014	Kim
8,164,899 B2	4/2012	Yamaguchi et al.	8,671,553 B1	3/2014	Raisch
D659,691 S	5/2012	Kim et al.	8,675,862 B1	3/2014	Lin
8,208,980 B2	6/2012	Wong et al.	8,676,280 B2	3/2014	Kong
D662,922 S	7/2012	Akana et al.	8,676,281 B1	3/2014	Caulder et al.
D662,923 S	7/2012	Piedra et al.	D703,211 S	4/2014	Weller et al.
D663,263 S	7/2012	Gupta et al.	D703,652 S	4/2014	Melanson et al.
8,253,518 B2	8/2012	Lauder et al.	D703,656 S	4/2014	Witter et al.
D666,924 S	9/2012	Ahlstrom	D704,182 S	5/2014	Smith
8,264,310 B2	9/2012	Lauder et al.	D704,688 S	5/2014	Reivo et al.
8,269,104 B2	9/2012	Choraku et al.	D705,763 S	5/2014	Fastman et al.
D668,660 S	10/2012	Norfolk	8,714,510 B2	5/2014	McCosh et al.
D668,661 S	10/2012	Norfolk	8,718,731 B1	5/2014	Tang
D669,062 S	10/2012	Rothbaum et al.	D706,253 S	6/2014	Simmer
8,289,115 B2	10/2012	Cretella, Jr. et al.	D706,272 S	6/2014	Poon
D670,280 S	11/2012	Rayner	D707,216 S	6/2014	Lee
D670,281 S	11/2012	Corpuz et al.	8,759,675 B2	6/2014	Rajeswaran et al.
D670,702 S	11/2012	Zhang et al.	8,761,388 B2	6/2014	Chen et al.
D671,107 S	11/2012	Rothbaum et al.	D709,057 S	7/2014	Wilson et al.
D671,932 S	12/2012	Azoulay	D709,059 S	7/2014	Kim et al.
D671,933 S	12/2012	Rodgers	D709,060 S	7/2014	Melanson et al.
D672,255 S	12/2012	Zanella et al.	D709,486 S	7/2014	Lin
D672,265 S	12/2012	Pulli	D709,869 S	7/2014	Witter et al.
8,328,008 B2	12/2012	Diebel et al.	8,763,802 B2	7/2014	Ellis-Brown
D673,477 S	1/2013	Szellos	8,770,402 B2	7/2014	Bergreen et al.
D675,210 S	1/2013	Kim	8,774,446 B2	7/2014	Merenda
8,342,325 B2	1/2013	Rayner	8,774,881 B2	7/2014	Johnson
8,344,836 B2	1/2013	Lauder et al.	8,777,003 B2	7/2014	Hong et al.
8,345,412 B2	1/2013	Maravilla et al.	8,780,535 B2	7/2014	Mongan et al.
D675,606 S	2/2013	Adelman et al.	8,787,009 B2	7/2014	Wilson et al.
D676,432 S	2/2013	Hasbrook et al.	D712,890 S	9/2014	McCormac et al.
8,382,059 B2	2/2013	Le Gette et al.	D712,893 S	9/2014	Lee
D677,249 S	3/2013	Li et al.	D712,895 S	9/2014	Lee et al.
D677,250 S	3/2013	Takamoto	D713,833 S	9/2014	Wilkey
D677,251 S	3/2013	Melanson et al.	D713,834 S	9/2014	Almstrom
D678,871 S	3/2013	Mishan et al.	D714,278 S	9/2014	Case et al.
8,390,411 B2	3/2013	Lauder et al.	8,825,124 B1	9/2014	Davies et al.
8,390,412 B2	3/2013	Lauder et al.	D714,769 S	10/2014	Rayner
8,393,464 B2	3/2013	Yang et al.	D714,770 S	10/2014	Nolan et al.
8,395,465 B2	3/2013	Lauder et al.	D714,771 S	10/2014	Rayner
D679,685 S	4/2013	Cox	D715,786 S	10/2014	Lee et al.
D679,714 S	4/2013	Smith et al.	D715,787 S	10/2014	Lee et al.
D680,120 S	4/2013	Cho et al.	D715,788 S	10/2014	Lee et al.
8,433,377 B1	4/2013	Oh et al.	D716,283 S	10/2014	Lee et al.
D683,136 S	5/2013	Wilson et al.	D716,784 S	11/2014	Wen
D683,338 S	5/2013	Wilson et al.	D716,786 S	11/2014	Wilson et al.
8,442,602 B2	5/2013	Wong et al.	D717,678 S	11/2014	Anderssen et al.
8,453,835 B2	6/2013	So	D717,781 S	11/2014	Kim
8,457,701 B2	6/2013	Diebel	D718,291 S	11/2014	Hong
D685,779 S	7/2013	Schriefer et al.	D718,316 S	11/2014	Veltz et al.
D687,026 S	7/2013	Ruvolo	8,879,773 B2	11/2014	Merenda
D687,426 S	8/2013	Requa	D718,756 S	12/2014	Barfoot et al.
D688,582 S	8/2013	Wilson	D718,759 S	12/2014	Barfoot et al.
D688,655 S	8/2013	Rey-Hipolito et al.	D719,143 S	12/2014	Vidovic
8,504,126 B1	8/2013	Maravilla et al.	D719,145 S	12/2014	Barfoot et al.
D688,967 S	9/2013	Wilson	D719,949 S	12/2014	Tussy
D689,852 S	9/2013	Azoulay	8,899,415 B2	12/2014	McCosh et al.
D690,292 S	9/2013	Bibla et al.	D720,739 S	1/2015	Liu
D691,124 S	10/2013	Yang	D721,356 S	1/2015	Hasbrook et al.
D691,990 S	10/2013	Rayner	D721,360 S	1/2015	Laffon de Mazieres et al.
D692,419 S	10/2013	Rayner	D721,685 S	1/2015	Hasbrook et al.
8,544,639 B2	10/2013	Yang et al.	D723,016 S	2/2015	Lee et al.
8,548,536 B1	10/2013	Gunnip	D723,019 S	2/2015	Chan et al.
D693,251 S	11/2013	Anderssen et al.	8,960,421 B1	2/2015	Diebel
D693,801 S	11/2013	Rayner	8,960,634 B2	2/2015	Le Gette et al.
			D723,531 S	3/2015	Katzke
			D724,066 S	3/2015	Fathollahi
			D724,094 S	3/2015	Blochinger et al.
			D725,091 S	3/2015	Wen

(56)

References Cited

U.S. PATENT DOCUMENTS

D725,117 S	3/2015	Melanson et al.	D754,652 S	4/2016	Roberts et al.
8,967,437 B2	3/2015	Wilson	D754,666 S	4/2016	Tiffen et al.
8,983,559 B2	3/2015	Chiu	9,316,344 B2	4/2016	Le Gette et al.
8,989,826 B1	3/2015	Connolly	D755,171 S	5/2016	Bae et al.
D726,172 S	4/2015	Watkins et al.	D755,172 S	5/2016	Lee et al.
D726,173 S	4/2015	Kim et al.	D755,187 S	5/2016	Shannon, III
D726,174 S	4/2015	Wahlin	D756,340 S	5/2016	Babichenko
D727,194 S	4/2015	Wilson	D756,343 S	5/2016	Wall et al.
D727,883 S	4/2015	Brand et al.	D756,344 S	5/2016	Roberts et al.
9,007,758 B2	4/2015	Wilson et al.	D756,345 S	5/2016	Roberts et al.
9,008,725 B2	4/2015	Schmidt	D756,357 S	5/2016	Akana et al.
9,008,738 B1	4/2015	Dong	D757,017 S	5/2016	Sirichai
D729,218 S	5/2015	Wilson et al.	D757,018 S	5/2016	Pearce
D729,785 S	5/2015	Magness et al.	D757,02 S	5/2016	Kanazawa
D729,786 S	5/2015	Lee et al.	D757,703 S	5/2016	Kanazawa
D730,338 S	5/2015	Lee et al.	D757,704 S	5/2016	Roberts et al.
D730,339 S	5/2015	Lee et al.	D759,641 S	6/2016	Lai et al.
D730,341 S	5/2015	Chan et al.	D759,644 S	6/2016	Penn
9,025,948 B2	5/2015	Tages et al.	D759,645 S	6/2016	Penn
9,031,623 B2	5/2015	Yoo	D759,658 S	6/2016	Lai et al.
D731,472 S	6/2015	Lee et al.	D759,725 S	6/2016	Akana et al.
D731,493 S	6/2015	Mills	D761,241 S	7/2016	Nguyen et al.
D731,494 S	6/2015	Barfoot et al.	D761,263 S	7/2016	Brinkman et al.
D732,042 S	6/2015	Chen et al.	D761,780 S	7/2016	Nguyen et al.
9,056,696 B1	6/2015	Reyes	D762,202 S	7/2016	Tseng et al.
D733,696 S	7/2015	Burgett et al.	D762,218 S	7/2016	Sirichai
D735,182 S	7/2015	Watkins et al.	D762,219 S	7/2016	Armstrong et al.
D735,184 S	7/2015	Lee et al.	D762,651 S	8/2016	Edwards et al.
D735,207 S	7/2015	Dahlberg	D763,239 S	8/2016	Chan et al.
9,077,013 B2	7/2015	Huang et al.	D763,264 S	8/2016	Smith et al.
D736,777 S	8/2015	Rayner	D763,853 S	8/2016	Pearce
D737,159 S	8/2015	Akana et al.	D763,854 S	8/2016	Domke et al.
D737,263 S	8/2015	Armstrong et al.	D763,855 S	8/2016	Poon et al.
9,101,184 B2	8/2015	Wilson	D763,856 S	8/2016	Moore
9,107,484 B2	8/2015	Chaney	D764,449 S	8/2016	Chan et al.
D739,768 S	9/2015	Hanshew et al.	D764,472 S	8/2016	Corcoran et al.
9,123,935 B2	9/2015	Huang	D764,474 S	8/2016	Penn
D740,798 S	10/2015	Poon et al.	D764,475 S	8/2016	Penn
D741,726 S	10/2015	Akana et al.	D765,086 S	8/2016	Lee et al.
D742,254 S	11/2015	Greusel et al.	D765,627 S	9/2016	Watt
D742,761 S	11/2015	Grazian et al.	D765,629 S	9/2016	Watt et al.
D742,868 S	11/2015	Odhwani et al.	D765,638 S	9/2016	Gaylord et al.
D742,869 S	11/2015	Odhwani et al.	D765,645 S	9/2016	Kim
D743,388 S	11/2015	Fitzpatrick et al.	D766,248 S	9/2016	Holladay et al.
D743,389 S	11/2015	Akana et al.	D766,249 S	9/2016	Veltz et al.
D744,356 S	12/2015	Akana et al.	9,444,506 B2	9/2016	Lai et al.
D745,421 S	12/2015	Akana et al.	D768,122 S	10/2016	Buffone
D745,505 S	12/2015	Barfoot et al.	D768,612 S	10/2016	Wright et al.
D745,506 S	12/2015	Barfoot et al.	D768,617 S	10/2016	Merenda
D746,275 S	12/2015	Mohammad	D769,880 S	10/2016	Moore et al.
9,223,346 B2	12/2015	Wilson	D770,458 S	11/2016	Corcoran et al.
9,225,377 B1	12/2015	Hart	D771,027 S	11/2016	Prstojevich et al.
D746,707 S	1/2016	Akana et al.	D772,208 S	11/2016	Merenda
D748,083 S	1/2016	Peterson, III	D772,210 S	11/2016	Igarashi
D748,085 S	1/2016	Merenda	D772,854 S	11/2016	Igarashi
D748,612 S	2/2016	Chan et al.	D772,855 S	11/2016	Ju
D748,613 S	2/2016	Sasaki et al.	D772,858 S	11/2016	Hu
D748,614 S	2/2016	Ju	D772,881 S	11/2016	Chang et al.
9,259,076 B2	2/2016	Gayler	D773,448 S	12/2016	Armillotti
9,264,088 B2	2/2016	Wojcik et al.	D773,470 S	12/2016	Akana et al.
9,264,089 B2	2/2016	Tages	D775,113 S	12/2016	Lim et al.
9,267,638 B2	2/2016	Le Gette et al.	D775,114 S	12/2016	Khalili
D750,610 S	3/2016	Chen	D775,132 S	12/2016	Smith et al.
D751,067 S	3/2016	Nousiainen	D775,617 S	1/2017	Samson
D751,550 S	3/2016	Solomon et al.	D775,628 S	1/2017	Brown et al.
D751,558 S	3/2016	Lee	D776,100 S	1/2017	Igarashi
D752,044 S	3/2016	Akana et al.	D776,102 S	1/2017	Kim
D752,579 S	3/2016	Lee	D776,120 S	1/2017	Brown et al.
9,301,414 B2	3/2016	Chao	D776,122 S	1/2017	Akana et al.
D752,996 S	4/2016	Ebersold	D776,123 S	1/2017	Akana et al.
D753,124 S	4/2016	Corcoran et al.	D777,715 S	1/2017	Sawaya
D753,641 S	4/2016	Roberts et al.	D777,719 S	1/2017	Kim
D754,132 S	4/2016	Dahlberg	D777,727 S	1/2017	Maicon et al.
D754,133 S	4/2016	Chen et al.	9,538,675 B2	1/2017	Le Gette et al.
D754,651 S	4/2016	Roberts et al.	D778,273 S	2/2017	Kim
			D778,274 S	2/2017	Lim et al.
			D778,275 S	2/2017	Gabriel et al.
			D779,473 S	2/2017	Lee
			9,568,954 B2	2/2017	Lauder et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

D780,738 S	3/2017	Barfoot et al.	2008/0068934 A1	3/2008	Hiranuma et al.
D781,277 S	3/2017	Cameron	2008/0094786 A1	4/2008	Liou et al.
D781,278 S	3/2017	Kim et al.	2008/0192114 A1	8/2008	Pearson et al.
D781,833 S	3/2017	Daniels et al.	2008/0298026 A1	12/2008	Wang et al.
D781,834 S	3/2017	Kim et al.	2009/0009945 A1	1/2009	Johnson et al.
D781,835 S	3/2017	Kim et al.	2009/0080153 A1	3/2009	Richardson et al.
D781,836 S	3/2017	Kim et al.	2009/0194400 A1	8/2009	Mackay
D781,837 S	3/2017	Kim et al.	2009/0215412 A1	8/2009	Liu et al.
D781,838 S	3/2017	Kim et al.	2009/0236207 A1	9/2009	Shi et al.
D781,839 S	3/2017	Kim et al.	2010/0008028 A1	1/2010	Richardson et al.
D781,840 S	3/2017	Kim et al.	2010/0104814 A1	4/2010	Richardson et al.
D781,863 S	3/2017	Lai et al.	2010/0113111 A1	5/2010	Wong et al.
D784,316 S	4/2017	Lim et al.	2010/0147737 A1	6/2010	Richardson et al.
D784,348 S	4/2017	Zhang	2010/0200456 A1	8/2010	Parkinson
D784,350 S	4/2017	Li	2010/0298025 A1	11/2010	Spence
D784,976 S	4/2017	Cebe	2010/0311475 A1	12/2010	Takatsuka et al.
D784,995 S	4/2017	Akana et al.	2011/0003213 A1	1/2011	Burchardt et al.
D785,636 S	5/2017	Oberpriller et al.	2011/0024315 A1	2/2011	Kim
D785,637 S	5/2017	Hennings et al.	2011/0073505 A1	3/2011	Stiehl
D786,230 S	5/2017	Yang	2011/0073608 A1	3/2011	Richardson et al.
D786,256 S	5/2017	Stewart	2011/0139643 A1	6/2011	Elenes
D786,257 S	5/2017	Feldman	2011/0143114 A1	6/2011	Horie et al.
D786,853 S	5/2017	Friedland et al.	2011/0182463 A1	7/2011	Lee
D786,881 S	5/2017	Stewart et al.	2011/0226545 A1	9/2011	Richardson et al.
D787,497 S	5/2017	Friedland et al.	2011/0228458 A1	9/2011	Richardson et al.
9,661,906 B2	5/2017	Diebel et al.	2011/0228459 A1	9/2011	Richardson et al.
D788,758 S	6/2017	Liu	2012/0018323 A1	1/2012	Johnson et al.
D789,341 S	6/2017	Brown et al.	2012/0018325 A1	1/2012	Kim
D789,343 S	6/2017	Hawes et al.	2012/0021810 A1	1/2012	Terry
D789,347 S	6/2017	Zamudio	2012/0031914 A1	2/2012	Liu
D789,936 S	6/2017	Nyholm	2012/0038117 A1	2/2012	Knapp
D789,937 S	6/2017	Zhang	2012/0043235 A1	2/2012	Klement
D790,526 S	6/2017	Babichenko	2012/0073093 A1	3/2012	Szellos
D790,550 S	6/2017	Chen	2012/0074005 A1	3/2012	Johnson et al.
9,680,518 B2	6/2017	Wojcik et al.	2012/0075809 A1	3/2012	Chen
D791,113 S	7/2017	Tien et al.	2012/0077548 A1	3/2012	Goldberg
D794,036 S	8/2017	Hennings et al.	2012/0088558 A1	4/2012	Song
D795,237 S	8/2017	Jung et al.	2012/0099266 A1	4/2012	Reber et al.
D795,264 S	8/2017	Wright et al.	2012/0118773 A1	5/2012	Rayner
D795,881 S	8/2017	Akana et al.	2012/0154119 A1	6/2012	Schepps
D798,287 S	9/2017	Wright et al.	2012/0211382 A1	8/2012	Rayner
D798,855 S	10/2017	Wright et al.	2012/0227251 A1	9/2012	Hyuga et al.
D800,133 S	10/2017	Wright et al.	2012/0261306 A1	10/2012	Richardson et al.
D800,712 S	10/2017	Lai et al.	2012/0284124 A1	11/2012	Harangozo et al.
D812,618 S	3/2018	Altaras	2012/0309472 A1	12/2012	Wong et al.
D816,074 S	4/2018	Deng	2012/0309475 A1	12/2012	Johnson
D819,622 S	6/2018	Wright et al.	2012/0315972 A1	12/2012	Olson et al.
D819,644 S	6/2018	Wright et al.	2012/0325723 A1	12/2012	Carnevali
D820,822 S	6/2018	Wright et al.	2012/0329535 A1	12/2012	Kuo
D821,383 S	6/2018	Deng	2013/0001263 A1	1/2013	Kai
9,997,751 B2	6/2018	Fathollahi et al.	2013/0063004 A1	3/2013	Lai et al.
D828,350 S	9/2018	Akana et al.	2013/0079067 A1	3/2013	Peng
D832,245 S	10/2018	Jeon	2013/0146491 A1	6/2013	Ghali et al.
D833,425 S	11/2018	Ahn	2013/0157730 A1	6/2013	McCormac et al.
D836,100 S	12/2018	Akana et al.	2013/0175186 A1	7/2013	Simmer
D839,863 S	2/2019	Ahn	2013/0203470 A1	8/2013	Schneider et al.
D842,292 S	3/2019	Ahn	2013/0210502 A1	8/2013	Maravilla et al.
D851,078 S	6/2019	Yuan	2013/0242481 A1	9/2013	Kim et al.
D852,184 S	6/2019	Hyun	2013/0255198 A1	10/2013	Guschke et al.
10,328,295 B2	6/2019	Cordani	2013/0264143 A1	10/2013	Richardson et al.
D855,601 S	8/2019	Dang et al.	2013/0271902 A1	10/2013	Lai et al.
10,383,416 B2	8/2019	Hynecek et al.	2013/0294020 A1	11/2013	Rayner et al.
10,496,197 B2 *	12/2019	Taira G06F 3/04847	2013/0319836 A1	12/2013	Chen et al.
10,694,625 B2	6/2020	Hynecek et al.	2013/0344925 A1	12/2013	Lu et al.
10,694,825 B2 *	6/2020	Hynecek A45C 11/00	2014/0016217 A1	1/2014	Rayner
2003/0063004 A1	4/2003	Anthony et al.	2014/0048574 A1	2/2014	Kimble
2003/0111366 A1	6/2003	Enners	2014/0066142 A1	3/2014	Gipson
2004/0173402 A1	9/2004	Morkerken	2014/0066143 A1	3/2014	Choi
2004/0178202 A1	9/2004	Serio, Jr.	2014/0066144 A1	3/2014	Hong
2005/0067216 A1	3/2005	Schuhmann et al.	2014/0069786 A1	3/2014	Werner et al.
2006/0279924 A1	12/2006	Richardson et al.	2014/0113691 A1	4/2014	Oh et al.
2007/0087640 A1	4/2007	Albertone et al.	2014/0117061 A1	5/2014	Hadi
2007/0115387 A1	5/2007	Ho	2014/0128130 A1	5/2014	Chiu
2007/0139873 A1	6/2007	Thomas et al.	2014/0152890 A1	6/2014	Rayner
2007/0297149 A1	12/2007	Richardson et al.	2014/0187295 A1	7/2014	Kumar et al.
			2014/0191034 A1	7/2014	Glanzer et al.
			2014/0194168 A1	7/2014	Lehmann
			2014/0200054 A1	7/2014	Fraden
			2014/0228082 A1	8/2014	Morrow et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2014/0235963	A1	8/2014	Edwards et al.
2014/0262712	A1	9/2014	Chu
2014/0274232	A1	9/2014	Tages
2014/0339104	A1	11/2014	Magness
2014/0356495	A1	12/2014	Teuscher
2014/0357328	A1	12/2014	Aharon et al.
2014/0357330	A1	12/2014	Lin
2014/0364176	A1	12/2014	Pintor
2014/0370946	A1	12/2014	Daniell et al.
2015/0001104	A1	1/2015	Kim
2015/0045096	A1	2/2015	Johnson
2015/0065206	A1	3/2015	Rojas
2015/0068935	A1	3/2015	Kay et al.
2015/0133203	A1	5/2015	Xie et al.
2015/0137734	A1	5/2015	Wojcik et al.
2015/0141090	A1	5/2015	Hwan et al.
2015/0141091	A1	5/2015	Oh et al.
2015/0189963	A1	7/2015	Lai et al.
2015/0195938	A1	7/2015	Witter et al.
2015/0365120	A1	12/2015	Wojcik et al.
2016/0056856	A1	2/2016	Diebel
2016/0084614	A1	3/2016	Ellingson
2016/0094263	A1	3/2016	Fathollahi
2016/0119013	A1	4/2016	Wojcik et al.
2016/0198824	A1	7/2016	Rayner
2016/0361852	A1	12/2016	Fathollahi
2020/0313713	A1	10/2020	Fathollahi

FOREIGN PATENT DOCUMENTS

CN	201639626	U	11/2010
CN	201700109	U	1/2011
CN	201853616	U	6/2011
CN	102123863	A	7/2011
CN	202455520	U	9/2012
EP	2081201		7/2009
EP	2640042	A1	9/2013
EP	3092878	A1	11/2016
EP	3373107		9/2018

JP	8046371	A	2/1996
JP	9023072	A	1/1997
JP	3044740	U	1/1998
JP	10079582	A	3/1998
JP	11231970	A	8/1999
JP	11231973	A	8/1999
JP	11284358	A	10/1999
JP	2000125916	A	5/2000
JP	2003324796	A	11/2003
JP	2004247297	A	9/2004
JP	2006064998	A	3/2006
WO	2012002899	A1	1/2012
WO	2012051358	A2	4/2012
WO	2015105894	A1	7/2015

OTHER PUBLICATIONS

Anonymous: “[Review] the Newest Waterproof Case on the Market: Introducing the Escape Capsule.” i PhoneLife.com” i Phone + i Pad Life Magazine Nov. 6, 2012 (Nov. 6, 2012) XP055292666 Retrieved from the Internet: URP: <http://www.iphonelife.com/blog/28861/review-newest-waterproof-case-market-introducing-escape-capsule> [retrieved on Aug. 2, 2016].

“Catalyst Impact Protection for iPhone X—Review.” YouTube, uploaded by Michael Billig, Nov. 8, 2017. Web. Accessed Nov. 23, 2020, https://www.youtube.com/watch?v=TA-yFKB_qAA.

Walters, Jon. “Catalyst Impact Case for iPhone X Review a Refinement in Performance and Style!” MacSources, Nov. 28, 2017. Web. Accessed Nov. 23, 2020, <https://macsources.com/catalyst-impact-case-for-iphone-x-review>.

Catalyst. “Catalyst Waterproof iPad Case for iPad Pro 12.9” 2018 Waterproof 6.6 ft—Full Body Protection, Heavy Duty Drop Proof 4ft, Kickstand, True Acoustic Sound Technology, Built-in Screen Protector.” Amazon.com, Inc., Date First Available Jul. 15, 2019. Web. <https://www.amazon.com/dp/B07Q2Y91Y1>.

Amazon.com “iPad Air Case, SUPCASE Heavy Duty Beetle Defense Series Full-Body Rugged Hybrid Protective Case Cover with Built-in Screen Protector for Apple iPad Air (Black/Black, not fit iPad Air 2).” Amazon.com, Inc., Date First Available Nov. 1, 2013. Web. <https://www.amazon.com/dp/B00GDHAT3W>.

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 3




FIG. 4A




FIG. 4B

1

SWITCH ASSEMBLY FOR ENGAGING A SWITCH OF AN ELECTRONIC DEVICE

TECHNICAL FIELD

The present specification generally relates to protective cases that cover electronic devices and, more specifically, cases that have a switch assembly for engaging a switch of an electronic device.

BACKGROUND

As background, electronic devices (e.g., smartphones, tablets, or the like) generally include switches to control various functionality of the device. For example, a switch may include a muting switch that turns off the volume of the mobile device, particularly to silence a ringtone. In order to provide additional protection against falls or fluid contact, protective cases may be arranged around the device while still allowing functional access to the screen and/or buttons of the device. Certain protective cases may include an opening around a switch to allow for direct user access to the sliding switch. However, direct access may inadvertently provide an entry point for fluid into the mobile device, which may lead to water damage. Other protective cases may include a protective switch that covers and engages with the switch of the mobile device such that the protective switch is actuable by a user to move in the same manner as the switch and move the switch. However, direct manipulation of such protective sliding switches may be difficult for some users.

SUMMARY

In one aspect, a switch assembly for engaging a switch of an electronic device includes a rotatable knob having an axis of rotation, a pin mechanism engaged with the rotatable knob, and a slider body. The pin mechanism includes a pin, the pin being offset from the axis of rotation of the rotatable knob. The slider body is shaped to include a slot in which the pin of the pin mechanism is positioned and a switch recess. The switch recess is shaped to receive and selectively contact the switch of the electronic device when the electronic device is positioned proximate the slider body. Rotation of the rotatable knob in a first direction causes the pin to travel in the slot in a first direction and move the slider body toward contact with a first portion of the switch to urge the switch into a first position, and rotation of the rotatable knob in a second direction causes the pin to travel in the slot in a second direction and move the slider body toward contact with a second portion of the switch to urge the switch into a second position.

In another aspect, a protective case for an electronic device includes a frame shaped to receive the electronic device therein and a switch assembly coupled to the frame for engaging a switch of the electronic device. The switch assembly includes a rotatable knob having an axis of rotation, a pin mechanism engaged with the rotatable knob, and a slider body. The pin mechanism includes a pin, the pin being offset from the axis of rotation of the rotatable knob. The slider body is shaped to include a slot in which the pin of the pin mechanism is positioned and a switch recess. The switch recess is shaped to receive and selectively contact the switch of the electronic device when the electronic device is positioned proximate the slider body. Rotation of the rotatable knob in a first direction causes the pin to travel in the slot in a first direction and move the slider body toward

2

contact with a first portion of the switch to urge the switch into a first position, and rotation of the rotatable knob in a second direction causes the pin to travel in the slot in a second direction and move the slider body toward contact with a second portion of the switch to urge the switch into a second position.

In yet another aspect, a protective case for an electronic device includes a frame having a front portion and a back portion coupled together to define a cavity shaped to receive and encapsulate the electronic device having a switch, and a switch assembly positioned on one of the front portion or the back portion of the frame for engaging the switch of the electronic device when the electronic device is positioned in the cavity defined by the front portion and the back portion. The switch assembly includes a rotatable knob having an axis of rotation, a pin mechanism engaged with the rotatable knob, and a slider body. The pin mechanism includes a pin, the pin being offset from the axis of rotation of the rotatable knob. The slider body is shaped to include a slot in which the pin of the pin mechanism is positioned and a switch recess. The switch recess is shaped to receive and selectively contact the switch of the electronic device when the electronic device is positioned proximate the slider body. Rotation of the rotatable knob in a first direction causes the pin to travel in the slot in a first direction and move the slider body toward contact with a first portion of the switch to urge the switch into a first position, and rotation of the rotatable knob in a second direction causes the pin to travel in the slot in a second direction and move the slider body toward contact with a second portion of the switch to urge the switch into a second position.

These and additional features provided by the embodiments described herein will be more fully understood in view of the following detailed description, in conjunction with the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

The embodiments set forth in the drawings are illustrative and exemplary in nature and not intended to limit the subject matter defined by the claims. The following detailed description of the illustrative embodiments can be understood when read in conjunction with the following drawings, where like structure is indicated with like reference numerals and in which:

FIG. 1A depicts a front portion of a protective case, according to one or more embodiments shown and described herein;

FIG. 1B depicts a back portion of the protective case, according to one or more embodiments shown and described herein;

FIG. 2A depicts an exploded view of a switch assembly for engaging a sliding switch of a mobile device, according to one or more embodiments shown and described herein;

FIG. 2B depicts another exploded view of the switch assembly of FIG. 2A, according to one or more embodiments shown and described herein;

FIG. 2C depicts another exploded view of the switch assembly of FIG. 2A, according to one or more embodiments shown and described herein;

FIG. 3 depicts an assembled interior view of the switch assembly of FIGS. 2A-2C, according to one or more embodiments shown and described herein;

FIG. 4A depicts a cross-sectional view of the switch assembly engaged with a sliding switch of a mobile device in a first position, according to one or more embodiments shown and described herein; and

FIG. 4B depicts the switch assembly moving the sliding switch of the mobile device to a second position, according to one or more embodiments shown and described herein.

DETAILED DESCRIPTION

The figures generally depict a protective case with an integrated switch assembly for engaging a switch of an electronic device. Switch assemblies according to the present disclosure may include a rotatable knob having an axis of rotation, a pin mechanism, and a slider body. The pin mechanism is engaged with the rotatable knob and includes a pin that is offset from an axis of rotation of the rotatable knob. The slider body may be shaped to include a slot in which the pin of the pin mechanism may be positioned. The slider body may further be shaped to include a switch recess that is shaped to receive and selectively contact the switch of the electronic device when the electronic device is positioned proximate the slider body. Rotation of the rotatable knob in a first direction may cause the pin to travel in the slot in a first direction and move the slider body toward contact with a first portion of the switch to urge the switch into a first position (e.g., an active or enabled position). Rotation of the rotatable knob in a second direction may cause the pin to travel in the slot in a second direction and move the slider body toward contact with a second portion of the switch to urge the switch into a second position (e.g., a deactivated or disabled position). Such switch assembly allows for a switch of an electronic device to be completely enclosed, to prevent ingress of fluid and/or debris, without limiting operation of the switch. Additionally, the present devices provides an easier and more comfortable way to engage the switch of the electronic device. Various embodiments of the switch assembly and protective case will be described in more detail herein.

An electronic device may include any electronic device such as a pager, PDA, cellphone, smart phone, tablet, laptop, or the like. Electronic devices according to the present disclosure may include a switch (e.g., a sliding switch, such as a muting switch). It is noted that a switch may be a switch that slides or toggles from a first position to a second position. As will be described herein, an electronic device may be positioned within the protective case. The protective case may provide a protective, and/or waterproof housing around the mobile the device.

Referring now to FIGS. 1A and 1B, an embodiment of a protective case 10 is generally depicted. The protective case 10 generally includes a frame 12. The frame 12 defines a cavity 11 within which an electronic device may be disposed. The frame 12 may be separable into one or more components to allow for insertion of the electronic device into the cavity 11 defined by the frame 12. For example, the frame 12 may include a front portion 14, illustrated in FIG. 1A and a back portion 16, illustrated in FIG. 1B. It is noted that each of the front portion 14 and the back portion 16 may be single integral articles or may be assemblies of sub-frame components.

The front portion 14 and the back portion 16 may be separably coupled to one another. That is, the front portion 14 may be assembled to and disassembled from the back portion 16 repeatedly (e.g., to allow for insertion and removal of the electronic device). When the front portion 14 is assembled to the back portion 16 around an electronic device, a fluid tight seal (e.g., a watertight seal and/or an airtight seal) may be formed between the front portion 14 and the back portion 16 to prevent ingress or egress of liquid, dirt, or other debris, into the protective case 10, thereby

protecting the electronic device from contact with liquid, dirt, or debris. That is, the protective case 10, when assembled, may provide a waterproof housing for the electronic device positioned therein.

The back portion 16 of the frame 12 may have a body 13 that is arranged to correspond to one or more features of a backside of an electronic device when the electronic device is received within the cavity 11 of the protective case 10. For example, the back portion 16 of the frame 12 may include one or more camera windows 17 or apertures that are aligned with one or more components of a camera device (e.g., a lens and/or flash) to allow for the capture of images by the electronic device when the electronic device is positioned within the protective case 10. In addition, the back portion 16 of the frame 12 may be shaped and sized to generally correspond to the shape and size of a particular electronic device such that the electronic device, when received in the protective case 10 fits within the cavity 11 defined by the frame 12.

The back portion 16 may include one or more projections 15 extending from the body 13 of the back portion 16. The one or more projections 15 are receivable by one or more receiving apertures 20 in the front portion 14 to couple the front portion 14 to the back portion 16, the one or more receiving apertures 20 corresponding in shape and size to the one or more projections 15 such that the one or more receiving apertures 20 retain the one or more projections 15 when the back portion 16 is joined with the front portion 14, as described herein. For example, the back portion 16 may include a plurality of projections disposed around a perimeter of the back portion 16 of the case. In other embodiments, the one or more projections 15 may be part of the front portion 14 of the frame 12 and the one or more receiving apertures 20 may be formed in the back portion 16 of the frame 12.

The front portion 14 of the frame 12 may be have a body 23 arranged to correspond to one or more features of a front side of an electronic device when the electronic device is received within the cavity 11 of the protective case 10. For example, the front portion 14 of the frame 12 may include a screen aperture 21 that is aligned within one or more portions of a touch screen or other user input hardware of the electronic device to allow for interaction of a user with the touch screen or other user input hardware. In some embodiments, the screen aperture 21 may include a protective screen made of plastic, glass, or any other suitable material. In addition, the front portion 14 of the frame 12 may be shaped and sized to generally correspond to the shape and size of a particular electronic device such that the electronic device, when received in the protective case 10 fits within the cavity 11 defined by the frame 12.

The front portion 14, the back portion 16, or a combination thereof may define a sidewall 22 of the frame 12. The sidewall 22 may be arranged to correspond to a perimeter of the electronic device when the electronic device is positioned within the frame 12. The sidewall 22 may define an interior side 64 and an exterior side 68, wherein the electronic device is position on an interior side 64 of the sidewall 22 when positioned within the frame 12. Formed within the sidewall 22 may be an assembly port 24 (further illustrated in FIGS. 2A-4B) to which a switch assembly 100 may be assembled.

That is, coupled to the frame 12 at an assembly port 24 is a switch assembly 100 for engaging a switch 52 of an electronic device 50, as illustrated in FIGS. 4A and 4B. The switch assembly 100 encloses around the switch 52 of the electronic device 50, and when actuated, allows the switch

assembly 100 to selectively contact the switch 52 to engage and disengage a function of the switch 52 by moving the switch 52 from an active position to an inactive position and vice versa.

FIGS. 2A-2C illustrate various exploded views of the switch assembly 100 from the sidewall 22 of the frame 12. The various portions of the assembly port 24 will be further described in relation to the various components of the switch assembly 100 mounted to the assembly port 24. In particular, the switch assembly 100 generally includes a rotatable knob 102, a pin mechanism 160, and a slider body 170 mounted to the frame 12 via the assembly port 24. The assembly port 24 may define one or more recesses for receiving and supporting motion of various components of the switch assembly 100. These and additional features will be described in greater detail below.

The rotatable knob 102 may include a knob ring 110, a limit pin 114, a coupler 106, and a coupler cover 104. The rotatable knob 102 has an axis of rotation 101 around which one or more components of the rotatable knob 102 rotates. It is noted that the rotatable knob 102 may include a greater or fewer number of components without departing from the scope of the present disclosure.

The knob ring 110 may be any rotatable or twistable device, which may be rotated or twisted around the axis of rotation 101 of the rotatable knob 102. For example, the knob ring 110 is illustrated as being approximately circular and defining a coupler-receiving aperture 111. It is noted that while the knob ring 110 is shown as being circular, other shapes are also contemplated and possible (e.g., oval, egg-shaped, square, rectangular, etc.). The knob ring 110 may define a user engagement surface 112. In some embodiments, the user engagement surface 112 of the knob ring 110 may be textured in order to improve a user's ability to grip and twist the knob ring 110. Coupled to an interior facing surface 113 of the knob ring 110, opposite the user engagement surface 112, and offset from the axis of rotation 101, may be the limit pin 114. That is, the limit pin 114 extends from the interior facing surface 113 of the knob ring 110 at a location that is not a center of the knob ring 110, as depicted, for example, in FIG. 2C.

For mounting of the knob ring 110 to the frame 12, the assembly port 24 of the frame 12 may include a knob mounting recess 32, in which the rotatable knob 102 may be inserted. For example, the knob mounting recess 32 may define a main chamber sized and shaped to receive the knob ring 110 and allow rotation of the knob ring 110 within the knob mounting recess 32. Stated another way, the knob recess 32 is a recess formed in to the sidewall 22 of the frame 12. The knob recess 32 may be defined by separated raised walls 62a, 62b that extend from the sidewall 112 formed about the assembly port 24 and contiguous to the assembly port 24. The knob mounting recess 32 may be limited by a backstop wall 33, which may act to limit an insertion distance of knob ring 110 therethrough. The backstop wall 33 may be recessed into the sidewall 22, such that when assembled the knob ring 110 sits at least partially recessed into the sidewall 22.

Positioned adjacent to the backstop wall 33 may be a rotational limit slot 34 in which the limit pin 114 may be positioned (see also FIGS. 4A and 4B). The rotational limit slot 34 may define an arc of less than 360° (e.g., less than or equal to 180°, less than or equal to 90°, or the like) around the axis of rotation 101. Accordingly, as the knob ring 110 is rotated about the axis of rotation 101 of the rotatable knob 102, the limit pin 114 traverses the rotational limit slot 34. Once the limit pin 114 reaches an end of the rotational limit

slot 34, the knob ring 110 is prevented from further rotation in that direction by the limit pin 114. The knob ring 110 may be rotated in an opposite direction until the limit pin 114 reaches a second end of the rotational limit slot 34. Stated another way, engagement of the limit pin 114 with the rotational limit slot 34 limits the angular rotation of the rotatable knob 102 about the axis of rotation 101 of the rotatable knob 102.

As noted above, the knob ring 110 may define a coupler-receiving aperture 111 that extends from the user engagement surface 112 to a stop wall 115. That is, the stop wall 115 may be inset into the knob ring 110. The coupler 106 may be any device configured to couple the knob ring 110 to the pin mechanism 160, as will be described in greater detail herein. For example, the coupler 106 may be a threaded fastener having a head 107 and a threaded shank 108. When assembled to the knob ring 110, the stop wall 115 of the coupler-receiving aperture 111 may be configured to engage with the head 107 of the coupler 106 to limit the insertion of the coupler 106 through the coupler-receiving aperture 111. The stop wall 115 may be of such a depth that the head 107 of the coupler 106 is completely positioned within the coupler-receiving aperture 111.

Referring to FIGS. 4A and 4B, which illustrate a cross-section of the protective case 10 along and parallel to the axis of rotation 101 of the switch assembly 100, formed within the stop wall 115 of the coupler-receiving aperture 111 may be a pass-through opening 116 to allow for the shank 108 of the coupler 106 to extend therethrough. The pass-through opening 116 may have a width larger than a width of the shank 108 to allow for both passage of the shank 108 and, insertion of a portion of a stem 162 of the pin mechanism 160. In particular, the pass-through opening 116 may be shaped to interlock with a stem 162 of the pin mechanism 160 such that rotation of the rotatable knob 102 causes rotation of the pin mechanism 160.

The coupler cover 104 may be any device for covering the head 107 of the coupler 106. For example, the coupler cover 104 may be a cap that may be pressed over the head 107 of the coupler 106 to cover or otherwise camouflage the head 107 of the coupler 106. The coupler cover 104 may include a locking flange 105 that interlocks with the knob ring 110, such as illustrated in FIGS. 4A and 4B. In particular, FIGS. 4A and 4B illustrate the locking flange 105 positioned within a locking recess 103 of the knob ring 110 adjacent to the stop wall 115. Stated another way, the locking flange 105 is sized and shaped to correspond to the locking recess 103. When in position within the locking recess 103, the locking flange 105 may be in contact with the stop wall 115.

Referring again to FIGS. 2A and 2B, the sidewall 22 may further define a sealant recess 35 for receiving an O-ring 120 or other sealant material. For example, inset further inward from the knob mounting recess 32 may be the sealant recess 35. The sealant recess 35 may have a width less than that of the knob recess 32. The sealant recess 35 may be sized and shaped for insertion of the O-ring 120 or other sealant material that may aid in preventing ingress of fluid into the protective case 10 through sidewall 22 or switch assembly 100. The sealant recess 35 may be of a depth such that the O-ring 120 or other sealant material is compressed between the knob ring 110 and a base 37 of the sealant recess 35. When assembled, the O-ring 120 or other sealant material may be positioned between and in contact with the knob ring 110 and the sidewall 22 (e.g., within the sealant recess 35) of the frame 12. The shank 108 of the coupler 106 may extend through a center of the O-ring 120 or other sealant material.

The sidewall 22 may define a through-passage 36 for one or more portions of the switch assembly 100 to extend. For example, the through-passage 36 may extend from the sealant recess 35 through the sidewall 22 to the interior side 68 of the sidewall 22. As illustrated in FIGS. 4A and 4B, when assembled the shank 108 of the coupler 106 may extend at least partially through the through-passage 36 to couple the knob ring 110 to the pin mechanism 160.

Referring now to FIG. 2C, the pin mechanism 160 may be any device engagable with the rotatable knob 102 and comprising a pin 168, which is offset from the axis of rotation 101 of the rotatable knob 102. For example, the pin 168 is spaced from the axis of rotation 101 and extends outwardly in a direction parallel to the axis of rotation 101. The pin mechanism 160 may include a stem 162 comprising a first end 163 and a second end 164, wherein the first end 163 of the stem 162 is engagable with the pass-through opening 116 of the knob ring 110. In embodiments, the first end 163 of the stem 162 may have a different cross-sectional shape than the second end 164 of the stem 162. For example, the first end 163 of the stem 162 may be shaped to substantially match a shape of the pass-through opening 116 of the knob ring 110, such that the first end 163 of the stem 162 may be nested within the pass-through opening 116 of the knob ring 110. The shape of the first end 163 of the stem 162 and the pass-through opening 116 may prevent rotation of the pin mechanism 160 relative to the knob ring 110. For example, the first end 163 of the stem 162 may be one or more straight wall sections that correspond to one or more straight wall sections of the pass-through opening 116 and prevent rotation of the first end 163 of the stem 162 within the pass-through opening 116. Such non-rotatable engagement may fix the pin mechanism 160 relative to the rotatable knob 102 such that rotation of the rotatable knob 102 rotates the pin mechanism 160.

In some embodiments, the first end 163 of the stem 162 and the second end 164 of the stem 162 may not have different cross-sectional shapes. For example, a non-rotatable engagement may be instead provided through friction (such as provided in a press-fit engagement) that prevents rotation of the pin mechanism 160 relative to the rotatable knob 102. In yet further embodiment, the action of tightening the coupler 106 may provide enough force to prevent rotation of the pin mechanism 160 relative to the rotatable knob 102.

A plate 166 may be coupled to the second end 164 of the stem 162 and the pin 168 may be coupled to and extend from the plate 166. The plate 166 of the pin mechanism 160 may extend past a width of the stem 162 to position the pin 168 further from the axis of rotation 101 of the rotatable knob 102. In other embodiments, the pin 168 may directly extend from the second end 164 of the stem 162.

Still referring to FIG. 2C, an interior side 62 of the sidewall 22 is depicted. Formed in the interior side of the sidewall 22, the assembly port 24 may further include one or more mounting recesses for mounting the pin mechanism 160 and slider body 170, described in greater detail below. The through-passage 36 may be sized to a dimension large enough to receive the stem 162 of the pin mechanism 160 therethrough and support rotational motion of the stem 162 about the axis of rotation 101. The through-passage 36 may open to a plate-receiving groove 38, which opens further into a slider groove 40. Stated another way, the plate-receiving groove 38 may be formed or otherwise inset into a back wall 41 of the slider groove 40.

Referring to FIGS. 4A and 4B, the stem 162 of the pin mechanism 160 may be advanced through the through-

passage 36, through a center of the O-ring 120 or other sealant material, until the plate 166 of the pin mechanism 160 is positioned and contacted with the plate-receiving groove 38 to abut the through-passage 36. The O-ring 120 or other sealant material may form a fluid and/or airtight seal around the stem 162 of the pin mechanism 160. The first end 163 of the stem 162 may then be inserted into the pass-through opening 116 of the knob ring 110. The shank 108 of the coupler 106 may be engaged with an opening 169 (e.g., a threaded passage) formed within and extending into the first end 163 of the stem 162. The coupler 106 can be advanced into the opening 169 of the stem 162 until the head 107 of the coupler 106 engages the stop wall 115 of the knob ring 110. The coupler cover 104 may then be snapped into place over the head 107 of the coupler 106 to conceal the coupler 106. When assembled, the pin 168 of the pin mechanism 160 extends from the plate 166 into a volume of the slider groove 40 and into slot 174 of slider body 170.

The slider body 170 may be slidably disposed in the slider groove 40 and configured to slide along the slide path (e.g., along the X-direction of the coordinate axes depicted in FIGS. 3, 4A, and 4B) defined by the slider groove 40. The slider body 170 may be shaped to include the slot 174 in which the pin 168 of the pin mechanism 160 is positioned when the switch assembly 100 is assembled. The slot 174 may define a travel path (e.g., along a Z-direction of the coordinate axes depicted in FIGS. 3, 4A, and 4B) through which the pin 168 can travel. As illustrated, the travel path as defined by the slot 174 may be perpendicular to the axis of rotation 101 (e.g., extending along the Y-direction of the coordinate axes depicted in FIGS. 3, 4A, and 4B) of the rotatable knob 102. Furthermore, the travel path as defined by the slot 174 may be perpendicular to a slide path of the slider body 170 defined by the slider groove 40. For example, and as illustrated in FIGS. 4A and 4B, as the rotatable knob 102 is rotated about the axis of rotation 101, the pin 168 traverses the slot 174, which pushes the slider body 170 to slide along the slider groove 40 in a direction perpendicular to the axis of rotation 101 along the rotatable knob 102.

The slider body 170 may further also be shaped to include a switch recess 178 shaped to receive and selective contact a switch 52 of the electronic device 50 (illustrated in FIGS. 4A and 4B). For example, the switch recess 178 may engage the switch 52 such that movement of the slider body 170 causes the switch 52 to move between a first position, shown in FIG. 4A, and a second position (e.g., a silencing position and a sound-on position where the switch 52 is a silencing switch 52), shown in FIG. 4B. For example, the slider body 170 may be moved into contact with a first portion 54 of the switch 52 to urge the switch 52 into a first position (e.g., as shown in FIG. 4A). The slider body 170 may be moved into contact with a second portion 56 of the switch 52 to urge the switch 52 into a second position (e.g., as shown in FIG. 4B).

To retain the slider body 170 within the slider groove 40, the slider body 170 may have one or more locking flanges. For example, the slider body 170 may include a first locking flange 173 coupled to and extending along a first edge 175 of the slider body 170. The first locking flange 173 may have a reduced thickness relative to a thickness of the first edge 175 of the slider body 170. The first locking flange 173 may be integral with the slider body 170 or a separate component therefrom. The first locking flange 173 may be continuous along the first edge 175 or may be discontinuous along the first edge 175. For example and as illustrated, the first locking flange 173 may not be continuous across a base of the slot 174.

The slider groove **40** may have a channel **42** formed at the base of the slider groove **40**. When assembled, the first locking flange **173** may be inserted into the channel **42** and slidable along the channel **42**. The first edge **175** of the slider body **170** may be positioned over and in contact with a base surface **44** of the slider groove **40**.

The slider body **170** may include a second locking flange **177** along a second edge **176** of the slider body **170** opposite the first edge **175**. The second locking flange **177** may have a reduced thickness relative to a thickness of the second edge **176** of the slider body **170**. The second locking flange **177** may be integral with the slider body **170** or a separate component therefrom. The second locking flange **177** may be continuous along the second edge **176** or may be discontinuous along the second edge **176**. In some embodiments, the switch recess **178** may have an inset depth greater than a thickness of the second locking flange **177**.

A locking mechanism **150** may be provided to engage the second locking flange **177** so as to lock the slider body **170** into the slider groove **40**. That is, the locking mechanism **150** may be arranged about the slider body **170** to restrict motion of the slider body **170** in a direction transverse to the slide path as defined by the slider groove **40**. To facilitate locking of the slider body **170** within the slider groove **40**, the locking mechanism **150** may comprise an elongate body **151**. Referring to FIG. 3, when assembled, the elongate body **151** may extend over the second locking flange **177** to prevent the slider body **170** from becoming dislodged from the slider groove **40**. The elongate body **151** may have a reduced thickness over the switch recess **178**, to allow for insertion of the switch **52** passed the elongate body **151** and into the switch recess **178**.

At either end of the elongate body **151**, may be locking prongs **152a**, **152b**, configured to mate with mating apertures **53a**, **53b** formed within the frame **12**, illustrated in FIG. 2C. Stated another way, a first locking prong **152a** may extend from a first end of the elongate body **151** and a second locking prong **152b** may extend from a second end of the elongate body **151**. The first mating aperture **53a** may extend into the frame **12** on one side of the assembly port **24** and the second mating aperture **53b** may extend into the frame **12** on a second side of the assembly port **24**. The locking prongs **152a**, **152b** may be pressed into the mating apertures **53a**, **53b** to mount the locking mechanism **150** to the frame **12**. The locking prongs **152a**, **152b** may engage the mating apertures **53a**, **53b** in a press fit to ensure a secure engagement between the locking prongs **152a**, **152b** and the mating apertures **53a**, **53b**. In some embodiments, the mating apertures **53a**, **53b** may include pressure release slits **54a**, **54b**, to allow for escape of air when mating the locking prongs **152a**, **152b** with the mating apertures **53a**, **53b**.

Referring now to FIGS. 4A and 4B, operation of the switch assembly **100** will now be described. FIG. 4A illustrates an electronic device **50** positioned within the protective case **10** to provide an electronic device assembly **200**. That is, the protective case **10** provides a protective covering to the electronic device **50**. Referring to FIGS. 1A and 1B, the front portion **14** couples to the back portion **16** of the frame **12** to encapsulate the electronic device **50** within the protective case **10** within cavity **11**. The switch **52** of the electronic device **50** is positioned in a first position (e.g., an active position) and at least partially positioned within the switch recess **178** of the slider body **170**. Accordingly, when the slider body **170** moves, the slider body **170** is selectively contacted with the first or second portions **54**, **56** of the switch **52**. The contact between the slider body **170**

and the switch **52** causes the switch **52** to move from the first position to the second position shown in FIG. 4B.

To cause the slider body **170** to move the switch **52** from the first position to the second position, a user may contact the contact surface **112** of the knob ring **110**, and twist the knob ring **110** about the axis of rotation **101** in a first direction (e.g., a clockwise direction). Such twisting causes the pin mechanism **160** to travel the pin **168** within the slot **174** of the slider body **170** in a first direction and move the slider body **170** toward contact with the first portion **54** of the switch **52** to urge the switch **52** to a first position. That is, movement of the pin **168** imparts a force to the slider body **170** surrounding the slot **174**, causing the slider body **170** to move along the slide path and the pin **168** to move along the slot **174**. As the slider body **170** moves, the force is transferred to the switch **52**, which causes the switch **52** to move with the slider body **170** to the second position shown in FIG. 4B.

To move the switch **52** back to the original position shown in FIG. 4A, a user may engage the contact surface **112** of the knob ring **110** and twist the knob ring **110** about the axis of rotation **101** in a second direction (e.g., a counterclockwise direction). The opposite twisting direction causes the pin mechanism **160** to traverse the pin **168** along the slot **174** in opposite second, opposite direction to move the slider body **170** toward contact with the second portion **26** of the switch **52** to urge the switch **52** to a second position. That is, the pin **168** applies a force to the slider body **170** to move the slider body **170** and the switch **52** back to the second position depicted in FIG. 4A.

Embodiments can be described with reference to the following numbered clauses, with preferred features laid out in the dependent clauses.

1. A switch assembly for engaging a switch of an electronic device, the switch assembly comprising: a rotatable knob having an axis of rotation; a pin mechanism engaged with the rotatable knob and comprising a pin, the pin being offset from the axis of rotation of the rotatable knob; and a slider body, the slider body being shaped to include a slot in which the pin of the pin mechanism is positioned and a switch recess, the switch recess being shaped to receive and selectively contact the switch of the electronic device when the electronic device is positioned proximate the slider body, rotation of the rotatable knob in a first direction causing the pin to travel in the slot in a first direction and move the slider body toward contact with a first portion of the switch to urge the switch into a first position, and rotation of the rotatable knob in a second direction causing the pin to travel in the slot in a second direction and move the slider body toward contact with a second portion of the switch to urge the switch into a second position.

2. The switch assembly of clause 1, wherein the rotatable knob comprises: a knob ring, and a limit pin coupled to the knob ring, wherein the limit pin limits an angular rotation of the rotatable knob.

3. The switch assembly of clause 1 or 2, wherein the slot defines a travel path perpendicular to the axis of rotation of the rotatable knob.

4. The switch assembly of any preceding clause, wherein the pin mechanism comprises: a stem comprising a first end and a second end; and a plate coupled to the second end of the stem, wherein the pin is coupled to the plate and extends therefrom and into the slot of the slider body.

5. The switch assembly of clause 4, wherein: the rotatable knob comprises a pass-through opening; and the first end of

11

the stem is positioned within the pass-through opening of the rotatable knob such that the stem is non-rotatable relative to the rotatable knob.

6. A protective case for an electronic device, the protective case comprising: a frame shaped to receive the electronic device therein; and a switch assembly coupled to the frame for engaging a switch of the electronic device, the switch assembly comprising: a rotatable knob having an axis of rotation; a pin mechanism engaged with the rotatable knob and comprising a pin, the pin being offset from the axis of rotation of the rotatable knob; and a slider body, the slider body being shaped to include a slot in which the pin of the pin mechanism is positioned and a switch recess, the switch recess being shaped to receive and selectively contact the switch of the electronic device when the electronic device is positioned proximate the slider body, rotation of the rotatable knob in a first direction causing the pin to travel in the slot in a first direction and move the slider body toward contact with a first portion of the switch to urge the switch into a first position, and rotation of the rotatable knob in a second direction causing the pin to travel in the slot in a second direction and move the slider body toward contact with a second portion of the switch to urge the switch into a second position.

7. The protective case of clause 6, wherein: the rotatable knob comprises: a knob ring, and a limit pin coupled to the knob ring; and the frame defines a rotational limit slot formed therein, wherein the limit pin is positioned within the rotational limit slot and movement of the pin through the rotational limit slot limits an angular rotation of the rotatable knob.

8. The protective case of clause 6 or 7, wherein the frame defines a slider groove defining a slide path and the slider body is slidably disposed within the slider groove.

9. The protective case of clause 8, further comprising a locking mechanism positioned to restrict motion of the slider body in a direction transverse to the slide path.

10. The protective case of clause 9, wherein the locking mechanism comprises: an elongate body spanning across a portion of the slider body; a first locking prong coupled to a first end of the elongate body and inserted into the frame proximate to a first side of the slider groove; and a second locking prong coupled to a second end of the elongate body and inserted into the frame proximate to a second side of the slider groove.

11. The protective case of any of clauses 6-10, wherein the pin mechanism comprises: a stem comprising a first end and a second end; and a plate coupled to the second end of the stem, wherein the pin is coupled to the plate and extends therefrom and into the slot of the slider body.

12. The protective case of clause 11, wherein the frame further defines a plate-receiving groove formed within a back wall of the slider groove, wherein the plate is engaged with the plate-receiving groove and the stem extends through the frame from a first side of the frame to a second side of the frame, and wherein the first end of the stem is positioned within a pass-through opening of the rotatable knob such that the stem is non-rotatable relative to the rotatable knob.

13. A protective case for an electronic device, the protective case comprising: a frame comprising a front portion and a back portion coupled together to define a cavity shaped to receive and encapsulate the electronic device having a switch; a switch assembly positioned on one of the front portion or the back portion of the frame for engaging the switch of the electronic device when the electronic device is positioned in the cavity defined by the front portion and the

12

back portion, the switch assembly comprising: a rotatable knob having an axis of rotation; a pin mechanism engaged with the rotatable knob and comprising a pin, the pin being offset from the axis of rotation of the rotatable knob; and a slider body, the slider body being shaped to include a slot in which the pin of the pin mechanism is positioned and a switch recess, the switch recess being shaped to receive and selectively contact the switch of the electronic device when the electronic device is positioned proximate the slider body, rotation of the rotatable knob in a first direction causing the pin to travel in the slot in a first direction and move the slider body toward contact with a first portion of the switch to urge the switch into a first position, and rotation of the rotatable knob in a second direction causing the pin to travel in the slot in a second direction and move the slider body toward contact with a second portion of the switch to urge the switch into a second position.

14. The protective case of clause 13, wherein: the rotatable knob comprises: a knob ring, and a limit pin coupled to the knob ring; and the front portion of the frame defines a rotational limit slot formed therein, wherein the limit pin is positioned within the rotational limit slot and movement of the pin through the rotational limit slot limits an angular rotation of the rotatable knob.

15. The protective case of clause 13 or 14, wherein the front portion of the frame defines a slider groove defining a slide path and the slider body is slidably disposed within the slider groove.

16. The protective case of any of clauses 13-15, further comprising a locking mechanism positioned to restrict motion of the slider body in a direction transverse to a slide path of the slider body.

17. The protective case of clause 16, wherein the locking mechanism comprises: an elongate body spanning across a portion of the slider body; a first locking prong coupled to a first end of the elongate body and inserted into the frame proximate to a first side of a slider groove in which the slider body is slidably disposed; and a second locking prong coupled to a second end of the elongate body and inserted into the frame proximate to a second side of the slider groove.

18. The protective case of clause 16, wherein the locking mechanism comprises an elongate body and a first locking prong at a first end of the elongate body and a second locking prong at a second end of the elongate body.

19. The protective case of any of clauses 13-19, wherein the pin mechanism comprises: a stem comprising a first end and a second end; and a plate coupled to the second end of the stem, wherein the pin is coupled to the plate and extends therefrom and into the slot of the slider body.

20. The protective case of clause 19, wherein the front portion of the frame wherein the frame further defines a plate-receiving groove formed within a back wall of the slider groove, wherein the plate is engaged with the plate-receiving groove and the stem extends through the frame from a first side of the frame to a second side of the frame, and wherein the first end of the stem is positioned within a pass-through opening of the rotatable knob such that the stem is non-rotatable relative to the rotatable knob.

It should now be understood that embodiments as provided herein are directed to switch assemblies that include a rotatable knob having an axis of rotation, a pin mechanism, and a slider body. The pin mechanism is engaged with the rotatable knob and includes a pin that is offset from an axis of rotation of the rotatable knob. The slider body may be shaped to include a slot in which the pin of the pin mechanism may be positioned. The slider body may further

13

be shaped to include a switch recess that is shaped to receive and selectively contact the switch of the electronic device when the electronic device is positioned proximate the slider body. Rotation of the rotatable knob in a first direction may cause the pin to travel in the slot in a first direction and move the slider body toward contact with a first portion of the switch to urge the switch into a first position (e.g., an active or enabled position). Rotation of the rotatable knob in a second direction may cause the pin to travel in the slot in a second direction and move the slider body toward contact with a second portion of the switch to urge the switch into a second position (e.g., a deactivated or disabled position). Such switch assembly allows for a switch of an electronic device to be completely enclosed, to prevent ingress of fluid and/or debris, without limiting operation of the switch. Additionally, the present devices provides an easier and more comfortable way to engage the switch of the electronic device.

It is noted that the terms “substantially” and “about” may be utilized herein to represent the inherent degree of uncertainty that may be attributed to any quantitative comparison, value, measurement, or other representation. These terms are also utilized herein to represent the degree by which a quantitative representation may vary from a stated reference without resulting in a change in the basic function of the subject matter at issue.

While particular embodiments have been illustrated and described herein, it should be understood that various other changes and modifications may be made without departing from the spirit and scope of the claimed subject matter. Moreover, although various aspects of the claimed subject matter have been described herein, such aspects need not be utilized in combination. It is therefore intended that the appended claims cover all such changes and modifications that are within the scope of the claimed subject matter.

What is claimed is:

1. A switch assembly for engaging a switch of an electronic device, the switch assembly comprising:

a rotatable knob having an axis of rotation;
a pin mechanism engaged with the rotatable knob and comprising a pin, the pin being offset from the axis of rotation of the rotatable knob; and

a slider body, the slider body being shaped to include a slot in which the pin of the pin mechanism is positioned and a switch recess, the switch recess being shaped to receive and selectively contact the switch of the electronic device when the electronic device is positioned within a protective case including the switch assembly such that the switch of the electronic device is positioned within the switch recess of the slider body, rotation of the rotatable knob in a first direction causing the pin to travel in the slot in a first direction and move the slider body toward contact with a first portion of the switch to urge the switch into a first position, and rotation of the rotatable knob in a second direction causing the pin to travel in the slot in a second direction and move the slider body toward contact with a second portion of the switch to urge the switch into a second position, wherein the slider body slides along a length of the protective case.

2. The switch assembly of claim 1, wherein the rotatable knob comprises:

a knob ring, and
a limit pin coupled the knob ring, wherein the limit pin limits an angular rotation of the rotatable knob.

14

3. The switch assembly of claim 1, wherein the slot defines a travel path perpendicular to the axis of rotation of the rotatable knob.

4. The switch assembly of claim 1, wherein the pin mechanism comprises:

a stem comprising a first end and a second end; and
a plate coupled to the second end of the stem, wherein the pin is coupled to the plate and extends therefrom and into the slot of the slider body.

5. The switch assembly of claim 4, wherein:
the rotatable knob comprises a pass-through opening; and
the first end of the stem is positioned within the pass-through opening of the rotatable knob such that the stem is non-rotatable relative to the rotatable knob.

6. A protective case for an electronic device, the protective case comprising:

a frame shaped to receive the electronic device therein; and

a switch assembly coupled to the frame for engaging a switch of the electronic device, the switch assembly comprising:

a rotatable knob having an axis of rotation;
a pin mechanism engaged with the rotatable knob and comprising a pin, the pin being offset from the axis of rotation of the rotatable knob; and

a slider body, the slider body being shaped to include a slot in which the pin of the pin mechanism is positioned and a switch recess, the switch recess being shaped to receive and selectively contact the switch of the electronic device when the electronic device is positioned within the protective case such that the switch of the electronic device is positioned within the switch recess of the slider body, rotation of the rotatable knob in a first direction causing the pin to travel in the slot in a first direction and move the slider body toward contact with a first portion of the switch to urge the switch into a first position, and rotation of the rotatable knob in a second direction causing the pin to travel in the slot in a second direction and move the slider body toward contact with a second portion of the switch to urge the switch into a second position, wherein the slider body slides along a length of the protective case.

7. The protective case of claim 6, wherein:

the rotatable knob comprises:

a knob ring, and
a limit pin coupled the knob ring; and
the frame defines a rotational limit slot formed therein, wherein the limit pin is positioned within the rotational limit slot and movement of the pin through the rotational limit slot limits an angular rotation of the rotatable knob.

8. The protective case of claim 6, wherein the frame defines a slider groove defining a slide path and the slider body is slidably disposed within the slider groove.

9. The protective case of claim 8, further comprising a locking mechanism positioned to restrict motion of the slider body in a direction transverse to the slide path.

10. The protective case of claim 9, wherein the locking mechanism comprises:

an elongate body spanning across a portion of the slider body;

a first locking prong coupled to a first end of the elongate body and inserted into the frame proximate to a first side of the slider groove; and

15

a second locking prong coupled to a second end of the elongate body and inserted into the frame proximate to a second side of the slider groove.

11. The protective case of claim 8, wherein the pin mechanism comprises:

a stem comprising a first end and a second end; and
a plate coupled to the second end of the stem, wherein the pin is coupled to the plate and extends therefrom and into the slot of the slider body.

12. The protective case of claim 11, wherein the frame further defines a plate-receiving groove formed within a back wall of the slider groove, wherein the plate is engaged with the plate-receiving groove and the stem extends through the frame from a first side of the frame to a second side of the frame, and wherein the first end of the stem is positioned within a pass-through opening of the rotatable knob such that the stem is non-rotatable relative to the rotatable knob.

13. A protective case for an electronic device, the protective case comprising:

a frame comprising a front portion and a back portion coupled together to define a cavity shaped to receive and encapsulate the electronic device having a switch;
a switch assembly positioned on one of the front portion or the back portion of the frame for engaging the switch of the electronic device when the electronic device is positioned in the cavity defined by the front portion and the back portion, the switch assembly comprising:

a rotatable knob having an axis of rotation;
a pin mechanism engaged with the rotatable knob and comprising a pin, the pin being offset from the axis of rotation of the rotatable knob; and

a slider body, the slider body being shaped to include a slot in which the pin of the pin mechanism is positioned and a switch recess, the switch recess being shaped to receive and selectively contact the switch of the electronic device when the electronic device is positioned within the protective case such that the switch of the electronic device is positioned within the switch recess of the slider body, rotation of the rotatable knob in a first direction causing the pin to travel in the slot in a first direction and move the slider body toward contact with a first portion of the switch to urge the switch into a first position, and rotation of the rotatable knob in a second direction causing the pin to travel in the slot in a second direction and move the slider body toward contact with a second portion of the switch to urge the switch into a

16

second position, wherein the slider body slides along a length of the protective case.

14. The protective case of claim 13, wherein: the rotatable knob comprises:

a knob ring, and
a limit pin coupled the knob ring; and
the front portion of the frame defines a rotational limit slot formed therein, wherein the limit pin is positioned within the rotational limit slot and movement of the pin through the rotational limit slot limits an angular rotation of the rotatable knob.

15. The protective case of claim 14, further comprising a locking mechanism positioned to restrict motion of the slider body in a direction transverse to a slide path of the slider body.

16. The protective case of claim 15, wherein the locking mechanism comprises:

an elongate body spanning across a portion of the slider body;
a first locking prong coupled to a first end of the elongate body and inserted into the frame proximate to a first side of a slider groove in which the slider body is slidably disposed; and
a second locking prong coupled to a second end of the elongate body and inserted into the frame proximate to a second side of the slider groove.

17. The protective case of claim 15, wherein the locking mechanism comprises an elongate body and a first locking prong at a first end of the elongate body and a second locking prong at a second end of the elongate body.

18. The protective case of claim 13, wherein the front portion of the frame defines a slider groove defining a slide path and the slider body is slidably disposed within the slider groove.

19. The protective case of claim 18, wherein the pin mechanism comprises:

a stem comprising a first end and a second end; and
a plate coupled to the second end of the stem, wherein the pin is coupled to the plate and extends therefrom and into the slot of the slider body.

20. The protective case of claim 19, wherein the front portion of the frame wherein the frame further defines a plate-receiving groove formed within a back wall of the slider groove, wherein the plate is engaged with the plate-receiving groove and the stem extends through the frame from a first side of the frame to a second side of the frame, and wherein the first end of the stem is positioned within a pass-through opening of the rotatable knob such that the stem is non-rotatable relative to the rotatable knob.

* * * * *