

US011078913B2

(12) **United States Patent**  
**Duppert**

(10) **Patent No.:** **US 11,078,913 B2**  
(45) **Date of Patent:** **Aug. 3, 2021**

(54) **TWO-PIECE SUCTION FITTING**

(56) **References Cited**

(71) Applicant: **Ronald J. Duppert**, Fayetteville, NY  
(US)

U.S. PATENT DOCUMENTS

(72) Inventor: **Ronald J. Duppert**, Fayetteville, NY  
(US)

3,870,440 A \* 3/1975 Zuercher, Jr. .... F04B 39/123  
417/902

(73) Assignee: **BITZER Kuehlmaschinenbau GmbH**,  
Sindelfingen (DE)

5,366,352 A 11/1994 Deblois et al.  
5,547,344 A \* 8/1996 Sugiyama ..... F04C 23/008  
137/625.43

6,171,084 B1 1/2001 Wallis et al.  
6,257,846 B1 \* 7/2001 Muramatsu ..... F04B 39/123  
417/410.3

(Continued)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 1164 days.

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **14/755,257**

CN 1243202 A 2/2000  
CN 1400392 A 3/2003

(Continued)

(22) Filed: **Jun. 30, 2015**

OTHER PUBLICATIONS

(65) **Prior Publication Data**

US 2017/0002812 A1 Jan. 5, 2017

U.S. Appl. No. 14/741,137, filed Jun. 16, 2015, Bessel et al.

*Primary Examiner* — Deming Wan

(74) *Attorney, Agent, or Firm* — Reinhart Boerner Van  
Deuren P.C.

(51) **Int. Cl.**

**F04C 18/02** (2006.01)

**F04C 29/12** (2006.01)

**F01C 21/10** (2006.01)

**F04C 23/00** (2006.01)

(57) **ABSTRACT**

A suction fitting coupled to a scroll compressor that has an outer housing with an inside diameter and a suction port defined in a wall of the outer housing. A suction duct is disposed inside the outer housing at a spaced distance from the wall of the outer housing. The suction duct defines an entrance port aligned with the suction port. The suction fitting includes a first member being generally cylindrical, and a second member being generally cylindrical. The second member is disposed inside the first member with a portion of the second member extending into the outer housing through the suction port, spanning the spaced distance to the suction duct, and coupling with the entrance port of the suction duct. Neither the first member nor the second member includes a suction screen for filtering out solid contaminants in a flow of refrigerant.

(52) **U.S. Cl.**

CPC ..... **F04C 29/12** (2013.01); **F01C 21/10**  
(2013.01); **F04C 18/0215** (2013.01); **F04C**  
**23/008** (2013.01); **F04C 2230/60** (2013.01);  
**F04C 2240/806** (2013.01)


(58) **Field of Classification Search**

CPC .. **F04C 18/0261**; **F04C 18/0215**; **F04C 29/12**;  
**F04C 23/008**; **F01C 21/10**

USPC ..... **418/55.1–55.6**, **180**, **46–47**; **285/158**;  
**248/49**, **58**

See application file for complete search history.

**9 Claims, 4 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS


6,398,530	B1	6/2002	Hasemann	
6,428,292	B1	8/2002	Wallis et al.	
6,582,211	B2	6/2003	Wallis et al.	
6,814,551	B2	11/2004	Kammhoff et al.	
6,960,070	B2 *	11/2005	Kammhoff .....	F04C 29/126 184/6.18
7,112,046	B2	9/2006	Kammhoff et al.	
8,133,043	B2 *	3/2012	Duppert .....	F04C 23/008 418/270
8,167,595	B2	5/2012	Duppert	
2003/0072662	A1 *	4/2003	Reinhart .....	F04C 23/008 418/55.1
2009/0041602	A1 *	2/2009	Ginies .....	F04C 23/008 418/55.1
2009/0185932	A1 *	7/2009	Beagle .....	F04C 23/008 418/55.2
2010/0092320	A1	4/2010	Duppert	
2010/0215533	A1	8/2010	Kiyokawa et al.	
2013/0248022	A1	9/2013	Roof	
2015/0354567	A1 *	12/2015	Lin .....	F04C 29/023 417/410.5
2016/0195090	A1 *	7/2016	Toyama .....	F04C 23/008 418/55.5

FOREIGN PATENT DOCUMENTS

CN	101223364	A	7/2008
EP	0974755	A2	1/2000
JP	2001-1280266	A	10/2001
JP	2003120539	A	4/2003

\* cited by examiner





**FIG. 1**  
PRIOR ART






FIG. 2




FIG. 3






FIG. 4



**TWO-PIECE SUCTION FITTING**

## FIELD OF THE INVENTION

The present invention relates to fittings for scroll compressors for compressing refrigerant and more particularly relates to suction fitting members at the inlet of such scroll compressors.

## BACKGROUND OF THE INVENTION

A scroll compressor is a certain type of compressor that is used to compress refrigerant for such applications as refrigeration, air conditioning, industrial cooling and freezer applications, and/or other applications where compressed fluid may be used. Such prior scroll compressors are known, for example, as exemplified in U.S. Pat. No. 6,398,530 to Hasemann; U.S. Pat. No. 6,814,551, to Kammhoff et al.; U.S. Pat. No. 6,960,070 to Kammhoff et al.; U.S. Pat. No. 7,112,046 to Kammhoff et al. and U.S. Pat. No. 8,167,595 to Duppert, all of which are assigned to a Bitzer entity closely related to the present assignee. As the present disclosure pertains to improvements that can be implemented in these or other scroll compressor designs, the entire disclosures of U.S. Pat. Nos. 6,398,530; 7,112,046; 6,814,551; 6,960,070, and 8,167,595 are hereby incorporated by reference in their entireties.

Additionally, particular embodiments of scroll compressors are disclosed in U.S. Pat. No. 6,582,211 to Wallis et al., U.S. Pat. No. 6,428,292 to Wallis et al., and U.S. Pat. No. 6,171,084 to Wallis et al., the teachings and disclosures of which are hereby incorporated by reference in their entireties.

As is exemplified by these patents, scroll compressors conventionally include an outer housing having a scroll compressor contained therein. A scroll compressor includes first and second scroll compressor members. A first compressor member is typically arranged stationary and fixed in the outer housing. A second scroll compressor member is moveable relative to the first scroll compressor member in order to compress refrigerant between respective scroll ribs which rise above the respective bases and engage in one another. Conventionally the moveable scroll compressor member is driven about an orbital path about a central axis for the purposes of compressing refrigerant. An appropriate drive unit, typically an electric motor, is provided usually within the same housing to drive the movable scroll member.

The present invention pertains to improvements in the state of the art.

## BRIEF SUMMARY OF THE INVENTION

The present invention is directed toward a suction fitting member for a scroll compressor incorporating such a suction fitting, that may be used to bridge the distance between an inlet fitting and an internal suction duct within a scroll compressor housing.

This disclosure describes a suction fitting coupled to a scroll compressor. The scroll compressor includes an outer housing having an inside diameter and a suction port defined in a wall of the outer housing. A suction duct is disposed inside the outer housing a spaced distance from the wall of the outer housing with the suction duct defining an entrance port aligned with the suction port.

The suction fitting includes a first member and a second member with the second member configured to slide through the first member to engage the suction duct disposed in the outer housing.

The first member is generally cylindrical and has a body portion with a second inside diameter and a nose portion with a first inside diameter. The second inside diameter is larger than the first inside diameter and the nose portion is disposed in the suction port defined in the outer housing.

The second member is generally cylindrical and has a body portion with a second outside diameter and a nose portion with a first outside diameter. The second outside diameter is larger than the first outside diameter with the second member disposed inside the first member with the nose portion of the second member extending into the outer housing through the suction port and spanning the spaced distance to the suction duct. The nose portion of the second member couples with the entrance port of the suction duct. Neither the first member nor the second member includes a suction screen for filtering out solid contaminants in a flow of refrigerant.

In one embodiment, an annular land is defined inside the first member by a change of inside diameter from the second inside diameter to the first inside diameter. The annular land is configured to butt against the body portion of the second member creating an annular seal of the second member to the first member. With second member sealed against the first member and with the nose portion of the second member engaged with the suction duct, substantially all of the fluid flow into the compressor housing does not bypass the suction duct since the nose portion bridges the spaced distance between the inside wall of the outer housing and the suction duct.

In another embodiment, the change of inside diameter is defined by a curve from the second inside diameter to the first inside diameter of the first member. In another embodiment, a series of annular steps may define the change of inside diameter of the first member.

With the second member installed in the first member and engaged with the entrance port, an unimpeded fluid flow path from a distal end of the first member to the suction duct is established. With the fluid flow not impeded through the suction fitting, a reduction of pressure drop along the flow path results in an increase in compressor efficiency.

In an embodiment, the suction fitting second member is composed of sheet metal, and the suction fitting first member is a turned steel component. In certain embodiments, the first member defines a first inside diameter, and the second member defines a second inside diameter, and, to reduce a flow restriction through the suction fitting. The second inside diameter is at least 95% of the diameter of the first inside diameter.

In at least one embodiment, the flow of refrigerant is directed through an opening of the second member, the opening having a cross-sectional area of at least 5 sq. cm.

In more particular embodiments, the second member provides a limiting flow restriction, wherein, by being free of a suction screen, the limiting flow restriction is no greater than 0.5 psi gage at a flow rate of 10 cubic feet per minute (cfm) through the suction fitting. The scroll compressor may include a suction duct screen disposed in the suction duct, the suction duct screen having no contact with the suction fitting.

There is also disclosed a method for installing a suction fitting in a scroll compressor. The scroll compressor includes an outer housing having an inside diameter and a suction port defined in a wall of the outer housing. A suction duct is disposed in the outer housing a spaced distance from the wall of the outer housing. The suction duct defines an entrance port aligned with the suction port.



The method includes installing a first member of the suction fitting into the suction port. The first member is generally cylindrical and has a body portion with a second inside diameter and a nose portion with a first inside diameter. The second inside diameter is larger than the first inside diameter and the nose portion is disposed in the suction port. The nose portion extends into the wall defining the suction port.

A second member of the suction fitting is inserted into the first member with the second member being generally cylindrical and having a body portion with a second outside diameter and a nose portion with a first outside diameter. The second outside diameter is larger than the first outside diameter with the second member disposed inside the first member with the nose portion of the second member extending through the wall of the outer housing through the suction port. The nose portion is spanning the spaced distance to the suction duct and coupling with the entrance port of the suction duct. In this method, neither the first member nor the second member includes a suction screen for filtering out solid contaminants in a flow of refrigerant.

The method includes butting the body portion of the second member against an annular land defined by a change of inside diameter of the first member from the second inside diameter to the first inside diameter. In one embodiment, the change of inside diameter is defined by a curve from the second inside diameter to the first inside diameter. With the second member inserted into the first member and engaging the suction duct an unimpeded fluid flow path is established from a distal end of the first member to the suction duct with the second member installed in the first member and engaged with the entrance port.

Other aspects, objectives and advantages of the invention will become more apparent from the following detailed description when taken in conjunction with the accompanying drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings incorporated in and forming a part of the specification illustrate several aspects of the present invention and, together with the description, serve to explain the principles of the invention. In the drawings:

FIG. 1 is a cross-section of a scroll compressor assembly in accordance with a prior art embodiment of a scroll compressor including a unitarily formed suction screen member;

FIG. 2 is a partial cross-section and cut-away view of a scroll compressor embodiment including an exemplary embodiment of a two-piece suction fitting, without a screen member, installed in the scroll compressor housing;

FIG. 3 is a detail cross-section of the two-piece suction fitting illustrated in FIG. 2, along the line 3-3;

FIG. 4 is a detail cross-section of the two-piece suction fitting illustrated in FIG. 3, with a second member (in broken line) of the two-piece suction fitting being disposed inside a first member of the two-piece with a nose portion of the second member extending into the scroll compressor housing and spanning the spaced distance from the housing inside wall to a suction duct inside the scroll housing.

While the invention will be described in connection with certain preferred embodiments, there is no intent to limit it to those embodiments. On the contrary, the intent is to cover all alternatives, modifications and equivalents as included within the spirit and scope of the invention as defined by the appended claims.

#### DETAILED DESCRIPTION OF THE INVENTION

A prior art embodiment of a scroll compressor is illustrated in FIG. 1. An embodiment of the present invention is illustrated in FIGS. 2-4 as a scroll compressor assembly 100 generally including an outer housing 106 in which a scroll compressor 102 can be driven by a drive unit 104. The scroll compressor assembly 100 may be arranged in a refrigerant circuit for refrigeration, industrial cooling, freezing, air conditioning or other appropriate applications where compressed fluid is desired. Appropriate connection ports provide for connection to a refrigeration circuit and include a refrigerant inlet port, also referred to as a suction port 108, and a refrigerant outlet port 112 extending through the outer housing 106. The scroll compressor assembly 100 is operable through operation of the drive unit 104 to operate the scroll compressor 102 and thereby compress an appropriate refrigerant or other fluid that enters the refrigerant inlet port 108 and exits the refrigerant outlet port 112 in a compressed high-pressure state.

A scroll compressor assembly with an inlet fitting and suction screen member is disclosed in U.S. Pat. No. 8,167,595 (hereinafter "the '595 patent", issued May 1, 2012, which has been incorporated by reference. The suction screen disclosed in the '595 patent, like that shown in FIG. 1, is configured to screen out solid contaminants in the flow of refrigerant. However, the suction screen does interfere, at least to some degree, with the flow of refrigerant, which results in a pressure drop which could adversely affect the efficiency of the compressor. In some scroll compressors, a larger screen may be placed in the suction duct 136. U.S. patent application Ser. No. 14/741,137, filed Jun. 16, 2015 discloses scroll compressors having screens in the suction duct for filtering out solid contaminants from refrigerant gas. The entire teachings and disclosure of U.S. patent application Ser. No. 14/741,137 are incorporated herein by reference thereto.

In particular embodiments, the larger screen results in a lower pressure drop and increased efficiency due to a decreased interference with the flow of refrigerant. As will be shown below, embodiments of the present invention include suction fittings that do not include a suction screen. It is envisioned that these screenless suction fittings may be used in conjunction with larger screens located either in the suction duct or elsewhere within the compressor housing. This configuration typically allows for greater flow of refrigerant flow than in conventional scroll compressors having suction screens designed to fit through the inlet fitting.

The outer housing 106 may take many forms. In the preferred embodiment, the outer housing includes multiple shell sections and preferably three shell sections to include a central cylindrical housing section 114, a top end housing section 118 and a bottom end housing section 122. Preferably, the housing sections 114, 118, 122 are formed of appropriate sheet steel and welded together to make a permanent outer housing 106 enclosure. However, if disassembly of the housing is desired, other housing provisions can be made that can include metal castings or machined components.

The central housing section 114 is preferably cylindrical and telescopically interfits with the top and bottom end housing sections 118, 122. This forms an enclosed chamber 126 for housing the scroll compressor 102 and drive unit 104. Each of the top and bottom end housing sections 118, 122 are generally dome shaped and include respective cylindrical side wall regions 120, 124 to mate with the center



section **114** and provide for closing off the top and bottom ends of the outer housing **106**. As can be seen in FIG. **1**, the top side wall region **120** telescopically overlaps the central housing section **114** and is exteriorly welded along a circular welded region to the top end of the central housing section **114**. Similarly the bottom side wall region **124** of the bottom end housing section **122** telescopically interfits with the central housing section **114** (but is shown as being installed into the interior rather than the exterior of the central housing section **114**) and is exteriorly welded by a circular weld region.

The drive unit **104** may preferably take the form of an electrical motor assembly **128**, which is supported by upper and lower bearing members **130**, **132**. The motor assembly **128** operably rotates and drives a shaft **134**. The electrical motor assembly **128** generally includes an outer annular motor housing, a stator comprising electrical coils and a rotor that is coupled to the drive shaft **134** for rotation together. Energizing the stator is operative to rotatably drive the rotor and thereby rotate the drive shaft **134** about a central axis.

During operation, the scroll compressor assembly **100** is operable to receive low-pressure refrigerant at the housing inlet port **108** and compress the refrigerant for delivery to the high-pressure chamber, where it can be output through the housing outlet port **112**. As shown in FIG. **1**, a suction duct **136** is connected internally of the housing **106** to guide the lower-pressure refrigerant from the inlet port **108** into housing and beneath the motor housing. This allows the low-pressure refrigerant to flow through and across the motor and thereby cool and carry heat away from the motor which can be caused by operation of the motor. Low-pressure refrigerant can then pass longitudinally through the motor housing and around through void spaces therein toward the top end where it can exit through a plurality of motor housing outlets that are equally angularly spaced about the central axis. The motor housing outlets may be defined either in the motor housing, the upper bearing member or by a combination of the motor housing and upper bearing member.

Upon exiting the motor housing outlet, the low-pressure refrigerant enters an annular chamber **142** formed between the motor housing and the outer housing. From there, the low-pressure refrigerant can pass through the upper bearing member through a pair of opposed outer peripheral through ports that are defined by recesses on opposed sides of the upper bearing member **130** to create gaps between the bearing member **130** and housing **106**. Upon passing through the upper bearing member **130** the low-pressure refrigerant finally enters the intake area of the scroll compressor bodies. From the intake area, the lower-pressure refrigerant finally enters the scroll ribs on opposite sides and is progressively compressed through chambers to where it reaches its maximum compressed state at the compression outlet where it subsequently passes through the check valve and into the high-pressure chamber. From there, high-pressure, compressed refrigerant may then pass from the scroll compressor assembly **100** through the refrigerant housing outlet port **112**.

Referring to FIGS. **2-4**, it is seen that a screenless suction duct **136** is preferably employed to direct incoming fluid flow (e.g. refrigerant) from the housing inlet **108** to the stator housing. To provide for the inlet port **108**, the housing includes an inlet opening **110** in which a suction fitting **144** is provided that may include a connector such as threads or other such connection means such as a barb or quick connect coupler, for example. The suction fitting **144** is welded to the

housing shell in engagement with the inlet opening **110**. The inlet opening **110** and the suction fitting **144** are thereby provided for communicating the refrigerant into the housing.

The suction fitting is provided to form a common bridge and thereby communicate refrigerant from the inlet **108** through the entrance opening and port **138** formed in the suction duct **136**. Substantially all (in other words—all or most) of the incoming refrigerant is thereby directed through the suction fitting **144**. Once passing through the suction fitting, refrigerant is then directed by the suction duct **136** to a location upstream and at the entrance of the motor housing.

Turning in greater detail to the suction duct **136**, and referring to FIGS. **2-4**, it is seen that the suction duct comprises a stamped sheet steel metal body having a wall thickness with an outer generally rectangular and arcuate mounting flange which surrounds a duct channel that extends between a top end and a bottom end. The entrance opening and port is formed through a channel bottom proximate the top end. This opening and port provide means for communicating and receiving fluid from the inlet **110** via a suction fitting **144** which is received through the outer compressor housing wall **116** and into duct channel of the suction duct **136**.

Preferably, the suction duct **136** is a metal stamping of sheet metal to provide the body and wall structure of the suction duct **136** as a unitary member. The rectangular and arcuate mounting flange and the duct channel can readily be stamped into the sheet metal to provide an elongated duct channel and bottom grooves as well as the fastener holes. The entrance port **138** is also formed by stamping and punching out the generally circular opening from the sheet metal. Material stamp forming of the punched out area creates an annular opening flange **140** defining the entrance port **138**, which projects from the channel bottom toward the mounting flange. The annular opening flange **140** tapers as it extends radially inward and away from the channel bottom of the suction duct so as to provide a tapered guide surface that facilitates insertion and assembly of the suction fitting into engagement and received within the suction duct **136**.

Turning in greater detail to the suction fitting **144** with additional reference to FIGS. **2-4**, the suction fitting as shown in FIG. **3**, bridges the gap or spaced distance, between the inlet **108** and the internal suction duct **136**. As shown, the entrance port **138** of the suction duct **136** is aligned with the inlet port **108** formed by the inlet opening **110** for the compressor housing. Preferably these openings are diametrically and concentrically aligned. The suction fitting acts as a bridging function bridging the spaced distance between the suction inlet **108** and the suction duct **136**.

This disclosure describes a suction fitting **144** coupled to a scroll compressor **102**. The scroll compressor **102** includes an outer housing **106** having an inside diameter and a suction port **108** defined in a wall **116** of the outer housing **106**. A suction duct **136** is disposed inside the outer housing **106** a spaced distance from the wall **116** of the outer housing **106** with the suction duct **136** defining an entrance port **138** aligned with the suction port **108**.

The suction fitting **144** includes a first member **146** and a second member **158** with the second member **158** configured to slide through the first member **146** to engage the suction duct **136** disposed in the outer housing **106**.

The first member **146** is generally cylindrical and has a body portion **148** with a second inside diameter **150** and a nose portion **154** with a first inside diameter **156**. The second inside diameter **150** is larger than the first inside diameter



**156** and the nose portion **154** is disposed in the suction port **108** defined in the outer housing **106**.

The second member **158** is generally cylindrical and has a body portion **160** with a second outside diameter **162** and a nose portion **164** with a first outside diameter **166**. The second outside diameter **162** is larger than the first outside diameter **166** with the second member **158** disposed inside the first member **146** with the nose portion **164** of the second member **158** extending into the outer housing **106** through the suction port **108** and spanning the spaced distance to the suction duct **136**. The nose portion **164** of the second member **158** couples with the entrance port **138** of the suction duct **136**.

In another embodiment, an annular land **168** is defined inside the first member **146** by a change of inside diameter from the second inside diameter **150** to the first inside diameter **156**. The annular land **168** is configured to butt against the body portion **160** of the second member **158** creating an annular seal **170** of the second member **158** to the first member **146**. The second member **158** sealed against the first member **146** and with the nose portion **164** of the second member **158** engaged with the suction duct **136**, substantially all of the fluid flow into the compressor housing **106** does not bypass the suction duct **136** since the nose portion **164** bridges the spaced distance between the inside face of the wall **116** of the outer housing **106** and the suction duct **136**.

In an embodiment, the change of inside diameter is defined by a curve **172** from the second inside diameter **150** to the first inside diameter **156** of the first member **146**. A series of annular steps may also alternatively define the change of inside diameter of the first member.

With the second member **158** installed in the first member **146** and engaged with the entrance port **138**, and by omitting any type of suction screen on the suction fitting **144**, an unimpeded fluid flow path from a distal end **152** of the first member **146** to the suction duct **136** is established. With the fluid flow not impeded through the suction fitting **144**, a reduction of the pressure drop, normally associated with conventional fittings having a suction screen, along the flow path results in an increase in compressor efficiency.

In an embodiment, the suction fitting second member **158** is composed of sheet metal, and the first member **146** is composed of turned steel.

There is also disclosed a method for installing a suction fitting **144** in a scroll compressor assembly **100**. The scroll compressor assembly **100** includes an outer housing **106** having an inside diameter and a suction port **108** defined in a wall **116** of the outer housing **106**. A suction duct **136** is disposed in the outer housing **106** a spaced distance from the wall **116** of the outer housing **106**. The suction duct **136** defines an entrance port **138** aligned with the suction port **108**.

The method includes installing a first member **146** of the suction fitting **144** into the suction port **108**. The first member **146** is generally cylindrical and has a body portion **148** with a second inside diameter **150** and a nose portion **154** with a first inside diameter **156**. The second inside diameter **150** is larger than the first inside diameter and the nose portion **154** is disposed in the suction port **108**. The nose portion **154** extends into the wall **116** defining the suction port **108**.

A second member **158** of the suction fitting **144** is inserted into the first member **146** with the second member **158** being generally cylindrical and having a body portion **160** with a second outside diameter **162** and a nose portion **164** with a first outside diameter **166**. The second outside diameter **162**

is larger than the first outside diameter **166** with the second member **158** disposed inside the first member **146** with the nose portion **164** of the second member **158** extending through the wall **116** of the outer housing **106** through the suction port **108**. The nose portion **164** spans the spaced distance to the suction duct **136** and couples with the entrance port **138** of the suction duct **136**.

The method includes butting the body portion **160** of the second member **158** against an annular land **168** defined by a change of inside diameter of the first member **146** from the second inside diameter **150** to the first inside diameter **156**. In one embodiment, the change of inside diameter is defined by a curve **172** from the second inside diameter **150** to the first inside diameter **156**. With the second member **158** inserted into the first member **146** and engaging the suction duct **136** an unimpeded fluid flow path is established from a distal end **152** of the first member **146** to the suction duct **136** with the second member **158** installed in the first member **146** and engaged with the entrance port **138** forming an annular seal **170**.

As explained above, in certain embodiments, the first member **146** has second inside diameter **150**, while the second member **158** has first inside diameter **156**. To reduce a flow restriction through the suction fitting **144**, the first inside diameter **156** is at least 95% of the diameter of the second inside diameter **150**.

In at least one embodiment, the flow of refrigerant is directed through an opening of the second member **158**, the opening having a minimum cross-sectional area of at least 5 sq. cm.

In more particular embodiments, the second member **158** provides a limiting flow restriction, wherein, by being free of a suction screen, the limiting flow restriction is no greater than 0.5 psi gage at a flow rate of 10 cubic feet per minute (cfm) through the suction fitting **144**. The scroll compressor **100** may include a suction duct screen disposed in the suction duct **136**, the suction duct screen having no contact with the suction fitting **144**.

Recognizing that there can be tolerance issues and/or assembly inaccuracies that result in slight misalignments between the suction duct and the inlet fitting in their respective openings, different means are contemplated for accommodating misalignment. For example, in the present embodiment, the second member **158** provides a surface of the nose portion **154** that helps to self locate during installation, as it can co-act with a tapered guide surface on the suction duct **136** to guide insertion. The second member **158** is configured to be closely received into complete or almost complete circular engagement with the opening flange **140** of the suction duct **136**.

All references, including publications, patent applications, and patents cited herein are hereby incorporated by reference to the same extent as if each reference were individually and specifically indicated to be incorporated by reference and were set forth in its entirety herein.

For purposes of this disclosure, the term "coupled" means the joining of two components (electrical or mechanical) directly or indirectly to one another. Such joining may be stationary in nature or moveable in nature. Such joining may be achieved with the two components (electrical or mechanical) and any additional intermediate members being integrally formed as a single unitary body with one another or the two components and any additional member being attached to one another. Such adjoining may be permanent in nature or alternatively be removable or releasable in nature.



The use of the terms “a” and “an” and “the” and similar referents in the context of describing the invention (especially in the context of the following claims) is to be construed to cover both the singular and the plural, unless otherwise indicated herein or clearly contradicted by context. The terms “comprising,” “having,” “including,” and “containing” are to be construed as open-ended terms (i.e., meaning “including, but not limited to,”) unless otherwise noted. Recitation of ranges of values herein are merely intended to serve as a shorthand method of referring individually to each separate value falling within the range, unless otherwise indicated herein, and each separate value is incorporated into the specification as if it were individually recited herein. All methods described herein can be performed in any suitable order unless otherwise indicated herein or otherwise clearly contradicted by context. The use of any and all examples, or exemplary language (e.g., “such as”) provided herein, is intended merely to better illuminate the invention and does not pose a limitation on the scope of the invention unless otherwise claimed. No language in the specification should be construed as indicating any non-

claimed element as essential to the practice of the invention. Preferred embodiments of this disclosure are described herein, including the best mode known to the inventors for carrying out the invention. Variations of those preferred embodiments may become apparent to those of ordinary skill in the art upon reading the foregoing description. The inventors expect skilled artisans to employ such variations as appropriate, and the inventors intend for the disclosure to be practiced otherwise than as specifically described herein. Accordingly, this disclosure includes all modifications and equivalents of the subject matter recited in the claims appended hereto as permitted by applicable law. Moreover, any combination of the above-described elements in all possible variations thereof is encompassed by the disclosure unless otherwise indicated herein or otherwise clearly contradicted by context.

What is claimed is:

1. A suction fitting coupled to a scroll compressor, the scroll compressor including an outer housing having an inside diameter and a suction port defined in a wall of the outer housing, and a suction duct disposed inside the outer housing a spaced distance from the wall of the outer housing, the suction fitting comprising:

a first member being generally cylindrical, the first member being installed in the suction port; and

a second member being generally cylindrical, with the second member disposed inside the first member with a portion of the second member extending into the outer housing through the suction port and spanning the spaced distance to the suction duct and coupling with an entrance port of the suction duct;

wherein the suction duct defines the entrance port aligned with the suction port, the suction port having openings at bottom end thereof to guide refrigerant from the inlet

port into the housing and beneath a motor housing of the scroll compressor, and to guide oil to an oil sump of the scroll compressor;

wherein neither the first member nor the second member includes a suction screen for filtering out solid contaminants in a flow of refrigerant;

wherein the first member defines a first inside diameter, and the second member defines a second inside diameter, and, to reduce a flow restriction through the suction fitting, the second inside diameter is at least 95% of the diameter of the first inside diameter.

2. The suction fitting coupled to a scroll compressor of claim 1, wherein the first member has a body portion with the second inside diameter and a nose portion with the first inside diameter, with the second inside diameter larger than the first inside diameter, and the nose portion disposed in the suction port, and the second member has a body portion with a second outside diameter and a nose portion with a first outside diameter, with the second outside diameter larger than the first outside diameter.

3. The suction fitting coupled to a scroll compressor of claim 2, further comprising an annular land inside the first member defined by a change of inside diameter from the second inside diameter to the first inside diameter, the annular land configured to butt against the body portion of the second member comprising an annular seal of the second member to the first member.

4. The suction fitting coupled to a scroll compressor of claim 3 with the change of inside diameter is defined by a curve from the second inside diameter to the first inside diameter.

5. The suction fitting coupled to a scroll compressor of claim 1, wherein the suction fitting, with the second member installed in the first member and engaged with the entrance port, provides a fluid flow path from a distal end of the first member to the suction duct.

6. The suction fitting coupled to a scroll compressor of claim 1, wherein each of the first member and second member is composed of metal.

7. The suction fitting coupled to a scroll compressor of claim 6, wherein the first member is turned steel and the second member is sheet metal.

8. The suction fitting coupled to a scroll compressor of claim 1, wherein the second member provides a limiting flow restriction, wherein, by being free of a suction screen, the limiting flow restriction is no greater than 0.5 psi gage at a flow rate of 10 cfm through the suction fitting.

9. The suction fitting coupled to a scroll compressor of claim 1, wherein the flow of refrigerant is directed through an opening of the second member, the opening having a minimum cross-sectional area of at least 5 sq. cm.

\* \* \* \* \*

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : 11,078,913 B2  
APPLICATION NO. : 14/755257  
DATED : August 3, 2021  
INVENTOR(S) : Ronald J. Duppert

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Claims

In Column 9, Claim 1, Line 16, delete “with the suction port, the suction port having openings” and insert -- with the suction port, the suction duct having openings --

Signed and Sealed this  
Twenty-eighth Day of September, 2021



Drew Hirshfeld  
*Performing the Functions and Duties of the  
Under Secretary of Commerce for Intellectual Property and  
Director of the United States Patent and Trademark Office*