

US011086597B2

(12) **United States Patent**  
**Yuan et al.**

(10) **Patent No.: US 11,086,597 B2**  
(45) **Date of Patent: Aug. 10, 2021**

(54) **METHODS AND SYSTEMS FOR ATTENDING TO A PRESENTING USER**

(71) Applicant: **GOOGLE LLC**, Mountain View, CA (US)

(72) Inventors: **Yuan Yuan**, San Jose, CA (US); **Johan Schalkwyk**, Sunnyvale, CA (US); **Kenneth Mixer**, Mountain View, CA (US)

(73) Assignee: **GOOGLE LLC**, Mountain View, CA (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/758,144**

(22) PCT Filed: **Aug. 14, 2018**

(86) PCT No.: **PCT/US2018/046654**  
§ 371 (c)(1),  
(2) Date: **Apr. 22, 2020**

(87) PCT Pub. No.: **WO2019/089108**  
PCT Pub. Date: **May 9, 2019**

(65) **Prior Publication Data**  
US 2020/0285443 A1 Sep. 10, 2020

**Related U.S. Application Data**  
(60) Provisional application No. 62/582,147, filed on Nov. 6, 2017.

(51) **Int. Cl.**  
**G10L 15/22** (2006.01)  
**G06F 3/16** (2006.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... **G06F 3/167** (2013.01); **G06F 3/165** (2013.01); **G06K 9/00302** (2013.01);  
(Continued)

(58) **Field of Classification Search**

CPC ..... G05D 1/0274; G06F 3/165; G06F 3/167;  
G06K 9/00302; G06K 9/00308;  
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,538,666 B1 \* 3/2003 Ozawa ..... G10L 15/22  
715/728  
6,914,622 B1 \* 7/2005 Smith ..... A47B 21/0073  
348/14.05

(Continued)

FOREIGN PATENT DOCUMENTS

EP 2492850 A1 8/2012  
WO WO 2007041295 A2 4/2007

OTHER PUBLICATIONS

Google LLC, International Search Report and Written Opinion, PCT/US2018/046654, dated Oct. 30, 2018, 10 pgs.


*Primary Examiner* — Gerald Gauthier

(74) *Attorney, Agent, or Firm* — Marshall, Gerstein & Borun LLP

(57) **ABSTRACT**

The various implementations described herein include methods, devices, and systems for attending to a presenting user. In one aspect, a method is performed at an electronic device that includes an image sensor, microphones, a display, processor(s), and memory. The device (1) obtains audio signals by concurrently receiving audio data at each microphone; (2) determines based on the obtained audio signals that a person is speaking in a vicinity of the device; (3) obtains video data from the image sensor; (4) determines via the video data that the person is not within a field of view of the image sensor; (5) reorients the electronic device based on differences in the received audio data; (6) after reorienting the electronic device, obtains second video data from the image sensor and determines that the person is within the

(Continued)



field of view; and (7) attends to the person by directing the display toward the person.

20 Claims, 14 Drawing Sheets

- (51)

Int. Cl.

G06K 9/00

(2006.01)

H04N 7/14

(2006.01)

H04N 7/15

(2006.01)

(52)

U.S. Cl.

CPC

G10L 15/22

(2013.01);

H04N 7/142

(2013.01);

H04N 7/15

(2013.01)

(58)

Field of Classification Search

CPC

G06K 9/00684; G06K 9/00221; G06K 9/00355; G10L 15/22; H04N 7/142; H04N 7/144; H04N 7/15; H04N 21/431; H04R 3/005; H04R 1/1083; G16H 40/67; H04L 12/1818; H04L 65/403

USPC

345/7, 156; 348/14.16, 14.08, 14.02, 348/14.05; 701/28; 704/201, 275, 276, 704/254; 382/254; 715/728

See application file for complete search history.

(56)

References Cited

U.S. PATENT DOCUMENTS

7,027,659	B1 *	4/2006	Thomas	H04N 13/383
				382/254
8,125,405	B2 *	2/2012	Dove	G06F 1/163
				345/7

8,296,151	B2 *	10/2012	Klein	G06F 3/038
				704/275
9,432,768	B1 *	8/2016	O'Neill	H04R 3/005
9,469,030	B2 *	10/2016	Wang	G06F 3/04842
9,635,072	B1 *	4/2017	Murphy	H04L 12/1818
9,942,513	B1 *	4/2018	Aarrestad	H04N 7/142
9,992,451	B2 *	6/2018	Ono	H04N 21/4788
10,140,515	B1 *	11/2018	Waldo	G06K 9/6273
2008/0180519	A1 *	7/2008	Cok	G06Q 10/10
				348/14.02
2010/0118112	A1 *	5/2010	Nimri	H04N 7/142
				348/14.08
2011/0082690	A1 *	4/2011	Togami	H04R 1/406
				704/201
2014/0172432	A1 *	6/2014	Sendai	G02C 11/10
				704/276
2015/0019226	A1 *	1/2015	Gazdzinski	G06F 21/44
				704/254
2015/0073646	A1 *	3/2015	Rosenstein	H04N 13/243
				701/28
2015/0331490	A1 *	11/2015	Yamada	G10L 25/78
				345/156
2015/0331664	A1 *	11/2015	Osawa	G10L 15/22
				704/275
2016/0028878	A1 *	1/2016	Davis	G06F 3/167
				704/275
2016/0057385	A1 *	2/2016	Burenius	H04N 7/147
				348/14.16
2016/0124501	A1 *	5/2016	Lam	G06F 3/048
				345/156
2017/0094179	A1 *	3/2017	Bellamy	H04N 5/91
2017/0308742	A1 *	10/2017	Yao	G06K 9/00221
2018/0260187	A1 *	9/2018	Yasuda	G06F 3/167
2018/0309957	A1 *	10/2018	Baldwin	G10L 25/78
2020/0285443	A1 *	9/2020	Yuan	G06F 3/167

\* cited by examiner




Figure 1B




Figure 1A






Figure 1C

Operating Environment 200




Figure 2




Figure 3




Figure 4






Figure 5A






Figure 5B




Figure 6A




Figure 6B






Figure 7A




Figure 7B




Figure 8A






Figure 8B




Figure 8C



## METHODS AND SYSTEMS FOR ATTENDING TO A PRESENTING USER

### CROSS REFERENCE TO RELATED APPLICATIONS

This application is a 35 U.S.C. § 371 U.S. National Stage Entry of International Application PCT/US2018/046654, entitled “Methods and Systems for Attending to a Presenting User,” filed Aug. 14, 2018, which claims the benefit of and priority to U.S. Provisional Application No. 62/582,147, entitled “Methods and Systems for Attending to a Presenting User,” filed Nov. 6, 2017. This application is also related to U.S. patent application Ser. No. 15/284,476, entitled “Multi-User Personalization at a Voice Interface Device,” filed Oct. 3, 2016, now U.S. Pat. No. 10,304,463. All of these applications are incorporated by reference in their entirety.

### TECHNICAL FIELD

This relates generally to automated assistants, including but not limited to methods and systems for attending to speaking person(s) in a room with an automated assistant.

### BACKGROUND

Electronic devices integrated with microphones and cameras are widely used to collect audio and visual data from users and implement voice-activated functions according to voice inputs. Devices are increasingly capable of accessing and presenting information to users. However, devices presenting visual information must be oriented toward a user in order for the user to view the presented information. This can be problematic for users who move between to different locations around the device.

Accordingly, it is desirable to employ an electronic device that is integrated with microphones and cameras to locate and orient on speaking person(s) in a room. For automated assistant devices, it is also desirable that they attend to users who are addressing them.

### SUMMARY

There is a need for methods, devices, and systems to locate and attend to speaking persons in a room. Various implementations of systems, methods and devices within the scope of the appended claims each have several aspects, no single one of which is solely responsible for the attributes described herein. Without limiting the scope of the appended claims, after considering this disclosure, and particularly after considering the section entitled “Detailed Description” one will understand how the aspects of various implementations are used to automatically (without user inputs) locate and attend to a speaking person. For example, there is a need for electronic devices that respond to both audio and visual user inputs. By locating user(s), indicating that they are listening to the user(s), and presenting visualizations to the user(s) in settings such as video conferences, these electronic devices create efficient and enhanced interactive experiences with users. Further, it is desirable for the electronic devices to show attention to a speaking person with mannerisms that will also seem natural to the user.

For example, an automated assistant device can be used to interact with user(s) via both audio and visual mediums. Such an assistant device can also use the audio and visual inputs to locate the users and attend to them (e.g., reorient itself to better receive information from the user and/or

better present information to the user). This improves the user’s experience as the user does not need to move to a particular location to view display data on the device, nor does the user need to reorient the device manually.

Electronic devices integrated with microphones and cameras are widely used to collect audio and visual inputs from users. By combining multiple sensing technologies, these electronic devices can find a user in a room with high accuracy and low latency.

The described implementations have an advantage over user localization methods based purely on audio signals, which have issues associated with finding paths to the user which may be non-direct. For example, in the case of a hard wall or surface behind a device, the device may find the path to the user as the path reflecting off the back wall.

In some implementations, an electronic device with multiple microphones and motor-mounted wide-lens camera is employed to locate user(s), e.g., to indicate that the device is listening to the user(s) or to obtain visualization of user(s) for video conferencing.

In some implementations, the user addresses the device with a known hotword/keyword. In some implementations, the device is configured to identify the speaking user. In some implementations, the device is configured to recognize the speaking user.

In some implementations, in response to detecting a hotword from a user, the device obtains video data from a camera of the device and determines based on the video data that the user is in the field of view of the camera. In some implementations, in accordance with a determination that the user is in the field of view of the camera, the device centers the user in the field of view of the camera.

In some instances, however, the user who is speaking is not in the field of view of the camera. In some implementations, after determining that the user is not in the field of view of the camera, the device reorients to look for the user. In some implementations, the device decides where to look based on beamforming of the audio received when user issued the hotword to the device. In some implementations, the device: (i) creates multiple hotword beams, (ii) identifies the beam that has the highest signal-to noise ratio, and (iii) locates the user in the direction of the beam with the highest signal-to-noise ratio. In some implementations, if the user is not located in the direction of the beam with the highest signal-to-noise ratio, the device proceeds to look in the direction of the beam with the second highest signal-to-noise ratio. In some implementations, the device can adaptively subdivide, looking up and down as well as left and right, by checking additional non-horizontal beams for power.

For example, a user John addresses the device with a hotword (“OK assistant.”) The device recognizes that the user is John by his voice, but does not see John in the camera’s view. The device determines that hotword energy is mostly coming from a direction that is behind and above the device, and accordingly, rotates and tilts the camera in the direction of the hotword energy. The device finds John’s face and centers the camera, assuring John that the device is attending to him.

Accordingly, by combining multiple advanced audio and visual sensing technologies, the device is able to find the user with high accuracy and low latency. In some implementations, the device’s mannerisms when looking for the user also seem natural to the user, thus improving the user interactions with the device.

In one aspect, some implementations include a method of attending to a presenting user performed at an electronic device having an image sensor, a plurality of microphones,



3

a display, one or more processors, and memory. The method includes: (1) obtaining audio signals by concurrently receiving audio data at each microphone of the plurality of microphones; (2) determining based on the obtained audio signals that a person is speaking in a vicinity of the electronic device; (3) obtaining video data from the image sensor; (4) determining based on analysis of the video data that the person is not within a field of view of the image sensor; (5) reorienting the electronic device based on differences in the audio data received at respective microphones of the plurality of microphones; (6) after reorienting the electronic device, obtaining second video data from the image sensor and determining from the second video data that the person is within the field of view of the image sensor; and (7) attending to the person by directing the display toward the person. In some implementations, the display includes a screen (e.g., a touch screen), one or more LEDs, and/or a user interface with one or more affordances.

In another aspect, some implementations include a computing system including one or more processors and memory coupled to the one or more processors, the memory storing one or more programs configured to be executed by the one or more processors, the one or more programs including instructions for performing any of the methods described herein.

In yet another aspect, some implementations include a non-transitory computer-readable storage medium storing one or more programs for execution by one or more processors of a computing system, the one or more programs including instructions for performing any of the methods described herein.

Thus, devices, storage mediums, and computing systems are provided with methods for attending to speaking users in a room, thereby enhancing user interactions (e.g., improving accuracy and/or efficiency in the interactions) and user satisfaction with such systems. Such methods may complement or replace conventional methods for interacting with users.

### BRIEF DESCRIPTION OF THE DRAWINGS

For a better understanding of the various described implementations, reference should be made to the Description of Implementations below, in conjunction with the following drawings in which like reference numerals refer to corresponding parts throughout the figures.

FIGS. 1A-1C illustrate representative electronic devices and displays for attending to a speaking user, in accordance with some implementations.

FIG. 2 is a block diagram illustrating a representative operating environment that includes an electronic device and a server system, in accordance with some implementations.

FIG. 3 is a block diagram illustrating a representative electronic device, in accordance with some implementations.

FIG. 4 is a block diagram illustrating a representative server system, in accordance with some implementations.

FIGS. 5A-5B illustrate a representative operation of the electronic device of FIG. 3, in accordance with some implementations.

FIGS. 6A-6B illustrate another representative operation of the electronic device of FIG. 3, in accordance with some implementations.

FIGS. 7A-7B illustrate another representative operation of the electronic device of FIG. 3, in accordance with some implementations.

4

FIGS. 8A-8C are flowchart representations of a method for attending to a presenting user, in accordance with some implementations.

Like reference numerals refer to corresponding parts throughout the several views of the drawings.

### DESCRIPTION OF IMPLEMENTATIONS

Reference will now be made in detail to implementations, examples of which are illustrated in the accompanying drawings. In the following detailed description, numerous specific details are set forth in order to provide a thorough understanding of the various described implementations. However, it will be apparent to one of ordinary skill in the art that the various described implementations may be practiced without these specific details. In other instances, well-known methods, procedures, components, circuits, and networks have not been described in detail so as not to unnecessarily obscure aspects of the implementations.

Electronic devices integrated with microphones and cameras can be used to collect audio and visual inputs from users and implement voice-activated functions according to voice inputs. Some electronic devices include a voice assistant feature that is configured to use audio inputs to perform many tasks. The functionality of these devices can be further expanded to locate and attend to user(s).

For example, Jane moves about a room while issuing multiple requests to an automated assistant device. The assistant device receives the requests and presents responses, which include visual information for Jane to view. In order to accommodate Jane's movement, the assistant device uses audio and visual cues to continually reorient on Jane as she moves about the room. This enables Jane to view the visual information without interrupting her activity. It also assures her that the assistant device is active and paying attention to her. In some instances, reorienting the assistant device also improves the quality of Jane's voice received at the device as well as the quality of device audio heard by Jane.

FIG. 1A illustrates an electronic device **100** for attending to a speaking user, in accordance with some implementations. In some implementations, the electronic device **100** includes microphones **102** (e.g., **102-1** and **102-2**), an array of illuminators **104** (e.g., LEDs), one or more speakers **106**, a camera **108**, and a display **110**. In some implementations, the electronic device **100** can rotate in a one or more directions (e.g., along an axis **112** and/or an axis **114** with the corresponding direction of rotation indicated by the respective arrows), thus enabling the electronic device **100** to direct the camera **108** and the display **110** to a speaking user. In some implementations, the camera **108** and/or the display **110** are translated and/or rotated (not shown) independently about multiple axes. In some implementations, the translation and/or rotation of the camera **108** and the display **110** are achieved without rotation of the electronic device **100**. Further, the rear side of the electronic device **100** optionally includes a power supply connector configured to couple to a power supply (not shown). In some implementations, the electronic device **100** includes more or fewer microphones **102** than shown in FIG. 1A. In some implementations, the microphones **102** are arranged at locations within the electronic device **100** other than the locations shown in FIG. 1A. In some implementations, the electronic device **100** includes more than one camera **108**. In some implementations, the electronic device **100** includes more than one display, or no display. In some implementations, the display **100** includes the array of illuminators **104**. In some implementations, the



## 5

display **100** consists of one or more illuminators. In some implementations, the display **100** includes zero or more screens and one or more illuminators. In some implementations, the display **100** includes one or more components configured to present visual data.

In some implementations, the electronic device **100** is voice-activated. In some implementations, the electronic device **100** presents a clean look having no visible button, and the interaction with the electronic device **100** is based on voice and touch gestures. Alternatively, in some implementations, the electronic device **100** includes one or more physical buttons (not shown), and the interaction with the electronic device is further based on presses of the button(s) in addition to the voice and/or touch gestures.

FIG. 1B illustrates another electronic device **120** for attending to a speaking user, in accordance with some implementations. In some implementations, the electronic device **120** includes the electronic device **100** on a base **122** that includes actuators **124** that are connected by hinges **126**. In some implementations, the base **122** is configured to vary the elevation (height) of the electronic device **120** (e.g., raising it to the eye level of the speaking user) so as to better attend to users. In some implementations, the actuators **124** include hydraulic, pneumatic, electrical, mechanical, telescopic, and electromechanical actuators that allow for linear motion, and/or other actuators (e.g., motors) that allow for rotational motion. In some implementations, the electronic device **120** includes more or fewer actuators **124** and/or hinges **126** than shown in FIG. 1B. Although FIG. 1B shows actuators that are external to a housing of the device **100**, in some implementations, the actuators and/or motors are enclosed within a housing of the device. In some implementations, the actuators **124** are internal to the device **120**. For example, the camera is optionally mounted to a track or other guide inside the housing, risers or other structures for changing height are optionally nested inside the housing, and etcetera. In some implementations, the electronic device **120** further includes a platform **128** on wheels **130** that enable the electronic device **120** to move to the proximity of the user in response to identifying the location of the user. In some implementations, the electronic device **120** includes a gripper arm (not shown) that secures the electronic device **100** while facilitating the motion of the electronic device **100**.

FIG. 1C illustrates a display **140** and its range of motions, in accordance with some implementations. In some implementations, the display **140** is the display **110** as shown in FIGS. 1A and 1B. The motions of the display **140** are optionally defined using a Cartesian coordinate system or a polar coordinate system. In some implementations, the motions of the display **140** include a rotation **142** about the x-axis (e.g., roll), a rotation **144** about the y-axis (e.g., pitch), a rotation **146** about the z-axis (e.g., yaw), and/or a tilting **148**. In some implementations, the display **140** can be moved in a translational manner, e.g., raised or lowered in a direction as indicated by arrow **152**, and/or forward or backward in a direction as indicated by arrow **154**. In some implementations, the display **140** is connected to a joint (e.g., a ball and socket joint) (not shown) and the motions of the display **140** are determined from the joint connection(s).

FIG. 2 is a block diagram illustrating an operating environment **200** that includes an electronic device **202**, server systems **206**, **220**, and one or more content host(s) **230**, in accordance with some implementations. In some implementations, the electronic device **202** includes the electronic device **100** and/or the electronic device **120**. In some implementations, the electronic device **202** is located at one or

## 6

more positions within a defined space, e.g., in a single room or space of a structure, or within a defined area of an open space.

In accordance with some implementations, the electronic device **202** is communicatively coupled through communication network(s) **210** to a server system **206**, a smart assistant system **220**, and one or more content host(s) **230**. In some implementations, a content host **230** is a remote content source from which content is streamed or otherwise obtained in accordance with a user request. In some implementations, a content host **230** is an information source from which the smart assistant system **220** retrieves information in accordance with a user request.

In some implementations, the electronic device **202** is a voice-activated device and the user request is a user voice request (e.g., a voice command). The electronic device **202** responds to voice commands by: generating and providing a spoken response to a voice command (e.g., speaking the current time in response to the question, “what time is it?”); streaming media content requested by a user (e.g., “play a Beach Boys song”); reading a news story or a daily news briefing prepared for the user; playing a media item stored on the personal assistant device or on the local network; changing a state or operating one or more other connected devices (not shown) within the operating environment **200** (e.g., turning lights, appliances or media devices on/off, locking/unlocking a lock, opening windows, etc.); or issuing a corresponding request to a server via the network **210**. In some implementations, the electronic device **202** displays one or more visual patterns via the array of illuminators **104** (e.g., LEDs) to convey information or to indicate visually a variety of voice processing states of the electronic device **202**.

In some implementations, the server system **206** includes a front end server **212** that facilitates communication between the server system **206** and the electronic device **202** via the communication network(s) **210**. For example, the front end server **212** receives audio content (e.g., the audio content is a hotword and/or speech) and/or visual content (e.g., video signals) from the electronic device **202**. In some implementations, the front end server **212** is configured to send information to the electronic device **202**. In some implementations, the front end server **212** is configured to send response information (e.g., addressing a user by his/her name, and/or directing attention to the user) to the electronic device **202**. In some implementations, the front end server **212** is configured to send data and/or hyperlinks to the electronic device **202**. For example, the front end server **212** is configured to send updates (e.g., database updates) to the electronic device **202**. In some implementations, the front end server **212** is configured to receive audio and/or visual data from the electronic device **202** and send orientation information to the electronic device **202**.

In some implementations, the server system **206** includes a response module **214** that determines information about a speaking user from the audio signals and/or video signals collected from the electronic device **202**. In some implementations, the response module obtains identification of the speaking user from the persons database **216** (e.g., to be sent to the electronic device via the front end server **212**).

In some implementations, the server system **206** includes a persons database **216** that stores information about known persons. For example, the persons database **216** includes voice signatures and/or facial features identification information about known persons.

In some implementations, the environment **200** includes multiple electronic devices **202** (e.g., devices **202-1** thru



202-N). In some implementations, the devices 202 are located throughout the environment 200 (e.g., all within a room or space in a structure, spread throughout the structure, some within the structure and some without). When a user makes an audio request, each of the devices 202 either receives the request or does not receive the input (e.g., if the device was too far away from the user). In some implementations, the electronic devices 202 receive the request at varying degrees of quality. The quality of the sample of the voice input at a device 202 is optionally based on multiple factors, including but not limited to distance of the user from the device and the noise around the device. In some implementations, the multiple devices 202 negotiate a leader amongst themselves to respond to and/or attend to the user, and to receive further voice input(s) from the user, based on the quality of the samples of the voice inputs received.

FIG. 3 is a block diagram illustrating the electronic device 202, in accordance with some implementations. In some implementations, the electronic device 202 includes one or more processor(s) 302, one or more network communication interface(s) 304, memory 306, and one or more communication buses 308 for interconnecting these components (sometimes called a chipset).

In some implementations, the electronic device 202 includes one or more input devices 312 that facilitate audio input, visual input, and/or user input, such as microphones 314, buttons 316, a touch sensor array 318, and one or more cameras 319. In some implementations, the microphones 314 include the microphones 102 and/or other microphones. In some implementations, the cameras 319 include the camera 108 and/or other cameras. In some implementations, the electronic device 202 includes one or more user affordances, such as dials, buttons, or switches.

In some implementations, the electronic device 202 includes one or more output devices 322 that facilitate audio output and/or visual output, including one or more speakers 324, LEDs 326, a display 328, and one or more actuators 330. In some implementations, the LEDs 326 include the illuminators 104 and/or other LEDs. In some implementations, the speakers 324 include the speakers 106 and/or other speakers. In some implementations, the display 328 includes the display 140 and/or other displays. In some implementations, the actuator(s) 330 include actuators that cause the electronic device 202 to change positions and/or elevations (e.g., the actuators 126 FIG. 1B), and other actuators (e.g., motors) that cause the electronic device 202 to change orientation (e.g., via rotation about the axis 112 and/or the axis 114 as shown in FIG. 1A) and/or motion in the device (e.g., via the wheels 130 in FIG. 1B). In some implementations, the actuators 330 produce one or more rotational, tilting, and/or translational motion(s) in the display 328 (e.g., the rotation 142, the rotation 144, the rotation 146, the tilting 148, translation 152, and/or the translation 154, as shown in FIG. 1C).

In some implementations, the electronic device 202 includes radios 320 and one or more sensors 330. The radios 320 enable connection to one or more communication networks, and allow the electronic device 202 to communicate with other devices. In some implementations, the radios 320 are capable of data communications using any of a variety of custom or standard wireless protocols (e.g., IEEE 802.15.4, Wi-Fi, ZigBee, 6LoWPAN, Thread, Z-Wave, Bluetooth Smart, ISA100.5A, WirelessHART, MiWi, etc.) custom or standard wired protocols (e.g., Ethernet, HomePlug, etc.), and/or any other suitable communication protocol, including communication protocols not yet developed as of the filing date of this document.

In some implementations, the sensors 330 include one or more movement sensors (e.g., accelerometers), light sensors, positioning sensors (e.g., GPS), and/or audio sensors. In some implementations, the positioning sensors include one or more location sensors (e.g., passive infrared (PIR) sensors) and/or one or more orientation sensors (e.g., gyroscopes).

The memory 306 includes high-speed random access memory, such as DRAM, SRAM, DDR RAM, or other random access solid state memory devices; and, optionally, includes non-volatile memory, such as one or more magnetic disk storage devices, one or more optical disk storage devices, one or more flash memory devices, or one or more other non-volatile solid state storage devices. The memory 306, optionally, includes one or more storage devices remotely located from one or more processor(s) 302. The memory 306, or alternatively the non-volatile memory within the memory 306, includes a non-transitory computer-readable storage medium. In some implementations, the memory 306, or the non-transitory computer-readable storage medium of the memory 306, stores the following programs, modules, and data structures, or a subset or superset thereof:

- operating logic 332 including procedures for handling various basic system services and for performing hardware dependent tasks;
- a user interface module 334 for providing and displaying a user interface in which settings, captured data including hotwords, and/or other data can be configured and/or viewed;
- a radio communication module 336 for connecting to and communicating with other network devices coupled to one or more communication networks 210 via one or more communication interfaces 304 (wired or wireless);
- an audio output module 338 for determining and/or presenting audio signals (e.g., in conjunction with the speaker(s) 324);
- an audio processing module 340 for obtaining and/or analyzing audio signals (e.g., in conjunction with the microphones 314), including and not limited to:
  - a hotword detection sub-module 3401 for determining whether the audio signals include a hotword for waking up the electronic device 202 and recognizing such in the audio signals;
  - a microphones analysis sub-module 3402 for analyzing audio signals collected from input devices (e.g., microphones 314) and determining audio properties (e.g., audio signatures, frequencies, phase shifts and/or phase differences);
  - an audio localizer sub-module 3403 for identifying and analyzing hotword and/or audio beam(s) to determine one or more hotword and/or audio beam properties (e.g., directions, signal-to noise-ratios etc.); and
  - an audio identification sub-module 3404 for obtaining identification(s) of speaking person(s), e.g., by comparing the obtained audio signals with audio identification data 3501 stored in a persons database 350;
- a video processing module 342 for obtaining and/or analyzing video data (e.g., in conjunction with the camera(s) 319), including and not limited to:
  - a visual speech detection sub-module 3421 for determining speaking person(s) in the video data by analyzing visual signals that are produced during speech (e.g., lips opening and/or eyebrows raising); and



- a visual recognition sub-module **3422** for determining whether the speaking person(s) is in the field of view of the camera based on the collected video data; and obtaining identification(s) of the speaking person(s), e.g., by comparing the obtained video data with visual identification data **3502** in the persons database **350**;
- a confidence analysis module **344** for assigning confidence score(s) to respective identified speaking person(s) based on analyzed audio signals and/or video data using the audio processing module **340** and the video processing module **342**; ranking the respective identified speaking person(s) based on confidence score(s); and/or determining the speaking person based on the highest assigned confidence score; and
- a response module **346** for directing attention to speaking user(s), including and not limited to:
  - an attention control sub-module **3461** for identifying the speaking person based on the highest assigned confidence score; and directing attention to identified speaking person (e.g., acknowledging the speaking person by his/her name); and
  - an actuator control sub-module **3462** for controlling the actuators **330** to direct the electronic device **202** toward the identified speaking person (e.g., rotating the electronic device **202**, rotating the display **328**, tilting the display **328**, and/or translating the display **328** toward the speaking person); and
- a device database **348** for storing information associated with the electronic device **202**, including, and not limited to:
  - sensor information **3481** from the sensors **330**;
  - device settings **3482** for the electronic device **202**, such as default options and preferred user settings; and
  - communications protocol information **3503** specifying communication protocols to be used by the electronic device **202**;
- a persons database **350** for storing persons information, which includes, in accordance with some implementations, the following datasets or a subset or superset thereof:
  - audio identification data **3501** including audio information (e.g., audio signatures, audio fingerprints etc.) corresponding to particular persons; and
  - visual identification data **3502** including visual information (e.g., facial features, hair color, eye color etc.) corresponding to particular persons.

Each of the above identified modules are optionally stored in one or more of the memory devices described herein, and corresponds to a set of instructions for performing the functions described above. The above identified modules or programs need not be implemented as separate software programs, procedures, modules or data structures, and thus various subsets of these modules may be combined or otherwise re-arranged in various implementations. In some implementations, the memory **306** stores a subset of the modules and data structures identified above. Furthermore, the memory **306**, optionally, stores additional modules and data structures not described above (e.g., module(s) for storing a layout of the room in which the electronic device **202** is located). In some implementations, a subset of the programs, modules, and/or data stored in the memory **306** are stored on and/or executed by the server system **206** and/or the voice assistance server **224**.

FIG. 4 is a block diagram illustrating the server system **206**, in accordance with some implementations. The server system **206** includes one or more processor(s) **402**, one or

more network interfaces **404**, memory **410**, and one or more communication buses **408** for interconnecting these components (sometimes called a chipset), in accordance with some implementations.

The server system **206** optionally includes one or more input devices **412** that facilitate user input, such as a keyboard, a mouse, a voice-command input unit or microphone, a touch screen display, a touch-sensitive input pad, a gesture capturing camera, or other input buttons or controls. In some implementations, the server system **206** optionally uses a microphone and voice recognition or a camera and gesture recognition to supplement or replace the keyboard. The server system **206** optionally includes one or more output devices **414** that enable presentation of user interfaces and display content, such as one or more speakers and/or one or more visual displays.

The memory **410** includes high-speed random access memory, such as DRAM, SRAM, DDR RAM, or other random access solid state memory devices; and, optionally, includes non-volatile memory, such as one or more magnetic disk storage devices, one or more optical disk storage devices, one or more flash memory devices, or one or more other non-volatile solid state storage devices. The memory **410**, optionally, includes one or more storage devices remotely located from the one or more processors **402**. The memory **410**, or alternatively the non-volatile memory within the memory **410**, includes a non-transitory computer-readable storage medium. In some implementations, the memory **410**, or the non-transitory computer-readable storage medium of the memory **410**, stores the following programs, modules, and data structures, or a subset or superset thereof:

- an operating system **416** including procedures for handling various basic system services and for performing hardware dependent tasks;
- a front end **212** for communicatively coupling the server system **206** to other devices (e.g., the electronic device **202**) and one or more networks, such as the Internet, other wide area networks, local area networks, metropolitan area networks, and so on;
- a user interface module **420** for enabling presentation of information (e.g., a graphical user interface for presenting application(s), widgets, websites and web pages thereof, games, audio and/or video content, text, etc.) either at the server system or at a remote electronic device;
- a device registration module **422** for registering devices (e.g., the electronic device **202**) for use with the server system **206**;
- an audio processing module **424** for obtaining and/or analyzing audio signals, including and not limited to:
  - a hotword detection sub-module **4241** for determining whether the audio signals include a hotword for waking up electronic device(s) (e.g., electronic device **202**) and recognizing such in the audio signals;
  - a microphones analysis sub-module **4242** for analyzing audio signals collected from one or more electronic devices (e.g., electronic device **202**) and determining audio properties (e.g., audio signatures, frequencies, phase shifts and/or phase differences);
  - an audio localizer sub-module **4243** for analyzing audio beams based on audio heard when the user hotwords the device (e.g., electronic device **202**), and for determining audio beam properties (e.g., directions, signal-to noise-ratios etc.); and



## 11

an audio identification sub-module **4244** for obtaining identification(s) of speaking person(s), e.g., by comparing the audio signals obtained from electronic device(s) (e.g., electronic device **202**) with audio identification data **3501** in a persons database **216**;

an video processing module **426** for obtaining and/or analyzing video data collected, including and not limited to:

- a visual speech detection sub-module **4261** for determining speaking person(s) from video data of electronic device(s) (e.g., electronic device **202**), e.g., by analyzing visual signals that are produced during speech (e.g., lips opening and/or eyebrows raising); and
- a visual recognition sub-module **4262** for determining whether the speaking person(s) is in the field of view of the camera of the electronic device(s) (e.g., camera(s) **319** of the electronic device **202**) based on the collected video data; and/or for obtaining identification of the speaking person(s), e.g., by comparing the obtained video data with visual identification data **2162** in the persons database **216**;
- a confidence analysis sub-module **428** for assigning confidence score(s) to respective identified speaking person(s) obtained from the audio processing module **424** and the video processing module **426**; ranking the respective identified speaking person(s) based on confidence score(s); and/or determining the speaking person based on the highest assigned confidence score;
- a response module **214** for directing attention to speaking user(s), including and not limited to:
  - an attention control sub-module **4291** for identifying the speaking person based on the highest assigned confidence score; and directing the electronic device (e.g., electronic device **202**) to attend to the identified speaking person (e.g., acknowledging the speaking person by his/her name); and
  - an actuator control sub-module **4292** for determining the coordinates (e.g., Cartesian coordinates and/or polar coordinates) corresponding to the location of the speaking person; and directing the actuator(s) of the electronic device(s) (e.g., the actuators **330** of the electronic device **202**) to the location of the speaking person; and
- server system data **430** storing data associated with the server system **206**, including, but not limited to:
  - client device settings **4301** including device settings for one or more electronic devices (e.g., electronic device(s) **202**), such as common device settings (e.g., service tier, device model, storage capacity, processing capabilities, communication capabilities, etc.), and information for automatic media display control;
  - audio device settings **4302** including audio settings for audio devices associated with the server system **206** (e.g., electronic device(s) **202**), such as common and default settings (e.g., volume settings for speakers and/or microphones etc.); and
  - voice assistance data **4303** for voice-activated devices and/or user accounts of the voice assistance server **224**, such as account access information and information for one or more electronic devices **202** (e.g., service tier, device model, storage capacity, processing capabilities, communication capabilities, etc.); and

## 12

a persons database **216** for storing persons information, which includes, in accordance with some implementations, the following datasets or a subset or superset thereof:

- audio identification data **4321** including audio information (e.g., audio signatures, audio fingerprints etc.) corresponding to particular persons; and
- visual identification data **4322** including visual information corresponding to particular persons

In some implementations, the server system **206** includes a notification module (not shown) for generating alerts and/or notifications for users of the electronic device(s). For example, in some implementations the persons database **216** is stored locally on the electronic device of the user, the server system **206** may generate notifications to alert the user to download the latest version(s) or update(s) to the persons database.

Each of the above identified elements may be stored in one or more of the memory devices described herein, and corresponds to a set of instructions for performing the functions described above. The above identified modules or programs need not be implemented as separate software programs, procedures, modules or data structures, and thus various subsets of these modules may be combined or otherwise re-arranged in various implementations. In some implementations, the memory **410**, optionally, stores a subset of the modules and data structures identified above. Furthermore, the memory **410** optionally stores additional modules and data structures not described above.

FIGS. **5A-5B** illustrate a representative operation of the electronic device **202** of FIG. **3**, in accordance with some implementations. In this example, the electronic device **202** is the electronic device **100** as shown in FIG. **1A**. FIG. **5A** shows a room **500** that includes a countertop **502**, a table **504**, and a sofa **506**. As shown in FIG. **5A**, the electronic device **100** is initially on the countertop **502** with the camera **108** and the display **110** of the electronic device **100** directed toward a wall **508** located on the right (+x direction) of the room **500**. The field of view of the camera **108** is illustrated by lines **512**. A user **520** addresses the electronic device **100** by speaking a hotword ("OK Assistant."). In some implementations, the electronic device **100** is in a standby mode and the detection of the hotword (also sometimes called a "wake word") awakens the electronic device **100** (e.g., via the hotword detection sub-module **3401**).

FIG. **5B** illustrates the electronic device **100** responding to the detection of the spoken hotword by the user **520**, in accordance with some implementations. As shown in FIG. **5B** the electronic device **100** reorients so that the user **520** is within the field of view of the device and responds by addressing the user **520** by name ("Yes, Jane?"). In some implementations, in response to the detected hotword, the electronic device **100** determines based on the obtained hotword signals that the person **520** is speaking in a vicinity of the electronic device (e.g., by identifying of one or more hotword beam(s) and their corresponding determining signal-to-noise ratios using the audio localizer sub-module **3402**). In some implementations, the electronic device **100** obtains identification of the speaking person by comparing the obtained audio signals with audio identification data (e.g., using the audio identification sub-module **3404**).

In some implementations, in response to the detected hotword, the electronic device **100** further determines that the speaking person **520** is not in the field of view of the camera **108** (e.g., using the visual speech detection sub-module **3421** and/or the visual recognition sub-module **3422**). In some implementations, the electronic device **100**



## 13

reorients itself based on differences in the audio data received at the respective microphones 102. In some implementations, orienting the electronic device 100 includes rotating the electronic device 100 (e.g., about the axis 112 and/or the axis 114). In some implementations, after reorienting, the electronic device 100 obtains video data from the camera 108 and determines from the video data that the speaking person is now in the field of view. In some implementations, the electronic device 100 directs attention to the identified speaking user including acknowledging the speaking person by his/her name ("Yes Jane?") (e.g., using the attention control sub-module 3461). In some implementations, directing attention to the identified speaking user includes re-positioning one or more physical features on the electronic device 100 (e.g., re-positioning the array of illuminators 104). In some implementations, directing attention to the identified speaking user includes re-directing presentation of visual data (e.g., re-directing illumination from the array of illuminators 104). In some implementations, directing attention to the identified speaking user includes adjusting a directionality of a presentation of visual data toward the identified user (e.g., adjusting illumination from the array of illuminators 104 to indicate a direction of the identified user).

FIGS. 6A-6B illustrate another representative operation of the electronic device 202 of FIG. 3, in accordance with some implementations. In this example, the electronic device 202 is the electronic device 120 as shown in FIG. 1B. FIG. 6A shows the room 500 with the electronic device 120 positioned on the table 504. As shown in FIG. 6A, the camera 108 and the display 110 of the electronic device 120 are initially directed toward the countertop 502. The field of view of the camera 108 is illustrated by lines 602. As shown in FIG. 6A, there are two users in the room 500, namely: the user 520 and another user 620, both of whom are sitting on the sofa 506. The user 620 addresses the electronic device 120 by speaking a hotword ("OK Assistant."). In some implementations, the electronic device 120 is in a standby mode and the detection of the hotword (e.g., via the hotword detection sub-module 3401) awakens the electronic device 120.

FIG. 6B illustrates the response of the electronic device 120 as a result of detecting the spoken hotword by the user 620, in accordance with some implementations. As shown in FIG. 6B the electronic device 120 reorients so that the user 620 is within the field of view of the device and responds by addressing the user 620 by name ("Yes, John?"). In some implementations, in response to the detected hotword, the electronic device 120 identifies one or more hotword beam(s) and determines the audio beam direction which has the highest-signal-to-noise ratio of the hotword power (e.g., using the audio localizer sub-module 3402). In some implementations, the electronic device 120 obtains identification of the speaking user by comparing the obtained audio signals with audio identification data (e.g., using the audio identification sub-module 3404). In some implementations, in response to the detected hotword, the electronic device 120 determines that the speaking user is not in the field of view of the camera 108 (e.g., using the visual speech detection sub-module 3421 and/or the visual recognition sub-module 3422).

In some implementations, the electronic device 120 reorients itself based on differences in the audio data received at the respective microphones 102. In some implementations, orienting the electronic device 120 includes rotating the electronic device 100 (e.g., about the axis 112 and/or the axis 114). In some implementations, reorienting the electronic

## 14

device 120 includes controlling the actuators 124 to change the position (e.g., increasing the height) of the electronic device 120. In some implementations, reorienting the electronic device 120 includes moving the electronic device to the proximity of the user (e.g., using the wheels 130 of FIG. 1B, not shown).

In some implementations, after reorienting itself, the electronic device 120 obtains additional video data using the camera 108, and determines that multiple users (e.g., user 520 and user 620) are within the field of view of the electronic device 120. In some implementations, in accordance with the determination that multiple users are in the field of view, the electronic device 120 assigns a confidence score (e.g., using the confidence analysis module 344) to each of the users 520 and 620. In some implementations, the assignment of the confidence score is based on the analysis of the audio and/or video signals. In this example, the electronic device 120 assigns a higher confidence score to the user 620 based on a determination (e.g., using the speech detection submodule 3421) that the eyebrows of the user 620 are raised and the mouth of the user 520 is open. Accordingly, the electronic device 120 determines identifies that the user 620 is the speaking user.

In some implementations, in accordance with the determination that the user 620 is the speaking user, the electronic device attends to the speaking user by directing the display 110 toward the user 620, as illustrated by lines 612 which indicate the field of view of the display 110. In some implementations, directing attention to the speaking user includes acknowledging the speaking user 620 by his name ("Yes John?") (e.g., using the attention control sub-module 34610).

FIGS. 7A-7B illustrate another representative operation of the electronic device 202 of FIG. 3, in accordance with some implementations. In this example, the electronic device 202 is the electronic device 120 as shown in FIG. 1B. FIG. 7A shows the room 500 with the electronic device 120 on the table 504. As shown in FIG. 7A, the camera 108 and the display 110 of the electronic device 120 are initially directed towards the right wall 508. The field of view of the camera 108 is illustrated by lines 712. As shown in FIG. 7A, the countertop 502 includes a stack of books 702, and the user 520 is located behind the countertop 502. The user 520 addresses the electronic device 120 by speaking a hotword ("OK Assistant."). In some implementations, the electronic device 120 is in a standby mode and the detection of the hotword (e.g., via the hotword detection sub-module 3401) awakens the electronic device 120.

FIG. 7B illustrates the response of the electronic device 120 as a result of detecting the spoken hotword by the user 520, in accordance with some implementations. As shown in FIG. 7B the electronic device 120 reorients in an attempt to have the user 520 within the field of view of the device, but its field of view is blocked by the books 702. Accordingly, the electronic device 120 responds by notifying the user 520 that the device is attending to the user 520 even though the device 120 does not have line-of-sight with the user. In some implementations, the electronic device 120 identifies one or more hotword beam(s) and determines the audio beam direction which has the highest-signal-to-noise ratio of the hotword power (e.g., using the audio localizer sub-module 3402). In some implementations, the electronic device 120 obtains identification of the speaking user by comparing the obtained audio signals with audio identification data (e.g., using the audio identification sub-module 3404).

In some implementations, in response to the detected hotword, the electronic device 120 further determines that



15

the speaking user **520** is not in the field of view of the camera **108** (e.g., using the visual speech detection sub-module **3421** and/or the visual recognition sub-module **3422**). In some implementations, the electronic device **120** reorients itself based on differences in the audio data received at the respective microphones **102**. In this example, the electronic device **120** reorients by rotating itself (e.g., about the axis **112** and/or the axis **114**) and by changing its position using the actuators **124** (e.g., using the actuator control sub-module **3462**).

In some implementations, after reorienting, the electronic device **120** obtains additional video data from the camera **108** and determines from the additional video data that the speaking person is not in the field of view. In this example, even though the camera **108** and the display **110** have been reoriented to face the user **520**, the stack of books **702** obstructs the user **520** from the field of view of the camera **108**. In some implementations, in accordance with a determination that the speaking user is not visible, the electronic device **120** indicates via the display **110** that the speaking user is not visible (e.g., using the attention control sub-module **3461**). In some implementations, in accordance with a determination that the speaking user **520** is not visible, the electronic device **120** acknowledges the speaking user **520** verbally and at the same time, presents a verbal indication (e.g., using the attention control sub-module **3461**) that the speaking user **520** is not visible to the electronic device **120** ("Hi Jane, I can't see you. What's your question?").

FIGS. **8A-8C** are flowchart representations of a method **800** for attending to a presenting user utilizing the electronic device **202** of FIG. **3**, in accordance with some implementations. In some implementations, the method **800** is performed by: (1) one or more electronic devices **202**; (2) one or more server systems, such as server system **206**; or (3) a combination thereof. In some implementations, the method **800** is governed by instructions that are stored in a non-transitory computer readable storage medium and that are executed by one or more processors of a device/computing system, such as the one or more processors **302** of the electronic device **202** and/or the one or more processors **402** of the server system **206**. For convenience, specific operations detailed below are described as being performed by the electronic device **202**.

The electronic device **202** obtains (**802**) audio signals by concurrently receiving audio data at each microphone of a plurality of microphones (e.g., microphones **314**). In some implementations, the received audio data includes hotwords. For example, FIG. **5A** shows the user **520** addressing the electronic device **100** by speaking a hotword. In some implementations, the electronic device **202** is in a standby mode and the hotword(s) for awaken the electronic device **202** (e.g., using the hotword detection sub-module **3401**). In some implementations, the received audio data includes a user query and the electronic device **202** gathers data from one or more remote sources (e.g., content host(s) **230**) to answer the user query.

The electronic device **202** determines (**806**) based on the obtained audio signals that a person is speaking in the vicinity of the electronic device **202**. For example, the device **202** identifies one or more words within the obtained audio signal. As another example, the device **202** determines that the audio includes a person speaking based on an analysis of the frequency, pitch, or cadence of the obtained audio. In some implementations, the electronic device **202** identifies (**807**) the speaking person based on the obtained audio signals. In some implementations, the electronic device **202** identifies the person by comparing the obtained

16

audio signals with audio identification data (e.g., the audio identification data **3501** in the persons database **350**).

In some implementations, upon detecting an unknown voice, the electronic device **202** queries the user for an identification and stores the identification and the voice in the persons database **350**. In some implementations, the electronic device **202** generates an audio query to the user. In some implementations, the electronic device generates an electronic notification (e.g., to be sent to the user's mobile device).

In some implementations, after determining that the person is speaking in the vicinity of the electronic device **202**, the electronic device **202** indicates (**808**) via the display (e.g., the display **328**) that a speaking person has been detected. In some implementations, indicating via the display that a speaking person has been detected includes turning on/off an illuminator (e.g., the LEDs **326**), adjusting a color of a display (e.g., the display **328**), or the like. In some implementations, after determining that the person is speaking, the electronic device **202** further determines that the person has spoken a hotword (e.g., using the hotword detection sub-module **3401**) and indicates via the display **328** that the hotword has been detected. In some implementations, after the electronic device **202** determines that the person is speaking, the electronic device **202** determines that the person is speaking to the electronic device **202**, and indicates via the display that the electronic device is aware of the person speaking. In some implementations, after determining that the person is speaking, the electronic device **202** further determines that the person has issued a query and the device indicates that the query has been received (e.g., via a visual and/or audio presentation).

The electronic device **202** obtains (**810**) video data from one or more image sensor(s) (e.g., the camera(s) **319**). In some implementations, video data is obtained on a continuous basis. In some implementations, video data is obtained continuously over a predetermined time period (e.g., 2 seconds, 30 seconds, etc.). In some implementations, video data is obtained intermittently over a predetermined time period (e.g., one frame every five seconds over a duration of ten minutes).

The electronic device **202** determines (**812**) based on analysis of the video data that the person is not within the field of view of the image sensor. In some implementations, the determination is made using the video processing module **342**, including the visual speech detection sub-module **3421** and/or the visual recognition sub-module **3422**. In some implementations, the determination is made by comparing the video data with visual identification data **3502** in the persons database **350**.

In some implementations, upon detecting an unknown person, the electronic device **202** queries the user for an identification and stores the identification and feature data of the person in the persons database **350**. In some implementations, the electronic device **202** generates an audio query to the user. In some implementations, the electronic device generates an electronic notification (e.g., to be sent to the user's mobile device). In some implementations, the identification and feature data correspond to a particular voice and the feature data is associated with the voice.

In some implementations, in accordance with the determination that the person is not within the field of view of the image sensor, the electronic device **202** determines (**814**) a preferred direction for reorienting on the person. In some implementations, determining the preferred direction is based on the hotword and/or audio beam(s) of the obtained audio signals that are created by the electronic device **202**



17

(e.g., using the audio localizer sub-module **3403**). In some implementations, determining the preferred direction is based on one or more hotword and/or audio beam properties (e.g., directions, signal-to noise-ratios, etc.) of the obtained audio signals.

In some implementations, determining a preferred direction for reorienting on the person includes identifying (**816**) a position of a surface in the vicinity of the electronic device **202**, the surface having reflected at least a portion of the audio data received by a first microphone of the plurality of microphones **314**. In some implementations, the preferred direction for reorienting (**817**) on the person is based on the position of the surface. For example, the device **202** determines that a wall is directly behind the device and that part of the audio data received was a reflection of audio from the wall. In this example, the device **202** accounts for the audio reflection and determines that the preferred direction is not the direction of the wall.

In some implementations, the preferred direction for reorienting (**818**) on the person is based on a layout of the room in which the electronic device **202** is located. In some implementations, the electronic device **202** stores a mapping of the room, dwelling, or structure. For example, as noted in the description of FIG. **3**, the memory **306** of the electronic device **202** optionally stores a layout of the room in which the electronic device **202** is located. To further illustrate, the electronic device **202** determines based on the room layout and an analysis of the hotword beam(s) that it is situated next to a wall, and therefore receives audio beams that originate from both a user as well as from reflection off a vicinity wall. In this example, the electronic device **202** determines the preferred direction for reorienting on the person to be the direction away from the wall.

In some implementations, the mapping of the room is obtained via radar, sonar, etc. (e.g., obtained via sensor **360** of the electronic device **202**). In some implementations, the layout of the room is obtained via an analysis of video data from the image sensor (e.g., the camera(s) **319**).

The electronic device **202** reorients (**820**) the electronic device **202** based on differences in the audio data received at respective microphones in the plurality of microphones **314**. In some implementations, reorienting the electronic device **202** includes rotating the electronic device **202** about its axis (e.g., about the axis **112** and/or the axis **114** as shown in FIG. **1A**). In some implementations, reorienting the electronic device **202** includes translating, elevating, and/or rotating the electronic device (e.g., using the actuators **330**).

In some implementations, reorienting the electronic device **202** includes rotating (**822**) the image sensor (e.g., camera(s) **319**) in the preferred orientation (as determined in **814**). In some implementations, reorienting the electronic device includes rotating the display (e.g., the display **319**) and the image sensor (e.g., camera(s) **319**). In some implementations, reorienting the electronic device **202** includes moving (**824**) the image sensor (e.g., camera(s) **319**) along multiple axes. In some implementations, moving the image sensor along multiple axes includes, e.g., adjusting pitch and yaw; tilting the display up/down to align with a person's line of sight; moving toward the person; adjusting elevation; etc. In some implementations, reorienting the electronic device **202** comprises moving the display and image sensor; or the entire device.

After reorienting, the electronic device **202** obtains (**826**) second video data from the image sensor (e.g., camera(s) **319**) and determines from the second video data that the person is within the field of view of the image sensor (e.g., using the video processing module **342**).

18

In some implementations, the electronic device **202** identifies (**828**) the person based on an analysis of the video data from the image sensor. In some implementations, the electronic device **202** performs (**830**) facial recognition on the video data to identify the person based on the analysis of the video data (e.g., by comparing the obtained video data with visual identification data **3502** in the persons database **350**). In some implementations, identifying the person includes identifying the person based on the person's dimensions, respiratory patterns, and/or gait. In some implementations, performing facial recognition includes a determination of the distance between the image sensor and the person.

In some implementations, the electronic device **202** identifies (**832**) the person based on an analysis of visual data from the image sensor. In some implementations, the identification of the person is based on visual speech detection technique (e.g., using the visual speech detection sub-module **3421**). In some implementations, the visual speech detection technique includes determining that the person's mouth/face (e.g., eyebrow) is moving. In some implementations, the visual speech detection technique includes determining that the person's mouth movements correlate with the received audio signals.

In some implementations, after the electronic device **202** reorients itself and obtains second video data from the image sensor, the electronic device **202** determines (**834**) that a plurality of persons is within the field of view of the image sensor. For example, FIG. **6B** illustrates two users, namely the user **520** and the user **620**, in the field of view of the camera **108** electronic device **202**. In accordance with the determination that a plurality of persons is within the field of view of the image sensor, the electronic device **202** assigns (**836**) a confidence score to each person of the plurality of persons (e.g., using the confidence analysis module **344**). In some implementations, the confidence score is based on analyzing (**838**) the audio signals and/or video signals from the image sensor (e.g., using one or more of: the audio localizer sub-module **3403**, the audio identification sub-module **3404**, the visual speech detection sub-module **3421**, and the visual recognition sub-module **3422**). In some implementations, different weights are assigned to the respective components of the audio signals and/or visual signals. In some implementations, determining that the person is within the field of view of the image sensor includes determining that the person is assigned (**840**) the highest confidence score.

The electronic device **202** attends (**842**) to the person by directing the display (e.g., the display **328**) to the person. In some implementations, the display includes a screen (e.g., a touch screen), one or more illuminators **104** (e.g., LEDs), and/or a user interface with one or more affordances. In some implementations, directing the display includes moving (e.g., translating and/or rotating) the display to the speaking user. For example, FIG. **6B** shows the electronic device **120** moving from an initial position (shown in FIG. **6A**) to an attentive position showing attention to the speaking user **620**, as illustrated by the lines **612**.

In some implementations, the electronic device **202** attends to the person by directing (**844**) the image sensor (e.g., camera(s) **319**) toward the person. In some implementations, directing the image sensor toward the person includes centering (**846**) the person within the field of view of the image sensor. In some implementations, directing the image sensor toward the person includes focusing the image sensor on the person. In some implementations, directing the image sensor toward the person includes adjusting a brightness and/or contrast to highlight the person. In some imple-



mentations, additional to directing the image sensor toward the person, the electronic device **202** also outputs a visual indication (e.g., a predefined pattern using the one or more illuminators **104** (e.g., LEDs) that it is listening to the person.

In some implementations, the electronic device **202** obtains (**848**) second audio signals by concurrently receiving second audio data at each microphone of the plurality of microphones **314**.

In some implementations, in accordance with obtaining second audio signals, the electronic device **202** determines (**850**) based on the second audio signals that a second person is speaking in a vicinity of the electronic device **202**. In some implementations, in accordance with the determination based on the second audio signals that a second person is speaking in a vicinity of the electronic device **202**, the electronic device **202** determines (**852**) whether the second person is within the field of view of the image sensor.

In some implementations, in accordance with the determination that the second person is within the field of view of the image sensor, the electronic device **202** attends (**854**) to the second person by directing the image sensor (e.g., camera(s) **319**) and the display **328** toward the second person.

In some implementations, in accordance with the determination that the second person is not within the field of view of the image sensor, the electronic device **202** reorients (**856**) itself based on differences in the second audio data received at respective microphones of the plurality of microphones **314**. In some implementations, after the electronic device **202** reorients itself based on differences in the second audio data, the electronic device **202** determines (**858**) that the second person is not visible to the electronic device **202**. In some implementations, in accordance with the determination that the second person is not visible, the electronic device **202** indicates (**860**) via the display **328** that the second person is not visible. In some implementations, in accordance with the determination that the second person is not visible, the electronic device **202** outputs a response (e.g., an audio response) indicating to the person that the person is not visible.

For situations in which the systems discussed above collect information about users, the users may be provided with an opportunity to opt in/out of programs or features that may collect personal information (e.g., information about a user's preferences or usage of a smart device). In addition, in some implementations, certain data may be anonymized in one or more ways before it is stored or used, so that personally identifiable information is removed. For example, a user's identity may be anonymized so that the personally identifiable information cannot be determined for or associated with the user, and so that user preferences or user interactions are generalized (for example, generalized based on user demographics) rather than associated with a particular user.

Although some of various drawings illustrate a number of logical stages in a particular order, stages that are not order dependent may be reordered and other stages may be combined or broken out. While some reordering or other groupings are specifically mentioned, others will be obvious to those of ordinary skill in the art, so the ordering and groupings presented herein are not an exhaustive list of alternatives. Moreover, it should be recognized that the stages could be implemented in hardware, firmware, software or any combination thereof.

It will also be understood that, although the terms first, second, etc. are, in some instances, used herein to describe

various elements, these elements should not be limited by these terms. These terms are only used to distinguish one element from another. For example, a first electronic device could be termed a second electronic device, and, similarly, a second electronic device could be termed a first electronic device, without departing from the scope of the various described implementations. The first electronic device and the second electronic device are both electronic devices, but they are not the same type of electronic device.

The terminology used in the description of the various described implementations herein is for the purpose of describing particular implementations only and is not intended to be limiting. As used in the description of the various described implementations and the appended claims, the singular forms "a", "an" and "the" are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will also be understood that the term "and/or" as used herein refers to and encompasses any and all possible combinations of one or more of the associated listed items. It will be further understood that the terms "includes," "including," "comprises," and/or "comprising," when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

As used herein, the term "if" is, optionally, construed to mean "when" or "upon" or "in response to determining" or "in response to detecting" or "in accordance with a determination that," depending on the context. Similarly, the phrase "if it is determined" or "if [a stated condition or event] is detected" is, optionally, construed to mean "upon determining" or "in response to determining" or "upon detecting [the stated condition or event]" or "in response to detecting [the stated condition or event]" or "in accordance with a determination that [a stated condition or event] is detected," depending on the context.

The foregoing description, for purpose of explanation, has been described with reference to specific implementations. However, the illustrative discussions above are not intended to be exhaustive or to limit the scope of the claims to the precise forms disclosed. Many modifications and variations are possible in view of the above teachings. The implementations were chosen in order to best explain the principles underlying the claims and their practical applications, to thereby enable others skilled in the art to best use the implementations with various modifications as are suited to the particular uses contemplated.

What is claimed is:

1. A method performed at an electronic device having an image sensor, a plurality of microphones, a display, one or more processors, and memory, the method comprising:

obtaining audio signals by concurrently receiving audio data at each microphone of the plurality of microphones;

determining based on the obtained audio signals that a person is speaking in a vicinity of the electronic device;

identifying the person based on the obtained audio signals;

obtaining video data from the image sensor;

determining based on analysis of the video data that the person is not within a field of view of the image sensor;

reorienting the electronic device based on differences in the audio data received at respective microphones of the plurality of microphones;



## 21

after reorienting the electronic device:  
 obtaining second video data from the image sensor,  
 determining from the second video data that the person  
 is within the field of view of the image sensor, and  
 identifying the person based on an analysis of the  
 second video data; and  
 attending to the person by directing the display toward the  
 person.

2. The method of claim 1, wherein attending to the person  
 includes directing the image sensor toward the person.

3. The method of claim 2, wherein directing the image  
 sensor toward the person comprises centering the person  
 within the field of view of the image sensor.

4. The method of claim 1, wherein identifying the person  
 based on the analysis of the second video data comprises  
 performing facial recognition on the second video data.

5. The method of claim 1, further comprising:  
 after determining that the person is not within the field of  
 view of the image sensor, determining a preferred  
 direction for reorienting on the person; and  
 wherein reorienting the electronic device comprises rotat-  
 ing the image sensor in the preferred direction.

6. The method of claim 5, further comprising:  
 identifying a position of a surface in the vicinity of the  
 electronic device, the surface having reflected at least a  
 portion of the audio data received by a first microphone  
 of the plurality of microphones;  
 wherein the preferred direction is based the position of the  
 surface.

7. The method of claim 5, wherein the preferred direction  
 is based on a layout of a room in which the electronic device  
 is located.

8. The method of claim 1, wherein reorienting the elec-  
 tronic device comprises moving the image sensor along  
 multiple axes.

9. The method of claim 1, further comprising:  
 obtaining second audio signals by concurrently receiving  
 second audio data at each microphone of the plurality  
 of microphones;  
 determining based on the second audio signals that a  
 second person is speaking in a vicinity of the electronic  
 device;  
 determining that the second person is not within the field  
 of view of the image sensor;  
 reorienting the electronic device based on differences in  
 the second audio data received at respective micro-  
 phones of the plurality of microphones;  
 after reorienting the electronic device based on differ-  
 ences in the second audio data, determining that the  
 second person is not visible to the electronic device;  
 and  
 in accordance with the determination that the second  
 person is not visible, indicate via the display that the  
 second person is not visible.

10. An electronic device comprising:  
 an image sensor;  
 a plurality of microphones;  
 a display;  
 one or more processors; and  
 memory coupled to the one or more processors, the  
 memory storing one or more programs configured to be  
 executed by the one or more processors, the one or  
 more programs including instructions for:  
 obtaining audio signals by concurrently receiving audio  
 data at each microphone

## 22

of the plurality of microphones;  
 determining based on the obtained audio signals that a  
 person is speaking in a vicinity of the electronic  
 device;  
 identifying the person based on the obtained audio  
 signals;  
 obtaining video data from the image sensor;  
 determining based on analysis of the video data that the  
 person is not within a field of view of the image  
 sensor;  
 reorienting the electronic device based on differences in  
 the audio data received at respective microphones of  
 the plurality of microphones;  
 after reorienting the electronic device:  
 obtaining second video data from the image sensor,  
 determining from the second video data that the  
 person is within the field of view of the image  
 sensor, and  
 identifying the person based on an analysis of the  
 second video data; and  
 attending to the person by directing the display toward the  
 person.

11. The electronic device of claim 10, wherein the instruc-  
 tions for attending to the person includes instructions for  
 directing the image sensor toward the person.

12. The electronic device of claim 11, wherein the instruc-  
 tions for directing the image sensor toward the person  
 comprises centering the person within the field of view of  
 the image sensor.

13. The electronic device of claim 10, wherein the instruc-  
 tions for determining that the person is within the field of  
 view of the image sensor comprises instructions for identi-  
 fying the person based on an analysis of visual data from the  
 image sensor.

14. The electronic device of claim 10, further comprising  
 instructions for: after determining that the person is speaking  
 in the vicinity of the electronic device, indicating via the  
 display that a speaking person has been detected.

15. The electronic device of claim 10, further comprising  
 instructions for:  
 obtaining second audio signals by concurrently receiving  
 second audio data at each microphone of the plurality  
 of microphones;  
 determining based on the second audio signals that a  
 second person is speaking in a vicinity of the electronic  
 device;  
 determining that the second person is not within the field  
 of view of the image sensor;  
 reorienting the electronic device based on differences in  
 the second audio data received at respective micro-  
 phones of the plurality of microphones;  
 after reorienting the electronic device based on differ-  
 ences in the second audio data, determining that the  
 second person is not visible to the electronic device;  
 and  
 in accordance with the determination that the second  
 person is not visible, indicate via the display that the  
 second person is not visible.

16. A non-transitory computer-readable storage medium  
 storing one or more programs, the one or more programs  
 comprising instructions, which when executed by an elec-  
 tronic device having an image sensor, a plurality of micro-  
 phones, a display, one or more processors, and memory,  
 cause the electronic device to perform the method of:  
 obtaining audio signals by concurrently receiving audio  
 data at each microphone of the plurality of micro-  
 phones;

**23**

determining based on the obtained audio signals that a person is speaking in a vicinity of the electronic device; identifying the person based on the obtained audio signals;

obtaining video data from the image sensor;

determining based on analysis of the video data that the person is not within a field of view of the image sensor; reorienting the electronic device based on differences in the audio data received at respective microphones of the plurality of microphones;

after reorienting the electronic device:

obtaining second video data from the image sensor, determining from the second video data that the person is within the field of view of the image sensor, and identifying the person based on an analysis of the second video data; and

attending to the person by directing the display toward the person.

**17.** The non-transitory computer-readable storage medium of claim **16**, wherein the one or more programs further comprise instructions for:

after reorienting the electronic device, determining that a plurality of persons is within the field of view;

assigning a confidence score to each person of the plurality of persons; and

**24**

wherein determining that the person is within the field of view comprises determining that the person is assigned the highest confidence score.

**18.** The non-transitory computer-readable storage medium of claim **17**, wherein the confidence score is based on an analysis of the obtained audio signals and/or video signals from the image sensor.

**19.** The non-transitory computer-readable storage medium of claim **16**, wherein the one or more programs further comprise instructions for:

obtaining second audio signals by concurrently receiving second audio data at each microphone of the plurality of microphones;

determining based on the second audio signals that a second person is speaking in a vicinity of the electronic device;

determining that the second person is within the field of view of the image sensor; and

attending to the second person by directing the image sensor and the display toward the second person.

**20.** The non-transitory computer-readable storage medium of claim **16**, wherein identifying the person based on the analysis of the second video data comprises performing facial recognition on the second video data.

\* \* \* \* \*