



US011089140B2

(12) **United States Patent**
Lee

(10) **Patent No.:** **US 11,089,140 B2**
(45) **Date of Patent:** ***Aug. 10, 2021**

(54) **INTELLIGENT CONTROLLER AND SENSOR NETWORK BUS, SYSTEM AND METHOD INCLUDING GENERIC ENCAPSULATION MODE**

H04Q 11/0067; H04Q 2011/0064; H04Q 2011/0092; H04Q 11/0071; H04L 2212/00; H04L 63/08; H04L 63/0861; H04L 63/20; G06F 21/45; G06F 21/31; G06F 21/32;

(71) Applicant: **Vulcan Technologies International Inc.**, Grand Cayman (KY)

(Continued)

(72) Inventor: **Eugene Lee**, San Jose, CA (US)

(56)

References Cited

(73) Assignee: **Vulcan Technologies Shanghai Co., Ltd.**, Shanghai (CN)

U.S. PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 65 days.

5,978,578 A 11/1999 Azarya et al.
6,013,108 A 1/2000 Karolys et al.
(Continued)

This patent is subject to a terminal disclaimer.

FOREIGN PATENT DOCUMENTS

CN 202331122 U 7/2012
CN 104378225 B 7/2018

(21) Appl. No.: **16/572,358**

OTHER PUBLICATIONS

(22) Filed: **Sep. 16, 2019**

(65) **Prior Publication Data**

US 2021/0037120 A1 Feb. 4, 2021

Zhou et al., "Communication buses and protocols for sensor networks.", In Sensors. Jul. 4, 2002, Retrieved on Sep. 17, 2020 from <https://www.mdpi.com/1424-8220/2/7/244/pdf>entire document.

Related U.S. Application Data

(Continued)

(63) Continuation-in-part of application No. 16/529,682, filed on Aug. 1, 2019, now Pat. No. 10,841,230.

Primary Examiner — Jung Liu

(51) **Int. Cl.**
H04L 12/807 (2013.01)
H04L 29/06 (2006.01)

(74) *Attorney, Agent, or Firm* — Haverstock & Owens LLP

(Continued)

(52) **U.S. Cl.**
CPC *H04L 69/22* (2013.01); *B60W 50/00* (2013.01); *H04L 12/18* (2013.01); *H04L 12/403* (2013.01);


(57) **ABSTRACT**

A machine automation system for controlling and operating an automated machine. The system includes a controller and sensor bus including a central processing core and a multi-medium transmission intranet for implementing a dynamic burst to broadcast transmission scheme where messages are burst from nodes to the central processing core and broadcast from the central processing core to all of the nodes.

(Continued)

(58) **Field of Classification Search**
CPC H04J 14/0201; H04J 14/0283; H04J 3/085;

30 Claims, 10 Drawing Sheets



- | | | | |
|--|--|--|---|
| (51) Int. Cl. | <i>H04L 29/08</i> (2006.01)
<i>H04L 12/403</i> (2006.01)
<i>H04L 12/40</i> (2006.01)
<i>B60W 50/00</i> (2006.01)
<i>H04L 12/18</i> (2006.01) | 2004/0081178 A1 4/2004 Fujimori
2007/0078736 A1 4/2007 Chand et al.
2008/0107269 A1 9/2008 Gehrman
2010/0031297 A1 2/2010 Klein et al.
2011/0142448 A1* 6/2011 Zou H04J 14/0201
398/58
2013/0250807 A1* 9/2013 Dai H04L 12/2889
370/254 | 2014/0297785 A1* 10/2014 Galles H04L 67/02
709/217
2014/0304511 A1 10/2014 Lewis
2015/0033305 A1* 1/2015 Shear G06F 21/53
726/6
2015/0063368 A1* 3/2015 Sharma H04L 1/0075
370/412
2016/0057098 A1* 2/2016 Han G06F 9/45558
370/390
2016/0204849 A1 7/2016 Behroozi
2017/0249099 A1 8/2017 Jun
2019/0054834 A1 2/2019 Bardot |
| (52) U.S. Cl. | CPC <i>H04L 12/40013</i> (2013.01); <i>H04L 67/12</i>
(2013.01); <i>B60W 2050/0043</i> (2013.01); <i>H04L</i>
<i>2012/4026</i> (2013.01); <i>H04L 2012/40273</i>
(2013.01); <i>H04L 2212/00</i> (2013.01) | | |
| (58) Field of Classification Search | CPC G06F 21/53; G06F 21/57; G06F 21/445;
G06F 21/6245; G06F 21/64; G06F
21/6218; G06F 21/575; G06F 21/316;
G06F 2221/2149; G06F 2221/2129
See application file for complete search history. | | |

- (56) **References Cited**
- U.S. PATENT DOCUMENTS
- | | | | |
|-----------------|--------|----------------|-----------------------|
| 6,356,968 B1 | 3/2002 | Kishon | |
| 7,484,008 B1 * | 1/2009 | Gelvin | H04L 67/12
709/249 |
| 2003/0135686 A1 | 7/2003 | Vorbach et al. | |

OTHER PUBLICATIONS

The Written Opinion and International Search Report for the International Application PCT/US2020/042894 dated Oct. 6, 2020. The International Search Report with Written Opinion dated Nov. 30, 2020 for PCT Patent Appl. No. PCT/US20/49935.

* cited by examiner




Fig. 1




Fig. 2




Fig. 3





Fig. 4

**Fig. 5**




Fig. 6A




Fig. 6B




Fig. 6C




Fig. 6D




Fig. 6E




Fig. 6F




Fig. 7A




Fig. 7B





Fig. 7C

**Fig. 8**

1

**INTELLIGENT CONTROLLER AND SENSOR
NETWORK BUS, SYSTEM AND METHOD
INCLUDING GENERIC ENCAPSULATION
MODE**

RELATED APPLICATIONS

This application is a continuation-in-part of the co-pending U.S. patent application Ser. No. 16/529,682, filed Aug. 1, 2019, entitled "INTELLIGENT CONTROLLER AND SENSOR NETWORK BUS, SYSTEM AND METHOD," which is hereby incorporated by reference.

FIELD OF THE INVENTION

The present invention relates to the field of buses. More particularly, the present invention relates to a controller and sensor network bus architecture.

BACKGROUND OF THE INVENTION

The field of machine automation is expanding rapidly with the development of self-driving cars, intelligent robots and factory automation. However, due to their varied and high-speed needs, there is no bus or network architecture that is able to efficiently handle all of the demands of these emerging technologies. Instead, the current networks latency is high, bandwidth is low, cabling is complex, with large electromagnetic interference (EMI), high cost, unsecured data and complex system integration. For example, networks do not have enough speed and throughput to carry sensor data like camera and light detection and ranging (LIDAR) data across the network to CPU Cores. Further, existing cable systems are complex, short-reach, and cannot deal with EMI without expensive shielding due to the use of copper cabling systems. There is no all-in-one "Controller and Sensor Network" system Bus solution that can support and carry internet L2/L3 Ethernet packets, Motor & Motion control messages, sensor data and CPU-CMD across a system from edge node to edge nodes.

SUMMARY OF THE INVENTION

A machine automation system for controlling and operating an automated machine. The system includes a controller and sensor bus including a central processing core and a multi-medium transmission intranet for implementing a dynamic burst to broadcast transmission scheme where messages are burst from nodes to the central processing core and broadcast from the central processing core to all of the nodes.

A first aspect is directed to a machine automation system for controlling and operating an automated machine. The system comprises a controller and sensor bus including plurality of input/output ports and a plurality of external machine automation devices operably coupled together via the ports of the bus, wherein the bus comprises a central processing core and a multi-medium transmission intranet comprising one or more central transmission networks directly coupled to the core and including a plurality of nodes and one or more gates and a plurality of subnetworks each coupled to a different one of the gates of one of the central transmission networks, the subnetworks including a plurality of subnodes, wherein each of the nodes and the subnodes is coupled with one or more of the devices via one or more of the ports, receives messages from the one or more of the devices coupled to the one or more of the ports,

2

encapsulates the messages into a generic encapsulation mode (GEM) format for transmission to the central processing core and decapsulates the messages as received from the central processing core from the GEM format to an original format of the input data as received from one of the devices.

In some embodiments, a header of the GEM format comprises a source/destination field that identifies one of the ports as a source of the message or one or more of the nodes and the subnodes as the destination of the message and a GEM packet identifier field that identifies one or more of the ports targeted by the message. In some embodiments, values of the source/destination field are selected from a first set of epoch identifier values when identifying the one of the ports as a source of the message and are selected from a second set of node identifier values when identifying the one or more of the nodes and the subnodes as the destination of the message. In some embodiments, the values of the GEM packet identifier field are selected from a third set of GEM identifier values and each of the node identifier values map to one or more of the epoch identifier values which each map to one or more of the GEM identifier values. In some embodiments, the header of the GEM format comprises a GEM packet type field that indicates the original format and header type of the message that is encapsulated within the GEM format. In some embodiments, a header of the GEM format includes a source identifier field that indicates a source of the message and a report message type field that indicates whether reported data within the message does not relate to the source of the message indicated in the source identifier field.

In some embodiments, a header of the GEM format includes a start-time field that indicates at what time a granted bandwidth window starts and a grant-size field that indicates a size of the granted bandwidth window. In some embodiments, the header of the GEM format includes a grant command field that indicates one or more types of messages that are permitted during the granted bandwidth window. In some embodiments, after encapsulating the messages into the GEM format, each of the nodes and the subnodes puts one or more of the messages into a burst physical layer frame format and transmits the messages to the central processing core by bursting the burst physical layer frame including the one or more of the messages to the central processing core. In some embodiments, the burst physical frame format includes a separate end of burst delimiter field for each one of the one or more messages that indicates an end of the one of the one or more messages within the burst physical layer frame. In some embodiments, each of the gates aggregates the messages in the GEM format from a plurality of the subnodes into a single larger message in a burst physical layer frame format. In some embodiments, each of the gates omit preambles of the messages from the plurality of the subnodes from the single larger message in the burst physical layer frame format. In some embodiments, the devices comprise one or more of the group consisting of an ultrasonic sensor, a light detection and ranging sensor, an infrared sensor, a camera, a motor and a microcontroller. In some embodiments, the automated machine is one of the groups consisting of a robot and a self-driving vehicle.

A second aspect is directed to a controller and sensor bus. The bus comprises a plurality of input/output ports for coupling with a plurality of external machine automation devices of a machine automation system, a central processing core and a multi-medium transmission intranet comprising one or more central transmission networks directly coupled to the core and including a plurality of nodes and

one or more gates and a plurality of subnetworks each coupled to a different one of the gates of one of the central transmission networks, the subnetworks including a plurality of subnodes, wherein each of the nodes and the subnodes is coupled with one or more of the devices via one or more of the ports, receives messages from the one or more of the devices coupled to the one or more of the ports, encapsulates the messages into a generic encapsulation mode (GEM) format for transmission to the central processing core and decapsulates the messages as received from the central processing core from the GEM format to an original format of the input data as received from one of the devices.

In some embodiments, a header of the GEM format comprises a source/destination field that identifies one of the ports as a source of the message or one or more of the nodes and the subnodes as the destination of the message and a GEM packet identifier field that identifies one or more of the ports targeted by the message. In some embodiments, values of the source/destination field are selected from a first set of epoch identifier values when identifying the one of the ports as a source of the message and are selected from a second set of node identifier values when identifying the one or more of the nodes and the subnodes as the destination of the message. In some embodiments, the values of the GEM packet identifier field are selected from a third set of GEM identifier values and each of the node identifier values map to one or more of the epoch identifier values which each map to one or more of the GEM identifier values. In some embodiments, the header of the GEM format comprises a GEM packet type field that indicates the original format and header type of the message that is encapsulated within the GEM format. In some embodiments, a header of the GEM format includes a source identifier field that indicates a source of the message and a report message type field that indicates whether reported data within the message does not relate to the source of the message indicated in the source identifier field.

In some embodiments, a header of the GEM format includes a start-time field that indicates at what time a granted bandwidth window starts and a grant-size field that indicates a size of the granted bandwidth window. In some embodiments, the header of the GEM format includes a grant command field that indicates one or more types of messages that are permitted during the granted bandwidth window. In some embodiments, after encapsulating the messages into the GEM format, each of the nodes and the subnodes puts one or more of the messages into a burst physical layer frame format and transmits the messages to the central processing core by bursting the burst physical layer frame including the one or more of the messages to the central processing core. In some embodiments, the burst physical frame format includes a separate end of burst delimiter field for each one of the one or more messages that indicates an end of the one of the one or more messages within the burst physical layer frame. In some embodiments, each of the gates aggregates the messages in the GEM format from a plurality of the subnodes into a single larger message in a burst physical layer frame format. In some embodiments, each of the gates omit preambles of the messages from the plurality of the subnodes from the single larger message in the burst physical layer frame format. In some embodiments, the devices comprise one or more of the group consisting of an ultrasonic sensor, a light detection and ranging sensor, an infrared sensor, a camera, a motor and a microcontroller. In some embodiments, the automated machine is one of the groups consisting of a robot and a self-driving vehicle.

A third aspect is directed to a method of operating a controller and sensor bus including a plurality of input/output ports for coupling with a plurality of external machine automation devices of a machine automation system, a central processing core and a multi-medium transmission intranet including one or more central transmission networks directly coupled to the core and including a plurality of nodes and one or more gates and a plurality of subnetworks each coupled to a different one of the gates of one of the central transmission networks, the subnetworks including a plurality of subnodes. The method comprises one or more of the nodes and the subnodes receiving messages from the one or more of the devices coupled to the one or more of the ports associated with the one or more of the nodes and the subnodes, encapsulating the messages into a generic encapsulation mode (GEM) format for transmission to the central processing core and decapsulating the messages as received from the central processing core from the GEM format to an original format of the input data as received from one of the devices.

In some embodiments, a header of the GEM format comprises a source/destination field that identifies one of the ports as a source of the message or one or more of the nodes and the subnodes as the destination of the message and a GEM packet identifier field that identifies one or more of the ports targeted by the message. In some embodiments, values of the source/destination field are selected from a first set of epoch identifier values when identifying the one of the ports as a source of the message and are selected from a second set of node identifier values when identifying the one or more of the nodes and the subnodes as the destination of the message. In some embodiments, the values of the GEM packet identifier field are selected from a third set of GEM identifier values and each of the node identifier values map to one or more of the epoch identifier values which each map to one or more of the GEM identifier values. In some embodiments, the header of the GEM format comprises a GEM packet type field that indicates the original format and header type of the message that is encapsulated within the GEM format. In some embodiments, a header of the GEM format includes a source identifier field that indicates a source of the message and a report message type field that indicates whether reported data within the message does not relate to the source of the message indicated in the source identifier field.

In some embodiments, a header of the GEM format includes a start-time field that indicates at what time a granted bandwidth window starts and a grant-size field that indicates a size of the granted bandwidth window. In some embodiments, the header of the GEM format includes a grant command field that indicates one or more types of messages that are permitted during the granted bandwidth window. In some embodiments, the method further comprises, after encapsulating the messages into the GEM format, putting one or more of the messages into a burst physical layer frame format with each of the nodes and the subnodes and transmitting the messages to the central processing core by bursting the burst physical layer frame including the one or more of the messages to the central processing core with each of the nodes and the subnodes. In some embodiments, the burst physical frame format includes a separate end of burst delimiter field for each one of the one or more messages that indicates an end of the one of the one or more messages within the burst physical layer frame. In some embodiments, the method further comprises aggregating the messages in the GEM format from a plurality of the subnodes into a single larger message in a burst

physical layer frame format with each of the gates. In some embodiments, the method further comprises omitting preambles of the messages from the plurality of the subnodes from the single larger message in the burst physical layer frame format with each of the gates. In some embodiments, the devices comprise one or more of the group consisting of an ultrasonic sensor, a light detection and ranging sensor, an infrared sensor, a camera, a motor and a microcontroller. In some embodiments, the automated machine is one of the groups consisting of a robot and a self-driving vehicle.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a machine automation system according to some embodiments.

FIG. 2 illustrates an intelligent controller and sensor intranet bus according to some embodiments.

FIG. 3 illustrates a tree topology of an intelligent controller and sensor intranet bus according to some embodiments.

FIG. 4 illustrates a block diagram of an exemplary computing device configured to implement the system according to some embodiments.

FIG. 5 illustrates a method of operating a machine automation system including an intelligent controller and sensor intranet bus according to some embodiments.

FIG. 6A illustrates an exemplary GEM packet format according to some embodiments.

FIG. 6B illustrates a detailed view of a GEM packet header format according to some embodiments.

FIG. 6C illustrates a detailed view of a GEM header format for a node report message according to some embodiments.

FIG. 6D illustrates a detailed view of a first variant of a GEM header format for a root port bandwidth grant message according to some embodiments.

FIG. 6E illustrates a detailed view of a second variant of a GEM header format for a root port bandwidth grant message according to some embodiments.

FIG. 6F illustrates a detailed view of a GEM header format for a control message according to some embodiments.

FIG. 7A illustrates a Broadcast-PHY-Frame according to some embodiments.

FIG. 7B illustrates a Burst-PHY-Frame according to some embodiments.

FIG. 7C illustrates a gate Burst-PHY-Frame according to some embodiments.

FIG. 8 illustrates a method of operating the intelligent controller and sensor intranet bus according to some embodiments.

DETAILED DESCRIPTION OF THE INVENTION

Embodiments described herein are directed to a machine automation system, method and device for controlling and operating an automated machine. The system, method and device including a controller and sensor bus including a central processing core and a multi-medium transmission intranet for implementing a dynamic burst to broadcast transmission scheme where messages are burst from nodes to the central processing core and broadcast from the central processing core to all of the nodes. As a result, the system, method and device provides the advantage of high speed performance despite combining lower speed network medium as well as one unified software image for the full

intranet system including all gate, node and root ports enabling simplified software architecture, shorter product development cycle, and easier system level debug, monitoring and trouble shooting remotely. In particular, the system, method and device provides a unique intranet system architecture specially defined and optimized for machine automation applications.

FIG. 1 illustrates a machine automation system 100 according to some embodiments. As shown in FIG. 1, the system 100 comprises one or more external devices 102 operably coupled together with an intelligent controller and sensor intranet bus 104. In some embodiments, the system 100 is able to be a part of an automated device such as a self-driving vehicle, an automated industrial machine or an automated self-controlled robot. Alternatively, the system 100 is able to be a part of other machine automation applications. The devices 102 are able to comprise one or more of sensor devices (e.g. ultrasonic, infrared, camera, light detection and ranging (LIDAR), sound navigation and ranging (SONAR), magnetic, radio detection and ranging (RADAR)), internet devices, motors, actuators, lights, displays (e.g. screens, user interfaces), speakers, a graphics processing units, central processing units, memories (e.g. solid state drives, hard disk drives) and controllers/micro-controllers. Each of the devices 102 is able to be operably wired and/or wirelessly coupled with the bus 104 via one or more bus input/output (IO) ports (see FIG. 2). Although as shown in FIG. 1, the system 100 comprises a discrete amount of external devices 102 and buses 104, more or less devices 102 and/or buses 104 are contemplated.

FIG. 2 illustrates the intelligent controller and sensor intranet bus 104 according to some embodiments. As shown in FIG. 2, the bus 104 comprises an intranet formed by a central core 200 that is coupled with one or more gates 202 and a plurality of edge nodes 204 (each having one or more external IO ports 99) via one or more central transmission networks 206, and coupled with one or more edge sub-nodes 208 (each having one or more external IO ports 99) via one or more sub-networks 210 that extend from the gates 202. As a result, as shown in FIG. 3, the bus 104 forms a network tree topology where the central networks 206 branch from the core 200 (e.g. root ports 230 of the core) to edge nodes 204 and gates 202, and the subnetworks 210 branch from the gates 202 to sub-nodes 208 and/or sub-gates 202'. In this way, the core 200 is able to see all of the nodes 204 and sub-nodes 208 (as the gates 202 and sub-gates 202' are transparent to the core 200). In some embodiments, one or more of the gates 202 are directly coupled with IO ports 99 without a node (e.g. to couple with external CPU, GPU, AI cores and/or solid state drives (SSD)).

The ports 99 are able to be any kind of interface port such as peripheral component interconnect express (PCIe), mobile industry processor interface (MIPI), Ethernet, universal serial bus (USB), general purpose input output (GPIO), universal asynchronous receiver/transmitter (UART), inter-integrated circuit (I²C) and/or other types of ports. Although as shown in FIG. 2, the bus 104 comprises a discrete amount of ports 99, cores 200, nodes 204, 208, gates 202, networks 206, 210, other elements and components thereof, more or less ports 99, cores 200, nodes 204, 208, gates 202, networks 206, 210, other elements and/or components thereof are contemplated.

The central transmission networks 206 are able to comprise connection media that is faster/lower latency than the connection media of the subnetworks 210 coupled to a gate 202 of that central transmission network 206. Similarly, the subnetworks 210 are able to comprise connection media that

is faster/lower latency than the connection media of the subnetworks **210'** coupled to a gate **202'** of the subnetwork **210** and so on for each iterative subnetwork. This network/subnetwork connection media speed/latency relationship enables the bus **104** to prevent the slowing of the processing of the entire bus **104** despite still including the slower connection media as describe in detail below. Alternatively, one or more of the subnetworks **210**, **210'** and/or the central networks **206** are able to have the same or other connection media speed/latency relationships.

In some embodiments, the connection media of the central transmission networks **206** comprises optical fiber cables **212** split using optical splitters **214** (e.g. 2-to-1 splitters) and having optical transceivers **216** to couple to and received data from the nodes **204**, **208**. In some embodiments, the connection media of the subnetworks **210** comprises optical connection media (e.g. like the central transmission networks **206**, but possibly slower rating), wireless connections (e.g. radio frequency transceivers **218**), copper connections (e.g. twisted-pair copper wires **220** optionally split using analog splitters **222** (e.g. fan-outs/multiplexers) and having serializer/deserializers (SERDES) **224** to couple to and received data from the nodes **204**, **208**), and/or combinations thereof (e.g. hybrid optical fiber, copper and/or wireless connection media). As a result, the bus **104** supports multi-rate traffic transmissions where depending on the latency/speed, connectivity and/or distance requirements of the data/traffic/external devices **102**, different nodes/networks are able to be used to coupled to the bus **104** while still providing the desired throughput. For example, for high speed, low latency and long-distance requirements the optical connection media of the central network is able to be used by coupling to the nodes **204**. Otherwise, the other networks **210** are able to be used depending on cost, speed, connection and/or distance requirements. In some embodiments, the central networks **206** are passive optical networks and/or the copper subnetworks **210** are active networks. In some embodiments as shown in FIG. 2, one or more of the nodes **204** is coupled to a controller area network (CAN) **226** such that the node inputs data from each of the controllers coupled to the controller are network. Alternatively, as shown in FIG. 3, one or more of the subnetworks **210** are able to be a CAN coupled with the core **200** via one of the gates **202**.

Multi-Layer Bus Addressing

The bus **104** is able to utilize a multi-layered addressing scheme where the root ports **230**, IO ports **99**, nodes **204**, **208**, **234** and/or gates **202** are able to use node, epoch and GEM identifying addresses for directing messages through the bus **104**. In particular, each of the root ports **230**, nodes **204**, **208**, **234** and gates **202** are able to be assigned a node identifier (node-ID), with the nodes **204**, **208** and gates **202** also being assigned at least one epoch identifier (epoch-ID) and at least one GEM identifier (GEM-ID). The epoch-IDs are able to be used to identify the source/destination of messages in the network **206**, **210** (e.g. node/gate devices and their IO ports, embedded CPUs and/or other types of services) while at the same time the GEM-IDs are able to be used to identify the targets of messages (e.g. sets and subsets of the node/gate devices and their IO ports, embedded CPUs and/or other types of services). As a result, the epoch-IDs are able to be used for the transmission/routing of messages throughout the network **206**, **210** while the GEM-IDs are able to be used by the devices themselves (via the ports **99**) to determine whether to capture received/broadcast messages as being targeted to them.

Depending on the service level agreement (SLA) profile of the node/gate (which is able to correspond to the devices coupled to the port(s) **99** of the node/gate), the nodes/gates are able to be assigned multiple epoch-IDs and multiple GEM-IDs. As a result, the node-ID of each of the nodes **204**, **208** and gates **202** is able to map to one or a plurality of epoch-IDs which are able to map to one or a plurality of GEM-IDs. For example, a node **204**, **208** coupled with two IO ports **99** is able to have a single node-ID, two epoch-IDs (one for each port **99**) and ten GEM-IDs (one associated with the first epoch-ID and first port **99** and nine associated with the second epoch-ID and second port **99**). Further, although the node-IDs and epoch-IDs are unique to each node/gate/port, the GEM-IDs are able to be shared between nodes/gates/ports. For example, ports **99** of the same node **204**, **208** or different ports **99** of different nodes **204**, **208** are able to both be associated with matching or overlapping sets GEM-IDs.

The gates **202** are also able to be assigned one or more virtual node-IDs for the ports **99** directly coupled with the gate **202**. Like the regular nodes, these virtual nodes represented by the gates **202** are able to be assigned multiple epoch-IDs and multiple GEM-IDs depending on the SLA profile of the gate **202** (which is able to correspond to the devices coupled to the port(s) **99** of the virtual node/gate).

The other nodes **234** and cores **232** (that are directly coupled to the core **200** such as IO devices and embedded CPU cores) are each able to have one or more GEM-IDs along with a global node-ID, but do not need to be assigned epoch-IDs, which are not required because messages to and from these nodes **234** to the core **200** are wholly within the core **200**. Like nodes **204**, **208**, the number of GEM-IDs assigned to each of the nodes **234** and cores **232** is able to be determined based on the SLA profile for that node **234** or core **232** (which is able to correspond to the devices coupled to the port(s) **99** of the node **234**). Each of the core switch **220**, root ports **230**, nodes **204**, **208**, **234**, and/or gates **202** are able to maintain and update a local SLA table that indicates the mapping between each of the node-IDs, epoch-IDs and GEM-IDs. As a result, the bus addressing provides the advantage of using epoch-IDs and/or node-IDs to facilitate simplified burst/broadcast messaging between nodes, gates and the core within the network **100**, while at the same time using GEM-IDs facilitate any desired more complex messaging between the devices/IO ports **99** and/or the core themselves.

Generic Encapsulation Mode

The bus **104** is able to encapsulate all input data and internally generated data (e.g. control, operation and management messages) into a generic encapsulation mode (GEM) for transport across the bus **104** intranet. Thus, the GEM acts as a unique standardized data and message container for transmitting data between nodes and/or to the core **200** via the bus **104** intranet. As a result, the input data is able to be encapsulated into the GEM format at each of the nodes as it enters the bus **104** and is routed through the core **200** (where it is decapsulated for processing and re-encapsulated for transmission) and onto its destination node which decapsulates the data back to the original format for egress to the target external device **102** or other destination. This input data is able to be from various sources (e.g. devices **102**, CAN **226**) input via the ports **99** at the nodes **204**, **208**, **234** or gates **202** and/or the embedded CPU cores **232**.

There are two types of GEM formats: GEM packet and GEM control. The GEM packet format comprises a GEM header plus a GEM payload (e.g. length from 8 bytes to 4 kilobytes). Typically, the GEM packet format what is used to

encapsulate the input port data, packets and messages at the ingress (e.g. nodes, ports). The following are some of the IO port data, packet and message examples that are able utilize the GEM packet format:

Use GEM packet format to carry Ethernet packets from local gate **202** and/or node **204, 208** through bus **104** after GEM encapsulation to far-end gate **202** and/or node **204** (e.g. this is able to be for internet and Wi-Fi interfaces through Ethernet Port or PCIe Ports);

Use GEM packet format to carry sensor data from local gate **202** and/or node **204**, transmit through bus **104** after GEM encapsulation to far-end gate **202** and/or node **204** (e.g. CAN bus data, Camera (MIPI) Frame data, Lidar (Ethernet) data, Magnetic Encoder data (ADC) and other type of Sensors data);

Use GEM packet format to carry jumbo size data and packets and transmit through fragmentation and defragmentation scheme, from local node **204, 208** to far-end node **204, 208**. This is able to include fragmentation, defragmentation and re-ordering/re-transmission functions;

Use GEM packet format to carry the network control, operation and management messages between core **200** and nodes **204, 208** (and/or gates), including physical layer operation, administration and maintenance (PLOAM), node management control interface (NMCI) and operations, administration and maintenance (OAM) messages;

Use GEM packet format to carry CPU/PCIe access CMD/DATA from core **200** and local gate **202** and/or node **204** through bus **104** after GEM encapsulation, to far-end local gate **202** and/or node **204** (e.g. CPU **232** access target device **102** from NODE-to-NODE through PCIe, USB, I2C, UART and GPIO interfaces).

Finally, use GEM packet format for VPN channel application between local-nodes **204, 208** to far nodes **204, 208** through bus **104**.

The GEM control message format comprises message plus extended message (e.g. length 8 bytes+8 bytes . . .). The GEM control message format is able to be used in the bus **104** for internal network management and control purposes, including messages of dynamic bandwidth allocation (DBA) reporting, DBA-Granting, GEM RX-Acknowledge, GEM Flow-Control, GEM Power-Management, GEM-Sniffer, GEM-Remote messages and/or other types of control messages. As described above, nodes **204** are responsible for encapsulating/decapsulating data to/from GEM packet and GEM control message format. This scheme is able to expand PCIe interface protocol from point-to-point topology to point-to-multi-point topology and extend the interface distance from short reach to long reach.

FIGS. **6A-F** illustrate an exemplary GEM packet format and GEM header formats according to some embodiments. As shown in FIG. **6A**, an GEM packet **600** is able to comprise a header **602** and a corresponding payload **604**. As described above, for message packets the header is able to be a set size (e.g. 8 bytes) and the payload is able to vary in length (e.g. length from 8 bytes to 4 kilobytes) and for control packet the header is able to be, for example, 8 bytes with or without one or more 8 byte extensions.

FIG. **6B** illustrates a detailed view of a GEM packet header format according to some embodiments. As shown in FIG. **6B**, the header **602** comprises a GEM type field **606**, a payload length indication field **608**, an encryption key index field **610** (e.g. AES Key Index), a node/epoch ID field **612**, a GEM-ID field **614**, a GEM packet type field **616**, a transmission sequence identifier field **618**, an acknowledg-

ment required field **620**, a last fragment indication field **622** and a header error correction/check (HEC) field **622**. Alternatively, one or more of the fields are able to be omitted and/or one or more additional fields are able to be added. In some embodiments, the GEM type field **606** is two bits, the payload length indication field **608** is twelve bits, the encryption key index field **610** is two bits, the node/epoch ID field **612** is twelve bits, the GEM-ID field **614** is twelve bits, the GEM packet type field **616** is three bits, the transmission sequence identifier field **618** is six bits, the acknowledgment required field **620** is one bit, the last fragment indication field **622** is one bit and the header error correction/check (HEC) field **622** is thirteen bits. Alternatively, one or more of the fields are able to be larger or smaller.

The GEM type field **606** indicates which type of header **602** (and thus which type of packet) the GEM packet **600** is. For example, the GEM type field is able to indicate that the header **602** is one or more of a packet header, a bandwidth grant message header (e.g. transmitted from a root port **230** to a gate/node), a bandwidth report message header (e.g. transmitted from a gate/node to a root port **230**) and/or a control message (e.g. between one or more of the root ports **230**, the gates **202** and/or the nodes **204, 208, 234**). The payload length indication field **608** indicates the length of the payload **604** of the packet **600**. The encryption key index field **610** indicates the type of encryption to use on the packet **600**. For example, the encryption key index field **610** is able to be used as an index value within an encryption table to identify one or more of: whether to encrypt the packet or not, which key to use to encrypt the packet, and/or which method of encryption to use.

The node/epoch ID field **612** is able to identify either the source node or the destination node of the packet **600**. For example, for a GEM packet **600** being burst from a node to the core, the field **612** is able to be or represent the node's epoch-ID to indicate the source of the packet **600**. As another example, for a GEM packet **600** being broadcast from a root port **230** to the nodes/gates within its network **206, 210**, the field **612** is able to be or represent the destination's node-ID (including a unicast node-ID, a multicast node-ID and/or a broadcast node-ID). The GEM-ID field **614** is able to be or represent the source node's data/packet/message identifier for a point to point message, or is able to be or represent the destination node's GEM-ID (e.g. including CAN message GEM-IDs, sensor data GEM-IDs and/or ethernet packet GEM-IDs) for point to multi-point messages. As a result, the GEM format provides the advantage of enabling the bus **104** to identify both the immediate source and/or destination nodes via the node/epoch ID field **612** while also enabling the target devices/port/services to be identified using the GEM-ID field **614**.

The GEM packet type field **616** is able to indicate the type and format of the header of the message encapsulated within the GEM format (e.g. as received from the devices **102** and/or through the ports **99**). For example, the field **616** is able to indicate that the message header is a PLOAM message, a node management and control interface (NMCI) message, a CAN command message, sensor data, an ethernet packet, CPU-IO (e.g. PCIe/USB) message and/or a node operation and control report (NOCR) message. The acknowledgment required field **620** is able to indicate if an acknowledgment message in response to the message is require and the transmission sequence identifier field **618** is able to identify the transmission sequence number of the packet **600** within a set of packets from the source node and/or an epoch-ID thereof (for a packet being burst from the node to the core **200**). In some embodiments, it requires

an acknowledgment message from the receiving root port **230** when indicated by the acknowledgment required field **620**. For a packet broadcast from the root port **230** to a node/gate, the transmission sequence identifier field **618** is able to identify the transmission sequence number of the unicast/broadcast/multi-cast GEM-ID (e.g. CAN Message GEM-ID, sensor Data GEM-ID, Ethernet Packet GEM-ID and CPU/PCIe/USB Data-Message GEM-ID). In some embodiments, it requires acknowledge from receiving root port **230** and/or node when indicated by the acknowledgment required field **620**. The last fragment indication field **622** is able to indicate if this packet **600** is the last fragment of a series of fragments of a large packet and the header error correction/check (HEC) field **622** is able to be used to check the header **602** for errors.

FIG. **6C** illustrates a detailed view of a GEM header format for a node report message according to some embodiments. As shown in FIG. **6C**, the header **602** comprises a GEM type field **606**, a report message type field **624**, a source epoch-ID field **626**, a report total size field **628**, a report threshold size field **630**, a report sequence number field **632**, one or more source node virtual output queue (VOQ) status fields **634** (e.g. CPU-IO, PLOAM, NMCI, CAN, Sensor, Ethernet, or other types), a report priority field **636** and a header error correction/check (HEC) field **622**. Alternatively, one or more of the fields are able to be omitted and/or one or more additional fields are able to be added. In some embodiments, the GEM type field **606** is two bits, the report message type field **624** is two bits, the source epoch-ID field **626** is twelve bits, the report total size field **628** is fourteen bits, the report threshold size field **630** is eight bits, the report sequence number field **632** is five bits, the one or more source node virtual output queue status fields **634** are each one bit (or a single field of six bits), the report priority field **636** is two bits and the header error correction/check (HEC) field **622** is thirteen bits. Alternatively, one or more of the fields are able to be larger or smaller.

The report message type field **624** indicates which type of report header **602** (and thus which type of report message) the GEM packet **600** is. For example, the report message type field **624** is able to indicate that the header **602** is one or more of an invalid report message, a node report message for itself (e.g. where the epoch-ID of the source of the packet is mapped to the node-ID of the source of the packet), a node report message for another node (e.g. where the epoch-ID of the source of the packet is not mapped to the node-ID of the source of the packet), and/or a dying gasp report message (e.g. a message that needs/requests top priority). The source epoch-ID field **626** is able to be or represent: the source node's epoch-ID (e.g. for a report for PLOAM and NMCI plus CAN/sensor/ethernet queue flags), the CAN's epoch-ID (e.g. for a report for the CAN), the epoch-ID of one of the sensors/nodes (e.g. for a report for the sensor), the ethernet epoch-ID (e.g. for a report for ethernet packets) and/or a PCIe/USB epoch-ID (e.g. for a PCIe/USB report message). The report total size field **628** is able to indicate the total size of the GEM data within the VOQ (for that epoch-ID and/or Node-ID), whereas the report threshold size field **630** is able to indicate the GEM packet boundary(ies) within the VOQ (e.g. for use when determining the size of burst windows granted for the epoch and/or node).

The report sequence number field **632** is able to indicate which number in the sequence that the message is (e.g. if there are a sequence of related report messages in order to determine if one is lost or mis-sequenced). The one or more source node virtual output queuing (VOQ) status fields **634** are each able to indicate a status of the source node with

respect to a particular function/type of data (e.g. CPU/IO, PLOAM, NMCI, CAN, sensor, ethernet). The report priority field **636** is able to indicate what priority to give the message (e.g. best efforts, normal bandwidth request priority, CAN message request priority, dying gasp request priority).

FIGS. **6D** and **E** illustrate a detailed view of two variants of a GEM header format for a root port bandwidth grant message according to some embodiments. As shown in FIG. **6D**, for a node grant message where the node-ID is the same as the epoch-ID, the header **602** is able to comprise a GEM type field **606**, an epoch-ID field **638**, a start time field **640**, a grant size field **642**, a grant flag field **644**, a report command field **646**, a grant command field **648**, a force wake-up indicator (FWI) field **650**, a burst profile field **652** and a header error correction/check (HEC) field **622**. Alternatively, one or more of the fields are able to be omitted and/or one or more additional fields are able to be added. In some embodiments, the GEM type field **606** is two bits, the epoch-ID field **638** is twelve bits, the start time field **640** is fourteen bits, the grant size field **642** is fourteen bits, the grant flag field **644** is one bit, the report command field **646** is three bits, the grant command field **648** is two bits, the force wake-up indicator field **650** is one bit, the burst profile field **652** is two bits and the header error correction/check (HEC) field **622** is thirteen bits. Alternatively, one or more of the fields are able to be larger or smaller.

The epoch-ID field **638** is able to be or represent the epoch-ID of the node or node-ID that the message is for. The start time field **640** is able to indicate a starting time of the grant window that is being granted to the target node (e.g. epoch of that node) and the grant size field **642** is able to indicate the size/duration of the grant window. The grant flag field **644** is able to indicate whether the window was granted. The report command field **646** is able to indicate what reporting is requested from the node/epoch/port. For example, the report command field **646** is able to indicate one or more of: no node request to send (RTS) status report or force node to report RTS message to port for blackbox and diagnostic test; combined with one or more of: PLOAM and NMCI reporting only forced reporting of CPU-IO messages, CAN messages and sensor data plus PLOAM/NMCI; forced reporting for ethernet packets plus CPU-IO/CAN/sensor and PLOAM/NMCI; and/or forced full report of PLOAM/NMCI/CPU-IO/CAN/sensor/ethernet plus a node operation and control report (NOCR). The grant command field **648** is able to indicate what type of messages/data are granted the burst window. For example, the grant command field **648** is able to indicate one or more of: the window is not for PLOAM and NMCI messages; the grant window is only for PLOAM messages; the grant window is only for NMCI messages; and/or the grant is for PLOAM, NMCI and NOCR messages. The FWI field **650** is to indicate whether to force a sleeping node to wake-up and the burst profile field **652** is able to indicate a burst configuration (e.g. length, pattern and/or other characteristics of the SOB delimiter, EOB delimiter and/or preamble).

As shown in FIG. **6E**, for a GEM grant message where the node-ID is not the same as the epoch-ID, the header **602** is able to be substantially the same as the header of FIG. **6D** except without the report command field **646** and the FWI field **650**. Further, unlike in FIG. **6D**, the grant command field **648** is able to be six bits. Alternatively, the grant command field **648** is able to be larger or smaller. Also unlike in FIG. **6D**, the grant command field **648** is able to indicate a GEM bandwidth grant of different types. For example, the field **648** is able to indicate a bandwidth grant for: all VOQ/CoS (class of service) based on the nodes's

output scheduling settings, for CAN messages only, for sensor data only, dying gasp messages only and/or for both CAN messages and sensor data. Additionally, the field **648** is able to force power saving for the node-ID where the node replies with an acknowledge message.

FIG. **6F** illustrates a detailed view of a GEM header format for a control message according to some embodiments. As shown in FIG. **6F**, the header **602** comprises a GEM type field **606**, a control message type field **654**, one or more control message fields **656** and a header error correction/check (HEC) field **622**. Alternatively, one or more of the fields are able to be omitted and/or one or more additional fields are able to be added. In some embodiments, the GEM type field **606** is two bits, the control message type field **654** is four bits, the one or more control message fields together are forty-five bits and the header error correction/check (HEC) field **622** is thirteen bits. Alternatively, one or more of the fields are able to be larger or smaller.

The control message type field **654** is able to indicate what type of control message the message is (e.g. so the control message fields **656** and their offsets are known for processing). In some embodiments, the control message type field **654** indicates one or more of: a report acknowledgment message; a CAN acknowledgment message; a flow control message; a power saving message; and IO event message (e.g. dying gasp); a run-time status message; and/or a timestamp update (e.g. from port to node). The control message fields **656** are able to include various control message fields based on the type of control message (as indicated in control message type field **654**).

Accordingly, the GEM format provides the benefit of enabling the bus **104** to encapsulate varying input data and messages of significantly different types of networks (e.g. controller area networks, optical networks, sensor device broadcasting networks, wireless networks, CPU access networks) to one unique format (GEM). This unique format is then able to facilitate high speed standardized processing and transmission of the varied data input in both burst and broadcast messages thereby enabling the efficient operation of the multi-network multi-device bus architecture required for modern machine automation applications.

Burst/Broadcast Frame Format

In some embodiments, the broadcast messages are formatted into a Broadcast-PHY-Frame defined by: Preamble+Start-of-Frame-Delimiter+Frame-Payload, wherein the frame payload includes multiple GEM-Packet data and GEM-Control messages. The Broadcast-PHY-Frame is able to be a fixed frame size (e.g. between 25-125 μ s). Alternatively, greater or smaller frame sizes are able to be used. For example, for central networks **206** and subnetworks **210** with less node devices **204, 208**, the frame size is able to be smaller (e.g. 25 μ s or 50 μ s). In some embodiments, the Broadcast-PHY-Frame is constructed to carry GEM-Packet and GEM-Control messages from the root ports **230** to the gate **202** and/or nodes **204, 208, 234** through the networks **206, 210** including optical, copper and wireless networks.

In some embodiments, the burst messages are formatted into a Burst-PHY-Frame defined by: Preamble+Start-of-Frame-Delimiter+Frame Payload+End-of-Frame-Delimiter, wherein the frame payload includes one or more GEM-Packet data and GEM-Control messages. The Burst-PHY-Frame size is able to vary depending on the total Burst-Window size of node/gate granted by root port HDBA and/or gate DBA. In some embodiments, the max size of Burst-PHY-Frame (from a gate **202** or a node **204, 208, 234**) cannot exceed the max Broadcast-PHY-Frame size (e.g. between 25-125 μ s). In some embodiments, the Burst-PHY-

Frame is constructed to carry GEM-Packet and GEM-Control messages from gates **202** and/or nodes **204, 208, 234** to the root ports **230** and/or gates **202** via the networks **206, 210** including optical, copper and wireless networks.

FIG. **7A** illustrates a Broadcast-PHY-Frame **700** according to some embodiments. As shown in FIG. **7A**, the Broadcast-PHY-Frame **700** comprises a physical synchronization block for broadcast (PSBbc) **702** and a broadcast framing sublayer frame **704** including a GEM control message **706**, one or more GEM packets **600** and a framing sublayer (FS) trailer **708**. Each of the GEM packets **600** include a header **602** and a payload **604** as described above. In some embodiments, the broadcast FS frame is FEC protected. FIG. **7B** illustrates a Burst-PHY-Frame **710** according to some embodiments. As shown in FIG. **7B**, the Burst-PHY-Frame **710** comprises a physical synchronization block unicast start of burst delimiter (PSBuc_sd) **712**, a burst framing sublayer (FS) **714** and a physical synchronization block unicast end of burst delimiter (PSBuc_ed) **716**. The PSBuc_sd **712** is able to include a preamble **718** and a start of burst (SOB) delimiter **720** and the PSBuc_ed **716** is able to include an end of burst (EOB) delimiter **722**. The burst FS **714** is able to include a FS header **724**, one or more epochs **726** and an FS trailer **708**. Each of the epochs **726** are able to include one or more GEM packets **600** having a header **602** and a payload **604** as described above. In some embodiments, the burst FS frame is FEC protected. In particular, by including an EOB delimiter (in addition to the SOB delimiter and a size of the frame), the structure **710** enables a sniffer, analytics engine or other element to monitor the traffic within the bus **104** because it enables the element to determine the end of each burst frame based on the EOB delimiter despite not knowing/accessing the size of the frame.

FIG. **7C** illustrates a gate Burst-PHY-Frame **728** according to some embodiments. As shown in FIG. **7C**, the gate Burst-PHY-Frame **728** is able to comprise one or more Burst-PHY-Frames **710** combined together into a single combined burst-PHY-frame having a single preamble **729** and one or more gaps **730**. In particular, as described in detail below, the gates **202** are able to receive burst frames **728** from one or more subnodes **208** as well as one or more IO ports **99** (for which they serve as a virtual node) and combine those frames **728** into a combined gate Burst-PHY-Frame **728** as shown in FIG. **7C**. As a result, the system **100** provides the advantage of more efficient message communication via combined burst frames as well as less overhead per frame by using only a single preamble for the combined frame as a whole instead of a separate preamble for each combined burst frame (whose preamble can be up to 256 bytes each or more).

FIG. **8** illustrates a method of operating the intelligent controller and sensor intranet bus **103** according to some embodiments. As shown in FIG. **8**, one or more of the nodes **204, 208** input one or more messages from the one or more of the devices **102** coupled to the one or more of the ports **99** at the step **802**. The nodes **204, 208** encapsulate the messages into the generic encapsulation mode (GEM) format for transmission to the central processing core **200** at the step **804**. If the destination(s) of the input messages is a node **234** inside the core **200**, the core decapsulates, processes and transmits the messages to their destination(s) without re-encapsulation at the step **806**. Otherwise, if the destination(s) of the input messages is one or more other nodes **204, 208** (outside the core **200**), the core **200** decapsulates, processes and re-encapsulates the messages back into the GEM format for broadcast to their destination(s) at

the step 808. The nodes 204, 208 decapsulate the messages as received from the core 200 from the GEM format to an original format of the input data as received from one of the devices 102 at the step 810. Alternatively, if the input messages are input from nodes 234 inside the core 200 they are able to be input and processed by the core 200 (without being encapsulated) and only encapsulated by the core 200 for broadcast if their destination is one or more nodes 204, 208 outside the core 200. As a result, the method provides the advantage of enabling the communication of many different types of data (e.g. sensor, controller bus, ethernet, or other types of data), more efficient message communication via combined burst frames, and less overhead per frame by using only a single preamble for the combined frame as a whole instead of a separate preamble for each combined burst frame.

Core

The core 200 is able to comprise a core switch 228, one or more root ports 230 (internal ports), a central processing unit 232 and one or more core nodes 234 having IO ports 99 (external ports). In some embodiments, the core 200 further comprises a secure memory (e.g. secure digital (SD) memory) node 236 for storing data in a black box memory 238. Alternatively, the SD node 236 and/or memory 238 are able to be omitted. The core nodes 234 enable a user to couple a user plug-in module (e.g. CPU core, WIFI LTE/5G, User Application software) directly to the core 200 bypassing the networks 206, 210.

The core switch 228 comprises a forwarding engine element, a queuing buffer manager and a traffic manager. Forwarding engine element is able to comprise a plurality of forwarding engines. For example, it is able to include one engine used for L2/L3/L4 Ethernet header parser, lookup and classification/access control list (ACL) function, including L2 medium access control (MAC) Address learning and forwarding functions, L3 internet protocol (IP) Address to GEM-ID Routing/mapping. Additional, one engine is able to be used for GEM Header message parser, lookup, ACL and forwarding and/or another is able to be used to support DOS attack functions to protect the bus 104 from external internet DOS attack. The GEM-Queuing-Buffer Manager is able to be a centralized buffering architecture, which employs link-list based buffer and queuing memory methods combining store-N-forward and cut-through forwarding schemes. For latency sensitive GEM-Packet and GEM-Messages, it is able to use a cut-through forwarding scheme and for congestion GEM-Packets it is able to use store-N-forward scheme. Both schemes are able to be dynamically mixed together and dynamically switched between each other depending on the run-time traffic congestion situations. The GEM-Traffic Manager supports GEM-ID and NODE-ID base dual-token policing, single-token rate-limiting and output shaping functions, including related management information base (MIB) counters. GEM-ID base weighted random early detection (WRED) and Tail-Drop functions are able to be supported as well as early traffic congestion detection and indication and feedback mechanisms to notify hybrid dynamic bandwidth allocation mechanisms (HDBA), root ports 230, gates 202 and nodes 204, 208, 234 to slow down traffic transmission in order to avoid traffic congestion from occurring.

As a result, the core switch 228 is able to provide the functions of on ingress, the switch 228 receives GEMs from one or more of the root ports 230, local nodes 234, computer 232 and/or other IO ports, processes the GEMs and on egress, forwards and transmits the received GEMs to one or more of the root ports 230, local nodes 234, computer 232

and/or other IO ports. In other words, the switch 228 is able to accept GEM-Packets from multiple sources; perform GEM and Ethernet L2/L3/L4 header parsing, L2 MAC lookup and learning, GEM message and 5-tuple ACL and classification; modify GEM-Header and GEM payload Ethernet header (if necessary); and store and forward GEM-Packet (or cut-through buffer memory) to one or multiple hybrid automatic repeat request (HARQ) functional blocks and the broadcast-MAC of one or more root ports 230.

In performing this processing and/or forwarding function, the switch 228 is able to support hybrid store- and forward and cut-through forwarding schemes in order to reduce propagation latency for latency sensitive GEMs and provide big enough buffering for over burst GEM traffic. Additionally, the switch 228 is able to support instant-flow-control mechanisms within the bus 104, including hybrid dynamic bandwidth allocation and granting to ensure overall quality of service (QoS) across the bus 104. Further, the switch 228 is able to support L2/L3/L4 ACL and classification, L2 MAC address learning and forwarding, L3 IP address to GEM-ID routing/mapping, as well as DOS attack protection. Finally, the switch 228 is able to support QoS scheduling, GEM buffering WRED/Tail dropping, node and/or GEM policing and output shaping functions.

Root Ports

The root ports 230 are able to comprise a root transmission MAC, a root reception MAC, a security engine (e.g. advanced encryption standard (AES)), a forward error correction (FEC) engine, a hybrid dynamic bandwidth allocation (HDBA) engine, an activation processor (e.g. activation state machine) and a burst-mode SERDES IP. Alternatively, one or more of the above elements are able to be omitted. The transmission MAC of each of the root ports 230 is responsible for accepting GEMs ready for egress from switch 228 and/or HARQ; map and pack the GEMs into a broadcast frame format (e.g. Broadcast PHY-Frame structure); and broadcast the GEMs to all of the gates 202 and/or nodes 204 on the central transmission network 206 to which the root port 230 is coupled (e.g. through root SERDES and optical/copper network broadcast domains). Conversely, the reception MAC of each of the root ports 230 is responsible for receiving GEMs in a burst frame format (e.g. Burst-PHY-Frame structure) from Burst-Mode SERDES and gates 202 and/or nodes 204, 208; extracting the GEMs from burst frame format; parsing the GEM-header of the GEMs; and accepting the GEMs addressed to it (e.g. based on the GEM-Header and system service level agreement (SLA) profile settings), then outputting the GEMs/data to the switch 228 for further processing and forwarding. In other words, the root ports 230 are each able to receive burst traffic from the nodes 204 and/or gates 202 (forwarded from nodes 208 in the subnetwork 210 of the gate 202), convert the burst traffic to the correct format for processing by the switch 228 and then reformat and broadcast output traffic to all of the nodes 204 and nodes 208 (via the gates 202) to destinations as directed by the switch 228.

The hybrid dynamic bandwidth allocation (HDBA) engine is responsible for receiving reports about bandwidth usage, traffic congestion and other factors (e.g. NODE-DBA Reports); performing HDBA analysis based on an SLA profile for the node/port/device associated with each report, the DBA-Report data itself and committed information rate (CIR)/peak information rate (PIR) feedback; and granting burst windows to each NODE device and assigned port/EPOCH-ID. In other words, the HDBA engine inputs data from each of the nodes 204, 208 (of the network 206 associated with the root port 230 and subnetworks 210

thereof) and/or other sources about bandwidth usage/traffic congestion and dynamically allocates burst transmission window start times and/or sizes to each of those nodes **204**, **208**. In performing this allocation for the nodes **208** within the subnetworks **210**, the gate **202** that provides access to the nodes **208** is transparent to the HDBA engine. As a result, as described in detail below, the gate **202** receives the desired data and performs the burst transmission within the assigned windows for each of the nodes **208** of the gate's **202** subnetwork **210**. The HDBA engine is also able issue reporting acknowledgment messages (GEM-Report-ACK message) to nodes **204**, **208** to confirm that the report messages (GEM-DBA Reports) were received.

The root Activation State-Machine is responsible for performing and completing node **204**, **208**, **234** device activation and registration through activation processes and procedures by exchanging physical layer operations, administration and maintenance (PLOAM) GEM messages between nodes **204**, **208**, **234** and the root port **230**. The security engine is able to be an AES-128/256 encryption and decryption functional block used for both the reception and transmission MACs. Alternatively, other encryption is able to be used. The forward error correction (FEC) engine is used for controlling errors in data transmission over unreliable or noisy communication channels. In some embodiments, the FEC engine uses Reed Solomon FEC coding schemes of RS(255,216) and RS(225,232) for 10G and 2.5G data rates, respectively. Alternatively, the FEC engine is able to use low-density parity-check (LDPC) schemes and/or other FEC algorithms. The burst-mode SERDES uses fast clock and data recovery (CDR) locking mode to ensure proper burst messages (e.g. burst-PHY-Frames) are received correctly. In some embodiments, the fast locking function of CDR is required in fiber-cut, fast fail-over and protection switch recovery.

Finally, after a registration process, the root ports **230** receive broadcast data distribution service (DDS) messages from nodes **204**, **208** that notify the root port **230** that new nodes/devices have joined and registered to bus **104**. Accordingly, the root ports **230** are configured to always listen and accept these data distribution service (DDS) messages from the switch **228** and new node's **204**, **208** declaration of joining the bus **104**, and update the Root-Port SLA profile database and settings to reflect the newly added nodes/devices.

Nodes

The edge nodes **204**, **208**, **234** provide a bridge function within the bus **104** to interface with external devices **102** via the IO ports **99** on one side and connect to bus intranet **104** on the other side. In order to provide data from the devices **102** coupled to the ports **99** of the nodes **204**, **28**, the nodes **204**, **208**, **234** construct and transmit burst messages (e.g. Burst-PHY-Frames of the data encapsulated as GEMs) through the bus **104** to the other nodes **204**, **208** via the root port **230** (of the network **206** of which they are a part or a subnetwork **210** thereof). Further, in order to provide data to the devices **102** coupled to the ports **99** of the nodes **204**, **28**, the nodes **204**, **208**, **234** receive broadcast message (e.g. Broadcast-PHY-Frames of the data encapsulated as GEMs) from other nodes **204**, **208** via the root port **230** (of the network **206** of which they are a part or a subnetwork **210** thereof), extract the data from the broadcast messages (e.g. GEMs from RX BC-PHY-Frames), and filter and accept the data that belongs (is addressed to) the node **204**, **208**.

To perform these and other functions, the edge nodes **204**, **208** are able to comprise one or more IO ports **99**, an encapsulation/decapsulation engine, a HARQ block and a

node MAC. Each of the ports **99** is able to be one of a CPU interface (e.g. PCIe, USB and UART), a sensor interface (e.g. MIPI, analog to digital converter (ADC), GPIO), an internet interface (e.g. Ethernet, EtherCAT, and CAN-Bus), and a motor module interface (e.g. pulse width modulation (PWM), I²C, ADC and GPIO). The encapsulation/decapsulation engine accepts input data from the ports **99** and encapsulates received data packets, commands (CMD) and messages received from the internet ports (e.g. Ethernet, Wi-Fi), sensor interfaces, motor module interface and CPU (e.g. PCIe and USB) to the GEM format at the ingress. The nodes **204**, **208** then are able to output to the encapsulated messages (e.g. GEMs) to the HARQ and/or node transmission MAC (described below). At the egress, it accepts GEM-packets from the node reception MAC (received from the root port **230** and/or another node **204**, **208**, **234**) and decapsulates the GEM back to the original data format (as received from the coupled device **102**) for output to the device **102** via one of the ports **99**. Like in the root ports **230**, the HARQ of the nodes **204**, **208** perform the hybrid automatic-repeat-request function to ensure that the GEM-Packets are delivered to their destination node or nodes **204**, **208**, **234** successfully. Specifically, the HARQ is able to be built-in with a repeat transmit timer, transmit GEM list flag table and receipt acknowledgment checking function (e.g. GEM RX-Acknowledge) to trigger GEM re-transmission when timer time-out occurs without receiving the acknowledgment.

The node MAC comprises a transmission MAC (TX MAC), a reception MAC (RX MAC), a security engine (e.g. AES), a forward error correction (FEC) engine, a DBA-Report engine and SERDES IP. The TX MAC is responsible for mapping/packing GEMs into a burst structure (e.g. Burst-PHY-Frame structure) and transmitting the burst messages to root ports **230** and/or nodes **204**, **208**, **234** during the burst window for the node granted by the dynamic burst allocation engine of the root port **230** for that node. The RX MAC is responsible for receiving and terminating broadcast messages (e.g. Broadcast-PHY-Frames) from root ports **230** and/or nodes **204**, **208**, **234**, extracting GEMs from the broadcast message format, parsing and accepting GEMs addressed to it (e.g. addressed to one of its ports **99**) based on the node's SLA Profile setting, and subsequently outputting the data to the encapsulation/decapsulation engine.

The DBA report engine reports total data packet and message in queues (e.g. EPOCH Queues) to the HDBA engine of the associated root port **230** through the burst reporting (as described above). Additionally, the DBA report engine accepts GEM-Grant messages from the HDBA of the associated root port **230** and/or the DBA of the associated gate **202**, and prepares the node transmission MAC to build a burst message (e.g. Burst-PHY-Frame) with the GEMs stored in the queues (e.g. EPOCH Queues).

The node activation processor is responsible for performing and completing the node **204**, **208**, **234** activation process and procedures between nodes **204**, **206**, **234** and root ports **230**. The security engine is able to be an AES-128/256 encryption and decryption functional block used for both the reception and transmission MACs. Alternatively, other encryption is able to be used. The FEC engine is used for controlling errors in data transmission over unreliable or noisy communication channels. In some embodiments, the FEC engine uses Reed Solomon FEC coding schemes of RS(255,216) and RS(225,232) for 10G and 2.5G data rates, respectively. The burst-mode SERDES uses fast clock and data recovery (CDR) locking mode to ensure fast fiber-cut, fast fail-over and protection switch recovery.

Finally, after activation processing (e.g. after the registration process is complete), the nodes **204**, **206**, **234** are able to broadcast a DDS message to entire bus **104** to inform and notice the root ports **230**, switch **228**, gates **202** and/or other nodes **204**, **206**, **234** that a new device has joined and registered to bus **104** at that node **204**, **208**, **234**. Further, the nodes **204**, **206**, **234** are able to listen to DDS messages from the switch **228** and other new the nodes' **204**, **206**, **234** declaration of joining the bus **104** and update their global SLA profile database and settings based on the DDS messages.

Gates

The gates **202** are able to comprise a node MAC (with multiple Virtual node State-Machines and buffering), an adaptive domain bridge (ADB), a root port MAC (with built-in gate DBA functionality/gate DBA), a gate SLA profile database and a burst-mode SERDES. The node MAC comprises one or more of a transmission MAC, reception MAC, security engine (e.g. AES), FEC engine, DBA report functional module, SERDES functional module and/or multiple sets (e.g. one for each node within the subnetwork **210**) of virtual node processors, virtual node profiles and settings, and related MIB counters and reporting logics. The transmission MAC receives GEMs from the gate ADB and maps and packs then into their associated virtual node burst structure (e.g. Burst-PHY-Frame structure) based on the gate's virtual node SLA Profile database settings. Further, the transmission MAC aggregates multiple virtual node burst structures (e.g. Burst-PHY-Frames) into one gate burst structure (e.g. GATE/Turbo Burst-PHY-Frame) and transmits burst message to the root port **230** through the network **206** based on the granted burst window for those nodes **208** received from the HDBA of the root port **230**. The node reception MAC receives broadcast messages (e.g. Broadcast-PHY-Frames) from the root port **230**, extracts GEMs from the messages, parses the headers of the GEMs, determines which messages are for nodes **208** within the subnetwork **210** of the gate **202** based on the GEM-Headers and virtual nodes SLA Profile database settings and outputs those messages to the ADB.

The ADB performs a bridging function between the node MAC and the root MAC of the gates **202**. Specifically, in the broadcast direction (from the root port **230** to the nodes **208**), the ADB receives GEMs from node reception MAC and performs a GEM header lookup, checking and filtering function based on the gate virtual node profile database in order to accept GEMs belonging to nodes **208** of the gate's **202** subnetwork **210**. The ADB is then able to output those GEMs to root port transmission MAC of the gate **202**. In the burst direction (from the nodes **208** to the root port **230**), the ADB receives GEMs from root reception MAC, stores them in their associated virtual node buffer memory, and output them to the virtual node transmission MAC when their burst window start time arrives.

The root port MAC of the gates **202** comprise a transmission MAC, a reception MAC, a security engine (e.g. AES), an FEC engine, a gate DBA and burst mode SERDES modules. The transmission MAC is responsible for accepting GEMs from ADB, mapping and packing the GEMs into a broadcast format (e.g. Broadcast-PHY-Frame structure), and outputting the broadcast formatted frames to burst-mode SERDES. The reception MAC is responsible for receiving burst messages (e.g. Burst-PHY-Frames) from burst-mode SERDES (e.g. a far end node), extracting the GEMs from the messages, parsing and accept only GEMs targeted for nodes **208** within the gate's **202** subnetwork **210** (as indicated based on the parsed GEM headers and the SLA Profile

settings), and then outputting the GEMs to the ADB of the gate **202**. The DBA of the gate **202** is an extension HDBA of the root ports **230**. The gate DBA grants and allocates node burst windows based on the gate DBA SLA profile settings (which is a subset of the root HDBA). The gate SLA profile database includes a list of node identifiers belonging to this gate **202** (e.g. located within the subnetwork **210** of the gate **202**), an SLA profile table of node identifiers for a gate DBA function and GEM forwarding information. The burst mode SERDES accepts broadcast messages (e.g. Broadcast-PHY-Frames) from the root transmission MAC and transmits to nodes **208** in the subnetwork **210** in the broadcast transmission direction. In reception direction, the burst-mode SERDES receives burst messages (e.g. Burst-PHY-Frames) from nodes **208** through the subnetwork **210** and outputs them to the root reception MAC for message/frame termination and GEM extraction.

The main function of gates **202** is to extend the central transmission network **206** of one of the root ports **230** by bridging to one or more subnetworks **210** (and the nodes **208** therein) through adaptive bridging. In particular, the gates **202** are able to burst messages from the nodes **208** and/or other gates **202'** within their subnetwork **210** to the root port **230** of the network **206** they are in as if the burst traffic were coming from nodes within the central transmission network **206**. Similarly, the gates **202** are able to broadcast messages received from other nodes **204**, **208**, **234**, the switch **228** and/or root port **230** to the nodes **208** and/or other gates **202'** within their subnetwork **210** they are in as if the nodes **208** and/or other gates **202'** were within the central transmission network **206**. As a result, the gates **202** are able to extend the central transmission networks **206** to additional nodes **208** and/or different types of subnetworks **210** while maintaining a burst/broadcast communication method within the central transmission networks **206**.

In more detail, in the transmission Burst direction (e.g. from the nodes/gates to the root ports/switch/core), the burst window granting mechanism from node **208** to gate **202** to root **230** is able to comprise the following steps. First, the DBA of the gate **202** is a subset of the HDBA of the root port **230** (of the network **206** that the gate **202** is a part of) and therefore is transparent to the root port **230** and nodes **208**. Second, when the gate **202** receives a burst window grant message (e.g. GEM-Grant message) broadcast from its root port **230**, it uses the message header (e.g. GEM-Header) to lookup gate SLA profile database for GEM forwarding information. In other words, it uses the header data to determine if the grant message is for any of the nodes **208** within its subnetwork **210** as indicated in the gate SLA profile database. If the grant message is not for any of the nodes **208** of its subnetwork **210** the gate **202** drops the grant message, otherwise, the gate stores the message in its virtual node database, updates the database and broadcasts a new window grant message (e.g. GEM-Grant message) to all the nodes/gates in its subnetwork **210** that is directed to the node **208** to which the original grant message was directed. In response, the node **208** provides a burst message to the gate **202** and the gate **202** formats and/or otherwise prepares the message for bursting to the root port **230** at the burst window start indicated in the received window grant message for that node **208**.

Third, in order to get best throughput bandwidth, high burst bandwidth efficiency and/or low transmission latency, gate **202** is able to adjust the grant window indicated in this new grant message to be at least a predetermined amount of time before the grant window indicated in the original grant message. In particular, this amount of time provides the gate

202 time to receive and format the burst data from the node 208 before bursting the data from the gate 202 to the root port 230 at the time indicated by the original window grant message. Indeed, by doing this for multiple nodes 208 at the same time, the gate 202 is able to aggregate the messages from multiple different nodes (e.g. multiple Burst-PHY-frames) into a single bigger burst message (e.g. GATE Burst-PHY-Frame).

Fourth, due to the protocols between gate traffic DBA reporting and the root port 230 window granting, root port 230 and gates 202 are able to maintain a group-membership list table and be aware of the virtual nodes 208 that each of the gates 230 below to as a group. Thus, when a node 208 issues a report message (e.g. GEM-Report) to HDBA of the root port 230, the gate 202 is able to intercept the report message, modify it to include the GEMs data temporarily stored in gate's 202 virtual node buffer memory if there is any, and issue a new report message to HDBA of the root port 230. In other words, the gates 202 are able to combine reporting messages from the nodes in their subnetworks 210 in order to make the reporting more efficient.

Additionally, when HDBA of the root ports 230 are issuing a grant message (e.g. GEM-Grant message) to nodes 208 that are in a subnetwork 210, because they are aware of all of the nodes 208 that are in that subnetwork 210 (e.g. via the virtual node database), the HDBA of the root ports 230 are able to ensure that the grant windows for nodes 208 that belong to the same gate 202 and/or subnetwork 210 are in sequence/continuous order so that the gate 202 is able to combine and/or burst all the virtual node's burst messages (e.g. burst-PHY-Frames) without each having a preamble except for the first one. This provides the benefit of reducing preamble overhead and increasing the burst bandwidth efficiency (especially for small bursts of GEM-Control messages).

In other words, for the data-path, the gates 202 receive burst messages (e.g. burst-PHY-frames) from burst-mode SERDES and far-end nodes 208, extracts the GEMs from the messages in the root reception MAC of the gate 202, stores the GEMs in their associated virtual NODE buffer memory and waits for the virtual node burst window grant to come in from the root port 230 for those virtual nodes 208. Then, the gates 202 are able to map and pack the stored GEMs for that node 208 and other nodes 208 back into the burst message format thereby aggregating multiple burst messages together into one bigger burst message in the node transmission MAC of the gates 202. Finally, the gates 202 are able to transmit this bigger burst message to the SERDES and to the root port 230 through the network 206 based on granted burst windows (e.g. the multiple consecutive virtual node burst windows of that gate 202).

Now looking to the broadcast direction (e.g. from the root ports/switch/core to the nodes/gates), again the gates 202 are able to extend central networks 206 to the subnetworks 210 while being transparent to both the root port 230 for their network 206 and the nodes 208 in their subnetwork 210. In order to effectuate this, the gates 202 are able to act like virtual nodes and receive broadcast messages (e.g. Broadcast-PHY-Frames) from the root ports 230, extract the GEMs from the messages, drop any GEMs that are not directed to one of the nodes 208/gates 202' in their subnetwork 210 (e.g. as indicated by the message headers and the gate SLA profile database). Otherwise, the gates 202 are able to use store-N-forward and/or cut-through schemes to pack and map the GEMs back into the root port broadcast message structure (e.g. Broadcast-PHY-Frame structure) in

a root transmission MAC of the gate 202 and broadcast the new broadcast message to all the nodes 208 and/or gates 202' in its subnetwork 210.

Data Transmission Operation

In operation, the bus 104 operates using a burst/broadcast communication scheme wherein all data messages from the nodes 204, 208, 234 (and gates 202) are funneled to the core 200 using a burst transmission method where transmission windows that are dynamically adjustable in size (by the core 200) are granted to the nodes 204, 208, 234 such that they (or a gate 202 on their behalf) are able transmit their data messages as a "burst" within the granted window. If the transmitting node is in a subnetwork 210, the gate 202 (acting as a root port of that network 210) receives the bursted message from the node 208 through the subnetwork 210 and then subsequently bursts the message through the central network 206 to the core 200 (as if the node 208 was a part of the central network 206). In doing this burst communication, the gate 202 is able to aggregate burst messages from multiple nodes 208 within the subnetwork 210 thereby increasing efficiency and reducing the effects of the subnetwork's 210 possibly increased latency relative to the central network 206. Indeed, this is able to be repeated for gates 202' within subnetworks 210 that provide a gate way to sub-subnetworks 210' and so on to support any number of "chained/gated" networks. Further, the gate 202 is able to be transparent to the core 200 and nodes 208 in this process such that messages do not need to be addressed to the gate 202.

The core 200 receives these messages (from one or more root ports 230 coupling the core 200 to each of the central networks 206), processes them (including modifying and/or determining their target destination), and broadcasts them (and any messages originating in the core 200) onto whichever central transmission network 206 the target node 204, 208, 234 (or gate 202 representing the target node 208) for that message is located. Like the burst communication above, if the target node 208 is within the subnetwork 210, the gate 202 bridging to that subnetwork 210 is able to receive/intercept the message from the core and rebroadcast the message to all of the node 208 (and/or gates 202') on the subnetwork 210. Any broadcast messages for target nodes 204 not on the subnetwork 210 (or a subnetwork thereof) are able to be discarded by the gate 202 in order to increase efficiency. Again, this process is transparent and able to be repeated by gates 202' within subnetworks 210 and so on for any number of chained networks to broadcast the messages through the networks. As a result, all the nodes 204, 208, 234 (and gates 202) on each of the networks 206 (and subnetworks 210 coupled thereto) receive all of the messages from the core 200 broadcast on that network 206 and merely need to look for which messages are directed to them while discarding the others.

In more detail, when the nodes 204, 208, 234 receive data from one or more external devices 102 through one or more of their IO ports 99, they store the data in a GEM-ID queue buffer memory and burst a report message (e.g. GEM-Report) to the root port 230 of the central network 206 that they are in (either directly or through one or more gates 202 if they are in a subnetwork 210 of the central network 206) and wait to be granted a burst window to transmit the input data. As described above, the gates 202 are able to collect and aggregate report messages from a plurality of the nodes 208 (and or gates 202') in their subnetwork 210 into a single bigger report message that the gate 202 is able to more efficiently burst to the root port 230 during the burst window for those ports 208.

At the same time, the nodes **204**, **208**, **234** are able to encapsulate the input data into the GEM format (fragmenting GEMs exceeding a predefined size into smaller GEMs), encrypt GEMs with the security key of the node **204**, **208**, **234**, update the HARQ table, map and pack the GEMs into a burst format (e.g. Burst-PHY-Frame format) and perform encoding (e.g. FEC RS(255,216) encoding). Subsequently, upon grant and arrival of the burst window for each of the nodes, the nodes burst the GEMs including the input data to the associated root port **230**.

The HDBA of the root ports **230** receive all of the report messages from the nodes **204**, **208** (and/or gates **202**) and perform a DBA analysis for each of the nodes **204**, **208** based on the SLA profile database, latency sensitive level, traffic congestion feedback, committed information rate (CIR)/peak information rate (PIR) feedback and/or other factors to determine grant window burst size and start-time for each of the nodes **204**, **208**. Once the granted burst windows have been determined for one or more of the nodes **204**, **208**, the root port **230** broadcasts the windows to each of the nodes in a broadcast grant message (e.g. GEM-Grant) to all of the nodes **204**, **208** in the associated central network **206** and/or any subnetworks **210** (via the gates **202**). As described above, the broadcast messages from the root ports **230** are the same size, whereas the burst windows from the nodes **204**, **208** to the root ports **230** are able to vary in size as dynamically assigned by the HDBA.

The gates **202**, upon receipt of the broadcast grant messages targeting nodes **208** within their subnetwork **210** (or a subnetwork thereof), broadcast new grant messages to all of the nodes **208** with the subnetwork **210**. Specifically, these new grant messages are able to specifying burst windows that occur before the time indicated by the original/root port grant window. This is to ensure the gates **202** to receive (e.g. be "burst") the input data/GEMs from the port **208** before the original/root port grant window, thereby giving the gates **202** time to aggregate the data/GEMs from multiple nodes **208** and/or ports **99** into single larger messages for burst to the root port **230** when the original/root port grant window arrives. As a result, the gates **202** are able to make up for inefficiencies and/or slower aspects of the subnetworks **210** such that they do not slow down the efficiency of the central transmission networks **206**.

Upon receipt of the burst messages including the GEMs (including the input data from the external devices **102**), the root ports **230** are able to perform decoding (e.g. FEC RS(255,216) decoding) and error correction on the burst messages to decode and correct any transmission errors. The root ports **230** are then able to extract the GEMs from the burst messages (e.g. the transmission frame format), decrypt the extracted GEMs (e.g. with AES-128/256 and a source-node security key), bypass the GEM fragmentation block and pass GEMs to the switch **228**. For each of the GEMs, the switch **228** is then able to perform a GEM-Header lookup, parse and classify Ethernet L2/L3 address and headers, process GEM forward flow-chart and determine GEM forwarding destination info, store the GEM in (cut-through) buffer-memory, and output the GEM to HARQ and to the destination root port **230** (e.g. the root port **230** whose network **206** or subnetwork **210** thereof includes the destination node **204**, **208**) based on the SLA database QoS output scheduler.

The root ports **230** receive the GEMs, perform GEM encryption (e.g. AES-128/256 encryption) with target node's (or broadcast GEM's) security key, pack and map GEMs into a broadcast message structure (e.g. Broadcast-Frame structure), encode the message (e.g. FEC RS(255,

216) encoding), and finally broadcast the broadcast messages to all of the nodes **204**, **208** in that root port's network **206** and subnetworks **210** thereof. If the node **208** is within a subnetwork **210**, the gate **202** to that subnetwork receives the broadcast message and broadcasts the message to all of the nodes **208** within the subnetwork **210**. In some embodiments, the gates **202** filter out any broadcast messages that are not targeted to nodes **208** within its subnetwork **210** (or a subnetwork thereof) and only broadcasts the broadcast messages that do target one of those nodes **208**. Alternatively, the gates **202** are able to rebroadcast all of the broadcast messages to the nodes **208** within its subnetwork **210** without determining if the messages relate to one of those nodes **208**.

All the nodes **204**, **208** monitor the received broadcast messages, processing those intended for the node **204**, **208** and discarding the others. Specifically, for the non-discarded messages, the nodes **204**, **208** decode and error correct the messages (e.g. FEC RS(255,216) decoding), extract the GEMs from the broadcast message format (e.g. BC-PHY-Frame), decrypt the extracted GEM (e.g. with AES-128/256 and the destination node's security key), decapsulate the data from the GEM format back to original IO-Port data format, and output the data through the designated IO port **99** to the external device **102**. As a result, the bus **104** and system **100** provides the benefit of being able to combine multiple different networks having varying input data, varying processing speeds and data constraints while still maintaining low latency and high throughput needed for machine automation systems. This is a unique intranet system architecture and specially defined and optimized for such machine automation applications.

FIG. 4 illustrates a block diagram of an exemplary computing device **400** configured to implement the system **100** according to some embodiments. In addition to the features described above, the external devices **102** are able to include some or all of the features of the device **400** described below. In general, a hardware structure suitable for implementing the computing device **400** includes a network interface **402**, a memory **404**, a processor **406**, I/O device(s) **408** (e.g. reader), a bus **410** and a storage device **412**. Alternatively, one or more of the illustrated components are able to be removed or substituted for other components well known in the art. The choice of processor is not critical as long as a suitable processor with sufficient speed is chosen. The memory **404** is able to be any conventional computer memory known in the art. The storage device **412** is able to include a hard drive, CDROM, CDRW, DVD, DVDRW, flash memory card or any other storage device. The computing device **400** is able to include one or more network interfaces **402**. An example of a network interface includes a network card connected to an Ethernet or other type of LAN. The I/O device(s) **408** are able to include one or more of the following: keyboard, mouse, monitor, display, printer, modem, touchscreen, button interface and other devices. The operating software/applications **430** or function(s)/module(s) thereof are likely to be stored in the storage device **412** and memory **404** and processed as applications are typically processed. More or fewer components shown in FIG. 4 are able to be included in the computing device **400**. In some embodiments, machine automation system hardware **420** is included. Although the computing device **400** in FIG. 4 includes applications **430** and hardware **420** for the system **100**, the system **100** is able to be implemented on a computing device in hardware, firmware, software or any combination thereof.

25

FIG. 5 illustrates a method of operating a machine automation system 100 including an intelligent controller and sensor intranet bus 104 according to some embodiments. As shown in FIG. 5, the nodes 204, 208 receive input data from a plurality of the external devices 102 via one or more ports 99 of the bus 104 at the step 502. The nodes 204, 208 burst the input data as burst messages to the core 200 in variable size burst windows at the step 504. In some embodiments, for each of the nodes 204, 208, the HDBA of the root ports 230 dynamically adjusts the burst window start time and size of the variable burst window and assign the adjusted window the corresponding node 204, 208 in a broadcast grant window message based on data traffic parameters reported from that one of the nodes 204, 208. In some embodiments, the gates 202 aggregate two or more burst messages including input data and/or traffic reporting received from the nodes 208 into single larger burst reporting or input data message for bursting to the core 200. In such embodiments, the gates 202 are able to omit portions of the received burst messages (e.g. preambles) in order to enhance the efficiency of the bus 104. In some embodiments, upon receiving the broadcast window grant messages from the core 200, the gates 202 adjust the original time of the burst window to an earlier time and broadcast the adjusted broadcast window grant messages to the nodes 208. As a result, the nodes 208 burst their data to the gates 202 before the window granted by the root port 230 such that the gates 202 are able to combine multiple burst messages together and burst them in the later original time window. The core 200 processes and broadcasts the input data as broadcast messages to each of the nodes 204, 208 within the central network 206 and subnetworks 210 required to reach the target node 204, 208 of the message at the step 506. The target node 204, 208 converts data of the broadcast message into a format accepted by the device 102 coupled to the node 204, 208 and outputs the data to the device 102 at the step 508. As a result, the method provides the advantage of enabling the bus 104 to maintain high speed despite the use of lower speed network mediums.

The system 100 and machine automation controller and sensor bus 104 implementing a dynamic burst to broadcast transmission network has numerous advantages. Specifically, it provides the benefit of a simple cable system and connection; the elimination of significant EMI impacts due to the user of optical fiber cable; guaranteed low latency for node-to-node communication; high throughput bandwidth from node to node transmission (10, 25, 100 or greater Gbps); can extend and reach up to 20 km from node to node devices; low power consumption due to passive-optical-network architecture; industry grade QoS without traffic congestion due to centralized DBA scheduling mechanism; built-in HARQ mechanism to guarantee node-to-node and GEM transmission successful; and one unified software image for full intranet system including all gate, node and root ports enabling simplified software architecture, shorter product development cycle, and easier system level debug, monitoring and trouble shooting remotely.

The present invention has been described in terms of specific embodiments incorporating details to facilitate the understanding of principles of construction and operation of the invention. Such reference herein to specific embodiments and details thereof is not intended to limit the scope of the claims appended hereto. It will be readily apparent to one skilled in the art that other various modifications may be made in the embodiment chosen for illustration without departing from the spirit and scope of the invention as defined by the claims. For example, although as described

26

herein the bus is described as operating within a machine automation system, it is understood that the bus is able to operate with other types of systems and devices thereof for facilitating the communication between the devices.

What is claimed is:

1. A machine automation system for controlling and operating an automated machine, the system comprising:
 - a controller and sensor bus including plurality of input/output ports; and
 - a plurality of external machine automation devices operably coupled together via the ports of the bus, wherein the bus comprises a central processing core and a multi-medium transmission intranet comprising:
 - one or more central transmission networks directly coupled to the core and including a plurality of nodes and one or more gates; and
 - a plurality of subnetworks each coupled to a different one of the gates of one of the central transmission networks, the subnetworks including a plurality of subnodes, wherein each of the nodes and the subnodes:
 - is coupled with one or more of the devices via one or more of the ports;
 - receives messages from the one or more of the devices coupled to the one or more of the ports;
 - encapsulates the messages into a generic encapsulation mode (GEM) format for transmission to the central processing core; and
 - decapsulates the messages as received from the central processing core from the GEM format to an original format of the input data as received from one of the devices;
 - wherein a header of the GEM format comprises a source/destination field that identifies one of the ports as a source of the message or one or more of the nodes and the subnodes as the destination of the message and a GEM packet identifier field that identifies one or more of the ports targeted by the message, and further wherein values of the source/destination field are selected from a first set of epoch identifier values when identifying the one of the ports as a source of the message and are selected from a second set of node identifier values when identifying the one or more of the nodes and the subnodes as the destination of the message.
2. The system of claim 1, wherein the values of the GEM packet identifier field are selected from a third set of GEM identifier values and each of the node identifier values map to one or more of the epoch identifier values which each map to one or more of the GEM identifier values.
3. The system of claim 2, wherein the header of the GEM format comprises a GEM packet type field that indicates the original format and header type of the message that is encapsulated within the GEM format.
4. The system of claim 1, wherein a header of the GEM format includes a source identifier field that indicates a source of the message and a report message type field that indicates whether reported data within the message does not relate to the source of the message indicated in the source identifier field.
5. The system of claim 1, wherein a header of the GEM format includes a start-time field that indicates at what time a granted bandwidth window starts and a grant-size field that indicates a size of the granted bandwidth window.

6. The system of claim 5, wherein the header of the GEM format includes a grant command field that indicates one or more types of messages that are permitted during the granted bandwidth window.

7. A machine automation system for controlling and operating an automated machine, the system comprising:

a controller and sensor bus including plurality of input/output ports; and

a plurality of external machine automation devices operably coupled together via the ports of the bus, wherein the bus comprises a central processing core and a multi-medium transmission intranet comprising:

one or more central transmission networks directly coupled to the core and including a plurality of nodes and one or more gates; and

a plurality of subnetworks each coupled to a different one of the gates of one of the central transmission networks, the subnetworks including a plurality of subnodes, wherein each of the nodes and the subnodes:

is coupled with one or more of the devices via one or more of the ports;

receives messages from the one or more of the devices coupled to the one or more of the ports;

encapsulates the messages into a generic encapsulation mode (GEM) format for transmission to the central processing core;

decapsulates the messages as received from the central processing core from the GEM format to an original format of the input data as received from one of the devices;

puts one or more of the messages into a burst physical layer frame format; and

transmits the messages to the central processing core by bursting the burst physical layer frame including the one or more of the messages to the central processing core, wherein the burst physical frame format includes a separate end of burst delimiter field for each one of the one or more messages that indicates an end of the one of the one or more messages within the burst physical layer frame.

8. A machine automation system for controlling and operating an automated machine, the system comprising:

a controller and sensor bus including plurality of input/output ports; and

a plurality of external machine automation devices operably coupled together via the ports of the bus, wherein the bus comprises a central processing core and a multi-medium transmission intranet comprising:

one or more central transmission networks directly coupled to the core and including a plurality of nodes and one or more gates; and

a plurality of subnetworks each coupled to a different one of the gates of one of the central transmission networks, the subnetworks including a plurality of subnodes, wherein each of the nodes and the subnodes:

is coupled with one or more of the devices via one or more of the ports;

receives messages from the one or more of the devices coupled to the one or more of the ports;

encapsulates the messages into a generic encapsulation mode (GEM) format for transmission to the central processing core; and

decapsulates the messages as received from the central processing core from the GEM format to an original format of the input data as received from one of the devices;

5 wherein each of the gates aggregates the messages in the GEM format from a plurality of the subnodes into a single larger message in a burst physical layer frame format, and further wherein each of the gates omit preambles of the messages from the plurality of the subnodes from the single larger message in the burst physical layer frame format.

9. The system of claim 1, wherein the devices comprise one or more of the group consisting of an ultrasonic sensor, a light detection and ranging sensor, an infrared sensor, a camera, a motor and a microcontroller.

10. The system of claim 1, wherein the automated machine is one of the groups consisting of a robot and a self-driving vehicle.

11. A controller and sensor bus, the bus comprising:

a plurality of input/output ports for coupling with a plurality of external machine automation devices of a machine automation system;

a central processing core; and

a multi-medium transmission intranet comprising:

one or more central transmission networks directly coupled to the core and including a plurality of nodes and one or more gates; and

a plurality of subnetworks each coupled to a different one of the gates of one of the central transmission networks, the subnetworks including a plurality of subnodes, wherein each of the nodes and the subnodes:

is coupled with one or more of the devices via one or more of the ports;

receives messages from the one or more of the devices coupled to the one or more of the ports;

encapsulates the messages into a generic encapsulation mode (GEM) format for transmission to the central processing core; and

decapsulates the messages as received from the central processing core from the GEM format to an original format of the input data as received from one of the devices;

wherein a header of the GEM format comprises a source/destination field that identifies one of the ports as a source of the message or one or more of the nodes and the subnodes as the destination of the message and a GEM packet identifier field that identifies one or more of the ports targeted by the message, and further wherein values of the source/destination field are selected from a first set of epoch identifier values when identifying the one of the ports as a source of the message and are selected from a second set of node identifier values when identifying the one or more of the nodes and the subnodes as the destination of the message.

12. The bus of claim 11, wherein the values of the GEM packet identifier field are selected from a third set of GEM identifier values and each of the node identifier values map to one or more of the epoch identifier values which each map to one or more of the GEM identifier values.

13. The bus of claim 12, wherein the header of the GEM format comprises a GEM packet type field that indicates the original format and header type of the message that is encapsulated within the GEM format.

14. The bus of claim 11, wherein a header of the GEM format includes a source identifier field that indicates a source of the message and a report message type field that

indicates whether reported data within the message does not relate to the source of the message indicated in the source identifier field.

15. The bus of claim 11, wherein a header of the GEM format includes a start-time field that indicates at what time a granted bandwidth window starts and a grant-size field that indicates a size of the granted bandwidth window.

16. The bus of claim 15, wherein the header of the GEM format includes a grant command field that indicates one or more types of messages that are permitted during the granted bandwidth window.

17. A controller and sensor bus, the bus comprising:
a plurality of input/output ports for coupling with a plurality of external machine automation devices of a machine automation system;
a central processing core; and
a multi-medium transmission intranet comprising:

one or more central transmission networks directly coupled to the core and including a plurality of nodes and one or more gates; and

a plurality of subnetworks each coupled to a different one of the gates of one of the central transmission networks, the subnetworks including a plurality of subnodes, wherein each of the nodes and the subnodes:

is coupled with one or more of the devices via one or more of the ports;

receives messages from the one or more of the devices coupled to the one or more of the ports;

encapsulates the messages into a generic encapsulation mode (GEM) format for transmission to the central processing core;

decapsulates the messages as received from the central processing core from the GEM format to an original format of the input data as received from one of the devices;

puts one or more of the messages into a burst physical layer frame format; and

transmits the messages to the central processing core by bursting the burst physical layer frame including the one or more of the messages to the central processing core,

wherein the burst physical frame format includes a separate end of burst delimiter field for each one of the one or more messages that indicates an end of the one of the one or more messages within the burst physical layer frame.

18. A controller and sensor bus, the bus comprising:
a plurality of input/output ports for coupling with a plurality of external machine automation devices of a machine automation system;
a central processing core; and

a multi-medium transmission intranet comprising:
one or more central transmission networks directly coupled to the core and including a plurality of nodes and one or more gates; and

a plurality of subnetworks each coupled to a different one of the gates of one of the central transmission networks, the subnetworks including a plurality of subnodes, wherein each of the nodes and the subnodes:

is coupled with one or more of the devices via one or more of the ports;

receives messages from the one or more of the devices coupled to the one or more of the ports;

encapsulates the messages into a generic encapsulation mode (GEM) format for transmission to the central processing core; and

decapsulates the messages as received from the central processing core from the GEM format to an original format of the input data as received from one of the devices;

wherein each of the gates aggregates the messages in the GEM format from a plurality of the subnodes into a single larger message in a burst physical layer frame format, and further wherein each of the gates omit preambles of the messages from the plurality of the subnodes from the single larger message in the burst physical layer frame format.

19. The bus of claim 11, wherein the devices comprise one or more of the group consisting of an ultrasonic sensor, a light detection and ranging sensor, an infrared sensor, a camera, a motor and a microcontroller.

20. The bus of claim 11, wherein the automated machine is one of the groups consisting of a robot and a self-driving vehicle.

21. A method of operating a controller and sensor bus including a plurality of input/output ports for coupling with a plurality of external machine automation devices of a machine automation system, a central processing core and a multi-medium transmission intranet including one or more central transmission networks directly coupled to the core and including a plurality of nodes and one or more gates and a plurality of subnetworks each coupled to a different one of the gates of one of the central transmission networks, the subnetworks including a plurality of subnodes, the method comprising:

one or more of the nodes and the subnodes:

receiving messages from the one or more of the devices coupled to the one or more of the ports associated with the one or more of the nodes and the subnodes; encapsulating the messages into a generic encapsulation mode (GEM) format for transmission to the central processing core; and

decapsulating the messages as received from the central processing core from the GEM format to an original format of the input data as received from one of the devices;

wherein a header of the GEM format comprises a source/destination field that identifies one of the ports as a source of the message or one or more of the nodes and the subnodes as the destination of the message and a GEM packet identifier field that identifies one or more of the ports targeted by the message, and further wherein values of the source/destination field are selected from a first set of epoch identifier values when identifying the one of the ports as a source of the message and are selected from a second set of node identifier values when identifying the one or more of the nodes and the subnodes as the destination of the message.

22. The method of claim 21, wherein the values of the GEM packet identifier field are selected from a third set of GEM identifier values and each of the node identifier values map to one or more of the epoch identifier values which each map to one or more of the GEM identifier values.

23. The method of claim 22, wherein the header of the GEM format comprises a GEM packet type field that indicates the original format and header type of the message that is encapsulated within the GEM format.

24. The method of claim 21, wherein a header of the GEM format includes a source identifier field that indicates a

31

source of the message and a report message type field that indicates whether reported data within the message does not relate to the source of the message indicated in the source identifier field.

25. The method of claim 21, wherein a header of the GEM 5 format includes a start-time field that indicates at what time a granted bandwidth window starts and a grant-size field that indicates a size of the granted bandwidth window.

26. The method of claim 25, wherein the header of the GEM 10 format includes a grant command field that indicates one or more types of messages that are permitted during the granted bandwidth window.

27. A method of operating a controller and sensor bus including a plurality of input/output ports for coupling with a plurality of external machine automation devices of a 15 machine automation system, a central processing core and a multi-medium transmission intranet including one or more central transmission networks directly coupled to the core and including a plurality of nodes and one or more gates and a plurality of subnetworks each coupled to a different one of 20 the gates of one of the central transmission networks, the subnetworks including a plurality of subnodes, the method comprising:

one or more of the nodes and the subnodes:

receiving messages from the one or more of the devices 25 coupled to the one or more of the ports associated with the one or more of the nodes and the subnodes;

encapsulating the messages into a generic encapsulation mode (GEM) format for transmission to the 30 central processing core;

decapsulating the messages as received from the central processing core from the GEM format to an original format of the input data as received from one of the devices;

putting one or more of the messages into a burst 35 physical layer frame format with each of the nodes and the subnodes; and

transmitting the messages to the central processing core by bursting the burst physical layer frame including 40 the one or more of the messages to the central processing core with each of the nodes and the subnodes, wherein the burst physical frame format

32

includes a separate end of burst delimiter field for each one of the one or more messages that indicates an end of the one of the one or more messages within the burst physical layer frame.

28. A method of operating a controller and sensor bus including a plurality of input/output ports for coupling with a plurality of external machine automation devices of a machine automation system, a central processing core and a multi-medium transmission intranet including one or more 5 central transmission networks directly coupled to the core and including a plurality of nodes and one or more gates and a plurality of subnetworks each coupled to a different one of the gates of one of the central transmission networks, the subnetworks including a plurality of subnodes, the method comprising:

one or more of the nodes and the subnodes:

receiving messages from the one or more of the devices 10 coupled to the one or more of the ports associated with the one or more of the nodes and the subnodes;

encapsulating the messages into a generic encapsulation mode (GEM) format for transmission to the central processing core;

decapsulating the messages as received from the central processing core from the GEM format to an original format of the input data as received from one of the devices;

aggregating the messages in the GEM format from a plurality of the subnodes into a single larger message in a burst physical layer frame format with each of the gates; and

omitting preambles of the messages from the plurality of the subnodes from the single larger message in the burst physical layer frame format with each of the gates.

29. The method of claim 21, wherein the devices comprise one or more of the group consisting of an ultrasonic sensor, a light detection and ranging sensor, an infrared sensor, a camera, a motor and a microcontroller.

30. The method of claim 21, wherein the automated machine is one of the groups consisting of a robot and a self-driving vehicle.

* * * * *