

US011097071B1

(12) **United States Patent**
Hunt et al.

(10) **Patent No.:** **US 11,097,071 B1**
(45) **Date of Patent:** **Aug. 24, 2021**

(54) **TAMPER EVIDENT ASSEMBLY**

(71) Applicants: **Timothy Brandon Hunt**, Ft.
Lauderdale, FL (US); **Patrick Vitello**,
Pompano Beach, FL (US); **Robert**
Banik, Ft. Lauderdale, FL (US)

(72) Inventors: **Timothy Brandon Hunt**, Ft.
Lauderdale, FL (US); **Patrick Vitello**,
Pompano Beach, FL (US); **Robert**
Banik, Ft. Lauderdale, FL (US)

(73) Assignee: **INTERNATIONAL MEDICAL**
INDUSTRIES INC., Pompano Beach,
FL (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 641 days.

(21) Appl. No.: **15/842,328**

(22) Filed: **Dec. 14, 2017**

Related U.S. Application Data

(60) Provisional application No. 62/434,240, filed on Dec.
14, 2016, provisional application No. 62/434,221,
filed on Dec. 14, 2016.

(51) **Int. Cl.**
A61M 5/50 (2006.01)
B65B 7/28 (2006.01)
A61M 5/31 (2006.01)

(52) **U.S. Cl.**
CPC **A61M 5/5086** (2013.01); **A61M 2005/312**
(2013.01); **A61M 2005/3104** (2013.01); **B65B**
7/2835 (2013.01)

(58) **Field of Classification Search**

CPC **A61M 5/5086**; **A61M 5/50**; **A61M**
2005/3104; **A61M 2005/312**;

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

732,662 A 6/1903 Smith
1,678,991 A 7/1928 Marschalek
(Continued)

FOREIGN PATENT DOCUMENTS

EP 0148116 A 7/1985
GB 486367 6/1938

(Continued)


Primary Examiner — Jason E Flick

(74) *Attorney, Agent, or Firm* — Malloy and Malloy PL

(57) **ABSTRACT**

A tamper evident assembly for attachment to a medical connector including a tamper evident cap having an end cap and a tip cap movably and removably disposed in an operative position within the end cap. A retaining structure on the end cap and a retention structure on the tip cap are cooperatively structured to define an interruptive engagement and unidirectional passage of the retention structure over said retaining structure, when disposing the tip cap in the operative position. The interruptive engagement also defines an abutting engagement of said retaining structure with said retention structure, wherein the abutting engagement is preventative of passage of said retention structure over said retaining structure, concurrent to disposition of said tip cap out of said operative position. An included flow controller regulates fluid flow through a connector attached to the tamper evident cap and may establish a path of fluid flow with an attached conduit and the attached connector.

31 Claims, 10 Drawing Sheets



(58) **Field of Classification Search**

CPC .. A61M 2005/3117; A61M 2005/3118; A61M
39/20; A61M 2039/1061; B65B 7/2835

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,970,631 A	8/1934	Sherman	5,230,429 A	7/1993	Etheredge, III
2,477,598 A	8/1949	Hain	5,267,983 A	12/1993	Oilschlager et al.
2,739,590 A	3/1956	Yochem	5,292,308 A	3/1994	Ryan
2,823,674 A	2/1958	Yochem	5,293,993 A	3/1994	Yates, Jr. et al.
2,834,346 A	5/1958	Adams	5,295,599 A	3/1994	Smith
2,875,761 A	3/1959	Helmer et al.	5,312,367 A	5/1994	Nathan
2,888,015 A	5/1959	Hunt	5,312,368 A	5/1994	Haynes
2,952,255 A	9/1960	Hein, Jr.	5,328,466 A	7/1994	Denmark
3,122,280 A	2/1964	Goda	5,328,474 A	7/1994	Raines
3,245,567 A	4/1966	Knight	5,356,380 A	10/1994	Hoekwater et al.
3,323,798 A	6/1967	Miller	5,380,295 A	1/1995	Vacca
3,364,890 A	1/1968	Andersen	5,405,339 A	4/1995	Kohnen et al.
3,368,673 A	2/1968	Cowley	5,456,668 A	10/1995	Ogle, II
3,598,120 A	8/1971	Mass	5,458,580 A	10/1995	Hajishoreh
3,610,241 A	10/1971	LeMarie	5,468,224 A	11/1995	Souryal
3,700,215 A	10/1972	Hardman et al.	5,531,695 A	7/1996	Swisher
3,706,307 A	12/1972	Hasson	5,540,666 A	7/1996	Barta et al.
3,712,749 A	1/1973	Roberts	5,549,571 A	8/1996	Sak
3,747,751 A	7/1973	Miller et al.	5,558,648 A	9/1996	Shields
3,872,867 A	3/1975	Killinger	5,584,817 A	12/1996	van den Haak
3,904,033 A	9/1975	Haerr	5,588,239 A	12/1996	Anderson
3,905,375 A	9/1975	Toyama	5,624,402 A	4/1997	Imbert
3,937,211 A	2/1976	Merten	5,674,209 A	10/1997	Yarger
3,987,930 A	10/1976	Fuson	5,695,470 A	12/1997	Roussigne et al.
4,005,739 A	2/1977	Winchell	5,700,247 A	12/1997	Grimard et al.
4,043,334 A	8/1977	Brown et al.	5,702,374 A	12/1997	Johnson
4,046,145 A	9/1977	Choksi et al.	5,713,485 A	2/1998	Liff et al.
4,068,696 A	1/1978	Winchell	5,776,124 A	7/1998	Wald
4,216,585 A	8/1980	Hatter	5,785,691 A	7/1998	Vetter et al.
4,216,872 A	8/1980	Bean	5,797,885 A	8/1998	Rubin
4,244,366 A	1/1981	Raines	5,807,343 A	9/1998	Tucker et al.
4,252,122 A	2/1981	Halvorsen	D402,766 S	12/1998	Smith et al.
4,271,972 A	6/1981	Thor	5,883,806 A	3/1999	Meador et al.
4,286,591 A	9/1981	Raines	5,884,457 A	3/1999	Ortiz et al.
4,286,640 A	9/1981	Knox et al.	5,902,269 A	5/1999	Jentzen
4,313,539 A	2/1982	Raines	5,951,522 A	9/1999	Rosato et al.
4,369,781 A	1/1983	Gilson et al.	5,951,525 A	9/1999	Thorne et al.
4,420,085 A	12/1983	Wilson et al.	5,954,657 A	9/1999	Rados
4,430,077 A	2/1984	Mittleman et al.	5,957,166 A	9/1999	Safabash
4,457,445 A	7/1984	Hanks et al.	5,957,314 A	9/1999	Nishida et al.
4,482,071 A	11/1984	Ishiwatari	5,963,136 A	10/1999	O'Brien
D277,783 S	2/1985	Beck	5,989,227 A	11/1999	Vetter et al.
4,521,237 A	6/1985	Logothetis	5,993,437 A	11/1999	Raoz
4,530,697 A	7/1985	Kuhlemann et al.	6,000,548 A	12/1999	Tsals
4,571,242 A	2/1986	Klein et al.	D419,671 S	1/2000	Jansen
4,589,171 A	5/1986	McGill	6,021,824 A	2/2000	Larsen et al.
4,664,259 A	5/1987	Landis	6,027,482 A	2/2000	Imbert
4,667,837 A	5/1987	Vitello et al.	6,068,614 A	5/2000	Kimber et al.
4,676,530 A	6/1987	Nordgren et al.	D430,293 S	8/2000	Jansen
4,693,707 A	9/1987	Dye	D431,864 S	10/2000	Jansen
4,726,483 A	2/1988	Drozdz	6,126,640 A	10/2000	Tucker et al.
4,743,229 A	5/1988	Chu	6,190,364 B1	2/2001	Imbert
4,743,231 A	5/1988	Kay et al.	6,193,688 B1	2/2001	Balestracci et al.
4,760,847 A	8/1988	Vaillancourt	6,196,593 B1	3/2001	Petrack et al.
4,813,564 A	3/1989	Cooper et al.	6,196,998 B1	3/2001	Jansen et al.
4,832,695 A	5/1989	Rosenberg et al.	6,235,376 B1	5/2001	Miyazaki et al.
4,834,706 A	5/1989	Beck et al.	6,280,418 B1	8/2001	Reinhard et al.
4,842,592 A	6/1989	Caggiani et al.	6,287,671 B1	9/2001	Bright et al.
4,844,906 A	7/1989	Hermelin et al.	6,322,543 B1	11/2001	Singh et al.
4,906,231 A	3/1990	Young	6,338,200 B1	1/2002	Baxa et al.
4,919,285 A	4/1990	Roof et al.	6,375,640 B1	4/2002	Teraoka
4,936,445 A	6/1990	Grabenkort	6,394,983 B1	5/2002	Mayoral et al.
5,009,323 A	4/1991	Montgomery et al.	6,485,460 B2	11/2002	Eakins et al.
5,049,129 A	9/1991	Zdeb et al.	6,500,155 B2	12/2002	Sasso
5,057,093 A	10/1991	Clegg et al.	6,520,935 B1	2/2003	Jansen et al.
D323,392 S	1/1992	Byrne	6,540,697 B2	4/2003	Chen
5,085,332 A	2/1992	Gettig et al.	6,565,529 B1	5/2003	Kimber et al.
5,135,496 A	8/1992	Vetter et al.	6,581,792 B1	6/2003	Limanjaya
5,165,560 A	11/1992	Enniss, III et al.	6,585,691 B1	7/2003	Vitello
			6,592,251 B2	7/2003	Edwards et al.
			6,666,852 B2	12/2003	Niedospial, Jr.
			6,682,798 B1	1/2004	Kiraly
			6,726,652 B2	4/2004	Eakins et al.
			6,726,672 B1	4/2004	Hanley et al.
			6,755,220 B2	6/2004	Castellano et al.
			6,764,469 B2	7/2004	Broselow
			6,796,586 B2	9/2004	Werth
			6,821,268 B2	11/2004	Balestracci
			D501,549 S	2/2005	McAllister et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,921,383 B2	7/2005	Vitello	9,227,019 B2	1/2016	Swift et al.
6,935,560 B2	8/2005	Andreasson et al.	D750,228 S	2/2016	Strong et al.
6,942,643 B2	9/2005	Eakins et al.	9,272,099 B2	3/2016	Limaye et al.
7,055,273 B2	6/2006	Roshkoff	9,311,592 B1	4/2016	Vitello et al.
7,125,397 B2	10/2006	Woehr et al.	D756,777 S	5/2016	Berge et al.
7,141,286 B1	11/2006	Kessler et al.	9,336,669 B2	5/2016	Bowden et al.
7,175,081 B2	2/2007	Andreasson et al.	D759,486 S	6/2016	Ingram et al.
7,182,256 B2	2/2007	Andreasson et al.	D760,384 S	6/2016	Niunoya et al.
7,232,066 B2	6/2007	Andreasson et al.	D760,902 S	7/2016	Persson
7,240,926 B2	7/2007	Dalle et al.	9,402,967 B1	8/2016	Vitello
7,299,981 B2	11/2007	Hickle et al.	9,427,715 B2	8/2016	Palazzolo et al.
7,374,555 B2	5/2008	Heinz et al.	9,433,768 B2	9/2016	Tekeste et al.
7,404,500 B2	7/2008	Marteau et al.	9,463,310 B1	10/2016	Vitello
7,410,803 B2	8/2008	Nollert et al.	D773,043 S	11/2016	Insgram et al.
7,425,208 B1	9/2008	Vitello	D777,903 S	3/2017	Schultz
7,437,972 B2	10/2008	Yeager	9,662,456 B2	5/2017	Woehr
7,482,166 B2	1/2009	Nollert et al.	D789,529 S	6/2017	Davis et al.
7,503,453 B2	3/2009	Cronin et al.	9,687,249 B2	6/2017	Hanlon et al.
7,588,563 B2	9/2009	Guala	9,744,304 B2	8/2017	Swift et al.
7,594,681 B2	9/2009	DeCarlo	D797,928 S	9/2017	Davis et al.
7,608,057 B2	10/2009	Woehr et al.	D797,929 S	9/2017	Davis et al.
7,611,487 B2	11/2009	Woehr et al.	9,764,098 B2	9/2017	Hund et al.
7,632,244 B2	12/2009	Buehler et al.	9,821,152 B1	11/2017	Vitello et al.
D608,900 S	1/2010	Giraud et al.	D806,241 S	12/2017	Swinney et al.
7,641,636 B2	1/2010	Moesli et al.	D807,503 S	1/2018	Davis et al.
D612,939 S	3/2010	Boone, III et al.	9,855,191 B1	1/2018	Vitello et al.
7,681,606 B2	3/2010	Khan et al.	D815,945 S	4/2018	Fischer
7,698,180 B2	4/2010	Fago et al.	9,987,438 B2	6/2018	Stillson
7,735,664 B1	6/2010	Peters et al.	D825,746 S	8/2018	Davis et al.
7,748,892 B2	7/2010	McCoy	10,039,913 B2	8/2018	Yeh et al.
7,762,988 B1	7/2010	Vitello	D831,201 S	10/2018	Holtz et al.
7,766,919 B2	8/2010	Delmotte	D820,187 S	11/2018	Ryan
7,802,313 B2	9/2010	Czajka	10,124,122 B2	11/2018	Zenker
7,918,830 B2	4/2011	Langan et al.	10,166,343 B1	1/2019	Hunt et al.
7,922,213 B2	4/2011	Werth	10,166,347 B1	1/2019	Vitello
8,034,041 B2	10/2011	Domkowski	10,183,129 B1	1/2019	Vitello
8,079,518 B2	12/2011	Turner et al.	10,207,099 B1	2/2019	Vitello
8,091,727 B2	1/2012	Domkowski	D842,464 S	3/2019	Davis et al.
8,118,788 B2 *	2/2012	Frezza A61M 5/5086	D847,373 S	4/2019	Hurwit et al.
		604/200	10,300,263 B1	5/2019	Hunt
8,137,324 B2	3/2012	Bobst	10,307,548 B1	6/2019	Hunt et al.
8,140,349 B2	3/2012	Hanson et al.	10,315,024 B1	6/2019	Vitello et al.
8,252,247 B2	8/2012	Ferlic	10,315,808 B2	6/2019	Taylor et al.
8,257,286 B2	9/2012	Meyer et al.	10,376,655 B2	8/2019	Pupke et al.
8,328,082 B1	12/2012	Bochenko et al.	D859,125 S	9/2019	Weagle et al.
8,348,895 B1	1/2013	Vitello	10,758,684 B1	9/2020	Vitello et al.
8,353,869 B2	1/2013	Ranalletta et al.	10,888,672 B1	1/2021	Vitello
8,443,999 B1	5/2013	Reinders	10,898,659 B1	1/2021	Vitello et al.
D684,057 S	6/2013	Kwon	10,912,898 B1	2/2021	Vitello et al.
8,512,277 B2	8/2013	Del Vecchio	10,933,202 B1	3/2021	Banik
8,556,074 B2	10/2013	Turner et al.	10,953,162 B1	3/2021	Hunt et al.
8,579,116 B2	11/2013	Pether et al.	11,040,149 B1	6/2021	Banik
8,591,462 B1	11/2013	Vitello	11,040,154 B1	6/2021	Vitello et al.
8,597,255 B2	12/2013	Emmott et al.	2001/0034506 A1	10/2001	Hirschman et al.
8,597,271 B2	12/2013	Langan et al.	2001/0056258 A1	12/2001	Evans
8,616,413 B2	12/2013	Koyama	2002/0007147 A1	1/2002	Capes et al.
D701,304 S	3/2014	Lair et al.	2002/0023409 A1	2/2002	Py
8,672,902 B2	3/2014	Ruan et al.	2002/0097396 A1	7/2002	Schafer
8,702,674 B2	4/2014	Bochenko	2002/0099334 A1	7/2002	Hanson et al.
8,777,910 B2	7/2014	Bauss et al.	2002/0101656 A1	8/2002	Blumenthal et al.
8,777,930 B2	7/2014	Swisher et al.	2002/0133119 A1	9/2002	Eakins et al.
8,852,561 B2	10/2014	Wagner et al.	2003/0055685 A1	3/2003	Cobb et al.
8,864,021 B1	10/2014	Vitello	2003/0146617 A1	8/2003	Franko, Sr.
8,864,707 B1	10/2014	Vitello	2003/0183547 A1	10/2003	Heyman
8,864,708 B1	10/2014	Vitello	2004/0008123 A1	1/2004	Carrender et al.
8,911,424 B2	12/2014	Weadock et al.	2004/0064095 A1	4/2004	Vitello
8,945,082 B2	2/2015	Geiger et al.	2004/0116858 A1	6/2004	Heinz et al.
9,082,157 B2	7/2015	Gibson	2004/0186437 A1	9/2004	Frenette et al.
9,101,534 B2	8/2015	Bochenko	2004/0225258 A1	11/2004	Balestracci
D738,495 S	9/2015	Strong et al.	2005/0146081 A1	7/2005	MacLean et al.
D743,019 S	11/2015	Schultz	2005/0148941 A1	7/2005	Farrar et al.
9,199,042 B2	12/2015	Farrar et al.	2005/0209555 A1	9/2005	Middleton et al.
9,199,749 B1	12/2015	Vitello	2006/0084925 A1	4/2006	Ramsahoye
9,220,486 B2	12/2015	Schweiss et al.	2006/0089601 A1	4/2006	Dionigi
9,220,577 B2	12/2015	Jessop et al.	2006/0173415 A1	8/2006	Cummins
			2006/0189933 A1	8/2006	Alheidt et al.
			2007/0060898 A1	3/2007	Shaughnessy et al.
			2007/0106234 A1	5/2007	Klein
			2007/0142786 A1	6/2007	Lampropoulos et al.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2007/0191690 A1 8/2007 Hasse et al.
2007/0219503 A1 9/2007 Loop et al.
2007/0257111 A1 11/2007 Ortenzi
2008/0068178 A1 3/2008 Meyer
2008/0097310 A1 4/2008 Buehler et al.
2008/0106388 A1 5/2008 Knight
2008/0140020 A1 6/2008 Shirley
2008/0243088 A1 10/2008 Evans
2008/0306443 A1 12/2008 Neer
2009/0084804 A1 4/2009 Caspary
2009/0099552 A1 4/2009 Levy et al.
2009/0149815 A1 6/2009 Kiel et al.
2009/0166311 A1 7/2009 Claessens
2009/0326481 A1 12/2009 Swisher et al.
2010/0084403 A1 4/2010 Popish et al.
2010/0126894 A1 5/2010 Koukol et al.
2010/0179822 A1 7/2010 Reppas
2010/0228226 A1 9/2010 Nielsen
2010/0252564 A1 10/2010 Martinez et al.
2010/0283238 A1 11/2010 Deighan et al.
2011/0044850 A1 2/2011 Solomon et al.
2011/0046550 A1 2/2011 Schiller et al.
2011/0046603 A1 2/2011 Felsovalyi et al.
2012/0064515 A2 3/2012 Knapp et al.
2012/0096957 A1 4/2012 Ochman
2012/0110950 A1 5/2012 Schraudolph
2013/0018356 A1 1/2013 Prince et al.
2013/0056130 A1 3/2013 Alpert et al.
2013/0088354 A1 4/2013 Thomas
2013/0237949 A1 4/2013 Miller
2013/0269592 A1 10/2013 Heacock et al.
2014/0000781 A1 1/2014 Franko, Jr.
2014/0034536 A1 2/2014 Reinhardt et al.
2014/0069202 A1 3/2014 Fisk
2014/0069829 A1 3/2014 Evans

2014/0135738 A1 5/2014 Panian
2014/0155868 A1 6/2014 Nelson et al.
2014/0163465 A1 6/2014 Bartlett, II et al.
2014/0257843 A1 9/2014 Adler et al.
2014/0326727 A1 11/2014 Jouin et al.
2014/0353196 A1 12/2014 Key
2015/0182686 A1 7/2015 Okihara
2015/0191633 A1 7/2015 De Boer et al.
2015/0305982 A1 10/2015 Bochenko
2015/0310771 A1 10/2015 Atkinson et al.
2016/0067422 A1 3/2016 Davis et al.
2016/0090456 A1 3/2016 Ishimaru et al.
2016/0144119 A1 5/2016 Limaye et al.
2016/0158110 A1 6/2016 Swisher et al.
2016/0158449 A1 6/2016 Limaye et al.
2016/0176550 A1 6/2016 Vitello et al.
2016/0279032 A1 9/2016 Davis
2016/0328586 A1 11/2016 Bowden et al.
2016/0361235 A1 12/2016 Swisher
2016/0367439 A1 12/2016 Davis et al.
2017/0007771 A1 1/2017 Duinat et al.
2017/0014310 A1 1/2017 Hyun et al.
2017/0124289 A1 5/2017 Hasan et al.
2017/0173321 A1 6/2017 Davis et al.
2017/0203086 A1 7/2017 Davis
2017/0225843 A1 8/2017 Glaser et al.
2017/0239141 A1 8/2017 Davis et al.
2017/0319438 A1 11/2017 Davis et al.
2017/0354792 A1 12/2017 Ward
2018/0001540 A1 1/2018 Byun
2018/0078684 A1 3/2018 Peng et al.
2018/0089593 A1 3/2018 Patel et al.

FOREIGN PATENT DOCUMENTS

WO WO2008/000279 1/2008
WO WO 2017086607 5/2015

* cited by examiner

FIG. 1





FIG. 2






FIG. 4A




FIG. 4B





FIG. 4C







FIG. 7







FIG. 8















FIG 13









TAMPER EVIDENT ASSEMBLY

CLAIM OF PRIORITY

This Non-Provisional patent application claims priority to a U.S. provisional patent application having Ser. No. 62/434,221 and a filing date of Dec. 14, 2016, and also to another U.S. provisional patent application, namely, that having Ser. No. 62/434,240 and a filing date of Dec. 14, 2016, both of which are incorporated herein by reference in its entirety.

BACKGROUND OF THE INVENTION

Field of the Invention

This invention is directed to a tamper evident assembly including a tamper evident cap (TEC) which may be structured for attachment to either a male or female connector. Structural features of one or more embodiments of the TEC also facilitate its operative attachment to at least one open end of a medical tube, tube set, conduit, and the like.

Description of the Related Art

In the medical field, it is a relatively common procedure to administer fluids to patients using syringes, intravenous (IV) infusion devices, medical conduits, tube sets, etc. Such devices or assemblies are useful in the treatment of a number of medical conditions, in that a variety of fluids and/or medicines can be administered to a patient utilizing such assemblies over a prescribed period of time and in controlled amounts. During periods of non-use, however, it is typically very important to maintain such medical devices, including any connectors associated with them, in a closed and fluid-sealed condition, whether to maintain sterility or to assure the integrity of the any drug or fluid contained in such medical devices prior to use. It is also important in order to restrict unauthorized access to a drug or fluid, including access to any connector associated with the medical device.

By way of example, a conventional IV administration assembly typically includes a reservoir or container, in the form of a bottle or more commonly, a flexible material bag, suspended on a pole or a like support structure located substantially adjacent to the patient being treated, typically in an elevated relation thereto. In addition, the IV fluid flows from the supported and elevated IV bag to the patient by means of an elongated, flexible medical tubing or "tube set" connected at a proximal end to the IV bag and at the other distal end, connected intravenously to the patient by way of a catheter or like administrative device or structure.

In some situations, administration of fluids and/or a drug to a patient having an IV line and/or connection to an IV bag is done by means of a syringe that has been pre-filled with a prescribed fluid or drug. As set forth above, during periods of non-use, the medical devices such as an IV bag or other container, an IV line, a prefilled syringe, etc. and connectors associated with them, should be closed or sealed, while concurrently also being protected from non-authorized use.

Medical connectors associated with such medical devices may have a male or female configuration, dependent upon the structure and purpose of the medical device to which such connectors are secured. Accordingly, the medical connectors are structured to close or seal the contents of a given medical device, while also being structured to facilitate access thereto. More specifically, connectors of the type referred to may be in the form of a male or female connector attached to an IV bag, prefilled syringe, or other fluid

container. Further, appropriate connectors of the type generally described above may be male or female Luer connectors, or another connector structured to be threadedly or otherwise removably attached. Further by way of example, a female connector may be secured to an IV delivery tubing, such as at the proximal end, and is structured to be attached to a male connector in a manner which establishes fluid communication with contents of the IV container. Once fluid communication is established, the flow of the IV fluid from the IV container or the contents of a prefilled syringe is facilitated through the attached male and female connectors. As a result, fluid flow between the patient and the interior of the IV bag is established.

In addition, known IV containers or reservoirs may incorporate an additional male or female connector disposed in fluid communication with a tube set or other type of conduit or delivery tubing. Additional male or female connectors of this type may be provided to administer additional liquid agents, such as pain medication, antibiotics, and/or other medicinal compositions, to the fluid being administered to the patient. However, such an additional male or female connector may remain unused or may be accessed subsequently to the initiation of the fluid administration, such as when additional medication or another composition is required or prescribed.

Therefore, there is a need in the medical field for an efficient, effective and easily applied closure assembly that would be capable of closing and sealing a male or female connector during periods of its non-use. Moreover, in order to detect and protect against non-authorized use, any such new closure assembly should preferably have tamper evident features, capable of providing a clear visual indication that use and/or non-authorized use has occurred. Accordingly, if any such tamper evident assembly were developed, it would preferably include a tamper evident cap structured to maintain a closed, sealed, tamper evident condition of the closed connector while being capable, through minimal structural modification, to be attached to a male or female connector associated with the fluid container or reservoir. If any such closure assembly were developed, it would preferably also be structured for efficient attachment to the connector associated with the reservoir in a manner which restricts or perhaps even stops fluid flow from the connector, and also the associated fluid reservoir to which it is attached. Any such tamper evident assembly developed would ideally also be structured to provide a clear indication whenever there has been tampering or other attempted access to the attached male or female connector and/or contents of the fluid reservoir or container associated with the male or female connector.

Additional features desirable in any such tamper evident assembly would include an ability to be used in combination with and connected to open ends of a medical conduit, tube set, etc. As such, the attached conduit or tube set could thereby be connected in direct fluid communication to the male or female connector associated with the fluid reservoir, by virtue of the interconnecting tamper evident assembly.

Finally, the structural components as well as the operational characteristics of any such proposed tamper evident assembly and associated tamper evident cap should ideally provide a sufficient degree of reliability relating to its intended use and function with a male or female connector to which it is attached, while restricting access and clearly indicating when access, including unauthorized access, thereto has occurred or been attempted.

SUMMARY OF THE INVENTION

The present invention is intended to present a solution to these and other needs, and accordingly, is directed to a

3

tamper evident assembly which includes a tamper evident cap (TEC) that may vary in its structural configuration so as to be adaptable for use with a male connector or a female connector. In each of the different structural configurations, the TEC can be used in combination with a conduit, medical tube or “tube set” by being attached to at least one open end thereof. As explained in greater detail hereinafter, different tamper evident caps can be used to be attached to opposite open ends of the conduit, medical tube, etc.

In more specific terms, the TEC comprises an end cap having a substantially hollow configuration including one open end dimensioned and configured to receive the male or female connector. The end cap is preferably formed of a one-piece, integral construction including an open end and an integrated closed-end. In addition, the TEC also comprises a tip cap disposed within the interior of the end cap in an “operative position”. When in such operative position, the tip cap is movable within and removable from the interior of the end cap. Further the tip cap is structured to be connected directly to the male or female connector, dependent on its structural configuration, when in the operative position. Accordingly, the structural features of the tip cap and its disposition in the aforementioned operative position defines a connection to the male or female connector with which the TEC is used. As will be explained in greater detail hereinafter, in at least some preferred embodiments of the tamper evident assembly of the present invention, the tip cap is disposed and structured to regulate fluid flow there-through, and through the discharge opening or discharge port of the connector to which it is attached. As used herein, the tip cap and a flow controller thereof disposed to “regulate fluid flow” through the discharge port of a connector may be interpreted to mean either the prevention of such fluid flow, or in contrast, the establishment of a direct fluid flow or communication with the male or female connector, as well as the fluid reservoir, medical device, container, to which the male or female connector is attached.

Additional structural and operative features of the TEC include the provision of a retaining structure formed on the interior of the end cap, and a retention structure removably connected to the exterior of the tip cap. The cooperative disposition, configuration and overall structure of the retaining structure and the retention structure collectively define an operative interaction which facilitates disposition of the tip cap in its operative position within the interior of the end cap. In addition, such operative interaction between the retaining structure and the retention structure initially restricts removal of the tip cap from its operative position within the end cap.

In more specific terms, the operative interaction between the retaining structure and the retention structure results in an “interruptive engagement” which facilitates a uni-directional passage of the retention structure over the retaining structure when the tip cap is being disposed within the end cap, into the operative position. As indicated, the “interruptive engagement” is facilitated by the cooperative configuration, dimension and disposition of the retaining and retention structures. As suggested above, such interruptive engagement comprises a substantially sliding engagement of the retention structure over the retaining structure concurrent to disposition of the tip cap into the operative position. However, and in contrast, the interruptive engagement further comprises an “abutting engagement” of the retaining and retention structures, wherein such abutting engagement is preventative of passage of the retention structure over the

4

retaining structure, concurrent to disposition of the tip cap out of its operative position and out of the interior of the end cap.

As a result, forced removal of the tip cap from its operative position within the interior of the end cap, such as when attached to a male or female connector, at least partially defines the “tamper evident” characteristics of the TEC. The retention structure is removably connected by one or more frangible members to the exterior of the tip cap. As a result, the forced removal of the tip cap from the interior of the end cap will result in the abutting engagement between the retaining and retention structures. In turn, this will result in a breakage of the one or more frangible members, and a detachment of the retention structure from the tip cap as it is being removed from its operative position within the end cap. Therefore, the retention structure will remain within the interior of the end cap, as the tip cap remains attached to the male or female connector while it is removed from the end cap. As a result, visual observation of the tip cap being attached to the connector of a reservoir or medical device on an exterior of the end cap, absent the presence of the retention structure, provides evidence of authorized or unauthorized use or access.

In various embodiments of the tamper evident assembly according to the present invention, the TEC includes a flow controller disposed on the interior of the tip cap. Also, a variance in the structural configuration of the tip cap may include structural modification of the flow controller so as to be disposed in fluid regulating relation with either a male connector or a female connector. As emphasized hereinafter, the disposition of the flow controller in “fluid regulating relation” to the attached male or female connector may include a prevention of fluid flow through the attached connector or an establishment of such fluid flow through the attached connector.

In addition, the various embodiments of the TEC may also include a one-way rotational drive structure, which may take the form of a modified “ramp and cliff” drive structure. The one-way rotational drive structure is thereby operative to prevent rotation of the tip cap relative to the end cap in one direction during a threaded or other attachment of the male or female connector to the tip cap. In contrast, the one-way drive assembly allows relative rotation of the tip cap and the end cap, thereby preventing the connector from being unthreaded from the tip cap, while the tip cap is in its operative position.

As set forth above, one or more additional embodiments of the tamper evident assembly includes a structural modification of the TEC, which allows it to be used in combination with a medical tube, conduit, tube set, etc. hereinafter collectively and independently referred to as a “conduit”. The conduit is structured to include an interior lumen which in turn, defines a path of fluid flow to or from the TEC and the reservoir, container, medical device, etc. to which the aforementioned male or female connector is secured. Moreover, an open end of the conduit is connected within an interior of the tip cap in fluid communication with the flow controller thereof. The flow controller, whether structurally modified for use with a male or female connector, is further structured to define a “flow-through” configuration. Such a flow-through configuration establishes a path of fluid flow and direct fluid communication between the conduit and the male or female connector attached to the TEC, as well as the container, reservoir or medical device on which the male or female connector is secured. Further, in order to assure a stable fluid communication and/or path of fluid flow between the conduit and the male or female connector,

5

through the TEC, the open end of the conduit is fixedly bonded, secured or attached within the interior of the tip cap.

The aforementioned modification of the structure of both the tip cap and the end cap to accommodate the use of the TEC with the conduit includes an apertured construction of the closed end of the end cap. Such an apertured construction allows the conduit, and at least a free end thereof, to extend through at least one aperture in the closed end into attachment with the interior of the tip cap. In addition, the flow controller may be structurally modified to define the aforementioned "flow-through configuration". Such a flow-through configuration differs from the flow controller having a substantially closed configuration to prevent fluid flow through the male or female connector, as well as the container, reservoir, with which the connector is operatively associated.

Accordingly, the structural components as well as the operational characteristics of the various embodiments of the tamper evident assembly of the present invention, as defined in greater detail hereinafter, will be operatively reliable for use with a male or female connector to which it is attached, while restricting access and clearly indicating when access, including unauthorized access, thereto has occurred or been attempted.

These and other objects, features and advantages of the present invention will become clearer when the drawings as well as the detailed description are taken into consideration.

BRIEF DESCRIPTION OF THE DRAWINGS

For a fuller understanding of the nature of the present invention, reference should be had to the following detailed description taken in connection with the accompanying drawings in which:

FIG. 1 is a perspective view of a tamper evident cap (TEC) having a male configuration and associated with the tamper evident assembly of the present invention.

FIG. 2 is an interior sectional view of the embodiment of FIG. 1.

FIG. 3 is a perspective interior sectional view of the embodiment of FIGS. 1 and 2.

FIG. 4-A is a perspective view in exploded form of the tamper evident cap (TEC) shown in the embodiment of FIGS. 1 to 3 in a position to be attached to a female connector associated with a syringe or other reservoir.

FIG. 4-B is a perspective view of the tamper evident cap (TEC) shown in FIGS. 1-4A secured to a syringe.

FIG. 4-C is a perspective view in exploded form of the syringe of the embodiment of FIGS. 4A and 4B being detached from the tamper evident cap (TEC) in the embodiment of FIGS. 1-3.

FIG. 5 is a perspective view in exploded form of a tip cap positioned for assembly within an end cap of the tamper evident cap (TEC) of the embodiment shown in FIGS. 1 through 4-C.

FIG. 6 is a perspective, exploded view of the tip cap and TEC illustrated in FIG. 5.

FIG. 7 is a perspective view in longitudinal section of the interior of the end cap of the embodiment of FIGS. 5 and 6.

FIG. 8 is an interior sectional view of the embodiment of FIG. 7.

FIG. 9 is an exterior perspective view of the tip cap of the tamper evident cap of the embodiment of FIGS. 1-3.

FIG. 10 is a perspective sectional view of the interior of the embodiment of FIG. 9.

FIG. 11 is a perspective view of another preferred embodiment of the tamper evident assembly incorporating a

6

conduit or tube set being attached to one embodiment of a tamper evident cap of the tamper evident assembly of the present invention.

FIG. 12 is a perspective view in partial cutaway of one end of the conduit or tube set of the embodiment of FIG. 11, wherein the end cap and the tip cap are separated.

FIG. 13 is a perspective view in partial section and cutaway of one embodiment the tamper evident cap of the embodiment of FIGS. 11 and/or 12, being attached to one end of a conduit or tube set.

FIG. 14 is a perspective sectional view of the interior of another embodiment of the end cap which may be associated with the tamper evident cap structured for connection to a tube set or conduit as represented in the embodiment of FIGS. 11 and 12.

FIG. 15 is a perspective interior view in longitudinal section of the embodiment of FIG. 14.

FIG. 16 is an exterior view of yet another embodiment of the tip cap having a male configuration and structurally configured for use with a conduit or tube set as represented in FIGS. 11-13.

FIG. 17 is a perspective interior view in longitudinal section of the embodiment of FIG. 16.

FIG. 18 is a perspective, longitudinal sectional view of the interior of another embodiment of the tamper evident cap, having a female configuration and associated with the tamper evident assembly of the present invention.

FIG. 19 is a perspective view in exploded form of yet another embodiment of a tamper evident cap, having a female configuration and structured for use with a conduit or tube set of the type represented in FIG. 11 and which may be associated with the tamper evident assembly of the present invention.

Like reference numerals refer to like parts throughout the several views of the drawings.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

As represented in the accompanying drawings, the present invention is directed to a tamper evident assembly 200 including a tamper evident cap (TEC) 10 comprising both an end cap 12 and a tip cap 14, as is perhaps best illustrated in FIG. 5. Also, and as shown in FIG. 3, the tip cap 14 is positioned within the interior of the end cap 12 in an operative position. Moreover, the TEC is capable of being modified to assume different structural configurations which facilitate its operative attachment to either a male connector or a female connector, while the tip cap 14 is in the aforementioned operative position.

The structural and operative versatility of the tamper evident assembly 200, specifically including the TEC 10, also facilitate it having tamper evident capabilities. More specifically, the structural features of the TEC 10 provide a clear visual indication of an attempted use or access, either authorized or unauthorized, of a container, reservoir, medical device, etc. to which the male or female connector is attached, as demonstrated in more detail with reference to at least FIGS. 4-A through 4-C.

In addition, and with reference to FIG. 11, in one or more preferred embodiments of the tamper evident assembly 200, an at least minimal modification of the TEC 10 facilitate its use with medical tubing, conduit or a "tube set", generally indicated as 210 in FIGS. 11-13. For purposes of clarity the tubing, tube set, etc. 210 are collectively and independently referred to herein as "conduit". It is further noted that use of the TEC 10' with the conduit 210, as structurally modified in

an appropriate manner, may be attached to either a male connector or a female connector, as represented in greater detail with specific reference to FIGS. 11-16.

With initial reference now to FIGS. 1-10, and as represented in more specific detail in FIGS. 5-10, one preferred embodiment of the TEC 10 comprises the end cap 12 and the tip cap 14. The end cap 12 is preferably formed of a one-piece integral construction including an open end 16 providing direct access to the hollow interior 17. The open end 16 also facilitates positioning of the tip cap 14 into and out of its operative position, as represented in FIGS. 1-3, as well as facilitates access to the tip cap 14 when being attached to the male or female connector. The end cap 12 also includes a closed end 18 integrally formed with a remainder of the end cap 12 and having an exterior structure generally indicated as 20.

As disclosed in detail in what may be considered related intellectual property rights, namely, U.S. Pat. Nos. 8,591,462 and 9,199,749, issued respectively on Nov. 26, 2013 and Dec. 1, 2015 to Vitello, and assigned to the same corporate entity as the present application, the exterior 20 of the integrally formed, closed end 18 includes a plurality of projections 21, shown in FIGS. 2 and 3, formed at least partially on the interior peripheral surfaces of a corresponding recess 23. The plurality of projections 21 may vary in number and placement, but are cooperatively disposed, structured and dimensioned to interact with correspondingly structured and dimensioned projections of outwardly protruding connectors, which may be part of a package or packaging structure for a plurality of TECs 10 and/or 10'. Reference is specifically, but not exclusively made to FIGS. 8-10 and 11-14, of the above noted patents.

As also represented in FIGS. 7 and 8, the interior surface of the closed end 18 includes a one-way rotational drive assembly, generally indicated as 22, in the form of a modified "ramp and cliff" drive assembly. The one-way rotational drive assembly 22 and/or ramp and cliff comprises a first drive segment 24 formed on the interior surface of the closed end 18. As referenced hereinafter, the one-way rotational drive assembly 22 also includes a second drive segment 26 formed on the interior sidewall of the tip cap 14, as clearly represented in at least FIGS. 3 and 10. As also indicated in greater detail, the structural and operative features of the rotational one way and/or ramp and cliff drive assembly 22 facilitates a threaded attachment of a connector, as at 200 in FIG. 4A, with the tip cap 14 while preventing an unthreading thereof.

Additional features of the TEC 10, and in particular, the end cap 12, include a retaining structure generally indicated as 28. The retaining structure 28 comprises at least one, but preferably a plurality of retaining members 30 disposed within the end cap 12, preferably on the interior surface thereof. In addition, the plurality of retaining members 30 are disposed in laterally spaced relation to one another so as to collectively and at least partially, surround the exterior of the end cap 14, when the end cap 14 is disposed in the operative position of FIGS. 1-3. It is further noted that each of the one or more retaining members 30 are disposed, dimensioned and configured to facilitate passage of the tip cap 14 into the interior 17 of the end cap 12, through the open end 16 thereof and into its operative position. In contrast, the disposition, dimension, configuration and overall structuring of the retaining structure 28, and in particular, the one or more retaining members 30 restricts removal of the tip cap 14 from its operative position and out of the end cap 12, as generally represented in FIG. 4-C. In the illustrated embodiment represented throughout the accompany-

ing Figures, the retaining structure 28, including the one or more retaining members 30, have a preferred configuration, which includes, but is not limited to, an angled, beveled, chamfered, etc. face or end portion 32, which faces outwardly from the interior 17 end cap 12 towards the open end 16.

It is emphasized that the specific disposition and overall structure of the one or more retaining members 30 may differ in size, placement and even configuration. As such, the one or more retaining members 30 may comprise elongated flanges or rib structures, having a curvilinear configuration which conforms to the interior surface portion(s) of the end cap 12 to which they are secured or connected.

With reference now to FIG. 2, in order to efficiently accomplish the intended operative interaction between the end cap 12 and the tip cap 14, which facilitates the tip cap 14 being disposed into its operative position, a retention structure, generally indicated as 36, is mounted on or connected to the exterior of the tip cap 14. More specifically, and as shown in FIG. 3, the retention structure 36 comprises a substantially circular or annular ring or similar structure connected to and extending at least minimally outward from the exterior surface of the tip cap 14. As such, the retention structure 36 may be in the form of a continuous ring or otherwise be at least partially segmented into a plurality of ring or rib segments (not shown), which individually or collectively are disposed in at least partially or completely surrounding relation to the exterior of the tip cap 14. The least partially surrounding relation of the retention structure 36 to the exterior of the tip cap 14 facilitates its "interruptive engagement" with the retaining structure 28 and the one or more of the plurality of retaining members 30. Additional structural and operative features of the retention structure 36 includes it being structured or disposed to have at least a minimal amount of flexure or flexibility. Such flexible characteristics may be attributed to its outward spacing from the exterior surface of the tip cap 14 and/or its removable connection thereto by a plurality of frangible members 37 and/or the forming of at least a portion of the retention structure 36 from an at least partially flexible material.

Therefore, the cooperative structuring, disposition and dimensioning of the retaining structure 28 and the retention structure 36 defines the aforementioned "interruptive engagement" with one another as the tip cap 14 passes into its operative position within the interior 17 of the end cap 12, as well as when it passes out of its operative position, through the open end 16, to an exterior of the end cap 12. Generally, such interruptive engagement defines a facilitated passage of the tip cap 14, with the retention structure 36 attached thereto, into its operative position. In contrast, the occurrence of such interruptive engagement at least partially restricts removal of the tip cap 14 from its operative position and in doing so prevents removal of the retention structure 36.

In more specific terms, the aforementioned interruptive engagement comprises a substantially sliding engagement of the retention structure 36 over the retaining structure 28, including the one or more retaining members 30, concurrent to disposition of the tip cap 14 through the open end 16 and into its operative position. In contrast, the interruptive engagement further comprises an "abutting engagement" of the retaining structure 36 with the one or more retaining members 30 of the retention structure 28. More specifically, as the tip cap 14 is forcibly removed from the interior 17 of the end cap 12. The "abutting engagement" between the retainer structure 28 and the retention structure 36 is preventative of passage of the retention structure 36 over the

one or more retaining members 30 of the retaining structure 28. Such “abutting engagement” further results in a breakage or fracture of the plurality of frangible members 37 serving to removably interconnect the retention structure 36 to the exterior surface of the tip cap 14. Therefore, upon breakage of the frangible members 37 and due to the abutting engagement, the retention structure 36 will be removed from the exterior of the tip cap 14 and remain captured within the interior of the end cap 12. A continued removal force, as schematically represented as 300 in FIG. 4C, being exerted on the tip cap 14 will result in its removal from the interior 17 of the end cap 12, such as when it is attached to a connector 201 of a syringe such as shown in FIG. 4A or other medical device 206.

As disclosed in detail in the embodiments of the accompanying Figures, the predetermined cooperative configuration of at least the plurality of retaining members 30, including the angled, beveled and/or chamfered faces 32, facilitate the aforementioned sliding engagement of the retention structure 36 over the plurality of retaining members 30. Moreover, the structural flexure or flexible capabilities of the retention structure 36, as set forth above, will allow it to be at least minimally flexed inwardly, towards the portion of the tip cap 14 to which it is attached. Such inward flexure of the retention structure 36 occurs as it engages the chamfered faces 32. Such interactive, “interruptive engagement” between the retention structure 36 and the chamfered faces 32 results in the aforementioned “sliding engagement” therebetween, as the tip cap 14 is placed or disposed into its operative position within the end cap 12, from an exterior thereof. Further, once the retention structure 36 passes over and beyond the chamfered surfaces 32 it will assume its normal, original outwardly expanded orientation, due in part to its flexible characteristics, as set forth above. As such the placement or positioning of the tip cap 14 into its operative position within the interior 17 of the end cap 12 may be accurately referred to as a “snap-fit” insertion. Such a “snap-fit” connection will, as should be apparent, be the result of the retention structure 36 assuming its normal, original, outwardly expanded orientation, subsequent to engaging the plurality of retaining members 30.

As represented in at least FIGS. 1-3, 9 and 10, the structural configuration of the tip cap 14 is that of a female connector dimensioned and structured to receive a female connector, as at 201 in FIG. 4A. Accordingly, the tip cap 14 additionally includes a flow controller 40 integrally or otherwise appropriately secured on the interior thereof. In the female connector of the indicated Figures, the flow controller 40 comprises a generally elongated, outwardly projecting plug 42, which may also include an open or hollow interior disposed in direct communication with an additional open interior 29 of the tip cap 14. The opposite end of the plug 42 of the flow controller 40 is closed as at 42' in order to prevent or restrict fluid flow through the female connector 201 to which it is attached.

In more specific terms, and again with primary reference to FIGS. 4A-4C, the TEC 10 is pre-assembled as represented in FIG. 4A and is ready for attachment to the female connector 201 of a container, reservoir, medical device, etc. such as a prefilled syringe 202. A threaded interconnection occurs therebetween due to the internal threads 46 formed on the interior of the tip cap 14, in at least partially surrounding relation to the plug 42. These internal threads or corresponding threaded surface 46 will mate by threaded engagement with the threads or outwardly extending ribs or ears 206 formed on the female connector 201. Upon connection, the closed end 42' and at least a portion of the plug

42 will pass into the discharge port or opening 204 of the connector 201, thereby restricting or preventing fluid flow into or out of the discharge port 204 and the female connector 201.

With primary reference to FIG. 4-C, use or access to the container, reservoir and/or syringe 202 and/or the contents thereof, is typically accomplished by removal of the tip cap 14 from the female connector 201. However, the provision of the aforementioned uni-directional, rotational ramp and cliff drive assembly 22 prevents the female connector 201 from being unthreaded from the fluid restricting engagement with the flow controller 40. In more specific terms, the first drive segment 24 formed on the interior surface of the closed end 18 and the second drive segment 26 formed on the interior sidewall surface of the tip cap 14 are cooperatively configured and disposed to prevent relative rotation of the tip cap 14 and the end cap 12 in one direction but allow relative rotation thereof in an opposite direction. As represented in FIG. 3, the threading of the female connector 201 onto the flow controller 40 will most probably result in a clockwise direction of rotation of the female connector 201 so as to cause a threaded engagement between the interior threaded portion 46 and the exterior ribs, ears or thread members 206 on the female connector 201. This clockwise direction of rotation will, in turn, cause the tip cap 14 to also rotate in a clockwise direction within the interior 16 of the end cap 12. As a result, the second drive segment 26 will engage a raised portion of the first drive segment 24. Such engagement will prevent relative rotation between the tip cap 14 and end cap 12 in a clockwise direction. As a result, the female connector 201 will be able to continue a clockwise direction of rotation and be threaded onto the flow controller 40. However, due to the slanted, sloped peripheral portion 26' of the second drive segment 26 and the cooperative disposition and configuration of the first drive segment 24, the rotation of the tip cap in the opposite or counter-clockwise direction will not be prevented. Such reversed or counter-clockwise direction of rotation will not be prevented due to the sliding engagement between the slanted periphery 26' and the portions of the first drive segment 24 which it engages. As a result, the connector 201 will not be able to be unthreaded from the tip cap 14.

Therefore, the only practical way of accessing the connector 201 would be to exert an outwardly directed pulling force or otherwise appropriate directional force 300, as schematically represented in FIG. 4-C, on the tip cap 14 while it is connected to the female connector 201. Such an outwardly directed pulling or other appropriate force 300 will result in the aforementioned interactive, abutting engagement of the retention structure 36 with the retaining structure 28. As stated herein, such an abutting engagement will result in a detachment of the retention structure 36 from the exterior of the tip cap 14, as the tip cap 14 is removed from its operative position within the interior 17 of the end cap 12. The retention structure 36 will remain captured within the interior 17 of the end cap 12 and the tip cap 14 will remain connected to the female connector 201, as represented in FIG. 4C. Moreover, upon removal from the end 12, the tip cap 14 will be visually observable without the retention structure 36 (also referred to as an indicator ring) being attached thereto. Therefore, a visual indication of attempted or actual use, whether authorized or unauthorized will be evident.

Yet another preferred embodiment of the tamper evident assembly 200 is represented in FIGS. 11-17. As set forth above, the tamper evident assembly 200 comprises a tamper evident cap (TEC) 10' which is structurally adapted to be

11

used with a medical conduit **210**. As with the embodiment of the TEC **10**, the TEC **10'** may also be structurally adapted for attachment to a female connector **201**, of the type represented in FIG. **4A**, or a male connector. Moreover, the TEC **10'** includes many of the structural features present in the TEC **10** as described above. Such common structural features include end cap **12'**, tip cap **14'**, a one-way rotational drive assembly **22**, preferably in the form of a ramp and cliff; a retaining structure **28** and a retention structure **36**.

However, modified structural features of the TEC **10'** further include a flow controller **40'** structured for attachment to a female connector by virtue of a threaded surface area **46**. As such, the flow controller **40'** includes an outwardly extending plug **42'** disposable in fluid regulating relation within the interior of a discharge opening or discharge port **204** as represented in FIG. **4A**. The modifications of the TEC **10'** further include the structuring of the flow controller **40'** to have a "flow-through" construction or configuration comprising an open end **43'** disposed in direct fluid communication with the hollow, open interior **44** of the flow controller/plug **40'**, **42'**. Further structural features of the TEC **10'** include the fixed attachment and/or bonded connection of an open end **210'** of the conduit **210** within the interior of the tip cap **14'**. Such a fixed, bonded connection assures the stability of a path of fluid flow through the interior lumen of the conduit **210** and into the interior of the tip cap **14'** so as to be in direct fluid communication with the "flow-through" structure of the flow controller **40'**. The fixed, bonded connection between the open end **210'** of the conduit **210** may be accomplished by a sleeve or receiving channel **48** integrally or otherwise fixedly disposed within the interior of the tip cap **14'** as clearly represented FIG. **13**. The sleeve or receiving channel **48** is disposed in direct fluid communication with the interior of the flow controller **40'** and more specifically, with the interior **44** of the plug **42'**.

Positioning of the open end **210'** in fixed attachment within the interior of the tip cap **14'** is accomplished by passage of the open end **210'** and at least a portion of the remainder of the conduit **210**, through the closed end **18'** of the end cap **12'**. Such passage is facilitated by the closed end **18'** having an apertured construction at least partially defined by at least one opening **50** formed in the closed end **18'**. The opening or aperture **50** is disposed, dimensioned and configured to facilitate passage of the open end **210'**, as well as an adjacent or adjoining portion of the conduit **210**, through the closed end **18'** and into the fixed, bonded engagement with the receiving, mounting channel **48**. As such, the path of fluid flow within the interior of the conduit **210** is disposed in direct fluid communication with the interior of the "flow-through" flow regulator **40'**, as clearly represented in FIG. **13**.

As represented in FIG. **11**, different ones of the TEC **10'** may be operatively connected to opposite open ends **201'** of the conduit **210**. Accordingly, the structural and operative features represented in FIGS. **12** and **13** are presented to indicate the structural and operative features of each of the TECs **10'** being attached to different ones of the open ends of the conduit **210**.

As emphasized herein, the tamper evident assembly **200** of the present invention includes a tamper evident cap (TEC) which may be structurally modified to assume either a male configuration, as represented in FIGS. **1-17**, or a female configuration as represented in FIGS. **18** and **19**. Accordingly, for purposes of clarity, the TEC having the female configuration is generally indicated as **110** and is structurally adapted to be incorporated within the tamper evident assembly **200** of the present invention, independent of connection

12

to the conduit or tube set **210**. In a further embodiment and/or structural modification, the TEC is generally represented as **210'** and includes the aforementioned flow through construction enabling it to be operatively bonded or otherwise fixedly connected to an open end **210'** of the conduit or tube set **210**, as described herein with reference to the embodiment of FIG. **13**.

It should also be apparent that many of the structural features and components of the TEC **10** and/or **10'**, having the male configuration, are incorporated in the TEC **110** and/or **110'** which has the female configuration. Further, it is emphasized for purposes of clarity and in order to avoid repetitive descriptive details, these common structural features and components are represented as having the same reference numerals in the embodiments of FIGS. **1-17** and the embodiments of FIGS. **18** and **19**. However, due to the male configuration of the embodiments of FIGS. **1-17**, different structural features exist in the embodiment of FIGS. **18** and **19** due to its female configuration.

In more specific terms, and with primary reference now to FIGS. **18** and **19**, the TEC **110** is structured for use independent of a conduit or tube set **210** of the type represented in FIGS. **11-13**.

As such, the TEC **110** is absent the aforementioned flow through construction and includes a flow controller **140** in the form of an open chamber **142** having an open outer end **143**. In addition, thread segments or ribs **146** are formed on the exterior of the flow controller **140** and are disposed to engage in a threaded, mating relation with a corresponding threaded surface on a male connector which may be associated with a nozzle or discharge port of a syringe of the type represented in FIGS. **4A-4C**. More in particular, such a male connector may be formed on and be structurally and operatively associated with a nozzle or discharge port of a syringe, such as of the type of syringe **202**, represented in FIGS. **4A-4C**. Moreover, the open chamber **142** of the flow controller **140** is disposed, dimensioned and configured to receive the nozzle or discharge port of such a male connector, in the open interior chamber **142**, concurrently to the ribs or thread segments **146** engaging corresponding threaded surfaces of the male connector. Accordingly, such interaction between the nozzle or discharge port of a male connector of a syringe being disposed within the open interior chamber **142** of the flow controller **140** will restrict the flow of fluid through the male connector of the syringe connected to the TEC **110**.

With primary reference now to FIG. **19**, the TEC **110'** is structurally modified from that of the TEC **110** of FIG. **18** and is representative of yet another preferred embodiment of the tamper evident assembly **200** of the present invention. More specifically, the TEC **110'** includes the aforementioned flow through configuration and facilitates connection to the open end **210'** of a conduit or tube set **210**. As such, the open end **210'** and adjacent portions conduit **210** may pass through the opening or aperture **50** defining an apertured construction of the integral closed end **18'** of the end cap **112'**. This is substantially equivalent to the apertured construction of the end cap **12'** represented in the embodiment of the TEC **10'** in FIGS. **14** and **15**. In addition, an open end **210'** of the conduit or tube set **210** is bonded and/or fixedly secured on the interior **29** of the tip cap **114'**. Further, an opening or aperture **143'** is formed in a normally segregating partition **145** at the bottom or base end of the open interior chamber **142** of the flow controller **140**. This opening **143'** establishes direct fluid communication between the open end **210'** of the conduit or tube set **201** and any male configured nozzle or discharge port of a syringe or other container

13

disposed within the open interior chamber 142. A further structural adaptation of the embodiment of FIG. 19 may include a similar connecting sleeve 48, as represented in FIG. 13, to facilitate the fixed attachment or bonding of the open end 210' on the interior of the tip cap 114'.

Since many modifications, variations and changes in detail can be made to the described preferred embodiment of the invention, it is intended that all matters in the foregoing description and shown in the accompanying drawings be interpreted as illustrative and not in a limiting sense. Thus, the scope of the invention should be determined by the appended claims and their legal equivalents.

What is claimed is:

1. A tamper evident assembly structured for attachment to a medical connector, said tamper evident assembly comprising:

a tamper evident cap including an end cap and a tip cap, said tip cap movably and removably disposed in an operative position within said end cap,

a retaining structure disposed on an interior surface of said end cap in retaining relation to said tip cap, said tip cap including a retention structure removably connected to an exterior of said tip cap,

said retaining structure disposed in removal preventing relation to said retention structure concurrent to said tip cap being in said operative position,

said retaining structure and said retention structure cooperatively structured and configured to define a substantially sliding engagement therebetween concurrent to passage of said tip cap from an exterior of said end cap into said operative position, and

said substantially sliding engagement comprises a flexure of at least one of said retaining structure and retention structure relative to the other one of said retaining structure and retention structure, concurrent to said passage of said tip cap into said operative position.

2. The tamper evident assembly as recited in claim 1 wherein said retaining structure comprises a predetermined configuration, at least partially facilitating said substantially sliding engagement; said predetermined configuration defining a unidirectional passage of said retention structure over said retaining structure.

3. The tamper evident assembly as recited in claim 2 wherein said unidirectional passage is concurrent to said passage of said tip cap into said operative position.

4. The tamper evident assembly as recited in claim 2 wherein said predetermined configuration defines an abutting engagement of said retaining structure with said retention structure, said abutting engagement preventative of said substantially sliding engagement and passage of said retention structure over said retaining structure, concurrent to disposition of said tip cap out of said operative position.

5. The tamper evident assembly as recited in claim 2 wherein said predetermined configuration comprises a chamfered shape of at least a portion of said retaining structure.

6. The tamper evident assembly as recited in claim 5 wherein said chamfered shape is disposed on said retaining structure in an outwardly facing relation to an open end of said end cap.

7. The tamper evident assembly as recited in claim 2 wherein said retaining structure comprises at least one retaining segment formed on and extending outwardly from an interior surface of said end cap in interruptive engagement with said retention structure.

8. The tamper evident assembly as recited in claim 7 wherein said retaining structure comprises a plurality of

14

retaining segments formed on and extending outwardly from said interior surface; said plurality of retaining segments disposed in laterally spaced relation to one another.

9. The tamper evident assembly as recited in claim 7 wherein said retention structure is disposed in at least partially surrounding relation to an exterior surface of said tip cap.

10. The tamper evident assembly as recited in claim 9 wherein said at least one retaining segment and said retention structure respectively extend outwardly from an inner surface of said end cap and an outer surface of said tip cap into said interruptive engagement with one another upon disposition of said tip cap into and out of said operative position.

11. The tamper evident assembly as recited in claim 9 wherein said interruptive engagement defines a detachment of said retention structure from said tip cap concurrent to passage of said tip cap out of said operative position.

12. The tamper evident assembly as recited in claim 11 wherein said interruptive engagement defines a sliding engagement of said retention structure over said retaining structure concurrent to disposition of said tip cap into said operative position.

13. A tamper evident assembly structured for attachment to a medical connector, said tamper evident assembly comprising:

a tamper evident cap including an end cap and a tip cap, said tip cap movably and removably disposed in an operative position within said end cap,

a retaining structure disposed on an interior surface of said end cap in retaining relation to said tip cap, said tip cap including a retention structure removably connected to an exterior of said tip cap,

said retaining structure disposed in removal preventing relation to said retention structure concurrent to said tip cap being in said operative position, and

said retaining structure and said retention structure cooperatively structured and configured to define a substantially sliding engagement therebetween concurrent to passage of said tip cap from an exterior of said end cap into said operative position.

14. The tamper evident assembly as recited in claim 13 further comprising a flow controller formed within the said tip cap; said flow controller disposed to engage and at least partially regulate fluid flow through the medical connector.

15. The tamper evident assembly as recited in claim 14 wherein said flow controller comprises a predetermined configuration structured to regulate fluid flow through a female medical connector.

16. The tamper evident assembly as recited in claim 15 wherein said predetermined configuration of said flow controller comprises a plug dimensioned and configured to extend into a discharge port of the female connector.

17. The tamper evident assembly as recited in claim 14 wherein said flow controller comprises a predetermined configuration structured to regulate fluid flow through a male medical connector.

18. The tamper evident assembly as recited in claim 17 wherein said flow controller comprises a chamber dimensioned and configured to receive a discharge port of the male connector therein.

19. A tamper evident assembly structured for attachment to a medical connector, said tamper evident assembly comprising:

a tamper evident cap including an end cap and a tip cap, said tip cap movably and removably disposed in an operative position within said end cap,

15

a retaining structure disposed on an interior of said end cap in retaining relation to said tip cap; said tip cap including a retention structure removably connected to an exterior thereof,

at least one of said retaining structure and said retention structure comprising a predetermined configuration, said predetermined configuration defining a unidirectional passage of said retention structure over said retaining structure,

said predetermined configuration and relative dispositions of said retaining structure and said retention structure collectively defining an interruptive engagement with one another upon disposition of said tip cap into and out of said operative position,

said interruptive engagement comprising a substantially sliding engagement of said retention structure over said retaining structure concurrent to disposition of said tip cap into said operative position,

said interruptive engagement further comprising an abutting engagement of said retaining structure with said retention structure, said abutting engagement preventative of passage of said retention structure over said retaining structure, concurrent to disposition of said tip cap out of said operative position, and

a flow controller formed within the said tip cap and disposed to engage and at least partially regulate fluid flow through the medical connector, when attached to said tamper evident cap.

20. The tamper evident assembly as recited in claim **19** further comprising a conduit having an open end connected within an interior of said tip cap in fluid communication with said flow controller.

21. The tamper evident assembly as recited in claim **20** wherein said flow controller comprises an open, flow-through configuration disposed to establish a path of fluid flow, through said open end, between an interior of said conduit and the connector attached to said tamper evident cap.

22. The tamper evident assembly as recited in claim **21** wherein said flow controller comprises a predetermined configuration structured to regulate fluid flow through a male medical connector.

16

23. The tamper evident assembly as recited in claim **22** wherein said predetermined configuration of said flow controller comprises a plug dimensioned and configured to extend into a discharge port of the female connector.

24. The tamper evident assembly as recited in claim **21** wherein said flow controller comprises a predetermined configuration structured to regulate fluid flow through a male medical connector.

25. The tamper evident assembly as recited in claim **24** wherein said flow controller comprises a chamber dimensioned and configured to receive a discharge port of the male connector therein.

26. The tamper evident assembly as recited in claim **20** wherein said open end is fixedly connected within said tip cap, concurrent to said tip cap being in said operative position.

27. The tamper evident assembly as recited in claim **26** wherein said at least one free end extends through said end cap and into fixed connection within said interior of said tip cap.

28. The tamper evident assembly as recited in claim **26** wherein said end cap includes a closed end having an apertured construction structured to receive said conduit, said open end disposed through said apertured construction of said closed end into said fixed connection with said interior of said tip cap.

29. The tamper evident assembly as recited in claim **28** wherein said closed end is integrally connected to a remainder of said end cap.

30. The tamper evident assembly as recited in claim **28** further comprising a unidirectional drive assembly including a first drive segment disposed on said end cap and a second drive segment disposed on said tip cap; said first and second drive segments disposed in interactive engagement, said interactive engagement defining relative rotation between said end cap and said tip cap restricted to a single direction.

31. A tamper evident assembly as recited in claim **30** wherein said first and second drive segments are respectively disposed on an inner surface of said closed end of said end cap and on an inner sidewall surface of said tip cap.

* * * * *