



US011105186B2

(12) **United States Patent**  
**Rio et al.**

(10) **Patent No.:** **US 11,105,186 B2**  
(45) **Date of Patent:** **Aug. 31, 2021**

(54) **CARBON SEQUESTRATION SYSTEM AND METHOD**

(71) Applicant: **Milestone Environmental Services, LLC**, Houston, TX (US)  
(72) Inventors: **Gabriel Rio**, Houston, TX (US); **Jason Larchar**, Spring, TX (US); **Steve Bills**, Houston, TX (US)

(73) Assignee: **MILESTONE ENVIRONMENTAL SERVICES, LLC**, Houston, TX (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **17/205,665**

(22) Filed: **Mar. 18, 2021**

(65) **Prior Publication Data**

US 2021/0222521 A1 Jul. 22, 2021

**Related U.S. Application Data**

(63) Continuation-in-part of application No. 16/387,207, filed on Apr. 17, 2019, now Pat. No. 11,008,833.

(51) **Int. Cl.**  
*E21B 41/00* (2006.01)  
*E21B 49/08* (2006.01)  
*E21B 21/06* (2006.01)

(52) **U.S. Cl.**  
CPC ..... *E21B 41/0057* (2013.01); *E21B 21/065* (2013.01); *E21B 49/0875* (2020.05)

(58) **Field of Classification Search**  
CPC ..... E21B 41/0064; E21B 41/0057; E21B 21/066; E21B 21/065; E21B 43/40; E21B 43/34; E21B 43/35

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,365,858 A	12/1944	Binkley	
4,216,836 A	8/1980	Rayborn	
4,250,974 A	2/1981	Heilhecker	
5,310,285 A	5/1994	Northcott	
5,335,732 A *	8/1994	McIntyre	E21B 33/124 166/250.01
5,570,749 A	11/1996	Reed	
6,002,063 A *	12/1999	Bilak	B09B 1/00 588/17
9,518,435 B2	12/2016	Fout	
10,909,547 B1 *	2/2021	Guyer	G06Q 20/085
2006/0124524 A1	6/2006	Duhe	
2008/0237141 A1	10/2008	Kerfoot	
2010/0186767 A1	7/2010	Martin	
2011/0303622 A1	12/2011	Saik	

(Continued)


Primary Examiner — Kipp C Wallace

(74) Attorney, Agent, or Firm — MH2 Technology Law Group LLP

(57) **ABSTRACT**

A system for injecting a portion of a fluid waste into a well includes a fluid waste processor configured to receive the fluid waste and process the fluid waste for storage in the well, a primary sensor coupled to the fluid waste processor at a primary location, the primary sensor being configured to measure a fluid flow rate of the fluid waste, a hydrocarbon content of the fluid waste at or proximal to the primary location of the primary sensor being determined, and a data processor configured to determine an amount of carbon sequestered in the well based at least in part on a combination of the fluid flow rate and the hydrocarbon content.

**15 Claims, 3 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS

2012/0090325 A1\* 4/2012 Lewis ..... E21B 41/0064  
60/772  
2014/0209312 A1 7/2014 Munisteri  
2014/0371113 A1 12/2014 Fout  
2016/0053594 A1\* 2/2016 Nazarian ..... E21B 43/164  
166/263  
2018/0016875 A1 1/2018 Shokanov

\* cited by examiner





FIG. 1

FIG. 2






FIG. 3

1

## CARBON SEQUESTRATION SYSTEM AND METHOD

### CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation-in-part of U.S. patent application having Ser. No. 16/387,207, which was filed on Apr. 17, 2019 and is incorporated herein by reference in its entirety.

### BACKGROUND

When drilling a wellbore in a subterranean formation, a fluid is pumped down into the wellbore to cool the drill bit and to circulate cuttings from the subterranean formation back to the surface. This fluid with cuttings is referred to as a drilling fluid waste. The drilling fluid waste may present environmental liabilities and may be expensive to dispose of at the surface. As a result, it may be desirable to dispose of the drilling fluid waste by pumping at least a portion of the drilling fluid waste back into the subterranean formation. However, particles in the drilling fluid waste may fall out of the drilling fluid waste if the density and/or viscosity of the drilling fluid waste is not within a predetermined range. This may limit the amount of drilling fluid waste that may be pumped back into the subterranean formation.

In the drilling fluid disposal context, or in other fluid disposal contexts, the fluids may contain hydrocarbons. Hydrocarbons can be difficult to dispose of effectively and safely, and limited options exist for doing so. In some situations, these hydrocarbons (and other carbon-based products) may be sequestered in these subterranean formations, so as to prevent greenhouse gas emissions, contamination of groundwater sources, etc.

### SUMMARY

A system for sequestering carbon in a well is disclosed. The system includes a receiving pit configured to receive a fluid waste, a shaker configured to receive the fluid waste from the receiving pit and to separate solids from the fluid waste so as to produce a separated fluid waste, a mixing tank configured to receive the separated fluid waste from the shaker and to mix the separated fluid waste, a pump configured to cause the separated fluid waste to flow into the well, a primary sensor at a primary location in the system, the primary sensor being configured to measure a fluid flow rate of the separated fluid waste, a hydrocarbon content of the separated fluid waste being determined at or proximal to the primary location, and a data processor configured to determine an amount of carbon sequestered in the well based at least in part on a combination of the fluid flow rate and the hydrocarbon content.

A method for sequestering carbon in a well is disclosed. The method includes processing a fluid waste using a fluid waste processor, introducing at least a portion of the fluid waste into the well using the fluid waste processor, determining a flow rate and a hydrocarbon content of the fluid waste introduced into the well, and determining an amount of carbon sequestration in the well based at least in part on the flow rate and the hydrocarbon content.

A system for injecting a portion of a fluid waste into a well is further disclosed. The system includes a fluid waste processor configured to receive the fluid waste and process the fluid waste for storage in the well, a primary sensor coupled to the fluid waste processor at a primary location,

2

the primary sensor being configured to measure a fluid flow rate of the fluid waste, a hydrocarbon content of the fluid waste at or proximal to the primary location of the primary sensor being determined, and a data processor configured to determine an amount of carbon sequestered in the well based at least in part on a combination of the fluid flow rate and the hydrocarbon content.

### BRIEF DESCRIPTION OF THE DRAWINGS

The present disclosure may best be understood by referring to the following description and accompanying drawings that are used to illustrate embodiments of the invention. In the drawings:

FIG. 1 illustrates a schematic view of a fluid disposal injection system, according to an embodiment.

FIG. 2 illustrates a flowchart of a method for injecting a portion of a drilling fluid waste into a well, according to an embodiment.

FIG. 3 illustrates a flowchart of a method for carbon sequestration, according to an embodiment.

### DETAILED DESCRIPTION

The following disclosure describes several embodiments for implementing different features, structures, or functions of the invention. Embodiments of components, arrangements, and configurations are described below to simplify the present disclosure; however, these embodiments are provided merely as examples and are not intended to limit the scope of the invention. Additionally, the present disclosure may repeat reference characters (e.g., numerals) and/or letters in the various embodiments and across the Figures provided herein. This repetition is for the purpose of simplicity and clarity and does not in itself dictate a relationship between the various embodiments and/or configurations discussed in the Figures. Moreover, the formation of a first feature over or on a second feature in the description that follows may include embodiments in which the first and second features are formed in direct contact, and may also include embodiments in which additional features may be formed interposing the first and second features, such that the first and second features may not be in direct contact. The embodiments presented below may be combined in any combination of ways, e.g., any element from one exemplary embodiment may be used in any other exemplary embodiment, without departing from the scope of the disclosure.

Additionally, certain terms are used throughout the following description and claims to refer to particular components. As one skilled in the art will appreciate, various entities may refer to the same component by different names, and as such, the naming convention for the elements described herein is not intended to limit the scope of the invention, unless otherwise specifically defined herein. Further, the naming convention used herein is not intended to distinguish between components that differ in name but not function. Additionally, in the following discussion and in the claims, the terms “including” and “comprising” are used in an open-ended fashion, and thus should be interpreted to mean “including, but not limited to.” All numerical values in this disclosure may be exact or approximate values unless otherwise specifically stated. Accordingly, various embodiments of the disclosure may deviate from the numbers, values, and ranges disclosed herein without departing from the intended scope. Finally, unless otherwise provided herein, “or” statements are intended to be non-exclusive; for

example, the statement “A or B” should be considered to mean “A, B, or both A and B.”

FIG. 1 illustrates a schematic view of a fluid disposal injection system **100**, according to an embodiment. The system **100** may be used to treat and subsequently inject a fluid (e.g., drilling fluid) waste into a disposal well in a subterranean formation, thereby sequestering the carbon content of the fluid waste in the well. Accordingly, the system **100** may include a fluid processing system (or “fluid waste processor” or “fluid processor”) configured to receive the waste, process (e.g., separate, dilute, mix, etc.) the waste, and inject (e.g., pump) the waste into the well.

In a specific embodiment, the system **100** (e.g., the fluid processor thereof) may include a trench **102** configured to receive a drilling fluid waste from a wellbore. The drilling fluid waste may include cuttings (e.g., clay), water, hydrocarbons, chemicals introduced into the wellbore, or a combination thereof. The trench **102** may include a grate or other screening device that may be configured to allow one or more vehicles (e.g., trucks) **104** to drive over the trench **102**, enabling a pull-through arrangement in the receiving area **105**, rather than a back-in. Thus, as shown, the drilling fluid waste may be transported from the wellbore to the trench **102** via the one or more trucks **104**. In another embodiment, the drilling fluid waste may be transported from the wellbore to the trench **102** via a pipeline.

The system **100** (e.g., the fluid processor thereof) may also include a receiving pit **106** that may receive the drilling fluid waste from the trench **102**. The receiving pit **106** may include one or more weirs **108** that form a tortuous path through the receiving pit **106**, which may serve to mix the drilling fluid waste into a substantially homogeneous state. A portion of the drilling fluid waste in the receiving pit **106** may be transferred (e.g., through line **110** via pump **112**) back to the trench **102** where the drilling fluid waste may be used to create a slurry in the trench **102** to help the solids flow into the receiving pit **106** rather than accumulate in the trench **102**. Another portion of the drilling fluid waste in the receiving pit **106** may be transferred (e.g., through line **114** via pump **116**) to a shaker **118** of the fluid processor.

The shaker **118** may be or include a shale shaker, a centrifuge, a filter, a strainer basket, a sieve, or the like. The shaker **118** may filter/separate solids (e.g., particles) from the drilling fluid waste, thereby producing a removed set of solids and a separated drilling fluid waste. In some embodiments, the shaker **118** may be provided by or otherwise representative of several shakers **118** operating in parallel. The solids separated by the shaker **118** may have a maximum cross-sectional dimension that is greater than about 100 microns, greater than about 200 microns, greater than about 300 microns, greater than about 400 microns, greater than about 500 microns, or larger. The size of the solids to be removed may be determined by formation properties, anticipated pumping schedules, and/or injection modeling software. For example, formations of higher porosity (e.g., >20%) can tolerate solids particles upwards of 1,000 microns, while formations of lower porosity (e.g., <10%) can tolerate fine particles less than 100 microns. In one example, the size of the solids may be determined by analyzing the formation porosity from gamma-ray emitting tools from open-hole logs and coordinating the porosity of a disposal well with an appropriate classification size.

The removed solids output from the shaker **118** may be transferred (e.g., through line **120**) to a drying slab **122** of the fluid processor. The solids may then be ground into smaller particles sizes and introduced into the receiving pit **106**, the shaker **118**, and/or a mixing tank **128** of the fluid processor.

In another embodiment, the solids may be introduced into a centrifuge (e.g., the shaker **118**) for dewatering. In yet another embodiment, the solids may be transported to a landfill.

In at least one embodiment, at least a portion of the solids in the drilling fluid waste in the receiving pit **106** may bypass the shaker **118** and be transferred (e.g., through line **124**) to the drying slab **122**. More particularly, the solids that settle on the bottom of the receiving pit **106** may bypass the shaker **118** and be transferred to the drying slab **122**.

The separated drilling fluid waste from the shaker **118** may be transferred (e.g., through line **126**) to the mixing tank **128**. The mixing tank **128** may also be referred to as a shaker tank. The mixing tank **128** may include one or more mixers **130** that stir/mix the separated drilling fluid waste from the shaker **118** into a substantially homogeneous state. In at least one embodiment, one or more chemical additives may be added to the separated drilling fluid waste in the mixing tank **128**. Although a single mixing tank **128** is shown, in other embodiments, a plurality of mixing tanks may be utilized. One or more of the additional mixing tanks may not have associated shakers (e.g., such as shaker **118**).

In at least one embodiment, at least a portion of the separated drilling fluid waste may be transferred (e.g., via line **132**) back into the receiving pit **106** to provide overflow protection (e.g., to prevent the mixing tank **128** from overflowing) and/or provide recirculation to clean the receiving pit **106**. At least a portion of the separated drilling fluid waste may be transferred (e.g., through line **134** via one or more pumps **136**, **138** of the fluid processor) into a well **140**. The pump **136** may be or include a charge pump, and the pump **138** may be or include an injection pump. The well **140** may be or include a disposal well (also referred to as an injection well).

The system **100** (e.g., the fluid processor thereof) may also include a plurality of tanks (four are shown: **142**, **144**, **146**, **148**). Water may be introduced into the first tank **142** (e.g., through line **150** via an offload pump **152**). The water may be introduced from one or more of the trucks. The water may be fresh water, salt water, brackish water, brine, or the like. The first tank **142** may be or include a de-sanding or buffer tank that is configured to separate solids (e.g., particles) such as sand from the water to produce a first separated water. The first separated water may be transferred into the second tank **144**.

The second tank **144** may be or include a skim tank (also referred to as a gun-barrel tank) that is configured to separate oil from the first separated water to produce a second separated water. The oil may be transferred from the second tank **144** to the third tank **146**, and the second separated water may be transferred from the second tank **144** to the fourth tank **148**.

At least a portion of the second separated water may be transferred (e.g., through line **154** via pump **156**) back to the trench **102** and/or the trucks **104**. For example, the second separated water may be sprayed onto the trench **102** and/or in the trucks **104** (e.g., by one or more sprinklers, automated tank cleaners, or hoses and valves) to clean or otherwise remove buildup of the drilling fluid waste and solids. At least a portion of the second separated water may be transferred (e.g., through lines **158**, **160** via pumps **136**, **138**) to the well **140**.

The system **100** may also include one or more sensors (seven are shown: **162A-G**). The sensor **162A** may be configured to measure one or more properties of the drilling fluid waste flowing from the receiving pit **106** to the trench **102** in line **110**. The sensor **162B** may be configured to

5

measure one or more properties of the drilling fluid waste flowing from the receiving pit 106 to the shaker 118 in line 114. The sensor 162C may be configured to measure one or more properties of the separated drilling fluid waste flowing from the shaker 118 to the mixing tank 128 in line 126. The sensor 162D may be configured to measure one or more properties of the separated drilling fluid waste flowing from the mixing tank 128 to the well 140 in line 134. The sensor 162E may be configured to measure one or more properties of the second separated water flowing from the fourth tank 148 to the well 140 in line 158. The sensor 162F and sensor 162G may be configured to measure one or more properties of the separated drilling fluid waste, the second separated water, or a combination/mixture thereof flowing to the well 140 in line 160. The properties may be or include flowrate, viscosity, density, pH level, percentage of solids, size of solids, pressure, temperature, or a combination thereof. A flowrate of the separated drilling fluid waste in line 134 and/or the second separated water in line 158 may be modified to obtain the desired ratio of the mixture for injection into the well 140. The ratio of the separated drilling fluid waste to the second separated water may be from about 10:1 to about 5:1, about 5:1 to about 3:1, about 3:1 to about 1:1, about 1:1 to about 1:3, about 1:3 to about 1:5, or about 1:5 to about 1:10. In another embodiment, the separated drilling fluid waste may be pumped into the well 140 before and/or after the second separated water, such that the separated drilling fluid waste and the second separated water are not combined/mixed prior to being pumped in to the well 140.

In some embodiments, the sensors 162D, 162E, and 162G may directly measure a composition (e.g., hydrocarbon content) of the fluid flowing in the respective, illustrated positions. In other embodiments, the fluid flowing at the respective positions may be sampled for further analysis at a different part of the site, or taken to a separate location (e.g., a laboratory) for analysis. As such, any one or more of the sensors 162D, 162E, and 162G may be omitted, or may be included to determine certain aspects, such as flow rate, in addition to providing sample locations for determining other characteristics.

Thus, a flowrate and composition of fluid at the locations of the sensors 162D, 162E, 162G may be measured, for example, with the fluid flowrate being metered continuously and the composition being measured continuously and/or determined at intervals by taking a sample and analyzing the sample. Specifically, the separated drilling fluid waste in line 134 may be measured at sensor 162D. The water may be measured at sensor 162E (e.g., after being processed in the tanks 142-148), and the combination of water and separated drilling fluid waste may be measured at 162G. In some embodiments, the composition may only be established at the location of the sensor 162G, which may be considered a "primary" sampling location. The sensor 162G may also be referred to as a "first" or "primary" sensor, although this should not be considered as contemplating a relative importance of the sensors or precluding embodiments with other sensors, e.g., sensors 162D and 162E (which may be referred to as "second" and "third" sensors). In other embodiments, the composition may be measured at the sensor 162D and at the sensor 162E in order to establish a source of the components that make up the composition measured at the sensor 162G.

The fluid sampled in the respective lines may be analyzed for hydrocarbon content (and/or certain other carbon-based content) in particular. Measuring the hydrocarbon content, in combination with a measurement of the amount of fluid

6

injected into the disposal wells 140, may provide data related to the amount of carbon that is sequestered in the disposal wells 140 by the system 100. For example, the system 100 may include a data processor 170, which may be any type of computing device, that receives the measurement data and determines the carbon sequestered in the well, e.g., during a given time (e.g., a day, an amount of time required to process a load from a truck 104, etc.).

The wells 140 may provide a convenient location for such carbon sequestration, as the wells 140 may extend below the water line, which may reduce the risk of hydrocarbons contaminating ground water. Further, once in the well 140, the hydrocarbons may not be exposed to the ambient, surface atmosphere, which may prevent greenhouse gases from being released into the environment.

Regulatory agencies may provide credits for carbon sequestration but may require records of the amount of carbon sequestered. Accordingly, measuring the hydrocarbon present, and the flowrate of the waste fluid at sensor 162G may provide measurements from which such carbon sequestration amounts can be calculated (e.g., by the data processor 170) in the well over a certain amount of time, thereby establishing basis for the carbon sequestration credits. Further, the amount of carbon being sequestered from the drilling fluid waste (e.g., received from the trucks 104) may be determined, e.g., by the data processor 170, based on the composition measurement taken at the sensor 162D, and the amount of carbon being sequestered from the water may be determined by the data processor 170 based on the composition measurement taken at the sensor 162G. In some embodiments, this may permit transfer of hydrocarbon credits to a particular customer that is responsible for bringing the drilling fluid waste to the system 100.

FIG. 2 illustrates a flowchart of a method 200 for carbon sequestration, e.g., by injecting a portion of a drilling fluid waste into the well 140, according to an embodiment. The method 200 may include introducing the drilling fluid waste into the trench, as at 202. The method 200 may also include transferring the drilling fluid waste from the trench into the receiving pit 106, as at 204. The method 200 may also optionally include transferring at least a portion of the drilling fluid waste from the receiving pit 106 back to the trench, as at 206. The method 200 may also or instead include transferring at least a portion of the drilling fluid waste from the receiving pit 106 to the shaker 118, as at 208. The method 200 may also or instead optionally include transferring at least a portion of the solids in the drilling fluid waste in the receiving pit 106 to the drying slab 122, as at 209.

The method 200 may also include separating solids from the drilling fluid waste (e.g., using the shaker 118) to produce solids and a separated drilling fluid waste, as at 210. The method 200 may also include transferring the solids to the drying slab 122, as at 212. The method 200 may also include transferring the separated drilling fluid waste from the shaker 118 to the mixing tank 128, as at 214. The method 200 may also optionally include transferring at least a portion of the separated drilling fluid waste from the mixing tank 128 back to the receiving pit 106, as at 216.

The method 200 may also include introducing water into the first tank 142, as at 218. The method 200 may also include separating, in the first tank 142, solids from the water to produce a first separated water, as at 220. The method 200 may also include transferring the first separated water into the second tank 144, as at 222. The method 200 may also include separating, in the second tank 144, oil from the first separated water to produce oil and a second sepa-



rated water, as at 224. The method 200 may also include transferring the oil from the second tank 144 to the third tank 146, as at 226. The method 200 may also include transferring the second separated water from the second tank 144 to the fourth tank 148, as at 228.

The method 200 may also optionally include transferring at least a portion of the second separated water from the fourth tank 148 back to the trench 102 and/or the trucks 104, as at 230. As mentioned above, the second separated water may be used to clean/wash the trench 102 and/or the trucks 104. The method 200 may also include combining and/or mixing the separated drilling fluid waste from the mixing tank 128 (in line 134) and the second separated water from the fourth tank 148 (in line 158) to form a mixture in line 160, as at 232. The method 200 may also include pumping the mixture in line 160 into the well 140 (e.g., using the pump(s) 136, 138), as at 234. One or more of the pumps 136, 138 may facilitate the mixing.

In another embodiment, the separated drilling fluid waste and the second separated water may not be combined/mixed prior to being pumped in to the well 140. Rather, they may be pumped separately into the well 140. For example, the separated drilling fluid waste may be pumped into the well 140 before the second separated water. In another example, the second separated water may be pumped into the well 140 before the separated drilling fluid waste. In yet another example, the order in which the separated drilling fluid waste and the second separated water are pumped into the well 140 may alternate (e.g., separated drilling fluid waste, second separated water, separated drilling fluid waste, second separated water, etc.).

The method 200 may also include measuring one or more properties of the drilling fluid waste, the water, and/or the mixture using the sensors 162A-G, as at 236. The method 200 may also include varying one or more of the properties of the water, the drilling fluid waste, and/or the mixture in response to the measurement(s), as at 238. In one example, the sensor 162D may measure a flow rate of the separated drilling fluid waste, and the sensor 162E may measure a flow rate of the second separated water. In response to these measurements, one or both flow rates may be varied to cause a ratio of the mixture to be within a predetermined range. The predetermined range may depend at least partially upon the drilling fluid waste received, the formation, and the conditions in and/or around the well 140. The flow rate(s) may be varied using one or more valves, pumps, or both.

In one example, the sensor 162D may obtain a measurement of the density and/or viscosity of the separated drilling fluid waste. In another example, the sensor 162F may obtain a measurement of the density and/or viscosity of the separated drilling fluid waste, the second separated water, or a combination/mixture thereof. In either of the foregoing examples, if the measurement is outside of a predetermined range, one or more additives may be added to change the measured property. The additives may be or include viscosifiers, barite, polymer, water, or a combination thereof. Alternatively, the amount/flow rate of the separated drilling fluid waste and/or the second separated water may be varied to change the measured property. In another embodiment, no blending, additives, or modifications are made to the separated drilling fluid waste.

The properties of the separated drilling fluid waste, the second separated water, and/or the combination/mixture may depend at least partially on the subterranean formation surrounding the well 140. For example, to carry particles deep within the formation, the viscosity may be sufficient to prevent premature settling. In the system 100, the viscosity

may be increased with barite or polymer additives using a series of viscometers and one or more polymer feed pumps with variable frequency drives.

To assist in achieving proper bottom-hole pressure (i.e., the primary force that induces flowrate through, and fracturing of, the subterranean formation), the density of the slurry may be maintained or modified to be sufficient to increase the hydrostatic pressure inside of the fluid column of the well 140. In the system 100, the density may be controlled by adding barite automatically with a barite feed auger in response to measurements from one or more of the sensors 162A-F (e.g., densitometers). In another embodiment, the separated drilling fluid waste, the second separated water, and/or the combination/mixture thereof may be manually weighed, and sacks of barite may be introduced in response to the weight.

The injection rate of the separated drilling fluid waste, the second separated water, and/or the combination/mixture into the well 140 may be set so as to provide a predetermined surface pressure and may, in some implementations, propagate fracture growth in the subterranean formation of the well 140. The injection rate may be controlled with the injection pump 138 automatically through the sensor 162F, which may include a pressure sensor, a flow meter, a densitometer, or a combination thereof. In another embodiment, the injection rate may be controlled manually by adjusting a variable frequency drive of the injection pump 138.

In another embodiment, the pump rate and/or the properties of the separated drilling fluid waste, the second separated water, and/or the combination/mixture may be adjusted based at least partially upon the response of the subterranean formation, the pressure in the well 140, or both. When the injection process is nearing completion, the well 140 may be flushed with water to clean the well 140 and push the particles into the formation. For example, when the injection of the separated drilling fluid waste is nearing completion, the second separated water may then be pumped into the well 140 to clean the well 140 and push the particles from the separated drilling fluid waste into the formation.

FIG. 3 illustrates a flowchart of a method 300 for sequestering carbon in a well, according to an embodiment. In some embodiments, the method 300 may incorporate aspects of the method 200 and may employ the system 100. The method 300 may include receiving (e.g., drilling) fluid waste in a receiving pit via a trench, as at 302, e.g., using the trench system discussed above. Solids may be separated from the drilling fluid waste, as at 304, e.g., as discussed above with reference to blocks 204-216 in FIG. 2. The method 300 may also include receiving a water (e.g., salt water) in a tank or another water source, as at 306. The water may go through one or more processing/separation stages before reaching and/or after leaving the tank, as discussed above with reference to blocks 218-230.

The method 300 may then include measuring or otherwise determining a flowrate and composition (e.g., hydrocarbon content) of the drilling fluid waste, as at 308. In some embodiments, the flowrate may be measured using a flowmeter or another sensor and may be employed to determine a flow rate (e.g., mass or volumetric) over a certain amount of time. The composition of the drilling fluid waste may be determined from an analysis of a sample of the drilling fluid waste taken downstream from where the solids are separated therefrom, as discussed above. In particular, the composition may indicate the hydrocarbon and/or other carbon content of the drilling fluid waste in the sample.

The method **300** may also include measuring a flowrate and composition of the water, as at **310**. The flowrate of the water may be measured using a flowmeter or another sensor and may be employed to determine a mass flow over a certain amount of time. Further, the composition may be determined from a sample of the water taken downstream from where the water treatment stages of the system **100** are located, and upstream of where the water is combined with the separated drilling fluid waste. In particular, a hydrocarbon and/or other carbon content of the water may be determined from the sample.

In some embodiments, the water and the drilling fluid waste may be combined to form a mixture, as at **312** (also discussed above with reference to block **232**). The flowrate and composition of the mixture may be measured (e.g., downstream from their mixing), as at **314**, similar to the measuring of the individual separated drilling fluid waste and the water, upstream of their mixing. In particular, the flowrate may be determined using a flowmeter and employed to determine a mass or volumetric flow over a certain period of time. The composition, specifically the hydrocarbon content, may be determined in a laboratory from a sample of the mixture, or using a sensor in the system **100**.

In some embodiments the water and fluid waste may be introduced into the well, as at **316**, e.g., to sequester the carbon contained therein permanently. This may proceed by pumping the mixture of water and fluid waste into the well **140**, or by pumping the fluid waste and the water separately.

Before, during, or after the actual introduction of the water and fluid waste in the well at **316**, the method **300** may include determining an amount of carbon that is/was injected and thus sequestered in the well(s) **140** based on the measurements taken and/or determinations made, as at **318**. For example, the flowrate and the hydrocarbon content of the mixture of the drilling fluid waste and the water may be employed to determine an amount of hydrocarbon that was injected into the wells **140** during a certain time period (e.g., during a day). In other embodiments, the combination of the flowrate and hydrocarbon content of the individual water and separated drilling fluid waste components of the mixture may be employed to determine the total hydrocarbon/other carbon content that was injected. In some embodiments, the hydrocarbon/other carbon content that was injected may be determined at specific intervals, and the composition may be assumed to be generally constant between the measurements.

The flowrate measurements discussed above may, in some cases, be acquired in real-time during the injection process; however, in at least some embodiments, the composition may be determined later, e.g., after transporting the sample to a laboratory or another location with suitable equipment. Thus, the flow rate may be recorded over a period of time and associated with the sample taken during that period of time, with it being assumed that the composition remained generally constant during the duration. Thus, the hydrocarbon/other carbon content may be calculated for the duration, but this calculation may take place after the measured water and waste have already been injected. In other embodiments, the hydrocarbon content may be established when a new truck **104** arrives, or in response to any other suitable factor. In still other embodiments, the composition of one of the fluids discussed above may be measured continuously (e.g., using sensors, rather than sampling), such that assumptions related to composition may be avoided.

As used herein, the terms “inner” and “outer”; “up” and “down”; “upper” and “lower”; “upward” and “downward”;

“above” and “below”; “inward” and “outward”; “uphole” and “downhole”; and other like terms as used herein refer to relative positions to one another and are not intended to denote a particular direction or spatial orientation. The terms “couple,” “coupled,” “connect,” “connection,” “connected,” “in connection with,” and “connecting” refer to “in direct connection with” or “in connection with via one or more intermediate elements or members.”

The foregoing has outlined features of several embodiments so that those skilled in the art may better understand the present disclosure. Those skilled in the art should appreciate that they may readily use the present disclosure as a basis for designing or modifying other processes and structures for carrying out the same purposes and/or achieving the same advantages of the embodiments introduced herein. Those skilled in the art should also realize that such equivalent constructions do not depart from the spirit and scope of the present disclosure, and that they may make various changes, substitutions, and alterations herein without departing from the spirit and scope of the present disclosure.

What is claimed is:

1. A system for sequestering carbon in a well, comprising:
  - a receiving pit configured to receive a fluid waste;
  - a shaker configured to receive the fluid waste from the receiving pit and to separate solids from the fluid waste so as to produce a separated fluid waste;
  - a mixing tank configured to receive the separated fluid waste from the shaker and to mix the separated fluid waste;
  - a pump configured to cause the separated fluid waste to flow into the well;
  - a primary sensor at a primary location in the system, the primary sensor being configured to measure a fluid flow rate of the separated fluid waste, wherein a hydrocarbon content of the separated fluid waste is determined at or proximal to the primary location;
  - a data processor configured to determine an amount of carbon sequestered in the well based at least in part on a combination of the fluid flow rate and the hydrocarbon content;
  - a water source configured to provide water for injection into the well, wherein the primary sensor is configured to measure a flowrate of the water in combination with the flowrate of the separated fluid waste at the primary location, wherein a hydrocarbon content of the water at the primary location is determined, and wherein the data processor is configured to determine the amount of carbon sequestered in the well based at least in part on the fluid flow rate of the water and the hydrocarbon content of the water; and
  - a second sensor at a second location, the second sensor configured to measure a fluid flow rate of the separated fluid waste but not a fluid flow rate of the water, wherein a hydrocarbon content of the separated fluid waste at the second location or proximal thereto is determined.
2. The system of claim **1**, further comprising a trench configured to receive the fluid waste from a pipeline or a truck, wherein the receiving pit is configured to receive the fluid waste from the trench.
3. The system of claim **1**, further comprising a third sensor at a third location, the third sensor configured to measure a fluid flow rate of the water but not the fluid flow rate of the separated fluid waste, wherein a hydrocarbon content of the water at the third location is determined.

## 11

4. The system of claim 1, further comprising:  
 a first tank configured to receive water and to separate solids from the water to produce a first separated water;  
 a second tank configured to receive the first separated water and to separate oil from the first separated water to produce a second separated water;  
 a third tank configured to receive the oil from the second tank; and  
 a fourth tank configured to receive the second separated water from the second tank, wherein the pump is configured to cause the second separated water to flow into the well.

5. The system of claim 4, further comprising a trench that receives the fluid waste and feeds the fluid waste to the receiving pit, wherein a portion of the second separated water is transferred from the fourth tank to the trench.

6. The system of claim 4, further comprising:  
 a second sensor configured to measure a first property of the separated fluid waste flowing from the mixing tank to the well; and  
 a third sensor configured to measure a second property of the water flowing from the fourth tank to the well, wherein the first property, the second property, or both comprises flowrate, density, viscosity, or a combination thereof.

7. The system of claim 1, wherein the fluid waste comprises a drilling fluid waste including drilling mud.

8. The system of claim 1, wherein the primary sensor is not configured to measure the hydrocarbon content, and wherein the data processor is configured to determine the amount of carbon sequestered based on a fluid sample taken during a time interval during which the hydrocarbon content is assumed to be generally constant.

9. A system for sequestering carbon in a well, comprising:  
 a receiving pit configured to receive a fluid waste;  
 a shaker configured to receive the fluid waste from the receiving pit and to separate solids from the fluid waste so as to produce a separated fluid waste;  
 a mixing tank configured to receive the separated fluid waste from the shaker and to mix the separated fluid waste;  
 a pump configured to cause the separated fluid waste to flow into the well;  
 a primary sensor at a primary location in the system, the primary sensor being configured to measure a fluid flow rate of the separated fluid waste, wherein a hydrocarbon content of the separated fluid waste is determined at or proximal to the primary location; and  
 a data processor configured to determine an amount of carbon sequestered in the well based at least in part on a combination of the fluid flow rate and the hydrocarbon content,

wherein at least a portion of the separated fluid waste is transferred from the mixing tank back into the receiving pit.

10. A method for sequestering carbon in a well, comprising:

processing a fluid waste using a fluid waste processor, wherein processing the fluid waste comprises;  
 transferring the fluid waste from a trench into a receiving pit and then into a shaker;  
 separating solids from the fluid waste, using the shaker, to produce a separated fluid waste; and

## 12

transferring the separated fluid waste from the shaker into a mixing tank;  
 introducing at least a portion of the separated fluid waste into the well using the fluid waste processor;  
 transferring a portion of the separated fluid waste from the receiving pit back to the trench;  
 transferring a portion of the separated fluid waste from the mixing tank to the receiving pit;  
 determining a flow rate and a hydrocarbon content of the separated fluid waste introduced into the well; and  
 determining an amount of carbon sequestration in the well based at least in part on the flow rate and the hydrocarbon content.

11. The method of claim 10, wherein determining the hydrocarbon content comprises:

taking a sample of the separated fluid waste; and  
 analyzing the sample during or after introducing the separated fluid waste into the well.

12. The method of claim 10, further comprising:  
 introducing water into the well in combination with the separated fluid or after the separated fluid waste is introduced into the well; and  
 determining a flow rate and a hydrocarbon content of the water introduced into the well,  
 wherein determining the amount of carbon sequestration is also based at least in part on the flow rate of the water and the hydrocarbon content of the water.

13. The method of claim 12, further comprising determining the flow rate and hydrocarbon content of the water upstream of the water mixing with the separated fluid waste.

14. The method of claim 10, wherein the fluid waste comprises drilling mud.

15. A method for sequestering carbon in a well, comprising:

processing a fluid waste using a fluid waste processor, wherein processing the fluid waste comprises:  
 transferring the fluid waste from a trench into a receiving pit and then into a shaker;  
 separating solids from the fluid waste, using the shaker, to produce a separated fluid waste; and  
 transferring the separated fluid waste from the shaker into a mixing tank;

introducing at least a portion of the separated fluid waste into the well using the fluid waste processor;  
 determining a flow rate and a hydrocarbon content of the separated fluid waste introduced into the well;  
 introducing water into the well in combination with the separated fluid waste;  
 determining a flow rate and a hydrocarbon content of the water introduced into the well,  
 mixing the water and the separated fluid waste upstream of the well;

measuring a flow rate and a hydrocarbon content of the separated fluid waste upstream of the separated fluid waste mixing with the water; and  
 determining an amount of carbon sequestration in the well based at least in part on:  
 the flow rate of the water;  
 the hydrocarbon content of the water; and  
 the flow rate of and hydrocarbon content of the separated fluid waste upstream of the separated fluid waste being mixed with the water.