

Related U.S. Application Data					
(60)	Provisional application No. 62/343,798, filed on May 31, 2016, provisional application No. 62/342,174, filed on May 26, 2016.		2007/0009859 A1	1/2007	Preston et al.
			2007/0099578 A1	5/2007	Adeney et al.
			2008/0130764 A1	6/2008	Xia et al.
			2008/0170523 A1	7/2008	Han et al.
			2008/0276821 A1	11/2008	Stancil
			2008/0300055 A1	12/2008	Lutnick et al.
			2009/0023401 A1	1/2009	Grandhi et al.
			2009/0053678 A1	2/2009	Falkenhayn et al.
(51)	Int. Cl.		2009/0196203 A1 *	8/2009	Taira H04B 7/0617
	H04B 7/06 (2006.01)				370/280
	H01Q 1/24 (2006.01)				
	H04B 7/0404 (2017.01)		2009/0217836 A1	9/2009	Dietrich et al.
	H04W 16/28 (2009.01)		2010/0054200 A1	3/2010	Tsai
	H04W 28/02 (2009.01)		2010/0093270 A1	4/2010	Bass
	H04W 40/08 (2009.01)		2010/0147177 A1	6/2010	Van Stratum
	H04W 52/04 (2009.01)		2010/0208633 A1 *	8/2010	Takano H04B 7/0617
	H04W 88/14 (2009.01)				370/310
(52)	U.S. Cl.		2010/0232311 A1	9/2010	Zhang et al.
	CPC H04B 7/0617 (2013.01); H04B 7/0623 (2013.01); H04B 7/0695 (2013.01); H04W 16/28 (2013.01); H04W 28/0221 (2013.01); H04W 40/08 (2013.01); H04W 52/04 (2013.01); H04W 88/14 (2013.01)		2011/0134850 A1 *	6/2011	Kishigami H04L 5/0053
					370/328
			2011/0174922 A1	7/2011	Berman et al.
			2011/0243075 A1	10/2011	Luo et al.
			2011/0305161 A1	12/2011	Ekpenyong et al.
			2012/0211589 A1	8/2012	Uzman
			2012/0286951 A1	11/2012	Hess et al.
			2013/0039345 A1	2/2013	Kim et al.
			2013/0040682 A1	2/2013	Chang et al.
(56)	References Cited		2013/0072243 A1 *	3/2013	Yu H04B 7/0665
					455/509
	U.S. PATENT DOCUMENTS		2013/0083774 A1	4/2013	Son et al.
	5,050,501 A	9/1991	Barditch et al.		
	5,198,612 A	3/1993	Myers		
	5,621,752 A	4/1997	Antonio et al.		
	5,813,278 A	9/1998	Schabdach et al.		
	6,037,899 A	3/2000	Weber		
	6,766,950 B2	7/2004	Hall		
	6,903,676 B1	6/2005	Fraday et al.		
	6,923,404 B1	8/2005	Liu et al.		
	7,146,170 B2	12/2006	Davidson		
	7,310,537 B2	12/2007	Wichman et al.		
	7,400,606 B2	7/2008	Padovani et al.		
	7,450,805 B2	11/2008	Park et al.		
	7,478,595 B1	1/2009	Herr et al.		
	7,645,643 B2	1/2010	Hiramoto		
	8,055,303 B2	11/2011	Wild		
	8,220,392 B1	7/2012	Maldonado et al.		
	8,315,657 B2	11/2012	Van Rensburg et al.		
	8,477,634 B2	7/2013	Yi et al.		
	8,515,409 B2	8/2013	Ramo et al.		
	8,600,441 B2	12/2013	Xu et al.		
	8,750,933 B2	6/2014	Song et al.		
	8,885,569 B2	11/2014	Dinan		
	8,913,582 B1	12/2014	Zhang et al.		
	8,923,218 B2	12/2014	Luo et al.		
	8,923,785 B2	12/2014	Howard et al.		
	8,939,056 B1	1/2015	Neal, III et al.		
	9,078,268 B2	7/2015	Jung		
	9,203,497 B2	12/2015	Kim et al.		
	9,234,728 B2	1/2016	Akcasu et al.		
	9,306,646 B2	4/2016	Park et al.		
	9,456,359 B2	9/2016	Kim et al.		
	9,473,269 B2	10/2016	Walton et al.		
	9,497,002 B2	11/2016	Wei et al.		
	9,500,454 B1	11/2016	Decker et al.		
	9,527,596 B1	12/2016	Adams		
	9,698,884 B2	7/2017	Guey et al.		
	9,705,581 B2	7/2017	Guey et al.		
	9,738,383 B2	8/2017	Adams		
	9,823,070 B2	11/2017	Stephens, Jr.		
	10,027,397 B2	7/2018	Kim		
	10,181,891 B2	1/2019	Islam et al.		
	10,425,138 B2	9/2019	Islam et al.		
	2003/0228865 A1 *	12/2003	Terry H04W 72/005		
					455/422.1
	2004/0204111 A1	10/2004	Ylitalo		
	2005/0051667 A1	3/2005	Arlton et al.		
	2005/0096090 A1	5/2005	Nagaraj		
	2005/0136980 A1	6/2005	Kim et al.		
	2006/0030364 A1	2/2006	Olesen et al.		
			2013/0083774 A1	4/2013	Son et al.
			2013/0091401 A1	4/2013	Pan
			2013/0121185 A1	5/2013	Li et al.
			2013/0155847 A1	6/2013	Li et al.
			2013/0223251 A1 *	8/2013	Li H04B 7/0619
					370/252
			2013/0229307 A1	9/2013	Chang et al.
			2013/0265866 A1	10/2013	Yi et al.
			2013/0286960 A1	10/2013	Li et al.
			2013/0301454 A1	11/2013	Seol et al.
			2013/0301567 A1	11/2013	Jeong et al.
			2014/0010178 A1	1/2014	Yu et al.
			2014/0120926 A1 *	5/2014	Shin H04W 56/00
					455/450
			2014/0163664 A1	6/2014	Goldsmith
			2014/0177607 A1	6/2014	Li et al.
			2014/0192917 A1 *	7/2014	Nam H04L 5/0023
					375/267
			2014/0233516 A1 *	8/2014	Chun H04W 74/0833
					370/329
			2014/0254515 A1	9/2014	Kim et al.
			2014/0284422 A1	9/2014	Sapir
			2014/0323143 A1	10/2014	Jung et al.
			2014/0328266 A1	11/2014	Yu et al.
			2014/0341048 A1	11/2014	Sajadieh et al.
			2014/0341310 A1	11/2014	Rahman et al.
			2014/0376466 A1	12/2014	Jeong et al.
			2015/0009951 A1	1/2015	Josiam et al.
			2015/0023677 A1	1/2015	Kanehara
			2015/0043673 A1	2/2015	Lee et al.
			2015/0049824 A1	2/2015	Kim et al.
			2015/0063488 A1	3/2015	Dinan
			2015/0124738 A1	5/2015	Ramakrishna et al.
			2015/0128823 A1	5/2015	Akcasu et al.
			2015/0139001 A1	5/2015	Xue et al.
			2015/0208443 A1	7/2015	Jung et al.
			2015/0230263 A1	8/2015	Roy et al.
			2015/0236774 A1	8/2015	Son et al.
			2015/0289147 A1	10/2015	Lou et al.
			2016/0011318 A1	1/2016	Cohen
			2016/0080064 A1	3/2016	Kim et al.
			2016/0087765 A1	3/2016	Guey et al.
			2016/0091285 A1	3/2016	Mason
			2016/0134352 A1	5/2016	Stirling-Gallacher
			2016/0142189 A1	5/2016	Shin et al.
			2016/0150435 A1	5/2016	Baek et al.
			2016/0183234 A1	6/2016	Sung et al.
			2016/0190707 A1	6/2016	Park et al.
			2016/0191137 A1	6/2016	Song et al.
			2016/0192401 A1	6/2016	Park et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2016/0236638 A1 8/2016 Lavie et al.
2016/0277091 A1 9/2016 Kim et al.
2016/0338033 A1* 11/2016 Xiao H04W 28/18
2017/0069214 A1 3/2017 Dupray et al.
2017/0086195 A1 3/2017 Yum et al.
2017/0111886 A1 4/2017 Kim et al.
2017/0146324 A1 5/2017 McFadyen
2017/0195998 A1 7/2017 Zhang et al.
2017/0202029 A1 7/2017 Qi et al.
2017/0215117 A1 7/2017 Kwon et al.
2017/0302355 A1 10/2017 Islam et al.
2017/0302414 A1 10/2017 Islam et al.
2017/0324459 A1 11/2017 Koskela et al.
2017/0331577 A1 11/2017 Parkvall et al.
2017/0346534 A1* 11/2017 Islam H01Q 1/245
2017/0346535 A1 11/2017 Islam et al.
2017/0346543 A1 11/2017 Islam et al.
2017/0346544 A1 11/2017 Islam et al.
2018/0027522 A1 1/2018 Lee et al.
2018/0097547 A1 4/2018 Turtinen et al.
2018/0132217 A1 5/2018 Stirling-Gallacher
2018/0167883 A1* 6/2018 Guo H04W 72/046
2018/0183507 A1 6/2018 Franz et al.
2018/0198499 A1 7/2018 Park et al.
2018/0206132 A1 7/2018 Guo et al.
2018/0219603 A1 8/2018 Park et al.
2018/0279218 A1 9/2018 Park et al.
2018/0279239 A1 9/2018 Si et al.
2018/0279297 A1 9/2018 Nogami et al.
2018/0302889 A1* 10/2018 Guo H04B 7/0617
2018/0351624 A1 12/2018 Hakola et al.
2019/0115967 A1 4/2019 Islam et al.
2019/0319682 A1 10/2019 Zhang et al.
2020/0052742 A1* 2/2020 Islam H04B 7/0623
2020/0106513 A1 4/2020 Islam et al.
2020/0389224 A1 12/2020 Islam et al.

FOREIGN PATENT DOCUMENTS


CN 103765794 A 4/2014
CN 104025469 A 9/2014
CN 104303477 A 1/2015
CN 104412519 A 3/2015
CN 104521155 A 4/2015
CN 104641716 A 5/2015
CN 104660311 A 5/2015
CN 104885499 A 9/2015
CN 105009626 A 10/2015
CN 105122662 A 12/2015
CN 105264788 A 1/2016
CN 105474556 A 4/2016





CN 105556869 A 5/2016
EP 2774282 A1 9/2014
EP 2882110 A1 6/2015
EP 2887558 A1 6/2015
JP 2014524705 A 9/2014
JP 2015530018 A 10/2015
KR 20150101750 A 9/2015
WO 9600466 A1 1/1996
WO 2005114868 A1 12/2005
WO WO-2010148132 12/2010
WO WO-2011053993 5/2011
WO 2015109153 A1 7/2015
WO 2015141072 A1 9/2015
WO 2016044991 A1 3/2016
WO 2016044994 A1 3/2016
WO 2016115711 A1 7/2016
WO 2016179804 A1 11/2016

OTHER PUBLICATIONS

International Search Report and Written Opinion—PCT/US2017/027992—ISA/EPO—dated Sep. 20, 2017.
Jeong C., et al., “Random Access in Millimeter-Wave Beamforming Cellular Networks: Issues and Approaches”, Millimeter-Wave Communications for 5G IEEE Communications Magazine, IEEE Service Center, Piscataway, US, vol. 53, No. 1, Jan. 1, 2015, pp. 180-185, XP011570628, ISSN: 0163-6804, DOI: 10.1109/MCOM.2015.7010532 [retrieved on Jan. 14, 2015].
Huawei et al., “UL SRS Design for CSI Acquisition and Beam Management”, 3GPP TSG RAN WG1 Meeting #88bis, 3GPP Draft; R1-1704241, Spokane, USA Apr. 3-7, 2017, 16 Pages.
ZTE et al., “Beam Management for DL Control Channel”, 3GPP TSG RAN WG1 NR Ad-Hoc Meeting, 3GPP Draft; R1-1700131, Spokane, USA, Jan. 16-20, 2017, pp. 1-6.
“3rd Generation Partnership Project, Technical Specification Group Radio Access Network, Evolved Universal Terrestrial Radio Access (E-UTRA), Physical layer procedures (Release 13)”, 3GPP Standard, 3gpp TS 36.213, 3rd Generation Partnership Project (3gpp), Mobile Competence Centre, 650, Route Des Lucioles, F-96921, Sophia-Antipolis, Cedex, France, vol. RAN WG1, No. V13.0.0, Jan. 5, 2016, XP051047450, pp. 7-224.
Qualcomm Incorporated: “CSI Feedback Performance Requirements for EB/FD-MIMO”, 3GPP Draft, 3GPP TSG-RAN WG4 #78, R4-160044, Malta, Feb. 15-19, 2016, pp. 1-10.
CATT: “Standard Enhancement to CSI-RS Beamforming”, R1-151366, 3GPP TSG RAN WG1 Meeting #80bis, Belgrade, Serbia, Apr. 20-24, 2015, Apr. 24, 2015, 3 Pages.
CATT: “Text Proposal on EIRP Accuracy Requirements”, 3GPP TSG-RAN WG4 Meeting #72bis, R4-145627, Oct. 6-10, 2014, 4 pages.

* cited by examiner








FIG. 3




FIG. 4B




FIG. 4A

500




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D




FIG. 5E




FIG. 5G




FIG. 5F




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10







FIG. 11

**FIG. 12**

**FIG. 13**

**FIG. 14**




FIG. 15




FIG. 16




FIG. 17

1800




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32

1

**SYSTEM AND METHOD FOR BEAM
SWITCHING AND REPORTING****CROSS-REFERENCE TO RELATED
APPLICATION(S)**

This Application is a Continuation of U.S. application Ser. No. 15/488,394, entitled "SYSTEM AND METHOD FOR BEAM SWITCHING AND REPORTING" and filed on Apr. 14, 2017, which claims the benefit of U.S. Provisional Application Ser. No. 62/342,174, entitled "BEAM MODIFICATION/SWITCHING PROCEDURES, BEAM STATE INFORMATION REPORTING PROCEDURES, AND BEAM STATE INFORMATION REPORTING DURING RANDOM ACCESS" and filed on May 26, 2016, and U.S. Provisional Application Ser. No. 62/343,798, entitled "BEAM MODIFICATION/SWITCHING PROCEDURES, BEAM STATE INFORMATION REPORTING PROCEDURES, AND BEAM STATE INFORMATION REPORTING DURING RANDOM ACCESS" and filed on May 31, 2016. The disclosures of the aforementioned applications are expressly incorporated by reference herein in their entireties.

BACKGROUND**Field**

The present disclosure relates generally to communication systems, and more particularly, to a user equipment and a base station that may communicate through one of more beams.

Background

Wireless communication systems are widely deployed to provide various telecommunication services such as telephony, video, data, messaging, and broadcasts. Typical wireless communication systems may employ multiple-access technologies capable of supporting communication with multiple users by sharing available system resources. Examples of such multiple-access technologies include code division multiple access (CDMA) systems, time division multiple access (TDMA) systems, frequency division multiple access (FDMA) systems, orthogonal frequency division multiple access (OFDMA) systems, single-carrier frequency division multiple access (SC-FDMA) systems, and time division synchronous code division multiple access (TD-SCDMA) systems.

These multiple access technologies have been adopted in various telecommunication standards to provide a common protocol that enables different wireless devices to communicate on a municipal, national, regional, and even global level. An example telecommunication standard is Long Term Evolution (LTE). LTE is a set of enhancements to the Universal Mobile Telecommunications System (UMTS) mobile standard promulgated by Third Generation Partnership Project (3GPP). LTE is designed to support mobile broadband access through improved spectral efficiency, lowered costs, and improved services using OFDMA on the downlink, SC-FDMA on the uplink, and multiple-input multiple-output (MIMO) antenna technology. However, as the demand for mobile broadband access continues to increase, there exists a need for further improvements in LTE technology. These improvements may also be applicable to other multi-access technologies and the telecommunication standards that employ these technologies.

2

An example of an improvement to LTE may include fifth generation wireless systems and mobile networks (5G). 5G is a telecommunications standard that may extend beyond LTE and/or 4G standards. For example, 5G may offer higher capacity and, therefore, serve a larger number of users in an area. Further, 5G may improve data consumption and data rates.

SUMMARY

The following presents a simplified summary of one or more aspects in order to provide a basic understanding of such aspects. This summary is not an extensive overview of all contemplated aspects, and is intended to neither identify key or critical elements of all aspects nor delineate the scope of any or all aspects. Its sole purpose is to present some concepts of one or more aspects in a simplified form as a prelude to the more detailed description that is presented later.

Path loss may be relatively high in millimeter wave (mmW) systems. Transmission may be directional to mitigate path loss. A base station may transmit one or more beam reference signals by sweeping in all directions so that a user equipment (UE) may identify a best "coarse" beam. Further, the base station may transmit a beam refinement request signal so that the UE may track "fine" beams. If a "coarse" beam identified by the UE changes, the UE may need to inform the base station so that the base station may train one or more new "fine" beams for the UE.

In a first aspect, a first method, first apparatus, and first computer-readable medium are provided. The first apparatus may receive, from a base station, a contention resolution message, the contention resolution message indicating at least a beam index corresponding to a beam. The first apparatus may determine whether the beam index is applicable to the first apparatus. The first apparatus may communicate with the base station through the beam corresponding to the beam index when the beam index is applicable to the first apparatus. The first apparatus may transmit, to the base station, an acknowledgement message when the beam index is determined to be applicable to the first apparatus. In an aspect, the contention resolution message is associated with a random access procedure. In an aspect, the determination of whether the beam index is applicable to the first apparatus includes attempting to decode the contention resolution message based on a radio network temporary identifier (RNTI) associated with the first apparatus, and the beam index is determined to be applicable to the first apparatus when the contention resolution message is successfully decoded. In an aspect, the first apparatus may refrain from transmitting a non-acknowledgement message to the base station when the beam index is determined to be inapplicable to the first apparatus or if the contention resolution message is unsuccessfully decoded. In an aspect, the contention resolution message further includes an indication of one or more channels associated with the beam index, and the communication with the base station through the beam corresponding to the beam index is performed on the one or more indicated channels. In an aspect, the first apparatus may transmit, to the base station, a random access preamble. The first apparatus may receive, from the base station, a random access response based on the random access preamble. The first apparatus may transmit, to the base station, a connection request message based on the random access response, and the contention resolution message is transmitted based on the connection request message.

3

In a second aspect, a second method, second apparatus, and second computer-readable medium are provided. The second apparatus may transmit, to a UE, a contention resolution message, and the contention resolution message may indicate at least a beam index corresponding to a beam and indicating that the beam index is applicable to the UE. The second apparatus may determine whether an acknowledgement message is received from the UE in response to the contention resolution message. The second apparatus may communicate with the UE through the beam corresponding to the beam index when the acknowledgement message is determined to be received from the UE. In an aspect, the contention resolution message is associated with a random access procedure. In an aspect, the second apparatus may scrambling at least a portion of the contention resolution message using an RNTI associated the UE. In an aspect, the contention resolution message further includes an indication of one or more channels associated with the beam index, and the communication with the UE through the beam corresponding to the beam index is performed on the one or more indicated channels. In an aspect, the second apparatus may communicate with the UE through a serving beam before transmission of the contention resolution message, and the communication with the UE continues through the serving beam based on an absence of an acknowledgement message from the UE. The second apparatus may receive, from the UE, a random access preamble. In an aspect, the second apparatus may transmit, to the UE, a random access response based on the random access preamble. The second apparatus may receive, from the UE, a connection request message based on the random access response, and the contention resolution message is transmitted based on the connection request message.

In a third aspect, a third method, third apparatus, and third computer-readable medium are provided. The third apparatus may receive, from a base station, a beam modification command indicating at least one beam index for communicating through at least one beam on at least one channel, each beam index of the at least one beam index indicating at least a direction for communicating through a corresponding beam of the at least one beam. The third apparatus may communicate, with the base station, through the at least one beam corresponding to the at least one beam index on the at least one channel. The third apparatus may communicate, with the base station, through a serving beam corresponding to a serving beam index, and switch, after receiving the beam modification command, from the serving beam to the at least one beam corresponding to the at least one beam index indicated by the beam modification command. In an aspect, the switching from the serving beam to the at least one beam is performed at a predetermined time. In an aspect, the predetermined time is associated with at least one of a symbol or subframe, and wherein the beam modification command indicates the at least one of the symbol or the subframe. In an aspect, the beam modification command indicates, for each beam index of the at least one beam index, a corresponding channel of the at least one channel. In an aspect, the at least one beam index comprises a plurality of beam indexes, and the at least one channel comprises a plurality of channels. In an aspect, the at least one beam index is applicable to one of uplink communication or downlink communication. In an aspect, the beam modification command is received in a medium access control (MAC) control element (CE). In an aspect, the beam modification command is received in a downlink control information (DCI) message. In an aspect, the third apparatus may determine the at least one channel based on a DCI

4

format of the DCI message. In an aspect, the beam modification command is received via radio resource control (RRC) signaling.

In a fourth aspect, a fourth method, fourth apparatus, and fourth computer-readable medium are provided. The fourth apparatus may receive a beam modification command that indicates a set of transmit beam indexes corresponding to a set of transmit beams of a base station, and each transmit beam index of the set of transmit beam indexes may indicate at least a transmit direction for transmitting a transmit beam by the base station. The fourth apparatus may determine a set of receive beam indexes corresponding to receive beams of the fourth apparatus based on the set of transmit beam indexes, each receive beam index of the set of receive beam indexes indicating at least a receive direction for receiving a receive beam by the fourth apparatus. The fourth apparatus may receive, from the base station, a beam refinement reference signal (BRRS) through at least one receive beam corresponding to at least one receive beam index included in the set of receive beam indexes. In an aspect, the receiving, from the base station, the BRRS through the at least one receive beam corresponding to the at least one receive beam index included in the set of receive beam indexes includes receiving a first portion of the BRRS in a first set of symbols through a first receive beam corresponding to a first receive beam index included in the set of receive beam indexes, and receiving a second portion of the BRRS in a second set of symbols through a second receive beam corresponding to a second receive beam index included in the set of receive beam indexes. In an aspect, the BRRS is received in one or more symbols corresponding to one or more symbol indexes. In an aspect, the beam modification command indicates the one or more symbol indexes, and a corresponding transmit beam index of the set of transmit beam indexes for each symbol index of the one or more symbol indexes. In an aspect, the one or more symbol indexes in which the BRRS is received are predetermined. In an aspect, the BRRS is received through the set of transmit beams from the base station corresponding to the set of transmit beam indexes. In an aspect, the BRRS is received through a different set of transmit beams from the base station than the set of transmit beams corresponding to the set of transmit beam indexes, the different set of transmit beams corresponding to a second set of transmit beam indexes different from the set of transmit beam indexes. In an aspect, the beam modification command is received in a MAC CE. In an aspect, the beam modification command is received in a DCI message. In an aspect, the beam modification command is received via RRC signaling.

In a fifth aspect, a fifth method, fifth apparatus, and fifth computer-readable medium are provided. The fifth apparatus may receive, from a base station, through a set of beams a set of beam reference signals (BRSs). The fifth apparatus may measure a signal quality of each BRS of the set of BRSs, each measured signal quality corresponding to a beam of the set of beams. In an aspect, the fifth apparatus may maintain a set of candidate beam indexes corresponding to a set of best measured signal qualities of the set of BRSs. In an aspect, the fifth apparatus may transmit, to the base station, beam state information (BSI) indicating at least one measured signal quality and at least one beam index from the set of maintained candidate beam indexes, the at least one beam index corresponding to the at least one measured signal quality. In an aspect, the set of the best measured signal qualities is a set of the highest measured signal qualities. In an aspect, N candidate beam indexes are maintained in the set of candidate beam indexes, N being

5

predetermined. In an aspect, the set of best measured signal qualities of the set of BRSs is based on a most recent set of signal qualities of the set of BRSs, a filtered set of signal qualities of the set of BRSs, or a time-averaged set of signal qualities of the set of BRSs. In an aspect, the maintenance of the set of candidate beam indexes is based on at least one hysteresis criteria for including a beam index in or excluding a beam index from the set of candidate beam indexes. In an aspect, the fifth apparatus may receive, from the base station, an indication of one or more beam indexes that are to be excluded from the maintained set of candidate beam indexes. In an aspect, the signal quality comprises at least one of a beam reference signal received power (BRSRP), a beam reference signal received quality (BRSRQ), a signal-to-interference ratio (SIR), a signal-to-interference-plus noise ratio (SINR), or a signal-to-noise ratio (SNR).

In a sixth aspect, a sixth method, sixth apparatus, and sixth computer-readable medium are provided. The sixth apparatus may receive, from a base station, a message requesting BSI. The sixth apparatus may determine a number N of BSI reports to send to the base station, and each BSI report may indicate a beam index corresponding to a beam and a received power associated with the beam. The sixth apparatus may send, to the base station, N BSI reports based on the message requesting BSI. The sixth apparatus may receive, from the base station, a set of signals through a set of beams, and determine the received power for each signal of the set of signals received through each beam of the set of beams, each received power associated with a beam of the set of beams. In an aspect, the N BSI reports include N received powers corresponding to the highest determined received powers. In an aspect, the determination of the number N of BSI reports to send to the base station is based on a type of the message requesting the BSI. In an aspect, the type of the message requesting the BSI comprises a DCI message. In an aspect, the number N of BSI reports to send to the base station is determined to be one based on the DCI message. In an aspect, the determined number N of BSI reports are sent on a physical uplink control channel (PUCCH). In an aspect, the type of message requesting the BSI comprises a random access response (RAR) message. In an aspect, the number N of BSI reports is determined to be greater than one based on the RAR message. In an aspect, the determined number N of BSI reports are sent on a physical uplink shared channel (PUSCH).

In a seventh aspect, a seventh method, seventh apparatus, and seventh computer-readable medium are provided. The seventh apparatus may select a first beam for communication with a base station. The seventh apparatus may attempt, through the selected first beam, at least one random access channel (RACH) procedure with the base station. The seventh apparatus may determine that the at least one RACH procedure failed with the base station. The seventh apparatus may send, after a successful RACH procedure with the base station, information indicating that the at least one RACH procedure failed. In an aspect, the seventh apparatus may select a new beam for communication with the base station after the determination that the at least one RACH procedure failed, and at least a portion of the successful RACH procedure is performed through the selected new beam. In an aspect, the seventh apparatus may increase a transmission power after the determination that the at least one RACH procedure failed, and at least a portion of the successful RACH procedure is performed with the increased transmission power. In an aspect, the seventh apparatus may store information associated with the selected first beam based on the determination that the at least one RACH procedure

6

failed. In an aspect, the information indicating that the at least one RACH procedure failed includes the stored information associated with the first beam. In an aspect, the information indicating that the at least one RACH procedure failed includes an indication of a subframe in which a RACH message associated with the at least one RACH procedure is carried. In an aspect, the seventh apparatus may exclude the selected first beam from a candidate beam set maintained by the UE based on the determination that the at least one RACH procedure failed. In an aspect, the information indicating that the at least one RACH procedure failed comprises a BSI report. In an aspect, the at least one RACH procedure includes at least one of transmitting, to the base station, a random access preamble, receiving, from the base station, a random access response based on the random access preamble, transmitting, to the base station, a connection request message based on the random access response, and/or receive a contention resolution message based on the connection request message. In an aspect, the seventh apparatus is synchronized with a network that includes the base station based on the successful RACH procedure.

To the accomplishment of the foregoing and related ends, the one or more aspects comprise the features hereinafter fully described and particularly pointed out in the claims. The following description and the annexed drawings set forth in detail certain illustrative features of the one or more aspects. These features are indicative, however, of but a few of the various ways in which the principles of various aspects may be employed, and this description is intended to include all such aspects and their equivalents.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a diagram illustrating an example of a wireless communications system and an access network.

FIGS. 2A, 2B, 2C, and 2D are diagrams illustrating LTE examples of a DL frame structure, DL channels within the DL frame structure, an UL frame structure, and UL channels within the UL frame structure, respectively.

FIG. 3 is a diagram illustrating an example of a base station and user equipment (UE) in an access network.

FIGS. 4A and 4B are call flow diagrams of a wireless communications system.

FIGS. 5A through 5G illustrate diagrams of a wireless communications system.

FIG. 6 is a diagram of a wireless communications system.

FIG. 7 is a diagram of a wireless communications system.

FIG. 8 is a diagram of a wireless communications system.

FIG. 9 is a diagram of a wireless communications system.

FIG. 10 is a diagram of a wireless communications system.

FIG. 11 is a diagram of a wireless communications system.

FIG. 12 is a flowchart of a method of wireless communication.

FIG. 13 is a flowchart of a method of wireless communication.

FIG. 14 is a flowchart of a method of wireless communication.

FIG. 15 is a flowchart of a method of wireless communication.

FIG. 16 is a flowchart of a method of wireless communication.

FIG. 17 is a flowchart of a method of wireless communication.

FIG. 18 is a flowchart of a method of wireless communication.

FIG. 19 is a conceptual data flow diagram illustrating the data flow between different means/components in an exemplary apparatus.

FIG. 20 is a diagram illustrating an example of a hardware implementation for an apparatus employing a processing system.

FIG. 21 is a conceptual data flow diagram illustrating the data flow between different means/components in an exemplary apparatus.

FIG. 22 is a diagram illustrating an example of a hardware implementation for an apparatus employing a processing system.

FIG. 23 is a conceptual data flow diagram illustrating the data flow between different means/components in an exemplary apparatus.

FIG. 24 is a diagram illustrating an example of a hardware implementation for an apparatus employing a processing system.

FIG. 25 is a conceptual data flow diagram illustrating the data flow between different means/components in an exemplary apparatus.

FIG. 26 is a diagram illustrating an example of a hardware implementation for an apparatus employing a processing system.

FIG. 27 is a conceptual data flow diagram illustrating the data flow between different means/components in an exemplary apparatus.

FIG. 28 is a diagram illustrating an example of a hardware implementation for an apparatus employing a processing system.

FIG. 29 is a conceptual data flow diagram illustrating the data flow between different means/components in an exemplary apparatus.

FIG. 30 is a diagram illustrating an example of a hardware implementation for an apparatus employing a processing system.

FIG. 31 is a conceptual data flow diagram illustrating the data flow between different means/components in an exemplary apparatus.

FIG. 32 is a diagram illustrating an example of a hardware implementation for an apparatus employing a processing system.

DETAILED DESCRIPTION

The detailed description set forth below in connection with the appended drawings is intended as a description of various configurations and is not intended to represent the only configurations in which the concepts described herein may be practiced. The detailed description includes specific details for the purpose of providing a thorough understanding of various concepts. However, it will be apparent to those skilled in the art that these concepts may be practiced without these specific details. In some instances, well known structures and components are shown in block diagram form in order to avoid obscuring such concepts.

Several aspects of telecommunication systems will now be presented with reference to various apparatus and methods. These apparatus and methods will be described in the following detailed description and illustrated in the accompanying drawings by various blocks, components, circuits, processes, algorithms, etc. (collectively referred to as “elements”). These elements may be implemented using electronic hardware, computer software, or any combination thereof. Whether such elements are implemented as hardware or software depends upon the particular application and design constraints imposed on the overall system.

By way of example, an element, or any portion of an element, or any combination of elements may be implemented as a “processing system” that includes one or more processors. Examples of processors include microprocessors, microcontrollers, graphics processing units (GPUs), central processing units (CPUs), application processors, digital signal processors (DSPs), reduced instruction set computing (RISC) processors, systems on a chip (SoC), baseband processors, field programmable gate arrays (FPGAs), programmable logic devices (PLDs), state machines, gated logic, discrete hardware circuits, and other suitable hardware configured to perform the various functionality described throughout this disclosure. One or more processors in the processing system may execute software. Software shall be construed broadly to mean instructions, instruction sets, code, code segments, program code, programs, subprograms, software components, applications, software applications, software packages, routines, subroutines, objects, executables, threads of execution, procedures, functions, etc., whether referred to as software, firmware, middleware, microcode, hardware description language, or otherwise.

Accordingly, in one or more example embodiments, the functions described may be implemented in hardware, software, or any combination thereof. If implemented in software, the functions may be stored on or encoded as one or more instructions or code on a computer-readable medium. Computer-readable media includes computer storage media. Storage media may be any available media that can be accessed by a computer. By way of example, and not limitation, such computer-readable media can comprise a random-access memory (RAM), a read-only memory (ROM), an electrically erasable programmable ROM (EEPROM), optical disk storage, magnetic disk storage, other magnetic storage devices, combinations of the aforementioned types of computer-readable media, or any other medium that can be used to store computer executable code in the form of instructions or data structures that can be accessed by a computer.

FIG. 1 is a diagram illustrating an example of a wireless communications system and an access network 100. The wireless communications system (also referred to as a wireless wide area network (WWAN)) includes base stations 102, UEs 104, and an Evolved Packet Core (EPC) 160. The base stations 102 may include macro cells (high power cellular base station) and/or small cells (low power cellular base station). The macro cells include eNBs. The small cells include femtocells, picocells, and microcells.

The base stations 102 (collectively referred to as Evolved Universal Mobile Telecommunications System (UMTS) Terrestrial Radio Access Network (E-UTRAN)) interface with the EPC 160 through backhaul links 132 (e.g., S1 interface). In addition to other functions, the base stations 102 may perform one or more of the following functions: transfer of user data, radio channel ciphering and deciphering, integrity protection, header compression, mobility control functions (e.g., handover, dual connectivity), inter-cell interference coordination, connection setup and release, load balancing, distribution for non-access stratum (NAS) messages, NAS node selection, synchronization, radio access network (RAN) sharing, multimedia broadcast multicast service (MBMS), subscriber and equipment trace, RAN information management (RIM), paging, positioning, and delivery of warning messages. The base stations 102 may communicate directly or indirectly (e.g., through the EPC 160) with each other over backhaul links 134 (e.g., X2 interface). The backhaul links 134 may be wired or wireless.

The base stations **102** may wirelessly communicate with the UEs **104**. Each of the base stations **102** may provide communication coverage for a respective geographic coverage area **110**. There may be overlapping geographic coverage areas **110**. For example, the small cell **102'** may have a coverage area **110'** that overlaps the coverage area **110** of one or more macro base stations **102**. A network that includes both small cell and macro cells may be known as a heterogeneous network. A heterogeneous network may also include Home Evolved Node Bs (eNBs) (HeNBs), which may provide service to a restricted group known as a closed subscriber group (CSG). The communication links **120** between the base stations **102** and the UEs **104** may include uplink (UL) (also referred to as reverse link) transmissions from a UE **104** to a base station **102** and/or downlink (DL) (also referred to as forward link) transmissions from a base station **102** to a UE **104**. The communication links **120** may use MIMO antenna technology, including spatial multiplexing, beamforming, and/or transmit diversity. The communication links may be through one or more carriers. The base stations **102**/UEs **104** may use spectrum up to Y MHz (e.g., 5, 10, 15, 20 MHz) bandwidth per carrier allocated in a carrier aggregation of up to a total of Yx MHz (x component carriers) used for transmission in each direction. The carriers may or may not be adjacent to each other. Allocation of carriers may be asymmetric with respect to DL and UL (e.g., more or less carriers may be allocated for DL than for UL). The component carriers may include a primary component carrier and one or more secondary component carriers. A primary component carrier may be referred to as a primary cell (PCell) and a secondary component carrier may be referred to as a secondary cell (SCell).

The wireless communications system may further include a Wi-Fi access point (AP) **150** in communication with Wi-Fi stations (STAs) **152** via communication links **154** in a 5 gigahertz (GHz) unlicensed frequency spectrum. When communicating in an unlicensed frequency spectrum, the STAs **152**/AP **150** may perform a clear channel assessment (CCA) prior to communicating in order to determine whether the channel is available.

The small cell **102'** may operate in a licensed and/or an unlicensed frequency spectrum. When operating in an unlicensed frequency spectrum, the small cell **102'** may employ LTE and use the same 5 GHz unlicensed frequency spectrum as used by the Wi-Fi AP **150**. The small cell **102'**, employing LTE in an unlicensed frequency spectrum, may boost coverage to and/or increase capacity of the access network. LTE in an unlicensed spectrum may be referred to as LTE-unlicensed (LTE-U), licensed assisted access (LAA), or MuLTEfire.

The millimeter wave (mmW) base station **180** may operate in mmW frequencies and/or near mmW frequencies in communication with the UE **182**. In one aspect, the UE **182** may be an aspect of the UE **104**. Extremely high frequency (EHF) is part of the RF in the electromagnetic spectrum. EHF has a range of 30 GHz to 300 GHz and a wavelength between 1 millimeter and 10 millimeters. Radio waves in the band may be referred to as a millimeter wave. Near mmW may extend down to a frequency of 3 GHz with a wavelength of 100 millimeters. The super high frequency (SHF) band extends between 3 GHz and 30 GHz, also referred to as centimeter wave. Communications using the mmW/near mmW radio frequency band has extremely high path loss and a short range. The mmW base station **180** may utilize beamforming **184** with the UE **182** to compensate for the extremely high path loss and short range.

The EPC **160** may include a Mobility Management Entity (MME) **162**, other MMEs **164**, a Serving Gateway **166**, a Multimedia Broadcast Multicast Service (MBMS) Gateway **168**, a Broadcast Multicast Service Center (BM-SC) **170**, and a Packet Data Network (PDN) Gateway **172**. The MME **162** may be in communication with a Home Subscriber Server (HSS) **174**. The MME **162** is the control node that processes the signaling between the UEs **104** and the EPC **160**. Generally, the MME **162** provides bearer and connection management. All user Internet protocol (IP) packets are transferred through the Serving Gateway **166**, which itself is connected to the PDN Gateway **172**. The PDN Gateway **172** provides UE IP address allocation as well as other functions. The PDN Gateway **172** and the BM-SC **170** are connected to the IP Services **176**. The IP Services **176** may include the Internet, an intranet, an IP Multimedia Subsystem (IMS), a PS Streaming Service (PSS), and/or other IP services. The BM-SC **170** may provide functions for MBMS user service provisioning and delivery. The BM-SC **170** may serve as an entry point for content provider MBMS transmission, may be used to authorize and initiate MBMS Bearer Services within a public land mobile network (PLMN), and may be used to schedule MBMS transmissions. The MBMS Gateway **168** may be used to distribute MBMS traffic to the base stations **102** belonging to a Multicast Broadcast Single Frequency Network (MBSFN) area broadcasting a particular service, and may be responsible for session management (start/stop) and for collecting eMBMS related charging information.

The base station may also be referred to as a Node B, evolved Node B (eNB), an access point, a base transceiver station, a radio base station, a radio transceiver, a transceiver function, a basic service set (BSS), an extended service set (ESS), or some other suitable terminology. The base station **102** provides an access point to the EPC **160** for a UE **104**. Examples of UEs **104** include a cellular phone, a smart phone, a session initiation protocol (SIP) phone, a laptop, a personal digital assistant (PDA), a satellite radio, a global positioning system, a multimedia device, a video device, a digital audio player (e.g., MP3 player), a camera, a game console, a tablet, a smart device, a wearable device, or any other similar functioning device. The UE **104** may also be referred to as a station, a mobile station, a subscriber station, a mobile unit, a subscriber unit, a wireless unit, a remote unit, a mobile device, a wireless device, a wireless communications device, a remote device, a mobile subscriber station, an access terminal, a mobile terminal, a wireless terminal, a remote terminal, a handset, a user agent, a mobile client, a client, or some other suitable terminology.

Referring again to FIG. 1, in certain aspects, the UE **104** may receive, from a base station (e.g., the base station **102** and/or the mmW base station **180**), a message requesting BSI **198**. The UE **104** may determine a number N of BSI reports to send to the base station, and each BSI report may indicate a beam index corresponding to a beam and a received power associated with the beam. The UE **104** may send, to the base station (e.g., the base station **102** and/or the mmW base station **180**), N BSI reports based on the message requesting BSI **198**. The UE **104** may receive, from the base station (e.g., the base station **102** and/or the mmW base station **180**), a set of signals through a set of beams, and determine the received power for each signal of the set of signals received through each beam of the set of beams, each received power associated with a beam of the set of beams. In an aspect, the N BSI reports include N received powers corresponding to the highest determined received powers. In an aspect, the determination of the number N of BSI reports

11

to send to the base station (e.g., the base station **102** and/or the mmW base station **180**) is based on a type of the message requesting the BSI. In an aspect, the type of the message requesting the BSI **198** comprises a DCI message. In an aspect, the number N of BSI reports to send to the base station is determined to be one based on the DCI message. In an aspect, the determined number N of BSI reports are sent on a PUCCH. In an aspect, the type of message requesting the BSI **198** comprises a RAR message. In an aspect, the number N of BSI reports is determined to be greater than one based on the RAR message. In an aspect, the determined number N of BSI reports are sent on a PUSCH.

FIG. 2A is a diagram **200** illustrating an example of a DL frame structure in LTE. FIG. 2B is a diagram **230** illustrating an example of channels within the DL frame structure in LTE. FIG. 2C is a diagram **250** illustrating an example of an UL frame structure in LTE. FIG. 2D is a diagram **280** illustrating an example of channels within the UL frame structure in LTE. Other wireless communication technologies may have a different frame structure and/or different channels. In LTE, a frame (10 ms) may be divided into 10 equally sized subframes.

In 5G, a frame may be less than 10 ms (and a subframe may be referred to as a slot, which may include one or more minislots). The structure is to be regarded as illustrative, and a subframe may be referred to a slot or a minislot. A slot may be one-fourth to one-fifth of a subframe (e.g., of an LTE subframe) and a minislot may include 1 to 7 OFDM symbols. Each subframe may include two consecutive time slots.

A resource grid may be used to represent the two time slots, each time slot including one or more time concurrent resource blocks (RBs) (also referred to as physical RBs (PRBs)). The resource grid is divided into multiple resource elements (REs). In LTE, for a normal cyclic prefix, an RB contains 12 consecutive subcarriers in the frequency domain and 7 consecutive symbols (for DL, OFDM symbols; for UL, SC-FDMA symbols) in the time domain, for a total of 84 REs. For an extended cyclic prefix, an RB contains 12 consecutive subcarriers in the frequency domain and 6 consecutive symbols in the time domain, for a total of 72 REs. The number of bits carried by each RE depends on the modulation scheme.

As illustrated in FIG. 2A, some of the REs carry DL reference (pilot) signals (DL-RS) for channel estimation at the UE. The DL-RS may include cell-specific reference signals (CRS) (also sometimes called common RS), UE-specific reference signals (UE-RS), and channel state information reference signals (CSI-RS). FIG. 2A illustrates CRS for antenna ports **0**, **1**, **2**, and **3** (indicated as R_0 , R_1 , R_2 , and R_3 , respectively), UE-RS for antenna port **5** (indicated as R_5), and CSI-RS for antenna port **15** (indicated as R). FIG. 2B illustrates an example of various channels within a DL subframe of a frame. The physical control format indicator channel (PCFICH) is within symbol **0** of slot **0**, and carries a control format indicator (CFI) that indicates whether the physical downlink control channel (PDCCH) occupies 1, 2, or 3 symbols (FIG. 2B illustrates a PDCCH that occupies 3 symbols). The PDCCH carries downlink control information (DCI) within one or more control channel elements (CCEs), each CCE including nine RE groups (REGs), each REG including four consecutive REs in an OFDM symbol. A UE may be configured with a UE-specific enhanced PDCCH (ePDCCH) that also carries DCI. The ePDCCH may have 2, 4, or 8 RB pairs (FIG. 2B shows two RB pairs, each subset including one RB pair). The physical hybrid automatic repeat request (ARQ) (HARQ) indicator channel (PHICH) is

12

also within symbol **0** of slot **0** and carries the HARQ indicator (HI) that indicates HARQ acknowledgment (ACK)/negative ACK (NACK) feedback based on the physical uplink shared channel (PUSCH). The primary synchronization channel (PSCH) is within symbol **6** of slot **0** within subframes **0** and **5** of a frame, and carries a primary synchronization signal (PSS) that is used by a UE to determine subframe timing and a physical layer identity. The secondary synchronization channel (SSCH) is within symbol **5** of slot **0** within subframes **0** and **5** of a frame, and carries a secondary synchronization signal (SSS) that is used by a UE to determine a physical layer cell identity group number. Based on the physical layer identity and the physical layer cell identity group number, the UE can determine a physical cell identifier (PCI). Based on the PCI, the UE can determine the locations of the aforementioned DL-RS. The physical broadcast channel (PBCH) is within symbols **0**, **1**, **2**, **3** of slot **1** of subframe **0** of a frame, and carries a master information block (MIB). The MIB provides a number of RBs in the DL system bandwidth, a PHICH configuration, and a system frame number (SFN). The physical downlink shared channel (PDSCH) carries user data, broadcast system information not transmitted through the PBCH such as system information blocks (SIBs), and paging messages.

As illustrated in FIG. 2C, some of the REs carry demodulation reference signals (DM-RS) for channel estimation at the eNB. The UE may additionally transmit sounding reference signals (SRS) in the last symbol of a subframe. The SRS may have a comb structure, and a UE may transmit SRS on one of the combs. The SRS may be used by an eNB for channel quality estimation to enable frequency-dependent scheduling on the UL. FIG. 2D illustrates an example of various channels within an UL subframe of a frame. A physical random access channel (PRACH) may be within one or more subframes within a frame based on the PRACH configuration. The PRACH may include six consecutive RB pairs within a subframe. The PRACH allows the UE to perform initial system access and achieve UL synchronization. A physical uplink control channel (PUCCH) may be located on edges of the UL system bandwidth. The PUCCH carries uplink control information (UCI), such as scheduling requests, a channel quality indicator (CQI), a precoding matrix indicator (PMI), a rank indicator (RI), and HARQ ACK/NACK feedback. The PUSCH carries data, and may additionally be used to carry a buffer status report (BSR), a power headroom report (PHR), and/or UCI.

FIG. 3 is a block diagram of an base station **310** in communication with a UE **350** in an access network. In an aspect, the base station **310** may be an aspect of the mmW base station **180** and/or the base station **102**. In the DL, IP packets from the EPC **160** may be provided to a controller/processor **375**. The controller/processor **375** implements layer **3** and layer **2** functionality. Layer **3** includes a radio resource control (RRC) layer, and layer **2** includes a packet data convergence protocol (PDCP) layer, a radio link control (RLC) layer, and a medium access control (MAC) layer. The controller/processor **375** provides RRC layer functionality associated with broadcasting of system information (e.g., MIB, SIBs), RRC connection control (e.g., RRC connection paging, RRC connection establishment, RRC connection modification, and RRC connection release), inter radio access technology (RAT) mobility, and measurement configuration for UE measurement reporting; PDCP layer functionality associated with header compression/decompression, security (ciphering, deciphering, integrity protection, integrity verification), and handover support functions; RLC layer functionality associated with the transfer of upper layer

packet data units (PDUs), error correction through ARQ, concatenation, segmentation, and reassembly of RLC service data units (SDUs), re-segmentation of RLC data PDUs, and reordering of RLC data PDUs; and MAC layer functionality associated with mapping between logical channels and transport channels, multiplexing of MAC SDUs onto transport blocks (TBs), demultiplexing of MAC SDUs from TBs, scheduling information reporting, error correction through HARQ, priority handling, and logical channel prioritization.

The transmit (TX) processor 316 and the receive (RX) processor 370 implement layer 1 functionality associated with various signal processing functions. Layer 1, which includes a physical (PHY) layer, may include error detection on the transport channels, forward error correction (FEC) coding/decoding of the transport channels, interleaving, rate matching, mapping onto physical channels, modulation/demodulation of physical channels, and MIMO antenna processing. The TX processor 316 handles mapping to signal constellations based on various modulation schemes (e.g., binary phase-shift keying (BPSK), quadrature phase-shift keying (QPSK), M-phase-shift keying (M-PSK), M-quadrature amplitude modulation (M-QAM)). The coded and modulated symbols may then be split into parallel streams. Each stream may then be mapped to an OFDM subcarrier, multiplexed with a reference signal (e.g., pilot) in the time and/or frequency domain, and then combined together using an Inverse Fast Fourier Transform (IFFT) to produce a physical channel carrying a time domain OFDM symbol stream. The OFDM stream is spatially precoded to produce multiple spatial streams. Channel estimates from a channel estimator 374 may be used to determine the coding and modulation scheme, as well as for spatial processing. The channel estimate may be derived from a reference signal and/or channel condition feedback transmitted by the UE 350. Each spatial stream may then be provided to a different antenna 320 via a separate transmitter 318TX. Each transmitter 318TX may modulate an RF carrier with a respective spatial stream for transmission.

At the UE 350, each receiver 354RX receives a signal through its respective antenna 352. Each receiver 354RX recovers information modulated onto an RF carrier and provides the information to the receive (RX) processor 356. The TX processor 368 and the RX processor 356 implement layer 1 functionality associated with various signal processing functions. The RX processor 356 may perform spatial processing on the information to recover any spatial streams destined for the UE 350. If multiple spatial streams are destined for the UE 350, they may be combined by the RX processor 356 into a single OFDM symbol stream. The RX processor 356 then converts the OFDM symbol stream from the time-domain to the frequency domain using a Fast Fourier Transform (FFT). The frequency domain signal comprises a separate OFDM symbol stream for each subcarrier of the OFDM signal. The symbols on each subcarrier, and the reference signal, are recovered and demodulated by determining the most likely signal constellation points transmitted by the base station 310. These soft decisions may be based on channel estimates computed by the channel estimator 358. The soft decisions are then decoded and deinterleaved to recover the data and control signals that were originally transmitted by the base station 310 on the physical channel. The data and control signals are then provided to the controller/processor 359, which implements layer 3 and layer 2 functionality.

The controller/processor 359 can be associated with a memory 360 that stores program codes and data. The

memory 360 may be referred to as a computer-readable medium. In the UL, the controller/processor 359 provides demultiplexing between transport and logical channels, packet reassembly, deciphering, header decompression, and control signal processing to recover IP packets from the EPC 160. The controller/processor 359 is also responsible for error detection using an ACK and/or NACK protocol to support HARQ operations.

Similar to the functionality described in connection with the DL transmission by the base station 310, the controller/processor 359 provides RRC layer functionality associated with system information (e.g., MIB, SIBs) acquisition, RRC connections, and measurement reporting; PDCP layer functionality associated with header compression/decompression, and security (ciphering, deciphering, integrity protection, integrity verification); RLC layer functionality associated with the transfer of upper layer PDUs, error correction through ARQ, concatenation, segmentation, and reassembly of RLC SDUs, re-segmentation of RLC data PDUs, and reordering of RLC data PDUs; and MAC layer functionality associated with mapping between logical channels and transport channels, multiplexing of MAC SDUs onto TBs, demultiplexing of MAC SDUs from TBs, scheduling information reporting, error correction through HARQ, priority handling, and logical channel prioritization.

Channel estimates derived by a channel estimator 358 from a reference signal or feedback transmitted by the base station 310 may be used by the TX processor 368 to select the appropriate coding and modulation schemes, and to facilitate spatial processing. The spatial streams generated by the TX processor 368 may be provided to different antenna 352 via separate transmitters 354TX. Each transmitter 354TX may modulate an RF carrier with a respective spatial stream for transmission.

The UL transmission is processed at the base station 310 in a manner similar to that described in connection with the receiver function at the UE 350. Each receiver 318RX receives a signal through its respective antenna 320. Each receiver 318RX recovers information modulated onto an RF carrier and provides the information to a RX processor 370.

The controller/processor 375 can be associated with a memory 376 that stores program codes and data. The memory 376 may be referred to as a computer-readable medium. In the UL, the controller/processor 375 provides demultiplexing between transport and logical channels, packet reassembly, deciphering, header decompression, control signal processing to recover IP packets from the UE 350. IP packets from the controller/processor 375 may be provided to the EPC 160. The controller/processor 375 is also responsible for error detection using an ACK and/or NACK protocol to support HARQ operations.

FIGS. 4A and 4B illustrate call flow diagrams of methods 400, 440 of RACH procedures. A UE 404 may perform a RACH procedure with a base station 402 (e.g., a mmW base station, an eNB, etc.), for example, in order to synchronize with a network. A RACH procedure may be either contention-based or non-contention based.

FIG. 4A illustrates a method 400 for a contention-based RACH procedure. First, the UE 404 may select a RACH preamble for the RACH procedure. Further, the UE 404 may determine a random access (RA) RNTI in order to identify the UE 404 during the RACH procedure. The UE 404 may determine an RA-RNTI based on, for example, a time slot number in which a MSG1 410 is sent. The UE 404 may include the RACH preamble and the RA-RNTI in the MSG1 410.

15

In an aspect, the UE 404 may determine at least one resource (e.g., a time and/or frequency resource) that is to carry the MSG1 410. For example, the base station 402 may broadcast system information (e.g., a SIB), and the UE 404 may acquire the at least one resource based on the system information (e.g., system information included in a SIB2). The UE 404 may send the MSG1 410 to the base station 402, for example, on the at least one resource. If the UE 404 does not receive a response to the MSG1 410 (e.g., after expiration of a timer), then the UE 404 may increase transmit power (e.g., by a fixed interval) and resend the MSG1 410.

Based on the MSG1 410, the base station 402 may send, to the UE 404, a MSG2 412. The MSG2 412 may also be known as a random access response and may be sent on a downlink shared channel (DL-SCH). The base station 402 may determine a temporary cell RNTI (T-CRNTI). Further, the base station 402 may determine a timing advance value so that the UE 404 may adjust timing to compensate for delay. Further, the base station 402 may determine an uplink resource grant, which may include an initial resource assignment for the UE 404 so that the UE 404 may use the uplink shared channel (UL-SCH). The base station 402 may generate the MSG2 412 to include the C-RNTI, the timing advance value, and/or the uplink grant resource. The base station 402 may then transmit the MSG2 412 to the UE 404. In an aspect, the UE 404 may determine an uplink resource grant based on the MSG2 412.

Based on the MSG2 412, the UE 404 may send, to the base station 402, a MSG3 414. The MSG3 414 may also be known as an RRC connection request message and/or a scheduled transmission message. The UE 404 may determine a temporary mobile subscriber identity (TMSI) associated with the UE 404 or another random value used to identify the UE 404 (e.g., if the UE 404 is connecting to the network for the first time). The UE 404 may determine a connection establishment clause, which may indicate why the UE 404 is connecting to the network. The UE 404 may generate the MSG3 414 to include at least the TMSI or other random value, as well as the connection establishment clause. The UE 404 may then transmit the MSG3 414 to the base station on the UL-SCH.

Based on the MSG3 414, the base station 402 may send, to the UE 404, a MSG4 416. The MSG4 416 may also be known as a connection resolution message. The base station 402 may address the MSG4 416 toward the TMSI or random value from the MSG3 414. The MSG4 416 may be scrambled with a C-RNTI associated with the UE 404. The base station 402 may transmit the MSG4 416 to the UE 404. The UE 404 may decode the MSG4 416, for example, using the C-RNTI associated with the UE 404. This RACH procedure may allow the UE 404 to be synchronized with a network.

FIG. 4B illustrates a method 440 of a non-contention-based RACH procedure. The non-contention-based RACH procedure may be applicable to handover and/or downlink data arrival.

The base station 402 may determine a random access preamble assigned to the UE 404. The base station 402 may transmit, to the UE 404, the random access preamble assignment 442. The UE 404 may respond to the random access preamble assignment 442 with the random access preamble 444 (e.g., an RRC connection message), which may be the random access preamble assigned to the UE 404. The UE 404 may then receive, from the base station 402, a random access response 446 (e.g., an uplink grant).

FIGS. 5A through 5G are diagrams illustrating an example of the transmission of beamformed signals between

16

a base station and a UE. The base station 502 may be embodied as a base station in a mmW system (mmW base station), such as the mmW base station 180. In one aspect, the base station 502 may be collocated with another base station, such as an eNB, a cellular base station, or other base station (e.g., a base station configured to communicate in a sub-6 GHz band). While some beams are illustrated as adjacent to one another, such an arrangement may be different in different aspects (e.g., beams transmitted during a same symbol may not be adjacent to one another). Additionally, the number of illustrated beams is to be regarded as illustrative.

Extremely high frequency (EHF) is part of the RF in the electromagnetic spectrum. EHF has a range of 30 GHz to 300 GHz and a wavelength between 1 millimeter and 10 millimeters. Radio waves in the band may be referred to as a millimeter wave. Near mmW may extend down to a frequency of 3 GHz with a wavelength of 100 millimeters (the super high frequency (SHF) band extends between 3 GHz and 30 GHz, also referred to as centimeter wave). While the disclosure herein refers to mmWs, it should be understood that the disclosure also applies to near mmWs. Further, while the disclosure herein refers to mmW base stations, it should be understood that the disclosure also applies to near-mmW base stations.

In order to build a useful communication network in the millimeter wavelength spectrum, a beamforming technique may be used to compensate for path loss. Beamforming technique focuses the RF energy into a narrow direction to allow the RF beam to propagate farther in that direction. Using the beamforming technique, non-line of sight (NLOS) RF communication in the millimeter wavelength spectrum may rely on reflection and/or diffraction of the beams to reach the UE. If the direction becomes blocked, either because of UE movement or changes in the environment (e.g., obstacles, humidity, rain, etc.), the beam may not be able to reach the UE. Thus, in order to ensure that the UE has continuous, seamless coverage, multiple beams in as many different direction as possible may be available. In an aspect, the beamforming technique may require that the mmW base stations and the UEs transmit and receive in a direction that allows the most RF energy to be collected.

The base station 502 may include hardware for performing analog and/or digital beamforming. If the base station 502 is equipped with analog beamforming, at any one time, the base station 502 may transmit or receive a signal in only one direction. If the base station 502 is equipped with digital beamforming, the base station 502 may concurrently transmit multiple signals in multiple directions or may receive multiple signals concurrently in multiple directions.

Further, the UE 504, for example, may include hardware for performing analog and/or digital beamforming. If the UE 504 is equipped with analog beamforming, at any one time, the UE 504 may transmit or receive a signal in only one direction. If the UE 504 is equipped with digital beamforming, the UE 504 may concurrently transmit multiple signals in multiple directions or may concurrently receive multiple signals in multiple directions.

In the mmW network, UEs may perform beam sweeps with mmW base stations within range. For example, the base station 502 may transmit m beams in a plurality of different spatial directions. The UE 504 may listen/scan for the beam transmissions from the base station 502 in n different receive spatial directions. When listening/scanning for the beam transmissions, the UE 504 may listen/scan for the beam sweep transmission from the base station 502 m times in each of the n different receive spatial directions (a total of

m*n scans). In another aspect, in a beam sweep, the UE 504 may transmit n beams in a plurality of different spatial directions. The base station 502 listens/scans for the beam transmissions from the UE 504 in m different receive spatial directions. When listening/scanning for the beam transmissions, the base station 502 may listen/scan for the beam sweep transmission from the UE 504 n times in each of the m different receive spatial directions (a total of m*n scans).

Based on the performed beam sweeps, the UEs and/or the mmW base stations may determine a channel quality associated with the performed beam sweeps. For example, the UE 504 may determine the channel quality associated with the performed beam sweeps. Alternatively, the base station 502 may determine the channel quality associated with the performed beam sweeps. If the UE 504 determines a channel quality associated with the performed beam sweeps, the UE 504 may send the channel quality information (also referred to as beam sweep result information) to the base station 502. The UE 504 may send the beam sweep result information to the base station 502. If the base station 502 determines a channel quality associated with the performed beam sweeps, the base station 502 may send the beam sweep result information to the UE 504. In an aspect, the channel quality may be affected by a variety of factors. The factors include movement of the UE 504 along a path or due to rotation (e.g., a user holding and/or rotating the UE 504), movement along a path behind obstacles, and/or movement within particular environmental conditions (e.g., obstacles, rain, humidity). The UE 504 and the base station 502 may also exchange other information, for example, associated with for beamforming (e.g., analog or digital beamforming capabilities, beamforming type, timing information, configuration information, etc.).

Based on the received information, the base station 502 and/or the UE 504 may determine various configuration information, such as mmW network access configuration information, information for adjusting beam sweeping periodicity, information regarding overlapping coverage for predicting a handoff to another base station, such as a mmW base station.

In an aspect, a beam set may contain eight different beams. For example, FIG. 5A illustrates eight beams 521, 522, 523, 524, 525, 526, 527, 528 for eight directions. In aspects, the base station 502 may be configured to beamform for transmission of at least one of the beams 521, 522, 523, 524, 525, 526, 527, 528 toward the UE 504. In one aspect, the base station 502 can sweep/transmit directions using eight ports during a subframe (e.g., synchronization subframe).

In an aspect, a base station may transmit a signal, such as a beam reference signal (BRS), in a plurality of directions, for example, during a synchronization subframe. In one aspect, this transmission may be cell-specific. Referring to FIG. 5B, the base station 502 may transmit a first set of beams 521, 523, 525, 527 in four directions. For example, the base station 502 may transmit a BRS in a synchronization subframe of each of the transmit beams 521, 523, 525, 527.

In an aspect, these beams 521, 523, 525, 527 transmitted in the four directions may be odd-indexed beams 521, 523, 525, 527 for the four directions out of a possible eight for the beam set. For example, the base station 502 may be capable of transmitting beams 521, 523, 525, 527 in directions adjacent to other beams 522, 524, 526, 528 that the base station 502 is configured to transmit. In an aspect, this

configuration in which the base station 502 transmits beams 521, 523, 525, 527 for the four directions may be considered a “coarse” beam set.

The UE 504 may determine a respective beam index (sometimes abbreviated as “BI”) corresponding to a respective beam. In various aspects, the beam index may be indicate at least a direction for communicating through a corresponding beam toward the UE 504 (e.g., a beamforming direction). For example, the beam index may be a logical beam index associated with an antenna port, OFDM symbol index, and/or BRS transmission period, which may be indicated by one or more bits (e.g., 9 bits). For example, the UE 504 may be configured to determine a beam index corresponding to a beam based on a time at which a BRS is received—e.g., a symbol or slot during which a BRS is received may indicate a beam index corresponding to a beam.

In FIG. 5C, the UE 504 may determine or select a beam index (sometimes abbreviated as “BI”) that is strongest or preferable. For example, the UE 504 may determine that the beam 525 carrying a BRS is strongest or preferable. The UE 504 may select a beam by measuring values for a received power or received quality associated with each of the first set of beams 521, 523, 525, 527. In one aspect, the received power may be referred to as a BRS received power (BRSRP).

The UE 504 may compare respective values to one another. The UE 504 may select a “best” beam. In an aspect, the best beam may be a beam that corresponds to the greatest or highest value (e.g., the best beam may be a beam with the highest BRSRP). The selected beam may correspond to a beam index, which may be a beam index with respect to the base station 502. For example, the UE 504 may determine that the BRSRP corresponding to the fifth beam 525 is the highest, and therefore the fifth beam 525 is the best beam as determined by the UE 504.

The UE 504 may transmit a first indication 560 of the fifth beam 525 to the base station 502. In an aspect, the first indication 560 may include a request to transmit a beam refinement reference signal (BRRS). The BRRS may be UE-specific. One of ordinary skill would appreciate that the BRRS may be referred to by different terminology without departing from the present disclosure, such as a beam refinement signal, a beam tracking signal, or another term.

In one aspect, the base station 502 may trigger transmission of the first indication 560. For example, the base station 502 may trigger transmission of the first indication 560 by a DCI message.

The base station 502 may receive the first indication 560. In one aspect, the first indication 560 may include a beam adjustment request (BAR). (e.g., a request for beam tracking, a request for a BRRS, a request for the base station to start transmitting on an indicated beam index without any further beam tracking, and the like). In one aspect, the first indication 560 may be indicated by a scheduling request. Based on the first indication 560, the base station 502 may determine the beam index corresponding to the fifth beam 525.

In FIG. 5D, the base station 502 may transmit a second set of beams based on the first indication 560 (e.g., based on a beam index indicated by the first indication 560). For example, the UE 504 may indicate that a fifth beam 525 is the best beam and, in response, the base station 502 may transmit a second set of beams 524, 525, 526 to the UE 504 based on the indicated beam index. In an aspect, the beams 524, 525, 526 transmitted based on the first indication 560

may be closer (e.g., spatially and/or directionally) to the fifth beam **525** than those other beams **521**, **523**, **527** of the first set of beams.

In an aspect, the beams **524**, **525**, **526** transmitted based on the first indication **560** may be considered a “fine” beam set. In an aspect, the base station **502** may transmit a BRRS through each of the beams **524**, **525**, **526** of the fine beam set. In an aspect, the beams **524**, **525**, **526** of the fine beam set may be adjacent. In an aspect, BRRS transmission can span 1, 2, 5 or 10 OFDM symbols and may be associated with a BRRS resource allocation, BRRS process indication, and/or a beam refinement process configuration.

Based on the BRRS transmission through the beams **524**, **525**, **526** of the fine beam set, the UE **504** may transmit a second indication **565** to the base station **502** to indicate a “best” beam. In an aspect, the second indication **565** may use two (2) bits to indicate the selected beam. For example, the UE **504** may transmit the second indication **565** that indicates a beam index corresponding to the selected beam **525**. In one aspect, the second indication **565** may report beam refinement information (BRI). In one aspect, the second indication **565** may include a resource index (e.g., a BRRS-RI) and/or a reference power (RP) associated with the reception of the BRRS as measured by the UE **504** (e.g., a BRRS-RP). The base station **502** may then communicate with the UE **504** through the selected beam **525**.

Referring to FIG. 5E, the base station **502** may transmit a BRS in a plurality of directions during a synchronization subframe. In an aspect, the base station **502** may transmit the BRS continuously, e.g., even after the UE **504** has communicated the second indication **565**. For example, the base station **502** may transmit beams **521**, **523**, **525**, **527** that each include a BRS (e.g., a “coarse” beam set).

Referring to FIG. 5F, the quality of a selected beam **525** may deteriorate so that the UE **504**. For example, when the base station **502** and the UE **504** are communicating through the selected beam **525**, the selected beam **525** may become occluded or otherwise unsatisfactory such that the base station **502** and the UE **504** may prefer to communicate through another beam. Based on the BRS (e.g., transmitted during a synchronization subframe), the UE **504** may determine a new beam **523** through which to communicate. For example, the UE **504** may determine that the third beam **523** through which a BRS is communicated may be the best beam. The UE **504** may select a beam based by measuring values for a received power (e.g., BRSRP) or received quality associated with each of the set of beams **521**, **523**, **525**, **527**, comparing respective values to one another, and selecting the beam that corresponds to the highest value. The selected beam may correspond to a beam index at the base station **502**. The UE **504** may transmit a third indication **570** indicating this beam index to the base station **502**. In an aspect, the third indication **570** may include a request to transmit a BRRS. The BRRS may be UE-specific. In one aspect, a BAR may be used to request the base station **502** to transmit a BRRS. In one aspect, the third indication **570** may be triggered by the base station **502**, such as by a DCI message. Similar to the first indication **560**, the third indication **570** may be included in a scheduling request.

With respect to FIG. 5G, the base station **502** may receive the third indication **570** from the UE **504**. The base station **502** may be configured to determine a beam index based on at least the third indication **570**. The base station **502** and the UE **504** may perform a beam refinement procedure, such as illustrated with respect to FIG. 5E (e.g., in order to select a new beam through which to communicate).

Referring to FIG. 6, a diagram of a wireless communications system **600** is illustrated. The base station **602** may be an aspect of the base station **502**, the base station **310**, the base station **102**, the mmW base station **180**, and/or another base station. The UE **604** may be an aspect of the UE **504**, the UE **350**, the UE **104**, the UE **182**, and/or another UE.

In the illustrated aspect, the base station **602** may include up to 8 antenna ports for BRS transmission. In various aspects, the base station **602** may send, to the UE **604**, one or more BRSs **612a-h** (e.g., as described with respect to FIGS. 5A-5G). Each BRS **612a-h** may be communicated through a respective beam **620a-h**. For example, the base station **602** may send a first BRS **612a** through the first beam **620a** with which the first BRS **612a** is associated. The UE **604** may track one or more beams **620a-h** through periodically measuring a BRS **612a-h** associated with a respective one of the beams **620a-h**. In an aspect, the transmission period of the BRSs **612a-h** may be configured by an indicator on a physical broadcast channel (PBCH), such as an enhanced or evolved PBCH (ePBCH). The transmission period may be associated with the time to sweep the beams **620a-h** through which the BRS **612a-h** is transmitted.

In aspects, the UE **604** may receive, through the set of beams **620a-h**, a set of BRSs **612a-h**. Each BRS **612a-h** may be associated with a beam index that corresponds to the beam **620a-h** through which the BRS **612a-h** is sent. The UE **604** may measure a signal quality of each BRS **612a-h**, and each measured signal quality may correspond to a beam **620a-h** of the set of beams. For example, the UE **604** may measure the signal qualities of the third BRS **612c**, the fourth BRS **612d**, the fifth BRS **612e**, and the sixth BRS **612f**, which respectively correspond to the third beam **620c**, the fourth beam **620d**, the fifth beam **620e**, and the sixth beam **620f**. In aspects, the UE **604** may not receive each of the BRSs **612a-h**.

In one aspect, the UE **604** may measure the signal quality as a received power. In one aspect, the signal quality may correspond to a BRSRP. For example, the UE **604** may measure the BRSRP in decibels (dB) and/or decibel-milliwatts (dBm). In other aspects, the UE **604** may measure the signal quality as another value, such as a received quality (RQ) (e.g., a BRSRQ), an signal-to-interference ratio (SIR), a signal-to-interference-plus-noise ratio (SINR), a reference signal received power (RSRP), a reference signal received quality (RSRQ), a received signal strength indicator (RSSI), or another metric.

In an aspect, the UE **604** may maintain a set of candidate beam indexes **630** corresponding to a set of the best measured signal qualities for BRSs **612a-h** received through the beams **620a-h**. For example, the best measured signal qualities may correspond to the highest measured signal qualities. The number N of candidate beam indexes in the set of candidate beam indexes **630** may be predetermined (e.g., N may equal 4). In an aspect, the UE **604** may record a null value when the UE **604** is unable to measure signal qualities of N beams. For example, if N equals four and the UE **604** is unable to measure a fourth signal quality, the UE **604** may record a null value in the set of candidate beam indexes **630**.

In an aspect, the UE **604** may maintain the set of candidate beam indexes **630** based on a most recent set of signal qualities measured for the set of BRSs **612a-h**. That is, the set of candidate beam indexes **630** may be the correspond to the measured signal qualities for each of the BRSs **612a-h** that is most recently received by the UE **604**.

In another aspect, the UE **604** may maintain the set of candidate beam indexes **630** based on a time-averaged set of signal qualities of the set of BRSs **612a-h**. For example, the

UE 604 may receive a plurality of sets of the BRSs 612a-h, which may be periodically transmitted by the base station 602. The UE 604 may average a respective signal qualities measured for each BRS of the set of BRSs 612a-h—e.g., the UE 604 may average the most recent three or four measured signal qualities for the first BRS 612a, the UE 604 may average the most recent three or four measured signal qualities for the second BRS 612b, and so forth. The UE 604 may maintain the set of candidate beam indexes 630 based on the time-averaged set of signal qualities of BRSs.

In another aspect, the UE 604 may maintain the set of candidate beam indexes 630 based on a filtered set of signal qualities of BRSs 612a-h. For example, the UE 604 may apply a filter during or after measuring the signal qualities for the BRSs 612a-h in order to determine the best or highest signal qualities corresponding to the best or highest BRSs of the set of BRSs 612a-h.

In one aspect, the UE 604 may maintain the set of candidate beam indexes 630 based on one or more other criteria, which may be received (e.g., from the base station 602) and/or determined by the UE 604. In one aspect, the UE 604 may maintain the set of candidate beam indexes 630 based on an indication of one or more beams to include or exclude from the maintained set of candidates beam indexes 630. The indication of one or more beams to include or exclude may be received from the base station 602, and may include one or more beam indexes. According to aspects, the UE 604 may then include or exclude indicated beam indexes from the set of candidate beam indexes 630.

In another aspect, the UE 604 may maintain the set of candidate beam indexes 630 based on one or more hysteresis criteria for including a beam index in or excluding a beam index from the set of candidate beam indexes 630. The hysteresis criteria may include, for example, inclusion in or exclusion from the set of candidate beam indexes 630 if a measured signal quality deviates from a predetermined value (e.g., a predetermined threshold) or deviates from another signal quality measured for another BRS of the set of BRSs 612a-h. In another aspect, the hysteresis criteria may include inclusion or exclusion from the set of candidate beam indexes 630 if a predetermined number of values (e.g., BRSRPs) measured for a BRSs of a beam fall below (e.g., for exclusion) or exceed (e.g., for inclusion) a predetermined threshold. For example, if the 3 most recent BRSRPs measured for the third BRSs 612c fall below a threshold value, then the beam index corresponding to the third beam 620c may be excluded from the candidate beam set 630 (although the beam index corresponding to the third beam 620c would not be excluded if only one BRSRP measured for the BRSs 612c falls below the threshold value).

According to various aspects, the UE 604 may transmit, to the base station 602, a beam state information (BSI) report 642 indicating at least one beam index. In an aspect, the BSI report 642 may be a BSI report that includes a beam index and a corresponding measured signal quality (e.g., the BRSRP measured for a BRS 612a-h received through a beam 620). For example, the UE 604 may select a beam index and corresponding signal quality from the maintained set of candidate beam indexes 630, and transmit the selected beam index and corresponding signal quality in the BSI report 642. In an aspect, the UE 604 may transmit the BSI report 642 in response to a request 640 received from the base station 602.

In an aspect, the BSI report 642 may be carried on a PUCCH or a PUSCH. For example, the UE 604 may send,

to the base station 602, the BSI report 642 on a PUCCH (e.g., an enhanced PUCCH) or a PUSCH (e.g., an enhanced PUSCH).

Referring to FIG. 7, a diagram of a wireless communications system 700 is illustrated. The base station 702 may be an aspect of the base station 602, the base station 502, the base station 310, the base station 102, the mmW base station 180, and/or another base station. The UE 704 may be an aspect of the UE 604, the UE 504, the UE 350, the UE 104, the UE 182, and/or another UE.

In the illustrated aspect, the base station 702 may include up to 8 antenna ports for BRS transmission. In various aspects, the base station 702 may send, to the UE 704, one or more BRSs 712a-h (e.g., as described with respect to FIGS. 5A-5G and/or FIG. 6). Each BRS 712a-h may be communicated through a respective beam 720a-h. For example, the base station 702 may send a first BRS 712a through the first beam 720a with which the first BRS 712a is associated. The UE 704 may track one or more beams 720a-h through periodically measuring a BRS 712a-h associated with a respective one of the beams 720a-h. In an aspect, the transmission period of the BRSs 712a-h may be configured by an indicator on a PBCH, such as an ePBCH. The transmission period may be associated with the time to sweep the beams 720a-h through which the BRS 712a-h is transmitted.

In aspects, the base station 702 may transmit a set of beams 720a-h. According to various aspects, the base station 702 may communicate with the UE 704 through a first serving beam 720e. The first serving beam 720e may correspond to a beam index.

In one aspect, the base station 702 and the UE 704 may communicate through the first serving beam 720e for uplink communication and/or downlink communication. In an aspect, the base station 702 and the UE 704 may use the first serving beam 720e for one of uplink communication or downlink communication, but may use a different beam (e.g., the fourth beam 720d) for the other of uplink communication or downlink communication (e.g., in aspects in which uplink/downlink reciprocity does not work or where the base station 702 is intended to serve the UE 704 on certain beams).

The base station 702 and the UE 704 may be configured to switch beams. In an aspect, the base station 702 may initiate the beam switching. For example, the base station 702 may set up a beam 720a-h for a channel for which a beam 720a-h is not configured. In another example, the base station 702 and/or the UE 704 may select a different beam 720a-h in order to provide a better connection for communication on a channel between the base station 702 and the UE 704. In one aspect, the base station 702 and the UE 704 may modify and/or set up a beam for uplink communication, downlink communication, or both uplink and downlink communication.

In an aspect, the base station 702 may send, to the UE 704, a command 710 associated with beam modification (e.g., a beam modification command or another signal). In one aspect, the base station 702 may include the command 710 in a MAC CE. In another aspect, the base station 702 may include the command 710 in a DCI message. In another aspect, the base station 702 may send the command 710 to the UE 704 via RRC signaling.

The base station 702 may select a beam 720a-h to which to switch for communication between the base station 702 and the UE 704. For example, the base station 702 may determine that communication with the UE 704 is to continue through the fourth beam 720d. The base station 702

may determine a beam index corresponding to the selected fourth beam 720d. The base station 702 may generate a command 710 that is to indicate at least one beam index for communicating through the selected fourth beam 720d on at least one channel. The base station 702 may send, to the UE 704, the command 710 in order to switch the serving beam from the current serving beam 720e to the selected fourth beam 720d.

In various aspects, the base station 702 may determine a channel for which the command 710 is applicable. For example, the base station 702 may determine a beam modification command for an individual channel or for a group of channels. In one aspect, the base station 702 may indicate, via the command 710, at least one channel to which the command 710 is applicable. That is, the base station 702 may indicate, by the command 710, a channel corresponding to a beam index indicated by the command 710. In an aspect, the command 710 may indicate a group of channels that includes the at least one channel determined by the base station 702.

In one aspect, the command 710 may indicate a channel (or group of channels) by a format. For example, the base station 702 may send the command 710 as a DCI message and the format of the DCI message may indicate a channel (or group of channels) to which at least one beam index indicated by the command 710 is applicable. According to another example, the command 710 may indicate a channel (or group of channels) based on inclusion of the command 710 in a MAC CE by the base station 702. For example, inclusion of the command 710 in a MAC CE may indicate, to the UE 704, that the UE 704 is to switch to the beam index indicated by the command 710 for PDCCH, PDSCH, CSI-RS, PUCCH, PUSCH, and/or SRS.

According to an aspect, the base station 702 may generate the command 710 to indicate a plurality of beam indexes. In one aspect, the base station 702 may generate the command 710 to indicate one or more channels. In one aspect, the base station 702 may generate the command 710 to indicate a corresponding channel(s) to which each beam index of the plurality of beam indexes is applicable. That is, the base station 702 may generate the command 710 to indicate a plurality of beam indexes and a plurality of channels, and the command 710 may indicate a corresponding channel (or channel group) for each beam index of the plurality of beam indexes.

According to one example, the base station 702 may determine that the current serving beam 720e should be modified for channel state information reference signals (CSI-RS) and/or BRRS, but the other downlink and/or uplink beams 720a-h should remain unchanged. For example, the base station 702 may continue communication through the current serving beam 720e for other channels other than the CSI-RS and/or BRRS, and switch to the selected fourth beam 720d for communication carried on the CSI-RS and/or BRRS.

In another example, the base station 702 may determine that at least one beam through which the PDCCH and/or PDSCH are communicated should be switched to at least the selected fourth beam 720d, but continue uplink communication through at least the current serving beam 720e.

In a third example, the base station 702 may determine that the current serving beam 720e is to be changed to the selected fourth beam 720d for uplink communication (e.g., including PUSCH, PUCCH, and SRS channels), but continue with the current serving beam 720e for downlink communication (e.g., including PDSCH, PDCCH, CSI-RS, and BRRS), for example, when reciprocity cannot be

assumed and/or to provide scheduling and/or multiplexing flexibility for the base station 702.

While the present disclosure illustrates communication on one beam (e.g., the current serving beam 720e and the selected fourth beam 720d), it will be appreciated that communication on channels may occur through more than one beam.

The UE 704 may receive, from the base station 702, the command 710. In response to the command 710, the UE 704 communicate on at least one channel with the base station 702 through the at least one beam corresponding to the at least one beam index indicated by the command 710. For example, the UE 704 may switch the current serving beam 720e at the UE 704 to the selected fourth beam 720d after receiving the command 710. Accordingly, the UE 704 may communicate with the base station 702 through the selected fourth beam 720d.

In one aspect, the UE 704 may switch beams at a determined time, which may correspond to a symbol or a subframe. The UE 704 may determine the time (e.g., subframe) based on the command 710. For example, when the base station 702 includes the command 710 in a MAC CE, the UE 704 may determine to switch communication through the current serving beam 720e to the selected fourth beam 720d at the beginning of a subframe $n+k_{\text{beamswitch-delay-mac}}$, where n is the subframe used for HARQ-ACK transmission associated with the MAC CE and $k_{\text{beamswitch-delay-mac}}$ is equal to 14.

According to another example, the UE 704 may receive the command 710 in a DCI message. In response to receiving the command 710 in a DCI message, the UE 704 may switch from the current serving beam 720e to the selected fourth beam 720d at the beginning of a subframe $n+k_{\text{beamswitch-delay-dci}}$, where n is the subframe used for transmission of a BSI report (e.g., the BSI report 642) and $k_{\text{beamswitch-delay-dci}}$ is equal to 11.

According to an aspect, the command 710 may include a request from the base station 702 for a BSI report, such as the request 640. The request for a BSI report may be communicated via a DCI message. In such an aspect, the base station 702 may set a field (e.g., a beam switch indication field) of DCI message to a predetermined value, such as "1" to indicate that the UE 704 is to switch beams and "0" to indicate that the UE 704 is to continue communicating using the current serving beam 720e. When the base station 702 indicates the command 710 by setting a field of a DCI message to a predetermined value indicating a beam switch command, the UE 704 may determine that the UE 704 is to switch to the first beam indicated by a BSI report (e.g., the BSI report 642).

After switching from the current serving beam 720e to the selected fourth beam 720d indicated by the command 710, the UE 704 and the base station 702 may communicate on at least one channel through the selected fourth beam 720d. Accordingly, the beam index corresponding to the selected fourth beam 720d for communication by the UE 704 may match the beam index corresponding to the selected fourth beam 720d for communication by the base station 702.

With reference to FIG. 8, a diagram of a wireless communications system 800 is illustrated. The base station 802 may be an aspect of the base station 702, the base station 602, the base station 502, the base station 310, the base station 102, the mmW base station 180, and/or another base station. The UE 804 may be an aspect of the UE 704, the UE 604, the UE 504, the UE 350, the UE 104, the UE 182, and/or another UE.

25

In the illustrated aspect, the base station **802** may include up to 8 antenna ports for BRS transmission. In various aspects, the base station **802** may send, to the UE **804**, one or more BRSs **812a-h** (e.g., as described with respect to FIGS. 5A-5G, FIG. 6, and/or FIG. 7). Each BRS **812a-h** may be communicated through a respective beam **820a-h**. For example, the base station **802** may send a first BRS **812a** through the first beam **820a** with which the first BRS **812a** is associated. The UE **804** may track one or more beams **820a-h** through periodically measuring a BRS **812a-h** associated with a respective one of the beams **820a-h**. In an aspect, the transmission period of the BRSs **812a-h** may be configured by an indicator on a PBCH, such as an ePBCH. The transmission period may be associated with the time to sweep the beams **820a-h** through which the BRS **812a-h** is transmitted.

In aspects, the UE **804** may receive, through the set of beams **820a-h**, a set of BRSs **812a-h**. Each BRS **812a-h** may correspond to a beam index that corresponds to the beam **820a-h** through which the BRS **812a-h** is sent. The UE **804** may measure a signal quality of each BRS **812a-h**, and each measured signal quality may correspond to a beam **820a-h** of the set of beams. For example, the UE **804** may measure the signal qualities of the third BRS **812c**, the fourth BRS **812d**, the fifth BRS **812e**, and the sixth BRS **812f**, which respectively correspond to the third beam **820c**, the fourth beam **820d**, the fifth beam **820e**, and the sixth beam **820f**. In aspects, the UE **804** may not receive each of the BRSs **812a-h**.

In one aspect, the UE **804** may measure the signal quality by determining a received power. In one aspect, the signal quality may correspond to a BRSRP. For example, the UE **804** may measure the BRSRP in dB and/or dBm. In other aspects, the UE **804** may measure the signal quality as another value, such as a RQ, an SIR, a SINR, a RSRP, a RSRQ, a RSSI, or another metric.

In an aspect, the UE **804** may maintain a set of candidate beam indexes **830** corresponding to a set of the best measured signal qualities for BRSs **812a-h** received through the beams **820a-h**. For example, the best measured signal qualities may correspond to the highest determined received powers (e.g., the highest determined BRSRPs). The number N of candidate beam indexes in the set of candidate beam indexes **830** may be predetermined (e.g., N may equal 4). In an aspect, the UE **804** may record a null value when the UE **804** is unable to measure signal qualities of N beams. For example, if N equals four and the UE **804** is unable to measure a fourth signal quality, the UE **804** may record a null value in the set of candidate beam indexes **830**. The UE may sort the set of candidate beam indexes **830** in decreasing order of BRSRP.

According to aspects, the base station **802** may determine a number of BSI reports that the UE **804** is to transmit to the base station **802**. For example, the base station **802** may communicate with the UE **804** through a second beam **820b**, which may be a serving beam. The base station **802** may determine that communication is to occur through a different beam and/or that the base station **802** is to store information indicating alternative (e.g., candidate) beam(s) that may be used for communication with the UE **804** in the future (e.g., in case a serving beam fails, a power and/or quality of a serving beam deteriorates, etc.). Accordingly, the base station **802** may request that the UE **804** send BSI reports to the base station **802**.

The base station **802** may determine that zero, one, or more than one (e.g., two or four) BSI reports should be sent to the base station by the UE **804**. Therefore, the base station

26

802 may send, to the UE **804**, a message **840** indicating a number X of BSI reports (e.g., zero, one, two, or four) that are to be sent to the base station **802** by the UE **804**.

In various aspects, the base station **802** may transmit, to the UE **804**, a message **840** requesting BSI reports. In one aspect, the message **840** may be a two-bit message. In one aspect, the message **840** may be included in or indicated by a DCI message. The message **840** may be included in an uplink DCI message or a downlink DCI message. Further, the message **840** may be one of a plurality of DCI formats. In another aspect, the message **840** may be included in a random access response (RAR) message (e.g., the MSG2 **412**, an uplink grant, etc.). In another aspect, the base station **802** may transmit, to the UE **804**, the message **840** via RRC signaling (e.g., the base station **802** may transmit the message **840** as an RRC message).

According to various aspects, the UE **804** may transmit, to the base station **802**, a BSI report **842** indicating at least one beam index. In an aspect, the BSI report **842** may be a BSI report that includes a beam index (e.g., a beam index **832**) and a corresponding measured signal quality (e.g., the BRSRP **834** measured for a BRS **812a-h** received through a beam **820**). In an aspect, the UE **804** may transmit the BSI report **842** in response to a message **840** (e.g., request) received from the base station **802**.

In the illustrated aspect, the UE **804** may determine a number N of candidate beam indexes (e.g., N may be equal to 4) based on determining BRSRPs **834** for BRSs **812a-h** corresponding to beams **820a-h**. For example, the UE **804** may measure a third BRSRP **834c** for the third BRS **812c** corresponding to the third beam **820c**, a fourth BRSRP **834d** for the fourth BRS **812d** corresponding to the fourth beam **820d**, a fifth BRSRP **834e** for the fifth BRS **812e** corresponding to the fifth beam **820e**, and a sixth BRSRP **834f** for the sixth BRS **812f** corresponding to the sixth beam **820f**.

The UE **804** may store the BRSRPs **834c-f** for the BRSs **812c-f** and respective corresponding beam indexes **832c-f** in the set of candidate beam indexes **830**. The UE **804** may maintain the set of candidate beam indexes **830** by sorting the beam indexes **832c-f** based on the corresponding BRSRPs **834c-f**. For example, the beam indexes **832c-f** may be sorted by the “best” (e.g., highest) corresponding BRSRPs **834c-f**. Further to such an example, the fifth BRSRP **834e** corresponding to the fifth beam index **832e** may be a highest BRSRP and, therefore, stored first in the set of candidate beam indexes **830**. The sixth BRSRP **834f** corresponding to the sixth beam index **832f** may be a second highest BRSRP and, therefore, stored second in the set of candidate beam indexes **830**, and so forth.

Based on the message **840** requesting BSI reports, the UE **804** may determine a number X of BSI reports **842** to send to the base station **802**. Each BSI report **842** may include at least a beam index (e.g., a beam index **832**) and a received power (e.g., a BRSRP **834**) associated with a beam **820a-h** through which a BRS **812a-h** is received.

According to aspects, the UE **804** may determine the number X of BSI reports **842** to send to the base station **802** based on the message **840** requesting the BSI. In one aspect, the number X may be greater than or equal to zero, but less than or equal to the number N of candidate beam indexes maintained by the UE. In an aspect, the UE **804** may determine the number X based on the message **840** by determining the number X based on a type of the message **840**. A type of message may be, for example, a DCI message (e.g., a downlink DCI message), an RAR message (e.g., the MSG2 **412**, an RAR grant, or another uplink grant, etc.), or another type of message.

In one aspect, the UE 804 may determine that the number X of BSI reports 842 to send to the base station 802 is one when the message 840 is a DCI message (e.g., a downlink DCI message). For example, when the UE 804 receives the message 840 in a downlink DCI message, the UE 804 may determine that one BSI report 842 is to be sent to the base station 802.

In one aspect, the base station 802 may include, in the message 840, an indication of a time and/or frequency resource for a channel that is to carry the BSI report 842. Accordingly, the UE 804 may determine a time and/or frequency resource for a channel that is to carry the BSI report 842 based on the message 840.

In an aspect, the UE 804 may determine the channel that is to carry the BSI report 842 based on the message 840 (e.g., the type of the message 840). For example, the UE 804 may determine that a PUCCH (e.g., an enhanced PUCCH (ePUCCH), xPUCCH, etc.) is to carry the BSI report 842 when the message 840 is a DCI message (e.g., a downlink DCI message).

According to one aspect, the UE 804 may determine the number X of BSI reports to send based on the channel that is to carry the BSI reports 842. For example, the UE 804 may determine that the UE 804 is to send the message on a PUCCH (e.g., based on the message 840). Accordingly, the UE 804 may determine that the UE 804 is to send one BSI report 842 on the PUCCH based on the determination that the PUCCH is to carry the BSI report 842.

In an aspect, when the UE 804 determines that the UE 804 is to send one BSI report, the UE 804 may send a BSI report that includes BSI indicating a beam index 832 corresponding to the highest BRSRP 834 in the set of candidate beam indexes 830. For example, the UE 804 may determine that the fifth BRS 812e received through the fifth beam 820e has a highest BRSRP 834e. Therefore, the UE 804 may send one BSI report 842 that includes the fifth beam index 832e corresponding to the fifth beam 820e and further includes the fifth BRSRP 834e corresponding to the fifth beam index 832e.

In another aspect, the UE 804 may determine that the number X of BSI reports 842 to send to the base station 802 is one or more when the message 840 is an RAR message (e.g., the MSG2 412, an uplink grant, etc.). The RAR message may indicate an uplink grant. In another aspect, another uplink grant may be indicated through an uplink DCI message. For example, when the UE 804 receives the message 840 in an RAR message, the UE 804 may determine that one or more BSI reports 842 are to be sent to the base station 802. In another example, when the UE 804 receives the message 840 in an uplink DCI message, the UE 804 may determine that one or more BSI reports 842 are to be sent to the base station 802.

In one aspect, the base station 802 may include, in the message 840, an indication of at least one time and/or frequency resource for a channel that is to carry the BSI reports 842. For example, the UE 804 may transmit a BSI report 842 on one or more uplink resources associated with a connection request message (e.g., the MSG3 414) granted through a contention-based RACH procedure (e.g., granted through an RAR or MSG2 412). Accordingly, the UE 804 may determine at least one time and/or frequency resource for a channel that is to carry the one or more BSI reports 842 based on the message 840.

In an aspect, the UE 804 may determine the channel that is to carry the one or more BSI reports 842 based on the message 840 (e.g., based on the type of the message 840). For example, the UE 804 may determine that a PUSCH (e.g.,

an enhanced PUSCH (ePUSCH), xPUSCH, etc.) is to carry the BSI reports 842 when the message 840 is included in an RAR message (e.g., the MSG2 412 or an uplink grant, such as an uplink DCI message).

According to one aspect, the UE 804 may determine the number X of BSI reports to send based on the channel that is to carry the BSI reports 842. For example, the UE 804 may determine that the UE 804 is to send the message on a PUSCH (e.g., based on the message 840). Accordingly, the UE 804 may determine that the UE 804 is to send more than one (e.g., two) BSI reports 842 on the PUSCH based on the determination that the PUSCH is to carry the BSI reports 842.

In one aspect, the base station 802 may include, in the message 840, an indication of the number X of BSI reports 842 to be sent. For example, the UE 804 may determine whether to send one, two, or four BSI reports 842 based on an indication of the number X included in the message 840. For example, when the message 840 is included in an uplink DCI message, the uplink DCI message may indicate that zero, two, or four BSI reports are to be sent.

In an aspect, when the UE 804 determines the number X of BSI reports 842 to send, the UE 804 may send X BSI reports 842 for the X beam indexes 832 corresponding to the X highest BRSRPs 834 in the set of candidate beam indexes 830. For example, the UE 804 may determine, based on the message 840, that four BSI reports 842 are requested by the base station 802. Accordingly, the UE 804 may determine that the fifth BRS 812e received through the fifth beam 820e has a highest BRSRP 834e, the sixth BRS 812f received through the sixth beam 820f has a second highest BRSRP 834f, the fourth BRS 812d received through the fourth beam 820d has a third highest BRSRP 834d, and the third BRS 812c received through the third beam 820c has a fourth highest BRSRP 834c. Therefore, the UE 804 may send four BSI reports 842: a first of which may include the fifth beam index 832e and the fifth BRSRP 834e, a second of which may include the sixth beam index 832f and the sixth BRSRP 834f, a third of which may include the fourth beam index 832d and the fourth BRSRP 834d, and a fourth of which may include the third beam index 832c and the third BRSRP 834c. In an aspect, the BSI reports 842 may be sorted in decreasing order of BRSRP 834.

The base station 802 may receive the one or more BSI reports 842. Based on the BSI reports 842, the base station 802 may select a beam 820a-h with which to communicate with the UE 804. For example, the base station 802 may select the fifth beam 820e corresponding to the fifth beam index 832e having the highest BRSRP 834e, as indicated by at least one BSI report 842. In an aspect, the base station 802 may select another beam (e.g., the sixth beam 820f) based on the BSI reports 842, for example, if communication through the selected beam (e.g., the fifth beam 820e) fails.

Turning to FIG. 9, a diagram of a wireless communications system 900 is illustrated. The base station 902 may be an aspect of the base station 802, the base station 702, the base station 602, the base station 502, the base station 310, the base station 102, the mmW base station 180, and/or another base station. The UE 904 may be an aspect of the UE 804, the UE 704, the UE 604, the UE 504, the UE 350, the UE 104, the UE 182, and/or another UE.

In the illustrated aspect, the base station 902 may include up to 8 antenna ports for BRS transmission. In various aspects, the base station 902 may send, to the UE 904, one or more BRSs 912a-h (e.g., as described with respect to FIGS. 5A-5G, FIG. 6, FIG. 7, and/or FIG. 8). Each BRS 912a-h may be communicated through a respective beam

920a-h. For example, the base station 902 may send a first BRS 912a through the first beam 920a with which the first BRS 912a is associated. The UE 904 may track one or more beams 920a-h through periodically measuring a BRS 912a-h associated with a respective one of the beams 920a-h. In an aspect, the transmission period of the BRSs 912a-h may be configured by an indicator on a PBCH, such as an ePBCH. The transmission period may be associated with the time to sweep the beams 920a-h through which the BRS 912a-h is transmitted.

In aspects, the UE 904 may receive, through the set of beams 920a-h, a set of BRSs 912a-h. Each BRS 912a-h may correspond to a beam index that corresponds to the beam 920a-h through which the BRS 912a-h is sent. The UE 904 may measure a signal quality of each BRS 912a-h, and each measured signal quality may correspond to a beam 920a-h of the set of beams. For example, the UE 904 may measure the signal qualities of the third BRS 912c, the fourth BRS 912d, the fifth BRS 912e, and the sixth BRS 912f, which respectively correspond to the third beam 920c, the fourth beam 920d, the fifth beam 920e, and the sixth beam 920f. In aspects, the UE 904 may not receive each of the BRSs 912a-h.

In one aspect, the UE 904 may measure the signal quality by determining a received power. In one aspect, the signal quality may correspond to a BRSRP. For example, the UE 904 may measure the BRSRP in dB and/or dBm. In other aspects, the UE 904 may measure the signal quality as another value, such as a RQ, an SIR, a SINR, a RSRP, a RSRQ, a RSSI, or another metric.

In an aspect, the UE 904 may select a beam 920a-h for communication with the base station 902. For example, the UE 904 may select the fifth beam 920e. The UE 904 may select this fifth beam 920e for one or both of uplink and/or downlink communication. The UE 904 may select the fifth beam 920e based on a signal quality measured for the fifth BRS 912e and/or based on resource information (e.g., time and/or frequency resource information, which may be broadcast by the base station 902 as system information). The UE 904 may select the fifth beam 920e because the UE 904 may anticipate or estimate that the base station 902 may communicate with the UE 904 through the fifth beam 920e, for example, based on the signal quality measured for the fifth BRS 912e corresponding to the fifth beam 920e and/or resource information (e.g., time and/or frequency resource information, which may indicate a time (e.g., subframe) and/or frequency).

The UE 904 may attempt a RACH procedure (e.g., the first RACH procedure 940, the second RACH procedure 942, etc.). A RACH procedure may include various operations described with respect to FIG. 4A or 4B. For example, the UE 904 may attempt a RACH procedure (e.g., a contention-based RACH procedure) by transmitting one or more RACH messages, such as a random access preamble (e.g., the MSG1 410). The UE 904 may be still attempting the RACH procedure when transmitting another RACH message, such as a connection request (e.g., the MSG3 414) in response to an RAR (e.g., the MSG2 412).

The UE 904 may determine the attempted RACH procedure has failed when the UE 904 fails to receive and/or decode a contention resolution message (e.g., the MSG4 416) during the attempted RACH procedure. By extension, the UE 904 would determine that an attempted RACH procedure has failed when the UE 904 fails to receive an RAR (e.g., the MSG2 412) because the UE 904 would neither send a connection request (e.g., the MSG 413) nor receive a contention resolution message (e.g., the MSG4

416) during the attempted RACH procedure. In an aspect, the UE 904 may determine a RACH procedure is successfully completed when the UE 904 receives a contention resolution message (e.g., the MSG4 416), when the UE 904 acquires a cell RNTI (C-RNTI) (e.g., based on the contention resolution message), when the UE 904 receives and decodes an RRC connection setup message, and/or when the UE 904 is synchronized with the network after the RACH procedure.

In an aspect, the UE 904 may attempt a first RACH procedure 940 with the base station 902 through the selected fifth beam 920e. For example, the UE 904 may send a random access preamble (e.g., the MSG1 410) through the selected fifth beam 920e. However, the UE 904 may determine that the first RACH procedure 940 has failed. For example, the UE 904 may fail to receive an RAR (e.g., the MSG2 412) or a contention resolution message (e.g., the MSG4 416).

Based on the attempted first RACH procedure 940, the UE 904 may determine information indicating that the first RACH procedure 940 failed. The UE 904 may store this determined information. In one aspect, the information indicating that the first RACH procedure 940 failed may include information associated with the selected fifth beam 920e, such as a beam index corresponding to the selected fifth beam 920e and/or a signal quality (e.g., a BRSRP) measured for the fifth BRS 912e received through the fifth beam 920e. In another aspect, the information indicating that the first RACH procedure 940 failed may include an indication of a subframe and/or symbol (e.g., a subframe index and/or a symbol index) during which a RACH message (e.g., a random access preamble or the MSG1 410) is sent through the selected fifth beam 920e.

According to aspects, the UE 904 may attempt a second RACH procedure 942 after the determination that the first RACH procedure 940 has failed. The UE 904 may determine that the second RACH procedure 942 is successful. For example, the UE 904 may successfully send a random access preamble (e.g., the MSG1 410) to the base station 402. The UE 904 may then successfully receive an RAR (e.g., the MSG2 412) from the base station 402 based on the random access preamble. The UE 904 may then successfully send a connection request message (e.g., the MSG3 414) to the base station 402 based on the RAR. The UE 904 may then successfully receive a contention resolution message (e.g., the MSG4 416) from the base station based on the connection request message. The UE 904 may be synchronized with a network that includes the base station 902 based on the successful second RACH procedure 942.

In one aspect, the UE 904 may attempt the second RACH procedure 942 by increasing a transmission power after the determination that the first RACH procedure 940 failed. When the UE 904 performs the second RACH procedure 942, the UE 904 may perform at least a portion of the second RACH procedure 942 with the increased transmission power. For example, the UE 904 may send the random access preamble (e.g., the MSG1 410) with the increased transmission power during the second RACH procedure 942.

In another aspect, the UE 904 may attempt the second RACH procedure 942 by selecting a new beam for communication with the base station 902 after the determination that the first RACH procedure 940 failed. For example, the UE 904 may select the sixth beam 920f. In an aspect, the UE 904 may select the new sixth beam 920f based on a signal quality measured for the sixth BRS 912f. In one aspect, the UE 904 may select the new sixth beam 920f based on

resource information (e.g., at least one time and/or frequency resource, which may be broadcast by the base station 902). The UE 904 may perform at least a portion of the second RACH procedure 942 with the base station 902 through the new sixth beam 920f. For example, the UE 904 may send a random access preamble (e.g., the MSG1 410) through the new sixth beam 920f.

According to various aspects, the UE 904 may send, to the base station 902, information 944 indicating that the first RACH procedure 940 failed. The information 944 may include the information determined by the UE 904, such as a beam index corresponding to the selected fifth beam 920e, a signal quality measured for the fifth BRS 912e, a subframe index at which the UE 904 used the selected fifth beam 920e, a symbol index at which the UE 904 used the selected fifth beam 920e, etc.

In one aspect, the UE 904 may send the information 944 in a BSI report (e.g., a BSI report 842). The information 944 may indicate the beam index corresponding to the selected fifth beam 920e through which the first RACH procedure 940 failed. In the context of FIG. 8, the UE 904 may send a BSI report 842 including the fifth beam index 832e corresponding to the selected fifth beam 820e/920e, and may send the information 944 indicating that the first RACH procedure 940 failed using the selected fifth beam 820e/920e. For example, the base station 902 may trigger BSI reporting by the UE 904 using a message 840 that is an RAR message received during the second RACH procedure 942. In response, the UE 904 may send a BSI report 842 that includes the fifth beam index 832e (and the fifth BRSRP 834e), but may indicate that the first RACH procedure 940 failed using the selected fifth beam 820e/920e corresponding to the fifth beam index 832e.

According to an aspect, the UE 904 may exclude a beam index corresponding to the selected fifth beam 920e from a set of candidate beam indexes. In the context of FIG. 6, for example, the UE 904 may exclude the fifth beam index corresponding to the fifth beam 620e/920e from the set of candidate beam indexes 630. The UE 904 may include another beam index corresponding to another beam 920a-h in the set of candidate beam indexes 630, for example, if a BRSRP is measured for another BRS 912a-h corresponding to another beam 920a-h.

In various aspects, the base station 902 may receive the information 944 indicating that the first RACH procedure 940 failed and may use this information 944 for communication with the UE 904. In one aspect, the base station 902 may schedule uplink or downlink communication with the UE 904 through different beams (e.g., the new sixth beam 920f), for example, when uplink/downlink reciprocity through one or more beams is unattainable for communication with the UE 904. For example, the base station 902 may determine a different beam index corresponding to a different beam than the beam index associated with the failed RACH procedure 940 for uplink or downlink communication with the UE 904. In another aspect, the base station 902 may exclude a beam index indicated by the information 944 from a set of candidate beam indexes associated with uplink or downlink communication with the UE 904.

While FIG. 9 illustrates one failed RACH procedure 940, similar operations may be performed when a plurality of RACH procedures fails. Accordingly, the UE 904 may send, to the base station 902, information similar to the information 944 indicating that each RACH procedure failed. For example, the UE 904 may send a respective beam index for each beam used for each failed RACH procedure.

FIG. 10 illustrates an aspect of a wireless communications system 1000, according to various aspects. The base station 1002 may be an aspect of the base station 902, the base station 802, the base station 702, the base station 602, the base station 502, the base station 310, the base station 102, the mmW base station 180, and/or another base station. The UE 1004 may be an aspect of the UE 904, UE 804, the UE 704, the UE 604, the UE 504, the UE 350, the UE 104, the UE 182, and/or another UE.

In the illustrated aspect, the base station 1002 may include up to 8 antenna ports for BRS transmission. In various aspects, the base station 1002 may send, to the UE 1004, one or more BRSs 1012a-h (e.g., as described with respect to FIGS. 5A-5G, FIG. 6, FIG. 7, and/or FIG. 8). Each BRS 1012a-h may be communicated through a respective beam 1020a-h. For example, the base station 1002 may send a first BRS 1012a through the first beam 1020a with which the first BRS 1012a is associated. The UE 1004 may track one or more beams 1020a-h through periodically measuring a BRS 1012a-h associated with a respective one of the beams 1020a-h. In an aspect, the transmission period of the BRSs 1012a-h may be configured by an indicator on a PBCH, such as an ePBCH. The transmission period may be associated with the time to sweep the beams 1020a-h through which the BRS 1012a-h is transmitted.

In aspects, the UE 1004 may receive, through the set of beams 1020a-h, a set of BRSs 1012a-h. Each BRS 1012a-h may be associated with a beam index that corresponds to the beam 1020a-h through which the BRS 1012a-h is sent. The UE 1004 may measure a signal quality of each BRS 1012a-h, and each measured signal quality may correspond to a beam 1020a-h of the set of beams. For example, the UE 1004 may measure the signal qualities of the third BRS 1012c, the fourth BRS 1012d, the fifth BRS 1012e, and the sixth BRS 1012f, which respectively correspond to the third beam 1020c, the fourth beam 1020d, the fifth beam 1020e, and the sixth beam 1020f. In aspects, the UE 1004 may not receive each of the BRSs 1012a-h.

In one aspect, the UE 1004 may measure the signal quality by determining a received power. In one aspect, the signal quality may correspond to a BRSRP. For example, the UE 1004 may measure the BRSRP in dB and/or dBm. In other aspects, the UE 1004 may measure the signal quality as another value, such as a RQ, an SIR, a SINR, a RSRP, a RSRQ, a RSSI, or another metric.

In an aspect, the UE 1004 may attempt a RACH procedure 1040 with the base station 1002 through a fifth beam 1020e. For example, the UE 1004 may send a random access preamble (e.g., the MSG1 410) through the fifth beam 1020e, the base station 1002 may send an RAR (e.g., the MSG2 412) to the UE 1004 based on the random access preamble, and the UE 1004 may send a connection request message (e.g., the MSG3 414) to the base station 1002 based on the RAR.

The base station 1002 may determine that communication with the UE 1004 is to occur through a serving beam of the beams 1020a-h. For example, the base station 1002 may select the sixth beam 1020f, which may be different than the beam through which at least a portion of the RACH procedure 1040 occurs. Therefore, the base station 1002 may determine that the base station 1002 is to inform the UE 1004 of the beam index corresponding to sixth beam 1020f, for example, by sending a beam modification command to the UE 1004.

The beam modification command may include at least a beam index corresponding to a respective one of the beams 1020a-h. In various aspects, the base station 1002 may

include the beam modification command in a contention resolution message **1042** (e.g., the MSG4 **416**), which may be in response to a connection request message (e.g., the MSG3 **414**) received from the UE **1004** during the RACH procedure **1040**. In other words, the base station **1002** may include, in a contention resolution message **1042**, an indication of at least a beam index corresponding to one of the beams **1020a-h** through which communication between the base station **1002** and the UE **1004** is to occur.

Because the contention resolution message **1042** may be received by more than one UE, the base station **1002** may indicate that the beam modification command included in the contention resolution message **1042** is applicable to the UE **1004**. In one aspect, the base station **1002** may indicate that the beam modification command included in the contention resolution message **1042** is applicable to the UE **1004** by scrambling at least a portion of the contention resolution message using an RNTI associated with the UE **1004** (e.g., an RNTI determined during a portion of the RACH procedure **1040**).

In one aspect, the beam modification command included in the contention resolution message **1042** may include an indication of one or more channels to which the beam modification command is applicable. For example, the base station **1002** may determine that communication with the UE **1004** is to occur through the sixth beam **1020f** for one or more uplink channels or one or more downlink channels. Therefore, the base station **1002** may indicate, in the contention resolution message **1042**, that the beam modification command included in the contention resolution message **1042** is applicable to one or more channels.

The UE **1004** may receive the contention resolution message **1042**, for example, during the RACH procedure **1040**. As described, the contention resolution message **1042** may include at least a beam index corresponding to a beam (e.g., a beam modification command).

The UE **1004** may determine whether the beam index is applicable to the UE **1004**. That is, the UE **1004** may determine whether the base station **1002** is instructing the UE **1004** to communicate with the base station **1002** through another beam, such as the sixth beam **1020f**. In one aspect, the UE **1004** may determine whether the beam index is applicable to the UE by attempting to decode the contention resolution message **1042** based on an RNTI associated with the UE **1004**. If the UE **1004** is able to successfully decode the contention resolution message **1042** based on the RNTI associated with the UE **1004**, the UE **1004** may determine that the beam modification command indicated by the contention resolution message **1042** is applicable to the UE **1004**.

The UE **1004** may provide ACK/NACK information to the base station **1002** based on the contention resolution message **1042**, for example, in order to indicate that the UE **1004** acknowledges the beam modification command. In an aspect, the UE **1004** may transmit, to the base station **1002**, an acknowledgment message **1044** based on a determination that the beam modification command included in the contention resolution message **1042** is applicable to the UE **1004**. In an aspect, the UE **1004** may transmit the acknowledgment message **1044** through the current beam (e.g., the fifth beam **1020e**).

In one aspect, the UE **1004** may refrain from transmitting a non-acknowledgment message to the base station **1002** based on a determination that the beam modification command included in the contention resolution message **1042** is inapplicable to the UE **1004**. For example, if the UE **1004** is

unable to decode the contention resolution message **1042** based on an RNTI associated with the UE **1004**, then the UE **1004** may take no action.

The base station **1002** may determine whether an acknowledgment message is received from the UE **1004** in response to the contention resolution message **1042**. If the base station **1002** determines that an acknowledgment message is unreceived (e.g., absent for a predetermined period of time), the base station **1002** may take no action. For example, the base station **1002** may continue communication with the UE **1004** through a current serving beam, such as the fifth beam **1020e**.

When the base station **1002** receives the acknowledgment message **1044** from the UE **1004**, the base station **1002** may determine that an acknowledgment message is received from the UE **1004** and the UE **1004** has been informed of the beam modification command. Accordingly, the base station **1002** may communicate **1046** through the beam (e.g., the sixth beam **1020f**) corresponding to the beam index indicated by the beam modification command included in the contention resolution message **1042**.

Correspondingly, when the UE **1004** determines that the beam modification command is applicable to the UE **1004**, the UE **1004** may communicate **1046** with the base station **1002** through the beam (e.g., the sixth beam **1020f**) corresponding to the beam index indicated by the beam modification command included in the contention resolution message **1042**. Because the beam modification command may include an indication of one or more channels to which the beam modification command is applicable, the UE **1004** may communicate **1046** with the base station **1002** on the one or more channels indicated by the beam modification command through the beam (e.g., the sixth beam **1020f**) corresponding to the beam index indicated by the beam modification command (e.g., other communication on other channels may occur through another beam, such as the current serving fifth beam **1020e**).

FIG. 11 illustrates an aspect of a wireless communications system **1100**, according to various aspects. The base station **1102** may be an aspect of the base station **1002**, the base station **902**, the base station **802**, the base station **702**, the base station **602**, the base station **502**, the base station **310**, the base station **102**, the mmW base station **180**, and/or another base station. The UE **1004** may be an aspect of the UE **1004**, the UE **904**, UE **804**, the UE **704**, the UE **604**, the UE **504**, the UE **350**, the UE **104**, the UE **182**, and/or another UE.

In the illustrated aspect, the base station **1102** may include up to 8 antenna ports for BRS transmission. In various aspects, the base station **1102** may send, to the UE **1104**, one or more BRSs **1112a-h** (e.g., as described with respect to FIGS. 5A-5G, FIG. 6, FIG. 7, and/or FIG. 8). Each BRS **1112a-h** may be communicated through a respective beam **1120a-h**. For example, the base station **1102** may send a first BRS **1112a** through the first beam **1120a** with which the first BRS **1112a** is associated. The UE **1104** may track one or more beams **1120a-h** through periodically measuring a BRS **1112a-h** associated with a respective one of the beams **1120a-h**. In an aspect, the transmission period of the BRSs **1112a-h** may be configured by an indicator on a PBCH, such as an ePBCH. The transmission period may be associated with the time to sweep the beams **1120a-h** through which the BRS **1112a-h** is transmitted.

In aspects, the UE **1104** may receive, through the set of transmit beams **1120a-h**, a set of BRSs **1112a-h**. Each BRS **1112a-h** may be associated with a beam index that corresponds to the beam **1120a-h** through which the BRS **1112a-h**

is sent. The UE 1104 may measure a signal quality of each BRS 1112*a-h*, and each measured signal quality may correspond to a beam 1120*a-h* of the set of beams. For example, the UE 1104 may measure the signal qualities of the third BRS 1112*c*, the fourth BRS 1112*d*, the fifth BRS 1112*e*, and the sixth BRS 1112*f*, which respectively correspond to the third beam 1120*c*, the fourth beam 1120*d*, the fifth beam 1120*e*, and the sixth beam 1120*f*. In aspects, the UE 1104 may not receive each of the BRSs 1112*a-h*.

In one aspect, the UE 1104 may measure the signal quality by determining a received power. In one aspect, the signal quality may correspond to a BRSRP. For example, the UE 1104 may measure the BRSRP in dB and/or dBm. In other aspects, the UE 1104 may measure the signal quality as another value, such as a RQ, an SIR, a SINR, a RSRP, a RSRQ, a RSSI, or another metric.

In one aspect, the UE 1104 may receive the set of BRSs 1112*a-h* through a set of receive beams 1140*a-h* at the UE 1104. For example, a sixth transmit beam 1120*f* may intersect a fifth receive beam 1140*e*. Therefore, a signal sent by the base station 1102 may be transmitted through a sixth transmit beam 1120*f* and received through a fifth receive beam 1140*e*.

The UE 1104 may not actively maintain all the beams 1140*a-h* simultaneously. In various aspects, the UE 1104 may be configured to generate one or more of the beams 1140*a-h*, for example, based on determination that the UE 1104 may receive a signal through one or more of the receive beams 1140*a-h*. Additionally, the base station 1102 and the UE 1104 may not have an equal number of beams—e.g., the UE 1104 may have fewer than eight beams for communication with the base station 1102.

In an aspect, the UE 1104 may receive a beam modification command 1142 from the base station 1102. For example, the UE 1104 may receive one or more BRSs 1112*a-h* from the base station 1102. The UE 1104 may determine (e.g., select or generate) a receive beam of the set of receive beams 1140*a-h* through which the UE 1104 may expect to receive signals from the base station 1102. For example, the UE 1104 may determine the fourth receive beam 1140*d* through which the UE 1104 may receive signals from the base station 1102. The UE 1104 may receive the beam modification command 1142 from the base station 1102, for example, through the fifth transmit beam 1120*e* and the fourth receive beam 1140*d*.

In an aspect, the beam modification command 1142 may indicate a set of transmit beam indexes corresponding to a set of the transmit beams 1120*a-h* of the base station 1102. For example, the beam modification command 1142 may indicate at least a sixth beam index corresponding to a sixth transmit beam 1120*f* of the base station 1102. The transmit beam index may indicate at least a transmit direction for transmitting a beam by the base station 1102.

In one aspect, the beam modification command 1142 may be received in a MAC CE. In another aspect, the beam modification command 1142 may be received in a DCI message. In another aspect, the beam modification command 1142 may be received via RRC signaling. In one aspect, the beam modification command 1142 may be carried on PDCCH.

The UE 1104 may determine the set of transmit beam indexes indicated by the beam modification command 1142. For example, the UE 1104 may determine that the beam modification command 1142 indicates at least a sixth beam index corresponding to a sixth transmit beam 1120*f* of the base station 1102.

Based on the determined set of transmit beams, the UE 1104 may determine a set of receive beam indexes corresponding to the receive beams 1140*a-h* of the UE 1104. Each receive beam index may indicate at least a receive direction for receiving a receive beam of the receive beams 1140*a-h* by the UE 1104. For example, the UE 1104 may determine at least a fifth receive beam index corresponding to a fifth receive beam 1140*e* of the UE 1104.

The UE 1104 may determine the set of receive beam indexes based on the determined set of transmit beams indicated by beam modification command 1142 in any suitable approach. For example, the UE 1104 may maintain a mapping that maps transmit beam indexes corresponding to transmit beams 1120*a-h* to receive beam indexes corresponding to receive beams 1140*a-h*.

In one aspect, the UE 1104 may be configured to populate the mapping based on reception of the set of BRSs 1112*a-h*. For example, the UE 1104 may receive a sixth BRS 1112*f* through a sixth transmit beam 1120*f* of the base station 1102. The UE 1104 may determine that the sixth BRS 1112*f* is received through a fifth receive beam 1140*e*. Accordingly, the UE 1104 may map maintain a mapping that indicates the sixth transmit beam index corresponding to the sixth transmit beam 1120*f* is mapped to the fifth receive beam index corresponding to the fifth receive beam 1140*e*.

Thus, when the UE 1104 receives the beam modification command 1142, the UE 1104 may determine at least one of the receive beams 1140*a-h* of the UE 1104 through which the UE 1104 may receive signals from the base station 1102 without the base station 1102 explicitly signaling a receive beam to the UE 1104 (e.g., the base station 1102 may elicit the appropriate receive beams 1140*a-h* of the UE 1104 by indicating beam indexes of transmit beams 1120*a-h* to the UE 1104). For example, the UE 1104 may determine a set of receive beam indexes that correspond to the transmit beam indexes indicated by the beam modification command 1142.

In an aspect, the UE 1104 may receive communication from the base station 1102 based on a receive beam corresponding to a receive beam index, which may be determined based on the beam modification command 1142. For example, the UE 1104 may determine that communication from the base station 1102 may be received through the fifth receive beam 1140*e* based on a transmit beam index corresponding to the sixth transmit beam 1120*f* indicated by the beam modification command 1142. In one aspect, the UE 1104 may generate the fifth receive beam 1140*e*, for example, if the fifth receive beam 1140*e* is inactive.

The UE 1104 may receive, from the base station 1102, a BRRS 1144 through the at least one receive beam determined based on the beam modification command 1142. For example, the UE 1104 may determine a fifth receive beam index corresponding to the fifth receive beam 1140*e*, and the UE 1104 may receive the BRRS 1144 through the fifth receive beam 1140*e*.

In an aspect, the BRRS 1144 may be used for beam refinement for communication—e.g., the BRRS may be used by the UE 1104 and the base station 1102 in order to determine a “fine” beam pair (e.g., the beam pair of transmit beam 1120*f* and receive beam 1140*e*) for communication between the UE 1104 and the base station 1102. The BRRS 1144 may span 1, 2, 5 or 10 OFDM symbols and may be associated with a BRRS resource allocation, BRRS process indication, and/or a beam refinement process configuration. For example, as described in FIGS. 5A-G, the UE 1104 may report BRI for beam refinement based on reception of a BRRS.

In one aspect, the UE 1104 may receive the BRRS 1144 in one or more symbols corresponding to one or more respective symbol indexes. For example, one or more symbol indexes may be predetermined (e.g., defined by one or more standards promulgated by 3GPP), and the UE 1104 may have those predetermined symbol indexes stored therein. Accordingly, the UE 1104 may receive the BRRS 1144 at those symbol indexes.

In another aspect, the beam modification command 1142 may indicate one or more symbol indexes in which the BRRS 1144 is to be received. For example, the beam modification command 1142 may indicate that the BRRS 1144 is carried in a fourth symbol of a subframe through a sixth transmit beam 1120f. Accordingly, the UE 1104 may determine that the UE 1104 is to receive at least a portion of the BRRS 1144 using a fifth receive beam 1140e during a fourth symbol of a subframe (e.g., the UE 1104 may actively receive or listen through the fifth receive beam 1140e during a fourth symbol of a subframe).

In one aspect, the UE 1104 may receive different portions of the BRRS 1144 through different receive beams. For example, the UE may receive a first portion of the BRRS 1144 (e.g., the first symbol or first 5 symbols) of the BRRS 1144 through the fifth receive beam 1140e determined based on the beam modification command 1142, and may receive a second portion of the BRRS 1144 (e.g., the second symbol or next 5 symbols) of the BRRS 1144 through the sixth receive beam 1140f, which may also be determined based on the beam modification command 1142 (e.g., included in the set of receive beam indexes determined based on the beam modification command).

In an aspect, the UE 1104 may determine symbol indexes corresponding to symbols of the BRRS 1144 and receive beam indexes corresponding to those symbol indexes. For example, the beam modification command 1142 may indicate a first set of transmit beam indexes corresponding to the fifth transmit beam 1120e and the sixth transmit beam 1120f. The UE 1104 may determine (e.g., based on the beam modification command 1142 and/or based on predetermined symbol indexes) that a first portion of the BRRS 1144 is to be received through the fifth transmit beam 1120e and a second portion of the BRRS 1144 is to be received through the sixth transmit beam 1120f. The UE 1104 may determine the fourth receive beam 1140d and the fifth receive beam 1140e respectively corresponding to the transmit beam indexes for the fifth transmit beam 1120e and the sixth transmit beam 1120f. Accordingly, the UE 1104 may receive a first portion of the BRRS 1144 (e.g., the first symbol or first 5 symbols) through the fourth receive beam 1140d and receive a second portion of the BRRS 1144 (e.g., the next symbol or next 5 symbols) through the fifth receive beam 1140e.

In an aspect, the UE 1104 may receive the BRRS 1144 through the set of transmit beams of the base station 1102 corresponding to the set of transmit beam indexes indicated by the beam modification command 1142 (e.g., through the sixth transmit beam 1120f).

In another aspect, the UE 1104 may receive the BRRS 1144 through a different set of transmit beams of the base station than those transmit beams corresponding to the transmit beam indexes indicated by the beam modification command 1142. For example, the UE 1104 may determine to use the fifth receive beam 1140e based on a transmit beam index corresponding to the sixth transmit beam 1120f, but the BRRS 1144 may be transmitted through the fifth transmit beam 1120e (e.g., due to reflection or obstruction).

FIG. 12 is a flowchart of a method 1200 of wireless communication. The method 1200 may be performed by a

UE, such as the UE 1104, the UE 1004, the UE 904, the UE 804, the UE 704, the UE 604, the UE 504, the UE 404, the UE 350, the UE 104, the UE 182, or another UE. In one aspect, the method 1200 may be performed by an apparatus, such as the apparatus 1902/1902'. One of ordinary skill would understand that one or more operations may be omitted, transposed, and or performed contemporaneously.

At operation 1202, the UE may communicate with a base station through a serving beam corresponding to a serving beam index. For example, the UE may send at least one signal through the serving beam corresponding to the serving beam index. In the context of FIG. 7, the UE 704 may communicate with the base station 702 through the first serving beam 720e, which may correspond to a beam index.

At operation 1204, the UE may receive, from the base station, a beam modification command. In aspects, the beam modification command may indicate at least a beam index for communicating through at least one beam on at least one channel. In aspects, each beam index of the at least one beam index indicates at least a direction for communicating through a corresponding beam of the at least one beam. In the context of FIG. 7, the UE 704 may receive, from the base station 702, the beam modification command 710.

In one aspect, the beam modification command is received in a MAC CE. In another aspect, the beam modification command is received in a DCI message. In another aspect, the beam modification command is received via RRC signaling.

According to an aspect, the beam modification command may indicate, for each beam index of the at least one beam index, a corresponding channel. Thus, communication carried on the corresponding channel may occur through the at least one beam corresponding to the at least one beam index indicated by the beam modification command. For example, the beam modification command may indicate that the at least one beam index corresponds to one or more uplink channel(s) and/or one or more downlink channel(s). In one aspect, the UE may determine the corresponding channel based on a DCI format of the DCI message.

In one aspect, the at least one beam index may be a plurality of beam indexes, and the at least one channel may be a plurality of channels. In such an aspect, each beam index of the plurality of beam indexes may be indicated as corresponding to at least one channel of the plurality of channels. In the context of FIG. 7, the UE 704 may receive, from the base station 702, the beam modification command 710 that indicates a channel corresponding to each beam index.

At operation 1206, the UE may switch, after receiving the beam modification command, from the serving beam to the at least one beam corresponding to the at least one beam index indicated by the beam modification command. For example, the UE may select the at least one beam corresponding to the at least one beam index, and the UE may change from the serving beam to the at least one beam for communication with the base station. In the context of FIG. 7, the UE 704 may switch, after receiving the beam modification command 710, from the first serving beam 720e to the selected fourth beam 720d, which may correspond to the at least one beam index indicated by the beam modification command 710.

In one aspect, the UE may switch from the serving beam to the at least one beam corresponding to the beam index indicated by the beam modification command at a predetermined time. In one aspect, UE may determine the predetermined time based on the beam modification command. For example, the beam modification command may indicate at

39

least one of a symbol or a subframe at which the UE is to switch from the serving beam to the at least one beam corresponding to the beam index indicated by the beam modification command. In the context of FIG. 7, the UE 704 may switch from the first serving beam 720e to the selected fourth beam 720d at a predetermined time (e.g., a symbol or subframe indicated by the beam modification command 710).

At operation 1208, the UE may determine at least one channel on which communication with the base station is to occur through the at least one beam corresponding to the beam index indicated by the beam modification command. For example, the UE may identify the at least one channel (e.g., based on the beam modification command), and the UE may associate the at least one channel with the at least one beam index. In one aspect, the UE may determine that at least one channel based on a DCI format when the beam modification command is included in a DCI message. In the context of FIG. 7, the UE 704 may determine at least one channel on which communication is to occur through the at least one beam corresponding to the beam index indicated by the beam modification command 710.

At operation 1210, the UE may communicate, with the base station, through the at least one beam corresponding to the beam index indicated by the beam modification command. The UE may communicate with the base station through the at least one beam on at least one channel (e.g., one or more uplink channels or one or more downlink channels). In the context of FIG. 7, the UE 704 may communicate, with the base station 702, through the selected fourth beam 720d corresponding to the at least one beam index indicated by the beam modification command 710. The UE 704 may communicate with the base station 702 through the selected fourth beam 720d on one or more channels (e.g., one or more uplink channels or one or more downlink channels).

FIG. 13 is a flowchart of a method 1300 of wireless communication. The method 1300 may be performed by a UE, such as the UE 1104, the UE 1004, the UE 904, the UE 804, the UE 704, the UE 604, the UE 504, the UE 404, the UE 350, the UE 104, the UE 182, or another UE. In one aspect, the method 1200 may be performed by an apparatus, such as the apparatus 2102/2102'. One of ordinary skill would understand that one or more operations may be omitted, transposed, and or performed contemporaneously.

At operation 1302, the UE may receive, from a base station, through a set of beams a set of BRSs. In the context of FIG. 6, the UE 604 may receive, from the base station 602, a set of BRSs 612a-h through a set of beams 620a-h. For example, the UE 604 may receive a third BRS 612c through a third beam 620c, a fourth BRS 612d through a fourth beam 620d, a fifth BRS 612e through a fifth beam 620e, and a sixth BRS 612f through a sixth beam 620f.

At operation 1304, the UE may measure a respective signal quality of each BRS of the set of BRSs. For example, the UE may identify a BRS of the set of BRSs, and the UE may measure a signal quality for the identified BRS. As each BRS may correspond to a beam, a signal quality measured for a BRS may also correspond to that beam through which the BRS is received. According to various aspects, the measurement of the signal quality of each BRS of the set of BRSs may include measurement of at least one of a BRSRP, a BRSRQ, an SIR, an SINR, and/or an SNR. In the context of FIG. 6, the UE 604 may measure a respective signal quality for each received BRS of the set of BRSs 612a-h, and a respective signal quality may correspond to a respective beam of the set of beams 620a-h.

40

At operation 1306, the UE may receive, from the base station, an indication of one or more beam indexes that are to be excluded from a set of candidate beam indexes. In the context of FIG. 6, the UE 604 may receive, from the base station 602, an indication of one or more beam indexes that are to be excluded from a set of candidate beam indexes 630.

At operation 1308, the UE may maintain a set of candidate beam indexes corresponding to a set of best measured signal qualities of the set of BRSs. For example, the UE may identify a beam index and a corresponding measured signal quality, and the UE may store (e.g., in a table or other data structure) the identified beam index in association with the corresponding measured signal quality. With respect to operation 1306, the UE may exclude one or more beam indexes indicated by the base station from the maintained set of candidate beam indexes. In one aspect, the UE may maintain a set of N candidate beam indexes, and N may be predetermined (e.g., stored in the UE, defined by a standard promulgated by 3GPP, etc.). In the context of FIG. 6, the UE 604 may maintain the set of candidate beam indexes 630 corresponding to a set of best measured signal qualities for the set of BRSs 612a-h.

In one aspect, the set of measured signal qualities may be a set of the highest measured signal qualities. In the context of FIG. 6, the set of candidate beam indexes may reflect the highest measured BRSRPs for the received set of BRSs 612c-f corresponding to the set of beams 620c-f.

In one aspect, the set of best measured signal qualities of the set of BRSs may be based on a most recent set of signal qualities of the set of BRSs. In another aspect, the set of best measured signal qualities of the set of BRSs may be based on a filtered set of signal qualities of the set of BRSs. In another aspect, the set of best measured signal qualities of the set of BRSs may be based on a time-averaged set of signal qualities of the set of BRSs. In one aspect, the set of best measured signal qualities may be maintained based on at least one hysteresis criteria for including a beam index in or excluding a beam index from the set of candidate beam indexes.

At operation 1310, the UE may transmit, to the base station, BSI indicating at least one measured signal quality and at least one beam index corresponding to the at least one measured signal quality. In the context of FIG. 6, the UE 604 may transmit, to the base station 602, a BSI report 642 indicating at least one beam index. In an aspect, the BSI report 642 may be a BSI report that includes a beam index and a corresponding measured signal quality (e.g., the BRSRP measured for a BRS 612a-h received through a beam 620a-h). In an aspect, the UE 604 may transmit the BSI report 642 in response to a request 640 received from the base station 602.

FIG. 14 is a flowchart of a method 1400 of wireless communication. The method 1400 may be performed by a UE, such as the UE 1104, the UE 1004, the UE 904, the UE 804, the UE 704, the UE 604, the UE 504, the UE 404, the UE 350, the UE 104, the UE 182, or another UE. In one aspect, the method 1200 may be performed by an apparatus, such as the apparatus 2302/2302'. One of ordinary skill would understand that one or more operations may be omitted, transposed, and or performed contemporaneously.

At operation 1402, the UE may receive, from a base station, a set of signals through a set of beams. In the context of FIG. 8, the UE 804 may receive, from the base station 802, a set of BRSs 812a-h through a set of beams 820a-h. For example, the UE 804 may receive a third BRS 812c through a third beam 820c, a fourth BRS 812d through a

fourth beam **820d**, a fifth BRS **812e** through a fifth beam **820e**, and a sixth BRS **812f** through a sixth beam **820f**.

At operation **1404**, the UE may determine a received power for each signal of the set of signals received through each beam of the set of beams. For example, the UE may identify the signal, and the UE may measure a received power corresponding to the identified signal. Each determined received power may be associated with a respective beam of the set of beams (e.g., each BRS may correspond to a beam and, therefore, a received power determined for a BRS may also correspond to that beam through which the BRS is received). According to various aspects, the determination of the received power of each BRS of the set of BRSs may include measurement of at least one of a BRSRP, a BRSRQ, an SIR, an SINR, and/or an SNR. In the context of FIG. 6, the UE **604** may determine a received power for each received BRS of the set of BRSs **612a-h**, and a respective received power may correspond to a respective beam of the set of beams **620a-h**.

At operation **1406**, the UE may receive, from the base station, a message requesting BSI. In one aspect, a DCI message (e.g., a downlink DCI message or an uplink DCI message) may include the message requesting BSI. In another aspect, an RAR message may include the message requesting BSI. In the context of FIG. 8, the UE **804** may receive, from the base station **802**, the message **840** requesting BSI.

At operation **1408**, the UE may determine a number N of BSI reports to send to the base station, and each BSI report may indicate a beam index corresponding to a beam and a received power associated with the beam. For example, the UE may identify the message from the base station requesting BSI, and the UE may identify the number N of BSI reports to send based on the identified message. In the context of FIG. 8, the UE **804** may determine a number N of BSI reports **842** to send to the base station **802**. Each BSI report **842** may include at least one of the beam indexes **832c-f** and a BRSRP **834c-f** corresponding to the at least one of the beam indexes **832c-f**.

In an aspect, the UE may determine the number N based on the message requesting BSI (e.g., based on the type of message). For example, the UE may determine that the number N is one when the message requesting BSI is included in a DCI message (e.g., a downlink DCI message). In another aspect, the UE may determine that the number N is greater than one (e.g., two or four) when the message requesting BSI is included in an RAR message (or an uplink DCI message); the number N greater than one may be indicated by the message (e.g., the message requesting BSI may indicate that the UE is to send two or four BSI reports). In the context of FIG. 8, the UE **804** may determine the number N of BSI reports **842** to send to the base station **802** based on the message **840** (e.g., the type or format of the message **840**).

In one aspect, the UE may determine a channel that is to carry the BSI reports based on the message. For example, the UE may determine that the number N of BSI reports are to be carried on a PUCCH when the number N is one and/or when the message requesting BSI is included in a DCI message (e.g., a downlink DCI message). In another aspect, the UE may determine that the number N of BSI reports are to be carried on a PUSCH when the number N is greater than one and/or when the message requesting BSI is included in an RAR message (or an uplink DCI message).

At operation **1410**, the UE may send, to the base station, N BSI reports based on the message requesting BSI. In an aspect, the N BSI reports include N received powers corre-

sponding to the highest determined received powers and the beam indexes corresponding to those highest determined received powers. In the context of FIG. 8, the UE **804** may send, to the base station **802**, N BSI reports **842** based on the message **840**. For example, at least one BSI report **842** may include a fifth beam index **832e** and a corresponding BRSRP **834e**, which may be the highest BRSRP of the BRSRPs measured for the BRSs **812a-h** received through the beams **820a-h**.

FIG. 15 is a flowchart of a method **1500** of wireless communication. The method **1500** may be performed by a UE, such as the UE **1104**, the UE **1004**, the UE **904**, the UE **804**, the UE **704**, the UE **604**, the UE **504**, the UE **404**, the UE **350**, the UE **104**, the UE **182**, or another UE. In one aspect, the method **1200** may be performed by an apparatus, such as the apparatus **2502/2502'**. One of ordinary skill would understand that one or more operations may be omitted, transposed, and/or performed contemporaneously.

At operation **1502**, the UE may select a first beam for communication with a base station. For example, the UE may select a beam index corresponding to a beam through which the UE estimates or expects the base station to be able to communicate with the UE. In the context of FIG. 9, the UE **904** may select the fifth beam **920e** as the first beam for communication with the base station **902**.

At operation **1504**, the UE may attempt at least one RACH procedure with the base station through the selected beam. For example, the UE may send at least one RACH message (e.g., the MSG1 **410**) to the base station, and the UE may determine that a response to the at least one RACH message is absent (e.g., not received within a predetermined period of time). In the context of FIG. 9, the UE **904** may attempt a first RACH procedure **940** with the base station **902** through the selected fifth beam **920e**.

At operation **1506**, the UE may determine that the at least one RACH procedure failed. For example, the UE may start a timer in association with one or more messages, and the UE may fail to receive or decode one or more messages associated with the at least one RACH procedure (e.g., a MSG2 or RAR, a MSG4 or contention resolution message, etc.) before expiration of the timer. In the context of FIG. 9, the UE **904** may determine that the first RACH procedure **940** failed with the base station **902**.

At operation **1508**, the UE may select a new beam for communication with the base station after the determination that the at least one RACH procedure failed. For example, the UE may access a stored set of candidate beam indexes, and the UE may select a next beam corresponding to a next beam index in a set of candidate beam indexes (e.g., a beam corresponding to a next highest BRSRP). In the context of FIG. 9, the UE **904** may select the sixth beam **920f** for communication with the base station **902** after the determination that the first RACH procedure **940** failed.

At operation **1510**, the UE may increase a transmission power after the determination that the at least one RACH procedure failed. For example, the UE may identify a current transmission power, and the UE may increase the identified current transmission power by a predetermined amount. In the context of FIG. 9, the UE **904** may increase a transmission power for the successful RACH procedure **942**.

In an aspect, the UE may perform one or both of operations **1508** and **1510**. In other words, the UE may increase a transmission power and attempt another RACH procedure through the selected first beam (e.g., instead of selecting a new beam for attempting another RACH procedure). Alternatively, the UE may use a same transmission power when

attempting another RACH procedure through a newly selected beam. Alternatively, the UE may both increase transmission power and use a newly selected beam when attempting another RACH procedure after a determination that the first RACH procedure failed.

At operation **1512**, the UE may store information associated with the selected first beam based on the determination that the at least one RACH procedure failed. For example, the UE may generate or access a data structure, and the UE may store a beam index corresponding to the first beam through which the UE attempted the failed RACH procedure (e.g., in the generated or accessed data structure). In an aspect, the UE may exclude the beam index corresponding to the first beam from a set of candidate beam indexes maintained by the UE based on the determination that the at least one RACH procedure failed. In another example, the UE may store an indication of a subframe in which a RACH message associated with the failed RACH procedure is carried (e.g., a MSG1 or random access preamble, a MSG3 or connection request message, etc.).

At operation **1514**, the UE may perform a successful RACH procedure with the base station. For example, the UE may send a connection request message (e.g., the MSG3 **414**) and the UE may receive a contention resolution message (e.g., the MSG4 **416**) in response to the connection request message. The UE may be synchronized with a network that includes the base station based on the successful RACH procedure. In the context of FIG. 9, the UE **904** may perform the successful RACH procedure **942** with the base station **902**, for example, through the sixth beam **920f**.

At operation **1516**, the UE may send, after the successful RACH procedure with the base station, information indicating that the at least one RACH procedure failed. In an aspect, this information may be the information stored as described at operation **1512**. For example, this information may include a beam index corresponding to the first beam and/or an indication of a subframe in which a message associated with the failed RACH procedure was carried. In one aspect, this information may be included in a BSI report. In the context of FIG. 9, the UE **904** may send, after the successful RACH procedure **942**, information **944** indicating that the first RACH procedure **940** failed.

FIG. 16 is a flowchart of a method **1600** of wireless communication. The method **1500** may be performed by a UE, such as the UE **1104**, the UE **1004**, the UE **904**, the UE **804**, the UE **704**, the UE **604**, the UE **504**, the UE **404**, the UE **350**, the UE **104**, the UE **182**, or another UE. In one aspect, the method **1200** may be performed by an apparatus, such as the apparatus **2702/2702'**. One of ordinary skill would understand that one or more operations may be omitted, transposed, and or performed contemporaneously.

At operation **1602**, the UE may receive, from a base station, a contention resolution message indicating at least one beam index corresponding to a beam. In the context of FIG. 10, the UE **1004** may receive, from the base station **1002**, the contention resolution message **1042**, for example, as part of the RACH procedure **1040**. For example, the UE **1004** may receive, from the base station **1002**, the contention resolution message **1042** through the fifth beam **1020e**, and the contention resolution message **1042** may indicate a beam index corresponding to the sixth beam **1020f**.

In an aspect, the contention resolution message may be received as part of a RACH procedure. The contention resolution message may also be known as a MSG4. In the context of FIG. 4A, the contention resolution message may be an aspect of the MSG4 **416**. Accordingly, the UE **404** may

receive, from the base station **402**, the MSG4 **416**, for example, according to a RACH procedure.

In an aspect, the contention resolution message may indicate one or more channels to which the at least one beam index corresponding to the beam is applicable. For example, the contention resolution message may indicate that the at least one beam index corresponding to the beam is applicable to one or more uplink channels and/or one or more downlink channels. In the context of FIG. 10, the contention resolution message **1042** may indicate one or more channels to which the at least one beam index corresponding to the beam is applicable. Accordingly, the UE **1004** may determine, based on the contention resolution message **1042**, one or more channels to which the at least one beam index corresponding to the beam is applicable.

At operation **1604**, the UE may determine whether the beam index is applicable to the UE. In other words, the UE may determine whether communication with the base station is to occur through the beam corresponding to the beam index indicated by the contention resolution message. In the context of FIG. 10, the UE **1004** may determine whether the beam index indicated by the contention resolution message **1042** is applicable to the UE **1004**.

In an aspect, operation **1604** may include operation **1620**. At operation **1620**, the UE may attempt to decode the contention resolution message based on an RNTI associated with the UE. When the UE successfully decodes the contention resolution message based on an RNTI associated with the UE, the UE may determine that the beam index indicated by the contention resolution is applicable to the UE. When the UE is unable to successfully decode the contention resolution message based on an RNTI associated with the UE, the UE may determine that the beam index is inapplicable to the UE. In the context of FIG. 10, the UE **1004** may attempt to decode the contention resolution message **1042** based on an RNTI associated with the UE **1004** (e.g., an RNTI determined during the RACH procedure **1040**).

When the UE determines that the beam index indicated by the contention resolution message is applicable to the UE, the method **1600** may proceed to operation **1606**. At operation **1606**, the UE may transmit, to the base station, an acknowledgment message—e.g., the UE may transmit ACK feedback indicating that the UE acknowledges the contention resolution message received from the base station. In one aspect, the UE may transmit the acknowledgment message through the beam used for the RACH procedure. In another aspect, the UE may transmit the acknowledgment message through the beam corresponding to the beam index indicated by the contention resolution message. In the context of FIG. 10, the UE **1004** may transmit, to the base station **1002**, the acknowledgment message **1044** based on the determination that the beam index indicated by the contention resolution message **1042** is applicable to the UE.

At operation **1608**, the UE may communicate with the base station through the beam corresponding to the beam index indicated by the contention resolution message. In an aspect, the UE may switch from a current serving beam to a new beam, and the new beam may correspond to the beam index indicated by the contention resolution message. In an aspect, the UE may communicate with the base station through the beam corresponding to the beam index indicated by the contention resolution message on one or more channels (e.g., one or more uplink channels or one or more downlink channels), which may also be indicated by the contention resolution message. In the context of FIG. 10, the UE **1004** may communicate **1046** with the base station **1002**

45

through the sixth beam 1020f, and the sixth beam 1020f may correspond to the beam index indicated by the contention resolution message 1042.

When the UE determines that the beam index indicated by the contention resolution message is inapplicable to the UE or if the UE is unable to successfully decode the contention resolution message, the method 1600 may proceed to operation 1610. At operation 1610, the UE may refrain from transmitting a non-acknowledgment message to the base station when the beam index is determined to be inapplicable to the UE or if the UE is unable to successfully decode the contention resolution message. For example, the UE may refrain from transmitting NACK feedback to the base station. In the context of FIG. 10, the UE 1004 may refrain from transmitting a non-acknowledgment message to the base station when the UE 1004 determines that the beam index indicated by the contention resolution message 1042 is inapplicable to the UE 1004 or when the UE 1004 is unable to successfully decode the contention resolution message 1042.

At operation 1612, the UE may continue to communicate with the base station through a current serving beam. For example, the UE may continue to communicate with the base station through the beam used for the RACH procedure with which the contention resolution message is associated (e.g., the UE may attempt a second RACH procedure through the same beam used for the first RACH procedure). In the context of FIG. 10, the UE 1004 may continue to communicate with the base station 1002 through the fifth beam 1020e used for the first RACH procedure 1040 (e.g., the UE 1004 may attempt another RACH procedure similar to the first RACH procedure 1040 through the fifth beam 1020e used for the first RACH procedure 1040).

FIG. 17 is a flowchart of a method 1700 of wireless communication. The method 1700 may be performed by a base station, such as the base station 1102, the base station 1002, the base station 902, the base station 802, the base station 702, the base station 602, the base station 502, the base station 402, the base station 310, the base station 102, the base station 180, or another base station. In one aspect, the method 1200 may be performed by an apparatus, such as the apparatus 2902/2902'. One of ordinary skill would understand that one or more operations may be omitted, transposed, and/or performed contemporaneously.

At operation 1702, the base station may scramble at least a portion of a contention resolution message using an RNTI associated with a UE. For example, the base station may identify an RNTI associated with the UE, and encode at least a portion of the contention resolution message using the identified RNTI. In the context of FIG. 10, the base station 1002 may scramble at least a portion of the contention resolution message 1042 using an RNTI associated with the UE 1004.

At operation 1704, the base station may transmit, to the UE, the contention resolution message indicating at least one beam index corresponding to a beam and further indicating that the beam index is applicable to the UE. The base station may indicate that the beam index is applicable to the UE by scrambling at least a portion of the contention resolution message using an RNTI associated with the UE, as described at operation 1702. In one aspect, the base station may select a beam for communication with the UE, and the selected beam may be different from the beam through which the contention resolution message is transmitted. In the context of FIG. 10, the base station 1002 may transmit, to the UE 1004, the contention resolution message 1042. The base station 1002 may transmit the contention

46

resolution message 1042 through the fifth beam 1020e, and the contention resolution message 1042 may indicate a beam index corresponding to the sixth beam 1020f.

In an aspect, the contention resolution message may be generated by the base station as part of a RACH procedure. The contention resolution message may also be known as a MSG4. The contention resolution message may be generated by the base station in response to a connection request message or MSG3 received from the UE as part of a RACH procedure. In the context of FIG. 4A, the contention resolution message may be an aspect of the MSG4 416. Accordingly, the base station 402 may transmit, to the UE 404, the MSG4 416, for example, according to a RACH procedure.

In an aspect, the contention resolution message may indicate one or more channels to which the at least one beam index corresponding to the beam is applicable. For example, the contention resolution message may indicate that the at least one beam index corresponding to the beam is applicable to one or more uplink channels and/or one or more downlink channels. In the context of FIG. 10, the contention resolution message 1042 may indicate one or more channels to which the at least one beam index corresponding to the beam is applicable. For example, the base station 1002 may indicate, by the contention resolution message 1042, one or more channels to which the at least one beam index corresponding to the beam is applicable.

At operation 1706, the base station may determine whether an acknowledgment message is received from the UE in response to the contention resolution message. In the context of FIG. 10, the base station 1002 may determine whether the acknowledgment message 1044 is received from the UE 1004 in response to the contention resolution message 1042.

When the base station determines that the acknowledgment message is received from the UE, the method 1700 may proceed to operation 1708. At operation 1708, the base station may communicate with the UE through the beam corresponding to beam index indicated by the contention resolution message. In an aspect, the base station may communicate with the UE through the beam corresponding to the beam index indicated by the contention resolution message on one or more channels (e.g., one or more uplink channels or one or more downlink channels), which may also be indicated by the contention resolution message. In the context of FIG. 10, the base station 1002 may communicate 1046 with the UE through the sixth beam 1020f, and the sixth beam 1020f may correspond to the beam index indicated by the contention resolution message 1042.

When the base station determines that the acknowledgment message is not received from the UE, the method 1700 may proceed to operation 1710. At operation 1710, the base station may communicate with the UE through a current serving beam, such as the beam used for the RACH procedure with which the contention resolution message is associated. In one aspect, the base station may take no action with the UE when the base station determines that the acknowledgment message is not received from the UE. In the context of FIG. 10, the base station 1002 may communicate with the UE through the fifth beam 1020e, which may be the beam through which one or more messages associated with the RACH procedure 1040 are communicated.

FIG. 18 is a flowchart of a method 1800 of wireless communication. The method 1800 may be performed by a UE, such as the UE 1104, the UE 1004, the UE 904, the UE 804, the UE 704, the UE 604, the UE 504, the UE 404, the UE 350, the UE 104, the UE 182, or another UE. In one aspect, the method 1200 may be performed by an apparatus,

such as the apparatus **3102/3102'**. One of ordinary skill would understand that one or more operations may be omitted, transposed, and or performed contemporaneously.

At operation **1802**, the UE may receive a beam modification command that indicates a set of transmit beam indexes corresponding to a set of transmit beams of a base station. Each transmit beam index of the set of transmit beam indexes may indicate at least a direction for transmitting a transmit beam by the base station. In the context of FIG. **11**, the UE **1104** may receive, from the base station **1102**, the beam modification command **1142** that indicates a set of transmit beam indexes corresponding to a set of transmit beams **1120a-h** of the base station **1102**.

In an aspect, the beam modification command may be received in a MAC CE. In an aspect, the beam modification command may be received in a DCI message. In an aspect, the beam modification command may be received via RRC signaling. In an aspect, the beam modification command may be carried on a PDCCH.

At operation **1804**, the UE may determine a set of receive beam indexes corresponding to a set of receive beams of the UE based on the set of transmit beam indexes. Each receive beam index of the set of receive beam indexes may indicate at least a receive direction for receiving a beam by the UE. In an aspect, the UE may determine the set of receive beam indexes by accessing a mapping that maps transmit beam indexes to receive beam indexes. The UE may be configured to populate this mapping. The UE may identify at least one receive beam index corresponding to at least one transmit beam index based on the accessed mapping.

In the context of FIG. **11**, the UE **1104** may determine a set of receive beam indexes corresponding to a set of receive beams **1140a-h** of the UE **1104** based on the set of transmit beam indexes indicated by the beam modification command **1142**. For example, the UE **1104** may determine a set of receive beam indexes corresponding to the fourth receive beam **1140d** and the fifth receive beam **1140e** based on a set of transmit beam indexes corresponding to the fifth transmit beam **1120e** and the sixth transmit beam **1120f**, respectively.

At operation **1806**, the UE may receive, from the base station, a BRRS through at least one receive beam corresponding to at least one receive beam index included in the determined set of receive beam indexes. In one aspect, the UE may generate a receive beam corresponding to the at least one receive beam index, for example, when the UE is not actively maintaining that beam. In the context of FIG. **11**, the UE **1104** may receive, from the base station **1102**, the BRRS **1144** through at least the fifth receive beam **1140e** corresponding to at least one receive beam index included in the determined set of receive beam indexes.

In one aspect, the UE may receive the BRRS through the set of transmit beams from the base station corresponding to the set of transmit beam indexes. In another aspect, the UE may receive the BRRS through a different set of transmit beams from the base station than the set of transmit beams corresponding to the transmit beam indexes indicated by the beam modification command. For example, obstruction and/or reflection may cause the UE to receive the BRRS through the determined set of receive beams, but through a different set of transmit beams than the set of transmit beams corresponding to the set of transmit beam indexes indicated by the beam modification command.

In one aspect, the UE may receive the BRRS in one or more symbols corresponding to one or more symbol indexes. For example, the UE may receive (e.g., listen) through the at least one receive beam corresponding to the at least one receive beam index during one or more symbols

corresponding to the one or more symbol indexes. In an aspect, the one or more symbol indexes may be predetermined (e.g., defined by one or more standards promulgated by 3GPP). In another aspect, the one or more symbol indexes may be indicated by the beam modification command. In one aspect, the beam modification command further indicates a corresponding transmit beam index of the set of transmit beam indexes for each symbol of the one or more symbol indexes.

In an aspect, operation **1806** may include operation **1820** and operation **1822**. At operation **1820**, the UE may receive a first portion of the BRRS in a first set of symbols through a first receive beam corresponding to a first receive beam index included in the determined set of receive beam indexes. In the context of FIG. **11**, the UE **1104** may receive a first portion of the BRRS **1144** in a first set of symbols through the fourth receive beam **1140d** corresponding to a fourth receive beam index, which may be determined based on a fifth transmit beam index corresponding to a fifth transmit beam **1120e** indicated by the beam modification command **1142**.

At operation **1822**, the UE may receive a second portion of the BRRS in a second set of symbols through a second receive beam corresponding to a second receive beam index included in the determined set of receive beam indexes. In the context of FIG. **11**, the UE **1104** may receive a second portion of the BRRS **1144** in a second set of symbols through the fifth receive beam **1140e** corresponding to a fifth receive beam index, which may be determined based on a sixth transmit beam index corresponding to a sixth transmit beam **1120f** indicated by the beam modification command **1142**.

FIG. **19** is a conceptual data flow diagram **1900** illustrating the data flow between different means/components in an exemplary apparatus **1902**. The apparatus may be a UE. The data flow illustrated in the diagram **1900** is to be regarded as illustrative. Therefore, one or more additional means/components may be present, and one or more illustrated means/components may be absent, according to various aspects. Further, various data flow may occur between means/components in addition to the illustrated data flow.

The apparatus **1902** may include a reception component **1904** configured to receive signals from a base station (e.g., the base station **1950**, a mmW base station, an eNB, etc.). The apparatus **1902** may further include a transmission component **1910** configured to transmit signals to a base station (e.g., the base station **1950**, a mmW base station, an eNB, etc.).

In an aspect, the apparatus **1902** may include a communication component **1912**. The communication component **1912** may be configured to receive, through the reception component **1904**, downlink data and/or control information. The communication component may be configured to determine (e.g., generate, select, etc.) uplink data and/or control information that is to be sent to the base station **1950** via the transmission component **1910**. In aspects, the communication component **1912** may communicate, with the base station **1950**, through a serving beam corresponding to a serving beam index. In one aspect, the communication component **1912** may communicate through a first beam corresponding to a first beam index for downlink communication received from the base station **1950** and communicate through a second beam corresponding to a second beam index for uplink communication sent to the base station **1950**. The first beam and the second beam are not

necessarily the same beam. Therefore, uplink communication and downlink communication may occur through different beams.

The apparatus **1902** may include an identification component **1906**. The identification component **1906** may receive a beam modification command from the base station. The beam modification command may indicate at least one beam index for communicating through at least one beam on at least one channel—each beam index may indicate at least a direction for communicating through a corresponding beam of the at least one beam. In an aspect, the beam modification command may indicate a plurality of beam indexes. The identification component **1906** may determine, based on the beam modification command, at least one beam index for communicating through at least one beam on at least one channel.

In one aspect, the identification component **1906** may receive the beam modification command in a MAC CE. In another aspect, the identification component **1906** may receive the beam modification command in a DCI message. In another aspect, the identification component **1906** may receive the beam modification command via RRC signaling.

In one aspect, the identification component **1906** may further determine at least one channel corresponding to at least one determined beam index. For example, the identification component **1906** may determine that the beam modification command is applicable to one or more uplink channels for uplink communication and/or is applicable to one or more downlink channels for downlink communication. In one aspect, the identification component **1906** may determine a plurality of channels corresponding to the at least one beam index.

The identification component **1906** may determine the at least one channel based on the beam modification command. For example, the identification component **1906** may determine the at least one channel based on a DCI format of a DCI message that indicates the at least one beam index. In an aspect, the identification component may determine, for each beam index, a corresponding channel to which each beam index is applicable.

The identification component **1906** may provide, to a selection component **1908**, beam index information that includes the at least one determined beam index. In an aspect, the identification component **1906** may provide, to the selection component **1908**, beam index information indicating one or more channels to which each beam index is applicable. For example, the identification component **1906** may provide, to the selection component **1908**, a beam index and an indication that the beam index is applicable to uplink channels for uplink communication or downlink channels for downlink communication.

In an aspect, the selection component **1908** may be configured to determine whether a first serving beam is to be switched based on the beam index information. The selection component **1908** may instruct the communication component **1912** to switch from the first serving beam to a second serving beam.

In an aspect, the selection component **1908** may determine a time at which communication through the second serving beam corresponding to the at least one beam index is to occur. In one aspect, the time may correspond to a symbol or a subframe. The selection component **1908** may determine the time and instruct the communication component **1912** to switch to the second serving beam at the determined time.

In one aspect, the selection component **1908** may determine the time based on the beam modification command.

For example, the selection component **1908** may determine, based on inclusion of the beam modification command in a MAC CE, to switch communication through the first serving beam to the second serving beam at the beginning of a subframe $n+k_{\text{beamswitch-delay-mac}}$, where n is the subframe used for HARQ-ACK transmission associated with the MAC CE and $k_{\text{beamswitch-delay-mac}}$ is equal to 14.

According to another example, based on inclusion of the beam modification command in a DCI message, the selection component **1908** may determine to switch from the first serving beam to the second serving beam at the beginning of a subframe $n+k_{\text{beamswitch-delay-dci}}$, where n is the subframe used for transmission of a BSI report and $k_{\text{beamswitch-delay-dci}}$ is equal to 11.

In an aspect, the selection component **1908** may receive a beam modification command indicating that the first serving beam is not to be switched. For example, a beam modification command may include a beam switch indication field having a predetermined value (e.g., “0”) from which the selection component **1908** may determine that the first serving beam used by the communication component **1912** is not to be switched. Accordingly, the selection component **1908** may instruct the communication component **1912** to continue communication through the first serving beam, or the selection component **1908** may refrain from providing beam index and/or channel information to the communication component **1912**.

Based on instruction from the selection component **1908**, the communication component **1912** may communicate with the base station **1950** through the at least one beam corresponding to the at least one beam index. In other words, the communication component **1912** may communicate with the base station **1950** through the second serving beam on or more channels, rather than communicate with the base station **1950** through the first serving beam.

In an aspect, the communication component **1912** may communicate with the base station **1950** through the second serving beam on one or more channels indicated by the selection component **1908**. For example, the communication component **1912** may communicate with the base station **1950** through the second serving beam on one or more uplink channels or one or more downlink channels.

The apparatus may include additional components that perform each of the blocks of the algorithm in the aforementioned flowcharts of FIG. 12. As such, each block in the aforementioned flowcharts of FIG. 12 may be performed by a component and the apparatus may include one or more of those components. The components may be one or more hardware components specifically configured to carry out the stated processes/algorithm, implemented by a processor configured to perform the stated processes/algorithm, stored within a computer-readable medium for implementation by a processor, or some combination thereof.

FIG. 20 is a diagram **2000** illustrating an example of a hardware implementation for an apparatus **1902'** employing a processing system **2014**. The processing system **2014** may be implemented with a bus architecture, represented generally by the bus **2024**. The bus **2024** may include any number of interconnecting buses and bridges depending on the specific application of the processing system **2014** and the overall design constraints. The bus **2024** links together various circuits including one or more processors and/or hardware components, represented by the processor **2004**, the components **1904**, **1906**, **1908**, **1910**, **1912**, and the computer-readable medium/memory **2006**. The bus **2024** may also link various other circuits such as timing sources,

51

peripherals, voltage regulators, and power management circuits, which are well known in the art, and therefore, will not be described any further.

The processing system **2014** may be coupled to a transceiver **2010**. The transceiver **2010** is coupled to one or more antennas **2020**. The transceiver **2010** provides a means for communicating with various other apparatus over a transmission medium. The transceiver **2010** receives a signal from the one or more antennas **2020**, extracts information from the received signal, and provides the extracted information to the processing system **2014**, specifically the reception component **1904**. In addition, the transceiver **2010** receives information from the processing system **2014**, specifically the transmission component **1910**, and based on the received information, generates a signal to be applied to the one or more antennas **2020**. The processing system **2014** includes a processor **2004** coupled to a computer-readable medium/memory **2006**. The processor **2004** is responsible for general processing, including the execution of software stored on the computer-readable medium/memory **2006**. The software, when executed by the processor **2004**, causes the processing system **2014** to perform the various functions described supra for any particular apparatus. The computer-readable medium/memory **2006** may also be used for storing data that is manipulated by the processor **2004** when executing software. The processing system **2014** further includes at least one of the components **1904**, **1906**, **1908**, **1910**, **1912**. The components may be software components running in the processor **2004**, resident/stored in the computer readable medium/memory **2006**, one or more hardware components coupled to the processor **2004**, or some combination thereof. The processing system **2014** may be a component of the UE **350** and may include the memory **360** and/or at least one of the TX processor **368**, the RX processor **356**, and the controller/processor **359**.

In one configuration, the apparatus **1902/1902'** for wireless communication includes means for receiving, from a base station, a beam modification command indicating at least one beam index for communicating through at least one beam on at least one channel, and each beam index of the at least one beam index may indicate at least a direction for communicating through a corresponding beam of the at least one beam. The apparatus **1902/1902'** may further include means for communicating, with the base station, through the at least one beam corresponding to the at least one beam index on the at least one channel.

In an aspect, the apparatus **1902/1902'** may further include means for communicating, with the base station, through a serving beam corresponding to a serving beam index; The apparatus **1902/1902'** may further include means for switching, after receiving the beam modification command, from the serving beam to the at least one beam corresponding to the at least one beam index indicated by the beam modification command. In an aspect, the means for switching from the serving beam to the at least one beam is configured to switch from the serving beam to the at least one beam at a predetermined time. In an aspect, the predetermined time is associated with at least one of a symbol or subframe, and wherein the beam modification command indicates the at least one of the symbol or the subframe.

In an aspect, the beam modification command indicates, for each beam index of the at least one beam index, a corresponding channel of the at least one channel. In an aspect, the at least one beam index comprises a plurality of beam indexes, and the at least one channel comprises a

52

plurality of channels. In an aspect, the at least one beam index is applicable to one of uplink communication or downlink communication.

In an aspect, the beam modification command is received in a MAC CE. In an aspect, the beam modification command is received in a DCI message. In an aspect, the apparatus **1902/1902'** may further include means for determining the at least one channel based on a DCI format of the DCI message. In an aspect, the beam modification command is received via RRC signaling.

The aforementioned means may be one or more of the aforementioned components of the apparatus **1902** and/or the processing system **2014** of the apparatus **1902'** configured to perform the functions recited by the aforementioned means. As described supra, the processing system **2014** may include the TX Processor **368**, the RX Processor **356**, and the controller/processor **359**. As such, in one configuration, the aforementioned means may be the TX Processor **368**, the RX Processor **356**, and the controller/processor **359** configured to perform the functions recited by the aforementioned means.

FIG. **21** is a conceptual data flow diagram **2100** illustrating the data flow between different means/components in an exemplary apparatus **2102**. The apparatus may be a UE. The data flow illustrated in the diagram **2100** is to be regarded as illustrative. Therefore, one or more additional means/components may be present, and one or more illustrated means/components may be absent, according to various aspects. Further, various data flow may occur between means/components in addition to and/or instead of the illustrated data flow.

The apparatus **2102** may include a reception component **2104** configured to receive signals from a base station (e.g., the base station **2150**, a mmW base station, an eNB, etc.). The apparatus **2102** may further include a transmission component **2110** configured to transmit signals to a base station (e.g., the base station **2150**, a mmW base station, an eNB, etc.).

In aspects, the reception component **2104** may receive, from the base station **2150**, through a set of beams a set of BRSs. Each BRS of the set of BRSs may correspond to a beam, and each beam may correspond to a beam index (ergo, each BRS may correspond to a beam index). Each BRS may be received through a beam that may be used for communication between the apparatus **2102** and the base station **2150**. The reception component **2104** may provide the set of BRSs to a measurement component **2106**.

The measurement component **2106** may be configured to measure a signal quality of each BRS of the set of received BRSs. For example, the measurement component **2106** may measure at least one of a BRSRP, a BRSRQ, an SIR, an SINR, an SNR, or another value indicative of signal quality.

The measurement component **2106** may provide measurement information to a candidate component **2108**. The candidate component **2108** may be configured to maintain a set of candidate beam indexes corresponding to a set of best measured signal qualities of the set of BRSs. For example, the set of best measured signal qualities may be a set of the highest measured signal qualities.

In an aspect, the candidate component **2108** may be configured to maintain N candidate beam indexes in the set of candidate beam indexes. The number N may be predetermined, for example, as defined by one or more standards promulgated by 3GPP. For example, the candidate component **2108** may maintain N=4 candidate beam indexes in the set of candidate beam indexes.

53

In an aspect, the candidate component **2108** may be configured to maintain the set of best measured signal qualities of the set of BRSs based on a most recent set of signal qualities of the set of BRSs (e.g., the most recent measured signal qualities for the most recently received set of BRSs). In another aspect, the candidate component **2108** may be configured to maintain the set of best measured signal qualities of the set of BRSs based on a filtered set of signal qualities of the set of BRSs. In another aspect, the candidate component **2108** may be configured to maintain the set of best measured signal qualities of the set of BRSs based on a time-averaged set of signal qualities of the set of BRSs.

In an aspect, the candidate component **2108** may be configured to maintain the set of candidate beam indexes based on one or more criteria. For example, the candidate component **2108** may maintain the set of candidate beam indexes based on one or more hysteresis criteria for including a beam index in or excluding a beam index from the set of candidate beam indexes.

In one aspect, the candidate component **2108** may be configured to maintain the set of candidate beam indexes based on beam index information received from the base station **2150**. For example, the candidate component **2108** may receive, from the base station **2150**, an indication of one or more beam indexes that are to be excluded from the maintained set of candidate beam indexes. Accordingly, the candidate component **2108** may exclude the indicated one or more beam indexes from the maintained set of candidate beam indexes.

In an aspect, the candidate component **2108** may be configured to provide candidate beam index information to a reporting component **2112** based on the set of candidate beam indexes. For example, the candidate component **2108** may select at least one best (e.g., highest) signal quality and provide the best signal quality and corresponding candidate beam index to the reporting component **2112**. In an aspect, the candidate beam index information may include at least a beam index and a signal quality corresponding to a beam through which the corresponding BRS is received. The reporting component **2112** may be configured to generate a BSI report indicating at least the signal quality and the beam index corresponding to the at least one measured signal quality. The reporting component **2112** may cause the transmission component **2110** to transmit the BSI report to the base station **2150**.

The apparatus may include additional components that perform each of the blocks of the algorithm in the aforementioned flowcharts of FIG. **13**. As such, each block in the aforementioned flowcharts of FIG. **13** may be performed by a component and the apparatus may include one or more of those components. The components may be one or more hardware components specifically configured to carry out the stated processes/algorithm, implemented by a processor configured to perform the stated processes/algorithm, stored within a computer-readable medium for implementation by a processor, or some combination thereof.

FIG. **22** is a diagram **2200** illustrating an example of a hardware implementation for an apparatus **2102'** employing a processing system **2214**. The processing system **2214** may be implemented with a bus architecture, represented generally by the bus **2224**. The bus **2224** may include any number of interconnecting buses and bridges depending on the specific application of the processing system **2214** and the overall design constraints. The bus **2224** links together various circuits including one or more processors and/or hardware components, represented by the processor **2204**,

54

the components **2104**, **2106**, **2108**, **2110**, **2112** and the computer-readable medium/memory **2206**. The bus **2224** may also link various other circuits such as timing sources, peripherals, voltage regulators, and power management circuits, which are well known in the art, and therefore, will not be described any further.

The processing system **2214** may be coupled to a transceiver **2210**. The transceiver **2210** is coupled to one or more antennas **2220**. The transceiver **2210** provides a means for communicating with various other apparatus over a transmission medium. The transceiver **2210** receives a signal from the one or more antennas **2220**, extracts information from the received signal, and provides the extracted information to the processing system **2214**, specifically the reception component **2104**. In addition, the transceiver **2210** receives information from the processing system **2214**, specifically the transmission component **2110**, and based on the received information, generates a signal to be applied to the one or more antennas **2220**. The processing system **2214** includes a processor **2204** coupled to a computer-readable medium/memory **2206**. The processor **2204** is responsible for general processing, including the execution of software stored on the computer-readable medium/memory **2206**. The software, when executed by the processor **2204**, causes the processing system **2214** to perform the various functions described supra for any particular apparatus. The computer-readable medium/memory **2206** may also be used for storing data that is manipulated by the processor **2204** when executing software. The processing system **2214** further includes at least one of the components **2104**, **2106**, **2108**. The components may be software components running in the processor **2204**, resident/stored in the computer readable medium/memory **2206**, one or more hardware components coupled to the processor **2204**, or some combination thereof. The processing system **2214** may be a component of the UE **350** and may include the memory **360** and/or at least one of the TX processor **368**, the RX processor **356**, and the controller/processor **359**.

In one configuration, the apparatus **2102/2102'** for wireless communication includes means for receiving, from a base station, through a set of beams a set of BRSs. The apparatus **2102/2102'** may further include means for measuring a signal quality of each BRS of the set of BRSs, and each measured signal quality may correspond to a beam of the set of beams. In an aspect, the apparatus **2102/2102'** may include means for maintaining a set of candidate beam indexes corresponding to a set of best measured signal qualities of the set of BRSs.

The apparatus **2102/2102'** may further include means for transmitting, to the base station, BSI indicating at least one measured signal quality and at least one beam index from the set of maintained candidate beam indexes, the at least one beam index corresponding to the at least one measured signal quality. In an aspect, the set of the best measured signal qualities is a set of the highest measured signal qualities. In an aspect, N candidate beam indexes are maintained in the set of candidate beam indexes, and N may be predetermined. In an aspect, the set of best measured signal qualities of the set of BRSs is based on a most recent set of signal qualities of the set of BRSs, a filtered set of signal qualities of the set of BRSs, or a time-averaged set of signal qualities of the set of BRSs. In an aspect, the maintenance of the set of candidate beam indexes is based on at least one hysteresis criteria for including a beam index in or excluding a beam index from the set of candidate beam indexes. In an aspect, the apparatus **2102/2102'** may further include means for receiving, from the base station, an indication of one or

55

more beam indexes that are to be excluded from the maintained set of candidate beam indexes. In an aspect, the signal quality comprises at least one of a BRSRP, a BRSRQ, an SIR, an SNR, or an SINR.

The aforementioned means may be one or more of the aforementioned components of the apparatus **2102** and/or the processing system **2214** of the apparatus **2102'** configured to perform the functions recited by the aforementioned means. As described supra, the processing system **2214** may include the TX Processor **368**, the RX Processor **356**, and the controller/processor **359**. As such, in one configuration, the aforementioned means may be the TX Processor **368**, the RX Processor **356**, and the controller/processor **359** configured to perform the functions recited by the aforementioned means.

FIG. **23** is a conceptual data flow diagram **2300** illustrating the data flow between different means/components in an exemplary apparatus **2302**. The apparatus may be a UE. The data flow illustrated in the diagram **2300** is to be regarded as illustrative. Therefore, one or more additional means/components may be present, and one or more illustrated means/components may be absent, according to various aspects. Further, various data flow may occur between means/components in addition to and/or instead of the illustrated data flow.

The apparatus **2302** may include a reception component **2304** configured to receive signals from a base station (e.g., the base station **2350**, a mmW base station, an eNB, etc.). The apparatus **2302** may further include a transmission component **2310** configured to transmit signals to a base station (e.g., the base station **2350**, a mmW base station, an eNB, etc.).

In aspects, the reception component **2304** may receive, from the base station **2350**, a set of signals (e.g., a signal may be an aspect of a BRS) through a set of beams. Each signal of the set of signals may correspond to a beam, and each beam may correspond to a beam index (ergo, each signal may correspond to a beam index). Each signal may be received through a respective beam that may be used for communication between the apparatus **2302** and the base station **2350**. The reception component **2304** may provide the set of BRSs to a measurement component **2306**.

The measurement component **2306** may be configured to determine a received power for each signal of the set of signals received through each beam of the set of beams. Each received power may be associated with a beam of the set of beams. For example, the measurement component **2306** may measure at least one of a BRSRP.

The measurement component **2306** may provide, to the reporting component **2312**, measurement information. The measurement information may include one or more beam indexes and one or more received powers (e.g., a first beam index and a corresponding first received power, a second beam index and a corresponding second received power, etc.).

In one aspect, the reporting component **2312** may be configured to maintain a set of candidate beam indexes. The set of candidate beam indexes may include a predetermined number of candidate beam indexes (e.g., four candidate beam indexes) and a respective received power for each BRS corresponding to each beam index of the predetermined number of candidate beam indexes. In an aspect, the set of candidate beam indexes may include a set of beam indexes corresponding to the highest received powers for a set of BRSs. The reporting component **2312** may sort the set of candidate beam indexes in decreasing order of highest

56

received power, beginning with the beam index corresponding to the highest received power.

The reporting component **2312** may be configured to generate one or more BSI reports. The reporting component **2312** may generate a BSI report to include at least a beam index and a corresponding received power. The reporting component **2312** may select a beam index and corresponding received power from the maintained set of candidate beam indexes. The reporting component **2312** may be configured to cause the transmission component **2310** to send one or more BSI reports to the base station **2350**. The number N of BSI reports to transmit to the base station **2350** may be determined by the determination component **2308**. Additionally, the determination component **2308** may determine a channel that is to carry the one or more BSI reports, and indicate the determined channel to the reporting component **2312** so that the one or more BSI reports are carried on the determined channel.

According to aspects, the determination component **2308** may determine the number N of BSI reports to send to the base station **2350** based on a message requesting BSI. For example, the determination component **2308** may determine the number N based on a type of the message received from the base station **2350**.

In an aspect, the type of message requesting BSI may be a DCI message (e.g., a downlink DCI message). The determination component **2308** may determine that the number N of BSI reports to send to the base station **2350** is one when the message requesting BSI is indicated by a DCI message (e.g., a downlink DCI message). In an aspect, the determination component **2308** may determine that the one BSI report is to be carried on a PUCCH (e.g., an ePUCCH).

In another aspect, the determination component **2308** may determine that the number N of BSI reports to send to the base station **2350** is different from one when the message requesting BSI is indicated by an uplink DCI message. For example, the determination component **2308** may determine that the number N is zero, two, or four based on an indication included in the uplink DCI message. When the determination component **2308** determines that the number N is greater than one (e.g., two or four), the determination component **2308** may determine that the BSI reports are to be carried on a PUSCH (e.g., an ePUSCH).

In another aspect, the type of message requesting BSI may be an RAR message (e.g., a MSG2, an uplink grant associated with a RACH procedure, etc.). The determination component **2308** may determine that the number N of BSI reports to send to the base station **2350** is different from one when the message requesting BSI is indicated by an RAR message. For example, the determination component **2308** may determine that the number N is zero, two, or four based on an indication included in the RAR message. When the determination component **2308** determines that the number N is greater than one (e.g., two or four), the determination component **2308** may determine that the BSI reports are to be carried on a PUSCH (e.g., an ePUSCH).

The determination component **2308** may indicate, to the reporting component **2312**, the number N and/or the channel on which the BSI report(s) are to be carried. As described, the reporting component **2312** may cause the transmission component **2310** to send, to the base station **2350**, the N BSI report(s) on the indicated channel.

The apparatus may include additional components that perform each of the blocks of the algorithm in the aforementioned flowcharts of FIG. **14**. As such, each block in the aforementioned flowcharts of FIG. **14** may be performed by a component and the apparatus may include one or more of

57

those components. The components may be one or more hardware components specifically configured to carry out the stated processes/algorithm, implemented by a processor configured to perform the stated processes/algorithm, stored within a computer-readable medium for implementation by a processor, or some combination thereof.

FIG. 24 is a diagram 2400 illustrating an example of a hardware implementation for an apparatus 2302' employing a processing system 2414. The processing system 2414 may be implemented with a bus architecture, represented generally by the bus 2424. The bus 2424 may include any number of interconnecting buses and bridges depending on the specific application of the processing system 2414 and the overall design constraints. The bus 2424 links together various circuits including one or more processors and/or hardware components, represented by the processor 2404, the components 2304, 2306, 2308, 2310, 2312 and the computer-readable medium/memory 2406. The bus 2424 may also link various other circuits such as timing sources, peripherals, voltage regulators, and power management circuits, which are well known in the art, and therefore, will not be described any further.

The processing system 2414 may be coupled to a transceiver 2410. The transceiver 2410 is coupled to one or more antennas 2420. The transceiver 2410 provides a means for communicating with various other apparatus over a transmission medium. The transceiver 2410 receives a signal from the one or more antennas 2420, extracts information from the received signal, and provides the extracted information to the processing system 2414, specifically the reception component 2304. In addition, the transceiver 2410 receives information from the processing system 2414, specifically the transmission component 2310, and based on the received information, generates a signal to be applied to the one or more antennas 2420. The processing system 2414 includes a processor 2404 coupled to a computer-readable medium/memory 2406. The processor 2404 is responsible for general processing, including the execution of software stored on the computer-readable medium/memory 2406. The software, when executed by the processor 2404, causes the processing system 2414 to perform the various functions described supra for any particular apparatus. The computer-readable medium/memory 2406 may also be used for storing data that is manipulated by the processor 2404 when executing software. The processing system 2414 further includes at least one of the components 2304, 2306, 2308, 2310, 2312. The components may be software components running in the processor 2404, resident/stored in the computer readable medium/memory 2406, one or more hardware components coupled to the processor 2404, or some combination thereof. The processing system 2414 may be a component of the UE 350 and may include the memory 360 and/or at least one of the TX processor 368, the RX processor 356, and the controller/processor 359.

In one configuration, the apparatus 2302/2302' for wireless communication includes means for receiving, from a base station, a message requesting BSI. The apparatus 2302/2302' may further include means for determining a number N of BSI reports to send to the base station, each BSI report indicating a beam index corresponding to a beam and a received power associated with the beam. The apparatus 2302/2302' may further include means for sending, to the base station, N BSI reports based on the message requesting BSI.

In an aspect, the apparatus 2302/2302' may further include means for receiving, from the base station, a set of signals through a set of beams. The apparatus 2302/2302'

58

may further include means for determining the received power for each signal of the set of signals received through each beam of the set of beams, each received power associated with a beam of the set of beams.

In an aspect, the N BSI reports include N received powers corresponding to the highest determined received powers. In an aspect, the determination of the number N of BSI reports to send to the base station is based on a type of the message requesting the BSI. In an aspect, the type of the message requesting the BSI comprises a DCI message. In an aspect, the number N of BSI reports to send to the base station is determined to be one based on the DCI message. In an aspect, the determined number N of BSI reports are sent on a PUCCH. In an aspect, the type of message requesting the BSI comprises an RAR message. In an aspect, the number N of BSI reports is determined to be greater than one based on the RAR message. In an aspect, the determined number N of BSI reports are sent on a PUSCH.

The aforementioned means may be one or more of the aforementioned components of the apparatus 2302 and/or the processing system 2414 of the apparatus 2302' configured to perform the functions recited by the aforementioned means. As described supra, the processing system 2414 may include the TX Processor 368, the RX Processor 356, and the controller/processor 359. As such, in one configuration, the aforementioned means may be the TX Processor 368, the RX Processor 356, and the controller/processor 359 configured to perform the functions recited by the aforementioned means.

FIG. 25 is a conceptual data flow diagram 2500 illustrating the data flow between different means/components in an exemplary apparatus 2502. The apparatus may be a UE. The data flow illustrated in the diagram 2500 is to be regarded as illustrative. Therefore, one or more additional means/components may be present, and one or more illustrated means/components may be absent, according to various aspects. Further, various data flow may occur between means/components in addition to and/or instead of the illustrated data flow.

The apparatus 2502 may include a reception component 2504 configured to receive signals from a base station (e.g., the base station 2550, a mmW base station, an eNB, etc.). The apparatus 2502 may further include a transmission component 2510 configured to transmit signals to a base station (e.g., the base station 2550, a mmW base station, an eNB, etc.).

In an aspect, the apparatus 2502 may include a selection component 2506. The selection component 2506 may be configured to select a first beam for communication with the base station 2550. For example, the selection component 2506 may select the first beam based on an estimation or determination of a beam through which the selection component 2506 expects the base station 2550 to be able to receive signals from the apparatus 2502.

In one aspect, the selection component 2506 may select the first beam based on reception of one or more BRSs from the base station 2550. The selection component 2506 may select a beam corresponding to a BRS with a highest received power or quality (e.g., a highest BRSRP). For example, the selection component 2506 may determine a beam index corresponding to a BRS with a highest received power or quality and select a beam corresponding to that beam index. The selection component 2506 may provide, to a RACH component 2508, an indication of the selected first beam (e.g., a first beam index corresponding to the selected first beam).

59

The RACH component **2508** may be configured to perform a RACH procedure with the base station **2550**. For example, the RACH component **2508** may determine that a RACH procedure is successful when the RACH component **2508** receives, from the base station **2550**, a contention resolution message (e.g., a MSG4) and/or when the RACH component **2508** causes the apparatus **2502** to be synchronized with a network that includes the base station **2550**.

In an aspect, the RACH component **2508** may perform a RACH procedure that includes communication of a plurality of RACH messages between the apparatus **2502** and the base station **2550**. For example, the RACH procedure may include transmission of a random access preamble (e.g., a MSG1) to the base station **2550**, reception of an RAR message (e.g., a MSG2) from the base station **2550** based on the random access preamble, transmission of a connection request message (e.g., a MSG3) to the base station **2550** based on the RAR message, and reception of a contention resolution message (e.g., a MSG4) from the base station **2550** based on the connection request message.

The RACH component **2508** may be configured to determine that a RACH procedure with the base station **2550** failed. For example, if the RACH component **2508** fails to receive and/or decode an RAR message or a contention resolution message, then the RACH component **2508** may determine that the RACH procedure with the base station **2550** has failed.

In an aspect, the RACH component **2508** may attempt, through the selected first beam, at least one RACH procedure. For example, the RACH component **2508** may cause the transmission component **2510** to send, through the selected first beam, a random access preamble. Additionally, the RACH component **2508** may cause the transmission component **2510** to send, through the selected first beam, a connection request message based on an RAR message.

In an aspect, the RACH component **2508** may determine that the at least one RACH procedure with the base station **2550** has failed. For example, the RACH component **2508** may fail to receive and/or decode an RAR message or a contention resolution message. The RACH component **2508** may provide information indicating the at least one RACH procedure failed to the selection component **2506** and/or a maintenance component **2512**.

According to an aspect, the information indicating that the at least one RACH procedure failed may include information associated with the selected first beam (e.g., a first beam index corresponding to the selected first beam). According to an aspect, the information indicating that the at least one RACH procedure failed may include information indicating a subframe in which a RACH message associated with the RACH procedure is carried.

In one aspect, the selection component **2506** may select a new beam for communication with the base station **2550** based on the information indicating that the at least one RACH procedure failed. In another aspect, the selection component **2506** may determine an increased transmission power for transmission of RACH messages based on the information indicating that the at least one RACH procedure failed. The selection component **2506** may indicate, to the RACH component **2508**, the new beam (e.g., a new beam index corresponding to the new beam) and/or the increased transmission power.

Accordingly, the RACH component **2508** may attempt a next RACH procedure through the new beam and/or using the increased transmission power. When next RACH procedure is successful, the RACH component **2508** may

60

indicate, to the maintenance component **2512**, that the next RACH procedure with the base station **2550** succeeded.

In an aspect, the maintenance component **2512** may store the information indicating that the at least one RACH procedure failed. For example, the maintenance component **2512** may store information associated with the selected first beam (e.g., a first beam index corresponding to the selected first beam).

In one aspect, the maintenance component **2512** may be configured to maintain a set of candidate beam indexes. The set of candidate beam indexes may include a predetermined number of candidate beam indexes (e.g., four candidate beam indexes) and a respective received power for each BRS corresponding to each beam index of the predetermined number of candidate beam indexes. In an aspect, the set of candidate beam indexes may include a set of beam indexes corresponding to the BRSs having the highest received powers. The maintenance component **2512** may sort the set of candidate beam indexes in decreasing order of highest received power, beginning with the beam index corresponding to the highest received power. In an aspect, the maintenance component **2512** may be configured to exclude, from the set of candidate beam indexes, the first beam index corresponding to the selected first beam.

When the next RACH procedure with the base station **2550** succeeds, the maintenance component **2512** may send, to the base station **2550**, information indicating that the at least one RACH procedure failed. In an aspect, the information indicating that the at least one RACH procedure failed may include information associated with the selected first beam (e.g., a first beam index corresponding to the selected first beam). In another aspect, the information indicating that the at least one RACH procedure failed may include an indication of a subframe in which a RACH message associated with the at least one RACH procedure is carried. For example, the information may indicate a subframe in which a random access preamble is carried or a subframe in which a connection request message is carried.

In one aspect, the maintenance component **2512** may generate a BSI report. The maintenance component **2512** may generate the BSI report to indicate the information associated with the at least failed RACH procedure (e.g., a first beam index corresponding to the selected first beam). The maintenance component **2512** may cause the transmission component **2510** to send the BSI report to the base station **2550**, for example, through the new beam associated with the successful RACH procedure.

The apparatus may include additional components that perform each of the blocks of the algorithm in the aforementioned flowcharts of FIG. **15**. As such, each block in the aforementioned flowcharts of FIG. **15** may be performed by a component and the apparatus may include one or more of those components. The components may be one or more hardware components specifically configured to carry out the stated processes/algorithm, implemented by a processor configured to perform the stated processes/algorithm, stored within a computer-readable medium for implementation by a processor, or some combination thereof.

FIG. **26** is a diagram **2600** illustrating an example of a hardware implementation for an apparatus **2502** employing a processing system **2614**. The processing system **2614** may be implemented with a bus architecture, represented generally by the bus **2624**. The bus **2624** may include any number of interconnecting buses and bridges depending on the specific application of the processing system **2614** and the overall design constraints. The bus **2624** links together various circuits including one or more processors and/or

61

hardware components, represented by the processor **2604**, the components **2504**, **2506**, **2508**, **2510**, **2512** and the computer-readable medium/memory **2606**. The bus **2624** may also link various other circuits such as timing sources, peripherals, voltage regulators, and power management circuits, which are well known in the art, and therefore, will not be described any further.

The processing system **2614** may be coupled to a transceiver **2610**. The transceiver **2610** is coupled to one or more antennas **2620**. The transceiver **2610** provides a means for communicating with various other apparatus over a transmission medium. The transceiver **2610** receives a signal from the one or more antennas **2620**, extracts information from the received signal, and provides the extracted information to the processing system **2614**, specifically the reception component **2504**. In addition, the transceiver **2610** receives information from the processing system **2614**, specifically the transmission component **2510**, and based on the received information, generates a signal to be applied to the one or more antennas **2620**. The processing system **2614** includes a processor **2604** coupled to a computer-readable medium/memory **2606**. The processor **2604** is responsible for general processing, including the execution of software stored on the computer-readable medium/memory **2606**. The software, when executed by the processor **2604**, causes the processing system **2614** to perform the various functions described supra for any particular apparatus. The computer-readable medium/memory **2606** may also be used for storing data that is manipulated by the processor **2604** when executing software. The processing system **2614** further includes at least one of the components **2504**, **2506**, **2508**, **2510**, **2512**. The components may be software components running in the processor **2604**, resident/stored in the computer readable medium/memory **2606**, one or more hardware components coupled to the processor **2604**, or some combination thereof. The processing system **2614** may be a component of the UE **350** and may include the memory **360** and/or at least one of the TX processor **368**, the RX processor **356**, and the controller/processor **359**.

In one configuration, the apparatus **2502/2502'** for wireless communication includes means for selecting a first beam for communication with a base station. The apparatus **2502/2502'** may further include means for attempting, through the selected first beam, at least one RACH procedure with the base station. The apparatus **2502/2502'** may further include means for determining that the at least one RACH procedure failed with the base station. The apparatus **2502/2502'** may further include means for sending, after a successful RACH procedure with the base station, information indicating that the at least one RACH procedure failed.

In an aspect, the apparatus **2502/2502'** may further include means for selecting a new beam for communication with the base station after the determination that the at least one RACH procedure failed. In an aspect, at least a portion of the successful RACH procedure is performed through the selected new beam.

In an aspect, the apparatus **2502/2502'** may further include means for increasing a transmission power after the determination that the at least one RACH procedure failed. In an aspect, at least a portion of the successful RACH procedure is performed with the increased transmission power.

In an aspect, the apparatus **2502/2502'** may further include means for storing information associated with the selected first beam based on the determination that the at least one RACH procedure failed. In an aspect, the information indicating that the at least one RACH procedure

62

failed includes the stored information associated with the first beam. In an aspect, the information indicating that the at least one RACH procedure failed includes an indication of a subframe in which a RACH message associated with the at least one RACH procedure is carried.

In an aspect, the apparatus **2502/2502'** may further include means for excluding the selected first beam from a candidate beam set maintained by the apparatus based on the determination that the at least one RACH procedure failed.

In an aspect, the information indicating that the at least one RACH procedure failed comprises a BSI report. In an aspect, the means for attempting the at least one RACH procedure is configured to at least one of: transmit, to the base station, a random access preamble; receive, from the base station, a random access response based on the random access preamble; transmit, to the base station, a connection request message based on the random access response; or receive a contention resolution message based on the connection request message. In an aspect, the apparatus **2502/2502'** is synchronized with a network that includes the base station based on the successful RACH procedure.

The aforementioned means may be one or more of the aforementioned components of the apparatus **2502** and/or the processing system **2614** of the apparatus **2502'** configured to perform the functions recited by the aforementioned means. As described supra, the processing system **2614** may include the TX Processor **368**, the RX Processor **356**, and the controller/processor **359**. As such, in one configuration, the aforementioned means may be the TX Processor **368**, the RX Processor **356**, and the controller/processor **359** configured to perform the functions recited by the aforementioned means.

FIG. **27** is a conceptual data flow diagram **2700** illustrating the data flow between different means/components in an exemplary apparatus **2702**. The apparatus may be a UE. The data flow illustrated in the diagram **2700** is to be regarded as illustrative. Therefore, one or more additional means/components may be present, and one or more illustrated means/components may be absent, according to various aspects. Further, various data flow may occur between means/components in addition to and/or instead of the illustrated data flow.

The apparatus **2702** may include a reception component **2704** configured to receive signals from a base station (e.g., the base station **2750**, a mmW base station, an eNB, etc.). The apparatus **2702** may further include a transmission component **2710** configured to transmit signals to a base station (e.g., the base station **2750**, a mmW base station, an eNB, etc.).

The apparatus **2702** may include a RACH component **2708** that may be configured to perform a RACH procedure with the base station **2750**. In an aspect, the RACH component **2708** may perform a RACH procedure that includes communication of a plurality of RACH messages between the apparatus **2702** and the base station **2750**. For example, the RACH procedure may include transmission of a random access preamble (e.g., a MSG1) to the base station **2750**, reception of an RAR message (e.g., a MSG2) from the base station **2750** based on the random access preamble, transmission of a connection request message (e.g., a MSG3) to the base station **2750** based on the RAR message, and reception of a contention resolution message (e.g., a MSG4) from the base station **2750** based on the connection request message.

In an aspect, the RACH component **2708** may provide a contention resolution message (e.g., a MSG4) to a selection component **2706**. The selection component **2706** may be

63

configured to select a new beam for communication with the base station 2750 based on the information included in the contention resolution message.

The selection component 2706 may be configured to determine whether a beam index included in the contention resolution message is applicable to the apparatus 2702, and the beam index may be indicated by the contention resolution message. In one aspect, the selection component 2706 may determine whether the beam index included in the contention resolution message is intended for the apparatus 2702. For example, the selection component 2706 may attempt to decode the contention resolution message based on an RNTI associated with the apparatus 2702 (e.g., an RNTI determined as part of a RACH procedure). The selection component 2706 may determine that the beam index included in the contention resolution message is applicable to the apparatus 2702 when the selection component 2706 successfully decodes the contention resolution message.

In an aspect, the selection component 2706 may provide an indication of the beam index to the reception component 2704 and/or the transmission component 2710. Therefore, the reception component 2704 and/or the transmission component 2710 may communicate with the base station 2750 through the beam corresponding to the beam index.

In an aspect, the selection component 2706 may determine one or more channels associated with the beam index, for example, as indicated by the contention resolution message. The selection component 2706 may provide an indication of the one or more channels to the reception component 2704 (e.g., for downlink channels) and/or the transmission component 2710 (e.g., for uplink channels). The reception component 2704 and/or the transmission component 2710 may then communicate with the base station 2750 through the beam corresponding to the beam index on the one or more indicated channels.

In an aspect, the selection component 2706 may provide an indication of whether the beam index is applicable to the apparatus 2702 to an acknowledgement component 2712. The acknowledgement component 2712 may be configured to determine whether to transmit feedback (e.g., acknowledgement/non-acknowledgement feedback) to the base station 2750. In an aspect, when the selection component 2706 indicates to the acknowledgement component 2712 that the beam index is applicable to the apparatus 2702, the acknowledgement component 2712 may generate an acknowledgement message and cause the transmission component 2710 to transmit the acknowledgement message to the base station 2750. In an aspect, when the selection component 2706 indicates to the acknowledgement component 2712 that the beam index is inapplicable to the apparatus 2702 or when the selection component 2706 indicates that the selection component 2706 is unable to successfully decode the contention resolution message, the acknowledgement component 2712 may refrain from sending a non-acknowledgment message to the base station 2750.

The apparatus may include additional components that perform each of the blocks of the algorithm in the aforementioned flowcharts of FIG. 16. As such, each block in the aforementioned flowcharts of FIG. 16 may be performed by a component and the apparatus may include one or more of those components. The components may be one or more hardware components specifically configured to carry out the stated processes/algorithm, implemented by a processor configured to perform the stated processes/algorithm, stored within a computer-readable medium for implementation by a processor, or some combination thereof.

64

FIG. 28 is a diagram 2800 illustrating an example of a hardware implementation for an apparatus 2702' employing a processing system 2814. The processing system 2814 may be implemented with a bus architecture, represented generally by the bus 2824. The bus 2824 may include any number of interconnecting buses and bridges depending on the specific application of the processing system 2814 and the overall design constraints. The bus 2824 links together various circuits including one or more processors and/or hardware components, represented by the processor 2804, the components 2704, 2706, 2708, 2710, 2712 and the computer-readable medium/memory 2806. The bus 2824 may also link various other circuits such as timing sources, peripherals, voltage regulators, and power management circuits, which are well known in the art, and therefore, will not be described any further.

The processing system 2814 may be coupled to a transceiver 2810. The transceiver 2810 is coupled to one or more antennas 2820. The transceiver 2810 provides a means for communicating with various other apparatus over a transmission medium. The transceiver 2810 receives a signal from the one or more antennas 2820, extracts information from the received signal, and provides the extracted information to the processing system 2814, specifically the reception component 2704. In addition, the transceiver 2810 receives information from the processing system 2814, specifically the transmission component 2710, and based on the received information, generates a signal to be applied to the one or more antennas 2820. The processing system 2814 includes a processor 2804 coupled to a computer-readable medium/memory 2806. The processor 2804 is responsible for general processing, including the execution of software stored on the computer-readable medium/memory 2806. The software, when executed by the processor 2804, causes the processing system 2814 to perform the various functions described supra for any particular apparatus. The computer-readable medium/memory 2806 may also be used for storing data that is manipulated by the processor 2804 when executing software. The processing system 2814 further includes at least one of the components 2704, 2706, 2708, 2710, 2712. The components may be software components running in the processor 2804, resident/stored in the computer readable medium/memory 2806, one or more hardware components coupled to the processor 2804, or some combination thereof. The processing system 2814 may be a component of the UE 350 and may include the memory 360 and/or at least one of the TX processor 368, the RX processor 356, and the controller/processor 359.

In one configuration, the apparatus 2702/2702' for wireless communication includes means for receiving, from a base station, a contention resolution message, the contention resolution message indicating at least a beam index corresponding to a beam. The apparatus 2702/2702' may further include means for determining whether the beam index is applicable to the apparatus 2702/2702'. The apparatus 2702/2702' may further include means for communicating with the base station through the beam corresponding to the beam index when the beam index is applicable to the apparatus 2702/2702'.

In an aspect, the apparatus 2702/2702' may further include means for transmitting, to the base station, an acknowledgement message when the beam index is determined to be applicable to the apparatus 2702/2702'. In an aspect, the contention resolution message is associated with a random access procedure. In an aspect, the means for determining whether the beam index is applicable to the apparatus 2702/2702' is configured to attempt to decode the

65

contention resolution message based on a RNTI associated with the apparatus **2702/2702'**, and the beam index is determined to be applicable to the apparatus **2702/2702'** when the contention resolution message is successfully decoded.

In an aspect, the apparatus **2702/2702'** further includes means for refraining from transmitting a non-acknowledgement message to the base station when the beam index is determined to be inapplicable to the apparatus **2702/2702'** or if the contention resolution message is unsuccessfully decoded. In an aspect, the contention resolution message further includes an indication of one or more channels associated with the beam index, and the communication with the base station through the beam corresponding to the beam index is performed on the one or more indicated channels.

In an aspect, the apparatus **2702/2702'** further includes means for transmitting, to the base station, a random access preamble. The apparatus **2702/2702'** further includes means for receiving, from the base station, a random access response based on the random access preamble. The apparatus **2702/2702'** further includes means for transmitting, to the base station, a connection request message based on the random access response. In an aspect, the contention resolution message is transmitted based on the connection request message.

The aforementioned means may be one or more of the aforementioned components of the apparatus **2702** and/or the processing system **2814** of the apparatus **2702'** configured to perform the functions recited by the aforementioned means. As described supra, the processing system **2814** may include the TX Processor **368**, the RX Processor **356**, and the controller/processor **359**. As such, in one configuration, the aforementioned means may be the TX Processor **368**, the RX Processor **356**, and the controller/processor **359** configured to perform the functions recited by the aforementioned means.

FIG. **29** is a conceptual data flow diagram **2900** illustrating the data flow between different means/components in an exemplary apparatus **2902**. The apparatus may be a base station. The data flow illustrated in the diagram **2900** is to be regarded as illustrative. Therefore, one or more additional means/components may be present, and one or more illustrated means/components may be absent, according to various aspects. Further, various data flow may occur between means/components in addition to and/or instead of the illustrated data flow.

The apparatus **2902** may include a reception component **2904** configured to receive signals from a UE (e.g., the UE **2950**, a mmW UE, etc.). The apparatus **2902** may further include a transmission component **2910** configured to transmit signals to a UE (e.g., the UE **2950**, a mmW UE, etc.).

The apparatus **2902** may include a RACH component **2908** that may be configured to perform a RACH procedure with the UE **2950**. In an aspect, the RACH component **2908** may perform a RACH procedure that includes communication of a plurality of RACH messages between the apparatus **2902** and the UE **2950**. For example, the RACH procedure may include reception of a random access preamble (e.g., a MSG1) from the UE **2950**, transmission of an RAR message (e.g., a MSG2) to the UE **2950** based on the random access preamble, reception of a connection request message (e.g., a MSG3) from the UE **2950** based on the RAR message, and transmission of a contention resolution message (e.g., a MSG4) to the UE **2950** based on the connection request message.

66

In an aspect, a selection component **2906** may be configured to determine a beam index applicable to the UE **2950**, such as a beam index to be used for communication between the apparatus **2902** and the UE **2950**. In one aspect, the selection component **2906** may be configured to determine the beam index based on feedback from the UE **2950** (e.g., feedback based on one or more BRSs transmitted by the apparatus **2902**). The selection component **2906** may provide the beam index to the RACH component **2908**.

In an aspect, the selection component **2906** may determine one or more channels associated with the beam index, for example, to be indicated by the contention resolution message. The selection component **2906** may provide an indication of the one or more channels to the RACH component **2908** (e.g., for inclusion in a contention resolution message).

The RACH component **2908** may be configured to include, in a contention resolution message, an indication of the beam index (and, optionally, an indication of one or more channels). In an aspect, the RACH component **2908** may indicate that the beam index is applicable to the UE **2950**. For example, the RACH component **2908** may scramble the contention resolution message based on an RNTI associated with the UE **2950** (e.g., an RNTI determined as part of a RACH procedure). The RACH component **2908** may cause transmission, to the UE **2950**, of the contention resolution message indicating the beam index corresponding to the beam and indicating that the beam index is applicable to the UE **2950**.

An acknowledgement component **2912** may be configured to determine whether to feedback (e.g., acknowledgement/non-acknowledgement feedback) is received from the UE **2950**. In an aspect, the acknowledgement component **2912** may receive an acknowledgement message from the UE **2950**, which may indicate that the UE **2950** acknowledges that communication between the apparatus **2902** and the UE **2950** is to occur on the beam corresponding to the beam index indicated by the contention resolution message. The acknowledgement component **2912** may provide an indication of the beam index to the reception component **2904** and/or the transmission component **2910** (e.g., based on one or more channels on which communication is to occur). The reception component **2904** and/or the transmission component **2910** may then communicate with the UE **2950** through the beam corresponding to the beam index on the one or more channels.

If the acknowledgement component **2912** does not receive an acknowledgement message, communication with the UE **2950** may occur through a serving beam that is used for communication before transmission of the contention resolution message.

The apparatus may include additional components that perform each of the blocks of the algorithm in the aforementioned flowcharts of FIG. **17**. As such, each block in the aforementioned flowcharts of FIG. **17** may be performed by a component and the apparatus may include one or more of those components. The components may be one or more hardware components specifically configured to carry out the stated processes/algorithm, implemented by a processor configured to perform the stated processes/algorithm, stored within a computer-readable medium for implementation by a processor, or some combination thereof.

FIG. **30** is a diagram **3000** illustrating an example of a hardware implementation for an apparatus **2902'** employing a processing system **3014**. The processing system **3014** may be implemented with a bus architecture, represented generally by the bus **3024**. The bus **3024** may include any number

of interconnecting buses and bridges depending on the specific application of the processing system **3014** and the overall design constraints. The bus **3024** links together various circuits including one or more processors and/or hardware components, represented by the processor **3004**, the components **2904**, **2906**, **2908**, **2910**, **2912** and the computer-readable medium/memory **3006**. The bus **3024** may also link various other circuits such as timing sources, peripherals, voltage regulators, and power management circuits, which are well known in the art, and therefore, will not be described any further.

The processing system **3014** may be coupled to a transceiver **3010**. The transceiver **3010** is coupled to one or more antennas **3020**. The transceiver **3010** provides a means for communicating with various other apparatus over a transmission medium. The transceiver **3010** receives a signal from the one or more antennas **3020**, extracts information from the received signal, and provides the extracted information to the processing system **3014**, specifically the reception component **2904**. In addition, the transceiver **3010** receives information from the processing system **3014**, specifically the transmission component **2910**, and based on the received information, generates a signal to be applied to the one or more antennas **3020**. The processing system **3014** includes a processor **3004** coupled to a computer-readable medium/memory **3006**. The processor **3004** is responsible for general processing, including the execution of software stored on the computer-readable medium/memory **3006**. The software, when executed by the processor **3004**, causes the processing system **3014** to perform the various functions described supra for any particular apparatus. The computer-readable medium/memory **3006** may also be used for storing data that is manipulated by the processor **3004** when executing software. The processing system **3014** further includes at least one of the components **2904**, **2906**, **2908**, **2910**, **2912**. The components may be software components running in the processor **3004**, resident/stored in the computer readable medium/memory **3006**, one or more hardware components coupled to the processor **3004**, or some combination thereof. The processing system **3014** may be a component of the base station **310** and may include the memory **376** and/or at least one of the TX processor **316**, the RX processor **370**, and the controller/processor **375**.

In one configuration, the apparatus **2902/2902'** for wireless communication includes means for means for transmitting, to a UE, a contention resolution message, the contention resolution message indicating at least a beam index corresponding to a beam and indicating that the beam index is applicable to the UE. The apparatus **2902/2902'** may further includes means for determining whether an acknowledgement message is received from the UE in response to the contention resolution message. The apparatus **2902/2902'** may further include means for communicating with the UE through the beam corresponding to the beam index when the acknowledgement message is determined to be received from the UE.

In an aspect, the contention resolution message is associated with a random access procedure. In an aspect, the apparatus **2902/2902'** may further include means for scrambling at least a portion of the contention resolution message using an RNTI associated the UE. In an aspect, the contention resolution message further includes an indication of one or more channels associated with the beam index, and the communication with the UE through the beam corresponding to the beam index is performed on the one or more indicated channels.

In an aspect, the apparatus **2902/2902'** may further include means for communicating with the UE through a serving beam before transmission of the contention resolution message, and the communication with the UE continues through the serving beam based on an absence of an acknowledgement message from the UE.

In an aspect, the apparatus **2902/2902'** may further include means for receiving, from the UE, a random access preamble. The apparatus **2902/2902'** may further include means for transmitting, to the UE, a random access response based on the random access preamble. The apparatus **2902/2902'** may further include means for receiving, from the UE, a connection request message based on the random access response, and the contention resolution message is transmitted based on the connection request message.

The aforementioned means may be one or more of the aforementioned components of the apparatus **2902** and/or the processing system **3014** of the apparatus **2902'** configured to perform the functions recited by the aforementioned means. As described supra, the processing system **3014** may include the TX Processor **316**, the RX Processor **370**, and the controller/processor **375**. As such, in one configuration, the aforementioned means may be the TX Processor **316**, the RX Processor **370**, and the controller/processor **375** configured to perform the functions recited by the aforementioned means.

FIG. **31** is a conceptual data flow diagram **3100** illustrating the data flow between different means/components in an exemplary apparatus **3102**. The apparatus may be a UE. The data flow illustrated in the diagram **3100** is to be regarded as illustrative. Therefore, one or more additional means/components may be present, and one or more illustrated means/components may be absent, according to various aspects. Further, various data flow may occur between means/components in addition to and/or instead of the illustrated data flow.

The apparatus **3102** may include a reception component **3104** configured to receive signals from a base station (e.g., the base station **3150**, a mmW base station, an eNB, etc.). The apparatus **3102** may further include a transmission component **3110** configured to transmit signals to a base station (e.g., the base station **3150**, a mmW base station, an eNB, etc.).

In aspects, the reception component **3104** may receive, from the base station **3150**, a set of signals (e.g., a signal may be an aspect of a BRS) through a set of beams. Each signal of the set of signals may correspond to a beam, and each beam may correspond to a beam index (ergo, each signal may correspond to a beam index). Each signal may be received through a respective beam that may be used for communication between the apparatus **3102** and the base station **3150**. The reception component **3104** may provide the set of BRSs to a command component **3106**. The command component **3106** may determine transmit beam indexes corresponding to transmit beams of the base station **3150** based on a respective BRS received through a respective transmit beam. The command component **3106** may provide the transmit beam indexes to a determination component **3108**. The determination component **3108** may maintain a mapping of transmit beam indexes to receive beam indexes.

In various aspects, the command component **3106** may receive, through the reception component **3104** from the base station **3150**, a beam modification command. The beam modification command may indicate a set of transmit beam indexes corresponding to a set of transmit beams of a base station, and each transmit beam index of the set of transmit

69

beam indexes may indicate at least a transmit direction for transmitting a transmit beam by the base station **3150**. The command component **3106** may be configured to determine the set of transmit beam indexes indicated by the beam modification command.

In an aspect, the beam modification command may be received in a MAC CE. In an aspect, the beam modification command may be received in a DCI message. In an aspect, the beam modification command may be received via RRC signaling. In an aspect, the beam modification command may be carried on a PDCCH.

In aspects, the command component **3106** may provide the set of transmit beam indexes to a determination component **3108**. The determination component **3108** may determine a set of receive beam indexes corresponding to a set of receive beams of the apparatus **3102** based on the set of transmit beam indexes. Each receive beam index of the set of receive beam indexes indicating at least a receive direction for receiving a beam by the apparatus **3102**. In an aspect, the determination component **3108** may determine the set of receive beam indexes by accessing a mapping that maps transmit beam indexes to receive beam indexes. The determination component **3108** and/or the command component **3106** may be configured to populate this mapping.

The determination component **3108** may provide the set of receive beam indexes to a BRRS component **3112**. Accordingly, the BRRS component **3112** may cause the reception component **3104** to receive through a receive beam corresponding to a receive beam index included in the set of receive beam indexes, for example, during a symbol in which a BRRS is to be received. In one aspect, the BRRS component **3112** may generate a receive beam corresponding to the at least one receive beam index, for example, when the apparatus **3102** is not actively maintaining that beam.

In one aspect, the BRRS component **3112** may receive the BRRS through the set of transmit beams from the base station **3150** corresponding to the set of transmit beam indexes. In another aspect, the BRRS component **3112** may receive the BRRS through a different set of transmit beam from the base station **3150** than the set of transmit beams corresponding to the transmit beam indexes indicated by the beam modification command. For example, obstruction and/or reflection may cause the apparatus **3102** to receive the BRRS through the determined set of received beams, but through a different set of transmit beams than the set of transmit beams corresponding to the set of transmit beam indexes indicated by the beam modification command.

In one aspect, the BRRS component **3112** may receive the BRRS in one or more symbols corresponding to one or more symbol indexes. For example, the BRRS component **3112** may receive (e.g., listen) through the at least one receive beam corresponding to the at least one receive beam index during one or more symbols corresponding to the one or more symbol indexes. In an aspect, the one or more symbol indexes may be predetermined (e.g., defined by one or more standards promulgated by 3GPP). In another aspect, the one or more symbol indexes may be indicated by the beam modification command (e.g., determined by the command component **3106** and provided to the BRRS component **3112**). In one aspect, the beam modification command further indicates a corresponding transmit beam index of the set of transmit beam indexes for each symbol of the one or more symbol indexes.

In an aspect, the BRRS component **3112** may receive a first portion of the BRRS in a first set of symbols through a first receive beam corresponding to a first receive beam index included in the determined set of receive beam

70

indexes. The BRRS component **3112** may receive a second portion of the BRRS in a second set of symbols through a second receive beam corresponding to a second receive beam index included in the determined set of receive beam indexes.

In one aspect, the BRRS component **3112** may generate a BRI report based on one or more received BRRSs. In an aspect, the BRI report may be similar to a BSI report, but may be used by the base station **3150** to determine a best fine beam. The BRRS component **3112** may transmit a BRI report to index a transmit beam index that is best (e.g., has a highest signal quality or power based on a received BRRS).

The apparatus may include additional components that perform each of the blocks of the algorithm in the aforementioned flowcharts of FIG. **18**. As such, each block in the aforementioned flowcharts of FIG. **18** may be performed by a component and the apparatus may include one or more of those components. The components may be one or more hardware components specifically configured to carry out the stated processes/algorithm, implemented by a processor configured to perform the stated processes/algorithm, stored within a computer-readable medium for implementation by a processor, or some combination thereof.

FIG. **32** is a diagram **3200** illustrating an example of a hardware implementation for an apparatus **3102** employing a processing system **3214**. The processing system **3214** may be implemented with a bus architecture, represented generally by the bus **3224**. The bus **3224** may include any number of interconnecting buses and bridges depending on the specific application of the processing system **3214** and the overall design constraints. The bus **3224** links together various circuits including one or more processors and/or hardware components, represented by the processor **3204**, the components **3104**, **3106**, **3108**, **3110**, **3112** and the computer-readable medium/memory **3206**. The bus **3224** may also link various other circuits such as timing sources, peripherals, voltage regulators, and power management circuits, which are well known in the art, and therefore, will not be described any further.

The processing system **3214** may be coupled to a transceiver **3210**. The transceiver **3210** is coupled to one or more antennas **3220**. The transceiver **3210** provides a means for communicating with various other apparatus over a transmission medium. The transceiver **3210** receives a signal from the one or more antennas **3220**, extracts information from the received signal, and provides the extracted information to the processing system **3214**, specifically the reception component **3104**. In addition, the transceiver **3210** receives information from the processing system **3214**, specifically the transmission component **3110**, and based on the received information, generates a signal to be applied to the one or more antennas **3220**. The processing system **3214** includes a processor **3204** coupled to a computer-readable medium/memory **3206**. The processor **3204** is responsible for general processing, including the execution of software stored on the computer-readable medium/memory **3206**. The software, when executed by the processor **3204**, causes the processing system **3214** to perform the various functions described supra for any particular apparatus. The computer-readable medium/memory **3206** may also be used for storing data that is manipulated by the processor **3204** when executing software. The processing system **3214** further includes at least one of the components **3104**, **3106**, **3108**, **3110**, **3112**. The components may be software components running in the processor **3204**, resident/stored in the computer readable medium/memory **3206**, one or more hardware components

71

coupled to the processor **3204**, or some combination thereof. The processing system **3214** may be a component of the UE **350** and may include the memory **360** and/or at least one of the TX processor **368**, the RX processor **356**, and the controller/processor **359**.

In one configuration, the apparatus **3102/3102'** for wireless communication includes means for receiving a beam modification command that indicates a set of transmit beam indexes corresponding to a set of transmit beams of a base station, and each transmit beam index of the set of transmit beam indexes may indicate at least a transmit direction for transmitting a transmit beam by the base station. The apparatus **3102/3102'** may include means for determining a set of receive beam indexes corresponding to receive beams of the apparatus based on the set of transmit beam indexes, each receive beam index of the set of receive beam indexes indicating at least a receive direction for receiving a receive beam by the apparatus **3102/3102'**. The apparatus **3102/3102'** may further include means for receiving, from the base station, a BRRS through at least one receive beam corresponding to at least one receive beam index included in the set of receive beam indexes.

In an aspect, the means for receiving, from the base station, the BRRS through the at least one receive beam corresponding to the at least one receive beam index included in the set of receive beam indexes is configured to receive a first portion of the BRRS in a first set of symbols through a first receive beam corresponding to a first receive beam index included in the set of receive beam indexes, and further configured to receive a second portion of the BRRS in a second set of symbols through a second receive beam corresponding to a second receive beam index included in the set of receive beam indexes.

In an aspect, the BRRS is received in one or more symbols corresponding to one or more symbol indexes. In an aspect, the beam modification command indicates the one or more symbol indexes, and a corresponding transmit beam index of the set of transmit beam indexes for each symbol index of the one or more symbol indexes. In an aspect, the one or more symbol indexes in which the BRRS is received are predetermined. In an aspect, the BRRS is received through the set of transmit beams from the base station corresponding to the set of transmit beam indexes. In an aspect, the BRRS is received through a different set of transmit beams from the base station than the set of transmit beams corresponding to the set of transmit beam indexes, the different set of transmit beams corresponding to a second set of transmit beam indexes different from the set of transmit beam indexes.

In an aspect, the beam modification command is received in a MAC CE. In an aspect, the beam modification command is received in a DCI message. In an aspect, the beam modification command is received via RRC signaling. In an aspect, beam modification command is carried on a PDCCH.

The aforementioned means may be one or more of the aforementioned components of the apparatus **3102** and/or the processing system **3214** of the apparatus **3102'** configured to perform the functions recited by the aforementioned means. As described supra, the processing system **3214** may include the TX Processor **368**, the RX Processor **356**, and the controller/processor **359**. As such, in one configuration, the aforementioned means may be the TX Processor **368**, the RX Processor **356**, and the controller/processor **359** configured to perform the functions recited by the aforementioned means.

It is understood that the specific order or hierarchy of blocks in the processes/flowcharts disclosed is an illustration

72

of exemplary approaches. Based upon design preferences, it is understood that the specific order or hierarchy of blocks in the processes/flowcharts may be rearranged. Further, some blocks may be combined or omitted. The accompanying method claims present elements of the various blocks in a sample order, and are not meant to be limited to the specific order or hierarchy presented.

The previous description is provided to enable any person skilled in the art to practice the various aspects described herein. Various modifications to these aspects will be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other aspects. Thus, the claims are not intended to be limited to the aspects shown herein, but is to be accorded the full scope consistent with the language claims, wherein reference to an element in the singular is not intended to mean "one and only one" unless specifically so stated, but rather "one or more." The word "exemplary" is used herein to mean "serving as an example, instance, or illustration." Any aspect described herein as "exemplary" is not necessarily to be construed as preferred or advantageous over other aspects. Unless specifically stated otherwise, the term "some" refers to one or more. Combinations such as "at least one of A, B, or C," "one or more of A, B, or C," "at least one of A, B, and C," "one or more of A, B, and C," and "A, B, C, or any combination thereof" include any combination of A, B, and/or C, and may include multiples of A, multiples of B, or multiples of C. Specifically, combinations such as "at least one of A, B, or C," "one or more of A, B, or C," "at least one of A, B, and C," "one or more of A, B, and C," and "A, B, C, or any combination thereof" may be A only, B only, C only, A and B, A and C, B and C, or A and B and C, where any such combinations may contain one or more member or members of A, B, or C. All structural and functional equivalents to the elements of the various aspects described throughout this disclosure that are known or later come to be known to those of ordinary skill in the art are expressly incorporated herein by reference and are intended to be encompassed by the claims. Moreover, nothing disclosed herein is intended to be dedicated to the public regardless of whether such disclosure is explicitly recited in the claims. The words "module," "mechanism," "element," "device," and the like may not be a substitute for the word "means." As such, no claim element is to be construed as a means plus function unless the element is expressly recited using the phrase "means for."

What is claimed is:

1. A method of wireless communication by a base station, the method comprising:

determining a number N greater than zero of beam state information (BSI) reports;
sending, to a user equipment (UE), a message requesting BSI, wherein the message indicates the determined number N of BSI reports requested from the UE;
sending, to the UE, a set of signals through a set of beams;
and
receiving, from the UE, N BSI reports based on the indicated number N of BSI reports, wherein each of the N BSI reports indicates at least one beam index corresponding to at least one beam of the set of beams and at least one received power associated with the at least one beam.

2. The method of claim 1, wherein the message further indicates a set of time and frequency resources on which the N BSI reports are to be carried, and wherein the N BSI reports are received on the indicated set of time and frequency resources.

73

3. The method of claim 1, wherein the message further indicates a channel on which the N BSI reports are to be carried, and wherein the number N of BSI reports is indicated based on the channel on which the N BSI reports are to be carried.

4. The method of claim 1, wherein the N BSI reports include N received powers corresponding to a set of highest received powers, and wherein each of the set of highest received powers is associated with a respective beam of the at least one beam.

5. The method of claim 1, further comprising:
determining a set of candidate beams for communication with the UE based on the N BSI reports.

6. The method of claim 1, further comprising:
switching from beam used for communication with the UE to one of the at least one beam based on the N BSI reports.

7. The method of claim 6, wherein the one of the at least one beam is associated with a highest received power indicated in the N BSI reports.

8. The method of claim 1, wherein the number N of BSI reports is indicated based on a type of the message.

9. The method of claim 8, wherein the type of the message comprises at least one of a downlink control information (DCI) message or a random access response (RAR) message.

10. The method of claim 9, wherein the message indicates that the number N of BSI reports is greater than one based on the type of the message comprising the RAR message.

11. An apparatus for wireless communication by a base station, the apparatus comprising:

means for determining a number N greater than zero of beam state information (BSI) reports;

means for sending, to a user equipment (UE), a message requesting BSI, wherein the message indicates the number N of BSI reports requested from the UE;

means for sending, to the UE, a set of signals through a set of beams; and

means for receiving, from the UE, N BSI reports based on the indicated number N of BSI reports, each of the N BSI reports indicating at least one beam index corresponding to at least one beam of the set of beams and a received power associated with the at least one beam.

12. The apparatus of claim 11, wherein the message further indicates a set of time and frequency resources on which the N BSI reports are to be carried, and wherein the N BSI reports are received on the indicated set of time and frequency resources.

13. The apparatus of claim 11, wherein the message further indicates a channel on which the N BSI reports are to be carried, and wherein the number N of BSI reports is indicated based on the channel on which the N BSI reports are to be carried.

14. The apparatus of claim 11, wherein the N BSI reports include N received powers corresponding to a set of highest received powers, and wherein each of the set of highest received powers is associated with a respective beam of the at least one beam.

15. The apparatus of claim 11, further comprising:
means for determining a set of candidate beams for communication with the UE based on the N BSI reports.

16. The apparatus of claim 11, further comprising:
means for switching from a beam used for communication with the UE to one of the at least one beam based on the N BSI reports.

74

17. The apparatus of claim 16, wherein the one of the at least one beam is associated with a highest received power indicated in the N BSI reports.

18. The apparatus of claim 11, wherein the number N of BSI reports is indicated based on a type of the message.

19. The apparatus of claim 18, wherein the type of the message comprises at least one of a downlink control information (DCI) message or a random access response (RAR) message.

20. The apparatus of claim 19, wherein the message indicates that the number N of BSI reports is greater than one based on the type of the message comprising the RAR message.

21. An apparatus for wireless communication by a base station, the apparatus comprising:

a memory; and

at least one processor coupled to the memory and configured to:

determine a number N greater than zero of beam state information (BSI) reports;

send, to a user equipment (UE), a message requesting BSI, wherein the message indicates the number N greater than or equal to zero of BSI reports requested from the UE;

send, to the UE, a set of signals through a set of beams; and

receive, from the UE, N BSI reports based on the indicated number N of BSI reports, each of the N BSI reports indicating at least one beam index corresponding to at least one beam of the set of beams and a received power associated with the at least one beam.

22. The apparatus of claim 21, wherein the message further indicates a set of time and frequency resources on which the N BSI reports are to be carried, and wherein the N BSI reports are received on the indicated set of time and frequency resources.

23. The apparatus of claim 21, wherein the message further indicates a channel on which the N BSI reports are to be carried, and wherein the number N of BSI reports is indicated based on the channel on which the N BSI reports are to be carried.

24. The apparatus of claim 21, wherein the N BSI reports include N received powers corresponding to a set of highest received powers, and wherein each of the set of highest received powers is associated with a respective beam of the at least one beam.

25. The apparatus of claim 21, wherein the at least one processor is further configured to:

determine a set of candidate beams for communication with the UE based on the N BSI reports.

26. The apparatus of claim 25, wherein the at least one processor is further configured to:

switch from a beam used for communication with the UE to one of the at least one beam based on the N BSI reports.

27. The apparatus of claim 26, wherein the one of the at least one beam is associated with a highest received power indicated in the N BSI reports.

28. The apparatus of claim 21, wherein the number N of BSI reports is indicated based on a type of the message.

29. The apparatus of claim 28, wherein the type of the message comprises at least one of a downlink control information (DCI) message or a random access response (RAR) message.

75

30. The apparatus of claim 29, wherein the message indicates that the number N of BSI reports is greater than one based on the type of the message comprising the RAR message.

31. A non-transitory computer-readable medium storing 5
computer-executable code for wireless communication by a base station, the code when executed by at least one processor cause the at least one processor to:

determine a number N greater than zero of beam state information (BSI) reports; 10

send, to a user equipment (UE), a message requesting BSI, wherein the message indicates the number N greater than or equal to zero of BSI reports requested from the UE;

send, to the UE, a set of signals through a set of beams; 15
and

receive, from the UE, N BSI reports based on the indicated number N of BSI reports, each of the N BSI reports indicating at least one beam index corresponding to at least one beam of the set of beams and a 20
received power associated with the at least one beam.

* * * * *

76