



US011109625B1

(12) **United States Patent**  
**Avasarala et al.**

(10) **Patent No.:** **US 11,109,625 B1**  
(45) **Date of Patent:** **Sep. 7, 2021**

(54) **FACE MASK AND SHIELD COMBINATION**

(71) Applicant: **Aver Technologies, Inc.**, Woodbridge, VA (US)

(72) Inventors: **Pallavi Avasarala**, Woodbridge, VA (US); **Pranav Avasarala**, Woodbridge, VA (US)

(73) Assignee: **Aver Technologies, Inc.**, Woodbridge, VA (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **17/245,365**

(22) Filed: **Apr. 30, 2021**

(51) **Int. Cl.**  
*A41D 13/11* (2006.01)  
*A62B 18/02* (2006.01)  
*A62B 18/08* (2006.01)

(52) **U.S. Cl.**  
CPC ..... *A41D 13/1184* (2013.01); *A41D 13/1138* (2013.01); *A62B 18/025* (2013.01); *A62B 18/08* (2013.01)

(58) **Field of Classification Search**  
CPC ..... A41D 13/1138; A41D 13/1184; A62B 18/02; A62B 18/025; A62B 18/10  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

403,966 A \* 5/1889 Smith ..... A62B 18/10  
128/206.15  
1,701,277 A \* 2/1929 Shindel ..... F16K 15/16  
137/855

2,578,621 A \* 12/1951 Yant ..... A62B 18/025  
128/206.24  
D188,021 S \* 5/1960 Fisher ..... D28/9  
3,528,415 A \* 9/1970 Malmin ..... A61F 9/025  
128/201.12  
D335,723 S \* 5/1993 Pawliszyn ..... A41D 13/1161  
D29/110  
5,372,130 A \* 12/1994 Stern ..... A62B 18/006  
128/205.25  
5,689,833 A \* 11/1997 Allen ..... A62B 18/08  
2/427  
6,216,695 B1 \* 4/2001 Ruben ..... A41D 13/11  
128/201.15  
6,460,539 B1 \* 10/2002 Japuntich ..... A41D 13/1138  
128/205.27  
2004/0069302 A1 \* 4/2004 Wilson ..... A41D 13/1184  
128/201.24  
2007/0101990 A1 \* 5/2007 Hacke ..... A61M 16/1065  
128/201.25

(Continued)

**FOREIGN PATENT DOCUMENTS**

GB 2354450 A \* 3/2001 ..... A62B 18/08  
WO WO-2019104584 A1 \* 6/2019 ..... A62B 18/10

**OTHER PUBLICATIONS**


Funbotics, "Funbotic Mask Filter Replacement Instructions", info@funbotics.org, 2 pages.

*Primary Examiner* — Kathryn E Ditmer  
(74) *Attorney, Agent, or Firm* — Bookoff McAndrews, PLLC

(57) **ABSTRACT**

A wearable face covering may include a mask including a filter and a cap, wherein the cap is configured to prevent any gas passing through the filter in a first direction from exiting the mask in the first direction; and a face shield including a partially-transparent screen, wherein the face shield is pivotally coupled to the mask.

**19 Claims, 10 Drawing Sheets**




(56)

**References Cited**


U.S. PATENT DOCUMENTS

2011/0036347 A1\* 2/2011 Morgan, III ..... A62B 18/025  
128/201.19  
2012/0090619 A1\* 4/2012 Levine ..... A61M 16/209  
128/207.15  
2017/0021203 A1\* 1/2017 Baker ..... A62B 18/02  
2018/0185677 A1\* 7/2018 Curran ..... A62B 23/025  
2020/0289859 A1\* 9/2020 Malloy ..... A62B 18/084


\* cited by examiner




**FIG. 1**




**FIG. 2**




**FIG. 2a**



**FIG. 2b**





**FIG. 3**




**FIG. 4A**

**FIG. 4B**




**FIG. 4C**




**FIG. 5**







**FIG. 6A**



**FIG. 6B**



**FIG. 6C**



**FIG. 6D**

**FACE MASK AND SHIELD COMBINATION**

## TECHNICAL FIELD

Aspects of this disclosure relate generally to protection systems, devices, and methods. More specifically, embodiments of the disclosure relate to a protection system (e.g., combined face mask and shield) for directing and/or filtering air and/or particulates being inhaled and/or exhaled by a user. The combined face mask and shield may be useful in the medical field, in the construction field, or in any other suitable field requiring face protection.

## BACKGROUND

Protection devices such as face masks, face shields, and the like are worn by a user in many fields (e.g., medical, construction, etc.) to help protect the user from air particulates, including, for example, dust, bacteria, viruses, allergens, spores, coarse particles, debris, etc. A mask helps to protect a user from air particulates by surrounding a user's mouth and nose and filtering air that is inhaled. For example, the mask may be a cloth or other material that covers the user's mouth and nose. However, during exhalation, the exhaled air remains within the confines of the mask, or a portion of the exhaled air is directed forward of the user. Shields are worn to help protect a portion of a user's face from air particulates. Shields often include a band that wraps around the user's head such that the shield extends in front of the user's face. The shield helps to protect the user's eyes and face from air particulates or debris. Shields also are rigid and/or fixed relative to the user's face, which requires the user to completely remove the shield to access the user's face, for example, to adjust the user's glasses. Additionally, as the user exhales, the shield becomes foggy, which impairing the user's eyesight. Even if the user is wearing a mask, the shield still becomes foggy since the exhaled air exits the front of the mask. Additionally, the shield moves and/or separates from the user's head when attached by a single band around the user's head. Masks also move and/or separate from the user's face, for example, when the user adjusts the attachment strap(s), talks, moves the user's mouth, etc. Furthermore, wearing both a shield and mask concurrently is time-consuming and/or difficult to adjust, manipulate, etc.

The systems, devices, and methods of the current disclosure may address one or more of the deficiencies described above.

## SUMMARY

Examples of the present disclosure relate to, among other things, wearable face coverings (e.g., combined mask and face shield assemblies), devices, and methods to help direct and/or filter air and/or air particulates being inhaled and/or exhaled by a user while also protecting the user's face from debris. In one example, the combined mask and shield may protect the wearer's face from flying objects at construction sites (e.g., chipped concrete) and also protect the user from inhaling dust. In some examples, the face shield or screen may be shatter-proof or otherwise shatter-resistant. Each of the examples disclosed herein may include one or more of the features described in connection with any of the other disclosed examples.

In one example, a wearable face covering, may include a mask, wherein the mask includes: a base with a first central opening, the base including an interior side at least partially

enclosing an interior volume, and an exterior side; an adapter including a flange and a coupling surface, the flange and coupling surface surrounding a second central opening, wherein the flange abuts the interior side of the base, and the coupling surface extends through the first central opening of the base, wherein the coupling surface includes at least one first slot in fluid communication with second central opening, wherein the at least one first slot has a portion that is substantially perpendicular to the second central opening, wherein the coupling surface also includes an interior recessed area; a filter removably disposed in the interior recessed area of the adapter; a face shield including a partially-transparent screen; a coupler including a flange, a venting surface surrounding a third central opening, and at least one second slot on the venting surface, wherein the second flange removably abuts the exterior side of the base, wherein the face shield is connected to the coupler and also configured to pivot relative to the coupler; and a cap removably engageable with the adapter, wherein the cap is configured to prevent any gas passing through the filter in a first direction from exiting the mask in the first direction.

The wearable face covering may direct any gas travelling from the interior volume of the base through the first central opening and through the second central opening before exiting the mask. The wearable face covering may direct any gas travelling from the interior volume of the base through the first central opening and through the third central opening before exiting the mask. The wearable face covering may direct any gas travelling from the interior volume of the base through the first central opening and through at least one first slot and at least one second slot before exiting the mask.

The wearable face covering may include a cap including a center portion that is received by the third central opening of the coupler, wherein the center portion includes one or more openings, wherein any gas travelling from the interior volume of the base through the first central opening, must pass through the one or more openings before exiting the mask.

The wearable face covering may include a face shield configured to pivot relative to the coupler and relative to the mask about a pivot axis disposed below the base of the mask. The face shield may be in a first position, wherein a majority of a longest dimension of the screen is disposed above the mask, wherein in the first position, a line extending through the first central opening and parallel to the first central opening, extends through the screen. The face shield may be in a second position, wherein a majority of the longest dimension of the screen is disposed below the mask, wherein in the second position, the line extending through the first central opening and parallel to the first central opening, does not extend through the screen.

The wearable face covering wherein the cap includes a first protrusion and the adapter includes a first key slot configured to receive the first protrusion, wherein the key slot is substantially parallel to a central longitudinal axis, and wherein, while the first protrusion is disposed within the first key slot, the cap and the adapter are rotationally fixed relative to one another. The first key slot connects to one of the at least one first slot of the adapter, wherein after the first protrusion has traversed the entirety of the first key slot and is disposed with a first slot, the cap and the adapter are configured to rotate relative to one another.

The wearable face covering may include a light source mounted to an exterior of the face shield.

The wearable face covering may include a porous disk disposed between the filter and the adapter, wherein the

3

porous disk is configured to secure the filter into the adapter. The adapter includes two first slots, wherein the two first slots are arranged vertically in the adapter and are parallel to one another.

The wearable face covering may include the coupler including two second slots, wherein the two second slots are arranged vertically in the adapter and are parallel to one another.

An entirety of the wearable face shield may be secured to a user without any direct attachment to a head of the user.

In another example, a wearable face covering may include a mask including, a base with a first central opening, the base including an interior side at least partially enclosing an interior volume, and an exterior side; an adapter including a flange and a coupling surface, the flange and coupling surface surrounding a second central opening, wherein the flange abuts the interior side of the base, and the coupling surface extends through the first central opening of the base, wherein the coupling surface includes at least one first slot in fluid communication with second central opening, wherein the at least one first slot has a portion that is substantially perpendicular to the second central opening, wherein the coupling surface also includes an interior recessed area; a filter removably disposed in the interior recessed area of the adapter; a face shield including a partially-transparent screen; a coupler including a flange, a venting surface surrounding a third central opening, and at least one second slot on the venting surface, wherein the second flange removably abuts the exterior side of the base, wherein the face shield is connected to the coupler and also configured to pivot relative to the coupler and relative to the mask about a pivot axis disposed below the base of the mask; and a cap removably engageable with the adapter, wherein the cap is configured to prevent any gas passing through the filter in a first direction from exiting the mask in the first direction, wherein the cap includes a center portion that is received by the third central opening of the coupler, wherein the center portion includes one or more openings, wherein: any gas travelling from the interior volume of the base through the first central opening, must pass through the second central opening, the third central opening, at least one first slot, at least one second slot, and the one or more openings of the cap, before exiting the mask; and an entirety of the face shield is configured to be secured to a user without any direct attachment to a head of the user. The face shield may be in a first position, wherein a majority of a longest dimension of the screen is disposed above the mask, wherein in the first position, a line extending through the first central opening and parallel to the first central opening, extends through the screen; when the face shield is in a second position, a majority of the longest dimension of the screen is disposed below the mask, wherein in the second position, the line extending through the first central opening and parallel to the first central opening, does not extend through the screen.

The wearable face covering may include a cap including a first protrusion and an adapter including a first key slot configured to receive the first protrusion, wherein the key slot is substantially parallel to a central longitudinal axis, and wherein, while the first protrusion is disposed within the first key slot, the cap and the adapter are rotationally fixed relative to one another; and the first key slot connects to one of the at least one first slot of the adapter, wherein after the first protrusion has traversed the entirety of the first key slot and is disposed with a first slot, the cap and the adapter are configured to rotate relative to one another. The adapter may include two first slots, wherein the two first slots are

4

arranged vertically in the adapter and are parallel to one another; and the coupler may include two second slots, wherein the two second slots are arranged vertically in the adapter and are parallel to one another.

In another example, a wearable face covering may include a mask including a filter and a cap, wherein the cap is configured to prevent any gas passing through the filter in a first direction from exiting the mask in the first direction; and a face shield including a partially-transparent screen, wherein the face shield is pivotally coupled to the mask.

It may be understood that both the foregoing general description and the following detailed description are exemplary and explanatory only and are not restrictive of the disclosure, as claimed.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate exemplary features of the present disclosure and together with the description, serve to explain the principles of the disclosure.

FIG. 1 illustrates an exemplary protection system/wearable face covering including a mask and a shield in an assembled configuration, according to an embodiment of the disclosure.

FIG. 2 illustrates an exploded view of the components of the protection system of FIG. 1.

FIG. 2A shows a side view of an exemplary linking rod. FIG. 2B shows a partial cross-sectional view of the linking rod of FIG. 2A.

FIG. 3 illustrates an exploded view of the mask.

FIG. 4A illustrates a perspective view of portions of the mask assembled.

FIG. 4B illustrates an end view of an inside of a cap.

FIG. 4C illustrates a detailed section view the cap of 4C.

FIG. 5 illustrates a perspective view of the protection system in a partially assembled configuration.

FIG. 6A illustrates a front view of the protection system of FIG. 1 in a first position.

FIG. 6B illustrates a side view of the protection system of FIG. 1 in the first position.

FIG. 6C illustrates a side view of the protection system of FIG. 1 in a plurality of positions.

FIG. 6D illustrates a side view of the protection system of FIG. 1 in a second position.

#### DETAILED DESCRIPTION

Embodiments of the present disclosure may relate to a protection system for directing and/or filtering air and/or particulates being inhaled and/or exhaled by a user. Various embodiments described herein may include a protection system that includes a mask and a shield. For example, the mask may be a face mask, and the shield may be a face shield. More specifically, in exemplary embodiments, the protection system may include a combined mask and shield, and may be configured to direct outward airflow rearward, for example, away from the shield. The airflow may be directed rearward, for example, by one or more vented slots and a cap.

FIGS. 1 and 2 depict a protection system 100 that includes a mask 101 and a shield 102. Protection system 100 may help protect a user's face from outside air particulates (e.g., dust, bacteria, viruses, allergens, spores, coarse particles, etc.) and/or other debris. FIG. 1 illustrates protection system 100 in an assembled configuration. As shown, mask 101 and shield 102 may be coupled together, for example, with a

## 5

mask and shield attachment or a coupler 205. Additionally, coupler 205 may pivotally couple mask 101 and shield 102, for example, allowing for shield 102 to pivot relative to mask 101, as shown in FIG. 6C.

## Mask

Referring to FIG. 2, mask 101 may be an at least partially flexible filtration mask, for example, to form a seal around at least a portion of a user's nose and face. Mask 101 may include a disk or a cap 207 to help direct airflow. In one or more aspects, cap 207 may help to direct air rearwards and/or away from shield 102 when the user exhales. Cap 207 may direct exhaled air rearward and help to prevent exhaled air from passing forward of the user's face. As shown in FIG. 4B, cap 207 may also include one or more openings 403 positioned centrally within the cap 207, for example, to allow airflow in through sides of mask 101 during an inhale of the user.

As discussed in detail below, mask 101 may be formed of a number of components or elements fitted or otherwise coupled together. For example, mask 101 may include a base 203 and cap 207. Furthermore, coupler 205 may help to form mask 101. Base 203 may include an interior at least partially enclosing an interior volume, and an exterior. Base 203 may be configured to fit around a user's mouth and nose. For example, as shown in FIGS. 2 and 3, base 203 may include a partially circular portion 309B, for example, to surround a user's mouth, and an extension portion 309A, for example, to surround a user's nose. In this aspect, partially circular portion 309B and extension portion 309A may surround a user's mouth and nose when the user wears mask 101. Base 203 may be coupled to coupler 205 via one or more of an adhesive, a snap fit, a press fit, etc. Furthermore, base 203 may include a plurality of retention holes 215. Retention holes 215 may allow for one or more retention elements (not shown) to be positioned around the user's head, ears, face, etc. to help couple mask 101 to the user's face. Retention elements, not shown, may include one or more strings, bands (e.g., an elastic band), straps, threaded knobs, etc. Base 203, for example, may include one or more retention holes 215 on each lateral side of base 203. As shown in FIGS. 1-5, base 203 may include two retention holes 215 on each lateral side of base 203. Although only one side of base 203 is shown in these figures, it is noted that the other side of base 203 may also include two retention holes 215. In these aspects, one or more retention elements, not shown, may pass through each of retention holes 215, and be secured to base 203, for example, via one or more knots, one or more clips, one or more adjustable buckles, etc. Retention element(s), not shown, may then be positioned around the user's head, ears, face, etc. to help couple mask 101 to the user's face.

Cap 207 may be coupled to one or more other components of mask 101. As discussed with respect to FIGS. 4A and 4B, cap 207 may be coupled to one or more components of mask 101 via a screw-fit. For example, cap 207 may include one or more keys 402 (FIG. 4B) positioned on an inner portion of cap 207, and the one or more keys 402 may be received within corresponding keyways. Cap 207 may also include a plurality of grips 303 positioned on an outer portion of cap 207. Coupling cap 207 to one or more other components of mask 101 may help retain mask 101 and/or protection system 100 in the assembled configuration.

As shown in FIGS. 2 and 3, mask 101 may further include an adapter 201, a filter 204, a seal 202, and a mask disk 206. Adapter 201 may include a coupling portion 301 that extends from a front of adapter 201. Adapter 201 may be inserted from an interior side of base 203, through a central opening 305 so that coupling portion 301 extends outward of

## 6

base 203. Adapter 201 may include a flange 301a extending circumferentially around adapter 201. Flange 301a may be a portion of adapter 201 that is closest to a face of the user when the mask is worn, and may abut an inner surface of base 203 to help retain adapter 201 to base 203.

Coupling portion 301 may include an exterior with a shape that is different from that of its interior. The exterior may be substantially octagonal, and the interior may be substantially circular. As shown in FIGS. 2 and 3, the exterior may include alternating rounded portions and straight portions. Central opening 305 of base 203 may have a shape corresponding to the shape of the exterior of coupling portion 301.

Coupling portion 301 may include one or more vertical slots 308, for example, to allow air to flow into and out of mask 101. Slots 308 may be positioned on opposing sides of coupling portion 301. For example, slots 308 may extend from opposing vertical portions (e.g., opposing straight portions) of the exterior of coupling portion 301. Slots 308 may be formed by substantially rectangular openings (vents) extending in the vertical direction of side portions of coupling portion 301. Although a rectangular shape is shown, the shape of slots 308 should not be considered limited, and other suitable shapes, such as ovular, circular, square or the like also are contemplated. Slots 308 on sides of adapter 201 may help to direct airflow, for example, as air is drawn into mask 101 during inhalation and/or as air is pushed out of mask 101 during exhalation. For example, slots 308 may allow for mask 101 to draw air in from the sides of adapter 201 and/or direct air out of the sides of adapter 201 (e.g., in the positive and negative directions of the z-direction). In these aspects, the air passing through slot(s) 308 may be directed toward (e.g., when exhaled) and/or have passed through (e.g., when inhaled) filter 204.

Adapter 201 may also contain indented recessed portion 310, for example, in a center of adapter 201, which faces outward and away from the user. Recessed portion 310 may be any shape suitable of containing and/or receiving a portion of a filter 204. For example, if filter 204 is square or rectangular (as shown, then indented portion 310 may also be square or rectangular. Furthermore, adapter 201 includes an adapter opening 311 also at the center of the adapter and extending through recessed portion 310, and also extending in the x-direction. In this aspect, filter 204 may be received in recessed portion 310 so that air flowing through adapter opening 311 must pass through filter 204. Accordingly, during inhalation, air must pass through filter 204 and through adapter opening 311 to the user. Similarly, during exhalation, air must pass through adapter opening 311 and filter from the user.

Although not shown, if filter 204 is substantially circular, then indented portion 310 may also be substantially circular. Filter 204 may be configured to filter air particulates from air passing through filter 204, for example, during inhalation and exhalation. As discussed below, filter 204 may be a replaceable and/or reusable filter. Filter 204 may be replaced, for example, by removing cap 207.

Seal 202 may be coupled to an interior periphery of base 203. Seal 202 and other components of mask 101 may help to ensure that air flowing to and/or from the user's face (e.g., the user's mouth and nose) passes through filter 204.

As mentioned above, coupler 205 is positioned between base 203 and cap 207. Coupler 205 may have a venting portion 302 thereon extending in the x direction. Venting portion 302 may include venting slots 306 on opposing sides of the venting portion 302. When mask 101 is assembled, each slot 306 may align with a slot 308 of adapter 201, so

that inhaled/exhaled air travelling through a given slot **306** must also travel through an immediately adjacent slot **308** and vice versa.

Coupler **205** may be coupled to base **203**, for example, by press fit when cap **207** is coupled to adapter **201**. For example, coupler **205** may include an abutting portion/flange **205a** that abuts an outward face **203a** of base **203**. Coupler **205** may be in contact with coupling portion **301** of adapter **201**, when coupling portion **301** extends through base **203**. For example, coupler **205** may receive a portion of coupling portion **301** of adapter **201**, and a portion of coupling portion **301** may extend distally beyond coupler **205**, for example, farther from the user in the positive x-direction. The exterior of coupling portion **301** may contact an interior face of venting portion **302**. Venting portion **302** may have an inner shape substantially similar to the exterior shape of coupling portion **302**. For example, inner shape of venting portion **302** may correspond to the alternating straight and rounded portions of the exterior of coupling portion **302**. Additionally, as discussed below, coupler **205** may also include a shield mounting portion **213**, for example, extending from a bottom portion of venting portion **302**. Shield mounting portion **213** may be coupled to a linking rod **208**, for example, to pivotably support shield **102**.

As shown in FIGS. **2** and **3**, disk **206** may be configured to fit within coupling portion **301** of adapter **201**. In this aspect, if coupling portion **301** has a substantially circular interior shape, mask disk **206** may also be substantially circular. As shown in FIG. **4A**, disk **206** may be positioned within coupling portion **301**, for example, in a position distal to (i.e., in the positive x-direction relative to) filter **204**. Disk **206** may help to retain filter **204** relative to adapter **201**, for example, such that filter **204** is retained at least partially within recessed portion **310**. Filter **204** may be positioned and configured to prevent rotation of the filter while cap **207** rotates. Disk **206** may include a plurality of through-holes **304**. Through-holes **304** may allow for air to flow through disk **206**, and thus through filter **204**, during inhalation and exhalation.

Securing cap **207** to adapter **201** may help retain filter **204** and disk **206** within the mask assembly. As mentioned above and as shown in FIGS. **4B** and **4C**, cap **207** may include one or more keys **402**. One or more keys **402** may extend from an outer ring **404** of a central portion of cap **207**. The central portion may include an inner ring **405** with a central hub **405a**. Central hub **405a** may include one or more channels **403**. The channels **403** are in fluid communication with a plurality of conduits **406** that extend radially outward from the central hub. The conduits **406** terminate at an outer circumference of inner ring **405**. In the assembled configuration inner ring **405** is received within the interior of adapter **201**. Therefore, exhaled air from the user travels through the one or more openings **403**, then through the one or more conduits **406**, and then through slots **308** and **306**, into the atmosphere.

Furthermore, the interior of coupling portion **301** may include one or more key slots **401**, which extend in the x direction and which are coupled to slots **308**. Key slots **401** (and slots **308**) may receive a portion of cap **207** to help secure the mask assembly together. Key slots **401** may each include a longitudinal portion extending in the x direction that connect to slots **308**. Key slots **401** may be positioned approximately 180 degrees apart from one another in the interior of coupling portion **301**. In order to couple cap **207** to coupling portion **301** of adapter **201**, keys **402** of cap **207** may be aligned with key slots **401**. Cap **207** may be

advanced longitudinally, for example, in the negative x-direction, which may also advance keys **402** longitudinally within key slots **401**. Cap **207** may then be rotated after keys **402** are prevented from further longitudinal movement, for example, clockwise, which may rotate keys **402** into slots **308**. After this rotation, cap **207** may be secured to adapter **201**, further securing base **203**, coupler **205**, filter **204**, and disk **206** in between cap **207** and adapter **201**.

Thus, coupling cap **207** to adapter **201** may help to couple the other components of mask **101**. For example, as shown in FIG. **5**, coupling cap **207** to adapter **201** may help to form a clamped assembly. Furthermore, when cap **207** is coupled to coupling portion **302** of adapter **201**, cap **207** directs exhaled air back toward the user's ears, instead of in the forward direction. In some embodiments, cap **207** is configured to substantially or entirely prevent the flow of exhaled air from travelling in the forward direction (away from the user). Cap **207** may achieve this result by virtue of a closed front end (without any holes, openings, or gaps, extending through its front surface. Furthermore, cap **207** may include a conical skirt **207a** that further diverts air exhaled through slots **306** and **308** rearward toward the user's ears and face. In some embodiments, air exiting mask **101** does not include any component travelling in the forward/positive X direction.

Moreover, cap **207** may be removable, for example, to access filter **204**. With cap **207** separated from adapter **201**, the user may access disk **206** and/or filter **204**, for example, to adjust, inspect, clean, replace, etc. either disk **206** and/or filter **204**.

As mentioned above, FIG. **4A** depicts mask **101** in a partially assembled configuration. As shown, when adapter **201** and coupler **205** are coupled, slots **308** of adapter **201** and venting slots **306** of coupler **205** are at least partially aligned. Although only one side of assembled mask **101** is shown in figures, it is noted that both sides of adapter **201** and coupler **205** may have slots **308** and venting slots **306** aligned. For example, aligning the slots **308** with venting slots **306** may allow air to flow from exterior of mask **101** to an interior of mask **101** and to filter **204**, for example, as the user inhales. For example, aligning the slots **308** with venting slots **306** may allow air to flow from inside mask **101** to filter **204** and out of mask **101** via the aligned slots **308** and venting slots **306**, for example, as the user exhales.

Shield

Referring back to FIGS. **1** and **2**, shield **102** may surround at least a portion of mask **101**. For example, shield **102** may include a front portion and one or more curved portions, to at least partially surround the front and/or sides of the user's face. Shield **102** may also include an extension **212**, for example, extending from a top edge of shield **102**. One or more lights **103** may be coupled to shield **102** and/or extension **212**, and light **103** may be connected to one or more wires **104**. While extension **212** is shown having a flat line surface disposed close to a user, one of skill in the art will appreciate that this surface could be curved to accommodate the contours of the user's forehead. In some embodiments, the shield **102** may be secured and worn by the user without any direct attachment or coupling of the shield to a forehead or head of the user. Instead, the shield may be directly coupled to coupler **105**/mask **101**.

As shown in FIG. **2**, shield **102** may include a screen **217**, e.g., a partially flexible and rigid plexiglass screen. When protection system **100** is worn by the user, screen **217** may at least partially surround the user's face, for example, by at least one flat front portion, and at least one curved side portions. Screen **217** may help to inhibit, minimize, or



prevent air particulates or other debris from contacting a user's face. Screen 217 may also help to inhibit, minimize, or prevent air particulates exhaled by the user from entering the user's surroundings, for example, by helping to prevent exhaled air from passing forward of the user's face. As mentioned, shield 102 may further include extension 212, for example to surround a portion of the top of the user's head and/or help to prevent air particulates from reaching the user's face from above.

Referring to FIGS. 2 and 5, shield 102 may include a support system 500. Support system 500 may help to couple screen 217 to other components in protective system 100. For example, support system 500 may include left and right holders 211A and 211B and bottom holders 209A and 209B. Additionally, support system 500 may include a plurality of clips 210, and each clip may include a shield receiving portion 210C, a supporting portion 210b, and a holder receiving portion 210a. Screen 217 may be coupled to left holder 211A and right holder 211B, for example, via one or more of an adhesive, screws, bolts, etc. Holders 211A and 211B may be coupled to a bottom edge of extension 212, and may help retain screen 217 relative to other components in protective system 100. The bottom of screen 217 may be secured between holders 209A/209B and clips 210.

In some aspects, and as shown in FIG. 1, light 103 may be coupled to shield 102, for example, to a top portion of screen 217 and/or to a portion of extension 212. For example, as shown in FIG. 2, extension 212 may include a mount 218, which may support light 103. Light 103 may be electrically connected to one or more power supplies and/or controls, for example, via one or more wires 104. Wire 104 may extend along outer portions of shield 102, for example, along outer portions of screen 217 and/or extension 212. Additionally, wire 104 may be retained along the outer portions of shield 102 by one or more clips or retention mechanisms 501. Retention mechanisms 501 may include two stepped portions with an opening between, for example, to receive a portion of wire 104. As shown in FIG. 5, retention mechanisms 501 may include one or more clips, brackets, etc. Alternatively, light 103 may be battery powered, and may not include one or more wires 104. The positioning of light 103 on extension 212 may help prevent a glare from forming on screen 217, since the light emitted from light 103 does not pass through screen 217. In other examples and applications, such as in a dentist office, there are focus headlights directed to the patient. This external light could fall on the inner face of the screen if an opaque or partially-opaque barrier is not present (such as extension 212). Thus, in some embodiments, extension 212 may prevent the external light to fall on the inner face of the screen, thus preventing glare from external sources. In examples of this application, shield 102 is mounted to mask 101 in such a way that the distance between the screen and the forehead allows for wearing normal eye glasses or surgical eye glasses with magnifying lenses. The light source 103 may be mounted exterior/outside the screen to help avoid the formation of glares. Even though some existing face shields/screens may provide enough room for these type of surgical glasses, a glare may form during normal use.

Bottom holders 209A and 209B may help to support screen 217 and couple shield 102 to coupler 205. Bottom holders 209A and 209B may be pivotally coupled to coupler 205 by a linking rod 208 and connection pins 214A and 214B, for example, to allow shield 102 to pivot around the z-axis of linking rod 208. Clips 210 may each include a receiving portion 210a that may be positioned over a portion

of bottom holders 209A and 209B. Clips 210 may each include a supporting portion 210B, for example, extending in the positive y-direction from receiving portion 210a, and configured to support screen 217 at a second end of screen 217.

#### Combined Mask/Shield

As shown in FIGS. 2 and 3, coupler 205 may include shield mounting portion 213. Shield mounting portion 213 may include one or more coupler arms, for example, two coupler arms 213a and 213b. Coupler arms 213a and 213b may be coupled to one or more connection pins 214a and 214b of bottom holders 209a and 209b and linking rod 208. Linking rod 208 may be positioned between openings 407 of coupler arms 213a and 213b of coupler 205 to help retain the components of wearable face covering 100. Linking rod 208 may have a D-shaped opening 208a. Connection pins 214a and 214b may also be D-shaped to fit within D-shaped opening 208a. In other words, openings 208a and connection pins 214a and 214b may have complementary shapes that prevent the relative rotation of bottom holders 209a and 209b and face shield 102. Other suitable shapes include square, rectangular, star, irregular, or the like. The friction fit between pins 214a/b and opening 208 may secure the bottom holders to the linking rod. Furthermore, connection pins 214a and 214b may be extended through D-shaped opening 208a of linking rod 208. Although only opening 407 of coupler arm 213a is shown in these figures, it is noted that coupler arm 213b may also include opening 407. Coupler arms 213a and 213b may include respective tracks 219a and 219b that each include an inward taper at each end of the track, for example, a taper of between 1 and 5 degrees, for example, approximately 3 degrees. Further, linking rod 208 may have linking pins 220a and 220b extending outwardly from linking rod 208, and the linking pins 220a and 220b are configured to travel through the tracks 219a and 219b, respectively. Inward tapers of tracks 219a and 219b may help to catch or otherwise secure linking pins 220a and 220b by friction/wedging when shield 102 is in its extreme open/closed positions. Additionally or alternatively, a latch mechanism may be used to keep shield 102 in the open and/or closed positions. Shield mounting portion 213 may help to prevent, reduce, and/or minimize unintended movement and/or rotation of shield 102.

FIG. 5 illustrates protection system 100 in a partially assembled configuration, for example, without screen 217 coupled to bottom holders 209A and 209B and left and right holders 211A and 211B and assembled support system 500. As mentioned above, one or more of left holder 211A and right holder 211B may each include a plurality of retention elements 501. Each retention element 501 may include a channel, for example, to receive wire 104 from light 103 (FIG. 1). For example, one of left holder 211A or right holder 211B may include retention elements 501, for example, for wire 104 to be coupled to left holder 211A. Alternatively, both of left holder 211A and right holder 211B may include retention elements 501, for example, for multiple wires 104 to be coupled to holders 211A and 211B, and to light 103 or for the user to have the option of coupling wire 104 to either left holder 211A or right holder 211B. Additionally, holders 211A and 211B, may each include a plurality of holes 502 to, for example, help retain screen 217, for example, with one or more of an adhesive, a bonding, a weld, one or more screws, bolts, etc. Although FIG. 5 illustrates holes 502 only in right holder 211B, it is noted that left holder 211A may also include one or more holes 502 to, for example, help retain screen 217.

## 11

As mentioned above, shield **102** may be pivotable relative to mask **101** and coupler **205**. In one example, pivoting shield **102** around the z-axis of linking rod **208** may allow a user to adjust the shield to personal comfort or to the specifics of the task being performed. In other examples, pivoting the shield may allow access to the user's face, for example, to adjust, clean, or otherwise reach their glasses, clean one or more portions of mask **101** or shield **102**, etc. Further, bottom holders **209a/209b** may include reinforcement pins **216a/216b**, shown in FIG. 2, for example, to help minimize bending forces on the bottom holder **209A** and **209B** about the z axis during the pivoting of the shield **102**. The reinforcing pins help achieve the strengthening effect while still helping to achieve a relatively low weight of the combined shield/mask.

FIGS. 6A-6D illustrate the pivoting movement of shield **102**. FIG. 6A is a front view of protective system **100** in a first configuration with shield **102** in a first position relative to mask **101**, and FIG. 6B is a side view of protective system **100** in the first configuration. FIG. 6C is a side view of shield **102** pivoting between a plurality of positions relative to mask **101**. FIG. 6D is a side view of shield **102** in a second position relative to mask **101**.

As shown in FIGS. 6A and 6B, the first position of protective system **100** is defined as shield **102** positioned adjacent to or forward of mask **101**. Shield **102** may partially surround cap **207**, base **203**, and coupler **205**. As shown in FIGS. 6C and 6D, the second position of protective system **100** is defined as shield **102** position approximately 180 degrees from the first position, thus no longer positioned adjacent to or forward of mask **101**. For example, shield **102** may pivot around the z-axis of linking rod **208**, as shown in FIG. 6C and as discussed above. Additionally, it is contemplated that system **100** may be configured to allow shield **102** to rotate upward relative to the mask using one or more additional linking bars. For example, in welding applications, a welding face shield may rotate over the head with a pivot at the forehead around a circular strap.

Furthermore, shield mounting portion **213** may help to secure linking pins **220a** and **220b** of linking rod **208** within tracks **219a** and **219b** to help limit and/or control movement and/or rotation of shield **102**. The user may secure the shield **102** in any of the positions shown in FIG. 6C. Additionally, the user may secure the shield **102** in a user selected position not shown. Forces, not shown, such as gravity may act on shield **102** and the shield mounting portion **213**, for example, to further secure/maintain the selected position. As stated before, alternatively, the user may release to allow for movement of shield **102**.

As discussed above, with shield **102** in the second position shown in FIG. 6D, the user's face may be exposed. In this aspect, the user may adjust, clean, or otherwise access the user's glasses, face, etc. Additionally, with shield **102** in the second position, cap **207** may be exposed.

As mentioned earlier, base **203** may include a flexible or rigid material capable of forming around the nose and face of a user. Screen **217** may include a plexiglass, a polyester (e.g., polyester terephthalate glycol (PETG)), a polycarbonate, a vinyl, etc. Filter **204** may be a 0.3 $\mu$  polypropylene based non-woven fabric (although other suitable pore sizes also are contemplated). Alternatively or additionally, filter **204** may include a polypropylene water repellent non-woven fabric. The seal **202** may include a more flexible material than the base **203**. Seal **202** may include a rubber gasket, a flexible plastic, silicone, or other suitable material. Disk **206** may include a flexible plastic, a woven fabric, a rubber gasket, plexiglass, a polyester (e.g., polyester terephthalate

## 12

glycol (PETG)), a polycarbonate, or a vinyl. Bottom holders **209A** and **209B** and/or clips **210** may include a plastic, plexiglass, a polyester (e.g., polyester terephthalate glycol (PETG)), a polycarbonate, a vinyl, etc.

Furthermore, one or more of base **203**, adapter **201**, coupler **205**, disk **206**, cap **207**, bottom holders **209A** and **209B**, clips **210**, linking rod **208**, extension **212**, left holder **211A**, and right holder **211B** may be formed via additive manufacturing or three-dimensional printing, or by other manufacturing techniques (e.g. molding, casting, extrusion, machining, or forming).

Aspects discussed herein of the disclosed protection system may help to enable a user to combine the benefits of a protective shield and a protective mask. Shield **102** may help to block, prevent, or minimize outside particulates from reaching a user's face. The user may secure shield **102** in one or more positions via locking mechanism **213**. The user may be able to quickly raise and lower shield **102**, for example, to access the user's face or mask **101**, without removing shield **102**. Further, shield **102** may support light **103** to illuminate a user's surroundings. Mask **101** may direct airflow during inhalation and exhalation. The airflow into mask **101** during an inhale may be filtered (e.g., by filter **204**) to minimize the particulates that reach the user's mouth and nose during an inhale. The airflow out of mask **101** during an exhale may also be filtered to minimize the particulates that reach the user's surroundings. Mask **101** may direct airflow during exhalation rearwards, for example, away from shield **102**, which may help to prevent shield **102** from fogging. Airflow may be directed rearward by the conical skirt of cap **207** directing flow towards the aligned slots **308** and venting slots **306**. Furthermore, cap **207** may be separated from adapter **201**, for example, to access mask disk **206** and/or filter **204**, for example, to adjust, inspect, clean, replace, etc. either mask disk **206** and/or filter **204**.

Mask **101**, shield **102**, and coupler **205** may be manufactured separately and may be assembled before or during use. For example, the user may couple mask **101**, shield **102**, and coupler **205** before use. Alternatively, the user may couple mask **101** and coupler **205** before use. Then, as the user is wearing mask **101** and coupler **205**, the user may couple shield **102**, for example, by placing shield **102** within shield receiving portion of the plurality of clips **210C**, with clips **210** coupled to bottom holders **209A** and **209B**. Shield **102** may be replaceable. For example, the user may remove the shield **102** from shield receiving portion **210C** of plurality of clips **210** by first removing extension **212** and lifting shield **102** away from shield receiving portions **210C**. For example, the user may recouple a new shield using the steps listed earlier. Similarly, the shapes of mask **101** and shield **102** may vary from those shown in FIGS. 1-6D without departing from the scope of this disclosure, including for example, a substantially ovular mask instead of the shown mask or a different shaped shield. The disclosed protection system **100** may enable quick positioning of shield **102**, and filtration of air by mask **101** during an inhale and exhale of user. The user may wear mask **101** without shield **102** if the user so chooses.

While principles of the present disclosure are described herein with reference to illustrative examples for particular applications, it should be understood that the disclosure is not limited thereto. Those having ordinary skill in the art and access to the teachings provided herein will recognize additional modifications, applications, embodiments, and substitution of equivalents all fall within the scope of the

## 13

features described herein. Accordingly, the claimed features are not to be considered as limited by the foregoing description.

We claim:

1. A wearable face covering, comprising:  
a mask, wherein the mask includes:
  - a base with a first central opening, the base including an interior side at least partially enclosing an interior volume, and an exterior side;
  - an adapter including a flange and a coupling surface, the flange and the coupling surface surrounding a second central opening, wherein the flange abuts the interior side of the base, and the coupling surface extends through the first central opening of the base, wherein the coupling surface includes at least one first slot in fluid communication with the second central opening, wherein the at least one first slot has a portion that is substantially perpendicular to a central longitudinal axis of the second central opening, wherein the coupling surface also includes an interior recessed area; and
  - a filter removably disposed in the interior recessed area of the adapter;
  - a face shield including a partially-transparent screen;
  - a coupler including a flange, a venting surface surrounding a third central opening, and at least one second slot on the venting surface, wherein the second flange removably abuts the exterior side of the base, wherein the face shield is connected to the coupler and also configured to pivot relative to the coupler; and
  - a cap removably engageable with the adapter, wherein the cap is configured to prevent any gas passing through the filter in a first direction from exiting the mask in the first direction.
2. The wearable face covering of claim 1, wherein any gas travelling from the interior volume of the base through the first central opening, must pass through the second central opening before exiting the mask.
3. The wearable face covering of claim 1, wherein any gas travelling from the interior volume of the base through the first central opening, must pass through the third central opening before exiting the mask.
4. The wearable face covering of claim 1, wherein any gas travelling from the interior volume of the base through the first central opening, must pass through at least one first slot and at least one second slot before exiting the mask.
5. The wearable face covering of claim 1, wherein the cap includes a center portion that is received by the third central opening of the coupler, wherein the center portion includes one or more openings, wherein any gas travelling from the interior volume of the base through the first central opening, must pass through the one or more openings before exiting the mask.
6. The wearable face covering of claim 1, wherein the face shield is configured to pivot relative to the coupler and relative to the mask about a pivot axis disposed below the base of the mask.
7. The wearable face covering of claim 6, wherein, when the face shield is in a first position, a majority of a longest dimension of the screen is disposed above the mask, wherein in the first position, a line extending through the first central opening and perpendicular to the first central opening, extends through the screen.
8. The wearable face covering of claim 7, wherein, when the face shield is in a second position, a majority of the longest dimension of the screen is disposed below the mask, wherein in the second position, the line extending through

## 14

the first central opening and perpendicular to the first central opening, does not extend through the screen.

9. The wearable face covering of claim 1, wherein the cap includes a first protrusion and the adapter includes a first key slot configured to receive the first protrusion, wherein the first key slot is substantially parallel to the central longitudinal axis of the second central opening, and wherein, while the first protrusion is disposed within the first key slot, the cap and the adapter are rotationally fixed relative to one another.

10. The wearable face covering of claim 9, wherein the first key slot connects to one of the at least one first slot of the adapter, wherein after the first protrusion has traversed an entirety of the first key slot and is disposed with a first slot, the cap and the adapter are configured to rotate relative to one another.

11. The wearable face covering of claim 1, further including a light source mounted to an exterior of the face shield.

12. The wearable face covering of claim 1, further including a porous disk disposed between the filter and the adapter, wherein the porous disk is configured to secure the filter into the adapter.

13. The wearable face covering of claim 1, wherein the adapter includes two first slots, wherein the two first slots are arranged vertically in the adapter and are parallel to one another.

14. The wearable face covering of claim 13, wherein the coupler includes two second slots, wherein the two second slots are arranged vertically in the coupler and are parallel to one another.

15. The wearable face covering of claim 1, wherein an entirety of the face shield is configured to be secured to a user without any direct attachment to a head of the user.

16. A wearable face covering, comprising:

a mask, wherein the mask includes:

a base with a first central opening, the base including an interior side at least partially enclosing an interior volume, and an exterior side;

an adapter including a flange and a coupling surface, the flange and the coupling surface surrounding a second central opening, wherein the flange abuts the interior side of the base, and the coupling surface extends through the first central opening of the base, wherein the coupling surface includes at least one first slot in fluid communication with the second central opening, wherein the at least one first slot has a portion that is substantially perpendicular to a central longitudinal axis of the second central opening, wherein the coupling surface also includes an interior recessed area;

a filter removably disposed in the interior recessed area of the adapter;

a face shield including a partially-transparent screen;

a coupler including a flange, a venting surface surrounding a third central opening, and at least one second slot on the venting surface, wherein the second flange removably abuts the exterior side of the base, wherein the face shield is connected to the coupler and also configured to pivot relative to the coupler and relative to the mask about a pivot axis disposed below the base of the mask; and

a cap removably engageable with the adapter, wherein the cap is configured to prevent any gas passing through the filter in a first direction from exiting the mask in the first direction, wherein the cap includes a center portion

**15**

that is received by the third central opening of the coupler, wherein the center portion includes one or more openings, wherein:  
 any gas travelling from the interior volume of the base through the first central opening, must pass through the second central opening, the third central opening, at least one first slot, at least one second slot, and the one or more openings of the cap, before exiting the mask; and  
 an entirety of the face shield is configured to be secured to a user without any direct attachment to a head of the user.

**17.** The wearable face covering of claim **16**, wherein:  
 when the face shield is in a first position, a majority of a longest dimension of the screen is disposed above the mask, wherein in the first position, a line extending through the first central opening and perpendicular to the first central opening, extends through the screen;  
 when the face shield is in a second position, a majority of the longest dimension of the screen is disposed below the mask, wherein in the second position, the line extending through the first central opening and perpendicular to the first central opening, does not extend through the screen.

**16**

**18.** The wearable face covering of claim **17**, wherein:  
 the cap includes a first protrusion and the adapter includes a first key slot configured to receive the first protrusion, wherein the first key slot is substantially parallel to the central longitudinal axis of the second central opening, and wherein, while the first protrusion is disposed within the first key slot, the cap and the adapter are rotationally fixed relative to one another; and  
 the first key slot connects to one of the at least one first slot of the adapter, wherein after the first protrusion has traversed an entirety of the first key slot and is disposed with a first slot, the cap and the adapter are configured to rotate relative to one another.

**19.** The wearable face covering of claim **18**, wherein:  
 the adapter includes two first slots, wherein the two first slots are arranged vertically in the adapter and are parallel to one another; and  
 the coupler includes two second slots, wherein the two second slots are arranged vertically in the coupler and are parallel to one another.

\* \* \* \* \*