



US011117280B2

(12) **United States Patent**
Zucker

(10) **Patent No.:** **US 11,117,280 B2**
(45) **Date of Patent:** **Sep. 14, 2021**

(54) **RAZOR CARTRIDGE**

(71) Applicant: **Personal Care Marketing And Research, Inc.**, Beverly Hills, CA (US)

(72) Inventor: **Shlomo Zucker**, Beverly Hills, CA (US)

(73) Assignee: **Personal Care Marketing & Research, Inc.**, Marina Del Rey, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/134,566**

(22) Filed: **Sep. 18, 2018**

(65) **Prior Publication Data**
US 2019/0016001 A1 Jan. 17, 2019

Related U.S. Application Data
(63) Continuation of application No. PCT/US2017/023078, filed on Mar. 17, 2017.
(60) Provisional application No. 62/310,099, filed on Mar. 18, 2016.

(51) **Int. Cl.**
B26B 21/22 (2006.01)
B26B 21/56 (2006.01)
B26B 21/40 (2006.01)
B26B 21/54 (2006.01)
B26B 21/44 (2006.01)

(52) **U.S. Cl.**
CPC **B26B 21/565** (2013.01); **B26B 21/22** (2013.01); **B26B 21/4012** (2013.01); **B26B 21/4018** (2013.01); **B26B 21/4031** (2013.01); **B26B 21/54** (2013.01); **B26B 21/56** (2013.01); **B26B 21/4037** (2013.01); **B26B 21/443** (2013.01)

(58) **Field of Classification Search**
CPC ... B26B 21/565; B26B 21/22; B26B 21/4012; B26B 21/4018; B26B 21/4031; B26B 21/54; B26B 21/4037; B26B 21/443
USPC 30/47-51, 54, 77-83, 74.1
See application file for complete search history.


(56) **References Cited**
U.S. PATENT DOCUMENTS
2,138,353 A 11/1938 Rodrigues
3,660,893 A * 5/1972 Welsh B26B 21/165 30/50
3,934,339 A 1/1976 Dawidowicz et al.
3,938,247 A 2/1976 Carbonell et al.
3,964,159 A 6/1976 Ferraro
(Continued)

FOREIGN PATENT DOCUMENTS
CN 1404433 A 3/2003
CN 1917988 A 2/2007
(Continued)

Primary Examiner — Kenneth E Peterson
Assistant Examiner — Liang Dong
(74) *Attorney, Agent, or Firm* — DLA Piper LLP (US)

(57) **ABSTRACT**
Disclosed here are shaving razor systems and methods including razor cartridges with a unitary frame having a length and width, a topside and an underside, wherein the unitary frame includes angled joints or bends connecting at least three guards running lengthwise on the unitary frame, the guards separated by at least three gaps in the frame, and at least three blades, affixed to the underside of the guards of the unitary frame, wherein the at least three blades include edges, and wherein the blade edges extend into the gaps in the frame when affixed to the underside of the guards of the unitary frame.

17 Claims, 16 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

4,016,648 A	4/1977	Chen et al.	5,016,352 A	5/1991	Metcalf
4,026,016 A	5/1977	Nissen	5,038,472 A	8/1991	Iderosa
4,057,896 A	11/1977	Trotta	5,044,077 A	9/1991	Ferraro et al.
4,063,354 A	12/1977	Oldroyd et al.	5,056,222 A	10/1991	Miller et al.
4,063,357 A	12/1977	Francis	5,067,238 A	11/1991	Miller et al.
4,083,104 A	4/1978	Nissen et al.	5,092,042 A	3/1992	Miller et al.
4,084,316 A	4/1978	Francis	5,107,590 A	4/1992	Burout et al.
4,094,063 A	6/1978	Trotta	5,134,775 A	8/1992	Althaus et al.
4,146,958 A	4/1979	Chen et al.	5,141,694 A	8/1992	Butlin et al.
4,168,571 A	9/1979	Francis	5,157,834 A	10/1992	Chen et al.
4,180,907 A	1/1980	Iten	5,182,858 A	2/1993	Chen
4,198,746 A	4/1980	Trotta	5,191,712 A	3/1993	Crook et al.
4,200,976 A	5/1980	Gooding	5,224,267 A	7/1993	Simms et al.
4,247,982 A	2/1981	Booth et al.	5,236,439 A	8/1993	Kozikowski
4,253,235 A	3/1981	Jacobson	5,249,361 A	10/1993	Apprille, Jr. et al.
4,253,236 A	3/1981	Jacobson	D346,042 S	4/1994	Chu
4,253,237 A	3/1981	Jacobson	5,313,705 A	5/1994	Rivers et al.
4,257,160 A	3/1981	Murai	5,313,706 A	5/1994	Motta et al.
4,258,471 A	3/1981	Jacobson	5,318,429 A	6/1994	Butlin et al.
4,265,015 A	5/1981	Asano	5,331,740 A	7/1994	Carson et al.
4,266,340 A	5/1981	Bowman	5,333,383 A	8/1994	Ferraro
4,270,268 A	6/1981	Jacobson	5,359,774 A	11/1994	Althaus
4,272,885 A	6/1981	Ferraro	5,365,665 A	11/1994	Coffin
4,275,498 A	6/1981	Ciaffone	5,373,638 A	12/1994	Coffin
4,281,454 A	8/1981	Trotta	5,377,409 A	1/1995	Chen
4,281,456 A	8/1981	Douglass et al.	5,410,812 A	5/1995	Althaus
4,282,650 A	8/1981	Trotta	5,416,974 A	5/1995	Wain
4,282,651 A	8/1981	Trotta	5,426,851 A	6/1995	Gilder et al.
4,283,850 A	8/1981	Douglass et al.	5,430,939 A	7/1995	Johnston
4,288,920 A	9/1981	Douglass et al.	5,456,009 A	10/1995	Wexler
4,300,285 A	11/1981	Endo	5,526,567 A	6/1996	Carson et al.
4,302,876 A	12/1981	Emmett	5,533,263 A	7/1996	Gilder
4,308,663 A	1/1982	Ciaffone	5,546,660 A	8/1996	Burout et al.
4,309,821 A	1/1982	Terry et al.	5,551,153 A	9/1996	Simms
4,324,041 A	4/1982	Trotta	5,557,851 A	9/1996	Ortiz
4,335,508 A	6/1982	Francis et al.	5,630,275 A	5/1997	Wexler
4,337,575 A	7/1982	Trotta	5,661,907 A	9/1997	Apprille, Jr.
4,345,374 A	8/1982	Jacobson	5,669,139 A	9/1997	Oldroyd et al.
4,354,312 A	10/1982	Trotta	5,711,076 A	1/1998	Yin et al.
4,378,633 A	4/1983	Jacobson	5,761,814 A	6/1998	Anderson et al.
4,378,634 A	4/1983	Jacobson	5,784,790 A	7/1998	Carson et al.
4,389,773 A	6/1983	Nissen et al.	5,787,586 A	8/1998	Apprille et al.
4,392,303 A	7/1983	Ciaffone	5,794,343 A	8/1998	Lee et al.
4,395,822 A	8/1983	Ciaffone	5,794,354 A	8/1998	Gilder
4,403,412 A	9/1983	Trotta	5,802,721 A	9/1998	Wain et al.
4,403,413 A	9/1983	Trotta	5,813,119 A	9/1998	Ferraro et al.
4,403,414 A	9/1983	Kiraly et al.	5,813,293 A	9/1998	Apprille et al.
4,407,067 A	10/1983	Trotta	5,822,869 A	10/1998	Metcalf et al.
4,411,065 A	10/1983	Trotta	5,823,082 A	10/1998	Wilson et al.
4,413,411 A	11/1983	Trotta	D402,084 S	12/1998	Chen et al.
4,422,237 A	12/1983	Trotta	5,855,071 A	1/1999	Apprille et al.
4,428,116 A	1/1984	Chen et al.	5,903,979 A	5/1999	Oldroyd
4,442,598 A	4/1984	Jacobson	5,915,791 A	6/1999	Yin et al.
4,443,940 A	4/1984	Francis et al.	5,918,369 A	7/1999	Apprille et al.
4,446,619 A	5/1984	Jacobson	5,953,819 A	9/1999	Simms et al.
4,486,952 A	12/1984	Trotta	5,953,824 A	9/1999	Ferraro et al.
4,488,357 A	12/1984	Jacobson	5,953,825 A	9/1999	Christman et al.
4,492,024 A	1/1985	Jacobson	5,956,851 A	9/1999	Apprille et al.
4,492,025 A	1/1985	Jacobson	D415,315 S	10/1999	Swanson et al.
4,498,235 A	2/1985	Jacobson	6,009,624 A	1/2000	Apprille et al.
4,514,904 A	5/1985	Bond	6,026,577 A	2/2000	Ferraro
4,551,916 A	11/1985	Jacobson	6,029,354 A	2/2000	Apprille et al.
4,573,266 A	3/1986	Jacobson	6,035,537 A	3/2000	Apprille et al.
4,574,476 A	3/1986	Ortiz	D422,751 S	4/2000	Gray
4,586,255 A	5/1986	Jacobson	6,044,542 A	4/2000	Apprille et al.
4,587,729 A	5/1986	Jacobson	D424,744 S	5/2000	Coffin et al.
4,599,793 A	7/1986	Iten	6,112,412 A	9/2000	Richard
4,621,424 A	11/1986	Jacobson	6,115,924 A	9/2000	Oldroyd
4,739,553 A	4/1988	Lazarchik	6,122,826 A	9/2000	Coffin et al.
4,785,534 A	11/1988	Lazarchik	6,138,361 A	10/2000	Richard et al.
4,797,998 A	1/1989	Motta	6,165,456 A	12/2000	Barnet et al.
4,868,983 A	9/1989	Francis	6,173,498 B1	1/2001	Warrick et al.
4,901,437 A	2/1990	Iten	6,182,365 B1	2/2001	Tseng et al.
4,932,122 A	6/1990	Shurland et al.	6,182,366 B1	2/2001	Richard
4,932,123 A	6/1990	Francis	6,212,777 B1	4/2001	Gilder et al.
			6,216,349 B1	4/2001	Gilder et al.
			6,216,561 B1	4/2001	Dischler
			6,233,829 B1	5/2001	Oglesby et al.
			6,266,884 B1	7/2001	Prochaska

(56)

References Cited

U.S. PATENT DOCUMENTS

6,276,062	B1	8/2001	Prochaska	D601,753	S	10/2009	Cataudella et al.
6,295,734	B1	10/2001	Gilder et al.	7,607,230	B2	10/2009	Aviza et al.
6,298,557	B1	10/2001	Gilder	D604,904	S	11/2009	Watson
6,305,084	B1 *	10/2001	Zucker	7,617,607	B2	11/2009	Pennell et al.
				7,621,203	B2	11/2009	Aviza
				7,669,335	B2	3/2010	Walker et al.
				7,676,929	B2	3/2010	Lembke et al.
				7,681,314	B2	3/2010	Follo
				7,685,720	B2	3/2010	Efthimiadis et al.
				7,690,122	B2	4/2010	Worrick et al.
6,311,400	B1	11/2001	Hawes et al.	D617,946	S	6/2010	Lukan et al.
6,317,990	B1	11/2001	Ferraro	D617,947	S	6/2010	Lukan et al.
6,381,857	B1	5/2002	Oldroyd	D617,948	S	6/2010	Lukan et al.
6,393,706	B1	5/2002	Ferraro	D617,949	S	6/2010	Lukan et al.
6,430,818	B1	8/2002	Wonderley	7,739,797	B2	6/2010	Rawle
6,434,839	B1	8/2002	Lee et al.	7,765,700	B2	8/2010	Aviza et al.
6,502,318	B1	1/2003	Gilder	7,770,294	B2	8/2010	Bruno et al.
6,516,518	B1	2/2003	Garraway et al.	7,802,368	B2	9/2010	Coffin et al.
6,550,141	B1	4/2003	Rivers et al.	D625,049	S	10/2010	Bridges et al.
6,560,881	B2	5/2003	Coffin	D625,883	S	10/2010	Wonderley
6,584,696	B2	7/2003	Ferraro	7,810,240	B2	10/2010	Lee et al.
6,601,303	B2	8/2003	Gilder et al.	7,811,553	B2	10/2010	O'Grady et al.
6,612,040	B2	9/2003	Gilder	D629,564	S	12/2010	Jung
6,615,498	B1	9/2003	King et al.	D630,378	S	1/2011	Jung
6,651,342	B1	11/2003	Walker, Jr.	D630,797	S	1/2011	Witkus
D484,275	S	12/2003	Prochaska	D631,198	S	1/2011	Adams et al.
6,655,029	B2	12/2003	Saito	D633,253	S	2/2011	Wonderley et al.
6,675,479	B1	1/2004	Walker et al.	D633,254	S	2/2011	Witkus
6,769,180	B2	8/2004	Coffin	7,877,879	B2	2/2011	Nakasuka
6,772,523	B1	8/2004	Richard et al.	D634,474	S	3/2011	Wilby
6,792,682	B2	9/2004	Follo et al.	7,895,754	B2	3/2011	Blackburn
6,807,739	B2	10/2004	Follo	7,913,393	B2	3/2011	Royle et al.
D499,843	S	12/2004	Nakasuka	D635,717	S	4/2011	Furtek
6,839,968	B2	1/2005	Brown et al.	D636,532	S	4/2011	Jessemey et al.
6,854,188	B1	2/2005	Wonderley	D639,507	S	6/2011	Furtek
6,880,253	B1	4/2005	Gyllerstrom	D640,415	S	6/2011	Wonderley et al.
6,935,032	B2	8/2005	Follo	7,966,731	B2	6/2011	Walker et al.
6,941,659	B2	9/2005	Gilder	D643,976	S	8/2011	Wonderley et al.
D514,253	S	1/2006	Gray	D643,977	S	8/2011	Wonderley et al.
6,990,740	B2	1/2006	Follo et al.	7,992,304	B2	8/2011	Nakasuka
D516,243	S	2/2006	Nakasuka	8,033,023	B2	10/2011	Johnson et al.
7,043,840	B2	5/2006	Walker et al.	D648,075	S	11/2011	Wonderley et al.
7,047,646	B2	5/2006	Coffin	D648,076	S	11/2011	Jessemey et al.
D524,986	S	7/2006	Prudden, Jr.	8,046,920	B2	11/2011	Nakasuka
D526,089	S	8/2006	Fischer et al.	D653,395	S	1/2012	Adams et al.
7,086,160	B2	8/2006	Coffin et al.	8,096,054	B2	1/2012	Denkert et al.
7,111,401	B2	9/2006	Richard	8,104,179	B2	1/2012	Nakasuka
7,137,205	B2	11/2006	Royle	8,104,184	B2	1/2012	Walker
7,140,116	B2	11/2006	Coffin	8,117,753	B2	2/2012	Gilder et al.
D533,684	S	12/2006	Gray et al.	8,146,255	B2	4/2012	Denkert et al.
7,152,512	B1	12/2006	Prochaska	8,151,472	B2	4/2012	Dimitris et al.
D535,784	S	1/2007	Wonderley et al.	D658,809	S	5/2012	Jessemey et al.
7,168,173	B2	1/2007	Worrick, III	8,186,062	B2	5/2012	Fischer et al.
7,191,523	B2	3/2007	Miyazaki et al.	D661,425	S	6/2012	Cataudella et al.
7,197,825	B2	4/2007	Walker et al.	D661,426	S	6/2012	Wain et al.
7,200,937	B2	4/2007	Richard et al.	D662,661	S	6/2012	Corbeil et al.
7,200,938	B2	4/2007	Lembke	8,205,343	B2	6/2012	Winter et al.
7,200,942	B2	4/2007	Richard	8,205,344	B2	6/2012	Stevens
7,210,229	B2	5/2007	Coffin	8,209,867	B2	7/2012	Clarke
D547,494	S	7/2007	Watson et al.	8,225,510	B2	7/2012	Peterson et al.
7,266,895	B2	9/2007	Pennella et al.	D665,130	S	8/2012	Wain et al.
7,272,991	B2	9/2007	Aviza et al.	8,234,789	B2	8/2012	Avens et al.
D556,378	S	11/2007	Watson et al.	8,281,497	B2	10/2012	Takeba
D560,034	S	1/2008	Fischer et al.	8,286,354	B2	10/2012	Walker et al.
D563,043	S	2/2008	Ramm	8,336,212	B2	12/2012	Bozikis et al.
D563,044	S	2/2008	Ramm	8,359,751	B2	1/2013	Efthimiadis et al.
7,331,107	B2	2/2008	Follo et al.	8,359,752	B2	1/2013	Bridges
D575,454	S	8/2008	Keene et al.	8,381,406	B2	2/2013	Miyazaki
7,448,135	B2	11/2008	Zhuk et al.	8,413,334	B2	4/2013	Walker et al.
7,461,458	B2	12/2008	Peyser et al.	8,429,826	B2	4/2013	Clarke
7,469,477	B2	12/2008	Coffin	8,438,736	B2	5/2013	Keene et al.
7,475,483	B2	1/2009	Peyser et al.	8,448,339	B2	5/2013	Walker et al.
D588,309	S	3/2009	Wonderley et al.	8,474,144	B2	7/2013	Royle
D588,744	S	3/2009	Fischer et al.	8,499,459	B2	8/2013	Efthimiadis et al.
D588,745	S	3/2009	Fischer et al.	8,533,959	B2	9/2013	Davis
7,526,869	B2	5/2009	Blatter et al.	8,533,961	B2	9/2013	Nicoll et al.
7,540,087	B2	6/2009	Rawle	8,544,177	B2	10/2013	Rawle et al.
7,540,088	B2	6/2009	Takeshita	8,555,900	B2	10/2013	Nicoll et al.
7,574,809	B2	8/2009	Follo et al.	8,567,068	B2	10/2013	Luxton
7,578,062	B2	8/2009	Blackburn				

(56)

References Cited

U.S. PATENT DOCUMENTS

8,590,162 B2	11/2013	Park et al.	D850,722 S	6/2019	Knapp
D699,892 S	2/2014	Wonderley	10,350,773 B2	7/2019	Hill et al.
8,640,342 B2	2/2014	Murgida	D867,661 S	11/2019	Ovvdias
D701,646 S	3/2014	Jobdevairakkam	10,538,007 B2	1/2020	Zucker
8,661,689 B2	3/2014	Fathallah et al.	2002/0000040 A1	1/2002	Gilder
8,707,562 B2	4/2014	Coffin	2002/0184770 A1	12/2002	Peysner
8,726,518 B2	5/2014	Bruno	2003/0046819 A1	3/2003	Ferraro et al.
8,732,955 B2	5/2014	Howell et al.	2003/0079348 A1	5/2003	Follo
8,732,965 B2	5/2014	Efthimiadis et al.	2003/0213130 A1	11/2003	Motta
D707,885 S	6/2014	Cataudella et al.	2004/0103538 A1	6/2004	Dansreau et al.
8,745,882 B2	6/2014	Murgida et al.	2004/0128835 A1	7/2004	Coffin et al.
8,745,883 B2	6/2014	Murgida et al.	2004/0168323 A1	9/2004	Lembke
8,769,825 B2	7/2014	Howell et al.	2004/0181949 A1	9/2004	Coffin et al.
8,782,903 B2	7/2014	Clarke et al.	2004/0181953 A1	9/2004	Follo et al.
8,789,282 B2	7/2014	Wilson et al.	2004/0181954 A1	9/2004	Folio et al.
8,793,880 B2	8/2014	Taub et al.	2004/0216310 A1	11/2004	Santhagens et al.
8,931,176 B2	1/2015	Johnson et al.	2004/0231161 A1	11/2004	Coffin et al.
8,931,380 B2	1/2015	Coffin	2004/0255467 A1	12/2004	Lembke et al.
8,938,885 B2	1/2015	Stevens	2005/0015991 A1	1/2005	Follo et al.
8,978,258 B2	3/2015	Patel et al.	2005/0039338 A1	2/2005	King et al.
8,984,756 B2	3/2015	Worrick, III	2005/0241162 A1	11/2005	Nicolosi et al.
8,991,058 B2	3/2015	Dimitris et al.	2006/0032056 A1	2/2006	Coffin et al.
9,015,951 B2	4/2015	Howell et al.	2006/0070240 A1	4/2006	Fischer
D730,578 S	5/2015	Long et al.	2006/0242847 A1	11/2006	Dansreau et al.
9,032,627 B2	5/2015	Dimitris et al.	2006/0254056 A1*	11/2006	Coffin B26B 21/44
9,032,631 B2	5/2015	Christie et al.			30/41
D731,119 S	6/2015	Daniel et al.	2006/0260131 A1	11/2006	Folio
D731,708 S	6/2015	Tucker et al.	2006/0272155 A1	12/2006	Mehta et al.
9,073,226 B2	7/2015	Szczepanowski et al.	2006/0283025 A1	12/2006	Follo et al.
D737,511 S	8/2015	Lettenberger et al.	2007/0056167 A1	3/2007	Richard et al.
D737,513 S	8/2015	Lettenberger et al.	2007/0227009 A1	10/2007	Zhuk et al.
D741,008 S	10/2015	Bruno et al.	2007/0266565 A1	11/2007	Aviza et al.
D741,009 S	10/2015	Bruno et al.	2008/0034590 A1	2/2008	Prudden et al.
D741,546 S	10/2015	Witkus et al.	2008/0034593 A1	2/2008	Coffin
D744,165 S	11/2015	Tucker et al.	2008/0250647 A1	10/2008	Fischer et al.
9,193,077 B2	11/2015	Worrick	2008/0256802 A1	10/2008	O'Connor et al.
9,193,078 B2	11/2015	Worrick, III	2009/0071006 A1	3/2009	Bruno
9,193,079 B2	11/2015	Howell et al.	2009/0071007 A1	3/2009	Bruno
D748,856 S	2/2016	Mahony et al.	2009/0083982 A1	4/2009	Forsdike
D749,265 S	2/2016	Cataudella et al.	2009/0113716 A1	5/2009	Wain et al.
9,248,579 B2	2/2016	Depuydt et al.	2009/0188112 A1	7/2009	Prochaska et al.
9,259,846 B1	2/2016	Robertson	2009/0193659 A1	8/2009	Park et al.
9,283,685 B2	3/2016	Griffin et al.	2010/0154220 A1	6/2010	Nakasuka
9,296,117 B2	3/2016	Fathallah et al.	2010/0251555 A1	10/2010	Park et al.
9,321,182 B2	4/2016	Bridges et al.	2010/0313424 A1	12/2010	Johnson et al.
9,327,414 B2	5/2016	Szczepanowski et al.	2011/0094108 A1	4/2011	Wain
9,333,657 B2	5/2016	Westerhof et al.	2011/0119922 A1	5/2011	Ntavos et al.
9,364,961 B2	6/2016	Lelieveld	2011/0232101 A1	9/2011	Park et al.
9,381,657 B2	7/2016	Xu et al.	2012/0124840 A1	5/2012	Iaccarino et al.
D764,100 S	8/2016	Park et al.	2012/0151772 A1	6/2012	Moon et al.
D764,101 S	8/2016	Cataudella et al.	2012/0279070 A1	11/2012	Seo
D766,505 S	9/2016	Coviello	2012/0304467 A1	12/2012	Garden, Jr.
9,434,079 B2	9/2016	Worrick, III	2013/0000127 A1*	1/2013	Coresh B26B 21/4012
9,469,038 B2	10/2016	Iaccarino et al.			30/41
9,475,202 B2	10/2016	Griffin et al.	2013/0008029 A1	1/2013	Hill et al.
9,486,930 B2	11/2016	Provost et al.	2013/0097869 A1	4/2013	Wang et al.
9,498,892 B2	11/2016	Nakasuka et al.	2013/0097872 A1	4/2013	Blatter
D776,875 S	1/2017	Ren	2013/0160305 A1	6/2013	Howell et al.
D779,121 S	2/2017	Bruno et al.	2013/0199346 A1	8/2013	Psimadas et al.
9,579,809 B2	2/2017	Hawes	2013/0205595 A1	8/2013	Bykowski et al.
9,586,330 B2	3/2017	Xu et al.	2013/0269190 A1	10/2013	Worrick, III
9,623,575 B2	4/2017	Griffin et al.	2013/0312265 A1	11/2013	Wilson et al.
9,630,331 B2	4/2017	Griffin et al.	2013/0326881 A1	12/2013	Blatter
9,643,327 B2	5/2017	Stevens et al.	2014/0000082 A1	1/2014	Xu
9,656,401 B2	5/2017	Burrowes et al.	2014/0000114 A1	1/2014	Wester et al.
9,738,000 B2	8/2017	Ariyanayagam et al.	2014/0026424 A1	1/2014	Oglesby et al.
D811,658 S	2/2018	Cataudella et al.	2014/0033551 A1	2/2014	Szczepanowski et al.
D816,905 S	5/2018	Zucker	2014/0068953 A1	3/2014	Wonderley
D816,906 S	5/2018	Zucker	2014/0083265 A1	3/2014	Provost et al.
D816,908 S	5/2018	Zucker	2014/0090254 A1	4/2014	Wang et al.
D816,909 S	5/2018	Zucker	2014/0096402 A1	4/2014	Nakasuka et al.
D816,910 S	5/2018	Zucker	2014/0116211 A1	5/2014	Griffin et al.
D816,912 S	5/2018	Zucker	2014/0165800 A1	6/2014	Griffin et al.
D829,991 S	10/2018	Zucker	2014/0237830 A1	8/2014	Wilson et al.
D844,898 S	4/2019	Knapp et al.	2014/0245613 A1	9/2014	Good et al.
			2014/0259675 A1	9/2014	Tucker et al.
			2014/0259677 A1	9/2014	Coresh
			2014/0283387 A1	9/2014	Bozikis et al.
			2014/0331500 A1	11/2014	Ren

(56)

References Cited

U.S. PATENT DOCUMENTS

2014/0366381 A1 12/2014 Phipps
 2015/0013169 A1 1/2015 Warrick
 2015/0040402 A1 2/2015 Carneiro et al.
 2015/0090085 A1 4/2015 Griffin et al.
 2015/0158190 A1 6/2015 Georgakis et al.
 2015/0190935 A1 7/2015 Griffin et al.
 2015/0197017 A1 7/2015 Lettenberger et al.
 2015/0217466 A1 8/2015 Leicht et al.
 2015/0217468 A1* 8/2015 Dryfhout B26B 21/12
 132/200
 2015/0239137 A1 8/2015 Davos et al.
 2015/0273708 A1 10/2015 Haba
 2015/0290819 A1 10/2015 Giannopoulos et al.
 2015/0314465 A1 11/2015 Giannopoulos et al.
 2015/0314466 A1 11/2015 Papadopoulos-Papageorgis et al.
 2016/0001454 A1 1/2016 Coresh
 2016/0001455 A1 1/2016 Swenson
 2016/0031101 A1 2/2016 Fulton
 2016/0082610 A1 3/2016 Bamundaga
 2016/0096280 A1 4/2016 Robertson
 2016/0129603 A1* 5/2016 Antoniou B26B 21/44
 30/50
 2016/0158948 A1 6/2016 Eagleton et al.
 2016/0158950 A1 6/2016 Griffin et al.
 2016/0236364 A1 8/2016 Varenberg et al.
 2016/0279817 A1 9/2016 Washington et al.
 2016/0297086 A1 10/2016 Efthimiadis et al.
 2017/0021513 A1 1/2017 Liberatore
 2017/0028577 A1 2/2017 Ntavos et al.
 2017/0151684 A1 6/2017 Bozikis et al.
 2017/0282389 A1 10/2017 Jolley et al.
 2018/0071931 A1 3/2018 Walker, Jr. et al.
 2018/0236677 A1 8/2018 Blatter

FOREIGN PATENT DOCUMENTS

CN 103282166 A 9/2013
 CN 104440969 A 3/2015
 CN 105358295 A 2/2016
 DE 60104558 7/2005
 DE 10327739 B4 6/2006

DE 102004061446 6/2006
 DE 102010006807 9/2010
 DE 202011107715 1/2012
 DE 202013002343 4/2013
 DE 202013003009 6/2013
 DE 102013007224 9/2014
 DE 102013007223 10/2014
 DE 202014007575 10/2014
 DE 102013213862 1/2015
 DE 102015002458 9/2016
 EP 1332026 B1 7/2004
 EP 1488894 A1 12/2004
 EP 1671761 A1 6/2006
 EP 1847360 A1 10/2007
 EP 2227360 9/2010
 EP 2583800 A1 4/2013
 EP 3075498 A1 10/2016
 ES 2290591 T3 2/2008
 ES 2342497 7/2010
 ES 1079011 4/2013
 GB 2461054 A 12/2009
 GB 2507971 A 5/2014
 IT PI20110077 1/2013
 JP H04361782 A 12/2012
 JP 2013099467 A 5/2013
 NL 2013416 10/2015
 RO 118269 4/2003
 RU 2433909 C1 11/2011
 SE 1230136 5/2014
 TR 200402255 10/2004
 WO 02/32632 A2 4/2002
 WO 02/32633 4/2002
 WO 2009/066218 5/2009
 WO WO2009153598 A1 12/2009
 WO 2010/139618 12/2010
 WO 2012/005839 1/2012
 WO 2012/158141 11/2012
 WO 2012/158142 A1 11/2012
 WO 2014/075844 5/2014
 WO 2014/139655 9/2014
 WO 2015/090385 6/2015
 WO 2016/036238 A2 3/2016
 WO 2016/040549 A1 3/2016
 WO 2016/113553 7/2016

* cited by examiner





FIG 1






FIG 3




FIG 4





FIG 5




FIG 6




FIG 7




FIG 8




FIG 9




FIG 10




FIG 11




FIG 12A




FIG 12B




FIG 13A




FIG 13B




FIG 13C

1**RAZOR CARTRIDGE****CROSS RELATED**

This application is a continuation of and claims priority under 35 USC 120 to International Patent Application Serial No. PCT/US2017/023078 filed 17 Mar. 2017 and claims priority to U.S. Provisional application 62/310,099 filed 18 Mar. 2016 the entirety of which is hereby incorporated.

TECHNICAL FIELD

This application relates to the field of shaving razors, razor cartridges, razor blades, frames, lubrication, and other cartridge features.

BACKGROUND

Previously, shaving razors and razor cartridges suffered from inherent drawbacks based on their razor blade arrangements. Blades did not have separate guards in place, angles of the blades were not customized for different shaving characteristics and components of the cartridge led to less comfortable shaving experiences.

SUMMARY

Systems and methods here include improved razor blade cartridges. Embodiments include shaving systems, including a unitary frame having a length and width, a topside and an underside. In some embodiments, the unitary frame includes angled bends forming at least three lengthwise guards on the unitary frame, the guards separated by at least three gaps in the frame, and at least three blades, affixed lengthwise to the underside of the guards of the unitary frame. In some embodiments, the at least three blades include edges, and the blade edges extend into the gaps in the frame when affixed to the underside of the guards of the unitary frame.

Additionally or alternatively, in some embodiments the guards include back walls that support the blades. And in some examples, the frame is made of a single piece of metal. Additionally or alternatively, some embodiments include a cartridge housing surrounding the frame leaving the blades and guards exposed, the housing including a cap. And in some embodiments, the cartridge housing includes a front guard. Additionally or alternatively, in some embodiments the cartridge housing front guard includes a lubrication strip. And in some examples, the blades are affixed to the unitary frame by welds. Additionally or alternatively, in some embodiments the cartridge housing is made of a top and bottom which are configured to snap together and hold the frame. And in some examples, the front guard includes capillary tubes with lubrication soap. Additionally or alternatively, in some embodiments, the cap includes capillary tubes with lubrication soap. And in some examples, the number of guards is four and the number of blades is four. And in some examples, the number of guards is five and the number of blades is five. In some examples, the front guard is made of lubrication soap. And in some examples, the lubrication soap is slidably removable from the cartridge.

Additionally or alternatively, the blades are affixed to the underside of the unitary frame structure. Additionally or alternatively, the unitary frame is curved into a concave shape. Additionally or alternatively, the unitary frame is curved into a convex shape. In some examples, the blades in the cartridge head are perpendicular to the cartridge head itself. Additionally or alternatively, in some examples, the

2

blades are canted from the perpendicular to impart a shearing force on a target hair. In such example embodiments, the canted blades may all be parallel to each other but not perpendicularly arranged in the cartridge head, rather, positioned in a canted arrangement. In some example embodiments, the canted blades may be grouped in parallel sets which are each canted in relation to one another with each set not perpendicularly arranged in the cartridge head, rather, positioned in a canted arrangement.

BRIEF DESCRIPTION OF THE DRAWINGS

For a better understanding of the embodiments described in this application, reference should be made to the Detailed Description below, in conjunction with the following drawings in which like reference numerals refer to corresponding parts throughout the figures.

FIG. 1 is a perspective illustration of a razor cartridge according to some embodiments described here.

FIG. 2 is a cut away illustration of a razor frame and blades according to some embodiments described here.

FIG. 3 is a cut away illustration of a razor cartridge according to some embodiments described here.

FIG. 4 is another cut away illustration of a razor cartridge according to some embodiments described here.

FIG. 5 is an exploded illustration of a razor cartridge according to some embodiments described here.

FIG. 6 is another illustration of a frame and blades according to some embodiments described here.

FIG. 7 is a cut away illustration of the cartridge according to some embodiments described here.

FIG. 8 is another cut away illustration of the cartridge according to some embodiments described here.

FIG. 9 is another cut away illustration of a frame and blades according to some embodiments described here.

FIG. 10 is another cut away illustration of a frame and blades according to some embodiments described here.

FIG. 11 is another cut away illustration of a frame and blades according to some embodiments described here.

FIG. 12A is a top view of an example frame before cutting and stamping according to some embodiments described here.

FIG. 12B is a perspective view of an example frame after cutting and stamping according to some embodiments described here.

FIG. 13A is a side-by-side diagram showing a cartridge and corresponding blade arrangement according to some embodiments described here.

FIG. 13B is another side-by-side diagram showing a cartridge and corresponding canted blade arrangement according to some embodiments described here.

FIG. 13C is another side-by-side diagram showing a cartridge and corresponding canted blade arrangement according to some embodiments described here.

DETAILED DESCRIPTION

Reference will now be made in detail to embodiments, examples of which are illustrated in the accompanying drawings. In the following detailed description, numerous specific details are set forth in order to provide a sufficient understanding of the subject matter presented herein. But it will be apparent to one of ordinary skill in the art that the subject matter may be practiced without these specific details. Moreover, the particular embodiments described

herein are provided by way of example and should not be used to limit the scope of the invention to these particular embodiments.

Overview

The razor cartridge embodiments described here include many of various features in any combination. Aspects of the razor cartridge include different embodiments of frame, blade arrangement, blade exposure, as well as guard aspects. Some example embodiments include an internal frame system which incorporates individual guards adjacent to portions to which blades may be affixed. FIG. 1 shows a perspective view of an example cartridge 100 according to some embodiments described here. The cartridge 100 example includes an overall housing 102 that has a front guard 106 and a cap 108. Either or both of the front guard 106 and the cap 108 may have lubrication features built in as described in more detail herein. The cartridge 100 example includes a unitary frame 110 element which include intermediary guards 114 spaced between portions where blades 112 may be mounted to run lengthwise down the cartridge 100. The example unitary frame 110 may be configured to support any number of blades including but not limited to one blade, two blades, three blades, four blades, five blades and six blades. The non-limiting example of FIG. 1 and throughout this description is four blades.

The geometry of the blades 112 in relation to the frame 110 and the guards 114 may include any of various arrangements as described here in order to affect the shaving experience of a user of the razor cartridge 100. A first general discussion of the frame 110 and blade 112 geometry is given below. Following this discussion are more detailed descriptions of various aspects of the razor cartridge 100 embodiments.

Geometry Examples

Three example geometry variables will be discussed that can be altered in the razor cartridge to affect a shave for a user. The three example geometry variables include gap, blade angle and blade exposure. The interplay of these variables among each other leads to trade-offs in the shaving experience. A less irritating arrangement may not be effective enough for users with tough beards. A very aggressive arrangement may be too harsh for users with sensitive skin. The embodiments described here include iterations of these three variables in multiple arrangements to achieve different shaving goals and delivering different shaving experiences to different users as well as tuning these variable to achieve the closest, most comfortable shave possible for as many users as possible.

FIG. 2 illustrates an example cut away view of a frame 210 assembly and four individual blades 212 which are shown affixed to the frame 210. To help describe the geometry of the configuration, x, y and z axis coordinates are shown in relation to the frame 210 is indicated.

The frame 210 includes intermediate guards 214 built into the frame itself which are shown both supporting each blade 212 by a back wall 240 and affixing to each blade 212 from above. The intermediate guards 214 also provide an intermediary guard fashioned as a ridge or hump that sticks out from the frame 210 in the y direction to engage the skin when the cartridge is applied in a shaving stroke. The frame 210 example also includes angled joints 220 which connect each blade 212 and guard 214 arrangement to the next and to the cartridge itself.

The first geometry variable of discussion is a gap. A gap 270 refers to the gap between a blade edge 212 and the next adjacent guard 212, whether that be the overall cartridge front guard or an intermediate guard in the frame. The larger

the gap 270, the more hair is able to fit in the gap 270 and interact with the blade edge 212. The smaller the gap 270, the less hair is able to fit in the gap, but comfort may be improved. The gap may allow wash through of water and shaving material as well.

The second geometry variable of discussion is blade angle. The blade angle refers to the angle at which the blades 212 are positioned in the cartridge and/or frame 210 and interact with the user's skin in a shaving stroke. Referring to the angle of the blades 212 to the skin of a shaving user, between 0 (parallel to skin—and the neutral exposure line 280) to 17 degrees may be considered less aggressive. Between 17 degrees up to 45 degrees may be considered more aggressive. Some example embodiments may utilize blade angles between 12 and 30 degrees, where between 12 and 17 degrees may be less aggressive and between 17 and 30 degrees may be more aggressive.

Again, a more aggressive blade angle may lead to a closer cut of hair from the skin in a shaving stroke but it may be more irritating than a less aggressive blade angle for some users. Different users with different beards and skin may prefer different blade angles. Also, different areas of the body may require different blade angles.

In some embodiments, the blades 212 may be at slightly different angles from one another. For example making the first few blades in the cartridge at a less aggressive angle because in a shaving stroke, they first interact with the skin and hairs, but the back of the frame having increasingly aggressive blade angles may increase the closeness of the shave. In some embodiments, a more aggressive blade angle is configured for the first blades and less aggressive angle is configured for the back blades. Any combination of blade angles in the frame could be configured and customized for different purposes.

The third geometry variable of discussion is blade exposure. The blade exposure refers to the exposure of the blade edges 222 in reference to a reference exposure line 280 drawn across the top of the overall cartridge. In other words, the exposure line 280 is drawn in reference to the frame 210, intermediate guards 214 as well as the overall cartridge cap 108 and guard 106 (from FIG. 1). Next, the blades 212 are affixed to the frame 210. The blade edges 222 that are affixed to the frame 210 to extend beyond the exposure line 280 result in a more exposed blade. The farther the blade edges 222 are affixed in the frame 210 set back from the exposure line 280, the less they are exposed.

The more the blade edges 222 are exposed, the more they may interact with the skin and hair in a shaving stroke and the more pressure may be applied to the skin and hair by the blades 212. The less the blade edges 222 are exposed, the less they may interact with the skin and hair in a shaving stroke. Again, as a trade-off, more exposed blades may result in a closer shave but less exposed blades may provide a more comfortable shaving stroke.

In relation to the blade angles and blade exposure, some embodiments include angled joints or bends 220 in the frame 210. These angled joints or bends 220 connect the blade 212 and guard 214 portions to the next blade 212 and guard 214. Different angled joint 220 angles may affect the blade angle and blade exposure as described below.

It should be noted that the blade arrangements could be used in conjunction with and in addition to any of the other embodiments or features described in this disclosure. Therefore, a system could be built using any combination of the features described here.

Cartridge Examples

FIG. 3 shows a side angle cut away view of an example cartridge 300. The cartridge 300 example includes a cap 308, a housing 304, and a front guard 306. Some embodiments include a lubrication strip in the cap 308. The cartridge 300 also includes a frame 310 which is shown affixed to the housing 304 and supporting any number of blades 312.

The blades 312 are shown affixed to the underside of the frame 310 and the blade edges 322 are shown as exposed between the guards 314 of the frame 310. These exposed blade 312 edges 322 protrude through the frame 310 at specific angles in order to interact with a the skin and hair in a shaving stroke. The blades 312 could be affixed to the underside of the frame 310 in any number of ways including, but not limited to, welding, gluing, melding, snapping, riveting, strapping or other adhesive method.

The blades 312 could be made of any material. In some embodiments, the blades are made of metal such as aluminum, steel, stainless steel, iron, bronze, copper, tin or any amalgam of these or other metals. In some embodiments the blades 312 are made of plastics and/or composites. In some embodiments the blades 312 are made of a carbon fiber and/or ceramic. In some embodiments, the blades 312 may be honed to an edge and coated with any number of materials such as but not limited to chrome, polytetrafluoroethylene, plastics, paint, lacquer, or other coatings.

The front guard 306 could be made of any kind of material including but not limited to silicon, rubber, or plastic and take any shape including having waves, a matrix, bumps or other features that interact with the skin and hair in a shaving stroke. The lubrication strip in the cap 308 could be made of any kind of lubricating materials including but not limited to polyethylene oxide, polystyrene, polyethylene glycol, aloe, vitamin E, etc. to deliver lubricating material to the skin and hair after the blades 312 cut the hair in a shaving stroke. More detail on various cap and guard lubrication elements are described below.

FIG. 4 shows another example cutaway detail view of a cartridge 400 in a perspective view. This view includes a cut away of the frame assembly 410 and the blades 412 affixed to the bottom of the frame 410 and shown exposing the blade edges 422 through the frame 410 and the intermediate guards 414 behind each blade 412. The guards 414 are shown as integral portions of the unitary frame 410 itself as will be described below. The blade edges 422 are shown spaced apart from each adjacent guards 414 forming a gap to allow wash through of water and shaving material. These guards 414 may have any kind of shape including the humped shape shown in FIG. 4. These intermediate guards 414 may interact with the skin and hair in a shaving stroke. These intermediate guards 414 are arranged between each blade edge 422 just as the front guard 406 is arranged before the first blade 490. These guards 406, 414 prepare the shaving target (e.g. the skin and hair) to be cut by the blades 412, 490.

The guards 414 may be coated with any kind of material to ease friction or aid in standing up hairs for closer cuts. Coatings may include chrome, polytetrafluoroethylene, plastics, paint, lacquer, or other coatings. Thus, the integrated frame system 410 as shown, includes at least as many guards 414 as blades 412 including a front guard 406 as well as a cap 408. The result of using intermediate guards 414 is prepared skin and hair for each blade as opposed to only the front blade 490 by the front guard 406.

The unitary frame 410 also provides strength and support for the blades 412 through its material and also through its shape. The guards 414 and back walls 440 provide a brace

for the individual blades 412 as shown. This keeps the blades 412 in place and secures them in a shaving stroke. The frame 410 also supports the blades which may be affixed to the bottom of the intermediate guards 414.

The frame 410 itself may also provide strength for the system as the frame 410 may be made of one unitary material in some embodiments. In some examples, the frame is coated with paint or lubricant or plastic or polytetrafluoroethylene or other coating to ease friction of the skin and hair during a shaving stroke.

FIG. 5 shows an example exploded cartridge assembly 500 as viewed from the side including a cap 502 and a housing 504. In between the cap 502 and housing 504, the frame 510 and the blades 512 are shown. As shown in FIG. 5, the blades 512 attach to the bottom or underside of the frame 510 and extend through holes that run along the length of the frame 510 as described below. The cap 502 and the housing 504 could be referred to as a top 504 and bottom 502 housing. Such housing units 502, 504 may be configured to snap together by plastic tabs and/or secured by pins and/or snap flanges and/or secured by rivets or staples. Such housing units 502, 504 may be configured to be glued together, welded or otherwise affixed to one another, and sandwich the frame 510 and blades 512 between them. In some embodiments, the top housing unit 504 may include recesses in the side walls which receive and hold the edges of the frame 510 in place. Alternative embodiments include securing the frame 510 and blades 512 into a single housing by bands or snap. The use of a two piece housing is not intended to be limiting and other housing examples could be used as well including but not limited to a single piece housing. In some embodiments, the top housing 504 includes wave elements 518 that follow the overall contours of the frame 510 and blade 512 assembly. Such shapes may aid in a shaving stroke to follow the contours of the intermediary guards 514.

In some embodiments, the frame 510 is made of one integrated piece of material as described in FIGS. 12A and 12B. In some embodiments the frame 510 could be made of any number of things including but not limited to, metal such as aluminum, steel, stainless steel, iron, bronze, copper, tin or any amalgam of these or other metals. In some embodiments the frame 510 could be made of plastics and/or composites. In some embodiments the frame 510 could be made of carbon fiber and/or ceramic. In embodiments where the frame 510 is made of one piece of metal, the undulations, guards 514, back walls 540 and spaces for the blades 512 to protrude, could all be stamped out of a single sheet as described in FIGS. 12A and 12B. In other words, the frame 510 could start out as a flat sheet of metal and be stamped to form the single unit with guards 514 including back walls 540, portions to affix the blades 512, portions to secure fit into the housing 504 and cap 502, etc. And again, any number of blades 512 could be adhered to the frame 510 according to the various embodiments.

FIG. 6 shows a detail perspective view of just the frame 610 and the blades 612 mounted to the underside of the frame 610. In the example, the guards 614 are shown both forming a gap before the blades 612 and also providing support for the blades 612. The guards 614 may be configured to engage the skin between blades 612 to prepare the skin and hair for the next blade 612 in a shaving stroke. The blade edges 622 are exposed in the gap formed between the blade 612 and the adjacent guard 614. This exposure of the blades is the exposure variable as discussed above, which is the exposure to the skin and hair during a shaving stroke. The frame 610 in FIG. 6 also shows the back walls 640

which form the back walls of the guards **614** and interact with the non-sharpened end of the blades **612** to help hold them in place and support them.

FIG. **6** also shows angled joints or bends **620** on the frame **610**. These angled joints or bends **620** form the side walls of the gap between the blade edges **622** and the next respective adjacent guard **614**. The angled joints or bends **620** may also help determine the angle of the blade **612** in relation to the overall frame **610**, depending on how the angled joints or bends **620** are configured. In some embodiments, the angled joints or bends **620** are made of a flexible material such as spring steel, plastics, rubber, or are jointed to allow flexing of the frame when in use. In some embodiments, the flexing is limited to one direction. More discussion of angled joints or bends and frames appear below and in FIGS. **11** and **12**.

In some embodiments, the distance between successive blade edges **622** may be between 1.5 and 1.7 millimeters. In some embodiments, the distance between successive blade edges **622** is between 1.1 and 1.7 millimeters. In some embodiments, the distance between successive blade edges **622** is less than 1 millimeter. In some embodiments, the angle of the angled joints or bends **620** raises the blades **612** to between 16 and 22 degrees from the horizontal. In some examples, the radius of the arc made by the inter blade guards is between 0.1 and 0.4 mm. In some examples, the radius of the arc made by the inter blade guards is between 0.3 and 0.5 mm.

In some embodiments, the exposure of the blades is neutral, in other words, the blade edges **622** do not protrude beyond an imaginary line drawn between the outermost surface of the cap and guard. In some embodiments, the exposure of the blades is all negative. In some embodiments, the exposure of the blades is all positive. In some embodiments, the exposure of the blades is progressive, ranging from positive to negative or regressive, negative to positive. In some examples, as shown in FIGS. **10** and **11**, the exposure between blades is arranged on a curved arc. In some embodiments, the width of each blade **612** is between 1.2 and 2.2 millimeters.

The example of FIG. **6** also shows connecting portions **630** or tabs on the frame **610**. These connecting portions **630** or tabs may be located on the edges of the frame **610** and interact with the cap and housing (not shown) in order to secure the frame into the cartridge by snapping, welding, gluing or other ways.

Lubrication Examples

Referring again to FIG. **1**, the cap **108** and/or guard **106** may have lubrication properties or features in them. In some examples, the cap **108** has a lubrication strip embedded into it or attached to it. In some examples, the guard **106** may have a lubrication strip embedded into it or attached to it. In some examples, the cap **108** and/or guard **106** itself is made of a lubricating material instead of attaching one to it. For example, the cap **108** and/or guard **106** may be made entirely or partially of a solid bar of shaving soap. Such soap could have lubricating properties when wetted and/or other properties such as antibacterial, fragrant, color, texture, etc. In some embodiments, the cap **108** and/or guard **106** may be replaceable. Such replaceable parts could allow a user or manufacturer to attach a cap **108** and/or guard **106** with some properties. Replaceable cap **108** and/or guards **106** may allow for refreshing the soap bar after a some number of uses, or replacement to gain features of another kind of soap bar. Attachment of such a replaceable cap **108** and/or guards **106** may include any kind of clamp, slide, snap, wedge, hook, lever, magnet, or other kind of mechanical attachment.

FIG. **3** shows a cut away view of the cartridge with the cap **308** and guard **306**. As can be seen in the cut away view, the cap **308** and/or guard **306** could be made of any kind of lubricating material including but not limited to shaving soap as discussed above. The shaving soap could be affixed to the cartridge body by any kind of friction fit, slide or other way. For example, the soap bar could have a T shape construction that allows it to slide into the cartridge head and remain in place with friction during shave operation.

FIG. **7** shows a cut away perspective view of an example cartridge **700** with the frame **710** and blades **712** attached. The frame **710** is shown attached to the cartridge housing **704** with the blades **712** affixed to the underside of the frame **710** and the back walls **740**. The blade edges **722** are shown exposed between guards **714**. The front guard **706** and the cap **708** with optional lubrication properties are also depicted.

The example cartridge **700** also depicts a particular cartridge wave shape **718** in the housing **704** side walls. In this example, the cartridge shape **718** follows the shape of the intermediary guards **714** in the frame **710**. Various embodiments may be made including cartridges which do not follow the shape of the guards **714** of the frame **710**.

FIG. **7** also shows an embodiment with lubrication on the guard **706** in the form of openings or wells **797** formed in the guard **706** surface. Such wells **797** may be loaded with shaving soaps, gels, lubricants, etc., as described above. The example wells **797** may be any depth and retain the soap or other material until it becomes wet during shaving, and then the material may be released or liquefy, depending on the properties of the material. The example of circular wells **797** is not intended to be limiting. Any pattern of any kind of shape could be used, including but not limited to circles, squares, triangles, hexagons, waves, ovals, trapezoids, grid, spiral, etc. In some examples, the guard **706** could be made of a polymer sponge or foam with open or closed cells that is able to absorb the lubrication and/or water during a shave. In some examples, these lubrication features may be found in the cap **708** as well as, or alternatively as in the guard **706**.

In some examples, the front guard **706** includes capillary tubes, arranged in the guard itself. These capillary tubes may be filled or partially filled with lubrication soap, or may interact with a lubrication reservoir in the guard itself. In use, the capillary tubes may release soap when wet and when contacted with skin and hair. Such capillary tubes may be formed from any kind of fibers arranged into tube like shapes, and draw lubrication soaps from an underside of the front guard to a surface of the front guard during use. In some examples, the cap **708** may have similar or different lubrication than the guard **706**, either or both may include lubrication aspects. In some example embodiments, the intermediary guards **714** may be coated with polytetrafluoroethylene (PTFE), or other friction reducing coating, and/or may be coated in lubricating soaps.

FIG. **8** shows another cut away perspective view of an example cartridge from the underside. The frame **810** is shown attached to the cartridge housing **804**. In this view, it can be seen that the blades **812** are affixed to the underside of the frame **810** supported by the back walls **840** which include the intermediate guards **814**. The front guard **806** and the lubrication strip **808** are also depicted.

In some embodiments, cartridge walls **860** are placed in the cartridge to help support the frame **810**. In some embodiments, these cartridge walls **860** run perpendicular to the direction of the blades **812** and guards **814** and are integrated into the cartridge housing **804**. In some embodiments, the back walls **840** interact with and are supported by the

cartridge walls **860**. In this way, the frame **810** is braced at various places along the length of the cartridge **800**. The number of cartridge walls **860** could vary from one, two, three, four, five, six, or even more, spaced evenly or unevenly over the length of the cartridge **800**.

These cartridge walls **860** could be made of any material including plastic, metal or other material. In some embodiments the material of the walls **860** may match the material of the cartridge housing **804**. In some embodiments, the material of the cartridge walls **860** may match the material of the frame **810**.

It should be noted that the lubrication examples could be used in conjunction with and in addition to any of the other embodiments or features described in this disclosure. Therefore, a system could be built using any combination of the features described here.

Frame Example Details

FIG. **9** shows a cut-away side view of an example frame **910** and blades **912** attached to it. For purposes of discussion, x, y, and z coordinates are depicted in the figure with the overall frame **910** is shown generally in the x-z plane.

The blades **912** are shown affixed to the underside of the frame **910** and interacting with, and supported by, the back walls **940**. In the example frame, the back walls **940** are a continuation of the guards **914** and thereby incorporated into one unit. The angled joints or bends **920** in the frame **910** are shown in detail and the angles of these joints or bends **920** may determine the overall posture of the adjacent blade **912** in relation to the frame **910** within which it is mounted, and thereby the overall posture of the frame **910** as a whole. As discussed above, the blades **912** may have the same angle or differing angles in comparison to one another, as they are affixed in the frame **910**. Progressively or regressively angled blades **912** may interact with the skin and hair differently in a shaving stroke than blades **912** angled in the same way throughout the frame **910**, thereby many different examples of blade **912** angles, gaps between blades **912**, posture based on the joints or bends **920** may be created using this frame **910** concept.

FIG. **10** shows an example side cut away view of a blade frame **1010** according to some embodiments that have a concave curvature **1003** to it, when viewed from the perspective of the shaving target **1001**. As discussed above, in embodiments where the angled joints or bends **1020** are configured with a wide angle, the overall effect on the frame **1010** as a whole is to curve, in this example in a concave direction **1003**. Such a curve may be held in place by a rigid frame **1010** and the cartridge housing (not pictured), or combination of these. In some example embodiments, the frame **1010** and/or angled joints or bends **1020** may flex when force is applied to them. In some examples, the frame **1010** may be made of a flexible material throughout, or include joints or bends **1020** which are made of flexible material. In such examples, the frame **1010** may have a flat appearance when not under pressure, but flex into a concave shape **1003** when force is applied to the frame **1010**, as in a shaving stroke. In examples with a concave frame **1010** arrangement, the blade angles and gaps and guards may be differently configured than in embodiments where the frame is relatively flat or convex as described in FIG. **11**.

FIG. **11** shows an example side cut away view of a blade frame **1110** according to some embodiments that have a convex curvature **1103** to it, when viewed from the perspective of the shaving target **1101**. As discussed above, in embodiments where the angled joints or bends **1120** are configured with a narrower angle or are bent a particular way, the overall effect on the frame **1110** as a whole is to

curve, in this example in a convex direction **1103**. Such a curve may be held in place by a rigid frame **1110** and/or the cartridge housing (not pictured). In some example embodiments, the frame **1110** and/or angled joints or bends **1120** may flex when force is applied to them. In such examples, the frame **1110** may have a flat appearance when not under pressure, but flex into a convex shape **1103** when force is applied to the back or underside of the frame **1110** by some pushing mechanism **1105** such as a wedge or other structure.

In examples with a convex frame **1110** arrangement, the blade angles and gaps and guards may be differently configured than in embodiments where the frame is relatively flat or concave as described in FIG. **10**.

Unitary Frame Example Details

As discussed above, in some embodiments as detailed in FIGS. **9**, **10** and **11**, the unitary frame is a made from one piece of flat material that is cut and bent into a frame. FIG. **12A** shows an example simplistic diagram of a flat piece of material which can be stamped into a frame, with solid lines **1292** drawn where cuts may be made and dashed lines **1294** where bends may be made. The shapes formed from the cuts **1292** can be bent so as to form the back walls of the frame to support the blades which may be mounted on the frame as well as the inter-blade guards. It should be noted that the actual cuts and bends in the unitary piece of material may be more nuanced and detailed than what is shown in FIG. **12**, including the addition of tabs for affixing the completed frame into the cartridge head, etc.

To manufacture such a frame using one unitary flat piece of material, the cuts and bends may be made all in one step using any combination of a stamp, laser cutter, press, or other manufacturing device or process. Alternatively or additionally, injection molding may be used to create a unitary frame as well. As can be seen, the entire frame is therefore made of one piece of material. Such material may be any number of things including but not limited to metals such as steel, aluminum, brass, copper, tin, an alloy or combination of these or other metals. The frame may be made molded or stamped using plastics, resins, ceramics, or other materials as well. The thickness of the material used to cut and bend the frame could be any amount, such as but not limited to, 1 mm thick, 0.75 mm thick, or 1.2 mm thick. In some embodiments, the flat piece of material may have different thicknesses in different parts. For example, the middle where the blades attach may be thinner than the edges which include the bent elbow portions.

FIG. **12B** shows a perspective view of the fully cut and bent, or molded frame **1290**. In the cut and bent embodiments, the cuts **1292** form the shapes which are bent **1294** to form the back walls of the blade supports. As can be seen from the perspective view, in some embodiments the entire frame **1290** is also bent into a stair step manner to allow for the blades (when affixed, not pictured) to tilt upwardly for exposure, and not lay flat. In some embodiments, other features such as tabs or bends **1295** may be included in the unitary frame **1290** to be used to secure the frame into or on the cartridge head. Again, these tabs **1295** may be stamped from the unitary frame as disclosed above.

It should be noted that the unitary frame could be used in conjunction with and in addition to any of the other embodiments or features described in this disclosure. Therefore, a system could be built using any combination of the features described here.

Canted Blade Examples

In some example embodiments, the blades in the razor cartridge are not aligned 90 degrees to the edge of the frame of the cartridge, instead, they are arranged in a slightly

11

canted manner. If the blades are slightly canted in the cartridge head itself, a normal shaving pull or stroke will place the blades at a slightly angled attack, creating a shearing force to go with the normal perpendicular cutting force, and thus may aid shaving closeness and comfort.

In order to demonstrate embodiments of such examples, it should be noted that FIGS. 13A, B and C show exaggerated blade angles in order to accentuate what the actual angles may be in the system itself. The actual angles which may be used to cant blades in a cartridge head may be imperceptible to human sight without aid, but could be on the order of 1 or 2 degrees from the perpendicular. In some example embodiments, blades may be canted as described here between 1 and 3 degrees from perpendicular. In some example embodiments, blades may be canted 5 or fewer degrees from perpendicular. In some examples, the blades may be canted between 3 and 9 degrees, or could be larger such as 12 to 14 degrees. Any amount of slight canting may allow for the shearing force to be applied by the blades to the target hair. The examples here are not intended to be limiting.

For example, FIG. 13A shows an example cartridge 1300 next to an abstraction of the arrangement of the blades 1380, in this example the blades are arranged in parallel and perpendicular 1389 to the edge of the cartridge as in a typical arrangement. Thus, FIG. 13A shows the blades 1394 aligned parallel to the x axis and aligned generally perpendicular to the direction of the intended shaving stroke 1398. This is a typical embodiment without canted blades.

FIG. 13B shows an example cartridge 1300 next to an abstraction of the arrangement of the blades 1380, and how they are arranged parallel to one another, but in this example canted slightly 1399 off of the x axis, and thus, not completely perpendicular to the direction of the shaving stroke 1398 or the sides of the cartridge itself 1300. In such an arrangement, because a user will pull the cartridge head in a shaving stroke 1398 that is based on the cartridge head itself 1300 and not the angle the blades are arranged 1380, a shearing force may be imparted on the target hair by the blades 1396 instead of or, in addition to, a head-on cutting force. This combination of shearing and cutting may make for a smoother, more comfortable shave with less irritation and/or tugging.

FIG. 13C shows an example cartridge 1300 next to an abstraction of the arrangement of the blades 1380, and how the blades are not arranged parallel to one another, but alternating, 1382, 1384. In such examples, the canted blades may be arranged in different canted alternating directions 1382, 1384 with one group of blades parallel to each other but another group of blades parallel to each other, but not to the first group of blades. The number of parallel groups is not limited to two and could be three or four. In some example embodiments, instead of groups of blades in parallel sets, there may be singular blades that are not in parallel with another group. In any of these embodiments, the differing canted blades would allow for different shearing forces to be exerted by each of the blades. In such arrangements, rather than all the blades canted the same way, they would each be different 1382, 1384 or grouped in different canted arrangements. In some embodiments, a combination of perpendicular and canted blades may be used to impart both cutting and shearing forces on the target hair.

It should be noted that the canted blade embodiments could be used in conjunction with and in addition to any of the other embodiments or features described in this disclosure. Therefore, a system could be built using any combination of the features described here.

12

CONCLUSION

The foregoing description, for purpose of explanation, has been described with reference to specific embodiments. However, the illustrative discussions above are not intended to be exhaustive or to limit the embodiments to the precise forms disclosed. Many modifications and variations are possible in view of the above teachings. The embodiments were chosen and described in order to best explain the principles of the embodiments and its practical applications, to thereby enable others skilled in the art to best utilize the various embodiments with various modifications as are suited to the particular use contemplated.

Unless the context clearly requires otherwise, throughout the description, the words "comprise," "comprising," and the like are to be construed in an inclusive sense as opposed to an exclusive or exhaustive sense; that is to say, in a sense of "including, but not limited to." Words using the singular or plural number also include the plural or singular number respectively. Additionally, the words "herein," "hereunder," "above," "below," and words of similar import refer to this application as a whole and not to any particular portions of this application. When the word "or" is used in reference to a list of two or more items, that word covers all of the following interpretations of the word: any of the items in the list, all of the items in the list and any combination of the items in the list.

Although some presently preferred implementations of the embodiments have been specifically described herein, it will be apparent to those skilled in the art to which the embodiments pertains that variations and modifications of the various implementations shown and described herein may be made without departing from the spirit and scope of the embodiments. Accordingly, it is intended that the embodiments be limited only to the extent required by the applicable rules of law.

What is claimed is:

1. A shaving system, comprising:

a unitary frame having a lengthy, a width, a topside and an underside,

wherein the unitary frame includes angled bends forming at least three lengthwise intermediary guards on the unitary frame, the least three lengthwise intermediary guards protruding outward toward the frame topside of the unitary frame to contact skin of a user in use, and the intermediary guards separated by at least three gaps in the unitary frame; and

at least three blades, welded lengthwise to lengthwise portions of the underside of the unitary frame, wherein the unitary frame is between 1.2 mm thick and 0.6 mm thick at the portions where the at least three blades are welded,

wherein each of the at least three lengthwise guards is arranged aft to each of the at least three gaps and each of the at least three blades respectively;

wherein the at least three blades each include an edge, wherein the edges of each of the three blades defining a plane, and

wherein the edge of each of the three blades extends into each of the at least three gaps in the unitary frame when welded to the lengthwise portions of the underside of each of the at least three lengthwise intermediary guards of the unitary frame, between angles of 12 and 30 degrees from the plane, and a distance between each successive edge of the edge of each of the at least three blades is between 1.1 mm and 1.7 mm.

13

2. The system of claim 1, wherein the guards include back walls that support the blades.

3. The system of claim 1 wherein the frame is made of a single piece of metal.

4. The system of claim 1 further comprising, a cartridge housing surrounding the frame leaving the at least three blades and least three lengthwise intermediary guards exposed, the housing including a cap.

5. The system of claim 1 wherein the number of guards is four and the number of blades is four.

6. The system of claim 4 wherein the cartridge housing is made of a top and bottom which are configured to snap together and hold the frame.

7. The system of claim 4 wherein the cap includes capillary tubes with lubrication soap.

8. The system of claim 4 wherein the cartridge housing includes a front guard.

9. The system of claim 8 wherein the cartridge housing front guard includes a lubrication strip.

10. The system of claim 8 wherein the front guard includes capillary tubes with lubrication soap.

11. The system of claim 8 wherein the front guard is made of lubrication soap.

12. The system of claim 11 wherein the lubrication soap is slidably removable from the cartridge.

13. A system comprising:

a bent metal frame including a topside, an underside, a width and a length, the length being longer than the width,

wherein the bent metal frame includes,

at least three holes running partially along the length; at least three intermediary humps formed in the bent metal frame running partially along the length before each of the at least three holes respectively, the at least three humps is configured to contact skin of a user in use;

14

at least three stainless steel flat razor blades, each having a width and a length, the length being longer than the width, each stainless steel flat razor blade having a sharpened edge along a first side of the length and a blunt side along a second side of the length;

the at least three stainless steel flat razor blades welded to the underside of the bent metal frame so that the sharpened edge of each of the at least three stainless steel flat razor blades each protrudes respectively through each of the at least three holes, the at least three sharpened edges of the at least three stainless steel flat razor blades defining a plane, wherein the at least three stainless steel flat razor blades are welded to the bent metal frame and at angles between 17 and 30 degrees from the plane, and a distance between each successive edge of the sharpened edge of each of the at least three stainless steel flat razor blades is between 1.1 mm and 1.7 mm,

wherein the bent metal frame is less than 1.2 mm thick at portions where the at least three stainless steel flat razor blades are welded.

14. The system of claim 13 wherein the bent metal frame is coated in polytetrafluoroethylene.

15. The system of claim 13 wherein the cartridge includes a top cartridge housing and a bottom cartridge housing, configured to secure to one another,

wherein the bent metal frame and mounted blades are supported between the top cartridge housing and bottom cartridge housing.

16. The system of claim 15 wherein the top cartridge housing includes a front guard and cap, the front guard including lubrication soap.

17. The system of claim 16 wherein the front guard includes capillary tubes which are loaded with the lubrication soap.

* * * * *