

US011122909B2

(12) **United States Patent**
Palashewski et al.

(10) **Patent No.:** **US 11,122,909 B2**
(45) **Date of Patent:** **Sep. 21, 2021**

(54) **INFLATABLE AIR MATTRESS SYSTEM WITH DETECTION TECHNIQUES**

(71) Applicants: **Sleep Number Corporation**, Minneapolis, MN (US); **Select Comfort Retail Corporation**, Minneapolis, MN (US)

(72) Inventors: **Wade Daniel Palashewski**, Andover, MN (US); **Rob Nunn**, Eden Prairie, MN (US); **Matthew Wayne Tilstra**, Rogers, MN (US); **Steven Jay Young**, Los Gatos, CA (US); **Carl Hewitt**, San Jose, CA (US); **Yuri Zhovnirovsky**, Campbell, CA (US)

(73) Assignee: **Sleep Number Corporation**, Minneapolis, MN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/841,105**

(22) Filed: **Apr. 6, 2020**

(65) **Prior Publication Data**
US 2020/0297126 A1 Sep. 24, 2020

Related U.S. Application Data

(63) Continuation of application No. 16/510,265, filed on Jul. 12, 2019, now abandoned, which is a (Continued)

(51) **Int. Cl.**
A47C 27/08 (2006.01)
A61B 5/11 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC *A47C 27/083* (2013.01); *A47C 27/10* (2013.01); *A47C 31/008* (2013.01);
(Continued)

(58) **Field of Classification Search**
None
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,727,606 A 4/1973 Sielaff
4,146,885 A 3/1979 Lawson, Jr.
(Continued)

FOREIGN PATENT DOCUMENTS

EP 0853918 7/1998
EP 2 649 908 4/2012
(Continued)

OTHER PUBLICATIONS


U.S. Appl. No. 14/146,281, filed Jan. 2, 2014, Palashewski et al.
(Continued)

Primary Examiner — Mohammad K Islam
Assistant Examiner — Terence E Stifter, Jr.
(74) *Attorney, Agent, or Firm* — Fish & Richardson P.C.

(57) **ABSTRACT**

In one example, this disclosure describes a method including receiving, at a central controller of an air mattress system, a plurality of air pressure value, determining a plurality of average values using the plurality of the received air pressure values, calculating a difference value between a first one of the plurality of average values and a second one of the plurality of average values, comparing the difference value to a threshold value, determining, based on the comparison, whether a user of the air mattress system moved.

16 Claims, 7 Drawing Sheets



Related U.S. Application Data

continuation of application No. 15/341,106, filed on Nov. 2, 2016, now Pat. No. 10,441,086, which is a continuation of application No. 14/209,414, filed on Mar. 13, 2014, now Pat. No. 9,510,688.

(60) Provisional application No. 61/781,311, filed on Mar. 14, 2013.

(51) **Int. Cl.**

A47C 31/12 (2006.01)
A61B 5/00 (2006.01)
A61B 5/01 (2006.01)
A47C 27/10 (2006.01)
A47C 31/00 (2006.01)
G01L 13/00 (2006.01)

(52) **U.S. Cl.**

CPC *A47C 31/123* (2013.01); *A61B 5/01* (2013.01); *A61B 5/1115* (2013.01); *A61B 5/1118* (2013.01); *A61B 5/4806* (2013.01); *A61B 5/6892* (2013.01); *G01L 13/00* (2013.01)

(56)

References Cited

U.S. PATENT DOCUMENTS

4,299,233 A 11/1981 Lemelson
 4,438,771 A 3/1984 Friesen et al.
 4,657,026 A 4/1987 Tagg
 4,662,012 A 5/1987 Tarbet
 4,766,628 A 8/1988 Walker
 4,788,729 A 12/1988 Walker
 4,829,616 A 5/1989 Walker
 4,890,344 A 1/1990 Walker
 4,897,890 A 2/1990 Walker
 4,908,895 A 3/1990 Walker
 4,991,244 A 2/1991 Walker
 5,062,169 A 11/1991 Kennedy et al.
 5,144,706 A 9/1992 Walker et al.
 5,170,522 A 12/1992 Walker
 5,197,490 A 3/1993 Steiner et al.
 5,459,452 A 10/1995 DePonte
 5,509,154 A 4/1996 Shafer et al.
 5,515,865 A 5/1996 Scanlon
 5,564,140 A 10/1996 Shoenhair et al.
 5,642,546 A 7/1997 Shoenhair
 5,652,484 A 7/1997 Shafer et al.
 5,675,855 A 10/1997 Culp
 5,684,460 A 11/1997 Scanlon
 5,699,038 A 12/1997 Ulrich et al.
 5,724,990 A 3/1998 Ogino
 5,765,246 A 6/1998 Shoenhair
 5,771,511 A 6/1998 Kummer et al.
 5,796,340 A 8/1998 Miller
 5,844,488 A 12/1998 Musick
 5,848,450 A 12/1998 Oexman et al.
 5,903,941 A 5/1999 Shafer et al.
 5,904,172 A 5/1999 Giff et al.
 5,948,303 A 9/1999 Larson
 5,964,720 A 10/1999 Pelz
 5,989,193 A 11/1999 Sullivan
 6,014,346 A 1/2000 Malone
 6,024,699 A 2/2000 Surwit et al.
 6,037,723 A 3/2000 Shafer et al.
 6,058,537 A 5/2000 Larson
 6,062,216 A 5/2000 Corn
 6,088,642 A 7/2000 Finkelstein
 6,108,844 A 8/2000 Kraft et al.
 6,120,441 A 9/2000 Griebel
 6,146,332 A 11/2000 Pinsonneault et al.
 6,147,592 A 11/2000 Ulrich et al.
 6,161,231 A 12/2000 Kraft et al.
 6,202,239 B1 3/2001 Ward et al.

6,208,250 B1 3/2001 Dixon et al.
 6,234,642 B1 5/2001 Bokaemper
 6,272,378 B1 8/2001 Baumgart-Schmitt
 6,386,201 B1 5/2002 Fard
 6,396,224 B1 5/2002 Luff et al.
 6,397,419 B1 6/2002 Mechache
 6,438,776 B2 8/2002 Ferrand et al.
 6,450,957 B1 9/2002 Yoshimi et al.
 6,468,234 B1 10/2002 Ford et al.
 6,483,264 B1 11/2002 Shafer et al.
 6,485,441 B2 11/2002 Woodward
 6,546,580 B2 4/2003 Shimada
 6,547,743 B2 4/2003 Brydon
 6,561,047 B1 5/2003 Gladney
 6,566,833 B2 5/2003 Bartlett
 6,686,711 B2* 2/2004 Rose G05D 16/2066
 318/16
 6,708,357 B2 3/2004 Gaboury et al.
 6,719,708 B1 4/2004 Jansen
 6,763,541 B2 7/2004 Mahoney et al.
 6,778,090 B2 8/2004 Newham
 6,804,848 B1 10/2004 Rose
 6,832,397 B2 12/2004 Gaboury et al.
 6,840,117 B2 1/2005 Hubbard, Jr.
 6,840,907 B1 1/2005 Brydon
 6,847,301 B1 1/2005 Olson
 6,878,121 B2 4/2005 Krausman
 6,883,191 B2 4/2005 Gaboury et al.
 6,993,380 B1 1/2006 Modarres
 7,041,049 B1 5/2006 Raniere
 7,077,810 B2 7/2006 Lange et al.
 7,150,718 B2 12/2006 Okada
 7,237,287 B2 7/2007 Weismiller et al.
 7,253,366 B2 8/2007 Bhai
 7,304,580 B2 12/2007 Sullivan et al.
 7,314,451 B2 1/2008 Halperin et al.
 7,321,811 B1 1/2008 Rawls-Meehan
 7,330,127 B2 2/2008 Price et al.
 7,389,554 B1 6/2008 Rose
 7,396,331 B2 7/2008 Mack
 7,429,247 B2 9/2008 Okada et al.
 7,437,787 B2 10/2008 Bhai
 7,465,280 B2 12/2008 Rawls-Meehan
 7,480,951 B2 1/2009 Weismiller
 7,506,390 B2 3/2009 Dixon et al.
 7,520,006 B2 4/2009 Menkedick et al.
 7,524,279 B2 4/2009 Auphan
 7,532,934 B2 5/2009 Lee et al.
 7,538,659 B2 5/2009 Ulrich
 7,557,718 B2 7/2009 Petrosenko et al.
 7,568,246 B2 8/2009 Weismiller et al.
 7,637,859 B2 12/2009 Lindback et al.
 7,652,581 B2 1/2010 Gentry et al.
 7,666,151 B2 2/2010 Sullivan et al.
 7,669,263 B2 3/2010 Menkedick et al.
 7,676,872 B2 3/2010 Block et al.
 7,685,663 B2 3/2010 Rawls-Meehan
 7,699,784 B2 4/2010 Wan et al.
 7,717,848 B2 5/2010 Heruth et al.
 7,749,154 B2 7/2010 Cornel
 7,784,128 B2 8/2010 Kramer
 7,785,257 B2 8/2010 Mack et al.
 7,805,785 B2 10/2010 Rawls-Meehan
 7,841,031 B2 11/2010 Rawls-Meehan
 7,849,545 B2 12/2010 Flocard et al.
 7,854,031 B2 12/2010 Rawls-Meehan
 7,860,723 B2 12/2010 Rawls-Meehan
 7,862,523 B2 1/2011 Ruotoistenmaki
 7,865,988 B2 1/2011 Koughan et al.
 7,868,757 B2 1/2011 Radivojevic et al.
 7,869,903 B2 1/2011 Turner et al.
 7,930,783 B2 4/2011 Rawls-Meehan
 7,933,669 B2 4/2011 Rawls-Meehan
 7,953,613 B2 5/2011 Gizewski
 7,954,189 B2 6/2011 Rawls-Meehan
 7,956,755 B2 6/2011 Lee et al.
 7,967,739 B2 6/2011 Auphan
 7,979,169 B2 7/2011 Rawls-Meehan
 8,002,553 B2 8/2011 Hastlestad et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,019,486 B2	9/2011	Rawls-Meehan	2005/0190068 A1	9/2005	Gentry et al.
8,020,230 B2	9/2011	Rawls-Meehan	2005/0283039 A1	12/2005	Cornel
8,028,363 B2	10/2011	Rawls-Meehan	2006/0020178 A1	1/2006	Sotos et al.
8,032,263 B2	10/2011	Rawls-Meehan	2006/0031996 A1	2/2006	Rawls-Meehan
8,032,960 B2	10/2011	Rawls-Meehan	2006/0047217 A1	3/2006	Mirtalebi
8,046,114 B2	10/2011	Rawls-Meehan	2006/0152378 A1	7/2006	Lokhorst
8,046,115 B2	10/2011	Rawls-Meehan	2006/0162074 A1	7/2006	Bader
8,046,116 B2	10/2011	Rawls-Meehan	2007/0118054 A1	5/2007	Pinhas et al.
8,046,117 B2	10/2011	Rawls-Meehan	2007/0149883 A1	6/2007	Yesha
8,050,805 B2	11/2011	Rawls-Meehan	2007/0179334 A1	8/2007	Groves et al.
8,052,612 B2	11/2011	Tang	2007/0180047 A1	8/2007	Dong et al.
8,065,764 B2	11/2011	Kramer	2007/0180618 A1	8/2007	Weismiller et al.
8,069,852 B2	12/2011	Burton	2007/0276202 A1	11/2007	Raisanen et al.
8,073,535 B2	12/2011	Jung et al.	2008/0052837 A1	3/2008	Blumberg
8,078,269 B2	12/2011	Suzuki et al.	2008/0071200 A1	3/2008	Rawls-Meehan
8,078,336 B2	12/2011	Rawls-Meehan	2008/0077020 A1	3/2008	Young et al.
8,078,337 B2	12/2011	Rawls-Meehan	2008/0092291 A1	4/2008	Rawls-Meehan
8,083,682 B2	12/2011	Dalal et al.	2008/0092292 A1	4/2008	Rawls-Meehan
8,090,478 B2	1/2012	Skinner et al.	2008/0092293 A1	4/2008	Rawls-Meehan
8,092,399 B2	1/2012	Sasaki	2008/0092294 A1	4/2008	Rawls-Meehan
8,094,013 B1	1/2012	Lee	2008/0093784 A1	4/2008	Rawls-Meehan
8,096,960 B2	1/2012	Loree et al.	2008/0097774 A1	4/2008	Rawls-Meehan
8,146,191 B2	4/2012	Bobey et al.	2008/0097778 A1	4/2008	Rawls-Meehan
8,150,562 B2	4/2012	Rawls-Meehan	2008/0097779 A1	4/2008	Rawls-Meehan
8,166,589 B2	5/2012	Hijlkema	2008/0104750 A1	5/2008	Rawls-Meehan
8,181,296 B2	5/2012	Rawls-Meehan	2008/0104754 A1	5/2008	Rawls-Meehan
8,266,742 B2	9/2012	Andrienko	2008/0104755 A1	5/2008	Rawls-Meehan
8,272,892 B2	9/2012	McNeely et al.	2008/0104756 A1	5/2008	Rawls-Meehan
8,276,585 B2	10/2012	Buckley	2008/0104757 A1	5/2008	Rawls-Meehan
8,279,057 B2	10/2012	Hirose	2008/0104758 A1	5/2008	Rawls-Meehan
8,280,748 B2	10/2012	Allen	2008/0104759 A1	5/2008	Rawls-Meehan
8,281,433 B2	10/2012	Riley et al.	2008/0104760 A1	5/2008	Rawls-Meehan
8,282,452 B2	10/2012	Grigsby et al.	2008/0104761 A1	5/2008	Rawls-Meehan
8,284,047 B2	10/2012	Collins, Jr.	2008/0109959 A1	5/2008	Rawls-Meehan
8,287,452 B2	10/2012	Young et al.	2008/0109964 A1	5/2008	Flocard et al.
8,336,369 B2	12/2012	Mahoney	2008/0109965 A1	5/2008	Mossbeck
8,341,784 B2	1/2013	Scott	2008/0115272 A1	5/2008	Rawls-Meehan
8,341,786 B2	1/2013	Oexman et al.	2008/0115273 A1	5/2008	Rawls-Meehan
8,348,840 B2	1/2013	Heit et al.	2008/0115274 A1	5/2008	Rawls-Meehan
8,350,709 B2	1/2013	Receveur	2008/0115275 A1	5/2008	Rawls-Meehan
8,375,488 B2	2/2013	Rawls-Meehan	2008/0115276 A1	5/2008	Rawls-Meehan
8,376,954 B2	2/2013	Lange et al.	2008/0115277 A1	5/2008	Rawls-Meehan
8,382,484 B2	2/2013	Wetmore et al.	2008/0115278 A1	5/2008	Rawls-Meehan
8,386,008 B2	2/2013	Yuen et al.	2008/0115279 A1	5/2008	Rawls-Meehan
8,398,538 B2	3/2013	Dothie	2008/0115280 A1	5/2008	Rawls-Meehan
8,403,865 B2	3/2013	Halperin et al.	2008/0115281 A1	5/2008	Rawls-Meehan
8,413,274 B2	4/2013	Weismiller et al.	2008/0115282 A1	5/2008	Rawls-Meehan
8,421,606 B2	4/2013	Collins, Jr. et al.	2008/0120775 A1	5/2008	Rawls-Meehan
8,428,696 B2	4/2013	Foo	2008/0120776 A1	5/2008	Rawls-Meehan
8,444,558 B2	5/2013	Young et al.	2008/0120777 A1	5/2008	Rawls-Meehan
8,491,492 B2	7/2013	Shinar et al.	2008/0120778 A1	5/2008	Rawls-Meehan
8,517,953 B2	8/2013	Lange et al.	2008/0120779 A1	5/2008	Rawls-Meehan
8,620,615 B2	12/2013	Oexman	2008/0120784 A1	5/2008	Warner et al.
8,672,853 B2	3/2014	Young	2008/0122616 A1	5/2008	Warner
8,679,034 B2	3/2014	Halperin et al.	2008/0126122 A1	5/2008	Warner et al.
8,769,747 B2	7/2014	Mahoney et al.	2008/0126132 A1	5/2008	Warner
8,840,564 B2	9/2014	Pinhas et al.	2008/0127418 A1	6/2008	Rawls-Meehan
8,931,329 B2	1/2015	Mahoney et al.	2008/0127424 A1	6/2008	Rawls-Meehan
8,966,689 B2	3/2015	McGuire et al.	2008/0147442 A1	6/2008	Warner
8,973,183 B1	3/2015	Palashewski et al.	2008/0162171 A1	7/2008	Rawls-Meehan
8,984,687 B2	3/2015	Stusynski et al.	2008/0189865 A1*	8/2008	Bhai A61B 5/1115 5/706
9,445,751 B2*	9/2016	Young A61B 5/0002	2008/0275314 A1	11/2008	Mack et al.
2002/0091467 A1*	7/2002	Rose G05D 16/2066 700/282	2008/0281611 A1	11/2008	Rawls-Meehan
			2008/0281612 A1	11/2008	Rawls-Meehan
			2008/0281613 A1	11/2008	Rawls-Meehan
			2008/0288272 A1	11/2008	Rawls-Meehan
			2008/0288273 A1	11/2008	Rawls-Meehan
2002/0124311 A1	9/2002	Peftoulidis	2008/0306351 A1	12/2008	Izumi
2003/0045806 A1	3/2003	Brydon	2008/0307582 A1	12/2008	Flocard et al.
2003/0128125 A1	6/2003	Burbank et al.	2009/0018853 A1	1/2009	Rawls-Meehan
2003/0166995 A1	9/2003	Jansen	2009/0018854 A1	1/2009	Rawls-Meehan
2003/0182728 A1	10/2003	Chapman et al.	2009/0018855 A1	1/2009	Rawls-Meehan
2003/0221261 A1	12/2003	Tarbet et al.	2009/0018856 A1	1/2009	Rawls-Meehan
2004/0049132 A1	3/2004	Barron et al.	2009/0018857 A1	1/2009	Rawls-Meehan
2005/0022606 A1	2/2005	Partin et al.	2009/0018858 A1	1/2009	Rawls-Meehan
2005/0038326 A1	2/2005	Mathur	2009/0024406 A1	1/2009	Rawls-Meehan
2005/0115561 A1	6/2005	Stahmann et al.	2009/0037205 A1	2/2009	Rawls-Meehan
2005/0131318 A1	6/2005	Peifer et al.	2009/0043595 A1	2/2009	Rawls-Meehan

(56)

References Cited

U.S. PATENT DOCUMENTS

2009/0051550 A1* 2/2009 Sasaki A61B 5/6887
340/575

2009/0064420 A1 3/2009 Rawls-Meehan

2009/0100599 A1 4/2009 Rawls-Meehan

2009/0121660 A1 5/2009 Rawls-Meehan

2009/0139029 A1 6/2009 Rawls-Meehan

2009/0203972 A1 8/2009 Henehgan et al.

2009/0275808 A1 11/2009 DiMaio et al.

2009/0314354 A1* 12/2009 Chaffee A47C 27/083
137/14

2010/0025900 A1 2/2010 Rawls-Meehan

2010/0090383 A1 4/2010 Rawls-Meehan

2010/0094139 A1 4/2010 Brauers et al.

2010/0099954 A1 4/2010 Dickinson et al.

2010/0152546 A1 6/2010 Behan et al.

2010/0170043 A1 7/2010 Young et al.

2010/0174198 A1 7/2010 Young et al.

2010/0174199 A1 7/2010 Young et al.

2010/0191136 A1 7/2010 Wolford

2010/0191390 A1 7/2010 Champion

2010/0199432 A1 8/2010 Rawls-Meehan

2010/0231421 A1 9/2010 Rawls-Meehan

2010/0302044 A1 12/2010 Chacon et al.

2010/0317930 A1 12/2010 Oexman et al.

2011/0001622 A1 1/2011 Gentry

2011/0010014 A1 1/2011 Oexman et al.

2011/0015495 A1 1/2011 Dothie et al.

2011/0041592 A1 2/2011 Schmoeller et al.

2011/0068935 A1 3/2011 Riley et al.

2011/0087113 A1 4/2011 Mack et al.

2011/0094041 A1 4/2011 Rawls-Meehan

2011/0115635 A1 5/2011 Petrovski et al.

2011/0138539 A1 6/2011 Mahoney et al.

2011/0144455 A1 6/2011 Young et al.

2011/0156915 A1 6/2011 Brauers et al.

2011/0224510 A1 9/2011 Oakhill

2011/0239374 A1 10/2011 Rawls-Meehan

2011/0252569 A1 10/2011 Rawls-Meehan

2011/0258784 A1 10/2011 Rawls-Meehan

2011/0282216 A1 11/2011 Shinar et al.

2011/0283462 A1 11/2011 Rawls-Meehan

2011/0291795 A1 12/2011 Rawls-Meehan

2011/0291842 A1 12/2011 Oexman

2011/0295083 A1 12/2011 Doelling et al.

2011/0302720 A1 12/2011 Yakam et al.

2011/0306844 A1 12/2011 Young

2012/0025992 A1 2/2012 Tallent et al.

2012/0053423 A1 3/2012 Kenalty et al.

2012/0053424 A1 3/2012 Kenalty et al.

2012/0056729 A1 3/2012 Rawls-Meehan

2012/0057685 A1 3/2012 Rawls-Meehan

2012/0090698 A1 4/2012 Giori et al.

2012/0110738 A1 5/2012 Rawls-Meehan

2012/0110739 A1 5/2012 Rawls-Meehan

2012/0110740 A1 5/2012 Rawls-Meehan

2012/0112890 A1 5/2012 Rawls-Meehan

2012/0112891 A1 5/2012 Rawls-Meehan

2012/0112892 A1 5/2012 Rawls-Meehan

2012/0116591 A1 5/2012 Rawls-Meehan

2012/0119886 A1 5/2012 Rawls-Meehan

2012/0119887 A1 5/2012 Rawls-Meehan

2012/0138067 A1 6/2012 Rawls-Meehan

2012/0154155 A1 6/2012 Brasch

2012/0186019 A1 7/2012 Rawls-Meehan

2012/0198632 A1 8/2012 Rawls-Meehan

2012/0259248 A1 10/2012 Receveur

2012/0311790 A1 12/2012 Nomura et al.

2013/0160212 A1 6/2013 Oexman et al.

2013/0174345 A1* 7/2013 Leu G05B 11/01
5/694

2013/0174347 A1 7/2013 Oexman et al.

2013/0227787 A1 9/2013 Herbst et al.

2014/0007656 A1 1/2014 Mahoney

2014/0137332 A1 5/2014 McGuire et al.

2014/0182061 A1 7/2014 Zaiss

2014/0250597 A1 9/2014 Chen et al.

2014/0257571 A1 9/2014 Chen et al.

2014/0259417 A1 9/2014 Nunn et al.

2014/0259418 A1 9/2014 Nunn et al.

2014/0259419 A1 9/2014 Stusynski

2014/0259431 A1 9/2014 Fleury

2014/0259433 A1 9/2014 Nunn et al.

2014/0259434 A1 9/2014 Nunn et al.

2014/0277611 A1 9/2014 Nunn et al.

2014/0277778 A1 9/2014 Nunn et al.

2014/0277822 A1 9/2014 Nunn et al.

2014/0283308 A1 9/2014 Chen

2014/0313700 A1 10/2014 Connell et al.

2015/0007393 A1 1/2015 Palashewski et al.

2015/0008710 A1 1/2015 Young et al.

2015/0025327 A1 1/2015 Young et al.

2015/0026896 A1 1/2015 Fleury et al.

2015/0136146 A1 5/2015 Hood et al.

2015/0157137 A1 6/2015 Nunn et al.

2015/0157519 A1 6/2015 Stusynski et al.

2015/0173671 A1* 6/2015 Paalasmaa A61B 5/6891
600/301

2015/0182033 A1 7/2015 Brosnan et al.

2015/0182397 A1 7/2015 Palashewski et al.

2015/0182399 A1 7/2015 Palashewski et al.

2015/0182418 A1 7/2015 Zaiss

2015/0290059 A1 10/2015 Brosnan et al.

2015/0374137 A1 12/2015 Mahoney et al.

2016/0100696 A1 4/2016 Palashewski et al.

FOREIGN PATENT DOCUMENTS

JP 2004/229875 8/2004

WO WO 91/13575 9/1991

WO WO 2004/006768 1/2004

WO WO 2004/082549 9/2004

WO WO 2005/024748 3/2005

WO WO 2006/135845 12/2006

WO WO 2008/128250 10/2008

WO WO 2009/108228 9/2009

WO WO 2009/123641 10/2009

WO WO 2014/143634 9/2014

OTHER PUBLICATIONS

International Preliminary Report on Patentability and Written Opinion in International Application No. PCT/US2014/026526, dated Sep. 24, 2015, 6 pages.

International Search Report and Written Opinion in International Application No. PCT/US2014/026526, dated May 15, 2014, 7 pages.

U.S. Appl. No. 60/702,645, filed Jul. 26, 2005, Bhai.

IEEE Standard Dictionary of Electrical and Electronics Terms, 3rd ed., Jay (ed)., Aug. 1984, 71-73, 6 pages.

* cited by examiner




Fig. 1




Fig. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7

INFLATABLE AIR MATTRESS SYSTEM WITH DETECTION TECHNIQUES

This application is a continuation of U.S. application Ser. No. 16/510,265, filed Jul. 12, 2019, which is a continuation of U.S. application Ser. No. 15/341,106, filed Nov. 2, 2016, which is a continuation of U.S. application Ser. No. 14/209,414, filed Mar. 13, 2014, now U.S. Pat. No. 9,510,688, which claims the benefit of priority of U.S. Provisional Application No. 61/781,311 titled, "INFLATABLE AIR MATTRESS SYSTEM WITH DETECTION TECHNIQUES" to Rob Nunn and filed on Mar. 14, 2013, the entire content being incorporated herein by reference in its entirety.

CROSS-REFERENCES

The subject matter described in this application is related to subject matter disclosed in the following applications: U.S. Application Ser. No. 61/781,266, filed on Mar. 14, 2013, titled "INFLATABLE AIR MATTRESS ALARM AND MONITORING SYSTEM"; U.S. Application Ser. No. 61/781,503, filed on Mar. 14, 2013, titled "INFLATABLE AIR MATTRESS SYSTEM ARCHITECTURE"; U.S. Application Ser. No. 61/781,541, filed on Mar. 14, 2013, titled "INFLATABLE AIR MATTRESS AUTOFILL AND OFF BED PRESSURE ADJUSTMENT"; U.S. Application Ser. No. 61/781,571, filed on Mar. 14, 2013, titled "INFLATABLE AIR MATTRESS SLEEP ENVIRONMENT ADJUSTMENT AND SUGGESTIONS"; U.S. application Ser. No. 61/782,394, filed on Mar. 14, 2013, titled "INFLATABLE AIR MATTRESS SNORING DETECTION AND RESPONSE"; U.S. Application Ser. No. 61/781,296, filed on Mar. 14, 2013, titled "INFLATABLE AIR MATTRESS WITH LIGHT AND VOICE CONTROLS." The contents of each of the above-references U.S. patent applications are herein incorporated by reference in their entirety.

TECHNICAL FIELD

This patent document pertains generally to mattresses and more particularly, but not by way of limitation, to an inflatable air mattress system.

BACKGROUND

Air bed systems, such as the one described in U.S. Pat. No. 5,904,172 which is incorporated herein by reference in its entirety, generally allow a user to select a desired pressure for each air chamber within the mattress. Upon selecting the desired pressure, a signal is sent to a pump and valve assembly in order to inflate or deflate the air bladders as necessary in order to achieve approximately the desired pressure within the air bladders.

In various examples, an air mattress control system allows a user to adjust the firmness or position of an air mattress bed. The mattress may have more than one zone thereby allowing a left and right side of the mattress to be adjusted to different firmness levels. Additionally, the bed may be adjustable to different positions. For example, the head section of the bed may be raised up while the foot section of the bed stays in place. In various examples, two separate remote controls are used to adjust the position and firmness, respectively.

BRIEF DESCRIPTION OF DRAWINGS

Some embodiments are illustrated by way of example and not limitation in the figures of the accompanying drawings in which:

FIG. 1 is a diagrammatic representation of an air bed system, according to an example.

FIG. 2 is a block diagram of various components of the air bed system of FIG. 1, according to an example.

FIG. 3 is a block diagram of an air bed system architecture, according to an example.

FIG. 4 is a block diagram of machine in the example form of a computer system within which a set instructions, for causing the machine to perform any one or more of the methodologies discussed herein, may be executed.

FIG. 5 is a flow diagram depicting an example method of detecting motion of a user of an air mattress, in accordance with various techniques of this disclosure.

FIG. 6 is a flow diagram depicting an example method of detecting the presence of a user of an air mattress, in accordance with various techniques of this disclosure.

FIG. 7 is a flow diagram depicting an example method of detecting the presence of a user of an air mattress, in accordance with various techniques of this disclosure.

DETAILED DESCRIPTION

FIG. 1 is a diagrammatic representation of air bed system 10 in an example embodiment. System 10 can include bed 12, which can comprise at least one air chamber 14 surrounded by a resilient border 16 and encapsulated by bed ticking 18. The resilient border 16 can comprise any suitable material, such as foam.

As illustrated in FIG. 1, bed 12 can be a two chamber design having a first air chamber 14A and a second air chamber 14B. First and second air chambers 14A and 14B can be in fluid communication with pump 20. Pump 20 can be in electrical communication with a remote control 22 via control box 24. Remote control 22 can communicate via wired or wireless means with control box 24. Control box 24 can be configured to operate pump 20 to cause increases and decreases in the fluid pressure of first and second air chambers 14A and 14B based upon commands input by a user through remote control 22. Remote control 22 can include display 26, output selecting means 28, pressure increase button 29, and pressure decrease button 30. Output selecting means 28 can allow the user to switch the pump output between the first and second air chambers 14A and 14B, thus enabling control of multiple air chambers with a single remote control 22. For example, output selecting means may be a physical control (e.g., switch or button) or an input control displayed on display 26. Alternatively, separate remote control units can be provided for each air chamber and may each include the ability to control multiple air chambers. Pressure increase and decrease buttons 29 and 30 can allow a user to increase or decrease the pressure, respectively, in the air chamber selected with the output selecting means 28. Adjusting the pressure within the selected air chamber can cause a corresponding adjustment to the firmness of the air chamber.

FIG. 2 is a block diagram detailing data communication between certain components of air bed system 10 according to various examples. As shown in FIG. 2, control box 24 can include power supply 34, processor 36, memory 37, switching means 38, and analog to digital (A/D) converter 40. Switching means 38 can be, for example, a relay or a solid state switch. Switching means 38 can be located in the pump 20 rather than the control box 24.

Pump 20 and remote control 22 can be in two-way communication with the control box 24. Pump 20 can include a motor 42, a pump manifold 43, a relief valve 44, a first control valve 45A, a second control valve 45B, and a

pressure transducer 46, and can be fluidly connected with the first air chamber 14A and the second air chamber 14B via a first tube 48A and a second tube 48B, respectively. First and second control valves 45A and 45B can be controlled by switching means 38, and can be operable to regulate the flow of fluid between pump 20 and first and second air chambers 14A and 14B, respectively.

In an example, pump 20 and control box 24 can be provided and packaged as a single unit. Alternatively, pump 20 and control box 24 can be provided as physically separate units.

In operation, power supply 34 can receive power, such as 110 VAC power, from an external source and can convert the power to various forms required by certain components of the air bed system 10. Processor 36 can be used to control various logic sequences associated with operation of the air bed system 10, as will be discussed in further detail below.

The example of the air bed system 10 shown in FIG. 2 contemplates two air chambers 14A and 14B and a single pump 20. However, other examples may include an air bed system having two or more air chambers and one or more pumps incorporated into the air bed system to control the air chambers. In an example, a separate pump can be associated with each air chamber of the air bed system or a pump may be associated with multiple chambers of the air bed system. Separate pumps can allow each air chamber to be inflated or deflated independently and simultaneously. Furthermore, additional pressure transducers can also be incorporated into the air bed system such that, for example, a separate pressure transducer can be associated with each air chamber.

In the event that the processor 36 sends a decrease pressure command to one of air chambers 14A or 14B, switching means 38 can be used to convert the low voltage command signals sent by processor 36 to higher operating voltages sufficient to operate relief valve 44 of pump 20 and open control valves 45A or 45B. Opening relief valve 44 can allow air to escape from air chamber 14A or 14B through the respective air tube 48A or 48B. During deflation, pressure transducer 46 can send pressure readings to processor 36 via the A/D converter 40. The A/D converter 40 can receive analog information from pressure transducer 46 and can convert the analog information to digital information useable by processor 36. Processor 36 may send the digital signal to remote control 22 to update display 26 on the remote control in order to convey the pressure information to the user.

In the event that processor 36 sends an increase pressure command, pump motor 42 can be energized, sending air to the designated air chamber through air tube 48A or 48B via electronically operating corresponding valve 45A or 45B. While air is being delivered to the designated air chamber in order to increase the firmness of the chamber, pressure transducer 46 can sense pressure within pump manifold 43. Again, pressure transducer 46 can send pressure readings to processor 36 via A/D converter 40. Processor 36 can use the information received from A/D converter 40 to determine the difference between the actual pressure in air chamber 14A or 14B and the desired pressure. Processor 36 can send the digital signal to remote control 22 to update display 26 on the remote control in order to convey the pressure information to the user.

Generally speaking, during an inflation or deflation process, the pressure sensed within pump manifold 43 provides an approximation of the pressure within the air chamber. An example method of obtaining a pump manifold pressure reading that is substantially equivalent to the actual pressure within an air chamber is to turn off pump 20, allow the

pressure within the air chamber 14A or 14B and pump manifold 43 to equalize, and then sense the pressure within pump manifold 43 with pressure transducer 46. Thus, providing a sufficient amount of time to allow the pressures within pump manifold 43 and chamber 14A or 14B to equalize may result in pressure readings that are accurate approximations of the actual pressure within air chamber 14A or 14B. In various examples, the pressure of 48A/B is continuously monitored using multiple pressure sensors.

In an example, another method of obtaining a pump manifold pressure reading that is substantially equivalent to the actual pressure within an air chamber is through the use of a pressure adjustment algorithm. In general, the method can function by approximating the air chamber pressure based upon a mathematical relationship between the air chamber pressure and the pressure measured within pump manifold 43 (during both an inflation cycle and a deflation cycle), thereby eliminating the need to turn off pump 20 in order to obtain a substantially accurate approximation of the air chamber pressure. As a result, a desired pressure setpoint within air chamber 14A or 14B can be achieved without the need for turning pump 20 off to allow the pressures to equalize. The latter method of approximating an air chamber pressure using mathematical relationships between the air chamber pressure and the pump manifold pressure is described in detail in U.S. application Ser. No. 12/936,084, the entirety of which is incorporated herein by reference.

FIG. 3 illustrates an example air bed system architecture 300. Architecture 300 includes bed 301, central controller 302, firmness controller 304, articulation controller 306, temperature controller 308 in communication with one or more temperature sensors 309, external network device 310, remote controllers 312, 314, and voice controller 316. While described as using an air bed, the system architecture may also be used with other types of beds.

As illustrated in FIG. 3, network bed architecture 300 is configured as a star topology with central controller 302 and firmness controller 304 functioning as the hub and articulation controller 306, temperature controller 308, external network device 310, remote controls 312, 314, and voice controller 316 functioning as possible spokes, also referred to herein as components. Thus, in various examples, central controller 302 acts a relay between the various components.

In yet another example, central controller 302 listens to communications (e.g., control signals) between components even if the communication is not being relayed through central controller 302. For example, consider a user sending a command using remote 312 to temperature controller 308. Central controller 302 may listen for the command and check to determine if instructions are stored at central controller 302 to override the command (e.g., it conflicts with a previous setting). Central controller 302 may also log the command for future use (e.g., determining a pattern of user preferences for the components).

In other examples, different topologies may be used. For example, the components and central controller 302 may be configured as a mesh network in which each component may communicate with one or all of the other components directly, bypassing central controller 302. In various examples, a combination of topologies may be used. For example, remote controller 312 may communicate directly to temperature controller 308 but also relay the communication to central controller 302.

In various examples, the controllers and devices illustrated in FIG. 3 may each include a processor, a storage device, and a network interface. The processor may be a general purpose central processing unit (CPU) or applica-

tion-specific integrated circuit (ASIC). The storage device may include volatile or non-volatile static storage (e.g., Flash memory, RAM, EPROM, etc.). The storage device may store instructions which, when executed by the processor, configure the processor to perform the functionality described herein. For example, a processor of firmness control **304** may be configured to send a command to a relief valve to decrease the pressure in a bed.

In various examples, the network interface of the components may be configured to transmit and receive communications in a variety of wired and wireless protocols. For example, the network interface may be configured to use the 802.11 standards (e.g., 802.11a/b/c/g/n/ac), PAN network standards such as 802.15.4 or Bluetooth, infrared, cellular standards (e.g., 3G/4G etc.), Ethernet, and USB for receiving and transmitting data. The previous list is not intended to be exhaustive and other protocols may be used. Not all components of FIG. 3 need to be configured to use the same protocols. For example, remote control **312** may communicate with central controller **302** via Bluetooth while temperature controller **308** and articulation controller **306** are connected to central controller using 802.15.4. Within FIG. 3, the lightning connectors represent wireless connections and the solid lines represent wired connections, however, the connections between the components is not limited to such connections and each connection may be wired or wireless.

Moreover, in various examples, the processor, storage device, and network interface of a component may be located in different locations than various elements used to affect a command. For example, as in FIG. 1, firmness controller **302** may have a pump that is housed in a separate enclosure than the processor used to control the pump. Similar separation of elements may be employed for the other controllers and devices in FIG. 3.

In various examples, firmness controller **304** is configured to regulate pressure in an air mattress. For example, firmness controller **304** may include a pump such as described with reference to FIG. 2 (see e.g., pump **20**). Thus, in an example, firmness controller **304** may respond to commands to increase or decrease pressure in the air mattress. The commands may be received from another component or based on stored application instructions that are part of firmness controller **304**.

As illustrated in FIG. 3 central controller **302** includes firmness controller **304** and pump **305**. Thus, in an example, the processor of central controller **302** and firmness control **304** may be the same processor. Furthermore, the pump may also be part of central controller **302**. Accordingly, central controller **302** may be responsible for pressure regulation as well as other functionality as described in further portions of this disclosure.

In various examples, articulation controller **306** is configured to adjust the position of a bed (e.g., bed **301**) by adjusting the foundation that supports the bed. In an example, separate positions may be set for two different beds (e.g., two twin beds placed next to each other). The foundation may include more than one zone that may be independently adjusted. Articulation control **306** may also be configured to provide different levels of massage to a person on the bed.

In various examples, temperature controller **308** is configured to increase, decrease, or maintain the temperature of a user. For example, a pad may be placed on top of or be part of the air mattress. Air may be pushed through the pad and vented to cool off a user of the bed. Conversely, the pad may include a heating element that may be used to keep the user warm. In various examples, the pad includes the temperature

sensor **309** and temperature controller **308** receives temperature readings from the temperature sensor **309**. In other examples, the temperature sensor **309** can be separate from the pad, e.g., part of the air mattress or foundation.

In various examples, additional controllers may communicate with central controller **302**. These controllers may include, but are not limited to, illumination controllers for turning on and off light elements placed on and around the bed and outlet controllers for controlling power to one or more power outlets.

In various examples, external network device **310**, remote controllers **312**, **314** and voice controller **316** may be used to input commands (e.g., from a user or remote system) to control one or more components of architecture **300**. The commands may be transmitted from one of the controllers **312**, **314**, or **316** and received in central controller **302**. Central controller **302** may process the command to determine the appropriate component to route the received command. For example, each command sent via one of controllers **312**, **314**, or **316** may include a header or other metadata that indicates which component the command is for. Central controller **302** may then transmit the command via central controller **302**'s network interface to the appropriate component. In some examples, the commands may be transmitted to one or more cloud-based servers for processing.

For example, a user may input a desired temperature for the user's bed into remote control **312**. The desired temperature may be encapsulated in a command data structure that includes the temperature as well as identifies temperature controller **308** as the desired component to be controlled. The command data structure may then be transmitted via Bluetooth to central controller **302**. In various examples, the command data structure is encrypted before being transmitted. Central controller **302** may parse the command data structure and relay the command to temperature controller **308** using a PAN. Temperature controller **308** may be then configured its elements to increase or decrease the temperature of the pad depending on the temperature originally input into remote control **312**.

In various examples, data may be transmitted from a component back to one or more of the remote controls. For example, the current temperature as determined by a sensor element of temperature controller **308**, e.g., temperature sensor **309**, the pressure of the bed, the current position of the foundation or other information may be transmitted to central controller **302**. Central controller **302** may then transmit the received information and transmit it to remote control **312** where it may be displayed to the user.

In various examples, multiple types of devices may be used to input commands to control the components of architecture **300**. For example, remote control **312** may be a mobile device such as a smart phone or tablet computer running an application. Other examples of remote control **312** may include a dedicated device for interacting with the components described herein. In various examples, remote controls **312/314** include a display device for displaying an interface to a user. Remote control **312/314** may also include one or more input devices. Input devices may include, but are not limited to, keypads, touchscreen, gesture, motion and voice controls.

Remote control **314** may be a single component remote configured to interact with one component of the mattress architecture. For example, remote control **314** may be configured to accept inputs to increase or decrease the air mattress pressure. Voice controller **316** may be configured to accept voice commands to control one or more components.

In various examples, more than one of the remote controls **312/314** and voice controller **316** may be used.

With respect to remote control **312**, the application may be configured to pair with one or more central controllers. For each central controller, data may be transmitted to the mobile device that includes a list of components linked with the central controller. For example, consider that remote control **312** is a mobile phone and that the application has been authenticated and paired with central controller **302**. Remote control **312** may transmit a discovery request to central controller **302** to inquiry about other components and available services, e.g., services or components available in the cloud. In response, central controller **302** may transmit a list of services that includes available functions for adjusting the firmness of the bed, position of the bed, and temperature of the bed. In various embodiments, the application may then display functions for increasing/decreasing pressure of the air mattress, adjusting positions of the bed, and adjusting temperature. If components are added/removed to the architecture under control of central controller **302**, an updated list may be transmitted to remote control **312** and the interface of the application may be adjusted accordingly.

In various examples, central controller **302** is configured as a distributor of software updates to components in architecture **300**. For example, a firmware update for temperature controller **308** may become available. The update may be loaded into a storage device of central controller **302** (e.g., via a USB interface, a smartphone over Bluetooth, and from the cloud over WiFi). In wireless applications, the central controller **302** may, for example, receive updates from the cloud either from wifi or from a mobile connection over Bluetooth. Central controller **302** may then transmit the update to temperature controller **308** with instructions to update. Temperature controller **308** may attempt to install the update. A status message may be transmitted from temperature controller **308** to central controller **302** indicating the success or failure of the update.

In various examples, central controller **302** is configured to analyze data collected by a pressure transducer (e.g., transducer **46** with respect to FIG. 2) to determine various states of a person lying on the bed. For example, central controller **302** may determine the heart rate or respiration rate of a person lying in the bed. Additional processing may be done using the collected data to determine a possible sleep state of the person. For example, central controller **302** may determine when a person falls asleep and, while asleep, the various sleep states of the person.

In various examples, external network device **310** includes a network interface to interact with an external server for processing and storage of data related to components in architecture **300**. For example, the determined sleep data as described above may be transmitted via a network (e.g., the Internet) from central controller **302** to external network device **310** for storage. In an example, the pressure transducer data may be transmitted to the external server for additional analysis. The external network device **310** may also analyze and filter the data before transmitting it to the external server.

In an example, diagnostic data of the components may also be routed to external network device **310** for storage and diagnosis on the external server. For example, if temperature controller **308** detects an abnormal temperature reading (e.g., a drop in temperature over one minute that exceeds a set threshold) diagnostic data (sensor readings, current settings, etc.) may be wireless transmitted from temperature controller **308** to central controller **302**. Central controller

302 may then transmit this data via USB to external network device **310**. External device **310** may wirelessly transmit the information to a WLAN access point where it is routed to the external server for analysis. In some examples, the external device **310** can transmit a message to a customer service division to initiate a repair call if necessary.

Example Machine Architecture and Machine-Readable Medium

FIG. 4 is a block diagram of machine in the example form of a computer system **400** within which instructions, for causing the machine to perform any one or more of the methodologies discussed herein, may be executed. In alternative embodiments, the machine operates as a standalone device or may be connected (e.g., networked) to other machines. In a networked deployment, the machine may operate in the capacity of a server or a client machine in server-client network environment, or as a peer machine in a peer-to-peer (or distributed) network environment. The machine may be a personal computer (PC), a tablet PC, a set-top box (STB), a Personal Digital Assistant (PDA), a cellular telephone, a web appliance, a network router, switch or bridge, or any machine capable of executing instructions (sequential or otherwise) that specify actions to be taken by that machine. Further, while only a single machine is illustrated, the term “machine” shall also be taken to include any collection of machines that individually or jointly execute a set (or multiple sets) of instructions to perform any one or more of the methodologies discussed herein.

The example computer system **400** includes a processor **402** (e.g., a central processing unit (CPU), a graphics processing unit (GPU), ASIC or a combination), a main memory **404** and a static memory **406**, which communicate with each other via a bus **408**. The computer system **400** may further include a video display unit **410** (e.g., a liquid crystal display (LCD) or a cathode ray tube (CRT)). The computer system **400** also includes an alphanumeric input device **412** (e.g., a keyboard and/or touchscreen), a user interface (UI) navigation device **414** (e.g., a mouse), a disk drive unit **416**, a signal generation device **418** (e.g., a speaker) and a network interface device **420**.

Machine-Readable Medium

The disk drive unit **416** includes a machine-readable medium **422** on which is stored one or more sets of instructions and data structures (e.g., software) **424** embodying or utilized by any one or more of the methodologies or functions described herein. The instructions **424** may also reside, completely or at least partially, within the main memory **404** and/or within the processor **402** during execution thereof by the computer system **400**, the main memory **404** and the processor **402** also constituting machine-readable media.

While the machine-readable medium **422** is shown in an example embodiment to be a single medium, the term “machine-readable medium” may include a single medium or multiple media (e.g., a centralized or distributed database, and/or associated caches and servers) that store the one or more instructions or data structures. The term “machine-readable medium” shall also be taken to include any tangible medium that is capable of storing, encoding or carrying instructions for execution by the machine and that cause the machine to perform any one or more of the methodologies of the present invention, or that is capable of storing, encoding or carrying data structures utilized by or associated with such instructions. The term “machine-readable medium” shall accordingly be taken to include, but not be limited to, solid-state memories, and optical and magnetic media. Specific examples of machine-readable media include non-volatile memory, including by way of example

semiconductor memory devices, e.g., Erasable Programmable Read-Only Memory (EPROM), Electrically Erasable Programmable Read-Only Memory (EEPROM), and flash memory devices; magnetic disks such as internal hard disks and removable disks; magneto-optical disks; and CD-ROM and DVD-ROM disks.

Transmission Medium

The instructions **424** may further be transmitted or received over a communications network **426** using a transmission medium. The instructions **424** may be transmitted using the network interface device **420** and any one of a number of well-known transfer protocols (e.g., HTTP). Examples of communication networks include a local area network (“LAN”), a wide area network (“WAN”), the Internet, mobile telephone networks, Plain Old Telephone (POTS) networks, and wireless data networks (e.g., WiFi and WiMax networks). The term “transmission medium” shall be taken to include any intangible medium that is capable of storing, encoding or carrying instructions for execution by the machine, and includes digital or analog communications signals or other intangible media to facilitate communication of such software.

Detection Techniques

In addition to the techniques described above, this disclosure is directed to techniques for detection of various aspects of a user of system architecture **300**. As described in more detail below, user sleeping motion, user presence, and/or user sleeping position can be detected using various techniques described in this disclosure

Regarding sleeping motion detection, the system architecture **300** can detect the motion of a user while the user is sleeping (“sleeping motion”) and determine from the detected motion the restlessness of the user. Using the determined restlessness, the system architecture **300** and, in particular, the central controller **302** can determine a sleep quality metric, index, number, or the like. In one example, the user can query the system architecture **300** to retrieve a previously determined sleep quality metric. In another example, the system architecture **300** can determine the sleep quality metric when queried by the user. In yet another example, the system architecture **300** can automatically, e.g., without user intervention, determine and report a sleep quality metric to the user, e.g., via a display.

In accordance with this disclosure, the central controller **302** can detect user sleeping motion via pressure changes. For example, the pressure transducer **46** (of FIG. 2) can be used to monitor the air pressure in the air mattress of the bed **301**. If the user on the air mattress is not moving, the air pressure in the mattress can be substantially constant and, as such, the pressure transducer **46** and the central controller **302** will measure no significant pressure changes. When the user on the air mattress is moving, however, the air pressure in the mattress can fluctuate and, as such, the pressure transducer **46** and the central controller **302** can measure pressure changes. Thus, pressure changes measured by the pressure transducer **46** and the central controller **302** can indicate motion of the user on the air mattress.

In one example implementation, the central controller **302** can execute instructions that cause the pressure transducer **46** to measure air pressure values at a sample rate. In one example, the central controller **302** can store the sampled air pressure values in a memory device. Using a moving (or rolling) average (or other central tendency), for example, the central controller **302** can determine average (or other central tendency) air pressure values and then determine whether the user has moved on the air mattress based on the rolling average. When the user is stationary, the rolling

average will be substantially constant, e.g., no pressure changes. When the user moves, e.g., rolls to the side, the air pressure values may fluctuate, thereby changing the value of the rolling average. The central controller **302** can calculate a difference between the rolling average values and determine that the user is moving based on the calculated difference. In some examples, the central controller **302** can initiate a timer using the rolling average values in order to determine how long the user was moving. For example, the central controller **302** can initiate a timer when the rolling average value exceeded a specified value and stop the timer when the rolling average value drops below the specified value. The accumulated time of the timer indicates how long the user was restless during their sleep.

As indicated above, the central controller **302** can determine a user’s sleep state, e.g., rapid eye movement (“REM”) or non-rapid eye movement (“NREM”). The central controller **302** can determine a user’s sleep state by using various biometric signals such as heart rate, respiration, and/or movement of the user. Techniques for monitoring a user’s sleep using heart rate information, respiration rate information, and other user information are disclosed in U.S. Patent Application Publication No. 20100170043 to Steven J. Young et al., titled “APPARATUS FOR MONITORING VITAL SIGNS,” the entire content of which is incorporated herein by reference. Using the techniques described above, the central controller **302** can detect user motion and correlate the detected motion with a determined sleep state.

FIG. 5 is a flow diagram depicting an example method of detecting motion of a user of an air mattress. In FIG. 5, the central controller **302** executes instructions that cause the pressure transducer **46** to measure air pressure values at a sample rate (**500**). The central controller **302** determines rolling average values, for example, based on the measured air pressure values (**502**). The central controller **302** calculates a difference value between the rolling average values and determines a pressure change based on calculated differences (**504**). The central controller **302** compares the determined pressure change to a threshold value, e.g., stored in a memory device, and determines that the user is moving if the determined pressure change is above the threshold value (**506**). In this manner, the central controller can detect sleeping motion of a user.

In some implementations, the example method shown in FIG. 5 further includes the optional act of the central controller **302** determining a sleep state, e.g., REM or NREM, of the user.

In addition to the techniques described above, this disclosure is directed to techniques for detecting whether a user is present on the bed **301**. In one example implementation, the central controller **302** can detect user presence via gross pressure changes. For example, the central controller **302** and the pressure transducer **46** (of FIG. 2) can be used to monitor the air pressure in the air mattress of the bed **301**. If the user sits or lies down on the air mattress, the air pressure in the air mattress changes, e.g., increases, due to the additional weight of the user, which results in a gross pressure change. The central controller **302** can determine whether the user is now on the bed based on the gross pressure change, e.g., over some time period. For example, by determining a rate of change of pressure, e.g., over 1-10 minutes, and comparing the determined rate of change to a threshold value, the central controller can determine whether the user is now on the bed.

Similarly, if the user is on the bed and then gets out of bed, the air pressure in the air mattress changes, e.g., decreases, which results in a gross pressure change. The central con-

11

troller **302** can determine whether the user left the bed based on the gross pressure change, e.g., over some time period. For example, by determining a rate of change of pressure, e.g., over 1-10 minutes, and comparing the determined rate of change to a threshold value, the central controller **302** can determine whether the user left the bed.

In some example implementations, the techniques for detecting whether a user is present on the bed **301** can be combined with the techniques for detecting user movement described above. For example, in addition to determining a rate of change of pressure and comparing the determined rate of change to a threshold value in order to determine whether the user is in or out of the bed **301**, the central controller **302** can also use the rolling average techniques described above to detect user movement. For instance, if the central controller **302** determines that a rate of change of pressure is greater than a threshold value, thereby indicating that a user has either gotten into or out of the bed **301**, the central controller **302** can further analyze rolling averages of received air pressure values from the pressure transducer **46** (of FIG. 2) to confirm that the user is in the bed **301**. If the rolling averages fluctuate, as would be consistent with movement of the user, then the central controller **302** can determine that the user is in the bed **301**.

FIG. 6 is a flow diagram depicting an example method of detecting the presence of a user of an air mattress. In FIG. 6, the central controller **302** executes instructions that cause the pressure transducer **46** to measure air pressure values at a sample rate (**600**). The central controller **302** determines a rate of gross pressure change, for example, based on the measured air pressure values (**602**). Then, the central controller **302** compares the determined rate of change to a threshold value (**604**). If the central controller **302** determines that the rate of change is greater than a threshold value, the central controller **302** determines that the user has either transitioned into or out of the bed **301**. If the rate of change is negative, then the central controller determines that the user has gotten out of bed. In this manner, the central controller can detect the presence or absence of a user.

In some examples, the central controller **302** can confirm the presence of the user in the bed **301**, as shown in the optional steps **606-610** of FIG. 6. To determine that the user remains in the bed **301**, the central controller **302** determines rolling average values, for example, based on the measured air pressure values (**606**). The central controller **302** calculates a difference value between the rolling average values and determines a pressure change based on calculated differences (**608**). The central controller **302** compares the determined pressure change to a threshold value, e.g., stored in a memory device, and determines that the user is moving if the determined pressure change is above the threshold value (**610**). The threshold value may be a static value, e.g., a specified or fixed value, or a dynamic value, e.g., a value that adjusts over time.

In some examples, the central controller **302** can detect user presence using instantaneous pressure changes. Then, presence can be verified via the detection of known biometric signals, for example.

In one example implementation, the central controller **302** can detect user presence using temperature changes detected in the mattress, e.g., using one or more temperature sensors positioned in or on the mattress. The temperature sensors and the central controller **302** can detect a rise in temperature, e.g., over a specified period of time, and determine that a user is present in the bed. For example, if the central controller **302** detects a rise in temperature and then determines that the detected rise in temperature was not caused by

12

the system's temperature controller **308**, the central controller **302** can determine that the user is present.

In addition to the techniques described above, this disclosure is directed to techniques for detecting a sleeping position of a user of the bed **301**, e.g., lying on a side, lying on a back, lying on a front. In one example implementation, the central controller **302** can determine a sleeping position of the user by first detecting user movement, e.g., via changes in a rolling average, and then a gross pressure change, as described in more detail below.

In one example implementation, the central controller **302** can execute instructions that cause the pressure transducer **46** to measure air pressure values at a sample rate. In one example, the central controller **302** can store the sampled air pressure values in a memory device. Using a moving (or rolling) average, for example, the central controller **302** can determine average (or other central tendency) air pressure values and then determine whether the user has moved on the air mattress based on the rolling average. That is, when the user is stationary, the rolling average will be substantially constant, e.g., no pressure changes. When the user moves, e.g., rolls to the side, the air pressure values may fluctuate, thereby changing the value of the rolling average. The central controller **302** can calculate a difference between the rolling average values and determine that the user is moving based on the calculated difference.

Once the movement has substantially stopped, the central controller **302** can determine a gross pressure change from the measured air pressure values to determine whether the user is on their side, back, or front. That is, because the pressure in an air mattress is different depending on whether the user is lying on their side, back, or front, the central controller **302** can determine a gross pressure change based on the air pressure in the air mattress before and after the detected movement. If the gross pressure change is positive and within a range of values, then the central controller **302** determines that the user has moved from their back to their side, for example. If the gross pressure change is negative and within a range of values, then the central controller **302** determines that the user has moved from their side to their back, for example. In this manner, the central controller **302** can determine a sleeping position of a user.

In addition, the central controller **302** can use biometric data to determine a sleeping position of the user. That is, because the received respiration rate signal, heart rate signal, and/or other biometric signals of the user may be different depending on whether the user is lying on their side, back, or front, the central controller **302** can determine a sleeping position based on the received biometric signals.

FIG. 7 is a flow diagram depicting an example method of detecting the presence of a user of an air mattress. In FIG. 7, the central controller **302** executes instructions that cause the pressure transducer **46** to measure air pressure values at a sample rate (**700**). The central controller **302** determines rolling average values, for example, based on the measured air pressure values (**702**). The central controller **302** calculates a difference value between the rolling average values and determines a pressure change based on calculated differences (**704**). The central controller **302** compares the determined pressure change to a threshold value, e.g., stored in a memory device, and determines that the user is moving, e.g., from their front to their side, if the determined pressure change is above the threshold value (**706**).

The central controller **302** determines a gross pressure change value, for example, based on the measured air pressure values (**708**) before and after the user movement. Then, the central controller **302** compares the determined

13

gross pressure change to a range of values (710). If the gross pressure change is positive and within the range of values, then the central controller 302 determines that the user has moved from their back to their side, for example. If the gross pressure change is negative and within a range of values, then the central controller 302 determines that the user has moved from their side to their back, for example. In this manner, the central controller 302 can determine a sleeping position of a user.

Although an embodiment has been described with reference to specific example embodiments, it will be evident that various modifications and changes may be made to these embodiments without departing from the broader spirit and scope of the invention. Accordingly, the specification and drawings are to be regarded in an illustrative rather than a restrictive sense. The accompanying drawings that form a part hereof, show by way of illustration, and not of limitation, specific embodiments in which the subject matter may be practiced. The embodiments illustrated are described in sufficient detail to enable those skilled in the art to practice the teachings disclosed herein. Other embodiments may be utilized and derived therefrom, such that structural and logical substitutions and changes may be made without departing from the scope of this disclosure. This Detailed Description, therefore, is not to be taken in a limiting sense, and the scope of various embodiments is defined only by the appended claims, along with the full range of equivalents to which such claims are entitled. As it common, the terms “a” and “an” may refer to one or more unless otherwise indicated.

The invention claimed is:

1. A method comprising:

receiving, at a central controller of an air mattress system having a mattress comprising a first-side to support a first-side user and a second-side to simultaneously support a second-side user, a plurality of air pressure values from a single pressure sensor configured to sense pressure changes on the mattress i) in the first-side caused by the first-side user laying on the mattress and also ii) in the second-side caused by the second-side user laying on the mattress, wherein the mattress comprises a first chamber and a second chamber, the first chamber corresponding to the first-side of the air mattress and the second chamber corresponding to the second-side of the air mattress;

determining a plurality of average values using the plurality of the received air pressure values;

calculating a difference value between a first one of the plurality of average values and a second one of the plurality of average values;

comparing the difference value to a threshold value; and simultaneously:

determining, based on the comparison, whether the first-side user of the air mattress system is present on the air mattress system;

determining, based on the comparison, whether the first-side user of the air mattress system moved;

determining, based on the comparison, whether the second-side user of the air mattress system is present on the air mattress system; and

determining, based on the comparison, whether the second-side user of the air mattress system moved.

2. The method of claim 1, wherein the plurality of average values comprises a rolling average of pressure values.

3. The method of claim 2, wherein the plurality of average values further comprises variations in the rolling average of pressure values.

14

4. The method of claim 1, wherein determining whether the first-side user of the air mattress system moved further comprises determining the first-side user's sleep state out of a group of possible sleep states.

5. The method of claim 4, wherein the group of possible sleep states includes, but is not limited to, a Rapid Eye Movement (REM) state and a Non-Rapid Eye Movement (NREM) state.

6. The method of claim 1, wherein determining whether the first-side user of the air mattress system moved further comprises determining the first-side user's sleep position out of a group of possible sleep positions.

7. The method of claim 6, wherein the group of possible sleep positions includes, but is not limited to, a laying-on-side sleep position, a laying-on-back sleep position, and a laying-on-front sleep position.

8. A system comprising:

a mattress having a first-side to support a first-side user and a second-side to simultaneously support a second-side user, wherein the mattress comprises a first chamber and a second chamber, the first chamber corresponding to the first-side of the mattress and the second chamber corresponding to the second-side of the mattress;

a single pressure sensor, the pressure sensor configured to sense pressure changes on the mattress i) in the first-side caused by the first-side user laying on the mattress and also ii) in the second-side caused by the second-side user laying on the mattress;

a processor configured to:

receive, from the pressure sensor, a plurality of pressure values;

calculate, from the plurality of pressure values, a plurality of calculated values; and

simultaneously:

classify, using the plurality of calculated values, the first-side user into one of two or more possible movement classifications;

classify, using the plurality of calculated values, the first-side user into one of two or more possible presence classifications;

classify, using the plurality of calculated values, the second-side user into one of two or more possible movement classifications; and

classify, using the plurality of calculated values, the second-side user into one of two or more possible presence classifications.

9. The system of claim 8, wherein the plurality of calculated values comprises a rolling average of pressure values.

10. The system of claim 9, wherein the plurality of calculated values further comprises variations in the rolling average of pressure values.

11. The system of claim 8, wherein the processor is further configured to simultaneously determine the first-side user's sleep state out of a group of possible sleep states.

12. The system of claim 11, wherein the group of possible sleep states includes, but is not limited to, a Rapid Eye Movement (REM) state and a Non-Rapid Eye Movement (NREM) state.

13. The system of claim 8, wherein the processor is further configured to simultaneously determine the first-side user's sleep position out of a group of possible sleep positions.

14. The system of claim 13, wherein the group of possible sleep positions includes, but is not limited to, a laying-on-side sleep position, a laying-on-back sleep position, and a laying-on-front sleep position.

15

15. The system of claim **8**, the system further comprising:
a first-side tube that fluidly connects the single pressure
sensor to the first-side;
a second-side tube that fluidly connects the single pres-
sure sensor to the second-side; 5
a first-side valve and a second-side valve operable to
regulate flow of fluid in the first-side tube and the
second-side tube.

16. The system of claim **8**, wherein the plurality of
pressure values comprise both i) some pressure values 10
corresponding to the first-side tube and ii) some other
pressure values corresponding to the second-side tube.

* * * * *

16