

US011123101B2

(12) **United States Patent**  
**Sgroi, Jr.**

(10) **Patent No.:** **US 11,123,101 B2**  
(45) **Date of Patent:** **Sep. 21, 2021**

(54) **RETAINING MECHANISMS FOR TROCAR ASSEMBLIES**

(71) Applicant: **Covidien LP**, Mansfield, MA (US)

(72) Inventor: **Anthony Sgroi, Jr.**, Wallingford, CT (US)

(73) Assignee: **Covidien LP**, Mansfield, MA (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 166 days.

(21) Appl. No.: **16/503,838**

(22) Filed: **Jul. 5, 2019**

(65) **Prior Publication Data**

US 2021/0000500 A1 Jan. 7, 2021

(51) **Int. Cl.**  
**A61B 17/34** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **A61B 17/3421** (2013.01); **A61B 17/3476** (2013.01); **A61B 2017/347** (2013.01); **A61B 2017/348** (2013.01); **A61B 2017/3435** (2013.01)

(58) **Field of Classification Search**

CPC ..... A61B 17/1155; A61B 2017/00486; A61B 17/115; A61B 17/3421; A61B 17/3476; A61B 2017/00371; A61B 2017/00384; A61B 2017/0046; A61B 2017/00473; A61B 2017/00477; A61B 2017/0053; A61B 2017/00862; A61B 2017/07257; A61B 2017/07271; A61B 2017/3435; A61B 2017/347; A61B 2017/348; A61B 17/3423; A61B 17/3439; A61B 17/3468;

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,777,340 A 1/1957 Hettwer et al.  
2,957,353 A 10/1960 Babacz  
3,111,328 A 11/1963 Di Rito et al.  
(Continued)

FOREIGN PATENT DOCUMENTS

CA 908529 A 8/1972  
CA 2451558 A1 1/2003  
(Continued)

OTHER PUBLICATIONS

European Search Report dated Nov. 27, 2020, issued in corresponding EP Appln. No. 20183904, 12 pages.  
(Continued)

*Primary Examiner* — Robert A Lynch


*Assistant Examiner* — Alyssa M Keane

(74) *Attorney, Agent, or Firm* — Carter, DeLuca & Farrell LLP

(57) **ABSTRACT**

An adapter assembly includes a sleeve, a trocar assembly releasably securable within the sleeve, and a retaining mechanism configured to releasably secure the trocar assembly within the sleeve. The retaining mechanism includes a retaining block, a cam wire moveably positioned relative to the retaining block between a lock position and a release position, a retaining block extension for maintaining the cam wire relative to the retaining block, a button member in operable engagement with the cam wire, and a pair of retaining members. The button member includes a center beam moveable from an unflexed position in engagement with a stop tab of the retaining block extension to prevent movement of the button member to a flexed position out of alignment with the stop tab to permit movement of the button member.

**20 Claims, 15 Drawing Sheets**







(56)

## References Cited

## U.S. PATENT DOCUMENTS

5,658,300	A	8/1997	Bito et al.	6,315,184	B1	11/2001	Whitman
5,662,662	A	9/1997	Bishop et al.	6,321,855	B1	11/2001	Barnes
5,667,517	A	9/1997	Hooven	6,329,778	B1	12/2001	Culp et al.
5,669,918	A	9/1997	Balazs et al.	6,338,737	B1	1/2002	Toledano
5,685,474	A	11/1997	Seeber	6,343,731	B1	2/2002	Adams et al.
5,693,042	A	12/1997	Boiarski et al.	6,348,061	B1	2/2002	Whitman
5,704,534	A	1/1998	Huitema et al.	6,368,324	B1	4/2002	Dinger
5,709,335	A	1/1998	Heck	6,371,909	B1	4/2002	Hoeg et al.
5,713,505	A	2/1998	Huitema	6,387,105	B1	5/2002	Gifford, III et al.
5,715,987	A	2/1998	Kelley et al.	6,398,795	B1	6/2002	McAlister et al.
5,718,360	A	2/1998	Green et al.	6,402,008	B1	6/2002	Lucas
5,720,755	A	2/1998	Dakov	6,434,507	B1	8/2002	Clayton et al.
5,732,872	A	3/1998	Bolduc et al.	6,439,446	B1	8/2002	Perry et al.
5,749,896	A	5/1998	Cook	6,443,973	B1	9/2002	Whitman
5,758,814	A	6/1998	Gallagher et al.	6,450,390	B2	9/2002	Heck et al.
5,762,603	A	6/1998	Thompson	6,461,372	B1	10/2002	Jensen et al.
5,779,130	A	7/1998	Alesi et al.	6,478,210	B2	11/2002	Adams et al.
5,782,396	A	7/1998	Mastri et al.	6,488,197	B1	12/2002	Whitman
5,782,397	A	7/1998	Koukline	6,491,201	B1	12/2002	Whitman
5,792,573	A	8/1998	Pitzen et al.	6,494,877	B2	12/2002	Odell et al.
5,797,536	A	8/1998	Smith et al.	6,503,259	B2	1/2003	Huxel et al.
5,799,857	A	9/1998	Robertson et al.	6,517,566	B1	2/2003	Hovland et al.
5,814,055	A	9/1998	Knodel et al.	6,520,398	B2	2/2003	Nicolo
5,820,009	A	10/1998	Melling et al.	6,533,157	B1	3/2003	Whitman
5,833,698	A	11/1998	Hinchliffe et al.	6,537,280	B2	3/2003	Dinger et al.
5,836,503	A	11/1998	Ehrenfels et al.	6,551,334	B2	4/2003	Blatter et al.
5,839,639	A	11/1998	Sauer et al.	6,578,751	B2	6/2003	Hartwick
5,855,312	A	1/1999	Toledano	6,585,144	B2	7/2003	Adams et al.
5,860,581	A	1/1999	Robertson et al.	6,588,643	B2	7/2003	Bolduc et al.
5,863,159	A	1/1999	Lasko	6,592,596	B1	7/2003	Geitz
5,868,760	A	2/1999	McGuckin, Jr.	6,601,749	B2	8/2003	Sullivan et al.
5,881,943	A	3/1999	Heck	6,605,078	B2	8/2003	Adams
5,908,427	A	6/1999	McKean et al.	6,605,098	B2	8/2003	Nobis et al.
5,915,616	A	6/1999	Viola et al.	6,610,066	B2	8/2003	Dinger et al.
5,947,363	A	9/1999	Bolduc et al.	6,611,793	B1	8/2003	Burnside et al.
5,951,576	A	9/1999	Wakabayashi	6,626,921	B2	9/2003	Blatter et al.
5,954,259	A	9/1999	Viola et al.	6,629,630	B2	10/2003	Adams
5,957,363	A	9/1999	Heck	6,631,837	B1	10/2003	Heck
5,964,774	A	10/1999	McKean et al.	6,632,227	B2	10/2003	Adams
5,993,454	A	11/1999	Longo	6,632,237	B2	10/2003	Ben-David et al.
5,993,468	A	11/1999	Rygaard	6,645,218	B1	11/2003	Cassidy et al.
6,010,054	A	1/2000	Johnson et al.	6,652,542	B2	11/2003	Blatter et al.
6,017,354	A	1/2000	Culp et al.	6,654,999	B2	12/2003	Stoddard et al.
6,024,748	A	2/2000	Manzo et al.	6,659,327	B2	12/2003	Heck et al.
6,032,849	A	3/2000	Mastri et al.	6,676,671	B2	1/2004	Robertson et al.
6,045,560	A	4/2000	McKean et al.	6,681,979	B2	1/2004	Whitman
6,050,472	A	4/2000	Shibata	6,685,079	B2	2/2004	Sharma et al.
6,053,390	A	4/2000	Green et al.	6,695,198	B2	2/2004	Adams et al.
6,068,636	A	5/2000	Chen	6,695,199	B2	2/2004	Whitman
6,083,241	A	7/2000	Longo et al.	6,698,643	B2	3/2004	Whitman
6,090,123	A	7/2000	Culp et al.	6,699,177	B1	3/2004	Wang et al.
6,102,271	A	8/2000	Longo et al.	6,716,222	B2	4/2004	McAlister et al.
6,117,148	A	9/2000	Ravo et al.	6,716,233	B1	4/2004	Whitman
6,119,913	A	9/2000	Adams et al.	6,726,697	B2	4/2004	Nicholas et al.
6,126,058	A	10/2000	Adams et al.	6,742,692	B2	6/2004	Hartwick
6,126,651	A	10/2000	Mayer	6,743,244	B2	6/2004	Blatter et al.
6,129,547	A	10/2000	Cise et al.	6,763,993	B2	7/2004	Bolduc et al.
6,142,933	A	11/2000	Longo et al.	6,769,590	B2	8/2004	Vresh et al.
6,149,667	A	11/2000	Hovland et al.	6,769,594	B2	8/2004	Orban, III
6,176,413	B1	1/2001	Heck et al.	6,783,533	B2	8/2004	Green et al.
6,179,195	B1	1/2001	Adams et al.	6,792,390	B1	9/2004	Burnside et al.
6,193,129	B1	2/2001	Bittner et al.	6,793,652	B1	9/2004	Whitman et al.
6,203,553	B1	3/2001	Robertson et al.	6,817,508	B1	11/2004	Racenet et al.
6,209,773	B1	4/2001	Bolduc et al.	6,820,791	B2	11/2004	Adams
6,239,732	B1	5/2001	Cusey	6,821,282	B2	11/2004	Perry et al.
6,241,139	B1	6/2001	Milliman et al.	6,827,246	B2	12/2004	Sullivan et al.
6,241,140	B1	6/2001	Adams et al.	6,830,174	B2	12/2004	Hillstead et al.
6,253,984	B1	7/2001	Heck et al.	6,840,423	B2	1/2005	Adams et al.
6,258,107	B1	7/2001	Balazs et al.	6,843,403	B2	1/2005	Whitman
6,264,086	B1	7/2001	McGuckin, Jr.	6,846,308	B2	1/2005	Whitman et al.
6,264,087	B1	7/2001	Whitman	6,846,309	B2	1/2005	Whitman et al.
6,269,997	B1	8/2001	Balazs et al.	6,849,071	B2	2/2005	Whitman et al.
6,273,897	B1	8/2001	Dalessandro et al.	6,852,122	B2	2/2005	Rush
6,279,809	B1	8/2001	Nicolo	6,860,892	B1	3/2005	Tanaka et al.
6,302,311	B1	10/2001	Adams et al.	6,866,178	B2	3/2005	Adams et al.
				6,872,214	B2	3/2005	Sonnenschein et al.
				6,874,669	B2	4/2005	Adams et al.
				6,884,250	B2	4/2005	Monassevitch et al.
				6,899,538	B2	5/2005	Matoba



(56)

## References Cited

## U.S. PATENT DOCUMENTS

6,905,057 B2	6/2005	Swayze et al.	7,422,137 B2	9/2008	Manzo
6,905,504 B1	6/2005	Vargas	7,422,138 B2	9/2008	Bilotti et al.
6,938,814 B2	9/2005	Sharma et al.	7,422,139 B2	9/2008	Shelton, IV et al.
6,942,675 B1	9/2005	Vargas	7,431,189 B2	10/2008	Shelton, IV et al.
6,945,444 B2	9/2005	Gresham et al.	7,431,191 B2	10/2008	Milliman
6,953,138 B1	10/2005	Dworak et al.	7,438,718 B2	10/2008	Milliman et al.
6,957,758 B2	10/2005	Aranyi	7,441,684 B2	10/2008	Shelton, IV et al.
6,959,851 B2	11/2005	Heinrich	7,448,525 B2	11/2008	Shelton, IV et al.
6,959,852 B2	11/2005	Shelton, IV et al.	7,455,676 B2	11/2008	Holsten et al.
6,964,363 B2	11/2005	Wales et al.	7,455,682 B2	11/2008	Viola
6,978,922 B2	12/2005	Bilotti et al.	7,464,846 B2	12/2008	Shelton, IV et al.
6,981,628 B2	1/2006	Wales	7,464,847 B2	12/2008	Viola et al.
6,981,941 B2	1/2006	Whitman et al.	7,464,849 B2	12/2008	Shelton, IV et al.
6,981,979 B2	1/2006	Nicolo	7,481,347 B2	1/2009	Roy
6,986,451 B1	1/2006	Mastri et al.	7,481,824 B2	1/2009	Boudreaux et al.
6,988,649 B2	1/2006	Shelton, IV et al.	7,487,899 B2	2/2009	Shelton, IV et al.
7,032,798 B2	4/2006	Whitman et al.	7,494,038 B2	2/2009	Milliman
RE39,152 E	6/2006	Aust et al.	7,506,791 B2	3/2009	Omaits et al.
7,055,731 B2	6/2006	Shelton, IV et al.	7,516,877 B2	4/2009	Aranyi
7,059,331 B2	6/2006	Adams et al.	7,527,185 B2	5/2009	Harari et al.
7,059,508 B2	6/2006	Shelton, IV et al.	7,537,602 B2	5/2009	Whitman
7,059,510 B2	6/2006	Orban, III	7,546,939 B2	6/2009	Adams et al.
7,077,856 B2	7/2006	Whitman	7,546,940 B2	6/2009	Milliman et al.
7,080,769 B2	7/2006	Vresh et al.	7,547,312 B2	6/2009	Bauman et al.
7,086,267 B2	8/2006	Dworak et al.	7,549,564 B2	6/2009	Boudreaux
7,111,769 B2	9/2006	Wales et al.	7,556,186 B2	7/2009	Milliman
7,114,642 B2	10/2006	Whitman	7,559,451 B2	7/2009	Sharma et al.
7,118,528 B1	10/2006	Piskun	7,565,993 B2	7/2009	Milliman et al.
7,122,029 B2	10/2006	Koop et al.	7,568,603 B2	8/2009	Shelton, IV et al.
7,122,044 B2	10/2006	Bolduc et al.	7,575,144 B2	8/2009	Ortiz et al.
7,128,748 B2	10/2006	Mooradian et al.	7,585,306 B2	9/2009	Abbott et al.
7,140,528 B2	11/2006	Shelton, IV	7,588,174 B2	9/2009	Holsten et al.
7,141,049 B2	11/2006	Stern et al.	7,588,175 B2	9/2009	Timm et al.
7,141,055 B2	11/2006	Abrams et al.	7,588,176 B2	9/2009	Timm et al.
7,143,923 B2	12/2006	Shelton, IV et al.	7,600,663 B2	10/2009	Green
7,143,925 B2	12/2006	Shelton, IV et al.	7,611,038 B2	11/2009	Racenet et al.
7,143,926 B2	12/2006	Shelton, IV et al.	7,635,385 B2	12/2009	Milliman et al.
7,147,138 B2	12/2006	Shelton, IV	7,637,409 B2	12/2009	Marczyk
7,168,604 B2	1/2007	Milliman et al.	7,641,093 B2	1/2010	Doll et al.
7,172,104 B2	2/2007	Scirica et al.	7,644,848 B2	1/2010	Swayze et al.
7,179,267 B2	2/2007	Nolan et al.	7,669,747 B2	3/2010	Weisenburgh, II et al.
7,182,239 B1	2/2007	Myers	7,670,334 B2	3/2010	Hueil et al.
7,195,142 B2	3/2007	Orban, III	7,673,780 B2	3/2010	Shelton, IV et al.
7,207,168 B2	4/2007	Doepker et al.	7,686,201 B2	3/2010	Csiky
7,220,237 B2	5/2007	Gannoe et al.	7,694,864 B2	4/2010	Okada
7,225,964 B2	6/2007	Mastri et al.	7,699,204 B2	4/2010	Viola
7,234,624 B2	6/2007	Gresham et al.	7,699,835 B2	4/2010	Lee et al.
7,235,089 B1	6/2007	McGuckin, Jr.	7,708,181 B2	5/2010	Cole et al.
7,238,021 B1	7/2007	Johnson	7,717,313 B2	5/2010	Criscuolo et al.
7,246,734 B2	7/2007	Shelton, IV	7,721,931 B2	5/2010	Shelton, IV et al.
7,252,660 B2	8/2007	Kunz	7,721,932 B2	5/2010	Cole et al.
RE39,841 E	9/2007	Bilotti et al.	7,726,539 B2	6/2010	Holsten et al.
7,285,125 B2	10/2007	Viola	7,738,971 B2	6/2010	Swayze
7,303,106 B2	12/2007	Milliman et al.	7,740,159 B2	6/2010	Shelton, IV et al.
7,303,107 B2	12/2007	Milliman et al.	7,743,958 B2	6/2010	Orban, III
7,309,341 B2	12/2007	Ortiz et al.	7,743,960 B2	6/2010	Whitman et al.
7,322,994 B2	1/2008	Nicholas et al.	7,744,627 B2	6/2010	Orban, III et al.
7,325,713 B2	2/2008	Aranyi	7,758,613 B2	7/2010	Whitman
7,328,828 B2	2/2008	Ortiz et al.	7,766,210 B2	8/2010	Shelton, IV et al.
7,334,718 B2	2/2008	McAlister et al.	7,770,773 B2	8/2010	Whitman et al.
7,335,212 B2	2/2008	Edoga et al.	7,770,775 B2	8/2010	Shelton, IV et al.
7,364,060 B2	4/2008	Milliman	7,770,776 B2	8/2010	Chen et al.
7,364,061 B2	4/2008	Swayze et al.	7,771,440 B2	8/2010	Ortiz et al.
7,380,695 B2	6/2008	Doll et al.	7,776,060 B2	8/2010	Mooradian et al.
7,380,696 B2	6/2008	Shelton, IV et al.	7,793,812 B2	9/2010	Moore et al.
7,398,908 B2	7/2008	Holsten et al.	7,793,813 B2	9/2010	Bettuchi
7,399,305 B2	7/2008	Csiky et al.	7,799,039 B2	9/2010	Shelton, IV et al.
7,401,721 B2	7/2008	Holsten et al.	7,802,712 B2	9/2010	Milliman et al.
7,401,722 B2	7/2008	Hur	7,822,458 B2	10/2010	Webster, III et al.
7,404,508 B2	7/2008	Smith et al.	7,823,592 B2	11/2010	Bettuchi et al.
7,407,075 B2	8/2008	Holsten et al.	7,837,079 B2	11/2010	Holsten et al.
7,407,078 B2	8/2008	Shelton, IV et al.	7,837,080 B2	11/2010	Schwemberger
7,410,086 B2	8/2008	Ortiz et al.	7,837,081 B2	11/2010	Holsten et al.
7,416,101 B2	8/2008	Shelton, IV et al.	7,845,534 B2	12/2010	Viola et al.
7,419,080 B2	9/2008	Smith et al.	7,845,536 B2	12/2010	Viola et al.
			7,845,537 B2	12/2010	Shelton, IV et al.
			7,845,538 B2	12/2010	Whitman
			7,857,185 B2	12/2010	Swayze
			7,857,187 B2	12/2010	Milliman



(56)

## References Cited

## U.S. PATENT DOCUMENTS

7,870,989 B2	1/2011	Viola et al.	8,201,720 B2	6/2012	Hessler
7,886,951 B2	2/2011	Hessler	8,203,782 B2	6/2012	Brueck et al.
7,896,215 B2	3/2011	Adams et al.	8,211,130 B2	7/2012	Viola
7,900,805 B2	3/2011	Shelton, IV et al.	8,220,367 B2	7/2012	Hsu
7,900,806 B2	3/2011	Chen et al.	8,225,799 B2	7/2012	Bettuchi
7,905,897 B2	3/2011	Whitman et al.	8,225,981 B2	7/2012	Criscuolo et al.
7,909,039 B2	3/2011	Hur	8,231,041 B2	7/2012	Marczyk et al.
7,909,219 B2	3/2011	Cole et al.	8,231,042 B2	7/2012	Hessler et al.
7,909,222 B2	3/2011	Cole et al.	8,235,273 B2	8/2012	Olson et al.
7,909,223 B2	3/2011	Cole et al.	8,241,322 B2	8/2012	Whitman et al.
7,913,892 B2	3/2011	Cole et al.	8,257,391 B2	9/2012	Orban, III et al.
7,918,230 B2	4/2011	Whitman et al.	8,267,301 B2	9/2012	Milliman et al.
7,918,377 B2	4/2011	Measamer et al.	8,272,552 B2	9/2012	Holsten et al.
7,922,061 B2	4/2011	Shelton, IV et al.	8,272,554 B2	9/2012	Whitman et al.
7,922,062 B2	4/2011	Cole et al.	8,276,802 B2	10/2012	Kostrzewski
7,922,719 B2	4/2011	Ralph et al.	8,281,975 B2	10/2012	Criscuolo et al.
7,922,743 B2	4/2011	Heinrich et al.	8,286,845 B2	10/2012	Perry et al.
7,931,183 B2	4/2011	Orban, III	8,292,150 B2	10/2012	Bryant
7,938,307 B2	5/2011	Bettuchi	8,292,888 B2	10/2012	Whitman
7,942,302 B2	5/2011	Roby et al.	8,308,045 B2	11/2012	Bettuchi et al.
7,947,034 B2	5/2011	Whitman	8,312,885 B2	11/2012	Bettuchi et al.
7,951,071 B2	5/2011	Whitman et al.	8,313,014 B2	11/2012	Bettuchi
7,951,166 B2	5/2011	Orban, III et al.	8,317,073 B2	11/2012	Milliman et al.
7,954,682 B2	6/2011	Giordano et al.	8,317,074 B2	11/2012	Ortiz et al.
7,959,050 B2	6/2011	Smith et al.	8,322,590 B2	12/2012	Patel et al.
7,959,051 B2	6/2011	Smith et al.	8,328,060 B2	12/2012	Jankowski et al.
7,963,433 B2	6/2011	Whitman et al.	8,328,062 B2	12/2012	Viola
7,967,178 B2	6/2011	Scirica et al.	8,328,063 B2	12/2012	Milliman et al.
7,967,179 B2	6/2011	Olson et al.	8,342,379 B2	1/2013	Whitman et al.
7,967,181 B2	6/2011	Viola et al.	8,343,185 B2	1/2013	Milliman et al.
7,975,895 B2	7/2011	Milliman	8,348,130 B2	1/2013	Shah et al.
7,992,758 B2	8/2011	Whitman et al.	8,348,855 B2	1/2013	Hillely et al.
8,002,795 B2	8/2011	Beetel	8,353,438 B2	1/2013	Baxter, III et al.
8,006,701 B2	8/2011	Bilotti et al.	8,353,439 B2	1/2013	Baxter, III et al.
8,006,889 B2	8/2011	Adams et al.	8,353,440 B2	1/2013	Whitman et al.
8,011,550 B2	9/2011	Aranyi et al.	8,353,930 B2	1/2013	Heinrich et al.
8,011,551 B2	9/2011	Marczyk et al.	8,357,144 B2	1/2013	Whitman et al.
8,011,554 B2	9/2011	Milliman	8,360,295 B2	1/2013	Milliman et al.
8,016,177 B2	9/2011	Bettuchi et al.	8,365,633 B2	2/2013	Simaan et al.
8,016,178 B2	9/2011	Colson et al.	8,365,972 B2	2/2013	Aranyi et al.
8,016,855 B2	9/2011	Whitman et al.	8,365,974 B2	2/2013	Milliman
8,016,858 B2	9/2011	Whitman	8,371,492 B2	2/2013	Aranyi et al.
8,020,741 B2	9/2011	Cole et al.	8,372,057 B2	2/2013	Cude et al.
8,020,743 B2	9/2011	Shelton, IV	8,391,957 B2	3/2013	Carlson et al.
8,025,199 B2	9/2011	Whitman et al.	8,403,926 B2	3/2013	Nobis et al.
8,028,885 B2	10/2011	Smith et al.	8,403,942 B2	3/2013	Milliman et al.
8,038,046 B2	10/2011	Smith et al.	8,408,441 B2	4/2013	Wenchell et al.
8,043,207 B2	10/2011	Adams	8,413,870 B2	4/2013	Pastorelli et al.
8,052,024 B2	11/2011	Viola et al.	8,413,872 B2	4/2013	Patel
8,066,167 B2	11/2011	Measamer et al.	8,418,904 B2	4/2013	Wenchell et al.
8,066,169 B2	11/2011	Viola	8,418,905 B2	4/2013	Milliman
8,070,035 B2	12/2011	Holsten et al.	8,418,909 B2	4/2013	Kostrzewski
8,070,037 B2	12/2011	Csiky	8,424,535 B2	4/2013	Hessler et al.
8,096,458 B2	1/2012	Hessler	8,424,739 B2	4/2013	Racenet et al.
8,109,426 B2	2/2012	Milliman et al.	8,424,741 B2	4/2013	McGuckin, Jr. et al.
8,109,427 B2	2/2012	Orban, III	8,430,291 B2	4/2013	Heinrich et al.
8,113,406 B2	2/2012	Holsten et al.	8,430,292 B2	4/2013	Patel et al.
8,113,407 B2	2/2012	Holsten et al.	8,453,910 B2	6/2013	Bettuchi et al.
8,114,118 B2	2/2012	Knodel et al.	8,453,911 B2	6/2013	Milliman et al.
8,123,103 B2	2/2012	Milliman	8,454,585 B2	6/2013	Whitman
8,127,975 B2	3/2012	Olson et al.	8,485,414 B2	7/2013	Criscuolo et al.
8,128,645 B2	3/2012	Sonnenschein et al.	8,490,853 B2	7/2013	Criscuolo et al.
8,132,703 B2	3/2012	Milliman et al.	8,505,802 B2	8/2013	Viola et al.
8,132,705 B2	3/2012	Viola et al.	8,511,533 B2	8/2013	Viola et al.
8,136,712 B2	3/2012	Zingman	8,517,241 B2	8/2013	Nicholas et al.
8,146,790 B2	4/2012	Milliman	8,523,043 B2	9/2013	Ullrich et al.
8,146,791 B2	4/2012	Bettuchi et al.	8,551,076 B2	10/2013	Duval et al.
8,152,516 B2	4/2012	Harvey et al.	8,551,138 B2	10/2013	Orban, III et al.
8,157,150 B2	4/2012	Viola et al.	8,561,871 B2	10/2013	Rajappa et al.
8,157,151 B2	4/2012	Ingmanson et al.	8,561,874 B2	10/2013	Scirica
8,181,838 B2	5/2012	Milliman et al.	8,567,655 B2	10/2013	Nalagatla et al.
8,182,494 B1	5/2012	Yencho et al.	8,579,178 B2	11/2013	Holsten et al.
8,186,555 B2	5/2012	Shelton, IV et al.	8,590,763 B2	11/2013	Milliman
8,186,587 B2	5/2012	Zmood et al.	8,590,764 B2	11/2013	Hartwick et al.
8,192,460 B2	6/2012	Orban, III et al.	8,602,287 B2	12/2013	Yates et al.
			8,608,047 B2	12/2013	Holsten et al.
			8,616,428 B2	12/2013	Milliman et al.
			8,616,429 B2	12/2013	Viola
			8,622,275 B2	1/2014	Baxter, III et al.



(56)

## References Cited

## U.S. PATENT DOCUMENTS

8,623,000 B2	1/2014	Humayun et al.	2007/0175947 A1	8/2007	Ortiz et al.
8,627,995 B2	1/2014	Smith et al.	2007/0175949 A1	8/2007	Shelton et al.
8,631,993 B2	1/2014	Kostrzewski	2007/0175950 A1	8/2007	Shelton et al.
8,632,463 B2	1/2014	Drinan et al.	2007/0175951 A1	8/2007	Shelton et al.
8,636,187 B2	1/2014	Hueil et al.	2007/0175955 A1	8/2007	Shelton et al.
8,636,766 B2	1/2014	Milliman et al.	2007/0270784 A1	11/2007	Smith et al.
8,640,940 B2	2/2014	Ohdaira	2008/0029570 A1	2/2008	Shelton et al.
8,647,258 B2	2/2014	Aranyi et al.	2008/0029573 A1	2/2008	Shelton et al.
8,652,121 B2	2/2014	Quick et al.	2008/0029574 A1	2/2008	Shelton et al.
8,657,174 B2	2/2014	Yates et al.	2008/0029575 A1	2/2008	Shelton et al.
8,657,177 B2	2/2014	Scirica et al.	2008/0058801 A1	3/2008	Taylor et al.
8,662,370 B2	3/2014	Takei	2008/0109012 A1	5/2008	Falco et al.
8,663,258 B2	3/2014	Bettuchi et al.	2008/0110958 A1	5/2008	McKenna et al.
8,672,206 B2	3/2014	Aranyi et al.	2008/0147089 A1	6/2008	Loh et al.
8,672,931 B2	3/2014	Goldboss et al.	2008/0185419 A1	8/2008	Smith et al.
8,678,264 B2	3/2014	Racenet et al.	2008/0188841 A1	8/2008	Tomasello et al.
8,684,248 B2	4/2014	Milliman	2008/0197167 A1	8/2008	Viola et al.
8,684,250 B2	4/2014	Bettuchi et al.	2008/0208195 A1	8/2008	Shores et al.
8,684,251 B2	4/2014	Rebuffat et al.	2008/0251561 A1	10/2008	Eades et al.
8,684,252 B2	4/2014	Patel et al.	2008/0255413 A1	10/2008	Zemlok et al.
8,696,552 B2	4/2014	Whitman	2008/0255607 A1	10/2008	Zemlok
8,708,213 B2	4/2014	Shelton, IV et al.	2008/0262654 A1	10/2008	Omori et al.
8,715,306 B2	5/2014	Faller et al.	2009/0012533 A1	1/2009	Barbagli et al.
8,733,611 B2	5/2014	Milliman	2009/0090763 A1	4/2009	Zemlok et al.
8,758,391 B2	6/2014	Swayze et al.	2009/0099876 A1	4/2009	Whitman
8,806,973 B2	8/2014	Ross et al.	2009/0138006 A1	5/2009	Bales et al.
8,808,311 B2	8/2014	Heinrich et al.	2009/0171147 A1	7/2009	Lee et al.
8,820,605 B2	9/2014	Shelton, IV	2009/0182193 A1	7/2009	Whitman et al.
8,851,355 B2	10/2014	Aranyi et al.	2009/0209990 A1	8/2009	Yates et al.
8,858,571 B2	10/2014	Shelton, IV et al.	2009/0236392 A1	9/2009	Cole et al.
8,888,762 B2	11/2014	Whitman	2009/0236398 A1	9/2009	Cole et al.
8,899,462 B2	12/2014	Kostrzewski et al.	2009/0236401 A1	9/2009	Cole et al.
8,905,289 B2	12/2014	Patel et al.	2009/0254094 A1	10/2009	Knapp et al.
8,919,630 B2	12/2014	Milliman	2009/0299141 A1	12/2009	Downey et al.
8,931,680 B2	1/2015	Milliman	2010/0019016 A1	1/2010	Edoga et al.
8,950,646 B2	2/2015	Viola	2010/0023022 A1	1/2010	Zeiner et al.
8,960,519 B2	2/2015	Whitman et al.	2010/0051668 A1	3/2010	Milliman et al.
8,967,443 B2	3/2015	McCuen	2010/0069942 A1	3/2010	Shelton, IV
8,968,276 B2	3/2015	Zemlok et al.	2010/0084453 A1	4/2010	Hu
9,016,545 B2	4/2015	Aranyi et al.	2010/0147923 A1	6/2010	D'Agostino et al.
9,023,014 B2	5/2015	Chowaniec et al.	2010/0163598 A1	7/2010	Belzer
9,033,868 B2	5/2015	Whitman et al.	2010/0224668 A1	9/2010	Fontayne et al.
9,055,943 B2	6/2015	Zemlok et al.	2010/0225073 A1	9/2010	Porter et al.
9,072,515 B2	7/2015	Hall et al.	2010/0230465 A1	9/2010	Smith et al.
9,113,847 B2	8/2015	Whitman et al.	2010/0258611 A1	10/2010	Smith et al.
9,113,875 B2	8/2015	Viola et al.	2010/0264195 A1	10/2010	Bettuchi
9,113,876 B2	8/2015	Zemlok et al.	2010/0327041 A1	12/2010	Milliman et al.
9,113,899 B2	8/2015	Garrison et al.	2011/0011916 A1	1/2011	Levine
2001/0031975 A1	10/2001	Whitman et al.	2011/0077673 A1	3/2011	Grubac et al.
2003/0038938 A1	2/2003	Jung et al.	2011/0114697 A1	5/2011	Baxter, III et al.
2003/0111507 A1	6/2003	Nunez	2011/0114700 A1	5/2011	Baxter, III et al.
2004/0111012 A1	6/2004	Whitman	2011/0121049 A1	5/2011	Malinouskas et al.
2004/0133189 A1	7/2004	Sakurai	2011/0125138 A1	5/2011	Malinouskas et al.
2004/0153124 A1	8/2004	Whitman	2011/0139851 A1	6/2011	McCuen
2004/0176751 A1	9/2004	Weitzner et al.	2011/0144640 A1	6/2011	Heinrich et al.
2004/0193146 A1	9/2004	Lee et al.	2011/0147432 A1	6/2011	Heinrich et al.
2005/0051597 A1	3/2005	Toledano	2011/0155783 A1	6/2011	Rajappa et al.
2005/0107813 A1	5/2005	Gilete Garcia	2011/0174099 A1	7/2011	Ross et al.
2005/0125027 A1	6/2005	Knodel et al.	2011/0184245 A1	7/2011	Xia et al.
2005/0131442 A1	6/2005	Yachia et al.	2011/0192882 A1	8/2011	Hess et al.
2006/0000869 A1	1/2006	Fontayne	2011/0204119 A1	8/2011	McCuen
2006/0011698 A1	1/2006	Okada et al.	2011/0218522 A1	9/2011	Whitman
2006/0142656 A1	6/2006	Malackowski et al.	2011/0290854 A1	12/2011	Timm et al.
2006/0142744 A1	6/2006	Boutoussov	2011/0295242 A1	12/2011	Spivey et al.
2006/0201989 A1	9/2006	Ojeda	2011/0295269 A1	12/2011	Swensgard et al.
2006/0259073 A1	11/2006	Miyamoto et al.	2012/0000962 A1	1/2012	Racenet et al.
2006/0278680 A1	12/2006	Viola et al.	2012/0089131 A1	4/2012	Zemlok et al.
2006/0284730 A1	12/2006	Schmid et al.	2012/0143002 A1	6/2012	Aranyi et al.
2007/0023477 A1	2/2007	Whitman et al.	2012/0145755 A1	6/2012	Kahn
2007/0027473 A1	2/2007	Vresh et al.	2012/0172924 A1	7/2012	Allen, IV
2007/0029363 A1	2/2007	Popov	2012/0193395 A1	8/2012	Pastorelli et al.
2007/0060952 A1	3/2007	Roby et al.	2012/0193398 A1	8/2012	Williams et al.
2007/0084897 A1	4/2007	Shelton et al.	2012/0223121 A1	9/2012	Viola et al.
2007/0102472 A1	5/2007	Shelton	2012/0232339 A1	9/2012	Csiky
2007/0152014 A1	7/2007	Gillum et al.	2012/0253329 A1	10/2012	Zemlok et al.
			2012/0273548 A1	11/2012	Ma et al.
			2012/0310220 A1	12/2012	Malkowski et al.
			2012/0323226 A1	12/2012	Chowaniec et al.
			2012/0325888 A1	12/2012	Qiao et al.



(56)

References Cited

U.S. PATENT DOCUMENTS

2013/0015232 A1 1/2013 Smith et al.  
 2013/0018361 A1 1/2013 Bryant  
 2013/0020372 A1 1/2013 Jankowski et al.  
 2013/0020373 A1 1/2013 Smith et al.  
 2013/0032628 A1 2/2013 Li et al.  
 2013/0056516 A1 3/2013 Viola  
 2013/0060258 A1 3/2013 Giacomantonio  
 2013/0105544 A1 5/2013 Mozdierz et al.  
 2013/0105546 A1 5/2013 Milliman et al.  
 2013/0105551 A1 5/2013 Zingman  
 2013/0126580 A1 5/2013 Smith et al.  
 2013/0153630 A1 6/2013 Miller et al.  
 2013/0153631 A1 6/2013 Vasudevan et al.  
 2013/0153633 A1 6/2013 Casasanta, Jr. et al.  
 2013/0153634 A1 6/2013 Carter et al.  
 2013/0153638 A1 6/2013 Carter et al.  
 2013/0153639 A1 6/2013 Hodgkinson et al.  
 2013/0175315 A1 7/2013 Milliman  
 2013/0175318 A1 7/2013 Felder et al.  
 2013/0175319 A1 7/2013 Felder et al.  
 2013/0175320 A1 7/2013 Mandakolathur Vasudevan et al.  
 2013/0181035 A1 7/2013 Milliman  
 2013/0181036 A1 7/2013 Olson et al.  
 2013/0186930 A1 7/2013 Wenchell et al.  
 2013/0193185 A1 8/2013 Patel  
 2013/0193187 A1 8/2013 Milliman  
 2013/0193190 A1 8/2013 Carter et al.  
 2013/0193191 A1 8/2013 Stevenson et al.  
 2013/0193192 A1 8/2013 Casasanta, Jr. et al.  
 2013/0200131 A1 8/2013 Racenet et al.  
 2013/0206816 A1 8/2013 Penna  
 2013/0214025 A1 8/2013 Zemlok et al.  
 2013/0214027 A1 8/2013 Hessler et al.  
 2013/0214028 A1 8/2013 Patel et al.  
 2013/0228609 A1 9/2013 Kostrzewski  
 2013/0240597 A1 9/2013 Milliman et al.  
 2013/0240600 A1 9/2013 Bettuchi  
 2013/0248581 A1 9/2013 Smith et al.  
 2013/0274722 A1 10/2013 Kostrzewski et al.  
 2013/0277411 A1 10/2013 Hodgkinson et al.  
 2013/0277412 A1 10/2013 Gresham et al.  
 2013/0282052 A1 10/2013 Aranyi et al.  
 2013/0284792 A1 10/2013 Ma  
 2013/0292449 A1 11/2013 Bettuchi et al.  
 2013/0292451 A1 11/2013 Viola et al.  
 2013/0299553 A1 11/2013 Mozdierz  
 2013/0299554 A1 11/2013 Mozdierz  
 2013/0306701 A1 11/2013 Olson  
 2013/0306707 A1 11/2013 Viola et al.  
 2013/0313304 A1 11/2013 Shelton, IV et al.  
 2013/0317486 A1 11/2013 Nicholas et al.  
 2013/0319706 A1 12/2013 Nicholas et al.  
 2013/0324978 A1 12/2013 Nicholas et al.  
 2013/0324979 A1 12/2013 Nicholas et al.  
 2013/0334281 A1 12/2013 Williams  
 2014/0008413 A1 1/2014 Williams  
 2014/0012236 A1 1/2014 Williams et al.  
 2014/0012237 A1 1/2014 Pribanic et al.  
 2014/0012289 A1 1/2014 Snow et al.  
 2014/0012317 A1 1/2014 Orban et al.  
 2014/0025046 A1 1/2014 Williams et al.  
 2014/0110455 A1 4/2014 Ingmanson et al.  
 2014/0166728 A1 6/2014 Swayze et al.  
 2014/0207125 A1 7/2014 Applegate et al.  
 2014/0207182 A1 7/2014 Zergiebel et al.  
 2014/0207185 A1 7/2014 Goble et al.  
 2014/0236173 A1 8/2014 Scirica et al.  
 2014/0236174 A1 8/2014 Williams et al.  
 2014/0276932 A1 9/2014 Williams et al.

2014/0299647 A1 10/2014 Scirica et al.  
 2014/0303668 A1 10/2014 Nicholas et al.  
 2014/0358129 A1 12/2014 Zergiebel et al.  
 2014/0361068 A1 12/2014 Aranyi et al.  
 2014/0365235 A1 12/2014 DeBoer et al.  
 2014/0373652 A1 12/2014 Zergiebel et al.  
 2015/0014392 A1 1/2015 Williams et al.  
 2015/0048144 A1 2/2015 Whitman  
 2015/0076205 A1 3/2015 Zergiebel  
 2015/0080912 A1 3/2015 Sapre  
 2015/0112381 A1 4/2015 Richard  
 2015/0122870 A1 5/2015 Zemlok et al.  
 2015/0133224 A1 5/2015 Whitman et al.  
 2015/0133957 A1 5/2015 Kostrzewski  
 2015/0150547 A1 6/2015 Ingmanson et al.  
 2015/0150574 A1 6/2015 Richard et al.  
 2015/0157320 A1 6/2015 Zergiebel et al.  
 2015/0157321 A1 6/2015 Zergiebel et al.  
 2015/0164502 A1 6/2015 Richard et al.  
 2015/0201931 A1 7/2015 Zergiebel et al.  
 2016/0361057 A1\* 12/2016 Williams ..... A61B 17/068

FOREIGN PATENT DOCUMENTS

CA 2824590 A1 4/2014  
 CN 102247182 A 11/2011  
 DE 1057729 B 5/1959  
 DE 3301713 A1 7/1984  
 DE 102008053842 A1 5/2010  
 EP 0152382 A2 8/1985  
 EP 0173451 A1 3/1986  
 EP 0282157 A1 3/1986  
 EP 0190022 A2 8/1986  
 EP 0503689 A2 9/1992  
 EP 0705571 A1 4/1996  
 EP 1354560 A2 10/2003  
 EP 1769754 A1 4/2007  
 EP 2055243 A2 5/2009  
 EP 2316345 A1 5/2011  
 EP 2333509 A1 6/2011  
 EP 2524656 A2 11/2012  
 EP 2524658 A1 11/2012  
 EP 3078335 A1 10/2016  
 EP 3146905 A1 3/2017  
 EP 3412226 A1 12/2018  
 ES 2333509 A1 2/2010  
 FR 1136020 A 5/1957  
 FR 1461464 A 2/1966  
 FR 1588250 A 4/1970  
 FR 2443239 A1 7/1980  
 GB 1185292 A 3/1970  
 GB 2016991 A 9/1979  
 GB 2070499 A 9/1981  
 JP 08038488 2/1996  
 JP 2005125075 A 5/2005  
 NL 7711347 A 4/1979  
 SU 1509052 A1 9/1989  
 WO 8706448 A1 11/1987  
 WO 8900406 A1 1/1989  
 WO 9006085 A1 6/1990  
 WO 0154594 A1 8/2001  
 WO 2008107918 A1 9/2008  
 WO 2011108840 A2 9/2011  
 WO 2012/040984 A1 4/2012

OTHER PUBLICATIONS

European Search Report dated Mar. 1, 2021, corresponding to counterpart European Application No. 20183904.0; 11 pages.

\* cited by examiner




FIG. 1






FIG. 2








FIG. 3






**FIG. 4**




**FIG. 5**







**FIG. 6**



**FIG. 7**




**FIG. 7A**




**FIG. 8**






**FIG. 9**




**FIG. 10**




**FIG. 11**







**FIG. 12**



**FIG. 13**




**FIG. 14**




**FIG. 15**





**FIG. 16**



**FIG. 17**




FIG. 18







FIG. 19






**FIG. 21**




**FIG. 22**




**FIG. 23**





**FIG. 24**



**FIG. 25**



**1****RETAINING MECHANISMS FOR TROCAR ASSEMBLIES**

## FIELD

The disclosure relates to reusable adapter assemblies for surgical stapling devices. More particularly, the disclosure relates to retaining mechanisms for releasably securing removable trocar assemblies within reusable adapter assemblies.

## BACKGROUND

Surgical devices for applying staples, clips, or other fasteners to tissue are well known. Typically, endoscopic stapling devices include an actuation unit, i.e., a handle assembly for actuating the device, a shaft for endoscopic access to a body cavity, and a tool assembly disposed at a distal end of the shaft. In certain of these devices, the shaft includes an adapter assembly having a proximal end securable to the handle assembly and a distal end securable to the tool assembly.

Circular stapling devices typically include a trocar assembly for supporting and positioning an attached anvil assembly in relation to a staple cartridge of the tool assembly. The trocar assembly may be releasably securable within the adapter assembly to permit cleaning, sterilizing, and reuse of the adapter assembly. It would be beneficial to have a retaining mechanism for releasably securing the trocar assembly to the adapter assembly.

## SUMMARY

An adapter assembly for connecting a loading unit to a handle assembly includes an outer sleeve, a trocar assembly releasably securable within the outer sleeve, and a retaining mechanism configured to releasably secure the trocar assembly within the outer sleeve. The trocar assembly includes a trocar housing defining first and second openings. The retaining mechanism includes a retaining block, a cam wire moveably positioned relative to the retaining block between a lock position and a release position, a retaining block extension configured to maintain the cam wire relative to the retaining block, a button member in operable engagement with the cam wire, and a pair of retaining members moveable from a first position received within the first and second openings of the trocar assembly when the cam wire is in the lock position and a second position spaced from the trocar assembly when the cam wire is in the release position. The retaining block extension includes a stop tab. The button member includes a center beam moveable from an unflexed position in engagement with the stop tab of the retaining block extension to prevent movement of the button member to a flexed position out of alignment with the stop tab to permit movement of the button member.

In embodiments, the button member is pivotable relative to the retaining block from a non-depressed position when the center beam is in the unflexed position and a depressed position when the center beam is in the flexed position. Depression of the button member may cause the cam wire to move from the lock position to the release position.

The center beam may include a rib configured for operable engagement by a user. The button member may define a relief on either side of the center beam to permit movement of the center beam between the unflexed and flexed positions. The button member may define a midline. The stop member may be aligned with the midline. The center beam

**2**

may be aligned with the midline when in the unflexed position and is misaligned with the midline when in the flexed position. The retaining block may define a central opening for receiving the trocar assembly. Each of the first and second retaining members may include a wedge-shaped free end.

Another adapter assembly for connecting a loading unit to a handle assembly includes an outer sleeve, a trocar assembly releasably securable within the outer sleeve, and a retaining mechanism configured to releasably secure the trocar assembly within the outer sleeve. The trocar assembly includes a trocar housing defining first and second openings. The retaining mechanism includes a retaining block, a cam wire moveably positioned relative to the retaining block between a lock position and a release position, an upper retaining block extension configured to maintain the cam wire relative to the retaining block, a button member for moving the cam wire between the lock and release positions, a pair of retaining members moveable from a first position received within the first and second openings of the trocar assembly when the cam wire is in the lock position and a second position spaced from the trocar assembly when the cam wire is in the release position, a lower retaining block extension disposed opposite the upper retaining block extension, and a sliding button moveable between a first position in engagement with the cam wire to a second position spaced from the cam wire. Movement of the sliding button member relative to the lower retaining block permits movement of the cam wire from the lock position to the release position.

In embodiments, the cam wire includes first and second free ends and the sliding button member includes first and second stop members configured to engage the free ends of the cam wire to prevent movement of the cam wire to the release position. The sliding button member may be biased to the first position by a biasing member. The biasing member may be a coil spring. The sliding button member may be configured for operable engagement by a user. The button member may be pivotable relative to the upper retaining block extension.

The adapter assembly may include a collar assembly received about the outer sleeve. Movement of the collar assembly from a first position to a second position moves the button member from the non-depressed position to the depressed position. The collar assembly may move proximally from the first position to the second position. Alternatively, the collar assembly is rotated about the outer sleeve when moved from the first position to the second position. The collar assembly may be biased to the first position by a coil spring. The outer sleeve may include a pin for engagement with the collar assembly to limit movement of the collar assembly.

## BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate embodiments of the disclosure and, together with a general description of the disclosure given above, and the detailed description of the embodiments given below, serve to explain the principles of the disclosure, wherein:

FIG. 1 is a perspective view of a surgical stapling device including an handle assembly and an adapter assembly according to an exemplary embodiment of the disclosure;

FIG. 2 is a perspective view of the adapter assembly shown in FIG. 1 with a removable trocar assembly extending from a distal portion of the adapter assembly;



## 3

FIG. 3 is a perspective view of the distal portion of the adapter assembly and the removable trocar assembly shown in FIG. 1, with the removable trocar removed from within the adapter assembly;

FIG. 4 is an exploded view of the indicated area of detail shown in FIG. 3;

FIG. 5 is a perspective view of the distal portion of the adapter assembly shown in FIG. 2, with an outer sleeve removed to expose a retaining mechanism;

FIG. 6 is a side perspective view of the retaining mechanism shown in FIG. 5, with components separated;

FIG. 7 is a cross-sectional end view the adapter assembly shown in FIG. 2 taken along line 7-7 shown in FIG. 3, with the retainer mechanism in a lock position;

FIG. 8 is a top view of a portion of the adapter assembly including a button member of the retainer mechanism shown in FIG. 5, with a center beam in a first or unflexed condition;

FIG. 9 is the top view shown in FIG. 8 with the center beam of the button member in a second of flexed condition;

FIG. 10 is the cross-sectional end view of the adapter assembly shown in FIG. 7, with the retainer mechanism in a release position;

FIG. 11 is a first perspective view of a distal portion of an adapter assembly according to another embodiment of the disclosure;

FIG. 12 is a second perspective view of the distal portion of the adapter assembly shown in FIG. 11;

FIG. 13 is a perspective view of the distal portion of the adapter assembly shown in FIG. 11, with an outer sleeve removed to expose a retaining mechanism;

FIG. 14 is a side perspective view of the retaining mechanism shown in FIG. 13, with components separated, and a cam wire, an upper retaining member, and a button member removed;

FIG. 15 is a perspective view of a lower retaining block extension of the retaining mechanism shown in FIG. 13;

FIG. 16 is a cross-sectional end view of the adapter assembly shown in FIG. 11 taken along line 16-16 of FIG. 11;

FIG. 17 is the perspective view of the distal portion of the adapter assembly shown in FIG. 13, with a sliding button member of the retaining mechanism shown in FIG. 13 in a proximal position;

FIG. 18 is a side view of the retaining mechanism shown in FIG. 17, with the sliding button member in the proximal position and the button member in a depressed condition;

FIG. 19 is a distal portion of an adapter assembly according to another exemplary embodiment of the disclosure including a collar assembly;

FIG. 20 is another perspective side view of a portion of the distal portion of the adapter assembly shown in FIG. 19;

FIG. 21 is a perspective side view of the collar assembly shown in FIG. 19;

FIG. 22 is a cross-sectional side view of the adapter assembly taken along line 22-22 of FIG. 19, with the collar assembly in a distal position;

FIG. 23 is the cross-sectional side view shown in FIG. 22, with the collar assembly in a proximal position;

FIG. 24 is a perspective side view of an adapter assembly according to yet another exemplary embodiment of the disclosure including a collar assembly and a biasing member for maintaining the collar assembly in a proximal position; and

FIG. 25 is a cross-sectional end view of an adapter assembly according to another exemplary embodiment of the disclosure including a collar assembly.

## 4

## DETAILED DESCRIPTION

Embodiments of the disclosed adapter assembly including a retaining mechanism for securing a removable trocar assembly therein will now be described in detail with reference to the drawings in which like reference numerals designate identical or corresponding elements in each of the several views. As is common in the art, the term “proximal” refers to that part or component closer to the user or operator, i.e. surgeon or clinician, while the term “distal” refers to that part or component further away from the user.

Referring initially to FIG. 1, an adapter assembly according to an embodiment of the disclosure, shown generally as adapter assembly 100, is a component of a surgical stapling device 10. The surgical stapling device 10 further includes a powered handle assembly 20 for actuating a loading unit 30, and an anvil assembly 40 supported relative to the loading unit 30. The loading unit 30 and the anvil assembly 40 form a tool assembly of the surgical stapling device 10.

Although shown and described with reference to surgical stapling device 10, aspects of the disclosure may be modified for use with manual surgical stapling devices having various configurations, and with powered surgical stapling devices having alternative configurations. For a detailed description of exemplary surgical stapling devices, please refer to U.S. Pat. Nos. 9,023,014 and 9,055,943. With reference to FIG. 2, the adapter assembly 100 includes a proximal portion 102 configured for operable connection to the handle assembly 20 (FIG. 1) and a distal portion 104 configured for operable connection to the loading unit 30 (FIG. 1) and to the anvil assembly 40 (FIG. 1). Although shown and described as forming an integral unit, it is envisioned that the proximal and distal portions 102, 104 may be formed as separate units that are releasably securable to one another.

The adapter assembly 100 will only be described to the extent necessary to fully disclose the aspects of the disclosure. For a detailed description of an exemplary adapter assembly, please refer to U.S. Pat. No. 10,226,254 (“the ’254 patent”).

With additional reference to FIGS. 3 and 4, the adapter assembly 100 includes an outer sleeve 106, and a connector housing 108 secured to a distal end of the outer sleeve 106. The connector housing 108 is configured to releasably secure a loading unit, e.g., the loading unit 30 (FIG. 1), to the adapter assembly 100. The outer sleeve 106 defines a flush port 105 (FIG. 3) and an opening 107 through which a button member 170 of a trocar retaining mechanism 130 is operably disposed. As will be described in further detail below, the outer sleeve 106 further includes an asymmetric cutout 107a (FIG. 4) in communication with the opening 107.

With additional reference to FIG. 5, the adapter assembly 100 further includes a trocar assembly 120 (FIG. 3), and a retaining mechanism 130 releasably securing the trocar assembly 120 relative to the outer sleeve 106 (FIG. 3) of the adapter assembly 100. The trocar assembly 120 will only be described to the extent necessary to fully describe the aspects of the disclosure. For a detailed description of the structure and function of an exemplary trocar assembly, please refer to the ’254 patent. With particular reference to FIG. 3, the trocar assembly 120 of the adapter assembly 100 (FIG. 2) includes a trocar housing 122, a trocar member 124 slidably disposed within the trocar housing 122, and a drive screw 126 operably received within the trocar member 124 for axially moving the trocar member 124 relative to the trocar housing 122. The trocar housing 122 defines first and second locking openings 123a, 123b (FIG. 7) for receiving



## 5

respective locking portions **182a**, **182b** of first and second retainer members **180a**, **180b** (FIG. 6) of a retaining mechanism **130** of the adapter assembly **100**.

Turning briefly to FIG. 7, the retaining mechanism **130** of the adapter assembly **100** is disposed between first and second drive members **110a**, **110b**, **112a**, **112b** of respective inner and outer drive assemblies **110**, **112**. The first and second drive assemblies **110**, **112** are operably connected to first and second drive shafts (not shown) in a proximal portion **102** of the adapter assembly **100** for effecting operation of a loading unit, e.g., the loading unit **30** (FIG. 1), to perform first and second functions. More particularly, the first and second drive members **110a**, **110b**, **112a**, **112b** of the respective first and second drive assemblies **110**, **112** are configured for longitudinal movement within the distal portion **104** of the adapter assembly **100**. In embodiments, advancement of the first drive assembly **110** effects tissue stapling, and advancement of the second drive assembly **112** effects tissue cutting.

The first and second drive assemblies **110**, **112** will only be described to the extent necessary to fully disclose the aspects of the disclosure. For a detailed description of exemplary drive assemblies, please refer to the '254 patent. With reference now to FIGS. 5 and 6, the retaining mechanism **130** of the adapter assembly **100** includes a retaining block **140**, a cam wire **150** (FIG. 6) supported by the retaining block **140**, a retaining block extension **160** for maintaining the cam wire **150** relative to the retaining block **140**, a button member **170** in operable engagement with the cam wire **150** and pivotally supported relative to the retaining block **140**, and first and second retainer members **180a**, **180b** (FIG. 6) supported by the cam wire **150** within the retaining block **140**.

With particular reference to FIG. 6, the retaining block **140** of the retaining mechanism **130** defines a central opening **141** for receiving the trocar assembly **120** (FIG. 3), first and second opposed cylindrical openings **143a**, **143b** in communication with the central opening **141** for receiving the respective first and second retainer members **180a**, **180b**, and a channel or slot **145** extending about a perimeter of the retaining block **140** and through the first and second cylindrical openings **143a**, **143b** in the retaining block **140** for receiving the cam wire **150**. The first and second retainer members **180a**, **180b** of the retaining mechanism **130** are supported within the first and second cylindrical openings **143a**, **143b** of the retaining block **140** by the cam wire **150** and are configured to be received within first and second locking openings **123a**, **123b** of the trocar housing **122** of the trocar assembly **120** when the trocar assembly **120** is fully received within the distal portion **104** (FIG. 2) of the adapter assembly **100**.

The cam wire **150** of the retaining mechanism **130** includes a substantially U-shaped member having a backspan **152**, and first and second legs **154a**, **154b** extending from the backspan **152**. The backspan **152** includes a button engagement portion **152a** and a pair of shoulders portions **152b** on either side of the button engagement portion **152a**. Each of the first and second legs **154a**, **154b** includes an opposed angled section **156a**, **156b**. The cam wire **150** is received within the channel **145** of the retaining block **140**. As will be described in further detail below, the cam wire **150** is moveable between a first or lock position (FIG. 8) when the button member **170** is in an initial or non-depressed position, and a second or release position when the button member **170** is depressed.

With continued reference to FIG. 6, the retaining block extension **160** includes a substantially rectangular frame **162**

## 6

defining an opening **161** and a pair semi-cylindrical recesses **163**. First and second pivot portions **174** (only one shown) of the button member **170** are pivotally supported within the semi-cylindrical recesses **163** in the frame **162** and a body portion **172** of the button member is disposed within the opening **161** in the frame **162**. The frame **162** includes a pair of stop surfaces **162a** (FIG. 7) for engaging the shoulder portions **152b** of the backspan **152** of the cam wire **150**, and a stop member, e.g., a stop tab **164**, along a midline "m" of the frame **162** for inhibiting depression of the button member **170**.

The button member **170** of the retaining mechanism **130** of the adapter assembly **100** (FIG. 2) includes the body portion **172** configured for operable engagement by a user, and the pair of pivot portions **174** configured for reception within the pair of semi-cylindrical recesses **163** of the retaining block extension **160**. The button member **170** is configured to engage the engagement portion **152a** of the backspan **152** of the cam wire **150**. In embodiments, the backspan **152** of the cam wire **150** is secured to the button member **170**. For example, and as shown, the body portion **172** of the button member **170** defines a cavity **171** (FIG. 7A) in which the engagement portion **152a** of the backspan **152** is retained through friction fit. Alternatively, the backspan **152** is secured within the cavity **171** with mechanical fasteners, bonding, welding, adhesives, or in any other suitable manner. The retaining mechanism **130** may include a biasing member, e.g., leaf springs **178** (FIG. 6) for biasing the cam wire **150** outwardly to the first position, and/or the button member **170** outwardly to the non-depressed position (FIG. 7).

The button member **170** of the trocar retaining mechanism **130** further includes a center beam **176**, and defines a relief **175** on either side of the center beam **176**. The center beam **176** includes a rib **176a**, or is otherwise configured for engagement by a user. The center beam **176** and reliefs **175** are configured such that the center beam **176** may be flexed away from a midline "M" of the button member **170**. More particularly, the center beam **176** of the button member **170** is configured to align with the stop tab **164** of the retaining block extension **160** when the center beam **176** is in an initial or unflexed condition. In this manner, the center beam **176** of the button member **170** prevents the button member **170** from being depressed. As will be described in further detail below, flexing of the center beam **176** away from the midline "M" of the button member **170** moves the center beam **176** out of alignment with the stop tab **164** of the retaining block extension **160**, thereby permitting depression of the button member **170**. The reliefs **175** in the button member **170** may also facilitate flushing and cleaning of the adapter assembly **100** (FIG. 2).

The first and second retaining members **180a**, **180b** of the retaining mechanism **130** form substantially cylindrical bodies **182a**, **182b** and are supported on the angled portions **156a**, **156b** of the respective first and second legs **154a**, **154b** of the cam wire **150**. In embodiments, the first and second retaining members **180a**, **180b** form a wedge-shaped configuration to be received within wedge-shaped first and second locking openings **123a**, **123b** in the trocar housing **122** of the trocar assembly **120**. The first and second retaining members **180a**, **180b** may include an inclined inner surface (not shown) to facilitate receipt of the trocar assembly **120** through the retaining block **140**.

The first and second retaining members **180a**, **180b** each define a stepped opening **181a**, **181b** through which the respective angled portion **156a**, **156b** of the cam wire **150** is received. The cam wire **150** and the stepped openings **181a**,



181b of the respective first and second retaining members 180a, 180b are configured such that when the cam wire 150 is in the first position, the first and second retaining members 180a, 180b extend from within the retaining block 140 into the central passage 141. In this manner, when a trocar assembly 120 is fully seated within the distal portion 104 (FIG. 2) of the adapter assembly 100, the first and second retaining members 180a, 180b are received within the respective first and second locking openings 123a, 123b (FIG. 7) of the trocar housing 122 of the trocar assembly 120. Conversely, when the cam wire 150 is in the second or release position, the first and second retainer members 180a, 180b are retracted from within the central opening 141 of the retaining block 140 to permit insertion and/or removal of the trocar assembly 120 from the distal portion 104 of the adapter assembly 100.

With reference now to FIGS. 7 and 8, the retaining mechanism 130 of the adapter assembly 100 is shown in a first or lock configuration, with the trocar assembly 120 securely received within the distal portion 104 of the adapter assembly 100. In the lock configuration, the cam wire 150 of the retaining mechanism 130, which is secured to the button member 170, is biased to the first position by the leaf springs 178 (FIG. 6). In the first position, the shoulder portions 152b of the backspan 152 of the cam wire 150 engage the stop surface 162a of the retaining block extension 160. As noted above, when the cam wire 150 is in the first position and the trocar assembly 120 is fully seated within the distal portion 104 (FIG. 2) of the adapter assembly 100, the first and second retainer members 180a, 180b are received within the respective first and second locking openings 123a, 123b in the trocar housing 122 of the trocar assembly 120.

The center beam 176 of the button member 170 of the retaining mechanism 130 is shown in the first or unflexed position. In the unflexed position, the center beam 176 aligns with the midline "M" of the button member 170. When aligned with the midline "M", the center beam 176 engages the stop tab 164 of the retaining block extension 160 which is also aligned with the midline "M" of the button member 170, thereby preventing the button member 170 from being depressed.

Turning to FIG. 9, following use of the adapter assembly 100, or to otherwise remove the trocar assembly 120 from the distal portion 104 of the adapter assembly 100, the rib 176a of the center beam 176 of the button member 170 of the retaining mechanism 130 is moved off-center, or away from the midline "M" of the button member 170, to the flexed position, as indicated by arrow "A", to move the center beam 176 of the button member 170 out of alignment with the stop tab 164 of the retaining block extension 160. As noted above, when the center beam 176 of the button member 170 is misaligned with the stop tab 164 of the retaining block extension 160, the stop tab 164 no longer obstructs or inhibits the button member 170 from being depressed.

With reference to FIG. 10, with the center beam 176 of the button member 170 is in the flexed position, the button member 170 is able to be depressed, as indicated by arrows "B". Depression of the button member 170 causes the cam wire 150 to move from its first position (FIG. 7) to its second position, as indicated by arrows "C". As the cam wire 150 moves to the second position, engagement of the angled portions 156a, 156b of the first and second legs 154a, 154b, respectively, with the respective first and second retainer members 180a, 180b cause the first and second retainer members 180a, 180b to move radially outward, as indicated by arrows "D". Radial outward movement of the first and

second retaining members 180a, 180b withdraws the first and second retaining members 180a, 180b from within the respective first and second locking openings 123a, 123b of the trocar housing 122 of the trocar assembly 120 to permit removal of the trocar assembly 120 from within the distal portion 104 of the adapter assembly 100 (FIG. 2).

FIGS. 11-18 illustrate another embodiment of a retaining mechanism according to the disclosure shown generally as retaining mechanism 230 (FIG. 13). The retaining mechanism 230 is substantially similar to the retaining mechanism 130 described hereinabove and will only be described in detail with regards to the differences therebetween. The retaining mechanism 230 releasably secures a trocar assembly 220 within a distal portion 204 of an adapter assembly 200. The trocar assembly 220 includes a trocar housing 222 (FIG. 16) defining first and second locking openings 223a, 223b for receiving retaining members 280a, 280b (FIG. 16), respectively, of the retaining mechanism 230.

With particular reference to FIGS. 13 and 14, the retaining mechanism 230 of the access assembly 200 includes a retaining block 240 (FIG. 13), a cam wire 250 (FIG. 16) moveably positioned relative to the retaining block 240, an upper retaining block extension 260 securing the cam wire 250 relative to the retaining block 240, a button member 270 pivotally supported by the upper retaining block 260 and in operable engagement with the cam wire 250, first and second retaining members 280a, 280b in operable engagement with the cam wire 250 and moveably disposed within the retaining block 230, a lower retaining block extension 290 disposed opposite the upper retaining block 260 in engagement with the retaining block 240, and a sliding button member 296 slidably supported on the lower retaining block extension 290.

The retaining block 240, cam wire 250, and first and second retaining members 280a, 280b of the retaining mechanism 230 of the access assembly 200 are substantially similar to the retaining block 140, cam wire 150, and first and second retaining members 180a, 180b described above. The upper retaining block extension 260 and the button member 270 are also substantially similar to the retaining block extension 160 and the button member 170. The button member 270 of the retaining mechanism 230 is accessible through a first opening 207 (FIG. 11) in an outer sleeve 206 of the adapter assembly 200. The sliding button member 296 is accessible through a second opening 207b (FIG. 12) in the outer sleeve 206.

FIGS. 14 and 15 illustrate the lower retaining block extension 290 of the retaining mechanism 230 which includes a substantially rectangular frame 292 defining an opening 291 for receiving the sliding button member 296. A pair of cutouts 293 in the frame 292 support a pair of stop members 298a of the sliding button member 296. The lower retaining block extension 290 is received within the outer sleeve 206 (FIG. 16) of the adapter assembly in engagement with the retaining block 240 and opposite the upper retaining block extension 260.

The sliding button member 296 of the retaining mechanism 290 includes a body portion 298 configured for operable engagement by a user, and the pair of stop members 298a extending outwardly from the body portion 298. The stop members 298a ride within the cutouts 293 of the lower retaining block extension 290. The sliding button member 296 is moveable between a first or distal position (FIG. 13) in which the stop members 298a of the sliding button member 296 are aligned with free ends 258a, 258b (FIG. 16) of legs 254a, 254b, respectively, of the cam wire 250 and a second or proximal position (FIG. 17) in which the stop



members **298a** are spaced from the free ends **258a**, **258b** of the legs **254a**, **254b**, respectively, of the cam wire **250**.

A cylindrical recess **297** (FIG. 15) in an end of the sliding button member **296** of the retaining assembly **230** is configured to receive a biasing member, e.g., a coil spring **299** (FIG. 14) for biasing the sliding button member **296** in a first direction, e.g., distally, as shown, to the distal position. The sliding button member **296** is accessible through the second opening **207b** (FIG. 12) in the outer sleeve **206** of the adapter assembly **200**.

FIG. 16 illustrates the retaining mechanism **230** in a first or lock position with the cam wire **250** in a first position and the sliding button member **296** in the distal position. The sliding button member **296** is maintained in the distal position by the coil spring **299**. As described above, when the sliding button member **296** of the retaining mechanism **230** is in the proximal position, the stop members **298a** of the sliding button member **298** are aligned with the free ends **258a**, **258b** of the legs **254a**, **254b**, respectively, of the cam wire **250** to prevent movement of the cam wire **250** to the second position.

FIGS. 17 and 18 illustrate the method for removal of the trocar assembly **230** from the adaptor assembly **200**. When the trocar assembly **230** is removed from the distal portion **204** of the adapter assembly **200**, the sliding button member **296** is moved proximally, against the bias of the coil spring **299**, as indicated by arrows "E". Proximal movement of the sliding button member **296** moves the stop members **298a** of the sliding button member **296** out of engagement with the free ends **258a**, **258b** (FIG. 16) of the legs **254a**, **254b**, respectively, of the cam wire **250**. With the stop members **298a** of the sliding button member **296** no longer preventing movement of the cam wire **250** to the second position, the button member **270** may be depressed, as indicated by arrow "F" to cause the cam wire **250** to move to the second position, as indicated by arrows "G". As discussed in detail above with respect to retaining mechanism **130**, as the cam wire **250** moves to the second position, the retaining members **280a**, **280b** (FIG. 16) move radially outward from within first and second locking openings **223a**, **223b** of a trocar housing **232** of the trocar assembly **230** to release the trocar assembly **230** from within the distal portion **204** of the adapter assembly **200**, and permit removal of the trocar assembly **230** from within the adapter assembly **200**.

FIGS. 19-25 illustrate a release mechanism according to another exemplary embodiment of the disclosure. The release mechanism is shown generally as collar assembly **390**. The collar assembly **390** is configured to depress a button member **370** of a trocar retaining mechanism **320**. More particularly, collar assembly **390** includes an annular member **392** receivable about a distal portion **304** of an adapter assembly **300**. The annular member **392** includes a cam lug **394** extending from an inner surface of the annular member **392** and having an inclined surface **394**. The cam lug **394** is configured to engage and depress the button member **370** during proximal movement of the collar assembly **390** relative to the outer sleeve **306** of the adapter assembly **300**.

The annular member **392** defines a pair of flush ports **391** (FIG. 21), and a slot **393** for receiving a pin **307** extending from an outer sleeve **306** of the adapter assembly **300**. The flush ports **391** align with a flush port **305** on the outer sleeve **306** of the adapter assembly **300**. The pin **307** limits travel of the collar assembly **390** relative to the adapter assembly **300**.

With particular reference to FIG. 22, the collar assembly **390** is shown in a first or distal position. In the distal

position, the cam lug **394** is spaced from the button member **370**. In this manner, the button member **370** is in a first or undepressed position. When the collar assembly **390** is in the distal position, the annular member **392** covers the button member **370** to prevent accidental depression of the button member **370**. In embodiments, the collar assembly **390** may be maintained in the distal position by a biasing member, e.g., coil spring **399** (FIG. 24), received about the outer sleeve **306** of the adapter assembly **300** proximal of the collar assembly **390**. It is envisioned that the collar assembly **390** may be biased distally using a pneumatic cylinder, or in any other suitable manner.

FIG. 23 illustrates the collar assembly **390** as it is moved proximally as indicated by arrows "H". When the collar assembly **390** is moved proximally, as indicated by arrows "H", the inclined surface **394a** of the cam lug **394** of the collar assembly **390** engages the button member **370**, causing the button member **370** to be depressed, as indicated by arrow "I". As the button member **370** is depressed, the cam wire **350** is moved to a second position to cause the release of trocar assembly **320** as described above with reference to retaining mechanism **130** and trocar assembly **120**. As noted above, the pin **307** (FIG. 24) extending from the outer sleeve **306** of the adapter assembly **300** limits travel of the collar assembly **390**.

With reference to FIG. 25, in an alternative embodiment, a collar assembly **490** is configured to be rotated relative to the outer sleeve **406** of the adapter assembly **400** to effect depression of a button member **470** of the retaining assembly **430**. The collar assembly **490** includes an annular member **492** and a cam lug **494** extending from an inner surface of the annular member **492**. The cam lug **494** is configured to engage the button member **470** and defines a slot **493** for receiving a pin **407**. The pin **407** extends from the outer sleeve **406** for limiting movement of the collar assembly **490**.

During use, the collar assembly **490** is rotated about the outer sleeve **406** of the adapter assembly **400**, as indicated by arrow "J". When the cam lug **496** of the collar assembly **490** engages the button member **496**, the button member **496** is depressed, causing a wire cam **450** to move to a second or release position, thereby unlocking a trocar assembly **420** received within the adapter assembly **400**.

Persons skilled in the art will understand that the devices and methods specifically described herein and illustrated in the accompanying drawings are non-limiting exemplary embodiments. It is envisioned that the elements and features illustrated or described in connection with one exemplary embodiment may be combined with the elements and features of another without departing from the scope of the disclosure. As well, one skilled in the art will appreciate further features and advantages of the disclosure based on the above-described embodiments. Accordingly, the disclosure is not to be limited by what has been particularly shown and described.

What is claimed is:

1. An adapter assembly for connecting a loading unit to a handle assembly, the adapter assembly comprising:
  - an outer sleeve;
  - a trocar assembly releasably securable within the outer sleeve, the trocar assembly including a trocar housing defining first and second openings; and
  - a retaining mechanism configured to releasably secure the trocar assembly within the outer sleeve, the retaining mechanism including a retaining block, a cam wire moveably positioned relative to the retaining block between a lock position and a release position, a



**11**

retaining block extension configured to maintain the cam wire relative to the retaining block, a button member in operable engagement with the cam wire, and a pair of retaining members moveable from a first position received within the first and second openings of the trocar assembly when the cam wire is in the lock position and a second position spaced from the trocar assembly when the cam wire is in the release position, the retaining block extension including a stop tab, wherein the button member includes a center beam moveable from an unflexed position in engagement with the stop tab of the retaining block extension to prevent movement of the button member to a flexed position out of alignment with the stop tab to permit movement of the button member.

2. The adapter assembly of claim 1, wherein the button member is pivotable relative to the retaining block from a non-depressed position when the center beam is in the unflexed position and a depressed position when the center beam is in the flexed position.

3. The adapter assembly of claim 2, wherein depression of the button member causes the cam wire to move from the lock position to the release position.

4. The adapter assembly of claim 2, wherein the center beam includes a rib configured for operable engagement by a user.

5. The adapter assembly of claim 2, wherein the button member defines a relief on either side of the center beam to permit movement of the center beam between the unflexed and flexed positions.

6. The adapter assembly of claim 2, wherein the button member defines a midline, the stop tab being aligned with the midline.

7. The adapter assembly of claim 6, wherein the center beam is aligned with the midline when in the unflexed position and is misaligned with the midline when in the flexed position.

8. The adapter assembly of claim 1, wherein the retaining block defines a central opening for receiving the trocar assembly.

9. The adapter assembly of claim 1, wherein each retaining member of the pair of retaining members include a wedge-shaped free end.

10. The adapter assembly of claim 1, wherein the retaining block defines a central opening for receiving the trocar assembly.

11. An adapter assembly for connecting a loading unit to a handle assembly, the adapter assembly comprising:

an outer sleeve; and

a retaining mechanism configured to releasably secure a trocar assembly within the outer sleeve, the retaining mechanism including a retaining block defining a longitudinal passage for receipt of the trocar assembly, a cam wire moveably positioned relative to the retaining block between a lock position and a release position, a retaining block extension configured to maintain the cam wire relative to the retaining block, a button member in operable engagement with the cam wire, and at least one retaining member moveable from a first position extending into the longitudinal passage when the cam wire is in the lock position and a second position clear of the longitudinal passage when the cam

**12**

wire is in the release position, the retaining block extension including a stop member, wherein the button member includes a flexible portion moveable from an unflexed position in engagement with the stop member of the retaining block extension to prevent movement of the button member to a flexed position out of alignment with the stop member to permit movement of the button member.

12. The adapter assembly of claim 11, wherein the button member is pivotable relative to the retaining block from a non-depressed position when the flexible portion is in the unflexed position to a depressed position when the center beam is in the flexed position.

13. The adapter assembly of claim 12, wherein depression of the button member causes the cam wire to move from the lock position to the release position.

14. The adapter assembly of claim 12, wherein the flexible portion includes a rib configured for operable engagement by a user.

15. The adapter assembly of claim 12, wherein the button member defines a relief on either side of the flexible portion to permit movement of the flexible portion between the unflexed and flexed positions.

16. The adapter assembly of claim 12, wherein the button member defines a midline, the stop member being aligned with the midline.

17. The adapter assembly of claim 16, wherein the flexible portion is aligned with the midline when in the unflexed position and the flexible portion is misaligned with the midline when in the flexed position.

18. The adapter assembly of claim 11, wherein the retaining block defines a central opening for receiving the trocar assembly.

19. The adapter assembly of claim 11, wherein each retaining member of the pair of retaining members include a wedge-shaped free end.

20. An adapter assembly for connecting a loading unit to a handle assembly, the adapter assembly comprising:

an outer sleeve; and

a retaining mechanism configured to releasably secure a trocar assembly within the outer sleeve, the retaining mechanism including a retaining block, a cam wire moveably positioned relative to the retaining block between a lock position and a release position, a retaining block extension configured to maintain the cam wire relative to the retaining block, a button member in operable engagement with the cam wire, and a pair of retaining members moveable from a first position engageable with the trocar assembly when the trocar assembly is received within the outer sleeve and the cam wire is in the lock position, and a second position spaced from the trocar assembly when the trocar assembly is received within the sleeve and the cam wire is in the release position, the retaining block extension including a stop member, wherein the button member includes a center beam moveable from an unflexed position in engagement with the stop member of the retaining block extension to prevent movement of the button member to a flexed position out of alignment with the stop member to permit movement of the button member.

\* \* \* \* \*