

US011143412B2

(12) **United States Patent**
Ha

(10) **Patent No.:** **US 11,143,412 B2**
(45) **Date of Patent:** ***Oct. 12, 2021**

(54) **KNOB ASSEMBLY FOR COOK TOP**

(71) Applicant: **LG Electronics Inc.**, Seoul (KR)

(72) Inventor: **Yeonsik Ha**, Seoul (KR)

(73) Assignee: **LG Electronics Inc.**, Seoul (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **16/923,831**

(22) Filed: **Jul. 8, 2020**

(65) **Prior Publication Data**

US 2020/0340676 A1 Oct. 29, 2020

Related U.S. Application Data

(62) Division of application No. 15/900,442, filed on Feb. 20, 2018, now Pat. No. 10,746,409.

(30) **Foreign Application Priority Data**

Feb. 22, 2017 (KR) 10-2017-0023773
Dec. 6, 2017 (KR) 10-2017-0167074

(51) **Int. Cl.**

F24C 3/12 (2006.01)

F24C 3/10 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **F24C 3/124** (2013.01); **F24C 3/103** (2013.01); **G01B 7/003** (2013.01); **G01D 5/145** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC **F24C 3/124**; **F24C 3/103**; **G01B 7/003**; **G01D 5/145**; **G05G 1/10**; **G05G 5/04**; **G05G 5/05**; **H01H 19/03**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,341,647 A 2/1944 Parkhurst
2,738,758 A * 3/1956 Cutler H03J 1/044
116/250

(Continued)

FOREIGN PATENT DOCUMENTS

CN 201408676 2/2010
CN 104508377 4/2015

(Continued)

OTHER PUBLICATIONS

European Office Action in European Appln. No. 18157422, dated Apr. 7, 2020, 6 pages.

(Continued)

Primary Examiner — Thomas C Diaz

(74) *Attorney, Agent, or Firm* — Fish & Richardson P.C.


(57)

ABSTRACT

A knob assembly includes a front panel, a knob located at a front side of the front panel and configured to rotate based on operation by a user, a knob shaft that is coupled to the knob and that extends through the front panel, a supporting pipe that receives the knob shaft and that supports the knob shaft, the supporting pipe being configured to maintain a position relative to the front panel, a valve configured to control supply of gas to the appliance, a valve shaft connected to the valve and configured to control the valve to adjust a flow rate of gas based on rotation of the valve shaft, and a joint that couples the knob shaft to the valve shaft and that is configured to transfer at least one of a rotational motion or a linear motion of the knob shaft to the valve shaft.

20 Claims, 57 Drawing Sheets

1



(51) **Int. Cl.**

G05G 1/10 (2006.01)
G01D 5/14 (2006.01)
G01B 7/00 (2006.01)
G05G 5/05 (2006.01)
G05G 5/04 (2006.01)
H01H 19/03 (2006.01)

FOREIGN PATENT DOCUMENTS

CN	104520646	4/2015
CN	104520646 A	4/2015
CN	205230900	5/2016
DE	202009009727	10/2009
DE	202009009727	11/2009
EP	1881514	1/2008
FR	625708	8/1927
FR	1165543	10/1958
GB	2186668	8/1987
JP	H08152932	6/1996
JP	4439129	1/2010
KR	100854156	8/2008

(52) **U.S. Cl.**

CPC **G05G 1/10** (2013.01); **G05G 5/04**
(2013.01); **G05G 5/05** (2013.01); **H01H 19/03**
(2013.01)

OTHER PUBLICATIONS

(56)

References Cited

U.S. PATENT DOCUMENTS

3,621,158	A	11/1971	Swinstead et al.	
4,300,525	A	11/1981	Delgado et al.	
6,627,828	B1	9/2003	McCartney	
7,479,607	B2 *	1/2009	Sack	B60K 37/06 200/4
9,646,783	B1	5/2017	Stoufer et al.	
2004/0070574	A1	4/2004	Wylie et al.	
2011/0030501	A1	2/2011	May	
2012/0243253	A1	9/2012	Claprod et al.	
2015/0153048	A1	6/2015	Moro et al.	
2016/0265786	A1	9/2016	Choi et al.	
2016/0333990	A1 *	11/2016	Edinger	H03K 17/965

Extended Search Report in European Appn. No. 18157422.9, dated Jul. 18, 2018, 11 pages.
Korean Notice of Allowance in Korean Application No. 10-2018-0135457, dated Oct. 20, 2020, 10 pages (with English translation).
Korean Notice of Allowance in Korean Application No. 10-2020-0048574, dated Nov. 23, 2020, 10 pages (with English translation).
EP Office Action in European Appln. No. 18157422.9, dated May 7, 2021, 6 pages.
U.S. Office Action in U.S. Appl. No. 16/923,831, dated Mar. 2, 2021, 18 pages.
U.S. Office Action in U.S. Appl. No. 16/923,854, dated Mar. 2, 2021, 19 pages.
Chinese Office Action in CN Appln. No. 201811487625.X, dated Dec. 7, 2020, 11 pages (with English translation).

* cited by examiner

FIG. 1




FIG. 2




FIG. 3





FIG. 4






FIG. 5




FIG. 6




FIG. 7

FIG. 8




FIG. 9





FIG. 10






FIG. 11

FIG. 12





FIG. 13






FIG. 14

FIG. 15




FIG. 16





FIG. 17






FIG. 18

FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32





FIG. 33







FIG. 34

FIG. 35






FIG. 36

FIG. 37




FIG. 38




FIG. 39




FIG. 40




FIG. 41




FIG. 42




FIG. 43




FIG. 44




FIG. 45




FIG. 46





FIG. 47






FIG. 48

FIG. 49




FIG. 50





FIG. 51






FIG. 52

FIG. 53




FIG. 54




FIG. 55




FIG. 56





FIG. 57






FIG. 58

KNOB ASSEMBLY FOR COOK TOPCROSS-REFERENCE TO RELATED
APPLICATIONS

This application is a divisional of U.S. application Ser. No. 15/900,442, filed on Feb. 20, 2018, which claims priority to and the benefit of Korean Patent Application No. 10-2017-0023733, filed on Feb. 22, 2017, and Korean Patent Application No. 10-2017-0167074, filed on Dec. 6, 2017, the disclosures of which are incorporated herein by reference in their entirety.

FIELD

The present disclosure relates to a knob assembly for adjusting a timer and a firepower level of a cooking appliance, and a cooking appliance including the same.

BACKGROUND

A cooking appliance can be classified variously, for example, according to the kind of fuel, a heat source, a form, etc., and may be one of home appliances for cooking food.

For example, the cooking appliance may be classified into an open type and a closed type depending on the form of a space where food is placed.

A closed type cooking appliance is a cooking appliance that closes the space where food is placed and cooks food by heating a closed space. For example, an oven, a microwave oven, etc. may belong to the closed type cooking appliance.

An open type cooking appliance is a cooking appliance that cooks food by heating a food item or a food container in an open space. For example, a cooktop, a hob, etc. may belong to the open the cooking appliance.

In some examples, the closed type cooking appliance and the open type cooking appliance may be installed in a single product, and a composite cooking appliance is proposed in which a plurality of heat sources are combined to cook various types of food or a plurality of items of food.

For example, in the composite cooking appliance, the open type cooking appliance may be arranged on the upper side of the closed type cooking appliance. The open cooking appliance may include a plurality of heaters or burners to enable cooking of a plurality items of food at the same time.

One example of the open type cooking appliance is a gas range that uses gas as a fuel. A gas range is a device that cooks food using a flame generated by burning gas.

There are various ways for a user to control an intensity of the flame of the cooking appliance. For example, a method of controlling firepower by adjusting the amount of rotation of a knob by using the knob rotating around a predetermined adjustment shaft are mostly used.

In some examples, the cooking appliance using gas may include a structure in which the amount of opening and closing of the valve of supplying gas is controlled according to the amount of rotation of the knob. In some cases, for safety, a gas valve may rotate with the knob only when the knob is pressed and rotated.

In some examples, the closed type cooking appliance may be used for a long time cooking, and may include a timer for setting a cooking time. In other examples, the open type cooking appliance may include a timer having a cooking time alarm function in order to improve a user convenience.

SUMMARY

The present disclosure may provide a fire power controlling knob assembly capable of setting a timer by using a

knob ring arranged around a knob for controlling the fire power and displaying information, and a cooking appliance including the same.

The present disclosure may mitigate a misalignment of the knob due to an accumulation of an assembly tolerance. A misalignment may cause a degrade of an appearance quality due to a position error of the knob, or operation failure, for example, for fitting the knob.

The present disclosure may provide a support structure in which the knob connected to a valve assembly can be stably supported, thereby improving a reliability of a knob operation.

The present disclosure may provide a structure that can stably couple a display device to a knob ring in which the display device can be properly insulated.

The present disclosure may provide a structure that restricts rotation of the knob in a state where the knob is not pushed, in a knock operation structure in a push and turn manner.

The present disclosure may enable a fine adjustment of a flow rate of the valve assembly according to an installation environment, and to facilitate the fine adjustment of the flow rate without separating the cooking appliance.

The present disclosure may provide a knob assembly in which a joint is arranged between a knob and a valve assembly so that assembly tolerance, etc. generated in the valve assembly may not be transferred to the knob.

The present disclosure may provide a knob assembly for allowing the joint to absorb a position error of a valve shaft so that the knob can be assembled at a predetermined position with regard to a front panel at a predetermined amount of protrusion.

The present disclosure may provide a knob assembly that is rotatable about a knob ring arranged in the periphery of the knob, wherein the knob ring can stably rotate and always return to a predetermined position by an elastic force.

The present disclosure may provide a knob assembly that allows the knob ring to be fixed constant in its initial position.

The present disclosure may provide a knob assembly having a sensor capable of sensing the amount of rotation of a valve shaft and capable of display the size of the fire power on the display device provided on the knob ring by using the sensed amount of rotation of the valve shaft.

The present disclosure may provide a knob assembly that uses a Hall sensor and a magnet as a sensor for sensing the amount of rotation of the valve shaft, and can maintain a constant spacing between the Hall sensor and the magnet even when an operation of the knob is repeated.

The knob assembly according to the present disclosure can be fixed in a state in which the knob handle is aligned in the front panel, thereby improving the appearance quality of the cooking appliance.

In addition, the knob assembly according to the present disclosure absorbs the position error of the valve shaft of the valve assembly in the joint, and a knob shaft coupled to the knob handle can be stably supported on the knob ring, which may mitigate a fitting problem generated during operation of the knob handle.

The knob assembly according to the present disclosure may include a knob ring which can be independently operated at a circumference of the knob handle so that the timer time of the cooker such as the corresponding burner or the oven can be set through the operation of the knob ring.

In some implementations, the display device is provided in the knob ring, and the fire power or the timer time, etc. of the corresponding cooker can be displayed on the display

3

device, thereby resulting in an effect of improving convenience for a user. For example, the display device may have the structure which is coupled to a knob ring body in a state surrounded by a side to the display housing, which is an insulating material, resulting in an effect of securing insulation performance of the display device even when the knob ring body is formed of a metal material.

In some implementations, the knob assembly according to the present disclosure can be stably operated in a state which the position of the knob ring is fixed with regard to the front panel, and by providing a structure in which the knob shaft of the knob is supported to the knob ring, resulting in an effect which can be aligned at a predetermined position with regard to the front panel of the knob handle and the knob ring.

According to the present disclosure, it may be possible to stably provide a measurement result of the knob rotation amount with high accuracy without a noise, and to provide an effect of stably perform an operation control for outputting a rotation state of the knob handle, or the control with regard to the operation performed through the rotation of the knob handle.

In some implementations, the present disclosure not only contributes to a significant reduction in the risk of generating fire due to gas leakage but also secures information on the failure of components for securing the rotation of the knob handle quickly and accurately. It may be possible to provide a highly reliable sensing result since an error due to a noise or an error of an electronic component may be prevented.

In some implementations, by providing an independent operation switch having a function and a shape different from those of an existing knob ring by using a knob ring installed for finishing the knob handle, so that the user can easily select an operation switch suitable for the use, thereby providing improved use convenience, and, by reducing the number of the operation switch arranged on the front surface of the cooking appliance, thereby improving a sense of beauty of the front surface of the device.

In some implementations, the present disclosure may provide a function in which a physical power transmission operation through a knob handle operation and a sensing operation for sensing an operation of the knob handle are simultaneously performed, while suppressing an increase of parts, an assembly process, and a manufacturing cost required for implementing this function. The manufacturing operation may be performed more easily. The present disclosure may effectively improve sensing performance of the operation of the operation switch such as the knob handle and the knob ring.

In some implementations, when two shafts are connected to both ends of the joint, respectively, a connection angle between the first shaft supporting portion and the second shaft connecting portion may be set to a state suitable for connecting the two shafts, and this state can be maintained or changed in accordance with the situation by the elastic force of the elastic member.

Therefore, the present disclosure may provide an effect of capable of effectively absorbing the position error between two shafts without a separate operation for controlling the connecting angle of the first shaft supporting portion and the second shaft supporting portion, and separate operation for fixing an adjusted connecting angle of the first shaft supporting portion and the second shaft supporting portion, and accordingly, effectively connecting two parts which are difficult to be connected to the same axis.

In some implementations, an installation process is possible without the additional operation for adjusting the

4

connection angle, by making the joint be assembled with only a small number of parts, the part management and an assembly operation can be easily made and the cost and time required for the manufacturing of the joint can be reduced.

In some implementations, the present disclosure can prevent a return position deviation of the knob ring provided by the independent operation switch from being generated, thereby effectively preventing an appearance defect of the cooking appliance due to the return defect of the knob ring from being generated.

In some implementations, since a rotation operation of knob ring is possible by applying force beyond a predetermined degree, an operating mistake of the knob ring may be prevented, and the operation feeling for easily recognizing the start of rotation of the knob ring can be provided to the user.

In some implementations, the present disclosure also provides a valve pushing force compensating structure which absorbs an influence due to performance deviation of the valve pressing force so that the valve can be opened only by a pushing force of beyond predetermined level, and thus, it may be possible to reduce a risk generating safety accidents such as fire due to a potential opening of the valve that is not made by an intended operation of the user.

According to one aspect of the subject matter described in this application, a knob assembly includes a front panel that defines an appearance of an appliance, a knob located at a front side of the front panel and configured to rotate based on operation by a user, a knob shaft that is coupled to the knob and that extends through the front panel, a supporting pipe that receives the knob shaft and that supports the knob shaft, the supporting pipe being configured to maintain a position relative to the front panel, a valve located in the appliance and configured to control supply of gas to the appliance, a valve shaft connected to the valve and configured to control the valve to adjust a flow rate of gas based on rotation of the valve shaft, and a joint that couples the knob shaft to the valve shaft and that is configured to transfer at least one of a rotational motion or a linear motion of the knob shaft to the valve shaft.

Implementations according to this aspect may include one or more of the following features. For example, the supporting pipe may include an outer supporting pipe that extends forward of the front panel along a line, and an inner supporting pipe that extends rearward of the front panel along the line. The knob shaft is configured to pass through the outer supporting pipe and the inner supporting pipe. The knob assembly may further include a knob ring located between the front panel and the knob and configured to receive the knob shaft in which the supporting pipe extends from the knob ring. The knob ring may be configured to rotate independently of rotation of the knob based on operation by a user, and the knob ring may include a handle that protrudes forward of the knob and that is configured to receive input from the user.

In some implementations, the joint may include a first shaft coupling portion configured to couple to the valve shaft, a second shaft coupling portion configured to couple to the knob shaft, a joint spring that is located between the first shaft coupling portion and the second shaft coupling portion, and that allows the knob shaft to couple to the valve shaft regardless of deviation of at least one of the knob shaft or the valve shaft from a coaxial direction, and a joint housing that accommodates the first shaft coupling portion, the second shaft coupling portion, and the joint spring, and that is configured to transfer a rotational motion of the first shaft coupling portion to the second shaft coupling portion.

5

In some examples, the valve may include a valve body that defines a gas flow path, a main adjustment part that is located inside of the valve body, and that is configured to, based on the main adjustment part being rotated by the valve shaft, control a flow rate of gas in the gas flow path, an auxiliary adjustment part that is located at a side of the main adjustment part in of the valve body, and that is configured to, based on the auxiliary adjustment part being rotated by a separate tool, control the flow rate of gas in the gas flow path, and a valve cap that is coupled to a front side of the valve body and that covers the front side of the valve body. The front panel may define a service hole that is located at a position corresponding to a projection of the auxiliary adjustment part to the front panel, and that allows access to the auxiliary adjustment part in a state in which the knob is separated from the front panel.

In some implementations, the knob assembly may further include a knob sensor configured to sense rotation of the valve shaft, and the valve cap includes a sensor fixing portion coupled to the knob sensor. The knob sensor may include a sensor plate configured to couple to the sensor fixing portion, a knob sensor housing configured to maintain a posture relative to the sensor plate, a sensor board configured to couple to the knob sensor housing, a plurality of Hall sensors that are radially arranged on the sensor board and that defines a sensing range, a rotating plate configured to couple to the valve shaft and rotate based on rotation of the valve shaft, and a knob sensor magnet located at the rotating plate and configured to pass the sensing range of the plurality of Hall sensors based on rotation of the valve shaft. The valve shaft may be configured to penetrate the sensor plate, the knob sensor housing, and the sensor board.

In some implementations, the knob assembly may further include a sensor spring that is located between the sensor plate and the knob sensor housing, and that is configured to provide elastic force to the knob sensor housing toward the rotating plate. In some examples, the knob assembly may further include a fixed pipe configured to couple to a rear side of the front panel and to support the knob shaft between the supporting pipe and the joint. The knob assembly may further include a support frame that is configured to receive the supporting pipe, that is configured to couple to the rear side of the front panel, and that defines a support frame through hole; and a fixed frame that is configured to couple to the support frame and that extends across the support frame through hole in which the fixed pipe is configured to couple to the fixed frame. In some examples, the fixed pipe may include a second tube part configured to rotatably couple to a front end of the joint.

In some implementations, the knob assembly may further include a locking bracket including a locking piece that is configured to couple to the front side of the front panel, that protrudes to an inside of the knob, and that defines a passage groove at a rear side of the locking piece. The knob may include a guide surface that has a ring shape and that is configured to interfere with the locking piece in which the guide surface defines a cutting section configured to receive the locking piece in an initial position. The guide surface is further configured to (i) based on the knob being in the initial position, interfere with the locking piece to restrict rotation of the knob, and (ii) based on the knob being pushed from the initial position, define a plane coplanar with the passage groove to allow rotation of the knob.

In some examples, the knob may include a knob body that defines an appearance of the knob, and a knob back plate that is coupled to an inside of the knob body, and the guide surface is located at the knob back plate.

6

According to another aspect, an appliance including a burner may include a valve configured to control a flow rate of gas that flows to the burner, and a knob assembly configured to operate the valve. The knob assembly may include a front panel that defines a surface of the appliance, a knob located at a front side of the front panel and configured to rotate based on operation by a user, a knob shaft that is coupled to the knob and that extends from the knob through the front panel, a supporting pipe that receives the knob shaft and that supports the knob shaft, the supporting pipe being configured to maintain a position relative to the front panel, a valve shaft connected to the valve and configured to control flow of gas in the valve, and a joint that is configured to couple the knob shaft to the valve shaft and to transfer at least one of a rotational motion or a linear motion of the knob shaft to the valve shaft.

Implementations according to this aspect may include one or more of the following features. For example, the joint may include a first shaft coupling portion configured to couple to the valve shaft, and a second shaft coupling portion configured to couple to the knob shaft, and the joint is configured to, regardless of deviation of at least one of the knob shaft or the valve shaft from a coaxial direction, transfer at least one of a rotational motion or a linear motion of the second shaft coupling portion to the first shaft coupling portion. The knob assembly may further include a knob ring located between the front panel and the knob and configured to receive the knob shaft, and the supporting pipe may include an outer supporting pipe that extends forward from the knob ring, and an inner supporting pipe that extends rearward from the knob ring.

In some implementations, the knob ring may be configured to rotate independently of rotation of the knob based on operation by a user, and the knob ring may include a handle that protrudes forward of the knob and that is configured to receive input from the user. The joint further may include a joint spring that is located between the first shaft coupling portion and the second shaft coupling portion, and that allows the knob shaft to couple to the valve shaft regardless of deviation of at least one of the knob shaft or the valve shaft from the coaxial direction, and a joint housing that accommodates the first shaft coupling portion, the second shaft coupling portion, and the joint spring, and that is configured to transfer the rotational motion of the first shaft coupling portion to the second shaft coupling portion.

In some examples, the valve may include a valve body that defines a gas flow path, a main adjustment part that is located inside of the valve body and that is configured to, based on the valve shaft rotating the main adjustment part, control a flow rate of gas in the gas flow path, an auxiliary adjustment part that is located inside of the valve body at a side of the main adjustment part, and that is configured to, based on the auxiliary adjustment part being rotated by a separate tool, control the flow rate of gas in the gas flow path, and a valve cap that is coupled to a front side of the valve body and that covers the front side of the valve body. The front panel may define a service hole that is located at a position corresponding to a projection of the auxiliary adjustment part to the front panel, and that allows access to the auxiliary adjustment part in a state in which the knob is separated from the front panel.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a view showing an example of a composite cooking appliance having a timer function.

FIG. 2 is a view showing an example of a position error of an example knob.

FIG. 3 is a perspective view illustrating an example fire power controlling knob assembly disposed in an example case.

FIG. 4 is a perspective view showing the knob assembly without a front panel in FIG. 3

FIG. 5 is a perspective view showing the fire power controlling knob assembly separated into three portions.

FIG. 6 is a perspective view showing the knob assembly of FIG. 4 viewed from a rear surface.

FIG. 7 is a side view of the knob assembly of FIG. 4.

FIG. 8 is a perspective view showing an example knob arranged at an outermost portion of an example case assembly.

FIG. 9 is a perspective view showing an example rear surface of the knob shown in FIG. 8.

FIG. 10 is a perspective view showing the knob of FIG. 8.

FIG. 11 is an exploded view showing the case assembly.

FIG. 12 is an exploded view showing an example inside of the case assembly.

FIG. 13 is a view showing an example arrangement inside of the front panel of the case assembly.

FIG. 14 is an exploded view showing example components arranged outside of the front panel of the case assembly.

FIG. 15 is a view showing an example state arranged outside of the front panel of the case cooking assembly.

FIG. 16 is a perspective view showing an example appearance of the knob ring in an assembled state.

FIGS. 17 and 18 are the exploded perspective views showing example assembly structures of the knob ring.

FIG. 19 is a perspective view of an example display device of an example knob assembly.

FIG. 20 is a perspective view showing a rear surface of an example display device.

FIG. 21 is a perspective view showing an example display housing.

FIG. 22 is a perspective view showing a rear surface of the display housing.

FIG. 23 is a perspective view showing a rear surface of an example knob ring of an example knob assembly.

FIGS. 24 and 25 are the views showing example coupling structures, an example display device, and an example knob assembly.

FIG. 26 is a perspective view showing an example knob ring back plate.

FIG. 27 is a perspective view showing a rear surface of the knob ring back plate.

FIG. 28 is a longitudinal sectional view showing an example knob ring.

FIG. 29 is a view showing an assembly of an example display cover.

FIG. 30 is a perspective view illustrating an example display cover.

FIG. 31 is a half sectional view showing an example display cover.

FIG. 32 is a sectional view showing an example state before the display cover of the knob assembly is coupled.

FIG. 33 is a cross-sectional view showing an example state in which an example display cover is coupled to the knob assembly.

FIG. 34 is a cross-sectional view showing an example joint separated from the knob assembly.

FIG. 35 is a perspective view showing an example joint of the knob assembly.

FIG. 36 is an exploded perspective view illustrating an example joint.

FIG. 37 is a longitudinal sectional view showing an example joint.

FIG. 38 is a transverse cross-sectional view showing an example joint.

FIG. 39 is a cross-sectional view showing an example joint portion.

FIGS. 40 and 41 are the views illustrating rotating operation of the joint.

FIG. 42 is a perspective view of an example valve assembly.

FIG. 43 is an exploded perspective view showing the valve assembly.

FIG. 44 is a perspective view showing an example valve.

FIG. 45 is an exploded perspective view showing an example valve.

FIG. 46 is a longitudinal sectional view showing an example valve.

FIG. 47 is a transverse cross-sectional view showing an example valve.

FIG. 48 is an exploded perspective view showing an example knob sensor.

FIG. 49 is a perspective view showing an example knob sensor board.

FIGS. 50 and 51 are the sectional views showing example operations of the valve assembly.

FIG. 52 is a longitudinal sectional view showing an example operation and supporting structure of the knob assembly.

FIG. 53 is a rear view showing the example knob ring.

FIG. 54 is a transverse cross-sectional view showing an example coupling state of knob ring of the knob assembly.

FIGS. 55 and 56 are views showing example operations of the knob ring.

FIG. 57 is a perspective view showing an example state in which the knob of the knob assembly is separated.

FIG. 58 is a transverse cross-sectional view showing an example state in which an example knob is separated from the knob assembly.

DETAILED DESCRIPTION

Hereinafter, the implementations of a fire power controlling knob assembly and a cooking appliance including the same according to the present disclosure will be described in detail with reference to the accompanying drawings. For convenience of explanation, the thicknesses of the lines and the size of the component shown in the drawings may be shown with exaggerated for clarity and convenience of explanation. In addition, the terms described below are the terms defined in consideration of a function of the present disclosure, which may vary depending on an intention or custom of the user and the operator. Therefore, the definition of these terms should be based on the contents throughout this specification.

FIG. 1 is a view showing an example of a composite cooking appliance having a general timer function.

The illustrated cooking appliance is a composite cooking appliance 1 including an oven and a cooktop.

The composite cooking appliance 1 may include a fire power controlling knob 2 for controlling the fire power of the cooking appliance on the front upper portion, a timer knob 3 for setting the timer time, a display device 4 for displaying various states of the cooking appliance, and a switch 5 for separate operation.

In the case of the cooking appliance such as an oven or a grill, since there are many cases that a long time operation is required, a timer is almost necessarily installed.

A fire power controlling knob **2** and the timer knob **3** perform different functions from each other, but have the advantage of being able to display a firepower or time through the amount of rotation. For unity of design and convenience of operation, it is general that knobs having the same outer shape are provided as a form arranged side by side.

In addition, the display device **4** serves to display an operation state of the cooking appliance, etc. Information displayed on the display device **4** may be an output (or temperature) of a burner, a timer time, a cooking of the automatic cooking function, etc.

However, when the number of burner provided with the timer function is increased, the number of the timer knob **3** has to be also increased, so that the problem that the front surface shape of the cooking appliance **1** becomes complicated is generated. In addition, a concern of confusing as to which timer knob **3** that performs cooking at the same time in various burners will indicate the cooking time of which burner.

FIG. **2** is a view for explaining a generation of position error of the fire power controlling knob.

As shown, the burner provided in the cooking appliance has a valve assembly **8** for controlling a gas supply amount, and the valve assembly **8** is operated by a knob **2** exposed to the front surface of a front panel **10** and adjusts the gas supply amount provided to the burner.

The connection between the valve assembly **8** and the knob **2** is made by a valve shaft **9** installed to connect between the valve assembly **8** and the knob **2**. When the knob **2** is turned in a state the connection between the valve assembly **8** and the knob **2** is made, this rotational force is transmitted to the valve assembly **8** through the valve shaft **9**, thereby operating the valve assembly **8**.

The opening and closing amount of the valve is controlled by the operation of the valve assembly **8** made as described above.

The knob **2** and a knob ring **6** that annularly surrounds the periphery of the knob **2** are exposed to the appearance of the front panel **10**.

The knob **2** is rotatably installed in the left and right direction and the valve shaft **9** is rotatably coupled in connection with the rotation of the knob **2**. The valve shaft **9** having one side in the axial direction coupled to the knob **2** is rotated in connection with the rotation of the knob **2** and the rotational force transmitted through the valve shaft **9** is a power for the operation of the valve assembly **8**.

In some examples, the valve assembly **8** is manufactured by a welding method on a casting. Thus, in the manufacture of the valve assembly **8**, the valve shaft **9** has a positional tolerance. This tolerance of the valve shaft **9** results in a positional deviation of the knob **2** which is eventually assembled to the valve shaft **9**. Further, the positional deviation of the knob **2** becomes larger as the length of the valve shaft **9** becomes longer.

That is, the tolerance of the valve shaft **9** is directly connected by the assembly tolerance of the knob **2** and the knob ring **6** assembled to the valve shaft **9**.

In the figure, the correct assembled positions the knob **2** and the knob ring **6** are the positions indicated by dotted lines. However, when the tolerance of the valve shaft **9** is generated as indicated by a solid line, the assembled position of the knob **2** and the knob ring **6** is changed as indicated by the solid line.

A single cooking appliance may include a plurality of burners. In some cases, the knob **2** and the knob ring **6** connected to the respective valves needs to be arranged with a predetermined alignment. In some cases, due to a tolerance in each of the valve shaft **9**, the alignment the knob **2** and the knob ring **6** may be externally misaligned, thereby degrading the appearance quality.

In some examples, the tolerance of the valve shaft **9** not only causes a simple appearance defect, but also causes an operation defect. The rotation operation of the knob **2** is not smoothly made due to the misalignment of the valve shaft **9** and it causes the defect which is not returned since the knob **2** is fitted.

The present disclosure is provided so as to improve the appearance quality of the cooking appliance and reduce the operation defect of the knob **2** by assembling the knob **2** and the knob ring **6** at a correct position, in order to resolve the above-mentioned problem.

FIG. **3** is a perspective view showing a state in which the fire power controlling knob assembly in accordance with an exemplary implementation of the present disclosure is assembled into a front panel, FIG. **4** is a perspective view showing by removing a front panel from FIG. **3**, FIG. **5** is a perspective view showing a state which a fire power controlling knob assembly in accordance with an exemplary implementation of the present disclosure is separated into **3** portions, FIG. **6** is a perspective view of the knob assembly of FIG. **4** viewed from the rear side, and FIG. **7** is a side view of the knob assembly of FIG. **4**.

As shown, the fire power controlling knob assembly in accordance with an exemplary implementation of the present disclosure includes a case assembly **100** assembled to the front panel **10**, a valve assembly **300** fixed in the cooking appliance, a joint **200** connecting a knob shaft (**116** of FIG. **8**) of the case assembly **100** and the valve shaft (**330** of FIG. **5**) of the valve assembly **300**.

In addition, a knob sensor **400** for sensing a rotation angle of the knob shaft **116** is arranged on the valve assembly **300** and a knob ring sensor **500** for sensing the rotation of the knob ring **120** is arranged on the case assembly **100**.

The case assembly **100** includes a knob **110** and a knob ring **120** which are exposed to the outside the front panel **10**. Inside of the case assembly **100**, a support frame **150** is coupled. The support frame **150** is directly fastened to the front panel **10** and the other components of the case assembly **100** have the structure coupled to or supported by the support frame **150**.

The knob **110** serves to control an ignition and firepower of the burner. The knob **110** is operated in such a manner that it is rotated while being pushed. Therefore, the knob **110** has to be movable in the front and rear direction of the front panel **10**. Hereinafter, the frontward and rearward working distance of the knob **110** is referred to as a front and rear direction stroke.

Since the knob **110** has frontward and rearward stroke, the knob **110** has to be spaced from the front panel **10** by a spacing corresponding to the forward and rearward strokes in a state of an external force is not applied. Such spacing of the knob **110** adversely affects the appearance quality.

The original knob ring **120** has begun to be applied for the purpose of covering that the knob **110** is separated from the front panel **10**. The knob ring **120** is fixed to the front panel **10** so as to surround the periphery of the knob **110** not to be exposed for the spacing of knob **110** from the front panel **10**. Thus, the knob ring **120** had a structure fixed to the front panel **10**, unlike the knob **110**.

11

As a result, the knob ring is fixed to the front panel **10**, and the knob **110** is the structure fixed to the valve shaft inside the cooking appliance. In such a structure, when a position error occurs in the valve shaft, it had a problem that the knob **110** is not arranged in a centering.

In order to solve such problem, the methods have been attempted to support the knob **110** so that it can be arranged at the center of the knob ring **120**. However, in this case, when an error occurs in the valve shaft, the knob is excessively rubbed with the knob ring, or the valve shaft is excessively rubbed at the support member, resulting in a result that the operation of the knob is not smooth.

In order to solve such a problem, the present disclosure provides that the fire power controlling knob assembly is divided into three portions, and the joint **200** is arranged between the case assembly **100** and the valve assembly **300**, so that the joint absorbs the positional error and secures operation performance of the knob **110**.

In addition, according to the present disclosure, the knob ring **120**, which had a character of an ornament for improving a conventional appearance quality, can perform a function as an operation switch for timer setting. In addition, it is characterized in that a display device **125** may be arranged on the knob ring **120** so that the set timer time can be displayed through the display device **125** arranged on the knob ring **120**.

At this time, the display device **125** attached to the knob ring **120** may display an intensity of the fire power together with the timer time. A display cover is provided outside the display device **125**, but a detailed assembly structure of the display device **125** will be described later. In the shown drawings, a reference numeral of the display device is displayed at a position corresponding to the position of the display device **125**.

The display device **125** is arranged at the upper center of the knob ring **120**. In addition, the display device **125** is arranged in an inclined form toward the upper portion so that it can be arranged to keep at a state close to right angle from the display device **125** and a view of the user, when the user positioned forward the cooking appliance views the display device **125**. It results in an effect of improving a visibility of the display device **125**.

This arrangement results in an effect of making it easy to identify the timer time displayed on the display device **125** during an operation of the knob ring **120**. The user turns to the left or right of the knob ring **120** and set the timer time. In this operation process, it results in an effect that the display device **125** is not covered by the user's hand.

The valve assembly **300** is assembled to a gas pipe **30** and a gas pipe frame **35**, which are fixed inside a cooking appliance body.

In the assembly process of a product, it is made by the method that the front panel **10** is assembled after manufacturing the cooking appliance body. When the gas pipe **30** and the gas pipe frame **35** are assembled to the cooking appliance body, the valve shaft **330** is fixed to the cooking appliance body.

In this state, after assembling the joint **200** to the valve shaft **330** and finally, the front panel assembled with the case assembly is assembled to the cooking appliance, main body and the knob shaft **116** is fitted into the joint **200**, and the assembly is coupled.

The joint **200** absorbs the position error between the knob shaft **116** and the valve shaft **330** and serves to transmit a rotation and pushing of the knob shaft **116** to the valve shaft **330**. Therefore, since the error of the valve shaft **330** is not

12

transmitted to the knob **110**, it is possible to reduce the position error of the knob **110** and secure operation performance of the knob **110**.

Conventionally, it has the structure that the knob is directly assembled to the valve shaft, so that the position error generated in the valve shaft is transferred directly to the knob, as itself, that is exposed to the appearance, and it has a problem of degrading the appearance quality of the cooking appliance.

In some implementations, the knob assembly of the present disclosure is assembled with a state that the knob **110** aligned with regard to the front panel **10**, and the position error of the valve shaft **330** is absorbed in the joint **200**, and thus, the knob **110** does not transfer the position error of the valve shaft **330** even when the position error is generated due to an assembly tolerance in the valve shaft **330** because the position error of the valve shaft **330** is absorbed in the joint **200**.

This is because the knob **110** is independently assembled at an aligned position with regard to the front panel **10** and then connected to the valve shaft **330** inside the cooking appliance by the joint **200**.

FIG. **8** is a perspective view showing a knob arranged at an outermost portion of the case assembly, FIG. **9** is a perspective view showing a rear surface of the knob in FIG. **8**, and FIG. **10** is a perspective view showing a state in which a knob back plate shown in FIG. **8** is separated.

In some examples, the knob **110** has the structure directly fitted to the valve shaft **330**, but it is characterized in that the knob **110** of the knob assembly according to the present disclosure provides the knob shaft **116** separately when the valve shaft **330**. As described above, the knob shaft **116** is connected to the valve shaft **330** through the joint **200**.

The knob **110** includes a knob body **112** that forms an appearance, a knob back plate **114**, and a knob shaft **116**. The knob body **112** and the knob shaft **116** may be integrally formed as a single portion and may be manufactured as separate portions and then coupled.

In some implementations, the knob shaft **116** may be made of a metal material for high strength and reliability. The knob body **112** may be manufactured of an injection portion forming the appearance, but a metal material processed goods is used in the case of an expensive product group.

In some examples, when the portion integrally made of the knob body **112** and the knob shaft **116** is manufactured through the metal processing, the time and cost required for manufacturing the portions become excessive. In order to manufacture the metal part having such a shape, a cutting processing is generally. However, since the size of a raw material for cutting processing is increased, there are many the cut scraps, thereby increasing the processing time and the processing unit cost.

However, even when the knob body **112** and the knob shaft **116** are the same metal material, the processing cost may be lowered when separately manufacturing it, and coupling it. In this case, the knob body **112** is manufactured by cutting processing, and the knob shaft **116** is applicable to a method of manufacturing a wire material such as rolling, etc.

At this time, the coupling between the knob body **112** and the knob shaft **116** can use the method of a shrinkage fitting, an indentation, and a welding, etc.

In some examples, the knob back plate **114** coupled to the rear surface of the knob body **112** is advantageous from the viewpoint of cost using a molding portion because it is less exposed externally and has a complicated shape.

13

The knob back plate **114** functions in order for not to be operate the knob **110** in a state without pushing the knob **110** together with a locking bracket (**140** of FIG. **11**) described later.

The knob back plate **114** provides a guide surface **114c** extending to the center side of the knob shaft **116** and the guide surface **114c** provides a cutting section **114b** at the portion corresponding to the position of the locking bracket **140** when the knob **110** is in the origin position (the position in an off state).

In other words, when the knob is not pushed when the knob **110** is in the off state, the locking piece (**142** in FIG. **14**) of the locking bracket is positioned inside the cutting section **114b**, one side of the guide surface **114c** becomes an engaging surface **114d** and interferes with the locking bracket **140**, and thus, a user may not rotate the knob **110**.

When the knob **110** is pushed, the engaging surface **114d** becomes a position corresponding to a knob passage groove **144** provided in the locking bracket **140**, and the engaging surface **114d** passes through the knob passage groove **144** and it is in a state of being able to rotate. Accordingly, in a state which the knob **110** is pushed, the knob **110** can be rotated.

General push and turn type knobs have a structure in which the knob **110** itself can rotate even in a state which the knob is not pressed, but the rotational force of the knob **110** is not transmitted to the valve. The present disclosure provides a structure which cannot be rotated even for the knob **110** in a state the knob **110** is pushed by using an interference of the locking bracket **140** and the knob back plate **114**, as described above.

In some examples, the engaging surface **114d** defined on the guide surface **114c** of the knob back plate **114** may be aligned with the locking bracket **140**, and the locking bracket **140** may be aligned with the origin position of the knob body **112**. Accordingly, the knob body **112** and the knob back plate **114** may be constrained and may not rotate with regard to each other.

In some implementations, the knob back plate **114** may be fastened to the knob body **112** through the fastening hole **114a**. Although the shown knob body **112** is shown as a straight handle shape, it may be formed simply as a conical shape, and may have a shape in which the origin position is engraved or colored, and a knob design having various other shapes may be applied in addition to that.

Hereinafter, all configuration of the case assembly except the knob will be described.

FIG. **11** is a view showing the separated state of all configurations of the case assembly, FIG. **12** is a view showing a separated state of the configurations arranged inside the front panel of the case assembly, FIG. **13** is a view showing a state which the configurations inside the front panel of the case assembly is arranged, and FIG. **14** is a view showing a separated state of the configurations arranged to the outside the front panel of the case assembly, and FIG. **15** is a view showing a state which the configurations arranged outside the front panel of the case assembly are assembled.

As shown, the case assembly **100** includes the knob (**110** of FIG. **8**), the knob ring **120**, a spacing plate **130**, the locking bracket **140**, the support frame **150**, a spacing pipe **160**, an actuating member **170**, a fixed frame **180**, and a fixed pipe **190**.

Among them, the knob **110**, the knob ring **120**, the spacing plate **130**, and the locking bracket **140** are arranged outside the front panel **10**.

14

The support frame **150**, the spacing pipe **160**, the actuating member **170**, and the fixed frame **180**, and the fixed pipe **190** are arranged inside the front panel **10**.

The present disclosure provides the structure which the knob ring **120** provided in the case assembly **100** is rotatable in both directions in a predetermined range and includes a knob ring sensor **500** of sensing the rotation of the knob ring **120**. In addition, a knob sensor **400** for sensing the amount of rotation of the knob **110** to be described later is arranged in the valve assembly **300** and connected to the valve shaft **330**.

The knob ring **120** includes a knob ring body **122**, a knob ring back plate **124**, a display device **125**, a display housing **126**, and a display cover **127**.

The knob ring body **122** forms the appearance of the knob ring **120** and serves to fix the display device **125**. The display housing **126** secures insulating performance of the display device **125**, which is an electronic component, and secures to be fastened to the knob ring body **122**. The display cover **127** together with the knob ring body **122** forms the appearance of the knob ring **120**.

The knob ring body **122** may be made of a metal material similar to the knob body **112**. Since the knob ring body **122** is a portion which the user's hand has to be continuously contacted like the knob body **112**, a metal material may be used for improving a sensitive quality, improving the appearance quality, and improving a durability.

The display cover **127** is coupled as a form of surrounding the outer surface of the display device **125** and the display housing **126** received therein. The display cover **127** may be made of a semi-translucent material so that only information displayed on the display device **125** can be viewed while the inner component is not visible to the outside.

Here, the translucency may be a degree of transmitting of a portion of a light emitted from a display, and does not mean of limiting the range of a predetermined translucent ratio.

The display device **125** is coupled to the display housing **126** and the display housing **126** coupled with the display device **125** is coupled to the knob ring back plate **124**, and then, the knob ring back plate **124** coupled with the display housing **126** is coupled to the knob ring body **122**.

In some implementations, the display housing **126** and the knob ring body **122** may provide the groove and the protrusion at positions corresponding to each other, so that the display housing **126** can be assembled at an aligned position with regard to the knob ring body **122**.

The display cover **127** which forms the appearance of the knob ring **120** together with the knob ring body **122** is a structure which is fitting coupled to the knob ring body **122** in a state which the knob ring body **122** and the knob ring back plate **124** are fastened.

In some examples, a spacing plate **130** is arranged between the knob ring back plate **124** of the knob ring **120** and the front panel **10**. The spacing plate **130** is a kind of thrust bearing and serves not to directly rub the knob ring **120** and the front panel **10**, and maintain the predetermined spacing between the knob ring **120** and the front panel **10**.

It is possible to set the spacing between the rear surface of the knob ring **120** (the rear surface of the knob ring back plate) and the outer surface of the front panel **10** by adjusting the thickness of the spacing plate **130**.

The spacing plate **130** may be made of a material having a low coefficient of friction such as Teflon, and a lubricant having viscosity may be applied to the surface of the spacing plate **130**.

15

The configuration which is directly fastened to the front panel **10** of the external configurations of the front panel **10** is the locking bracket **140**. The locking bracket **140** serves not to rotate without pushing the knob **110** in Push & Turn method.

The locking bracket **140** is directly fastened to the front panel **10** through a bracket hole **124b** provided in the knob ring back plate **124**.

Since the knob ring back plate **124** rotates in both directions together with the knob ring **120**, the bracket hole **124b** is formed as an arc long hole in the knob ring back plate **124**. It is such that the knob ring back plate **124** is rotated in a state which the locking bracket **140** is fastened to the front panel.

In addition, the spacing plate **130** is closely attached to the outer surface of the front panel **10**. In the shown implementation, the spacing plate **130** is provided with a bracket groove **132** at a portion corresponding to the fastening position of the locking bracket **140**.

It is for the locking bracket **140** to be directly attached to the surface of the front panel **10** and fastened. However, since the spacing plate **130** does not rotate with the knob ring but maintains the fixed position, it is sufficient that the bracket groove **132** is formed to have a size corresponding to the fastening surface of the locking bracket **140**.

Of course, as another implementation, the locking bracket **140** may be fastened to the front panel through the spacing plate **130**. In this case, the spacing plate **130** may be provided with a fastening hole which can be extension formed to the portion corresponding to the fastening surface of the locking bracket **140** and can penetrate a fastening vole **S3** for fastening the locking bracket **140**. The locking bracket **140** can be repeatedly applied with a lateral force, and the fixing of the center position is important. In some implementations, the locking bracket **140** may be fastened to the front panel **10** with at least two fastening bolts **S3**.

In some examples, the front panel **10** is provided with a wiring hole **12** for passing through the wiring connected to the display device **125**. The wiring hole **12** is for passing the wiring that supplies power and a signal to the display device **125**. The display device **125** is fixed to the knob ring **120** and rotates together with the knob ring **120** so that the wiring is rotated together with the knob ring **120**. Therefore, the wiring hole **12** is formed as an arc-shaped long hole.

The support frame **150**, the spacing member **160**, the actuating member **170**, the fixed frame **180**, the fixed pipe **190**, and the knob ring sensor **500** of FIG. **12** are arranged inside the front panel **10**.

The support frame **150** is directly fastened to the front panel **10** through the fastening bolt **S1** penetrating through the front panel **10** in a state which is arranged on the inner surface of the front panel **10**. The head of the fastening bolt **S1** is inserted into the bolt receiving hole **133** of the spacing plate **130** to serve as a fixing protrusion for fixing the position of the spacing plate **130**.

The support frame **150** provides a pair of spring fixing portions **155** to which the restoring springs **156a** and **156b** of providing the restoring force of the actuating member **170** are fixed. In addition, a restoring magnet **158** is fixed to the support frame **150** so that the actuating member **170** can have a fixing force at the origin.

The actuating member **170** is fitted inside the support frame **150** and then is fastened to the knob ring **120** through a fastening bolt **S2**. Thus, the actuating member **170** can rotate integrally with the knob ring **120**. The actuating member **170** provides the spring fixing portion **175** to which the restoring spring **156a**, **156b** is fixed. The spring fixing

16

portion **175** of the actuating member **170** is arranged between the spring fixing portions **155** of the support frame **150** and they are connected by a pair of restoring spring **156a**, **156b**.

When the knob ring **120** is rotated to one side, it is configured such that one restoring spring is tensioned and the other restoring spring is compressed. When the external force applied to the knob ring **120** is released, it is configured such that the knob ring **120** can be returned to the origin position by the elastic force of the restoring spring **156a**, **156b**.

In addition, the actuating member **170** is provided with a restoration magnet **178** paired with the restoration magnet **158** of the above-mentioned support frame **150**. The restoring magnet **158** arranged in the support frame **150** and the restoring magnet **178** arranged in the actuating member **170** are arranged at a position corresponding to each other such that the knob ring **120** is the closest position in a state which it is located at the origin.

In the illustrated implementation, four fastening bolts **S2** are applied to firmly fasten the actuating member **170** having a cylindrical shape and the knob ring back plate **124**. However, three fastening bolts **S2** can be fastened at a spacing of 120° .

In some examples, the actuating member **170** is partially protruded from the front surface of the front panel **10** through the support frame **150** so as to be in direct contact with the knob ring back plate **124** and can be fastened. This is to make the actuating member **170** protruding outside the front panel **10** support the knob ring back plate **124**.

The actuating member **170** includes an operating portion **171** inserted into the support frame **150**, a support portion **172** formed in a flange shape at the inner end of the operating portion **171**, and an extended portion **173** from both sides of the support portion **172** to the outside. A spring fixing portion **175** is provided on the extended portion **173** on one side.

In addition, the extended portion **173** is provided with a magnet groove **177** into which the restoring magnet **178** is inserted. The restoration magnet **178** fixed to the actuating member **170** is arranged so as to generate a magnetic force in a direction closely attached to the restoring magnet **178** fixed to the support frame **150**. It is for the actuating member **170** to be fixed by the attaching power of the restoring magnets **158,178** at the origin position.

In addition, the outer circumferential surface of the actuating member **170** operates by the rubbing with the inner surface of a support frame through hole **151** of the support frame **150**.

In some examples, the spacing member **160** is made of Teflon, etc. having a low coefficient of friction like the spacing plate **130** and inserted between the outer circumferential surface of the actuating member **170** and the inner circumferential surface of the support frame through hole **151**. The spacing member **160** may be formed in a cylindrical shape which one surface is cut so as to have a variable diameter.

In the case of the illustrated implementation, the spacing plate **130** and the spacing member **160** are shown as separate portion. However, the spacing plate **130** and the spacing member **160** are made of the same material such as Teflon having a low coefficient of friction and they may be integrally formed as a single part because there are the portions which are in contact with each other.

In addition, a lubricant (for example, grease) for reducing the rubbing and the noise can be applied to the surface of the spacing plate **130** and the spacing member **160**.

The fixed frame **180** secures to support the rear surface of the actuating member **170** to prevent the actuating member **170** from being pushed and entered into the inside of the front panel.

The fixed frame **180** may be provided for convenience of the assembly. The actuating member **170** has to be fastened to the knob ring **120** as described above. When the fixed frame **180** is not provided, a fastening work has to be performed in a state when the knob ring **120** and the actuating member **170** are fixed by hands or a tool.

However, when the fixed frame **180** is provided, when the actuating member **170** is inserted into the support frame **150** and the fixed frame **180** is fastened to the rear surface of the actuating member **170**, the actuating member **170** cannot deviate from the support frame **150**. Therefore, when the knob ring **120** is assembled, the knob ring **120** is aligned to the actuating member **170** on the front side of the front panel, and then the fastening operation can be performed, and thus, workability is improved. The fixed frame **180** has a rotatable region **182** that defines a rotation angle of the extended portion **173** of the actuating member **170**.

In addition, since the actuating member **170** is integrally rotated with the knob ring **120**, the knob ring sensor **500** senses the knob ring sensor magnet **530** fixed to the actuating member **170** and can recognize the operation of the knob ring **120**.

The knob ring sensor **500** is fastened to the support frame **150** directly fastened to the front panel **10**. Since the knob ring sensor **500** is sufficient to be fixed at a position close to the actuating member **170**, it may be fastened to the fixed frame **180** or directly fastened to the front panel **10**, depending on the shape.

In addition, a fixed pipe **190** is fastened to the rear surface of the fixed frame **180**. The fixed pipe **190** serves to support the knob shaft **116** provided on the knob **110** and guide the assembly of the joint **200**.

Referring to FIG. **14**, the head of the fastening bolt **S1** of fixing the support frame **150** and the front panel **10** is a state exposed on the outer surface of the front panel **10**. An appearance exposure of the fastening bolt **S1** results in a degradation of the appearance quality.

In some examples, in order to make the knob ring **120** rotate in both directions, a gap may be defined between the knob ring **120** and the front panel **10**.

As described above, the gap between the knob ring **120** and the front panel **10** can be secured by the spacing plate **130**. In addition, the present disclosure provides a structure in which the spacing plate **130** surrounds the support frame fastening bolt **S1** to which the appearance is exposed, so that the fastening bolt **S1** is not externally exposed.

Of course, since the knob ring **120** is arranged on the front surface of the fastening bolt **S1**, the fastening bolt **S1** is not exposed on the front surface. However, when the user views it from the side, this is because that the fastening bolt **S1** can be viewed through a gap (a gap for the rotation of the knob ring) between the knob ring **120** and the front panel **10**.

For this, the spacing plate **130** is provided with a bolt receiving hole **133** at a position corresponding to the support frame fastening bolt **S1**. In addition, the spacing plate **130** has a through hole **135** at the center and an inner circumferential surface of the through hole **135** has the surface of being supported by the actuating member **170** protruding to the outside the front panel **10**.

Therefore, the spacing plate **130** may not require separate fastening. This is because the knob ring **120** which is closely

attached to the front surface of the spacing plate **130** is fastened to the actuating member **170** with the front panel **10** therebetween.

Next, the assembly structure of the knob ring **120** will be described in more detail.

FIG. **16** is a perspective view showing an appearance in a state which the knob ring is assembled, and FIGS. **17** and **18** are the exploded perspective views for explaining an assembling structure of the knob ring.

As shown, the knob ring body **122** has a ring shape surrounding the rear surface of the knob, and the remaining portions except the portion penetrating through the knob shaft **116** at the center are covered by the knob ring back plate **124**.

The knob ring body **122** has a protruding portion **122a** that covers both sides of the display device **125** on the upper side. The protruding portion **122a** provides a structure for fixing the display device **125** while securing to protect the side of the display device **125**. In addition, the protruding portion **122a** of the knob ring body **122** can be used as a handle when the user operates the knob ring body **122**.

When rotating a circular product, the force to rotate only through the frictional force of the surface is transmitted. There are many cases that it is not easy to secure a frictional force in a kitchen environment having many cases that a lot of water is used and the gloves are used by wearing.

In this case, when the protruding portion **122a** is on one side of the ring shape, by pushing it, the protruding portion in the rotating direction, the rotating force can be transmitted. For example, when the knob ring **120** is to be rotated in clockwise, the side of the left protruding portion **122a** may be pressed to the right side. In some examples, when the knob ring **120** is to be rotated counterclockwise, the side of the right protruding portion can be pressed to the left.

The knob ring body **122** provides a knob ring back plate **124** and a fastening hole **122h** for fastening. Although four fastening holes **122h** are provided for firm and accurate fastening of the shown implementation, the number of fastening holes **122h** may vary depending on the fastening structure, the size of the knob ring **120**, etc.

When the protruding portion **122a** is provided on the upper part of the knob ring body **122** and the display device **125** is inserted therebetween, both sides and the bottom surface of the display device **125** are surrounded by the knob ring body **122**. In addition, the display cover **127** is coupled in a form of covering the upper surface of the display device **125** and the rear surface of the display device **125** is coupled to the knob ring back plate **124**. As a result, all of six sides of the display device are wrapped, and provide the structure which the display device **125**, which is vulnerable to moisture and impact, can be securely coupled to the knob ring **120**.

A protrusion **122a** and a groove **122b** for constraining the display housing **126** to a center position are provided inside the protruding portion **122a** of the knob ring body **122**.

The knob ring body **122** may be made of a metal material like the knob body **112**. The knob body **112** and the knob ring body **122** are the portions exposed to the appearance, and are the portions which the user's hands are repeatedly contacted and may be manufactured of a metal material for improving durability and appearance quality.

In some examples, the knob ring body **122** is fastened to the knob ring back plate **124** and the fastening bolt **S5** is fastened at the knob ring back plate **124** side. It is for the fastening bolt **S5** not to be exposed to the appearance, thereby resulting in an effect of improving the appearance quality.

The rear surface of the knob ring back plate **124** provides an inner circular plate area **124j** in which the actuating member **170** is received and a donut-shaped outer circular plate area **124k** formed outside the inner circular plate area **124j**. A spacing plate **130** is received inside the outer circular plate area **124k**.

The side of the inner circular plate area **124j** surrounds and supports the outer circumferential surface of the actuating member **170** while the side of the outer circular plate area **124k** surrounds and supports the outer surface of the spacing plate **130**. Such a structure provides a structure that allows the knob ring **120** to stably rotate in both directions at the center position.

The spacing between the knob ring back plate **124** and the front panel **10** can be adjusted by adjusting the thickness of the spacing plate **130** and the recessed depth of the outer circular plate area.

For example, when the thickness of the spacing plate **130** is set to be 0.2 mm larger than the recessed depth of the outer circular plate area **124k**, the spacing between the knob ring back plate **124** and the case is set to 0.2 mm.

This serves to prevent a scratch from being generated on the surface of the front panel **10** by directly rubbing to the knob ring back plate **124** on the surface of the front panel **10**. Since the knob ring back plate **124** has a shape in which the upper portion arranged with the display device **125** is protruded, when the scratch is generated in this portion, even when the knob ring is in the origin position, the scratch portion can be exposed externally to left and right.

The display device **125** is fastened to the knob ring back plate **124**. The display device **125** is provided with a fastening hole **125d** and the knob ring back plate **124** is provided with a fastening hole **124e** at a position corresponding to the fastening hole **125d** of the display device **125**.

In addition, the display housing **126** coupled to the display device **125** has a fastening boss **126d** at a position aligned with the fastening holes **124e** and **125d**. A fastening bolt **S4** inserted in the knob ring back plate **124** sequentially passes through the fastening hole **124e** of the knob ring back plate **124** and the fastening hole **125d** of the display device **125**, and then, is fastened to the fastening boss **126d** of the display housing **126**. The knob ring back plate **124**, the display device **125**, and the display housing **126** are integrally fastened through the fastening bolt **S4**.

In other words, the fastening is made in a state that the display device **125** is fitted between the knob ring back plate **14** and the display housing **126**. As described above, the knob ring body **122** may be made of a metal material. In order to prevent the display device **125** included with an electronic circuit from being a short circuit with the knob ring body **122**, the display housing **126** may be made of an insulating material. Through this, stable operation performance of the display device **125** can be secured.

The display housing **126** may be formed as a frame form that surrounds the outer circumferential surface of the display device **125**.

In addition, the fastening boss **126d** of the display housing **126** forms the guide protrusion **126b** to the front side of the display housing **126**. The guide protrusion **126b** is inserted into the receiving groove **122b** provided on the rear surface of the protruding portion of the knob ring body **122** to provide a structure in which the display housing **126** can be coupled in a state aligned with the knob ring body **122**.

FIG. **19** is a perspective view showing a display device, and FIG. **20** is a perspective view showing a rear surface of a display device of a knob assembly according to the present disclosure.

As shown, the display device **125** of the knob assembly according to the present disclosure includes a display board **125b** and a display module **125a**. A connector **125c** is provided on the rear surface of the display board **125b**. In addition, the display board **125b** is formed larger than the display module **125a** to the both sides. The display board **125b** exposed to both sides of the display module **125a** is provided with a fastening hole **125d**.

The above described knob ring back plate **124**, the display device **125**, and the display housing **126** are fastened through the fastening hole **125d**. The display module **125a** may be configured to be of a type that the light is emitted.

FIG. **21** is a perspective view showing a display housing, and FIG. **22** is a perspective view showing a rear surface of a display housing.

The display housing **126** has a frame shape that surrounds the outer surface of the display device **125**. The display housing **126** is coupled in a form of fitting with the display device **125**, and the knob ring back plate **124** is fastened having the display device **125** therebetween by the fastening bolt **S4**.

The display housing **126** includes a frame portion **126f** surrounding the display module **125a** of the display device **125** and a wing portion **126w** surrounding the display board **125b**.

The display housing **126** may be manufactured by a method of injection molding with a material having an insulating material. Insulation performance of the display housing **126** may provide protection for the display device **125** that includes electronic components.

The display housing **126** fixes the display device **125** and is coupled to the knob ring body **122**.

The coupling of the display housing **126** and the knob ring body **122** is a structure for allowing the display housing **126** to be fixed in the center position with regard to the knob ring body **122** by a fitting coupling structure.

The display housing **126** is fastened to the knob ring back plate **124** by the fastening bolt **S4** having the display board **125b** of the display device **125** therebetween and is not substantially fastened to the knob ring body **122**. In addition, since the knob ring back plate **124** is fastened to the knob ring body **122**, the display housing **126** has the structure of fastened to the knob ring body **122** through the knob ring back plate **124**.

Since the display housing **126** is not directly fastened to the knob ring body **122**, a structure for a position alignment with regard to the knob ring body **122** of the display housing **126** is needed.

For this, the present disclosure includes a guide protrusion **126b** on the front surface of a wing portion **126w** of the display housing **126**, and provides a guide groove **126c** on a side.

In addition, a front support portion **126a** is provided on the forward side of the frame portion **126f**. The front support portion **126a** is protruded in a form of blocking the through hole exposed with the display device **125** and supports the front surface of the display module **125a**, thereby serving to prevent the front surface of the display module **125a** from being protruded at the display housing **126**.

Referring to the rear surface of the display housing **126**, the fastening boss **126d** is provided. The fastening bolt **S4** fastened through the knob ring back plate **124** is fastened to the fastening boss **126d**. The fastening boss **126d** is con-

nected to the guide protrusion **126b** on the front surface of the display housing **126** on a straight line. In other words, the fastening hole of the fastening boss **126d** is connected to the inside the guide protrusion **126b**.

In addition, a rear support portion **126e** is provided on the rear surface of the frame portion of the display housing **126**. The rear support portion **126e** is supported on the front surface of the knob ring back plate **124** contacting with the rear surface of the display housing **126**, thereby securing to prevent the knob ring back plate **124** from entering inside the display housing **126**.

FIG. **23** is a perspective view showing a rear surface of a knob ring, and FIGS. **24** and **25** are the views for explaining a coupling structure of the display device and the knob ring of the knob assembly according to the present disclosure.

As shown, the knob ring body **122** is provided with a pair of protruding portion **122a** at an upper portion. A display is coupled between the protrusion **122a**.

The display device **125** is constrained to the knob ring body **122** through the display housing **126** described above.

The receiving groove **122b** to which the guide protrusion **126b** of the display housing **126** is provided inside the protruding portion **122a** of the knob ring body **122** and the guide rail **122c** to which a guide groove **126c** of the display housing **126** is inserted is provided to the inner side of the protruding portion **122a**.

As shown, the display housing **126** has the structure which is fitting coupled between the protruding portion **122a** of the knob ring body **122** in a state of fitting the display device **125** to the display housing **126**.

When the guide protrusion **126b** of the display housing **126** is inserted into the receiving groove **122b** of the knob ring body **122**, it can prevent the up and down and left and right flow of the display housing **126**.

In addition, the guide rail **122c** of the knob ring body **122** is inserted into the guide groove **126c** of the display housing **126** to guide the coupling of the display housings **126** and prevent the up and down directions deviation of the display housing **126**.

In addition, a coupling hole **122h** for fastening with the knob ring back plate **124** is provided on the rear surface of the knob ring body **122**. In a state which the knob ring body **122** is directly fastened to the knob ring back plate **124** and the display device **125** is fastened to the knob ring back plate **124** together with the display housing **126**, the knob ring back plate **124** is fastened to the knob ring body **122** and inserted into between the protruding protrusion **122a** of the knob ring body **122** and fixed.

In some examples, the upper surface groove **122t** is provided on the upper surface of the protruding portion **122a** of the knob ring body **122**. The upper surface groove **122t** is a configuration for coupling with the display cover **127**.

FIG. **26** is a perspective view showing a knob ring back plate, FIG. **27** is a perspective view showing a rear surface of a knob ring back plate, and FIG. **28** is a longitudinal sectional view of the knob ring back plate of the knob assembly in accordance with an exemplary implementation of the present disclosure.

As shown, the knob ring back plate **124** can be largely divided into three portion, a circular plate portion **124-1**, an extended portion **124-2**, and supporting pipe portion **124c**, **124f**.

The circular plate portion **124-1** has a circular plate shaped outer shape, and the extended portion **124-2** has a shape protruded outward so as to shield the rear surface of the protrusion of the knob body.

The supporting pipe portion includes an outer supporting pipe **124c** protruded toward outside of the front panel and an inner supporting pipe **124f** protruding toward inside of the front panel. The outer supporting pipe **124c** and the inner support pipe **124f** are formed on the same axis, and a knob shaft insertion hole **124d** is formed therein.

The circular plate portion **124-1** includes an inner circular plate area **124j** having a size corresponding to the actuating member **170** again and an outer circular plate area **124k** having a size corresponding to the spacing plate **130**.

The supporting pipe portion **124c**, **124f** is formed in a form protruded from the center of the circular plate portion **124-1** to both sides. The supporting pipe portions **124c**, **124f** serve to support the knob shaft **116** inserted therein. The knob shaft **116** and the supporting pipe portion **124c**, **124f** serves to mutually support. When the knob is operated, it is supported by the supporting pipe portion **124c**, **124f** to which the knob shaft is fixed. When the knob ring is operated, the supporting pipe portions **124c**, **124f** is supported by the knob shaft inserted therein.

The outer circular plate area **124k** of the knob ring back plate **124** is provided with a fastening hole **124h** for fastening with the knob body **112** and the inner circular plate area **124j** is provided with the fastening hole **124i** for fastening with the actuating member. Through this, the knob body **112** and the actuating member **170** are fastened with the knob ring back plate **124** as the medium.

In addition, the outer circular plate area **124k** of the knob ring back plate **124** is provided with a bracket hole **124b** through which the locking bracket penetrates and is coupled to the front panel. The bracket hole **124b** is formed into an arc shape long hole by reflecting the rotation range of the knob ring.

In some examples, the inner supporting pipe **124f** is divided into cut section **124g** so as to have a flexibility. This is to allow the inner supporting pipe **124f** to be smoothly assembled with other component during the assembly process.

The inner supporting pipe **124f** is assembled in a form inserted inside the fixed frame **180** and the fixed pipe **190** are inserted inside, and at this time, when an outer diameter of the inner supporting pipe **124f** is contracted, the assembly convenience can be improved. Therefore, the inner supporting pipe **124f** is divided into the cut section **124g** so that the outer diameter of the inner supporting pipe **124f** can be contracted during the assembly process.

In some implementations, the cut section **124g** cuts the inner supporting pipe **124f** in the lateral direction. This results in an effect that the inner supporting pipe **124f** can reduce the up and down external diameter in the up and down direction due to the pressure in the up and down direction during the assembling process.

The extended portion **124-2** is provided with a fastening hole **124e** for fastening the display board **125b** and the display housing **126** together. The fastening bolt S4 entering from the rear surface of the knob ring back plate **124** is fastened to the fastening boss **126d** of the display housing **126** after passing through the fastening hole **125d** of the display board **125b**.

In addition, the extended portion **124-2** is provided with a wiring hole **124a** through which the wiring connected to the connector **125c** provided on the rear surface of the display board **125b** passes. The assembling of the wiring is made after the assembly of the knob ring **120**. After assembling the knob ring **120** to the front panel, the wiring is coupled to the connector **125c** exposed through the wiring hole **124a**.

The inner circular plate area **124j** of the circular plate portion **124-1** has a shape protruded forward compared with the outer circular plate area **124k**. This is such that the actuating member **170** is inserted into the inner circular plate area **124j** so that the side of the actuating member can be supported by the side of the inner circular plate area **124j**. A spacing plate **130** is received inside the outer circular plate area **124k** so that the outer surface of the spacing plate **130** is supported by the side of the outer circular plate area **124k**.

The knob ring back plate **124** has a complicated shape to be fastened to other configurations, and it is advantageous in manufacturing cost aspect to manufacture by injection molding.

FIG. **29** is a view for explaining the assembly of the display cover of the knob assembly in accordance with an exemplary implementation of the present disclosure, FIG. **30** is a perspective view showing the display cover of the knob assembly in accordance with an exemplary implementation of the present disclosure, FIG. **31** is a half cross sectional view showing the display cover of the knob assembly in accordance with an exemplary implementation of the present disclosure, FIG. **32** is a sectional view showing a state before the display cover of the knob assembly in accordance with an exemplary implementation of the present disclosure is coupled, and FIG. **33** is a sectional view showing a state which the display cover of the knob assembly in accordance with an exemplary implementation of the present disclosure is coupled.

As shown, the display cover **127** is configured to be coupled with the fitting coupling at the upper portion of the protrusion of the knob ring body **122** after the knob ring body **122**, the knob ring back plate **124**, the display device **125**, and the display housing **126** are assembled.

The display cover **127** together with the knob ring body **122** forms the appearance of the knob ring.

The knob ring body **122** has a slot groove **122d** into which the insertion protrusion **127a** formed at a lower end of the display cover **127** is fitted. The insertion protrusion **127a** is formed at the lower end of the front surface of the display cover **127** and is inserted into the slot groove **122d** of the knob ring body **122**. The insertion protrusion **127a** of the display cover **127** is fitted into the slot groove **122d** of the knob ring body **122** so that the surface of the display cover **127** aligns with the outer surface of the knob ring body **122** and is constrained. However, the insertion protrusion **127a** is not fixed to the slot groove **122d**, and thus, the fastening force is not generated due to the coupling of the insertion protrusion **127a** and the slot groove **122d**.

A pair of restraining protrusion **127b** is provided on the upper bottom surface of the display cover **127**. The restraining protrusion **127b** is resiliently deformed and inserted into the protruding portion **122a** of the knob ring body **122** and then restrained by the upper inner surface of the protruding portion **122a**. The coupling force of the display cover **127** is secured by the restraining protrusion **127b**.

In addition, a pair of side support protrusions **127t** are provided on both sides of the upper bottom surface of the display cover **127**. The side supporting protrusion **127t** is fitted into the upper surface groove **122t** provided on the upper surface of the knob ring body **122**. The pair of side supporting protrusion **127t** is constrained to the upper surface groove **122t** provided in the protruding portion **122a** in both sides, respectively and aligns the coupling of the knob ring body **122** with the display cover **127**.

In addition, a rear surface supporting protrusion **127c** is provided on the upper bottom surface of the display cover **127**. The rear surface supporting protrusion **127c** supports

the front surface of the knob ring back plate **124** to align the coupling of the knob ring back plate **124** and the display cover.

In addition, the display cover **127** has a thin walled portion **127f** having a thickness thinner than the other portion in a portion corresponding to the display portion area of the display module **125a**.

In some implementations, since the display cover **127** may define the appearance, the display cover **127** may be made of a translucent material so as not to expose an inside complicated shape to the outside. By the way, the transmittance of the translucent material can be controlled by the thickness. When the portion corresponding to the display portion area of the display module **125a** is made thinner than the other area, it is possible to reduce a change in brightness or color of light emitted from the display module **125a**.

Next, the structure of the joint will be described.

FIG. **34** is a cross section showing a state which the joint is separated from the knob assembly in accordance with an exemplary implementation of the present disclosure, FIG. **35** is a perspective view showing a joint of the knob assembly in accordance with an exemplary implementation of the present disclosure, and FIG. **36** is an exploded perspective view illustrating a joint of the knob assembly in accordance with an exemplary implementation of the present disclosure. FIG. **37** is a longitudinal cross section showing a joint of the knob assembly in accordance with an exemplary implementation of the present disclosure, FIG. **38** is a transverse sectional view showing the joint of the knob assembly in accordance with an exemplary implementation of the present disclosure, FIGS. **40** and **41** are the views for explaining a rotation operation of the joint of the knob assembly in accordance with an exemplary implementation of the present disclosure.

The joint **200** serves to connect the case assembly **100** and the valve assembly **300**.

The joint **200** is fitted to the knob shaft **116** provided in the knob and the valve shaft **330** provided in the valve assembly.

The joint **200** is installed between the valve shaft **330** and the knob shaft **116** and connects the valve shaft **330** and the knob shaft **116**, and it includes the joint housing **210** and the first shaft coupling portion **220**, the second shaft coupling portion **230**, a joint spring **260**, a reinforcement insert ring **240**, and a reinforcement cap **250**.

The joint housing **210** has a predetermined length and is formed into a cylindrical shape formed with a hollow. At one side of the longitudinal direction of the joint housing **210**, a hollow, that is, an insertion portion for opening the inner space of the joint housing **210** to the outside of the joint housing **210** is formed. In addition, a side plate portion **214** of blocking a longitudinal other side of the joint housing **210** is provided on the side facing with the insertion portion, that is, the longitudinal other side of the joint housing **210**. A through hole **214a** for opening the inner space of the joint housing **210** to the outside of the joint housing **210** is formed in the inner side of the side plate portion **214**.

Also, a plurality of slots **216**, **218** may be formed in the joint housing **210**. Each slot **216**, **218** is formed in a long hole shape extending along the longitudinal direction of the joint housing **210** and may be formed as the long hole shape having a predetermined width extending along the circumferential direction of the joint housing **210** and the predetermined length along the longitudinal direction of the joint housing **210**.

According to the present implementation, the joint housing **210** is formed with a pair of first slot **216** and a pair of second slot **218**.

25

The pair of first slot **216** is formed to be penetrated to the side of the joint housing **210**, respectively, and viewed from longitudinal one side or other side of the joint housing **210**, it is arranged to face each other.

In addition, the pair of second slot **218** is formed to be penetrated to the side of the housing forming a curved surface, respectively, and viewed from longitudinal one side or other side of the joint housing **210**, it is arranged to face each other at a position different from the first slot **216**.

That is, viewed from longitudinal one side or other side of the joint housing **210**, the pair of first slot **216** and second slot **218** are arranged to form a cross shape.

The pair of first slot **216** arranged to face each other is inserted with the first coupling shaft **225** arranged to in a row to the first shaft coupling portion **220** such that the straight line direction movement and the rotation to the longitudinal direction of each joint housing **210** are possible. Further, the pair of second slot **218** arranged to face each other is inserted with the pair of the second coupling shaft **235** arranged in a row to the second shaft coupling portion **230** such that the straight line direction movement and the rotation to the longitudinal direction of the joint housing **210** are possible, respectively.

By the fitting coupling made between the pair of the first slot **216** and the first coupling shaft **225**, the straight line direction movement and the rotation of the first shaft coupling portion **220** are possible to the joint housing **210**. In addition, by the fitting coupling between the pair of the second slot **218** and the second coupling shaft **235**, the straight line movement and the rotation of the second shaft coupling portion **230** can be coupled to the joint housing **210**.

The first shaft coupling portion **220** is inserted to the inner space of the joint housing **210** through the insertion portion. Such first shaft coupling portion **220** is connected to any one of the valve shaft **330** and the knob shaft **116**, and it includes the first coupling shaft **225** and the first shaft coupling pipe **227**. In the present implementation, the first shaft coupling portion **220** is exemplified as being connected with the valve shaft **330**.

The first shaft coupling portion **220** is inserted into the inner space of the joint housing **210** and coupled to the joint housing **210** by the pair of first coupling shaft **225** arranged in a row, and thus, it can be moved and rotated integrally with the first coupling shaft **225**.

The first shaft coupling pipe **227** is formed to be extended to the longitudinal direction of the joint housing **210** and protruded outside the joint housing **210**, and can be moved and rotated integrally with the first shaft coupling portion **220**. The first shaft coupling pipe **227** is the part provided for connecting between the first shaft coupling portion **220** and the valve shaft **330**, and the knob shaft **116** is coupled to the first shaft coupling pipe **227**, and thus, the connection between the first shaft coupling pipe **220** and the valve shaft **330** is made.

The first shaft coupling pipe **227** is protruded to the outside the joint housing **210** via the longitudinal other side of the joint housing **210** and coupled with the valve shaft **330** from the outside the joint housing **210** and can be protruded to the outside the joint housing **210** by passing through the side plate portion **214** via the secured passage by the through hole **214a** formed to be penetrated inside the side plate portion **214**.

According to the present implementation, the rotation of the first shaft coupling portion **220** is made about the first coupling shaft **225** by the rotation of the first coupling shaft **225**, a direction to which the end of the first shaft coupling

26

pipe **227** faces can be changed as an angle by which the first shaft coupling portion **220** is rotated. Hereinafter, the direction to which the end of the first shaft coupling pipe **227** faces will be expressed as a position of the first shaft coupling portion **220** is changed.

The second shaft coupling portion **230** is inserted into the inner space of the joint housing **210** through the insertion portion and arranged between the insertion portion and the first shaft coupling portion **220**. The second shaft coupling portion **230** is connected to other one of the valve shaft **330** and the knob shaft **116** and may include a second coupling shaft **235** and a second shaft coupling pipe **237**. In the present implementation, the second shaft coupling portion **230** is illustrated as being connected to the knob shaft **116**.

The second shaft coupling portion **230** is inserted into the inner space of the joint housing **210** and is coupled to the joint housing **210** by a pair of second coupling shafts **235** arranged in a row, and can be moved and rotated integrally with the second coupling shaft **235**.

The second shaft coupling pipe **237** is formed to extend in the longitudinal direction of the joint housing **210** and is protruded to the outside the joint housing **210**, and can be moved and rotated integrally with the second shaft coupling portion **230**. The second shaft coupling pipe **237** is the portion provided for the connection between the second shaft coupling portion **230** and the knob shaft **116**. The knob shaft **116** is coupled to the second shaft coupling pipe **237**, and thus, the connection between second shaft coupling portion **230** and the knob shaft **116** can be made.

The second shaft coupling pipe **237** protrudes to the outside of the joint housing **210** through longitudinal one side of the joint housing **210** and is coupled to the knob shaft **116** from the outside the joint housing **210**, and may be protruded to the outside the joint housing **210** through the secured passage by the insertion portion.

According to the present implementation, when the rotation of the second shaft coupling portion **230** is made about the second coupling shaft **235** by the rotation of the second coupling shaft **235**, the direction to which the end of the second shaft coupling pipe **237** faces may be changed by the angle at which the second shaft coupling portion **230** is rotated. Hereinafter, the direction to which the end of the second shaft coupling pipe **237** changes will be expressed as a change in the posture of the second shaft coupling portion **230**.

The joint spring **260** is inserted into the inner space of the joint housing **210** through the insertion portion and arranged between the first shaft coupling portion **220** and the second shaft coupling portion **230**. The joint spring **260** provides elastic force for recovering the positions of the first shaft coupling portion **220** and the second coupling portion **230** changed by the straight line direction movement of the shaft coupling portion **220**, **230**, and a posture of the first shaft coupling portion **220** and the second shaft coupling portion **230** changed by the rotation of the shaft coupling pipe **227**, **237**.

In the present implementation, the joint spring **260** is illustrated as including a coil spring formed to have a length extended along the longitudinal direction of the joint housing **210**. Longitudinal one side of the joint spring **260** is coupled to the first shaft coupling portion **220** and the longitudinal other side of the joint spring **260** is coupled to the second shaft coupling portion **230**. The joint spring **260** is provided such that an elastic stretch to the longitudinal direction and the elastic bending deformation to the rotational direction of the first shaft coupling portion **220** or the second shaft coupling portion **230**.

The inner surfaces of the first shaft coupling portion **220** and the second shaft coupling portion **230** facing each other, for example, the outer surface of the support boss **224**, **234** is formed with a fitting groove **222**, **232** fitting coupled on the longitudinal both sides of the joint spring **260**.

Both ends of the joint spring **260** becomes a state received in the fitting groove **222** provided in the first shaft coupling portion **220** and the fitting groove **232** provided in the second shaft coupling portion **230**. In addition, since the supporting boss **224** of the first shaft coupling portion **220** and the support boss **234** of the second shaft coupling portion **230** become an inserted state inside the joint spring **260**, the elastic force is provided to the direction which the spacing between the first shaft coupling portion **220** and the second shaft coupling portion **230** is spaced apart in a state to which the joint spring **260** is stably fixed.

In the joint **200**, the first shaft coupling portion **220** is rotatably coupled to the joint housing **210** in any one of the up and down direction and the left and right direction, and the second shaft coupling portion **230** is rotatably coupled to the joint housing **210** in the other one direction of the up and down direction and the left and right direction.

That is, the joint **200** of the present implementation can transmit the rotational motion of the knob shaft **116** to the valve shaft **330** while connecting the valve shaft **330** and the knob shaft **116** with one flexible shaft in a form which the first shaft coupling portion **220** is connected to the valve shaft **330** and the second shaft coupling portion **230** is connected to the knob shaft **116**.

When the direction to which the valve shaft **330** extends does not coincide or align with the direction to which the knob shaft **116** extends due to the tolerance of the valve shaft **330** generated in the valve assembly **300**, with regard to the joint **200**, as a posture of at least any one of the first shaft coupling portion **220** and the second shaft coupling portion **230** changes, the connecting angle between the first shaft coupling portion **220** and the second shaft coupling portion **230** is changed, thereby absorbing the tolerance of the valve shaft **330** generated in the valve assembly **300**.

At this time, in the process of connecting the joint **200** to the valve shaft **330** and the knob shaft **116**, the operator does not have to adjust the connection angle between the first shaft coupling portion **220** and the second shaft coupling portion **230**. When the valve shaft **330** and the knob shaft **116** are connected to both ends of the joint **200** so that the postures of the first shaft coupling portion **220** and the second shaft coupling portion **230** are changed to a state for suitable to connect the valve shaft **330** and the knob shaft **116**.

In some examples, since the postures of the first shaft coupling portion **220** and the second shaft coupling portion **230** can be maintained or changed according to the situation by the elastic force provided by the joint spring **260**, separate work for fixing these postures may not be required.

In some example, the joint **200** according to the implementation of the present disclosure also serves to transmit a longitudinal motion of the shaft.

As shown in FIG. **39**, in a state which the joint **200** is assembled to the knob assembly, it has the state which the joint spring **260** is compressed. At this time, the support boss **224** of the first shaft coupling portion **220** and the support boss **234** of the second shaft coupling portion **230** are spaced apart from by a predetermined spacing. However, when the stroke in which the knob is pushed is greater than the spacing between the supporting boss **224**, **234**, the axial motion of the first shaft coupling portion **220** is transmitted

to the motion of the second shaft coupling portion **230**, and thus, the valve shaft **330** can be pushed.

The structure may result in an effect that the longitudinal error of the shaft can be absorbed at a spacing between the supporting boss **224**, **234** even when the longitudinal error or the tolerance of the shaft is generated in a manufacturing process of the knob shaft **116** or the valve shaft **330**.

The reinforcement cap **250** is coupled to the outside the shaft coupling pipe **227**, **237** and a reinforcement insert ring **240** is coupled inside the shaft coupling pipes **227**, **237**. The reinforcement cap **250** and the reinforcement insert ring **240** can be coupled in a fixing method.

The knob shaft **116** and the valve shaft **330** inserted into the shaft coupling pipe **227**, **237** have a D-shaped cross section. The shaft coupling pipe **227**, **237** is continuously subjected to a torsion torque in a state which the knob shaft **116** and the valve shaft **330** are coupled. The first shaft coupling portion **220** and the second shaft coupling portion **230** may be manufactured by an injection molding method using a synthetic resin material. In this case, the shaft coupling pipe **227**, **237** is a synthetic resin material. In some examples, it is general that the knob shaft **116** and the valve shaft **330** are the metal material.

When the torsion torque is continuously subjected in a state which the knob shaft **116** having a D-shaped cross section and the valve shaft **330** are coupled inside the shaft coupling pipe **227**, **237** which is the synthetic resin material, the shaft coupling pipe **227**, **237** can be damaged.

In order to secure the durability of the shaft coupling pipe **227**, **237**, it has the structure that the reinforcement cap **250** of metal material surrounds the outer circumferential surface of the shaft coupling pipe **227**, **237**, and the reinforcement insert ring **240** surrounds the inner circumferential surface of the shaft coupling pipe **227**, **237**.

Such structure reinforces the strength of the shaft coupling pipe **227**, **237**, thereby improving the durability of the joint **200**.

In some examples, the reinforcement insert ring **240** is provided with a slit **242**. The slit **242** serves to secure the flexibility such that it can be restored to the original shape after the cross section of the reinforcement insert ring **240** is changed by corresponding to the rotating valve shaft **330** or the knob shaft **116**, even when the valve shaft **330** or the knob shaft **116** having the D-shaped cross section is rotated inside the reinforcement insert ring **240** having the D-shaped cross section.

In addition, inside the shaft coupling pipe **227**, **237** is provided with a blocking protrusion **221**, **231** for limiting the coupling depth of the knob shaft **116** or the valve shaft **330**. The knob shaft **116** and the valve shaft **330** contact with the blocking protrusions **221**, **231** so that it cannot be inserted beyond the above, thereby adjusting the coupling depth between the knob shaft **116** and the valve shaft **330**. The blocking protrusion **221**, **231** serves to transmit the axial motion of the knob shaft **116** to the first shaft coupling portion **220** and transmit the axial motion of the second shaft coupling portion **230** to the valve shaft **330**.

The joint **200** having the above-described configuration can be assembled in the following manner.

Firstly, the first shaft coupling portion **220** is tilted and inserted inside the joint housing **210** through the insertion hole and then the first coupling shaft **225** is fitted into the first slot **216** to make the assembly of the joint housing **210** and the first shaft coupling portion **220**. At this time, when the rotation direction of the first shaft coupling portion **220** is left and right direction, the direction of tilting the first

shaft coupling portion 220 in order to insert the first shaft coupling portion 220 inside the joint housing 210 is up and down direction.

Then, after inserting the joint spring 260 inside the joint housing 210 through the insertion portion, the second shaft coupling portion 230 is inserted by tilting, and then the second coupling shaft 235 is fitted into the second slot 218, so as to form an assembly between the joint housing 210 and the second shaft coupling portion 230. At this time, when the rotation direction of the second shaft coupling portion 230 is the up and down directions, in order to insert the second shaft coupling portion 230 inside the joint housing 210, the direction of tilting the second shaft coupling portion 230 is the left and right directions.

In this process, the joint springs 260 can be stably coupled to the first shaft coupling portion 220 and the second shaft coupling portion 230 in a state that the longitudinal both sides thereof are fitted into the fitting groove 222 and the longitudinal both sides of the movement are constrained.

As described above, the assembly of the joint 200 according to the present implementation is made by fitting the first shaft coupling portion 220 to the joint housing 210 and assembling it, and inserting the joint spring 260 to the joint housing 210, and subsequently, fitting the second shaft coupling portion 230 to the housing and assembling it.

For example, the assembly of the joint 200 can be easily and quickly made only by a sequential fitting operation without using separate fastening structure or an adhesive. In this example, since the joint 200 includes only four parts, the manufacturing and the management of the part is easy and the assembly of the joint 200 can be made more easily and quickly.

In some implementations, when the assembly of the joint 200 is completed, the fitting coupling state of the first shaft coupling portion 220 and the second shaft coupling portion 230 is stably maintained by the elastic force provided by the joint spring 260, and thus, the assembly of the joint 200 is not optionally released during use of the joint 200.

The joint 200 serves to absorb the position error of the valve shaft 330 between the knob shaft 116 and the valve shaft 330 and provides the structure that the rotation of the first shaft coupling portion 220 and the second shaft coupling portion 230 is possible in order to absorb the position error of the valve shaft 330. However, it needs a structure for limiting the rotation range of the first shaft coupling portion 220 and the second shaft coupling portion 230, that is, the posture change range of the first shaft coupling portion 220 and the second shaft coupling portion 230 within the necessary range, according to the property of the product which the joint 200 is installed.

The posture change range of the first shaft coupling portion 220 is determined by the size of the through hole 214a. For example, the first shaft coupling portion 220 can be rotated only within a range in which interference between the inner circumferential surface of the first shaft coupling pipe 227 and the side plate portion 214 is not generated, and the further rotation of the first shaft coupling portion 220 is limited from the point in which the interference between the inner circumferential surface of the first shaft coupling pipe 227 and the side plate portion 214 is generated. Therefore, the posture change range of the first shaft coupling portion 220 is determined by the size of the through hole 214a whose the first shaft coupling portion 22y determines the size of the passage for passing through the side plate portion 214.

In other words, the rotation of the first shaft coupling portion 220, that is, the posture change of the first shaft

coupling portion 220 is limited to the range between the point which the interference between the inner circumferential surface of the side plate portion 214 and the first shaft coupling pipe 227 at the time of one direction rotation of the first shaft coupling portion 220 and the point which the interference between the inner circumferential surface of the side plate portion 214 and the first shaft coupling pipe 227 is made at the time of the other side rotation of the first shaft coupling portion 220.

According to the present implementation, the size of the through hole 214a is determined such that the inner diameter of the side plate portion 214 formed with the through hole 214a is larger than the outer diameter of the first shaft coupling pipe 227 and is smaller than the inner diameter of the joint housing 210. At this time, the size of the through hole 214a can be suitably adjusted depending on the posture change range of the first shaft coupling portion 220 to be established. That is, by increasing the size of the through hole 214a close to the inner diameter of the joint housing 210, the posture change range of the first shaft coupling portion 220 can be enlarged, and by reducing the size of the through hole 214a close to the outer diameter of the first shaft coupling pipe 227, the posture change range of the first shaft coupling portion 220 can be reduced.

The second coupling shaft 235 provided in the second shaft coupling portion 230 may include a stopper 235a.

The stopper 235a is formed so as to be protruded outside the second coupling shaft 235 and the position inside the second slot 218 in accordance with the rotation of the second coupling shaft 235 is changed. The stopper 235a is arranged inside the second slot 218 such that the interference with the inner wall of the joint housing 210 formed by the second slot 218 at a set position is made.

According to the present implementation, the second slot 218 is formed with a width corresponding to the outer diameter of the second coupling shaft 235 (the outer diameter except the stopper). That is, the second slot 218 is formed so that the width of the second slot 218 and the outer diameter of the second coupling shaft 235 are identical, the coupling between the second shaft coupling portion 230 and the joint housing 210 can be made without generating a rattling when the second shaft coupling portion 230 moves and rotates on the joint housing 210 and it can be applied to even the coupling between the first shaft coupling portion 220 and the joint housing 210.

In addition, the stopper 235a is formed so as to be protruded toward the inside of the second slot 218 and is formed to be protruded with narrower width than the width of the second slot 218. Thus formed stopper 235a is rotated together with the second coupling shaft 235 when the rotation of the second coupling shaft 235 is made, and when the rotation of the second coupling shaft 235 is made by the predetermined angle or more, it is interfered with the inner wall of the joint housing 210 formed by the second slot 218, thereby limiting further rotation of the second coupling shaft 235.

In other words, the rotation of the second shaft coupling portion 230, that is, the posture change of the second shaft coupling portion 230 is limited to the range between the point which the interference between the inner wall of the joint housing 210 and the stopper 235a at the time of one direction rotation of the second shaft coupling portion 230 is made and the point which the interference between the inner wall of the joint housing 210 and the stopper 235a is made at the time of the other direction rotation of the second shaft coupling portion 230.

As another example, instead of providing the stopper **235a** on the second coupling shaft **235**, the structure for the posture change range limitation of the second shaft coupling portion **230** may be formed in a form identical to the structure for limiting the posture change range of the first shaft coupling portion **220**.

That is, a structure for limiting the posture change range of the second shaft coupling portion **230** may be formed in a form of adjusting the posture change range of the second shaft coupling portion **230** by covering the side plate portion **214** on longitudinal one side portion of the joint housing **210** and adjusting the size of the through hole **214a** formed in the inner side of the side plate portion **214**.

However, when the structure for limiting the posture change range of the second shaft coupling portion **230** is formed as such form, unlike the side plate portion **214** integrally formed with the joint housing **210** at the longitudinal other portion of the joint housing **210**, the side plate portion at longitudinal one side portion of the joint housing **210** has to be provided in the form of separate cap shaped part form separable from the joint housing **210**.

When even the side plate portion of longitudinal one side portion of the joint housing **210** is integrally formed with the joint housing **210**, the passage to be inserted inside the joint housing **210** in order to assembly the parts such as the first shaft coupling portion **220**, the second shaft coupling portion **230**, and the joint spring **260** are blocked.

However, as such, when the side plate portion of one side portion in the longitudinal direction of the joint housing **210** is provided in the form of separate cap-shaped part, the number of parts for manufacturing the joint **200** is added to that extent, and as the number of parts is added, the process for manufacturing it is added. Therefore, the part management is much more difficult and the cost and time required for the manufacturing of the joint **200** is increased to that extent.

In consideration of this point, instead of adding the part in separate cap shape, by taking the structure of adding the stopper **235a** for limiting the rotation of the second coupling portion **230** as the protrusion form integrally formed with the second coupling shaft **235**, the joint **200** of the present implementation forms the structure of adjusting the posture change range of the second shaft coupling portion without adding separate part.

In some implementations, the joint **200** of the present implementation may be a structure that can be assembled with four parts including the fewer number of parts, for example, the joint housing **210**, the first shaft coupling portion **220**, the second shaft coupling portion **230**, and the joint spring **260**. In this case, the part management and the assembly work may be facilitated, and cost and time required for the manufacturing of the joint **200** may be reduced.

FIG. **42** is a perspective view showing a valve assembly of the knob assembly in accordance with an exemplary implementation of the present disclosure, and FIG. **43** is a perspective view showing a state in which the valve assembly of the knob assembly in accordance with an exemplary implementation of the present disclosure is separated.

As shown, the valve assembly **300** includes a valve **310** coupled to the gas pipe frame **35** and the gas pipe **30**, an ignition switch **360** fitted to the valve shaft **330** of the valve **310**, and the knob sensor **400**.

The knob sensor **400** includes a knob sensor plate **410** fastened to the valve **310**, a knob sensor housing **430** movably coupled to the knob sensor plate **410** in an axial direction, a sensor spring **420** providing the elastic force

between the knob sensor housing **430** and the knob sensor plate **410**, a knob sensor board **440** having the Hall sensor **444** and fastened to the knob sensor housing **430**, and a rotating plate **450** coupled with a knob sensor magnet **460** which is coupled to the valve shaft, rotates integrally with the valve shaft, and sensed by the Hall sensor **444**.

The ignition switch **360** has a valve shaft coupling hole **362** having a D-shaped cross section, and is coupled to the valve shaft. Therefore, the ignition switch **360** receives the rotational force of the valve shaft, so that the on/off state of the valve shaft can be switched by the rotational angle. When the valve shaft is rotated by a predetermined angle, the ignition switch **360** becomes on state, it servers to making a spark be generated in the burner.

FIG. **44** is a perspective view of showing a valve, FIG. **45** is an exploded perspective view of a valve, FIG. **46** is a longitudinal sectional view of a valve of a knob assembly according to the present disclosure, and FIG. **47** is a transverse cross-sectional view of a valve.

As shown, the valve **310** includes a valve body **312**, a valve cap **314**, a main adjustment piece **320**, a valve shaft **330**, a valve spring **340**, and an auxiliary adjustment piece **350**.

The main adjustment piece **320** and the auxiliary adjustment piece **350** are arranged inside the valve body **312**.

The valve body **312** includes an inflow pipe **312a** connected to the gas pipe, and a first gas supply pipe connecting portion **312b** connected to the burner, and a second supply pipe connecting portion **312c**.

In addition, inside the valve body **312**, the first flow path **312d** connecting the outer circumferential surface space of the main adjustment piece **320** and the auxiliary adjustment piece **350**, and the second flow path **312e** connecting the auxiliary adjustment piece **350** and the second supply pipe connecting portion **312c**.

The main adjustment piece **320** and the auxiliary adjustment piece **350** have the rotation center parallel to the longitudinal direction of the valve shaft and arranged inside the valve body **312**.

The main adjustment piece **320** includes a connection hole **325** formed from the rear surface to the front surface, an opening and closing hole **324** penetrating through the inner and outer circumferential surface of the connection hole **325**, and a groove **326** formed along the outer circumferential surface in one side of the opening and closing hole **324**.

The auxiliary adjustment piece **350** may include a T-shaped adjustment hole **354** capable of adjusting the amount which gas supplied through the first flow path **312d** to the second flow path **312e**.

The main adjustment piece **320** has a structure for adjusting the gas supply flow rate according to the degree of which the opening and closing hole **324** and the inflow pipe **312a** are overlapped. Gas introduced through the opening and closing hole **324** is supplied to the first gas supply pipe connection portion **312b** through the connection hole **325**.

At this time, gas supplied through the groove **326** formed on the outer circumferential surface of the main adjustment piece **320** is also supplied through the first flow path **312d**. In gas supplied through the first flow path **312d**, the flow rate supplied to the second supply pipe connecting portion **312c** is adjusted according to the overlapped degree of an adjustment hole **354** of the auxiliary adjustment piece **350** and the first flow path **312d**.

The main adjustment piece **320** is adjusted by the valve shaft **330** and the auxiliary adjustment piece **350** is adjusted by separate tool such as a driver.

The auxiliary adjustment piece **350** is for fine adjustment of the amount of gas to be supplied, and may not be adjusted after one adjustment according to the installation environment, and may be adjusted by a service engineers rather than being adjusted by the user.

If an access to the auxiliary adjustment piece **350** is not easy, an excessive disassembly operation of the cooking appliance may be needed for the repair engineers to adjust the auxiliary adjustment piece **350**.

In the present disclosure, the auxiliary adjustment piece **350** is arranged adjacent to one side of the main adjustment piece **320**, and after separating the knob, the service hole **129** in FIG. **57** may provide an access to the auxiliary adjustment piece **350**.

The main adjustment piece **320** has a key groove **322** into which a key **332** provided on the valve shaft **330** is inserted and a valve spring **340** is arranged between the main adjustment piece **320** and the valve shaft **330**. The valve spring **340** provides the elastic force to a direction which the valve shaft **330** is spaced apart from the main adjustment piece **320**, and provides a structure that the rotation of the valve shaft **330** is transmitted to the main adjustment piece **320** by pressing the valve shaft **330** in a axial direction and inserting the key **332** of the valve shaft **330** to a key groove **322** of the main adjustment piece **320**.

The assembly process of the valve **310** is made method by coupling the main adjustment piece **320** and the auxiliary adjustment piece **350** to the valve body **312**, and fastening the valve cap **314** in the valve body **312** in a state that the valve spring **340** and the valve shaft **330** are fitted into the main adjustment piece **320**. The fastening of the valve cap **314** and the valve body **312** may be made by the method of penetrating the fastening hole **314f** formed in the valve cap **314** and fastening to the fastening hole **314f** formed in the valve body **312** by using the fastening volt **S6**.

The valve cap **314** according to the present disclosure includes a sensor fixed portion **314d** for fixing the knob sensor **400** described below, and a service hole **314b** of providing a path in which the tool is accessible with the auxiliary adjustment piece **350**. The service hole **314b** is provided with the knob assembly provided in the front of the valve **310** and the front panel is provided with the service hole aligned with the service hole **314b**. The sensor fixed portion **314d** is fastened with the knob sensor plate **410** of the knob sensor **400**.

FIG. **48** is an exploded perspective view showing a knob sensor of the knob assembly in accordance with an exemplary implementation of the present disclosure, FIG. **49** is a perspective view showing a state which the knob sensor board of the knob assembly in accordance with an exemplary implementation of the present disclosure is assembled to the knob sensor housing, and FIGS. **50** and **51** are the cross sectional views for explaining the operation of the valve assembly of the knob assembly of the present disclosure.

As shown, the knob sensor **400** includes a sensor plate **410**, a sensor spring **420**, a knob sensor housing **430**, a knob sensor board **440**, and a rotating plate **450**.

The sensor plate **410** provides a fastening hole **432** to be fastened to the valve cap **314** described above. The sensor plate **410** is fixed to the valve cap **314** and serves to fix the position of the sensor housing **430** and to support the sensor spring **420** that provides the elastic force to the sensor housing **430**.

The fastening hole **432** of the sensor plate **410** is fastened to the fastening hole **314d** of the valve cap (**314** in FIG. **44**) using a fastening bolt **S7**.

The sensor plate **410** provides a valve shaft hole **412** at a central portion. Since the sensor plate **410** should not be affected by the pressing or rotation of the valve shaft **330**, the valve shaft through hole **412** has an inner diameter larger than the outer diameter of the valve shaft **330**.

A spring fixed portion **415** in which the sensor spring **420** is seated to the outside of the valve shaft through hole **412** is provided. The rear end side of the sensor spring **420** is inserted into the spring fixed portion **415** and the portion is fixed. The sensor spring **420** provides an elastic force in a direction in which the knob sensor housing **430** positioned in front of the sensor plate **410** is spaced apart from the sensor plate **410**. It is such that the knob sensor board **440** mounted on the knob sensor housing **430** and the rotating plate **450** arranged in front of the knob sensor board **440** to maintain the predetermined spacing.

Since the sensor plate **410** has a structure in which the elastic force of the sensor spring **420** is repeatedly applied, three or more points are fastened to the valve cap **314** for stable fastening, for instance. In some examples, the sensor plate **410** may maintain a fixed state correctly in a predetermined posture.

In some implementations, the sensor plate **410** provides a plurality of guide protrusions **411** protruded forward. The guide protrusion **411** is inserted into a guide portion **431** provided in the knob sensor housing **430** so that the knob sensor housing **430** can maintain a predetermined posture.

In some examples, three or more guide protrusions **411** are arranged at the circumference of the valve shaft through hole **412**. The knob sensor housing **430** can move forward and rearward to the longitudinal direction of the valve shaft **330** while maintaining the state parallel to the sensor plate **410** by the guide protrusion **411**.

The knob sensor housing **430** serves to fix the knob sensor board **440** and to maintain the rotating plate **450** and the knob sensor board **440** at a predetermined spacing.

The knob sensor **400** is operated in a principle of sensing the rotational angle of the valve shaft **330** by sensing the position of the knob sensor magnet **460** provided in the rotating plate **450** via the plurality of Hall sensors **444** arranged radially to the knob sensor board **440**.

Referring to FIG. **49**, seven Hall sensors **444** are arranged on the knob sensor board **440** so as to have a radially equal spacing. The rightmost Hall sensor below the rightmost is referred to as the first, and others are referred to as the second to the seventh Hall sensor.

The knob sensor **400** constitutes an absolute coordinate in such a manner that a signal of a different kind is generated for each Hall sensor **444** and the position of the knob sensor magnet **460** is sensed by using the absolute coordinate configured as such.

For example, regardless of the position immediately before the knob sensor magnet **460**, if a finally received signal is a signal generated by the n^{th} Hall sensor, the position of the knob sensor magnet **460** is sensed as a position corresponding to the n^{th} Hall sensor area.

Therefore, even when the operation of the knob is rapidly made, finally, the final position of the knob sensor magnet **460** can be precisely sensed in a state when the rotation of the knob handle is completed, thereby accurately grasping the fire power thus set.

When the knob sensor **400** has a method of using a relative coordinate which is a method that senses a position change from a position immediately before the knob sensor magnet **460**, when the knob is rotated at a very high speed, a problem may be generated that the position sensing of the knob sensor magnet **460** may not be made properly.

For example, in order for the position of the knob sensor magnet **460** moved from the position corresponding to the first Hall sensor area to the position corresponding to the seventh Hall sensor area to be accurately recognized, on state change in the second to the seventh Hall sensors has to be made sequentially. When the movement of the knob sensor magnet **460** is made at a rapid speed, on status change in some Hall sensor cannot be made, and in this case, the error can be generated in the positioning of the knob sensor magnet **460**. In this case, the error of recognizing the position of the knob sensor magnet **460** as the position corresponding to the area between the second Hall sensor and the sixth Hall sensor, or recognizing that the rotation of the knob is not made.

In some examples, the rotating plate **450** may be fixed to rotate together with the valve shaft **330**. In other examples, the knob sensor board **440** may maintain a predetermined posture regardless of the rotation of the valve shaft **330**.

In some examples, the valve shaft **330** not only rotates but also moves forward and backward even in the axial direction. The rotating plate **450** fixed to the valve shaft **330** moves along with the movement of the valve shaft **330**. Hereinafter, the direction in which the valve shaft **330** is moved to the inner side of the cooking appliance by pushing the knob is referred to as backward, and the opposite direction is referred to as forward.

When the rotating plate **450** is moved backward, the knob sensor housing **430** positioned at the rear of the rotating plate **450** is pushed by the rotating plate **450** and moved to the inside of the cooking appliance.

When the valve shaft **330** moves forward due to the restoring force of the valve spring, the rotating plate **450** also moves forward. At this time, since the knob sensor housing **430** is not affected by the movement of the valve shaft **330**, it moves forward with the rotating plate **450** by the restoring force of the sensor spring **420** provided between the knob sensor housing **430** and the knob sensor plate **410**.

Therefore, the knob sensor housing **430** is also moved forward and backward in response to the forward and backward movement of the rotating plate **450**, so that the spacing between the rotating plate **450** and the knob sensor housing **430** is maintained constant. As a result, the spacing between the knob sensor magnet **460** provided on the rotating plate **450** and the Hall sensor **444** provided on the knob sensor board **440** fastened to the knob sensor housing **430** can be maintained constant.

In some examples, the spacing between the knob sensor board **440** and the rotating plate **450** may be set by a plurality of support protrusion **435** provided on the knob sensor housing **430**. In some examples, three support protrusions **435** may be arranged with a spacing of 120°. Since three points can define a plane, when forming three support protrusions, the support protrusion **435** may contact the rotating plate **450** to maintain a constant spacing between the rotating plate **450** and the knob sensor housing **430**.

The center of the knob sensor board **440** is provided with a valve shaft through hole **442** through which the valve shaft **330** is penetrated, and the periphery thereof is provided with the support protrusion through hole **445** through which the support protrusion **435** provided on the knob sensor housing **430** is penetrated.

The knob sensor board **440** may be coupled to the knob sensor housing **430** through a fastening bolt **S8** and a fastening protrusion **434**. In the case of the illustrated implementation, the knob sensor board **440** is provided with four fastening holes **443** and the knob sensor housing **430** is provided with two fastening holes **433** and two fastening

protrusions **434**, and it is the structure which two points are fastened to the fastening bolt **S8** and other two points are fixed to the fastening protrusion **434**, but the number of the fastening of the fastening bolt **S8** can be increased and decreased.

Referring to FIGS. **50** and **51**, when the knob is pushed, the joint **200** is moved to the right in the figure, the sensor spring **420** and the valve spring **340** are compressed by the movement of the joint **200**, and the valve shaft **330** and the knob sensor housing **430** in which the rotating plate **50** and the knob sensor board **440** are fastened together, and are moved together to the right.

When the pushing force is removed, by the restoring force of the valve spring **340** and the sensor spring **420**, the valve shaft **330**, the knob sensor housing **430** to which the knob sensor board **440** is fastened, and the rotating plate **450** are restored to the original position.

The knob sensor plate **410** is fastened to the valve cap **314** and the sensor spring **420** provides elastic force in a direction to closely attach the knob sensor housing **430** to the rotating plate **450**. Therefore, the rotating plate **450** contacts with the first shaft coupling pipe **227** of the joint **200**, and in the knob sensor housing **430**, the support protrusion **435** contacts with the rotating plate **450**.

A state which the supporting protrusion **435** of the knob sensor housing **430** contacts with the rotating plate **450** is always maintained in a state before the knob is pushed such as FIG. **50**, or in a state when the knob is pushed as show in FIG. **51**.

Therefore, in spite of the axial movement of the valve shaft, the knob sensor plate **410** and the rotating plate **450** of the knob sensor can always maintain the predetermined spacing, and thus, the spacing between the knob sensor magnet **460** arranged to the rotating plate **450** and the Hall sensor **444** arranged at the knob sensor plate **410** can be maintained constantly. Such structure improves the operation reliability of the knob sensor **400**.

FIG. **52** is a longitudinal sectional view for explaining the operation and supporting structure of the knob of the knob assembly in accordance with an exemplary implementation of the present disclosure.

First, the support structure of the knob **110** will be reviewed. The knob **110** has the structure which penetrates through the inner support pipe **124f** and the outer supporting pipe **124c** of the knob ring **120**, and penetrates through the fixed pipe **190**, and fitting coupled to the first shaft coupling portion of the joint **200**.

The knob shaft **116** is supported at the first support point **P1** on the inner surface of the inner supporting pipe and may be supported at the second supporting point **P2** inside the fixed pipe **190**. The rotational force of the knob shaft **116** is transmitted to the second shaft coupling portion **230** of the joint **200** to which the end is fastened, and the knob ring **120** and the fixed pipe **190** merely perform the function of supporting the knob shaft **116**, and the rotational force of the knob shaft **116** is not received.

In some examples, in order to improve the assembly convenience of the knob shaft **116**, the knob shaft **116** includes a large diameter portion **116a** starting from a portion to which the knob ring body is coupled, a small diameter portion **116c** starting from an end coupled to the joint, and a tapered portion **116b** whose outer diameter is reduced therebetween.

A portion of the large diameter portion **116a** and the first tube part **192** are received in the outer supporting pipe **124c** of the knob ring **120**.

The outer supporting pipe **124c** of the knob ring back plate **124** is formed to have an inner diameter corresponding to the large diameter portion **116a** and the inner supporting pipe **124f** of the knob ring back plate **124** is formed with the first portion **124f_1** having the inner diameter corresponding to the large diameter portion **116a** and the second portion **124f_2** having the inner diameter corresponding to the small diameter section. Such structure results in an effect of capable of smoothly inserting the knob shaft **116** to the outer supporting pipe **124f**.

In addition, a first supporting point P1 is formed on the inner circumferential surface of the second portion **124f_2**.

In some implementations, it provides the structure that the small diameter portion **116c** of the knob shaft **116** protruded to the inner supporting pipe **124f** is again supported at the second supporting point P2 inside the fixed pipe **190** and two points are supported as a whole. The fixed pipe **190** includes a fixed circular plate portion **191** fastened to the fixed frame, the first tube part **192** extending from the fixing circular plate portion and having a shape which the inner diameter is reduced, and the second tube part surrounding the second shaft coupling pipe **237** of the joint **200**. In some examples, the second tube part **193** has an incision portion **193a** formed in the longitudinal direction of the shaft so that the second shaft coupling pipe **237** can be easily coupled to the second tube part **193**.

The knob shaft **116** has the structure fitting coupled to the second shaft coupling pipe **237** of the joint **200** inside the second tube part **193** of the fixed pipe **190**, after penetrating through the outer supporting pipe **124c** and the inner supporting pipe **124f** of the knob ring back plate **124**, and at this time, the supporting of the knob shaft **116** are made at a first supporting point P1 arranged inside the inner supporting pipe **124f** and the second point P2 arranged inside the fixed pipe **190**.

FIG. **53** is a rear view showing a knob ring of the knob assembly in accordance with an exemplary implementation of the present disclosure, FIG. **54** is a transverse cross-sectional view showing the coupling state of the knob ring of the knob assembly in accordance with an exemplary implementation of the present disclosure, and FIGS. **55** and **56** are the views for explaining the operation of the knob ring of the knob assembly in accordance with an exemplary implementation of the present disclosure.

The knob **110** and the knob ring **120** are coupled to the front surface of the front panel **10** and the support frame **150** and the actuating member **170** and the fixed frame **180** are coupled to the rear surface of the front panel **10**.

The support frame **150** is fastened to the rear surface of the front panel **10** and the actuating member **170** penetrates through the front panel **10** and is fastened to the knob ring **120**. At this time, the rotation center of the actuating member **170** is arranged to coincide with the rotation center of the knob **110**. The actuating member **170** serves to constrain the rotation center of the knob **110** to be at a center position with regard to the front panel **10**. For example, when the actuating member **170** is fixed in the center position about the front panel **10**, the knob **110** can be fixed in the correct position with regard to the front panel **10**.

The actuating member **170** is inserted inside the support frame **150** and some are protruded to the front surface of the front panel **10** through the front panel **10**. The front of the actuating member **170** is protruded to the front surface of the front panel which the operating portion **171** having the cylindrical shape is formed and the operating portion **171** is formed longer than the thickness of the support frame **150**.

The inner circular plate area **124j** of the knob ring back plate **124** is coupled with the operating portion **171** of the actuating member **170** protruded to the front surface of the front panel **10**. The knob ring **120** is coupled to the actuating member **170** supported by the support frame **150**, and, consequently, the supporting structure in which the knob ring **120** is supported by the support frame **150** is formed.

The operation of the knob ring **120** can be recognized by the rotation of the actuating member **170** rotated connected with the rotation of the knob ring **120**. Since the knob ring **120** is the part exposed to the outside the front panel **10**, a knob ring sensor **500** for sensing the operation of the knob ring **120** being installed around the knob ring **120** from the outside of the front panel **10** is externally not good.

In view of the above, in the present implementation, the knob ring sensor **500** is installed around the actuating member **170** inside the front panel **10**, and the knob ring sensor **500** installed as such can sense the rotation of the knob ring **120** in a manner of sensing the rotation of the actuating member **170** inside the front panel **10**.

In some examples, the knob assembly structure of the present implementation is provided with a fixed frame **180** for preventing the actuating member **170** from being deviate to the rear surface so that the actuating member **170** can stably operate.

The fixed frame **180** is provided as the form across the rear surface of the actuating member **170** and is fixed to the support frame **150**. The fixed frame **180** makes the actuating member **170** not be deviated to the rear surface while limiting the rotation range of the actuating member **170** within the designated range. And the extended portion **173** of the actuating member **170** can be moved only within the pivotable region **182** of the fixed frame **180**.

According to the present implementation, the actuating member **170** has an extended portion **173** formed to be extended outwardly the circular plate portion **172** formed on the rear surface, and the extended portion **173** is formed inside the fixed frame **180**.

As such, the extended portion **173** arranged inside the fixed frame **180** can move within a movable region within the fixed frame **180**, and, from the point interfered with the upper side inner wall and the lower side inner wall of the fixed frame **180**, the movement thereof is limited.

As such, when the movement range of the extended portion **173** is limited by the fixed frame **180**, the rotation angle in both directions of the actuating member **170** can be limited within the predetermined range.

By applying the structure in which the extended portion **173** is provided on both sides of the actuating member **170** and the movement range limitation of each extended portion **173** is made at the same position, the rotational range limit of the actuating member **170** can be made more stably.

In addition, the actuating member **170** is coupled to a pair of restoring springs **156a**, **156b** that provide an elastic force to return the actuating member **170** to the initial position, which is rotated from its initial position to spaced position.

The actuating member **170** and the knob ring **120** are integrally rotated so that the knob ring **120** maintains the initial position due to the elastic force of the restoring spring **156** connected to the actuating member **170**. Further, the knob ring **120** maintaining the initial position as the above can rotate clockwise or counterclockwise at a predetermined angle. When the external force is released in the rotated state, it can be returned to the initial position by the restoring force which the restoring spring **156a**, **156b** provides.

For example, when the actuating member **170** is rotated in the counterclockwise by the operation of the knob ring **120**,

as shown in FIG. 54, the first restoring spring 156a of the pair of restoring springs provides the elastic force working clockwise so that the actuating member 170 can be returned to its initial position. Further, the second restoring spring 156b, which is the other one of the pair of restoring springs 156 provides the elastic force working counterclockwise such that the actuating member 170 is returned to the initial position, when the actuating member 170 is rotated clockwise by the operation of the knob ring 120, as shown in FIG. 10.

In some examples, referring to FIG. 54, the restoring magnet 158, 178 is provided at the corresponding portion to each other of the support frame 150 and the circular plate portion 172 of the actuating member 170, respectively. The restoring magnet 158 is arranged such that the restoring magnet 178 provided in the actuating member 170 and the restoring magnet 158 provided in the support frame 150 are aligned when the actuating member 170 is in the origin. The restoring magnet 158, 178 is arranged such that a different polarity from each other is arranged in order to work an attraction mutually.

The restoring magnet 158 provided in the support frame 150 is fitted coupled from the left side to the right side in the drawing and is fitted and coupled from the right side to the left side in the drawing of the restoring magnet 178 provided on the actuating member 170. This is for the attraction working between the restoring magnets 158, 178 to work in the direction in which the restoring magnet 158, 178 is inserted into the groove. Such structure results in an effect of preventing the restoring magnet 158, 178, which is tilted by fitting the restoring magnet 158, 178, from deviating without using separate adhesive.

The knob ring sensor magnet 530 is provided to change the position by being connected with the rotation of the actuating member 170 and the knob ring sensor 500 senses a position change of the knob ring sensor magnet 530, thereby sensing the rotation of the knob ring 120, and, senses the rotation of the knob ring 120 connected to the actuating member 170.

The knob ring sensor magnet 530 is the configuration which is the sensing subject of the knob ring sensor 500 and installed on the actuating member 170. In the present implementation, it is exemplified as for the knob ring sensor magnet 530 to be installed at the circular plate portion 172 of the actuating member 170. In FIGS. 55, 56, the knob ring sensor magnet 530 is covered at the rear side of the knob ring sensor board 520, and the knob ring sensor magnet 530 is shown in a dotted line in the above Figures.

The knob ring sensor magnet 530 is installed on the circular plate portion 172 and installed so as to be arranged on one side of the circular plate portion 172 facing the knob ring sensor 500. The position of the knob ring sensor magnet 530 installed as such can be changed in a form that it is rotated together with the actuating member 170 when rotating the actuating member 170.

In the present implementation, it is exemplified that the knob ring sensor magnet 530 is arranged at a position adjacent to the outer circumferential surface of the circular plate portion 172. The position of the knob ring sensor magnet 530 arranged at such a position can be changed by drawing a trajectory similar to the shape of the outer circumferential surface of the circular plate portion 172 which is circular shape when rotating the actuating member 170.

The knob ring sensor 500 is provided to sense a position change of the knob ring sensor magnet 530 and is fastened to the support frame 150 at the rear surface of the actuating member 170.

As an example, the knob ring sensor 500 may include a knob ring sensor housing 510, a knob ring sensor board 520, and Hall sensor 522a, 522b.

The knob ring sensor housing 510 is installed to be fixed to the support frame 150 or, for example, to the lower side of the frame main body portion 141. The knob ring sensor housing 510 is installed with the knob ring sensor board 520 connected to the controller of the cooking appliance.

In the present implementation, the knob ring sensor board 520 is installed on the knob ring sensor housing 510 and is illustrated as being installed on the side facing the frame main body portion 141 and the knob ring sensor magnet 530. Further, a sensor for sensing the position change of the knob ring sensor magnet 530 is installed on the knob ring sensor board 520.

The knob ring sensor 500 having the above-described configuration senses the position of the knob ring sensor magnet 530 in a non-contact manner, like the knob sensor 400. For this, the knob ring sensor magnet 530 includes a magnetic member of generating a magnetic force, and the knob ring sensor 500 includes a Hall sensor 522 of sensing the magnetic force of the magnetic member adjacent with a predetermined distance. The Hall sensor 522 is installed on the knob ring sensor board 520. When the knob ring sensor magnet 530 approaches the Hall sensor 522 within a predetermined distance, it senses the magnetic force of the knob ring sensor magnet 530, and generates a signal corresponding thereto.

The knob ring sensor 500 includes a plurality of Hall sensors 522 and the plurality of Hall sensors 522 are arranged to be spaced apart at a predetermined spacing along the rotation path of the knob ring sensor magnet 530.

That is, when rotating the actuating member 170, when the knob ring sensor magnet 530 is rotated in the circular trajectory similar to the shape of the outer circumferential surface of the circular plate portion 172, the knob ring sensor 500 is arranged in a form which the plurality of Hall sensors 522 are positioned on the arc corresponding to the rotation trajectory of the knob ring sensor magnet 530.

In the present implementation, it is exemplified that a pair of Hall sensors 522a and 522b are arranged on the knob ring sensor 500, and the arrangement of the Hall sensor 522a, 522b and the knob ring sensor magnet 530 is made in a form positioning between the pair of the Hall sensors 522 when the knob ring 120 and the actuating member 170 are in the initial position.

According to it, at the time of one direction rotation of the knob ring 120, the knob ring sensor magnet 530 approaches to any one (hereinafter referred to as "left side Hall sensor") of the pair of Hall sensors 522, and the sensing about the knob ring sensor magnet 530 in the corresponding Hall sensor 522a is made, and at the time of the other direction of the knob ring 120, the knob ring sensor magnet 530 approaches to the other one (hereinafter referred to as "the right side Hall sensor") of the pair of Hall sensors 522, and the sensing about the knob ring sensor magnet 530 in the corresponding Hall sensor 522b is made.

When the knob ring 120 is provided to provide a timer function, and the knob ring 120 is rotated in one direction, the knob ring sensor magnet 530 approaches within the predetermined distance to the left Hall sensor 522a, the sensing with regard to the knob ring sensor magnet 530 in the left Hall sensor 522a is made, and accordingly, the

operation of the knob ring 120 for the time operation initiation is sensed by the knob ring sensor 500 such that the operation of the timer can be proceeded.

In addition, the knob ring is rotated to the other direction, the knob ring sensor magnet 530 approaches within the predetermined distance to the right Hall sensor 522b and the sensing with regard to the knob ring sensor magnet 530 in the right Hall sensor 522b is made, and accordingly, the operation of the knob ring 120 for the time operation initiation is sensed such that the operation of the timer can be proceeded.

In the present implementation, it is exemplified as generating a different kind of signal for each Hall sensor 522. That is, the signal generated by the left Hall sensor 522a is different from the signal generated by the right Hall sensor 522b.

By using this, the function of the knob ring 120 may be configured such that the set time of the timer is set differently according to the rotation direction of the knob ring 120 and the function of the knob ring 120 may be configured such that each different function is provided according to the rotation direction of the knob ring 120.

As an example, the function of the knob ring 120 may be configured such that the set time of the timer is set in a 10 minutes unit at the time of one direction rotation, and the set time of the timer is set in 1 minute unit at the time of the other direction rotation.

In addition, when maintaining the state rotated in one direction for a predetermined time or more, the set time can be continuously increased. For example, when the knob ring 120 is rotated to the right, the timer set time is increased by 10 minutes unit, and the knob ring 120 is rotated to the left and then immediately returned (hereinafter, referred to as a click), in the case of increasing by the timer set time by 1 minute unit, when the state rotated to the right is maintained for a predetermined time (for example, 3 seconds) or more (hereinafter referred to as long pushing), the timer set time is continuously increased in 10 minutes unit.

In other words, the timer set time of one unit can be increased by a short click, and the continuous increase of the timer set time can be made through a long push.

Since this click and long push all can be applied to the left and right direction of both sides, four signals can be set using two Hall sensors.

In some cases, two of four signals may be used as a signal for the timer time setting, and the remaining two signals may be used as a signal for setting other function such as selecting a cooking mode.

As another example, the function of the knob ring 120 may be configured such that a timer is set at the time of one way rotation of the knob ring 120 and the release of the timer set is released at the time of the other direction rotation of the knob ring 120.

As still another example, the function of the knob ring 120 may be configured such that the timer function is provided at the time of one direction rotation of the knob ring 120 and other function is provided other than the timer function at the time of the other direction timer function.

In some examples, the signal generated through the Hall sensor 522 may be provided as basic information for grasping information output through the display device 125.

For example, by using a signal generated from the left Hall sensor as basic information, information such as whether to initiate the timer operation, the timer time, etc., can be grasped, and information thus grasped can be displayed in a form of letters, graphics, or colors through the display device 125.

FIG. 57 is a perspective view showing a state in which the knob of the knob assembly in accordance with an exemplary implementation of the present disclosure is separated, and FIG. 58 is a transverse cross-sectional view in a state which the knob of the knob assembly in accordance with an exemplary implementation of the present disclosure with the knob is separated.

The knob assembly according to the present disclosure can be separated by pulling the knob. When the knob is separated, the knob ring back plate 124, which was covered by the knob, is exposed to the outside.

Referring to FIG. 57, it can be seen that the locking bracket 140 passes through the bracket hole 124b of the knob ring back plate 124 and is fastened to the front panel 10. At this time, a knob passage groove 144 is formed in the rear of the locking piece 142 of the locking bracket 140.

In a state which the knob is not pushed, the engaging surface (114d in FIG. 9) of the knob back plate is adjacent to the right side of the locking piece 142 of the locking bracket 140. When the knob is pushed, the engagement surface (144d in FIG. 9) is adjacent to the right side of the knob passage groove 144 of the locking bracket 140. Therefore, the knob can be rotated only when the knob is pushed.

A service hole 129 is provided on the left of the knob ring back plate 124. The service hole 129 is formed in a position aligned with the auxiliary adjustment piece 350 of the valve 310 in a straight line.

A tool such as the driver can be entered through the service hole 129 to adjust the auxiliary adjustment piece 350 of the valve 310.

The service hole 129 is formed to penetrate through the knob ring back plate 124, the front panel 10, the support frame 150, and the actuating member 170, as shown in FIG. 58.

Such structure results in an effect of improving the convenience of maintenance by separating only the knob without separating the front panel 10 and adjusting the auxiliary adjustment piece 350 of the valve 310.

In some examples, the spacing between the valve shaft 330 and the service hole 129 has to be set in consideration of the size of the joint 200 and the knob sensor 400. When the radius of the joint 200 is larger than the spacing between the valve shaft 330 and the service hole 129, the joint interferes on the path of the service hole 129.

Likewise, when the radius of the knob sensor 400 is larger than the spacing between the valve shaft 330 and the service hole 129, the knob sensor 400 interferes on the path of the service hole 129. Of course, the service hole 129 may also be penetrated also in the knob sensor 400.

An adjustment of the auxiliary adjustment piece 350 using the service hole 129 may not be generally made, but may be sometimes necessary in the case of manual adjustment by a user. In some cases, the front panel 10 may be disassembled to operate the auxiliary adjustment piece 350, which may be difficult to be performed by the user and may need to be performed by a service engineer. In some examples, when the knob may be separated, as described in the present disclosure, to operate the auxiliary adjustment piece 350, a user may perform an adjustment of the auxiliary adjustment piece 350.

While the present disclosure has been described with reference to the implementations shown in the drawings, it will be understood that it is merely illustrative and many variations and equivalent other implementation are possible from the above for those skilled in the art. Therefore, the true technical protection range of the present disclosure should be defined by claims below.

What is claimed is:

1. A knob ring assembly for an appliance, comprising:
a knob ring back plate that is configured to be disposed at
a front surface of a front panel of the appliance; and
a knob ring body that is provided at a front side of the
knob ring back plate and that is configured to circum-
ferentially surround a knob of the appliance, the knob
ring body being attached to the knob ring back plate
and configured to rotate together with the knob ring
back plate independently of a rotation of the knob,
wherein the knob ring back plate includes:
a ring supporting portion that is configured to support
the knob ring body, and
a knob supporting portion that is configured to surround
a shaft of the knob that is inserted into an interior of
the appliance and to guide a rotation of the shaft, and
wherein the knob supporting portion includes a sleeve
portion that extends away from the knob ring and is
configured to pass through the front panel and into the
interior of the appliance.
2. The knob ring assembly according to claim 1, wherein
the knob supporting portion includes an additional sleeve
portion that extends toward the knob ring body.
3. The knob ring assembly according to claim 2, wherein
the knob is connected to a front of the shaft, a rear of the
knob is opened, and the additional sleeve portion is extended
to an inner space of the knob.
4. The knob ring assembly according to claim 1, further
comprising a spacing plate which is arranged between the
knob ring back plate and the front panel and forms a gap
between the knob ring back plate and the front panel,
wherein a through hole is provided at a center of the
spacing plate, and the sleeve portion passes through the
through hole.
5. The knob ring assembly according to claim 1, further
comprising a spacing plate which is arranged between the
knob ring back plate and the front panel and forms a gap
between the knob ring back plate and the front panel.
6. The knob ring assembly according to claim 5, further
comprising an actuating member that is disposed in the
interior of the appliance, rotatably supported by the front
panel, and coupled to the ring supporting portion.
7. The knob ring assembly according to claim 6, wherein
a through hole is provided at a center of the spacing plate and
the actuating member passes through the through hole.
8. The knob ring assembly according to claim 1, further
comprising an actuating member that is disposed in the
interior of the appliance, rotatably supported by the front
panel, and coupled to the ring supporting portion.
9. The knob ring assembly according to claim 8, further
comprising a support frame which is fixed to a rear of the
front panel,
wherein the actuating member is rotatably supported by
the support frame.
10. The knob ring assembly according to claim 8, wherein
the ring supporting portion comprises:
an inner circular plate area which receives a front end of
the actuating member, and
an outer circular plate area which is arranged radially
outward from the inner circular plate area,
wherein the knob ring body is attached to the knob ring
back plate at a front of the outer circular plate area, and

the actuating member is attached to the knob ring back
plate at a rear of the inner circular plate area.

11. The knob ring assembly according to claim 1, wherein
the knob ring body includes at least one protrusion which
radially extends from the knob ring body and is configured
to be used as a handle for rotating the knob ring.

12. The knob ring assembly according to claim 1, wherein
the knob ring body includes a pair of protrusions which
radially extend from the knob ring body and a display device
is arranged between the pair of protrusions.

13. An appliance provided with a knob assembly at a case
of the appliance, the knob assembly comprising:

a knob that includes a shaft inserted into an interior of the
case; and

a knob ring that rotates independently of a rotation of the
knob and includes:

a knob ring back plate configured to be disposed at a front
surface of the case, and

a knob ring body provided at a front side of the knob ring
back plate, and that is configured to circumferentially
surround the knob, the knob ring body being attached
to the knob ring back plate and configured to rotate
together with the knob ring back plate,

wherein the knob ring back plate includes:

a ring supporting portion that is configured to support
the knob ring body, and

a knob supporting portion that is configured to surround
the shaft of the knob and to guide a rotation of the
shaft, and

wherein the knob supporting portion includes a sleeve
portion that extends away from the knob ring and is
configured to pass through a front panel of the appli-
ance and into the interior of the appliance.

14. The appliance according to claim 13, wherein the
knob supporting portion includes an additional sleeve por-
tion that extends toward the knob ring body.

15. The appliance according to claim 13, the knob assem-
bly further comprising a spacing plate which is arranged
between the knob ring back plate and the case and fixed to
the case, the spacing plate forms a gap between the knob ring
back plate and the case.

16. The appliance according to claim 13, the knob assem-
bly further comprising an actuating member that is disposed
in the interior of the case, rotatably supported by the case,
and coupled to the ring supporting portion.

17. The appliance according to claim 13, the knob ring
body includes at least one protrusion which radially extends
from the knob ring body and is configured to be used as a
handle for rotating the knob ring.

18. The appliance according to claim 13, wherein the
knob ring body includes a pair of protrusions which radially
extend from the knob ring body and a display device is
arranged between the pair of protrusions.

19. The appliance according to claim 14, wherein a rear
of the knob is opened, and the additional sleeve portion
extends to an inner space of the knob.

20. The appliance according to claim 15, wherein a
through hole is provided at a center of the spacing plate, and
the sleeve portion passes through the through hole.