



US011150378B2

(12) **United States Patent**  
**Root et al.**

(10) **Patent No.:** **US 11,150,378 B2**  
(45) **Date of Patent:** **Oct. 19, 2021**

(54) **METHOD OF OUTPUTTING WEATHER/ENVIRONMENTAL INFORMATION FROM WEATHER/ENVIRONMENTAL SENSORS**

(71) Applicant: **LOCATOR IP, L.P.**, State College, PA (US)

(72) Inventors: **Steven A. Root**, Edmond, OK (US);  
**Michael R. Root**, Edmond, OK (US)

(73) Assignee: **Locator IP, L.P.**, State College, PA (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 195 days.

(21) Appl. No.: **14/073,418**

(22) Filed: **Nov. 6, 2013**

(65) **Prior Publication Data**

US 2014/0137644 A1 May 22, 2014

**Related U.S. Application Data**

(63) Continuation of application No. 11/035,654, filed on Jan. 14, 2005, now abandoned.

(51) **Int. Cl.**  
**G01W 1/00** (2006.01)  
**G06Q 10/06** (2012.01)  
**G06Q 30/02** (2012.01)

(52) **U.S. Cl.**  
CPC ..... **G01W 1/00** (2013.01); **G06Q 10/06** (2013.01); **G06Q 10/063112** (2013.01); **G06Q 30/02** (2013.01); **G06Q 30/0205** (2013.01)

(58) **Field of Classification Search**  
CPC ..... **G01W 1/00**; **G06Q 10/06**; **G06Q 30/02**  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,596,264 A \* 7/1971 Ciemochowski ..... 340/870.16  
3,891,979 A \* 6/1975 Braun et al. .... 340/581  
(Continued)

FOREIGN PATENT DOCUMENTS

AU 2001277030 B2 3/2006  
AU 2006204945 A1 7/2006  
(Continued)

OTHER PUBLICATIONS

Enrique R. Vivoni et al, Real-time streaming of environmental field data, Computers & Geosciences 29 (2003) 457-468 (Year: 2003).\*  
(Continued)


*Primary Examiner* — Andre D Boyce

(74) *Attorney, Agent, or Firm* — Perkins Coie LLP; Drew Schulte

(57) **ABSTRACT**

A method of generating individualized real-time weather and environmental information, including receiving weather or environmental condition data from weather and environmental sensors, analyzing the data received from the sensors to generate weather and environmental information, and transmitting the information to a communicator device. The method may include determining a spatial range of a sensor and/or determining if a communicator device is within close proximity of a sensor. The sensors may be mounted in fixed locations along a roadway or a railway. The sensors may be approximately equidistant.

**20 Claims, 4 Drawing Sheets**



(56)

References Cited

U.S. PATENT DOCUMENTS

4,015,366 A	4/1977	Hall, III		5,790,664 A	8/1998	Coley et al.	
4,222,044 A *	9/1980	Boschung .....	340/581	5,790,953 A	8/1998	Wang et al.	
4,438,439 A	3/1984	Shreve		5,794,234 A	8/1998	Church et al.	
4,459,682 A	7/1984	Mossberg		5,819,227 A	10/1998	Obuchi	
4,473,844 A	9/1984	Klein		5,828,843 A	10/1998	Grimm et al.	
4,521,857 A	6/1985	Reynolds, III		5,839,088 A	11/1998	Hancock et al.	
4,529,982 A	7/1985	Karlstrom et al.		5,845,276 A	12/1998	Emerson et al.	
4,577,109 A	3/1986	Hirschfeld		5,848,131 A	12/1998	Shaffer et al.	
4,586,827 A	5/1986	Hirsch et al.		5,848,378 A *	12/1998	Shelton et al. ....	702/3
4,755,942 A	7/1988	Gardner et al.		5,864,860 A	1/1999	Holmes	
4,774,658 A	9/1988	Lewin		5,864,875 A	1/1999	Van Huben et al.	
4,845,629 A *	7/1989	Murga .....	G08G 5/0026 169/61	5,867,109 A	2/1999	Wiedeman	
4,892,335 A	1/1990	Taft		5,867,110 A	2/1999	Naito et al.	
4,901,300 A	2/1990	Van Der Zande et al.		5,867,821 A	2/1999	Ballantyne et al.	
4,945,355 A	7/1990	Blanchette		5,874,914 A	2/1999	Krasner	
4,972,319 A	11/1990	Delorme		5,880,958 A	3/1999	Helms et al.	
5,111,111 A	5/1992	Stevens et al.		5,884,267 A	3/1999	Goldenthal et al.	
5,111,391 A	5/1992	Fields et al.		5,884,309 A	3/1999	Vanechanos, Jr.	
5,117,353 A	5/1992	Stipanovich et al.		5,892,917 A	4/1999	Myerson	
5,122,959 A	6/1992	Nathanson et al.		5,893,905 A	4/1999	Main et al.	
5,131,020 A	7/1992	Liebesny et al.		5,898,680 A *	4/1999	Johnstone et al. ....	370/316
5,164,904 A *	11/1992	Sumner .....	G08G 1/0104 340/905	5,948,041 A	9/1999	Abo et al.	
5,193,143 A	3/1993	Kaemmerer		5,950,161 A	9/1999	Kozuma et al.	
5,214,757 A *	5/1993	Mauney .....	G01C 21/32 340/990	5,963,130 A	10/1999	Schlager et al.	
5,214,793 A *	5/1993	Conway .....	G08G 1/096716 340/905	5,974,447 A	10/1999	Cannon et al.	
5,229,975 A *	7/1993	Truesdell .....	G01S 7/64 367/107	5,978,730 A *	11/1999	Poppen .....	G01C 21/3446 370/351
5,250,955 A	10/1993	Major et al.		5,982,860 A *	11/1999	Kim .....	H04M 1/654 379/100.01
5,265,024 A *	11/1993	Crabill et al. ....	701/538	5,991,735 A	11/1999	Gerace	
5,298,760 A	3/1994	Fuchs et al.		5,999,126 A	12/1999	Ito	
5,365,290 A	11/1994	Suzuki et al.		5,999,882 A	12/1999	Simpson et al.	
5,398,021 A	3/1995	Moore		6,000,285 A	12/1999	Leslie et al.	
5,416,694 A	5/1995	Parrish et al.		6,014,090 A	1/2000	Rosen et al.	
5,432,509 A *	7/1995	Kajiwara .....	340/903	6,018,699 A *	1/2000	Baron et al. ....	702/3
5,434,565 A	7/1995	Simon et al.		6,021,432 A	2/2000	Sizer, II et al.	
5,442,147 A	8/1995	Burns et al.		6,023,223 A *	2/2000	Baxter, Jr. ....	G06Q 10/06 340/3.4
5,444,444 A	8/1995	Ross		6,023,765 A	2/2000	Kuhn	
5,448,696 A	9/1995	Shimada et al.		6,028,514 A	2/2000	Lemelson et al.	
5,467,268 A	11/1995	Sisley et al.		6,031,455 A	2/2000	Grube et al.	
5,481,254 A	1/1996	Gaskill et al.		6,040,781 A	3/2000	Murray	
5,486,830 A	1/1996	Axline, Jr. et al.		6,043,756 A	3/2000	Bateman et al.	
5,488,697 A	1/1996	Kaemmerer		6,047,236 A	4/2000	Hancock et al.	
5,493,709 A	2/1996	Duckeck et al.		6,047,327 A	4/2000	Tso et al.	
5,528,678 A	6/1996	Kaplan		6,049,776 A	4/2000	Donnelly et al.	
5,544,140 A	8/1996	Seagrave et al.		6,054,950 A	4/2000	Fontana	
5,550,981 A	8/1996	Bauer et al.		6,055,434 A *	4/2000	Seraj .....	G01S 5/0045 455/456.1
5,555,446 A	9/1996	Jasinski		6,070,143 A	5/2000	Barney et al.	
5,565,863 A	10/1996	Simon et al.		6,078,260 A	6/2000	Desch	
5,606,699 A	2/1997	De Pauw et al.		6,084,510 A	7/2000	Lemelson et al.	
5,607,187 A	3/1997	Salive et al.		6,088,679 A	7/2000	Barkley	
5,615,121 A	3/1997	Babayev et al.		6,091,956 A	7/2000	Hollenberg	
5,615,223 A	3/1997	Carr		6,091,959 A	7/2000	Souissi et al.	
5,615,400 A	3/1997	Cowsar et al.		6,094,509 A	7/2000	Zheng et al.	
5,628,050 A	5/1997	McGraw et al.		6,098,048 A	8/2000	Dashefsky et al.	
5,629,854 A *	5/1997	Schulte .....	G01C 21/3632 701/431	6,100,806 A	8/2000	Gaukel	
5,634,057 A	5/1997	Dickinson		6,101,443 A *	8/2000	Kato .....	G01C 21/3415 340/995.21
5,642,303 A	6/1997	Small et al.		6,108,699 A	8/2000	Moiin	
5,649,182 A	7/1997	Reitz		6,112,074 A *	8/2000	Pinder .....	455/404.2
5,671,412 A	9/1997	Christiano		6,112,075 A *	8/2000	Weiser .....	455/404.1
5,684,476 A	11/1997	Anderson		6,133,853 A	10/2000	Obradovich et al.	
5,689,650 A	11/1997	McClelland et al.		6,133,912 A	10/2000	Montero	
5,703,930 A	12/1997	Miska et al.		6,138,073 A	10/2000	Uchigaki	
5,706,505 A	1/1998	Fraley et al.		6,144,739 A	11/2000	Witt et al.	
5,717,589 A	2/1998	Thompson et al.		6,148,261 A	11/2000	Obradovich et al.	
5,725,253 A	3/1998	Salive et al.		6,161,092 A	12/2000	Latshaw et al.	
5,754,782 A	5/1998	Masada		6,167,255 A	12/2000	Kennedy, III et al.	
5,757,322 A	5/1998	Ray et al.		6,177,873 B1 *	1/2001	Cragun .....	340/601
5,764,906 A	6/1998	Edelstein et al.		6,181,260 B1	1/2001	Simon et al.	
5,768,577 A	6/1998	Kleewein et al.		6,185,427 B1	2/2001	Krasner et al.	
				6,199,045 B1	3/2001	Giniger et al.	
				6,202,023 B1	3/2001	Hancock et al.	
				6,204,761 B1 *	3/2001	Vanderable .....	340/539.28
				6,209,026 B1	3/2001	Ran et al.	
				6,212,393 B1	4/2001	Suarez et al.	
				6,219,667 B1	4/2001	Lu et al.	

(56)

References Cited

U.S. PATENT DOCUMENTS

6,231,519 B1	5/2001	Blants et al.	6,650,972 B1 *	11/2003	Robinson et al. ....	701/3
6,233,122 B1	5/2001	Summers	6,654,689 B1 *	11/2003	Kelly et al. ....	702/3
6,240,369 B1 *	5/2001	Foust ..... 702/3	6,658,568 B1	12/2003	Ginter et al.	
6,252,539 B1 *	6/2001	Phillips et al. .... 342/26 D	6,675,151 B1	1/2004	Thompson et al.	
6,252,544 B1	6/2001	Hoffberg	6,677,894 B2	1/2004	Sheynblat et al.	
6,255,953 B1 *	7/2001	Barber ..... 340/601	6,678,700 B1	1/2004	Moore et al.	
6,266,612 B1	7/2001	Dussell et al.	6,680,675 B1	1/2004	Suzuki	
6,266,683 B1	7/2001	Yehuda et al.	6,684,136 B2	1/2004	Sinex	
6,269,309 B1	7/2001	Buckingham	6,697,859 B1	2/2004	Takahashi	
6,275,231 B1	8/2001	Obradovich	6,700,482 B2 *	3/2004	Ververs et al. .... 340/500	
6,289,277 B1 *	9/2001	Feyereisen et al. .... 701/528	6,708,211 B1	3/2004	Tingley et al.	
6,295,001 B1 *	9/2001	Barber ..... 340/601	6,714,793 B1	3/2004	Carey et al.	
6,295,502 B1	9/2001	Hancock et al.	6,731,940 B1	5/2004	Nagendran	
6,297,766 B1 *	10/2001	Koeller ..... 342/357.31	6,742,002 B2	5/2004	Arrowood	
6,329,904 B1	12/2001	Lamb	6,745,021 B1	6/2004	Stevens	
6,334,133 B1	12/2001	Thompson et al.	6,745,036 B1 *	6/2004	Dunne ..... G01S 5/00	
6,339,744 B1	1/2002	Hancock et al.			455/422.1	
6,339,747 B1	1/2002	Daly et al.	6,751,553 B2	6/2004	Young et al.	
6,343,255 B1 *	1/2002	Peek et al. .... 702/3	6,753,784 B1 *	6/2004	Sznaideret al. .... 340/601	
6,347,216 B1	2/2002	Marko et al.	6,754,585 B2	6/2004	Root et al.	
6,351,218 B1 *	2/2002	Smith ..... 340/601	6,792,615 B1	9/2004	Rowe et al.	
6,356,834 B2	3/2002	Hancock et al.	6,798,358 B2	9/2004	Joyce et al.	
6,360,172 B1	3/2002	Burfeind et al.	6,812,855 B1	11/2004	Sudou et al.	
6,363,411 B1	3/2002	Dugan et al.	6,816,878 B1	11/2004	Zimmers et al.	
6,380,869 B1	4/2002	Simon et al.	6,823,263 B1	11/2004	Kelly et al.	
6,381,535 B1	4/2002	Durocher et al.	6,823,315 B1	11/2004	Bucci et al.	
6,396,397 B1 *	5/2002	Bos ..... B60N 2/002	6,823,344 B1	11/2004	Isensee et al.	
		180/167	6,826,481 B2	11/2004	Root et al.	
6,404,880 B1 *	6/2002	Stevens ..... 379/221.11	6,829,233 B1	12/2004	Gilboy	
6,405,134 B1	6/2002	Smith et al.	6,829,334 B1	12/2004	Zirngibl et al.	
6,408,337 B1	6/2002	Dietz et al.	6,829,536 B2 *	12/2004	Moore ..... 702/3	
6,411,687 B1	6/2002	Bohacek et al.	6,836,730 B2 *	12/2004	Root et al. .... 702/3	
6,411,809 B1	6/2002	Haakana et al.	6,838,998 B1	1/2005	Brown et al.	
6,418,371 B1	7/2002	Arnold	6,845,324 B2	1/2005	Smith	
6,430,562 B1	8/2002	Kardos et al.	6,850,895 B2	2/2005	Brodersen et al.	
6,446,004 B1	9/2002	Cao et al.	6,853,915 B2	2/2005	Hubschneider et al.	
6,449,488 B1	9/2002	Cheng et al.	6,861,959 B1 *	3/2005	Torres Sabate ..... G08B 25/016	
6,456,852 B2 *	9/2002	Bar ..... G01C 21/26			340/901	
		342/357.52	6,892,390 B1	5/2005	Lieberman et al.	
6,462,665 B1 *	10/2002	Tarlton et al. .... 340/601	6,909,361 B2	6/2005	McCarthy et al.	
6,469,664 B1	10/2002	Michaelson et al.	6,909,903 B2	6/2005	Wang	
6,473,692 B2	10/2002	Hancock et al.	6,912,545 B1	6/2005	Lundy et al.	
6,484,033 B2	11/2002	Murray	6,941,126 B1	9/2005	Jordan, Jr.	
6,493,633 B2 *	12/2002	Baron et al. .... 702/3	6,944,447 B2	9/2005	Portman et al.	
6,496,776 B1	12/2002	Blumberg et al.	6,962,531 B2	11/2005	Pace et al.	
6,497,367 B2	12/2002	Conzola et al.	6,973,384 B2	12/2005	Zhao et al.	
6,498,987 B1 *	12/2002	Kelly et al. .... 702/3	6,975,942 B2	12/2005	Young et al.	
6,501,392 B2	12/2002	Gremmert et al.	6,980,909 B2	12/2005	Root et al.	
6,505,123 B1 *	1/2003	Root et al. .... 702/3	6,985,813 B2	1/2006	Root et al.	
6,519,571 B1	2/2003	Guheen	6,985,929 B1	1/2006	Wilson et al.	
6,522,875 B1	2/2003	Dowling et al.	6,988,037 B2	1/2006	Root et al.	
6,522,888 B1	2/2003	Garceran et al.	6,989,765 B2	1/2006	Gueziec	
6,526,268 B1	2/2003	Marrah et al.	6,990,458 B2	1/2006	Harrison et al.	
6,526,335 B1	2/2003	Treyz	7,010,501 B1	3/2006	Roslak et al.	
6,531,218 B2	3/2003	Hoyt et al.	7,016,689 B2	3/2006	Clark et al.	
6,535,817 B1	3/2003	Krishnamurti	7,024,205 B1	4/2006	Hose	
6,542,825 B2	4/2003	Jones et al.	7,024,310 B2	4/2006	Root et al.	
6,552,682 B1	4/2003	Fan	7,031,724 B2	4/2006	Ross et al.	
6,553,317 B1	4/2003	Lincoln et al.	7,047,114 B1	5/2006	Rogers	
6,560,456 B1	5/2003	Lohtia et al.	7,053,780 B1 *	5/2006	Straub et al. .... 340/601	
6,564,143 B1	5/2003	Alewine et al.	7,058,510 B2	6/2006	Kelly et al.	
6,571,279 B1	5/2003	Herz et al.	7,072,666 B1	7/2006	Kullman et al.	
6,578,005 B1	6/2003	Lesaint et al.	7,079,631 B1	7/2006	Kaufman	
6,587,813 B1	7/2003	Whitt et al.	7,080,018 B1	7/2006	Fox et al.	
6,587,831 B1	7/2003	O'Brien	7,084,757 B2 *	8/2006	Terui ..... G08G 1/0104	
6,587,851 B1	7/2003	Ditcharo et al.			340/436	
6,590,529 B2	7/2003	Schwoegler	7,084,775 B1 *	8/2006	Smith ..... 340/601	
6,597,983 B2	7/2003	Hancock	7,089,115 B2 *	8/2006	Chapman et al. .... 702/3	
6,603,405 B2 *	8/2003	Smith ..... 340/905	7,089,116 B2	8/2006	Smith	
6,609,062 B2	8/2003	Hancock	7,096,276 B2	8/2006	Bodin et al.	
6,611,687 B1	8/2003	Clark et al.	7,103,596 B2	9/2006	Abe et al.	
6,633,900 B1	10/2003	Khalessi et al.	7,123,926 B2	10/2006	Himmelstein	
6,646,559 B2	11/2003	Smith	7,139,664 B2	11/2006	Kelly et al.	
6,647,257 B2	11/2003	Owensby	7,171,372 B2	1/2007	Daniel et al.	
6,650,902 B1	11/2003	Richton	7,181,345 B2 *	2/2007	Rosenfeld et al. .... 702/3	
			7,184,540 B2	2/2007	Dezonno et al.	
			7,184,896 B1	2/2007	Benson	
			7,185,044 B2 *	2/2007	Ryan et al. .... 709/200	
			7,191,064 B1	3/2007	Myers et al.	

(56)

References Cited

U.S. PATENT DOCUMENTS

7,191,065 B2	3/2007	Root et al.	2002/0165732 A1	11/2002	Ezzeddine et al.
7,197,308 B2	3/2007	Singhal et al.	2002/0173981 A1	11/2002	Stewart
7,212,811 B2	5/2007	Dowling et al.	2002/0175211 A1	11/2002	Dominguez et al.
7,212,829 B1	5/2007	Lau et al.	2002/0183117 A1	12/2002	Takahashi et al.
7,218,938 B1	5/2007	Lau et al.	2002/0194366 A1	12/2002	Bodin et al.
7,231,657 B2	6/2007	Honarvar et al.	2003/0004780 A1	1/2003	Smith et al.
7,233,781 B2	6/2007	Hunter et al.	2003/0004802 A1	1/2003	Callegari
7,242,988 B1	7/2007	Hoffberg et al.	2003/0014297 A1	1/2003	Kaufman et al.
7,248,159 B2	7/2007	Smith	2003/0028410 A1	2/2003	House et al.
7,254,481 B2	8/2007	Yamada et al.	2003/0040849 A1	2/2003	Hathout et al.
7,254,588 B2	8/2007	Sung et al.	2003/0043073 A1	3/2003	Gray
7,269,505 B2	9/2007	Zhao et al.	2003/0059158 A1	3/2003	Lacey
7,284,000 B2	10/2007	Kuehr-Mclaren et al.	2003/0060211 A1	3/2003	Chern et al.
7,284,033 B2	10/2007	Jhanji	2003/0068974 A1	4/2003	Kanamaluru et al.
7,289,908 B2	10/2007	Root et al.	2003/0100315 A1	5/2003	Rankin
7,299,492 B2	11/2007	Thrash et al.	2003/0107490 A1	6/2003	Sznaider et al.
7,315,782 B2	1/2008	Root et al.	2003/0113014 A1	6/2003	Katoh
7,321,305 B2	1/2008	Gollu	2003/0125963 A1	7/2003	Haken
7,327,271 B2	2/2008	Greenstein et al.	2003/0132298 A1	7/2003	Swartz et al.
7,330,112 B1	2/2008	Emigh et al.	2003/0149607 A1	8/2003	Ogasawara et al.
7,330,693 B1	2/2008	Goss	2003/0156049 A1	8/2003	Behr et al.
7,337,146 B2	2/2008	Heelan et al.	2003/0169367 A1	9/2003	Ranta
7,366,522 B2	4/2008	Thomas	2003/0171870 A1	9/2003	Gueziec
7,383,130 B1 *	6/2008	Koosam ..... 702/3	2003/0191765 A1	10/2003	Bargh et al.
7,397,390 B2 *	7/2008	DiPiazza ..... G08G 1/01 340/905	2003/0191795 A1	10/2003	Bernardin et al.
7,400,976 B2	7/2008	Young et al.	2003/0198337 A1	10/2003	Lenard
7,403,925 B2	7/2008	Schlesinger et al.	2003/0200027 A1	10/2003	Root et al.
7,406,382 B2	7/2008	Brulle-Drews	2004/0002348 A1	1/2004	Fraccaroli
7,411,493 B2	8/2008	Smith	2004/0010372 A1	1/2004	Schwogler
7,421,344 B1 *	9/2008	Marsh et al. .... 702/3	2004/0010591 A1	1/2004	Sinn et al.
7,426,203 B1	9/2008	McNamara et al.	2004/0023666 A1	2/2004	Moon et al.
7,502,748 B1	3/2009	Baldwin et al.	2004/0059996 A1	3/2004	Fasciano
7,557,730 B2	7/2009	Gueziec	2004/0077347 A1 *	4/2004	Lauber ..... G08G 1/0962 455/428
7,567,575 B2	7/2009	Chen et al.	2004/0093265 A1	5/2004	Ramchandani et al.
7,568,217 B1	7/2009	Prasad et al.	2004/0107126 A1	6/2004	Kataoka et al.
7,599,795 B1	10/2009	Blumberg et al.	2004/0110515 A1	6/2004	Blumberg et al.
7,602,285 B2	10/2009	Sznaider et al.	2004/0130463 A1 *	7/2004	Bloomquist ..... G08G 1/096716 340/907
7,606,663 B2	10/2009	Neef et al.	2004/0161097 A1	8/2004	Henry
7,647,022 B2	1/2010	Ng et al.	2004/0167813 A1	8/2004	Robertson et al.
7,650,633 B2	1/2010	Whitson	2004/0172343 A1	9/2004	Allibhoy et al.
7,668,832 B2	2/2010	Yeh et al.	2004/0199655 A1	10/2004	Davies et al.
7,716,077 B1	5/2010	Mikurak	2004/0203854 A1	10/2004	Nowak
7,720,606 B2	5/2010	Burfeind et al.	2004/0210479 A1	10/2004	Perkowski et al.
7,917,555 B2	3/2011	Gottumukkala et al.	2004/0221308 A1	11/2004	Cuttner et al.
8,229,467 B2	7/2012	Root et al.	2004/0267595 A1	12/2004	Woodings et al.
8,483,651 B1	7/2013	Zamora et al.	2005/0001720 A1	1/2005	Mason
8,634,814 B2	1/2014	Root et al.	2005/0003828 A1	1/2005	Sugar et al.
8,769,480 B1	7/2014	Wagner et al.	2005/0021666 A1	1/2005	Dinnage et al.
8,971,913 B2	3/2015	Moeglein et al.	2005/0021806 A1	1/2005	Richardson et al.
9,237,416 B2	1/2016	Root et al.	2005/0021980 A1	1/2005	Kanai
9,392,460 B1	7/2016	Blake et al.	2005/0025132 A1	2/2005	Harper et al.
2001/0029160 A1	10/2001	Aznal	2005/0027449 A1	2/2005	Marsh
2001/0030624 A1 *	10/2001	Schwogler ..... 342/357.13	2005/0038876 A1	2/2005	Chaudhuri
2001/0042001 A1	11/2001	Goto et al.	2005/0040847 A1	2/2005	Unger et al.
2001/0045886 A1	11/2001	Minowa	2005/0049789 A1 *	3/2005	Kelly et al. .... 702/3
2001/0049584 A1	12/2001	Jones et al.	2005/0050008 A1	3/2005	Root et al.
2001/0049636 A1	12/2001	Hudda et al.	2005/0055374 A1	3/2005	Sato
2001/0051888 A1	12/2001	Mayhak et al.	2005/0096962 A1	5/2005	Narasimhan et al.
2001/0053999 A1	12/2001	Feinberg	2005/0136917 A1	6/2005	Taylor
2002/0000930 A1	1/2002	Crowson et al.	2005/0136949 A1	6/2005	Barnes, Jr.
2002/0009353 A1	1/2002	Kelsey et al.	2005/0136983 A1	6/2005	Agapi et al.
2002/0010615 A1	1/2002	Jacobs	2005/0154531 A1 *	7/2005	Kelly et al. .... 702/3
2002/0025964 A1	2/2002	Streuff et al.	2005/0174235 A1	8/2005	Davis et al.
2002/0029160 A1	3/2002	Thompson et al.	2005/0181803 A1	8/2005	Weaver et al.
2002/0040313 A1	4/2002	Hunter et al.	2005/0192724 A1	9/2005	Hendry
2002/0048283 A1	4/2002	Lin	2005/0227709 A1	10/2005	Chang et al.
2002/0049310 A1	4/2002	Tateishi et al.	2005/0228873 A1	10/2005	Tapuska et al.
2002/0052674 A1	5/2002	Chang et al.	2005/0240378 A1	10/2005	Smith et al.
2002/0062451 A1	5/2002	Scheidt et al.	2005/0243784 A1	11/2005	Fitzgerald et al.
2002/0077876 A1	6/2002	O'Meara et al.	2005/0245243 A1	11/2005	Zuniga
2002/0091568 A1	7/2002	Kraft et al.	2005/0251370 A1	11/2005	Li et al.
2002/0095333 A1	7/2002	Jokinen et al.	2005/0256781 A1	11/2005	Sands et al.
2002/0147642 A1	10/2002	Avallone et al.	2006/0009155 A1	1/2006	Paalasmaa et al.
2002/0160745 A1	10/2002	Wang	2006/0010467 A1	1/2006	Segel
			2006/0015254 A1 *	1/2006	Smith ..... 702/3
			2006/0020480 A1	1/2006	Hickey
			2006/0022846 A1	2/2006	Tummala

(56)

References Cited

U.S. PATENT DOCUMENTS

2006/0028400 A1 2/2006 Lapstun et al.  
 2006/0030354 A1 2/2006 Ho et al.  
 2006/0046740 A1 3/2006 Johnson  
 2006/0052090 A1 3/2006 Behr et al.  
 2006/0111089 A1 5/2006 Winter et al.  
 2006/0123053 A1 6/2006 Scannell  
 2006/0142024 A1 6/2006 Thalanany et al.  
 2006/0161469 A1 7/2006 Root et al.  
 2006/0164259 A1 7/2006 Winkler et al.  
 2006/0178140 A1 8/2006 Smith et al.  
 2006/0187017 A1 8/2006 Kulesz et al.  
 2006/0194595 A1 8/2006 Myllynen et al.  
 2006/0200480 A1 9/2006 Harris et al.  
 2006/0265238 A1 11/2006 Perrier et al.  
 2006/0271560 A1 11/2006 Mitchell  
 2006/0293065 A1 12/2006 Chew et al.  
 2006/0294147 A1 12/2006 Root et al.  
 2007/0001904 A1 1/2007 Mendelson  
 2007/0005363 A1 1/2007 Cucerzan et al.  
 2007/0021906 A1 1/2007 Yeh et al.  
 2007/0050128 A1 3/2007 Lee et al.  
 2007/0061300 A1 3/2007 Ramer et al.  
 2007/0061844 A1 3/2007 Hakusui et al.  
 2007/0072595 A1 3/2007 Pi et al.  
 2007/0094071 A1 4/2007 Seraji et al.  
 2007/0094262 A1 4/2007 Suzuki et al.  
 2007/0112511 A1 5/2007 Burfeind et al.  
 2007/0127423 A1 6/2007 Ho  
 2007/0162320 A1 7/2007 Joshi et al.  
 2007/0162328 A1 7/2007 Reich  
 2007/0168131 A1 7/2007 Root et al.  
 2007/0168524 A1 7/2007 Chao et al.  
 2007/0180119 A1 8/2007 Khivesara et al.  
 2007/0192159 A1 8/2007 Root et al.  
 2007/0197231 A1 8/2007 Lin  
 2007/0249323 A1 10/2007 Lee et al.  
 2007/0260531 A1 11/2007 Bezancon  
 2007/0260708 A1 11/2007 Beaton et al.  
 2007/0260741 A1 11/2007 Bezancon  
 2007/0270165 A1 11/2007 Poosala  
 2007/0270166 A1 11/2007 Hampel et al.  
 2007/0293240 A1 12/2007 Drennan  
 2008/0020702 A1 1/2008 Jendbro et al.  
 2008/0021645 A1 1/2008 Lau et al.  
 2008/0070550 A1 3/2008 Hose  
 2008/0082264 A1 4/2008 Hill et al.  
 2008/0084857 A1 4/2008 Gorti et al.  
 2008/0134043 A1 6/2008 Georgis et al.  
 2008/0134258 A1 6/2008 Goose et al.  
 2008/0140318 A1 6/2008 Breed  
 2008/0157990 A1 7/2008 Belzer et al.  
 2008/0160956 A1 7/2008 Jackson et al.  
 2008/0161012 A1 7/2008 Haran et al.  
 2008/0162036 A1 7/2008 Breed  
 2008/0183710 A1 7/2008 Serjeantson et al.  
 2008/0189028 A1 8/2008 Nair et al.  
 2008/0207183 A1 8/2008 Root et al.  
 2008/0270030 A1 10/2008 Copley  
 2008/0271120 A1 10/2008 Parkes et al.  
 2008/0275759 A1 11/2008 Parkes et al.  
 2008/0294478 A1 11/2008 Joshi et al.  
 2008/0313037 A1 12/2008 Root et al.  
 2008/0319652 A1 12/2008 Moshfeghi  
 2008/0319653 A1 12/2008 Moshfeghi  
 2009/0061903 A1 3/2009 Khokhar  
 2009/0073885 A1 3/2009 Jalil et al.  
 2009/0083150 A1 3/2009 Mashinsky  
 2009/0131080 A1 5/2009 Nadler et al.  
 2009/0156161 A1 6/2009 Strahs  
 2009/0176511 A1 7/2009 Morrison  
 2009/0176512 A1 7/2009 Morrison  
 2009/0177374 A1 7/2009 Liu  
 2009/0198641 A1 8/2009 Tortoriello  
 2009/0205036 A1 8/2009 Slaton et al.  
 2009/0209233 A1 8/2009 Morrison

2009/0210441 A1 8/2009 Mercer et al.  
 2009/0233575 A1 9/2009 Morrison  
 2009/0233633 A1 9/2009 Morrison  
 2009/0239511 A1 9/2009 Chen et al.  
 2009/0240428 A1 9/2009 Shahrestani  
 2009/0265099 A1 10/2009 Gottlieb  
 2009/0275348 A1 11/2009 Weinreich et al.  
 2009/0285483 A1 11/2009 Guven et al.  
 2009/0287587 A1 11/2009 Bloebaum  
 2009/0305645 A1 12/2009 Watanabe  
 2010/0009657 A1 1/2010 Dingler et al.  
 2010/0013629 A1 1/2010 Sznajder et al.  
 2010/0036717 A1 2/2010 Trest  
 2010/0042483 A1 2/2010 Hipsher  
 2010/0069052 A1 3/2010 Ahomaki et al.  
 2010/0069093 A1 3/2010 Morrison  
 2011/0066497 A1 3/2011 Gopinath et al.  
 2011/0128144 A1 6/2011 Baron et al.  
 2012/0085828 A1 4/2012 Ziegler  
 2012/0099756 A1 4/2012 Sherman et al.  
 2012/0116861 A1 5/2012 Dobyms  
 2012/0173075 A1 7/2012 Mays  
 2012/0229624 A1 9/2012 Calman et al.  
 2012/0229657 A1 9/2012 Calman et al.  
 2012/0278172 A1 11/2012 Mercuri et al.  
 2013/0029693 A1 1/2013 Bradley, Jr. et al.  
 2013/0046589 A1 2/2013 Grigg et al.  
 2013/0080055 A1 3/2013 Speier et al.  
 2013/0085673 A1 4/2013 Cavalcante et al.  
 2013/0091452 A1 4/2013 Sorden  
 2013/0165070 A1 6/2013 Hoffberg  
 2013/0290106 A1 10/2013 Bradley et al.  
 2013/0057551 A1 12/2013 Ebert et al.  
 2014/0137644 A1 5/2014 Root et al.  
 2014/0258109 A1 9/2014 Jiang et al.  
 2015/0182843 A1 7/2015 Esposito  
 2015/0186538 A1 7/2015 Yan  
 2017/0295265 A1 10/2017 Hala et al.

FOREIGN PATENT DOCUMENTS

AU 2007207616 A1 7/2007  
 AU 2006202473 A1 1/2010  
 AU 2012200288 A1 2/2012  
 CA 2 418 268 A1 1/2002  
 CA 2418268 A1 1/2002  
 CA 2514868 A1 8/2004  
 CA 2594001 A1 7/2006  
 CN 1230265 A 9/1999  
 CN 1449615 A 10/2003  
 CN 1659602 A 8/2005  
 CN 1745540 A 3/2006  
 CN 101083784 A 12/2007  
 CN 101120316 A 2/2008  
 CN 102682395 A 9/2012  
 EP 0436263 A1 7/1991  
 EP 0703463 A2 3/1996  
 EP 0798539 A2 10/1997  
 EP 1143399 A1 10/2001  
 EP 1303965 A2 4/2003  
 EP 1473684 A1 11/2004  
 EP 1593085 A2 11/2005  
 EP 1856608 A2 11/2007  
 EP 1912409 A1 4/2008  
 EP 1999665 A2 12/2008  
 EP 2115613 A2 11/2009  
 EP 2720481 A2 4/2014  
 GB 2201865 A 9/1988  
 GB 2216319 A 10/1989  
 JP 1065596 A 3/1989  
 JP 06508964 10/1994  
 JP 08221694 A 8/1996  
 JP H10-65596 A 3/1998  
 JP H1128879 A 2/1999  
 JP 11-136365 A 5/1999  
 JP H11-215569 A 8/1999  
 JP 2000030148 A 1/2000  
 JP 2000167232 A 6/2000  
 JP 2001126170 A 5/2001

(56)

## References Cited

FOREIGN PATENT DOCUMENTS		
JP	2001135285	A 5/2001
JP	2001175718	A 6/2001
JP	2001-229168	A 8/2001
JP	2001282831	A 10/2001
JP	2001290727	A 10/2001
JP	2002019928	A 1/2002
JP	2002028137	A 1/2002
JP	2002056156	A 2/2002
JP	2002162478	A 6/2002
JP	2002216021	A 8/2002
JP	2002251484	A 9/2002
JP	2002255465	A 9/2002
JP	2002255465	A 9/2002
JP	2002269335	A 9/2002
JP	2002303527	A 10/2002
JP	2002324075	A 11/2002
JP	2003099350	A 4/2003
JP	2003186900	A 7/2003
JP	2003187371	A 7/2003
JP	2003196284	A 7/2003
JP	2003208367	A 7/2003
JP	200245339	A 9/2003
JP	2003272078	A 9/2003
JP	2003280561	A 10/2003
JP	2003281694	A 10/2003
JP	2003281694	A 10/2003
JP	2003323528	A 11/2003
JP	2003323570	A 11/2003
JP	2003337874	A 11/2003
JP	2004505501	A 2/2004
JP	200427044	A 4/2004
JP	2004110496	A 4/2004
JP	2004511836	A 4/2004
JP	2004514333	A 5/2004
JP	2004157863	A 6/2004
JP	2004529543	A 9/2004
JP	2004282610	A 10/2004
JP	2004328308	A 11/2004
JP	2004334782	A 11/2004
JP	2004538558	A 12/2004
JP	2005073147	A 3/2005
JP	2005080208	A 3/2005
JP	2005094229	A 4/2005
JP	2005175896	A 6/2005
JP	2005184065	A 7/2005
JP	2005293255	A 10/2005
JP	2005-309489	A 11/2005
JP	2006011617	A 1/2006
JP	2006-48295	A 2/2006
JP	2006107136	A 4/2006
JP	2006113620	A 4/2006
JP	2006127144	A 5/2006
JP	2006198838	A 8/2006
JP	2006520497	A 9/2006
JP	2007-041642	A 2/2007
JP	2007-265449	A 10/2007
JP	2008305037	A 12/2008
JP	2009524150	A 6/2009
JP	2010530187	A 9/2010
JP	2011/242924	A 12/2011
KR	20010100635	A 11/2001
KR	20020090910	A 12/2002
KR	20030075238	A 9/2003
KR	20040010513	A 1/2004
KR	20050080370	A 8/2005
KR	20110012122	A 2/2011
KR	20140100173	A 8/2014
KR	20140100173	A 8/2014
TW	M445732	U 1/2013
WO	9607110	A1 3/1996
WO	9741654	A1 11/1997
WO	9802824	A1 1/1998
WO	9819479	A1 5/1998
WO	9923591	A1 5/1999
WO	1999057700	A1 11/1999

WO	0004730	A1 1/2000
WO	0004734	A1 1/2000
WO	0004737	A1 1/2000
WO	0013047	A1 3/2000
WO	0041104	7/2000
WO	200041104	A2 7/2000
WO	2001095140	A2 12/2001
WO	0209353	A2 1/2002
WO	200209353	A2 1/2002
WO	2002009353	A2 1/2002
WO	0221864	A1 3/2002
WO	0225964	A2 3/2002
WO	200225964	A2 3/2002
WO	2002025964	A2 3/2002
WO	WO 0221864	3/2002
WO	WO-02/28137	A1 4/2002
WO	02039217	5/2002
WO	200239217	A2 5/2002
WO	2002039732	A1 5/2002
WO	WO-02/39217	A2 5/2002
WO	0249310	A2 6/2002
WO	2002049310	A2 6/2002
WO	2003069576	A1 8/2003
WO	2004059996	A1 7/2004
WO	WO-2004/059996	A1 7/2004
WO	04070993	A2 8/2004
WO	2005040847	A2 5/2005
WO	06076460	A2 7/2006
WO	WO 2006/094086	A3 9/2006
WO	WO-2006094086	A2 9/2006
WO	WO-2006105088	A2 10/2006
WO	07084458	A2 7/2007
WO	WO-2008157334	A1 12/2008
WO	WO-2010/131629	A1 11/2010
WO	WO 2014/161078	A1 10/2014

## OTHER PUBLICATIONS

Maxima Advantage Call Center CRM Solutions, vol. 18, No. 7, Jan. 2000.

MobileCentrex.com Web Pages, Mobile Centrex, Mar. 2003, Retrieved from Archive.org Oct. 15, 2008.

Murray R. Barrick et al., "The Big Five Personality Dimensions and Job Performance: A Meta-Analysis"; *Personnel Psychology*; Spring 1991; vol. 44; No. 1, pp. 1-26.

Myers, "Personal Digital Radio Service," *IBM Technical Disclosure Bulletin*, Aug. 1995, pp. 315-316, vol. 38, No. 8, IBM Corporation, Armonk, New York, USA.

Author Unknown, "The Nexterna Clearview Dispatch Module," 2005, 2 pp., Nexterna Limited, Burlington, Ontario, Canada.

Author Unknown, "Dispenser Services Inc. Selects Web-Based Field Resource Management Solution From Nexterna," *PR Newswire*, Aug. 14, 2002, 2 pp., ProQuest LLC, New York, NY, USA.

Author Unknown, "Nexterna Announces Newest Release of Nexterna Clearview," *PR Newswire*, Sep. 26, 2002, 2 pp., ProQuest LLC, New York, NY, USA.

Author Unknown, "Nexterna.com Web Pages Nexterna Inc. 2002-2003," retrieved from Archive. Org on May 20 2009, 31 pp.

Author Unknown, "Nexterna Optitrac," Nexterna Inc. 2002-2003, retrieved from Archive.Org on May 20, 2009, pp. 32-38.

Bisio, et al., "Effective Resource Scheduling in Work Force Management Context for Telecommunication Work Centers," *Centro Studi E. Laboratori Telecomunicazioni Via G. Reiss Romoli*, 1999, pp. 1-5, vol. 274, Torino, Italy.

Boselly III, et al., "Road Weather Information Systems vol. 2: Implementation Guide," *Strategic Highway Research Program*, 1993, pp. 1-82, National Academy of Sciences, Washington, DC, USA.

Collins, et al., "Automated Assignment and Scheduling of Service Personnel," *AI in Corporate Service & Support*, Apr. 1994, pp. 33-39, *IEEE Expert*.

Author Unknown, "Computer-Assisted Dispatch," definition retrieved from Wikipedia.org on Oct. 15, 2008, 15 pp.

Author Unknown, "Dispatch (Logistics)," definition retrieved from Wikipedia.org on Oct. 15, 2008, 11 pp.

(56)

**References Cited**

## OTHER PUBLICATIONS

Feldman, et al., "Making Cell Phones Indispensable for Techs," Contractor, Jul. 2004, pp. 40 & 54, vol. 51, No. 7, ABI/INFORM Global.

Author Unknown, "iMedeon Announces Support for Microsoft Windows CE Devices for its Wireless Web-based Mobile Workforce Management Applications," Business Wire, Feb. 5, 2001.

Jing, et al., "WHAM: Supporting Mobile Workforce and Applications in Workflow Environments RIDE 2000," Research Issues in Data Engineering, Feb. 2000, 8 pp.

Kruse, "Snow and Ice Go Hi-Tech," Mobile Radio Technology Magazine, Oct. 1, 1999, pp. 1-4.

Lesaint, et al., "Dynamic Workforce Management," AI for Network: Management Systems, Apr. 14, 1997, pp. 1-5, IEE, London, UK.

Author Unknown, "TMC Labs Reviews—Maxima Advantage," Call Center CRM Solutions, Jan. 2000, 4 pp., vol. 18, No. 7, ABI/Inform Global.

Author Unknown, "MDSI Mobile Data Solution—Innovative and Effective Mobile Workforce Management," MDSI-Advantex.com, Feb. 1999, 19 pp.

Author Unknown, "MobileAria and WeatherBank Announce Partnership to Avert Delays, Increase Driver Productivity," Business Wire, Jun. 26, 2001, pp. 1-2, ProQuest LLC, New York, NY, USA.

Author Unknown, "Real-Time Wireless Workforce Solutions—MC Field Manager," Mobile Centrex Inc., retrieved from Archive.org on Oct. 15, 2008, 7 pp.

Author Unknown, "Real-Time Wireless Workforce Solutions—With Mobile Centrex You Can . . .," Mobile Centrex Inc., retrieved from Archive.org on Oct. 15, 2008, 5 pp.

Author Unknown, "Real-Time Wireless Workforce Solutions—Features That Work for You," Mobile Centrex Inc., retrieved from Archive.org on Oct. 15, 2008, 10 pp.

Partyka, et al., "On the Road to Service," ORMS Today, Aug. 2000, pp. 1-8, Lionheart Publishing, Inc., Marietta, GA, USA.

Rhinehart, "City Uses GIS to Monitor Snow-Fighting Fleet," The American City & County, Apr. 1999, p. 31, vol. 144, No. 4, ABI/Inform Global.

Timmins, "Mobile Workers Sync Up—PeopleSoft, Eduprise.com Team for KCVU," IT Support News, Dec. 1999, pp. 28 & 30, vol. 19, No. 13, ProQuest Computing.

Author Unknown, "Vantive and MDSI to Provide Enterprise Wide Wireless Field Service Solution," PR Newswire, Oct. 26, 1998, pp. 1-3, ProQuest LLC, New York, NY, USA.

Author Unknown, "Visual Staff Scheduler Pro Version 3.0 User Guide," 1997, pp. 1-152, Atlas Business Solutions, Inc.

Weigel, et al., "Applying GIS and OR Techniques to Solve Sears Technician-Dispatching and Home-Delivery Problems," Interfaces, Jan.-Feb. 1999, pp. 112-130, vol. 29, No. 1, Institute for Operations Research and Management Sciences.

Author Unknown, "iMedeon Announces Support for Microsoft Windows CE Devices for its Wireless, Web-Based Mobile Workforce Management Applications," Business Wire, Feb. 5, 2001, 2 pp., ProQuest LLC, New York, NY, USA.

Howard County Bureau of Highways, "Web-Enabled Snowplow Tracking System," Howard County, 1999, pp. 1-11.

Author Unknown, "Motorola iRadio(TM) System Hits the Road at Consumer Electronics Show 2001," PR Newswire, Jan. 4, 2001, pp. 1-2, ProQuest LLC, New York, NY, USA.

Le Comte, "Using Your Computer—Software Review," Weatherwise, Aug. 1991, pp. 48-51, vol. 44, No. 4.

Freedman, "Pinpoint Weather," Technology Review, Jun. 2003, pp. 52-58, vol. 106, No. 5, ABI/Inform Global.

Author Unknown, "Yahoo! and Weather.com Forge Multi-National Agreement to Provide Enhanced Weather Reports," Business Wire, Jan. 7, 2002, pp. 1-3, ProQuest LLC, New York, NY, USA.

Ohta, et al., "Real-World Community Platform: Mobile Multi-User Communication System," Multimedia Laboratories, NTT DoCoMo, Inc., 2000, pp. 601-606.

Lee, et al., "Statistical Analysis with Arcview GIS," 2001, pp. 1-192, John Wiley & Sons, Inc., New York, NY, USA.

Ohbuchi, et al., "Shape-Similarity Search of Three-Dimensional Models Using Parameterized Statistics," Oct. 9-11, 2002, in the Proceedings of the 10th Pacific Conference on Computer Graphics and Applications, pp. 265-274, IEEE.

Myers, "Personal Digital Radio Service," IBM Technical Bulletin, vol. 38, No. 8, p. 315, Aug. 1995.

Oh et al., "A Model for Role Administration Using Organization Structure", SACMAT '02, Jun. 3-4, 2002, pp. 155-162.

Botha, R.A. et al., "Separation of duties for access control enforcement in workflow environments", IBM Systems Journal, vol. 40, No. 3, 2001, pp. 666-682.

What is Access Management?, 2AB Inc., Jan. 2004, 6 pages.

Harris, Shon, Mike Myer's Certification Passport CISSP, McGraw-Hill, 2002, ISBN 0-07-222578-5, Chapter 2, 54 pages.

Park, Joon S. et al., "Role-Based Access Control on the Web", ACM Transactions on Information and System Security, vol. 4, No. 1, Feb. 2001, pp. 37-71.

McCormick, Vickie L., "Using HR Information systems for HIPAA role-based access compliance", Journal of Health Care Compliance, vol. 5, No. 2, Mar./Apr. 2003, pp. 31-32.

Langford, Jeff, "Implementing Least Privilege at your Enterprise", SANS Institute, Jul. 5, 2003, 21 pages.

Cuppens, Frederick et al., "Modeling Contexts in the Or-BAC Model", ACSAC'03, 2003, pp. 1-10.

Principles of Least Privilege definition, Wikipedia.org, Reprinted Jul. 11, 2012, 5 pages.

Sakagumi et al., "ActiveTrace: Mobile Marketing Platform for Location and Behavior-Dependent Information Distribution and Analysis," Collection of Papers/Multimedia, Distribution, Collaboration and Mobile (DICOMO) Symposium, Jun. 27, 2001, vol. 2001, Abstract No. 7, pp. 501-506.

International Search Report for PCT/US2016/053456 dated Jan. 5, 2017.


International Search Report for PCT/US2016/066198 dated Mar. 9, 2017.

International Search Report PCT/US2017/012155, dated Apr. 30, 2017.


International Patentability Report and Written Opinion issued for PCT/US2015/067694 dated Jun. 27, 2017.

Mcnamee, Ethical Issues Arising From the Real Time Tracking and Monitoring of People Using GPS-Based Location Services.


\* cited by examiner








**FIG. 2**





1

**METHOD OF OUTPUTTING  
WEATHER/ENVIRONMENTAL  
INFORMATION FROM  
WEATHER/ENVIRONMENTAL SENSORS**

CROSS-REFERENCE TO RELATED  
APPLICATIONS

The present application is a Continuation of U.S. patent application Ser. No. 11/035,654, filed Jan. 14, 2005, the disclosure of which is hereby incorporated by reference in its entirety.

STATEMENT REGARDING FEDERALLY  
SPONSORED RESEARCH OR DEVELOPMENT

Not applicable.

BACKGROUND OF THE INVENTION

During recent years, the demand for detailed information, such as for example weather information, has risen sharply. Personal computers and communication devices have increased the demand for more information because of their power to gather, manipulate, transmit and receive data. As a result, specialized information and value-added services are in great demand. End users no longer desire to gather, manipulate and evaluate raw data. For instance, nowhere is this condition more apparent than with weather services across North America.

Years ago, radio and television broadcasters recognized an increasing demand for weather information from their audience, and thus increased the number of on-air weather segments as a means for increasing market ranking. Today, the demand for specific content in weather information has exceeded the ability of broadcasters to meet this demand. Virtually every facet of business and personal activities are continually influenced by the weather, good or bad.

In the United States as in most countries, a governmental agency (the National Weather Service in the United States), has the primary responsibility of generating weather products for the general public. These products, such as advisories, statements, and forecasts are generated and made available to third parties, such as broadcasters, newspapers, internet web sites, paging companies and others who, in turn, distribute them to the public. However, this chain of data custody is one way.

Today's lifestyles are fast-paced and sophisticated. Requests for detailed weather information for specific applications outnumber the governments' ability to process them. However, adhering to their mandated responsibility, the National Weather Service generates the general products for public consumption twice daily. This condition forces the public to interpret general and outdated advisories to meet their needs. Often, this interpretation is made erroneously. Even worse, these products are usually regional or national in scope, and may not apply to a particular location where various local activities are underway.

By way of example, weather warnings are broadcast by radio stations across the United States. These warnings identify certain weather impacts within a specified area. In most cases, the warning area includes one or more counties, covering dozens to hundreds of square miles. Most often, these threats (such as severe thunderstorms, tornadoes, etc.), only impact a very small zone within the warning area. These threats also move rapidly. As impacts approach specific zones, they are in fact, moving away from other zones,

2

inside the total warning area. Essentially, the existing reporting system is insufficient to specifically identify and adequately warn of personal risk. Furthermore, if the threat is imminent, the existing system cannot and does not provide preventive measures for each user near or at the threat. Thus, by default, distant or unaffected users are placed "on alert" unnecessarily when the threat may be moving away from their location.

Another common example further clarifies the problem. A family, excited to attend the championship softball game this upcoming weekend, closely monitors the local weather forecast. All week-long the forecast has advised fair to partly cloudy weather for game day. Early on game day, the forecast changes to partly cloudy, with a thirty percent chance for late afternoon showers. The family decides to attend the game, believing that the chances for rain are below their perceived risk level. Unknown to the family at midday, some clusters of showers are intensifying, and will place dangerous lightning over the game field. While the morning weather report was not completely inaccurate, the participants and spectators are exposed to risk. If later asked, it is likely the family members did not hear or remember the weather forecast. They also failed to link their limited knowledge of the weather to their own needs and risk exposure. They did not monitor changing weather events. Most likely, they had no ability to monitor developing risk at the game. Clearly, these people were forced to interpret outdated, limited information as applied to their specific application.

Therefore, a need exists for a system to automatically and continuously provide consumer customized reports, advisories, alerts, forecasts and warnings relevant to a consumer-defined level of need or dynamic spatial location. It is to such a system that the present invention is directed.

SUMMARY OF THE INVENTION

The present invention provides an interactive advisory system and method of delivering individualized information. More specifically, the present invention relates to a broadcast network for selectively transmitting individualized output signals to remote communicator devices. The broadcast network includes a user input database, a communicator location database, an analysis unit and a communication network.

The user input database contains user-defined parameters and each of the user-defined parameters desirably includes a spatial range identifier and a user profile. The user profile in each of the user-defined parameters at least identifies a communicator device associated with a particular user. The communicator location database contains real-time data indicative of the spatial locations of the communicator devices. In one preferred version of the present invention, the communicator location database is automatically and/or continuously updated by the communicator devices.

The information database contains data, such as real-time weather data for at least the spatial locations contained in the communicator location database. The term "data" describes a wide variety of products including, but not limited to, past and current conditions of weather events, textual products, graphic products, and the like. The analysis unit receives the real-time data from the information database, and automatically and continuously compares the spatial range identifier included in the user-defined parameters and the spatial locations of the corresponding communicator devices contained in the communicator location database with the real-time data and, upon demand of the user, or even

continuously, generates an individualized output signal such as weather information within the spatial range identified by the spatial range identifier for the user-defined parameters. As new locations are defined by the communicator location database, the information database is automatically updated in real-time.

The communication network transmits each individualized output signal to the particular communicator device defined in the user profile included in the user-defined parameter corresponding with the real-time data and prediction of events. Thus, a user can receive information in real-time specific to the user's immediate spatial location regardless of whether or not the user's location remains fixed or dynamic throughout time.

Other advantages and features of the present invention will become apparent to those skilled in the art when the following detailed description is read in view of the attached drawings and appended claims.

#### BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

FIG. 1 is a block diagram of an interactive weather advisory system constructed in accordance with the present invention.

FIG. 2 is a coordinate system illustrating a spatial location identifier and a spatial range identifier utilized by versions of the present invention.

FIG. 3 is a block diagram of an interactive advisory system constructed in accordance with the present invention.

FIG. 4 is a block diagram of an interactive weather advisory system constructed in accordance with the present invention.

#### DETAILED DESCRIPTION OF THE INVENTION

Referring now to the drawings and more particularly to FIG. 1 shown therein in block diagram form, is one embodiment of the invention in the form of an interactive weather advisory system constructed in accordance with the present invention. The weather advisory system 8 is provided with a broadcast network 10 for selectively transmitting individualized weather output signals to remote communicator devices 11. The broadcast network 10 includes a weather analysis unit 12, a user input database 14, a communicator location database 16, and a communication network 20. The weather analysis unit 12 receives real-time weather data from a weather information database 21. The weather information database 21 can be located at the broadcast network 10, or remotely from the broadcast network 10. The weather analysis unit 12, the user input database 14, the communicator location database 16, the weather information database 21, and the communication network 20, interrelate and communicate via signal paths 22, 24, 26, 28, 30 and 32.

The user input database 14 permits a plurality of users to input data corresponding to the weather reports, advisories or forecasts such that individualized weather reports, advisories or prediction of events can be transmitted to each individual user. The user input database 14 contains data representative of at least one user-defined parameter correlated to each one of a plurality of users. In one version of the present invention, each of the user-defined parameters includes various information related to weather output signals, such as a spatial range identifier, a user profile, one or more weather content identifiers for identifying particular weather patterns, one or more time identifiers for identifying

particular times or time intervals that a user may desire a weather product, a spatial location fixed or dynamic code, and a spatial location identifier for identifying particular spatial locations of interest to the user if the spatial location fixed or dynamic code indicates that the spatial location is to be fixed. The user profile in each of the user-defined parameters includes at least a user identifier code for identifying a particular communicator device 11 associated with a particular user.

For instance, the user identifier code could be a mobile telephone number identifying one of the communicator devices 11, which in this instance could be a mobile telephone or a pager, for example. The weather content identifier could be a computer code to identify one or a variety of weather conditions or events such as tornadoes, thunderstorms, hail storms, lightning storms, showers, snow storms, blizzards, high winds, winds aloft, rapidly rising or rapidly falling barometric pressure or other such weather patterns or conditions. The time identifier desirably could be a computer code for identifying the particular time, times, or time intervals the user desires the interactive weather advisory system 8 to communicate weather data to the user or to monitor the real-time weather data for a particular time and/or date. The spatial location identifier 26 could be a computer code identifying a particular predetermined spatial location such as, by way of example but not limitation, a longitude and latitude anywhere in the world, a town, a county, a township, address, zip code, altitude and combinations thereof.

As discussed above, the spatial location identifier identifies a particular spatial location anywhere in the world and/or altitude above sea level. The spatial range identifier identifies a particular spatial range surrounding the spatial location identifier. Each of the users can select the spatial location identifier and the spatial range identifier so as to receive weather forecasts and/or weather advisories or any other weather information for the spatial location identified by the spatial location identifier, and within the spatial range identified by the spatial range identifier.

For example, referring to FIG. 2, shown therein is a coordinate system illustrating four spatial location identifiers and four spatial range identifiers selected by different users of the present invention. That is, one of the users selects the spatial location identifier (X1, Y1, Z1), and the spatial range identifier (R1). Another one of the users selects the spatial location identifier (X2, Y2, Z2), and the spatial range identifier (R2).

The user who selected the spatial location identifier (X1, Y1, Z1) and the spatial range identifier R1 will receive weather products and advisories concerning the spatial range identified by the spatial location identifier (X1, Y1, Z1) and the spatial range identifier R1, as predefined in his user input database. The user who selected the spatial location identifier (X2, Y2, Z2) and the spatial range identifier R2 will receive weather products and advisories concerning the spatial range identified by the spatial location identifier (X2, Y2, Z2) and the spatial range identifier R2, and as predefined in the user input database 14. Likewise, the users who selected the spatial location identifiers (X3, Y3, Z3) and (X4, Y4, Z4) and the spatial range identifiers R3 and R4 will receive weather products and advisories concerning the spatial range identified by the spatial location identifiers (X3, Y3, Z3), (X4, Y4, Z4) and the spatial range identifier R3, R4, and as predefined in the user input database 14.

The magnitudes of the spatial range identifiers R1, R2, R3 and R4 can be different or the same. In addition, the

## 5

magnitudes of the spatial range identifiers R1, R2, R3 and R4 can vary widely and are desirably selected by the users.

Particular users can input the user-defined parameters into the user input database 14 via any suitable method. For example, the user input database 14 is desirably configured to acquire its data from a variety of optional sources preferably chosen by the user, such as verbally through a telephone customer service network, a mobile phone network equipped with wireless application protocol technology, email, a personal digital assistant, a laptop computer, or an interactive web site. Furthermore, users could mail the user-defined parameters to the broadcast network 10, and an individual at the broadcast network 10 could input the user-defined parameters directly into the user input database 14 via a keyboard or other similar input device. In one embodiment, the user inputs the selected information into the user input database 14 via the user's communicator device 11.

The weather information database 21 contains real-time weather data for at least the spatial locations contained in the communicator location database 16 and the spatial locations identified by the spatial location identifier in the user input database 14. The weather analysis unit 12 generates predictions of all weather events based on the real-time weather data. The weather information database 21 desirably receives its real-time weather data from at least one of a plurality of possible resources such as, by way of example but not limitation, government weather information resources, privately operated weather information resources, and other various meteorological resources. The real-time weather data could also be either input directly at the physical location of the weather information database 21 or input via a mobile phone network, a mobile phone network with wireless application protocol, the Internet, aircraft communication systems, email, a personal digital assistant, a laptop computer, regular computer, or other wireless devices.

The communicator location database 16 is an optional feature of the present invention, and is enabled via the signal path 22 when the user requests real-time weather advisories or prediction of events at the dynamic spatial location of the user's communicator device 11. The communicator location database 16 is continuously updated such that the communicator location database 16 contains real-time data indicative of the spatial locations of the communicator devices 11. In one embodiment, the user identifier code in the user's profile is transmitted to the communicator location database 16 via the signal path 22. The communicator location database 16 desirably receives data from the communicator devices 11 identified by the user identifier codes via at least one of a variety of possible resources such as a mobile phone network, a mobile phone network equipped with the wireless application protocol technology, global positioning satellite technology, the Internet, loran technology, radar technology, transponder technology or any other type of technology capable of tracking the spatial location of a communicator device 11 and communicating the location of such communicator device 11 to the communicator location database 16 of the broadcast network 10. Preferably, the communicator location database 16 is continuously and automatically updated as to the location of each of the communicator devices 11, such as by the wireless application protocol technology.

The communication network 20 can be, by way of example but not limitation, a mobile phone network, a mobile phone network with wireless application protocol technology, the Internet, a facsimile network, a satellite

## 6

network (one or two-way), a RF radio network, or any other means of transmitting information from a source to an end user.

The communicator devices 11 can be bidirectional or unidirectional communicator devices. The communicator devices 11 can be, by way of example but not limitation, a portable device, such as a mobile telephone, a smart phone, a pager, a laptop computer or a personal digital assistant, or any other electronic device capable of receiving weather information data. Furthermore, the communicator device 11 can be incorporated into an object that is utilized or accessible by the user, such as a helmet, an automobile, or an airplane, for example. While only three communicator devices 11 are represented in FIG. 1 for purposes of illustration, the interactive weather advisory system 8 contemplates the utilization of a large number of communicator devices 11.

The weather analysis unit 12 receives the data in the user input database 14, the communicator location database 16, and the weather information database 21 from the signal paths 24, 26, and 28. The weather analysis unit 12 can be, by way of example but not limitation, a computer desirably programmed to automatically and continuously compare the data in the user input database 14, communicator location database 16, and weather information database 21 so as to generate an individualized weather output signal including weather information within the spatial range identified by the spatial range identifier for each user-defined parameter in the user input database 14. The weather output signals are transmitted to the communication network 20 via the signal path 32.

The weather analysis unit 12 gathers the real-time weather data from the weather information database 21. The term "real-time weather data", as used herein, refers to weather data which is continually updated so as to indicate current or near current information. In some instances, the "real-time weather data" may be delayed by relatively small increments of five minutes, 15 minutes, or 30 minutes, for example. In other instances, the "real-time weather data" can be provided with substantially no delay. It is expected that the increments will become smaller as communication networks and weather related technology become faster.

The weather analysis unit 12 generates predictions of all weather related events and compares past and current events contained in the weather information database 21 (such as future position, strength, trajectory, etc.), to construct a four-dimensional database. Three dimensions of the database define a physical location on or above the earth's surface (the spatial location identifier (X1, Y1, Z1)). The fourth dimension is time—past, present or future (identified as T1, T2, T3, T4). By employing high speed computer processors in real-time, the weather analysis unit 12 compares all events (past, current and predicted), at specific positions (X1, Y1, Z1, T1) with identical user supplied data (the user input database—X1, Y1, Z1, R1, T1), and identifies any matches (weather output signals) to the user through the communication network 20 and communication devices 11.

The communication network 20 receives the weather output signals and the user identification codes via the signal paths 32 and 30. In response thereto, the communication network 20 transmits the individualized weather output signals to the communicator devices 11 associated with the user identification codes via the signal paths 34a, 34b and 34c, such that each user receives the individualized weather information that was requested.

The signal paths 34a, 34b and 34c refer to any suitable communication link which permits electronic communica-

tions. For example, the signal paths **34a**, **34b** and **34c** can be point-to-point shared and dedicated communications, infra red links, microwave links, telephone links, CATV links, satellite and radio links and fiber optic links.

Various combinations of weather information can be incorporated into the user input database **14** so as to provide the user with selected and specific weather information. For example, a user traveling in his automobile may wish to be informed by the interactive weather advisory system **8** concerning all hailstorms for an area within a 2.5 mile radius of his vehicle as he is traveling from his point of origin to his destination. The user, for example, through his smart phone (communicator device **11**) in his vehicle working in conjunction with a mobile phone network (communication network **20**) with wireless application protocol, inputs selected information into the user input database **14**; namely, the user's smart phone number (user identifier code), hail (weather content identifier), 2.5 mile radius (spatial range identifier **24**) and spatial location dynamic (spatial location of the user's smart phone is then automatically and continuously monitored), and the like.

The interactive weather advisory system **8** then monitors weather information and predictions of events in the weather analysis unit **12**, and transmits the individualized weather output signal to the user's smart phone if a hailstorm is detected or is highly likely to form within a 2.5 mile radius of the vehicle along the vehicle's path of travel, for the duration of travel.

The individualized weather output signal can be an audio and/or video data signal. For example, the individualized weather output signal can be a .WAV file or other suitable file containing an animated representation of a real or hypothetical individual speaking an individualized message to the user. In the example given above, the individualized message may be that the hailstorm is 2.5 miles ahead of the vehicle and thus, the user should consider stopping for a short period of time so as to avoid the hailstorm. Alternatively, the individualized message may be that the hailstorm is 2.5 miles ahead of the vehicle and thus, the user should consider stopping until further notified by another individualized weather output signal so as to avoid the hailstorm. In other words, the weather analysis unit **12** may transmit another individualized weather output signal to the user via the communication network **20** and the communicator devices **11** notifying the user that the weather condition identified by the weather content identifier has passed or is beyond the spatial location identified by the spatial range identifier.

As another example, a user may desire to be informed of all real-time weather data and predictions of events within a particular spatial range of a particular dynamic spatial location. For instance, the user may be interested in whether his aircraft is at risk of icing as he flies from Oklahoma City to Tulsa, Okla. To provide a suitable level of comfort and safety, the user may wish to be informed of icing conditions within 10 miles of the dynamic spatial location of his aircraft. The user, for example, through his smart phone or other suitable avionic device (communicator device **11**) in his aircraft working in conjunction with a mobile phone network (communication network **20**) with wireless application protocol, inputs selected information into the user input database **14**; namely, the user's smart phone number (user identifier code), icing (weather content identifier), 10 mile radius (spatial range identifier **24**), and the spatial location dynamic. The spatial location of the user's smart phone or other suitable avionic device is then automatically and continuously monitored as the aircraft traverses through

time and space from (X1, Y1, Z1, T1) to (X4, Y4, Z4, T4). The interactive weather analysis unit **12** then monitors the real-time weather data in the weather information database **21** and the predicted events in the weather analysis unit **12** so as to transmit the individualized weather output signal to the user's smart phone or other avionic device identifying, if icing is detected or is highly likely to form relevant to a 10 mile radius of the aircraft.

As yet another example, perhaps the user is only interested in a particular weather pattern at a particular fixed spatial location and within a particular spatial range irrespective of the immediate location of the communicator device **11**. To accomplish this user's request, the broadcast network **10** does not utilize the communicator location database **16**. The user inputs selected information into the user input database **14**, namely the user's phone number (user identifier code), the code for the particular weather pattern in which the user is interested (weather content identifier), the spatial range around the spatial location in which the user is interested (spatial range identifier), and the spatial location in which the user is interested (spatial location identifier). The weather analysis unit **12** then monitors the real-time weather data in the weather information database **21** and the predicted events in the weather analysis unit **12** so as to transmit the individualized weather information concerning the weather pattern in the spatial location and range requested by the user.

As a further example, perhaps the user is only interested in a particular weather condition at the spatial location and within a particular spatial range at a particular time. The user inputs selected information into the user input database **14**, namely, the user's phone number (user identifier code), the code for the particular weather pattern in which the user is interested (weather content identifier), the spatial range around the spatial location in which the user is interested (spatial range identifier and the spatial location in which the user is interested spatial location identifier) and the time and date (time identifier) that the user wishes to be informed of the weather conditions at the spatial location of interest. In response thereto, the weather analysis unit **12** monitors the real time weather data from the weather information database **21** for the spatial location and range identified by the spatial range identifier and spatial location identifier to determine the probability of the particular weather pattern occurring at the time identified by the time identifier. The weather analysis unit **12** sends, via the signal path **32**, the individualized weather output signal to the communication network **20**. The communication network **20** receives the user identifier code, via signal path **30**, from the user input database **14** and transmits the weather output signal received from the weather analysis unit **12** to the particular communicator device **11** identified by the user identifier code. Thus, the user receives the individualized weather information concerning the spatial location, spatial range and time requested by the user.

The signal paths **22**, **24**, **26**, **28**, **30** and **32** can be logical and/or physical links between various software and/or hardware utilized to implement the present invention. It should be understood that each of the signal paths **22**, **24**, **26**, **28**, **30** and **32** are shown and described separately herein for the sole purpose of clearly illustrating the information and logic being communicated between the individual components of the present invention. In operation, the signal paths may not be separate signal paths but may be a single signal path. In addition, the various information does not necessarily have to flow between the components of the present invention in the manner shown in FIG. 1. For example, although FIG. 1

illustrates the user identifier code being transmitted directly from the user input database 14 to the communication network 20 via the signal path 30, the user identifier code can be communicated to the weather analysis unit 12 via the signal path 24 and then communicated to the communication network 20 via the signal path 32.

It should be understood that although the user has been described as manually inputting the user identifier code into the user input database 14, the user identifier code could be automatically input into the user input database 14 by the communicator device 11.

Once the user-defined parameters have been input into the user input database 14, the user-defined parameters can be analyzed by the weather analysis unit 12 along with weather content identifiers for purposes of targeted marketing. A plurality of vendors 36 can be provided access to the weather analysis unit 12 of the broadcast network 10 via a plurality of signal paths 38a, 38b, and 38c. The vendors 36 can independently input search information into the weather analysis unit 12 for compiling a data set of information which is useful to the vendors 36.

For example, a particular vendor 36a, who is in the business of selling snow blowers, may input a weather content identifier and time identifier into the weather analysis unit 12 so as to request a list of all spatial locations in the United States which are expected to receive at least 10 inches of snow in the next week. The weather analysis unit 12 would then compile the data set of all spatial locations in the United States which is expected to receive at least 10 inches of snow in the next week based on at least one weather content identifier, the time identifier, and the real-time weather data stored in the weather information database 21. The data set is then output to the vendor 36a. Based on the data set, the vendor 36a may send advertisements or additional snow blowers to the areas identified in the data set.

As another example, the particular vendor 36a, who is in the business of selling snow blowers, may input a weather content identifier and time identifier into the weather analysis unit 12 so as to request a list of all user profiles identifying users who resided in spatial locations in the United States which are expected to receive at least 10 inches of snow in the next week. The weather analysis unit 12 would then compile the data set of all spatial locations in United States which is expected to receive at least 10 inches of snow in the next week based on at least one weather content identifier, the time identifier, the user profiles, and the real-time weather data stored in the weather information database 21. The data set is then output to the vendor 36a. Based on the data set, the vendor 36a may send advertisements to the users who are identified in the data set.

It is envisioned that users will subscribe to the services provided by the broadcast network 10. In this regard, the broadcast network 10 may or may not charge a service fee to the users. In addition, some services may be provided by the broadcast network 10 for one charge and additional services may be provided at an enhanced charge.

To save processing power, the weather analysis unit 12 may periodically determine which communicator devices 11 are turned off or out of range. Once this has been determined, the weather analysis unit 12 would then not generate any individualized weather output signals for the communicator devices 11 which are turned off or out of range. Once a particular one of the communicator devices 11 is turned on or comes within range, the weather analysis unit 12 would then attempt to generate individualized weather output signals for such communicator devices 11. In other words, to

save processing power the weather analysis unit 12 may only generate individualized weather output signals for the communicator devices 11 which are active and within range.

The weather analysis unit 12 can be located at the broadcast network 10. Alternatively, the weather analysis unit 12 can be separate from the remainder of the broadcast network 10 and provided as a service to the broadcast network 10.

In one preferred embodiment, rather than or in addition to the user providing user-defined parameters to the user input database 14, the user input database 14 is programmed to provide a plurality of pre-defined user profiles with each of the pre-defined user profiles directed to an activity designated by the user optionally including data and time of the activity. The activity can be a business, personal or recreational need. For example, the business need can be any work dependent upon or impacted by weather conditions to carry out a desired activity, such as, but not limited to a rancher, contractor, farmer, or painter. The personal need can be any activity positively or negatively impacted by weather conditions, such as but not limited to, duties performed by a homeowner, such as mowing the lawn, painting the house, trimming trees, or the like. The recreational need can be any recreational or other outdoor activity dependent upon weather conditions, such as but not limited to golfing, cycling, boating, hiking, fishing, or snow skiing.

In this case, the user selects or provides an activity or category to the user input database 14. The user input database 14 retrieves pre-defined information concerning such activity or category and stores or links such pre-defined information with the user's user profile. The broadcast network 10 and/or weather analysis unit 12 then functions as set forth above to provide weather alerts or other information concerning the information contained in the user's user profile.

For example, a user may plan on golfing on a particular weekend during the hours of 9:00 a.m. to 4:00 p.m. In this case, the user would select the pre-defined user profile for "golfing", and the time frame of such planned activity. The location of planned activity can also be entered into the user input database 14, or the location of the communicator device 11 can be monitored by the communicator location database 16. The information contained in the pre-defined user profile is input into the user input database 14 and output weather alerts and forecasts are then generated as discussed above.

The pre-defined user profiles are determined by member (s) of the broadcast network 10 and/or weather analysis unit 12, who identify weather conditions which are typically suitable and/or adverse to each designated activity. Thus, for example, a pre-defined user profile for "golfing" will contain data such as wind conditions, lightning, rain, temperature and other conditions which will positively or negatively impact a golfing activity. The data in the pre-defined user profile can be determined either before or after selection of the activity by the user.

If desired by the user, the broadcast network 10 and/or weather analysis unit 12 can assume the responsibility for generating the appropriate size of the spatial range identifier (as in the case with the user profile, or pre-defined user profile). Alternatively, the spatial range identifier can be determined by the nature of the weather event. In the latter case, member(s) of the broadcast network 10 and/or weather analysis unit 12 would determine an "area of concern" around each weather event that would or could occur and the communication network 20 would then send notifications to



## 11

any user or communicator device **11** that may come into contact with the area of concern.

For example, a tornado may be ½ mile wide and the broadcast network **10** and/or weather analysis unit **12** would, based upon its experience, knowledge and/or abilities, determine that the area of concern would be 1½ miles wide and 8 miles long—moving northeasterly. Any user contained within the user input database **14** would be notified, as discussed above, if the user's location comes into contact with the "area of concern".

#### Other Uses of this System

Shown in FIGS. **3-4**, are advisory systems **8a** and **8b** which can be used for delivering other types of information or for more accurately predicting weather related events. The advisory systems **8a** and **8b** are similar in construction and function to the weather advisory system **8**, except as described below. For purposes of clarity, similar components have been provided with the same numeric prefix, and different alphabetic suffix.

The advisory system **8a** is provided with a broadcast network **10a**. In one embodiment, the broadcast network **10a** is used for transmitting individualized real-time work assignments from, for example, an employer to an employee. The broadcast network **10a** is provided with an analysis unit **12a**, a communicator location database **16a**, and communicator devices **11a** and **11b**. The communicator device **11a** is referred to herein as an "employer communicator device", and the communicator device **11b** is referred to herein as an "employee communicator device." The communicator location database **16a** is continuously updated to contain real-time data indicative of the spatial locations of the communicator devices **11a** and **11b**. In a similar manner as described above, the analysis unit **12a** makes comparisons between user profiles (as represented by a box **80a**), dynamic locations stored in the communicator location database **16a**, fixed locations as represented by a box **82a** and job assignments entered into the analysis unit **12a** from one of the employer communicator devices **11a**. The system **8a** may be further described as an employer system **40a** and an employee system **42a** to delineate the types of information being conveyed within the system **8a**.

For example, an employer uses the employer communicator device **11a** to input employee information and/or criteria into an employee's user profile such as, for example, job location, job schedule, skill set requirements, personality traits, and other criteria as represented by a box **84a**. Further, the employer inputs work or job assignment criteria into the analysis unit **12a** such as, for example, job location, job schedule, skill set requirements, personality traits, and other criteria. The employer inputs the above criteria into one of the employer communicator devices **11a** which may be, for example, a computer, a personal digital assistant (PDA), a cellular phone, a combination cellular phone/PDA, or any other device which may then transmit the employee information and/or job assignment criteria to the analysis unit **12a**. The analysis unit **12a** may be, for example, a computer or a web server. The analysis unit **12a** matches the employee user profile criteria with the work assignment criteria to generate a data set of at least one individualized work assignment.

The individualized real-time work assignment is transmitted to one of the employee communicator devices **11b** based upon the matching of the work assignment criteria with the employee user-profile. The data set can be transmitted to the employer communicator device **11a** such that the employer can review the data set to assign the work assignment to a particular one of the employees, or alterna-

## 12

tively, the analysis unit **12a** can automatically assign the work assignment to a particular one of the employees and thereby transmit the work assignment to the employee's communicator device **11b** without any intervention by the employer. The employee's communicator device **11b** may be, for example, a PDA, a cellular phone, a combination cellular phone/PDA, a pager, or any other device in which the analysis unit **12a** or the employer may communicate information to the employee.

The user profile for each of the employees includes information relating to the employee's traits such as, for example, personality, sales style, dress, skill set, location, schedule, or any other quality or trait relating to the particular employee. Further, the user profile is preferably accessible by both the employer communicator device **11a** and the employee communicator device **11b**. However, it is preferred that the employer communicator device **11a** have access to the entire user profile, while the employee communicator device **11b** only have access to a subset of the user profile. Thus, the user profile accessible by the employer system **40a** may differ from the user profile accessible by the employee system **42a**.

For example, the user profile accessible by the employer system **40a** may include traits related to a particular employee that remain hidden or unknown to the employee. For instance, the employee may have access to information stored in his user profile such as location, schedule, skill set, and other criteria as represented by a box **86a** and may be provided access to his user-profile to update information as needed. In addition to the above-mentioned employee-accessible information, the employer may have access to the employee user profile to input and access employee traits such as personality, sales style, dress, and skill set and may be provided access to update this information as needed.

In another embodiment, the system **8a** is used to deliver goods based upon real-time location of a carrier of the goods. More specifically, the system **8a** can be used to accommodate purchasers of products ordered online in order to quickly and efficiently deliver goods to the purchaser's specified location.

The analysis unit **12a** is loaded with employee user profiles and locations. The analysis unit **12a** identifies delivery persons (employees) located near a purchaser's location. Part of the employee's user profile can include an inventory of the goods on the employee's delivery truck. The employee need not know what inventory is located on his delivery truck, but only his delivery destination.

For example, a purchaser may order fresh produce online. The employer may input the purchaser's order (work assignment) into the employer communicator device **11a** (which inputs the work assignment into the analysis unit **12a**) so that the analysis unit **12a** may determine which delivery person may efficiently deliver the specified goods to the purchaser. Also, by ordering online, the purchaser may send his order directly to the analysis unit **12a** such that the analysis unit **12a** automatically determines the appropriate delivery person to deliver goods to the purchaser and sends the assignment to the delivery person via the employee's communicator device **11b**. Further, the employer updates the user profile to track and monitor the precise inventory located on the employee's delivery truck, the inventory being delivered, and any inventory that may be stolen from the delivery truck.

In yet another embodiment, the system **8a** can be used for sending salesmen to the field for soliciting new clients. For example, a company may receive an inquiry from a sales lead. Information about the lead is entered into the analysis

unit **12a** as a job assignment from the employer communicator device **11a**. The analysis unit **12a** then determines the appropriate salesman to send to the lead based on information stored in the salesman's user-profile. The salesman's user-profile may include information such as salesman location, personality traits, dress style or other attributes used to determine which salesman may be appropriate to send to the lead.

Shown in FIG. 4 is another advisory system **8b** constructed in accordance with the present invention. The advisory system **8b** includes a broadcast network **10b**. The broadcast network **10b** is similar in construction and function as the broadcast network **10** discussed above, except that the broadcast network **10b** includes individualized sensor networks **48a** having weather and environmental sensors **48b** which are specifically associated with geographic areas associated with predetermined users.

For example, the weather and environmental data collection sites are tremendously sparse in growing areas of the world. In the state of Iowa, only a minimal number of National Weather Service data collection points exist. The scarcity of weather data hinders farmers because a dense grid of weather data points is non-existent in order for farmers to make critical decisions about their crops. For example, how do you know what 160-acre tract of land to fertilize when soil temperature data, crop moisture data, and chance of precipitation data is unavailable?

The sensor network **48a** includes temporary or permanent data collection sensors **48b** which may be installed, for example, on a 10 acre to 40 acre grid on the land of a subscriber or user of the system **8b**. Each sensor **48b** may have a unique spatial range associated with it such as, for example, a five mile or twenty mile radius. The spatial range associated with each sensor **48b** can be selected by the user and specified as a result of the sensor **48b** type and purpose as well as the density of the sensor network **48a**. For example, if the user is interested in soil moisture in order to schedule a fertilizer treatment, the spatial range associated with the chosen sensor **48b** may be set, for example, at 375 feet. In another example, the user may be interested in soil temperature for placing seeds in the ground and the desired spatial range associated with the chosen sensor **48b** may be, for example, 2,000 feet. The user of the system **8b** includes a user profile as discussed above, which is supplemented with information regarding the sensors **48b** associated with the user, e.g., installed on or near the user's land. The sensors **48b** transmit site-specific, individualized information to the weather analysis unit **12b** so that more detailed information can be used by the weather analysis unit **12b** in generating the site-specific weather information for the user.

The sensors **48b** can be any type of sensor which generates information usable for forecasting weather, transmitting current weather conditions, transmitting current environmental conditions, and/or forecasting environmental conditions. For example, the sensors **48b** can be used to sample or record such parameters as, but not limited to, air temperature, humidity, precipitation, solar radiation, wind speed and direction, soil temperature, soil moisture, and/or chemical constituents in the soil.

For example, a user may enter into his user profile types of information the user would like the sensor network **48a** to monitor such as, for example, temperature, moisture and/or soil conditions. The weather analysis unit **12b** receives the sensor data from the sensor network **48a** and transmits information to the user via the user's communicator device **50b** based on information entered into his user profile. The

user may also choose a specific sensor for monitoring a specific area at any given time by modifying his user profile.

Further, the system **8b** may be used to transmit real-time road condition information to the weather analysis unit **12b** to enhance the weather information transmitted to the users of the system **8b**. Although the sensors **48b** can include their own power source such as a battery or solar power source, the sensors **48b** are preferably positioned on a device which has its own electrical power source. For example, a temporary or permanent sensor or sensors **48b** may be placed in various locations along a roadway such as on a vehicle, on or beside the roadway, on a billboard, gas pump, cell phone tower or sign alongside the roadway or railway, on a delivery vehicle(s) such as, for example, UPS and/or FedEx, or on the streetlights. If the sensor **48b** is placed on the roadway, it may be placed in the concrete or asphalt. If placed beside the roadway, the sensor **48b** may be placed in, for example, a ditch. The sensor(s) **48b** may detect, for example, moisture, temperature or any other weather or environmental condition associated with the roadway, sign alongside the roadway, on streetlights, or on delivery vehicles such as, for example, UPS and/or FedEx, or on railway cars. Alternatively, the sensor(s) **48b** may be used to detect traffic conditions or any other condition associated with a particular roadway or railway.

For example, each sensor **48b** may be placed 100 feet away from the nearest sensor in order to create the sensor network **48a** for determining conditions for a specified area along a roadway or railway. Further, the sensor(s) **48b** may be placed on various cellular phone towers so that users of a particular cellular phone system associated with the tower may access various conditions using the system **8b**.

Each of the weather sensors **48a** can also include a system such as a GPS system for determining the current location of such weather sensor so that the current location of the weather sensor is transmitted to the weather analysis unit **12b**.

One skilled in the art will recognize many uses of the system **8b**. For example, when sensor data is collected by sensors **48a** positioned on moving vehicles along roadways or railways, the weather analysis unit **12b** can transmit such weather information to communicator devices **11b** located in close proximity to where the sensor data is being collected. Thus, assuming that a Federal Express truck is located 5 miles from a subscriber, the information collected from the sensor on the Federal Express truck can be transmitted to the subscriber.

From the above description, it is clear that the present invention is well adapted to carry out the objects and to attain the advantages mentioned herein as well as those inherent in the invention. While presently preferred embodiments of the invention have been described for purposes of this disclosure, it will be readily understood that numerous changes may be made which will readily suggest themselves to those skilled in the art and which are accomplished within the spirit of the invention disclosed.

What is claimed is:

1. A method of outputting weather or environmental condition information to a user, the method comprising:
  - a. storing user profiles associated with users in a user profile database, the user profiles including a user identifier code for identifying a communicator device associated with a user;
  - b. receiving, by a weather analysis unit, weather or environmental condition information from weather and environmental sensors;

## 15

receiving real-time data indicative of a spatial location of the communicator device;  
 storing the real-time data indicative of the spatial location of the communicator device in a communicator location database;  
 5 determining whether the communicator device is located in close proximity to a location of one or more of the weather and environmental sensors by:  
 determining a unique spatial range of each of the one or more weather and environmental sensors; and  
 determining whether the communicator device is within the unique spatial range of the one or more weather and environmental sensors; and  
 10 outputting the weather or environmental condition information received from the one or more weather and environmental sensors in close proximity to the communicator device to a communication network for transmittal to the communicator device in response to a determination that the communicator device is in close proximity to the one or more weather and environmental sensors.  
 15  
 2. The method of claim 1, wherein the unique spatial range is determined based on a type of the weather or environmental condition information to be monitored by the one or more weather and environmental sensors.  
 25  
 3. The method of claim 1, wherein the unique spatial range is determined based on a sensor type of the one or more weather and environmental sensors.  
 4. The method of claim 1, wherein the unique spatial range is determined based on a distance between the one or more weather and environmental sensors.  
 5. The method of claim 1, wherein the weather and environmental sensors are approximately equidistant.  
 6. The method of claim 1, wherein one or more of the weather and environmental sensors is mounted on a billboard, a gas pump, a tower for cell phone communication, or a structure supporting a light.  
 7. The method of claim 1, wherein one or more of the weather and environmental sensors is mounted on a vehicle.  
 8. The method of claim 1, wherein one or more of the weather and environmental sensors is mounted on a billboard.  
 9. The method of claim 1, wherein one or more of the weather and environmental sensors is mounted on a gas pump at a gas station.  
 10. The method of claim 1, wherein one or more of the weather and environmental sensors is mounted on a tower for cell phone communication.  
 11. A method of outputting environmental condition information to a user, the method comprising:

## 16

storing user profiles associated with users in a user profile database, the user profiles including a user identifier code for identifying a communicator device associated with a user;  
 5 receiving environmental condition information from environmental sensors;  
 receiving real-time data indicative of a spatial location of the communicator device;  
 storing the real-time data indicative of the spatial location of the communicator device in a communicator location database  
 10 determining whether the communicator device is located in close proximity to a location of one or more of the environmental sensors by:  
 determining a unique spatial range of each of the one or more environmental sensors; and  
 determining whether the communicator device is within the unique spatial range of the one or more environmental sensors; and  
 15 outputting the environmental condition information received from the one or more environmental sensors in close proximity to the communicator device to a communication network for transmittal to the communicator device in response to a determination that the communicator device is in close proximity to the one or more environmental sensors.  
 20  
 12. The method of claim 11, wherein the unique spatial range is determined based on a type of the environmental condition information to be monitored by the one or more environmental sensors.  
 13. The method of claim 11, wherein the unique spatial range is determined based on a sensor type of the one or more environmental sensors.  
 14. The method of claim 11, wherein the unique spatial range is determined based on a distance between the one or more environmental sensors.  
 15. The method of claim 11, wherein the environmental sensors are approximately equidistant.  
 16. The method of claim 11, wherein one or more of the environmental sensors is mounted on a billboard, a gas pump, a tower for cell phone communication, or a structure supporting a light.  
 17. The method of claim 11, wherein one or more of the environmental sensors is mounted on a vehicle.  
 18. The method of claim 11, wherein one or more of the environmental sensors is mounted on a billboard.  
 19. The method of claim 11, wherein one or more of the environmental sensors is mounted on a gas pump at a gas station.  
 20. The method of claim 11, wherein one or more of the environmental sensors is mounted on a tower for cell phone communication.  
 50

\* \* \* \* \*