



US011150432B2

(12) **United States Patent**  
**Faulkner et al.**

(10) **Patent No.:** **US 11,150,432 B2**  
(45) **Date of Patent:** **Oct. 19, 2021**

(54) **HIGH FIBER COUNT PRE-TERMINATED OPTICAL DISTRIBUTION ASSEMBLY**

(71) Applicant: **CORNING RESEARCH & DEVELOPMENT CORPORATION**,  
Corning, NY (US)

(72) Inventors: **Michael Todd Faulkner**, Granite Falls,  
NC (US); **Lars Kristian Nielsen**,  
Hickory, NC (US)

(73) Assignee: **CORNING RESEARCH & DEVELOPMENT CORPORATION**,  
Corning, NY (US)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/896,389**

(22) Filed: **Jun. 9, 2020**

(65) **Prior Publication Data**  
US 2020/0301091 A1 Sep. 24, 2020

**Related U.S. Application Data**  
(62) Division of application No. 16/011,938, filed on Jun.  
19, 2018, now Pat. No. 10,712,519.  
(Continued)

(51) **Int. Cl.**  
**G02B 6/44** (2006.01)  
**G02B 6/38** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **G02B 6/4476** (2013.01); **G02B 6/3873**  
(2013.01); **G02B 6/3889** (2013.01); **G02B**  
**6/4472** (2013.01); **G02B 6/4477** (2013.01)

(58) **Field of Classification Search**  
CPC .. **G02B 6/4476**; **G02B 6/3873**; **G02B 6/3889**;  
**G02B 6/4472**; **G02B 6/4477**  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,547,194 A \* 10/1985 Moorehead ..... A61M 25/0014  
285/24  
5,210,810 A 5/1993 Darden et al.  
(Continued)

FOREIGN PATENT DOCUMENTS

WO 2016/086881 A1 6/2016

OTHER PUBLICATIONS

International Search Report and Written Opinion of the Interna-  
tional Searching Authority; PCT/US2018/038426; dated Nov. 5,  
2018; 9 Pages; European Patent Office.  
(Continued)


*Primary Examiner* — Peter Radkowski

(74) *Attorney, Agent, or Firm* — William D. Doyle

(57) **ABSTRACT**

Embodiments of a furcated optical fiber cable are provided. A main distribution cable has optical fibers surrounded by a cable jacket. The optical fibers are divided into at least two furcation legs. A furcation plug is located at a transition point between the main distribution cable and the at least two furcation legs. The furcation plug surrounds at least a portion of the main distribution cable and each of the at least two furcation legs. Optical connectors are provided for each of the at least two furcation legs, and each connector includes optical fibers that are spliced at a splice location to the optical fibers of the connector's respective furcation leg. The splice location is closer to the connector than to the furcation plug. A method of furcating an optical fiber cable and a pulling configuration for the furcated optical fiber cable are also provided.

**8 Claims, 6 Drawing Sheets**



**Related U.S. Application Data**

(60) Provisional application No. 62/525,970, filed on Jun. 28, 2017.

**References Cited**

U.S. PATENT DOCUMENTS

5,231,688 A 7/1993 Zimmer  
 5,768,460 A 6/1998 Levi et al.  
 5,903,693 A 5/1999 Brown  
 5,966,489 A 10/1999 Harwell et al.  
 5,970,195 A 10/1999 Brown  
 6,278,831 B1 8/2001 Henderson et al.  
 6,389,214 B1 5/2002 Smith et al.  
 6,438,299 B1 8/2002 Brown et al.  
 6,738,555 B1 5/2004 Cooke et al.  
 7,270,485 B1 9/2007 Robinson et al.  
 7,280,725 B2 10/2007 Brown et al.  
 7,302,152 B2 11/2007 Luther et al.  
 7,349,605 B2 3/2008 Noonan et al.  
 7,409,127 B1 8/2008 Hurley et al.  
 7,415,181 B2\* 8/2008 Greenwood ..... G02B 6/4404  
 385/100  
 7,463,803 B2 12/2008 Cody et al.  
 8,410,909 B2 4/2013 De Jong  
 8,737,786 B1\* 5/2014 Compton ..... G02B 6/4472  
 385/100  
 9,052,459 B2\* 6/2015 Compton ..... G02B 6/2558  
 9,176,295 B2 11/2015 Sakabe et al.  
 9,235,021 B2 1/2016 Islam  
 9,535,230 B2 1/2017 Newbury et al.  
 9,618,718 B2 4/2017 Islam  
 10,012,802 B2 7/2018 Newbury et al.  
 2003/0210875 A1 11/2003 Wagner et al.  
 2005/0002621 A1\* 1/2005 Zimmel ..... G02B 6/4476  
 385/100  
 2005/0053341 A1 3/2005 Zimmel  
 2005/0276551 A1 12/2005 Brown et al.  
 2006/0120672 A1 6/2006 Cody et al.  
 2006/0147172 A1 7/2006 Luther et al.  
 2006/0233506 A1 10/2006 Noonan et al.  
 2007/0025668 A1\* 2/2007 Greenwood ..... G02B 6/4494  
 385/103  
 2007/0110384 A1 5/2007 Cody et al.  
 2008/0013888 A1\* 1/2008 Barnes ..... G02B 6/3887  
 385/53

2008/0019646 A1\* 1/2008 deJong ..... G02B 6/2558  
 385/99  
 2008/0138026 A1\* 6/2008 Yow ..... G02B 6/4471  
 385/137  
 2008/0253729 A1\* 10/2008 Gronvall ..... G02B 6/4472  
 385/137  
 2009/0060431 A1\* 3/2009 Lu ..... G02B 6/4475  
 385/114  
 2009/0060440 A1 3/2009 Wright et al.  
 2009/0074364 A1 3/2009 Bringuier et al.  
 2009/0103881 A1 4/2009 Gonzalez et al.  
 2009/0162019 A1\* 6/2009 Lichoulas ..... G02B 6/3846  
 385/99  
 2010/0098386 A1\* 4/2010 Kleeberger ..... G02B 6/4472  
 385/100  
 2011/0280525 A1\* 11/2011 Marcouiller ..... G02B 6/2558  
 385/99  
 2011/0317968 A1\* 12/2011 Cline ..... G02B 6/4471  
 385/111  
 2012/0007717 A1 1/2012 Jong  
 2012/0106906 A1 5/2012 Sakabe et al.  
 2012/0170899 A1\* 7/2012 Homma ..... G02B 6/2558  
 385/99  
 2012/0308184 A1 12/2012 Pina et al.  
 2013/0251319 A1\* 9/2013 Compton ..... G02B 6/4495  
 385/99  
 2013/0294733 A1 11/2013 Wright et al.  
 2014/0140662 A1 5/2014 McDonald et al.  
 2015/0160075 A1\* 6/2015 Taverner ..... G02B 6/125  
 374/161  
 2015/0260936 A1 9/2015 Newbury et al.  
 2016/0041354 A1 2/2016 Guenter et al.  
 2016/0327763 A1 11/2016 Hurley et al.  
 2017/0102506 A1 4/2017 Newbury et al.  
 2018/0024294 A1 1/2018 Wang et al.

OTHER PUBLICATIONS

Invitation to Pay Additional Fees of the International Searching Authority; PCT/US2018/038426; dated Aug. 27, 2018; 2 Pages; European Patent Office.  
 European Patent Application No. 18824386.9, Partial Supplementary European Search Report dated Mar. 3, 2021; 13 pages; European Patent Office.

\* cited by examiner




FIG. 1




FIG. 2









FIG. 3








FIG. 9




FIG. 10




FIG. 11




FIG. 12



## HIGH FIBER COUNT PRE-TERMINATED OPTICAL DISTRIBUTION ASSEMBLY

### PRIORITY APPLICATION

This application is a divisional of U.S. application Ser. No. 16/011,938, filed Jun. 19, 2018, which claims the benefit of U.S. Provisional Application No. 62/525,970, filed on Jun. 28, 2017, the content of which is relied upon and incorporated herein by reference in its entirety.

### BACKGROUND

The disclosure relates generally to optical cables and more particularly to a furcated optical fiber cable. A main optical cable line can include many branch lines that divert a portion of the optical fibers of the main optical cable to end users. Some main optical cable lines are manufactured with branch lines located in predetermined locations in order to avoid having a technician splice on branch lines in the field, which typically is costly, time-consuming, and less accurate than can be accomplished in the manufacturing facility. In branching the optical fibers, vulnerabilities tend to be created in the protective jacket of the main optical cable line at the location of the branch, for example as a result of the opening in the cable jacket created to access the fibers to create the branch. These vulnerabilities are potential sources of mechanical and environmental damage to the underlying optical fibers.

### SUMMARY

In one aspect, embodiments of an optical fiber cable are provided. The optical fiber cable includes a main distribution cable having a plurality of optical fibers surrounded by a cable jacket. Further the optical fiber cable includes at least two furcation legs into which the plurality of optical fibers are divided. The at least two furcation legs transition from the main distribution cable, and each of the at least two furcation legs extends from the distribution cable along a longitudinal axis. The optical fiber cable further includes a furcation plug located at a transition point between the main distribution cable and the at least two furcation legs. The furcation plug surrounds at least a portion of the main distribution cable and each of the at least two furcation legs. Also included in the optical fiber cable is an optical connector for each of the at least two furcation legs. Each connector includes optical fibers that are spliced at a splice location to the optical fibers of the connector's respective furcation leg. Moreover, for each of the at least two furcation legs, the splice location is closer to the connector than to the furcation plug as measured in a direction along the longitudinal axis of each furcation leg.

In another aspect, embodiments of a method of furcating an optical fiber cable are provided. The method includes a step of dividing a plurality of optical fibers from a main distribution cable into at least two furcation legs. Also, a jacket of each of the at least two furcation legs is slid towards the main distribution cable so as to expose at least a three-inch portion of the optical fibers in each of the at least two furcation legs. Further, optical fibers of a connector are spliced to the exposed portion of the optical fibers of each furcation leg. The jacket of each furcation leg is then slid toward the connector, and a furcation plug is placed at a location where the main distribution cable is divided into the at least two furcation legs. Finally, the exposed portion of the optical fibers of each furcation leg is covered.

In still another aspect, embodiments of a pulling configuration for a furcated optical fiber cable are provided. The pulling configuration includes a main distribution cable including a plurality of optical fibers surrounded by a cable jacket and at least two furcation legs into which the plurality of optical fibers are divided. The at least two furcation legs transition from the main distribution cable. Further, a furcation plug is located at a transition point between the main distribution cable and the at least two furcation legs. The furcation plug surrounds at least a portion of the main distribution cable and each of the at least two furcation legs. A pulling ring encircles the main distribution cable and is located on a side of the furcation plug opposite the furcation legs. A pulling mesh surrounds the at least two furcation legs, and a pulling loop is formed at an end of the pulling mesh. The pulling loop is mechanically linked to the main distribution cable via the pulling ring such that pulling forces on the pulling loop are primarily borne by the main distribution cable.

Additional features and advantages will be set forth in the detailed description that follows, and in part will be readily apparent to those skilled in the art from the description or recognized by practicing the embodiments as described in the written description and claims hereof, as well as the appended drawings.

It is to be understood that both the foregoing general description and the following detailed description are merely exemplary, and are intended to provide an overview or framework to understand the nature and character of the claims.

### BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings are included to provide a further understanding and are incorporated in and constitute a part of this specification. The drawings illustrate one or more embodiment(s), and together with the description serve to explain principles and the operation of the various embodiments.

FIG. 1 depicts a furcated optical fiber cable, according to an exemplary embodiment.

FIG. 2 depicts a cross-sectional view of the main distribution cable portion of the furcated optical fiber cable, according to an exemplary embodiment.

FIG. 3 depicts an optical fiber ribbon usable in a furcated optical fiber cable, according to an exemplary embodiment.

FIG. 4 is a detailed view of a furcation location showing a distribution cable ribbon being split into two furcation legs in an initial step of a furcation method, according to an exemplary embodiment.

FIG. 5 is a detailed view showing sliding of a furcation leg jacket forward after a splice has been made, according to an exemplary embodiment.

FIG. 6 is a detailed view of the furcation legs and main distribution cable after the furcation jackets have been slid forward to meet the connectors, according to an exemplary embodiment.

FIG. 7 is a detailed view of a furcation leg after a heat shrink wrap has been applied around the splice and exposed optical fiber ribbons, according to an exemplary embodiment.

FIG. 8 is a detailed view of the furcation plug being sealed to the main distribution cable and the furcation legs, according to an exemplary embodiment.

FIG. 9 is a detailed view of an overmold applied around the heat shrink wrap of a furcation leg, according to an exemplary embodiment.

3

FIG. 10 depicts a first configuration for pulling a furcated optical fiber cable through ductwork, according to an exemplary embodiment.

FIG. 11 depicts a second configuration for pulling a furcated optical fiber cable through ductwork, according to an exemplary embodiment.

FIG. 12 depicts a third configuration for pulling a furcated optical fiber cable through ductwork, according to an exemplary embodiment.

#### DETAILED DESCRIPTION

Referring generally to the figures, various embodiments of a furcated optical fiber cable are depicted. In particular, the furcated optical fiber cable includes two or more furcation legs that are spliced near to the connector instead of near to the location of the furcation. In particular, each furcation leg includes a slidable jacket that can be moved to provide enough room for fusion splicing of the optical fiber or fibers to the optical fiber or fibers of the connector. The slidable jacket creates two sections of exposed fiber in which a first section is covered with a furcation plug and a second section is covered with an overmold and/or heat shrink wrap. Furcating and splicing the cable in this way lowers the overall profile of the cable. Indeed, as compared to previous furcated optical fiber cables, the presently disclosed optical fiber cable advantageously allows for smaller sections of cable disruption resulting from furcation. Additionally, the presently disclosed optical fiber cable is able to provide staggered connectors to facilitate pulling the cable in standard two inch ducts. Further, the presently disclosed optical fiber cable utilizes a short, rigid furcation plug that provides superior anchoring for high strength pulling grips. These and other advantages will be discussed below with reference to non-limiting, exemplary embodiments. Other modifications may become apparent to one of ordinary skill in the art upon consideration of the present disclosure, and such modifications are considered to be within the scope of the present disclosure.

With initial reference to FIG. 1, an embodiment of a furcated optical fiber cable 10 is depicted. As can be seen, the furcated optical fiber cable 10 has a main distribution cable 12 from which four furcation legs 14 extend. While four furcation legs 14 are shown for illustrative purposes, in other embodiments, the main distribution cable 12 can be furcated into, e.g., from two to twelve or more furcation legs 14. The furcation of the furcation legs 14 from the main distribution cable 12 is facilitated by a furcation plug 16. The furcation plug 16 stabilizes and protects the location of furcation such that the interior of the main distribution cable 12 is not exposed to environmental hazards. As is also depicted in FIG. 1, the furcation legs 14 have different lengths such that each leg is customized in length to cover the particular distance to the installation point. Generally, the furcation legs 14 are from three to six feet in length; however, in certain embodiments, the furcation legs are up to eighteen or twenty feet in length. In a particular embodiment, a furcated optical fiber cable 10 contains twelve furcation legs 14 that are staggered in length from three to six feet, e.g., each furcation leg 14 is three inches shorter than the successive furcation leg 14. The ability to stagger the length of the furcation legs 14 decreases the overall profile of the furcated optical fiber cable 10, which as will be discussed more fully below has advantages for pulling the cable 10 through ductwork.

Also, advantageously, each furcation leg 14 is connectorized, i.e., each furcation leg 14 is pre-terminated with a

4

connector 18. In embodiments, the connectors 18 are a multi-fiber, mechanical transfer (“MT”) connector, such as the OptiTip® MT connector (available from Corning Incorporated, Corning, N.Y.). As will be discussed more fully below, the connectors 18 are spliced to the furcation leg 14 near the end of the furcation leg 14, and the splices are protected, in part, with an overmold 20. The connectors 18 allow the furcation legs 14 to be plugged into multiport terminals, splitters, etc. without requiring in-field termination and connectorization.

In order to facilitate discussion of the furcation process, the components of the main distribution cable 12 are discussed herein and depicted in FIG. 2. In FIG. 2, the main distribution cable 12 is depicted as an optical fiber ribbon cable; however, in other embodiments, the main distribution cable 12 is a loose tube cable. In particular, the main distribution cable 12 is depicted as an elongated or racetrack profile cross-section cable, such as RPX® Gel-Free Ribbon Cable (available from Corning Incorporated, Corning, N.Y.). The main distribution cable 12 includes an outer cable jacket, shown as outer cable jacket 22. As will be generally understood, the interior of the cable jacket 22 defines an internal region within which the various cable components discussed herein are located.

In various embodiments, cable jacket 22 is formed from an extruded thermoplastic material. In various embodiments, cable jacket 22 may be a variety of materials used in cable manufacturing such as polyethylene, medium density polyethylene, polyvinyl chloride (PVC), polyvinylidene difluoride (PVDF), nylon, polyester or polycarbonate and their copolymers. In addition, the material of cable jacket 22 may include small quantities of other materials or fillers that provide different properties to the material of cable jacket 22. For example, the material of cable jacket 22 may include materials that provide for coloring, UV/light blocking (e.g., carbon black), burn resistance/flame retardance, etc.

Contained within main distribution cable 12 is a stack 24 of optical fiber ribbons 26. Each ribbon 26 includes multiple optical transmission elements or optical waveguides, shown as optical fibers 28. As shown in FIG. 2, main distribution cable 12 includes a single stack 24 of optical fiber ribbons 26. In various embodiments, main distribution cable 12 includes at least two ribbons 26 within stack 24, and each ribbon 26 supports from four to twenty-four optical fibers 28. In the particular embodiment depicted in FIG. 2, the stack 24 contains three ribbons 26 with twenty-four optical fibers 28 in each optical fiber ribbon 26. However, in other embodiments, a different number of ribbons 26, including more or less than shown in FIG. 2, may be provided in the main distribution cable 12. Additionally, in other embodiments, a different number of optical fibers 28, including more or less than shown in FIG. 2, may be provided within each ribbon 26. Still further, in other embodiments, multiple stacks 24, each included, e.g., in separate buffer tubes, are contained in the main distribution cable 12.

In the embodiment shown, multiple strength members 32 are embedded in cable jacket 22 to provide structure and protection to the optical fibers 28 during and after installation (e.g., protection during handling, protection from the elements, protection from the environment, protection from vermin, etc.). In various embodiments, main distribution cable 12 includes two strength members 32 that are arranged on opposite sides of the main distribution cable 12. Each strength member 32 may be any suitable axial strength member, such as a glass-reinforced plastic rod, steel rod/wire, etc. Main distribution cable 12 may include a variety of other components or layers, such as a metal armor layer,

helically wrapped binders, circumferential constrictive thin-film binders, water blocking tape materials, water-blocking fiber materials, etc. In particular, in the embodiment shown, main distribution cable **12** includes water swellable tape **34** above and below the stack **24** of optical fiber ribbons **26**. Still further, the main distribution cable **12** can include one or more preferential tear feature and/or ripcord embedded in or underneath cable jacket **22**.

FIG. **3** depicts the construction of an exemplary embodiment of an optical fiber ribbon **26** such as might be carried in the main distribution cable **12** (shown in FIGS. **1** and **2**). As can be seen, the optical fiber ribbon **26** includes a plurality of optical fibers **28**. In the embodiment depicted, there are twelve optical fibers **28**. Each optical fiber **28** includes a glass core and cladding region **36** along which optical signals propagate. In particular, the core is surrounded by the cladding so as to substantially keep the optical signals within the core during transmission. The core and cladding region **36** is surrounded by a primary coating **38** and a secondary coating **40**. The dual layer coating, i.e., primary coating **38** and secondary coating **40**, provide enhanced protection for the core and cladding region **36** against microbending-induced attenuation. In embodiments, each optical fiber **28** in the optical fiber ribbon **26** has a different color ink layer applied to the secondary coating **40** such that the optical fibers **28** can be discerned from each other during installation, splicing, repair, etc.

A polymeric matrix **42** holds the optical fibers **28** together in a parallel arrangement within the optical fiber ribbon **26**. Surrounding the polymeric matrix **42** is an outer coating **44**. In embodiments, ribbon identification information is printed on to polymeric matrix **42**, and the outer coating **44** helps to preserve the printing from smudging, rubbing off, abrasion, etc.

Having described the main distribution cable **12** and its components, the process for furcating the optical fiber cable **10** will now be discussed with reference to FIG. **4**. For clarity and ease of illustration, two furcation legs **14** are shown in the embodiment of FIG. **4**; however, the process depicted is equally applicable to furcated optical fiber cables **10** having more than two furcation legs **14**. Initially, the cable jacket **22** is stripped from the main distribution cable **12**, revealing the optical fiber ribbons **26**. Further, the optical fiber ribbons **26** are able to be further divided into furcation legs. For example, the optical fiber ribbons **26** depicted in FIG. **2** contain twenty-four optical fibers **28**. In embodiments and as shown in FIG. **4**, during furcation, each twenty-four fiber optical fiber ribbon **26** (“large optical fiber ribbon **26**”) is divided into two twelve fiber ribbons **45** (“small optical fiber ribbons **45**”) for each furcation leg **14**.

During the step of stripping the cable jacket **22**, sections of the strength members **32** of the main distribution cable are left exposed as well, which as will be discussed more fully below help to support the furcation location. In embodiments, three to five inches of the strength members **32** are left exposed after the initial stripping step.

After stripping the main distribution cable **12**, a furcation leg jacket **46** is then pushed over each of the exposed small optical fiber ribbons **45**. As can be seen in FIG. **4**, the furcation leg jacket **46** also includes strength members **48**, which are in part exposed so as to support the splice region. The furcation leg jacket **46** is of a length so that between one half and two inches of the small optical fiber ribbons **45** remain exposed at the end of the furcation leg **14** by the main distribution cable **12**. Additionally, between three and five

inches of the small optical fiber ribbons **45** remain exposed for performing the splice to the connectors **18** as shown in FIG. **5**.

The splice to the connectors **18** is performed via mass fusion splicing. More specifically, the connectors **18** have their own optical fiber ribbon **47** extending from a crimp body **49** of the connector **18**. The optical fiber ribbon **47** of the connectors **18** are spliced to the small optical fiber ribbons **45** of the furcation legs **14**. In order to perform this splice, the individual optical fibers **28** are exposed by stripping the primary coating **38**, secondary coating **40**, polymeric matrix **42**, and outer coating **44** from the optical fibers **28** (as shown in FIG. **3**). As shown on a single furcation leg **14** in FIG. **5**, the optical fibers **28** (also stripped) of the connectors **18** are then fused to the optical fibers **28** of the furcation leg **14** to form a splice **51** using a mass fusion splicer. Generally, mass fusion splicers feature precision cleaving, aligning, and positioning tools such that the ends of the optical fibers **28** are able to be brought into close proximity and fused together using, e.g., an electric arc, laser, gas flame, etc., to produce connections having losses of less than 0.03 dB. In embodiments, the splice **51** is located near to the connectors **18**. That is, when the furcation leg **14** is unfurled or laid out along its longitudinal axis, the splice **51** is located closer to the connectors **18** than to the furcation plug **16** (as shown, e.g., in FIG. **8**). In a particular embodiment, each furcation leg **14** is spliced within ten inches of a downstream end of its respective connector **18**. In a more particular embodiment, each furcation leg **14** is spliced within five inches of the downstream end of its respective connector **18**.

Immediately after the splicing is performed, a splice protection tube or sleeve may be slid over the splice region of the optical fibers **28**. The splice protection tube is made of an inner tube and a strength member contained inside a heat shrink wrap. Once the inner tube is placed over the splice region, the heat shrink wrap is heated to seal the inner tube and strength member in place. In this way, the spliced optical fiber ribbon **26** is able to be safely handled with a substantially reduced risk of damage to the optical fibers **28**.

Once the splice protection tube is in place, the furcation leg jacket **46** is pushed forward (as illustrated by the arrows in FIG. **5**) toward the connector **18** until the strength members **48** contact the end of the connector **18** as shown in FIG. **6**. More specifically, the strength members **48** are inserted into the crimp body **49** of the connector **18**. In embodiments and as shown in FIG. **7**, a heat shrink wrap **50** is placed around the splice region, including the strength members **48**, and heat shrunk into place as an initial layer of environmental protection for the splice region. In embodiments, superabsorbent polymer powder and/or water swellable yarn are contained inside the heat shrink wrap **50** to prevent water from reaching the connector **18**.

Next, the furcation plug **16** is molded, formed, or otherwise placed around the location of furcation as shown in FIG. **8**. In an embodiment, the furcation plug **16** is an aluminum tube with a heat shrink wrap. In such embodiments, the aluminum tube furcation plug **16** is sealed with a sealant **52**, such as a polyurethane, epoxy, urethane, or other hardenable resin (e.g., LOCTI 3360, available from Henkel Corporation). In another embodiment, the furcation plug **16** is a rigid, molded resin. In FIG. **8**, the furcation plug **16** is placed around the exposed portion of the optical fiber ribbons **26** near the main distribution cable **12** (the exposed portion being larger as a result of the sliding forward of the furcation leg jacket **46**) and around the strength members **32** of the main distribution cable **12**. As mentioned above, the

strength members 32 provide structure and protection for main distribution cable 12 at the location of the furcation plug 16.

In the embodiment shown in FIG. 9, the furcation legs 14 are also provided with the overmold 20 to further protect the splice region. Thus, the overmold 20 is located from directly behind the connectors 18 to from three to five inches or more behind the location of the splice. In embodiments, the overmold 20 is a polyurethane composition capable of protecting the splice region from mechanical stresses and enhancing the environmental resistance of the furcated optical fiber cable 10.

Advantageously, embodiments of the presently disclosed furcated optical fiber cable 10 enable outdoor operation and can be used with fiber counts up to or exceeding 144 fibers. In particular, the furcated optical fiber cable 10 is constructed of outdoor rated materials that, e.g., include mildewcides and are capable of withstanding extreme cold (e.g., as low as  $-40^{\circ}$  C.) and extreme hot temperatures (e.g., up to  $80^{\circ}$  C.). Another advantage of the furcated optical fiber cable 10 is that the splice regions near the connectors 18 maintain flexibility, which aids in the installation process. Additionally, because the furcated optical fiber cable 10 utilizes a short, rigid furcation plug 16 at the location of furcation, use of a pulling grip that can withstand forces greater than the cable installation rating of around 600 pounds is possible.

In particular, FIGS. 10-12 depict embodiments of how the furcated optical fiber cable 10 can be configured for pulling through a duct using a pulling attachment 58. In the embodiment shown in FIG. 10, a pulling ring 56 encircles the main distribution cable 12. A high-tensile strength mesh fabric, or pulling mesh 60, is attached to the pulling ring 56 and surrounds the furcation legs 14 and furcation plug 16. At the opposite end, the pulling mesh 60 is knotted into a pulling loop 62. Advantageously, the furcated optical fiber cable 10 is able to be used with such existing pulling attachments 58. Such pulling attachments 58 are able to easily be put together and removed in the field without any special tools.

Referring now to FIG. 11, the main distribution cable 12 is stripped along a section and the optical fiber ribbons 26 are exposed. The furcation legs 14 are spliced to the exposed optical fiber ribbons 26 in the stripped section, and a protective sleeve 65 is positioned around the splice region. After the stripped section, the main distribution cable 12 continues for the purposes of installation, and as part of the installation, the end section of the main distribution cable 12 is removed. In particular, the central strength member or members 32 of the main distribution cable 12 are used to pull the furcated optical fiber cable 10 through ductwork.

In furtherance of this goal, the end section of the main distribution cable 12 and the exposed optical fiber ribbons 26 are contained in a corrugated protective tube 64. A heat shrink wrap 66 is then applied over at least a part of the protective sleeve 65 and over at least part of the corrugated protective tube 64. A second heat shrink wrap 66 is placed over at least a part of the other end of the protective sleeve 65 and at least a part of the main distribution cable 12. An overmold 20 is then applied over both heat shrink wraps 66, over the protective sleeve 65, and over at least a portion of the corrugated protective tube 64. A pulling grip 70 is attached to the end of the main distribution cable 12 or the corrugated protective tube 64. In an embodiment, the pulling grip 70 is a wire mesh sleeve that constricts around the main distribution cable 12 when a tensile force is applied.

Using the embodiment depicted in FIG. 11, the main distribution cable 12 is able to be pulled through an installation ductwork with commonly known cable pulling grips

and methods. Additionally, the installer is able to use the installer's own pulling grip for installation. Also, the strength member or members 32 of the main distribution cable 12 carry the load of the cable per currently performed processes.

Referring now to FIG. 12, another embodiment is provided in which the furcation legs 14 are contained in a corrugated protective tube 64, similar to the previous embodiment. Also like the previous embodiment, a section of the main distribution cable 12 is stripped to expose the optical fiber ribbons 26 for splicing within a protective sleeve 65. Further, the protective sleeve 65 and the corrugated protective tube 64 are covered with a heat shrink wrap 66 and an overmold 20. However, unlike the previous embodiment, the main distribution cable 12 ends at the stripped section such that the central strength member 32 does not continue forward. In order to provide a mechanical link to the main distribution cable 12, a pulling plug 72, such as an epoxy plug, is provided behind the overmold 20, and a pulling wire 68, such as mule tape, connects the pulling ring 56 to the pulling loop 62, which in embodiments is a knot formed from the pulling wire 68. Advantageously, this embodiment provides a slimmer overall design for pulling through ductwork.

Unless otherwise expressly stated, it is in no way intended that any method set forth herein be construed as requiring that its steps be performed in a specific order. Accordingly, where a method claim does not actually recite an order to be followed by its steps or it is not otherwise specifically stated in the claims or descriptions that the steps are to be limited to a specific order, it is in no way intended that any particular order be inferred. In addition, as used herein, the article "a" is intended to include one or more than one component or element, and is not intended to be construed as meaning only one.

It will be apparent to those skilled in the art that various modifications and variations can be made without departing from the spirit or scope of the disclosed embodiments. Since modifications, combinations, sub-combinations and variations of the disclosed embodiments incorporating the spirit and substance of the embodiments may occur to persons skilled in the art, the disclosed embodiments should be construed to include everything within the scope of the appended claims and their equivalents.

What is claimed is:

1. A method of furcating an optical fiber cable, comprising the steps of:

- dividing a plurality of optical fibers from a main distribution cable into at least two furcation legs;
- pushing a furcation jacket over each of the at least two furcation legs;
- sliding the furcation jacket of each of the at least two furcation legs towards the main distribution cable so as to expose at least a three-inch portion of the optical fibers in each of the at least two furcation legs;
- splicing optical fibers of a connector to the exposed portion of the optical fibers of each furcation leg;
- sliding the furcation jacket of each furcation leg toward the connector;
- placing a furcation plug at a location where the main distribution cable is divided into the at least two furcation legs; and
- covering the exposed portion of the optical fibers of each furcation leg.

2. The method of claim 1, wherein the furcation jacket of each of the at least two furcation legs comprises one or more strength members and wherein the step of sliding the fur-

9

cation jacket of each furcation leg toward the connector further comprises sliding the furcation jacket of each furcation leg toward the connector until the one or more strength members contacts the connector.

3. The method of claim 1, wherein the step of covering the exposed portion of the optical fibers of each furcation leg further comprises covering the exposed portion of the optical fibers of each furcation leg with a heat shrink wrap.

4. The method of claim 1, wherein the step of covering the exposed portion of the optical fibers of each furcation leg further comprises covering the exposed portion of the optical fibers of each furcation leg with an overmold.

5. The method of claim 1, wherein the step of splicing a connector to the exposed portion of the optical fibers of each furcation leg is performed at a location that is nearer to the connector of each furcation leg than to the furcation plug.

6. The method of claim 1, wherein the step of dividing a plurality of optical fibers from a main distribution cable into at least two furcation legs further comprises dividing from 72 to 144 optical fibers from the main distribution cable into the at least two furcation legs.

7. The method of claim 1, further comprising the step of: sealing the furcation plug to the main distribution cable and to each of the at least two furcation legs with a urethane sealant.

10

8. A pulling configuration for a furcated optical fiber cable, comprising:

a main distribution cable including a plurality of optical fibers surrounded by a cable jacket;

at least two furcation legs into which the plurality of optical fibers are divided, the at least two furcation legs transitioning from the main distribution cable;

a furcation plug located at a transition point between the main distribution cable and the at least two furcation legs, the furcation plug surrounding at least a portion of the main distribution cable and each of the at least two furcation legs;

a pulling ring encircling the main distribution cable and located on a side of the furcation plug opposite the furcation legs;

a pulling mesh surrounding the at least two furcation legs; and

a pulling loop formed at an end of the pulling mesh; wherein the pulling loop is mechanically linked to the main distribution cable via the pulling ring such that pulling forces on the pulling loop are primarily borne by the main distribution cable.

\* \* \* \* \*