



US011154136B2

(12) **United States Patent**
Prestwich et al.

(10) **Patent No.:** **US 11,154,136 B2**
(45) **Date of Patent:** **Oct. 26, 2021**

- (54) **DOUBLE SHELL SEAT**
- (71) Applicant: **Davis Furniture Industries, Inc.**, High Point, NC (US)
- (72) Inventors: **Jonathan Prestwich**, London (GB); **William R. Easton**, High Point, NC (US); **Daniel K. Davis**, High Point, NC (US)
- (73) Assignee: **Davis Furniture Industries, Inc.**, High Point, NC (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 32 days.

(21) Appl. No.: **16/816,804**

(22) Filed: **Mar. 12, 2020**

(65) **Prior Publication Data**
US 2021/0282555 A1 Sep. 16, 2021

- (51) **Int. Cl.**
A47C 3/12 (2006.01)
A47C 1/024 (2006.01)
A47C 3/22 (2006.01)
A47C 1/032 (2006.01)

(52) **U.S. Cl.**
CPC *A47C 3/12* (2013.01); *A47C 1/024* (2013.01); *A47C 1/03266* (2013.01); *A47C 3/22* (2013.01); *A47C 1/0325* (2013.01)

(58) **Field of Classification Search**
CPC *A47C 3/12*; *A47C 7/405*; *A47C 1/03294*
USPC 297/452.12–452.14, 452.19, 256.1
See application file for complete search history.

(56) **References Cited**
U.S. PATENT DOCUMENTS

- 4,840,426 A 6/1989 Vogtherr et al. 297/300
- 5,015,038 A * 5/1991 Mrotz, III A47C 3/12
297/452.15

- 5,052,753 A 10/1991 Buchacz 297/361
- 7,344,192 B2 * 3/2008 Kespohl B60N 2/2821
297/230.14
- 8,061,775 B2 11/2011 Diffrient 297/300.1
- 10,231,546 B2 3/2019 Loew et al. A47C 1/03272
- 10,966,527 B2 * 4/2021 Deevers B29D 99/0092
- 2016/0031560 A1 2/2016 Zheng et al.
- 2016/0374471 A1 * 12/2016 Colonello A47C 3/12
297/326

(Continued)

FOREIGN PATENT DOCUMENTS

DE 102018108351 A1 10/2019

OTHER PUBLICATIONS

Leggett & Platt Flyer on LP19 Easy flex (2018).



(Continued)

Primary Examiner — Sarah B Mcpartlin
(74) *Attorney, Agent, or Firm* — MacCord Mason PLLC

(57) **ABSTRACT**

A double shell seat includes a base for resting on a floor, an outer shell supported by the base, and an inner shell movably supported within the outer shell. The inner shell has a seat support, a backrest support, and a hinge between the seat support and the backrest support. The inner shell is movable with respect to the outer shell from an upright condition in which the seat support has a position toward the rear of the outer shell, the backrest support has a position that is relatively vertical, and the hinge is at a first angle, to a reclined condition in which the seat support is forward of its position in the upright condition, the backrest support is less vertical than its position in the upright condition, and the hinge is open at a greater angle than the first angle. The seat is preferably free of coil springs.

17 Claims, 8 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2018/0249835 A1* 9/2018 Loew A47C 1/03272
2018/0352961 A1* 12/2018 Deevers A47C 7/445
2021/0179274 A1 6/2021 Lueck et al.

OTHER PUBLICATIONS

Steelcase Silq Chair User Guide (2018) Flyer “Understanding and Specifying SILQ418 Series” (Oct. 2019).
Search Report for European Patent Application No. 21161515.8 dated Aug. 12, 2021.

* cited by examiner




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10

1**DOUBLE SHELL SEAT**

BACKGROUND OF THE INVENTION

U.S. Pat. No. 4,840,426 (426 patent) discloses a chair that can alternate between the original and reclined positions. When the backrest tilts backwards, the seat is pushed forward, in what has come to be known as "synchronous motion." A coil spring enclosed in a cylindrical housing is attached to the seat. When the chair is released from the reclined position, the coil spring pulls the seat backwards into the original position. There is a need for a seat or chair that allows synchronous motion without the need for a coil spring.

SUMMARY OF THE INVENTION

The present invention addresses one or more of these needs by providing a double shell seat that includes a base for resting on a floor, an outer shell supported by the base, and an inner shell movably supported within the outer shell. The inner shell has a seat support, a backrest support, and a hinge between the seat support and the backrest support. The inner shell is movable with respect to the outer shell from an upright condition in which the seat support has a position toward the rear of the outer shell, the backrest support has a position that is relatively vertical, and the hinge is at a first angle, to a reclined condition in which the seat support is forward of its position in the upright condition, the backrest support is less vertical than its position in the upright condition, and the hinge is open at a greater angle than the first angle. The seat is preferably free of coil springs.

The inner shell is preferably a single piece of molded plastic, such as polypropylene. The outer shell may also be a single piece of molded plastic that has a seat, back, and arms, with the arms connecting and spanning the seat and back. The outer shell may have the shape of a plastic tub chair.

The outer shell typically has a seat with an upper face, and cooperating ramps and rollers that are on the upper face and the bottom of the seat support are located at positions on the upper face and the bottom of the seat support so that the rollers encounter the ramps, so that a front of the seat support rises as the seat support moves from the upright condition to the reclined condition. The ramps may be on an upper face of the seat, and the inner shell may have the rollers on the bottom of the seat support. The rollers preferably have a barrel shape.

The upper face of the seat of the outer shell may have stops to prevent forward movement of the seat support beyond a completed reclined condition.

The inner shell preferably has flexible edges to avoid injurious finger pinches between the inner and outer shells. The inner shell's flexible edges may be provided in the form of finger-shapes with spaces between the finger-shapes. An upper face of the inner shell may have padding and upholstery.

The outer shell typically has a back with an inner face that has forward pegs, the backrest support of the inner shell has a rear face with vertical slots, and the forward pegs extend into the vertical slots so that the location of the forward pegs in the vertical slots varies as the inner shell moves between the upright and reclined conditions.

Shelves on the upper face of the seat of the outer shell may extend front-to rear, and guides on the bottom face of the seat support may be located at positions so that the guides

2

extend under the shelves to restrain the seat support from separating from the upper face of the outer shell.

Preferably, the inner shell moves from the upright condition to the reclined condition when a person's weight on the inner shell shifts forwardly. The hinge may have resilience that helps restore the inner shell to the upright condition when a person's weight is removed from the inner shell.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be better understood by a reading of the Detailed Description of the Examples of the Invention along with a review of the drawings, in which:

FIG. 1 is a perspective view of a seat in accordance with an embodiment;

FIG. 2 is a perspective view of the inside face of the inner shell of the embodiment of FIG. 1;

FIG. 3 is a perspective view of the outside face of the inner shell of the embodiment of FIG. 1;

FIG. 4 is a perspective view of the inside face of the outer shell of the embodiment of FIG. 1;

FIG. 5 is an enlarged view of a portion of the inside face of the back of the outer shell of the embodiment of FIG. 1;

FIG. 6 is an enlarged view of a portion of the inside face of the seat of the outer shell of the embodiment of FIG. 1;

FIG. 7 is an enlarged view of a portion of the bottom face of the inner shell of the embodiment of FIG. 1;

FIG. 8 is an enlarged view of a portion of the bottom face of the inner shell of the embodiment of FIG. 1;

FIG. 9 is a perspective view of the outside face of the inner shell, with upholstery, of the embodiment of FIG. 1; and

FIG. 10 is a sectional view through the seat portions of the assembled inner and outer shells.

DETAILED DESCRIPTION OF EMBODIMENTS

FIG. 1 shows the front view of a chair in accordance with an embodiment of the invention. The chair 10 includes a base 11 for resting on a floor. The base can be any conventional configuration, but as shown in FIG. 1 is a 4 legged version. The legs come together to support a post 12. Above the post 12 is a seat 14, a back rest 16, and left and right armrests 18 and 20, respectively. In preferred embodiments, the post 12 is provided with a conventional gas cylinder 80 to which gas can be admitted or released through a valve. Other seat base configurations can be used.

FIG. 1 shows that above the base 11, the chair is assembled as an inner shell 22 and an outer shell 24. Outer shell 24 includes a seat 26, back 28, and arms 30, the arms connecting and spanning the seat and back. The outer shell is preferably a single piece of molded plastic, but it could be made of other materials and could be an assembly of subcomponents. The outer shell should be relatively rigid, however, as it primarily defines the shape of the chair for the user of the chair. As seen in FIGS. 1, 9, and 10 the inner shell has padding 32 and an upholstered cover 34, which can be fabric, leather, or other appropriate material.

FIGS. 2 and 3 are perspective views of the inside and outside faces, respectively, of the inner shell 22 of the embodiment of FIG. 1. The inner shell is preferably made of a single piece of molded plastic, such as polypropylene. The inner shell has a seat support 42, a backrest support 38, and a hinge 40 between the seat support and the backrest support. The hinge has resilience that gives it properties that restore the inner shell to the upright condition when a person's weight is removed from the inner shell.

The inner shell **22** is movable with respect to the outer shell **24** to provide the chair's user with the option of an upright condition or a reclined condition. The relative movement between the upright condition and the reclined condition is shown by the arrows U-R in FIG. **1**. Normally, when unoccupied by a user or other weight, the inner shell is in the upright condition. When the backrest reclines the backrest slides downwards and the seat moves forwards to increase the comfort and give a more ergonomic position. The user's positioning in the chair can drive the back **38** of the inner shell to move down and the seat support **42** of the inner shell to move forward to the reclined condition, which causes the angle of the hinge **40** between the back of the inner shell and the seat of the inner shell to increase. When the sitter moves forward, the person's weight on the seat returns the seat and therefore backrest to the upright condition. The hinge **40** of the inner shell **22** may have sufficient resilience to return to the upright condition when the user's weight or other force no longer forces the inner shell into the reclined condition.

As shown in FIGS. **2** and **3**, the inner shell **22** has flexible left and right edges **44** in the form of finger-shapes **46** with spaces **48** between the finger-shapes. The flexible edges reduce the likelihood that user's fingers or other item may get injured by being pinched between the edge of the inner shell and the outer shell. They also allow for the inner shell to bear onto the outer shell, even as the relative height of the inner shell above the outer shell varies as the inner shell transitions between the upright and the reclined conditions.

FIGS. **2** and **3** show that the backrest support **38** has two laterally spaced vertical slots **50**, with a widened bottom **52**. These slots **50** are configured and positioned to receive pegs **54** (see FIGS. **4** and **5**) on the inside face of the back **28** of the outer shell. The pegs **54** extend into the vertical slots **50** so that the location of the pegs in the vertical slots varies as the inner shell moves between the upright and reclined conditions.

The seat support **42** of the inner shell has rollers **56** that are exposed at the bottom face of the seat support. FIG. **3** shows the location of six rollers **56**. The rollers are configured and positioned to contact and ride on ramps **58** on the top face of the seat **26** of the outer shell, as seen in FIGS. **4** and **6**. As the seat transitions from the upright condition to the reclined condition, the rollers **56** ride up the ramps **58** on the upper face of the seat of the outer shell, so the front of the seat support rises. The rollers move about 40 millimeters (1.6 inch) in one embodiment. The top face **59** of ramps and the roller **56** may be made of POM nylon, which has a lubricity to minimize noise or squeaks. Pegs **54** and their mount **55** may also be made of POM nylon to reduce noise. The rollers preferably have a barrel shape, with the center of the roller having a larger circumference than the ends. The barrel shape reduces the contact area with the ramps, which can also reduce noise.

No coil spring is needed in the chair. Instead, the seat shell has a living hinge **40** between the seat support **42** and backrest support **38** in the form of a resilient plastic connection that gives resistance when being opened. However, the main resistance comes from the fact that the seat is on an inclined ramp so when the backrest moves, the seat raises the weight of the sitter and thus gives an appropriate resistance to the backrest in accordance to the sitter's weight.

When the sitter starts to shift his weight forward (as in arising from the seat), the seat support **42** travels back down the inclined ramp, pushing the backrest support **38** upwards and into an upright position. The backrest is proportionally by weight helping the sitter to move to an upright position

by the seat support travelling down the ramps, as an automatic mechanism. As the seat support moves forward, it also moves a little bit upwards and thus lifting the sitter to create this automatic mechanism.

While the embodiment shown has the ramps on the top of the seat of the outer shell, and the rollers on the bottom of the seat support of the inner shell, it is within the scope of the invention for the rollers to be on the outer shell and the ramps on the inner shell.

FIGS. **4** and **6** show shelves **62** on the upper face of the seat **26** of the outer shell that extend front-to-rear. The axle **64** of one of the rollers **56** can be seen in FIG. **6** as extending under the shelf **62** like a guide to restrain the seat support from separating from the upper face of the outer shell, but if the seat support moves forward sufficiently, the guides or axles can be lifted past the shelves. As seen in FIG. **4**, the shelves and axles are located at positions so that axles extend under the shelves on both the left and right sides of the outer shell.

FIGS. **7** and **8** are enlarged images of features on the bottom face of the seat support **42** of the inner shell **22**. FIG. **7** shows a bearing **66** to receive and retain an axle **64** of a roller.

FIGS. **3** and **8** show that the bottom face of the seat support **42** has protrusions **67**. Protrusions **67** are located so they come into contact with stops **68** on the upper face of the seat of the outer shell at the completion of a transition to the reclined condition, preventing movement of seat support beyond the completed reclined condition, as seen in FIG. **10**.

Small holes **70** formed in the outer shell's seat **26** just behind the stops **68** enable a dowel to be inserted to compress the protrusion **67** so it can clear the top of the stop and allow further forward movement of the seat support **42**, so the axles **64** are no longer below the shelves **62**. This permits removal of the inner shell from the outer shell in the unusual event that the inner shell needs repair or replacement.

FIG. **9** shows a rear view of the inner shell once the padding **32** and upholstery **34** have been put in place. The padding can be installed by masking the locations of the rollers **56** and the vertical slots **50** to shield them, followed by mounting the inner shell **22** in a mold and injecting foam into the mold to form the padding. The foam padding can be wrapped with the upholstery cover **34**, and the cover **34** can be held in place by staples **72** or the like. A plate **74** with slots **76** can be added to align its slots with the slots **50**.

The inner shell can be attached to the outer shell by positioning the axles **64** under the shelves **62** to locate the seat support **42** and then inserting the pegs **54** into the slots **76**, **50** to hang the back **38** on the back **28**.

Certain modifications and improvements will occur to those skilled in the art upon reading the foregoing description. It should be understood that all such modifications and improvements have been omitted for the sake of conciseness and readability but are properly within the scope of the following claims

What is claimed is:

1. A double shell seat comprising a base for resting on a floor, an outer shell supported by the base, and an inner shell movably supported within the outer shell, the inner shell having a seat support, a backrest support, and a hinge between the seat support and the backrest support, the inner shell being movable with respect to the outer shell from

5

an upright condition in which the seat support has a position toward a rear of the outer shell, the backrest support has a position that is relatively vertical, and the hinge is at a first angle,

to a reclined condition in which the seat support is forward of its position in the upright condition, the backrest support is less vertical than its position in the upright condition, and the hinge is open at a greater angle than the first angle, wherein the outer shell has a seat with ramps on an upper face of the seat, and the inner shell has rollers on a bottom of the seat support at positions of the seat support so that the rollers encounter the ramps on the upper face of the seat of the outer shell, so the seat support rises as it moves from the upright condition to the reclined condition.

2. A double shell seat as claimed in claim 1 wherein the inner shell is a single piece of molded plastic.

3. A double shell seat as claimed in claim 1 wherein the inner shell is a single piece of molded polypropylene.

4. A double shell seat as claimed in claim 1 wherein the outer shell is a single piece of molded plastic that has a seat, back, and arms, the arms connecting and spanning the seat and back.

5. A double shell seat as claimed in claim 1 wherein the outer shell is shaped like a plastic tub chair.

6. A double shell seat as claimed in claim 1 wherein the rollers have a barrel shape.

7. A double shell seat as claimed in claim 1 wherein the upper face of the seat of the outer shell has stops to prevent forward movement of the seat support beyond a completed reclined condition.

8. A double shell seat as claimed in claim 1 wherein the inner shell has flexible edges.

9. A double shell seat as claimed in claim 8 wherein the inner shell's flexible edges are provided in the form of finger-shapes with spaces between the finger-shapes.

10. A double shell seat as claimed in claim 1 wherein an upper face of the inner shell has padding and upholstery.

11. A double shell seat as claimed in claim 1 wherein the outer shell has a back with an inner face that has forward pegs, the backrest support of the inner shell has a rear face with vertical slots, and the forward pegs extend into the vertical slots so that the location of the forward pegs in the vertical slots varies as the inner shell moves between the upright and reclined conditions.

12. A double shell seat as claimed in claim 1 wherein the outer shell has a seat with an upper face and shelves on the seat extend front-to rear and guides on a bottom face of the seat support are located at positions so that the guides extend under the shelves to restrain the seat support from separating from the upper face of the outer shell.

13. A double shell seat as claimed in claim 1 wherein the inner shell moves from the upright condition to the reclined condition when a person's weight on the inner shell shifts forwardly.

14. A double shell seat as claimed in claim 1 wherein the hinge has resilience that helps restore the inner shell to the upright condition when a person's weight is removed from the inner shell.

15. A double shell seat as claimed in claim 1 that is free of coil springs.

16. A double shell seat comprising
a base for resting on a floor,
an outer shell supported by the base, and
an inner shell movably supported within the outer shell,
the inner shell having a seat support, a backrest support,

6

and a hinge between the seat support and the backrest support, the inner shell being movable with respect to the outer shell from

an upright condition in which the seat support has a position toward a rear of the outer shell, the backrest support has a position that is relatively vertical, and the hinge is at a first angle,

to a reclined condition in which the seat support is forward of its position in the upright condition, the backrest support is less vertical than its position in the upright condition, and the hinge is open at a greater angle than the first angle,

wherein the outer shell has a seat with an upper face, and cooperating ramps and rollers that are on the upper face and a bottom of the seat support are located at positions on the upper face and the bottom of the seat support so that the rollers encounter the ramps, whereby a front of the seat support rises as the seat support moves from the upright condition to the reclined condition.

17. A double shell seat comprising

a base for resting on a floor,

an outer shell supported by the base, the outer shell being a single piece of molded plastic that has a seat, back, and arms, the arms connecting and spanning the seat and back, and

an inner shell made of a single piece of molded plastic movably supported within the outer shell, the inner shell having a seat support, a backrest support, and a hinge between the seat support and the backrest support, wherein the inner shell has flexible edges in the form of finger-shapes with spaces between the finger-shapes, the inner shell being movable with respect to the outer shell from

an upright condition in which the seat support has a position toward a rear of the outer shell, the backrest support has a position that is relatively vertical, and the hinge is at a first angle,

to a reclined condition in which the seat support is forward of its position in the upright condition, the backrest support is less vertical than its position in the upright condition, and the hinge is open at a greater angle than the first angle,

the inner shell moving from the upright condition to the reclined condition when a person's weight on the inner shell shifts forwardly, and the hinge having resilience that helps restore the inner shell to the upright condition when a person's weight is removed from the inner shell,

wherein the outer shell has a seat with ramps on an upper face of the seat, and the inner shell has rollers on a bottom of the seat support at positions of the seat support so that the rollers encounter the ramps on the upper face of the seat of the outer shell, so the seat support rises as it moves from the upright condition to the reclined condition,

wherein shelves on the upper face of the seat of the outer shell extend front-to rear and guides on the bottom face of the seat support are located at positions so that the guides extend under the shelves to restrain the seat support from separating from the upper face of the outer shell,

wherein the upper face of the seat of the outer shell has stops to prevent forward movement of the seat support beyond a completed reclined condition, and wherein the outer shell has a back with an inner face that has forward pegs, the backrest support of the

7

8

inner shell has a rear face with vertical slots, and the forward pegs extend into the vertical slots so that the location of the forward pegs in the vertical slots varies as the inner shell moves between the upright and reclined conditions.

5

* * * * *